

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250284060

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Kim; Ki Tae et al.

OPTICAL DEVICE FOR AUGMENTED REALITY

Abstract

An optical device for augmented reality, includes: a light generating unit for generating a first light; a first optical element for transmitting or reflecting an incident light according to an incident angle; a light guide for reflecting the incident light; and a second optical element formed with a predetermined slope and reflecting the incident light.

Inventors: Kim; Ki Tae (Seoul, KR), Roh; Jihyung (Suwon-si, KR), Jung; YeonPil (Yongin-si, KR)

Applicant: Noble M & B Co., LTD (Yongin-si, KR)

Family ID: 96949017

Assignee: Noble M & B Co., LTD (Yongin-si, KR)

Appl. No.: 18/631064

Filed: April 10, 2024

Foreign Application Priority Data

KR

10-2024-0031022

Mar. 05, 2024

Publication Classification

Int. Cl.: G02B6/26 (20060101); G02B27/01 (20060101)

U.S. Cl.:

CPC G02B6/262 (20130101); G02B27/0172 (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S)

[0001] This application claims priority to Korean Patent Application No. 10-2024-0031022, filed on Mar. 5, 2024, the disclosure of which is incorporated herein by reference in its entirety.

BACKGROUND OF THE INVENTION

Technical Field

[0002] The present invention relates to an optical device for augmented reality.

Description of the Related Art

[0003] In general, augmented reality (AR) is a field of virtual reality, and is a computer graphic technique that synthesizes virtual objects or information of an environment that actually exists to make them look like objects existing in an original environment.

[0004] In order to implement such augmented reality, a virtual image generated by a device such as a computer or an image is implemented by being superimposed on a real image using optical means such as a prism or the like that reflects or refracts a virtual image incident on a display by using optical means.

[0005] In an optical system using a beam splitter among devices implementing the augmented reality, an augmented reality image is reflected by the beam splitter and reaches a user, and there is a limitation in reducing the size and weight of the optical system according to the beam splitter. There is a need to develop an optical system technology capable of reducing a weight to the level of general glasses and enabling a design by reducing a thickness (width) of an augmented reality lens while securing a sufficient Field of View (FOV) capable of solving such a problem.

DESCRIPTION OF THE RELATED ART

Document of Related Art

[0006] (Patent Document 0001) Korean Patent Registration No. 10-1660519 (2016 Sep. 29)

SUMMARY OF THE INVENTION

[0007] The present invention has been made in an effort to provide an optical device for augmented reality with an improved thickness of the optical device for augmented reality.

[0008] An object of the present invention is to provide an optical device for augmented reality, which is capable of reducing weight by improving the thickness of the optical device while sufficiently securing a Field of View (FOV).

[0009] An object of the present invention is to provide an optical device for augmented reality with improved image quality of augmented reality.

[0010] An objective of the present invention is to provide an optical device for augmented reality in which a manufacturing process is simplified.

[0011] The objects of the present invention are not limited to the above-mentioned objects, and other objects not mentioned may be clearly understood by the skilled person in the art from the following description.

Solution to Problem

[0012] According to an aspect of the present invention, there is provided an optical device for augmented reality, the optical device including: a light generating unit configured to generate a first light; a first optical element configured to transmit or reflect incident light according to an incident angle; a light guide configured to reflect the incident light; and a second optical element formed at a predetermined slope and configured to reflect the incident light, wherein the first light is incident on the first optical element and thus a transmitted second light is incident on the light guide, the second light is incident on the light guide and thus a reflected third light is incident on the second optical element, the third light is incident on the second optical element and thus a reflected fourth light is incident on the light guide, the fourth light is incident on the light guide and thus a reflected fifth light is incident on the first optical element, and the fifth light incident on the first optical element is reflected and thus incident on an eye of a user.

[0013] According to a configuration of the present disclosure, the first optical element may have a

dielectric coating layerformed thereon.

[0014] According to an embodiment of the present disclosure, an incident angle at which the first light is incident on the first optical element may be smaller than an incident angle at which the fifth light is incident on the first optical element.

[0015] According to an embodiment of the present disclosure, an incident angle at which the first light is incident on the first optical element may be in a range of 0° to 45°.

[0016] According to an embodiment of the present disclosure, an incident angle at which the fifth light is incident on the first optical element may be in a range of 0° to 45°.

[0017] According to an embodiment of the present disclosure, the first optical element may be included to be inclined such that the first light is incident and transmitted to the first optical element at a predetermined incident angle and the fifth light is incident and reflected to the first optical element at a predetermined incident angle.

[0018] According to an embodiment of the present disclosure, the second optical element may be included to be inclined so that the third light is reflected and incident on the light guide.

Effects of the Invention

[0019] According to an embodiment of the present disclosure, it is possible to provide an optical device for augmented reality in which the thickness of the optical device is improved while sufficiently securing a Field of View (FOV).

[0020] According to an embodiment of the present disclosure, it is possible to provide an optical device for implementing augmented reality in which the weight of the optical device is reduced by improving the thickness of the optical device.

[0021] According to a configuration of the present invention, it is possible to provide an optical device for implementing augmented reality with improved image quality of augmented reality.

[0022] According to an embodiment of the present disclosure, it is possible to provide an optical device for augmented reality in which a manufacturing process is simplified.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0023] FIG. 1 is a view showing an optical device for augmented reality according to an exemplary embodiment of the present invention, FIG. 2 is a cross-sectional view taken along line A-A' of the optical device for augmented reality of FIG. 1, FIGS. 3 and 4 are views showing transmission and reflection of light of the optical device for augmented reality according to an exemplary embodiment of the present invention, and FIG. 5 is a view showing transmission and reflection of light of the optical device for augmented reality according to an exemplary embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

[0024] Hereinafter, an embodiment of an optical device for augmented reality according to the present invention will be described in detail with reference to the accompanying drawings.

[0025] In adding reference numerals to elements of each drawing, it should be noted that the same feature elements are designated by the same reference numerals although they are shown in different drawings. Further, in describing the embodiments of the present invention, when it is determined that the detailed description of the related known feature or function interferes with the understanding of the embodiments of the present invention, the detailed description thereof will be omitted.

[0026] In describing components of the embodiments of the present invention, terms such as first, second, A, B, (a), (b), etc. may be used. The terms are used only to distinguish the components from other feature elements, and the nature, order, or sequence of the components is not limited by the terms. Further, unless otherwise defined, all terms used herein, including technical or scientific

terms, have the same meaning as that generally understood by those skilled in the art. It will be further understood that terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the relevant art and will not be interpreted in an idealized or overly formal sense unless expressly so defined herein.

[0027] An augmented reality device provides augmented reality to a user. Here, the augmented reality is a real screen or a real image (hereinafter, referred to as a “real screen”) viewed by the user. It is a technology that superimposes and synthesizes virtual information such as text and graphics in real time on JPEG-D, JPEG-D, and JPEG-D, and displays a single image. The user may recognize the augmented reality by overlaying the augmented reality image provided by the augmented reality device on a reality screen that can be viewed by the augmented reality device and viewing the superimposed augmented reality image.

[0028] FIG. 1 is a view showing an optical device for augmented reality according to an exemplary embodiment of the present invention, FIG. 2 is a cross-sectional view taken along line A-A' of the optical device for augmented reality of FIG. 1, and FIGS. 3 to 5 are views showing transmission and reflection of light of the optical device for augmented reality according to an exemplary embodiment of the present invention.

[0029] The optical device for augmented reality **10** according to FIGS. 1 to 5 may include a light generating unit **110** that generates a first light **L1**, a first optical element **120** that transmits or reflects incident light according to an incident angle, a light guide **101** that reflects the incident light, and a second optical element **130** that has a predetermined slope and reflects the incident light.

[0030] More specifically, the first light **L1** generated and emitted from the light generating unit **110** may be incident on the first optical element **120**. The first light **L2** may be incident on the first optical element **120**, and the transmitted second light **L2** may be incident on the light guide **101**. A third light **L3**, which is the second light **L2** incident on the light guide **101** and reflected therefrom, may be incident on the second optical element **130**, and a fourth ((**L4**)) light, which is the third light **L3** incident on the second optical element **130** and reflected therefrom, may be incident on the light guide. A fifth light **L5** that the fourth light **L4** is incident on the light guide **101** and reflected therefrom may be incident on the first optical element **120**, and the fifth light **L5** incident on the first optical element **120** may be reflected and incident on the user's eye, thereby implementing augmented reality.

[0031] Here, the light generated by the light generating unit **110** may refer to light that is transmitted and reflected to implement a character, an image, and a video on the user's eye **1**. In addition, the user's eye **1** referred to in the present disclosure may preferably refer to the pupil of the user, but is not limited thereto.

[0032] The optical device for augmented reality **10** may include a light generating unit **110** that emits the first light **L1**. The light generating unit **110** may be included as a micro display that generates the first light **L1**, but is not limited thereto. Here, the micro display may emit light in which characters, images, and images including image information are implemented so that the image information may be provided to the user's eyes. The first light **L1** emitted from the microdisplay may be incident on the first optical element **120** and transmitted.

[0033] Here, the light generating unit **110** may further include a collimator for collimating the first light **L1** emitted from the microdisplay.

[0034] The optical device for augmented reality **10** may include a first optical element **120**. The first light **L1** generated by the light generating unit **110** may be incident on the first optical element **120**. The first optical element **120** may be included to transmit or reflect light according to an incident angle, and the first light **L1** generated and incident from the light generating unit **110** may be favorably transmitted to increase an amount of transmitted light, and the fifth light **L5** incident from the light guide **101** may be inclined at a predetermined inclination to increase an amount of

reflected light.

[0035] More specifically, the first optical element **120** may be included by being dielectric-coated. The first optical element **120** may be dielectric-coated to include a dielectric coating layer. More specifically, the dielectric coating layer of the first optical element **120** may be formed on a surface facing the second optical element **130**, but is not limited thereto. The first optical element **120** may be dielectric-coated to adjust the reflectance of the first optical element **120**. The dielectric coating is a type of coating made of an electrical insulator material and is a coating for obtaining a specific reflectance in a specific wavelength region. Since the dielectric coating layer is formed on the first optical element **120**, the dielectric coating layer may be coated on the dielectric coating layer, and even when light is incident at a small incident angle, the reflection angle may be increased, thereby increasing light efficiency.

[0036] Transmission and reflectance may vary according to the thickness of the dielectric coating coated on the first optical element **120**.

[0037] The transmission of the dielectric coating layer may vary depending on the incident angle. The reflectance and the transmittance are determined according to the angle, and the light incident on the dielectric coating layer may be reflected or transmitted according to the incident angle.

[0038] For example, the dielectric coating layer may be, but is not limited to, a dielectric coating that may include thin layers of materials such as magnesium, calcium fluoride, and various metal oxides. By selection of the composition, thickness, and number of these layers, the reflectance and transmittance of the coating can be tuned.

[0039] That is, the surface of the first optical element **120** may be coated with a dielectric material, and the reflectance and transmittance of the first optical element **120** may be adjusted by the dielectric coating.

[0040] The dielectric coating may form a plurality of dielectric layers, and the refractive index of the dielectric coating or the refractive index of sub-layers in the plurality of dielectric coatings and the order of the dielectric layers may also be adjusted. The increase in transmittance can reduce the overall reflectance, and increase or decrease the thickness of the dielectric layers to adjust the reflectance and transmittance of the coating.

[0041] The thickness of the dielectric layer of the side surface through which the first light **L1** generated and incident from the light generating unit **110** is incident and transmitted to the first optical element **120** may be different from the thickness of the dielectric layer of the side surface through which the fifth light **L5** reflected by the light guide **101** is incident to the first optical element **120**. Since the dielectric layers are different from each other, reflectivity and transmittance may be different from each other, and the thickness of the dielectric coating may be adjusted to facilitate transmission and reflection according to an incident angle.

[0042] The first optical element **120** may be dielectric-coated and may transmit the first light **L1** generated and incident from the light generating unit **110** according to an angle at which it is incident on the first optical element, and the fifth light **L5** reflected by the light guide **101** and incident on the first optical element **120** may be reflected toward the user's eye **1**.

[0043] Also, the first optical element **120** may be included with an inclination in a predetermined direction. The first optical element **120** may be inclined in a predetermined direction to transmit the first light **L1** generated by the light generating unit **110** and incident at a predetermined incident angle, and the fifth light **L5** reflected by the light guide **101** may be incident at a predetermined incident angle and reflected toward the user's eye **1**.

[0044] The optical device for augmented reality **10** may include a light guide **101**. The light guide **101** may be made of a material that is transmitted or reflected according to an incident angle, but is not limited thereto. The light guide **101** may reflect the second light **L2** transmitted through the first optical element **120** in a predetermined direction.

[0045] A second optical element **130** that reflects the third light **L3** reflected by the light guide **101** may be included. The second optical element **130** may reflect the third light **L3** reflected and

incident from the light guide **101** to be incident on the light guide **101** at a predetermined angle, and the light guide **101** may allow the fifth light **L5** reflecting the fourth light **L4** reflected and incident from the second optical element **130** to be incident on the first optical element **120** at a predetermined angle.

[0046] In addition, the reflective surface of the second optical element **130** may be disposed to be inclined toward the light guide **101**. The second optical element **130** may be disposed to be inclined toward the light guide **101** to reflect the third light **L3** reflected from the light guide **101** and incident thereon, and the fourth light **L4** in which the third light **L3** is reflected from the second optical element **130** may be incident on the light guide **101**.

[0047] Fourth light **L4** may be incident on the light guide **101** by being reflected from the second optical element **130**, and fifth light **L5**, which is incident on the fourth light **L4** and is reflected from the light guide **101**, may be incident on the first optical element **130** in a predetermined direction and be reflected therefrom. The fifth light **L5** incident on the first optical element **120** may be emitted to the user's eye **1** to implement the augmented reality and be incident on the user's eye **1**.

[0048] More specifically, the first light **L** may be emitted from the light generating unit **110** of the optical device for augmented reality **10**, and the first light **L2** emitted from the light generating unit **110** may pass through the first optical element **120**. The second light **L**, which is transmitted through the first optical element, may be incident on the light guide **101**. The second light **L2** may be incident on the light guide **101** to be reflected, and the third light **L3**, which is the second light **L2** reflected by the light guide **101**, may be reflected by the second optical element **130**. The third light **L3** may be reflected by the light guide **101**, the third light **L3** may be reflected by the light guide **101** to be incident on the second optical element **130**, and the fourth light **L4** that is reflected by the second optical element **130** may be incident on the light guide **101**. The fifth light, in which the fourth light **L4** is reflected by the light guide **101**, is incident on the first optical element **120** at a predetermined incident angle, is reflected toward the user's eye **1**, and is incident on the user's eye **1**, thereby implementing augmented reality.

[0049] The optical device for augmented reality **10** may include an optical unit **100**. The optical unit **100** may perform a function of transmitting light emitted from an object in the real world and emitting light reflected by the first optical element **120** to the user's eye **1**.

[0050] In the optical unit, the light guide **101**, the first optical element **120**, and the second optical element **130** may be embedded and included, but may be included in the optical device for augmented reality **10** according to the selection of the skilled person in the art. The optical unit may transmit the real image light to the user's eyes.

[0051] As illustrated in FIG. 3, when the first light **L1** is emitted from the light generating unit **110**, the first light **L1** may be transmitted through the first optical element **120**, and the first light **L1** may be incident and the second light **L2** transmitted through the first optical element **120** may be incident on the light guide **101**. The second light **L2** may be reflected by the light guide **101**, and the third light **L3**, which is the second light **L2** reflected by the light guide **101**, may be incident on the second optical element **130**. The third light **L3** may be reflected by the second optical element **130**, and the fourth light **L4** that is reflected by the second optical element **130** after the third light **L3** is incident may be incident on the light guide **101**. Fifth light **L5** obtained by reflecting the fourth light **L4** to the light guide **101** may be incident on the first optical element **120** at a predetermined incident angle, and the fifth light **L5** may be incident on the first optical element **120** at the predetermined incident angle, reflected by the first optical element **120**, and reflected toward the user's eye **1**, thereby implementing augmented reality.

[0052] An incident angle at which the first light **L1** is incident on the first optical element **120** may be a first incident angle θ_1 , and an incident angle at which the fifth light is incident on the first optical element **120** may be a second incident angle θ_2 .

[0053] Preferably, a first incident angle θ_1 at which the first light **L1** is incident on the first optical

element **120** may be greater than 0° and less than 45° , and a second incident angle $\theta 2$ at which the fifth light **L5** is incident on the first optical element **120** may be greater than 0° and less than 45° , and may be incident on the first optical element **120**.

[0054] In addition, the first incident angle $\theta 1$ may be incident at an angle lower than the second incident angle $\theta 2$.

[0055] The first incident angle $\theta 1$ may be incident on the first optical element **120** at an angle lower than the second incident angle $\theta 2$ to be transmitted without being reflected by the first optical element **120**, and the second incident angle $\theta 2$ may be incident at a larger angle to be reflected by the light guide **101** to be incident on the first optical element **120** without being transmitted to be reflected to be incident on the user's eyes, thereby implementing augmented reality.

[0056] An optical device for augmented reality **10** according to an exemplary embodiment of the present invention includes a light generating unit **110** generating a first light **L1**, a first optical element **120** transmitting the first light **L1**, a light guide **101** on which the first light **L1** is incident and on which a second light **L2** transmitted by the first optical element **120** is incident, and which reflects the second light **L2**, and a second optical element **130** on which the second light **L2** is incident and on which a third light **L3** reflected by the light guide **101** is incident, and which reflects the third light **L3**, and in which a fourth light **L4** incident on and reflected by the second optical element **130** is incident on the light guide **101**, and a fifth light **L5**, which is the fourth light **L4** incident on the light guide **101** and reflected therefrom, is incident on the first optical element **120** and reflected toward the user's eye **1**, thereby implementing an augmented reality, so that the thickness and structure of the optical device for augmented reality **10** may be simplified to improve the atomness of the optical device and provide an optical device for augmented reality that is easily manufactured.

[0057] The exemplary embodiment of the present invention is not necessarily limited to the above-described exemplary embodiment, and it will be apparent that various modifications and implementation within an equivalent range by those skilled in the art to which the present invention belongs are possible. Therefore, the true scope of the present invention is defined by the following claims.

CODE DESCRIPTION

[0058] **1**: User's eyes [0059] **10**: an Optical device for augmented reality [0060] **100**: an Optical unit [0061] **101**: a Light guide [0062] **110**: a Light generating unit [0063] **120**: a First optical element [0064] **130**: a Second optical element

Claims

1. An optical device for augmented reality comprising: a light generating unit configured to generate a first light; a first optical element configured to transmit or reflect an incident light according to an incident angle; a light guide configured to reflect the incident light; and a second optical element comprising a predetermined slope and configured to reflect the incident light, wherein a second light, which is the first light incident on and transmitted through the first optical element, is incident on the light guide, wherein a third light, which is the second light incident on and reflected by the light guide, is incident on the second optical element, wherein a fourth light, which is the third light incident on and reflected by the second optical element, is incident on the light guide, wherein a fifth light, which is the fourth light incident on and reflected by the light guide, is incident on the first optical element, and wherein a fifth light, which is the first optical element, is reflected and incident on user's eyes.

2. The optical device for augmented reality according to claim 1, wherein the first optical element includes a coating layer.

3. The optical device for augmented reality according to claim 1, wherein an incident angle at which the first light is incident on the first optical element is smaller than an incident angle at

which the fifth light is incident on the first optical element.

4. The optical device for augmented reality according to claim 1, wherein an incident angle at which the first light is incident on the first optical element is in a range of 0° to 45° .
 5. The optical device for augmented reality according to claim 1, wherein an incident angle at which the fifth light is incident on the first optical element is in a range of 0° to 45° .
 6. The optical device for augmented reality according to claim 1, wherein the first optical element is obliquely included such that the first light is incident on and transmitted through first the optical element at a predetermined incident angle and the fifth light is incident on and reflected by the first optical element at a predetermined incident angle.
 7. The optical device for augmented reality according to claim 1, wherein the second optical element is obliquely included such that the third light is reflected and is incident on the light guide.
-