

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250286196

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Ramabadhran; Krishna Prasath et al.

MOUNTING ASSEMBLY FOR BATTERY PACKS

Abstract

A mounting assembly, for mounting battery pack(s) to a machine, includes a main frame coupled to a structure of the machine, and auxiliary frame(s) coupled to the main frame. The main frame includes first engagement surfaces facilitating at least one of a transportation or a mounting of the main frame on the structure. The main frame defines first mating features and second mating features. Each auxiliary frame includes: mounting features to mount the battery pack(s) on the auxiliary frame; second engagement surfaces facilitating at least one of a transportation or a mounting of the auxiliary frame on the main frame; and coupling features to be engaged with the first mating features when a number of the auxiliary frames to be coupled to the main frame is odd, and with the second mating features when a number of the auxiliary frames to be coupled to the main frame is even.

Inventors: Ramabadhran; Krishna Prasath (Krishnagiri, IN), Bell; Brian Richard (West Lafayette, IN)

Applicant: Caterpillar Inc. (Peoria, IL)

Family ID: 1000007812988

Assignee: Caterpillar Inc. (Peoria, IL)

Appl. No.: 18/596991

Filed: March 06, 2024

Publication Classification

Int. Cl.: H01M50/244 (20210101)

U.S. Cl.:

CPC H01M50/244 (20210101);

Background/Summary

TECHNICAL FIELD

[0001] The present disclosure relates to energy storage devices, such as battery packs. More specifically, the present disclosure relates to a mounting assembly for mounting battery packs, of different sizes and configurations, onto machines with different power requirements.

BACKGROUND

[0002] Battery packs of different sizes and configurations, for example, a single-string pack configuration, a double-string pack configuration, and so on, are widely used to meet a spectrum of power requirements of a variety of commercial, industrial, or household applications. In an example, a single-string battery pack of 60 kilowatt-hours capacity may be used to power operations of a small-size work machine (e.g., an excavator), whereas a four-string battery pack of 240 kilowatt-hours capacity may be used in a containerized power module to supply electrical power to a power grid. Such varying configurations of battery packs require that each battery pack use a corresponding (and mostly customized) mounting assembly and/or a mechanisms, therefore making one mounting assembly and/or a mechanism different from the other, thus increasing overall cost and inventory.

[0003] Chinese patent no. 216,507,983 discloses a battery position expanding mechanism and battery replacing equipment. The battery position expanding mechanism includes a base assembly, a telescopic frame assembly and a supporting frame assembly. The base frame assembly includes at least two base frames sequentially connected, a connecting structure used for connecting and fixing arranged on the base frame assembly. Each base frame is provided with a first battery positioning structure. Each telescopic frame assembly is connected to the corresponding base frame in a sliding mode. Each supporting frame assembly is connected to the corresponding telescopic frame assembly in a sliding manner, and a second battery positioning structure is arranged on each support frame assembly. A first telescopic mechanism is arranged between the telescopic frame assembly and the corresponding base frame, a second telescopic mechanism is arranged between the supporting frame assembly and the telescopic frame assembly. The battery position expanding mechanism can be installed on a chassis of battery replacing equipment, two or more battery positions are expanded, and the battery replacing effect is improved. Once a plurality of battery positions are expanded, all battery boxes on the power transmission vehicle can be stored on the battery replacement equipment at one time.

SUMMARY OF THE INVENTION

[0004] In one aspect, the disclosure relates to a mounting assembly for mounting one or more battery packs to a machine. The mounting assembly includes a main frame and one or more auxiliary frames. The main frame is configured to be coupled to a structure of the machine. The main frame includes first engagement surfaces to engage with an implement to facilitate at least one of a transportation or a mounting of the main frame on the structure. The main frame defines first mating features and second mating features. The one or more auxiliary frames are configured to be coupled to the main frame. Each auxiliary frame includes mounting features, second engagement surfaces, and coupling features. The mounting features is configured to fixedly mount the one or more battery packs on the auxiliary frame. The second engagement surfaces is configured to engage with an equipment to facilitate at least one of a transportation or a mounting of the auxiliary frame on the main frame. The coupling features are configured to be engaged: with the first mating features when a number of the one or more auxiliary frames to be coupled to the main frame is odd; and with the second mating features when a number of the one or more auxiliary frames to be coupled to the main frame is even.

[0005] In yet another aspect, the disclosure relates to a method for mounting one or more battery

packs to a machine. The method includes coupling a main frame to a structure of the machine. The main frame includes first engagement surfaces to engage with an implement to facilitate at least one of a transportation or a mounting of the main frame on the structure. The main frame defines first mating features and second mating features. Further, the method includes coupling one or more auxiliary frames to the main frame. Each auxiliary frame includes mounting features, second engagement surfaces, and coupling features. The mounting features is configured to fixedly mount the one or more battery packs on the auxiliary frame. The second engagement surfaces is configured to engage with an equipment to facilitate at least one of a transportation or a mounting of the auxiliary frame on the main frame. The coupling features are configured to be engaged: with the first mating features when a number of the one or more auxiliary frames to be coupled to the main frame is odd; and with the second mating features when a number of the one or more auxiliary frames to be coupled to the main frame is even.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0006] FIG. 1 illustrates an exemplary machine accommodating a mounting assembly and a battery pack mounted on the mounting assembly, in accordance with an embodiment of the present disclosure;

[0007] FIG. 2 illustrates a main frame of the mounting assembly, in accordance with an embodiment of the present disclosure;

[0008] FIG. 3 is a bottom cross-sectional view of the main frame, taken along a plane 3-3 parallel to a plane defined by axes A1-A2 of the main frame, in accordance with an embodiment of the present disclosure;

[0009] FIG. 4 illustrates an auxiliary frame of the mounting assembly, in accordance with an embodiment of the present disclosure;

[0010] FIG. 5 illustrates an assembly of the battery pack and the auxiliary frame, in accordance with an embodiment of the present disclosure;

[0011] FIGS. 6 and 7 illustrate an assembly of the auxiliary frame (along with the battery pack mounted thereon) and the main frame, in accordance with an embodiment of the present disclosure; and

[0012] FIGS. 8 and 9 illustrate an assembly of two auxiliary frames (along with their corresponding battery packs) and the main frame, in accordance with an embodiment of the present disclosure; and

[0013] FIG. 10 illustrate an assembly of the mounting assembly (with the battery pack mounted thereon) and a structure of the machine, in accordance with an embodiment of the present disclosure.

DETAILED DESCRIPTION

[0014] Reference will now be made in detail to specific embodiments or features, examples of which are illustrated in the accompanying drawings. Generally, corresponding reference numbers may be used throughout the drawings to refer to the same or corresponding parts, e.g., **1**, **1'**, **1''**, **101** and **201** could refer to one or more comparable components used in the same and/or different depicted embodiments.

[0015] Referring to FIG. 1, an exemplary machine **100** is shown. The machine **100** may be used in various industries and application areas such as construction, forestry, agriculture, mining, excavation etc. In an example, as shown in FIG. 1, the machine **100** is embodied as a containerized power module **100'**. Alternatively, the machine **100** may be a mobile machine, for example, an earth-moving machine configured to perform earth altering functions, including displacing, spreading, distributing, leveling, and grading materials. Examples of such mobile machines

include, but are not limited to, excavators, backhoe loaders, dozers, pavers, motor graders, loaders, trenchers, scrapers, crushers, draglines, or any type of machine that includes an implement for moving material.

[0016] Although references to the containerized power module **100'** are used, aspects of the present disclosure may also be applicable to other machines, such as excavators, backhoe loaders, dozers, pavers, motor graders, loaders, trenchers, scrapers, crushers, draglines, or any other machines known to those skilled in the art, and references to the containerized power module **100'** in the present disclosure is to be viewed as purely exemplary.

[0017] The machine **100** (i.e., the containerized power module **100'**) may be used to store and/or supply electrical energy, for example, to an electrical grid, or directly to electrical loads. For that, the machine **100** is provided with battery pack(s), such as a battery pack **102**. In an example, the battery pack **102** includes a housing **104** and multiple battery modules (not shown) (each battery module formed of one or more battery cells) arranged in a stacked relationship within the housing **104**. As shown in FIG. **1**, the battery pack **102** is formed of two columns of the battery modules that are electrically coupled to one another to provide a desired electrical energy output and voltage output. It may be contemplated that, in other embodiments, the battery pack **102** may include a higher or lower number of battery modules, each including a suitable number of battery cells, depending on energy storage and supply capacity of the containerized power module **100**.

[0018] The machine **100** defines a structure **106** for mounting battery packs **102**. In an example, as shown in FIG. **1**, the machine **100** (e.g., the containerized power module **100'**) includes an enclosure **108** that may define a base floor **110**, a ceiling **112**, and sidewalls **114**. The sidewalls **114** may extend between the base floor **110** and the ceiling **112** to connect the base floor **110** with the ceiling **112**. At least one sidewall **114**, such as a sidewall **116**, may include doors, such as a door **118**, that may provide access to an interior **120** of the enclosure **108**, for example, for mounting the battery pack **102** (or assemblies associated with the machine **100**). The base floor **110** may define or be one and the same as the structure **106**.

[0019] The structure **106** defines at least one mounting arrangement (e.g., mounting arrangement **124**), as shown in FIG. **10**. The mounting arrangement **124** may include a mounting hole **126**. In some cases, the mounting hole **126** may include a threaded hole. The mounting arrangement **124** may facilitate fixedly mounting one or more battery packs (e.g., the battery pack **102**) to the structure **106**. In the present embodiment, in total eighteen mounting arrangements, such as the mounting arrangement **124**, are defined at the structure **106** of the machine **100**. The remaining mounting arrangements may be similar to the mounting arrangement **124** in construction and configuration, and hence will not be discussed. Further, higher, or lesser number of the mounting arrangements, such as the mounting arrangement **124**, may be provided at various locations on the structure **106** of the machine **100**.

[0020] A mounting assembly **128** for mounting the battery pack(s), such as the battery pack **102**, on the structure **106** of the machine **100** is now discussed. The mounting assembly **128** includes a main frame **130** and one or more auxiliary frames, such as an auxiliary frame **132**. Each of the main frame **130** and the auxiliary frame **132** is discussed with reference to FIGS. **2-4**.

[0021] The main frame **130** is an elongated main frame **134**. The elongated main frame **134** may define a first longitudinal end **136**, a second longitudinal end **138**, a first lateral end **140**, and a second lateral end **142**. Each of the first longitudinal end **136** and the second longitudinal end **138** may be spaced from one another in a direction along a longitudinal axis 'A1' of the main frame **130**, and each of the first lateral end **140** and the second lateral end **142** may be spaced from one another in a direction along a lateral axis 'A2' of the main frame **130**. Further, the main frame **130** (or the elongated main frame **134**) defines a length 'L1' that may extend between the first longitudinal end **136** and the second longitudinal end **138** along the longitudinal axis 'A1'.

[0022] The main frame **130** includes first engagement surfaces **144**, first mating features **146**, **146'**, and second mating features **148**, **148**. Further, the main frame **130** may include a first rail **150**, a

second rail **152** (shown in FIG. 3), a first longitudinal beam **154**, a second longitudinal beam **156**, a first lateral beam **158**, and a second lateral beam **160**. Furthermore, the main frame **130** may include a reinforcement beam **162**. In addition, the main frame **130** may include a first link **164**, a second link **166**, a first reinforcement plate **168**, a second reinforcement plate **170**, a third reinforcement plate **172**, mounting blocks **174**, and tiedown rings **176**.

[0023] Each of the first rail **150** and the second rail **152** may extend along the length 'L1' and between the first longitudinal end **136** and the second longitudinal end **138** of the main frame **130**. The first rail **150** and the second rail **152** may be spaced from one another in a direction along the lateral axis 'A2'. As shown in FIG. 2, the first rail **150** is disposed towards the first lateral end **140**, and the second rail **152** is disposed towards the second lateral end **142**. For explanatory purposes, the first rail **150** will be explained in detail with reference to FIGS. 2 and 3. However, it should be noted that the description provided below for the first rail **150** is equally applicable to the second rail **152**, without any limitations.

[0024] The first rail **150** may define a first end **180** (towards the first longitudinal end **136**) and a second end **182** (towards the second longitudinal end **138**). The first rail **150** may have an open cross-section shape, such as a C-shape, I-shape, or angle. In an example, as shown in FIG. 2, the first rail **150** is a C-shaped rail that includes a first end plate **184** (hereinafter referred to as 'end plate **184**'), a second end plate **186**, and a third plate **188**. The end plate **184** and the second end plate **186** may extend parallel to a plane defined by the longitudinal axis 'A1' and the lateral axis 'A2'. The third plate **188** may extend from the end plate **184** to the second end plate **186** to connect the end plate **184** with the second end plate **186**.

[0025] Further, the first rail **150** defines the first mating features **146** and the second mating features **148** of the main frame **130**. In an example, as shown in FIG. 3, the first mating features **146** and the second mating features **148** are defined at the end plate **184** of the first rail **150**. The first mating features **146** are arranged sequentially on the end plate **184** along the length 'L1' of the main frame **130**. The first mating features **146** are configured to facilitate coupling an odd number of auxiliary frames **132** to the main frame **130**. In an example, as shown in FIGS. 2 and 3, the first mating features **146** may include a set of first through-holes **190**. Similarly, the second mating features **148** are arranged sequentially on the end plate **184** along the length 'L1' of the main frame **130**. The second mating features **148** are configured to facilitate coupling an even number of auxiliary frames **132** to the main frame **130**. In an example, as shown in FIGS. 2 and 3, the second mating features **148** may include a set of second through-holes **192**.

[0026] Furthermore, the first rail **150** may define a plurality of first channels **194**. In an example, as shown in FIG. 2, the first rail **150** defines two first channels **196**, **198**. The first channels **196**, **198** may extend across the third plate **188** in a direction along the lateral axis 'A2'. The first channel **196** may be defined at a first distance from the first channel **198**. Each of the first channels **196**, **198** may include a rectangular cross-sectional shape. In other embodiments, the first channels **196**, **198** may include any suitable cross-sectional shape known in the art.

[0027] As stated above, the second rail **152** may have a construction and configuration similar to that of the first rail **150**, except that the first mating features **146** and the second mating features **148** are omitted. Instead, the second rail **152** defines the first mating features **146'** and the second mating features **148'** of the main frame **130**. In an example, as shown in FIG. 3, the first mating features **146'** and the second mating features **148'** are defined at an end plate **184** (shown in FIG. 3) of the second rail **152**. The first mating features **146'** are arranged sequentially on the end plate **184'** along the length 'L1' of the main frame **130**. The first mating features **146'** are configured to facilitate coupling an odd number of auxiliary frames **132** to the main frame **130**. In an example, as shown in FIG. 3, the first mating features **146'** may include a set of first through-holes **190**. Similarly, the second mating features **148'** are arranged sequentially on the end plate **184'** along the length 'L1' of the main frame **130**. The second mating features **148'** are configured to facilitate coupling an even number of auxiliary frames **132** to the main frame **130**. In an example, as shown

in FIG. 3, the second mating features **148'** may include a set of second through-holes **192**.

[0028] Further, instead of the first channels **194** (i.e., the first channels **196**, **198**), the second rail **152** defines a plurality of second channels **200**. In an example, as shown in FIG. 3, the second rail **152** defines two second channels **202**, **204**. The second channels **202**, **204** may extend across a third plate **188** (shown in FIG. 3) of the second rail **152** in a direction along the lateral axis 'A2'. The second channel **202** may be defined at a second distance from the second channel **204**. The second distance (between the second channels **202**, **204**) may be equal to the first distance (between the first channels **196**, **198**). Each of the second channels **202**, **204** may include a rectangular cross-sectional shape. In other embodiments, the second channels **202**, **204** may include any suitable cross-sectional shape known in the art.

[0029] The first longitudinal beam **154** may have a closed cross-section shape, such as a rectangular cross-section shape, a square cross-section shape, an oval cross-section shape, a hexagonal cross-section shape, or any irregular cross-section shape. In an example, as shown in FIGS. 2 and 3, the first longitudinal beam **154** has a rectangular cross-section shape. The first longitudinal beam **154** may include an interior cavity **206** and a wall **208** surrounding the interior cavity **206** (as shown in FIG. 3). Alternatively, the first longitudinal beam **154** may have an open cross-section shape, such as a C-channel, I-beam, or angle.

[0030] Further, the first longitudinal beam **154** may define first apertures **210**, **212**. The first apertures **210**, **212** may extend across the wall **208** of the first longitudinal beam **154** in a direction along the lateral axis 'A2'. The first aperture **210** may be defined at a third distance from the first aperture **212**. The third distance (between the first apertures **210**, **212**) may be equal to the first distance (between the first channels **196**, **198**). Each of the first apertures **210**, **212** may include a rectangular cross-sectional shape. In other embodiments, the first apertures **210**, **212** may include any suitable cross-sectional shape known in the art.

[0031] The first longitudinal beam **154** includes first connecting features **214**. The first connecting features **214** may facilitate coupling the main frame **130** (e.g., the first lateral end **140**) to the structure **106** (of the machine **100**). In an example, as shown in FIGS. 2 and 3, the first connecting features **214** includes a set of first through-bores **216** arranged sequentially along a length of the first longitudinal beam **154**. Each of the first through-bores **216** may extend from a top wall portion **218** to a bottom wall portion **220** of the wall **208** (of the first longitudinal beam **154**) in a direction transverse to the longitudinal axis 'A1' and the lateral axis 'A2'. As shown in FIG. 2, the top wall portion **218** and the end plate **184** (of the first rail **150**) lie in a common plane parallel to a plane defined by the longitudinal axis 'A1' and the lateral axis 'A2'.

[0032] The first longitudinal beam **154** may be disposed towards the first lateral end **140** of the main frame **130**. The first longitudinal beam **154** may be coupled to the first rail **150**. In an example, as shown in FIGS. 2 and 3, a portion of the wall **208** (of the first longitudinal beam **154**) may be coupled to the third plate **188** of the first rail **150**, by a welded connection (not shown) therebetween, such that the first apertures **210**, **212** (of the first longitudinal beam **154**) may correspondingly align with the first channels **196**, **198** (of the first rail **150**).

[0033] The construction and configuration of the second longitudinal beam **156** may be similar to that of the first longitudinal beam **154**, except that the first apertures **210**, **212** are omitted. Instead, the second longitudinal beam **156** may define second apertures **222**, **224**. The second apertures **222**, **224** may extend across the wall **226** of the second longitudinal beam **156** in a direction along the lateral axis 'A2'. The second aperture **222** may be defined at a fourth distance from the second aperture **224**. The fourth distance (between the second apertures **222**, **224**) may be equal to the second distance (between the second channels **202**, **204**). Each of the second apertures **222**, **224** may include a rectangular cross-sectional shape. In other embodiments, the second apertures **222**, **224** may include any suitable cross-sectional shape known in the art.

[0034] Further, the second longitudinal beam **156** includes first connecting features **214'** (shown in FIG. 3) (similar to the first connecting features **214**). The first connecting features **214'** may

facilitate coupling the main frame **130** (e.g., the second lateral end **142**) to the structure **106** (of the machine **100**). In an example, as shown in FIG. 3, the first connecting features **214'** includes a set of first through-bores **216'** arranged sequentially along a length of the second longitudinal beam **156**. Each of the first through-bores **216'** may extend from a top wall portion **228** to a bottom wall portion **230** of the wall **226** (of the second longitudinal beam **156**) in a direction transverse to the longitudinal axis 'A1' and the lateral axis 'A2'. The top wall portion **228** and the end plate **184** (of the second rail **152**) lie in a common plane parallel to a plane defined by the longitudinal axis 'A1' and the lateral axis 'A2'.

[0035] The second longitudinal beam **156** may be disposed towards the second lateral end **142** of the main frame **130**. The second longitudinal beam **156** may be coupled to the second rail **152**. In an example, as shown in FIG. 3, a portion of the wall **226** of the second longitudinal beam **156** may be coupled to the third plate **188'** of the second rail **152**, by a welded connection (not shown) therebetween, such that the second apertures **222**, **224** may correspondingly align with the second channels **202**, **204** (of the second rail **152**).

[0036] The first lateral beam **158** may extend between the first rail **150** and the second rail **152** to couple the first ends **180**, **180** of the first rail **150** and the second rail **152** respectively, for example, via welded connections. The first lateral beam **158** may have a closed cross-section shape, such as a rectangular cross-section shape, a square cross-section shape, an oval cross-section shape, a hexagonal cross-section shape, or any irregular cross-section shape. In an example, as shown in FIGS. 2 and 3, the first lateral beam **158** has a rectangular cross-section shape. The first lateral beam **158** may include an interior cavity **232** and a wall **234** surrounding the interior cavity **232**. In other embodiments, the first lateral beam **158** may have an open cross-section shape, such as a C-channel, I-beam, or angle.

[0037] Further, the first lateral beam **158** may define openings, namely-first openings **236**, **238**. The first openings **236**, **238** may extend across the wall **234** of the first lateral beam **158** in a direction along the longitudinal axis 'A1'. The first opening **236** may be defined at a fifth distance from the first opening **238**. Each of the first openings **236**, **238** may be configured to receive a work tool (e.g., a forklift tine, not shown) to facilitate a transportation of the main frame **130** from one location to another location (e.g., in a manufacturing facility), or to facilitate mounting of the main frame **130**, for example, on the structure **106** of the machine **100**.

[0038] The second lateral beam **160** may extend between the first rail **150** and the second rail **152** to couple the second ends **182**, **182** of the first rail **150** and the second rail **152** respectively, for example, via welded connections. The second lateral beam **160** may have a closed cross-section shape, such as a rectangular cross-section shape, a square cross-section shape, an oval cross-section shape, a hexagonal cross-section shape, or any irregular cross-section shape. In an example, as shown in FIGS. 2 and 3, the second lateral beam **160** has a rectangular cross-section shape. The second lateral beam **160** may include an interior cavity **240** and a walls **242** surrounding the interior cavity **240**. In other embodiments, the second lateral beam **160** may have an open cross-section shape, such as a C-channel, I-beam, or angle.

[0039] Further, the second lateral beam **160** may define openings, namely-second openings **244**, **246**. The second openings **244**, **246** may extend across the wall **242** of the second lateral beam **160**, for example, in a direction along the longitudinal axis 'A1'. The second opening **244** may be defined at a sixth distance from the second opening **246**. The sixth distance may be equal to the fifth distance (between the first openings **236**, **238**). Each of the second openings **244**, **246** may be configured to receive a work tool (e.g., a forklift tine, not shown) to facilitate transportation of the main frame **130** from one location to another location (e.g., in a manufacturing facility), or to facilitate mounting of the main frame **130**, for example, on the structure **106** of the machine **100**.

[0040] Continuing with FIG. 3, the first lateral beam **158** and the second lateral beam **160** includes second connecting features **248**, **250**, respectively. The second connecting features **248**, **250** may facilitate coupling the first longitudinal end **136** and the second longitudinal end **138** respectively

(of the main frame **130**) to the structure **106** of the machine **100**. In an example, the second connecting features **248** includes a through-bore **252** that extend through the wall **234** (of the first lateral beam **158**) in a direction transverse to the longitudinal axis 'A1' and the lateral axis 'A2', and the second connecting features **250** includes a through-bore **254** that extend through the wall **242** (of the second lateral beam **160**) in a direction transverse to the longitudinal axis 'A1' and the lateral axis 'A2'.

[0041] The reinforcement beam **162** may extend between the first lateral beam **158** and the second lateral beam **160** in a direction along the longitudinal axis 'A1' to couple the first lateral beam **158** with the second lateral beam **160**. The reinforcement beam **162** may include an interior cavity **256** and a wall **258** surrounding the interior cavity **256** (as shown in FIG. 3). The reinforcement beam **162** may define third apertures **260**, **262**. The third apertures **260**, **262** may extend across the wall **258** of the reinforcement beam **162**, for example, in a direction along the lateral axis 'A2'. The third aperture **260** may be defined at a seventh distance from the third aperture **262**. The seventh distance (between the third apertures **260**, **262**) may be equal to the first distance (between the first channels **194**, **196**).

[0042] The first link **164** may include a tubular element or a beam. The first link **164** may include a cross-sectional shape complementary to cross-sectional shapes of the first channel **196**, the second channel **202**, the first aperture **210**, the second aperture **222**, and the third aperture **260**. In an example, as shown in FIGS. 2 and 3, the first link **164** has a rectangular cross-sectional shape. The first link **164** defines a first end **264** and a second end **266**. In addition, the first link **164** includes a first pocket **268**. The first pocket **268** may extend from the first end **264** to the second end **266**. The first pocket **268** defines a first engagement surface **270** (of the first engagement surfaces **144**) of the main frame **130**. The first engagement surface **270** is configured to engage with an implement (e.g., a forklift tine) to facilitate transportation of the main frame **130** from one location to another location (e.g., in a manufacturing facility), or to facilitate mounting of the main frame **130**, for example, on the structure **106** of the machine **100**.

[0043] The first link **164** is fixedly coupled (e.g., welded) to the first rail **150** at the first end **264** and is fixedly coupled (e.g., welded) to the second rail **152** at the second end **266**, thereby coupling the first rail **150** with the second rail **152**. In an exemplary assembly, as shown in FIG. 3, the first link **164** passes through and is received within the first channel **196**, the second channel **202**, the first aperture **210**, the second aperture **222**, and the third aperture **260**. Once assembled, the first end **264** may extend outwardly from the first longitudinal beam **154** towards the first lateral end **140** (of the main frame **130**), and the second end **266** may extend outwardly from the second longitudinal beam **156** towards the second lateral end **142** (of the main frame **130**).

[0044] The second link **166** may include a tubular element or a beam. The second link **166** may include a cross-sectional shape complementary to cross-sectional shapes of the first channel **198**, the second channel **204**, the first aperture **212**, the second aperture **224**, and the third aperture **262**. In an example, as shown in FIGS. 2 and 3, the second link **166** has a rectangular cross-sectional shape. The second link **166** defines a first end **272** and a second end **274**. In addition, the second link **166** includes a second pocket **276**. The second pocket **276** may extend from the first end **272** to the second end **274**. The second pocket **276** defines a first engagement surface **278** of the first engagement surfaces **144** of the main frame **130**. The first engagement surface **278** is configured to engage with an implement (e.g., a forklift tine) to facilitate transportation of the main frame **130** from one location to another location (e.g., in a manufacturing facility), or to facilitate mounting of the main frame **130**, for example, on the structure **106** of the machine **100**.

[0045] The second link **166** is fixedly coupled (e.g., welded) to the first rail **150** at the first end **272** and is fixedly coupled (e.g., welded) to the second rail **152** at the second end **274**, thereby coupling the first rail **150** with the second rail **152**. In an exemplary assembly, as shown in FIG. 3, the second link **166** passes through and is received within the first channel **198**, the second channel **204**, the first aperture **212**, the second aperture **224**, and the third aperture **262**. Once assembled,

the first end **272** may extend outwardly from the first longitudinal beam **154** towards the first lateral end **140** (of the main frame **130**), and the second end **274** may extend outwardly from the second longitudinal beam **156** towards the second lateral end **142** (of the main frame **130**).

[0046] The first reinforcement plate **168** may be a flat elongated plate **168** having a shape in conformance with the shape of the top wall portion **218** (of the first longitudinal beam **154**) and the end plate **184** (of the first rail **150**). The first reinforcement plate **168** may define third mating features **280**, fourth mating features **282**, and third connecting features **284**. The third mating features **280** may include through-holes **286** complementary to the first through-holes **190** (i.e., the first mating features **146**). The fourth mating features **282** may include through-holes **288** complementary to the second through-holes **192** (i.e., the second mating features **148**). The third connecting features **284** may include through-holes **290** complementary to the first through-bores **216** (i.e., the first connecting features **214**).

[0047] The first reinforcement plate **168** is connected to the first longitudinal beam **154** and the first rail **150**. In an example, as shown in FIG. 2, the first reinforcement plate **168** is abutted against the top wall portion **218** (of the first longitudinal beam **154**) and the end plate **184** (of the first rail **150**), and is coupled to the top wall portion **218** and the end plate **184**, via welded connections. In this configuration, the third mating features **280** and the fourth mating features **282** are respectively aligned with their corresponding first mating features **146** and the second mating features **148** of the first rail **150**, and the third connecting features **284** are aligned with their corresponding first connecting features **214** of the first longitudinal beam **154**. Once connected to the first longitudinal beam **154** and the first rail **150**, the first reinforcement plate **168** supports the first longitudinal beam **154** and the first rail **150** to withstand loads, such as, fastening loads applied to the first through-holes **190**, the second through-holes **192**, and the first through-bores **216**, by their corresponding fasteners **292** and **294** (shown in FIGS. 6, 8, and 10).

[0048] The construction and configuration of the second reinforcement plate **170** may be similar to that of the first reinforcement plate **168**, except that the third mating features **280**, the fourth mating features **282**, and the third connecting features **284** are omitted. Instead, the second reinforcement plate **170** may define third mating features **280'**, fourth mating features **282**, and third connecting features **284**. The third mating features **280'** may include through-holes **286** complementary to the first through-holes **190'** (i.e., the first mating features **146'**). The fourth mating features **282'** may include through-holes **288'** complementary to the second through-holes **192** (i.e., the second mating features **148**). The third connecting features **284'** may include through-holes **290'** complementary to the first through-bores **216'** (i.e., the first connecting features **214'**).

[0049] The second reinforcement plate **170** is connected to the second longitudinal beam **156** and the second rail **152**, via welded connections, such that the third mating features **280'** and the fourth mating features **282'** are aligned with their corresponding first mating features **146'** and the second mating features **148** (of the second rail **152**) respectively, and the third connecting features **284'** are aligned with their corresponding first connecting features **214'** of the second longitudinal beam **156**. Once connected to the second longitudinal beam **156** and the second rail **152**, the second reinforcement plate **170** supports the second longitudinal beam **156** and the second rail **152** to withstand loads, such as, fastening loads applied to the first through-holes **190'**, the second through-holes **192**, and the first through-bores **216'**, by their corresponding fasteners **292'** and **294** (shown in FIGS. 6, 8, and 10).

[0050] The third reinforcement plate **172** may be a flat elongated plate **172**. The third reinforcement plate **172** may define fourth connecting features **298**. The fourth connecting features **298** may include through-holes **300**, **302** complementary to the through-bores **252**, **254**, respectively (i.e., the second connecting features **248**, **250**). The third reinforcement plate **172** is connected to the first lateral beam **158**, the second lateral beam **160**, and the reinforcement beam **162**, for example, via welded connections, such that the through-holes **300**, **302** are respectively aligned with their corresponding through-bores **252**, **254**. Once connected, the third reinforcement

plate **172** supports the first lateral beam **158** and the second lateral beam **160** to withstand loads, such as, fastening loads applied to the through-bores **252, 254** (or the second connecting features **248, 250**), by their respective fasteners **304, 306** (shown in FIG. **10**).

[0051] The mounting blocks **174** may be fixedly mounted on the first lateral beam **158** and the second lateral beam **160**. In an example, as shown in FIG. **2**, two mounting blocks **308, 310** (of the mounting blocks **174**) are connected on the first lateral beam **158**, for example, via welded connections. Similarly, two mounting blocks **312, 314** (of the mounting blocks **174**) are mounted on the second lateral beam **160**, for example, via welded connections. The mounting blocks **308, 310, 312, 314** may restrict movement of the auxiliary frames **132** (mounted to the main frame **130**) and the battery packs **102** (each fixedly mounted to the auxiliary frame **132**) with respect to the main frame **130**, for example, in a direction along the longitudinal axis 'A1' under loading conditions.

[0052] The tiedown rings **176** may be fixedly mounted on the first reinforcement plate **168** and the second reinforcement plate **170**. In an example, as shown in FIG. **2**, four tiedown rings **316** (of the tiedown rings **176**) are connected to the first reinforcement plate **168**, for example, via welded connections. Similarly, four tiedown rings **318** (of the tiedown rings **176**) are connected to the second reinforcement plate **170**, for example, via welded connections. The tiedown rings **316, 318** may be configured to secure the battery pack(s) **102** (fixedly mounted on the auxiliary frame **132** that, in turn, is mounted on the main frame **130**) onto the main frame **130**, for example, using a rope (not shown) that may extend between the tiedown rings **316, 318** and the battery pack(s) **102**. The tiedown rings **316, 318** enable safe and secure transportation of the battery pack(s) **102** along with corresponding auxiliary frame **132** and the main frame **130**.

[0053] Referring to FIG. **4**, an auxiliary frame **400** of the one or more auxiliary frames **132** is discussed. It should be noted that the description provided below for the auxiliary frame **400** is equally applicable to the remaining auxiliary frames **132**, without any limitations. The auxiliary frame **400** may define a third longitudinal end **402**, a fourth longitudinal end **404**, a third lateral end **406**, and a fourth lateral end **408**. Each of the third longitudinal end **402** and the fourth longitudinal end **404** may be spaced from one another in a direction along a longitudinal axis 'A3' of the auxiliary frame **400**, and each of the third lateral end **406** and the fourth lateral end **408** may be spaced from one another in a direction along a lateral axis 'A4' of the auxiliary frame **400**. Further, the auxiliary frame **400** defines a length 'L2' that may extend between the third longitudinal end **402** and the fourth longitudinal end **404** along the longitudinal axis 'A3'.

[0054] The auxiliary frame **400** includes mounting features **410**, second engagement surfaces **412**, and coupling features **414**. In addition, the auxiliary frame **400** may include a third rail **416**, a fourth rail **418**, a third link **420**, and a fourth link **422**.

[0055] Each of the third rail **416** and the fourth rail **418** may extend along the length 'L2' and between the third longitudinal end **402** and the fourth longitudinal end **404** of the auxiliary frame **400**. The third rail **416** and the fourth rail **418** may be spaced from one another in a direction along the lateral axis 'A4'. As shown in FIG. **4**, the third rail **416** is disposed towards the third lateral end **406**, and the fourth rail **418** is disposed towards the fourth lateral end **408**.

[0056] The third rail **416** may define a first end **424** (towards the third longitudinal end **402**) and a second end **426** (towards the fourth longitudinal end **404**). The third rail **416** may have an open cross-section shape. In an example, as shown in FIG. **4**, the third rail **416** defines a base portion **428** and a ridge **430**. The base portion **428** may extend between the first end **424** and the second end **426**. In addition, the base portion **428** may extend parallel to a plane defined by the longitudinal axis 'A3' and the lateral axis 'A4'. The ridge **430** may extend outwardly from the base portion **428** in a direction transverse to the longitudinal axis 'A3' and the lateral axis 'A4' to define a ridge top surface **432** away from the base portion **428**. The ridge top surface **432** may extend parallel to a plane defined by the longitudinal axis 'A3' and the lateral axis 'A4'.

[0057] Further, the third rail **416** may define a plurality of third channels **434**. In an example, as

shown in FIG. 4, the third rail **416** defines third channels **436, 438**. The third channels **436, 438** may be sequentially defined on the third rail **416** in a direction along the longitudinal axis 'A4'. The third channels **436, 438** may extend across the base portion **428** and the ridge **430**, for example, in a direction along the lateral axis 'A4'. The third channels **436, 438** may include a rectangular cross-sectional shape. In other embodiments, the third channels **436, 438** may include any suitable cross-sectional shape known in the art.

[0058] The fourth rail **418** may define a first end **440** (towards the third longitudinal end **402**) and a second end **442** (towards the fourth longitudinal end **404**). The fourth rail **418** may have an open cross-section shape. In an example, as shown in FIG. 4, the fourth rail **418** defines a base portion **444** and a ridge **446**. The base portion **444** may extend between the first end **440** and the second end **442**. In addition, the base portion **444** may extend parallel to a plane defined by the longitudinal axis 'A3' and the lateral axis 'A4'. The ridge **446** may extend outwardly from the base portion **444** in a direction transverse to the longitudinal axis 'A3' and the lateral axis 'A4' to define a ridge top surface **448** away from the base portion **444**. The ridge top surface **448** may extend parallel to a plane defined by the longitudinal axis 'A3' and the lateral axis 'A4'.

[0059] Further, the fourth rail **418** may define a plurality of fourth channels **450**. In an example, as shown in FIG. 4, the fourth rail **418** defines fourth channels **452, 454**. The fourth channels **452, 454** may be sequentially defined on the fourth rail **418** in a direction along the longitudinal axis 'A4'. The fourth channels **452, 454** may extend across the base portion **444** and the ridge **446**, for example, in a direction along the lateral axis 'A4'. The fourth channels **452, 454** may include a rectangular cross-sectional shape. In other embodiments, the fourth channels **452, 454** may include any suitable cross-sectional shape known in the art.

[0060] Mounting features **456, 456'** (of the mounting features **410**) are defined on the ridge top surfaces **432, 448**, respectively. The mounting features **456** may be arranged sequentially on the ridge top surface **432** (of the third rail **416**), and the mounting features **456'** may be arranged sequentially on the ridge top surface **448** (of the fourth rail **418**). In an example, as shown in FIG. 4, the mounting features **456, 456'** include mounting through-holes **458, 458**, respectively. The mounting features **456, 456'** (or mounting through-holes **458, 458**) are configured to facilitate fixedly mounting one battery pack **102** on the auxiliary frame **400**. In other embodiments, the mounting features **456, 456'** may facilitate fixedly mounting more than one battery pack **102** on the auxiliary frame **400**.

[0061] Continuing with FIG. 4, the third link **420** and the fourth link **422** are discussed. The third link **420** may include a tubular element, or a beam. The third link **420** may include a cross-sectional shape complementary to cross-sectional shapes of the third channel **436** and the fourth channel **452**. In an example, as shown in FIG. 4, the third link **420** has a rectangular cross-sectional shape. The third link **420** defines a first end **460** and a second end **462**. In addition, the third link **420** includes a third pocket **464**. The third pocket **464** may extend from the first end **460** to the second end **462**. The third pocket **464** defines a second engagement surface **466** of the second engagement surfaces **412** of the auxiliary frame **400**. The second engagement surface **466** is configured to engage with an equipment (e.g., a forklift tine) to facilitate transportation of the auxiliary frame **400** from one location to another location (e.g., in a manufacturing facility), or to facilitate mounting of the auxiliary frame **400** on the main frame **130**.

[0062] The third link **420** is fixedly coupled to the third rail **416** and the fourth rail **418**. In an exemplary assembly, as shown in FIG. 4, the third link **420** passes through and is received within the third channel **436** and the fourth channel **452** such that the third link **420** is coupled (e.g., welded) to the third rail **416** at the first end **460** and to the fourth rail **418** at the second end **462**, thereby coupling the third rail **416** with the fourth rail **418**.

[0063] The fourth link **422** may include a tubular element, or a beam. The fourth link **422** may include a cross-sectional shape complementary to cross-sectional shapes of the third channel **438** and the fourth channel **454**. In an example, as shown in FIG. 4, the fourth link **422** has a

rectangular cross-sectional shape. The fourth link 422 defines a first end 468 and a second end 470. In addition, the fourth link 422 includes a fourth pocket 472. The fourth pocket 472 may extend from the first end 468 to the second end 470. The fourth pocket 472 defines a second engagement surface 474 of the second engagement surfaces 412 of the auxiliary frame 400. The second engagement surface 474 is configured to engage with an equipment (e.g., a forklift tine) to facilitate transportation of the auxiliary frame 400 from one location to another location (e.g., in a manufacturing facility), or to facilitate mounting of the auxiliary frame 400 on the main frame 130. [0064] The fourth link 422 is fixedly coupled to the third rail 416 and the fourth rail 418. In an exemplary assembly, as shown in FIG. 4, the fourth link 422 passes through and is received within the third channel 438 and the fourth channel 454 such that the fourth link 422 is coupled (e.g., welded) to the third rail 416 at the first end 468 and to the fourth rail 418 at the second end 470, thereby coupling the third rail 416 with the fourth rail 418.

[0065] The coupling features 414 includes coupling features 476, 476'. The coupling features 476 are defined on the base portion 428, the third link 420 (e.g., towards the first end 460), and the fourth link 422 (e.g., towards the first end 468). The coupling features 476 may be arranged sequentially on the base portion 428, the third link 420, and the fourth link 422 in a direction along the longitudinal axis 'A3'. In an example, as shown in FIG. 4, the coupling features 476 include a set of third through-holes 478. Similarly, the coupling features 476' are defined on the base portion 444, the third link 420 (e.g., towards the second end 462), and the fourth link 422 (e.g., towards the second end 470). The coupling features 476' may be arranged sequentially on the base portion 444, the third link 420, and the fourth link 422 in a direction along the longitudinal axis 'A3'. In an example, as shown in FIG. 4, the coupling features 476' include a set of third through-holes 478.

[0066] The coupling features 476, 476' facilitates mounting the auxiliary frame 400 onto the main frame 130. In one instance, the coupling features 476, 476' (i.e., third through-holes 478, 478) are configured to correspondingly engage (e.g., via respective fasteners 292, 292) with the first mating features 146, 146 (i.e., first through-holes 190, 190) of the main frame 130 when a number of the auxiliary frames 132 to be coupled to the main frame 130 is odd, for example, one auxiliary frame 400 (as shown in FIGS. 6 and 7). In another instance, the coupling features 476, 476' (i.e., third through-holes 478, 478) are configured to correspondingly engage (e.g., via respective fasteners 292, 292') with the second mating features 148, 148 (i.e., second through-holes 192, 192') of the main frame 130 when a number of the auxiliary frames 132 to be coupled to the main frame 130 is even, for example, two auxiliary frames 400, 400 (respectively carrying two battery packs 102, 102) (as shown in FIGS. 8 and 9).

[0067] Additionally, the auxiliary frame 400 may include a first set of reinforcement plates 480 and a second set of reinforcement plates 480. The reinforcement plates 480 may be fixedly coupled (e.g., welded) to the base portion 428. As shown in FIG. 4, the reinforcement plates 480 define through-holes 482 complementary to the third through-holes 478 (i.e., the coupling features 476). In an exemplary assembly of the reinforcement plates 480 with the base portion 428, the reinforcement plates 480 are placed on the base portion 428 such that the through-holes 482 are aligned with their corresponding third through-holes 478, and are welded to the base portion 428. Once coupled, the reinforcement plates 480 support the auxiliary frame 400 to withstand loads, such as, fastening loads applied to the third through-holes 478 by the fasteners 292.

[0068] The reinforcement plates 480' may be fixedly coupled (e.g., welded) to the base portion 444. As shown in FIG. 4, the reinforcement plates 480' define through-holes 482 complementary to the third through-holes 478 (i.e., the coupling features 476'). In an exemplary assembly of the reinforcement plates 480' with the base portion 444, the reinforcement plates 480' are placed on the base portion 444 such that the through-holes 482' are aligned with their corresponding third through-holes 478, and are welded to the base portion 444. Once coupled, the reinforcement plates 480' support the auxiliary frame 400 to withstand loads, such as, fastening loads applied to the third through-holes 478 by the fasteners 292.

[0069] In some embodiments, the auxiliary frame **400** may include reinforcement ribs, such as ribs **484, 484'**. The ribs **484** may be fixedly coupled to the base portion **428**, the third link **420**, and the fourth link **422**. The ribs **484** may be fixedly coupled to the base portion **444**, the third link **420**, and the fourth link **422**. The ribs **484, 484'** may support the auxiliary frame **400** in retaining its shape under loading.

INDUSTRIAL APPLICABILITY

[0070] An exemplary method for mounting one or more battery packs, such as the battery pack **102, 102**, to the machine **100** is discussed. The method is discussed in conjunction with FIGS. 5-10. Initially, the one or more battery packs **102** are assembled with the one or more auxiliary frames **132**. In an exemplary assembly of the battery pack **102** with the auxiliary frame **400** (of the auxiliary frames **132**), as shown in FIG. 5, the battery pack **102** is placed on the ridge top surfaces **432, 448** such that the mounting through-holes **458, 458** are aligned with their corresponding fastening holes (not shown) formed on the housing **104** of the battery pack **102**. Subsequently, fasteners **486, 486'** are inserted into their respective mounting through-holes **458, 458** and the fastening holes (formed on the housing **104**) to fixedly secure the battery pack **102** to the auxiliary frame **400**.

[0071] Next, the one or more auxiliary frames **132** (along with their respective battery pack(s) **102** mounted thereon) are coupled to the main frame **130**. In an exemplary assembly of an odd number of auxiliary frames **132** (e.g., one auxiliary frame **400**) with the main frame **130**, as shown in FIGS. 6 and 7, the auxiliary frame **400** is transported and mounted on the main frame **130**, for example, by using tines of the equipment (e.g., forklift) (not shown) received within their corresponding second engagement surfaces **412** (e.g., second engagement surfaces **466, 474**) of the auxiliary frame **400**. The auxiliary frame **400** is mounted onto the main frame **130** in a manner such that the base portions **428, 444** (of the auxiliary frame **400**) are placed on the first reinforcement plate **168** and the second reinforcement plate **170**, respectively, of the main frame **130**. In addition, the auxiliary frame **400** is positioned onto the main frame **130** such that the coupling features **476, 476** (i.e., third through-holes **478, 478**) (and the through-holes **482, 482**) are aligned with their corresponding first mating features **146, 146'** (i.e., first through-holes **190, 190'**) (and the through-holes **286, 286'**) of the main frame **130**. Next, the fasteners **292, 292** are inserted into the corresponding third through-holes **478, 478**, the through-holes **482, 482**, the first through-holes **190, 190**, and the through-holes **286, 286'**, and are tightened to fixedly secure the auxiliary frame **400** to the main frame **130**.

[0072] When the odd number of the auxiliary frames **132**, such as the auxiliary frame **400**, is mounted on the main frame **130** in the above-discussed configuration, a geometrical center (lying along a dashed line 'B' bisecting the length 'L2' of the auxiliary frame **400**, as shown in FIG. 4) of the auxiliary frame **400** lies on or along a plane 'P' symmetrically bisecting the main frame **130** about the length 'L1' of the main frame **130**, as shown in FIGS. 3 and 7. As a result of this mounting arrangement for odd number of the auxiliary frames **132**, a center of gravity defined combinedly by the battery pack **102** and the mounting assembly **128** (i.e., the auxiliary frame **400** and the main frame **130**) may be defined on or along the plane 'P'.

[0073] Referring to FIGS. 8 and 9, an exemplary assembly of an even number of auxiliary frames **132** (e.g., two auxiliary frames **400, 400'** with their corresponding battery packs **102**) with the main frame **130** is discussed. The auxiliary frames **400, 400** are transported and mounted (simultaneously as shown in FIGS. 6 and 7, or one at a time in a serial manner), for example, by using tines of the equipment in the same manner as explained in FIGS. 6 and 7. The auxiliary frames **400, 400** is mounted onto the main frame **130** in a manner such that the base portions **428, 444** of each of the auxiliary frames **400, 400'** are placed on the first reinforcement plate **168** and the second reinforcement plate **170**, respectively, of the main frame **130**. In addition, each of the auxiliary frames **400, 400** is positioned onto the main frame **130** such that its corresponding coupling features **476, 476'** (i.e., third through-holes **478, 478**) (and the through-holes **482, 482**) are

aligned with their respective second mating features **148, 148** (i.e., second through-holes **192, 192'**) (and the through-holes **288, 288**) of the main frame **130**. Next, the fasteners **292, 292'** are inserted into their corresponding third through-holes **478, 478**, the through-holes **482, 482**, the second through-holes **192, 192**, and the through-holes **288, 288**, and are tightened to fixedly secure each of the auxiliary frames **400, 400** to the main frame **130**.

[0074] When the even number of the auxiliary frames **132**, such as two auxiliary frames **400, 400'**, is mounted on the main frame **130** in the above-discussed configuration, an end of one of the auxiliary frames **132** lies on or along the plane 'P' symmetrically bisecting the main frame **130** about the length 'L1' of the main frame **130**. For instance, as shown in FIG. 9, at least one of the fourth longitudinal end **404** (of the auxiliary frame **400**) and the third longitudinal end **402** (of the auxiliary frame **400'**) lies on or along the plane 'P'. As a result of this mounting arrangement for even number of the auxiliary frames **132**, a center of gravity defined combinedly by the battery pack **102** and the mounting assembly **128** (i.e., the auxiliary frame **400** and the main frame **130**) may be defined on or along the plane 'P'.

[0075] Referring to FIG. 10, coupling of the main frame **130** (along with one auxiliary frame **400** mounted thereon) to the structure **106** of the machine **100** is discussed. Once the auxiliary frame **400** (along with the battery pack **102** mounted thereon) is fixedly coupled to the main frame **130**, the main frame **130** may be transported and placed on the structure **106**, for example, by using tines of the implement (e.g., forklift) (not shown) received within the corresponding first engagement surfaces **144** (e.g., first engagement surfaces **270, 278**) of the main frame **130**. The main frame **130** is placed on the structure **106** in a manner that the first connecting features **214, 214** (i.e., the first through-bores **216, 216'**), the second connecting features **248, 250** (i.e., the through-bores **252, 254**), the third connecting features **284, 284** (i.e., the through-holes **290, 290'**), and the fourth connecting features **298** (i.e., the through-holes **300, 302**) are aligned with their corresponding mounting arrangements **124**. Subsequently, the fasteners **294, 294, 304, 306** are inserted into their corresponding first through-bores **216, 216'**, the through-bores **252, 254**, the through-holes **290, 290'**, and the through-holes **300, 302**, and are tightened to fixedly secure the main frame **130** to the structure **106** of the machine **100**.

[0076] The mounting assembly **128** may be retrofitted (removably) on any machine having a structure, such as the structure **106**. The mounting assembly **128** provides a simple and cost-effective solution for mounting battery packs (e.g., the battery pack **102**) of varying configurations and types, onto a variety of machines, such as the machine **100**. As a result, the mounting assembly **128** may reduce and/or eliminate requirement of different battery mounting structures for mounting different types of battery packs onto different types of machines, thereby reducing overall cost and inventory. In addition, the mounting assembly **128** is provided with provisions (e.g., the first pocket **268**, the second pocket **276**, the third pocket **464**, the fourth pocket **472**, the first openings **236, 238**, and the second openings **244, 246** that facilitate easy and secure transportation and mounting of the battery packs **102** (mounted thereon).

[0077] Unless explicitly excluded, the use of the singular to describe a component, structure, or operation does not exclude the use of plural such components, structures, or operations or their equivalents. The use of the terms "a" and "an" and "the" and "at least one" or the term "one or more," and similar referents in the context of describing the invention (especially in the context of the following claims) are to be construed to cover both the singular and the plural, unless otherwise indicated herein or clearly contradicted by context. The use of the term "at least one" followed by a list of one or more items (for example, "at least one of A and B" or one or more of A and B") is to be construed to mean one item selected from the listed items (A or B) or any combination of two or more of the listed items (A and B; A, A and B; A, B and B), unless otherwise indicated herein or clearly contradicted by context. Similarly, as used herein, the word "or" refers to any possible permutation of a set of items. For example, the phrase "A, B, or C" refers to at least one of A, B, C, or any combination thereof, such as any of: A; B; C; A and B; A and C; B and C; A, B, and C; or

multiple of any item such as A and A; B, B, and C; A, A, B, C, and C; etc.

[0078] It will be apparent to those skilled in the art that various modifications and variations can be made to the mounting assembly and/or the method of the present disclosure without departing from the scope of the disclosure. Other embodiments will be apparent to those skilled in the art from consideration of the specification and practice of the mounting assembly and/or the method disclosed herein. It is intended that the specification and examples be considered as exemplary only, with a true scope of the disclosure being indicated by the following claims and their equivalent.

Claims

1. A mounting assembly for mounting one or more battery packs to a machine, the mounting assembly comprising: a main frame configured to be coupled to a structure of the machine and including first engagement surfaces to engage with an implement to facilitate at least one of a transportation or a mounting of the main frame on the structure, the main frame defining first mating features and second mating features; and one or more auxiliary frames configured to be coupled to the main frame, each auxiliary frame including: mounting features to fixedly mount the one or more battery packs on the auxiliary frame; second engagement surfaces to engage with an equipment to facilitate at least one of a transportation or a mounting of the auxiliary frame on the main frame; and coupling features configured to be engaged with: the first mating features when a number of the one or more auxiliary frames to be coupled to the main frame is odd, and the second mating features when a number of the one or more auxiliary frames to be coupled to the main frame is even.
2. The mounting assembly of claim 1, wherein the main frame is an elongated main frame defining a length, the one or more auxiliary frames are serially mountable onto the elongated main frame along the length such that a center of gravity defined combinedly by the mounting assembly and the one or more battery packs is defined on or along a plane symmetrically bisecting the elongated main frame about the length of the elongated main frame.
3. The mounting assembly of claim 2, wherein the main frame includes a first rail and a second rail spaced from the first rail, each of the first rail and the second rail defines an end plate, wherein the first mating features and the second mating features are defined in the end plate.
4. The mounting assembly of claim 3, wherein the first rail defines a plurality of first channels and the second rail defines a plurality of second channels, wherein the main frame includes: a first link and a second link received within their corresponding first and second channels coupling the first rail with the second rail, the first link includes a first pocket, the second link including a second pocket, and wherein each of the first pocket and the second pocket includes the first engagement surfaces.
5. The mounting assembly of claim 3, wherein the main frame includes: a first longitudinal beam coupled to the first rail; and a second longitudinal beam coupled to the second rail, wherein each of the first longitudinal beam and the second longitudinal beam includes first connecting features to facilitate coupling the main frame to the structure of the machine.
6. The mounting assembly of claim 5, wherein each of the first rail and the second rail defines a first end and a second end spaced from the first end, wherein the main frame includes: a first lateral beam extending between the first rail and the second rail coupling the first end of the first rail with the first end of the second rail; and a second lateral beam extending between the first rail and the second rail coupling the second end of the first rail with the second end of the second rail, wherein at least one of the first lateral beam and the second lateral beam defines a plurality of openings configured to receive a work tool to facilitate at least one of a transportation or a mounting of the main frame on the structure of the machine.
7. The mounting assembly of claim 6, wherein each of the first lateral beam and the second lateral

beam includes second connecting features to facilitate coupling the main frame to the structure of the machine.

8. The mounting assembly of claim 7, wherein the main frame includes: a plurality of mounting blocks fixedly mounted on the first lateral beam and the second lateral beam, each mounting block of the plurality of mounting blocks is configured to restrict movement of the one or more auxiliary frames and the one or more battery packs with respect to the main frame in a direction along the length of the main frame.

9. The mounting assembly of claim 5, wherein the main frame includes: a plurality of tiedown rings fixedly mounted on the first longitudinal beam and the second longitudinal beam, each tiedown ring of the plurality of tiedown rings is configured to secure the one or more battery packs to the main frame to facilitate transportation of the one or more battery packs and the mounting assembly.

10. The mounting assembly of claim 2, wherein each auxiliary frame includes a third rail and a fourth rail spaced from the third rail, each of the third rail and the fourth rail defines a base portion and a ridge extending outwardly from the base portion to define a ridge top surface away from the base portion, and wherein the mounting features being defined in the ridge top surface.

11. The mounting assembly of claim 10, wherein the third rail defines a plurality of third channels, the fourth rail defines a plurality of fourth channels, wherein each auxiliary frame includes: a third link and a fourth link received within their corresponding third and fourth channels coupling the third rail with the fourth rail, and wherein the coupling features being defined in the base portion, the third link, and the fourth link.

12. The mounting assembly of claim 11, wherein the third link includes a third pocket, the fourth link includes a fourth pocket, and wherein each of the third pocket and the fourth pocket includes the second engagement surfaces.

13. The mounting assembly of claim 1, wherein the first mating features include a set of first through-holes, the second mating features include a set of second through-holes, and the coupling features include a set of third through-holes.

14. A method for mounting one or more battery packs to a machine, the method comprising: coupling a main frame to a structure of the machine, the main frame including first engagement surfaces to engage with an implement to facilitate at least one of a transportation or a mounting of the main frame on the structure, the main frame defining first mating features and second mating features; coupling one or more auxiliary frames to the main frame, each auxiliary frame including: mounting features to fixedly mount the one or more battery packs on the auxiliary frame; second engagement surfaces to engage with an equipment to facilitate at least one of a transportation or a mounting of the auxiliary frame on the main frame; and coupling features configured to be engaged with: the first mating features when a number of the one or more auxiliary frames to be coupled to the main frame is odd, and the second mating features when a number of the one or more auxiliary frames to be coupled to the main frame is even.

15. The method of claim 14, wherein the main frame is an elongated main frame defining a length, wherein coupling the one or more auxiliary frames to the main frame includes: serially mounting an odd number of the one or more auxiliary frames on the elongated main frame along the length such that a geometrical center of one of the one or more auxiliary frames lies on or along a plane symmetrically bisecting the elongated main frame about the length of the elongated main frame; and serially mounting an even number of the one or more auxiliary frames on the elongated main frame along the length such that an end of one of the one or more auxiliary frames lies on or along the plane symmetrically bisecting the elongated main frame about the length of the elongated main frame.

16. The method of claim 14, wherein the main frame includes a first rail and a second rail spaced from the first rail, each of the first rail and the second rail defines an end plate, wherein the first mating features and the second mating features are defined in the end plate.

17. The method of claim 16, wherein the first rail defines a plurality of first channels and the

second rail defines a plurality of second channels, wherein the main frame includes: a first link and a second link received within their corresponding first and second channels coupling the first rail with the second rail, the first link includes a first pocket, the second link including a second pocket, and wherein each of the first pocket and the second pocket includes the first engagement surfaces.

18. The method of claim 17, wherein each of the first rail and the second rail defines a first end and a second end spaced from the first end, the main frame includes: a first longitudinal beam coupled to the first rail and a second longitudinal beam coupled to the second rail; a first lateral beam extending between the first rail and the second rail coupling the first end of the first rail with the first end of the second rail; and a second lateral beam extending between the first rail and the second rail coupling the second end of the first rail with the second end of the second rail, wherein: each of the first longitudinal beam and the second longitudinal beam includes first connecting features to facilitate coupling the main frame to the structure of the machine, and at least one of the first lateral beam and the second lateral beam defines a plurality of openings configured to receive a work tool to facilitate at least one of a transportation or a mounting of the main frame on the structure of the machine.

19. The method of claim 14, wherein each auxiliary frame includes a third rail and a fourth rail spaced from the third rail, each of the third rail and the fourth rail defines a base portion and a ridge extending outwardly from the base portion to define a ridge top surface away from the base portion, and wherein the mounting features being defined in the ridge top surface.

20. The method of claim 19, wherein the third rail defines a plurality of third channels, the fourth rail defines a plurality of fourth channels, each auxiliary frame includes: a third link and a fourth link received within their corresponding third and fourth channels coupling the third rail with the fourth rail, the third link includes a third pocket, the fourth link includes a fourth pocket, wherein: the coupling features being defined in the base, the third link, and the fourth link, and each of the third pocket and the fourth pocket includes the second engagement surfaces.
