

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250287299

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

GOLDBERG; ADAM et al.

EXTERNAL NETWORK CONNECTIVITY BASED ON ACCESS POINT HANDOVER THROUGH MESH NETWORK

Abstract

An electronic device and a method is provided for external network connectivity based on access point handover through mesh network. A first access point associated with a first wireless network is detected within a first predefined radius. A first connection with the first wireless network is established, based on the first access point being within the first predefined radius. It is determined whether an external network is accessible, based on the established first connection. Detection of a second access point associated with a second wireless network within a second predefined radius from the first access point is controlled. It is determined whether the external network is accessible from the second access point, through the mesh network. The establishment of a second connection between the first access point and the second access point is controlled, based on the external network being accessible from the second access point, through the mesh network.

Inventors: GOLDBERG; ADAM (SAN DIEGO, CA), FAY; LUKE (SAN DIEGO, CA)

Applicant: SONY GROUP CORPORATION (TOKYO, JP)

Family ID: 95024849

Appl. No.: 18/596557

Filed: March 05, 2024

Publication Classification

Int. Cl.: H04W48/20 (20090101); H04W36/30 (20090101); H04W84/18 (20090101)

U.S. Cl.:

CPC H04W48/20 (20130101); H04W36/302 (20230501); H04W84/18 (20130101)

Background/Summary

REFERENCE

[0001] None

FIELD

[0002] Various embodiments of the disclosure relate to external network connectivity. More specifically, various embodiments of the disclosure relate to an electronic device and a method for external network connectivity based on access point handover through mesh network.

BACKGROUND

[0003] Advancements in the field of information and communication technology (ICT) have led to development of electronic devices that may be capable of communicating with one another through wireless networks. An electronic device may use a communication channel to transmit media content to other devices. Quality of a communication channel used to transmit the media content by the electronic device may be based on a set of connectivity parameters associated with the communication channel. For example, the set of connectivity parameters may include, but is not limited to, a signal strength, a signal-to-noise (SNR) ratio, a bit error rate (BER), and a cross-channel interference.

[0004] To connect to external networks, an electronic device may connect to an access point, such as, a base station. The access point may establish a connection between the electronic device and the external networks. Typically, there may be various limitations in the connection between the electronic device and the external networks, via the access points. For example, a signal strength of the connection may reduce with distance of the electronic device and the access point. The weaker is the signal strength, the lower may be the quality of a communication channel that may be established between the electronic device and the external network. However, a reduction of the distance between the electronic device and the access point may improve the signal strength, but may reduce the mobility of the electronic device. In such a scenario, the electronic device may be moved within a limited region in a vicinity of the access point for better signals and connectivity.

[0005] Limitations and disadvantages of conventional and traditional approaches will become apparent to one of skill in the art, through comparison of described systems with some aspects of the present disclosure, as set forth in the remainder of the present application and with reference to the drawings.

SUMMARY

[0006] An electronic device and method for external network connectivity based on access point handover through mesh network is provided substantially as shown in, and/or described in connection with, at least one of the figures, as set forth more completely in the claims.

[0007] These and other features and advantages of the present disclosure may be appreciated from a review of the following detailed description of the present disclosure, along with the accompanying figures in which like reference numerals refer to like parts throughout.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] FIG. 1 is a block diagram that illustrates an exemplary network environment for external network connectivity based on access point handover through mesh network, in accordance with an embodiment of the disclosure.

[0009] FIG. 2 is a block diagram that illustrates an exemplary electronic device of FIG. 1, in accordance with an embodiment of the disclosure.

[0010] FIG. 3A is a diagram that illustrates an exemplary processing pipeline for external network

connectivity based on access point handover through mesh network, in accordance with an embodiment of the disclosure.

[0011] FIG. 3B is a diagram that illustrates an exemplary processing pipeline for external network connectivity based on access point handover through mesh network, in accordance with an embodiment of the disclosure.

[0012] FIG. 4A is a flowchart that illustrates operations of an exemplary method for third access point detection, in accordance with an embodiment of the disclosure.

[0013] FIG. 4B is a flowchart that illustrates operations of an exemplary method for fourth access point detection, in accordance with an embodiment of the disclosure.

[0014] FIG. 4C is a flowchart that illustrates operations of an exemplary method for fifth access point detection, in accordance with an embodiment of the disclosure.

[0015] FIG. 5 is a flowchart that illustrates operations of an exemplary method for external network connectivity based on access point handover through mesh network, in accordance with an embodiment of the disclosure.

DETAILED DESCRIPTION

[0016] The following described implementation may be found in an electronic device and method for external network connectivity based on access point handover through a mesh network.

Exemplary aspects of the disclosure may provide an electronic device that may detect a first access point associated with a first wireless network within a first predefined radius. The electronic device may establish a first connection with the first wireless network, based on the first access point being within the first predefined radius. Further, the electronic device may determine whether an external network is accessible, based on the established first connection. The electronic device may control detection of a second access point associated with a second wireless network within a second predefined radius from the detected first access point. The control of the detection of the second access point may be based on the external network being inaccessible, and the first wireless network and the second wireless network may correspond to a mesh network of a set of interconnected access points. Furthermore, the electronic device may determine whether the external network is accessible from the second access point, through the mesh network. The electronic device may control establishment of a second connection between the first access point and the second access point, based on the external network being accessible from the second access point, through the mesh network, where the electronic device is connected to the external network through the established first connection and the control of the established second connection.

[0017] To connect to external networks, an electronic device may connect to an access point, such as, a base station. The access point may establish a connection between the electronic device and the external networks. Typically, there may be various limitations in the connection between the electronic device and the external networks, via the access points. For example, a signal strength of the connection may reduce with distance of the electronic device and the access point. The weaker is the signal strength, the lower may be the quality of a communication channel that may be established between the electronic device and the external network. However, a reduction of the distance between the electronic device and the access point may improve the signal strength, but may reduce the mobility of the electronic device. In such a scenario, the electronic device may be moved within a limited region in a vicinity of the access point for better signals and connectivity.

[0018] The electronic device of the present disclosure may provide connection with the external network through an access point handover in a mesh network including a set of interconnected access points. The electronic device may detect an access point within a certain radius from the electronic device. In case, an access point is identified within the particular radius from the electronic device, the electronic device may establish a connection with the access point through a wireless network associated with the particular access point. The electronic device may then determine whether an external network is accessible from the access point. In case, the external network is inaccessible directly from the access point, an accessibility to the external network from

another access point within a certain radius of the initial access point may be determined. In case, the external network is determined to be accessible from the other access point (i.e., a one-hop access point), the initial access point and the one-hop access point may be connected (e.g., through a mesh network) with each other to provide an end-to-end connectivity with the external network to the electronic device. Thus, the connectivity range of the electronic device to the external network may be extended based on connectivity of the directly connected access point with a one-hop access point connected to the external network. The connectivity range may be extended further based on more than one intermediate access points with a certain access point (an n-hop access point) being connected to the external network. Also, based on the distance of the electronic device with nearby access points, a handover between access points in the mesh network may take place. Such handovers may maintain a signal strength of the connection of the electronic device to the external network, while the mobility of the electronic device may also be maintained.

[0019] FIG. 1 is a block diagram that illustrates an exemplary network environment for external network connectivity based on access point handover through mesh network, in accordance with an embodiment of the disclosure. With reference to FIG. 1, there is shown a network environment **100**. The network environment **100** may include an electronic device **102**, a first access point **104**, a second access point **108**, a server **106**, and a communication network **110**. Further, the network environment **100** may include a first wireless network **104A** associated with the first access point **104**, and may further include a second wireless network **108A** associated with the second access point **108**. The first access point **104** may be situated at a first location **114** and the second access point **108** may be situated at a second location **116**. In FIG. 1, there is further shown a user **112** who may be associated with and/or control the operation of the electronic device **102**.

[0020] The electronic device **102** may include suitable logic, circuitry, interfaces, and/or code that may be configured to detect the first access point **104** associated with the first wireless network **104A** within a first predefined radius of the electronic device **102**. The electronic device **102** may establish a first connection with the first wireless network **104A**, based on the first access point **104** being within the first predefined radius. Further, the electronic device **102** may determine whether an external network is accessible, based on the established first connection. The electronic device **102** may control detection of the second access point **108** associated with the second wireless network **108A** within a second predefined radius from the detected first access point **104**. The first wireless network **104A** and the second wireless network **108A** may correspond to a mesh network of a set of interconnected access points. The electronic device **102** may determine whether the external network is accessible from the second access point **108**, through the mesh network. Further, the electronic device **102** may control establishment of a second connection between the first access point **104** point and the second access point **108**, based on the external network being accessible from the second access point **108**, through the mesh network. Examples of the electronic device **102** may include, but are not limited to, a computing device, a smartphone, a cellular phone, a mobile phone, a gaming device, a mainframe machine, a server, a computer workstation, a communication device (enabled with or hosting, for example, a computing resource, a memory resource, and a networking resource), a television, a radio device, a display device, and/or a streaming device.

[0021] Each of the first access point **104** and the second access point **108** may include a communication medium through which the electronic device **102** and the server **106** may communicate with one another. For example, the first access point **104** (and/or the second access point **108**) may be a device that may be configured to provide a wireless connectivity through a wireless local area network, or WLAN, typically in a home, an office, a building, or any other indoor or outdoor premises. The first access point **104** (and/or the second access point **108**) may correspond to, for example, a Wi-Fi router, a Wi-Fi hotspot, switch, or hub via an Ethernet cable, for connection to an external network, through one or more other access points and/or servers.

[0022] In an embodiment, the first access point **104** may be associated with the first wireless

network **104A** within a first predefined radius of the electronic device **102**. Further, the second access point **108** may be associated with the second wireless network **108A** within a second predefined radius of the first access point **104**. The first wireless network **104A** and the second wireless network **108A** may correspond to a mesh network of a set of interconnected access points. Each of the first wireless network **104A** and the second wireless network **108A** may be defined by a coverage area (CA) associated with the first access point **104** and the second access point **108**, respectively. In an embodiment, a coverage area of an access point may be a certain area that is within proximity of the particular access point in which a device may be able to connect to another device or any access point, through the particular access point. In an example, the coverage area may have a regular (e.g. circular, rectangular, etc.) shape or an irregular shape. In case, the coverage area has a circular shape, the coverage area of the access point may be calculated by a radius (r) associated with a connectivity provided by the access point. For example, the coverage area may be calculated using equation (1):

$$[00001] \text{ CA} = \pi r^2 \quad (1)$$

[0023] Examples of the first wireless network **104A** and the second wireless network **108A** include, but are not limited to, the Internet, a cloud network, a radio frequency (RF) connection, a cellular network or a wireless mobile network (such as Long-Term Evolution and 5.sup.th Generation (5G) New Radio (NR)), a satellite communication system (using, for example, low earth orbit satellites), a Wireless Fidelity (Wi-Fi) network, a Personal Area Network (PAN), a Local Area Network (LAN), or a Metropolitan Area Network (MAN), a Low-Power Wide Area Network (LPWAN), an ultra-wideband (UWB) network, a sensor network, a Bluetooth network, or a Zigbee network. In an embodiment, the first access point **104** and second access point **108** may correspond to a mesh network, where the distance (d) between the first access point **104** and second access point **108** may be equation (2) or (3), as follows:

$$[00002] \text{ } d = r + \Delta r \quad (2) \quad d = R + \Delta R \quad (3) \quad [0024] \text{ Where, } \Delta r = R - r, \text{ when } r < R; [0025] \Delta R = r - R, \text{ when } r > R; [0026] \text{ “R” may represent a radius associated with the coverage area of the second wireless network } \mathbf{108A}, \text{ and } [0027] \text{ “r” may represent a radius associated with the coverage area of the first wireless network } \mathbf{104A}.$$

[0028] In an embodiment, the value of Δr or ΔR may be a positive or a negative number based on a placement of the access points. Further, the value of Δr or ΔR may be 0 in case the second access point **108** is situated on an edge of the coverage area of the first wireless network **104A** associated with the first access point **104**. For example, a mesh network may include only two access points, such as, the first access point **104** and the second access point **108**. The second access point **108** may be situated on the edge of the coverage area associated with the first access point **104**. In such case, if the connectivity radius (such as, “r”) of the first access point **104** is “10” and the connectivity radius (such as, “R”) of the second access point **108** is “12”, then the distance (such as, “d”) between the access points may be “12” (i.e., $d = 10 + (12 - 10)$).

[0029] The server **106** may include suitable logic, circuitry, and interfaces, and/or code that may be configured to detect the first access point **104** associated with the first wireless network **104A** within the first predefined radius of the electronic device **102**. The server **106** may establish a first connection with the first wireless network **104A**, based on the first access point **104** being within the first predefined radius. Further, the server **106** may determine whether an external network is accessible, based on the established first connection. The server **106** may control detection of the second access point **108** associated with the second wireless network **108A** within the second predefined radius from the detected first access point **104**. The server **106** may determine whether the external network is accessible from the second access point **108**, through the mesh network and may control establishment of a second connection between the first access point **104** point and the second access point **108**, based on the external network being accessible from the second access point **108**, through the mesh network.

[0030] The server **106** may be implemented as a cloud server and may execute operations through web applications, cloud applications, HTTP requests, repository operations, file transfer, and the like. Other example implementations of the server **106** may include, but are not limited to, a database server, a file server, a web server, a media server, an application server, a mainframe server, a machine learning server (enabled with or hosting, for example, a computing resource, a memory resource, and a networking resource), or a cloud computing server.

[0031] In at least one embodiment, the server **106** may be implemented as a plurality of distributed cloud-based resources by use of several technologies that are well known to those ordinarily skilled in the art. A person with ordinary skill in the art will understand that the scope of the disclosure may not be limited to the implementation of the server **106** and the electronic device **102**, as two separate entities. In certain embodiments, the functionalities of the server **106** can be incorporated in its entirety or at least partially in the electronic device **102** without a departure from the scope of the disclosure.

[0032] The communication network **110** may include a communication medium through which the electronic device **102** and the server **106** may communicate with one another. The communication network **110** may be one of a wired connection or a wireless connection. Examples of the communication network **110** may include, but are not limited to, the Internet, a cloud network, Cellular or Wireless Mobile Network (such as Long-Term Evolution and 5.sup.th Generation (5G) New Radio (NR)), satellite communication system (using, for example, low earth orbit satellites), a Wireless Fidelity (Wi-Fi) network, a Personal Area Network (PAN), a Local Area Network (LAN), or a Metropolitan Area Network (MAN). Various devices in the network environment **100** may be configured to connect to the communication network **110** in accordance with various wired and wireless communication protocols. Examples of such wired and wireless communication protocols may include, but are not limited to, at least one of a Transmission Control Protocol and Internet Protocol (TCP/IP), User Datagram Protocol (UDP), Hypertext Transfer Protocol (HTTP), File Transfer Protocol (FTP), Zig Bee, EDGE, IEEE 502.11, light fidelity (Li-Fi), 502.16, IEEE 502.11s, IEEE 502.11g, multi-hop communication, wireless access point (AP), device to device communication, cellular communication protocols, and Bluetooth (BT) communication protocols.

[0033] The first location **114** may be associated with the first wireless network **104A**. The first location **114** may include the first access point **104** that may be associated with the first wireless network **104A** within the first predefined radius of the electronic device **102**. For example, the first location **114** may be defined as a point (e.g. an address, coordinates, etc.), or as an area (e.g. an area defined by the connectivity area of the first access point **104**) with a regular (e.g. circular, rectangular, etc.) or irregular shape associated with the first wireless network **104A**.

[0034] The second location **116** may be associated with the second wireless network **108A**. The second location **116** may include the second access point **108** associated with the second wireless network **108A** within the second predefined radius from the first access point **104**. Further, the first location **114** and second location **116** may have overlapping regions as the first wireless network **104A** and the second wireless network **108A** may be associated with a mesh network. For example, the second location **116** may be defined as a point (e.g. an address, coordinates, etc.), or as an area (e.g. an area defined by the connectivity area of the second access point **108**) with a regular (e.g. circular, rectangular, etc.) or irregular shape associated with the first wireless network **104A**.

[0035] In operation, the electronic device **102** may be configured to detect the first access point **104**. The first access point **104** may be associated with the first wireless network **104A** within the first predefined radius of the electronic device **102**. The first predefined radius may be the radius associated with the connectivity area of the first wireless network **104A**. Further, the first access point **104** may correspond to a mesh network of a set of interconnected access points. The first access point **104** may be the intermediate device that may be configured to provide accessibility of the external network associated with the mesh network to the electronic device **102**. The accessibility to the external network may be provided either directly or through one or more other

access points, by the first access point **104**. The first access point **104** may establish a wireless network connection with the electronic device **102** associated with the user **112**. Details related to the detection of the first access point **104** are further described, for example, in FIG. 3A (at **302**).

[0036] The electronic device **102** may be configured to establish the first connection of the electronic device **102** with the first wireless network **104A**. The first connection may be established between the electronic device **102** and the first wireless network **104A** based on the first access point **104** that may be within the first predefined radius of electronic device **102**. The first connection may be a wired or a wireless communication of the electronic device **102** with the first access point **104**. The first connection may include, but is not limited to, a daisy-chain connection, a Bluetooth network connection, a Wi-Fi network connection, a cellular network connection, a sensor network connection, a near-field connection, a radio-frequency (RF) network connection, a satellite network connection, or other suitable network connection. Details related to the establishment of the first connection are further described, for example, in FIG. 3A (at **304**).

[0037] The electronic device **102** may be configured to determine an external network accessibility. The accessibility of the external network associated with the mesh network may be determined based on the established first connection. The external network accessibility may be determined based on a connectivity between the electronic device **102** with the first access point **104** and a connectivity of the first access point **104** with the external network. The external network accessibility of the first access point **104** may depend upon transmission power of the first access point **104**, locations, and physical structures of the buildings, premises, or campus on which the first access point **104** may be located. Details related to the external network accessibility are further described, for example, in FIG. 3A (at **306**).

[0038] The electronic device **102** may be configured to control detection of the second access point **108**. The second access point **108** may be associated with the second wireless network **108A** within the second predefined radius from the detected first access point **104**. The second predefined radius may be the radius associated with the connectivity area of the first access point **104**. Further, the second access point **108** correspond to the mesh network of the set of interconnected access points. The second access point **108** may be an intermediate device that may be configured to provide accessibility of the external network associated with the mesh network. The second access point **108** may establish a wireless network connection with the first access point **104** associated with the electronic device **102**. Details related to the detection of the second access point **108** are further described, for example, in FIG. 3A (at **308**).

[0039] The electronic device **102** may be configured to determine external network accessibility from the second access point **108**. The accessibility of the external network may be detected through the mesh network. The external network accessibility may be determined based on the connectivity between the second access point **108** with the external network. The external network accessibility of the second access point **108** may depend upon transmission power, locations, and the physical structure of the building, premises, or campus on which the second access point **108** may be located. Details related to the external network accessibility are further described, for example, in FIG. 3A (at **310**).

[0040] The electronic device **102** may be configured to control the establishment of the second connection. The second connection may be established between the first access point **104** and second access point **108**. The control of the establishment of the second connection may be based on the external network being accessible from the second access point, through the mesh network. The second connection may include, but is not limited to, a daisy-chain connection, a Bluetooth network connection, a Wi-Fi network connection, a cellular network connection, a sensor network connection, a near-field connection, a radio-frequency (RF) network connection, a satellite network connection, or other suitable network connection. Details related to the second connection are further described, for example, in FIG. 3A (at **312**).

[0041] To connect to external networks, an electronic device may connect to an access point, such

as, a base station. The access point may establish a connection between the electronic device and the external networks. Typically, there may be various limitations in the connection between the electronic device and the external networks, via the access points. For example, a signal strength of the connection may reduce with distance of the electronic device and the access point. The weaker is the signal strength, the lower may be the quality of a communication channel that may be established between the electronic device and the external network. However, a reduction of the distance between the electronic device and the access point may improve the signal strength, but may reduce the mobility of the electronic device. In such a scenario, the electronic device may be moved within a limited region in a vicinity of the access point for better signals and connectivity.

[0042] The electronic device **102** of the present disclosure may provide connection with an external network (e.g., the communication network **110**) through an access point handover in a mesh network including a set of interconnected access points. The electronic device **102** may detect an access point (e.g., the first access point **104**) within a certain radius (e.g., the first predefined radius) from the electronic device **102**. In case, an access point is identified within the particular radius from the electronic device **102**, the electronic device **102** may establish a connection with the access point (e.g., the first access point **104**) through a wireless network (e.g., the first wireless network **104A**) associated with the particular access point. The electronic device **102** may then determine whether an external network (e.g., the communication network **110**) is accessible from the access point. In case, the communication network **110** is inaccessible directly from the access point, an accessibility to the communication network **110** from another access point (e.g., the second access point **108**) within a certain radius (e.g., the second predefined radius) of the initial access point may be determined. In case, the communication network **110** is determined to be accessible from the other access point (i.e., a one-hop access point), the initial access point (e.g., the first access point **104**) and the one-hop access point (e.g., the second access point **108**) may be connected (e.g., through a mesh network) with each other to provide an end-to-end connectivity with the communication network **110** to the electronic device **102**. Thus, the connectivity range of the electronic device **102** to the communication network **110** may be extended based on connectivity of the directly connected access point with a one-hop access point connected to the communication network **110**. The connectivity range may be extended further based on more than one intermediate access points with a certain access point (an n-hop access point) being connected to the communication network **110**. Also, based on the distance of the electronic device **102** with nearby access points, a handover between access points in the mesh network may take place. Such handovers may maintain a signal strength of the connection of the electronic device **102** to the communication network **110**, while the mobility of the electronic device **102** may also be maintained.

[0043] FIG. **2** is a block diagram that illustrates an exemplary electronic device of FIG. **1**, in accordance with an embodiment of the disclosure. FIG. **2** is explained in conjunction with elements from FIG. **1**. With reference to FIG. **2**, there is shown the exemplary electronic device **102**. The electronic device **102** may include a network interface **202**, an input/output (I/O) device **204**, a memory **206**, and a processor **208**. The memory **206** may store the connection information. The input/output (I/O) device **204** may include a display device **210**.

[0044] The network interface **202** may include suitable logic, circuitry, interfaces, and/or code that may be configured to facilitate communication between the electronic device **102** and the server **106**, via the communication network **110**. The network interface **202** may be implemented by use of various known technologies to support wired or wireless communication of the electronic device **102** with the communication network **110**. The network interface **202** may include, but is not limited to, an antenna, a radio frequency (RF) transceiver, one or more amplifiers, a tuner, one or more oscillators, a digital signal processor, a coder-decoder (CODEC) chipset, a subscriber identity module (SIM) card, or a local buffer circuitry.

[0045] The network interface **202** may be configured to communicate via wireless communication

with networks, such as the Internet, an Intranet, a wireless network, a cellular telephone network, a wireless local area network (LAN), or a metropolitan area network (MAN). The wireless communication may be configured to use one or more of a plurality of communication standards, protocols and technologies, such as Global System for Mobile Communications (GSM), Enhanced Data GSM Environment (EDGE), wideband code division multiple access (W-CDMA), Long Term Evolution (LTE), 5.sup.th Generation (5G) New Radio (NR), code division multiple access (CDMA), time division multiple access (TDMA), Bluetooth, Wireless Fidelity (Wi-Fi) (such as IEEE 802.11a, IEEE 802.11b, IEEE 802.11g or IEEE 802.11n), voice over Internet Protocol (VOIP), light fidelity (Li-Fi), Worldwide Interoperability for Microwave Access (Wi-MAX), a protocol for email, instant messaging, and a Short Message Service (SMS).

[0046] The I/O device **204** may include suitable logic, circuitry, interfaces, and/or code that may be configured to receive an input and provide an output based on the received input. For example, the I/O device **204** may receive a user input indicative of an instruction or intention of a user (e.g., the user **112**) to connect the electronic device **102** with any of network, such as, the first wireless network **104A**, the second wireless network **108A** (directly or indirectly through a mesh network), or any other network with enhanced connectivity. The I/O device **204** may be further configured to display or render information indicative of an establishment of the connection with any of the networks and also parameters corresponding to the established connection (for example, data transmission speed, bit error rate, and signal strength). The I/O device **204** may include the display device **210**. Examples of the I/O device **204** may include, but are not limited to, a display (e.g., a touch screen), a keyboard, a mouse, a joystick, a microphone, or a speaker. Examples of the I/O device **204** may further include braille I/O devices, such as, braille keyboards and braille readers.

[0047] The memory **206** may include suitable logic, circuitry, interfaces, and/or code that may be configured to store one or more instructions to be executed by the processor **208**. The one or more instructions stored in the memory **206** may be configured to execute the different operations of the processor **208** (and/or the electronic device **102**). The memory **206** may be further configured to store information associated with the first connection and the second connection. Examples of implementation of the memory **206** may include, but are not limited to, Random Access Memory (RAM), Read Only Memory (ROM), Electrically Erasable Programmable Read-Only Memory (EEPROM), Hard Disk Drive (HDD), a Solid-State Drive (SSD), a CPU cache, and/or a Secure Digital (SD) card.

[0048] The processor **208** may include suitable logic, circuitry, and/or interfaces that may be configured to execute program instructions associated with different operations to be executed by the electronic device **102**. The operations may include the detection of the first access point **104**, the establishment of the first connection, the determination of accessibility of the external node from the electronic device **102**, the control for detection of the second access point **108**, the determination of the accessibility of the external network from the second access point **108**, and the control for the establishment of the second connection. The processor **208** may include one or more processing units, which may be implemented as a separate processor. In an embodiment, the one or more processing units may be implemented as an integrated processor or a cluster of processors that perform the functions of the one or more specialized processing units, collectively. The processor **208** may be implemented based on a number of processor technologies known in the art. Examples of implementations of the processor **208** may be an X86-based processor, a Graphics Processing Unit (GPU), a Reduced Instruction Set Computing (RISC) processor, an Application-Specific Integrated Circuit (ASIC) processor, a Complex Instruction Set Computing (CISC) processor, a microcontroller, a central processing unit (CPU), and/or other control circuits.

[0049] The display device **210** may include suitable logic, circuitry, and interfaces that may be configured to display or render information associated with the establishment of the first connection and/or the second connection. For example, the display device **210** may display or render information such as, a duration of a connection, a download/upload speed of the connection,

a signal strength of the connection, a bit error rate of the connection, and a count of data bits transmitted or received. The display device **210** may be a touch screen which may enable a user (e.g., the user **112**) to provide a user-input via the display device **210**. The touch screen may be at least one of a resistive touch screen, a capacitive touch screen, or a thermal touch screen. The display device **210** may be realized through several known technologies such as, but not limited to, at least one of a Liquid Crystal Display (LCD) display, a Light Emitting Diode (LED) display, a plasma display, or an Organic LED (OLED) display technology, or other display devices. In accordance with an embodiment, the display device **210** may refer to a display screen of a head mounted device (HMD), a smart-glass device, a see-through display, a projection-based display, an electro-chromic display, or a transparent display. Various operations of the processor **208** to connect the electronic device **102** to an access point that has accessibility of the external network are described further, for example, in FIG. 3A.

[0050] FIG. 3A is a diagram that illustrates an exemplary processing pipeline for external network connectivity based on access point handover through mesh network, in accordance with an embodiment of the disclosure. FIG. 3A is explained in conjunction with elements from FIG. 1 and FIG. 2. With reference to FIG. 3A, there is shown an exemplary processing pipeline **300A** that illustrates exemplary operations from **302** to **320** for implementation of external network connectivity based on access point handover through mesh network. The exemplary operations **302** to **320** may be executed by any computing system, for example, by the electronic device **102** of FIG. 1 or by the processor **208** of FIG. 2. In FIG. 3A, there are further shown, the electronic device **102**, a first wireless network **302A**, a first predefined radius **302B**, a second wireless network **308A**, a second predefined radius **308B**, a mesh network **310A**, a third predefined radius **318A**, and a third wireless network **320A**.

[0051] At **302**, an operation for a detection of a first access point may be executed. In an embodiment, the processor **208** may be configured to detect the first access point **104** associated with a first wireless network (e.g., the first wireless network **302A**) within the first predefined radius (e.g., the first predefined radius **302B**) of the electronic device **102**. The first access point **104** may be associated with the first wireless network **104A** and may be within the first predefined radius of the electronic device **102**. The first predefined radius may be the radius associated with a connectivity area of the first wireless network **302A** around the first access point **104**. Further, the first access point **104** correspond to the mesh network of a set of interconnected access points. In an embodiment, the first access point **104** may be an intermediate device that may be configured to provide an accessibility of an external network associated with the mesh network to the electronic device **102**. The first access point **104** may establish a wireless network connection with the electronic device **102** associated with the user **112**. Examples of the first access point **104** may include, but is not limited to, a Wi-Fi router, a mobile hotspot, a Bluetooth device, a ZigBee device, a sensor network hub, or a cellular base station.

[0052] In an embodiment, the first access point **104** may correspond to a Wi-Fi router connected to the electronic device **102** associated with the user **112**. The electronic device **102** may be connected to the Wi-Fi router, in case, the Wi-Fi is within the first predefined radius **302B** of the electronic device **102**. It may be appreciated that in certain cases the Wi-Fi router may be an intermediate device configured to provide the electronic device **102** with connectivity to the external network (such as, the internet). For example, the electronic device **102** may be operated by the user **112** may to watch a video on the electronic device **102** (such as, a mobile device or a Wi-Fi enabled television). The Wi-Fi router may correspond to a mesh network (e.g., the mesh network **310A**) of a plurality of Wi-Fi routers, wherein at least one of the plurality of Wi-Fi routers may be connected to an external network, such as, the Internet. In order to connect to the internet, the electronic device **102** may connect to the Wi-Fi router in the first predefined radius.

[0053] In an embodiment, the first access point **104** may correspond to a mobile hotspot connected to the electronic device **102** associated with the user **112**. The electronic device **102** may be

connected to the mobile hotspot, in case, is the mobile hotspot is within the first predefined radius **302B** of the electronic device **102**. It may be appreciated that the mobile hotspot may be an intermediate device configured to provide the electronic device **102** with connectivity to the external network (such as the internet). For example, the electronic device **102** may be used by the user **112** to stream games on the electronic device **102** (such as, a mobile device or a smart television). Further, the mobile hotspot may correspond to a mesh network of a plurality of the mobile hotspots or the Wi-Fi router. In order to connect to the internet, the electronic device **102** may connect to the mobile hotspot in the first predefined radius.

[0054] At **304**, an operation for establishment of a first connection may be executed. The processor **208** may be configured to establish the first connection of the electronic device **102** with the first wireless network **302A**, based on the first access point **104** being within the first predefined radius **302B**. The first connection may be a wired or a wireless connection of the electronic device **102** with the first access point **104**. The first connection may include, but is not limited to, a daisy-chain connection, a Bluetooth network connection, a Wi-Fi network connection, a cellular network connection, a sensor network connection, a near-field connection, a radio-frequency (RF) network connection, a satellite network connection, or other suitable network connection.

[0055] In an embodiment, the first connection may correspond to a Wi-Fi network connection. The electronic device **102** may be a display device (such as, a Wi-Fi-enabled television) and the first access point **104** may be a first Wi-Fi router with the first wireless network **104A**. The first connection may be established using a Wi-Fi discovery routine between the television and the first Wi-Fi router. Thus, the television may identify the nearest router network, then passes data or messages to connect back to the first Wi-Fi router. The television may connect to the first Wi-Fi router if the first Wi-Fi router provides accessibility to an external network, such as, the Internet.

[0056] At **306**, an operation for a determination of an external network accessibility may be executed. The processor **208** may be configured to determine whether an external network is accessible from the electronic device **102**, based on the established first connection. The accessibility of the external network from the electronic device **102** may be determined based on the connectivity of the electronic device **102** and/or the first access point **104** with the external network. In an embodiment, the external network accessibility through the first access point **104** may be based on a transmission power of the first access point **104**, a location, and a physical structure of a building, a premises, or campus on which the first access point **104** may be located. In an example, the external network may be, but is not limited to, an internet, a Local Area Network (LAN), a Metropolitan Area Network (MAN), a Wide Area Network (WAN), a public switched telephone network (PSTN), a mobile telephone switching office (MTSO), or a satellite network.

[0057] In an embodiment, the external network correspond to the Internet, which may be accessed through the server **106**. The server **106** may be associated with an Internet Service Provider (ISP) or any other network service provider (such as, a mobile/cellular network service provider). The electronic device **102** may be a display device (such as, a mobile device). In an example, the mobile device may establish a first connection with the first access point **104** (such as, a Wi-Fi router) to access the Internet. The Wi-Fi router may further determine the accessibility of the internet based on the first connection and at least one of, the transmission power of the first access point **104**, the locations, and the physical structure of the building, the premises, or campus on which the first access point **104** may be located. The Wi-Fi router may act as an intermediate device configured to provide the mobile device with an accessibility to the Internet.

[0058] At **308**, an operation for control of detection of a second access point detection may be executed. The processor **208** may be configured to control detection of the second access point **108** associated with the second wireless network **308A** within the second predefined radius **308B** from the detected first access point **104**. The second predefined radius may be the radius associated with a connectivity area or a coverage range of the first access point **104**. Further, the second access

point **108** may correspond to a mesh network (e.g., the mesh network **310A**) of the set of interconnected access points. The second access point **108** may be an intermediate device that may provide accessibility of the external network associated with the mesh network **310A**. The second access point **108** may establish a wireless network connection with the first access point **104** associated with the electronic device **102**. The second access point **108** may be a Wi-Fi router, a Bluetooth device, a ZigBee device, a base station, and the like. The detection of the second access point **108** may be similar to the detection of the first access point **104** (as described in FIG. 3A, at **302**).

[0059] In an embodiment, the second access point **108** may correspond to a Wi-Fi router connected to the first access point **104** associated with the electronic device **102**. In one scenario, the first access point **104** may also be another Wi-Fi router corresponding to a television (such as, the electronic device **102**) associated with the user **112**. The television may render video, that may be streamed on the Internet, for the user **112**. In case, the external network, i.e., the Internet, is not accessible from the television or the first access point **104**, i.e., a first Wi-Fi router, then, the detection of the second access point **108**, i.e., a second Wi-Fi router, may be controlled. In an example, a second Wi-Fi router may be within the second predefined radius **308B** from the detected the first Wi-Fi router. (i.e., where the first Wi-Fi router and the second Wi-Fi router may be within each other's coverage area). For example, the second Wi-Fi router (i.e., the second access point **108**) may be within the sec The first Wi-Fi router and the second Wi-Fi router may correspond to the mesh network of the set of interconnected Wi-Fi routers. In order to connect to the internet, the television may connect to the first Wi-Fi router within the first predefined radius of the television. Further, the first Wi-Fi router may be connected to the determined the second Wi-Fi router, wherein the second Wi-Fi router may be within the second predefined radius of the first predefined radius.

[0060] At **310**, an operation for determination of an accessibility of the external network accessibility may be executed. In an embodiment, the processor **208** may be configured to control determination of whether the external network (e.g., the communication network **110**) is accessible from the second access point **108**, based on the external network being inaccessible from the electronic device **102**. The second access point **108** may be determined through the mesh network **310A**, wherein the mesh network **310A** may be with the set of interconnected access points including the first access point **104** and the second access point **108**. The external network accessibility may be determined based on the connectivity of the second access point **108** with the external network. The external network accessibility of the second access point **108** may be based on the transmission power, the locations, and the physical structure of the building, premises, or campus on which the second access point **108** may be located. In an example, the external network may be, but is not limited to, an internet, a Local Area Network (LAN), a Metropolitan Area Network (MAN), a Wide Area Network (WAN), a public switched telephone network (PSTN), a mobile telephone switching office (MTSO), and a satellite networks. In an embodiment, the external network may be the internet provided by the server **106**. For example, the second access point **108** may be the second Wi-Fi router. In such a scenario, the second Wi-Fi router may determine the accessibility of the internet through the mesh network.

[0061] At **312**, an operation for control of the second connection establishment may be executed. The processor **208** may be configured to control establishment of a second connection between the first access point **104** and the second access point **108**, based on the external network being accessible from the second access point **108**, through the mesh network **310A**. The electronic device **102** may be connected to the external network (e.g., the Internet and/or the communication network **110**) through the established first connection and the control of the established second connection. In case, the second access point **108** is able to access the external network, then the second access point **108** may establish the second connection with the first access point **104** to provide the electronic device **102** with an access to the external network.

[0062] In an embodiment, the established second connection may be a Wi-Fi connection, and the

external network may be the Internet. The electronic device **102** may be a display device (such as, a television), and the first access point **104** may be the first Wi-Fi router associated with the first wireless network **302A**. Further, the second access point **108** may be a second Wi-Fi router associated with the second wireless network **308A**. For example, the Wi-Fi connection establishment between the first Wi-Fi router and the second Wi-Fi router may be based on the Internet accessibility from the second Wi-Fi router. The accessibility of Internet from the second Wi-Fi router may be based on the mesh network **310A**. The television may connect directly to the first Wi-Fi router and may access the internet through the established first connection (between the first Wi-Fi router) and the established second connection (between the second Wi-Fi router).

[0063] In an embodiment, the second connection may be established using a Wi-Fi discovery routine between the first Wi-Fi router and the second Wi-Fi router. The first Wi-Fi router may identify the nearest Wi-Fi router (e.g., the second Wi-Fi router) with an accessibility to internet, then pass data or message to connect to the second Wi-Fi router, via the first Wi-Fi router directly connected to the television. The television may establish the first connection with the first Wi-Fi router. Further, the first Wi-Fi router may provide accessibility of the Internet through the second connection of the first Wi-Fi router and the second Wi-Fi router to the television. That is, the first Wi-Fi router and the second Wi-Fi router may act as intermediate devices to provide the television accessibility of the Internet.

[0064] In an embodiment, a number of the one or more other access points through which the external network is accessible may be less than a predefined hop value. The predefined hop value may refer to a predefined number of access points through which data passes from the electronic device **102** to server **106** (depending on routing protocol, that may include the source/destination, that is, the first hop may be counted as hop 0 or hop 1). The hop count may be a rough measure of a routing distance between the electronic device **102** and the server **106**. For example, the first access point **104** may be the first Wi-Fi router, the second access point **108** may be the second Wi-Fi router and the electronic device **102** may be a mobile device. The first Wi-Fi router and the second Wi-Fi router may be in vicinity of each other, and the first Wi-Fi router may be in the vicinity of the mobile device. The first Wi-Fi router and the second Wi-Fi router may act as intermediate devices. Further, the mobile device may establish the first connection with the first Wi-Fi router, and the first Wi-Fi router may establish the second connection with the second Wi-Fi router. Furthermore, the second Wi-Fi router may be wirelessly connected to the external network (i.e., the internet) via the server **106**. Thus, the mobile device may connect with the internet via the intermediate devices. Thus, in the current case, the hop value for the Internet connection may be 2 (for example, hop 0 and hop 1).

[0065] In an embodiment, a first hop may be a scenario in which a data packet may be passed from the first connection (between the electronic device **102** and the first access point **104**) to the second connection (between the first access point **104** and the second access point **108**). Further, a second hop may be a scenario in which the data packet may be passed from the second connection to a connection between the second access point **108** and the server **106**. For example, a first hop may be associated with a data packet communication between the television to the second Wi-Fi router, via the first Wi-Fi router. Further, a second hop may be associated with a data packet communication between the second Wi-Fi router and the server **106** (i.e., the external network provider).

[0066] At **314**, an operation for first signal strength monitoring may be executed. The processor **208** may be configured to monitor a first signal strength associated with the first wireless network **302A**, at the electronic device **102**. The first signal strength may correspond to a quality of the radio frequency (RF) signals (or electro-magnetic (EM) signals) received at the electronic device **102**, wherein the electronic device **102** may be located at a certain distance from the first access point **104** and within a coverage range of the first wireless network **104A**. In an example, the first signal strength may be expressed in dB-microvolts per meter (dBμV/m) or in decibels. For

example, the electronic device **102** may receive a signal transmitted from the first access point **104** with a signal to interference plus noise ratio (SINR), a received signal strength index (RSSI), and interference from another access points (such as, the second access point **108** or other access points). The interference from another access points may be received as the first access point **104** may belong a mesh network of the set of interconnected access points.

[0067] In an embodiment, the electronic device **102** may be a television and the first access point **104** may be a first Wi-Fi router. For example, the first signal strength of the RF/EM signals received at the television may be monitored. The RF/EM signals may be transmitted by the first Wi-Fi router to the television.

[0068] At **316**, an operation for the first threshold comparison may be executed. The processor **208** may be configured to compare the first signal strength with a first threshold. The comparison may be performed to determine whether the monitored first signal strength associated with the first wireless network **302A** is lower than the first threshold. The processor **208** may be configured to determine whether the monitored first signal strength associated with the first wireless network **302A** is lower than the first threshold. The first threshold may refer to a predefined minimum signal level that may be required for the access points or the electronic device **102** to maintain stability in connection such that a noise or a bit error rate of the connection remains within an acceptable range. Further, when the signal strength falls below the first threshold, the connection may become unstable or drop altogether. The first threshold may be adjusted by the user **112** for some access points to optimize the quality of the connection.

[0069] In an embodiment, the electronic device **102** may be a television and the first access point **104** may be a first Wi-Fi router. For example, the television may be connected to the first Wi-Fi router and may render video content, streamed from the Internet via the first Wi-Fi router. In such a scenario, the television may monitor the first signal strength from the first Wi-Fi router. Further, the television may determine whether the first signal strength is lower than the first threshold. In case, the first signal strength received from the first Wi-Fi router is lower than the first threshold, then the quality of connection provided by the first Wi-Fi router may be low.

[0070] In an embodiment, the external network may be accessible from one or more access points of the mesh network. For example, the one or more access points (other than the first access point and the second access point) from which the external network may be accessible may include access points, such as, a third access point, a fourth access point, and a fifth access point.

[0071] At **318**, an operation for control of detection of the third access point may be executed. The processor **208** may be configured to detect a third access point associated with a third wireless network (e.g., the third wireless network **320A**) within a third predefined radius (e.g., the third predefined radius **318A**) of the electronic device **102**. The detection of the third access point may be based on the determination that the monitored first signal strength associated with the first access point **104** is lower than the first threshold. Further, the third predefined radius **318A** may correspond to a radius associated with a connectivity area of the third access point. The third access point may be detected as an access point capable of connecting with the electronic device **102**, in case, a distance between the third access point and the electronic device **102** is less than or equal to the third predefined radius **318A**. In such a case, the electronic device **102** may be within the connectivity area of the third access point. The third access point may correspond to the mesh network of the set of interconnected access points. The third access point may be an intermediate device that may provide an accessibility of the external network associated with the mesh network. Furthermore, the third access point may establish a wireless network connection with the electronic device **102** associated with the user **112**. Examples of the third access point may include, but is not limited to, a Wi-Fi router, a mobile hotspot, a Bluetooth device, a ZigBee device, and a base station.

[0072] In an embodiment, the third access point may correspond to a third Wi-Fi router. Further, the electronic device **102** may correspond to a television associated with the user **112**. The

television may be initially connected with the first Wi-Fi router i.e., first access point **104**. The television may detect the third Wi-Fi router based on the determination that the first signal strength of the first Wi-Fi router is lower than the first threshold value. The television may be within a predefined radius (e.g., the third predefined radius **318A**) of the third Wi-Fi router.

[0073] At **320**, an operation for a third connection establishment may be executed. The processor **208** may be configured to may be configured to establish the third connection of the electronic device **102** with a third wireless network (e.g., the third wireless network **320A**) based on the third access point being within the third predefined radius **318A**. The third connection may be a wired or a wireless communication of the electronic device **102** with the third access point. The third connection may include, but is not limited to, a daisy-chain connection, a Bluetooth network connection, a Wi-Fi network connection, a cellular network connection, a sensor network connection, a radio-frequency (RF) network connection, a satellite network connection, or other suitable network connection.

[0074] In an embodiment, the established third connection may be a Wi-Fi connection. The electronic device **102** may be a display device (such as, a television), the first access point **104** may be a first Wi-Fi router and the third access point may be a third Wi-Fi router. The third connection may be established using a Wi-Fi discovery routine between the television and the third Wi-Fi router. In case, for example, the television determines that a connectivity with the first Wi-Fi router corresponds to a low quality connection, then the television may control identification of y a nearest router (by the first Wi-Fi router), and pass data or messages to connect to the nearest router, such as, the third Wi-Fi router. The television may establish the third connection with the third Wi-Fi router as the third Wi-Fi router may provide an accessibility of the external network (such as the internet) with a better quality. It may be appreciated that the electronic device **102** may handover connections between the access points through the mesh network to provide better quality connection to the external network. Furthermore, the third Wi-Fi router may be an intermediate device to provide the television with connectivity to the external network (such as the Internet).

[0075] In an embodiment, the electronic device **102** may access the external network through the detected third access point, upon a determination that a second signal strength associated with the third wireless network **320A** is higher than the first threshold. In such a scenario, the electronic device **102** may perform the handover from the first access point **104** to the third access point. For example, a television may connect to a first Wi-Fi router to access the Internet. In case, the first signal strength of the first Wi-Fi router is less than the first threshold value and the second signal strength of the third access point (such as, a third Wi-Fi router) is greater than the first threshold, the television may establish the third connection with the third Wi-Fi router. The third connection may be established based on a handover of connectivity with the electronic device **102** between the first Wi-Fi router and the third Wi-Fi router. Thus, based on the establishment of the third connection with the third Wi-Fi router, the television may be able to access the internet through the third Wi-Fi router.

[0076] FIG. **3B** is a diagram that illustrates an exemplary processing pipeline for external network connectivity based on access point handover through mesh network, in accordance with an embodiment of the disclosure. FIG. **3B** is explained in conjunction with elements from FIG. **1**, FIG. **2**, and FIG. **3A**. With reference to FIG. **3B**, there is shown an exemplary processing pipeline **300B** that illustrates exemplary operations from **322** to **340** for implementation of external network connectivity based on access point handover through mesh network. The exemplary operations **322** to **340** may be executed by any computing system, for example, by the electronic device **102** of FIG. **1** or by the processor **208** of FIG. **2**. In FIG. **3B**, there are further shown, the electronic device **102**, a third wireless network **322A**, a third access point **324A**, a fourth predefined radius **326A**, a fourth wireless network **326B**, a third signal strength **332A**, and a fifth predefined radius **336A**.

[0077] At **322**, an operation for monitoring of a second signal strength may be executed. The processor **208** may be configured to monitor a second signal strength associated with the third

wireless network **322A**, at the electronic device **102**.

[0078] The second signal strength may correspond to a quality of the radio frequency (RF) signals (or electro-magnetic (EM) signals) received at the electronic device **102**, wherein the electronic device **102** may be located at a certain distance from the third access point **324A** and within a coverage range of the third wireless network **322A**. In an example, the second signal strength may be expressed in dB-microvolts per meter (dB μ V/m) or in decibels. For example, the electronic device **102** may receive a signal transmitted from the third access point **324A** with a signal to interference plus noise ratio (SINR), a received signal strength index (RSSI), and interference from another access points (such as, a fourth access point or other access points). The interference from another access points may be received as the third access point **324A** may belong a mesh network of the set of interconnected access points.

[0079] In an embodiment, the electronic device **102** may be a television and the third access point **324A** may be a third Wi-Fi router. For example, the second signal strength of the RF/EM signals received at the television may be monitored. The RF/EM signals may be transmitted by the third Wi-Fi router to the television.

[0080] At **324**, an operation for the first threshold comparison may be executed. The processor **208** may be configured to compare the second signal strength with the first threshold. The comparison of the second signal strength to the first threshold may be performed to determine whether the monitored second signal strength associated with the third wireless network **322A** is higher than the first threshold. The first threshold may refer to a predefined minimum signal level that may be required for access points or the electronic device **102** to maintain a stable connection. In certain cases, when the signal strength falls below the first threshold, the connection may become unstable or drop altogether. Also, when a signal strength is higher than the first threshold, the quality of connectivity between the access point and the electronic device **102** also be higher. The first threshold may be adjusted by the user **112** in some access points to optimize the quality of the connection. Further, the detection of the third access point **324A** may be based on the determination that the monitored second signal strength is higher than the first threshold. Upon determination that the second signal strength is higher than the first threshold, the electronic device **102** may establish a third connection with the third access point **324A**. Herein, the third access point **324A** may be associated with the third wireless network **322A** within the third predefined radius of the electronic device **102**.

[0081] In an embodiment, the electronic device **102** may be a television and the third access point **324A** may be a third Wi-Fi router. For example, the television may receive media content from an external network and render the received media content for the user **112n**. The television may monitor the second signal strength from the third Wi-Fi router. Further, the television may determine whether the second signal strength is higher than the first threshold. Upon determination that the second signal strength associated with the third Wi-Fi router is higher than the first threshold, the television may detect the third access point **324A** to establish a third connection with the third access point **324A**. As the second signal strength received from the third Wi-Fi router may be higher than the first threshold, a quality of connection provided by the third Wi-Fi router may also be better than quality of connections provided by other Wi-Fi routers, which may be in a vicinity of the electronic device **102**.

[0082] In an embodiment, the third predefined radius associated with the third access point **324A** may correspond to the first predefined radius associated with the first access point **104**. Further, the external network may be accessible from one or more access points of the mesh network. Thus, the processor **208** may be configured to determine whether the external network is accessible from the electronic device **102**, based on the established third connection.

[0083] At **326**, an operation for a fourth access point detection may be executed. The processor **208** may be configured to control detection of the fourth access point associated with the fourth wireless network **326B** within the fourth predefined radius **326A** from the third access point **324A**.

The control of the detection of the fourth access point may be based on the inaccessibility of the external network from the electronic device **102**, via the third access point **324A**. Further, the third wireless network **322A** and the fourth wireless network **326B** may correspond to the mesh network of the set of interconnected access points. Further, the fourth predefined radius **326A** may be a radius associated with a connectivity area of the detected third access point **324A**. The fourth access point may be an intermediate device that may provide accessibility of an external network associated with a mesh network. Furthermore, the fourth access point may establish a wireless network connection with the third access point. Examples of the fourth access point may include, but is not limited to, a Wi-Fi router, a mobile hotspot, a Bluetooth device, a ZigBee device, and a base station.

[0084] In an embodiment, the fourth access point may correspond to a fourth Wi-Fi router. For example, a television (i.e., the electronic device **102**) associated with the user **112** may be initially connected with a third Wi-Fi router (i.e., the third access point **324A**). Furthermore, the television may detect the fourth Wi-Fi router based on a determination that the external network (e.g., the Internet) may be inaccessible from the electronic device **102**, though the third Wi-Fi router. The fourth Wi-Fi router may be within the fourth predefined radius **326A** may be from the third Wi-Fi router. In an embodiment, the fourth predefined radius **326A** of the fourth access point may correspond to the second predefined radius of the second access point **108**. In such case, the fourth wireless network **326B** associated with the fourth access point may be different from the second wireless network **108A** associated with the second access point **108**. Also, the fourth access point may be different from the second access point **108**. In another embodiment the fourth wireless network **326B** associated with the fourth access point may correspond to the second wireless network **108A** associated with the second access point **108**. Also, the fourth access point may correspond to the second access point **108**.

[0085] At **328**, an operation for detection (or determination) of an accessibility of the external network from the fourth access point may be executed. The processor **208** may be configured to detect (or determine) whether the external network is accessible from the fourth access point, through the mesh network. The external network accessibility may be determined based on the connectivity of the fourth access point with the external network. The external network accessibility of the fourth access point may be based on a transmission power, locations, and the physical structure of a building, premises, or campus on which the fourth access point may be located. In an example, the external network may be, but is not limited to, an internet, a Local Area Network (LAN), a Metropolitan Area Network (MAN), a Wide Area Network (WAN), a public switched telephone network (PSTN), a mobile telephone switching office (MTSO), and a satellite networks. In an embodiment, the external network may be the Internet accessible through the server **106**. Also, the fourth access point may be a fourth Wi-Fi router. For example, the electronic device **102** may determine whether the fourth Wi-Fi router can access the Internet through the mesh network.

[0086] At **330**, an operation for the fourth connection establishment control may be executed. The processor **208** may be configured to control establishment of a fourth connection between the third access point **324A** and the fourth access point, based on the external network being accessible from the fourth access point, through the mesh network. The fourth connection may be established between the third access point and the fourth access point. The electronic device **102** may connect to the external network through the established third connection and the established fourth connection.

[0087] In an embodiment, the fourth connection establishment may be a Wi-Fi connection, and the external network may be the internet. The electronic device **102** may be a display device (such as, a television), and the third access point **324A** may be a third Wi-Fi router with the third wireless network **322A**. Further, the fourth access point may be a fourth Wi-Fi router with the fourth wireless network **326B**. For example, the establishment of a Wi-Fi connection between the fourth

Wi-Fi router and the third Wi-Fi router may be based on the internet inaccessibility from the third Wi-Fi router. The accessibility of Internet from the fourth Wi-Fi router may depend on the mesh network. Then, the television may connect to the Internet through the established third connection and the established fourth connection.

[0088] In an embodiment, the fourth connection may be established using the Wi-Fi discovery routine between the third Wi-Fi router and the fourth Wi-Fi router. Thus, the third Wi-Fi router identifies the nearest the fourth Wi-Fi router network with accessibility of internet, then passes data or message to connect to the third Wi-Fi router. The third Wi-Fi router may establish the fourth connection with the fourth Wi-Fi router. Further, the fourth Wi-Fi router may provide accessibility of the Internet through the fourth connection with the third Wi-Fi router to the television. That is, the third Wi-Fi router and the fourth Wi-Fi router may act as intermediate devices to provide the television with accessibility of the Internet.

[0089] At **332**, an operation for first information reception may be executed. The processor **208** may be configured to receive the first information indicative of a third signal strength associated with the second wireless network **108A**, at the first access point **104**. The first information is generated at the first access point **104**. The first information may be indicative of the third signal strength that may correspond to the information of the quality of the RF/EM signals received from the second access point **108**, wherein the second access point **108** may be located at a certain distance from the first access point **104** and within the coverage range of the first wireless network **104A**. In an example, the third signal strength may be expressed in dB-microvolts per meter (dB μ V/m) or in decibels. For example, the first access point **104** may receive a signal transmitted from the second access point **108**, a signal to interference plus noise ratio (SINR) considering a received signal strength index (RSSI) and interference from another access points (such as, the second access point **108** or others). The interference from another access points may be received as the second access point **108** may correspond to a mesh network of the set of interconnected access points.

[0090] In an embodiment, the first access point **104** may be a first Wi-Fi router and the second access point **108** may be a second Wi-Fi router. For example, the first information indicative of the third signal strength of the RF/EM signals received at the first Wi-Fi router may be monitored. The EM signal may be transmitted by the second Wi-Fi router to the first Wi-Fi router.

[0091] At **334**, an operation for a second threshold comparison may be executed. The processor **208** may be configured to compare the third signal strength with the second threshold, wherein the comparison may be performed to determine whether the third signal strength associated with the second wireless network **108A** is lower than the second threshold. The second threshold may refer to a predefined minimum signal level that may be required for the access points or the electronic device **102** to maintain stability in a connection. Further, in case, a signal strength falls below the second threshold, the connection may become unstable or drop altogether. The second threshold may be adjusted by the user **112** in some access points to optimize the quality of the connection.

[0092] In an embodiment, the electronic device **102** may be a television, the first access point **104** may be a first Wi-Fi router and the second access point **108** may be a second Wi-Fi router. For example, the television may receive media content from the Internet and render the received media content for the user **112**. The television may monitor the first signal strength from the first Wi-Fi router, and further, the television may receive the first information from the first Wi-Fi router. The received first information may be indicative of the third signal strength associated with the second wireless network **108A**. The television may determine whether the third signal strength is lower than the second threshold. In case, the third signal strength associated with the second wireless connection is lower than the first threshold, then the quality of connection provided by the second Wi-Fi router may be low.

[0093] At **336**, an operation for detection of a fifth access point may be executed. The processor **208** may be configured to control detection of the fourth access point associated with a fifth

wireless network within the fifth predefined radius **336A** from the first access point **104**. The control of the detection of the fifth access point may be based on the determination that the third signal strength is lower than the second threshold. Further, the fifth wireless network may correspond to the mesh network of the set of interconnected access points. Further, the fifth predefined radius **336A** may correspond to the second predefined radius associated with the second access point **108**. The fifth access point may be the intermediate device that provides accessibility of the external network associated with the mesh network. Examples of the fifth access point may include, but is not limited to, a Wi-Fi router, a mobile hotspot, a Bluetooth device, a ZigBee device, and a base station.

[0094] At **338**, an operation for determination (or detect) of external network accessibility from the fifth access point may be executed. The processor **208** may be configured to determine (or detect) the accessibility of the external network from the fifth access point. The accessibility of the external network from the fifth access point may be determined through the mesh network, wherein the mesh network may be with the set of interconnected access points. The external network accessibility may be determined based on the connectivity of the fifth access point with the external network. The external network accessibility of the fifth access point may be based on a transmission power, locations, and a physical structure of a building, premises, or campus on which the fifth access point may be located. In an example, the external network may be, but is not limited to, an internet, a Local Area Network (LAN), a Metropolitan Area Network (MAN), a Wide Area Network (WAN), a public switched telephone network (PSTN), a mobile telephone switching office (MTSO), and a satellite networks. In an embodiment, the external network may be the Internet that may be connected through the server **106**. Also, the fifth access point may be a fifth Wi-Fi router. For example, the fifth Wi-Fi router may determine the accessibility of the internet through the mesh network.

[0095] At **340**, an operation for control of establishment of a fifth connection may be executed. The processor **208** may be configured to control establishment of a fifth connection between the first access point and the fifth access point, based on the external network being accessible from the fifth access point, through the mesh network. The fifth connection may be established between the first access point **104** and the fifth access point. The electronic device **102** may connect to the external network through the established first connection and the established fifth connection.

[0096] In an embodiment, the established fifth connection may be a Wi-Fi connection, and the external network may be the Internet. The electronic device **102** may be a display device (such as, a television), and the first access point **104** may be a first Wi-Fi router associated with the first wireless network **104A**. Further, the fifth access point may be a fifth Wi-Fi router associated with the fifth wireless network. For example, the establishment of a Wi-Fi connection between the fifth Wi-Fi router and the first Wi-Fi router may be based on the internet accessibility from the fifth Wi-Fi router. The accessibility of internet from the fifth Wi-Fi router may depend on the mesh network. Then, the television may connect to the internet through the established fifth connection and the established first connection.

[0097] In an embodiment, the fifth connection may be established using the Wi-Fi discovery routine between the first Wi-Fi router and the fifth Wi-Fi router. Thus, the first Wi-Fi router may identify a nearest Wi-Fi router (e.g., the fifth Wi-Fi router) with accessibility of internet, and pass data or message to connect to the fifth Wi-Fi router. The first Wi-Fi router may establish the fifth connection with the fifth Wi-Fi router. Further, the fifth Wi-Fi router may provide accessibility of the internet to the television, through the fifth connection with the first Wi-Fi router. The first Wi-Fi router and the fifth Wi-Fi router may act as the intermediate devices to provide the television with accessibility of the Internet.

[0098] To connect to external networks, an electronic device may connect to an access point, such as, a base station. The access point may establish a connection between the electronic device and the external networks. Typically, there may be various limitations in the connection between the

electronic device and the external networks, via the access points. For example, a signal strength of the connection may reduce with distance of the electronic device and the access point. The weaker is the signal strength, the lower may be the quality of a communication channel that may be established between the electronic device and the external network. However, a reduction of the distance between the electronic device and the access point may improve the signal strength, but may reduce the mobility of the electronic device. In such a scenario, the electronic device may be moved within a limited region in a vicinity of the access point for better signals and connectivity.

[0099] The electronic device **102** of the present disclosure may provide connection with an external network (e.g., the communication network **110**) through an access point handover in a mesh network including a set of interconnected access points. The electronic device **102** may detect an access point (e.g., the first access point **104**) within a certain radius (e.g., the first predefined radius) from the electronic device **102**. In case, an access point is identified within the particular radius from the electronic device **102**, the electronic device **102** may establish a connection with the access point (e.g., the first access point **104**) through a wireless network (e.g., the first wireless network **104A**) associated with the particular access point. The electronic device **102** may then determine whether an external network (e.g., the communication network **110**) is accessible from the access point. In case, the communication network **110** is inaccessible directly from the access point, an accessibility to the communication network **110** from another access point (e.g., the second access point **108**) within a certain radius (e.g., the second predefined radius) of the initial access point may be determined. In case, the communication network **110** is determined to be accessible from the other access point (i.e., a one-hop access point), the initial access point (e.g., the first access point **104**) and the one-hop access point (e.g., the second access point **108**) may be connected (e.g., through a mesh network) with each other to provide an end-to-end connectivity with the communication network **110** to the electronic device **102**. Thus, the connectivity range of the electronic device **102** to the communication network **110** may be extended based on connectivity of the directly connected access point with a one-hop access point connected to the communication network **110**. The connectivity range may be extended further based on more than one intermediate access points with a certain access point (an n-hop access point) being connected to the communication network **110**. Also, based on the distance of the electronic device **102** with nearby access points, a handover between access points in the mesh network may take place. Such handovers may maintain a signal strength of the connection of the electronic device **102** to the communication network **110**, while the mobility of the electronic device **102** may also be maintained.

[0100] FIG. 4A is a flowchart that illustrates operations of an exemplary method for third access point detection, in accordance with an embodiment of the disclosure. FIG. 4A is described in conjunction with elements from FIG. 1, FIG. 2, FIG. 3A, and FIG. 3B. With reference to FIG. 4A, there is shown an exemplary flowchart **400A**. The flowchart **400A** may include operations from **402** to **414** and may be implemented by the electronic device **102** of FIG. 1 or by the processor **208** of FIG. 2. The flowchart **400A** may start at **402** and proceed to **404**.

[0101] At **404**, the first signal strength associated with the first wireless network may be monitored at the electronic device. The processor **208** may be configured to monitor the first signal strength associated with first wireless network **104A**, at the electronic device **102**. The first signal strength may correspond to quality of the RF/EM signals received at the electronic device **102**, wherein the electronic device **102** may be located at a certain distance from the first access point **104** and within a coverage range of the first wireless network **104A**. Further, the first signal strength may be expressed in dB-microvolts per meter (dB μ V/m) or in decibels. For example, the electronic device **102** may receive a signal transmitted from the first access point **104**, a signal to interference plus noise ratio (SINR) considering a received signal strength index (RSSI), and interference from another access points (such as, the second access point **108** or others). The interference from another access points may be received as the first access point **104** may correspond to a mesh

network of the set of interconnected access points. Details related to the first signal strength monitoring are described further, for example, in FIG. 3A (at **314**).

[0102] At **406**, it may be determined whether the monitored first signal strength associated with the first wireless network is less than the first predefined threshold. The processor **208** may be configured to determine whether the monitored first signal strength associated with the first wireless network is less than the first predefined threshold. The processor **208** may be configured to compare the first signal strength with the first threshold. The comparison may be performed to determine whether the monitored first signal strength associated with the first wireless network **104A** is lower than the first threshold. The first threshold may refer to a predefined minimum signal level that may be required for the access points or the electronic device **102** to maintain a stability in connection. Further, when the first signal strength falls below the first threshold, the connection may become unstable or drop altogether. The first threshold may be adjusted by the user **112** in some access points to optimize the quality of the connection. Details related to the determination whether the monitored first signal strength is lower than the first threshold are described further, for example, in FIG. 3A (at **316**).

[0103] At **408**, the third access point within the third predefined radius of the electronic device may be detected, wherein the detection of third access point may be based on the determination that the monitored first signal strength is lower than the first threshold. The processor **208** may be configured to detect the third access point associated with the third wireless network within the third predefined radius of the electronic device **102**. The detection of the third access point may be based on the determination that the monitored first signal strength associated with the first access point **104** may be lower than the first threshold. The third predefined radius may be a radius associated with a connectivity area of the third access point. The third access point may be detected if the electronic device **102** lies within the third predefined radius, inside the connectivity area of the third access point. The third access point may correspond to the mesh network of the set of interconnected access points. The third access point may be an intermediate device that may provide an accessibility of the external network associated with the mesh network. Furthermore, the third access point may establish a wireless network connection with the electronic device **102** associated with the user **112**. Examples of the third access point may include, but is not limited to, a Wi-Fi router, a mobile hotspot, a Bluetooth device, a ZigBee device, and a base station. Details related to the detection of the third access point are described further, for example, in FIG. 3A (at **318**).

[0104] At **410**, the third connection of the electronic device with the third wireless network may be established, based on the third access point being within the third predefined radius. The processor **208** may be configured to establish the third connection of the electronic device **102** with the third wireless network based on the third access point being within the third predefined radius. The third connection may be a wired or a wireless communication of the electronic device **102** with the third access point. The third connection may include, but is not limited to, a daisy-chain connection, a Bluetooth network connection, a Wi-Fi network connection, a cellular network connection, a sensor network connection, a near-field connection, a radio-frequency (RF) network connection, a satellite network connection, or other suitable network connection. Details related to the establishment of the third connection are described further, for example, in FIG. 3A (at **320**).

[0105] At **412**, the second signal strength associated with third wireless network may be monitored, at the electronic device. The processor **208** may be configured to monitor the second signal strength associated with the third wireless network, at the electronic device **102**. The second signal strength may correspond to a quality of the RF/EM signals received at the electronic device **102**, wherein the electronic device **102** may be located at a certain distance from the third access point and within a coverage range of the third wireless network. Further, the second signal strength may be expressed in dB-microvolts per meter (dBμV/m) or in decibels. For example, the electronic device **102** may receive a signal transmitted from the third access point, a signal to interference plus noise

ratio (SINR) considering a received signal strength index (RSSI), and interference from another access points (such as, the second access point **108** or others). The interference from another access point may be received as the third access point may correspond to a mesh network of the set of interconnected access points. Details related to the monitoring of the second signal strength are described further, for example, in FIG. 3B (at **322**).

[0106] At **414**, it may be determined whether the monitored second signal strength associated with the third wireless network is higher than the first threshold, wherein the detection of the third access point may be based on the determination that the monitored second signal strength is higher than the first threshold. The processor **208** may be configured to determine whether the monitored second signal strength associated with the third wireless network is higher than the first threshold. The processor **208** may be configured to compare the second signal strength with the first threshold. The comparison may be to determine whether the monitored second signal strength associated with the third wireless network is higher than the first threshold. The first threshold may refer to a predefined minimum signal level that is required for the access points or the electronic device **102** to maintain a stability in connection. Further, in case, the second signal strength falls below the first threshold, the connection may become unstable or drop altogether. Also, when the second signal strength is higher than the first threshold, the connection may become stronger and provide better quality connectivity. The first threshold may be adjusted by the user **112** in some access points to optimize the quality of the connection. Further, the detection of the third access point may be based on the determination that the monitored second signal strength is higher than the first threshold. Upon determination that the second signal strength is higher than the first threshold, the electronic device **102** may establish a third connection with the third access point. Herein, the third access point may be associated with the third wireless network within the third predefined radius of the electronic device **102**. Control may pass to end.

[0107] Although the flowchart **400A** is illustrated as discrete operations, such as, **404**, **406**, **408**, **410**, **412**, and **414** the disclosure is not so limited. Accordingly, in certain embodiments, such discrete operations may be further divided into additional operations, combined into fewer operations, or eliminated, depending on the implementation without detracting from the essence of the disclosed embodiments.

[0108] FIG. 4B is a flowchart that illustrates operations of an exemplary method for fourth access point detection, in accordance with an embodiment of the disclosure. FIG. 4B is described in conjunction with elements from FIG. 1, FIG. 2, FIG. 3A, FIG. 3B, and FIG. 4A. With reference to FIG. 4B, there is shown an exemplary flowchart **400B**. The flowchart **400B** may include operations from **416** to **422** and may be implemented by the electronic device **102** of FIG. 1 or by the processor **208** of FIG. 2. The flowchart **400B** may start at **416** and proceed to **418**.

[0109] At **418**, control the detection of the fourth access point associated with fourth wireless network within fourth predefined radius from detected third access point. The control of the detection of the fourth access point may be based on the external network being inaccessible from the electronic device, and the third wireless network and the fourth wireless network corresponding to the mesh network of a set of interconnected access points. The processor **208** may be configured to control detection of the fourth access point associated with a fourth wireless network within a fourth predefined radius from the third access point. The control of the detection of the fourth access point may be based on the inaccessibility of the external network from the electronic device **102**. Further, the third wireless network and the fourth wireless network may correspond to the mesh network of the set of interconnected access points. Further, the fourth predefined radius may be the radius associated with the connectivity area of the detected third access point. The fourth access point may be an intermediate device that may provide an accessibility of the external network associated with the mesh network. Furthermore, the fourth access point may establish a wireless network connection with the third access point. Examples of the fourth access point may include, but is not limited to, a Wi-Fi router, a mobile hotspot, a Bluetooth device, a ZigBee device,

and a base station. Details related to the detection of the fourth access point are described further, for example, in FIG. 3B (at **326**).

[0110] At **420**, it may be determined whether the external network is accessible from the fourth access point, through the mesh network. The processor **208** may be configured to determine whether the external network is accessible from the fourth access point, through the mesh network. The mesh network may include the set of interconnected access points. The external network accessibility may be determined based on the connectivity of the fourth access point with the external network. The external network accessibility from the fourth access point may be based on a transmission power, locations, and a physical structure of a building, premises, or campus on which the fourth access point may be located. In an example, the external network may be, but is not limited to, an internet, a Local Area Network (LAN), a Metropolitan Area Network (MAN), a Wide Area Network (WAN), a public switched telephone network (PSTN), a mobile telephone switching office (MTSO), and a satellite networks. In an embodiment, the external network may be the Internet that may be accessible through the server **106**. Also, the fourth access point may be a fourth Wi-Fi router. For example, the fourth Wi-Fi router may determine the accessibility of the internet through the mesh network. Details related to the determination of the accessibility of the external network from the fourth access point are described further, for example, in FIG. 3B (at **328**).

[0111] At **422**, control the establishment of the fourth connection between the third access point and the fourth access point based on the external network being accessible from the fourth access point, through the mesh network, wherein the electronic device may be connected to the external network through the established third connection and the control of establishment of the fourth connection. The processor **208** may be configured to control the establishment of the fourth connection between the third access point and the fourth access point, based on the external network being accessible from the fourth access point, through the mesh network. The electronic device **102** may be connected to the external network through the established third connection and the control of establishment of the fourth connection. Details related to the control of the establishment of the fourth connection are further described, for example, in FIG. 3B (at **330**). Control may pass to end.

[0112] Although the flowchart **400B** is illustrated as discrete operations, such as, **404**, **418**, **420**, and **422** the disclosure is not so limited. Accordingly, in certain embodiments, such discrete operations may be further divided into additional operations, combined into fewer operations, or eliminated, depending on the implementation without detracting from the essence of the disclosed embodiments.

[0113] FIG. 4C is a flowchart that illustrates operations of an exemplary method for fifth access point detection, in accordance with an embodiment of the disclosure. FIG. 4C is described in conjunction with elements from FIG. 1, FIG. 2, FIG. 3A, FIG. 3B, FIG. 4A, and FIG. 4B. With reference to FIG. 4C, there is shown an exemplary flowchart **400C**. The flowchart **400C** may include operations from **424** to **438** and may be implemented by the electronic device **102** of FIG. 1 or by the processor **208** of FIG. 2. The flowchart **400C** may start at **424** and proceed to **426**.

[0114] At **426**, the first information indicative of the third signal strength associated with the second wireless network, at the first access point may be received. The processor **208** may be configured to receive the first information indicative of the third signal strength associated with the second wireless network **108A**, at the first access point **104**. The first information may be received from the first access point **104**. The first information may be indicative of the third signal strength corresponding to information of a quality of the RF/EM signals received at the second access point **108**, wherein the second access point **108** may be located at a certain distance from the first access point **104** and within a coverage range of the first wireless network **104A**. Further, the third signal strength may be expressed in dB-microvolts per meter (dBμV/m) or in decibels. For example, the first access point **104** may receive a signal transmitted from the second access point **108**, a signal to

interference plus noise ratio (SINR) considering a received signal strength index (RSSI) and interference from another access points (such as, the second access point **108** or others). The interference from another access point may be received as the second access point **108** may correspond to a mesh network of the set of interconnected access points. Details related to the reception of the first information are described further, for example, in FIG. 3B (at **332**).

[0115] At **428**, it may be determined whether the third signal strength associated with second wireless network is lower than the second threshold. The processor **208** may be configured to determine whether the third signal strength associated with second wireless network **108A** is lower than the second threshold. The processor **208** may compare the third signal strength with the second threshold, wherein the comparison may be performed to determine whether the third signal strength associated with the second wireless network is lower than the second threshold. The second threshold may refer to a predefined minimum signal level that is required for the access points or the electronic device **102** to maintain stability in connection. Further, when the third signal strength falls below the second threshold, a connection may become unstable or drop altogether. Also, when the third signal strength is higher than the second threshold, the connection may become stronger and provide better quality connectivity. The second threshold may be adjusted by the user **112** in some access points to optimize the quality of the connection. Details related to the second threshold comparison are described further, for example, in FIG. 3B (at **334**).

[0116] At **430**, control the detection of the fifth access point associated with the fifth wireless network within the fifth predefined radius of the first access point. The control of the detection of fifth access point may be based on the determination that the third signal strength is lower than the second threshold, and the fifth wireless network corresponds to a mesh network of a set of interconnected access points. The processor **208** may be configured to control detection of the fifth access point associated with a fifth wireless network within a fifth predefined radius from the first access point **104**. The fifth access point may be an intermediate device that may be configured to provide accessibility of the external network associated with the mesh network to the electronic device **102**. The fifth access point may establish a wireless network connection (such as, the fifth connection) with the first access point **104** associated with the electronic device **102**. The accessibility to the external network may be provided either directly or through one or more other access points, by the fifth access point. Details related to the detection of the fifth access point are described further, for example, in FIG. 3B (at **336**).

[0117] At **432**, it may be determined whether the external network is accessible from the fifth access point, through the mesh network. The processor **208** may be configured to determine whether the external network is accessible from the fifth access point, through the mesh network. The mesh network may include the set of interconnected access points. The external network accessibility may be determined based on the connectivity of the fifth access point with the external network. The external network accessibility from the fifth access point may be based on a transmission power, locations, and a physical structure of the building, premises, or campus on which the fifth access point may be located. In an example, the external network may be, but is not limited to, an internet, a Local Area Network (LAN), a Metropolitan Area Network (MAN), a Wide Area Network (WAN), a public switched telephone network (PSTN), a mobile telephone switching office (MTSO), and a satellite networks. In an embodiment, the external network may be the Internet that may be accessible through the server **106**. Also, the fifth access point may be a fifth Wi-Fi router. For example, the fifth Wi-Fi router may determine the accessibility of the internet through the mesh network. Details related to the detection of the accessibility of the external network from the fifth access point are described further, for example, in FIG. 3B (at **338**).

[0118] At **434**, control the establishment of the fifth connection between the first access point **104** and the fifth access point based on the external network being accessible from the fifth access point, through the mesh network, wherein the electronic device **102** may be connected to the external network through the established first connection and the control of establishment of the

fifth access point. The processor **208** may be configured to control the establishment of the fifth connection between the first access point **104** and the fifth access point, based on the external network accessibility from the fifth access point. Further, when the fifth access point may be able to access the external network, the fifth access point may establish the fifth connection with the first access point **104** to provide the electronic device **102** with connectivity to the external network. Furthermore, the electronic device **102** may connect to the external network through the established first connection and the established fifth connection. Herein, the established first connection may be between the electronic device **102** and the first access point **104**. Furthermore, the fifth connection may include, but is not limited to, a daisy-chain connection, a Bluetooth network connection, a Wi-Fi network connection, a cellular network connection, a sensor network connection, a radio-frequency (RF) network connection, a satellite network connection, or other suitable network connection. Details related to the establishment of the fifth connection are described further, for example, in FIG. 3B (at **340**).

[0119] At **436**, the second information indicative of a fourth signal strength associated with the fifth wireless network, at the first access point **104**, may be received. The processor **208** may be configured to receive the second information indicative of the fourth signal strength associated with the fifth wireless network, at the first access point **104**. The second information may be received from the first access point **104**. The second information may be indicative of the fourth signal strength corresponding to information of a quality of the RF/EM signal received at the fifth access point, wherein the fifth access point may be located at a certain distance from the first access point **104** and within the first wireless network **104A**. Further, the fourth signal strength may be expressed in dB-microvolts per meter (dB μ V/m) or in decibels. For example, the first access point **104** may receive a signal transmitted from the fifth access point, a signal to interference plus noise ratio (SINR) considering a received signal strength index (RSSI) and interference from another access points (such as, the second access point **108** or others). The interference from another access point may be received as the fifth access point may correspond to a mesh network of the set of interconnected access points.

[0120] At **438**, it may be determined whether the fourth signal strength associated with the fifth wireless network is higher than the second threshold. The control of detection of the fifth access point is further based on determination that the fourth signal strength is higher than the second threshold. The processor **208** may be configured to determine whether the fourth signal strength associated with the fifth wireless network is higher than the second threshold. The processor **208** may compare the fourth signal strength with the second threshold, wherein the comparison may be performed to determine whether the fourth signal strength associated with the fifth wireless network is higher than the second threshold. The second threshold may refer to a predefined minimum signal level that may be required for the access points or the electronic device **102** to maintain stability in connection. Further, when the fourth signal strength falls below the second threshold, a connection may become unstable or drop altogether. Also, when the fourth signal strength is higher than the second threshold, the connection may become stronger and provide better quality connectivity. The second threshold may be adjusted by the user **112** in some access points to optimize the quality of the connection. Further, based on determining that the fourth signal strength is higher than the second threshold, the electronic device **102** may detect the fifth access point to establish the fifth connection with the fifth access point. The fifth access point may be associated with the fifth wireless network within the fifth predefined radius of the electronic device **102**. Control may pass to end.

[0121] Although the flowchart **400C** is illustrated as discrete operations, such as, **426**, **428**, **430**, **432**, **434**, **436** and **438** the disclosure is not so limited. Accordingly, in certain embodiments, such discrete operations may be further divided into additional operations, combined into fewer operations, or eliminated, depending on the implementation without detracting from the essence of the disclosed embodiments.

[0122] FIG. 5 is a flowchart that illustrates operations of an exemplary method for external network connectivity based on access point handover through mesh network, in accordance with an embodiment of the disclosure. FIG. 5 is described in conjunction with elements from FIG. 1, FIG. 2, FIG. 3A, FIG. 3B, FIG. 4A, FIG. 4B, and FIG. 4C. With reference to FIG. 5, there is shown a flowchart 500. The flowchart 500 may include operations from 502 to 514 and may be implemented by the electronic device 102 of FIG. 1 or by the processor 208 of FIG. 2. The flowchart 500 may start at 502 and proceed to 504.

[0123] At 504, the first access point 104 associated with the first wireless network 104A may be detected. The processor 208 may be configured to detect the first access point 104 associated with the first wireless network 104A. The first wireless network may be within the first predefined radius of the electronic device 102. Details related to the first access point are further described, for example, in FIG. 3A (at 302).

[0124] At 506, the first connection of the electronic device 102 may be established. The processor 208 may be configured to establish the first connection of the electronic device 102 with the first wireless network 104A, based on the first access point 104 being within the first predefined radius. Details related to the first connection are further described, for example, in FIG. 3A (at 304).

[0125] At 508, the accessibility of the external network from the first access point 104 may be determined. The processor 208 may be configured to determine whether the external network is accessible from the electronic device 102, based on the established first connection. Details related to the external network are further described, for example, in FIG. 3A (at 306).

[0126] At 510, a detection of the second access point 108 associated with the second wireless network 108A from the detected first access point 104 may be controlled. The processor 208 may be configured to control detection of the second access point 108 associated with the second wireless network 108A within the second predefined radius from the detected first access point 104. The control of the detection of the point may be based on the external network being inaccessible from the electronic device 102, and the first wireless network 104A and the second wireless network 108A may correspond to the mesh network of the set of interconnected access points. Details related to the second access point are further described, for example, in FIG. 3A (at 308) and details related to the mesh network are further described, for example, in FIG. 3A (at 310).

[0127] At 512, the accessibility of the external network from the second access point 108 may be determined. The processor 208 may be configured to determine whether the external network is accessible from the second access point 108, through the mesh network. Details related to the external network are further described, for example, in FIG. 3A (at 310).

[0128] At 514, the establishment of the second connection may be controlled. The processor 208 may be configured to control establishment of the second connection between the first access point 104 and second access point 108, based on the external network being accessible from the second access point 108, through the mesh network. The electronic device 102 may be connected to the external network through the established first connection and the control of the established second connection. Details related to the second connection are further described, for example, in FIG. 3A (at 312). Control may pass to end.

[0129] Although the flowchart 500 is illustrated as discrete operations, such as, 504, 506, 508, 510, 512 and 514 the disclosure is not so limited. Accordingly, in certain embodiments, such discrete operations may be further divided into additional operations, combined into fewer operations, or eliminated, depending on the implementation without detracting from the essence of the disclosed embodiments.

[0130] Various embodiments of the disclosure may provide a non-transitory computer-readable medium and/or storage medium having stored thereon, computer-executable instructions executable by a machine and/or a computer to operate an electronic device (for example, the electronic device 102 of FIG. 1). Such instructions may cause the electronic device 102 to perform

operations that may include detection of a first access point (e.g., the first access point **104**) associated with a first wireless network (e.g., the first wireless network **104A**) within a first predefined radius. The operations may further include establishment of a first connection of the electronic device **102** with the first wireless network **104A**, based on the first access point **104** being within the first predefined radius. The operations may further include determination of whether an external network is accessible from the electronic device **102**, based on the established first connection. The operations may further include control of detection of a second access point (e.g., the second access point **108**) associated with a second wireless network (e.g., the second wireless network **108A**) within a second predefined radius from the detected first access point **104**, wherein the control of the detection of the second access point may be based on the external network being inaccessible from the electronic device **102**. The first wireless network **104A** and the second wireless network **108A** may correspond to a mesh network of a set of interconnected access points. The operations may further include determination of whether the external network is accessible from the second access point **108**, through the mesh network. The operations may further include control of establishment of a second connection between the first access point **104** and the second access point **108**, based on the external network being accessible from the second access point **108**, through the mesh network, where the electronic device **102** may be connected to the external network through the established first connection and the control of the established second connection.

[0131] Exemplary aspects of the disclosure may provide an electronic device (such as, the electronic device **102** of FIG. **1**) that includes circuitry (such as, the processor **208**). The processor **208** may be configured to detect a first access point (e.g., the first access point **104**) associated with a first wireless network (e.g., the first wireless network **104A**) within a first predefined radius. The processor **208** may be configured to establish a first connection of the electronic device **102** with the first wireless network **104A**, based on the first access point **104** being within the first predefined radius. The processor **208** may be further configured to determine whether an external network is accessible from the electronic device **102**, based on the established first connection. The processor **208** may be configured to control of detection of a second access point (e.g., the second access point **108**) associated with a second wireless network (e.g., the second wireless network **108A**) within a second predefined radius from the detected first access point **104**, wherein the control of the detection of the second access point **108** may be based on the external network being inaccessible from the electronic device **102**. The first wireless network **104A** and the second wireless network **108A** may correspond to a mesh network of a set of interconnected access points. The processor **208** may be configured to determine whether the external network is accessible from the second access point **108**, through the mesh network. The processor **208** may be configured to control establishment of a second connection between the first access point **104** and the second access point **108**, based on the external network being accessible from the second access point **108**, through the mesh network, wherein the electronic device **102** may be connected to the external network through the established first connection and the control of the established second connection.

[0132] In an embodiment, the external network may be accessible directly from the second access point **108**.

[0133] In an embodiment, the external network may be accessible through one or more access points of the mesh network, the one or more access points being other than the first access point **104** and the second access point **108**.

[0134] In an embodiment, the number of the one or more other access points through which the external network is accessible may be less than a predefined hop value.

[0135] In an embodiment, the processor **208** may be further configured to monitor a first signal strength associated with the first wireless network **104A**, at the electronic device **102**. The processor **208** may be further configured to determine whether the monitored first signal strength

associated with the first wireless network **104A** is lower than a first threshold. The processor **208** may be further configured to detect a third access point associated with a third wireless network within a third predefined radius of the electronic device **102**, wherein the detection of the third access point may be based on the determination that the monitored first signal strength is lower than the first threshold. The processor **208** may be further configured to establish a third connection of the electronic device **102** with the third wireless network, based on the third access point being within the third predefined radius.

[0136] In an embodiment, the processor **208** may be further configured to monitor a second signal strength associated with the third wireless network, at the electronic device **102**. The processor **208** may be further configured to determine whether the monitored second signal strength associated with the third wireless network is higher than the first threshold. The detection of the third access point may be further based on the determination that the monitored second signal strength being higher than the first threshold.

[0137] In an embodiment, the third predefined radius may correspond to the first predefined radius.

[0138] In an embodiment, the processor **208** may be further configured to determine whether the external network is accessible from the electronic device **102**, based on the established third connection.

[0139] In an embodiment, the processor **208** may be further configured to control detection of a fourth access point associated with a fourth wireless network within a fourth predefined radius from the detected third access point, wherein the control of the detection of the fourth access point may be based on the external network being inaccessible from the electronic device **102**. The third wireless network and the fourth wireless network may correspond to the mesh network of the set of interconnected access points. The processor **208** may be further configured to determine whether the external network is accessible from the fourth access point, through the mesh network. The processor **208** may be further configured to control establishment of a fourth connection between the third access point and the fourth access point, based on the external network being accessible from the fourth access point, through the mesh network. The electronic device **102** may be connected to the external network through the established third connection and the control of the establishment of the fourth connection.

[0140] In an embodiment, the fourth predefined radius may correspond to the second predefined radius.

[0141] In an embodiment, the fourth wireless network may be different from the second wireless network **108A**.

[0142] In an embodiment, the fourth access point may be different from the second access point **108**.

[0143] In an embodiment, the fourth wireless network may correspond to the second wireless network **108A**.

[0144] In an embodiment, the fourth access point may correspond to the second access point **108** associated with the second wireless network **108A**.

[0145] In an embodiment, the processor **208** may be further configured to receive first information indicative of a third signal strength associated with the second wireless network **108A**, at the first access point **104**. The processor **208** may be further configured to determine whether the third signal strength associated with the second wireless network is lower than a second threshold. The processor **208** may be further configured to control detection of a fifth access point associated with a fifth wireless network within a fifth predefined radius of the first access point **104**. The control of the detection of the fifth access point may be based on the determination that the third signal strength may be lower than the second threshold, and the fifth wireless network may correspond to the mesh network of the set of interconnected access points. The processor **208** may be further configured to determine whether the external network is accessible from the fifth access point, through the mesh network. The processor **208** may be further configured to control establishment

of a fifth connection between the first access point **104** and the fifth access point, based on the external network being accessible from the fifth access point, through the mesh network. The electronic device **102** may be connected to the external network through the established first connection and the control of the establishment of the fifth connection.

[0146] In an embodiment, the processor **208** may be further configured to receive second information indicative of a fourth signal strength associated with the fifth wireless network, at the first access point **104**. The processor **208** may be further configured to determine whether the fourth signal strength associated with the fifth wireless network is higher than the second threshold. The control of the detection of the fifth access point may be further based on the determination that the fourth signal strength is higher than the second threshold.

[0147] In an embodiment, the fifth predefined radius may correspond to the second predefined radius.

[0148] The present disclosure may also be positioned in a computer program product, which comprises all the features that enable the implementation of the methods described herein, and which when loaded in a computer system is able to carry out these methods. Computer program, in the present context, means any expression, in any language, code or notation, of a set of instructions intended to cause a system with information processing capability to perform a particular function either directly, or after either or both of the following: a) conversion to another language, code or notation; b) reproduction in a different material form.

[0149] While the present disclosure is described with reference to certain embodiments, it will be understood by those skilled in the art that various changes may be made, and equivalents may be substituted without departure from the scope of the present disclosure. In addition, many modifications may be made to adapt a particular situation or material to the teachings of the present disclosure without departure from its scope. Therefore, it is intended that the present disclosure is not limited to the embodiment disclosed, but that the present disclosure will include all embodiments that fall within the scope of the appended claims.

Claims

1. An electronic device, comprising: circuitry configured to: detect a first access point associated with a first wireless network within a first predefined radius of the electronic device; establish a first connection of the electronic device with the first wireless network, based on the first access point being within the first predefined radius; determine whether an external network is accessible from the electronic device, based on the established first connection; control detection of a second access point associated with a second wireless network within a second predefined radius from the detected first access point, wherein the control of the detection of the second access point is based on the external network being inaccessible from the electronic device, and the first wireless network and the second wireless network correspond to a mesh network of a set of interconnected access points; determine whether the external network is accessible from the second access point, through the mesh network; and control establishment of a second connection between the first access point and the second access point, based on the external network being accessible from the second access point, through the mesh network, wherein the electronic device is connected to the external network through the established first connection and the control of the established second connection.

2. The electronic device according to claim 1, wherein the external network is accessible directly from the second access point.

3. The electronic device according to claim 1, wherein the external network is accessible through one or more access points of the mesh network, the one or more access points being other than the first access point and the second access point.

4. The electronic device according to claim 3, wherein a number of the one or more other access

points through which the external network is accessible is less than a predefined hop value.

5. The electronic device according to claim 1, wherein the circuitry is further configured to: monitor a first signal strength associated with the first wireless network, at the first electronic device; determine whether the monitored first signal strength associated with the first wireless network is lower than a first threshold; detect a third access point associated with a third wireless network within a third predefined radius of the electronic device, wherein the detection of the third access point is based on the determination that the monitored first signal strength is lower than the first threshold; and establish a third connection of the electronic device with the third wireless network, based on the third access point being within the third predefined radius.

6. The electronic device according to claim 5, wherein the circuitry is further configured to: monitor a second signal strength associated with the third wireless network, at the first electronic device; and determine whether the monitored second signal strength associated with the third wireless network is higher than the first threshold, wherein the detection of the third access point is further based on the determination that the monitored second signal strength is higher than the first threshold.

7. The electronic device according to claim 5, wherein the third predefined radius corresponds to the first predefined radius.

8. The electronic device according to claim 5, wherein the circuitry is further configured to determine whether the external network is accessible from the electronic device, based on the established third connection.

9. The electronic device according to claim 8, wherein the circuitry is further configured to: control detection of a fourth access point associated with a fourth wireless network within a fourth predefined radius from the detected third access point, wherein the control of the detection of the fourth access point is based on the external network being inaccessible from the electronic device, and the third wireless network and the fourth wireless network correspond to the mesh network of the set of interconnected access points; determine whether the external network is accessible from the fourth access point, through the mesh network; and control establishment of a fourth connection between the third access point and the fourth access point, based on the external network being accessible from the fourth access point, through the mesh network, wherein the electronic device is connected to the external network through the established third connection and the control of the establishment of the fourth connection.

10. The electronic device according to claim 9, wherein the fourth predefined radius corresponds to the second predefined radius.

11. The electronic device according to claim 9, wherein the fourth wireless network is different from the second wireless network.

12. The electronic device according to claim 9, wherein the fourth access point is different from the second access point.

13. The electronic device according to claim 9, wherein the fourth wireless network corresponds to the second wireless network.

14. The electronic device according to claim 9, wherein the fourth access point corresponds to the second access point associated with the second wireless network.

15. The electronic device according to claim 1, wherein the circuitry is further configured to: receive first information indicative of a third signal strength associated with the second wireless network, at the first access point; determine whether the third signal strength associated with the second wireless network is lower than a second threshold; control detection of a fifth access point associated with a fifth wireless network within a fifth predefined radius of the first access point, wherein the control of the detection of the fifth access point is based on the determination that the third signal strength is lower than the second threshold, and the fifth wireless network corresponds to the mesh network of the set of interconnected access points; determine whether the external network is accessible from the fifth access point, through the mesh network; and control

establishment of a fifth connection between the first access point and the fifth access point, based on the external network being accessible from the fifth access point, through the mesh network, wherein the electronic device is connected to the external network through the established first connection and the control of the establishment of the fifth connection.

16. The electronic device according to claim 15, wherein the circuitry is further configured to: receive second information indicative of a fourth signal strength associated with the fifth wireless network, at the first access point; and determine whether the fourth signal strength associated with the fifth wireless network is higher than the second threshold, wherein the control of the detection of the fifth access point is further based on the determination that the fourth signal strength is higher than the second threshold.

17. The electronic device according to claim 15, wherein the fifth predefined radius corresponds to the second predefined radius.

18. A method, comprising: in an electronic device: detecting a first access point associated with a first wireless network within a first predefined radius of the electronic device; establishing a first connection of the electronic device with the first wireless network, based on the first access point being within the first predefined radius; determining whether an external network is accessible from the electronic device, based on the established first connection; controlling detection of a second access point associated with a second wireless network within a second predefined radius from the detected first access point, wherein the control of the detection of the second access point is based on the external network being inaccessible from the electronic device, and the first wireless network and the second wireless network correspond to a mesh network of a set of interconnected access points; determining whether the external network is accessible from the second access point, through the mesh network; and controlling an establishment of a second connection between the first access point and the second access point, based on the external network being accessible from the second access point, through the mesh network, wherein the electronic device is connected to the external network through the established first connection and the control of the established second connection.

19. The method according to claim 18, wherein the external network is accessible through one or more access points of the mesh network, the one or more access points being other than the first access point and the second access point, and a number of the one or more other access points through which the external network is accessible is less than a predefined hop value.

20. A non-transitory computer-readable medium having stored thereon, computer-executable instructions that when executed by an electronic device, causes the electronic device to execute operations, the operations comprising: detecting a first access point associated with a first wireless network within a first predefined radius of the electronic device; establishing a first connection of the electronic device with the first wireless network, based on the first access point being within the first predefined radius; determining whether an external network is accessible from the electronic device, based on the established first connection; controlling detection of a second access point associated with a second wireless network within a second predefined radius from the detected first access point, wherein the control of the detection of the second access point is based on the external network being inaccessible from the electronic device, and the first wireless network and the second wireless network correspond to a mesh network of a set of interconnected access points; determining whether the external network is accessible from the second access point, through the mesh network; and controlling an establishment of a second connection between the first access point and the second access point, based on the external network being accessible from the second access point, through the mesh network, wherein the electronic device is connected to the external network through the established first connection and the control of the established second connection.
