

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250276244

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

KALABOUKIS; Chris et al.

RECONFIGURING REALITY USING A REALITY OVERLAY DEVICE

Abstract

Virtual entities are displayed alongside real world entities in a wearable reality overlay device worn by the user. Information related to an environment proximate to the wearable device is determined. For example, a position of the wearable device may be determined, a camera may capture an image of the environment, etc. Virtual entity image information representative of an entity desired to be virtually displayed is processed based on the determined information. An image of the entity is generated based on the processed image information as a non-transparent region of a lens of the wearable device, enabling the entity to appear to be present in the environment to the user. The image of the entity may conceal a real world entity that would otherwise be visible to the user through the wearable device. Other real world entities may be visible to the user through the wearable device.

Inventors: KALABOUKIS; Chris (Los Gatos, CA), DOURIS; Stephan (San Jose, CA), PERRY; Marc (San Francisco, CA), CRANE; Barry (Menlo Park, CA)

Applicant: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Family ID: 42116986

Assignee: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Appl. No.: 19/209990

Filed: May 16, 2025

Related U.S. Application Data

parent US continuation 18198879 20230518 parent-grant-document US 12311261 child US 19209990

parent US continuation 15335503 20161027 parent-grant-document US 11691080 child US 18198879

Publication Classification

Int. Cl.: **A63F13/53** (20140101); **A63F13/213** (20140101); **A63F13/335** (20140101); **A63F13/65** (20140101); **A63F13/90** (20140101); **G02B27/01** (20060101); **G06F3/01** (20060101); **G06F3/04815** (20220101); **G06T19/00** (20110101); **G06T19/20** (20110101); **G09G3/00** (20060101); **G09G5/00** (20060101)

U.S. Cl.:

CPC **A63F13/53** (20140902); **A63F13/335** (20140902); **A63F13/65** (20140902); **A63F13/90** (20140902); **G02B27/0172** (20130101); **G06F3/011** (20130101); **G06F3/012** (20130101); **G06F3/04815** (20130101); **G06T19/006** (20130101); **G06T19/20** (20130101); **A63F13/213** (20140902); **A63F2300/1043** (20130101); **A63F2300/105** (20130101); **A63F2300/1093** (20130101); **A63F2300/205** (20130101); **A63F2300/303** (20130101); **A63F2300/69** (20130101); **A63F2300/8082** (20130101); **G02B2027/0138** (20130101); **G02B2027/014** (20130101); **G02B2027/0178** (20130101); **G06T2219/2004** (20130101); **G06T2219/2016** (20130101); **G09G3/001** (20130101); **G09G5/003** (20130101)

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation application of U.S. application Ser. No. 18/198,879, filed on May 18, 2023, which is a continuation application of U.S. application Ser. No. 15/335,503, filed on Oct. 27, 2016, now U.S. Pat. No. 11,691,080, issue on Jul. 4, 2023, and claims priority from co-pending U.S. patent application Ser. No. 12/257,832, filed on Oct. 24, 2008, now U.S. Pat. No. 9,480,919, issued on Nov. 1, 2016, the disclosures of which are incorporated herein in their entirety by reference.

BACKGROUND OF THE INVENTION

Field of the Invention

[0002] The present invention relates to the overlay of virtual entities on a real-world environment.

Background Art

[0003] Virtual reality (VR) is a technology which allows a user to interact with a computer-simulated environment. Virtual reality is typically presented to a user as a visual experience, displayed either on a computer screen or through special (e.g., stereoscopic) displays. Some virtual reality systems may include additional sensory information, such as sound provided through speakers or headphones, and/or tactile information. Users can interact with a virtual environment or a virtual artifact (VA) through the use of standard input devices such as a keyboard and mouse, or through multimodal devices such as a wired glove, a Polhemus boom arm, or an omnidirectional treadmill.

[0004] A virtual reality environment can be similar to the real world. For example, virtual reality environments include simulations for pilot or combat training. Alternatively, a virtual reality environment can differ significantly from reality. For instance, virtual reality environments include games and alternate world simulations (e.g., a simulation of a medieval world).

[0005] In virtual reality techniques that provide a visual experience to the user through a computer screen or special display, only virtual entities are included in the provided virtual experience. In

other words, the visual experience provided to the user is entirely virtual. Real world entities in the field of view of the user are not included in the provided visual experience. What is desired are ways of including both real world entities and virtual reality entities in a virtual reality experience provided to users.

BRIEF SUMMARY OF THE INVENTION

[0006] Virtual entities are displayed alongside real world entities in a wearable reality overlay device worn by the user. Information related to an environment proximate to the wearable device is determined. For example, a position of the wearable device may be determined, an image of the environment may be captured, etc. Virtual entity image information representative of an entity desired to be virtually displayed is processed based on the determined information. An image of the entity is generated based on the processed image information as a non-transparent region of a lens of the wearable device, enabling the entity to appear to be present in the environment to the user.

[0007] The image of the entity may be generated to conceal a real world entity that would otherwise be visible to the user through the wearable device. Other real world entities may be visible to the user through the wearable device.

[0008] The wearable device has numerous applications. In an example configuration, a virtual gaming environment is enabled by a wearable device. Image information corresponding to one or more virtual game entities is received. A next game state is determined based on a determined position of the wearable device, an image of the local environment, one or more rules of a game, a virtual player artificial intelligence, a game field configuration, a current game state, and/or information regarding at least one additional real-world game player. The image information is processed based on the determined next game state. One or more images corresponding to the one or more virtual game entities are generated based on the processed image information as one or more corresponding non-transparent region of a lens of the wearable device

[0009] The virtual game entities enable a user of the wearable device to participate in a game that incorporates virtual entities and real world entities.

[0010] In another example, a wearable device is provided. The wearable device includes a position monitor, a lens, and a display generator. The position monitor is configured to determine a position of the wearable device. The display generator is configured to receive image information processed based at least on the determined position. The image information is representative of an entity. The display generator is configured to generate an image of the entity as a non-transparent region of the lens based on the processed image information to enable the entity to appear to be present to a user of the wearable device in an environment proximate to the wearable device.

[0011] In one example configuration, the display generator includes an image projector configured to project the image of the entity on the lens. In another example configuration, the display generator is a display device that includes an array of image pixels. The lens may include the display device. The display device is configured to selectively activate pixels of the array of image pixels to form the image of the entity.

[0012] The wearable device may include one or more lenses. For example, the wearable device may include a right lens and a left lens corresponding to a right eye and a left eye of the user. One or more display generators may be present to generate an image of the entity on each lens.

[0013] In a further example, the wearable device may include an image processor configured to process image information representative of the entity based at least on the determined position of the wearable device, the determined orientation of the wearable device, or the determined speed of the wearable device to generate the processed image information.

[0014] In a further example, the display generator may be configured to optically align the image of the first entity on the lens with a second entity visible through the lens to at least partially conceal the second entity to the user of the wearable device. The image processor may be configured to process image information representative of the second entity based at least on a determined position of the second entity, a determined orientation of the second entity, or a speed

of the second entity to generate the processed image information.

[0015] In an example configuration, the wearable device may include a camera configured to capture an image of the environment. The image processor may be configured to process an image of the second entity captured by the camera to determine a location of the second entity.

[0016] In a still further example configuration, the wearable device may include a game engine. The display generator may generate an image of a virtual playing field and/or other virtual game features, virtual game participants, and/or virtual game implements.

[0017] The game engine is configured to enable the user to participate in a game configured to take place in the virtual playing field.

[0018] The image processor and/or game engine may be internal to the wearable device. In a still further example configuration, the wearable device may include a communication interface configured for wired and/or wireless communications with devices (e.g., a server) that may be remote from the wearable device that may include the image processor and/or the game engine.

[0019] In another configuration, a reality overlay image processing server is provided. The reality overlay image processing server includes a communication interface, storage, and an entity image processor. The communication interface is configured to receive position information from a wearable device. The storage stores image information representative of an entity. The entity image processor is configured to process the image information representative of the entity based at least on the determined position. The communication interface is configured to transmit the processed image information to the wearable device. The wearable device is configured to receive the processed image information, and to generate an image of the entity as a non-transparent region of a lens based on the processed image information to enable the entity to appear to be present to a user of the wearable device in an environment proximate to the wearable device.

[0020] In a further example, the reality overlay image processing server includes a game engine configured to enable the user to participate in a game that includes the entity.

[0021] These and other objects, advantages and features will become readily apparent in view of the following detailed description of the invention. Note that the Summary and Abstract sections may set forth one or more, but not all exemplary embodiments of the present invention as contemplated by the inventor(s).

Description

BRIEF DESCRIPTION OF THE DRAWINGS/FIGURES

[0022] The accompanying drawings, which are incorporated herein and form a part of the specification, illustrate the present invention and, together with the description, further serve to explain the principles of the invention and to enable a person skilled in the pertinent art to make and use the invention.

[0023] FIG. 1 shows a block diagram of a system for reconfiguring reality using a wearable reality overlay device, according to an example embodiment of the present invention.

[0024] FIG. 2 shows an example of a processed environment view that may be generated by the wearable device of FIG. 1, according to an embodiment of the present invention.

[0025] FIG. 3 shows a view of an example environment that includes an entity.

[0026] FIG. 4 shows an example of a processed environment view that may be generated by the wearable device of FIG. 1, according to an embodiment of the present invention.

[0027] FIG. 5 shows a block diagram of an example wearable reality overlay device, according to an embodiment of the present invention.

[0028] FIGS. 6 and 7 show block diagrams of a display generator, according to example embodiments of the present invention.

[0029] FIG. 8 shows a portion of a display of a display device, according to an example

embodiment.

[0030] FIG. **9** shows a flowchart for performing reality overlay, according to an example embodiment of the present invention.

[0031] FIG. **10** shows a block diagram of a wearable device, according to an example embodiment of the present invention.

[0032] FIG. **11** shows a flowchart providing a process for processing position information regarding a real-world entity, according to an example embodiment of the present invention.

[0033] FIG. **12** shows a flowchart that is an example of the flowchart shown in FIG. **11**, according to an embodiment of the present invention.

[0034] FIG. **13** shows an example wearable device that includes a camera, according to an embodiment of the present invention.

[0035] FIG. **14** shows a block diagram of an entity image optically aligned between an eye of a user and a real-world entity, according to an example embodiment of the present invention.

[0036] FIG. **15** shows a block diagram of a reality overlay system, according to an example embodiment of the present invention.

[0037] FIG. **16** shows a wearable device, according to an example embodiment of the present invention.

[0038] FIG. **17** shows a block diagram of a viewable environment where a variety of virtual entity images and real world entities are viewable by a user of a wearable device, according to example embodiment of present invention.

[0039] FIG. **18** shows a block diagram of an example wearable reality overlay device, according to an embodiment of the present invention.

[0040] FIG. **19** shows a flowchart for performing reality overlay in a gaming environment, according to an example embodiment of the present invention.

[0041] FIG. **20** shows an example of an environment viewable to a user when a wearable device is not activated.

[0042] FIG. **21** shows the environment of FIG. **20** with an example virtual game overlaid thereon by a wearable device, according to an example embodiment of the present invention.

[0043] The present invention will now be described with reference to the accompanying drawings. In the drawings, like reference numbers indicate identical or functionally similar elements. Additionally, the left-most digit(s) of a reference number identifies the drawing in which the reference number first appears.

DETAILED DESCRIPTION OF THE INVENTION

I. Introduction

[0044] The present specification discloses one or more embodiments that incorporate the features of the invention. The disclosed embodiment(s) merely exemplify the invention. The scope of the invention is not limited to the disclosed embodiment(s). The invention is defined by the claims appended hereto.

[0045] References in the specification to “one embodiment,” “an embodiment,” “an example embodiment,” etc., indicate that the embodiment described may include a particular feature, structure, or characteristic, but every embodiment may not necessarily include the particular feature, structure, or characteristic. Moreover, such phrases are not necessarily referring to the same embodiment. Further, when a particular feature, structure, or characteristic is described in connection with an embodiment, it is submitted that it is within the knowledge of one skilled in the art to effect such feature, structure, or characteristic in connection with other embodiments whether or not explicitly described.

[0046] Embodiments are described herein that enable real world entities and virtual entities to be provided to a user in a virtual environment. In an embodiment, a virtual reality overlay device includes a lens through which a user can view the surrounding environment. The reality overlay device is configured to selectively generate opaque portions (e.g., in black-and-white, grayscale,

and/or color) of the lens to correspond to virtual entities displayed to the user. The opaque portions of the lens may conceal real world entities that would otherwise be visible to the user through the lens. One or more other portions of the lens remain transparent through which the user can view corresponding portions of the surrounding environment to view real world entities. In this manner, the reality overlay device can “re-present” or “re-paint” sections of the users view.

[0047] Example embodiments and applications of the present invention are described in the following section.

II. Example Embodiments for Reconfiguring Reality Using a Reality Overlay Device

[0048] FIG. 1 shows a block diagram of a system **100** for reconfiguring reality using a wearable reality overlay device **104** (hereinafter “wearable device **104**”), according to an example embodiment of the present invention. In FIG. 1, a user **102** interacts with wearable device **104** to view environment **106**. For example, wearable device **104** may have the form of a pair of glasses, a pair of goggles, a mask, or other wearable item through which user **102** may view environment **106**. As shown in FIG. 1, environment includes a real-world entity **112**. Real-world entity **112** may be any living being, geographical feature, structure, or other entity described elsewhere herein or otherwise known.

[0049] As shown in FIG. 1, wearable device **104** enables user **102** to view a portion of environment **106**. For example, a real environment view **110** is received by wearable device **104** that includes real-world entity **112**. Wearable device **104** is configured to process real environment view **110** to generate a processed environment view **108** that is viewable by user **102**. Wearable device **104** may be configured to process real environment view **110** in various ways. For example, wearable device **104** may be configured to insert images of one or more entities to appear in processed environment view **108** that are not present in environment **106**. In this manner, even though the one or more entities are not present in environment **106**, the one or more entities appear to be present to user **102**. The one or more entities may be separate entities or may partially or entirely conceal real world entities that are present in environment **106**.

[0050] FIG. 2 shows a block diagram of an example of processed environment view **108** that may be generated by wearable device **104**, in an embodiment. As shown in FIG. 2, wearable device **104** may process real environment view **110** so that an entity image **202** is present in processed environment view **108** that is viewable by user **102**, but that is not present in real environment view **110**. Entity image **202** may be an image of any object, living being, geographical feature, structure, or other entity described elsewhere herein or otherwise known. In this example, when user **102** views environment **106** through wearable device **104** as shown in FIG. 1, user **102** may see real world entity **112** and entity image **202** even though the entity corresponding to entity image **202** is not present in environment **106**. Entity image **202** is inserted into processed environment view **108** by wearable device **104**.

[0051] In another example, environment **106** may appear as shown in FIG. 3. FIG. 3 shows a block diagram of environment **106** including a real-world entity **302**. Entity **302** may be any object, living being, geographical feature, structure, or other real world entity described elsewhere herein or otherwise known. FIG. 4 shows a block diagram of an example of processed environment view **408** that may be generated by wearable device **104** based upon receiving a real environment view **110** corresponding to FIG. 3, in an embodiment. As shown in FIG. 4, wearable device **104** may process real environment view **110** so that an entity image **402** is present in processed environment view **408**. Entity image **402** may be an image of any entity described herein or otherwise known, including an entity that is similar or different than entity **302**. In this example, when user **102** views environment **106** through wearable device **104** as shown in FIG. 1, user **102** may see processed environment view **408**, with entity image **402** partially or entirely concealing entity **302**. Entity image **402** is inserted into processed environment view **408** by wearable device **104** in alignment with entity **302** to conceal entity **302** from view by user **102**.

[0052] In this manner, wearable device **104** enables real world entities (e.g., entity **112**) to be

viewed by user **102** alongside virtual entities (e.g., entity image **202**) and/or enables real world entities (e.g., entity **302**) to be concealed by a virtual entities (e.g., entity image **402**). User **102** may be enabled to select which virtual entities are to be made viewable by wearable device **104**, including being enabled to select virtual entities to conceal real world entities in the field of view of user **102** through wearable device **104**. Accordingly, wearable device **104** has a multitude of applications. Some examples of applications of wearable device include: [0053] 1. Virtual interior decorating: User **102** could select a new painting or an image of a wall to appear to be present in a home, and the selected painting or wall image may be generated as a virtual entity by wearable device **104**. User **102** could select particular paintings and/or other images to appear as virtual entities according to their preference. User **102** can view the paintings and/or other images using wearable device **104**. As user **102** turns his/her head from side to side, wearable device **104** can adjust the view of the virtual images to the user, virtually moving the paintings/other images from side to side, to maintain the paintings/other images in their original positions. For example, wearable device **104** may include position/orientation detectors, such as one or more accelerometers. [0054] 2. Different views for different people: User **102** may prefer to have a room painted a particular color, such as green. In such case, wearable device **104** could be configured to cause the exposed portions of a wall in the view of user **102** to appear to be colored green. In another example, a married couple may not be able to decide on a color with which to paint their living room. Using wearable device **104**, the couple could leave the living room a particular color, such as white, and a first wearable device **104** of the husband may be configured to “virtually paint” the room red (i.e., cause the walls of the living room to appear red when viewed through first wearable device **104**), while a second wearable device **104** of the wife may be configured to virtually paint the room yellow. [0055] 3. One or more aspects of reality may be “substituted” in this way: If user **102** prefers to view another person (e.g., a significant other) in an alternative piece of clothing than currently worn by the person (e.g., a leopard skin jacket), user **102** may be enabled to configure wearable device **104** to cause the alternative piece of clothing to appear to be worn by the person when the person is viewed through wearable device **104**. In such case, wearable device **104** may be configured to conceal the piece of clothing currently worn by the person with an image of the alternative piece of clothing (e.g., as described above with respect to FIGS. **3** and **4**) so that the person appears to be wearing the alternative piece of clothing. [0056] 4. Such aspects may include substituting physical aspects of persons: The appearance of persons may be “edited” by wearable device **104**. If user **102** prefers to view a person's face, hair, body, arms, legs, etc., to appear in a manner other than they appear in reality, wearable device **104** may be configured to cause the person to appear as such. For example, wearable device **104** may be configured to “erase” blemishes (e.g., conceal blemishes with generated skin tone images) and/or otherwise change the visual appearance of other people. For instance, if user **102** prefers to see a particular celebrity when looking at another person (e.g., their spouse), wearable device **104** may be configured to conceal the person with an image of the celebrity (e.g., as described above with respect to FIGS. **3** and **4**) so that the celebrity appears to be present to user **102** instead of the person. Wearable device **104** may be configured to continually update the generated image of the celebrity to maintain concealing the person with the image of the celebrity as the person talks, moves about, etc. [0057] Example embodiments and applications of wearable device **104** are described in the following subsections.

A. Example Wearable Reality Overlay Device System and Method Embodiments

[0058] Example embodiments are described in this section for wearable device **104**. The example embodiments described herein are provided for illustrative purposes, and are not limiting. Further structural and operational embodiments, including modifications/alterations, will become apparent to persons skilled in the relevant art(s) from the teachings herein.

[0059] FIG. **5** shows a block diagram of an example wearable reality overlay device **500** (hereinafter “wearable device **500**”), according to an embodiment of the present invention.

Wearable device **500** is an example of wearable device **104** shown in FIG. **1**. As shown in FIG. **5**, wearable device **500** includes a user interface **502**, an entity information storage **504**, a position monitor **506**, an entity image processor **508**, a display generator **510**, and a lens **512**. As shown in FIG. **5**, wearable device **500** interacts with an eye **514**. Eye **514** may be an eye of user **102** shown in FIG. **1**, for example.

[0060] User interface **502** enables a user to configure wearable device **500**. User interface **502** may be configured to enable user **102** to edit, input, and/or select one or more virtual entity images to be displayed to user **102** by wearable device **500**. User device **502** may also be configured to enable user **102** to select an initial position, a size, and/or an orientation for the one or more virtual entity images. User device **502** may also be configured to enable user **102** to select a real entity to which a virtual entity image may be assigned.

[0061] User interface **502** may include any number and combination of user interface elements, including an interface provided by a computer (mobile or desktop), such as an interface provided by a computer-based or web-based application. For example, user interface **502** may include a keyboard, a thumb wheel, a mouse pointer, a roller ball, a stick pointer, a display, any number of virtual interface elements (e.g., such as a keyboard or other user interface element displayed by a display generator **510** at lens **512**), a voice recognition system, and/or other user interface elements described elsewhere herein or otherwise known.

[0062] Entity information storage **504** may store a library of one or more virtual entity descriptions **520** that user **102** may select for display by wearable device **104** as one or more corresponding virtual entity images. User interface **502** may be configured to provide a list of the one or more virtual entity descriptions **520** from which user **102** may select virtual entities to be displayed. User interface **502** may interact with entity information storage **504** to provide such information as virtual entity configuration information **518**, which is received and stored as virtual configuration **526** by entity information storage **504**. Virtual entity configuration information **518** may include the selection provided by user **102** of the one or more virtual entities for display, including the selected initial position, size, and/or orientation of the virtual entity images. Virtual entity configuration information **518** may also include the identification of one or more real world entities with which one or more of the selected virtual entities are to be associated (e.g., to partially or entirely conceal the real world entities). Each virtual entity description **520** stored in entity information storage **504** may include information necessary for graphically rendering an image of the corresponding virtual entity in two or three dimensions, depending on the type of virtual entity.

[0063] Entity information storage **504** may include one or more of any type of storage mechanism for storing virtual entity descriptions **520** and virtual configuration **526**, including a hard disk drive, an optical disc drive, a memory device such as a RAM device, a ROM device, etc., and/or any other suitable type of storage medium.

[0064] Position monitor **506** is configured to determine location information regarding wearable device **500**. The location of wearable device **500**, including the orientation of wearable device **500**, varies as the user wearing wearable device **500** moves about. For example, position monitor **506** may be configured to determine a location (e.g., coordinates of wearable device **500**) of wearable device **500**, an orientation of wearable device **500**, and/or a speed at which wearable device **500** is moving. For example, position monitor **506** may include a global positioning system (GPS) device configured to enable coordinates of wearable device **500** to be determined. In an embodiment, position monitor **506** may include one or more gyroscopes that may be configured to determine an orientation of wearable device **500**. In another embodiment, position monitor **506** may include an accelerometer that may be used to determine an orientation and/or speed at which wearable device **500** is moving. In further embodiments, position monitor **506** may include additional and/or alternative mechanisms for determining a location, an orientation, and/or a speed of wearable device **500**. As shown in FIG. **5**, position monitor **506** generates a position information signal **522**.

[0065] As shown in FIG. **5**, entity image processor **508** receives virtual entity image information

524. For example, entity image processor **508** may access entity information storage **504** for image information relating to a virtual entity image to be displayed, and in response, entity information storage **504** may output the requested image information as virtual entity image information **524**. Virtual entity image information **524** may include one or more of virtual entity descriptions **520**, for instance. As shown in FIG. 5, entity image processor **508** also receives position information signal **522**. Entity image processor **508** is configured to process virtual entity image information **524** for display. For example, entity information processor **508** may process virtual entity image information **524** based upon position information of wearable device **500** received in position information signal **522**. In this manner, entity information processor **508** may be enabled to configure a location, size, and/or orientation of a virtual entity image displayed by wearable device **500** to user **102** relative to a location, orientation, and speed of wearable device **500**. As shown in FIG. 5, entity image processor **508** generates a processed image information signal **528**. Processed image information signal **528** includes image information configured for display, to display one or more virtual entity images for the user of wearable device **500** at the proper location, size, and orientation.

[0066] Entity image processor **508** may be implemented in hardware, software, firmware, or any combination thereof. For example, entity image processor **508** may be implemented as computer code configured to be executed in one or more processors. Alternatively, entity image processor **508** may be implemented as hardware logic/electrical circuitry.

[0067] Display generator **510** receives processed image information signal **528**, and generates a virtual entity image **516** displayed at lens **512**. Virtual entity image **516** is viewable by an eye **514** of user **102** that is aligned with lens **512**. Entity image **516** is an example of entity images **202** and **402** described above. Display generator **510** displays entity image **516** at lens **512** at a size and a location of lens **512** according to processed image information signal **528**. As shown in FIG. 5, portions of lens **512** where entity image **516** is not present are transparent (e.g., light **530** from environment **106** is shown passing through lens **512** to eye **514**). Display generator **510** may be configured to generate entity image **516** at lens **512** as focused at infinity or at other suitable distance, as desired. Display generator **510** may include any suitable mechanism for displaying entity image **516** at lens **512**, such as a projection mechanism, a display device, or other suitable mechanism.

[0068] For example, FIG. 6 shows a block diagram of an embodiment of display generator **510**. In FIG. 6, display generator **510** includes an image projector **602**. Image projector **602** is configured to project a display of entity images, such as entity image **516**, on lens **512**, similar to a heads-up display (e.g., a head mounted display or helmet mounted display) that may be used in aircraft cockpits, automobiles, and other types of vehicles. In such an embodiment, lens **512** may include a surface coating or inner layer of a reflective material, such as a metal, that is configured to receive light representative of entity image **516** projected from image projector **602**, and reflect the light towards eye **514** (similar to a heads-up display combiner), but that is transparent to light received from the environment. Image projector **602** may include any suitable type of projection unit to project entity image **516**, including a cathode ray tube (CRT), a light emitting diode (LED), a liquid crystal display (LCD), a digital micro-mirror device (digital light processing (DLP) device), a liquid crystal on silicon (LCoS) device, etc.

[0069] In another example, FIG. 7 shows a block diagram of another embodiment of display generator **510**. In FIG. 7, display generator **510** is integrated with lens **512**. For example, display generator **510** may be an inner or outer layer of lens **512**. As shown in FIG. 7, display generator **510** includes a display device **702**. Display device **702** is configured to display entity images, such as entity image **516**. For example, display device **702** may be an LCD that can have selectively transparent and non-transparent portions. Display device **702** may be opaque where entity image **516** is displayed, while other portions of display device **702** are transparent. For instance, display device **702** may be an LCD where each pixel includes electrode layers made of a transparent

conductor (such as indium tin oxide (ITO)), a pair of polarizing filter layers, and an enclosed liquid crystal material that can selectively be made transparent or non-transparent (e.g., by application of an electric field).

[0070] For instance, FIG. 8 shows a display **800** that is a portion of a complete display of display device **702**, according to an example embodiment. As shown in FIG. 8, display **800** includes an array of pixels **806**. In the example of FIG. 8, display **800** includes a 12×9 array of pixels **806**. A first portion **802** of display **800** is transparent, and a second portion **804** of display **800** is not transparent. Thus, light from the environment may pass through first portion **802**. However, light may not pass through second portion **804**, and instead a virtual entity image is present at second portion **804** (e.g., entity image **516**). Second portion **804** includes a first section of pixels **808** displaying a first color and a second section of pixels **810** displaying a second color. For instance, second portion **804** may be a corner portion of a virtual painting, where first section of pixels **808** is a frame portion of the painting, and section of pixels **810** is a painted portion of the painting.

[0071] Example structure and operation of wearable device **500** is further described with respect to FIG. 9. FIG. 9 shows a flowchart **900** for performing reality overlay, according to an example embodiment of the present invention. Flowchart **900** may be performed by wearable device **500**, for example. Further structural and operational embodiments will be apparent to persons skilled in the relevant art(s) based on the discussion regarding flowchart **900**. Flowchart **900** and wearable device **500** are described as follows.

[0072] Flowchart **900** begins with step **902**. In step **902**, information related to an environment proximate to a wearable device is determined. For example, as described above, position monitor **506** may determine a location of wearable device **500** in the local environment (e.g., environment **106** shown in FIG. 1). Furthermore, as described further below, location information may be determined regarding real entities in the local environment using image recognition, radio signatures, and/or other location information determining techniques.

[0073] In step **904**, image information is processed based at least on the determined information, the image information being representative of an entity. For example, as described above, entity image processor **508** may receive image information from entity information storage **504** as virtual entity image information **524**, and may receive position information **522** from position monitor **506**. Virtual entity image information **524** may include image information representative of one or more virtual entity images. Entity image processor **508** may process the received image information based on position information **522**. As described further below, the received image information may be additionally and/or alternatively processed based on determined location information regarding real entities in the local environment.

[0074] As described above, position information **522** may include a location, an orientation, and/or a speed of wearable device **500**. Entity image processor **508** is configured to process virtual entity image information **524** based on position information **522**. For example, the closer that the location of wearable device **500** is to the location of the virtual entity, the larger will be the image of the virtual entity generated for display by entity information processor **508**. Conversely, the farther away that the location of wearable device **500** is from the location of the virtual entity, the smaller will be the image of the virtual entity generated for display by entity information processor **508**. Thus, entity information processor **508** may determine a distance between wearable device **500** and the virtual entity based upon position information of wearable device **500** received in position information signal **522** and the location of the virtual entity provided in virtual entity image information **524**. Entity image processor **508** may scale the size of the virtual entity generated for display based upon the determined distance. Furthermore, the location of the virtual entity image displayed in lens **512** is configured by entity image processor **508** according to an orientation of wearable device **500** received in position information signal **522**. Still further, the orientation of the virtual entity image displayed in lens **512** may be configured by entity image processor **508** according to the orientation of the virtual entity provided in virtual entity image information **524**.

relative to wearable device **500**. Still further, entity image processor **508** may process virtual entity image information **524** according to the speed at which wearable device **500** is moving, because movement of wearable device **500** may modify the orientation, location, and/or size of the virtual entity image displayed by wearable device **500** at a particular rate.

[0075] In step **906**, the processed image information is received. For example, as described above, display generator **510** receives processed image information signal **528**.

[0076] In step **908**, an image of the entity is generated based on the processed image information as a non-transparent region of a lens of the wearable device to enable the entity to appear to be present in the environment to a user of the wearable device. For example, as described above, display generator **510** generates an image of one or more virtual entities based on processed image information signal **528**. The generated image of the one or more virtual entities is displayed at lens **516**, such as entity image **516** shown in FIG. 5. Entity image **516** is generated as a nontransparent region of lens **512**. The generation of entity image **516** on lens **512** enables a virtual entity corresponding to entity image **516** to appear to be present in the environment (e.g., environment **106**) to user **102** wearing wearable device **500**. Transparent regions of lens **512** enable user **102** to view real-world entities in the environment alongside the virtual entity corresponding to entity image **516**.

[0077] In an embodiment, wearable device **500** may include a single lens **512** through which one or both eyes of user **102** view the local environment and view generated entity images. In another embodiment, wearable device **500** may include a pair of lenses, with each lens aligned with the corresponding eye of user **102**. In such an embodiment, steps **904-908** of flowchart **900** may be performed once for both lenses (such that each lens receives the same processed entity image), or may be performed separately for each lens (such that a different entity image is received by each lens).

[0078] For instance, FIG. 10 shows a block diagram of a wearable device **1000**, according to an example embodiment of the present invention. As shown in FIG. 10, wearable device **1000** is configured to generate right and left entity images **516a** and **516b** at right and left lenses **512a** and **512b**, respectively, which are respectively aligned with right and left eyes **514a** and **514b** of user **102**. In the example of FIG. 10, entity image processor **508** includes a right image processor **1002a** and a left image processor **1002b**. Right image processor **1002a** receives position information signal **522** and virtual entity image information **524**, and generates processed right image information signal **528a**. Right display generator **510a** receives processed right image information signal **528a** and generates right entity image **516a** at right lens **512a**. Left image processor **1002a** receives position information signal **522** and virtual entity image information **524**, and generates processed left image information signal **520b**. Left display generator **510b** receives processed left image information signal **528b** and generates left entity image **516b** at left lens **512b**.

[0079] Right eye **514a** views right entity image **516a** at right lens **512a**, and left eye **514b** views left entity image **516b** at left lens **512b**. Processed right image information signal **528a** and processed left image information signal **528b** may be configured such that right entity image **516a** and left entity image **516b** form a stereoscopic image of the virtual entity to user **102**, creating an illusion of depth. In this manner, the virtual entity corresponding to right and left entity images **516a** and **516b** may appear to be three-dimensional when viewed through wearable device **1000**.

[0080] As described above, wearable device **104** may be configured to superimpose a virtual entity image on a real world entity to enable user **102** to view the virtual entity image in place of the real world entity. In such case, the position of the real world entity may need to be determined and/or tracked, so that wearable device **104** can maintain the virtual entity image in position on lens **512** to conceal the real world entity. In such case, position information regarding a real-world entity may be determined, and image information regarding a virtual entity may be processed based on that determined position information. For instance, FIG. 11 shows a flowchart **1100** providing a process for processing position information regarding a real-world entity, according to an example

embodiment of the present invention. Flowchart **1100** is described as follows.

[0081] Flowchart **1100** begins with step **1102**. In step **1102**, at least one of a location of the second entity, an orientation of the second entity, or a speed at which the second entity is moving is determined. The second entity may be a real-world entity, such as entity **302** shown in FIG. **3**. A location, orientation, and/or speed of the second entity may be determined in any suitable manner, including using image recognition, tracking the second entity with a radio frequency identification (RFID) device (e.g., tag) attached to the second entity, and/or using other techniques. For example, a wearable device may include a camera (for image recognition) and/or a RFID reader (to track a RFID device). Step **1102** may be performed during step **902** of flowchart **900** shown in FIG. **9**, for example.

[0082] In step **1104**, the image information representative of the first entity is processed based on the determined at least one of the location of the second entity, the orientation of the second entity, or the speed at which the second entity is moving. Image information received from entity information storage **504** regarding the first entity (the entity to be displayed as a virtual entity image (e.g., entity image **516**)), may be processed based on the determined location, orientation, and/or speed of the second entity (the real world entity). As described above, the distance between the location of wearable device **500** and the virtual location of the virtual entity (e.g., the location of the real-world entity), the larger will be the image of the virtual entity generated for display by entity image processor **508**. Such distance may change as the position of the real world entity changes, at a rate of speed of movement of the real-world entity. Entity image processor **508** may scale the size of the virtual entity generated for display based upon the distance. Furthermore, as the orientation of the real world entity changes, the orientation of the virtual entity may need to be changed. The orientation of the virtual entity image displayed in lens **512** may be modified by entity image processor **508**. Step **1104** may be performed during step **904** of flowchart **900** shown in FIG. **9**, for example.

[0083] FIG. **12** shows a flowchart **1200** that is an example of flowchart **1100** shown in FIG. **11**, according to an embodiment of the present invention. Flowchart **1200** is described with respect to a wearable device **1300** shown in FIG. **13**. Wearable device **1300** is an example of wearable device **104** shown in FIG. **1**, according to an embodiment of the present invention. Flowchart **1200** is described as follows.

[0084] In step **1202**, an image of the second entity is captured. Wearable device **1300** shown in FIG. **13** is generally similar to wearable device **500** shown in FIG. **5**, with differences described as follows. As shown in FIG. **13**, wearable device **1300** includes a camera **1302**. Camera **1302** is configured to capture an image of an environment viewable by user **102**, including capturing an image of a real-world entity **1308**. Camera **1302** may be any type of suitable image capturing device mountable in wearable device **1300**, as would be known to persons skilled in the relevant art(s). For example, camera **1302** may include an image sensor, such as a charge coupled device (CCD) or a CMOS (complementary metal-oxide-semiconductor) sensor. As shown in FIG. **13**, camera **1302** generates a captured image information signal **1306**. Step **1202** may be performed during step **1102** of flowchart **1100** shown in FIG. **11**, for instance.

[0085] In step **1204**, the captured image is processed to determine a location of the second entity. For instance, as shown in FIG. **13**, entity image processor **508** includes an image recognition module **1304**. Entity image processor **508** receives captured image information signal **1306**. Image recognition module **1304** processes captured image information signal **1306** to identify real-world entity **1308** in the captured image, and to determine a location of real-world entity **1308** in the local environment. Image recognition module **1304** may use any suitable pattern/image recognition techniques known to persons skilled in the relevant art(s). For example, pose estimation techniques may be performed by image recognition module **1304** on captured image information signal **1306** to estimate a position and/or orientation of real world entity **1308** relative to camera **1302**. Entity image processor **508** generates processed image information signal **1310**, which includes the image

information regarding the virtual entity received in virtual entity image information **524** processed according to the determined position and/or orientation of real-world entity **1308**. Step **1204** may be performed during step **1104** of flowchart **1100** shown in FIG. **11**, for instance.

[0086] In step **1206**, the image of the first entity on the lens is optically aligned with the second entity visible through the lens to at least partially conceal the second entity to the user of the wearable device. For instance, display generator **510** receives processed image information signal **1310**, and generates an entity image **1312** at lens **512**, which is representative of the virtual entity selected to replace entity **1308** in the viewable environment of user **102**. Entity image **1312** is positioned at lens **512** to conceal entity **1308** from the view of user **102**. For example, FIG. **14** shows a block diagram representation of entity image **1312** optically aligned on lens **512** between eye **514** of user **102** and real-world entity **1308**. Entity image **1312** is sized and positioned to substantially conceal real-world entity **1308** with respect to eye **514**. As described above, entity image **1312** may be focused by display generator **510** to appear at the distance of entity **1308** from wearable device **1300**.

[0087] Note that in an embodiment, a pair of cameras **1302** may be included in wearable device **1300**. For example, wearable device **1000** shown in FIG. **10** may include a first camera **1302a** associated with right eye **514a** and a second camera **1302b** associated with left eye **514b**. Right image processor **1002a** may include a first image recognition module **1304a** configured to process a captured image information signal **1306a** generated by first camera **1302a**, to generate a processed image information signal **1310a**. Left image processor at **1002b** may include a second image recognition module **1304b** (or may use the same image recognition module **1304**) configured to process captured image information signal **1306b** generated by second camera **1302b**, to generate a processed image information signal **1310b**. Right display generator **510a** may receive processed image information signal **1310a**, and may generate a corresponding right entity image **1312a** in optical alignment with right eye **514a** and entity **1308**. Left display generator **510b** may receive processed image information signal **1310b**, and may generate a corresponding left entity image **1312b** in optical alignment with left eye **514b** and entity image **1308**. In this manner, user **102** may be presented with a stereoscopic view of entity image **1312** that conceals real world entity **1308**.

[0088] As shown in FIGS. **5**, **10**, and **13**, wearable devices may be configured to be self-contained. In further embodiments, wearable devices, including the wearable devices shown in FIGS. **5**, **10**, and **13**, may be configured as not self-contained. In such embodiments, a first set of the elements described above may be included in a wearable device and a second set of the elements described above may be separate from the wearable device.

[0089] For instance, FIG. **15** shows a block diagram of a reality overlay system **1500**, according to an example embodiment of the present invention. As shown in FIG. **15**, system **1500** includes a computer **1502**, a reality overlay server **1504**, and a wearable device **1506**. Computer **1502** includes user interface **502** and a communication interface **1518**. Reality overlay server **1504** includes entity information storage **504**, entity image processor **508**, and a communication interface **1508**. As shown in FIG. **15**, communication interface **1508**, entity image processor **508**, and entity information storage **504** are coupled together in server **1504** by a communication signal/bus. Wearable device **1506** includes position monitor **506**, camera **1302** (when present), display generator **510**, lens **512**, a communication interface **1510**, and a body **1522**. Body **1522** includes (e.g., mounts and/or contains) position monitor **506**, camera **1302** (when present), display generator **510**, lens **512**, and communication interface **1510**.

[0090] Computer **1502** and reality overlay server **1504** communicate over a communication link **1516**. Communication interface **1518** of computer **1502** may transmit signals that are received by communication interface **1508** of reality overlay server **1504**, and communication interface **1508** may transmit signals that are received by communication interface **1518**. For instance, as described above, communications regarding selecting and configuring virtual entities (e.g., virtual entity

configuration information **518** exchanged between user interface **502** and entity information storage **504**) may occur over communication link **1516** between communication interfaces **1508** and **1518**.

[0091] Reality overlay server **1504** and wearable device **1506** communicate over a communication link **1520**. Communication interface **1508** of reality overlay server **1504** may transmit signals that are received by communication interface **1510** of wearable device **1506**, and communication interface **1510** may transmit signals that are received by communication interface **1508**. For instance, as shown in FIG. **15**, communication interface **1510** may receive position information signal **522** and captured image information signal **1306**, and transmit the corresponding position and captured image information from wearable device **1506** to communication interface **1508** at reality overlay server **1504** in a first communication signal **1512**. Communication interface **1508** may receive first communication signal **1512**, and may provide the associated position and captured image information to entity image processor **508**. Entity image processor **508** may also receive virtual entity image information **524** from entity information storage **504**, and may generate processed image information signal **1310**. Communication interface **1508** may receive and transmit processed image information signal **1310** from server **1504** to communication interface **1510** at wearable device **1506** in a second communication signal **1514**. Communication interface **1510** may receive second communication signal **1514**, and may transmit processed image information signal **1310** to display generator **510**. Display generator **510** may generate a virtual entity image at lens **512** based upon processed image information signal **1310**, as described above.

[0092] Communication links **1516** and **1520** may be wired and/or wireless links, such as an IEEE 802.11 wireless LAN (WLAN) wireless link, a Worldwide Interoperability for Microwave Access (Wi-MAX) wireless link, an Ethernet interface, a Universal Serial Bus (USB), etc. For example, communication links **1516** and/or **1520** may include a local area network (LAN), a wide area network (WAN), a personal area network (PAN), or a combination of networks, such as the Internet. Communication interfaces **1508**, **1510**, and **1518** may be any type of communication/network interfaces (e.g., network interface card (NIC)), wired or wireless, such as an as IEEE 802.11 WLAN wireless interface, a Wi-MAX interface, an Ethernet interface, a Universal Serial Bus (USB) interface, etc.

[0093] In an embodiment where communication link **1520** includes a wireless link, wearable device **1506** may be wirelessly worn by user **102** without the hassles of a communication wire being attached to wearable device **1506**. In the embodiment of FIG. **15**, position information collection is performed in wearable device **1506** (e.g., by position monitor **506** and camera **1302**), and image processing is performed in server **1504**. It is noted that **1500** is provided for illustrative purposes, and is not intended to be limiting. The elements of computer **1502**, server **1504**, and wearable device **1506** shown in FIG. **15** may be redistributed between computer **1502**, server **1504**, and wearable device **1506** in other ways, including between additional or fewer devices, as would be understood to persons skilled in the relevant art(s) based on the teachings provided herein.

[0094] Body **1522** of wearable device **1506** may have various form factors, including the form of glasses, goggles, a mask, or other suitable form factor. For instance, FIG. **16** shows a wearable device **1600**, according to an example embodiment of the present invention. Wearable device **1600** is still another example of wearable device **104** shown in FIG. **1**. As shown in FIG. **16**, wearable device **1600** includes a start button **1602**, a plurality of sensors **1604**, a microphone **1606**, a pair of sound captors **6008**, a set of headphones **1610**, a visual indicator **1612**, a pair of transparent lenses **1614**, and a body **1616**. As shown in FIG. **16**, body **1616** is shaped as a pair of glasses or goggles. Body **1616** may be modified to further prevent light from reaching the eyes of the user from around body **1616**. For example, a flexible extended lip may be provided around each lens **1614** to conform closely to the face of the user. An example of wearable device **1600** is described in co-pending U.S. patent application Ser. No. 12/125,877, titled "Reality Overlay Device," filed on May 22, 2008, which is incorporated by reference herein in its entirety. Wearable device **1600** is further

described as follows.

[0095] As shown in FIG. 16, lenses **1614** enable a user to view his or her surroundings through lenses **1614**. Lenses **1614** may function as screens that enable a non-transparent reality overlay to be displayed to the user, as described above. In embodiments, each of the lenses **1614** may include a liquid crystal display (LCD) or a display projector.

[0096] Wearable device **1600** may support connection to a wireless network such as a cell phone network, localized Bluetooth devices, Worldwide Interoperability for Microwave Access (Wi-MAX) and Wireless Fidelity (Wi-Fi), as described above. In addition, wearable device **1600** may support further communication mechanisms such as Universal Serial Bus (USB), etc. Start button **1602** may enable the user to turn wearable device **1600** on (or off). In one embodiment, when wearable device **1600** is off, wearable device **1600** may be used as a pair of sunglasses. When wearable device **1600** is on, wearable device **1600** may receive and capture information that is pertinent to physical surroundings with respect to wearable device **1600**, enabling a reality overlay to be generated in the form of one or virtual entity images, as described above. For instance, the information that is captured may include position, visual, and/or audio information.

[0097] The visual information may be captured via one or more visual inputs such as visual sensors **1604**, which may each be camera **1302** shown in FIG. 13, for example. For instance, each of visual sensors **1604** may be a still or video camera that is capable of capturing one or more still images or video images, respectively. These images may be captured in two-dimensional form or three-dimensional form. In one embodiment, visual sensors **1604** may include two sensors, where one of the sensors **1604** is positioned at the left side of the lenses **1614** of wearable device **1600** and another one of the sensors **1604** is positioned at the right side of the lenses **1614** of wearable device **1600**. For instance, the sensors **1604** may be placed near the hinges of wearable device **1600**, as shown in FIG. 16. In this manner, the two sensors **1604** may capture images that would be viewed by a user's left and right eyes. The images captured via the two sensors **1604** may be combined to replicate a single image that would be perceived by a user viewing the two separate images through the two different lenses **1614**. The visual sensors **1604** may further include a third sensor at the center of the lenses **1614** of wearable device **1600**.

[0098] Audio information may be captured via one or more audio sensors. For instance, the audio sensors may include one or more microphones. As shown in this example, one or more microphones **1606** may be provided on the bridge of wearable device **1600** for purposes of capturing voice commands from a user of wearable device **1600** and/or for capturing surrounding sounds. In an embodiment, wearable device **1600** may also support voice recognition to assist in capturing voice commands. The audio sensors may also include one or more sound captors (e.g., microphones) **1608** at various locations on wearable device **1600**. In the example of FIG. 16, sound captors **1608** include two separate sound captors, where each of the sound captors is positioned on the external side of one of the arms of wearable device **1600**. Sound captors **1608** may function to receive sounds from the surroundings (e.g., rather than from the user of the device).

[0099] As described above, wearable device **1600** may also include position monitor **506** configured to determine information such as a location of wearable device **1600** (e.g., coordinates of the device), an orientation of wearable device **1600**, or a speed with which wearable device **1600** is moving. For example, wearable device **1600** may include a global positioning system (GPS) device to enable coordinates of wearable device **1600** to be determined. As another example, wearable device **1600** may include one or more gyroscopes that may be used to determine an orientation of wearable device **1600**. As yet another example, wearable device **1600** may include an accelerometer that may be used to determine an orientation and/or speed with which wearable device **1600** is traveling.

[0100] Other information that may be captured by the device may include identifying one or more entities in the field of vision of wearable device **1600**. For instance, wearable device **1600** may support pattern recognition by including or accessing image recognition module **1304** shown in

FIG. 13. Thus, wearable device **1600** may process at least a portion of the received information (e.g., one or more images) in order to identify one or more entities using pattern recognition. Such entities may include environmental features such as a mountain, a road, a building, a sidewalk, and/or other fixed position entities. Moreover, entities that are recognized may also include people, animals, vehicles, and/or other mobile entities. Pattern recognition may also be used to identify specific buildings by identifying letters, words, or addresses posted in association with a particular building. In addition, the device may enable entities to be recognized by a Radio Frequency Identification (RFID) or similar hardware tag. Similarly, entities may be recognized using the location of wearable device **1600** and orientation of wearable device **1600**.

[0101] Wearable device **1600** may obtain virtual entity overlay information for use in generating and providing a non-transparent overlay of a virtual entity image and/or audio overlay using at least a portion of the information that wearable device **1600** has captured. The virtual entity in which information may be obtained at entity image storage **504** locally (e.g., from one or more local memories and/or processors) or remotely. For instance, virtual entity image information may be obtained remotely from one or more servers using an Internet browser via a wireless connection to the Internet, as described above. Wearable device **1600** or a remotely located server may identify one or more entities in the information that wearable device **1600** has captured. This may be accomplished by accessing a map of the location in which wearable device **1600** is being used, using RFID, and/or by using pattern recognition, as set forth above. Information that is pertinent to the identified entities may then be obtained.

[0102] The virtual entity image information may also specify placement of a virtual entity with respect to real world entities. For example, the location of an entity in the visual information may be used to determine an optimum placement of the virtual entity image at lenses **1614**. For example, where a real-world entity is a restaurant, the virtual entity image information associated with the restaurant may be positioned immediately next to or in front of the restaurant.

[0103] Similarly, in accordance with various embodiments, audio overlay information may be provided via one or more audio outputs (e.g., speakers) of wearable device **1600**. In this example, wearable device **1600** includes a headphone **1610** that includes a speaker on the internal side of both the left and right arms of wearable device **1600**. In this manner, a user may receive audio overlay information such as directions a voice or sounds made by a virtual entity displayed at lenses **1614**.

[0104] Wearable device **1600** may further include visual indicator **1612** configured to signal whether wearable device **1600** is online or offline. Visual indicator **1612** may also be used to indicate whether the user is on a wireless call.

[0105] The identity of the user of wearable device **1600** may be ascertained and used in various embodiments in order to tailor the operation of wearable device **1600** to preferences of the user. An identity of the user (e.g., owner) of wearable device **1600** may be statically configured. Thus, wearable device **1600** may be keyed to an owner or multiple owners. In some embodiments, wearable device **1600** may automatically determine the identity of the user (e.g., wearer) of wearable device **1600**. For instance, a user of the device may be identified by deoxyribonucleic acid (DNA) and/or retina scan.

[0106] It is important to note that wearable device **1600** shown and described with reference to FIG. **16** is provided for illustrative purposes, and therefore wearable device **1600** may be implemented in different forms. Moreover, wearable device **1600** may support some or all of the above listed features, as well as additional features not set forth herein.

B. Example Wearable Reality Overlay Device Application Embodiments

[0107] The wearable devices described herein may be used in a variety of applications, and may be used to display any number of virtual entities with respect to any number of real world entities in a viewable environment. For example, FIG. **17** shows a block diagram of processed environment view **108** provided by wearable device **104**, where a variety of virtual entity images **1702** and real

world entities **1704** are viewable by user **102** of wearable device **104**. Virtual entity images **1702** are generated for display at the lenses of wearable device **104** so that their corresponding virtual entities appear to be present to user **102**. In some cases, virtual entity images **1702** may be configured to partially or entirely conceal one or more real world entities **1704** from the view of user **102**.

[0108] For instance, user **102** may desire to simulate a trip to another place (e.g., an interstellar location), with a friend. Wearable device **104** may be configured to generate various virtual entity images that combine with real world entities to generate a virtual view of the other place to user **102**. For example, a virtual entity image **1702a** (e.g., the planet Mars) is generated to be visible to user **102**. A virtual entity image **1702b** (e.g., a spaceship) is generated to be visible to user **102** that entirely conceals a real-world entity (e.g., a car) from the view of user **102**. A portion of a real-world entity **1704a** (e.g., a friend of user **102**) is visible to user **102**. A virtual entity image **1702c** (e.g., a spacesuit) is generated to be visible to user **102**, and partially conceals real-world entity **1704b** from the view of user **102**. A real-world entity **1702b** (e.g., user **102**'s dog) is visible to user **102**. A virtual entity image **1702d** (e.g., the lunar landscape) is generated to be visible to user **102** that entirely conceals a real world entity (e.g., the ground of the local environment) from user **102**.

[0109] This description of processed environment view **108** generated by wearable device **104** with respect to FIG. **17** is provided for illustrative purposes, and is not intended to be limiting. Any number of virtual entities and/or any type of virtual environment may be generated by wearable device **104** to be overlaid over a real-world environment. Further example embodiments of the present invention include:

[0110] 1. Creation of monetizable virtual entities: As wearable reality overlay devices become prevalent in the marketplace, individuals and/or companies that generate and/or sell virtual entities, including any virtual entities described elsewhere herein (virtual clothing, toys, pets, objects, etc.), may be able to generate income based on the sales.

[0111] 2. Locking the appearance of persons: As described herein, wearable reality overlay devices enable the appearance of others to be modified. Persons may desire to lock their appearance to a particular selected appearance, so that their appearance in other users' wearable devices will always appear the same. For instance, a user may have a full body, three-dimensional scan of their body performed. The full body scan may be uploaded into storage (e.g., in entity information storage **504**), and may be available at a central server (e.g., server **1504** shown in FIG. **15**) to be accessed by various wearable devices. The stored full body scan is a canonical source of imagery for any other user having a wearable reality overlay device that views the user. In addition, a user can optionally configure clothing patterns for their self and others to view using a wearable device.

[0112] 3. Maintaining the appearance of entities: In a world where wearable reality overlay devices are prevalent, because the “real world” can be re-skinned in the view of users, real world entities in physical space may fall into disrepair. The virtual appearance of decaying real world entities such as furniture, buildings, clothing, etc., can continue to appear well-maintained using wearable reality overlay devices. Furthermore, such real world entities can be revised and/or upgraded by overlaying virtual entities on the real world entities that are revised virtual and/or upgraded versions. For example, instead of purchasing a new real world dresser for an old dresser, the old dresser could be made to virtually appear in new shape or as a different style of dresser, such as a colonial or mid-century dresser to users of wearable devices.

[0113] 4. Example application—living in another era: a user who has a penchant for nostalgia can substitute reality with an earlier era by “re-skinning” the real-world entities around them with virtual versions of the real-world entities from an earlier era.

[0114] 5. Example application—living in an alternative city: a user can re-skin entities present in their current city so it appears to be a different city. For example, a San Francisco resident who just travelled to Paris may wish to re-skin San Francisco with Parisian themed virtual entities.

[0115] 6. Example application—adding life caching: Virtual entities representative of absent or dead relatives can be added to the field of view of a user of a wearable reality overlay device. Artificial intelligence (AI) technologies can be used to simulate the actions

of such virtual persons as viewed in a wearable device if such persons can be “life cached.” A user may be enabled to have a conversation with a virtual representation of a dead, famous, absent or other person, based on their cached life. [0116] 7. Example application—games: Users of wearable devices can insert themselves into games having a virtual gaming environment (e.g., a virtual game field of play), virtual competitors and/or teammates, virtual game implements (e.g., virtual game balls, rackets, bats, gloves, guns, etc.), that are displayed alongside real-world components of the games, including real-world game field features, real-world persons that are teammates or competitors, real world game implements, etc. The following subsection describes some example wearable reality overlay device embodiments in a gaming environment.

C. Example Wearable Reality Overlay Device Gaming Embodiments

[0117] In embodiments, wearable reality overlay devices are configured to enable reality and virtual aspects to be presented together to manipulate reality for gaming purposes. Examples of such embodiment are described in the present subsection. The example embodiments described herein are provided for illustrative purposes, and are not limiting. Further structural and operational embodiments, including modifications/alterations, will become apparent to persons skilled in the relevant art(s) from the teachings herein.

[0118] FIG. **18** shows a block diagram of an example wearable reality overlay device **1800** (hereinafter “wearable device **1800**”), according to an embodiment of the present invention. Wearable device **1800** is an example of wearable device **104** shown in FIG. **1**. As shown in FIG. **18**, wearable device **1800** includes user interface **502**, entity information storage **504**, position monitor **506**, display generator **510**, lens **512**, a game engine **1802**, a microphone **1822**, and a speaker **1824**. Game engine **1802** includes entity image processor **508**, a rules engine **1810**, an AI module **1812**, a game field layout module **1814**, an audio processor **1816**, and a remote player interface **1818**. As shown in FIG. **18**, wearable device **500** interacts with eye **514**, which may be an eye of user **102** shown in FIG. **1**, for example.

[0119] The elements of wearable device **1800** shown in FIG. **18** may be included in a self-contained wearable device, or may be included in different devices (e.g., as shown in FIG. **15**, where computer **1502**, server **1504**, and wearable device **1506** each include respective elements). For example, game engine **1802** may be included in a server that is accessible by one or more wearable devices, including wearable device **1800**. Furthermore, wearable device **1800** may include dual image processing (e.g., generating virtual images for a pair of lenses as shown in FIG. **10**) and/or dual audio processing (e.g., receiving sound at right and left microphones **1822**, and generating sound at right and left speakers **1824**).

[0120] Wearable device **1800** is generally similar to the wearable devices described above, with differences described as follows. Wearable device **1800** is described below with respect to FIG. **19**. FIG. **19** shows a flowchart **1900** for reality overlay in a gaming environment, according to an example embodiment of the present invention. For example, the steps of flowchart **1900** may be integrated in flowchart **900** shown in FIG. **9**. Flowchart **1900** may be performed by wearable device **1800**, for example. Wearable device **1800** and flowchart **1900** are described as follows.

[0121] In step **1902**, image information corresponding to one or more virtual game entities is received. As shown in FIG. **18**, virtual entity descriptions **520** stored in entity information storage **504** include various game related virtual entity descriptions, such as characters **1804**, implements **1806**, and features **1808**. The characters **1804**, implements **1806**, and features **1808** descriptions may be received at entity image processor **508** in game engine **1802** from entity information storage **504** in virtual entity image information **524**.

[0122] Characters **1804** may include graphical information necessary for graphical rendering of an image of the one or more virtual characters of a game served by game engine **1802**. Characters **1804** may also include game parameters related to the corresponding virtual characters, including artificial intelligence characteristics and sound characteristics. The graphical information may include information for rendering virtual characters in two or three dimensions, depending on the

particular character and/or game. Examples of virtual characters that may have descriptors included in characters **1804** include opponents and/or teammates of a user of wearable device **1800**, and may include virtual characters such as virtual animals, people (e.g., celebrities, athletes, famous people, historical figures, friends, relatives, etc.), video game characters, monsters, cartoon characters, and other virtual characters.

[0123] Implements **1806** may include graphical information necessary for graphical rendering of an image of the one or more virtual implements of a game served by game engine **1802**. The graphical information may include information for rendering virtual implements in two or three dimensions, depending on the particular implement and/or game. Examples of virtual implements that may have descriptors included in implements **1806** include virtual game balls (e.g., virtual baseballs, golf balls, soccer balls, footballs, basketballs, tennis balls, ping-pong balls, racquet balls, etc.), rackets, bats, firearms, other weapons, vehicles, musical instruments, and other virtual implements.

[0124] Features **1808** may include graphical information necessary for graphical rendering of an image of the one or more virtual features of a game served by game engine **1802**. The graphical information may include information for rendering virtual features in two or three dimensions, depending on the particular feature and/or game. Examples of virtual features that may have descriptions included in features **1808** include virtual game fields (e.g., turf, grass, hard court, field markers, a battlefield, etc.), trees, dwellings, mountains, goals, goalposts, targets, nets (e.g., a tennis net, a basketball net, etc.), and other virtual features.

[0125] In step **1904**, a next game state is determined based on one or more of the determined information, one or more rules of a game, a virtual player artificial intelligence, a game field configuration, a current game state, or at least one additional real-world game player. Game engine **1802** may be configured to perform step **1904**. Game engine **1802** may maintain a game state **1830**. Based upon the maintained game state **1830**, game engine **1802** may determine a next game state **1830**. One or more of rules engine **1810**, AI module **1812**, game field layout module **1814**, and audio processor **1816** of game engine **1802** may be present to process corresponding received information and/or information related to game state **1830** to generate a next game state **1830**.

[0126] For example, rules engine **1810** may be configured to process game physics according to the particular rules of the game, which may be a sport (e.g., basketball, football, baseball, tennis, ping-pong, swimming, track, soccer, etc.), an arcade game, a simulation game (e.g., military, medieval, outer space, etc.), or other type of game. Rules engine **1810** may be configured to process movements of real world players, including movements of user **102**, movements of virtual implements of the game according to the particular rules of the game to generate updated positions for virtual game entities.

[0127] AI module **1812** may be configured to handle the artificial intelligence of virtual characters of the game. For example, AI **1812** may be configured to determine actions of opponents and/or teammates of the user in the game. Based upon the maintained game state **1830**, AI module **1812** may determine the next actions of the virtual characters to be included in the next game state **1830**.

[0128] Game field layout module **1814** may be configured to maintain a layout of the various features of the game relative to motions of wearable device **1802**. For example, game field layout module **1814** may be configured to maintain the positions of features such as those described above with respect to features **1808**, as the game progresses from the current game state **1830** to a next game state **1830**.

[0129] Audio processor **1816**, microphone **1822**, and/or speaker **1824** may each be optionally present. Audio processor **1816** may be configured to receive a voice input **1826** of user **102** received at microphone **1822**, and to analyze voice input **1826** for instructions provided by user **102**. Determined instructions may be provided to rules engine **1810** to be processed with respect to the rules of the game, to AI module **1812** to be processed as instructions to virtual characters of the game, and/or to be communicated to remote real-world persons participating in the game (e.g., over a communication link **1820**). Audio processor **1816** may also generate sound information **1828** to

be broadcast by speaker **1824** to user **102**. The broadcast of sound information **1828** may include voice communications from virtual characters and/or from remote real-world persons participating in the game, and/or may include sound effects of the game.

[0130] Remote player interface **1818** provides an interface between game engine **1802** and other persons participating in the game. Remote player interface **1818** is configured to communicate over a communication link **1820** with remote wearable devices and/or other electronic devices associated with the remote players. In an embodiment where game engine **1802** is separate (e.g., located in a separate server) from wearable device **1800**, communications of camera **1302**, display generator **510**, microphone **1822**, and speaker **1824** may occur from wearable device **1800** over communication link **1820** to game engine **1802** rather than directly to game engine **1802** as shown in FIG. **18**. Remote player interface **1818** may include any suitable communication interface described elsewhere herein or otherwise known.

[0131] In step **1906**, the image information is processed based on the determined next game state **1830**. Entity image processor **508** is configured to process the image information corresponding to the virtual game entities received in virtual entity image information **524** based on the next game state **1830** determined by game engine **1802** to generate processed image information signal **528**. Processed image information signal **528** may include processed image information corresponding to any number of virtual entities of the game including virtual characters, virtual features, and virtual implements of the game. Step **1906** may be performed during step **904** of flowchart **900** shown in FIG. **9**, for example.

[0132] In step **1908**, one or more images corresponding to the one or more virtual game entities are generated based on the processed image information as one or more corresponding non-transparent region of a lens of the wearable device. As shown in FIG. **18**, display generator **510** receives processed image information signal **528**, and is configured to generate one or more entity images **516** at lens **512** as non-transparent regions. The one or more entity images **516** correspond to virtual entities of the game. The non-transparent regions enable the one or more virtual entities to appear to be present in the environment to user **102** of wearable device **1800**.

[0133] For example, FIG. **20** shows an example of environment **106** viewable to user **102** when wearable device **1800** is not present or activated. As shown in FIG. **20**, environment **106** includes a tree **2002**, a real-world game participant **2004**, a lot **2006**, a house **2008**, and a handheld game controller **2010**. When user **102** is wearing wearable device **1800**, and has activated a game of lacrosse, a processed environment view **108** shown in FIG. **21** may be provided to user **102** through wearable device **1800**, in an example embodiment. Virtual entities in processed environment view **108** may be generated by wearable device **1800** that interact in the game of lacrosse with user **102** according to game engine **1802**.

[0134] For instance, various virtual entity images are displayed to user **102** by wearable device **1800** that correspond to the game of lacrosse. As shown in FIG. **21**, processed environment view **108** includes tree **2002**, real-world game participant **2004**, lot **2006**, and house **2008**, and further includes a virtual scoreboard **2102**, a virtual goal **2104**, a virtual lacrosse stick **2106**, a virtual ball **2108**, a virtual opponent **2110**, a virtual player outfit **2112**, and virtual field marker lines **2114**. Virtual scoreboard **2102** is positioned to in front of tree **2002** to partially conceal tree **2002**. Virtual scoreboard **2102** is configured by game engine **1802** to display a score of the game. Virtual goal **2104** is positioned at an end of a virtual game field indicated by virtual field marker lines **2114**. Real world game participant **2004** is provided with virtual lacrosse stick **2106** that conceals handheld game controller **2010**. Wearable device **1800** is configured to virtually replace handheld game controller **2010** with virtual lacrosse stick **2106**. Real world game participant **2004** may pick up virtual ball **2108** using virtual lacrosse stick **2106** (by moving handheld game controller **2010**), and may score a goal by throwing virtual ball **2008** into virtual goal **2104** using virtual lacrosse stick **2106** (by moving handheld game controller **2010**). Virtual opponent **2110** may attempt to try to prevent real-world game participant **2004** from scoring a goal by intercepting virtual ball **2108** or

otherwise virtually interacting with real world game participant **2004** according to the rules of lacrosse. User **102** may interact in the game using a virtual lacrosse stick (not visible in FIG. **21**) as a teammate or opponent of real-world game participant **2004**, for example.

[0135] As described above, real world game participant **2004** may use handheld game controller **2010**. Handheld game controller **2010** may be similar to the Wii Remote™ distributed for the Nintendo® Wii™ game console by Nintendo Company Ltd, of Kyoto, Japan, for example. Movements of handheld game controllers **2010** held by user **102** and/or real world game participant **2004** can be tracked by wearable device **1800** to aid in simulating a tennis court, a boxing ring (complete with bystanders), a golf course, a bowling alley, or a baseball stadium, for example, in a virtual environment. For example, controller **2010** may include a RFID tag, an infrared emitter, or other mechanism enabling its motions to be tracked. Games, such as a virtual boxing match may be undertaken between user **102** and real-world game participant **2004** using controller **2010**. The surroundings may be replaced by a virtual boxing ring environment generated by wearable device **1800** that is viewable by user **102**. User **102** and real-world game participant **2004** may be enabled to virtually fight against each other in this manner.

[0136] These examples of wearable device **1800** enabling user **102** to participate in the above described game environments are provided for illustrative purposes, and are not intended to be limiting. Any type of game environment may be enabled by wearable device **1800** that includes any number of virtual entities and real world entities. Further example embodiments are described as follows: [0137] 1. A capture the flag game can be enabled by wearable device **1800**. For example, user **102** may travel to a specific physical location and make a specific hand movement in order to capture a virtual flag. [0138] 2. A virtual Pac-man game may be enabled by wearable device **1800**. For example, user **102** may travel along a specific path in order to touch floating virtual dots suspended in his/her field of vision by wearable device **1800** (this approach can be modified to lead a wearer to a location by walking by following virtual “bread crumbs”). [0139] 3. A virtual maze can be generated in an open field by wearable device **1800**. User **102** may be enabled to navigate the virtual maze by wearable device **1800** by walking through the virtual maze. [0140] 4. An open space can have any kind of field virtually imposed upon it by wearable device **1800**. For example, a soccer game can be enabled to be played with a virtual ball, a civil war strategy game can be enabled to be played with the real world participants wearing virtual period clothing and brandishing virtual period weapons. Real world physical characteristics can be embedded directly in the game, such as enabling a hill to be overtaken by an opposing force, etc. [0141] 5. A laser tag game can be enabled to be played in the real world by wearable device **1800**, using virtual laser guns, and using real world physical objects to block shots, etc. [0142] 6. Virtual people, avatars, cartoon characters, etc., can be generated by wearable device **1800** to provide user **102** with clues in order to move forward in a game. [0143] 7. A virtual World Of Warcraft-type overlay can be generated that is superimposed on the real world by wearable device **1800** instead of being viewed on a computer screen. According to the virtual overlay, user **102** can be enabled to play in the real world, but be fighting virtual characters. Note that in any game, wearable device **1800** may be enabled with overrides configured to reveal real world entities to user **102** as required to avoid real world dangers/accidents/collisions. [0144] 8. User **102**, real world game participant **2004**, and/or other real world game participants may each be wearing a corresponding wearable device **1800**, and may be enabled by game engine **1802** (which may be located in a separate server) to interact in games together. For example, user **102** and the other game participants may be enabled to re-enact famous battles or points of time in history. For example, the battle of Gettysburg may be virtually reenacted while user **102** and the other game participants stand, walk, and/or run in a common field. Wearable device **1800** may be configured to virtually overlay the armies over the real world field. As user **102** turns his/her head wearable device **1800** correspondingly re-aligns the virtual infantry over the hills. [0145] 9. In typical “cosplay,” or “costume play,” a person physically dresses like their favorite character and can emulate that character. Using wearable device **1800** as

a cosplay device, user **102** can simulate the appearance of their favorite characters appearance by virtually applying their appearance/clothing to them self, and to other cosplay participants. [0146] 10. Amateur and professional sports players can wear wearable devices **1800** in order to receive real time play information from their coaches. For example, a football game may no longer require huddles for the players to confer with each other or for the coach to confer with the players, but instead, plays may be fed in real time to the players through wearable devices **1800** while they are on the field. Wearable device **1800** may be configured to display to user **102** where user **102** needs to go on the field in order to complete a play and to set up a next play. [0147] 11. A concert may be virtually displayed by wearable device **1800** to user **102**. For example, wearable device **1800** may display a concert to user **102** of their favorite band. Wearable device **1800** may virtually overlay the concert at any place that user **102** is located, such as in a park full of people, or in the living room of user **102**. [0148] 12. Monetization: Wearable device **1800** may enable monetizing of various aspects of games. For example, sponsors can use “reality show”-type virtual gaming to encourage individuals to perform tasks for rewards. Additional advertisement inventory can be generated by wearable device **1800** by displaying virtual advertisements on real world objects during games. Furthermore, any needed development infrastructure/platform for wearable device **1800** (e.g., a server for game engine **1802**) can be resold/rented to game developers.

III. Example Computer Implementation

[0149] Note that wearable devices **104**, **500**, **1000**, **1300**, **1506**, **1600**, and **1800**, computer **1502**, and server **1504** may each include hardware, software, firmware, or any combination thereof to perform their respective functions. For example, any one or more of wearable devices **104**, **500**, **1000**, **1300**, **1506**, **1600**, and **1800**, computer **1502**, and server **1504** may include computer code configured to be executed in one or more processors. Alternatively or additionally, any one or more of wearable devices **104**, **500**, **1000**, **1300**, **1506**, **1600**, and **1800**, computer **1502**, and server **1504** may be implemented in hardware logic/electrical circuitry.

[0150] Devices in which embodiments may be implemented may include storage, such as storage drives, memory devices, and further types of computer-readable media. Examples of such computer-readable media include a hard disk, a removable magnetic disk, a removable optical disk, flash memory cards, digital video disks, random access memories (RAMs), read only memories (ROM), and the like. As used herein, the terms “computer program medium” and “computer-readable medium” are used to generally refer to the hard disk associated with a hard disk drive, a removable magnetic disk, a removable optical disk (e.g., CDRoms, DVDs, etc.), zip disks, tapes, magnetic storage devices, MEMS (micro-electromechanical systems) storage, nanotechnology-based storage devices, as well as other media such as flash memory cards, digital video discs, RAM devices, ROM devices, and the like. Such computer-readable media may store program modules that include logic for enabling wearable devices **104**, **500**, **1000**, **1300**, **1506**, **1600**, and **1800**, computer **1502**, server **1504**, flowchart **900** of FIG. **9**, flowchart **1100** of FIG. **11**, flowchart **1200** of FIG. **12**, flowchart **1900** of FIG. **19**, and/or further embodiments of the present invention described herein. Embodiments of the present invention are directed to computer program products comprising such logic (e.g., in the form of program code) stored on any computer useable medium. Such program code, when executed in a processing unit (that includes one or more data processing devices), causes a device to operate as described herein.

Conclusion

[0151] While various embodiments of the present invention have been described above, it should be understood that they have been presented by way of example only, and not limitation. It will be apparent to persons skilled in the relevant art that various changes in form and detail can be made therein without departing from the spirit and scope of the invention. Thus, the breadth and scope of the present invention should not be limited by any of the above-described exemplary embodiments, but should be defined only in accordance with the following claims and their equivalents.

Claims

1. A method comprising: tracking, by at least one processor, a position of a movable physical entity among a plurality of physical entities in an area of a physical environment viewable through a wearable device, wherein the tracking comprises: capturing an image of the area by a camera of the wearable device; and processing the captured image to detect the movable physical entity and determine a position of the movable physical entity in the area, the movable physical entity being detected by determining that the movable physical entity corresponds to a predetermined physical entity; determining a virtual entity corresponding to the detected movable physical entity, from among at least one pre-stored virtual entity; and displaying an image of the determined virtual entity at a predefined position relative to a position of the detected movable physical entity such that the image of the determined virtual entity is viewable in the wearable device and appears to be present in the area, wherein the displaying the image of the determined virtual entity comprises scaling a size of the image of the virtual entity relative to a size of the detected movable physical entity as captured in the captured image.

2. The method as claimed in claim 1, further comprising: determining a distance between the wearable device and the movable physical entity, wherein the scaling the size of the image of the virtual entity relative to the size of the detected movable physical entity comprises scaling the size of the image of the virtual entity based on the determined distance between the wearable device and the movable physical entity.

3. The method as claimed in claim 1, wherein the displaying further comprises: determining an orientation of the detected movable physical entity; and displaying the image of the determined virtual entity at a predefined position relative to the position of the detected movable physical entity and at an orientation corresponding to the determined orientation of the detected movable physical entity.

4. The method as claimed in claim 1, wherein the image of the determined virtual entity is displayed by overlaying the image of the virtual entity on the captured area of the physical environment at the predefined position relative to the position of the detected movable physical entity, such that both the image of the virtual entity and at least portions of the captured area of the physical environment are simultaneously viewable through the wearable device.

5. The method as claimed in claim 1, wherein the at least one pre-stored virtual entity comprises the virtual entity configured to be displayed based on detection of the predetermined physical entity and another virtual entity configured to be displayed based on detection of another predetermined physical entity, different from the predetermined physical entity.

6. The method as claimed in claim 1, wherein the predefined position relative to the position of the detected movable physical entity is at least a portion of the movable physical entity, such that the virtual entity is displayed to be overlayed on the at least the portion of the movable physical entity.

7. The method as claimed in claim 1, further comprising: detecting a stationary physical entity in the captured image of the area, the stationary physical entity being detected by determining that the stationary physical entity corresponds to another predetermined physical entity; and displaying an image of another virtual entity at another predefined position relative to a position of the detected stationary physical entity, such that both the image of the virtual entity and the image of the other virtual entity are simultaneously viewable in the wearable device.

8. A wearable device comprising: at least one processor comprising a processing circuitry; and memory storing one or more instructions that, when executed by the at least one processor, cause the wearable device to perform operations comprising: tracking a position of a movable physical entity among a plurality of physical entities in an area of a physical environment viewable through the wearable device, wherein the tracking comprises: capturing an image of the area by a camera of the wearable device; and processing the captured image to detect the movable physical entity and

determine a position of the movable physical entity in the area, the movable physical entity being detected by determining that the movable physical entity corresponds to a predetermined physical entity; determining a virtual entity corresponding to the detected movable physical entity, from among at least one pre-stored virtual entity; and displaying an image of the determined virtual entity at a predefined position relative to a position of the detected movable physical entity such that the image of the determined virtual entity is viewable in the wearable device and appears to be present in the area, wherein the displaying the image of the determined virtual entity comprises scaling a size of the image of the virtual entity relative to a size of the detected movable physical entity as captured in the captured image.

9. The wearable device as claimed in claim 8, wherein the operations further comprise: determining a distance between the wearable device and the movable physical entity, wherein the scaling the size of the image of the virtual entity relative to the size of the detected movable physical entity comprises scaling the size of the image of the virtual entity based on the determined distance between the wearable device and the movable physical entity.

10. The wearable device as claimed in claim 8, wherein the displaying further comprises: determining an orientation of the detected movable physical entity; and displaying the image of the determined virtual entity at a predefined position relative to the position of the detected movable physical entity and at an orientation corresponding to the determined orientation of the detected movable physical entity.

11. The wearable device as claimed in claim 8, wherein the image of the determined virtual entity is displayed by overlaying the image of the virtual entity on the captured area of the physical environment at the predefined position relative to the position of the detected movable physical entity, such that both the image of the virtual entity and at least portions of the captured area of the physical environment are simultaneously viewable through the wearable device.

12. The wearable device as claimed in claim 8, wherein the at least one pre-stored virtual entity comprises the virtual entity configured to be displayed based on detection of the predetermined physical entity and another virtual entity configured to be displayed based on detection of another predetermined physical entity, different from the predetermined physical entity.

13. The wearable device as claimed in claim 8, wherein the predefined position relative to the position of the detected movable physical entity is at least a portion of the movable physical entity, such that the virtual entity is displayed to be overlaid on the at least the portion of the movable physical entity.

14. The wearable device as claimed in claim 8, wherein the operations further comprise: detecting a stationary physical entity in the captured image of the area, the stationary physical entity being detected by determining that the stationary physical entity corresponds to another predetermined physical entity; and displaying an image of another virtual entity at another predefined position relative to a position of the detected stationary physical entity, such that both the image of the virtual entity and the image of the other virtual entity are simultaneously viewable in the wearable device.

15. A non-transitory computer-readable recording medium for tangibly storing thereon program logic for execution by at least one processor of a wearable device to cause the at least one processor to perform a method comprising: tracking, by the at least one processor, a position of a movable physical entity among a plurality of physical entities in an area of a physical environment viewable through a wearable device, wherein the tracking comprises: capturing an image of the area by a camera of the wearable device; and processing the captured image to detect the movable physical entity and determine a position of the movable physical entity in the area, the movable physical entity being detected by determining that the movable physical entity corresponds to a predetermined physical entity; determining a virtual entity corresponding to the detected movable physical entity, from among at least one pre-stored virtual entity; and displaying an image of the determined virtual entity at a predefined position relative to a position of the detected movable

physical entity such that the image of the determined virtual entity is viewable in the wearable device and appears to be present in the area, wherein the displaying the image of the determined virtual entity comprises scaling a size of the image of the virtual entity relative to a size of the detected movable physical entity as captured in the captured image.

16. The non-transitory computer-readable recording medium as claimed in claim 15, further comprising: determining a distance between the wearable device and the movable physical entity, wherein the scaling the size of the image of the virtual entity relative to the size of the detected movable physical entity comprises scaling the size of the image of the virtual entity based on the determined distance between the wearable device and the movable physical entity.

17. The non-transitory computer-readable recording medium as claimed in claim 15, wherein the displaying further comprises: determining an orientation of the detected movable physical entity; and displaying the image of the determined virtual entity at a predefined position relative to the position of the detected movable physical entity and at an orientation corresponding to the determined orientation of the detected movable physical entity.

18. The non-transitory computer-readable recording medium as claimed in claim 15, wherein the image of the determined virtual entity is displayed by overlaying the image of the virtual entity on the captured area of the physical environment at the predefined position relative to the position of the detected movable physical entity, such that both the image of the virtual entity and at least portions of the captured area of the physical environment are simultaneously viewable through the wearable device.

19. The non-transitory computer-readable recording medium as claimed in claim 15, wherein the at least one pre-stored virtual entity comprises the virtual entity configured to be displayed based on detection of the predetermined physical entity and another virtual entity configured to be displayed based on detection of another predetermined physical entity, different from the predetermined physical entity.

20. The non-transitory computer-readable recording medium as claimed in claim 15, wherein the predefined position relative to the position of the detected movable physical entity is at least a portion of the movable physical entity, such that the virtual entity is displayed to be overlayed on the at least the portion of the movable physical entity.
