

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250278711

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Bedier; Osama et al.

PAYMENT TERMINAL SYSTEM AND METHOD OF USE

Abstract

A payment terminal, including: a display, an input device configured to generate input signals indicative of a user input, a payment instrument reader configured to receive payment instrument data from a financial payment instrument, a secure processor connected to the payment instrument reader, a main processor connected to the display, the main processor separate and distinct from the secure processor, a secure input processor connected to the input device and the secure processor, wherein the secure processor is operable between an unsecured mode, wherein the secure processor sends input coordinates based on the input signals received from the secure input processor to the main processor; and a secured mode, wherein the secure input processor ceases input coordinate forwarding to the main processor.

Inventors: Bedier; Osama (Palo Alto, CA), Tanaka; Ray (Palo Alto, CA), Hernandez; Robert (Palo Alto, CA)

Applicant: Poynt LLC (Tempe, AZ)

Family ID: 53638483

Appl. No.: 19/172333

Filed: April 07, 2025

Related U.S. Application Data

parent US continuation 18501715 20231103 parent-grant-document US 12271884 child US 19172333

parent US continuation 17962296 20221007 parent-grant-document US 11829980 child US 18501715

parent US continuation 17186331 20210226 parent-grant-document US 11468419 child US 17962296

parent US continuation 16700145 20191202 parent-grant-document US 10977637 child US 17186331

parent US continuation 16119072 20180831 parent-grant-document US 10528934 child US

16700145

parent US continuation 15635462 20170628 parent-grant-document US 10096012 child US 16119072

parent US continuation 14743356 20150618 parent-grant-document US 9721247 child US 15635462

parent US continuation 14526033 20141028 parent-grant-document US 9092766 child US 14743356

Publication Classification

Int. Cl.: **G06Q20/20** (20120101); **G06F3/041** (20060101); **G06F3/14** (20060101); **G06K7/00** (20060101); **G06Q20/04** (20120101); **G06Q20/08** (20120101); **G06Q20/10** (20120101); **G06Q20/38** (20120101); **G06Q20/40** (20120101); **G07G1/00** (20060101); **G07G1/01** (20060101)

U.S. Cl.:

CPC **G06Q20/204** (20130101); **G06K7/0004** (20130101); **G06Q20/047** (20200501); **G06Q20/085** (20130101); **G06Q20/102** (20130101); **G06Q20/108** (20130101); **G06Q20/20** (20130101); **G06Q20/209** (20130101); **G06Q20/382** (20130101); **G06Q20/401** (20130101); **G06Q20/4016** (20130101); **G07G1/0009** (20130101); **G07G1/0018** (20130101); **G07G1/01** (20130101); **G06F3/041** (20130101); **G06F3/1423** (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 18/501,715, filed Nov. 3, 2023, which is a continuation of U.S. patent application Ser. No. 17/962,296, filed Oct. 7, 2022, now issued as U.S. Pat. No. 11,829,980, which is a continuation of U.S. patent application Ser. No. 17/186,331, filed Feb. 26, 2021, now issued as U.S. Pat. No. 11,468,419, which is a continuation of U.S. patent application Ser. No. 16/700,145 filed Dec. 2, 2019, now issued as U.S. Pat. No. 10,977,637, which is a continuation of U.S. patent application Ser. No. 16/119,072, filed Aug. 31, 2018, now issued as U.S. Pat. No. 10,528,934, which is a continuation of U.S. patent application Ser. No. 15/635,462, filed Jun. 28, 2017, now issued as U.S. Pat. No. 10,096,012, which is a continuation of U.S. patent application Ser. No. 14/743,356, filed Jun. 18, 2015, now issued as U.S. Pat. No. 9,721,247, which is a continuation of U.S. patent application Ser. No. 14/526,033, filed Oct. 28, 2014, now issued as U.S. Pat. No. 9,092,766, all of which are incorporated in their entirety by this reference.

TECHNICAL FIELD

[0002] This invention relates generally to the payment instruments field, and more specifically to a new and useful payment terminal in the payment instruments field.

Description

BRIEF DESCRIPTION OF THE FIGURES

[0003] FIGS. 1A and 1B are schematic representations of the payment terminal in the secured and unsecured mode, respectively.

[0004] FIG. 2 is an isometric view of a variation of the payment terminal.

[0005] FIG. **3** is a power rail diagram of a specific example of the payment terminal.

[0006] FIG. **4** is a side view representation of a variation of the payment terminal resting on a support surface.

[0007] FIG. **5** is an exploded cutaway view of a variation of the payment terminal.

[0008] FIG. **6** is an exposed wireframe view of a variation of the payment terminal.

[0009] FIG. **7** is a schematic representation of a variation of the payment terminal interacting with peripheral devices, a remote system, and a user device with a wireless payment instrument.

[0010] FIG. **8** is a schematic representation of a variation of the payment terminal displaying a display element and interacting with a payment card.

[0011] FIG. **9** is a schematic representation of a variation of the payment terminal interpreting input coordinates in light of a coordinate map.

[0012] FIG. **10** is an end on view of a variation of the payment terminal including a printer, wherein the printer door is in an open configuration.

[0013] FIG. **11** is an isometric view of a variation of the payment terminal including a printer, wherein the printer door is in an open configuration.

[0014] FIG. **12** is an isometric view of a variation of the payment terminal including a printer interacting with printing substrate, wherein the printer door is in an open configuration.

[0015] FIG. **13** is a schematic representation of a variation of the payment terminal including a printer dispensing printed substrate.

[0016] FIG. **14** is a schematic representation of a variation of the payment terminal including a first and second camera, and a position sensor.

[0017] FIGS. **15-19** are schematic representations of different variations of the payment terminal.

[0018] FIGS. **20A** and **20B** are schematic representations of a variation of the payment terminal including a secure side that rotates about a rotational axis parallel to the junction in a first and second position, respectively.

[0019] FIGS. **21A** and **21B** are schematic representations of a variation of the payment terminal including a secure side that rotates about a rotational axis perpendicular to the junction in a first and second position, respectively.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0020] The following description of the preferred embodiments of the invention is not intended to limit the invention to these preferred embodiments, but rather to enable any person skilled in the art to make and use this invention.

[0021] As shown in FIGS. **1A** and **1B**, the payment terminal **1** includes a secure display **240**, a secure input device **230** associated with the secure display **240**, a secure processor **210** connected to the secure input device **230**, and a main processor **110**, distinct from the secure processor **210**, which is connected to the secure display **240**. The payment terminal **1** functions to provide standard-compliant payment processing (e.g., PCI-complaint payment processing) while enabling access to the merchant-level information. In particular, the payment terminal **1** can function to receive and process payment information in a standard-compliant manner. The payment terminal **1** can additionally function to collect payment information associated with orders or transactions for the merchant. The payment terminal **1** can additionally function as a platform through which third party applications can access and/or process the payment information. The payment terminal **1** can additionally function to automatically determine a type of payment used by a customer, and initiate different consumer payment flows based on the payment type. The payment terminal **1** can additionally function to integrate non-secure payment methods (e.g., cash, payment instruments **50**, rewards cards, etc.) into the same payment flow as secured payment methods. The payment terminal **1** can additionally function to interface with peripheral devices, such as legacy payment devices (e.g., pre-existing cash boxes, scanners, etc.), new payment devices, customer traffic trackers, or any other suitable peripheral device. The payment terminal **1** can additionally function to extract information from non-payment instruments, such as drivers licenses, QR codes, or any

other suitable information source. Examples of extracted information use include: unique identification of a user for a non-transaction use (e.g., identity verification during voting or by police, loyalty account identification, coupon retrieval or application, etc.), advertising campaign planning, customer purchase prediction, customer traffic prediction, employee performance tracking, employee acquisition planning, automated loan application, automated credit verification, automated settlement, automated accounting, automated or semi-automated tax preparation, automated inventory ordering, automated sale recommendations, or any other suitable transaction-related business functionality.

1. Potential Benefits

[0022] This payment terminal **1** can confer several benefits over conventional systems. First, the payment terminal **1** enables application interaction with transaction data generated by conventional payment terminals **600** (e.g., data manipulation) by introducing a main processor **110**. Second, the payment terminal **1** can alter the payment terminal user experience by introducing a customer-facing touchscreen display, such that the terminal **1** is no longer a merchant-only device.

Introducing a customer-facing touchscreen display can additionally confer the benefit of enabling a dynamically adjustable interface. Third, the payment terminal **1** enables both desktop and mobile use by introducing wireless payment information communication and by forming a handle **310** from its component parts.

2. Auxiliary Systems and Components

[0023] The payment terminal **1** can be used with a payment instrument **50** that functions to store financial transaction information that functions as a payment authenticating piece used to carry out a financial transaction. The payment instrument **50** can be a payment card, a token, or any other suitable payment instrument. The payment card can be a credit card, debit card, gift card, fund transfer card, or any other suitable financial transaction card. The token can be a secure element, such as a secure element chip or a virtual element, an integrated circuit (e.g., an IC card, such as an EMV card), or any other suitable token.

[0024] The payment terminal **1** can receive, process, and transmit sensitive information and non-sensitive information. Sensitive information can be a set of information required to complete a financial transaction, access a confidential account, or any other suitable information. Examples of sensitive information can include the full payment instrument identifier (e.g., full credit card number), a PIN number, a verification code, a social security number, or any other suitable sensitive information. Non-sensitive information can be any information that is not considered sensitive. Examples of non-sensitive information can include the cart items, the transaction amount, the transaction time, the customer name or other identifier, issuer identifier, last four digits of a payment card identifier, or any other suitable non-sensitive information.

[0025] Transmitting information can include sending information, broadcasting information, or otherwise communicating information. Sending information can include passing the information to a limited, predetermined set of endpoints (e.g., a single endpoint) in a targeted manner (e.g., through a targeted distribution channel), wherein endpoints outside of the predetermined set do not receive the information. Broadcasting information can include sending the information or an event associated with the information to multiple endpoints (e.g., all endpoints) through a common distribution channel, such as by putting the information on a common bus. Any endpoint connected to the common distribution channel can subsequently receive and/or the information from the source. However, information can be otherwise transmitted from sources to endpoints.

[0026] The payment terminal **1** can function to generate or otherwise process order information. Order information can include transaction information, cart or product information (e.g., product identifier, number of each product, etc.), customer identifiers, merchant identifiers, employee identifiers, order status (e.g., completed, open, paid but not picked up, etc.), or any other suitable order information. Transaction information can include a transaction identifier, transaction amount, merchant information, customer identifier, payment type, terminal identifier, and/or any other

suitable information about the transaction. The transaction identifier can be universally unique, unique to the merchant, unique to the customer identifier, generic, or be defined in any other suitable manner.

[0027] The payment terminal **1** can interact with a payment verification system (payment entity) that functions to verify payments or otherwise facilitate payment verification. The payment verification system can be the payment instrument **50** (e.g., the IC chip or secure element), a payment gateway, a payment processor, a financial service provider (e.g., a credit card provider, bank, etc.), or be any other suitable entity or system capable of verifying or facilitating verification of a payment.

[0028] As shown in FIG. **7**, the payment terminal **1** can interact with a remote system **40** which functions to store merchant information. The remote system can additionally or alternatively function to facilitate payment verification, wherein the remote system can send secured payment information to the payment verification system. The secured payment information can be received from the payment terminal **1**, or be automatically generated by the remote system. The merchant information can be sensitive information, non-sensitive information, or a combination thereof. The merchant information can include order information, transaction information, customer information, merchant account information, user account information for users associated with the merchant (e.g., employee accounts), permissions for user application access, permissions for application information access, permissions for order information access (e.g., authorization, authentication, etc.), terminal activation control, or any other suitable merchant information. The remote system can be a remote computing system or be any other suitable system. The payment terminal **1** can be connected to the remote system through a wired connection (e.g., LAN, cable, etc.) or wireless connection (e.g., WiFi, cellular, Bluetooth, etc.).

[0029] The payment terminal **1** can function to secure information. Securing information can include obfuscating information, encrypting information (e.g., using symmetric key encryption, public key encryption, etc.), or otherwise securing the information.

3. Payment Terminal Components and Variations

[0030] As shown in FIG. **8**, the secure display **240** (customer display, first display) of the payment terminal **1** functions to display order information, user interface elements, targets, windows for user input receipt, or any other suitable image to a user. In some variations of the payment terminal **1** (e.g., those with a single display), the secure display **240** can additionally function as the merchant display, wherein the processor controlling secure display operation (e.g., the main processor **110**) can dynamically shift secure display control between a first and second distinct kernel, switch operation modes between a secured and unsecured mode, or otherwise shift control of the secure display **240** based on user selections (e.g., a payment initiation selection) and/or information received at the secure processor **210** (e.g., payment instrument detection). The secure display **240** can be an LCD display, LED display, plasma display, OLED display, or any other suitable display. The secure display **240** can define a broad face having a longitudinal axis and lateral axis. The secure display **240** can be planar, curved, or have any other suitable broad face configuration. The secure display **240** can be substantially rectangular (e.g., square or with a length longer than a width), triangular, circular, or have any other suitable profile. The secure display **240** is preferably controlled by the main processor **110**, but can alternatively be controlled by a processor that is separate and distinct from the main processor **110**. The secure display **240** is preferably controlled by a secure display resource of the main processor **110**, but can alternatively be controlled by a payment resource or any other suitable resource of the main processor no. In a specific example, the secure display **240** can only be controlled by the main processor no. However, the secure display **240** can be controlled by any other suitable component. The secure display **240** can be connected to the main processor **110** by a wired connection, such as a display cable, display bus, male/female connection (e.g., PCI express, etc.), MIPI, or any other suitable wired connection, or a wireless connection, such as Bluetooth, BLE, NFC, or any other suitable wireless communication

system.

[0031] The secure input device **230** (customer input device, secure input, first input device) of the payment terminal **1** functions to receive a user input and convert the user input into input signals **231** (e.g., measurements) indicative of the user input. In some variations of the payment terminal **1** (e.g., those with a single display or input device), the secure input device **230** can additionally function as the merchant input device, wherein the processor controlling secure display operation (e.g., the secure input processor **220**) can dynamically switch operation modes or otherwise shift operation based on user selections (e.g., a payment initiation selection) and/or information received at the secure processor **210** (e.g., payment instrument detection).

[0032] The secure input device **230** is preferably associated with the secure display **240**, wherein the user input measurements generated by the secure input device **230** are translated into selection information based on the actual or anticipated image or interface (display element **242**) concurrently displayed on the secure display **240** during measurement receipt. However, the secure input device **230** can be associated with any other suitable display.

[0033] The secure input device **230** is preferably connected to the secure processing system **200**, more preferably the secure input processor **220** but alternatively the secure processor **210** or any other suitable processor. Alternatively or additionally, the secure input device **230** can be connected to the main processor **110**, main input processor **140**, or any other suitable processor. The secure input device **230** preferably only sends the measurements or other signals to the connected processor, but can alternatively or additionally send the measurements to any other suitable endpoint. The secure input device **230** can additionally be controlled by the connected processor, wherein the connected processor can control power provision to the secure input device **230**, control or instruct the secure input device **230** to introduce signal noise into the measurement, or control or instruct the secure input device **230** to operate in any other suitable manner. The secure input device **230** can receive power directly from a power source **600**, such as a charging port **630** or a power storage unit (e.g., battery), receive power indirectly from the power source **600** through the connected processor, or be powered in any suitable manner. The secure input device **230** can be connected to the secure processor **210** by a wired connection, such as a cable, bus, male/female connection, MIPI, or any other suitable wired connection, or a wireless connection, such as Bluetooth, BLE, NFC, or any other suitable wireless communication system.

[0034] The secure input device **230** is preferably operable in a single mode (e.g., a secured mode), but can alternatively operate between a secured mode and an unsecured mode, or between any other suitable set of modes. In the secured mode, the secure input device **230** can secure (e.g., obfuscate) the measurements sent to the secure input processor **220**, secure processor **210**, other component of the secure processing system **200**, main processor **110**, or any other suitable destination. In the unsecured mode, the secure input device **230** can send unsecured measurements to the secure input processor **220**, secure processor **210**, other component of the secure processing system **200**, main processor no, or any other suitable destination. The secure input device operation mode can be controlled by the secure input processor **220**, a separate and distinct processor or driver, or by any other suitable control system. The secure input device operation mode can be the same as (e.g., reflect) the connected processor operation mode, or can be independent of the connected processor operation mode.

[0035] The secure input device **230** can be a touchscreen **232**, a pointing device, a keyboard, a sound input (e.g., a microphone), or any other suitable input device. The secure touchscreen can function to enable a user to interact directly with what is displayed on the secure display **240**. The pointing device, keyboard, or other input devices can enable the user to interact indirectly with what is displayed on the secure display **240**. The secure touchscreen is preferably overlaid over the secure display **240**, such that touch coordinates registered by the secure touchscreen can be mapped to pixel sets, digital interaction elements, or other virtual targets displayed on the secure display **240**. The secure touchscreen preferably has substantially the same dimensions as the secure display

240, but can alternatively be larger (e.g., extend over all or a portion of the display bezel) or smaller. The secure touchscreen preferably has a similar pixel density as the secure display **240**, but can alternatively be denser (e.g., 3 times denser) or sparser. The secure touchscreen is preferably substantially aligned with the secure display **240**, such that the touchscreen longitudinal axis and lateral axis are substantially aligned with the secure display **240** longitudinal axis and lateral axis. However, the secure touchscreen can be misaligned with the secure display **240** (e.g., with an offset central normal axis), or aligned in any other suitable orientation. The secure touchscreen can include a broad face, wherein the secure touchscreen broad face is substantially parallel the secure display broad face. Alternatively, the secure touchscreen can be arranged in any suitable configuration relative to the broad face.

[0036] The touchscreen can be a resistive touchscreen, surface acoustic wave touchscreen, capacitive touchscreen, infrared grid touchscreen, infrared acrylic projection touchscreen, optical imaging touchscreen, dispersive signal technology touchscreen, acoustic pulse recognition touchscreen, or utilize any other suitable touchscreen technology. Examples of capacitive touchscreens include a surface capacitance touchscreen, projected capacitance touchscreen, such as mutual capacitance touchscreen or self-capacitance touchscreen, or any other suitable capacitive touchscreen. In a specific example, the touchscreen is a PIN transaction security (PTS)-compliant and/or PIN encryption device (PED)-compliant touchscreen. The measurements or signals output by the touchscreen are preferably touch measurements, and can include the capacitance change for each of a plurality of touchscreen points, capacitor, or any other suitable measurement location. However, the measurements or signals can be determined from the position of a switch, a potential voltage magnitude, a change in the voltage magnitude, the current magnitude, the current frequency, or from any other suitable signal.

[0037] The touchscreen can include one or more layers. In one variation, the touchscreen includes a translucent top layer including a metallic coating along a first surface, an adhesive spacer proximal the first surface, a translucent bottom layer including metallic coating along a second surface proximal the first surface, and a translucent mounting layer. The touchscreen is preferably substantially transparent, but can alternatively have any other suitable translucidity. The top and bottom layers can be formed from the same materials or different materials. The top and/or bottom layers can be formed from polymer (e.g., polyester, PEG, etc.), glass, or any other suitable substrate material. The touchscreen can additionally include a polarizing filter that functions to limit the viewing angle, coupled along a second surface of the top layer opposing the first surface, the first surface of the top layer, the first or second surface of the bottom layer, along the broad face of the display proximal the touchscreen, or along any other suitable surface. The touchscreen can include a first broad face extending over the respective display broad face, more preferably proximal the display active surface but alternatively along any other suitable portion of the display.

[0038] The secure processor **210** of the payment terminal **1** functions to perform a predefined set of functionalities. The secure processor **210** can additionally function to determine whether received information includes sensitive information, separate the sensitive information from non-sensitive information, secure sensitive information, or otherwise process received information. Application interaction (e.g., reading, writing, editing, and/or deletion) from all or some of the memory and processes connected to or supported by the secure processor **210** is preferably limited to a predetermined set of main processor modules (e.g., standard-certified or compliant modules, such as the payment module), but can alternatively be entirely prevented or otherwise limited. The secure processor **210** can be dynamically updated (e.g., wherein the secure processor **210** receives encrypted update information from the main processor **110**) or be otherwise adjusted in any other suitable manner. The secure processor **210** is preferably separate (e.g., forming or viewed as a unit apart or by itself) and distinct (e.g., recognizably different in nature) from the main processor **110**, but can alternatively be separate from the main processor **110**, distinct from the main processor **110**, be a portion (e.g., a core) of the main processor **110**, be a sub-processing module of a

processor that also supports the main processor **110**, or have any other suitable relation to the main processor **110**. The secure processor **210** can be supported on a different chipset, different circuit board, different core, different kernel, different thread, or otherwise separated and/or distinguished from the main processor **110**. The secure processor **210** can be standard-compliant, standard-certified, standard-signed, otherwise compliant with a payment industry security standard, or be non-compliant with industry standards. Examples of a payment card industry standard includes PCI DSS (Payment Card Industry Data Security Standard), PCI P2PE, PTS, or EMVCo, but any other suitable payment industry security standard can be used. The secure processor **210** can include or be associated with secure memory (e.g., volatile memory, non-volatile memory, etc.), wherein the secure memory can be separate and distinct, integrated with, or be the same as the main memory. The secure memory can store encryption keys, coordinate maps (e.g., for input coordinate interpretation when the terminal is in the secured mode), firmware, certificates, or any other suitable information. The secure memory can be read only, write only, read/write, or have any other suitable functionality.

[0039] The secure processor **210** can be connected to the secure input device **230**, wherein the secure processor **210** can receive information from the secure input device **230**. In one variation, the secure processor **210** can be indirectly connected to the secure input device **230** through an intermediary processor, such as a secure input processor **220** (e.g., secure touch processor). In this variation, the received information can include a set of input coordinates (e.g., touch coordinates, selection coordinates). The set of input coordinates can be determined from the measurements (e.g., input signals) by the intermediary processor, or otherwise determined. The set of input coordinates can be secured or unsecured (e.g., by the intermediary processor or secure input device **230**). However, the received information can additionally or alternatively include any other suitable information. In this variation, the secure processor **210** can be selectively operatively connected to the secure input device **230** by the intermediary processor or continuously operatively connected to the secure input device **230** by the intermediary processor. The secure processor **210** can receive secure input device information (e.g., input signals, input coordinates, etc.) from the intermediary processor when operatively connected to the secure input device **230**, and cannot receive secure input device information from the intermediary processor when not operatively connected to the secure input device **230**. The secure processor **210** can be prevented from receiving secure input device information when not operatively connected to the secure input device **230**, or simply not sent secure input device information by the intermediary processor. The secure processor **210** can be virtually prevented from receiving the secure input device information, such as by implementing a firewall or virtually disconnecting the secure processor **210** from the secure input device **230**, physically prevented from receiving the secure input device information, such as by disconnecting the secure processor **210** from the secure input device **230** (e.g., by changing the state of a switch), or otherwise prevented from receiving secure input device information.

[0040] In a second variation, the secure processor **210** can be directly connected to the secure input device **230**. In this variation, the received information can include all or a portion of the measurements from the secure input device **230**. However, the secure processor **210** can be otherwise connected to and receive information from the secure input device **230**.

[0041] The secure processor **210** can additionally be connected to the payment hardware **250**. The secure processor **210** can be directly connected to the payment hardware **250**, indirectly connected to the payment hardware **250** (e.g., through a secure financial information processor, in a similar manner to indirect secure processor connection with the secure input device **230**, as discussed above), or otherwise connected to the payment hardware **250**. When the terminal **1** includes a secure financial transaction processor, the secure financial information processor can receive information (e.g., payment instrument data or information, identification information, etc.) from the payment hardware **250**, determine whether the information is sensitive, and send the information to the secure processor **210** in response to the financial information being sensitive information, and

to the main processor **110** in response to the financial information being non-sensitive information. Alternatively, these functionalities can be performed by the secure processor. The secure financial transaction processor can be operable only in the secured mode, or can be operable between a secured mode and an unsecured mode, or operate between any suitable set of operation modes. However, the secure financial transaction processor can operate in any other suitable manner. The secure financial transaction processor can be separate and/or distinct from the secure processor **210**, integrated with the secure processor **210**, integrated with the main processor **110**, or otherwise configured.

[0042] The secure processor **210** can be operatively connected to the payment hardware **250**, or be otherwise connected. When the secure processor **210** is operatively connected to the payment hardware **250**, the secure processor **210** can receive all or a portion of the information determined by the payment hardware **250**. The secure processor **210** can additionally or alternatively control payment hardware operation when operatively connected to the payment hardware **250**. The secure processor **210** is preferably continuously operatively connected to the payment hardware **250**, but can alternatively be selectively operatively connected to the payment hardware **250** (e.g., by an intermediary payment hardware **250** processor), only connected to the payment hardware **250** by a power connection, or otherwise connected to the payment hardware **250**.

[0043] The secure processor **210** can additionally be connected to the main processor **110**. The secure processor **210** can be directly connected to the main processor **110**, indirectly connected to the main processor **110** (e.g., in a similar manner to indirect secure processor connection with the secure input device **230**, as discussed above), or otherwise connected to the main processor **110**. The secure processor **210** can be operatively connected to the main processor **110**, or be otherwise connected. When the secure processor **210** is operatively connected to the main processor **110**, the secure processor **210** can only send information **202** (e.g., data) to the main processor **110**.

Alternatively, the secure processor **210** can only receive information from the main processor **110** when operatively connected. Alternatively, the secure processor **210** can both send and receive information to and from the main processor no when operatively connected. Alternatively, the secure processor **210** can be limited to only receiving information from the main processor **110** when operatively connected to the main processor no. The secure processor **210** is preferably continuously operatively connected to the main processor **110**, but can alternatively be selectively operatively connected to the main processor **110**, only connected to the main processor **110** by a power connection, or otherwise connected to the main processor **110**.

[0044] The secure processor **210** is preferably connected to the main processor no by a single connection **800**, but can alternatively be connected to the main processor **110** by multiple connections. The connection Boo preferably includes both power and data connections, but can alternatively only include a power or data connection. The connection can be a two-way connection (e.g., send data to and from both endpoints), or be a one-way connection (single-direction connection, e.g., only transmit data in one direction from a source to a destination), or be any other suitable type of connection. The connection Boo is preferably a physical connection, such as a wire, bus, or board-to-board connection, but can alternatively be a wireless connection, such as a short-range data connection (e.g., NFC, Bluetooth, BLE, RF, IR, etc.) or long-range data connection (e.g., WiFi, Zigbee, Z-wave, etc.), or be any other suitable connection. In a specific example, the connection can be a USB connector, FireWire connector, or any other suitable wired connector. The connection Boo can additionally include a hardware security module, be formed from optical fiber, be configured to sever in response to physical tampering, or be secured in any other suitable manner. In one variation of the payment terminal **1**, the secure processor **210** only outputs information to the main processor **110**, and otherwise only received inputs from other terminal components. In a second variation of the payment terminal **1**, the secure processor **210** can output information (e.g., control information, etc.) to other terminal components. The connector preferably extends across the junction, but can alternatively extend along any other suitable portion

of the terminal **1**.

[0045] The secure processor **210** preferably operates in a single mode, more preferably the secured mode, but can alternatively operate between a secured mode and an unsecured mode, or between any other suitable set of modes. In the secured mode, the secure processor **210** can secure (e.g., encrypt, obfuscate, etc.) all information output by the secure processor **210** (output information), a subset of the output information (e.g., only information determined to be secure information, such as information satisfying a condition indicative of sensitive information, etc.), or any other suitable portion of the output information. In the unsecured mode, the secure processor **210** can output (e.g., send, transmit, broadcast, etc.) unsecured output information. When the secure processor **210** is operable between a set of operation modes, the secure processor operation mode is preferably controlled by the secure processor **210** but can alternatively be controlled by the main processor **110** or by any other suitable control system.

[0046] The secure processor **210** is preferably arranged proximal the secure display **240**, but can alternatively be arranged proximal the main display **120**, proximal the secure input device **230**, proximal the main input device **160**, or arranged in any other suitable location. The secure processor **210** is preferably arranged with a broad face substantially parallel the respective display broad face, but can alternatively be arranged in any suitable orientation. The secure processor **210** can be substantially centered with the respective display, offset from the respective display, be arranged proximal an end of the respective display (e.g., along the display longitudinal axis), or otherwise arranged.

[0047] The secure input processor **220** (first input processor) of the payment terminal **1** functions to interpret measurements determined at the secure input device **230** into secure reference coordinates. The reference coordinates **221** can be input coordinates (e.g., touchscreen coordinates), display coordinates, or any other suitable reference point that can subsequently be used to determine a user selection with reference to the image or interface concurrently displayed on the secure display **240** during measurement registration. In a specific example, the user selection can be determined based on a coordinate map **244** associated with the concurrently displayed image or interface, as shown in FIG. **9**. However, the user selection can be determined in any other suitable manner. The secure input processor **220** can be connected to the secure input device **230**, wherein the secure input processor **220** can receive information from the secure input device **230** only (e.g., through a one-way connection), both send and receive information to and from the secure input device **230** (e.g., control information, etc. through a two-way connection), send information to the secure input device **230** only, or be otherwise operatively connected to the secure input device **230**. The secure input processor **220** can be connected to the secure input device **230** by a wired connection, such as a cable, bus, male/female connection, or any other suitable wired connection, or a wireless connection, such as Bluetooth, BLE, NFC, or any other suitable wireless communication system. The secure input processor **220** can be standard-compliant, standard-certified, standard-signed, otherwise compliant with a payment industry security standard, or be non-compliant with industry standards.

[0048] In one variation, the secure input processor **220** is a secure touch processor that functions to convert touch signals (e.g., changes in capacitance) to the reference coordinates **221**. In another variation, the secure input processor **220** is a secure device processor that functions to determine a virtual pointer position relative to the image concurrently displayed on the secure display **240**. However, the secure input processor **220** can be any other suitable input processor.

[0049] The secure input processor **220** can additionally function to secure the reference coordinates **221**, or any other suitable information output by the secure input processor **220**. The secure input processor **220** can secure all information output by the secure input processor **220**, secure output information only when operating in the secure mode, or secure information based on any other suitable operation parameter.

[0050] The secure input processor **220** can additionally function to selectively determine the

endpoint for the reference coordinates **221**. The secure input processor **220** is preferably operable between a secured and an unsecured mode, but can alternatively be operable only in the secured mode, in the unsecured mode, or between any suitable set of operation modes. The secure input processor operation mode is preferably independent of the secure processor **210** (e.g., even when the secure input processor **220** is an integral module of the secure processor **210**), but can alternatively be the same as the secure processor operation mode. The secure input processor operation mode is preferably determined (and/or controlled) by the secure input processor itself, but can alternatively be determined by the secure processor **210**, the main processor **110**, or any other suitable component.

[0051] In the secured mode, the secure input processor **220** is preferably operatively connected to and sends reference coordinates to the secure processor **210**, but can alternatively send the reference coordinates **221** to any other suitable endpoint. In a first variation, the secure input processor **220** operating in the secured mode broadcasts the reference coordinates **221** to all connected endpoints. In this variation, the secure input processor **220** can encrypt the reference coordinates **221** prior to broadcasting, wherein only endpoints with the decryption key (e.g., the secure processor **210**) can read the information. In a second variation, the secure input processor **220** operating in the secured mode only sends the reference points to the endpoints that are operatively connected to the secure input processor **220**. In this variation, the secure input processor **220** can selectively operatively connect or disconnect different endpoints, such that only the secured processor can be operatively connected to the secure input processor **220** operating in the unsecured mode, both the secure and main processor **110** can be concurrently operatively connected to the secure input processor **220** operating in the unsecured mode, or any suitable endpoint can be operatively connected to the secure input processor **220** operating in the secured mode. In a specific example of the payment terminal **1**, the secure input processor **220**, operating in the secured mode, only sends the reference coordinates **221** to the secure processor **210**, and does not send the reference coordinates **221** to the main processor **110**. In this example, the secure processor **210** can be operatively connected to the secure input processor **220** and the main processor **110** can be operatively disconnected from the secure input processor **220**. However, the secure input processor **220** can operate in any suitable manner while in the secured mode.

[0052] In the unsecured mode, the secure input processor **220** is preferably operatively connected to and sends reference coordinates to the main processor **110**, but can alternatively send the reference coordinates **221** to any other suitable endpoint. In a first variation, the secure input processor **220** operating in the unsecured mode broadcasts the reference coordinates **221** to all connected endpoints. In a second variation, the secure input processor **220** operating in the unsecured mode only sends the reference points to the endpoints that are operatively connected to the secure input processor **220**. In the second variation, only the main processor **110** can be operatively connected to the secure input processor **220** operating in the unsecured mode, both the secure and main processor **110** can be concurrently operatively connected to the secure input processor **220** operating in the unsecured mode, or any suitable endpoint can be operatively connected to the secure input processor **220** operating in the unsecured mode. In a specific example of the payment terminal **1**, the secure input processor **220**, operating in the unsecured mode, only sends the reference coordinates **221** to the main processor **110**, and does not send the reference coordinates **221** to the secure processor **210**. In this example, the main processor **110** can be operatively connected to the secure input processor **220** and the secure processor **210** can be operatively disconnected from the secure input processor **220**. However, the secure input processor **220** can operate in any suitable manner while in the unsecured mode.

[0053] The secure input processor **220** or secure processor **210** is preferably operable between the secured and unsecured modes in response to a secure event and/or an unsecure event. The secure input processor **220** can operate in the secured mode in response to detection of the secure event or the absence of the unsecure event, and can operate in the unsecured mode in response to detection

of the unsecure event or the absence of the secure event. The secure event can include payment initiation notification **203** receipt, payment initiation notification activation (e.g., received from the main processor **110**), secure information collection notification (e.g., received from the secure processor **210** in response to detection of secure information from the payment hardware **250** or determination that secure information is to be collected), notification that a secure user interaction flow is being initiated (e.g., notification that a payment flow has been initiated), request for a PIN entry (e.g., determined based on the payment instrument or based on the payment amount, wherein the payment amount exceeds a threshold amount), or any other suitable event indicative of a need for the secure processor **210** to receive reference coordinates. The unsecure event can include payment initiation notification deactivation, notification that a secure user interaction flow is being ended (e.g., notification that a payment flow has been ended), or any other suitable event indicative of a need for the main processor **110** to receive reference coordinates, or the end of the need for the secure processor **210** to receive reference coordinates. The secure input processor **220** or secure processor **210** can operate in the unsecured mode by default, and switch to secure mode operation in response to determination of the secure event. Alternatively, the secure input processor **220** or secure processor **210** can operate in the secured mode by default, and switch to unsecured mode operation in response to determination of the unsecure event.

[0054] The secure input processor **220** is preferably a separate and distinct processor from the secure processor **210**, but can alternatively be integrated into the same circuit board, chipset, kernel, thread, or be a module of the secure processor **210**. However, the secure input processor **220** can be otherwise configured. In a first variation, the secure input processor **220** can be only connected to the secure processor **210**, wherein the secure processor is operable between the secured and unsecured mode and selectively forwards reference coordinates to the main processor. In a second variation wherein the secure input processor **220** is separate and distinct from the secure processor **210**, the secure input processor **220** can be connected to both the main processor **110** and the secure processor **210**. The secure input processor **220** can be only operatively connected to the secure processor **210** in the secure mode, and only operatively connected to the main processor **110** in the unsecured mode, but can be otherwise connected. The secure input processor **220** can be connected to the secure processor **210** by a wired connection, such as a cable, bus, male/female connection, or any other suitable wired connection, or a wireless connection, such as Bluetooth, BLE, NFC, or any other suitable wireless communication system. In a third variation wherein the secure input processor **220** is integrated with the secure processor **210**, the secure input processor **220** can be always operatively connected to the secure processor **210**, wherein the secure processor **210** can be selectively operatively connected to the main processor **110** between the secured and unsecured modes, or selectively secure information sent to the main processor **110** between the secured and unsecured modes. In a fourth variation, the secure input processor **220** can be a separate and distinct processor from the secure processor **210**, but be only connected to the secure processor **210**, wherein the secure processor **210** can determine and/or selectively secure input device information (e.g., reference coordinates) to pass to the main processor **110**. In this variation, the terminal **1** can include a secure processing system **200** that includes the secure processor **210**, secure input processor **220**, and/or secure financial transaction processor. However, the secure input processor **220** can be connected to processing endpoints and operate in any other suitable manner.

[0055] The secure input processor **220** is preferably arranged proximal the secure processor **210**, but can alternatively be arranged proximal the secure display **240**, main display **120**, secure input device **230**, main input device **160**, or arranged in any other suitable location. The secure input processor **220** is preferably arranged with a broad face substantially coplanar with a secure processor broad face, but can alternatively be arranged with the broad face parallel the secure processor **210** broad face, parallel the respective display broad face, or arranged in any suitable orientation.

[0056] The main processor **110** of the payment terminal **1** functions as the main computing system of the payment terminal **1**. The main processor **110** can be a CPU, set of CPUs or any other suitable processing system. The main processor **110** is preferably separate and distinct from the secure processor **210** or any other suitable component of the secure processing system **200**, but can alternatively be integrated with the secure processor **210** or secure processing system **200**. The main processor **110** can include or be associated with main memory (e.g., volatile memory, non-volatile memory, etc.), wherein the main memory can be separate and distinct, integrated with, or be the same as the secure memory. The main memory can function to store and/or support applications, display elements, transaction or order information, permissions, or any other suitable piece of information. The main memory can be read only, write only, read/write, or have any other suitable functionality.

[0057] The main processor **110** is preferably arranged proximal the main display **120**, but can alternatively be arranged proximal the secure display **240**, proximal the main input device **160**, proximal the secure input device **230**, or arranged in any other suitable location. The main processor **110** is preferably arranged with a broad face substantially parallel the display broad face, but can alternatively be arranged in any suitable orientation. The main processor **110** is preferably arranged proximal an end of the respective display (e.g., along the display longitudinal axis), but can alternatively be substantially centered with the respective display or otherwise arranged. In one variation, the main processor **110** can be arranged proximal the connector of the main display, proximal the junction, or arranged in any other suitable location.

[0058] The main processor **110** of the payment terminal **1** functions to control the secure display **240**. In one example of main processor secure display control, the main processor **110** can control which images or interfaces are displayed on the secure display **240**. In a second example of main processor secure device control, the main processor **110** can polarize or otherwise limit the visual angle of the images displayed on the device during sensitive information entry or display, wherein sensitive information entry or display can be associated with a predetermined subset of images (e.g., PIN number entry, social security number display, cart item list, signature screen, welcome screen, etc.). A distinct resource on the main processor **110** preferably controls the secure display **240**, but the secure display **240** can be controlled by any other suitable portion of the main processor **110**. The distinct resource can be secured or unsecured, and can be standard-compliant, standard-certified, standard-signed, otherwise compliant with a payment industry security standard, or be non-compliant with industry standards.

[0059] The main processor **110** can additionally or alternatively function to receive information from the secure input processor **220**, and process the reference coordinates **221** into user interface elements, alphanumeric characters, or other functional information **211**. The main processor **110** preferably processes the reference coordinates **221** into functional information using a coordinate map **244** associated with the image displayed concurrently with user input receipt (e.g., the image that was displayed at the timestamp associated with the measurements), but can alternatively process the reference coordinates **221** in any other suitable manner.

[0060] The main processor **110** can additionally or alternatively function to control a main display **120**, a main input device **160**, a printer **500**, a power source **400**, one or more wireless communication modules **190**, one or more sensors **400**, indicators, memory, and/or any other suitable component. The main processor **110** is preferably connected, more preferably continuously or selectively operatively connected to the respective component, but can alternatively otherwise control the component.

[0061] The main processor **110** can additionally or alternatively function to store and execute applications (e.g., native applications, browser applications, etc.), wherein the applications can substantially freely read, write, edit, and/or delete from all or some of the memory and processes connected to or supported by the main processor **110**. The main processor **110** can additionally or alternatively function to process payments, generate payment initiation notifications, and/or control

the payment flow. The main processor no can additionally or alternatively function to receive secured information from the secure processor **210**, and send the secured information to the remote system **40** and/or payment gateway. The main processor no can additionally or alternatively function to receive, store, and/or communicate unsecured information from the secure processor **210** to a remote system. The main processor **110** can additionally function to generate or determine process flow events, such as payment initiation events, transaction completion events, or any other suitable event, and can additionally extract non-sensitive information from the events. The main processor **110** can additionally function to interface (e.g., send or receive information) with a remote system.

[0062] The payment terminal **1** can additionally include a main display **120** (second display) that functions to display application data (e.g., third party application data, native application data, etc.), browser data, or any other suitable data. The main display **120** is preferably a merchant display (e.g., intended for the merchant to view and interact with information), but can alternatively be used by the customer. The displayed information is preferably non-sensitive data, but can alternatively or additionally be sensitive data. The main display **120** can be a LCD display, LED display, plasma display, OLED display, or any other suitable display. The main display **120** can define a broad face having a longitudinal axis and lateral axis. The main display **120** can be planar, curved, or have any other suitable broad face configuration. The main display **120** can be substantially rectangular (e.g., square or with a length longer than a width), triangular, circular, or have any other suitable profile. The main display **120** is preferably larger than the secure display **240**, but can alternatively be substantially the same size or smaller. In a specific variation, the main display **120** is approximately three times the size of the secure display **240**.

[0063] The main display **120** is preferably connected to the main processor **110**, but can alternatively be connected to any other suitable component. The main display **120** is preferably controlled by only the main processor no (i.e., operatively connected to the main processor no), but can alternatively or additionally be controlled by any other suitable component. The main display **120** can be connected to the main processor **110** by a wired connection, such as a display cable, display bus, male/female connection (e.g., PCI express, etc.), or any other suitable wired connection, or a wireless connection, such as Bluetooth, BLE, NFC, or any other suitable wireless communication system.

[0064] The main display **120** is preferably mounted to the secure display **240**, but can alternatively be separate and distinct from the secure display **240** (e.g., located on a separate system). In a first variation, the main display **120** is statically mounted to the secure display **240**. The main display **120** is preferably statically mounted to the secure display **240** at an obtuse angle (e.g., at 120°, 150°, etc.) but can alternatively be mounted to the secure display **240** at an acute angle (e.g., 0°, 30°, 45°, 60°), a normal angle (e.g., 90°), mounted coplanar to the secure display **240**, or mounted to the secure display **240** at any other suitable orientation. The main display **120** is preferably mounted to the secure display **240** with the respective display active surfaces oriented away from (e.g., distal) each other, but can alternatively be mounted to the secure display **240** with the respective active surfaces toward (proximal) each other, with the respective active surfaces directed in the same direction, or arranged in any other suitable configuration. The main display **120** and secure display **240** are preferably coupled with the respective orientation vectors **80** directed away from each other (e.g., in a mutually opposing orientation, separated by the coupling angle, etc.), but can alternatively be coupled with the respective orientation vectors directed toward each other, arranged in parallel and directed in the same direction, or arranged in any other suitable orientation. A first edge of the main display **120** is preferably joined to a first edge of the secure display **240**, but the secure display **240** can alternatively be joined to the body of the main display **120** (e.g., to the back face opposing the active surface **122**, between a first and second opposing edge) or the main display **120** can alternatively be joined to the body of the secure display **240**. However, the main display **120** and secure display **240** can be joined along any other suitable portion of the

respective displays.

[0065] In a first specific example, a lateral edge of the main display **120** can be joined to a longitudinal edge of the secure display **240**. In this example, the orientation vector of the main display **120** can be substantially parallel the respective longitudinal edge, and the orientation vector of the secure display **240** can be substantially parallel the respective lateral edge. In a second specific example, a lateral edge of the secure display **240** can be joined to a longitudinal edge of the main display **120**. In this example, the orientation vector of the secure display **240** can be substantially parallel the respective longitudinal edge, and the orientation vector of the main display **120** can be substantially parallel the respective lateral edge. However, the orientation vectors can be otherwise configured. In a third specific example, a longitudinal edge of the main display **120** can be joined to a longitudinal edge of the secure display **240**. In this example, the orientation vectors of the main display **120** and secure display **240** can be substantially parallel the respective longitudinal edges. In a fourth specific example, a longitudinal edge of the main display **120** can be joined to a longitudinal edge of the secure display **240**, wherein the orientation vectors of the main display **120** and secure display **240** can be substantially perpendicular the respective longitudinal edges. In a fifth specific example, a lateral edge of the main display **120** can be joined to a lateral edge of the secure display **240**, wherein the orientation vectors of the main display **120** and secure display **240** can be substantially perpendicular the respective lateral edges.

[0066] In a second variation, the secure display **240** can be translationally mounted to the main display **120**. The secure display **240** preferably rotates relative to the main display **120** about a rotational axis, but can alternatively slide laterally or longitudinally along a translational axis, or translate relative to the main display **120** in any other suitable manner. The rotational axis is preferably parallel to the junction **320** between the secure display **240** and the main display **120** (e.g., extend along the junction **320**, be offset from the junction **320**), as shown in FIGS. **20A** and **20B**, but can alternatively be perpendicular to the junction **320** between the main display **120** and secure display **240**, as shown in FIGS. **21A** and **21B**, or be positioned at any suitable angle relative to the junction **320**.

[0067] The payment terminal **1** can additionally include a main input device **160** (second input device), which functions to receive a user input and convert the user input into measurements indicative of the user input. The main input device **160** is preferably associated with the main display **120**, wherein the user input measurements generated by the main input device **160** are translated into selection information based on the actual or anticipated image or interface concurrently displayed on the main display **120** during measurement receipt. However, the main input device **160** can be associated with any other suitable display. The main input device **160** is preferably substantially similar to the secure input device **230**, but can alternatively be any other suitable input device, as disclosed above.

[0068] The main input device **160** is preferably connected to the main processor **110**, but can alternatively be connected to a main input processor **140** (which, in turn, can be connected to the main processor **110**), the secure processor **210**, the secure input processor **220**, or any other suitable processor. The main input device **160** preferably only sends the measurements or other signals to the connected processor, but can alternatively or additionally send the measurements to any other suitable endpoint. The main input device **160** can additionally be controlled by the connected processor, wherein the connected processor can control power provision to the main input device **160**, control or instruct the main input device **160** to introduce signal noise into the measurement, or control or instruct the main input device **160** to operate in any other suitable manner. The main input device **160** can receive power directly from a power source **600**, such as a charging port **630** or a power storage unit (e.g., battery), receive power indirectly from the power source **600** through the connected processor, or be powered in any suitable manner. The main input device **160** can be connected to the respective processor by a wired connection, such as a cable, bus, male/female connection, or any other suitable wired connection, or a wireless connection, such as Bluetooth,

BLE, NFC, or any other suitable wireless communication system.

[0069] The main input device **160** is preferably operable in a single mode (e.g., an unsecured mode), but can alternatively be operable between a secured mode and an unsecured mode, or between any other suitable a set of modes. In one variation of the payment terminal **1**, the main input device **160** can register measurements in the unsecured mode, and can be turned off (e.g., disconnected from power), switched into a standby mode, or otherwise prevented from registering measurements in the secured mode.

[0070] The main input device **160** can be a touchscreen, a pointing device, a keyboard, a sound input (e.g., a microphone), or any other suitable input device. The main touchscreen **162** can function to enable a user to interact directly with what is displayed on the main display **120**. The pointing device, keyboard, or other input devices can enable the user to interact indirectly with what is displayed on the main display **120**. The main touchscreen is preferably overlaid over the main display **120**, such that touch coordinates determined by the main touchscreen can be mapped to pixel sets, digital interaction elements, or other virtual targets displayed on the main display **120**. However, the main touchscreen can be arranged in any other suitable position relative to the main display **120**. The main touchscreen preferably has substantially the same dimensions as the main display **120**, but can alternatively be larger (e.g., extend over all or a portion of the display bezel) or smaller. The main touchscreen is preferably substantially aligned with the main display **120**, such that the main touchscreen longitudinal axis and lateral axis are substantially aligned with the main display **120** longitudinal axis and lateral axis. However, the main touchscreen can be misaligned with the main display **120** (e.g., with an offset central normal axis), or aligned in any other suitable orientation. The main touchscreen can include a broad face, wherein the main touchscreen broad face is substantially parallel the main display broad face. Alternatively, the main touchscreen can be arranged in any suitable configuration relative to the broad face. The main touchscreen is preferably substantially similar to the secure touchscreen, but can alternatively be any other suitable touchscreen, as disclosed above.

[0071] The payment terminal **1** can additionally include a main input processor **140** (second input processor) that functions to interpret measurements registered by the main input device **160** into main reference coordinates. The reference coordinates **221** can be input coordinates (e.g., touchscreen coordinates), display coordinates, or any other suitable reference point that can subsequently be used to determine a user selection with reference to the image or interface concurrently displayed on the main display **120** during measurement registration. In a specific example, the user selection can be determined based on a coordinate map **244** associated with the concurrently displayed image or interface. However, the user selection can be determined in any other suitable manner.

[0072] The main input processor **140** can be connected to the main input device **160**, wherein the main input processor **140** can receive information from the main input device **160** only (e.g., through a one-way connection), both send and receive information to and from the main input device **160** (e.g., control information, etc. through a two-way connection), send information to the main input device **160** only, or be otherwise operatively connected to the main input device **160**. The main input processor **140** can be connected to the main input device **160** by a wired connection, such as a cable, bus, male/female connection, or any other suitable wired connection, or a wireless connection, such as Bluetooth, BLE, NFC, or any other suitable wireless communication system.

[0073] In one variation, the main input processor **140** is a main touch processor that functions to convert touch signals (e.g., changes in capacitance) to the reference coordinates **221**. In another variation, the main input processor **140** is a main device processor that functions to determine a virtual pointer position relative to the image concurrently displayed on the main display **120**. However, the main input processor **140** can be any other suitable input processor.

[0074] The main input processor **140** is preferably operable in a single mode (e.g., an unsecured

mode), but can alternatively be operable between an unsecured and secured mode, or between any other suitable set of modes. In the unsecured mode, the main input processor **140** preferably sends unsecured main reference coordinates, determined from the main input device **160** measurements, to the main processor **110**. However, the main input processor **140** can send the main reference coordinates to the secure processor **210** or to any other suitable endpoint in the unsecured mode. In the secured mode, the main input processor **140** can be turned off, switched to a standby mode, or otherwise prevented from processing (e.g., interpreting) measurements in the secured mode. The main input processor **140** preferably operates in the secured mode in response to secure processor operation in the secured mode, but can alternatively operate in the secured mode independently of secure processor operation, such as in response to payment initiation determination, payment instrument **50** coupling to the payment hardware **250**, or in response to any other suitable event.

[0075] The main input processor **140** is preferably a separate and distinct processor from the main processor **110**, but can alternatively be integrated into the same circuit board, chipset, kernel, thread, or be a module of the main processor **110**. However, the main input processor **140** can be otherwise configured. The main input processor **140** can be connected to the main processor **110** by a wired connection, such as a cable, bus, male/female connection, or any other suitable wired connection, or a wireless connection, such as Bluetooth, BLE, NFC, or any other suitable wireless communication system. The main input processor **140** can alternatively be integrated with the main processor **110**. However, the main input processor **140** can be connected to processing endpoints and operate in any other suitable manner.

[0076] The main input processor **140** is preferably arranged proximal the main processor **110**, but can alternatively be arranged proximal the secure display **240**, main display **120**, secure input device **230**, main input device **160**, or arranged in any other suitable location. The main input processor **140** is preferably arranged with a broad face substantially coplanar with a main processor broad face, but can alternatively be arranged with the broad face parallel the main processor broad face, parallel the respective display broad face, or arranged in any suitable orientation.

[0077] The payment terminal **1** can additionally include a set of payment hardware **250** (financial transaction information inputs, payment reader, payment instrument reader) that function to receive payment information from a financial payment instrument, such as a credit card, debit card, mobile device, token, or secure element. The payment hardware **250** can additionally function to receive auxiliary information from other information sources. For example, the payment hardware **250** can receive information from any card including a magnetic stripe, IC chip, NFC transmitter **256**, barcode, QR code, Bluetooth, BLE, image, or any other suitable informational token.

[0078] The payment hardware **250** can be a card reader (e.g., payment card reader), a secure element transceiver, a camera, scanner, short-range communication transceiver, or any other suitable information input. The card reader can be a magnetic stripe reader, an IC chip reader **254**, or any other suitable reader capable of extracting information from a card. The card reader preferably includes a body and a card opening (card aperture) configured to receive an inserted card. The payment hardware **250** can be a single-system reader capable of extracting information from a single type of information storage (e.g., a magnetic stripe reader), or can be a hybrid-system reader capable of extracting information from multiple types of information storage.

[0079] In a first variation, the payment hardware **250** can be a hybrid-system card reader including a magnetic stripe reader and an IC chip reader **254**. The magnetic stripe reader can be a 3-track head reader, a 2-track head reader, or any other suitable reader. The integrated circuit (IC) chip reader can include a set of contacts, a contactless reader, or any other suitable IC chip reader **254**. In a specific example, the hybrid-system card reader includes a body defining a card opening, wherein the card opening has a longitudinal axis extending along its length. The magnetic stripe reader can be arranged along a first longitudinal edge of the card opening, proximal an end of the card opening longitudinal axis, wherein the first longitudinal edge extends along a first broad face of the body. The IC chip reader **254** can be arranged proximal a first end of the body opposing the

card opening, along a second broad face of the body opposing the first broad face.

[0080] The hybrid card reader **252** can additionally include a switch **257** arranged at the first end of the body. The switch can be configured to be operable in a coupled mode in response to card coupling with the switch (e.g., indicating full card insertion), and in an uncoupled mode when a card is not coupled to the switch. The switch can be coupled to the secure processor (e.g., wherein the secure processor can generate an event indicative of card coupling), an insertion confirmation output, such as a light or microphone, wherein the insertion confirmation output operation state (e.g., output light or sound) can be dependent on the switch operation state. The switch can additionally be connected to the secure processor **210** or payment hardware **250**, wherein the secure processor **210** or payment hardware **250** can read information from the card in response to switch operation in the coupled mode. However, the hybrid card reader **252** or payment hardware **250** can include any other suitable payment instrument coupling indicator.

[0081] In one example of hybrid card reader operation, the connected processor (e.g., the secure processor **210**) can dynamically determine the payment information storage types available on an inserted card. In response to substantially or near-real time determination that the card includes an IC chip, the connected processor can instruct the main processor **110** to display instructions associated with IC chip payment flow (e.g., to display instructions to leave the card in, to display a PIN pad, etc.). In response to substantially or near-real time determination that the card does not include an IC chip but does include a magnetic stripe, the connected processor can instruct the main processor **110** to display instructions associated with magnetic stripe payment flow, wherein the connected processor can control the magnetic stripe reader of the hybrid card reader **252** to read the magnetic stripe during card extraction from the card reader.

[0082] In a second variation, the payment hardware **250** can include an NFC transceiver configured to facilitate NFC payment information transfer between an NFC payment instrument and the payment terminal **1**. The NFC transceiver can include an antenna, wherein the antenna can extend along all or a portion of the secure display **240**, secure input device **230**, or along any other suitable portion of the payment terminal **1**. The antenna can be arranged in the same plane as the respective display, behind the display (e.g., distal the input device), or arranged in any other suitable location.

[0083] The payment hardware **250** can define a reference plane. The reference plane can be a broad face of a card reader body or chassis, a plane of the card reader opening, a plane of antenna winding, a plane extending in parallel to the longitudinal axis of an antenna, a plane extending perpendicular an antenna or coil central axis, or any other suitable plane. However, the payment hardware **250** can define a longitudinal axis or any other suitable reference point.

[0084] A payment hardware **250** can be arranged with the respective reference plane or point extending along a side of the secure display **240** (e.g., at a non-zero angle to the display broad face), an edge of the secure display broad face, a side of the main display **120**, an edge of the main display broad face, or arranged in any other suitable location on the payment terminal **1**. The payment hardware **250** can be arranged with the respective reference plane or point extending along a lateral edge, lateral side, longitudinal edge, or longitudinal side of the respective display. Alternatively, the payment hardware **250** can be arranged with the respective reference plane extending along a broad face of the respective display. Alternatively, the payment hardware **250** can be separate from the payment terminal **1**. The payment hardware **250** is preferably arranged proximal the secure display **240** and/or secure input device **230**, but can alternatively be arranged proximal the main display **120** and/or main input device **160** in variations of the payment terminal **1** including such components.

[0085] In a first example of payment hardware arrangement, the payment terminal **1** can include a housing **300** joining an edge of a secure display **240** and an edge of a main display **120** with a junction **320**. The payment hardware **250** can be a card reader, wherein the card opening can be arranged along the junction **320**, with the card opening longitudinal axis extending in parallel with the display edges joined by the junction **320**. The card reader body can be arranged with a broad

face substantially parallel the secure display broad face, substantially parallel the main display broad face, or at any other suitable angle relative to the main display or secure display broad faces. [0086] In a second example of payment hardware arrangement, the payment hardware **250** can be a card reader, wherein the card opening can be arranged along a side of a secure display **240** or main display **120**, with the card reader body substantially parallel to the respective display broad face. The card reader can be arranged with the opening extending along a lateral side or longitudinal side. The display can include an orientation vector (e.g., wherein text or other objects displayed on the displayed are aligned relative to the orientation vector), wherein the opening can be arranged along the right side of the display, the left side of display, the upper side of the display, or the lower side of the display.

[0087] In a third example of payment hardware arrangement, the payment hardware **250** can include an antenna. The antenna can be arranged within the housing **300** or along the housing exterior. The antenna can extend along a side of a secure display **240** or main display **120**, along an edge of the respective display broad face, or along a junction **320** between the secure display **240** and main display **120**, or along any other suitable portion of the payment terminal **1**. The antenna can be substantially coplanar with the respective display, or offset from the respective display.

[0088] The payment terminal **1** can include one or more pieces of payment hardware **250**. When the payment terminal **1** includes multiple payment hardware **250**, the payment hardware **250** are preferably not redundant, but can alternatively be redundant and have multiple readers for a single information storage type (e.g., multiple IC chip readers **254**). When the payment terminal **1** includes multiple payment hardware **250**, the payment hardware **250** can be arranged at one or more of the aforementioned locations (e.g., colocalized or dispersed).

[0089] The payment hardware **250** is preferably connected to the secure processor **210**, but can alternatively be connected to a secure financial information processor, the main processor **110**, and/or any other suitable processor. The payment hardware **250** can be operatively connected to only the secure processor **210**, only the main processor **110**, both the main and secure processors **210**, or to any other suitable component. The connection between the payment hardware **250** and the endpoint is preferably a one-way connection, wherein the payment hardware **250** can only send and not receive information, but can alternatively be a two-way connection or any suitable connection. The connection is preferably wired, but can alternatively be wireless. The payment hardware **250** can be powered through the connection, or can be powered through a separate power connection. The payment hardware **250** is preferably continuously operatively connected to the endpoint, but can be selectively operatively connected to the endpoint or connected in any other suitable manner.

[0090] The payment terminal **1** can additionally include a printer **500** that functions to print information on a substrate **570**, as shown in FIG. **13**. The processor is preferably controlled by the main processor **110**, but can alternatively be controlled by any other suitable processor. The printer **500** can include a printer body **510**, a printer door **540**, and a print mechanism. The printer **500** can be operable between a high voltage mode wherein the printer **500** prints at full speed, and a low voltage mode wherein the printer **500** prints at partial speed (e.g., based on a baud rate sent by the main processor to the printer). In a specific variation, the number of times the printer **500** can print in the high voltage mode is limited when the payment terminal **1** is disconnected from a high-voltage power source boo (e.g., a charging dock), wherein the printer **500** operation switches to the low voltage mode after the threshold number has been reached. However, the printer **500** can operate in any other suitable manner.

[0091] The printer body **510** of the printer **500** can define a printing substrate receptacle having a printer opening **520**, wherein a printing substrate storage mechanism (e.g., a paper roll) can be inserted through the printer opening **520** into the printing substrate receptacle, as shown in FIG. **12**. The printing substrate receptacle can include a set of tracks, a set of grooves, a set of dimples, or any other suitable insertion guidance and/or substrate retention mechanism. The retention

mechanism can additionally be configured to permit substrate dispensation (e.g., rotation about a dispensation axis). The printer opening **520** can include a first and second opposing edge, wherein the opposing edges can be parallel or have any other suitable relation. The printer body **510** preferably traces the shape of the substrate storage mechanism, but can alternatively have any other suitable shape. In one variation of the printer **500**, the printer body **510** includes an arcuate surface. [0092] The printer door **540** of the printer **500** functions to substantially seal the printer opening **520**, and is operable between an open position and a closed position. In the printer opening **520** is preferably unobstructed when the printer door **540** is in the open position, and is preferably partially or substantially entirely obstructed when the printer door **540** is in the closed position. However, the printer door **540** can be operable between any other suitable set of positions, and can interact with the printer opening **520** in any other suitable manner. The printer door **540** preferably matches the profile of the printer body **510** (e.g., includes substantially the same curvature), but can alternatively have a different profile. The printer door **540** preferably has substantially the same dimensions as the printer opening **520**, but can alternatively be smaller or larger.

[0093] The printer door **540** is preferably movably connected to the printer body **510**, but can be otherwise coupled to the printer body **510**. The printer door **540** is preferably connected to a first edge of the printer opening **520**, more preferably a first longitudinal edge **530** of the printer opening **520**, but can alternatively be connected to a first lateral edge of the printer opening **520** or be connected to any other suitable portion of the printer body **510**. A printer door **540** longitudinal edge is preferably connected to the printer body **510**, but a printer door **540** lateral edge, corner, or broad face can alternatively be connected to the printer body **510**. The printer door **540** connector is preferably a hinge **580**, such that the printer door **540** can actuate about a rotational axis substantially parallel to the first longitudinal edge of the printer opening **520** or printer door **540**, but can alternatively be a slot, clip, set of tracks (e.g., wherein the printer door **540** slides along the printer body **510** in a direction substantially perpendicular the first longitudinal edge or slides along the printer body **510** in a direction substantially parallel the first longitudinal edge, etc.), or be any other suitable actuatable coupling mechanism.

[0094] The print mechanism of the printer **500** functions to create a substantially persistent human or computer-readable representation of graphics (e.g., QR codes) or text on the printing substrate **570**. The printer mechanism **590** is preferably arranged distal the first longitudinal edge of the printer opening **520** (e.g., such that the printed image is distal the first longitudinal edge), but can alternatively be arranged proximal the first longitudinal edge of the printer opening **520** or arranged in any other suitable position. The print mechanism can be a toner-based, liquid inkjet, solid ink, dye- sublimation, thermal, laser, or any other suitable printing mechanism.

[0095] The printer **500** can additionally include a substrate gap **550** through which the printing substrate can be dispensed (e.g., from the printer **500** interior to the printer **500** exterior). In one variation, the substrate gap **550** can be cooperatively defined between the printer door **540** and the printer body **510**. In this variation, the printer door **540** can be slightly smaller than the printer opening **520** along a lateral axis, such that the printer door **540** leaves a gap between the printer opening **520** longitudinal edge and the printer door **540** longitudinal edge when the printer door **540** is in the closed position. However, the printer door **540** can have any other suitable dimensions. The gap is can be defined substantially parallel the retention mechanism support axis (e.g., the substrate storage winding axis), defined parallel a longitudinal axis of the arcuate surface, or extend along any other suitable portion of the printer **500**. The gap is preferably at least as wide as, if not longer than, the substrate width, but can alternatively be equal or shorter. The gap is preferably defined along the second edge of the printer opening **520** and/or printer door **540** opposing the connection edge, but can alternatively be defined along an edge adjacent the connection edge, be defined as an aperture through the printer door **540** body, or be defined in any other suitable manner.

[0096] The printer **500** can additionally include a substrate separation mechanism **560** that

functions to separate a first portion of the substrate from the remainder of the substrate stored in the substrate storage mechanism. The substrate separation mechanism **560** can be a toothed mechanism that functions to perforate and facilitate substrate tearing, a shearing mechanism, or any other suitable separation mechanism **560**. The printer **500** can include a first and second set of toothed mechanisms arranged along the first and second edges of the gap, respectively (e.g., second edges of the printer door **540** and printer opening **520**, respectively), such that the substrate can be separated by applying force in a first or second direction, wherein the first and second directions can be at an angle to the longitudinal axes of the first and second toothed mechanisms, respectively. However, the printer **500** can include a single set of toothed mechanisms arranged along the edge of the printer door **540** or the printer opening **520**, or include any suitable number of substrate separation mechanisms **560** arranged in any other suitable location.

[0097] The printer **500** is preferably coupled to the main display **120** or secure display **240**, such that the respective display and printer **500** are housed in a singular housing **300**. However, the printer **500** can be housed in a separate and distinct housing from the main display **120** or main housing. The printer **500** can be arranged along the edge of the respective display active surface, along the side of the respective display, along the edge of the respective display back surface (surface opposing the active surface), along the body of the respective display back surface, or along any suitable portion of the respective display. In one example of the payment terminal **1**, the printer **500** coupled along a portion of the secure display back surface. In a specific example, the printer **500** can be coupled along the secure display back surface, proximal a secure display edge distal the junction **320** between the secure display **240** and main display **120**. The printer **500** can occupy the entirety of the secure display back surface or a portion thereof. In the latter instance, the printer body **510** can cooperatively form a void with the connected display and second display, wherein the void defined along the respective display back surface between the printer body **510** and the joined second display functions as a hand support (e.g., cradle). However, the printer **500** can be arranged in any other suitable location (e.g., coupled to any other suitable portion of any other suitable component) of the payment terminal **1**. The printer body **510** can additionally define a contact surface **340** distal the respective display and substantially parallel the longitudinal axis, wherein the contact surface **340** can be configured to support the respective display at a predetermined angle upon a supporting surface **10**, such as a table.

[0098] The payment terminal **1** can additionally include a power source **600** that functions to provide electrical power. The power source **600** can be a power storage unit, wireless power system (e.g., inductive charging system, RF power system, etc.), renewable power system (e.g., solar, wind, piezoelectric, etc.), or any other suitable power source **600**. The power storage unit can function to store electrical power, receive electrical power, convert electrical power to power suitable for the payment terminal components, and/or otherwise interact with electrical power. The power storage unit is preferably a battery, more preferably a secondary battery but alternatively a primary battery, but can alternatively be a fuel cell system (e.g., wherein power is stored in a chemical form), or any other suitable power storage unit. The secondary battery can have lithium chemistry (e.g., be lithium ion, lithium polymer, etc.), nickel cadmium chemistry, magnesium chemistry, or any other suitable chemical composition. The power supply unit can be arranged proximal the main display **120**, the secure display **240**, or in any other suitable location. The power supply unit can be arranged with a power supply unit broad face substantially parallel the display broad face, wherein the power supply unit is preferably arranged proximal the display back surface. In a specific example in which the payment terminal **1** include a main display **120** joined to the secure display **240** along a junction **320**, the power supply unit can be arranged substantially parallel one of the displays, proximal an end of the respective display distal the junction **320**, as shown in FIG. **6**. This can assist with weight distribution. In one variation of the payment terminal, the mass of the battery is preferably offset by the mass of the printer across the junction. However, the weight distribution between the secure side and main side can be 50/50, 40/60, 30/70, 70/30,

60/40, or have any other suitable distribution. However, the power supply unit can be arranged in any other suitable location within the payment terminal **1**. The power supply unit can have a capacity of several thousand mA/h (e.g., 5,000 mA/h, 1,000 mA/h, 10,000 mA/h, etc.), several hundred mA/h (e.g., 500 mA/h, 100 mA/h, etc.), or any other suitable capacity. However, any other suitable power supply unit can be used. The power supply unit can include one or more battery cells. The power terminal can include one or more power supply units, no power supply units (e.g., wherein the power terminal can be powered on mains power), or any suitable number of power supply units.

[0099] The power source **600** is preferably electrically connected to all powered components of the payment terminal **1**, such as the secure processor **210**, secure display **240**, secure input device **230**, secure input processor **220**, and main processor **110**, and the main display **120**, main input display, printer **500**, sensors **400**, communication modules **190**, and/or any other suitable component, if included. The power source **600** can be directly connected to the payment terminal components, but can alternatively be indirectly connected to the payment terminal components (e.g., wherein an intermediary component receives the power from the power source **600** and sends the power to the endpoint component). However, power can be provided in any other suitable manner.

[0100] The power source **600** can additionally include one or more charging contacts **620** that function to receive power from an outside source. The charging contacts **620** can additionally function to transfer information. For example, the payment terminal **1** can include a first set of high voltage charging contacts **620** and a second set of charging contacts **620**, wherein the first and second set of charging contacts **620** can both be electrically connected to the power source **600**. Examples of charging contacts **620** that can be used include power and data contacts (e.g., male or female connectors), exposed contacts, inductive charging coils, or any other suitable power and/or data transfer system. The charging contacts **620** can additionally or alternatively be directly connected to a payment terminal component. For example, the first set of charging contacts **620** can be arranged along the printer body **510** and be electrically connected to the printer **500**, such that the printer **500** can be directly powered by the first set of charging contacts **620**, as shown in FIG. **11**, but can alternatively be arranged in any other suitable position. The second set of charging contacts **620** can additionally function to transfer information (e.g., be a power and data port, such as a USB port or FireWire port), and can be arranged proximal the main processor **110**, preferably between the main processor **110** and power source **600** but alternatively in any other suitable location. However, the power source **600** can include any other suitable power connection. The charging contacts **620** are preferably arranged along the exterior of the payment terminal **1** (e.g., along the housing **300** body). The charging contacts **620** can be arranged proximal a contact surface **340**, along a side of the terminal **1**, or along any other suitable portion of the terminal **1**. For example, the charging contacts **620** can be arranged distal the display connected to the printer **500**, but can alternatively be arranged proximal the display. In one variation, the charging contacts **620** are arranged along the curved face of the printer door **540**. However, the charging contacts **620** can be arranged along the printer body **510** or along any other suitable portion of the printer **500**. In a second example, the charging contacts **620** can be arranged along an edge of the main display back surface, distal the junction **320** and proximal the respective contact surface **340**. However, the charging contacts **620** can be arranged in any other suitable position.

[0101] The power source **600** can additionally include one or more power conversion circuits **640** that function to convert power source **600** power to power suitable for the component. In one variation, the power source **600** includes a boost converter (step-up converter) that functions to convert battery power (e.g., 5V, 3V, etc.) to printer power (e.g., 9V). In a specific example, as shown in FIG. **3**, the first set of charging contacts **620**, printer **500**, and boost converter are connected to a first set of high voltage electrical rails, while the power source **600**, second set of charging contacts **620**, processors, displays, and inputs are connected to a second set of low voltage rails. The power source **600** can additionally be connected to the boost converter and/or a buck

converter. However, the power circuitry can be connected in any other suitable manner.

[0102] The payment terminal **1** can additionally include a set of communication modules **190**. Each communication module **190** is preferably controlled by the main processor **100**, but can alternatively be controlled by the secure processor **210** or by any other suitable processor. The communication modules **190** are preferably connected to the power source **600**, but can alternatively be powered in any other suitable manner. The communication module **190** preferably functions to communicate with a peripheral or remote device (e.g., the remote system). For example, the communication module **190** can function to communicate data with the remote system, determine inventory based on inventory-associated signals, receive application or software updates, connect to peripheral devices **30** (e.g., printers **500**, scanners, cash boxes, registers, etc.), user devices **2** (e.g., mobile devices), introduce connectivity to physically connected devices, and/or enable any other suitable functionality.

[0103] The communication module **190** can simultaneously communicate with multiple devices (e.g., with multiple channels), communicate with a single device (e.g., includes only a single channel), with networked application services, or communicate with any other suitable endpoint. The communication module **190** can additionally function as the payment hardware **250**, but the payment hardware **250** can alternatively be a separate and distinct component. The communication module **190** is preferably a transceiver and enables two-way (e.g., data transmission and receipt), but can alternatively enable only one-way communication (e.g., only a transmitter capable of data transmission or only a receiver capable of data receipt). The communication modules **190** can be wired or wireless communication modules **190**. The wired communication module **190** can be a USB module (e.g., connector and circuit board), FireWire module, Lightning module, and/or any other suitable connector module. The wireless communication module **190** can be a WiFi module, cellular module, satellite module, RF module, IR module, Zigbee module, Bluetooth module, NFC module, or any other suitable module. The wireless communication module **190** can additionally include one or more antennae. Each antenna can be arranged within the housing **300**, along the surface of the housing **300**, or arranged in any other suitable location. The antennae can extend along a portion of a display length, display width, printer **500** length, or along any other suitable portion of the payment terminal **1**.

[0104] The housing **300** (casing) of the payment terminal **1** functions to mechanically protect and retain the payment terminal components. The housing **300** preferably substantially cooperatively encapsulates the processors, displays, printers **500**, communication modules **190**, sensors **400**, and/or any other suitable payment terminal component with the secure input devices **230**. However, the housing **300** can alternatively enclose any other suitable portion of the payment terminal components. The housing **300** is preferably formed from a polymer, but can alternatively be formed from metal or any other suitable material.

[0105] The housing **300** can additionally define a set of contact surfaces **340** that function to support the payment terminal **1** in a predetermined orientation relative to support surface (as shown in FIG. **4**), such as a table. The contact surface **340** can be defined along an end of the display (e.g., a side of the display), a broad surface of the display, a portion of the printer body **510** (e.g., as discussed above), or along any other suitable portion of the payment terminal **1**. The contact surface **340** is preferably substantially planar, but can alternatively be curved, angled, or have any other suitable configuration. The contact surface **340** can be substantially smooth, include a friction-increasing material (e.g., rubber or sandpaper), include traction features (e.g., protrusions, grooves, etc.), or include any other suitable surface.

[0106] The housing **300** can additionally include one or more drainage holes **350** that function to drain liquids from the housing interior. The drainage hole is preferably arranged along the interior angle of the junction, but can alternatively be arranged along the surface of the housing distal a display, along an end of the display, or along any other suitable surface. The drainage hole can be an oval aperture through the housing thickness, a set of holes or grooves through the housing

thickness, or have any other suitable configuration. The drainage hole can additionally include a mesh or any other suitable covering, which can function to prevent substance ingress into the drainage hole.

[0107] The payment terminal **1** can additionally include a handle or resting surface **310**, which functions to provide a gripping surface or hand support such that a user can hold the payment terminal **1**. The handle **310** can be a set of voids defined by the housing **300**, a strap or movable piece coupled to the handle **310** (e.g., wherein the housing **300** can define a set of mounting points), or be defined in any other suitable manner. In a first specific example, the handle **310** can be cooperatively defined by the secure display **240**, the main display **120**, and the printer body **510**, as discussed above.

[0108] The payment terminal **1** can additionally include a set of sensors **400** that function to measure payment terminal **1** parameters. The payment terminal **1** parameters can include ambient parameters (e.g., ambient temperature, pressure, light, sound, etc.), operational parameters (e.g., system temperature, power consumption, etc.), user parameters (e.g., biometric information, optical information, etc.), or any other suitable parameters. Each sensor is preferably controlled by and/or operatively connected to the main processor **110**, but can alternatively be controlled by and/or operatively connected to the secure processor **210** or any other suitable processor. The set of sensors **400** can include light sensors (e.g., camera **430**, ambient light sensor, etc.), sound sensors (e.g., microphones), motion sensors (e.g., accelerometer, gyroscope, etc.), location sensors (e.g., GPS, GSM, cellular triangulation, etc.), proximity sensors, biometric sensors (e.g., a fingerprint reader), or any other suitable sensor. The payment terminal **1** can additionally include additional visual outputs, audio outputs (e.g., speakers), or any other suitable output.

[0109] In one example, the payment terminal **1** includes a first and second camera. The first camera (customer camera) can be arranged proximal the secure display **240**, and the second camera (merchant camera) can be arranged proximal the main display **120**. In a specific example, the first camera can be arranged with a camera active surface normal vector at a non-zero angle to the secure display active surface normal vector. More preferably, the first camera can be arranged with an active surface normal vector **432** directed substantially perpendicular a contact surface broad face, as shown in FIG. **14**. However, the first camera can be otherwise arranged. The second camera is preferably arranged with an active surface normal vector **432'** parallel the main display active surface normal vector, but can be otherwise arranged. Both the first and second cameras can be operatively connected to the main processor **110**, such that the main processor **110** receives the optical output from both cameras. The main processor **110** can display the optical output of the first camera on the secure display **240**, and can display the optical output of the second camera on the main display **120**. The main processor **110** can additionally process the optical outputs of the first and/or second camera to identify items (e.g., QR codes, barcodes, etc.).

[0110] In a second example, the payment terminal operation mode can be determined based on the sensor measurements. The payment terminal **1** can be operable between a desktop mode and mobile mode. The payment terminal **1** can be operable in the desktop mode when coupled to a dock (e.g., a charging dock), when the payment terminal **1** is resting with an imaginary support plane extending between a first and second support point on the terminal **1** substantially perpendicular to a gravity vector, when the first and second support point on the terminal **1** are simultaneously coupled to a surface, or in response to any other suitable event indicative of payment terminal **1** coupling to a surface. The payment terminal **1** can be operable in the mobile mode when an on-board motion sensor (e.g., accelerometer, gyroscope, etc.) measures movement above a predetermined jerk, acceleration, or velocity, when the first and second support points are not simultaneously coupled to a surface, when a third support point (e.g., in a handle **310**) is coupled to a surface, or in response to any other suitable event indicative of payment terminal **1** usage in a handheld or mobile application. The payment terminal **1** can have the same or different functionalities when in the desktop mode or mobile mode. In one example of the latter variation,

the payment terminal **1** can selectively enable a first set of applications and disable a second set of applications or functionalities (e.g., camera, functionalities, etc.) when in the desktop mode, and selectively enable the second set of applications and enable the first set of applications or functionalities when in the mobile mode.

[0111] As shown in FIG. **10**, the payment terminal **1** can additionally include a set of indicators **420** that function to indicate an interaction status. Examples of interaction statuses that can be indicated include card insertion status (e.g., successful card insertion, failed card insertion, etc.), payment entry status, user prompts (e.g., for required user actions), merchant prompts, or any other suitable interaction status. The indicator can be a set of light emitting elements (e.g., a first and second light emitting element), an audio output, a user interface element (e.g., an icon, etc.), or any other suitable indicator. One or more indicators of the set of indicators can be controlled by the main processor **110**, the secure processor **210**, the payment hardware **250**, or any other suitable component. In one example, the hybrid card reader **252** can include a set of light emitting elements (e.g., LEDs, OLEDs, etc.) triggered by the switch (e.g., through the secure processor). In a specific example, the light emitting elements emit light having a first frequency in response to switch operation in the coupled mode, and emit light having a second frequency in response to switch operation in the uncoupled mode. The light emitting elements can be arranged along a protrusion of the hybrid card reader **252**, wherein the protrusion can additionally house the magstripe reader **253**. However, the indicators can be arranged in any other suitable location.

[0112] The payment terminal **1** can additionally include a security mesh **212** that functions to detect tampering. The security mesh **212** is preferably connected to the secure processor, but can alternatively or additionally be connected to the main processor or any other suitable processing system. The security mesh is preferably arranged along the interface between the printer body and the secure processor (e.g., wherein the card reader body is metallic and coupled to the secure display), but can alternatively be arranged about the secure processor, around the IC chip reader, arranged between the secure display and secure processor, arranged along the junction, or arranged along any other suitable portion of the payment terminal **1**. The security mesh can have adjacent ground and power wires (e.g., wherein the ground and power wires are arranged in a single plane in a boustrophedonic pattern), interwoven ground and power wires, or any other suitable security mesh.

4. Specific Examples

[0113] In a first example of the payment terminal **1**, as shown in FIG. **2**, the payment terminal **1** includes a main display **120**, a main input device **160**, a main processor **110**, a main input processor **140**, a secure display **240**, a secure input device **230**, a secure processor **210**, a secure input processor **220**, and a power source **600**. The main input device **160** is only connected to the main input processor **140** and the power source **600**, directly or indirectly through the main input processor. The remainder of the components can be directly connected to the power source **600** or indirectly connected to the power source **600** through an intermediary processor. The secure input device **230** is only connected to the secure input processor **220** and the power source **600**, directly or indirectly through the input processor. The main processor **110** is connected to and receives data from the main input processor **140** and secure input processor **220**. The main processor **110** is connected to and sends data to the main display **120** and secure display **240**. The secure processor **210** is connected to and receives data from the secure input processor **220**. The secure processor **210** is connected to the main processor **110** by a wired connection **800**, wherein the wired connection is preferably the only connection between the secure processor **210** and main processor **110**. The connection **800** is preferably a one way connection, such that the secure processor **210** preferably is capable of only sending data **202** to the main processor **110** over the connection **800**, but can alternatively or additionally be a two way connection such that the secure processor **210** can receive data from the main processor **110**. However, the processors can be otherwise connected. The secure processor **210** is operable between a secured and unsecured mode, wherein

the secure processor **210** does not forward unsecured input coordinates to the main processor in the secured mode, and forwards unsecured input coordinates received from the secure input processor to the main processor **110** in the unsecured mode. The secure processor, in the secured mode, can send events descriptive of user interactions to the main processor (e.g., key pressed, user cancelled, user deleted key, etc.). The payment terminal **1** can additionally include a hybrid card reader **252**, wherein the hybrid card reader **252** is only connected to and configured to send information to the secure processor **210**. The hybrid card reader **252** can additionally be connected to the power source **600**, indirectly or directly. The payment terminal **1** can additionally include a printer **500**, wherein the printer **500** is connected to and controlled by the main processor **110**. The payment terminal **1** can additionally include a set of sensors **400**, such as cameras, wherein the sensors **400** are connected to and send information to the main processor **110**.

[0114] The main input device **160** and secure input device **230** are both touchscreens and overlaid over the main display **120** and secure display **240**, respectively. The main display **120** and the secure display **240** are both LCD displays. The main display **120** is larger than the secure display **240**. In a specific example, the main display **120** length can be two times the width of the secure display **240**, wherein the main display **120** width can be substantially equal to the secure display length. The main display **120** and secure display **240** can be joined along a junction **320** formed by the housing **300**, forming a secure side **201** including the secure display **240**, secure input device **230**, secure input processor **220**, and secure processor **210**, and a main side **101** including the main display **120**, main input device **160**, main input processor **140**, and main processor **110**. The wired connection extends across the junction **320**. In a specific example, a lateral edge of the main display **120** is joined to a longitudinal edge of the secure display **240**. The hybrid card reader **252** is arranged along the junction **320**, with the opening extending along the junction **320** and the card reader body extending parallel the secure display **240**. The power source **600** (e.g., battery) is arranged parallel the main display **120** proximal the main display back surface, proximal the end of the main display **120** distal the junction **320** (distal main display end). The main processor **110** is arranged between the power source **600** and the junction **320**. The printer **500** is arranged along a portion of the secure display back surface. In a specific example, the printer **500** is arranged along an end of the secure display back surface distal the junction **320** (distal secure display end). The gap of the printer **500** is oriented to be substantially parallel with the distal secure display end. The gap includes toothed separation mechanisms **560** along both longitudinal edges of the gap. The printer door **540** is arranged distal the secure display back surface, with the hinge **580** distal the distal secure display end, such that the printer door **540** opens away from the secure display **240**. The housing **300** preferably traces the surfaces of the printer body **510**, remainder of the secure display back face, and main display **120** to cooperatively form a handle **310**. The weight of the printer **500** preferably counterbalances the weight of the power source **600**. A first contact surface **340** is defined along the distal main display end) and a second contact surface **340** is defined along a longitudinal, arcuate surface of the printer **500** (e.g., along the printer body **510** or the printer door **540**). A first camera is arranged along the side of the secure display **240**, proximal the distal secure display end, and is oriented with the camera active surface normal vector substantially perpendicular the second contact surface normal vector (e.g., perpendicular a gravity vector). The payment terminal **1** can additionally include a power and data connector arranged between the processor and power source **600**, along a longitudinal side of the main display **120**. The payment terminal **1** can additionally include a set of docking connectors arranged along an arcuate surface of the printer body **510**, configured to connect to an external dock. The power and data connector and docking connectors are connected to the power source **600**. The payment terminal **1** can additionally include a WiFi transceiver configured to communicate with a remote device, an NFC transceiver, a Bluetooth transceiver, a beacon transceiver, or any other suitable communication mechanism. The short-range communication modules (e.g., NFC, Bluetooth, beacon, etc.) that function as payment hardware are connected to the secure processor **210**. The long-range

communication modules are connected to the main processor **110**.

[0115] In a second example, the payment terminal **1** includes a single display (secure display **240**) and a single input device (secure input device **230**), a main processor **110**, a secure processor **210**, a secure input processor **220**, a power source **600**, and a set of payment hardware **250** (e.g., short-range communication modules, card reader, etc.). The single input device is only connected to and sends information to the secure input processor **220**. The secure input processor **220** is connected to and sends information to the main processor **110** and the secure processor **210**. The main processor **110** is connected to the secure input processor **220**, the power source **600**, and the display. The secure processor **210** is only connected to the power source **600**, the payment hardware **250**, the main processor **110**, and the secure input processor **220**. The secure processor **210** is connected to the main processor **110** by a power and data cable. The secure input processor **220** is operable between a secured mode, wherein information is sent to the secure processor **210**, and an unsecured mode, wherein information is sent to the main processor no. The secure input processor **220** switches between the secured and unsecured mode in response to a switching event. The switch event can be the initiation of a payment flow (e.g., in response to selection of a “charge” icon), the receipt of financial transaction information from the payment hardware **250**, the detected position of the payment terminal **1**, or any other suitable event. In a first specific example, the payment terminal **1** can operate in the unsecured mode in response to the accelerometer indicating a first terminal orientation, and in a secured mode in response to the accelerometer indicating a second terminal orientation (e.g., opposing the first orientation). In a second specific example, the payment terminal **1** can operate in the unsecured mode in response to a switch operating in a first position, and in the secured mode in response to the switch operating in a second position. The switch is preferably switched from the first to the second position when the terminal **1** is rotated about a rotational axis substantially normal to a terminal contact surface **340**.

[0116] Although omitted for conciseness, the preferred embodiments include every combination and permutation of the various system components and the various method processes.

[0117] As a person skilled in the art will recognize from the previous detailed description and from the figures and claims, modifications and changes can be made to the preferred embodiments of the invention without departing from the scope of this invention defined in the following claims.

Claims

1. A terminal, comprising: a housing comprises a first portion and a second portion; a payment card industry (PCI)-compliant secure processing system disposed in the housing; a touchscreen connected to the secure processing system and connected to the first portion of the housing, wherein the touchscreen is configured to receive an input from a first user; a payment instrument reader connected to the secure processing system in the housing; a main processing system separate from and connected to the secure processing system, the main processing system disposed in the housing; a display connected to the second portion of the housing and operably connected to the main processing system, the display configured to display information to a second user; wherein the first portion of the housing is disposed at a suitable angle relative to the second portion of the housing such that the touchscreen is compliant with a PIN transaction security (PTS) requirement.
