

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12385317
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Gorman; Christopher Allen

Glazed panel installation system and method

Abstract

A fenestration opening is provided with opposing receptors on opposite sides of the fenestration opening. Each of the receptors is configured to capture and opposing end of a glazed panel with a capture feature or features on each receptor that hold the respective end of the glazed panel from moving laterally, in or out of the fenestration opening. The glazed panel is installed by angling the glazed panel with respect to the fenestration opening and inserting one end of the glazed panel into engagement with one of the receptors, then moving the opposite end of the glazed panel so that the panel is aligned between the receptors, and then moving the panel so that the opposite end of the receptor is captured by the opposite receptor.

Inventors:	Gorman; Christopher Allen (Fort Lauderdale, FL)
Applicant:	CHAMPION TRUST LLC (Fort Lauderdale, FL)
Family ID:	80004193
Assignee:	CHAMPION TRUST LLC (Fort Lauderdale, FL)
Appl. No.:	17/889000
Filed:	August 16, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220389751 A1	Dec. 08, 2022

Related U.S. Application Data

division parent-doc US 17188213 20210301 US 11414914 child-doc US 17889000
us-provisional-application US 63058926 20200730

Publication Classification

Int. Cl.: E06B1/36 (20060101); E06B1/56 (20060101); E06B1/60 (20060101)

U.S. Cl.:

CPC E06B1/36 (20130101); E06B1/56 (20130101); E06B1/6015 (20130101);

Field of Classification Search

CPC: E06B (1/36); E06B (1/56); E06B (1/6015); E06B (1/60)

USPC: 49/425; 52/213

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1660408	12/1927	Bayley	N/A	N/A
2504701	12/1949	Krantz	N/A	N/A
2504702	12/1949	Krantz	N/A	N/A
2629467	12/1952	Fry	N/A	N/A
2771970	12/1955	Geyser	52/204.5	E06B 1/56
2788099	12/1956	Geyser	52/214	E06B 1/6046
2863180	12/1957	Birdwell	52/209	E06B 3/60
3119155	12/1963	Schlegel	49/495.1	E06B 1/6061
3267629	12/1965	Waring et al.	N/A	N/A
3315426	12/1966	Rolland	N/A	N/A
3568383	12/1970	Judkins et al.	N/A	N/A
4151691	12/1978	Wendt	52/395	E04B 2/82
4881768	12/1988	Lange	N/A	N/A
5392574	12/1994	Sayers	52/204.55	E06B 1/30
5884361	12/1998	Richardson	16/102	E05F 1/16
6173541	12/2000	Petta	N/A	N/A
6427398	12/2001	Levine	52/745.15	E06B 1/28
6532705	12/2002	Gorman	52/212	E06B 1/6015
8776460	12/2013	Carlson et al.	N/A	N/A
8776461	12/2013	Carlson	52/60	E06B 1/56
9115489	12/2014	Bourdon	N/A	E04B 1/36
9512656	12/2015	Lee	N/A	E05D 15/0682
9631373	12/2016	Loyd	N/A	N/A
9920522	12/2017	Staten et al.	N/A	N/A
2001/0020350	12/2000	Gorman	N/A	N/A
2007/0245649	12/2006	Habeck	52/212	E06B 1/62
2008/0054137	12/2007	Poulin	N/A	N/A
2008/0190030	12/2007	Cheon	49/425	E05D 15/0665
2009/0108154	12/2008	Lucci	N/A	N/A

2010/0115877	12/2009	Yoo	52/656.2	E05D 15/0686
2011/0041431	12/2010	McKenna	N/A	N/A
2011/0258947	12/2010	Peterson	N/A	N/A
2016/0115726	12/2015	Hodgson et al.	N/A	N/A
2019/0112863	12/2018	Rocca, Jr. et al.	N/A	N/A
2020/0347665	12/2019	Gordon	N/A	N/A
2021/0238911	12/2020	Theriault	N/A	N/A
2021/0246712	12/2020	Crochetiere et al.	N/A	N/A
2021/0277710	12/2020	Edlin et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2225952	12/1998	CA	N/A
102009005177	12/2009	DE	N/A
202018103083	12/2017	DE	N/A
0890698	12/1998	EP	N/A
2226456	12/2009	EP	N/A
2886772	12/2014	EP	N/A
3438394	12/2017	EP	N/A
2351766	12/2000	GB	N/A
2015051985	12/2014	WO	N/A
2017068408	12/2016	WO	N/A

OTHER PUBLICATIONS

Machine Translation of WO 2015051985 obtained by the European Patent Office at <https://worldwide.espacenet.com/obtained> on Nov. 22, 2021. cited by applicant
Derwent Abstract of KR 2031955 B1 by Hyun (Year: 2019). cited by applicant

Primary Examiner: Agudelo; Paola

Attorney, Agent or Firm: The Concept Law Group, PA

Background/Summary

CROSS-REFERENCE (1) This application is a divisional of U.S. patent application Ser. No. 17/188,213, filed Mar. 1, 2021, and granted as U.S. Pat. No. 11,414,914 on Aug. 16, 2022, and through that application further claims priority to U.S. provisional application No. 63/058,926, filed Jul. 30, 2020, the entireties of each of which are hereby incorporated by reference.

FIELD OF THE INVENTION

(1) The present invention relates generally to the design of commercial fixed windows, and, more particularly, relates to a system that allows substantially simpler installation of residential and commercial fixed and operable windows in building fenestrations by a unique structural attachment in which the window unit floats in and is captured by receptors.

BACKGROUND OF THE INVENTION

(2) Many commercial buildings have fixed windows, including office buildings, hotels, and other buildings. These windows are not able to be opened, which is why they are referred to as “fixed.” A common arrangement of fixed windows involves the building being designed with individual window openings in the exterior wall. This is different than, for example, buildings that use

continuous glass to form a curtain wall on the exterior of the building. For these individual windows, fixed windows are typically installed using prepared window units. A window unit contains the glass, and a carrier, that is made of a material such as aluminum or vinyl, in which the glass is mounted. The window unit is prepared for a given size window opening by cutting the glass to size so that the carrier containing the glass will fit into the window opening. To install the window unit, the window unit is lifted into place in a window opening, and then screws are used to fasten the window unit to the four sides of the window formed by the walls and sills. Caulking is then applied on the exterior around the window unit to prevent water ingress. These kinds of windows are used in both commercial and residential applications, and for both operable and fixed windows in building fenestrations.

(3) One of the issues using this conventional approach is the amount of time it takes to install each window unit. Once the window unit is in place, it must be stabilized in place while being held, and then fasteners such as screws are driven through the aluminum carrier into the walls and sills to hold the window panel in place. The crew needed to lift and install the window units is substantial. Typically, after applying the fasteners, an inspection of the installed window units is performed, which may occur days or weeks after the window units are installed. Once the inspection process is complete, then screw cover panels are installed on the carrier to prevent removal of the screws. Accordingly, it can take a substantial period of time to install the windows.

(4) Therefore, a need exists to overcome the problems with the prior art as discussed above.

SUMMARY OF THE INVENTION

(5) In accordance with the inventive disclosure, there is provided a method for installing fixed windows, that includes installing an upper window panel receptor in a top of a window opening and installing a lower window panel receptor in a bottom of the window opening. The lower window panel receptor is “U” shaped and has a base with sides extending perpendicularly to the base of the lower window panel receptor. The upper window panel receptor is “U” shaped and has a base with sides extending perpendicularly to the base. The sides of the upper window panel receptor are longer than the sides of the lower window panel receptor. The method further includes placing a window panel into the window opening such that a top of the window panel is captured between the sides of the upper window panel receptor and a bottom of the window panel is captured between the sides of the lower window panel receptor.

(6) In accordance with a further feature, wherein the window opening is rectangular, placing the window panel into the window opening comprises inserting the top of the window panel into the upper window panel receptor and lifting the window panel so that the bottom of the window panel is above the sides of the lower window panel receptor. While the top of the window panel is inserted into the upper window panel receptor, the method further includes moving the bottom of the window panel over the lower window panel receptor. The method further includes lowering the window panel such that the bottom of the window panel is inserted into the lower window panel receptor.

(7) In accordance with the inventive disclosure, there is provided a system for installing fixed window units that includes an upper window panel receptor in a top of a window opening and a lower window panel receptor in a bottom of the window opening. The lower window panel receptor is “U” shaped and has a base with sides extending perpendicularly to the base of the lower window panel receptor. The upper window panel receptor is “U” shaped and has a base with sides extending perpendicularly to the base. The sides of the upper window panel receptor are longer than the sides of the lower window panel receptor. The system includes a window panel placed in the upper window panel receptor and the lower window panel receptor such that a top of the window panel is captured between the sides of the upper window panel receptor and a bottom of the window panel is captured between the sides of the lower window panel receptor.

(8) Although the invention is illustrated and described herein as embodied in a fixed window installation method and system, it is, nevertheless, not intended to be limited to the details shown

because various modifications and structural changes may be made therein without departing from the spirit of the invention and within the scope and range of equivalents of the claims. Additionally, well-known elements of exemplary embodiments of the invention will not be described in detail or will be omitted so as not to obscure the relevant details of the invention.

(9) Other features that are considered as characteristic for the invention are set forth in the appended claims. As required, detailed embodiments of the present invention are disclosed herein; however, it is to be understood that the disclosed embodiments are merely exemplary of the invention, which can be embodied in various forms. Therefore, specific structural and functional details disclosed herein are not to be interpreted as limiting, but merely as a basis for the claims and as a representative basis for teaching one of ordinary skill in the art to variously employ the present invention in virtually any appropriately detailed structure. Further, the terms and phrases used herein are not intended to be limiting; but rather, to provide an understandable description of the invention. While the specification concludes with claims defining the features of the invention that are regarded as novel, it is believed that the invention will be better understood from a consideration of the following description in conjunction with the drawing figures, in which like reference numerals are carried forward. The figures of the drawings are not drawn to scale.

(10) Before the present invention is disclosed and described, it is to be understood that the terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting. The terms “a” or “an,” as used herein, are defined as one or more than one. The term “plurality,” as used herein, is defined as two or more than two. The term “another,” as used herein, is defined as at least a second or more. The terms “including” and/or “having,” as used herein, are defined as comprising (i.e., open language). The term “coupled,” as used herein, is defined as connected, although not necessarily directly, and not necessarily mechanically. The term “providing” is defined herein in its broadest sense, e.g., bringing/coming into physical existence, making available, and/or supplying to someone or something, in whole or in multiple parts at once or over a period of time.

(11) In the description of the embodiments of the present invention, unless otherwise specified, azimuth or positional relationships indicated by terms such as “up”, “down”, “left”, “right”, “inside”, “outside”, “front”, “back”, “head”, “tail” and so on, are azimuth or positional relationships based on the drawings, which are only to facilitate description of the embodiments of the present invention and simplify the description, but not to indicate or imply that the devices or components must have a specific azimuth, or be constructed or operated in the specific azimuth, which thus cannot be understood as a limitation to the embodiments of the present invention. Furthermore, terms such as “first”, “second”, “third” and so on are only used for descriptive purposes, and cannot be construed as indicating or implying relative importance. Furthermore, relational terms are used, such as “opposite” and “opposing.” These terms refer to opposite ends or sides of something. A distal end of something is opposite a proximate end, a top end is opposite a bottom end, and so on.

(12) In the description of the embodiments of the present invention, it should be noted that, unless otherwise clearly defined and limited, terms such as “installed”, “coupled”, “connected” should be broadly interpreted, for example, it may be fixedly connected, or may be detachably connected, or integrally connected; it may be mechanically connected, or may be electrically connected; it may be directly connected, or may be indirectly connected via an intermediate medium. As used herein, the terms “about” or “approximately” apply to all numeric values, whether or not explicitly indicated. These terms generally refer to a range of numbers that one of skill in the art would consider equivalent to the recited values (i.e., having the same function or result). In many instances these terms may include numbers that are rounded to the nearest significant figure. Those skilled in the art can understand the specific meanings of the above-mentioned terms in the embodiments of the present invention according to the specific circumstances.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The accompanying figures, where like reference numerals refer to identical or functionally similar elements throughout the separate views and which together with the detailed description below are incorporated in and form part of the specification, serve to further illustrate various embodiments and explain various principles and advantages all in accordance with the present invention.
- (2) FIG. 1 is an external elevational view of an installed window unit using upper and lower window panel receptors, in accordance with some embodiments;
- (3) FIG. 2 is a side cross cut view of window opening with the upper and lower window panel receptors installed, and prior to the window panel being installed, in accordance with some embodiments;
- (4) FIGS. 3A-3C show a side view cross cut view of a window opening in which a window panel is installed, in accordance with some embodiments;
- (5) FIGS. 4A-4D shown a front elevational view of a non-rectangular window opening in which several window panels are installed, in accordance with some embodiments;
- (6) FIG. 5 shows cross sectional view of upper and lower receptors having a center panel capture feature, in accordance with some embodiments;
- (7) FIG. 6 shows a side view of a window panel configured to be used with the upper and lower receptors of FIG. 5, in accordance with some embodiments;
- (8) FIG. 7 shows a side cross cut view of window opening with the upper and lower window panel receptors installed, and prior to the window panel being installed, wherein the upper and lower window panel receptors have a central tang, in accordance with some embodiments;
- (9) FIG. 8 side cross cut view of window opening with the upper and lower window panel receptors installed, and prior to the window panel being installed, using a mix of receptor styles, in accordance with some embodiments;
- (10) FIG. 9 shows an end-view of a pair of opposing window receptors having substantially identical dimensions, and wherein the window receptor used as the lower window receptor includes a spacer to reduce the effective height in the receptor, in accordance with some embodiments;
- (11) FIG. 10 is a flow chart diagram of a method for installing window panels in building, in accordance with some embodiments;
- (12) FIG. 11 shows an end perspective view of a receptor as shown in FIG. 2, in accordance with some embodiments;
- (13) FIG. 12 shows an end perspective view of a receptor as shown in FIG. 5, in accordance with some embodiments;
- (14) FIG. 13 is a dimensional diagram showing the dimensional relationships between the window panel and the receptors, and between the receptors, in order for the window panel to be able to be inserted between the receptors and to be thereafter captured by the receptors.
- (15) FIG. 14 shows an end view of end view of receptors including an upper receptor and a lower receptor for receiving vinyl-framed window panels, in accordance with some embodiments;
- (16) FIG. 15 shows an elevational view of the inside of a lower receptor as shown in FIG. 14, in accordance with some embodiments;
- (17) FIG. 16 shows a partial end perspective view of a lower receptor as shown in FIG. 14, in accordance with some embodiments;
- (18) FIG. 17 shows a side view of a panel stabilizer for a window panel installed between a pair of receptors, in accordance with some embodiments;
- (19) FIG. 18A shows a perspective view of a panel stabilizer for a window panel installed between a pair of receptors, in accordance with some embodiments;

- (20) FIG. **18B** shows and adjustable panel stabilizer for a range of window panels of different side member widths, in accordance with some embodiments;
- (21) FIG. **19** shows a partial top cross-sectioned view of a window panel installed with a panel stabilizer, in accordance with some embodiments;
- (22) FIG. **20** shows a segmented elevational view of a window panel installed with a panel stabilizer, between receptors, in accordance with some embodiments;
- (23) FIG. **21** shows a perspective view of generalized window panel; and
- (24) FIG. **22** show a fenestration opening having a pre-cast lintel and sill that each have a receptor formed in them, in accordance with some embodiments.

DETAILED DESCRIPTION

(25) While the specification concludes with claims defining the features of the invention that are regarded as novel, it is believed that the invention will be better understood from a consideration of the following description in conjunction with the drawing figures, in which like reference numerals are carried forward. It is to be understood that the disclosed embodiments are merely exemplary of the invention, which can be embodied in various forms.

(26) The present inventive disclosure provides a novel and efficient window installation system generally for glazed panels, such as, for example, commercial fixed windows. In general, a glazed panel is any structure holding one or more glass panes in a frame. This can include moveable windows, sliding glass doors, fixed windows, residential windows, commercial windows, and so on. These glazed panels are installed in fenestration openings in the walls of buildings such that the frame of the panel is held in place and weather sealed. In general, the system and components of the inventive disclosure make the installation of a panel in an opening of a wall greatly simplified and the construction process is substantially reduced in time. FIG. **21** shows a representation of a window panel **2100** as one example of a glazed panel. The window panel **2100** includes one or more panes of glass **2102** captured in a frame that is typically made of aluminum, wood, vinyl, or similar materials. The frame comprises a top member **2104**, a bottom member **2106**, and side members **2108**, **2110**. The portions of the window panel comprised of the top member **2104**, the bottom member **2106**, and side members **2108** and **2110** are referred to herein as ends. Thus, the window panel **2100** has two sets of opposing ends, where a first end, such as the top member **2104**, opposes a second end, such as bottom member **2106**. While an “end” includes the outermost surface (e.g. the top surface **2112**), it also includes a portion of the sides (e.g. side **2114**) of the frame member in a direction parallel to the pane **2102**. Each frame member **2104**, **2106**, **2108**, **2110** will have opposing sides, which can be referred to as the interior and exterior sides, or simply first and second sides. As such, an end in some embodiments can include one to two inches of the side from the outermost surface of that end.

(27) A similar frame arrangement can also be used to capture sliding elements including window and door assemblies that can be opened and closed, as is well known. In the construction of a building, standard sized openings for windows and door can be used, as well as custom designed openings to serve ornamental/architectural purposes. Window panels likewise be constructed to fit into standard or custom sized openings. The frame members **2104-2110** are typically screwed together, and vinyl strips are placed between the glass pane(s) **2102** and the frame members as both a weather seal and to provide some resilient “cushion” to prevent breakage. Other features such as weep holes, for example, that are well known, are also included in the construction of the window panel **2100**.

(28) Conventionally, a window panel such as panel **2100** is lifted into an opening, and upon aligning and placement of any weather sealing or other materials, the window panel is screwed to the wall support portions forming the opening, such as a sill, jambs, and lintel, which form the structural support around the opening in which the window panel is mounted. Once screwed into place, caulking is then applied to seal the panel to the structure. In the construction of buildings with many window panels, such as, for example, hotels and office buildings, the process of lifting a

window panel into, aligning it, and then screwing it into place is time consuming.

(29) To simplify the process of installing window and other types of glazed panels, embodiments of the inventive disclosure provide for installing receptors in a window opening of a wall. The window opening is a fenestration opening intended to receive the window panel. That is, the wall and sills include elements to ensure that the window panel will remain in place given the effects of wind, gravity, rain, etc. Rather than directly attaching the window panel to the walls and sills, an upper window panel receptor is mounted on top portion of the window opening, and a lower window panel receptor is mounted in the lower or bottom portion of the window opening. The upper and lower window panel receptors are sized so that the top of window panel can be inserted into the upper window panel receptor, at a slight angle. Once the window panel is raised into the upper window panel receptor sufficient for the bottom of the window panel to clear the lower window panel receptor, then the bottom of the window panel can be swung over the lower window panel receptor and lowered into the lower window panel receptor. The window panel is held in place by the upper and lower window panel receptors, and the sides can then be caulked to prevent water ingress. As a result, the window panel is “floating” in the receptors because it is not directly attached to any part of the building structure. Using this method and arrangement of components it has been found that a substantial amount of time can be saved installing windows in a building. What would take weeks for a given job to be completed can be done in a matter of hours using the inventive method and components. In addition to ease of installation, vibrations experienced by the building structure are not as tightly coupled to the window glass, giving the inventive window system resistance to such events as earthquakes.

(30) FIG. 1 is an external elevational view of an installed window unit **100** using upper and lower window panel receptors, in accordance with some embodiments. Shown here the external wall **102** of a building having a window opening **104**. The window opening **104** can be a rectangular opening in the external wall **102**, and is bounded by the sides, top, and bottom by the wall **102**. However, other configuration besides rectangular window openings can be used. Further, the sides, top, and bottom of the window opening **104** have been constructed to meet applicable building requirements for window installation. An upper window panel receptor **106** is installed on the top portion of the window opening, and a lower window panel receptor **108** is installed on the bottom portion of the window opening. A window panel is shown installed in the upper and lower window panel receptors **106**, **108**, and includes a glass section **110** that is surrounded by an aluminum structure **112** that holds the glass section **110**. The glass section **110** is typically a glass laminate that is designed to resist breaking due to impact (e.g. “impact glass”). The window panel, as a unit, can be thought of as a frame that includes the glass section **110**. It is constructed according to the size of the window opening **104**, and can therefore be a custom size or a standardized size. While the glass section **110** can be on the order of one quarter inch to one inch thick in most application, the sides of the aluminum structure **112** will extend substantially further, having a front to back (the view here showing the front side) on the order of several inches. The aluminum structure **112** can surround the glass section **110** on all sides/edges of the glass section **110**.

(31) FIG. 2 is a side cross cut view of window opening **104** with the upper and lower window panel receptors **106**, **108** installed, and prior to the window panel being installed, in accordance with some embodiments. Specifically, the view shown here is looking in the direction of line A-A shown in FIG. 1. The middle section has been removed in the view as the side of the window opening is consistent from top to bottom. The external surface **102** of the wall is on the left, and the interior surface **212** is on the right. The upper window panel receptor **106** is mounted on the upper portion **202** of the window opening **104**, and can be seen here to have a “U” shape with a flat base **218** that fits against the surface of the top portion **202** of the window opening **104**, and sides **220**, **222** that extend from the base **218** by a distance **214**. Likewise the lower window panel receptor **108** has a flat base **224** and sides **226**, **228** that extend a distance **216** from the base **224**. The upper and lower window panel receptors **106**, **108** can be attached to the upper and lower portions **202**, **204** of the

window opening **104** using screws **208**. The upper window receptor **106** includes a pair of gasket members **208** on the inside of each of the sides **220**, **222** near the end of the sides **220**, **222** farthest from the base **218**. The gasket members **208** run along the entirety of the sides **220**, **222**. Similarly, the lower window receptor **108** includes gasket members **210** positioned on the inside of sides **226**, **228** which run along the entirety of the sides **226**, **228**. As shown in FIG. 1, the upper and lower window panel receptors span substantially the entire width of the window opening.

(32) The height of the sides **220**, **222**, indicated by distance **214** is substantially greater than that of sides **226**, **228**, indicated by distance **216**. In some embodiments distance **214** can be on the order of two inches, and distance **216** can be on the order of one inch. This allows the top of the window panel to be inserted into the upper window panel receptor **106**, and then raised enough inside the upper window panel receptor **106** so that the bottom of the window panel clears the side **226** of the lower window panel receptor **108**, allowing the bottom of the window panel to be swung, while the top of the window panel remains inserted between the sides **220**, **222** of the upper window panel receptor **106**, such that the bottom of the window panel is then aligned to fit between the sides **226**, **228** of the lower window panel receptor **108**. Once aligned, the window panel is allowed to lower into the lower window panel receptor **108**. The window panel is wider at the top and bottom than the distance between gasket elements **208** in sides **220**, **222** and gasket elements **210** in sides **226**, **228**, but is narrower at the top and bottom between the insides of sides **220**, **222** and **226**, **228**, respectively. This ensures contact between the gasket elements **208**, **210** and the window panel to create a water tight barrier.

(33) The above-described process is illustrated in FIGS. 3A-3C, which show a side view cross cut view of a window opening in which a window panel is installed, in accordance with some embodiments. FIGS. 3A-3C show the view of FIG. 2, but show the entire window opening **104**. In FIG. 3A it can be seen that a window panel **302** is lifted towards window opening **104**. Upper window panel receptor **106** and lower window panel receptor **108** are installed in the window opening **104** at the top and bottom portions, respectively, of the window opening **104** as shown in FIG. 2. The aluminum structure **112**, seen here in a side view, is slightly narrower than the distance between the sides of the upper and lower window panel receptors **106**, **108**. As indicated by arrow **304**, the top of the window panel **302** is inserted into the upper window panel receptor, at a slight angle to vertical. In FIG. 3B the top of the window panel **320** is inserted into the upper window panel receptor **106**, and the bottom of the window panel **312** is raised high enough to be above the top of the sides **226**, **228** (see FIG. 2) of the lower window panel receptor **108**, and the bottom of the window panel **302** is swung in the direction of arrow **306** to be aligned with the lower window panel receptor **108**. In FIG. 3C, the window panel is then lowered so that the bottom of the window panel **302** is inserted between the sides (e.g. **226**, **228**) of the lower window panel receptor **108**. The window panel **302** is sized so that, even though the bottom of the window panel **302** is lowered into the lower window panel receptor **108**, the top of the window panel **302** remains between the sides (e.g. **220**, **222**) of the upper window panel receptor **106**. This is facilitated by the sides of the upper window panel receptor **106** being substantially longer/higher than the side of the lower window panel receptor.

(34) Thus, as shown in FIG. 3C, the window arrangement is substantially the same as shown in FIG. 1. As there are no screws used to fasten the window panel to the window opening, the time to install the window is greatly reduced. The space between the vertical sides of the window panel and the window opening can be filled with backing material and then caulked over on the outside and inside. As a result, there will be a gap between the top of the window panel and the base of the upper window panel receptor, but because of the length/height of the sides of the upper window panel receptor, the top of the window panel remains captured between the sides of the upper window panel receptor.

(35) It will be appreciated by those skilled in the art that the same arrangement can be positioned side to side, as well as top to bottom. That is upper window panel receptor **106** can be positioned

on a side (jamb) and lower window panel receptor **108** can be placed on the opposite side of the window opening. In such an arrangement, FIGS. **3A-3C**, instead of being a side view, could be a top (or bottom) view of the process. Furthermore, it will be understood that the “U” shaped receptors, while shown here as separate elements, can be features built into the sides of the fenestration opening. For example, as shown in FIG. **22**, the lintel and sill of a window opening can be constructed with opposing “U” shaped features to receive, for example, the top and bottom ends of a window panel equivalently to that shown in FIGS. **1-3C**.

(36) As used herein, the term “capture” and “captured” refers to a mechanical arrangement where something is prevented from moving in at least one dimension. Here, the top of the window panel is captured between the sides of the upper window panel receptor, which provide a mechanical barrier to horizontal movement, while still allowing vertical movement. In some contexts the terms “capture” and “captured” can refer to an element being unable to move, such as the glass pane in a window frame; the pane is captured in the frame, and prevented from moving in any direction relative to the frame, even though some frames can move (e.g. portions of the double hung window frame, a sliding glass door).

(37) Although a rectangular window has been shown here as an example, other shapes of windows can be installed similarly. For example, the top and bottom portions of the window opening do not have to be parallel to each other. The same process and components can be used, for example, where the bottom is horizontal and the top of the window opening is at an angle to horizontal. Further, a window opening can include more than one window panel. Multiple window panels can be installed, side by side, across a window opening. In an arrangement where multiple window panels are used and the top of the window opening is at an angle to horizontal, then the smaller window panel units can be slid into position by placing them into the lower window panel receptor and sliding it over into position. This arrangement is shown in FIGS. **4A-4C**. Briefly, in FIG. **4A** a window opening **400** is provided with an upper window panel receptor **402** and a lower window panel receptor **404**. A window panel **406** is to be installed into the window opening **400**.

Accordingly, the window panel **406** can be placed into to window opening **400** at a location where the window opening **400** is taller than the window panel **406**, with the bottom of the window panel being inserted into the lower window panel receptor **404**, as shown in FIG. **4B**. Once inserted into the lower window panel receptor **404**, the window panel can be slid over as indicated by arrow **410** into the position shown in FIG. **4C**. Then subsequently installed window panels can similarly be installed into the window opening, with the exception of the last window panel which will be installed as shown in FIGS. **3A-3C** into window opening **400** (e.g. at the far left side). The finished window installation is shown in FIG. **4D** with additional window panels **412-422** installed in window opening **400**.

(38) FIG. **5** shows side end views of upper and lower receptors having a center panel capture feature, in accordance with some embodiments. As alternative to the arrangement of the receptors of FIGS. **1-4D**, where the sides, at the outside edges of the receptor, are used to capture the window panel, in this alternate configuration one or more centrally positioned tangs or walls are used that interface with and mate into a corresponding slot in the window panel at the top and bottom of the window panel. Specifically, as shown here, there is an upper receptor **502** and a lower receptor **504**. The upper receptor **502** is intended to be attached to the upper portion boundary wall portion of a window opening in a building. Likewise, the lower receptor **504** is intended to be attached to the lower boundary or sill of the window opening in correspondence with the upper receptor **502** such that they are vertically aligned. The upper receptor includes a base **506** that, from a top view is rectangular, and is flat. On the bottom of the base **506** is a centrally located wall **508** that depends from the bottom of the base **506**. The wall **508** can be in the center (from left to right) or off center. The wall **508** can run the length of the base **506** (i.e. into the page), or the wall **508** can run less than the length of the base **506**. The wall **508** has a height **510**, which is the distance from the bottom of the base **506** to the lowermost or distal end of the wall **508**. FIG. **12** shows an end

perspective view of the upper receptor **502**, including holes for attaching the upper receptor **502** to the top of a window opening. The lower receptor **504** has a base **512** that can be otherwise substantially the same size and shape as the base **506** of the upper receptor **502**. The lower receptor **504** includes a wall **516** that extends from a central portion of the base **512** at a top of the base **512**. The wall **514** has a height **516** that is less than the height **510** of wall **508** of the upper receptor **502**. (39) FIG. **6** shows a side view of a window panel **600** configured to be used with the upper and lower receptors **502**, **504** of FIG. **5**, in accordance with some embodiments. The window panel **600** is shown broken in the center to remove redundant matter. the window panel, in generally, comprises a pane of tempered impact glass laminate **606** that is transparent, and that is held and surrounded around the sides of the glass laminate **606** by extruded aluminum members. An inset **622** shows a partial cut-away perspective view of the window panel **600** for reference. A top member **602** and a bottom member couple to side members such as side member **620**, and upper and lower capturing members **608**, **610** and **616**, **618** respectively, that fix the glass laminate **606** in the panel. Although not shown, it is well known that vinyl members can be placed between the glass laminate **606** and the metal members (e.g. **602**, **604**, **608**, **610**, **616**, **618**, and **620**) to prevent metal to glass contact and provide a water/weather seal. As can be seen the top member **602** includes top notch **604** that is generally centrally located along the top member **602** and creates a space or gap that extends from the top of the top member **602** into the top member **602**. Similarly, the bottom member **612** has a similar notch **614** formed in the bottom of the bottom member **612**. Notch **604** is sized to receive wall **508**, and notch **614** is sized to receive wall **514**.

(40) When installing the upper and lower receptors **502**, **504** in a window opening, the upper and lower receptors have to be positioned, vertically, relative to each other such that a window panel installed between them is vertically oriented, as is shown in FIG. **7**. The installation is substantially similar to that shown in FIGS. **3A-3C**. After the upper and lower receptors **502**, **504** are installed, a window panel configured to mount on, and be captured by, the upper and lower receptors **502**, **502**, is raised into the window opening at a slight angle so that the top member **602** can engage the upper receptor **502** such that wall **508** enters into notch **604**. Then the bottom of the panel, and specifically bottom member **612**, can be swung over lower receptor **504** until notch **614** is over wall **514**, and then the window panel can be lowered such that the bottom of bottom member **612** sits on base **512** of the lower receptor, but wall **508** will still be partially in notch **604**, thereby capturing the window panel between the upper and lower receptors **502**, **504**. Notch **604** can have a compressible lining **605** on each side of the vertical walls of the notch **604** that compress as the window panel **600** is raised into place, and retain contact with the wall **508** to prevent water intrusion. Once the window panel **600** is in place between the upper and lower receptors **502**, **504**, there will be a gap between the top of top member **602** and the base **506** of the upper receptor that can be sealed and caulked.

(41) FIG. **7** shows a side cross cut view of window opening **700** with the upper and lower receptors **502**, **504** installed, and prior to the window panel being installed, wherein the upper and lower receptors **504**, **506** each have a central wall **508**, **514**, respectively, in accordance with some embodiments. The upper receptor **502** can be held in place in the top wall **702** bordering the window opening with fasteners such as screws **708**. There can be rows of screws along the length of the upper receptor, which extends into and out of the page (see, e.g., FIG. **12**). Likewise, the lower receptor **504** can be attached to the sill **704** by fasteners such as screws **708**. The jamb **706** form the side of the window opening. Window panel **600** can be inserted into the window opening by aligning notch **604** with wall **508**, and lifting the window panel such that wall **508** extends into notch **604** sufficient such that the bottom member **612** can be swung over wall **514** of the lower receptor until the wall **514** is aligned with notch **614** of the bottom member **612** of the window panel **600**, wherein the window panel **600** can be lowered such that the bottom of bottom member **612** rests on the base **512** of the lower receptor, and the wall **514** of the lower receptor is captured in the notch **614** of the bottom member **612** of the window panel **600**. However, since wall **508**

extends further from the base **506** of the upper receptor **502** than wall **514** extends from the base **512** of the lower receptor **504**, the wall **508** of the upper receptor will remain partially captured in notch **604** of the top member **602** of the window panel. As a result, the window panel **600** is then secured at the top and bottom. The upper and lower receptors **106**, **108** and **502**, **504** can be secured well enough in the structure that additional fasteners are not needed at the sides, between the jamb and the window panel. Only weather sealing is necessary on the sides. Weather seals such as vinyl strips **802** can be present on the base **512** of the lower receptor, which are compressed to form a water tight seal between the top of the base **512** and the bottom of the bottom member **612**.

(42) FIG. **8** side cross cut view of window opening **800** with the upper and lower window panel receptors installed, and prior to the window panel being installed, using a mix of receptor styles, in accordance with some embodiments. Specifically, the arrangement used here shows a combination of using upper receptor **106** that is “U”-shaped as in FIG. **2**, with lower receptor **504**, as in FIG. **7**, which has the central wall **514** or lengthwise ridge. The principle remains the same; the upper receptor **106** has a “capture length” of the sides **220**, **222** that is taller in distance **214** than the height of wall **514**. This allows the top of a window panel to be inserted into the upper receptor **106** such that the bottom of the window panel can pass over the wall **514**. A window panel for use with this arrangement would have a top member that is wide enough allow the top of the window panel to be raised into the upper receptor, but not so narrow as to not compress weather stripping members **208**.

(43) As shown in FIG. **13**, a window panel **1302** has a height **1312**. The height **1312** of the window panel **1302** is less than the distance **1318** between the upper and lower receptors **1304**, **1308**, meaning specifically the distance between the bottom of the base of the upper receptor **1304** and the top of the base of the lower receptor **1308**. Further, the height **1312** of the window panel **1302** is also less than the distance **1316** between the top of the wall or sides of the lower receptor **1308** and the base of the upper receptor **1304** facing the lower receptor **1308**. However, the height **1312** of the window panel **1302** is more than the distance **1314** between the bottom of the wall or sides of the upper receptor **1304** and the base of the lower receptor **1308** on which the window panel **1302** will rest. So long as these dimensional relationships are satisfied, the window panel **1302** can be raised into position between the upper and lower receptor **1304**, **1308**, swung over the bottom receptor **1308**, and then lowered onto the lower receptor **1308** such that the top of the window panel **1302** is captured by the upper receptor **1304**.

(44) FIG. **9** shows an end-view **900** of a pair of opposing window receptors **902a**, **902b** having substantially identical dimensions, and wherein the window receptor **902b** used as the lower window receptor includes a spacer **904** to reduce the effective height **906** in the receptor, in accordance with some embodiments. Upon inserting a window panel between the upper and lower receptors **902a**, **902b**, the bottom of the window panel will rest on the spacer **904**. The presence of the spacer reduces the effective height of the lower receptor **902b** from that of **908** to **906**, which is less than height **908**. Thus, the spacer **904** effectively lowers the capture height of the lower receptor **902b**. This allows the use of only one receptor, which reduces the inventory and supply chain needs such that only one receptor dimension is needed, and an inexpensive spacer can be used to create the lower receptor.

(45) In general, the window receptors, or simply receptors, have a capture feature that engages with a corresponding feature of the window panel to prevent movement in or out of the window opening. The capture feature can be, for example, the sides **220**, **222** of upper receptor **106** or sides **226**, **228** of lower receptor **108**, which engage the sides of the top and bottom frame members of a window panel. The central wall **508** of receptor **502** is a capture feature that engages notch **604**. These elements can be equivalently reversed such that the capture feature of a receptor is a notch which engages a wall or tang extending from the corresponding end of a window panel. The capture features can be mixed such that the opposing receptors have different capture features. The inventive embodiments only require that a maximum distance between the opposing receptors (e.g.

base to base) is greater than the end to end distance across the window frame, and that the distance between the capture features of the opposing receptors, at their closest points across the window opening, is less than the distance across the window frame in a direction between the opposing receptors. This relationship applies whether the receptors are mounted in the top and bottom of the window opening, or on the vertical sides of the window opening.

(46) FIG. **10** is a flow chart diagram of a method **1000** for installing window panels in building, in accordance with some embodiments. The method **1000** applies equally to other products, such as, for example, sliding glass doors, that was contained in a panel assembly. Thus, a window panel is an assembly of glass pane products contained in a frame of, typically, extruded aluminum or equivalent members. Prior to the present invention, window panels have been attached to receptors using fasteners. The present invention, however, eliminates the need to join the window panel to the receptors. The method **1000** starts **1002** by providing upper and lower receptors that are sized, lengthwise to the width or distance across the top and bottom of a window opening. The window receptors each have differing capture heights; the lower receptor will have a lower/shorter capture height than the upper receptor. The window panel that is to be installed in the receptors is sized according to the dimensional relationships shown in FIG. **13**. In steps **1004**, **1006** the upper and lower receptors are installed in the window opening. The upper receptor is attached to the wall structure at the top of the window opening and the lower receptor is attached to the wall structure (e.g. the sill) at the bottom of the window opening. The upper and lower receptors are vertically aligned to capture the window panel between them. In step **1008** the window panel is raised in a substantially vertical position, but at a slight angle to vertical such that the top of the window panel is matingly engaged with the upper receptor. The top of the window panel is raised into engagement with the upper receptor higher than it will sit at the end of the method so that the bottom of the window panel can, in step **1010**, be moved over the lower receptor. Then in step **1012**, the window panel is lowered into mating engagement with the lower receptor. So long as the dimensional relationships of FIG. **13** are met, the top of the window panel will remain captured by the upper receptor. The in step **1014** the gaps between the vertical sides of the window panel and walls structure at the sides of the window opening can be sealed and caulked, and the method is then complete **1016**.

(47) FIG. **14** shows an end view of end view of receptors including an upper receptor **1400** and a lower receptor **1402** for receiving vinyl-framed window panels, in accordance with some embodiments. Similar to the receptors previously shown and described, upper receptor **1400** and lower receptor **1402** are used together to capture a window panel in an installation, and to hold the window panel in place permanently. The receptors **1400**, **1402** are sized to allow an appropriately sized window panel to be lifted into the upper receptor **1400** at a slight angle such that the top of the window panel is in the receptor **1400**, whereupon the lower end of the window panel is moved over the lower receptor **1402** and then the window panel is lowered into the lower receptor **1402**.

(48) The upper receptor **1400** has a base **1406** and opposing walls **1408**, **1410** that extend from the long sides of the base **1406** and have a height indicated by arrow **1423**. The bottom **1418** of each of the walls **1408**, **1410** include an offset portion that turns inward toward the opposing wall a distance indicated by arrows **1416**, and upward a height indicated by arrows **1420**. These bottom features create the offset portion that is offset from the inner side of the walls **1408**, **1410** and allow the top of a window panel to be inserted at an angle indicated by lines **1412**. Upon being inserted, the window panel, if inserted as indicated by lines **1412**, will be closest to the bottom inner edge **1413** of the offset portion of wall **1408**, and the upper inner edge **1415** of offset portion of the wall **1410**, which is slightly more distance than the distance directly across, horizontally, between corresponding points on the two walls **1408**, **1410**. When the window panel is sufficiently inserted between the walls **1408**, **1410**, the inner faces of the bottoms **1418** of the walls **1408**, **1410** will bear against the sides of the upper frame member of the window panel, which can be made of vinyl. The design of the upper receptor **1400** obviates the need for a vinyl bead on the inside of

walls **1408**, **1410** as a weather seal.

(49) The lower receptor **1402** likewise includes a base **1432** and has opposing walls **1424**, **1426** that extend a height **1428** that is less than the height **1423** of the walls **1408**, **1410** of the upper receptor **1400**. The height difference allows for the sizing of the window panel to ensure it remains captured in the upper receptor **1400** when the window panel is seated in the lower receptor **1402**. The width between the inside of the walls **1424**, **1426** can be about the same as the width or distance between the bottom inner edges **1413** of the bottoms of the walls **1408**, **1410** of the upper receptor **1400** since the bottom of the window panel does not have to be angled into the lower receptor **1402**. On the inside surfaces of the walls **1424**, **1426** of the lower receptor **1402** are linear ridges **1430** that extend horizontally along the walls. The ridges **1430** are designed to engage the bottom of the window panel frame and provide a weather seal in embodiments where the window panel frame is made of vinyl. FIG. **15** shows an elevational view of the inside of a lower receptor **1402**, and FIG. **16** shows a partial end perspective view of a lower receptor **1402**. In FIG. **15** the base **1432** is cut to show the ridges **1430**. As shown here the ridges **1430** have a triangular profile, but can be shaped differently and achieve a similar effect.

(50) FIG. **17** shows a side view of a panel stabilizer **1700** for a window panel installed between a pair of receptors, and FIG. **18A** shows a perspective view of the panel stabilizer **1700**. Since window panels experience pressure resulting from wind, it is expected that larger window panels that are captured between opposing receptors may experience a significant amount of bowing at the middle of the panel in response to high winds. This is of concern particularly in multistory buildings such as hotels, office buildings, and high rise residential buildings where the upper floors may not be shielded from wind. To prevent bowing, a pair of panel stabilizers such as stabilizer **1700** can be used to anchor the mid-section of the window panel in the window opening. The stabilizer **1700** includes a base **1702** from which a pair of catch features **1704**, **1706** extend from. The catch features **1704**, **1706** provide flat faces that are perpendicular to the base **1702** that are separated by a width **1708** that is sized to receive a side frame member of a window panel. That is, width **1708** is sized to be just large enough to fit over the side member of a window panel frame. Different sized side frame members will require correspondingly sized stabilizers. The end catch feature **1704** can be fixed to the base **1702** at a distal end of the base **1702**, and will be on the outside of the window panel upon installation of the window panel. The inside catch feature **1706** extends from the base **1702** in a more central position on the base **1702**, and will be positioned on the inside of the window panel when installed.

(51) The panel stabilizer **1700** is placed over the side frame member (e.g. **2109**, **2110**) of a window panel such that the side frame member fits between the catch features **1704**, **1706** and against the base **1702** between the catch features **1704**, **1706**. When installed, the stabilizer **1700** will be between the window panel and the jamb, and the stabilizer can be screwed into place by installing a screw through screw opening **1710**. FIG. **19** shows a partial top cross-sectioned view of a window panel **1902** installed with a panel stabilizer **1700**, in accordance with some embodiments. The window panel **1902** can be substantially similar to window panel **2100** of FIG. **21**, and includes one or more glass panes **1904**, a bottom frame member **1903**, and a side frame member **1906**. The side frame member fits between the catch features **1704**, **1706**, and the stabilizer **1700** is secured to the jamb of the wall **1900** with a screw **1908** that passes through a screw hole in the stabilizer **1700**. A corresponding stabilizer is likewise installed on the opposite side of the window panel to the opposite jamb.

(52) FIG. **20** shows a segmented elevational view, from the outside, of the window panel of FIG. **19** installed with a panel stabilizer, between receptors in accordance with some embodiments. A wall **1900** includes an opening into which a window panel is installed and secured using a panel stabilizer. The view has been segmented to show the top portion **2006**, a middle portion **2008**, and a bottom portion **2010** of the assembly, with the interim portions removed in order to show the details. An upper receptor **2002** is installed along the top of the window opening, and a lower

receptor **2004** is installed along the bottom of the window opening on the sill. The upper frame member **1910** of the window panel is captured in the upper receptor **2002**, and the lower frame member **1903** of the window panel is captured in the lower receptor **2004**, using, for example, the process of FIGS. 3A-3C. The side frame member **1906** forms the vertical side of the window panel between the top frame member **1910** and the lower frame member **1906**, and the glass pane or panes **1906** are captured in the frame formed by the frame members **1903**, **1906**, **1910** (and the opposite side frame member not shown here). The end catch feature **1704** of the stabilizer can be seen on the outside of the side frame member **1906**. The opposing catch feature **1706** is on the inside of the side frame member. When wind is incident on the window panel, the stabilizer prevents the window frame from bowing due to wind pressure. As wind exerts pressure on the window, catch feature **1706** bears against the inside of the side frame member **1906** to prevent inward movement of the window frame at the side of the window frame. A corresponding stabilizer installed on the opposite side of the window panel likewise prevent movement/deflection of the window frame. Similarly, the window is prevented from bowing outward due to catch feature **1704** of the stabilizer when the window is subjected to a low external pressure.

(53) FIG. 18B shows an arrangement of a stabilizer **1800** that can be used with a variety of side frame member widths, in accordance with some embodiments. The stabilizer **1800** includes a base **1802** having an outside catch feature **1804** at a distal end of the base **1802**. The base **1802** further includes a slot **1816** in which a sliding tang **1810** sits, which can be moved along the slot **1816**. A moveable catch feature **1806** is attached to the tang **1810** and can be moved in order to accommodate a variety of sizes of window frame side members. In installation, the base **1802** is positioned on the side of a window panel. In fact, the base **1802** can be placed into position after the window panel is installed between the upper and lower receptors by sliding the base between the window panel and the jamb with the catch feature **1804** on the outside of the window panel. Once in place, the base can be secured to the jamb by placing screws into screw holes **1812**. Once the base **1802** is secured, then the tang **1810** can be placed in the slot **1816** and positioned so that catch feature **1806** bears against the inside of the window panel side frame member, whereupon the tang can then be secured in place by installing a screw through screw hole **1814** on the tang **1810**.

(54) FIG. 22 show a side cut-away view of a wall **2200** in which a fenestration opening **2202** is formed and provided with pre-cast lintel **2206** and sill **2208** members. The jamb **2204** forms the side of the fenestration opening **2202**. The lintel **2206** and sill **2208** members can be pre-cast of a concrete or similar compound and mounted in place to form the top and bottom of the fenestration opening **2202**. The lintel **2206** includes a receptor channel **2210**, and the sill **2208** includes a receptor channel **2212**. The depth or height of the lintel receptor channel **2210** is greater than that of the sill receptor channel **2212**. As such the pre-cast lintel **2206** and sill **2208** are functionally equivalent to the upper and lower receptors **106**, **108** of FIGS. 1-3C. The sill **2208** can be cast to include weep channels **2214** to allow any water that may overcome weather sealing measures (e.g. caulk) from entering the structure. The widths of the lintel and sill receptor channels **2210**, **2212** can be sized to receive the top and bottom ends of a glazed panel, which is inserted using the a similar method as that shown in FIGS. 3A-3C.

(55) A glazed panel installation system and method, has been disclosed that substantially reduces the time needed to install glazed panels. The system uses receptors that are attached opposite sides of a fenestration opening which capture a glazed panel in place without the need to attach the glazed panel to the walls or sills forming the fenestration opening. This allows an advance crew to install the receptors in the fenestration openings first, prior to the glazed panels arriving on site. The number of people needed to install receptors is smaller than the number of people needed to install glazed panels in the conventional manner, where each glazed panel is lifted into place, secured with fasteners, and then inspected, and finally to have to screw covers put in place. Instead, the inventive disclosure allows glazed panels to be put in place in relatively rapid succession without the need for fastener inspection because no additional fasteners are used when the glazed

panels are installed. Furthermore, because the glazed panel is not directly coupled to the building structure, the effects of vibrations experienced by the building structure are less evident at the glass due to the floating of the window panel between the receptors.

Claims

1. A system for installing a glazed panel in a fenestration opening, comprising: a first receptor fixedly mounted on a first side of the fenestration opening and which spans a width of the first side of the fenestration opening, the first receptor being configured to receive a first end of the glazed panel and having a first base and a first capture feature that extends from the first base, a first capture distance being defined between a distal end of the first capture feature, that is furthest from the first base, and the first base; a second receptor fixedly mounted on a second side of the fenestration opening opposite the first side of the fenestration opening and which spans a width of the second side of the fenestration opening, the second receptor being configured to receive a second end of the glazed panel and having a second base and a second capture feature that extends from the second base, a second capture distance being defined between a distal end of the second capture feature, that is furthest from the second base, and the second base; wherein the first capture distance is greater than the second capture distance, and wherein the first receptor and the second receptor are oriented to hold the glazed panel in a vertical orientation and wherein the first receptor and the second receptor are configured to hold the glazed window panel fixed in place upon the glazed panel being installed in the first and second receptors; and wherein the first capture feature comprises a first wall on first side of the first base and a second wall on a second side of the first base, and wherein a distance between the first side and the second side is selected to hold a first end of a glazed panel between the first side and the second side.
2. The system of claim 1, wherein the second end of the glazed panel rests against the base of the second receptor and the first end of the glazed panel is separated from the base of the first receptor.
3. The system of claim 2, wherein a distance across the glazed panel from the first end to the second end is less than a distance between the first base and the second base and more than a distance between the distal end of the first capture feature and the distal end of the second capture feature.
4. The system of claim 2, further comprising a panel stabilizer having a capture feature to capture a third side of the glazed panel, and wherein the panel stabilizer is fixedly coupled to the third side of the fenestration opening.
5. The system of claim 1, wherein the first wall has an offset portion that extends toward the second wall and the second wall has an offset portion that extends toward the first wall.
6. The system of claim 1, wherein the second capture feature comprises a first wall on first side of the second base and a second wall on a second side of the second base, and wherein a distance between the first side and the second side is selected to hold a second end of a glazed panel between the first side and the second side.
7. The system of claim 1, wherein the first side of the fenestration opening is a top side of the fenestration opening, and the second side of the fenestration opening is a bottom side of the fenestration opening.
8. The system of claim 1, wherein the first side of the fenestration opening is a first vertical side of the fenestration opening, and the second side of the fenestration opening is a second vertical side of the fenestration opening.
9. A fixed window system, comprising: a first receptor fixedly mounted on a first side of the fenestration opening and which spans a width of the first side of the fenestration opening, the first receptor having a first base and a first capture feature that extends from the first base, a first capture distance being defined between a distal end of the first capture feature, that is furthest from the first base, and the first base; and a second receptor fixedly mounted on a second side of the fenestration

opening opposite the first side of the fenestration opening and which spans a width of the second side of the fenestration opening, the second receptor having a second base and a second capture feature that extends from the second base, a second capture distance being defined between a distal end of the second capture feature, that is furthest from the second base, and the second base; a glazed panel having a frame installed between the first receptor and the second receptor such that a first end of the frame is captured by the capture feature of the first receptor, a second end of the frame that is opposite the first end is captured by the capture feature of the second receptor, and wherein the frame is fixed in place in the first and second receptors; wherein the first capture distance is greater than the second capture distance, and wherein the first receptor and the second receptor are oriented to hold the glazed panel in a vertical orientation; and wherein the first capture feature comprises a first wall on first side of the first base and a second wall on a second side of the first base, and wherein a distance between the first side and the second side is selected to hold the first end of the glazed panel between the first side and the second side.

10. The fixed window system of claim 9, wherein caulk is applied in a gap between the frame and first receptor and a gap between the frame and the second receptor.

11. The fixed window system of claim 9, wherein the frame is sized such that the first receptor, second receptor, and the frame cover the entire fenestration opening.

12. The window system of claim 9, wherein the first side of the fenestration opening is a top side of the fenestration opening, and the second side of the fenestration opening is a bottom side of the fenestration opening.

13. The window system of claim 9, wherein the first side of the fenestration opening is a first vertical side of the fenestration opening, and the second side of the fenestration opening is a second vertical side of the fenestration opening.

14. A system for installing a glazed panel in a fenestration opening, comprising: a first receptor fixedly mounted on a first side of the fenestration opening and which spans a width of the first side of the fenestration opening, the first receptor being configured to receive a first end of the glazed panel and having a first base and a first capture feature that extends from the first base, a first capture distance being defined between a distal end of the first capture feature, that is furthest from the first base, and the first base; a second receptor fixedly mounted on a second side of the fenestration opening opposite the first side of the fenestration opening and which spans a width of the second side of the fenestration opening, the second receptor being configured to receive a second end of the glazed panel and having a second base and a second capture feature that extends from the second base, a second capture distance being defined between a distal end of the second capture feature, that is furthest from the second base, and the second base; wherein the first capture distance is greater than the second capture distance, and wherein the first receptor and the second receptor are oriented to hold the glazed panel in a vertical orientation and wherein the first receptor and the second receptor are configured to hold the glazed window panel fixed in place upon the glazed panel being installed in the first and second receptors; and wherein the second capture feature comprises a first wall on first side of the second base and a second wall on a second side of the second base, and wherein a distance between the first side and the second side is selected to hold a second end of a glazed panel between the first side and the second side.

15. The system of claim 14, wherein the second end of the glazed panel rests against the base of the second receptor and the first end of the glazed panel is separated from the base of the first receptor.

16. The system of claim 15, wherein a distance across the glazed panel from the first end to the second end is less than a distance between the first base and the second base and more than a distance between the distal end of the first capture feature and the distal end of the second capture feature.

17. The system of claim 15, further comprising a panel stabilizer having a capture feature to capture a third side of the glazed panel, and wherein the panel stabilizer is fixedly coupled to the third side of the fenestration opening.

18. The system of claim 14, wherein the first capture feature comprises a first wall on first side of the first base and a second wall on a second side of the first base, and wherein a distance between the first side and the second side is selected to hold a first end of a glazed panel between the first side and the second side.

19. The system of claim 14, wherein the first side of the fenestration opening is a top side of the fenestration opening, and the second side of the fenestration opening is a bottom side of the fenestration opening.

20. The system of claim 14, wherein the first side of the fenestration opening is a first vertical side of the fenestration opening, and the second side of the fenestration opening is a second vertical side of the fenestration opening.
