

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12385687
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Lee; Sanggyun et al.

Refrigerator

Abstract

A refrigerator comprises: a cabinet including a storage space; a hinge bracket coupled to the cabinet; a door which is rotatably coupled to a shaft included in the hinge bracket and opens/closes the storage space; and an auto-closing device installed at the door in a position spaced apart from the center line of rotation of the door, the auto-closing device operating such that same acts with the hinge bracket while the door is being closed, thereby causing the door to automatically be closed. The auto-closing device may include a lever and an elastic member for elastically supporting the lever. The hinge bracket may include a contact surface which is brought into contact with the lever while the door is being closed. The contact surface may be formed such that, with reference to the front surface of the cabinet, while a contact part of the lever moves along one portion of the contact surface, the contact part approaches the front surface of the cabinet, and, while the contact part moves along another portion of the contact surface, the contact part becomes more distant from the front surface of the cabinet.

Inventors:	Lee; Sanggyun (Seoul, KR), Lee; Younseok (Seoul, KR), Dong; Yongwon (Seoul, KR)
Applicant:	LG ELECTRONICS INC. (Seoul, KR)
Family ID:	80117461
Assignee:	LG ELECTRONICS INC. (Seoul, KR)
Appl. No.:	18/020009
Filed (or PCT Filed):	July 23, 2021
PCT No.:	PCT/KR2021/009558
PCT Pub. No.:	WO2022/030833
PCT Pub. Date:	February 10, 2022

Prior Publication Data

Document Identifier

US 20230288129 A1

Publication Date

Sep. 14, 2023

Foreign Application Priority Data

KR

10-2020-0099091

Aug. 07, 2020

Publication Classification

Int. Cl.: F25D23/02 (20060101); E05F1/12 (20060101); F16C11/04 (20060101)

U.S. Cl.:

CPC F25D23/028 (20130101); E05F1/1207 (20130101); F16C11/04 (20130101); E05Y2900/31 (20130101)

Field of Classification Search

CPC: F25D (23/028); F25D (2323/024); F16C (11/04); E05F (1/1207); E05Y (2900/31)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5138743	12/1991	Hoffman	16/303	E05F 1/1223
10584524	12/2019	Fang et al.	N/A	N/A
2006/0232176	12/2005	Kim	312/401	E05D 3/12
2013/0264930	12/2012	Kim et al.	N/A	N/A
2023/0304726	12/2022	Lee et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103363755	12/2012	CN	N/A
106766595	12/2016	CN	N/A
102013224272	12/2014	DE	N/A
2650626	12/2012	EP	N/A
4194781	12/2022	EP	N/A
2001-173306	12/2000	JP	N/A
10-0874633	12/2007	KR	N/A
10-2015-0047976	12/2014	KR	N/A
10-1910655	12/2017	KR	N/A
10-1978452	12/2018	KR	N/A

Primary Examiner: Hansen; James O

Attorney, Agent or Firm: Bryan Cave Leighton Paisner LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application is the National Stage Application of International Application No. PCT/KR2021/009558, filed on Jul. 23, 2021, which claims the benefit of Korean Application No. 10-2020-0099091, filed on Aug. 7, 2020, the contents of which are all hereby incorporated by reference herein in their entirety.

TECHNICAL FIELD

(2) The present disclosure relates to a refrigerator.

BACKGROUND ART

(3) In general, refrigerators are home appliances for storing foods at low temperature in an inner storage space covered by a refrigerator door. Here, the inside of the storage space is cooled using cool air that is generated by being heat-exchanged with a refrigerant circulated in a refrigeration cycle to store the foods in an optimal state.

(4) The refrigerator may be independently placed in a kitchen or living room or may be accommodated in a space defined by a furniture cabinet of the kitchen.

(5) As the refrigerator increases in size more and more, and multi-functions are provided to the refrigerator due to dietary life changes and pursues of high quality, refrigerators of various structures in consideration of user convenience are being brought to the market.

(6) The refrigerator may include a cabinet defining a storage space and a door connected to the cabinet and having the storage space. A door storage portion for storing food may be provided in the door. When the door storage portion is provided, a lot of force is required for the user to close the door due to weight of the food stored in the door storage portion as well as a weight of the door itself.

(7) In order for the user to easily close the door, recently, the refrigerator is provided with a hinge device for automatically closing the door when the door is closed at a certain angle.

(8) An automatic return hinge device including a restoring device is disclosed in Korean Patent Registration No. 10-0874633.

(9) In the document, the hinge device may include a body, a clutch device mounted inside the body, a shaft coupled to pass through the clutch device, and a first spring that transmits restoring force to the shaft when the door is closed.

(10) The shaft serves to provide a rotational center of the door, and the first spring in the form of a coil spring is disposed in a direction parallel to the shaft.

(11) In the case of the document, since the restoration device is disposed in a direction parallel to the rotational center of the door, a space for positioning the restoration device as high as the height of the restoration device is required in the door, and thus, there is a restriction in installing the restoration device.

(12) In addition, the position of the rotational center of the door may vary according to a thickness of the door, and when the thickness of the door becomes thin, it may be impossible to install the restoration device in a direction parallel to the rotational center of the door.

SUMMARY

(13) Embodiments provide a refrigerator provided with an auto closing device installed in a door regardless of a thickness of a door to provide closing force of the door.

(14) Additionally or optionally, embodiments also provide a refrigerator in which a phenomenon, in which when a door is closed, the door opens again due to excessive closing force of the door, which is prevented from occurring by an auto closing device.

(15) In one embodiment, a refrigerator includes: a cabinet having a storage space; a hinge bracket coupled to the cabinet; a door rotatably coupled to a shaft provided on the hinge bracket and

configured to open and close the storage space; and an auto closing device installed in the door at a position spaced apart from a rotational center line of the door and configured to interact with the hinge bracket in a process of closing the door to automatically close the door. Thus, closing force may be provided to the door by using an auto closing device regardless of a thickness of the door. (16) The auto closing device may include a lever and an elastic member configured to elastically support the lever. The hinge bracket may include a contact surface that is in contact with the lever in the process of closing the door.

(17) The contact surface may be provided so that, while a contact portion of the lever moves along a portion of the contact surface, the contact portion gets closer to the front surface of the cabinet, and while the contact portion moves along the other portion of the contact surface, the contact portion is away from the front surface of the cabinet. Thus, when the door is closed by the auto closing device, a phenomenon in which the door is closed and then opened again due to excessive closing force of the door may be prevented.

(18) When a line perpendicular to the front surface of the cabinet while passing through the rotational center line of the door is a virtual line, the contact surface may include: a first surface inclined in a direction that is away from the virtual line as the first surface is closer to the front surface of the cabinet; a second surface inclined in a direction that gets closer to the virtual line as the second surface is closer to the front surface of the cabinet; and a third surface configured to extend in the direction that gets closer to the virtual line as the third surface further is away from the front surface of the cabinet.

(19) While the contact portion of the lever moves along the first surface and the second surface, the contact portion may get closer to the front surface of the cabinet, and while the contact portion of the lever moves along the third surface, the contact portion may be away from the front surface of the cabinet.

(20) When the door is in the closed state, the contact portion of the lever may be maintained in a state of being in contact with the third surface.

(21) While the contact portion of the lever moves along the first surface and the second surface, the contact portion may get closer to a rear surface of the door, and while the contact portion of the lever moves along the third surface, the contact portion may be away from the rear surface of the door.

(22) While the contact portion of the lever moves along the first surface, the contact portion may get closer to a rear surface of the door, while the contact portion of the lever moves along a portion of the second surface, the contact portion may get closer to the rear surface of the door, while the contact portion of the lever moves along a remaining portion of the second surface, the contact portion may be away from the rear surface of the door, and while the contact portion of the lever moves along the third surface, the contact portion may be away from the rear surface of the door.

(23) When the door rotates in a first direction to be closed, while the contact portion of the lever moves along the first surface and the second surface, the lever may rotate in a second direction opposite to the first direction, and while the contact portion of the lever moves along the third surface, the lever may rotate in the first direction.

(24) When the door rotates in a first direction to be closed, while the contact portion of the lever moves along the first surface, the lever may rotate in a second direction opposite to the first direction, while the contact portion of the lever moves along a portion of the second surface, the lever may rotate in the second direction, while the contact portion of the lever moves along a remaining portion of the second surface, the lever may rotate in the first direction, and while the contact portion of the lever moves along the third surface, the lever may rotate in the first direction.

(25) When the door rotates in a direction to be closed, while the contact portion of the lever moves along the first surface, the lever may rotate in a second direction opposite to the first direction, while the contact portion of the lever moves along the second surface, the lever may rotate in the first direction, and while the contact portion of the lever moves along the third surface, the lever

may rotate in the first direction.

(26) The lever may rotate based on a rotational center line spaced apart from the rotational center line of the door. In the state in which the door is closed, the rotational center line of the lever may be disposed closer to the front surface of the cabinet than the rotational center line of the door.

(27) The elastic member may be a torsion spring.

(28) The lever may include a roller rotatably coupled to the lever, and the contact portion may be the roller.

(29) The auto closing device may include: a body configured to accommodate the elastic member; and a connector connected to the elastic member within the body, wherein the connector may include a lever coupling portion configured to extend to the outside of the body, and the lever may be coupled to the lever coupling portion. The connector may rotate together with the lever.

(30) The elastic member may include: a body portion provided by winding a wire several times; and an extension portion configured to extend from the body portion, wherein the extension portion may be coupled to the connector at a position spaced apart from a rotational center line of the connector.

(31) In another embodiment, a refrigerator includes: a cabinet having a storage space; a hinge bracket coupled to the cabinet; a door rotatably coupled to a shaft provided on the hinge bracket and configured to open and close the storage space; and an auto closing device installed in the door at a position spaced apart from a rotational center line of the door and configured to interact with the hinge bracket in a process of closing the door to automatically close the door, wherein the auto closing device includes a lever and an elastic member configured to elastically support the lever, and the hinge bracket includes a contact surface that is in contact with the lever in the process of closing the door, wherein the contact surface is provided so that, while a contact portion of the lever moves along a portion of the contact surface, the contact portion gets closer to the rear surface of the door, and while the contact portion moves along the other portion of the contact surface, the contact portion is away from the rear surface of the door.

(32) In further another embodiment, a refrigerator includes: a door; and an auto closing device configured to provide closing force to the door, wherein the auto closing device includes: a lever; and an elastic member configured to elastically support the lever.

(33) The hinge bracket may include a contact surface that is in contact with the lever in the process of closing the door. In the process of closing the door, while the contact portion of the lever moves along a portion of the contact surface, elastic force accumulated in the elastic member may increase, and while the contact portion of the lever moves along the other portion of the contact surface, the elastic force accumulated in the elastic member may decrease. In a section in which the elastic force of the elastic member decreases, the elastic force of the elastic member may act as closing force of the door.

(34) When a line perpendicular to the front surface of the cabinet while passing through the rotational center line of the door is a virtual line, the contact surface may include: a first surface inclined in a direction that is away from the virtual line as the first surface is closer to the front surface of the cabinet; a second surface inclined in a direction that gets closer to the virtual line as the second surface is closer to the front surface of the cabinet; and a third surface configured to extend in the direction that gets closer to the virtual line as the third surface is further away from the front surface of the cabinet.

(35) In the process of closing the door, when the contact portion of the lever moves along the first surface and the second surface, the elastic force accumulated in the elastic member may increase, and when the contact portion of the lever moves along the third surface, the elastic force accumulated in the elastic member may decrease. When the door is in the closed state, the contact portion of the lever may be maintained in a state of being in contact with the third surface.

(36) In the process of closing the door, when the contact portion of the lever moves along the first surface, the elastic force accumulated in the elastic member may decrease, and when the contact

portion of the lever moves along a portion of the second surface, the elastic force accumulated in the elastic member may further increase, and also, when the contact portion of the lever moves along the other portion of the second surface, the elastic force accumulated in the elastic member may decrease, and when the contact portion of the lever moves along the third surface, the elastic force accumulated in the elastic member may decrease.

(37) In the process of closing the door, when the contact portion of the lever moves along the first surface, the elastic force accumulated in the elastic member may increase, when the contact portion of the lever moves along the second surface, the elastic force accumulated in the elastic member may decrease, and when the contact portion of the lever moves along the third surface, the elastic force accumulated in the elastic member may decrease.

(38) The elastic force accumulated in the elastic member in the state in which the door is closed may be equal to or greater than that accumulated in the elastic member in the state in which the lever is spaced apart from the contact surface by the opening of the door.

(39) In further another embodiment, a refrigerator includes: a cabinet having a storage space; a hinge bracket coupled to the cabinet; a door rotatably coupled to a shaft provided on the hinge bracket and configured to open and close the storage space; and an auto closing device installed in the door at a position spaced apart from a rotational center line of the door and configured to interact with the hinge bracket in a process of closing the door to automatically close the door, wherein the auto closing device comprises a lever configured to rotate based on a rotational center line spaced apart from a rotational center line of the door, and an elastic member configured to increase or decrease in elastic force accumulated while the lever rotates.

(40) In the state in which the door is closed, the rotational center line of the door may be disposed closer to a front surface of the door than a rear surface of the door, and the rotational center line of the lever may be disposed closer to the rear surface of the door than the rotational center line of the door.

(41) The hinge bracket may include a contact surface that is in contact with the lever in the process of closing the door.

(42) The contact surface may be provided so that, while a contact portion of the lever moves along a portion of the contact surface, the contact portion gets closer to the front surface of the cabinet, and while the contact portion moves along the other portion of the contact surface, the contact portion is away from the front surface of the cabinet.

(43) In the state in which the door is closed, a portion of the contact surface, which is in contact with the lever, may be disposed closer to the front surface of the door than the rotational center line of the lever.

(44) According to the proposed embodiments, since the auto closing device is disposed to be spaced apart from the rotational center line of the door, even when the thickness of the door is reduced, the closing force may be provided to the door when the door is closed.

(45) In addition, according to this embodiment, when the door is closed by the auto closing device, the phenomenon in which the door is closed and then opened again due to the excessive closing force of the door, may be prevented from occurring.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a front view of a refrigerator according to an embodiment.

(2) FIG. 2 is an enlarged view illustrating a portion A of FIG. 1.

(3) FIG. 3 is a perspective view illustrating a hinge bracket and an auto closing device according to an embodiment.

(4) FIG. 4 is a perspective view of an auto closing device when viewed from the below according

to an embodiment.

(5) FIG. 5 is a side view of the auto closing device according to an embodiment.

(6) FIG. 6 is a bottom view of the auto closing device according to an embodiment.

(7) FIG. 7 is an exploded perspective view of the auto closing device according to an embodiment.

(8) FIG. 8 is a view illustrating the hinge bracket fixed to a cabinet when viewed from the below.

(9) FIG. 9 is a view illustrating a position of a lever of the auto closing device in a state in which a first door is closed.

(10) FIG. 10 is a view illustrating a state in which the lever moves along a first surface of a bracket body in the process of closing the first door.

(11) FIG. 11 is a view illustrating a state in which the lever moves along a second surface in the process of closing the first door.

(12) FIG. 12 is a view illustrating a position of the lever in the state in which the first door is closed.

DETAILED DESCRIPTION

(13) Hereinafter, embodiments of the present disclosure will be described in detail with reference to the accompanying drawings. It should be noted that when components in the drawings are designated by reference numerals, the same components may have the same reference numerals even though the components are illustrated in different drawings. Further, in description of embodiments of the present disclosure, when it is determined that detailed descriptions of well-known configurations or functions obscure the understanding of the embodiments of the present disclosure, the detailed descriptions may be omitted.

(14) Also, in the description of the embodiments of the present disclosure, the terms such as first, second, A, B, (a) and (b) may be used. Each of the terms is merely used to distinguish the corresponding component from other components, and does not delimit an essence, an order or a sequence of the corresponding component. It should be understood that when one component is “connected”, “coupled” or “joined” to another component, the former may be directly connected or joined to the latter or may be “connected”, “coupled” or “joined” to the latter with a third component interposed therebetween.

(15) FIG. 1 is a front view of a refrigerator according to an embodiment, and FIG. 2 is an enlarged view illustrating a portion A of FIG. 1.

(16) Referring to FIGS. 1 and 2, a refrigerator 1 according to an embodiment may be installed independently in a kitchen or installed in an indoor furniture cabinet or wall. When the refrigerator 1 is installed in the indoor furniture cabinet, the refrigerator 1 may be installed alone or arranged side by side with another refrigerator.

(17) The refrigerator 1 may include a cabinet 10 having a storage space and a refrigerator door 20 that opens and closes the storage space.

(18) The storage space may not be limited, but may be divided into an upper first space and a lower second space, and the refrigerator door 20 may also include a first door 21 that opens and closes the first space and a second door 22 that opens and closes the second space.

(19) The first space may be a refrigerating compartment, and the second space may be a freezing compartment or vice versa. Alternatively, the storage space may include a first space and a second space, which are divided into left and right sides. Alternatively, the storage space may be a single space, and a single refrigerator door may open and close the storage space.

(20) At least one or more of the first door 21 and the second door 22 may be a rotation type door. Alternatively, the single refrigerator door 20 may be a rotation type door.

(21) In this embodiment, the rotation type refrigerator door 20 may include an auto closing device 40 that provides closing force to the refrigerator door 20 in a state in which the refrigerator door 20 is opened and then closed again at a certain angle.

(22) In FIG. 2, an example in which the auto closing device 40 is provided in the first door among the first door and the second door, which are arranged in a vertical direction will be described. It

should be noted that the position of the auto closing device **40** is not limited.

(23) When the first door **21** and the second door **22** are arranged in the vertical direction, a hinge bracket **30** is provided between the first door **21** and the second door **22**.

(24) The hinge bracket **30** may provide a rotational center of the first door **21**. Alternatively, the hinge bracket may also be disposed at an upper side of the first door **21**.

(25) The hinge bracket **30** may be fixed to a front surface **10a** of the cabinet **10**. A gap **G** having a predetermined size is defined between the first door **21** and the second door **22**. A portion of the hinge bracket **30** is disposed between the first door **21** and the second door **22** so that the first door **21** and the second door **22** rotate without interfering with each other, and also is spaced apart from a top surface of the second door **22** as well as a bottom surface of the first door **21**.

(26) The auto closing device **40** according to this embodiment may provide closing force to the first door **21** in a process of closing the first door **21** while acting with the hinge bracket **30**.

Alternatively, the auto closing device **40** may provide the closing force to the second door **22**.

(27) In order for the auto closing device **40** to provide the closing force to the first door **21**, the auto closing device **40** may be installed in the first door **21**.

(28) The auto closing device **40** may be installed at a lower side of the first door **21**, and in order to interact with the hinge bracket **30**, a portion of the auto closing device **40** may protrude downward from the bottom surface of the first door **21**.

(29) When the auto closing device **40** is installed at the lower side of the first door **21**, the auto closing device **40** may not be easily seen from the outside while the first door **21** is opened and closed. A body to be described later may be inserted into the lower side of the first door **21**, and a lever may protrude to the outside of the first door **21**.

(30) The auto closing device **40** may be spaced apart from a top surface of the second door **22** so that the auto closing device **40** does not interfere with the second door **22**.

(31) FIG. **3** is a perspective view illustrating the hinge bracket and the auto closing device according to an embodiment.

(32) For example, FIG. **3** illustrates relative positions of the auto closing device **40** and the hinge bracket **30** in the state in which the first door **21** is closed.

(33) Referring to FIGS. **2** and **3**, the hinge bracket **30** may include a coupling portion **310** to be coupled to the cabinet **10**, and a bracket body **320** extending horizontally from the coupling portion **310**. For example, the coupling portion **310** may be coupled to a front surface **10a** of the cabinet **10**.

(34) The coupling portion **310** may include one or more coupling holes **312**. A coupling member may be coupled to the cabinet **10** through the coupling holes **312**.

(35) A height of the bracket body **320** may be less than that of the coupling portion **310**. The bracket body **320** may extend in a horizontal direction from a position spaced apart from upper and lower ends of the coupling portion **310**. For example, the bracket body **320** may extend from an intermediate portion of the coupling portion **310**.

(36) A shaft **354** may be provided in the bracket body **320**. The shaft **320** may protrude upward from a top surface of the bracket body **320**. The shaft **354** is coupled to the first door **21** to provide a rotational center of the first door **21**.

(37) The auto closing device **40** may be disposed at a position spaced apart from the shaft **354** in the horizontal direction. That is, the auto closing device **40** may be coupled to the first door **21** at a position spaced apart from the shaft **354**.

(38) The auto closing device **40** rotates together with the first door **21**, and in the process of closing the first door **21**, the auto closing device **40** interacts with the bracket body **320** to provide the closing force to the first door **21**.

(39) Hereinafter, the auto closing device **40** will be described in detail.

(40) FIG. **4** is a perspective view of the auto closing device when viewed from the below according to an embodiment, FIG. **5** is a side view of the auto closing device according to an embodiment,

FIG. 6 is a bottom view of the auto closing device according to an embodiment, and FIG. 7 is an exploded perspective view of the auto closing device according to an embodiment.

(41) Referring to FIGS. 3 to 7, the auto closing device **40** according to this embodiment may include a body **410**, an elastic member **450** accommodated in the body **410**, and a lever **420** connected to the elastic member **450**.

(42) The body **410** may define an outer appearance of the auto closing device **40**.

(43) The lever **420** may be outside the body **410** and directly or indirectly connected to the elastic member **450** to rotate with respect to the body **410**.

(44) For example, the lever **420** may rotate in the horizontal direction based on a rotational center line extending in the vertical direction. That is, the rotational center line of the first door **21** and the rotational center line of the lever **420** may be parallel to each other and spaced apart from each other in the horizontal direction.

(45) The body **410** may include an upper opening. The body **410** may further include an accommodation space **411**. The elastic member **450** may be accommodated in the accommodation space **411** through the upper opening.

(46) The body **410** may include one or more coupling extension portions **413**. A coupling hole **414** may be defined in a coupling extension portion **413**. Although not limited, the plurality of coupling extension portions **413** may be disposed to extend horizontally from the body **410**.

(47) The auto closing device **40** may further include a connector **440** accommodated in the body **410**.

(48) The connector **440** may be connected to the lever **420** to rotate together with the lever **420**. Also, the connector **440** may be connected to the elastic member **450**. That is, the connector **440** connects the elastic member **450** to the lever **420**.

(49) A rotational center of the connector **440** may be the same as the rotational center of the lever **420**.

(50) The connector **440** may be accommodated in the accommodation space **411** through the upper opening of the body **410**.

(51) The connector **440** may include a connector body **442** and a lever coupling portion **445** extending downward from the connector body **442**.

(52) The elastic member **450** may be coupled to the connector body **442**. A lower portion of the elastic member **450** may be connected to the connector body **442**.

(53) A connection groove **443** may be defined in a top surface of the connector body **442**. The connection groove **443** may be spaced apart from the rotational center of the connector **440** in a radial direction.

(54) A diameter of the connector body **442** may be the same as or slightly less than that of the accommodation space **411**. Thus, movement of the connector body **442** in the accommodation space **411** in the horizontal direction may be minimized.

(55) The connector body **442** may be provided, for example, in a circular plate shape. A protrusion **444** may be provided on a side surface of the connector body **442**. The protrusion **444** may protrude outward in the radial direction from a side surface of the connector body **442**.

(56) The body **410** may include an accommodation portion **412** in which the protrusion **444** is accommodated. The accommodation portion **412** may be provided from the top surface of the body **410** and is recessed downward. Therefore, when the connector **440** is accommodated in the accommodation space **411** from the upper side, the protrusion **444** may be accommodated in the accommodation portion **412** without interfering with the body **410**. The accommodation portion **412** may extend radially outward from the accommodation space **411**.

(57) A horizontal length (or length in a circumferential direction) of the accommodation portion **412** may be greater than a horizontal length (or length in a circumferential direction) of the protrusion **444**.

(58) Thus, the connector **440** may rotate within a length range of the accommodation portion **412** in

the state in which the protrusion **444** is accommodated in the accommodation portion **412**.

(59) The protrusion **444** and the accommodation portion **412** may restrict the horizontal movement of the connector **440** as well as the rotation range. That is, the connector **440** may rotate within a predetermined angle range due to a length difference between the protrusion **444** and the accommodation portion **412**. Since the lever **420** is connected to the connector **440**, the lever **420** may also be restricted to rotate within the predetermined angle range.

(60) The lever coupling portion **445** may be smaller than the diameter of the connector body **442**. The lever coupling portion **445** may extend downward from a bottom surface of the connector body **442**.

(61) Although not shown, the body **410** may include a lower wall, and the lever coupling portion **445** may pass through the lower wall. The lever coupling portion **445** passing through the lower wall may protrude downward from the body **410**.

(62) A portion of the lever coupling portion **445** protruding from the lower wall of the body **410** may be coupled to the lever **420**.

(63) A vertical length of the lever coupling portion **445** may be longer than that of the connector body **442**.

(64) The lever coupling portion **445** may be inserted into the lever **420**. A horizontal cross-section of the lever coupling portion **445** may be provided in a non-circular shape so that the lever coupling portion **445** is prevented from rotating relative to the lever **420** while coupled to the lever **420**.

(65) A pin insertion hole **446** may be provided in the lever coupling portion **445**. The lever coupling portion **445** may be coupled to the lever **420** in the vertical direction, and the pin insertion hole **446** may extend in the horizontal direction.

(66) The lever **420** may include a first portion **422** coupled to the connector **440**. The first portion **422** may also be referred to as a connector coupling portion.

(67) The first portion **422** may include a coupling slot **423** into which the lever coupling portion **445** is inserted. The coupling slot **423** may be defined by being recessed downward from a top surface of the first portion **422**.

(68) A horizontal cross-section of the coupling slot **423** may be defined in the same shape as that of the lever coupling portion **445**.

(69) For example, the lever coupling portion **445** may be coupled to the coupling slot **423** in a press-fitting manner.

(70) With the lever coupling portion **445** inserted into the coupling slot **423**, the lever coupling portion **445** and the first portion **422** may be coupled to each other by a coupling pin **427**. The first portion **422** may include a through-hole **428** through which the coupling pin **427** passes. The through-hole **428** may extend in the horizontal direction from a side surface of the first portion **422** to communicate with the coupling slot **423**.

(71) When the coupling pin **427** passes through the through-hole **428** and is inserted into the pin insertion hole **446** of the lever coupling portion **445**, the lever coupling portion **445** and the lever **420** may be prevented from being separated from each other.

(72) In the state in which the lever **420** and the lever coupling portion **445** are coupled by the coupling pin **427**, the top surface of the first portion **422** may be spaced apart from the bottom surface of the body **410**.

(73) The lever **420** may further include a second portion **424** extending in the horizontal direction from the first portion **422**.

(74) A vertical length of the second portion **424** may be less than that of the first portion **422**. A top surface of the second portion **424** may be disposed lower than the top surface of the first portion **422**.

(75) The reason in which the vertical length of the first portion **422** is greater than the vertical length of the second portion **424** is to secure a depth into which the lever coupling portion **445** is inserted.

(76) The second portion **424** may be in contact with the bracket body **320**. Alternatively, the lever **420** may further include a roller **430** that is coupled to the second portion **424** and is in contact with the bracket body **320**.

(77) In this specification, a portion of the lever **420**, which is in contact with the bracket body **320**, may be referred to as a contact portion. In this case, the second portion **424** may be the contact portion, or the roller **430** may be the contact portion. FIG. 7 illustrates an example in which the roller **430** is provided on the second portion **424**. The roller **430** may be rotatably coupled to the second portion **424**. When the rotation roller **430** is in contact with the bracket body **320**, frictional force may be reduced more than when the second portion **424** is in contact with the bracket body **320**, and wear due to friction may be reduced.

(78) The second portion **424** may include a roller accommodation portion **425** in which a portion of the roller **430** is accommodated.

(79) A vertical length of the roller **430** may be less than a vertical length of the second portion **424**. The roller accommodation portion **425** may be disposed between top and bottom surfaces of the second portion **424**. That is, the roller accommodation portion **425** may be disposed at a position spaced apart from the top surface of the second portion **424** by a predetermined distance and at a position spaced apart from the bottom surface of the second portion **424** by a predetermined distance.

(80) In the state in which the roller **430** is accommodated in the roller accommodation portion **425**, a roller coupling pin **432** couples the roller **430** to the second portion **424**.

(81) Thus, the roller **430** may be supported by the lever **420** so as to be rotatable with the roller coupling pin **432** as the rotational center.

(82) A diameter of the roller **430** may be greater than a recessed depth (a depth in the horizontal direction based on FIG. 5) of the roller accommodation portion **425**. A diameter of the roller **430** may be greater than a width of the second portion **424**.

(83) Thus, in the state where the roller **430** is coupled to the lever **420** by the roller coupling pin **432**, the roller **430** may protrude outward from the second portion **424**.

(84) The elastic member **450** may be, for example, a torsion spring. The elastic member **450** may include a body portion **452** provided by winding a wire multiple times. The body portion **452** may have a cylindrical or truncated cone shape.

(85) The elastic member **450** may further include a first extension portion **454** extending from a lower end of the body portion **452**. The first extension portion **454** may extend downward from the body portion **452**.

(86) The first extension portion **454** may be inserted into the connection groove **443** of the connector **440**. For example, the first extension portion **454** may be inserted into the connection groove **443** in a press-fitting manner.

(87) The elastic member **450** may further include a second extension portion **456** extending from an upper end of the body portion **452**. The second extension portion **456** may extend upward from the body portion **452**.

(88) The auto closing device **40** may further include a cap **470** covering an upper opening of the body **410**.

(89) The cap **470** may include a connection groove **472** into which the second extension portion **456** is inserted. The connection groove **472** may be defined by being recessed upward from a bottom surface of the cap **470**. For example, the first extension portion **456** may be inserted into the connection groove **443** in a press-fitting manner.

(90) The cap **470** may further include a first coupling hole **474** aligned with a coupling hole **414** of the body **410**. A coupling member (not shown) may be coupled to the coupling hole **414** of the body **410** and the first coupling hole **474**. Thus, the cap **470** and the body **410** may be coupled to each other by the coupling member.

(91) The cap **470** may further include one or more second coupling holes **476**. A coupling member

(not shown) may pass through the second coupling hole **476** and be coupled to the first door **21**.

(92) Since the cap **470** is coupled to the body **410**, a position of the cap **470** is fixed. On the other hand, the connector **440** is rotatable within the body **410**.

(93) Since a second extension end **456** of the elastic member **450** is connected to the cap **470**, and a first extension end **454** is connected to the connector **440**, in this embodiment, the second extension end **456** may be referred to as a fixed end, and the first extension portion **454** may be referred to as a movable end.

(94) Thus, in a state in which the second extension portion **456** is fixed, the first extension portion **454** is rotatable together with the lever **420**.

(95) When the first extension portion **454** of the elastic member **450** rotates in one direction while the second extension portion **456** is fixed, the elastic member **450** accumulates an elastic force. The elastic force accumulated by the elastic member **450** may act on the lever **420** so that the lever **420** rotates in another direction opposite to the one direction.

(96) In this manner, the elastic force accumulated by the elastic member **450** substantially acts on the first door **21** in the process of closing the first door **21** so that the first door **21** is automatically closed from a predetermined position.

(97) The auto closing device may further include a bearing **460** that reduces friction between the connector body **442** and the lower wall of the body **410**. The bearing **460** is seated on an upper side of the lower wall of the body **410**, and the lever coupling portion **445** may pass through the bearing **460**.

(98) FIG. **8** is a view illustrating the hinge bracket fixed to the cabinet when viewed from the below.

(99) Referring to FIG. **8**, the bracket body **320** of the hinge bracket **30** may include a contact surface that is in contact with the lever **420**.

(100) For example, the roller **430** of the lever **420** may be in contact with the contact surface. While the lever **420** moves along the contact surface, the lever **420** may rotate.

(101) The contact surface may include a first surface **322** on which the lever **420** is in initially contact with the contact surface in the process of closing the first door **21**. In a state where the first door **21** is opened at a predetermined angle or more, the lever **420** may not be in contact with the first surface **322**, and in the process of closing the first door **21**, the lever **420** may be in contact with the first surface **322**.

(102) The first surface **322** is not only disposed to be inclined with respect to the front surface **10a** of the cabinet **10**, but also disposed to be inclined with respect to a virtual line **L1** that is perpendicular to the front surface **10a** of the cabinet **10** by passing through a rotational center line **C1** of the first door **21**. The rotational center line **C1** is a line passing through the rotational center of the first door **21**.

(103) The first surface **322** may be inclined in a direction away from the virtual line **L1** as the first surface **322** approaches the front surface **10a** of the cabinet **10**.

(104) The contact surface may further include a second surface **323** extending from the first surface **322**. The second surface **323** may be inclined with respect to the first surface **322**. A length of the second surface **323** may be less than that of the first surface **322**.

(105) The second surface **323** may be inclined not only with respect to the front surface **10a** of the cabinet **10**, but also with respect to the virtual line **L1**.

(106) The second surface **323** may be inclined in a direction closer to the virtual line **L1** as the second surface **323** approaches the front surface **10a** of the cabinet **10**.

(107) The contact surface may further include a third surface **324** extending from the second surface **323**. The third surface **324** may be inclined with respect to the second surface **323**.

(108) The third surface **324** may be inclined not only with respect to the front surface **10a** of the cabinet **10**, but also with respect to the virtual line **L1**.

(109) The third surface **324** extends in a direction closer to the virtual line **L1** as a distance from the

front surface **10a** of the cabinet **10** increases.

(110) The bracket body **320** may further include an accommodation groove **327** that accommodates the roller **430** of the lever **420**. As the roller **430** is being accommodated in the accommodation groove **327**, the roller **430** that is in contact with the second surface **323** is now in contact with the third surface **324**. That is, in the state in which the first door is closed, the roller **430** may be disposed in the accommodation groove **327** and may be in contact with the third surface **324**.

(111) FIG. **9** is a view illustrating a position of the lever of the auto closing device in the state in which a first door is closed. FIG. **9** illustrates a view of the auto closing device viewed from a lower side of the first door.

(112) Referring to FIG. **9**, when the refrigerator according to this embodiment is installed in a furniture cabinet, it is preferable that a thickness of the first door **21** is reduced to reduce the forward protrusion of the first door **21** from the front surface of the furniture cabinet.

(113) When the thickness of the first door **21** is reduced, in order for the auto closing device **40** to be installed in the first door **21**, the auto closing device **40** may be installed at a position spaced apart from the rotational center line **C1** of the first door **21**.

(114) For example, when the first door **21** is closed, the rotational center line **C1** of the first door **21** and the rotational center line **C2** of the lever **420** are spaced apart from each other. The rotational center line **C2** of the lever **420** is a line passing through the rotational center of the lever **420**.

(115) In addition, when the refrigerator is installed in the furniture cabinet, an opening angle needs to be secured so that the first door **21** does not collide with the furniture cabinet during the rotation of the first door **21**.

(116) Therefore, in this embodiment, the rotational center line **C1** of the first door **21** may be disposed close to the front and side surfaces of the first door **21**.

(117) For example, in the state in which the first door **21** is closed, the rotational center line **C1** of the first door **21** may be disposed closer to a front surface **21a** than a rear surface **21b** of the first door **21**.

(118) A distance between the rotational center line **C1** of the first door **21** and the rear surface **21b** of the first door **21** may be more than twice a distance between the rotational center line **C1** of the first door **21** and the front surfaces **21a** of the first door **21**.

(119) In the state in which the first door **21** is closed, the rotational center line **C1** of the first door **21** may be disposed closer to a first side surface **21d** of the two side surfaces of the first door **21**.

(120) In the state in which the first door **21** is closed, a distance between the rotational center line **C1** of the first door **21** and the first side surface **21d** may be less than that between the rotational center line **C1** of the first door **21** and the rear surface **21b** of the first door **21**.

(121) In the state in which the first door **21** is closed, a distance between the rotational center line **C1** of the first door **21** and the front surface **21a** of the first door **21** may be less than between the front surface **21a** of the first door **21** and the rotational center line **C2** of the lever **420**.

(122) In the state in which the first door **21** is closed, a distance between the rotational center line **C1** of the first door **21** and the front surface **10a** of the cabinet **10** may be greater than that between the rotational center line **C2** of the lever **420** and the front surface **10a** of the cabinet **10**.

(123) In the state in which the first door **21** is closed, the roller **430** of the lever **420** may be disposed on an area between the virtual line **L1** (first virtual line) and the virtual line **L2** (second virtual line) perpendicular to the front surface **10a** of the cabinet **10** while passing through the rotational center line **C2** of the lever **420**.

(124) A gasket **21c** that is in contact with the cabinet **10** in the state in which the first door **21** is closed may be provided on the rear surface **21b** of the first door **21**. In order for the gasket **21c** to be coupled to the first door **21**, a groove in which a portion of the gasket **21c** is accommodated may be defined in the rear surface of the first door **21**.

(125) In the state in which the first door **21** is closed, the roller **430** of the lever **420** may be disposed closer to the rear surface **21b** of the first door **21** than the rotational center line **C1** of the

first door **21**.

(126) In the state in which the first door **21** is closed, a portion of the first surface **322** may be disposed closer to the front surface **21a** of the first door **21** than to the rotational center line **C1** of the first door **21**. In the state in which the first door **21** is closed, the other portion of the first surface **322** may be disposed closer to the rear surface **21b** of the first door **21** than the rotational center line **C1** of the first door **21**.

(127) In the state in which the first door **21** is closed, the second surface **323** and the third surface **324** may be disposed closer to the rotational center line **C1** of the first door **21** than the rear surface **21b** of the first door **21**.

(128) In the state in which the first door **21** is closed, the second surface **323** and the third surface **324** may be disposed closer to the rotational center line **C2** of the lever **420** than the front surface **21a** of the first door **21**.

(129) The roller **430** of the lever **420** is maintained in the state of being in contact with the third surface **324** while being accommodated in the accommodation groove **327**.

(130) Since the roller **430** is in contact with the third surface **324**, the closed state of the first door **21** may be stably maintained when the first door **21** is closed.

(131) FIG. **10** is a view illustrating a state in which the lever moves along the first surface of the bracket body in the process of closing the first door, FIG. **11** is a view illustrating a state in which the lever moves along the second surface in the process of closing the first door, and FIG. **12** is a view illustrating a position of the lever in the state in which the first door is closed.

(132) Referring to FIGS. **10** to **12**, when the lever **420** is spaced apart from the bracket body **320** in the process of closing the first door **21** after the first door **21** is opened, external force may not act on the lever **420**.

(133) In the process of closing the first door **21** in a direction A, when the door **21** is angled at a reference angle with respect to the front surface **10a** of the cabinet **10**, the lever **420** may be in contact with the first surface **322** of the bracket body **320**.

(134) When the first door **21** further rotates in the A direction while the lever **420** is in contact with the first surface **322** of the bracket body **210**, the lever **420** may rotate in a direction B opposite to the direction A by an inclination of the first surface **322**.

(135) The first surface **322** applies resistive force to the lever **420** so that the lever **420** rotates in the direction B.

(136) When the lever **420** is rotated in the direction B, the first extension portion **454** of the elastic member **450** also rotates in the direction B so that the elastic member **450** accumulates elastic force.

(137) When the lever **420** approaches the second surface **323** while the second door **21** is closing, the elastic force accumulated in the elastic member **450** increases.

(138) When the lever **420** is in contact with the second surface **323** while the first door **21** is closing, the lever **420** additionally rotates in the direction B. When the lever **420** additionally rotates in the direction B, the elastic force accumulated in the elastic member **450** increases.

(139) According to this embodiment, the elastic force accumulated in the elastic member **450** is maximized in the state in which the lever **420** is in contact with the second surface **323**. The elastic force accumulated in the elastic member **450** in the state in which the lever **420** is in contact with the second surface **323** is greater than that accumulated in the elastic member **450** in the state in which the lever **420** is in contact with the first surface **322**.

(140) The lever **420** may rotate in the direction A in the state in which the lever **420** is in contact with the second surface **323** according to an angle of the second surface **323**. When the lever **420** rotates in the A direction, the elastic force accumulated in the elastic member **450** decreases. In this case, the elastic force accumulated in the elastic member **450** is maximized in the state in which the lever **420** is in contact with the first surface **322**. Since the lever **420** inertially rotates in the direction A, and the rotation angle of the lever **420** in the direction A is less than the rotation angle

of the lever **420** in the direction B, a torque loss of the lever **420** may be reduced, or a degree of reduction of the elastic force accumulated in the elastic member **450** may be minimized.

(141) Alternatively, according to the angle of the second surface **323**, the lever **420** may rotate in the direction B in the state in which the lever **420** is in contact with a portion of the second surface **323**, and also, the lever **420** may rotate in the direction A in the state in which the lever **420** is in contact with the other portion of the second surface **323**. Even in this case, the elastic force accumulated in the elastic member **450** is maximized in the state in which the lever **420** is in contact with the second surface **323**.

(142) When the lever **420** deviates from the second surface **323** in the process of closing the first door **21**, the resistive force applied to the lever **420** is removed, and the elastic force accumulated in the elastic member **450** may act on the lever **420** to increase in rotation angle in the direction A of the lever **420**, and thus, the first door **21** may be automatically closed.

(143) That is, while the lever **420** moves along the third surface **324**, the elastic force accumulated in the elastic member **450** decreases. That is, the elastic force decreases as it acts as the closing force of the first door **21**.

(144) Here, since the lever **420** rotates while the roller **430** of the lever **420** is being accommodated in the accommodation groove **327**, the elastic force of the elastic member **450** acts in a direction crossing the third surface **324** or in a normal direction in the state in which the roller **430** is in contact with the third surface **324**. Therefore, the elastic force may be prevented from being concentrated at a specific point of the third surface **324**, and efficiency of transmitting the elastic force to the third surface **324** is high.

(145) As described above, when the elastic force of the elastic member **450** acts in a direction crossing the third surface **324**, rattling of the first door **21** or a phenomenon in which the first door **21** is closed and then opened again due to the excessive action of the elastic force at a time point at which the first door **21** is closed may be prevented from occurring.

(146) In this embodiment, torque of the lever **420** may be maximized when the opening angle (an angle angled between the door and the front surface of the cabinet when the door is closed) of the first door **21** is approximately 10 degrees or less. When the first door **21** is disposed in the left and right direction, a pillar may be provided on either the left door or the right door. The pillar serves to block leakage of cold air from the storage space between the left and right doors.

(147) For example, the pillar is rotatably disposed on the left door, and the pillar is automatically unfolded while the left door is closed. An angle at which the pillar is unfolded may be a case in which the opening angle of the left door is approximately 10 degrees or less and be designed so that the torque is maximized when the opening angle of the left door is approximately 10 degrees or less so that the pillar is easily unfolded.

(148) In this embodiment, as illustrated in FIG. 12, the roller **430** of the lever **420** is in contact with the third surface **324** when the door is closed.

(149) The third surface **324** may provide the resistive force to the lever **420**, and thus, the lever **420** exists in a substantially rotating state at a predetermined angle in the state in which the first door **21** is closed so that the elastic member **450** is maintained in the state of accumulating a certain amount of elastic force. Therefore, since the elastic member **450** applies force in the direction in which the first door **21** is closed in the state in which the first door **21** is closed, the closed state of the first door **21** may be stably maintained.

(150) In the state in which the first door **21** is closed, and the lever **420** is in contact with the third surface **324**, the elastic force accumulated in the elastic member **450** may be equal to or greater than the elastic force accumulated in the elastic member **450** in a state in which the first door **21** is opened at a predetermined angle, and the lever **420** is spaced apart from the first surface **322**.

(151) In summary, when the first door **21** is closed, while the lever **420** moves along a partial section of the contact surface **321**, the elastic force is accumulated in the elastic member **450** and is maximized, and the elastic force of the elastic member **450** acts on the lever **420** in a different

section of the contact surface so that the first door **21** is automatically closed.

(152) While the lever **420** moves along a portion of the contact surface **321** based on the front surface **10a** of the cabinet **10**, the roller **430** gets closer to the front surface **10a** of the cabinet **10**, and while the lever **420** moves along the other portion of the contact surface **321**, the contact surface **321** of the bracket body **320** is defined so that the roller **430** is away from the front surface **10a** of the cabinet **10**.

(153) Alternatively, while the lever **420** moves along a portion of the contact surface **321** based on the rear surface **21b** of the first door **21**, the roller **430** gets closer to the rear surface **21b**, and while the lever **321** moves along the other portion of the contact surface **321**, the contact surface **321** of the bracket body **320** is defined so that the roller **430** is away from the rear surface **21b**.

(154) For example, while the contact portion of the lever **420** moves along the first surface **322** and the second surface **323**, the contact portion may get closer to the rear surface **21b** of the first door **21**. While the contact portion of the lever **420** moves along the third surface **324**, the contact portion may be away from the rear surface **21b** of the first door **21**.

(155) As another example, while the contact portion of the lever **420** moves along the first surface **322**, the contact portion may get closer to the rear surface **21b** of the first door **21**. While the contact portion of the lever **420** moves along a portion of the second surface **323**, the contact portion may get closer to the rear surface **21b** of the first door **21**, and while the contact portion of the lever **420** moves along a remaining portion of the second surface **323**, the contact portion may be away from the rear surface **21b** of the first door **21**. While the contact portion of the lever **420** moves along the third surface **324**, the contact portion may be away from the rear surface **21b** of the first door **21**.

(156) A case in which the first door **21** is opened will be briefly described.

(157) When the first door **21** is initially opened in the closed state, the lever **420** moves along the third surface **324**. While the lever **420** moves along the third surface **324**, the elastic force accumulated in the elastic member **450** increases.

(158) When the opening angle of the first door **21** increases, the lever **420** moves from the third surface **324** to the second surface **323** and then moves along the second surface **323**.

(159) While the lever **420** moves along the second surface **323**, the elastic force accumulated in the elastic member **450** may decrease slightly. Alternatively, while the lever **420** moves along the second surface **323**, the elastic force accumulated in the elastic member **450** may increase.

(160) When the opening angle of the first door **21** further increases, the lever **420** moves from the second surface **323** to the first surface **322** and then moves along the first surface **322**. While the lever **420** moves along the first surface **322**, the elastic force accumulated in the elastic member **450** decreases. When the lever **420** is spaced apart from the first surface **322**, the elastic force accumulated in the elastic member **450** is minimized.

Claims

1. A refrigerator comprising: a cabinet having a storage space; a hinge bracket coupled to the cabinet; a door to open and close the storage space, and rotatably coupled to a shaft provided at the hinge bracket; and an auto closing device installed at the door at a position spaced apart from a rotational center line of the door and to interact with the hinge bracket in a process of closing the door to automatically close the door, wherein the auto closing device comprises a lever and an elastic member to elastically support the lever, and the hinge bracket comprises a contact surface to contact with the lever, wherein the contact surface includes a contour so that, during a process of closing the door, while a contact portion of the lever moves along a portion of the contact surface, the contact portion moves closer to a front surface of the cabinet, and while the contact portion moves along another portion of the contact surface, the contact portion moves away from the front surface of the cabinet.

2. The refrigerator of claim 1, wherein, based on a virtual line that is perpendicular to the front surface of the cabinet and passes through the rotational center line of the door, the contact surface comprises: a first surface inclined in a direction that is farther from the virtual line as the first surface is closer to the front surface of the cabinet; a second surface inclined in a direction that is closer to the virtual line as the second surface is closer to the front surface of the cabinet; and a third surface extending in a direction that is closer to the virtual line as the third surface is farther away from the front surface of the cabinet.
3. The refrigerator of claim 2, wherein, the contact portion of the lever moves closer to the front surface of the cabinet as the contact portion moves along the first surface and then along the second surface and the contact portion moves away from the front surface of the cabinet as the contact portion moves along the third surface away from the second surface.
4. The refrigerator of claim 3, wherein, the contact portion of the lever is maintained in a state of being in contact with the third surface when the door is in the closed state.
5. The refrigerator of claim 2, wherein, the contact portion of the lever moves closer to a rear surface of the door as the contact portion moves along the first surface and then along the second surface, and the contact portion moves away from the rear surface of the door as the contact portion moves along the third surface away from the second surface.
6. The refrigerator of claim 2, wherein, the contact portion of the lever moves closer to a rear surface of the door as the contact portion moves along the first surface toward the second surface, the contact portion moves closer to the rear surface of the door the contact portion moves along a portion of the second surface toward the third surface, the contact portion moves away from the rear surface of the door as the contact portion moves along a remaining portion of the second surface away from the portion of the second surface, and the contact portion move away from the rear surface of the door as the contact portion moves along the third surface away from the remaining portion of the second surface.
7. The refrigerator of claim 2, wherein, the door rotates in a first direction to be closed, the lever rotates in a second direction opposite to the first direction as the contact portion of the lever moves along the first surface toward the second surface, and the lever rotates in the first direction as the contact portion along the third surface away from the second surface.
8. The refrigerator of claim 2, wherein, when the door rotates in a first direction to be closed, the lever rotates in a second direction opposite to the first direction as the contact portion of the lever moves along the first surface toward the second surface, the lever rotates in the second direction as the contact portion moves along a portion of the second surface away from the first surface, the lever rotates in the first direction as the contact portion moves along a remaining portion of the second surface away from the portion of the second surface, and the lever rotates in the first direction as the contact portion moves along the third surface away from the remaining portion of the second surface.
9. The refrigerator of claim 2, wherein, the door rotates in a first direction to be closed, the lever rotates in a second direction opposite to the first direction as the contact portion of the lever moves along the first surface toward the second surface, the lever rotates in the first direction as the contact portion of the lever moves along the second surface toward the third surface, and the lever rotates in the first direction as the contact portion of the lever moves along the third surface away from the second surface.
10. The refrigerator of claim 1, wherein the lever rotates based on a rotational center line spaced apart from the rotational center line of the door.
11. The refrigerator of claim 10, wherein, in the state in which the door is closed, the rotational center line of the lever is disposed closer to the front surface of the cabinet than the rotational center line of the door.
12. The refrigerator of claim 10, wherein the lever comprises a roller rotatably coupled to the lever, and the contact portion is the roller.

13. The refrigerator according to claim 10, wherein the auto closing device comprises: a body to accommodate the elastic member; and a connector connected to the elastic member within the body, wherein the connector comprises a lever coupling portion that extends to an outside of the body, and the lever is coupled to the lever coupling portion.

14. The refrigerator of claim 13, wherein the connector rotates together with the lever, the elastic member comprises: a body portion provided by winding a wire several times; and an extension portion to extend from the body portion, wherein the extension portion is coupled to the connector at a position spaced apart from a rotational center line of the connector.

15. A refrigerator comprising: a cabinet having a storage space; a hinge bracket coupled to the cabinet; a door to open and close the storage space and rotatably coupled to a shaft provided at the hinge bracket; and an auto closing device installed at the door at a position spaced apart from a rotational center line of the door and to interact with the hinge bracket in a process of closing the door to automatically close the door, wherein the auto closing device comprises a lever and an elastic member to elastically support the lever, and the hinge bracket comprises a contact surface to contact with the lever, wherein the contact surface includes a contour so that, while a contact portion of the lever moves along a portion of the contact surface, the contact portion moves closer to a rear surface of the door, and while the contact portion moves along an other portion of the contact surface, the contact portion moves away from the rear surface of the door.

16. A refrigerator comprising: a cabinet having a storage space; a hinge bracket coupled to the cabinet; a door to open and close the storage space and rotatably coupled to a shaft provided at the hinge bracket; and an auto closing device installed at the door at a position spaced apart from a rotational center line of the door and to interact with the hinge bracket in a process of closing the door to automatically close the door, wherein the auto closing device comprises a lever and an elastic member to elastically support the lever, and the hinge bracket comprises a contact surface to contact with the lever, the contact surface includes a contour so that, during a process of closing the door, elastic force accumulated in the elastic member increases as the contact portion of the lever moves along a portion of the contact surface, the contact portion moves closer to a front surface of the cabinet, and the elastic force accumulated in the elastic member decreases as the contact portion of the lever moves along an other portion of the contact surface, the contact portion moves away from the front surface of the cabinet, and the elastic force of the elastic member acts as a closing force of the door in a section of the contact surface in which the elastic force of the elastic member decreases.

17. The refrigerator of claim 16, wherein the elastic force accumulated in the elastic member in the state in which the door is closed is equal to or greater than that the elastic force accumulated in the elastic member in the state in which the lever is spaced apart from the contact surface by an opening of the door.

18. A refrigerator comprising: a cabinet having a storage space; a hinge bracket coupled to the cabinet; a door to open and close the storage space and rotatably coupled to a shaft provided at the hinge bracket; and an auto closing device installed at the door at a position spaced apart from a rotational center line of the door and to interact with the hinge bracket in a process of closing the door to automatically close the door, wherein the auto closing device comprises a lever to rotate based on a rotational center line spaced apart from a rotational center line of the door, and an elastic member to increase or decrease in an accumulation of an elastic force while the lever rotates, the hinge bracket comprises a contact surface to contact with the lever, and in the state in which the door is closed, the rotational center line of the door is disposed closer to a front surface of the door than a rear surface of the door, and the rotational center line of the lever is disposed closer to the rear surface of the door than the rotational center line of the door.

19. The refrigerator of claim 18, wherein the contact surface includes a contour so that, during a process of closing the door, while a contact portion of the lever moves along a portion of the contact surface, the contact portion moves closer to the front surface of the cabinet, and while the

contact portion of the lever moves along an other portion of the contact surface, the contact portion moves away from the front surface of the cabinet.

20. The refrigerator of claim 19, wherein in the state in which the door is closed, a portion of the contact surface, which is in contact with the lever, is disposed closer to the front surface of the door than the rotational center line of the lever.
