

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12402764
B2
September 02, 2025
Collins; David et al.

Ventilation and particulate matter removal system

Abstract

Apparatus and a method for removing particulate matter from an enclosure having an internal space and an opening into the internal space. The apparatus includes: a cover positionable over the opening; an inlet conduit that extends through the cover and is adapted to direct gas from a gas source to a gas outlet within the internal space so that particulate matter within the internal space is dislodged. Gas and entrained particulate matter is drawn from the internal space firstly through an outlet conduit and the particulate matter is separated. Concentration of particulate matter in gas leaving the enclosed space is sensed and its value displayed to an operator so that operation can continue until a satisfactory value of the concentration is achieved. The gas outlet may be comprised in an elongate lance that is passed through the cover and can be manipulated by a user. The lance may display data.

Inventors:	Collins; David (Parkville, AU), Brett; James (West Melbourne, AU), Forsyth; James (Cheltenham, AU), Maltby; Callum (West Melbourne, AU)
Applicant:	Synergetics Pty. Ltd. (West Melbourne, AU)
Family ID:	73459528
Assignee:	Synergetics Pty. Ltd. (West Melbourne, AU)
Appl. No.:	17/612884
Filed (or PCT Filed):	May 21, 2020
PCT No.:	PCT/IB2020/054843
PCT Pub. No.:	WO2020/234825
PCT Pub. Date:	November 26, 2020

Prior Publication Data

Foreign Application Priority Data

AU	2019901732	May. 21, 2019
AU	2019902397	Jul. 05, 2019
AU	2019902513	Jul. 16, 2019
AU	2019902685	Jul. 28, 2019
AU	2019904558	Dec. 02, 2019

Publication Classification

Int. Cl.: **A47L5/14** (20060101); **A47L9/02** (20060101); **A47L9/12** (20060101); **A47L9/28** (20060101); **B01D50/20** (20220101); B05B13/04 (20060101); B60S3/00 (20060101); H02G3/08 (20060101)

U.S. Cl.:

CPC **A47L5/14** (20130101); **A47L9/02** (20130101); **A47L9/12** (20130101); **A47L9/281** (20130101); **A47L9/2857** (20130101); **A47L9/2889** (20130101); **A47L9/2894** (20130101); **B01D50/20** (20220101); B05B13/0405 (20130101); B60S3/008 (20130101); H02G3/088 (20130101)

Field of Classification Search

CPC: A47L (5/14); A47L (9/02); A47L (9/12); A47L (9/281); A47L (9/2857); A47L (9/2889); A47L (9/2894); A47L (7/0095); A47L (9/16); A47L (9/19); A47L (9/2815); A47L (9/2821); A47L (9/2831); A47L (9/30); B01D (50/20); B05B (13/0405); B05B (1/005); B60S (3/008); H02G (3/088); B08B (5/04); B08B (9/00); B08B (15/04); B08B (5/02); B08B (13/00); H02B (1/28); H02K (15/14)

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4242114	12/1979	Deacon	55/304	B01D 46/04
5460193	12/1994	Levallois	134/167R	B08B 9/0936
6256832	12/2000	Dyson	15/337	A47L 5/30
6766558	12/2003	Matsumoto	15/353	A47L 9/2821
2005/0086762	12/2004	Paris	15/327.5	A47L 5/36
2008/0289141	12/2007	Oh	15/354	A47L 9/0488
2011/0225765	12/2010	Liu	15/347	A47L 9/1666
2016/0100724	12/2015	Valentini	15/319	A47L 9/2836

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2019201437	12/2018	AU	N/A
2019201437	12/2018	AU	N/A
205429520	12/2015	CN	N/A
205628781	12/2015	CN	N/A
205628781	12/2015	CN	N/A
106269712	12/2016	CN	B08B 1/002
105057276	12/2016	CN	N/A
10732711	12/2016	CN	N/A
207183892	12/2017	CN	N/A
19811738	12/1998	DE	A47L 9/02
0367276	12/1989	EP	N/A
WO 1992018260	12/1991	WO	N/A

OTHER PUBLICATIONS

CN-205628781-U Written Description (Year: 2016). cited by examiner

CN-106269712-A Written Description (Year: 2017). cited by examiner

EP 0367276 A1 Written Description (Year: 1990). cited by examiner

DE-19811738-A1 Written Description (Year: 1999). cited by examiner

International Search Report from PCT/IB2020/054843, dated Aug. 24, 2020 (6 pages). cited by applicant

Written Opinion from PCT/ IB2020/054843, dated Aug. 24, 2020 (9 pages). cited by applicant

Primary Examiner: Golightly; Eric W

Attorney, Agent or Firm: Anderson Gorecki LLP

Background/Summary

FIELD

(1) Apparatus systems and methods are disclosed for removal of particulate matter from enclosed spaces and enclosures, with particular reference to removal of dust, dirt and the like from enclosed cabinets containing electrical components.

BACKGROUND

(2) In many industries, electrical, electronic and other sensitive equipment is housed in enclosures designed to provide a safe and clean operating environment for that equipment and to prevent unauthorized or inadvertent access. This can be the case in both fixed industrial installations and mobile equipment.

(3) Although such enclosures are generally designed and maintained to prevent or limit ingress of particulate matter, for example dust and dirt, it has been found in some applications that enclosures do sometimes need to be cleaned out of such particulate matter. Failure to do so in these applications can eventually threaten proper operation of the electrical or electronic equipment.

(4) For example, in the mining industry, haul trucks with diesel-electric drives have enclosures (cabinets) for electrical components which are sometimes found to accumulate significant quantities of particulate matter, even when carefully maintained, but particularly with ageing and

when maintenance is imperfect. Other mobile equipment used in the surface mining industry, eg electric blasthole drills, shovels and draglines may have enclosures that are similarly affected.

(5) Cleaning out of particulate matter from such enclosures to a suitable standard of cleanliness can itself be difficult and time consuming. Water cleaning is unsuitable for cleaning electrical and electronic equipment. Vacuum cleaning is often ineffective in removing particulate matter from spaces within and between components. The use of compressed air can create occupational, environmental and ecological exposure risks from airborne particulate matter.

(6) It is believed that there are other areas of activity including for example underground mining, and certain above-ground industrial/manufacturing installations in which the above problems occur. In some of these, the particulate matter in question may be considered toxic either inherently because of its chemistry or because of factors such as particle size or shape or even the expected sensitivity of persons likely to be exposed to the matter.

(7) Disclosed herein are equipment, systems and methods for addressing the problem of cleaning particulate matter from enclosed spaces.

(8) In this specification, no reference to prior art or to what is known, is to be taken as a concession that anything is a part of the common general knowledge in Australia or elsewhere.

DISCLOSURE OF THE INVENTION

(9) The invention provides in a first aspect a cleaning and ventilation system.

(10) More particularly there is provided apparatus for removing particulate matter from an enclosure having an internal space and an opening into the internal space, comprising: a cover positionable adjacent the opening so that the cover covers the opening; a gas source external to the internal space; an inlet conduit that in use extends through the cover and is adapted to direct gas from the gas source to at least one gas outlet within the internal space whereby particulate matter within the internal space is dislodged and entrained in gas within the internal space; a source of partial vacuum adapted to maintain a partial vacuum within the internal space and to draw gas and particulate matter entrained therein from the internal space firstly through an outlet conduit and then through a particulate matter separation means comprising at least one filter; a sensor for sensing concentration of particulate matter in gas leaving the enclosed space; a display adapted to provide to a user information on concentration of particulate matter leaving the internal space so that the operator can continue use of gas from the gas source to dislodge particulate matter in the internal space until a satisfactory value of the concentration is achieved.

(11) Preferably the apparatus further comprises means for storing data obtained from the sensor.

(12) Preferably also, the apparatus further comprises means for transmitting data obtained from the sensor to a location remote from the apparatus.

(13) The outlet conduit is preferably in use secured to the cover and draws gas through an opening in the cover.

(14) Preferably the or at least one gas outlet is movable relative to the cover among multiple positions within the internal space.

(15) In a preferred embodiment the gas outlet is at an end of an elongate lance comprised in the inlet conduit, the lance in use extending through a port in the cover so that a portion of its length is in the internal space and the user can manually move the lance to cause the gas outlet to take up any of the said multiple positions within the internal space.

(16) It is particularly preferred that the elongate lance comprises a display adapted to display data sensed by the sensor.

(17) Gas flow to the gas outlet may be able to be interrupted periodically so that the flow of gas leaving the elongate lance within the internal space pulsates.

(18) The port in the cover may be one of a plurality of ports in the cover so positioned that the user can withdraw the lance from one port and enter the lance into another port as required to access multiple parts of the internal space.

(19) Desirably, each of the plurality of ports is adapted to prevent or limit escape of particulates

therethrough when the port does not have the lance extending through it.

(20) The cover may comprise a sheet of flexible transparent material so that a user may see through the cover when using the elongate lance.

(21) The invention further provides a method for removing particulate matter from an enclosure having an internal space and an opening into the internal space, comprising the steps of: positioning a cover adjacent the opening so that the cover covers the opening; providing a gas source external to the internal space; providing an inlet conduit that in use extends through the cover and is adapted to direct gas from the gas source to at least one gas outlet within the internal space whereby particulate matter within the internal space is dislodged and entrained in gas within the internal space; providing a source of partial vacuum adapted to maintain a partial vacuum within the enclosed space and to draw gas and particulate matter entrained therein from the internal space firstly through an outlet conduit and then through a particulate matter separation means comprising at least one filter; providing a sensor for sensing concentration of particulate matter in gas leaving the enclosed space; using the sensor to derive and provide to a user information on concentration of particulate matter leaving the internal space; the user using gas from the gas source to dislodge particulate matter in the internal space until a satisfactory value of the concentration is achieved.

(22) The method may further comprise the steps of: repeatedly sensing concentration of particulate matter in gas leaving the internal space during cleaning thereof and storing digital records thereof.

(23) The method may include the step of transmitting the digital records to a remote location. This enable analysis at the remote location, which may be done for validation that cleaning is satisfactory and for regulatory approval purposes.

(24) The method therefore may include the step of receiving transmitted the digital records and analysing the effectiveness of cleaning on the basis of the digital records.

(25) There is also provided a system for instrumentation and control of a mechanical ventilation system where both equipment-related sensors and workspace- and/or user-related sensors are provided, and wherein signals from specific ones of the sensors (workplace-, user-, or equipment-related) are used to provide any or all of alarms (or warnings), display the parameter value(s) of concern and if desired or necessary shut down or otherwise control either the ventilation system or the equipment being ventilated.

(26) Some industrial processes require different levels of ventilation according to how a the process is being carried out or the stage it has reached, and it is desirable to be able to adjust ventilation to suit—either to provide adequate ventilation or to limit wastage of energy when a particular level of ventilation is not required. Therefore, instead of, or in addition to, alarms, warnings and shutdown commands, the system may provide for automatic control of the ventilation system to maintain effectiveness and save energy in a range of conditions.

(27) The systems and embodiments described above amount to examples of the further inventive concept introduced in the previous paragraph. Further examples of potential application areas include grinding equipment and saws (eg for cutting stone kitchen benchtops, a known area of particulate problems). Both mobile and fixed types of equipment can provide other potential applications.

(28) Further embodiments and additional features and inventive concepts are described in the following detailed description, based on the attached drawings.

(29) Everywhere in this specification, the word “comprise” and derivatives thereof including “comprising”, “comprised” and the like, when used in relation to items, elements or steps, are to be taken as indicating presence of those items elements or steps, but not as precluding the possible presence of other items, elements or steps.

(30) Everywhere in this specification, the terms “particulate” and “particulates” are to be understood as short and convenient terms for particulate matter. It is further to be understood that the particulate matter described will in some applications comprise particles with a range of sizes.

Except where otherwise stated, the terms “sealingly” and “gas-sealingly”, where used in this specification in relation to two parts or elements, are to be taken to mean that gas and particulate matter entrained in that gas are wholly or substantially or at least to a useful degree prevented from leaking or passing between the two parts or elements.

Description

BRIEF DESCRIPTIONS OF THE DRAWINGS

- (1) FIG. 1(b) is a perspective view of an enclosure being cleaned;
- (2) FIG. 1(a) is a cross-sectional view of the enclosure shown in FIG. 1(b) being cleaned;
- (3) FIG. 2 is a schematic diagram showing components of a cleaning system according to an aspect of the invention and connections between those components;
- (4) FIG. 3 is a block diagram of instrumentation and control components;
- (5) FIG. 4 is a perspective view of a cabinet for electrical components partially modified to implement the invention;
- (6) FIG. 5 is a partial exploded perspective view of the cabinet shown in FIG. 4;
- (7) FIG. 6 is a perspective partially exploded view of an assembly comprising a frame and door of the cabinet shown in FIG. 4;
- (8) FIG. 7 is a front elevation of the cabinet shown in FIG. 4;
- (9) FIG. 8 is a partial section of the cabinet of FIG. 7, the section being taken at station BB in FIG. 7;
- (10) FIG. 9 is an enlarged view of detail A of FIG. 8;
- (11) FIG. 10 is a sectional view of the cabinet as shown in FIG. 7, the section being taken at station DD of FIG. 6;
- (12) FIG. 11 is a vertical section through an alternative port assembly according to the invention, when in use;
- (13) FIG. 12 is a vertical section equivalent to FIG. 11 showing the alternative port assembly of FIG. 11, now when not in use.
- (14) FIG. 13 is a view exactly equivalent to FIG. 8 of a temporary version of the frame shown in FIG. 8;
- (15) FIG. 14 is a vertical section view of an enclosure fitted with a temporary cover according to an embodiment of the invention;
- (16) FIG. 15 is a side view of a cleaning lance according to the invention fitted with a collar assembly;
- (17) FIG. 16 is a perspective view of a cabinet and a further cover assembly positioned ready to be secured to the cabinet;
- (18) FIG. 17 is an elevation of a clamp assembly as shown in FIG. 16 and as seen looking in the direction of arrow “17”;
- (19) FIG. 18 is a cross-sectional view of a port assembly of the cover shown in FIG. 16;
- (20) FIG. 19 is a perspective view of the port assembly shown in FIG. 18;
- (21) FIG. 20 is a sectional view of an enclosure showing a method of blowing gas according to the invention that is an alternative to that of FIG. 1(a);
- (22) FIG. 21 is a sectional view of an enclosure showing an method of blowing gas according to the invention that is an alternative to that of FIG. 1(a);
- (23) FIG. 22 is a side view of an open-topped railcar (whose upper section is shown in longitudinal cross-section) and a cleaning apparatus according to a further aspect of the invention;
- (24) FIG. 23 is a side view, with one portion shown in section, of an assembly of components of the system shown in FIG. 2;
- (25) FIG. 24 is a perspective view of a cabinet and a further cover assembly positioned ready to be

secured to the cabinet;

(26) FIG. 25 is a longitudinal central section of a shipping container (with some detail omitted) fitted with particulate removing equipment;

(27) FIG. 26 is a longitudinal central section (equivalent to FIG. 25) of a shipping container (with some detail omitted) fitted with alternative particulate removing equipment;

(28) FIG. 27 is a longitudinal central section of a barrel-type container fitted with apparatus for removing particulate matter;

(29) FIG. 28 is a set of three schematic diagrams showing different ways in which the apparatus and methods described herein may be applied;

(30) FIG. 29 is an elevation of an exterior side of a further enclosure cover according to the invention;

(31) FIG. 30 is a partial cross-section taken at station "30-30" in FIG. 29;

(32) FIG. 31 is a partial cross-section taken at station "31-31" in FIG. 29;

(33) FIG. 32 is a schematic view of an enclosure of components of the invention and an enclosure being cleaned, these two enclosures being connected by a duct through which gas and particulate matter is withdrawn from the enclosure being cleaned. The duct is shown in section;

(34) FIG. 33 is a perspective view of yet another cover assembly according to the invention;

(35) FIG. 34 is an elevation of a portion of a prototype system according to the invention;

(36) FIG. 35 is an exploded view of the prototype portion shown in FIG. 34, now with a filter holder and screw cap removed as if for emptying of filter bag;

(37) FIG. 36 is a perspective view of an elongate filter bag holder for use in the invention;

(38) FIG. 37 is a transverse sectional view of the holder of FIG. 36 in use with a contained filter bag, the section being taken at station "A" of FIG. 36;

(39) FIG. 38 is a perspective view of still another cover assembly according to the invention, shown in a vertical orientation;

(40) FIG. 39 is a perspective schematic view of a light source for use in the cover assembly of FIG. 38;

(41) FIG. 40 is a cross sectional view on a vertical plane through one port of the cover assembly shown in FIG. 38;

(42) FIG. 41 is a schematic block diagram of an instrumentation, data processing and communication system of an embodiment;

(43) FIG. 42 is a perspective view of a further cover assembly and an enclosure, the cover assembly being shown positioned for placement on an opening of the enclosure;

(44) FIG. 43 is a partial cross-section of the cover assembly of FIG. 42, the section taken at station "AX-AX";

(45) FIG. 44 is a perspective view of an exterior portion of the cover assembly shown in FIG. 42;

(46) FIG. 45 is a perspective view of a still further cover assembly and an enclosure, the cover assembly being shown positioned for placement on an opening of the enclosure;

(47) FIG. 46 is a side elevation of a cleaning lance according to the invention;

(48) FIG. 47 is a perspective view of a portion of the cleaning lance as shown in FIG. 46;

(49) FIG. 48 is a schematic diagram showing components of a further cleaning system according to the invention;

(50) FIG. 49 is a schematic elevation of a motor-generator set;

(51) FIG. 50 is a schematic elevation of the motor generator set of FIG. 49, now showing by dotted lines spaces in which the invention may be applied;

(52) FIG. 51 is a side elevation of a portion of the motor generator set as shown in FIG. 49;

(53) FIG. 52 is a side elevation the same as FIG. 51, save for the addition of a cover assembly according to the invention;

(54) FIG. 53 is a cross-section taken at station "Q-Q" of FIG. 52;

(55) FIG. 54 is a cross-sectional view of a cover assembly portion, the section being taken at

station "R-R" of FIG. 52;

(56) FIG. 55 is a perspective view of an end portion of the motor generator set of FIG. 49, now fitted with cover assemblies according to the invention;

(57) FIG. 56 is a schematic view of an arrangement in which a dust hood is ventilated and may be cleaned according to the invention;

(58) FIG. 57 is a view of a particulate cleaning and ventilation system according to the invention comprising the system as shown in FIG. 34 in combination with a pre-treatment system;

(59) FIG. 58 is a schematic of the pre-treatment system as shown in FIG. 57;

(60) FIG. 59 is a partial view of a modified version of the system as shown in FIG. 34, in use and with a portion of its ductwork shown in section;

(61) FIG. 60 is the same view as in FIG. 59 of the system shown in FIG. 59 in use and with a portion of its ductwork shown in section;

(62) FIG. 61 is a perspective view of a further cleaning lance according to the invention;

(63) FIG. 62 is a perspective view of a duct connection assembly for use with a flexible cover assembly, secured to a structure;

(64) FIG. 63 is a schematic view of an enclosure being cleaned in accordance with an aspect of the invention;

(65) FIG. 64 is a schematic view of an enclosure being cleaned in accordance with an additional aspect of the invention;

(66) FIG. 65 is a perspective exploded view of a yet further cover assembly according to the invention;

(67) FIG. 66 is a horizontal cross-section of the cover assembly as shown in FIG. 65 in position for placement over an opening of a cabinet, the section being taken at the position of arrow "Z" in FIG. 65;

(68) FIG. 67 is a partial horizontal cross-section of the cover assembly as shown in FIG. 65, the section being taken at the position of arrow "Z" in FIG. 65;

(69) FIG. 68 is a partial horizontal cross-section of a modified form of the cover assembly as shown in FIG. 65, the section being taken at the position of arrow "Z" in FIG. 65;

(70) FIG. 69 is a partial horizontal cross-section of a further modified form of the cover assembly as shown in FIG. 65, the section being taken at the position of arrow "Z" in FIG. 65;

(71) FIG. 70 is a partial horizontal cross-section of a yet further modified form of the cover assembly as shown in FIG. 65, the section being taken at the position of arrow "Z" in FIG. 65;

(72) FIG. 71 is a perspective view of a yet further cleaning lance according to the invention;

(73) FIG. 72, is a further perspective view of the cleaning lance shown in FIG. 71;

(74) FIG. 73 is a perspective view of a cleaning lance portion according to the invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

(75) The following description, based on FIGS. 1-3, is based for convenience on arrangements and methods for cleaning particulates from cabinets such as those used for containment of electrical and electronic components and the like. However, other arrangements and applications are disclosed also, and it is to be understood that the same principles are applicable to them.

(76) FIGS. 1(a) and 1(b) show schematically how an internal space 2 of a cabinet (that is, an enclosure) 4 containing electrical (or other) components 6 can have accumulations of particulates removed.

(77) A door 8 of cabinet 4 seals against fixed part 5 of cabinet 4 due to a seal 7 that extends peripherally around the edge of door 8. Door 8 has at least one port assembly 10 through which a rigid, elongate cleaning lance 12 can be inserted so that a part of its length is in internal space 2. Cleaning lance 12 is elongate and tubular and provided with gas from a source 32 (see FIG. 2) external to cabinet 4, the gas being expelled in a stream or jet from a nozzle 14, nozzle 14 being inside internal space 2 during that part of the cleaning process shown in FIG. 1(a). In some embodiments, cleaning lance 12 has a manually operable valve 16 for control (including shutoff) of

gas flow through nozzle **14**. Blowing a stream or jet of gas into internal space **2**, as shown in FIG. **1(a)**, allows dislodgement of particulates from internal surfaces of cabinet **4** and components **6** and agitation of dislodged particulates so that they are entrained in gas within the internal space **2**. Cleaning lance **12** can be manipulated by a user outside enclosure **4** so as to move the stream of gas ejected from it inside enclosure **4**.

(78) Cabinet **4** also has at least one outlet port **18** through which gas and entrained particulates can leave internal space **2** and be drawn into a duct **20** by an external source (see item **46**, FIG. **2**) of at least partial vacuum. As will be described further below, at least some of the particulates removed through outlet port **18** are removed from the gas downstream of outlet port **18**. Outlet port **18** is shown as comprised in door **8**, but may in alternative embodiments (not shown) be comprised in fixed part **5** of cabinet **4**. The position of the outlet port is selected to benefit from gravitational settling and stratification of the dust so that the dust can be extracted as completely as possible. Further, an extension duct (not shown) may be fitted to the outlet port **18** to move the location from which gas and entrained particulates further into the enclosure **4**. (This approach may also be taken in other embodiments described below.)

(79) Cleaning lance **12** can be manually oriented (as shown by arrows **15**), and the extent of its penetration into space **2** varied (as shown by arrows **17**), by a user of cleaning lance **12** to orient and position nozzle **14** to best effect for dislodging particulates. Door **8** is provided with a transparent viewing window **22** so that the cleaning lance **12** in internal space **2** can be seen during cleaning. The purpose of providing multiple ports **10** is to enable a user to withdraw cleaning lance **12** from one port **10** and then insert it into another port **10** so as to dislodge particulates in multiple locations in internal space **2**.

(80) Cleaning lance **12** is a gas discharging device and essentially comprises a gas flow control valve **16** for manual operation by a user and an elongate tube **13** through which gas leaving valve **16** passes to nozzle **14** from which it issues in a gas stream or jet. Nozzle **14** may be of any suitable form or may be omitted altogether so that gas simply issues from an open end of tube **13**. Nozzle **14** may direct gas at an angle to the length of tube **13**, for example, or may even be freely rotatable about a lengthwise axis of tube **13** and expel gas at an angle to tube **13** such that reaction force from the gas stream causes the nozzle **14** and its emerging jet of gas to rotate. Nozzle **14** may optionally simply comprise an open end of tube **13**, but in other embodiments would comprise a fixture that causes gas to increase in speed (hence momentum) as it leaves tube **13**. Such a nozzle **14** may be detachable from tube **13**.

(81) In use of the method and apparatus illustrated in FIG. **1(a)**, particulate dislodgement and removal from the internal space **2** is continued until there is a satisfactorily low concentration of particulate matter entrained in the gas leaving the internal space **2**. As set out below, a sensor for such concentration is provided, and information on the concentration is provided to a user so that cleaning can cease when the concentration is low enough. By maintaining a pressure in the internal space **2** that is lower than the atmosphere outside the internal space **2**, leakage of particulate around the door **8** or through the ports **10** during the cleaning operation is limited or prevented.

Concentration measurement provides an objective criterion for ending the cleaning process.

(82) FIG. **1(b)** shows another mode for particulate removal from internal space **2**. Door **8** has been opened and particulates are being drawn into a duct **24** by the above (or a second) partial vacuum source. Particulate removal in this way may be done before or after a period of particulate blowing as shown in FIG. **1(a)** as found appropriate or between periods of particulate blowing.

(83) In some applications, it is appropriate to remove significant accumulations of particulates first by the method shown in FIG. **1(a)** and then through use of the conventional vacuuming approach of FIG. **1(b)**.

(84) While the methods of FIGS. **1(a)** and **1(b)** have been illustrated by reference to an enclosure **4** with modifications to its door **8**, there will be described below embodiments in which a temporary cover is placed over an opening of an enclosure having an internal space instead of a door.

(85) Although FIG. 1(a) shows all port assemblies **10** to be provided in door **8**, it is possible to provide port assemblies (not shown) in other parts (eg top, bottom or side walls) of cabinet **4**.

(86) The gas may be air in suitable cases or may be an inert gas such as (for example only) nitrogen or carbon dioxide (derived for example from dry ice). Inert gas may be appropriate where fire, explosion or chemical reaction is a potential hazard.

(87) FIGS. **2** and **3** show schematically an embodiment of a cleaning system **30** that is operable as described above to remove particulates from the enclosure **4**. System **30** includes an instrumentation and control system **199** that is not shown in FIG. **2**, but whose functionality is illustrated separately and schematically in FIG. **3**.

(88) Referring firstly to FIG. **2**, a gas source **32** is provided to direct gas to nozzle **14** through a conduit **34** which includes both a flexible hose portion **33** and cleaning lance **12**. Where air is to be the gas, gas source **32** may comprise, for example, a pump or blower (centrifugal or axial or a hybrid of these) or a reciprocating-piston compressor or a container of compressed air. In some applications and facilities, a reticulated compressed air supply (not shown) may be available and a connection thereto can constitute gas source **32**. Gases other than air may be used, being stored as a gas, or as a liquid or solid that changes phase on or before discharge, or generated by chemical reaction.

(89) Conduit **34** may comprise flexible hose to enable manipulation of the cleaning lance **12**.

(90) Item **52** in FIG. **2** represents one or more components for conditioning and controlling the gas supply to lance **12**. It is preferred that the gas supply is conditioned to be substantially oil- and moisture-free, and components are known in the art for achieving this. More will be said about item **52** below.

(91) Gas and entrained particulates are drawn out of enclosure **4** through duct **20** connected to enclosure **4** at outlet port **18** and then through a cyclone separator **38** (of which one is shown, but multiple cyclones may be used if appropriate to a particular application) and filters **40** and **42** by a blower **46**. Together the cyclone **38** and filters **40** and **42** remove particulate matter to a desired standard (particle size and concentration). One or more of the filters **40**, **42** may be a “High Efficiency Particulate Air” (HEPA) filter. Although two filters **40** and **42** are shown in FIG. **2**, this is not intended to be a limitation. More than two filters may be used, or in suitable cases even one filter only or no filter at all. Duct **20** may comprise a length of suitable flexible ducting. Where duct **20** comprises a flexible material reinforced with a spiral wire, or otherwise comprises conductive material along its length, that wire or conductive material may be preferably earthed to limit explosion risk when battery power is used for the system **30**.

(92) To draw gas and entrained particulates from the enclosure **4**, a vacuum source, such as a suitable fan or blower **46** is provided so that pressure in duct **20** is reduced. As shown in FIG. **2**, this may be located downstream of the cyclone **38** and filters **40** and **42**.

(93) To also enable direct vacuuming of particulates from enclosure **4** as shown in FIG. **1(b)**, duct **20** may be disconnected from outlet port **18** and used as vacuum hose **24**. Alternatively, as shown in FIG. **2**, a separate duct **48** may be provided that is connected to duct **20** via a selector valve **50** and used as duct **24**. Selector valve **50** allows selection of direct vacuuming through duct **48** (as in FIG. **1(b)**) or removal of gas and entrained particulates as in FIG. **1(a)**. Duct **48** is shown with an end fitting **47** for increasing the flow velocity of flow into duct **48**. Such a fitting may also be used (not shown) with duct **20** if duct **20** is used as duct **24** for direct vacuuming.

(94) Selector valve **50**, where provided, may be adapted to ensure that some suction is maintained in duct **20** even when duct **48** is in use.

(95) In some embodiments, end fitting **47** may be of the same or similar form as lance **12**, so as to be enterable into any of ports **10** and enable direct vacuuming of particulates with door **8** closed. In still further embodiments lance **12** itself is provided with an inlet for gas from the gas source **32**, as above, and additionally with a connection for duct **48**, allowing either suctioning via duct **48** or blowing with gas from gas source **32**. In such embodiments valve **16** comprises a selector for

enabling sucking or blowing.

(96) Still another alternative to the arrangement mentioned in the previous paragraph is to use a separate vacuum cleaner (not shown) for direct vacuuming in cabinet **4**.

(97) Depending on the intended capacity of the system **30**, some or all of the components shown to the left of station “XX” in FIG. **2**, including relevant parts of instrumentation and control system **199** may be provided in a single enclosure. This may be a fixed installation (not shown), or wheel or skid-mounted (not shown), or even comprised in a backpack-type enclosure. In some embodiments, as stated above, gas supply **32** is simply a connection to a reticulated compressed air supply.

(98) It has been confirmed by applicants that a version of system **30** adequate for use in cleaning particulates from electrical cabinets of large diesel-electric mining haul trucks can be implemented in an enclosure the size of a small-to-medium suitcase.

(99) Instrumentation and Control

(100) Instrumentation and control system **199** will now be described, still using the electrical cabinet cleaning application shown in FIG. **1** for illustrative purposes. (Some other applications mentioned below may not require all the functionality described.) Locations in the system **30** which may be provided with sensors of various types are labelled A to L in FIG. **2**.

(101) FIG. **3** is not intended as a detailed indication of hardware components and their connections. It is intended to explain what the system **199** does. The functions are straightforward enough for persons of ordinary skill in the art to implement without more specific detail.

(102) Sensors and associated signal conditioning may be provided in system **30** for the following purposes: (a) to ensure that when particulates are being removed by entrainment, as in FIG. **1(a)**, it is able to be known when a satisfactorily low concentration of particulates is entrained in gas being drawn from the enclosure being cleaned (eg cabinet **4**), (whichever one of port assemblies **10** is in use) so that that process is complete; (b) to enable monitoring of gas leaving blower **46** to ensure it has a satisfactorily low concentration of entrained particulates, so that persons near the point of discharge of gas leaving blower **46** are protected from harm; (c) to enable monitoring of the operation of the various particulate-separation components of the system **30** and so ensure that filters **40** and **42** and cyclone **38** (in particular) are cleaned or emptied when appropriate and blower **46** cleaned if necessary; (d) to ensure that components **6** in the enclosure being cleaned (eg **4**, **60**) and blower **46** are not exposed to unsafe/damaging temperature levels; (e) to enable monitoring of pressure in the enclosure **4** being cleaned to ensure it remains in a range where there is neither damage to the enclosure **4** nor leakage of particulates from the enclosure **4**, in particular by maintaining pressure in the enclosure below atmospheric pressure in the surroundings where work is being carried out; (f) to enable monitoring of the position and/or functioning of the seal **7** and door **8**; and (g) to provide necessary inputs for automatic control of parts of the system **30**; (h) to enable remote (or local) monitoring of the condition of the various parts of the system, so that maintenance and servicing can be carried out in a timely fashion.

(103) Depending on requirements of particular applications and users, embodiments may comprise sensors for all or some only of these purposes. Outputs from the sensors can be used in some or all of the following several ways, as follows:

(104) First, sensor outputs may be displayed directly as numerical measures—for example, pressure or blower **46** temperature in the enclosure being cleaned may be displayed on a suitable display. Alternatively, they can be displayed as “OK/Not OK” visual signals—for example it may be sufficient to indicate that a connected gas supply has pressure enough to be used rather than display its actual value.

(105) Second, numerical quantities may be computed from sensor outputs and displayed—for example flow rate of gas through fan **46** or cleaning lance **12**. Derived quantities also may be provided only as “OK/Not OK” visual indications.

(106) Third, audible or visible alarms can be generated where necessary and diagnostic messages

displayed to guide correction by users. Further, alarm conditions may be used to trigger an automatic shutdown or otherwise limit operation of the system, i.e. to provide a “fail-safe” capability.

(107) Fourth, sensor outputs and quantities derived from them may be recorded by a data logging facility, for verification or diagnostic purposes. For data logging, time stamping of data may be provided and even location may be recorded by provision of a GPS module. This use of sensor outputs is particularly important where it is desired not only to clean enclosures but to ensure that there is proof and/or certification of the standard of cleaning that has been carried out. This is potentially vital in applications where diseases such as silicosis, “black lung” disease and diseases associated with asbestos are to be avoided, for example. Further, purpose (h) above becomes very important in applications where logged data is to be provided to an off-site organisation for monitoring/certification purposes. Only if the equipment's condition can be maintained properly can results be relied upon.

(108) Fifth, as well as the fail-safe capability mentioned above, automatic control of parameters and components may be provided using sensor outputs, as discussed below.

(109) Particular choices from the above can be made according to intended applications.

(110) Regarding purposes (a) and (b) above, the extent of particulate concentration in gas flows can be sensed using triboelectric particulate sensors. These are available from suppliers such as Auburn Filtersense LLC of Beverly, Massachusetts, USA. While triboelectric-type sensors are suitable, other types are known in the instrumentation art and can be used as appropriate, for example sensors based on interruption or attenuation or transformation of a beam or beams of infra-red radiation, visible light, laser, beta rays or other EMF or nuclear radiation by particulates, or even acoustic-type sensors (in effect microphones) which react to impacts of particulates on a surface. The appropriate choice will depend on the particular application at hand.

(111) Thus, to achieve aim (a) above, there may be provided one or more triboelectric (or other suitable) sensor(s) at station F (or a position upstream of it, or even inside space 2),

(112) Operation of triboelectric sensors are sensitive to electric charge due to contact between dust particles and a sensing element of the sensor. However, applicants have found that where a triboelectric sensor is used (at least for purpose (a)), accuracy can be reduced due to charges on dust particles acquired in the space being cleaned and in the duct **20** through which dust laden air is drawn from that space. It has been found that this effect can be reduced by providing an electrical connection between the container being cleaned, the ductwork upstream of the triboelectric sensor and the sensor itself. The connection can be made through a spiral wire on the duct **20** to the fitting by which ductwork **20** is connected to the container. This does not fully eliminate the unwanted charges, but a further improvement can be made by carrying out tests on representative flows of representative dust-laden air through similar duct geometries with actual weighing of the dust content to produce calibration curves relating sensor output to actual flow. Temperature and humidity can also affect accuracy, and by varying and controlling these quantities in such calibration tests, further corrections can be made. The data handling system (described herein by reference to FIGS. **3** and **41**) can be provided with the calibration curves in software form.

(113) To achieve purpose (b) above, there may be provided one or more triboelectric (or other suitable) sensor(s) at station K, downstream of the cyclone **38**, filters **40** and **42** and blower **46**. In some embodiments, a duct (which may be flexible) may be provided to take discharged gas and residual (i.e. unremoved) particulate well away from the area in which the cleaning operation is taking place.

(114) Depending on the gas source, it may be appropriate to provide sensing of gas quality upstream of cleaning lance **12**, for example at stations A or B. At station A, a pressure sensor may be provided to indicate, when cleaning lance **12** is not in use, that gas for blowing is available.

(115) Display(s) for displaying measured quantities may be provided on a casing containing the main components shown in FIG. **2**, or in a separate unit (not shown) connected thereto and in use

placed in a position visible to a user. Key operating parameters such as the concentration of particulate matter at the outlet from the space being cleaned are displayed.

(116) Regarding purpose (c) above, pressure sensors (not shown) may be provided at stations G, H and I to provide a measure of fouling of filters **40** and **42** with particulates, based on pressure drop through them, so that the need for cleaning can be indicated at an appropriate time. Rather than three such separate sensors, two differential pressure sensors (not shown) may be provided, respectively sensing pressure differences between stations G and H and H and I.

(117) Similarly, in some embodiments either another sensor (not shown) is provided to measure the pressure difference between stations F and G, before and after the cyclone **38**, or alternatively separate sensors at stations F and G can be provided. Excessive pressure difference across cyclone **38** can indicate fouling or blockage.

(118) It is also possible to provide a pressure sensor at station K in addition to a pressure sensor at station I, so that the pressure change through blower **46** is known, or alternatively to provide a differential pressure sensor to sense the pressure change between stations I and K, i.e. across blower **46**. The speed of blower **46** may be sensed at station J as well.

(119) Also in relation to purpose (c), at station L, a sensor (not shown) may be provided to indicate that a certain quantity of particulates has been collected in cyclone separator **38** (or a particulates container (not shown) secured thereto), so that for best operation, cyclone **38** should be emptied. This may be of the optical or infra-red type, that senses interruption of a beam, these sensors being well known in the instrumentation art. Alternatively an ultrasonic type may be used, or even a simple “sight-glass” type indicator or transparent section of cyclone **38** may be provided that can be seen by a user. When a “sight-glass” type indicator is used, an LED light positioned and coloured to minimize glare may be used internally within the cyclone **38** or particulates container to enhance visual clarity.

(120) Regarding purpose (d) above, in some embodiments, temperature of the blower **46** is sensed at station J and/or temperature of gas within space **2** is sensed at station C (or even F), in each case with suitable temperature sensors.

(121) Regarding purpose (e) above, during use of cleaning lance **12**, it is desirable that gas pressure in cabinet **4** be maintained at a level that does not lead to significant risk of particulates leakage from the cabinet **4** through for example port assemblies **10** or past seal **7** around door **8**. A pressure in cabinet **4** slightly below external (atmospheric) pressure is suitable in many applications, as it limits the potential for leakage of particulates from cabinet **4**.

(122) It is also desirable that during the blowing operation, pressure in cabinet **4** not become too high or too low, to avoid distortion or even structural failure of cabinet **4**. A simple approach is to provide a pressure sensor (not shown) at station C (i.e. sensing absolute pressure within space **2** of cabinet **4**, or the difference between the pressure inside space **2** and the atmosphere). Actual control of the pressure in space **2** is described below. The pressure sensor (not shown) may be located physically on the cabinet **4** or on door **8** with signals communicated to instrumentation and control system **199** via copper cable, optical fibre, wireless or other suitable means. Alternatively, the pressure sensor may be mounted away from the cabinet **4** and communicate with space **2** via a small-bore flexible tube.

(123) Regarding purpose (f) above, it is important when blowing gas into an enclosure such as cabinet **4** that there be no leakage of air (and entrained particulates) past elastomeric seals such as seal **7** of cabinet **4**, due for example to seal **7** failing to close off excessive gaps between door **8** and cabinet **4** at positions along the seal **7**. For applications such as that shown in FIG. 1), where a hinged door **8** is sealed by seal **7**, a single sensor (not shown) may be provided to sense whether the door **8** is in the correct position, relative to cabinet **4**, for correct operation of seal **7**. This could be a simple microswitch or a proximity sensor mounted to door **8** or cabinet **4**. If seal **7** is a pneumatic (i.e. inflated) seal, a pressure sensor may be provided to sense pressure in the seal **7**.

(124) However, in some embodiments described below, a detachable cover (see for example item

310 in FIG. 16, item **310a** in FIG. 24, item **310b** in FIG. 33, item **310c** in FIG. 29) is used to close off an enclosure or space. In these cases, multiple proximity or other suitable sensors (not shown) may be provided at spaced-apart positions around the cover periphery to enable monitoring of seal operation. These sensors may be of proximity type as above, or be responsive to pressure between the seal and enclosure or electrical conductivity between metallic areas on either side of the seal and facing parts of the enclosure or cover. The sensor locations would correspond for example to stations D and E in FIG. 2.

(125) If measurement of gas flow rate to lance **12** is required, a flow meter (not shown) may be provided at station B. This could be of any suitable type, for example a venturi section or calibrated orifice plate with sensor(s) to measure the pressure change therethrough (and ideally temperature as well), or a sophisticated thermal sensor such as those available from E+E Elektronik GmbH of Germany. Also, and in the same or any other suitable way, the gas flow rate out of space **2** may be measured. This may be done at station I or station K, where the measurement is unlikely to be influenced by entrained particulates. For applications where concentrations are expected to be sufficiently small, outlet flow rate measurement may be made with sensors at any of stations F, G, H or I.

(126) Regarding purpose (g) above, control of the blowing/entraining operation will now be described.

(127) In some embodiments, gas flow to the cleaning lance **12** from supply **32** is simply turned on or off as required, by a user, with blower **46** running continuously. The user, as well as monitoring the extent of particulate concentration (visually, or by use of particulate concentration sensor(s) as described above) can monitor pressure in the space **2** if displayed, or simply be alert for alarms based on the sensed pressure in space **2** being, or threatening to be, out of a specified range.

(128) A more sophisticated approach in other embodiments is to include in item **52** (FIG. 2) a solenoid valve that can interrupt (or vent to atmosphere) gas flow to cleaning lance **12** automatically if required to prevent overpressure (or loss of appropriate partial vacuum) in space **2**. Similarly, blower **46** can be stopped automatically or slowed down, (or a damper operated) if required to prevent an excessively low pressure in space **2**. The system **199** generates signals to control the blower **46** and/or solenoid valve in item **52**, based on sensed pressure in space **2** or a mismatch of inlet and outlet flow rates.

(129) For either of the approaches described in the previous two paragraphs, generation of an alarm and/or of automatic control signals can be anticipatory, based on rate of change of pressure or gas flow rates.

(130) In still other embodiments, closed-loop automatic control is used, subject to maintenance of a “fail-safe” capability. For example, cleaning lance **12** may be manually controllable by a user (i.e. with gas flow rate set to off, fully on, or any intermediate value), with blower **46** and/or a variable-flow valve included in item **52** controlled automatically by system **199** to maintain a chosen value (i.e. set point) of pressure in space **2** or net gas flow rate into space **2**. Alarms and/or display of operating parameters may be provided also in these embodiments. For further example, cleaning lance **12** may be simply set to “off” or “fully on”, with closed loop control of a set pressure in space **2**, net flow rate into the space **2**, or a specified flow rate through lance **12**.

(131) Note that while maintaining appropriate pressure within a space being cleaned is important, it is to be noted that in many industrial, mining and similar applications, it is unlikely that an excessively high or low pressure will in fact be encountered. This may be, for example because an enclosure being cleaned is itself leaky and therefore an accumulator of particulate matter. Accordingly, in some applications, sophisticated control and even sensing of cleaned space pressure can be safely dispensed with.

(132) Referring now to FIG. 3, the presence of block **200** indicates the presence of one or more data processing components adapted to provide the functionality described herein. It is to be understood that block **200** may simply comprise a single processor (microprocessor or otherwise)

or several processors each covering a subset of the functions required. For example, if there is a closed-loop control functionality as described herein, that may have a dedicated processor. Some or all of the functions carried out within block **200** may be implemented wholly or partially by other means than microprocessors—for example field-programmable gate arrays (FPGAs) may be used to implement some functionalities. Multiple data processing components may be comprised in block **200**, for example, where a variable-flow valve is included at item **52** and has its own internal electronics or where a particulate concentration sensor is provided that has its own data processing components.

(133) The data processing componentry of block **200** is provided to receive inputs from sensors and system controls and, using these, to drive a display at **208**, and/or a set of alarms at **210** and, as applicable, control outputs at **207**. It may not be essential for a particular application or embodiment to provide and use all of the sensors described above. For example, in some embodiments reliance may be placed on visual inspection of cyclone **38** to determine that it needs emptying, rather than providing a sensor at station L. However, in general some sensors will be used, and block **202** represents a set of sensor excitation (i.e. powering) and any necessary signal conditioning functions, all as required to convert raw signals from the sensors to a form (digital or analog) suitable for the processing function **200**. (Note that many processors have internal analog-to-digital converters and so can accept analog signals.) The triboelectric sensors of the prototype system described below provide outputs in current-loop form, while the pressure transducers provide digital outputs directly.

(134) Block **204** represents presentation of sensor outputs to the processor at **200**. For example in the prototype system described below, a multiplexer is used to provide **8** scannable channels for pressure sensors via the I^{sup}.2C bus protocol. Multiplexing of sensor outputs may be provided if there are more sensors used than the number of inputs provided by the chosen microprocessor **200**. Note that as discussed above there may be several sensors at some stations, for example a pressure sensor and a temperature sensor at station C. FIG. **2** is not intended to suggest a maximum of 12 sensors (A-L). Block **200** may also include any or all of: automated fault detection, diagnostics and datalogging capabilities.

(135) System **30** also requires some control inputs provided at block **206** such as on/off switches (not shown) for the blower **46** and the gas supply **32** if it includes a dedicated compressor for example, and to initiate operation of data acquisition by system **199**. If any quantity is to be controlled in closed-loop manner, there may be a control (eg potentiometer) to provide a set point for the mass flow rate. There may also be controls (eg potentiometers in the case of analog control implementation) to set allowed maximum and minimum pressures in the enclosure to be cleaned.

(136) Block **207** represents provision of signals required for automatic functions—for example shutting off the gas source **32** if pressure at station C rises too much or a continuous control signal where closed-loop pressure control is provided.

(137) Block **208** represents provision of the function of one or more suitable display(s) for visual output of system **30** information as required. For example, there may be display of outputs for particulate concentration from triboelectric sensors at stations F and K. Displays (not shown) may use any suitable technology, for example LED, LCD or OLED. The two last of these may be of a touch screen type arranged to receive any or all of the inputs mentioned in relation to block **206** above.

(138) Block **210** represents provision of a separate display of alarm conditions for system **30**. For example, it may indicate that cyclone **38** requires emptying or that filters **40** or **42** have pressure drops indicating that they need cleaning, or that pressure in the enclosure being cleaned is outside its set limits, risking damage or particulates leakage. Such alarm functions may actually be incorporated in and displayed on the display **208**, or may be provided separately, for example using a known “traffic light” format (not shown) based on green, yellow and red LEDs to indicate respectively—no alarm or normal operation, warning, alarm condition.

(139) The following is a list of conditions and responses that may be automatically recognized and caused within block **200** to generate alarms or control signals that provide system **30** with a “fail safe” capability. Excessive particulate contents at either inlet or outlet of blower **46**—shut down blower, provide diagnostics. Where intention is to operate at negative pressure—pressure excessively low (with risk to structure) or not low enough (risking leakage of particulates). If not low enough, interrupt flow into the enclosure, also check blower, filter(s) cyclone fouling. If too low either stop blower or reduce blower speed. Where positive pressure in enclosure **4** is allowed—pressure excessively high risking structural damage or leakage of particulates. Interrupt flow into enclosure, increase blower speed, check for fouling of filter(s) or fouling or filling of cyclone(s). Fouling of filter(s)—stop operation of system. Fouling or filling of cyclone(s) **38**—stop operation of system. Blower **46** temperature excessive—stop operation of system. Blower **46** not operating or underspeed—stop operation of system. Where seal **7** is a pneumatic seal—seal pressure out of allowable range—stop operation of system. Where seal **7** is pneumatic or non-pneumatic—any one or more of seal position measurements (if sensors fitted) out of allowed range. (Or if pressure sealing pressure sensor(s) fitted, any one or more of their outputs out of range. Stop operation of system.

(140) Block **211** represents the writing of sensor and other data to some form of storage. For example, the prototype system described below is provided with a facility to write data based on sensor outputs to an SD card for later downloading and checking. In that system, all active sensors are scanned cyclically once the system is in operation and derived outputs from them are time stamped using a real-time clock module and written to an SD card.

(141) Block **213** represents communication of data to location(s) away from the worksite and receipt of instructions and/or the like from external sources. For example, where a service provider wishes to provide checking and certification of critical particulate removal operations from a location away from the site of the operation, it is possible to provide a communications interface for the transmission and receipt of data and instructions. As an example, a mine may have a wireless packet-switched digital data network covering its entire site that can be used to communicate with a base station, and that base station may communicate via the mobile phone network or via the internet by whatever other connection means is available. Where mobile phone network accessibility is available at a worksite, it may be used and the base station may not be necessary. The service provider may carry responsibility for correct functioning, calibration and the lie for the equipment used for particulate removal, and receipt of data from the various sensors described facilitates this function. Data and instructions may be transmitted substantially in real time or data may be written to memory (eg using an SD card) by system **199** for later transmission.

(142) Note that although the above disclosure has referred to particulate removal, it is possible to use the apparatus as shown in FIGS. **1(a)**, **2** and **3** for purging of gases from enclosed spaces, either as an alternative to particulate removal or in any application where both particulates and undesired gas are both present. An online gas analysis device suited to the gas in question may be provided at for example any of stations F, G, H, I or K, instead of or in addition to a particulate concentration sensor.

(143) Ways to arrange for the methods of FIGS. **1(a)** and **1(b)**, and the operation of system **30** (including system **199**) to be applied to other enclosures will now be described.

Example—Application to Cabinets

(144) FIGS. **4** to **10** show one way in which a typical existing cabinet **60** for electrical components (not shown) can be modified to implement the invention using cleaning system **30**, cabinet **60** corresponding to enclosure **4** in FIGS. **1** and **2**. Cabinet **60**, is a cabinet such as might typically be found in an industrial facility or in heavy mobile equipment such as a locomotive or mining haul truck, and has a fixed main portion **62** defining enclosed upper and lower spaces **64** and **66** respectively for electrical components. Cabinet **60** has been modified to enable cleaning of particulates using the invention, but only in respect of the upper space **64**.

(145) Closure of opening **68** of lower enclosed space **66** is provided by a conventional hinged door **70** normally held closed by a handle-operated latch **72**. A peripheral elastomeric seal **74** mounted to main portion **62** extends around opening **68** to limit ingress of contaminants such as particulates when door **70** is closed.

(146) Normally, cabinet **60** would have a hinged door essentially the same as door **70** except for its dimensions being suited to close opening **76** of upper space **64**, and also a similar peripheral sealing arrangement. However, according to the modification, a rectangular frame **78** is secured (for example by welding at **81**) to main portion **62** and extends peripherally around opening **76** of the upper space **64**. A hinged door **80** is supported on frame **78** and can be opened to allow access to upper space **64** when required. Door **80** is received in frame **78** and held closed by handle-operated latches **82**, and contaminant ingress and between door **80** and frame **78** is limited by a peripherally extending elastomeric seal **84**. Because cleaning can involve temporarily increasing pressure in upper space **64**, door **80** includes a reinforcing member **79** extending around its periphery.

(147) Door **80** has features that enable the invention to be implemented for cleaning of upper space **64**.

(148) First, door **80** is provided with port assemblies **86** (corresponding to port assemblies **10**) through any of which cleaning lance **12** can be pushed partway into upper space **64** at in the way shown for enclosure **4** in FIG. **1(a)**. Door **80** also has a transparent viewing window **88** corresponding to window **22** in FIG. **1(a)**.

(149) Second, for removal of particulates from upper space **64**, at least one outlet port **90** (corresponding to outlet port **18** in FIG. **1(a)**) for gas and entrained particulates is provided in door **80**. This has a removable cover **92** that can close outlet port **90** when cleaning is not underway. Duct **36** is secured to outlet port **90** for use when cleaning upper space **64**. Outlet port **90** is provided in door **80**, however in some embodiments (not shown) it may be provided (or an additional outlet port may be provided) at a suitable location in cabinet main portion **62**.

(150) In FIG. **6**, one of port assemblies **86** is shown in exploded fashion. One or more discs **94** of gas impermeable elastomeric material (for example formed from an artificial or vulcanized natural rubber) are provided, each with a slit **96** extending across part of a diameter, and discs **94** are arranged in layered fashion with slits **96** oriented in different directions as shown. Discs **94** are secured against the door **80** by a ring **98** using fasteners (not shown) extending through holes **100** in ring **98** and door **80**, ring **98** being concentric with a hole **102** in door **80**. Port assemblies **86** can be reasonably (not absolutely) gas- and particulates-tight when not in use. Cleaning lance **12** can be pushed through slits **96** so that its nozzle **14** is inside the enclosure, while the gas supply hose **34** remains outside cabinet **60**. Moreover, cleaning lance **12** can be rotated about its length as required, its angle to the door **80** varied, and the distance beyond door **80** to nozzle **14** can be varied by a user as required. The number of port assemblies **86** on door **80**, and their positions, may in some embodiments be chosen to suit the arrangement of components within the enclosure **60** to enable most effective and thorough cleaning.

(151) Note that the use of frame **78** as shown in FIGS. **4** to **10** is a measure that was adopted for the particular cabinet **60** described here, which had inadequate gas and particulates sealing around door **80**. For a cabinet and door having adequate sealing arrangements (not shown) the door features described above may be able to be implemented by simply modifying the original door.

(152) As shown in FIG. **15**, the cleaning lance **12** may have a collar assembly **170** securable in any of a range of positions on tube **13** so as to prevent excessive penetration of cleaning lance **12** into the enclosure (for example cabinet **60**, cabinet **150** or enclosure **4**), leading to potential damaging of components therein.

(153) Alternatives to the port assemblies **10** shown in FIGS. **4** to **10** are possible. One such is shown in FIGS. **11** and **12**. FIG. **11** shows a port assembly **200** secured to an enclosure door **202** (similar for example to door **80** or door **8**) and providing access for cleaning lance **12** to an internal

space **204**. Port assembly **200** comprises an elastomeric bellows or boot **206**, secured to door **202** by a ring **208** and fasteners **211**. Secured to bellows **206** is a block **210** through which, in use, tube **13** of cleaning lance **12** can pass. Tube **13** can slide lengthwise in, and rotate relative to, block **210**, and be angled in horizontal and vertical planes as shown by arrows **214**, and sealing between tube **13** and block **210** is provided by an elastomeric O-ring seal. Other seal arrangements may be used depending on the application (eg lip seals, multiple seals). When port assembly **200** is not in use, a lid **216** is screwed onto a threaded portion of ring **208**, after withdrawal of tube **13**, to prevent gas and particulates egress. (Note that a lid (not shown) equivalent in function to lid **216** could be screwed to block **210** instead of ring **208**.) Port assembly **200** requires that any nozzle **14** comprised in cleaning lance **12** be of lesser diameter than tube **13**, so that tube **13** can be entered through block **210**.

Alternative Embodiments—Cover Assemblies

(154) Further alternatives to the arrangements that were described above by reference to FIGS. **4** to **10** will now be described.

(155) FIGS. **4** to **10** showed a permanent modification to an existing cabinet **60** to implement the invention, in which a frame **78** was secured to a main portion **62** of the cabinet **60**, the frame **78** itself incorporating a door **80**. Another approach applicable to cleaning of cabinets with hinged doors will now be described. This is to provide a temporary cover which can be secured sealingly over the opening of the cabinet after either removing or swinging open the cabinet's existing door.

(156) FIG. **13** shows in a view equivalent to FIG. **9** a temporary cover **77** comprising a frame **78a** that is exactly the same as frame **78** in all respects, including provision of a door **80a** equivalent to door **80**, except that frame **78a** lacks a member equivalent to member **83** (see FIG. **9**) secured to cabinet portion **62** at **81**. Instead, a retaining member extending peripherally around frame **78a** is provided together with an elastomeric seal **87**, also extending peripherally around frame **78a**. When particulates are to be dislodged by use of cleaning lance **12**, cover **78a** is temporarily secured to cabinet main portion **62**, being held in place by suitable clamps (not shown), the original door (not shown) of cabinet **60** being swung aside or removed altogether. Seal **87** may be inflatable with a gas to enhance its sealing action. When cleaning is complete, frame **78a** is removed.

(157) FIG. **14** shows a view (in vertical section) of a cabinet **150** fitted with an alternative temporary cover **152** for cleaning. Cover **152** is secured by suitable clamps **154** on its periphery. Cover **152** is sealed against cabinet **150** by a peripheral seal **156**. This may if desired be of a type inflatable by gas. Cover **152** has port assemblies **158** which may be the same as port assemblies **10** and a gas-and-particulates outlet port **160** for connection of duct **20**. Cover **152** has a dished shape (as seen in the section of FIG. **14**) to provide more room between the port assemblies **158** and components **162** in cabinet **150** than would be provided by for example cover **78a**. Where practicable, this shape can be advantageous in enabling easier and better positioning of cleaning lance **12** and reduced risk of contact with and damage to components in cabinet **150**. Further, cover **152** is formed from a substantially transparent plastics material (eg polycarbonate or acrylic) to provide for easy visibility of the cabinet interior while cleaning lance **12** is in use. Anti-scratch treatments are known in the art and may be applied to at least the inward surface of cover **152**. Still further, a set of light-emitting components (eg LEDs) is provided inside the space **164** formed by cabinet **150** and cover **152** to enhance visibility within space **164**. (This approach to lighting is applicable also to other embodiments, such as those shown in FIGS. **4** to **10** and **13**.) Cover **152** is shown without a door equivalent to door **80a** of cover **77** but a hinged door could be provided in cover **77** if desired (not shown).

(158) FIG. **16** shows still another temporary cover **310** that is an alternative to those described above. A cabinet **300** has an internal space **302** that is to be cleaned of particulates. Cabinet **300** has a flange **304** surrounding an opening **306** that in ordinary use of cabinet **300** would be closed by a door or other cover. (No such door or cover is shown in FIG. **16**.) Hinges **308** could for example support such a door that either is simply swung open or removed from cabinet **300**. To cover

opening **306**, cover **310** is provided.

(159) Cover **310** has a formation **312** on its upper edge **314** that can be hooked over an upper part of flange **304** when cover **310** is moved in the direction of arrows **305** towards flange **304**. Cover **310** is then held in position over opening **306** by clamps **316**. Extending around the periphery of cover **310** is a seal **318** that in use of cover **310** bears sealingly against flange **304** to prevent or limit passage of particulates from internal space **302** during cleaning (similarly to seal **84** of FIG. **8**). Seal **318** is of rubber or a rubber-like material and may optionally be of a pneumatic type inflated with a gas. (A seal (not shown) serving the same purpose as seal **318** may, in alternative embodiments, be provided on an enclosure being cleaned for use with a cover otherwise equivalent to cover **310**. Further, such a cover or a cover with a seal such as cover **310** may instead of being hung from a flange (such as flange **304** in FIG. **16**, be hung from a suitable temporary or permanent formation specifically provided.)

(160) FIG. **17** shows one of the clamps **316**. This has a magnet **322** that in use holds itself against surface **307** of cabinet **300**, and captive thereon a bolt **324** passing through cover **310**. A wingnut **326** can be screwed on bolt **324** to move cover **310** towards surface **320**. Bolt **324** passes through a compression coil spring **325** between the magnet **322** and cover **310** to aid correct positioning of magnet **322** when cover **310** is being positioned ready for use.

(161) Any other suitable clamp arrangement can be used as an alternative to clamps **316**. In other embodiments, where control of pressure within an enclosure being cleaned is sufficiently reliable, to maintain a negative pressure within that enclosure at all times and dispense with some or all clamps such as clamps **316**. The cover **310** is then held in place entirely or partially by atmospheric pressure due to the lesser pressure inside the enclosure. Another approach (not shown) as an alternative to clamps **316** is to provide magnetic tape to cover **310** extending around all or part of the periphery of cover **310** so as to be attracted to (for example) flange **304**. Still another approach (not shown) is to provide discrete magnets recessed into cover **310** on its enclosure-facing side that are positioned to be abut flange **304** and be held by the magnets against it.

(162) While port assemblies of the types described above (i.e. items **10**, **200**) may be used for cover **310** for insertion of a cleaning lance such as lance **12**, cover **310** is shown with port assemblies **340** of a further type. Cover **310** has multiple openings **330** each covered (on the outer side of cover **310**) by a movable cover **332**, as shown in FIGS. **18** and **19**. Movable cover **332** acts as a restriction to flow and possible particulate leakage through opening **330** when the port assembly **340** is not in use accommodating a lance **12**. Openings **330** are bevelled at **331** to accommodate a range of angular movement of lance **12**. Each cover **332** is supported on a pivot pin **334** so as to be freely swingable about an axis **336** by a user to uncover the associated opening **330**. A cleaning lance such as cleaning lance **12** can then be inserted through the opening **330** in the same way as shown in FIG. **1(a)** for use in blowing gas into internal space **302** to dislodge particulates therein. Thus, each combination of an opening **330**, cover **332** and pivot pin **334** amounts to a port assembly **340** analogous to a port assembly **10**. Port assemblies **340** are simpler than port assemblies **10** and **200** and are suitable for use where it is intended that the internal space of a cabinet (or other enclosure) being cleaned will be held at a lower pressure than the surroundings of that cabinet enclosure. The low pressure at least limits any escape of particulates from the space **302** through port assemblies **340**. Although not shown, it would be possible to provide a seal (for example an O-ring) surrounding opening **330** in either cover **332** or cover **310** to better seal cover **332** against cover **310** when the pressure is lower in the internal space than outside.

(163) Cover **310** is shown as made from a sheet of transparent or at least translucent material, which is advantageous because a user has better visibility of what is happening inside the enclosure being cleaned. Suitable polycarbonate plastics materials can be used, for example, and may be treated with a scratch-resistant treatment as known in the art. Alternatively (not shown) a window (similar to window **88**) may be provided, with cover **310** being otherwise non-transparent.

(164) Cover **310** is shown with an outlet port **346** similar to outlet port **18** of FIG. **1(a)**, for

connection of a duct (not shown) to be held at low pressure and receive gas and entrained particulates gas from the enclosure being cleaned.

(165) FIG. **24** shows a cover **310a** that is an alternative version of the cover **310** also positioned ready for securing to cabinet **300**. Parts of cover **310a** that are, and that function, the same as corresponding parts of cover **310** are indicated by item numbers including the suffix “a” and are not described again here. Cover **310a** has several differences from cover **310**, as follows. First, cover **310a** comprises a central portion **311** and two side portions **313** and **315**, that are hinged to central portion **311** by “piano”-type hinges **319** and **317** on the outward-facing side of cover **310a**. This enables cover **310a** to be folded, so as to be easier than cover **310** for one person to carry.

(However, it is to be noted that hinges such as **317** and **319** preferably avoided where folding is not necessary as having no hinge is simpler.) Formation **312a** is shorter than formation **312** of cover **310**, extending only along a top edge of portion **311**, to enable folding. Second, cover **310a** has no attached seal corresponding to seal **318** of cover **310**. Instead, a seal **321** is secured to, and extends around, flange **304**. This may be either a pneumatic seal with an inflating connection **323**, as shown, or a non-pneumatic elastomeric seal (not shown). To provide an adequate seal on cover **310a** itself instead of flange **304**, would be problematic due to the feature of folding. The chain-dotted outline **321b** in FIG. **24** does not represent an actual component, but the area on cover **310a** that is contacted by seal **321** when cover **310a** is secured on cabinet **300**. Note: cover **310a** is shown with a different number and arrangement of port assemblies **340a** from cover **310**, but this is simply a matter of choice for any particular application.

(166) While various embodiments of cabinet doors and enclosure covers have been described above, it is to be understood that particular features of any one may where practicable be combined with features of another. For example, LED lighting may be used in any of the designs described above, as may any of the port assemblies **10**, **200** or **340** or the “dished” shape of cover **152**.

Alternative Embodiments and Applications

(167) Instead of a manually-manipulated and operated cleaning lance **12**, some further embodiments provide for mechanical means for moving gas nozzle(s). Examples will now be given.

(168) FIG. **20** shows an enclosure **100** in a view equivalent to FIG. **1(a)**. Nozzles **102** are mounted to, and able to rotate on, manifolds **104** that are in turn secured by brackets **106** to door **108**. Manifolds **104** are supplied with gas from an external source (not shown) via conduits **110** that extend through door **108**. Rotating seals (not shown) enable gas to flow from manifolds **104** into nozzles **102** even as nozzles **102** oscillate about manifolds **104**. Conduits **106** are connected to an external manifold **112** on door **108**. A rotating crank member **114** connects via a link **116** to a link **118** that can oscillate nozzles **102** about manifolds **104** through a range of angles as shown by arrows **120**. Crank member **114** extends sealingly to the exterior of enclosure **100** and is rotated manually or by a motor (not shown). Gas with entrained particulates is drawn from enclosure **100** through a duct **122** equivalent to duct **20** of FIG. **2**. There are several nozzles **102** on each manifold **104**. Alternatively, an “air knife” type nozzle, not shown, elongate along the length of each manifold **104** may be provided instead of nozzles **102**.

(169) In a still further alternative shown in FIG. **21**, a single “air knife” **124**, so-called, that is elongate across the width of an enclosure **126** may be provided and arranged to be fed with gas from an external supply and to produce a flow of the type shown by arrows **128** in FIG. **21**, with the air knife **124** being able to traverse up and down (as shown by arrows **130**) and to oscillate around an axis **132** extending lengthwise of the air knife **124**. A suitable mechanism (not shown) could readily be provided by a person skilled in the art and enable such motions to be provided. Duct **134** extracts gas and entrained particulates from enclosure **126**.

(170) In each of the arrangements shown in FIGS. **20** and **21**, the system external to the enclosures **100** and **126** is in some embodiments the same as system **30** described above except for absence of cleaning lance **12**. In some embodiments, the arrangements shown in FIGS. **20** and **21** are provided

with motorized and automatically controlled positioning of the nozzles (**102** or air knife **124**), such positioning being under the control of microprocessor **200** or a separate microcontroller (not shown). In these embodiments, item **207** in FIG. **3** includes control outputs for any or all of positioning, orienting, movement speed control, and gas flow control for nozzles **102** or air knife **124**.

(171) Positioning and orientation of the nozzles **102** or air knife **124**, the flow rate of gas through them, and traversing speed may all be controlled by processor **200** to execute a pre-defined or programmed cleaning scheme input by a user, with instructions stored in a memory (not shown) accessible and executable by the processor **200**. In some embodiments, the scheme may be executed repeatedly until a preset acceptable level of particulate concentration is achieved at the gas outlet from the enclosure **100** or **126**. In other embodiments, multiple cleaning schemes may be entered with provision for execution of several of them where one only does not lead to acceptable particulate concentration at the outlet.

(172) In some embodiments, a user may enter multiple schemes for different requirements, such as for example a fastest satisfactory clean or a most thorough clean.

(173) Cleaning schemes may include instructions to cause nozzles **102** or air knife **124** to dwell at specific locations and orientations for preset times or until particular outlet particulate levels are achieved. Provision may be made for sudden variations in gas flow through the nozzles **102** or air knife **124**.

(174) In some embodiments, processor **200** is adapted to record and store a manually executed cleaning and thereafter execute that scheme whenever cleaning is subsequently required.

(175) In some embodiments, processor **200** executes a randomly or pseudo-randomly selected series of movements and re-orientations of nozzles **102** or air knife **124** until a satisfactory outlet particulate level is achieved. The scheme thus executed may be recorded for future automatic repetition in future under processor **200** control.

(176) In some embodiments, processor **200** may be programmed to automatically execute a number of random or pseudo-random schemes and select the best according to a specified criterion, such as lowest particulate level achieved, or least time to reach a specified outlet particulate level. It is further possible to provide for machine learning, by providing for replacement in memory of a previously stored cleaning scheme by one recorded (for example when manually executed by a user or in additional random or pseudo-random cleaning schemes) that achieves an improved result.

(177) An embodiment will now be described that provides for cleaning of an open-top rail car (for example of the type used for transport of coal or other minerals) or the like, and that involves essentially the same principle as the embodiments described above. A problem with such rail cars is excessive particulates remaining in the car after emptying, these particulates later being disturbed when the empty car is in motion and so polluting the environment.

(178) FIG. **22** shows a typical open top rail car **400** whose upper part, comprising a load containing space **402**, is shown in longitudinal section. A tubular-section rail **404** extends around the top of the rail car. At a location where the car **400** is to be cleaned, a platform-like cover **410** is provided that when cleaning is to be carried out can be positioned over car **400** and lowered (in the direction of arrows **406**) onto the rail **404** from above, whereby to close space **402**. An elastomeric seal **412** contacts rail **404** after such lowering.

(179) A carriage **412** moves lengthwise of the car **400** on a rail **414** (propelled for example by an air motor (not shown)) and has mounted thereon one or more nozzles **420** for blasting internal surfaces of space **402** with air (or other gas) supplied through a hose **416** and gas inlet **418**.

(180) To remove air (or gas) and entrained particulates from space **402**, one or more ducts **422**, of which four are shown, are provided on the underside of platform **410** and extend downward into space **402**. Ducts **422** communicate with a manifold **424** from which air (or gas) and entrained particulates are drawn at **426** by a vacuum source (not shown). Internal space **402** may be kept during cleaning at a pressure below atmospheric.

(181) When cleaning is complete, cover **410** is lifted upward to clear rail car **400**. The arrangement shown in FIG. **22** may be used in a building (not shown) with ends through which cars **400** (or other vehicles where applicable) are sequentially driven with lifting of platform **410** effected by a fixed lifting equipment in the building. Alternatively, a truck or specialized vehicle (not shown) with a pivoted or articulated arm may be used to manipulate platform **400** and associated equipment as required for cleaning.

(182) Other types of container or enclosure are not open-topped but rather open at an end. As an example, FIGS. **25** and **26** are longitudinal central sections on standard shipping containers. (Some detail of these containers has been omitted, including doors.)

(183) In FIG. **25**, container **600** is closed by a cover **602** that fits into its open end when the outward-opening doors (not shown) are opened. Cover **602** is sealed against gas and particulate movement by a peripheral seal **604** that extends wholly around cover **602** and seals against inner surfaces (floor **606**, walls **608** and ceiling **610**) of the container **600**. Seal **604** may be a pneumatically inflated seal. Sealing is not against end surfaces of container **600** because of the presence thereon of latch fittings (not shown). In container **600** is a support carriage **612** movable under user remote control on wheels **614**, and that has a gas nozzle **616** that can be remotely controlled by a user, outside container **600**, to move in a range of ways, as indicated by arrows **618**. Gas is supplied to nozzle **616** by a conduit **620** (including a hose portion) connected through cover **602** to a gas source (not shown) so that a jet of the gas can be used to dislodge and entrain particulates. Carriage **612** is also fitted with at least one inlet **622** for gas and entrained particulates, that in turn is connected via a flexible outlet duct **624** to a system (not shown) equivalent in function to system **30** of FIG. **2**. A window **623** is provided in cover **602** so that the user (not shown) can see and guide the carriage **612** as required until the monitored concentration of particulates leaving the container **600** is sufficiently low. Suitable lifting and manipulation equipment (not shown) is provided for positioning carriage **612** and then cover **602** for use, and for subsequently removing them from container **600**.

(184) FIG. **26** shows an alternative arrangement in which a cover **626** is fitted into an end of a shipping container **628** in essentially the same way as cover **602** is fitted to container **600**. A pneumatic or other suitable seal **603** equivalent to seal **604** is provided to prevent escape of gas and particulates around the periphery of cover **626**. A nozzle **629** directs a jet of gas to dislodge and entrain particulates in the same way as nozzle **616** and is movable under user remote control in a range of ways as indicated by arrows **630**. A gas supply (not shown) external to cover **626** is provided and supplies nozzle **629** through a hose **631**. Nozzle **629** is supported in this embodiment by a structure **633** secured to cover **626**. This is shown as a multi-section telescopic arm, but other arrangements will readily suggest themselves to persons skilled in the art. Exhaust inlets **632** are provided on a structure **634** that is also secured to cover **626** and that incorporates outlet ducting for gas and entrained particulates. A window **635** is provided in cover **626** for a user outside container **628**. Not shown in FIG. **26** is a system equivalent in function to system **30**. Suitable manipulating equipment (not shown) is provided to enable cover **626** and the components secured to it to be entered longitudinally (i.e. in the direction of arrow **637**) into container **628** and later removed.

(185) Although standard shipping containers have been referred to in relation to FIGS. **25** and **26**, other types of enclosures could be suitable for similar arrangements. For example, some road vehicles (not shown) have enclosures with end doors, and the arrangements shown in FIGS. **25** and **26** could apply to them.

(186) FIG. **27** shows a still further application similar to that described above by reference to FIG. **26**. A container **650** (such as for example a plastics barrel of the type used for solid-phase chemicals) is temporarily closed by a cover **652** that is sealed to the container **650** by a suitable peripheral seal **654** (pneumatic or otherwise). Cover **652** has a gland **656** through which there passes sealingly a gas inlet duct **658** through which an external gas source (not shown) supplies gas to a nozzle **660** within container **650**. Nozzle **660** is able to be moved angularly as shown by arrow

662, and the duct **658** is able to be both traversed up and down (as drawn) and rotated as shown by arrows **664** and **666** respectively. The movements of the nozzle **660** and duct **658** are controlled either by an automatic mechanism (not shown) or manually by a user whereby a jet of gas from nozzle **660** can be directed over the entire internal inner surface **668** of container **650**. Also extending through the cover **652** into container **650** is an outlet duct **670** through which gas and entrained particulates are drawn out. Also provided is a system (not shown) equivalent to system **30**, for providing gas to duct **658** and drawing out, treating and monitoring gas and articulates flowing through duct **670**.

(187) FIG. **23** shows an assembly **500** usable in some embodiments of the system **30** shown in FIG. **2**, specifically comprising elements **40**, **42** and **46**. Assembly **500** comprises a firstly centrifugal fan (blower) **502** corresponding to blower **46** in system **30**. Fan **502** is coupled to and driven by a shaft (not visible) of an electric motor **504**. Gas enters assembly **500** through an inlet port **506** after leaving cyclone separator **38** and so contains less particulates than at outlet **18**. From inlet port **506** the gas enters a plenum chamber **508** and then passes through a filter bag **510** that is supported by a ring **512** at its upper end in a cylindrical casing **514** which is shown partially sectioned. Filter bag **510** corresponds to filter **40** of system **30** and may comprise a woven textile or unwoven material (as known in the filter art) suitable for catching particulates while the gas passes through it and into an outer space **520** of casing **514**. From space **520**, the gas then enters a modular HEPA filter **518** (corresponding to element **42** in FIG. **2**), thereafter passing into fan **502** and out through outlet **536** (corresponding to outlet **53** of system **30**). Casing **514** may advantageously be formed from a transparent plastics material so that any fouling of space **520** by particulates becomes apparent to a user.

(188) Removal of filter bag **510** for emptying or disposal can be effected through a lid **522** at the top (as drawn) of the plenum chamber **508**. Bag **510** is preferably of conical shape and proportioned to at least approximately equalize along its length the flux of gas through its surface.

(189) To hold the parts of assembly **500** together securely and sealingly against gas and particulates leakage and enable easy disassembly when required, casing **514** is fitted with a flanged ring **524** and a base plate or ring **526** is provided at an end of motor **504**. Spaced circumferentially around and extending between and through ring **524** and plate (or ring) **526** are several (for example three) tension members **528** which once placed in tension hold together the fan **502** and motor **504**, HEPA filter **518**, and casing **514**. Members **528** may be for example solid rods threaded at each end for nuts or (as shown) lengths **530** of wire rope with threaded end fittings **532** swaged on at each end and secured by nuts **534**.

(190) Motor **504** has its own integral air pump (not shown) for cooling with inlet **536** and outlet **538** separate from the gas flow circuit of system **30**.

(191) Assembly **500** is convenient for some embodiments and applications, including where components of system **30** are provided in a backpack (not shown).

Further Cover Assembly Embodiments

(192) Yet another cover **310c**, shown in FIG. **29** and similar to cover **310a** (shown in FIG. **24**) will now be described. Cover **310c** has a number of features that differ from features present in cover **310a**. Parts of cover **310c** that are, and that function in essentially the same as corresponding parts of cover **310a** are indicated in FIG. **29** by item numbers that are the same as those corresponding parts with an added suffix “c” so as to not need further explanation. Thus, for example, items **312ac** in FIG. **29** do for cover **310c** what items **312a** do for cover **310a**, namely allow cover **310c** to be hooked over an upper part of a flange of a cabinet (not shown).

(193) Instead of being made in three panels **313**, **315** and **311** connected by two hinges, cover **310c** has two panels **802** and **804** connected by a single hinge **806**. (Of course, hinge **806** may be omitted altogether where foldability is not required.) Panels **802** and **804** are flat and may be of a suitable translucent or transparent sheet plastics material. Port assemblies **340ac** are provided, but in different locations from the port assemblies **340a** of cover **310a** that facilitate folding of the two

panels **802** and **804** flat against each other when cover **310c** is not in use. Not shown, but another possibility, is to provide port assemblies **340ac** in locations tailored to allow best access to items (not shown) in enclosures on which cover **310c** will in use be deployed.

(194) FIG. **30** shows a particular port assembly **808**, comprising a cover portion **810** that threadably engages with a collar **812** secured gas-sealingly to panel **802**. Cover portion **810** can be screwed into or out of collar **812** as required using handle formations **816** and has an opening **814** that allows a lance (such as lance **12**) to be pushed into an enclosure (not shown) on which cover **310c** is secured. The other port assemblies **340ac** have collars (not shown) the same as collars **812** and cover portions **818** the same as cover portion **810** except that no opening corresponding to opening **814** is provided. These cover portions **818** have annular elastomeric seals (not shown) the same as seal **820** of cover portion **810**.

(195) Instead of a single port for extraction of gas (like port **346a** of cover **310a**) cover **310c** has two ports **821** and **822** that are in fluid communication with chambers **823** and **824** on the sides of panels **802** and **804** respectively that in use of cover **310c** lie in the opening of an enclosure (not shown) to be cleaned. Chambers **823** and **824** have internal spaces **825** and **826** respectively. (Chambers **823** and **824** are shown in FIG. **29** as they would be seen through transparent panels **802** and **804**.)

(196) Chamber **823** (the same as chamber **823**) is shown in section in FIG. **31**. Space **825** is defined by walls **827**, **828** and **829**. Wall **828** has elongate slots **829**, so that entry of gas and entrained matter is through multiple slots **829** as shown by arrow **830**. This arrangement provides for better removal of entrained matter than a single position port such as **346a**. Item **831** is a portion of an enclosure to which cover **310c** could be secured for use. Flexible duct **832** (corresponding to duct **20** of FIG. **1**) is shown in FIG. **31** as positionable sealingly by an end fitting **833** enterable into port **821**. Because there are two ports **821** and **822**, two such ducts are required and may be joined into a single flexible duct (not shown) by a suitable fitting. The essential here is that gas and entrained particulate matter can be collected at multiple points with an enclosure being cleaned.

(197) Still further arrangements for effective removal of gas and entrained particulates will readily suggest themselves to persons skilled in the art.

(198) Referring to FIG. **2**, in practical realisations of the invention, many, most or all of the sensors provided may be in an enclosure that is separate from the enclosure being cleaned and connected to the latter by the conduits **34** and **20**. However, the measurement of pressure within the enclosure being cleaned is particularly important and sensing of that pressure may be done at a point within the enclosure being cleaned. As an alternative to a sensor at a station such as station C (FIG. **2**) with an electrical connection for its output to an enclosure containing the other components left of station “XX” in FIG. **2**, it is possible instead to provide an orifice opening into the enclosure being cleaned and in fluid communication through a flexible tube with a sensor (pressure transducer) located in the enclosure containing those other components. FIGS. **32** and **33** show two ways to do this.

(199) FIG. **32** shows an enclosure **900** being cleaned, with a duct **901** (corresponding to duct **20** of FIG. **2**) connecting the interior of enclosure **900** to an enclosure **902** containing the components shown to the left of station “XX” in FIG. **2**. Duct **901** is of the known type having a flexible tube **910** held open by a spiral formation **911** such as a wire.

(200) A small-diameter tube **904** enabling an orifice **905** open to the interior of the enclosure **900** to connect to a sensor **906** in enclosure **902** may conveniently be provided inside the flexible duct **901**, with the tube **904** terminating in the orifice **905** in a fitting **903** by which the duct **901** is secured to the enclosure **900**. At its other end, tube **904** terminates at a fitting **913** with a passage **914** in fluid communication with a pressure transducer **906** in enclosure **902**.

(201) Another possibility is to eliminate tube **904** and provide instead that the duct **901** is again of the type having a flexible tube **910** held open by a spiral formation **911**, but in which that spiral formation is itself hollow along its length, so as to be in effect a small-diameter tube. The orifice

905, in fitting **903**, is in this case in fluid communication with the hollow interior (not shown) of the spiral formation **911**. At the other end of the duct **901**, the spiral formation **911** and its interior (lumen) is in fluid communication via passage **914** in fitting **913** with the pressure sensor **906** in enclosure **902**.

(202) In each of these two arrangements, it is appropriate to provide at the orifice that opens into enclosure **900** a plug or cover, for example of sintered metal, (not shown) adapted to prevent clogging of the orifice, which could adversely affect the pressure measurement.

Further Embodiments—Cover Assemblies

(203) To disclose yet further additional options for covers according to the invention, FIG. **33** shows a cover **310b** that is an alternative to covers **310**, **310a**, and **310c**. Cover **310b** comprises a single transparent plastics panel **1024** shaped and proportioned to fit over an opening into an internal space of an enclosure (not shown). Cover **310b** is provided with multiple ports **1012** of the type shown in FIGS. **18** and **19**, located specifically in positions that provide optimal access for a cleaning lance such as lance **12**. There is also a port **1020** that in use of the cover **310b** receives an end fitting **1026** of an outlet conduit **1002** for gas and entrained particulate matter that corresponds in function to conduit **20** of FIG. **2**.

(204) Banks **1018** of light emitting diodes (LEDs) are provided on the internal-space-facing face of panel **1024** for internal lighting of the internal space. The LEDs are protected by transparent or translucent elongate covers glued or otherwise secured to panel **1024**. Extending around the periphery of panel **1024** is a seal **1016** that in use of cover **310b** lies between panel **1024** and a facing part of the enclosure being cleaned. Seal **1016** may be formed from rubber or a rubber-like material or other material (for example felt) to provide at least some degree of sealing against gas and particulate leakage as cover **310b** is pushed against the enclosure by the difference between atmospheric pressure and the partial vacuum maintained in the enclosure. Perfect sealing is not essential where there is a partial vacuum in the enclosure.

(205) Two additional provisions are made for holding the cover **310b** in place. First, magnets **1014** are secured in recesses in panel **1024** and pull panel **1024** toward the enclosure (if it is ferromagnetic). Second, a formation **1010** is provided whereby the cover **310b** can be hooked onto an upper edge of a flange (not shown) on the enclosure, in the same way as described for covers **310** and **310c**.

(206) Two forms of sensor are provided on cover **310b**. First, a pressure sensor **1022** is provided for sensing pressure inside the enclosure, having a pressure-sensitive diaphragm or surface (as opposed to a small hole leading to such diaphragm or surface) so as to be immune from clogging with particulate matter. Second, at each port **1012** there is provided a sensor (not shown) that indicates whether the port is “open” (i.e. in use to accommodate a cleaning lance such as lance **12**) or closed. The sensor may be of any suitable type for example a microswitch or Hall effect proximity sensor actuated by a movable portion of the port assembly, such as movable covers **332** of port assemblies **340**).

(207) The functionality of instrumentation and control system **199** of FIG. **3** may be expanded to include sensing of the state of ports **1012** during a cleaning session, to provide to supervisors and/or others (including in reports of the cleaning process generated by the system) an indication of how the operation was carried out, for example, whether all of ports **1012** were used at some point, and for how long. Moreover, it is possible to provide through system **199** a defined sequence to be followed in cleaning a particular enclosure and to display prompts to an operative as to that sequence at block **208**.

(208) To direct power to the sensors and LED banks **1018** and to allow transmission of their outputs to other parts of the system a connecting cable **1004** is provided that is secured (at **1006**) by tape, suitable clips or the like to duct **1002**. Necessary electronics, signal conditioning for the sensors and power connections (not shown) are protected in a housing **1008** secured to panel **1024**, at which an end of cable **1004** terminates. Note that with suitable end fittings for outlet conduit

1002, it is possible to run cable **1004** inside conduit **1002**, thus reducing the risk of damage to cable **1004**.

(209) As an alternative to cable **1004**, it is possible to provide for signals from the sensors on cover **310b** to be transmitted to the rest of the system by a short-range wireless connection for example using the “Bluetooth” or “Bluetooth Low Energy” or other suitable protocol. In this case, housing **1008** may contain a battery for supplying power to the sensors as required and to the LED banks **1018**. Note that as a further alternative, the functions of housing **1008**, pressure sensor **1022** may be provided in a housing secured temporarily or even permanently to the enclosure to be cleaned.

(210) Note also that in embodiments where the pressure sensor for internal space pressure is to be located elsewhere in the system and connected to a tapping in a cover such as **310**, **310b** or **310c**, a flexible tube can be provided terminating at a tapping in the cover and secured along duct **1002** as shown in FIG. **33**, although such embodiments are not preferred.

(211) Outlet conduit **1002** (or other outlet conduits described herein) that correspond to outlet conduit **20** of FIG. **2** are preferred to have smooth inner wall surfaces to avoid fouling with particulate material. Thus wire reinforced hose having a non-smooth inner surface is less preferred than hose with a smooth inner wall surface.

Exemplary Embodiment—Backpack

(212) A prototype system **999** according to the invention has been developed and has proved satisfactory for cleaning electrical component cabinets on large surface mining haul trucks. The system uses a conventional reticulated workshop air supply as its gas source (item **32** of FIG. **2**) and the other components to the left of station “XX” in FIG. **2** (excluding selector **50** which was not included) and were able to be accommodated in a suitcase-sized plastics casing **1030** suitable for carrying as a backpack or otherwise reasonably portable. FIG. **34** is an elevation showing how the major components (only) of system **999** were able to be accommodated in the casing **1030**. Casing **1030** is shown without its lid, which is hinged at moulded fittings **1050**. Note that system **999** comprises casing **1030**, the equipment within it as shown in FIG. **34**, a cleaning lance (for example lance **12** or one of the others lances **1160** or **2600** described herein), and all associated ducting.

(213) A cyclone corresponding to cyclone **38** of FIG. **2** is shown at **1036**, with its inlet for gas and particulates drawn from enclosures shown at **1034**. Item **1042** is a container inside which is a receptacle (not shown) for collection of particulates received from the cyclone at **1036**, the receptacle being emptiable when an ultrasonic transducer pair (sender and receiver, not shown) provides a signal indicating it is full.

(214) At **1038** is a duct from the cyclone at **1036** leading to a cylindrical casing **1040** containing firstly a disposable paper bag-type filter (not shown in FIG. **34**) receiving gas and unremoved particulates from the duct at **1038**, and secondly a HEPA filter downstream of the paper-bag-type filter. At **1032** is a screw cap for accessing the interior of casing **1040** for removal and replacement of the paper-bag filter and removal and servicing of the HEPA filter.

(215) The source of vacuum for drawing gas and particulates through the system is shown at **1044** (casing for a centrifugal or blower fan (not visible) and **1048** (motor for the fan). Gas leaves the system via a muffler **1046** via a port (not visible) at the left side of the casing **1030**.

(216) Not shown in FIG. **34** are triboelectric sensors for sensing particulate concentration at locations corresponding to stations F and K of FIG. **2**. Electronics componentry (not shown) is housed in the lid (not shown) of the casing **1030**. Pressure transducers for locations corresponding to stations C, F, G, H and I of FIG. **2** are mounted on a printed circuit board in the lid and connected to those locations by small-bore flexible plastics tubes.

(217) Also housed in the lid is a relay-operated valve corresponding to item **52** of FIG. **2** for controlling gas supply to the lance (not shown), and in particular shutting off that supply if pressure in the enclosure being cleaned rises to become too close to pressure in the surroundings (i.e. if there is a risk of loss of partial vacuum in the enclosure being cleaned).

(218) FIG. 35 shows the casing **1030** in the same elevation as FIG. 34 but now with screw cap **1032** removed and a filter bag holder **1052** removed from casing **1040** as is required for emptying. Bag holder **1052** (shown in FIG. 36) comprises a plastics moulding in which vertical bars **1041** are arranged in a circle supported by circular parts **1057**. No filter bag is shown in FIG. 36, for clarity. As can be seen in the sectional view of FIG. 37, bars **1041** lie adjacent to the wall of casing **1040** when holder **1052** is placed in casing **1040**. Filter bag **1045** is held away from the wall of casing **1040** by bars **1041** when, in use, there is gas under pressure in bag **1045**. This ensures that between each pair of adjacent bars **1041** there is a space **1047** into which and down which gas passing through bag **1045** can pass as shown by arrows **1043**. Holding the bag away from casing **1040** in this way ensures that a large portion of the bag's surface is available for catching particulate material entrained in the gas in the bag **1045**. Item **1059** defines a space above the HEPA filter (not shown) so that its whole cross-sectional area is used.

(219) The filter bag used in holder **1052** in the prototype is a commercially available porous paper filter bag having a circular opening. Gas and particulates enter the bag through a short duct **1051** that is separate from holder **1052** but is received therein as shown. A seal **1049** is provided on duct **1051** that when the bag is placed in holder **1052** seals against the inner wall of casing **1040**.

Additional Embodiments—Lighting

(220) FIG. 38 shows a further cover assembly **310d** that is similar in most respects to cover **310c** and used in the same way. Items with numbers ending with “d” are the same as the corresponding items without the “d” as described above in relation to cover **310b** as shown in FIG. 33 and so need not be described again. (For example, item **1008d** in FIG. 38 corresponds in description and function to item **1008** of FIG. 33.) The difference between cover **310b** and cover **310d** is that lighting is provided in a different way. Associated with each port **1012d** is a light source **1013d** that, instead of providing diffused light as in the case of the LED banks **1018** of cover **310b**, project a thin sheet of light **1054** into an enclosure (not shown) on which cover **310d** is used. (For clarity, such a sheet of light is shown only for one of the light sources **1013d** in FIG. 38.) This is helpful to an operator in that particles in or passing through the light sheet **1054** are illuminated by the “Tyndall” effect and a user cleaning the enclosure has a clear indication of whether and where particles are still present in the enclosure and therefore need further attention.

(221) FIG. 39 shows one way in which such a sheet of light can be produced. A miniature laser **1051** generates a narrow beam of light in the direction of an axis **1060** that passes through a transparent or translucent cylinder **1052** made of for example a suitable plastic material or even glass, the cylinder **1052** having a lengthwise axis **1053** perpendicular to axis **1060**. The effect of the cylinder **1052** is to convert the beam into a fan-shaped flat sheet of light **1054** in a plane perpendicular to the axis **1053**.

(222) FIG. 40 shows this arrangement as realized in cover **310d** for a typical port **1012d**. The panel **1024d** of cover **310d** comprises two layers secured together—one is a sheet **1055d** of a suitably stiff plastics material and the other, on an outer face of panel **1024d**, is a sheet **1056d** of a vacuum-formable transparent plastics material in which holes corresponding to ports **1012d** are provided and in which are formed elongate dimples **1057**, one for each laser **1051**. Cylinder **1052** and laser **1051** are positioned within dimple **1057** between sheet **1056d** and sheet **1055d** in the desired orientation. In some embodiments, sheet **1055d** is recessed as shown at **1061**. Electrical connections supplying power for the laser **1051** (not shown in FIG. 38 or 40) may be run between sheets **1055d** and sheet **1056d** to a suitable termination (not shown) and may be flat copper strips, for example. The orientation of axis **1053** is vertical when the cover assembly **310d** is oriented as shown in FIG. 38, so that a horizontal sheet of light **1054** is provided, as shown in FIGS. 38 and 40, although other orientations may be chosen. It will be recognized that other, different ways may be chosen to realize the described arrangement of laser **1051** and cylinder **1052**. (For example, not shown, panel **1024d** may comprise only a single sheet such as sheet **1055d**, with laser **1051** and cylinder **1052** being accommodated in a short length of tube secured by gluing or otherwise, to

panel **1024d** at one end and closed at the other end.) Also, instead of a cylinder **1052**, a suitably shaped lens (not shown) may be used.

(223) An embodiment with a further, optional enhancement is now described. FIG. **40** also shows a light emitting diode (LED) **1058** optionally accommodated in dimple **1057** and oriented facing away from the sheet of light **1054** so as to be visible to a user. LED **1058** is arranged to be lit with power provided by the system in a colour that is modulated (by the processor shown in FIG. **3** at **200**) according to the measured concentration of particulates at the enclosure outlet **102d** when its associated port **1012d** was last detected (by the means described earlier above) as being in use—for example green in the event of a negligible concentration and red in the case of a heavy concentration. A user seeing that the LED **1058** for a particular port **1012d** is showing red knows to take cleaning action at that port until the LED **1058** turns green, due to the particulate concentration at outlet **1020d** falling. When the LEDs for every port **1012d** are green and the measured concentration of particulates at outlet **1020d** is adequately low, and the light from each light sheet **1054** does not show particles, the user has some assurance that cleaning is complete. As for lasers **1051**, conductors (not shown) providing power for the optional LEDs can be run between sheets **1055d** and **1056d** to suitable terminations for onward connection to the system. In some embodiments power for the LEDs is provided by the same power supply that supplies power to the instrumentation and control system shown in FIG. **3**.

(224) Although cover **310d** is shown to have one light source **1013d** associated with each port **1012d**, it is possible to provide them in other, or additional, positions.

(225) In some embodiments, it is possible to make cylinder **1052** rotatable by a user so that the sheet of light **1054** can have any of a range of orientations. This can be achieved for example by securing a ferromagnetic element (not shown, for example a small disc) to cylinder **1052** and providing a magnet outside dimple **1057** to act on the ferromagnetic element to rotate the cylinder **1052**.

(226) In other embodiments, the colour of the light from the laser is made adjustable by the user to enable a most suitable colour to be chosen.

(227) Note that cover assemblies as described herein may comprise lighting as described herein, even where a cleaning lance such as lance **1160** with its own lighting is to be used.

Additional Embodiments—Workspace Environment Instrumentation

(228) FIG. **41** shows an extended version **1075** of the instrumentation and data processing arrangement shown in FIG. **3** and is representative of the instrumentation system of system **999**. Items having the suffix “b” in FIG. **41** directly correspond to items with the same item number but no “b” suffix and so need not be described again, except to the extent that the extended arrangement of FIG. **41** alters them. Thus, for example display **208b** essentially is as described above for display **208**.

(229) Instrumentation and data processing system **1075** has provision for two groups of sensors, the first being equipment sensors **202b** that sense operating parameters as described above.

(230) The second set of sensors **1070** comprises one or more sensors (not individually shown) for sensing parameters that relate to the condition of the workspace in which a user of the system shown in FIG. **2** works and/or to the condition of the user him- or herself. For example, workspace-related sensors include in some embodiments an air quality sensor, such as a particulate level sensor or a temperature sensor. User-related sensors may include for example a temperature sensor that directly senses temperature inside an item of protective clothing.

(231) The significance of workplace- and user-related sensors is that it is important in industry today to ensure that working conditions are reasonable and can be proven to be so, particularly where substances that are inherently toxic or harmful in certain concentrations or particle sizes are being dealt with. A further issue may be pollution by harmful substances. Therefore, system **1075** in some embodiments provides for sensing, recording (at item **211b**) and transmission (at **213b**) of data on workplace- and user-related parameters alongside equipment-related parameters. Further,

system **1075** provides for the alarm, control and display functions **210b**, **207b** and **208b** to reflect the importance of workspace and user-related parameters.

(232) In some embodiments, item **1070** includes a particulate sensor (not shown) located in a workspace of a user but away from Station K, the blower **46** outlet (FIG. 2).

(233) This particulate sensor senses particulate levels independently of the system shown in FIG. 2. As an example, a suitable sensor for some applications could be an HPM-Series laser particulate sensor available from Honeywell, Inc. This has its own fan for continuous sampling of air and sensing of particulate levels using a laser light scattering method to detect and count particles in the sampled air flow. In some embodiments, the sensor is powered from the same power supply as that used by the other items in system **1075** (at block **1072**). The sensor may be connected to data processing unit **200b** (at block **204b**) either by cable or wirelessly using any suitable protocol.

(234) The sensed particulate levels in some embodiments are recorded alongside equipment-related quantities such as particulate concentration at Station F (FIG. 2), so that a record is obtained of the particulate levels experienced by the user during a cleaning operation.

(235) Further, data processing unit **200b** may provide for alarms to be made drawing the user's attention to particulate levels in his or her workspace that are becoming excessive, display of the workspace particulate level, and, if particulate levels rise to a predetermined unsafe level actual shutdown of the equipment via control outputs (block **207b**).

(236) As described herein the system shown in FIG. 2 may be operated to achieve cleaning of an enclosed space by either blowing gas into, and sucking it out of, the enclosed space or simply extraction by suction alone. In either case sensing of workspace- and user-related quantities may be used.

Additional Embodiments—Flexible Cover Assemblies

(237) The cover assemblies **310**, **310a**, **310b**, **310c**, **310d** described above are rigid or substantially rigid. However, it is possible to provide cover assemblies that are formed using flexible materials. Such cover assemblies can offer the advantage of being easier to store, when not in use, and easier to transport to and from a worksite. Further, an advantage may be avoidance of danger from breakage. Acrylic sheet such as that sold under such trade names as “Plexiglass” or “Perspex” may break under stress, with broken pieces potentially causing injury.

(238) As an example of a suitable material for cover assemblies that are flexible, PVC material is available in the form of sheets that are transparent and flexible, being supplied in rolls. Note that the word “transparent” is here not intended to necessarily imply the degree of transparency of a pane of glass, but rather to imply sufficient transparency that a user of the invention can see inside an enclosure being cleaned sufficiently well to be able to assess the progress of cleaning and manipulate a cleaning lance (such as lance **12**) adequately.

(239) FIG. 42 shows a cover assembly **1100** formed in part from a sheet **1102** of flexible transparent plastics sheet material such as a suitable PVC material, positioned for fitment against an opening **1104** of an enclosure **1106** of ferromagnetic material whose interior is to be cleaned according to the invention. Cover assembly **1100** is shaped and sized to be able to abut a peripheral flange **1108** of enclosure **1106** and to span and close off the opening **1104** defined by flange **1108**. This is indicated in FIG. 42 by the chain-dotted lines **1110**. Cover assembly **1100** has covers **1112** (described below) for ports **1114** allowing insertion of a cleaning lance (such as lance **12** or the lance **1160** described below) and an outlet port assembly **1116** for connection of an outlet duct (not shown) for removal of the cleaning gas and entrained particulate matter.

(240) FIG. 43 is a cross-sectional view of a portion of cover assembly **1100** taken at station “AX-AX” showing two only of the ports **1114**, with one of them **1114a** shown in use for insertion of a cleaning lance such as lance **12**. To secure cover assembly **1100** against gas leakage around its edge, cover assembly **1100** is provided with a flexible magnetic strip **1118** around its periphery that holds cover assembly **1100** against flange **1108** of the enclosure **1106**. Magnetic strip **1118** and the sheet **1102** are held together by a double-sided adhesive tape **1120** having a plastics foam between

its two faces (as known in the adhesive tape art), also extending peripherally around the sheet **1102**. Tape **1118** and magnetic strip **1120** are shown in FIG. **42** by dotted lines **1122**. Note that if required, cover assembly **1100** can be secured in place more reliably by the use of suitable adhesive tape (for example so-called duct tape) if required.

(241) With a suitable choice of magnetic strip **1118**, cover assembly **1100** has been found practicable in many applications because the necessary difference between pressures inside and outside the enclosure **1106** can be not large enough for cover assembly to be sucked off flange **1108** and into enclosure **1106**.

(242) The outlet port assembly **1116** is secured gas-sealingly to sheet **1102** by a suitable adhesive or by heat or solvent welding and/or by stapling or stitching.

(243) FIG. **44** shows two only of the ports **1114**, **1144a** and associated port covers **1112**, **1112a** of two different types. Ports **1114**, **1114a** comprise slits formed in the sheet **1102** and preferably provided with holes **1124** at each end to prevent tearing of sheet **1102**. To limit flow of cleaning gas through ports **1114** when they are not in use, flexible port covers **1112** are provided that when their associated ports **1114** are not in use abut sheet **1102**. Chain dotted lines in FIG. **44** show the positions of covers **1112**, **1112a** when they abut sheet **1102**. Covers **1112** and **1112a** can be swung aside as shown for insertion of a cleaning lance such as **12** or **1160**. This can be done in two ways. Cover **1112** is secured to sheet **1102** along a vertical edge **1126** and cover **1112a** is secured to sheet **1102** along a horizontal (as drawn) edge **1126a**. The covers **1112**, **1112a** may optionally be of the same type of material as the sheet **1102** and secured thereto by adhesive, solvent welding stitching or any other suitable method. As desired, the covers **1112** of cover assembly **1100** may be all of the type shown as **1112**, all of the type shown as **1112a**, or a mixture of both.

(244) However, it has been found that in many applications pressure differences between an internal space being cleaned and the workspace outside are and can be maintained small enough that there is no significant leakage of particulate material through ports such as **1114** and **1114a** even if the flaps **1112** and **1112a** are omitted altogether. Accordingly, any of the flexible covers described in this specification may for suitable applications be provided with ports for cleaning lance insertion that comprise simply a slit (such as **1114** or **1114a**) with anti-tearing holes at each end (such as the holes **1124**). It is preferred that where such ports are provided, the slit extends in at least approximately an upright direction in covers intended to be used on vertical openings. Such ports are particularly convenient where they can be used, as they do not hamper folding or rolling up of flexible cover assemblies when not in use.

(245) FIG. **45** shows a further flexible enclosure cover assembly **1130** positioned (as indicated by chain-dotted lines **1136**) ready to be secured over an opening **1132** of an enclosure **1134**. Cover assembly **1130** is the same as cover assembly **1100** as described above save for two modifications. Elements of cover assembly **1130** that are the same as corresponding ones of cover assembly **1100** are numbered the same as in FIG. **42**, save for a suffix “a”. The first modification is that an elongate stiffener **1138** is secured to and extends across the outer side of the cover assembly **1130**, for example by adhesive or heat- or solvent-welding or retention in a pocket. The purpose of stiffener **1138** is to prevent that part of cover assembly **1130** that extends over the opening **1132** from deflecting excessively into enclosure **1134** due to the pressure difference maintained across the cover assembly **1130** in use. Only one stiffener **1138** is shown, but in other embodiments several are provided where required.

(246) The second difference between cover assembly **1130** and cover assembly **1100** is that cover assembly **1130** has peripheral flaps **1140** that in use are wrapped around corner edges **1142** of a peripheral flange **1144** around opening **1132**. Gaps **1146** are left between flaps **1140** where necessary to clear obstacles such as hinges **1148**. Flaps **1140** may be of a different material from plastics sheet **1102a**, for example of a suitable textile material with or without a plastics or rubberlike coating, for ease of bending around corners **1142**, and need not be transparent.

(247) The portion **1149** of cover **1130** that abuts flange **1144** may be provided with double-sided

tape and magnetic strip as shown in FIG. 43 for cover **1100** or with a suitable sealing material only. Magnetic strip or individual magnets are provided at **1150** on flaps **1140**. Cover **1130** can provide a more secure connection to an enclosure (such as **1106** or **1134**) than cover **1100**.

(248) Both covers **1100** and **1130** can be rolled up for convenient storage and transport, due to the use of flexible material in their construction.

(249) In other embodiments, flexible cover assemblies (not shown) can be provided with both stiffener(s) such as **1138** and flaps such as **1140** or only one of those features, as required.

(250) A possible difficulty associated with flexible cover assemblies **1100** and **1130** is illustrated by the presence of outlet port assemblies **1116** (in cover assembly **1100**) and **1116a** (in cover assembly **1130**). When ducts are connected to components, **1116** and **1116a**, they place stress on them which may significantly deflect the surrounding flexible material (**1102** or **1102a** respectively). This can risk separation of the cover assembly from the structure whose internal space is to be cleaned of particulates, and associated leakage of particulate material.

(251) One solution is shown in FIG. 62. A plate **2700** of steel having a duct connection **2702** is secured to a structure **2704** whose interior is to be cleaned of particulates in a suitable position for connection of the duct (not shown) to connection **2704**. This may be done using any suitable form of fasteners, such as spring pins **2706** or screws (not shown) in holes provided in structure **2704** for the purpose or even by strong magnets. The flexible cover assembly (not shown) is then secured to plate **2700** by its magnetic tape as previously described. Thus, stress on the flexible cover assembly due to the duct connection is avoided.

(252) Chain dotted outline **2708** shows one possible location for the magnetic tape to contact plate **2700**. However, the flexible cover assembly could extend to outer edges **2710** and **2712** of plate **2700** and be provided with cutouts to clear connection **2702** and fasteners **2706**, which would provide even more security against separation of the flexible cover from structure **2704**.

(253) FIGS. 65 and 66 show yet another cover assembly **3000** for closing an opening in a container and for use in practice of the invention. Cover assembly **3000** is adapted to be placed against a surface surrounding an opening in a container to be cleaned, such as for example the cabinet **300** shown in FIG. 16, which has an opening **306** into an internal space **302**, the opening surrounded by a flange **304**. Such a container will be used here as one example for purposes of explaining cover assembly **3000**.

(254) Cover assembly comprises a sheet **3002** of a flexible material that is translucent or (preferably) transparent and flexible, such as certain types of PVC. Secured to the edges of sheet **3002** around its periphery (and facing the inner side of cover **3000**) are flexible magnetic strips **3004**, which in use of cover assembly **3000** hold sheet **3002** against flange **304**. An elongate element **3005** is secured along a top edge of sheet **3002** and is adapted to hook over an upper portion of flange **304**, for additional support of the weight of cover assembly **3000**, both in use and when it is being positioned on flange **304** for use.

(255) FIG. 67 is a partial cross-sectional view on a plane normal to sheet **3002** at location “Z” on cover assembly **3000**, shown in position on flange **304**, and shows that the magnetic strip is secured to sheet **3002** by double sided adhesive tape **3006**. Suitable tapes for use with flexible transparent PVC sheet can be selected from among a range of tapes available from the Industrial Adhesives and Tapes Division of 3M (3M Center, St Paul, MN 55144-1000, USA), and are characterized in that they resist migration of plasticizer from the PVC into the adhesive, leading to weakening of bond strength. Transfer Tape 3M transfer tape F9465PC is one example of this class of tape. The same arrangement as in FIG. 67 is used at each end of each of battens **3008**.

(256) To limit bulging of sheet **3002** into opening **306** in use, cover assembly **3000** is stiffened by battens **3008** extending parallel to each other and to element **3005**. Battens **3008** are preferably made of a plastics material of suitably less flexibility than sheet **3002**. For example, in many industrial applications, battens **3008** may be made of the plastic or glass-reinforced plastic used in battens for stiffening sails of small sailboats. Battens **3008** can also be secured to sheet **3002** using

double sided tape **3007** of suitable type, from the class mentioned above, although other suitable methods of securing may be used if required.

(257) FIG. **66** is a horizontal cross-sectional view of the cover assembly **3000** in position ready to be moved in the direction of arrow “Q” to close opening **306** of cabinet **300**.

(258) A modified cover assembly **3000a** can provide extra security of positioning and retention on flange **304**. Cover assembly **3000a** is identical to cover assembly **3000** except that battens **3008** are replaced by battens **3008a** the same as battens **3008** but with ends adapted to hook onto flange **304**. FIG. **68** shows one end of a batten **3008a** of which each end has a hook **3010**. If, at each end of batten **3008a**, the dimension marked “FH” in FIG. **68**) of each hook **3010** is not more than about half of the flange **304** dimension marked “FF”, it is found that with some sideways movements and/or a little bending of battens **3008a** both hooks **3010** can be made to hook over the flange **304** on opposite sides of opening **306**.

(259) As an alternative to the arrangement shown in FIG. **68**, one or both hooks **3010** of batten **3008a** can be replaced by a slidably movable hook **3012** as shown in FIG. **69**. A spring **3014** is attached at one end to an anchor **3016** on a batten **3008b**, otherwise similar to battens **3008** or **3008a**, and at its other end to hook **3012**. Spring **3014** holds hook **3012** in position on flange **304** as shown in FIG. **69** but allows hook **3012** to be moved sideways in the direction shown by arrow **3015**, for convenience during installation on the cabinet **300**.

(260) Cover assembly **3000** (or versions with the any of the hooking arrangements mentioned above) is provided with a hole **3018** to which can be secured a rigid ferromagnetic plate **3020** having an exhaust duct **3022** thereon. Plate **3020** is formed on one edge **3024** to be able to hook over one of the battens **3008** (or **3008a** or **3008b** as applicable) which is taped to sheet **3002** only over part of the batten's width along a portion **3026** of its length. Magnetic strips **3028** are secured by double sided adhesive tape along sides of hole **3018** to hold plate **3020** onto sheet **3002** in use.

(261) Ports **3028** for cleaning lance insertion are provided on cover assembly. These are shown as being of the type described elsewhere herein as having an elongate slit with anti-tearing holes at each end. However, it is to be understood that other suitable ones of the various port arrangements for flexible cover assemblies described herein may also be used instead if desired.

(262) Cover assembly **3000** and its described variants are convenient to use and to store, as they can be folded or even rolled up, for easy carrying and storage after use.

(263) A further feature of cover assembly **3000** and its described variants is that lighting of the space being covered can be provided by installing one or more LEDs or other lighting devices in the battens **3008**, or **3008a** or **3008b**. FIG. **70** shows a cross-section of a portion of cover **3000** at a batten **3008** provided with a recess **3009** in the batten **3008** for an LED **3032**. Double sided tape **3034** has a hole **3011** near the recess **3030** to allow light from LED **3032** to pass through sheet **3002**. The forms and refinements of lighting referred to in this specification by reference to FIGS. **38-40** may optionally be applied to lighting provided in this manner if required, the battens such as **3008**, **3008a**, **3008b** in effect providing support for their elements in the same way that non-flexible cover assemblies of FIGS. **38-40** do.

(264) Further flexible cover assemblies are described below by reference to FIGS. **49** to **55**.
Additional Embodiments—Cleaning Lances

(265) There will now be described further embodiments of cleaning lances that are alternatives to cleaning lance **12**.

(266) In some embodiments, a cleaning lance with more functionality than cleaning lance **12** may be provided. FIG. **46** shows a cleaning lance **1160** with additional functionality and features. In addition to providing an outlet for a jet of cleaning gas (for example air) cleaning lance **1160** has the following additional functions: 1. Provision of lighting inside an enclosure being cleaned using lance **1160** rather than or additional to lighting comprised in a cover assembly; 2. Provision of an inlet port for air to be sampled for the presence of particulate matter in the workspace where the lance **1160** is in use, but outside the enclosure being cleaned; 3. Provision of sensor(s) for

continuous determination of a difference in pressure between the work area outside, and the interior of, the enclosure being cleaned using lance **1160**; 4. Provision for sensing which of the available port assemblies is in use at a given time (i.e. which port assembly has cleaning lance **1160** inserted into it); and 5. Provision of alarms well-located to warn a user of a system condition or malfunction.

(267) While items 1 and 3 may be provided in the enclosure cover being used (as described above in relation to covers **310**, **310a**, **310b**, **310c** for example) their incorporation in lance **1160** instead can simplify the design of enclosure covers with which it is used. This is particularly advantageous in the case of the flexible enclosure covers (including **1100** and **1130**) as described above.

(268) While lance **1160** as described below incorporates all of the items 1 to 5, it is possible and within the scope of the invention to provide embodiments that are lances (not shown) comprising or adapted to provide only one or more of them.

(269) Lance **1160** comprises a duct **1162** for direction of cleaning gas (eg air) from an inlet hose **1164** to an outlet **1166** that in use of lance **1160** is positioned within an enclosure being cleaned in the same way as described above in relation to lance **12**. A valve (not shown) controlled by a movable element on a handle assembly **1168** such as a trigger **1170** is provided to enable control of gas supply.

(270) A rounded formation **1172** is secured on duct **1162** adjacent to outlet **1166** and is sufficiently soft and resilient to reduce any tendency of the outlet end of lance **1160** to damage componentry in an enclosure being cleaned. (This feature could optionally also be incorporated in lance **12**.) Formation **1172** may be formed from a suitable resilient plastic or rubber or rubberlike material, for example.

(271) Also secured on duct **1162** is a rounded formation (called herein an “olive”) **1174** that contains, in a portion having a clear plastics cover **1176**, lighting elements **1178** positioned to provide light close to the area in which the outlet **1166** is positioned. Olive **1174** is so positioned along duct **1162** as to be, in use, within the enclosure being cleaned. Lighting elements **1178** in some embodiments are light emitting diodes (LEDs). Optionally, as best seen in FIG. 47, additional lighting elements **1180** comprise lenses that in the same way as discussed by reference to FIG. 39 provide lighting only in flat “sheets”, to help a user assess visually the quantity of particulates present near outlet **1166** using the Tyndall effect. Switches **1182** (or a multi-position switch, not shown) on handle assembly **1168** can enable a user to switch between lighting elements **1180** and lighting elements **1178** as required.

(272) Cleaning lance **1160** further comprises sensor(s) (not shown) for sensing the pressure difference between the interior of the enclosure being cleaned and its exterior, i.e the workspace. This quantity is important because if the interior is not held at a pressure sufficiently lower than the exterior uncontrolled leakage of particulates may result. In one embodiment ports **1190** and **1192**, respectively at the handle assembly **1168** and olive **1174**, are provided and in fluid communication with a differential pressure sensor (not shown) within handle assembly **1168** or olive **1174** for sensing the pressure difference. In another embodiment, separate absolute pressure sensors are provided, one connected to port **1190** and the other connected to port **1192**.

(273) For sensing of particulate concentration where a user is working, the lance **1160** is provided with a port **1184** for sampling the atmosphere at the end of lance **1160** opposite outlet **1166**, i.e. outside the enclosure being cleaned. A duct **1188** is provided from port **1184** through which air is drawn from the workspace through a particulate concentration sensor (not shown). FIG. 48 shows schematically a system **30a** that is a modified version of the system **30** (FIG. 2), the modification being inclusion of duct **1188** connecting port **1184** to the inlet of cyclone **38a** so that workspace air is sucked through port **1184** and that air's particulate concentration sensed by a suitable sensor (not shown) at a station “N”. Duct **1188** is shown in FIG. 48 as joining the stream of cleaning gas and entrained particulates from duct **20a** or duct **48a** upstream of station “F” but may instead be downstream of station “F”. Station “N” and the workspace particulate concentration sensor may be

within an enclosure containing some or all of the components shown to the left of the chain-dotted line in FIG. 48.

(274) The particulate concentration at the lance **1160** is thus sensed along with the other sensed quantities mentioned above, and may be logged along with those quantities. (In FIG. 48, to avoid repetition of the description of system **30**, components having corresponding functions to components of system **30** are for simplicity numbered the same as those components of system **30**.) Station “T” in FIG. 48 is where the pressure difference between the interior of the enclosure being cleaned and the surrounding workspace is sensed. (In embodiments where the function of measuring pressure difference is not included in lance **1160**, it can be sensed by a differential pressure sensor having ports inside and outside the enclosure being cleaned, for example at a location such as station “C” in FIG. 2.)

(275) In an alternative cleaning lance embodiment (not shown), a particulate concentration sensor (not shown) may instead be provided directly on lance **1160**, for example in handle assembly **1168**. Duct **1188** is then not required.

(276) In other alternative embodiments (not shown), particulate concentration sensing in the user workspace is not incorporated in the cleaning lance but provided by a sensor (not shown) simply placed at a suitable location in the workspace. Where an enclosure is provided (for example a backpack) for major components such as blower **46** or **46a**, cyclone **38** or **38a** for example, the workspace particulate concentration sensor may be located in that enclosure with an inlet port on the exterior of the enclosure. Duct **1188** is then not required.

(277) Warning lights **1194**, **1196** are provided on handle assembly **1168** (i.e. at positions outside the enclosure being cleaned) where they are difficult not to notice. These can warn of malfunctions or indicate the status of other quantities. In one embodiment, lights **1194** and **1196** warn respectively of (a) an inadequate pressure differential between the interior of the enclosure being cleaned and the atmosphere in the workspace and (b) any one of the other sensed quantities being outside specified limits—for example, a full load of collected particulate matter (for example in container **1042**) sensed at Station “L” in system **30a**, or excessive particulate concentration in the workspace (as sensed at Station “N”). Lights **1194**, **1196** are shown on one side of handle assembly **1168** but may be provided on both sides thereof for convenience of users who may be either left- or right-handed. The warning lights **1194**, **1196** are driven by the data processor (See block **200b**, FIG. 41) via the “alarm” outputs (block **210b**).

(278) Cleaning lance **1160** may be used with enclosure covers that do not have the feature, mentioned above, of sensors that identify which port assembly is in use. Cleaning lance **1160** may optionally include means for doing this. This can be explained using cover assembly **1100** as an example. It is possible to provide, adjacent to each cover port or port assembly, a passive RFID (Radio Frequency Identification) or passive NFC (Near Field Communication) tag identifying the particular port or port assembly, and to provide in olive **1174** or handle assembly **1168** a reader (not shown) for the tags. Thus, passive NFC tags **1200** are shown near port covers **1112** on cover assembly **1100**. NFC-type technology is the preferred form of RFID because of its short range. As the lance **1160** is inserted into a port **1114**, or as it is withdrawn, the reader can sense (read) the particular tag associated with that port and identify it to the data processor **200b**. This may be logged along with the various sensed quantities, so that when a record of a period of cleaning is examined, it can be verified, for example, that every port was used. In other embodiments a tag may be provided adjacent each port or port assembly that bears a visual symbol such as a linear-type or circular barcode or QR code, and a suitable reader may be provided in olive **1174** or handle assembly **1168**, again to identify the port in use. A circular barcode may be used. Being able to avoid provision on an enclosure cover of port-identifying sensors is convenient in the case of flexible enclosure covers such as **1100**, **1130**.

(279) To enhance the reliability of port identification, lance **1160** may be provided with multiple NFC tag readers spaced along its length. For example, in addition to a reader in olive **1174**, there

may be another reader in the formation **1172**. As lance **1160** is entered into a port with an associated passive NFC tag, the reader in formation **1172** first detects the tag, and as olive **1174** passes inwardly through the port, its reader detects the tag. The reverse occurs as lance **1160** is withdrawn from the port. Thus, two readers detect the tag, and the order in which they are detected allows both insertion and withdrawal to be distinguished.

(280) In some embodiments, the gas supply valve (for example valve **32a** of system **30a**) is prevented by the data processor **200b** from allowing cleaning gas to flow to the lance **1160** if sensors or readers comprised in the enclosure cover (as previously described) or comprised in lance **1160** do not indicate that a port has been opened (and, if the refinement of the previous paragraph is included, that lance **1160** has been inserted). This avoids the potential safety hazard of escape of cleaning gas outside the enclosure being cleaned.

(281) Wiring (not shown) for lighting elements **1178** and **1180**, and in applicable embodiments for any pressure sensor or tag reader comprised in olive **1174**, and a small-bore tube in embodiments where port **1192** in olive **1174** is connected to a pressure sensor in handle assembly **1168**, extends in a conduit **1202** from olive **1174** to handle **1168**.

(282) Between lance **1160** and the remainder of the system **30a**, there extends the hose **1164** for cleaning gas, wiring for lighting elements **1178**, **1180** and sensors or readers (not shown) in cleaning lance **1160**, and in applicable embodiments duct **1188**. These may be held together for at least part of their length or contained in a single flexible conduit, for safety and convenience of use.

(283) Still other possible features may be provided a cleaning lance. Thus, FIG. **61** shows another cleaning lance **2600** that is an alternative to lances **12** and **1160**. Lance **2600** has a duct **2602** for directing gas into an enclosed space to be cleaned and a handle assembly **2604** for manipulation of lance **2600** by a user. Lance **2600** has an “olive” **2612** essentially the same as olive **1174** of lance **1160**, except as described below. (Lance **2600** does not have a formation corresponding to formation **1172** of lance **1160**, but may be provided with one if required.)

(284) Lance **2600** has the same sensing capabilities as described above for lance **1160**, namely sensing: pressure difference between the portion (eg olive **2612**) inside the space being cleaned; particulate concentration in the workspace (more particularly at the lance **2600** itself); whether a port assembly is in use and if so, which one, using for example an on-lance barcode or other optical reader or an NFC or other reader.

(285) There may also be provided a GPS capability on the lance **2600**. Location of the lance is a useful quantity to record as a part of the process of independently verifying cleaning work, but also for other purposes as set out below.

(286) Lance **2600**, instead of a wired connection to other parts of the system in which it is comprised (as in lance **1160**) communicates through a wireless link using a suitable digital protocol such as Bluetooth, Bluetooth Low Energy or even (where longer range is required) the LORA protocol. Power is provided by a rechargeable battery **2626**, for example a Lithium-Ion type. By this means sensor data from lance **2600** is sent to the data processing system (eg system **1075** of FIG. **41**) and alarms, warnings and desired computed sensor outputs are sent back to the lance **2600**.

(287) A digital alphanumeric screen **2614** is provided on lance **2600** for display of warning and alarm information and of sensor outputs. This includes in particular at least the key quantities required by a user during the cleaning operation. In particular, screen **2614** may display particulate concentration from the workspace particulate concentration sensor so that the user can monitor it for his or her own safety, and the concentration of particulate matter in air leaving the space being cleaned, a key parameter in establishing successful completion of cleaning. The electronics associated with receiving data for display and driving the screen are also energized by the battery.

(288) Screen **2614** may be for example of LED, OLED, LCD or so called “e-ink” type, the latter providing good visibility in high ambient light conditions.

(289) Screen **2614** may be touch sensitive so that selection of options (see discussion of options

below) can be by touching the screen **2614**. Alternatively, a separate control **2616** may be provided. (290) The following are additional features that make lance **2600** differ from lances **12** and **1160**, and the reasons for them.

(291) Pulsating Flow Capability

(292) Control of gas flow through (and from) the cleaning lance (eg **12** or **1160**) by means of a user-operable valve on the lance itself (for example item **16** on lance **12** or **1170** on lance **1160**) and a gas supply control valve (eg **52**, **52a**) provides “on/off” control and steady or slowly variable flow when gas is flowing. However, lance **2600** is adapted to make gas stream **2606** pulsating, either at all times when that gas stream is turned “on” (by trigger **2608**) or when the user makes a deliberate selection of pulsating flow instead of steady flow. Gas is supplied to lance **2600** through flexible hose **2610**.) Pulsating flow in duct **2602** can be provided by a solenoid-operated valve member (not shown) within the lance **2600** with time-varying current being supplied to the solenoid. When non-pulsating flow is required, the solenoid is caused to move the valve member to a position in which gas flows directly and without interruption from hose **2610** to duct **2602**. In an alternative way of providing pulsating flow, energy in the gas supply itself can be used to move a valve member (not shown) cyclically, by use of the principle of a pneumatic hammer or riveter, as known in the art. Providing pulsating flow either at all times or when selected has several advantages. One is the potential for more effective cleaning in at least some circumstances, and the other is the potential for reduced cleaning gas flow. In some embodiments and applications, the latter advantage means that an adequate cleaning gas supply for some tasks may practicably be provided by a simple pressure vessel (eg a lightweight carbon-fibre reinforced plastics pressure vessel. Where a solenoid-operated valve is used to provide pulsating flow, the solenoid can be operated from the battery located at **2626**.

(293) “Before and After” Image Capturing Capability

(294) The availability of very small video cameras based on charge-coupled devices (CCDs), as known for example in the mobile telephone art, enables a further enhancement of the cleaning lance. Lance **2600** is provided not only with lighting that is close to the point where cleaning is actually taking place, as described above in relation to olive **1174** of lance **1160**, but with a video camera (not shown) located for example within the olive **2612**. Such a camera can be controlled by the system **1075** to take “before and after” images of an area being cleaned when there is detection (by the NFC method or barcode reading as described above) of lance **1160** being entered into a new port assembly and being withdrawn, the images being stored along with sensor data to further enhance verification that cleaning has been adequate.

(295) Lighting

(296) Where lance **1160** provides for two types of lighting within olive **1174**, lance **2600** further enables adjustment by a user of the intensity and/or the colour of the lighting provided. It is found that visibility in a dusty environment can sometimes be enhanced by varying these quantities.

(297) Multiple Alarm/Warning Methods

(298) Instead of or in addition to the warning lights **1194**, **1196** of lance **1160**, cleaning lance **1160** may be enabled to provide warning or alarm signals to a user by provision of onboard sound transducer(s) (not shown) for example of piezoelectric type, and/or handle vibration transducer(s) **2614** so that a user is unlikely to fail to notice such conditions. Further, an LED, OLED or LCD (or other digitally operated) screen may be provided on the lance itself to display nominated sensed values, for example particle concentration outside the space being cleaned and at the lance.

(299) Particulate Sampling at the Lance

(300) Lance **2600** may be provided with a particulate sampling capability in the same way as described above in relation to lance **1160** (using a sensor remote from lance **1160** and a sampling tube **1188**) or alternatively, a particulate concentration sensor may be provided on lance **2600** itself, also operated from the battery **2626**. It is not necessary that the on-lance particulate sensor be of the same type as the particulate concentration detectors. In fact, having readings from different types of

sensors can be useful as they may be affected differently by particular environmental conditions, particulate size distributions and the like and any significant difference in readings can be a useful indicator of a need for investigation and or action. System **1075** can be adapted to flag such a situation with a warning or alarm.

(301) A still further cleaning lance **3500** will now be described, by reference to FIGS. **71**, **72** and **73**. Lance **3500** includes certain additional differences from cleaning lance **1160** and **2600** shown in FIGS. **46** and **47** and FIG. **61** respectively. Cleaning lance **3500** has a main body **3512**, a handle **3513**, a trigger-type switch **3515** for control of cleaning gas flow, a detachable rechargeable battery pack **3517** for powering all its electronic and electric onboard functions, and a cleaning gas inlet hose connection **3519**.

(302) Instead of the “olive” **1174** of lance **1160** (and **2612** of lance **2600**) cleaning lance has a group of three separate conduits **3502**, **3504** and **3506** that enter a space to be cleaned through a port such as port **1114** for example, these conduits being held closely adjacent to each other along their length, and there is no formation corresponding to formation **1172** of lance **1160**. The intent is to ensure that the cross-section of that portion **3501** of the lance **3500** that actually enters a space to be cleaned is of more nearly constant cross-section than olives **1174**, **2612** and formation **1172** allow. It has been found that this is preferable where flexible cover assemblies such as cover assembly **300** for example, with slit-type ports such as ports **3028** are in use. Lance insertion and manipulation is easier and there is less chance of damage to such a cover assembly.

(303) Duct **3502** is for the cleaning gas (eg air). Duct **3504** has at its free end a small digital video camera **3508** corresponding to the camera of lance **2600**. Duct **3506** has at its free end a light source such as an LED **3510**, to provide illumination of the area to which cleaning gas is being directed. Wiring to the camera **3508** and light source **3510** extends along ducts **3504** and **3506** back to main body **3512** of cleaning lance **3500**. Light source **3510** may be for example a “white” LED whose light colour is controllable, and the colour used may be made variable by a user to enhance the ease of recognition of dust for a particular application.

(304) Instead of the alphanumeric screen **2614** of cleaning lance **2600** there is installed in main body **3512** a screen **3514** capable of showing video from the camera **3508**. Screen **3514** is able also to show alarm signals, and menus of available operational choices that a user may make. The system is adapted to enable not only the capture of “before and after” images of areas subject to cleaning (as in lance **2600**) but to provide an aid for aiming and positioning the lance as required. Screen **3514** also of course is able to display all parameters able to be displayed by the screen **2614** of lance **2600**.

(305) Simple pushbutton or other suitable controls **3516** are provided for selection of the various functions of the lance **3500** as required.

(306) In addition to the potential to show alarm conditions on the screen **3514** a warning light **3518** is provided to alert a user to any condition requiring action.

(307) Optionally, accelerometers and a GPS-based position-determining capability (not shown) may also be provided in the main body **3512** of cleaning lance **3500**. The intent is that accelerometers can detect large values consistent with dropping or abuse of the lance **3500** that risks damage and that the positioning capability allows location—and lack of movement—to be detected and logged.

(308) The pulsating flow capability of lance **2600** is also provided via a valve (not shown, but preferably in main body **3512**) controlled by (for example) a pulse-width modulated signal to turn flow off and on. The frequency and mark-space ratio of valve operation may be made variable or selectable by a user to suit a particular application.

(309) Also in common with lance **2600** is provision of one, and preferably two, airborne dust monitoring sensors (not shown, but having inlet ports **3520**) for monitoring and logging of workspace air quality, and the provision of an alarm in the event of excessive dust in the workspace. Suitable gas detecting sensors include for example the laser-based type sold by

Honeywell, including type HPM A11550-XXX. These are very small and have their own fan. Particulate capability as small as PM2.5 are available as is PM10 capability. The provision of two dust sensors provides reliable operation and some insurance against one of them losing correct calibration.

(310) Excessive disagreement between their readings may itself be made an alarm condition. It is possible instead of two identical dust sensors to use two different types, so as to further enhance confidence in their readings.

(311) Pressure sensors (not shown) may be provided in lance **3500**, as for lance **2600**.

(312) A barcode or QR code reader **3522** is provided also, to identify both the equipment being cleaned and the particular port being used, from for example stickers applied to the particular cover assembly in use adjacent to their ports. Other port identifiers, readers and protocols may be used as desired, for example, such as NFC technology.

(313) It is desirable to ensure that there is positive verification of actual insertion of the lance **3500** into all required ports, and to this end sensors are provided on lance portion **3501**. In one embodiment, a set of several miniature Hall Effect sensors are provided in a housing **3524** close-fittingly wrapped around the ducts **3502**, **35104** and **3506**. These can be triggered (i.e. change state) as they pass small magnets (not shown, but which may be short lengths of magnetic strip) secured on the cover assembly in use closely adjacent to each port. These sensors are positioned at a range of positions along and (preferably also) around the lance portion **3501** so that their triggering can allow the instrumentation software (running in block **200b** of FIG. **41**) to determine that insertion has happened, and when and, to a degree governed by the number of sensors, the extent or depth of insertion.

(314) In some embodiments, Hall Effect sensors can be placed at a range of positions along ducts **3504** and/or **3506** provided the material of those ducts is chosen so as not to interfere with their operation.

(315) FIG. **73** shows another arrangement for a portion **3530** of a lance (not shown, but otherwise functionally similar to lance portion **3501**) that enters a space to be cleaned. Lance portion **3530** comprises a single duct **3531** that contains at its free end **3532** a camera **3534** and light source **3536** that do what camera **3508** and light source **3510** of lance **3500** do. A duct for cleaning gas runs inside duct **3531** and has an outlet **3538**. This arrangement can be more readily twisted about its own longitudinal axis than lance portion **3501** when in use.

(316) It is to be understood that in the design of a system according to the invention, a selection of the various features described herein for lances **12**, **1160**, **2600** and **3500** can be made. Some features may be incorporated and some may not. Not all applications would for example require the comparative sophistication of cleaning lance **3500**. For example, although in some applications sensing the pressure differential between a space being cleaned and the workspace outside it is very important, in others, it can be quite unimportant, so that no sensor for the space being cleaned need be provided.

(317) Application of Ventilation or Vacuum Cleaning Alone

(318) It is to be noted that there are many applications in industry where extraction of air or gases, in each case with or without particulates, is achieved by mechanical suction means alone.

Accordingly, a further inventive concept using a system as shown in FIG. **3** or **41** above, is provision of a mechanical ventilation system where both equipment-related sensors and workspace- and/or user-related sensors are provided, and wherein signals from specific ones of the sensors (workplace-, user-, or equipment-related) are used to provide any or all of alarms (or warnings), display the parameter value(s) of concern and if desired or necessary shut down or otherwise control either the ventilation system or the equipment being ventilated. A very wide range of sensors is available today, for sensing not only of particulate levels, but also of potentially harmful gases (eg Hydrogen Sulphide) and suitable ones of these may be selected and used.

(319) Some industrial processes require different levels of ventilation according to how a the

process is being carried out or the stage it has reached, and it is desirable to be able to adjust ventilation to suit—either to provide adequate ventilation or to limit wastage of energy when a particular level of ventilation is not required. Therefore, instead of, or in addition to, alarms, warnings and shutdown commands, it is possible to provide for automatic control of the ventilation system to maintain effectiveness and save energy in a range of conditions.

(320) The systems and embodiments described above amount to examples of the further inventive concept introduced in the previous paragraph. Further examples of potential application areas include grinding equipment and saws (eg for cutting stone kitchen benchtops, a known area of particulate problems). Both mobile and fixed types of equipment can provide other potential applications.

(321) The apparatus and methods described herein may be adapted to removal of particulate matter from various entities, with various geometries. Referring to FIG. 28, (a) represents schematically applications of the type disclosed above, showing in section a cover **700** (corresponding to cover **310** for example) is fitted over an opening **702** of a cavity **704** in an object **706**. Item **708** is a cleaning lance (similar to lance **12**), items **710** are ports (similar to ports **340**), item **712** is an outlet duct (similar to duct **20**), and item **714** is a seal (similar to seals **318** or **321**).

(322) Diagram (b) of FIG. 28 represents schematically an application to removal of particulate matter from a surface **716**. Hood **718** (shown in section) is positioned to abut surface **716** with a seal **728** extending around the area of surface **716** covered by hood **718**. Cleaning lance **722** extends through one of several ports **720** in hood **718**. **726** is an enclosed space defined between surface **716** and hood **718**. An outlet duct **724** is provided for removal of gas and particulate matter.

(323) Diagram (c) of FIG. 28 represents schematically an application where an object **730** is to have particulate matter received and is covered for the purpose by a cover **734** that abuts a surface **732**. Cleaning lances **736** extend through ports **738** and are moved as required. Seal **740** limits or prevents leakage between cover **734** and surface **732**.

(324) Although examples (a), (b) and (c) all show covers (**700**, **718**, **734**) that can abut a flat surface, this is not essential. Where an application requires it, the boundary between cover and the entity it abuts in use need not be planar.

(325) Note also that the object **730** could be an object, or surface **732** could be a surface, on which some particulate-generating process is being carried out, for example sanding, grinding or “scabbling”. Although not shown, the apparatus and methods described may be adapted to contain, and enable removal of, particulates in such cases also, for example by providing an extra access port in the cover for equipment used in the process or for the arm of an operator reaching into the cover.

(326) Covers according to the invention need not necessarily be shaped to cover a flat surface (such as a flange around an opening of an electrical cabinet). Covers for performing the invention (in the same way as covers **310**, **310a**, **310b** and **310c**) may be contoured to suit other enclosure geometries. For example, large electric motors (not shown) may have openings for access to brushes and commutators, and these are components that may need to be cleaned. It is possible to make a cover similar for example to cover **310b** (FIG. 33) save that it is arcuately shaped to cover such an opening during cleaning. In this case, however, ports such as ports **1012** and port assemblies **340** are unsuitable. However, port assemblies of the type shown in FIG. 4 can be used, with at least one slit disc (the same as disc **94**) having its slit (corresponding to slit **96**) parallel to the motor shaft.

(327) Application to Cleaning of Sets of Electrical Machines

(328) A particular example of an application where covers that do not seal against a flat surface will now be described.

(329) FIG. 49 shows an arrangement **1401** (known as a motor-generator set or MG set) of electric machines that can present a cleaning problem. MG set **1401** comprises a synchronous AC electric motor **1403** that drives a number of DC generators **1405**, **1406** **1407** simultaneously, these and the

motor **1403** having their shafts connected to each other in a chain-like manner to rotate as a unit. Bearing blocks **1409** are typically provided between adjacent pairs of the machines **1403-1407** in this arrangement and at the end-most generators **1405**. MG sets of this type can be found in some electric walking draglines, as found in surface coal mining operations, where the generators provide power to DC motors (not shown) that in turn drive bucket hoisting, bucket dragging and swinging functions of the draglines. Variation of the motors' field strengths provides speed control for these functions. MG sets as described here are not found in all draglines but are still common.) (330) Cleaning of commutator/brush assemblies of the generators and of particulate matter that accumulates between and also within the individual machines **3-7** is generally time-consuming, hence expensive in terms of machine downtime, and can present difficulties through exposure of personnel to hazardous particulate matter.

(331) FIG. **50** shows in a schematic manner how embodiments of the present invention may be applied to such cleaning. Spaces **1411** between each pair of machines **1403-1407**, are temporarily enclosed as described below, in part using cover assemblies described below. Also, spaces **1413** at the outer ends of the endmost generators **1405**, including in typical cases the outboard bearing blocks **1409** there, are enclosed, also as described below. The cover assemblies for spaces **1411** and **1413** are shown in FIG. **50** schematically only, by dotted lines.

(332) During cleaning, some or all of spaces **1411** and **1413** are maintained at a pressure below atmospheric pressure by drawing gas (for example, air) out through ducts **1415** that carry air and particulate matter entrained in that gas. The particulate matter within each of spaces **1411** and **1413** is dislodged by blowing gas (for example air) into them using cleaning lances as described above, such as lance **12** or lance **1160**. In FIG. **50**, ducts **1415** are shown as parts of a manifold **1417**, with an outlet **1471** to a system (not shown) such as has been described above by reference to FIG. **2** or FIG. **48**. However, individual spaces **1411** or **1413** may be ventilated individually or in smaller groups, in alternative embodiments.

(333) Thus, it can be seen that the cleaning method is essentially as described earlier herein. This can extend further to direct vacuum cleaning of parts in spaces **1411**, **1413** once gas drawn therefrom is found to have satisfactorily low particulate content. Instrumentation, control and cleaning gas supply arrangements may be in accord with any of the arrangements for these described for other embodiments above.

(334) Note that when the spaces **1411** and **1413** are enclosed, they are connected to each other by the gaps between stators and armatures of the machines, and flow of air (or other gas) and entrained particulate matter through these gaps must be taken account of in the cleaning process. This is described below.

(335) FIG. **51** shows a side view of a pair of generators **1406** and **1407** of MG Set **1401**, mounted (along with the other parts of the MG Set **1401**) on bearers **1419**. FIG. **52** shows the same components (and from the same viewpoint) as FIG. **51**, with the space **1411** between generators **1406** and **1407** now closed in part by cover assembly **1421**. FIG. **53** shows these components in section, at station "Q-Q" shown in FIG. **52**.

(336) Cover assembly **1421** is flexible and able to be draped over the two adjacent generators **1406** and **1407**, being temporarily secured to their casings **1423** and **1425**.

(337) Cover assembly **1421** comprises a sheet **1427** of flexible airtight (or substantially airtight) material that is flexible to enable draping over generators **1406** and **1407** from above. To support sheet **1427** over the space **1411**, stiffening rods **1429** extending parallel to each other and generator shaft **1431**, are provided. These rods **1429** are received in longitudinal pockets formed on the sheet **1427**, as shown. (However, any suitable alternative arrangement for providing stiffening rods **1429** may be used, for example by use of a suitable adhesive to stick them to sheet **1427**.) The stiffening rods extend far enough longitudinally along sheet **1427** to in use bear directly or through their pockets **1433** and sheet **1427** on the casings **1423** and **1425** of generators **1406** and **1407**. Stiffening rods **1429** do not only support the weight of sheet **1427** but prevent excessive inward deflection of

sheet **1427** due to the lower-than atmospheric pressure maintained in space **1411** in use. Cover assembly **1421** is provided with a fitting **1435** for its duct **1415** for removal of gas and particulate matter from space **14112**.

(338) To hold cover assembly in place on casings **1423** and **1425**, pockets **1437** are formed along its end edges, these pockets **1437** containing continuous lengths of magnetic strip **1441** (or, not shown, magnetic strip segments or individual (for example “button”-shaped) magnets). Also provided adjacent to each pocket **1437** are suitable elongate flexible seals **1439**.

(339) Similarly, pockets **1443** with magnets, or magnetic strip or magnetic strip segments therein and seals (not shown) similar to seals **1439** are formed along its longitudinal edges so that the cover assembly **1421** can be secured sealingly to the bearers (or other structure) on which generators **1406** and **1407** are mounted.

(340) As an alternative or adjunct to the magnetic method of attachment described in the previous two paragraphs, adhesive tape may be used to secure cover **1421** to bearers **1419** and generator casings **1423** and **1425**.

(341) Sheet **1427** is shown as formed from a sheet of flexible but transparent or translucent material such as PVC (as described above in relation to cover assembly **1130**), so that a user can see what he or she is doing when cleaning space **1411**. However, alternatively, other materials may be used such as textile material with a elastomeric and gas-sealing coating as is known in the art. Where an alternative material is not transparent, window segments (not shown) of transparent material may be provided at suitable locations in sheet **1427** to allow space **1411** to be seen into.

(342) The sheet **1427** is provided with multiple port covers **1445** in appropriate positions so that a cleaning lance **1447** can be inserted and used to dislodge particulate matter in space **1411**. Lance **1447** may be similar to (or the same as) lance **12** or lance **1160** described above, and connected to a system the same in its functionality as the system **30a** (FIG. **48**). Lighting of space **1411** may be provided by lighting on a lance such as lance **1160** or on cover assembly **1421** itself in essentially any of the ways described above in relation to other cover assemblies. Similarly instrumentation may be provided in essentially the same ways as described above, including sensors (not shown) secured on cover assembly **1421** or on lance **1447** or both.

(343) In FIGS. **52** and **53** port covers **1445** of either of the types shown in FIGS. **42-46** are shown. However, other port arrangements as described earlier above may be used if required. Those port arrangements which require a fixed portion (eg such as component **812**) simply require that the fixed portion be secured to the flexible sheet **1427**.

(344) Cover assembly **1421** has been described by reference to generators **1406** and **1407** but is equally applicable to any of the spaces **1411** shown in FIG. **50**. Where a space **1411** adjacent to motor **1403** is to be covered, it may be necessary to provide a temporary or permanently attached flange (not shown) on motor **1403** to enable use of a cover assembly **1421**.

(345) It will be appreciated that cover assembly **1421** can be simply rolled up when not in use, for ease of transport and storage, similarly to cover **1100**.

(346) To enable maintenance of below-atmospheric pressure in spaces **1411**, it is generally necessary to seal areas below the cover assembly **1421** such as gaps between the generator casings and bearers **1419** or floor structures (not shown). It has been found in tests that this can usually be done easily and adequately by using suitably-shaped pieces of sheet material (exemplified as **1451**) placed in gaps and if necessary taped in place. A very suitable sheet material is of the kind formed by extrusion having twin parallel walls separated by elongate flutes or ribs therebetween, for example as sold under such names as “Corflute”. This is easy to cut to shape and reasonably robust for multiple uses, and has a degree of stiffness for resisting pressure differences.

(347) A slightly different arrangement is required for spaces **1413** at ends of the MG set **1401**. FIG. **55** shows a temporary bulkhead **1459** that is stiff enough to withstand the pressure difference associated with cleaning and that can be sealingly attached to floor structure **1461** using adhesive tape (not shown) and/or magnets or magnetic strip or strip elements in pockets **1463**. A flange (not

visible) on its periphery **1465** is provided for attachment of a cover assembly **1467** similar in its construction as cover assembly **1421** to enclose space **1413**. Bulkhead **1459** may be secured to a bearing block **1409** at the outer end of generator **1405**. Bulkhead **1459** may be provided with a hinge for compact folding when not in use. As for cover assembly **1421**, additional sealing sheets (similar to sheet **1451**) may be provided below cover assembly **1467** as required.

(348) During cleaning of each of the spaces **1411** and **1413**, it is desirable that dislodged particulate matter not be simply blown into the gap between stator and armature of the motor or generator(s) adjacent to the space **1411** or **1413**, or even blown through into a neighbouring gap **1411** or **1413** communicating with the one in which a cleaning lance is in use. A simple approach is to connect only the space being cleaned to the gas-and-entrained-particulates inlet of system **30a** (for example).

(349) However, it is also possible to draw gas and particulates simultaneously from several or all of the spaces **1411** or **1413**, and to this end some embodiments provide that each duct **1415** is connectable to manifold **1417** (formed in practice using flexible hose) via a valve **1475** that can be operated together or individually under control of the data processing system (eg element **204b** of FIG. **41**) so as to control the pressure in each of spaces **1411** or **1413**. For example, it is possible to provide for the space **1411** or **1413** in which lance **1447** is being used to be held at the lowest pressure of all those spaces, with progressively increasing (but sub-atmospheric) pressures being maintained in the spaces on either side of the space so that flow in the armature/stator gaps tends always to be towards the space **1411** or **1413** in which the lance is operating.

(350) It will be appreciated that the method described here for cleaning sets of electrical machines can be applied to other equipment where gaps lend themselves to the use of flexible cover assemblies or can be made to do so by for example provision of components having surfaces suitable for flexible cover assemblies to attach themselves to.

Ventilating and Vacuuming Embodiments

(351) As mentioned above, it is possible to remove particulates from a space by dislodging the particulates using gas expelled from a cleaning lance (for example lance **12**) and drawing the gas and entrained particulates out through a duct (such as **24**) using a vacuum source (for example blower **46** or by direct vacuum cleaning, without the use of a cleaning lance, as shown in FIG. **1(b)**. For cleaning a particular space, both approaches may be used.

(352) In some embodiments of the system **30** shown in FIG. **2** and the system **30a** shown in FIG. **48**, the instrumentation and control system (**199** or **1075**) provides to a user the ability to select multiple modes of operation to facilitate use of both modes as required. For ease of description, this will be described by reference to system **30a** and instrumentation and control system **1075**.

(353) The control inputs (block **206b** in FIG. **41**) may include a mode selection input wherein a user can select either a “blowing mode” wherein supply of cleaning gas through valve **52a** is enabled, for operation of a cleaning lance such as lance **1160**, or a “ventilation/vacuum mode” wherein valve **52a** is closed so that cleaning lance operation is not possible. In

“ventilation/vacuuming mode”, system **30a** becomes an instrumented system for drawing gas and entrained particulates out of a space through duct **20a** or duct **48a**.

(354) In addition to controlling valve **52a** to allow or suppress flow through valve **52a** according the selected operation mode, data processing unit **200b** may also: enable and monitor the sensors at the stations appropriate to the selected mode, so that for example sensors at stations A, B, T are not enabled or monitored in “ventilation/vacuum mode”; control lighting of the space being cleaned, for example by not powering lighting on lance **1160** in “ventilation/vacuum mode”; control display (block **208b**), alarms (block **210b**) to operate according to the selected mode, for example not providing for alarms relating to pressure differential measured at station “T” in ventilation/vacuum mode”; where data is to be logged during cleaning, ensuring that data applicable to the selected mode is appropriately formatted in generated files and transmitted, for example not recording a cleaning lance port in use (in embodiments where that facility is sensed) in “ventilation/vacuum

mode”.

(355) In further embodiments, valve **50a** may be subject to control by data processing unit **200b** so that a user may select (at block **206b**), after selecting “ventilation/vacuum mode”, which of ducts **20a** or **48a** is to be used in “ventilation/vacuum mode”. Alternatively, there may instead simply be provided three possible modes—“blowing mode” (flow permitted through valve **52a** and duct **20a**), “ventilation mode” (no flow through valve **52a**, flow permitted in duct **20a**) and “vacuum mode” (no flow through valve **52a**, flow permitted in duct **48a**). All three of these combinations may operate best with different flow rates through blower **46a**, and data processing unit **200b** may automatically adjust this according to the mode selected.

(356) It is also possible for blower **46a** to be provided instead or additionally with a manual speed control if required.

(357) Some embodiments that enable selection of a “ventilation/vacuum mode” or of either “ventilation mode” or “vacuum mode” have a yet further enhancement. This is provision of a control output for one or more devices external to the system. For example only, a system such as system **30a** may be employed to ventilate, and later clean particulate matter from, a space in which a power tool is used. FIG. **56** shows schematically an arrangement in which system **30a** is shown as a block and is used to ventilate (through duct **20a**) later and clean a dust hood **2014** in which a power saw **2010** is being used to cut a material generating particulates. Power for saw **2010** passes from a mains supply through a relay **2012** that can switch that power on and off. Data processing unit **200b** may be programmed to enable generation of a signal at block **207b** (FIG. **41**) that operates relay **2012** to interrupt power supply to saw **2010** if a chosen sensed quantity (for example particulate concentration in ventilating duct **20a**, sensed at station “F”) exceeds a specified value. Relay **2012** may be a separate device, connected by a cable **2016** to an output location **2018** on enclosure **2002** of the major components of system **30a**, or may be incorporated in system **30a**.

(358) In some applications, it may not be appropriate to cut off power to a device in this way without warning. An enhancement may therefore be provided whereby detection of excess particulates first activates an audible and/or visible alarm and then, if after a specified time particulate concentration does not fall to a satisfactory value, interrupts power to saw **2010**. Any other quantity sensed by system **30a** may be specified to operate relay **2012**.

(359) When cleaning of dust hood **2014** is required, the operating mode of system **30a** can be changed to enable operation of cleaning lance **1160** with drawing out of particulates and gas through duct **20a** or vacuuming through duct **48a** as required.

(360) Note that it is possible to apply system **30a** to ventilation and/or vacuuming of spaces that are not enclosed, for example a dust hood (not shown) on or near a power tool.

(361) A system such as system **30a** may be employed as an instrumentation system only when not in use for cleaning purposes. An example is testing of a centralized industrial ventilation system (not shown) in which multiple dust hoods are connected by ducting to a central particulate collecting installation. Points in such a system may have flow rates much higher than are necessary for cleaning of individual spaces or pieces of equipment, and provided by blower **46a**. For periodic testing of the operation of such a centralized system, system **30a** may be used with duct **20a** acting as a sampling tube taking air and particulates from the centralized system's ducting. At the same time, a workplace particulate sensor, where included in system **30a** would also be able to indicate whether the workplace around the ducting is safe. That is, a cleaning system according to the invention such as system **30a** can have additional uses.

(362) Pretreatment of Particulate-Laden Gas

(363) The relative proportions of fine and coarse particles to be dealt with will vary from application to application, in some cases to the point where correct operation is compromised. This can be a particular problem where the proportion of relatively coarse particles is high. Taking system **999** (FIG. **34**) as an example, large amounts of coarse particulates may require emptying of the container **1042** more often than is desirable, may cause fouling of the fine-fraction bag and

HEPA filters in casing **1040**, and cause inaccuracies in operation of the various sensors.

(364) FIGS. **57** and **58** show a way of dealing with this, again using system **999** as an example. Between a container **2500** whose interior is to be cleaned and the system as described above in its enclosure **1030**, there is provided a pre-treatment system **2502**. Dust laden gas (eg air) is drawn from container **2500** through a duct **2504** as before, but instead of entering enclosure **1030** via inlet **1034**, passes into pre-treatment system **2502**. System **2502** is adapted to remove all or a large proportion of relatively coarse particulate material from this incoming gas. The gas with the unremoved portion of the particulates, then passes from an outlet **2506** through a duct **2508** and into enclosure **1030**.

(365) Pre-treatment system **2502** includes an emptiable receptacle **2510** for receipt of particulates removed by system **2502**.

(366) System **2502** may be designed in various ways. For example, it may simply comprise one or more woven or non-woven textile bag filters or one or more cyclone separators or any other known particulate separation device or combinations of these.

(367) FIG. **58** shows in schematic form a particular realization of system **2502** that applicants have found useful and suitable for use with system **999**. Within an enclosure **2512** (represented in FIG. **58** by chain-dotted lines) are provided two cyclone separators **2514** and **2516** whose particulate outlet ducts **2518** and **2520** direct separated particulates into receptacle **2510**. Gas entering the enclosure **2512** at inlet **2521** is split (at **2522**) into two streams that enter cyclone separators **2514** and **2516**. Relative to receptacle **2510**, the flows in cyclone separators **2514** and **2516** are contra-rotating. This has been found useful in at least limiting movement of particulates within receptacle **2510** during use. It has also been found useful to assist in limiting movement of particulates in receptacle **2510** to extend the particulate outlet ducts **2518** and **2520** partway into receptacle **2510**. Suitable lengths for this extension will depend on design of the receptacle **2510**, and can be found by straightforward experiment or by the use of computerized fluid dynamic (CFD) methods without any need for inventive effort.

(368) Outlet gas streams from separators **2514** and **2516** are combined at **2524** and directed to an outlet **2526**. From outlet **2526**, the combined gas stream passes to enclosure **1030**.

(369) The use of the two separators **2514** and **2516**, instead of one, can provide better utilization of space within enclosure **2512**. Further, although FIG. **58** shows separators **2514** and **2516** connected in parallel, it is also possible (not shown) for them to be connected in series. Moreover, it is also possible to provide multiple separators (not shown) that are differently sized and/or proportioned so as to better deal with a range of particle sizes.

(370) Depending on expected particulate concentrations and cyclone separator (or other separation device) characteristics, it may be necessary or desirable to provide in system **2502** a dedicated fan or blower **2528** as shown in FIG. **58**.

(371) Instrumentation may also be provided in system **2502**. By way of example only, FIG. **58** shows four possible stations labelled X, Y Z and W. Particulate concentration sensors may be provided at stations X and Z, with a suitable sensor for degree of filling of receptacle **2510** at station W. Where a fan or blower **2528** is provided, pressure difference between stations Y and Z may also be sensed.

(372) Outputs from the instrumentation are preferably directed to, and treated as part of, the instrumentation and control system **1075** as shown in FIG. **41**. This enables recording and display of pre-treatment instrumentation outputs and generation of alarms. Communication between the sensors of system **2502** and the remaining part of instrumentation system **1075** may be by cable or may be wireless, using any suitable digital protocol, for example Bluetooth or the like.

(373) Where, as shown in FIG. **57**, a pre-treatment system such as **2502** is used in conjunction with a main system having its own coarse particulate separation device(s) such as system **999**, the coarse particulate separation devices of the main system may or may not be used, as appropriate to their design and/or the application. FIGS. **59** and **60** show one way in which, for system **999**, these

alternatives may conveniently be handled, with a slight modification of duct **1038**. In addition to the gas inlet **1034**, there is provided a separate inlet **2530**. This inlet communicates with a duct **2532** that can receive gas from either the cyclone separator **1036** or inlet **2530**. FIG. **59** shows gas from the system **2502** entering enclosure **1030** at inlet **1034** so as to pass through cyclone separator **1036**. A plug **2534** is placed in inlet **2530** and is shaped (as shown at **2536**) to allow gas leaving separator **1036** to flow efficiently in duct **2532**.

(374) Alternatively, as shown in FIG. **60**, separator **1036** can be bypassed, with gas from pre-treatment system **2502** entering at inlet **2530**. Instead of plug **2534**, an adaptor tube **2538** is now located in inlet **2530**, seals off the outlet of separator **1036** and allows gas to flow past the outlet of separator **1036**, as shown by arrow **2531**.

(375) Data Analysis and Reporting

(376) As described above, a wide range of information can be sensed, displayed locally and/or recorded, and/or transmitted to remote locations—either within a user's enterprise or even further afield. Thus it is possible, at one level, to provide a high level of assurance to an actual user of equipment according to the invention that his or her cleaning activity is working effectively and safely or has reached a defined state of completion and safety. The user can see that the workplace is not being contaminated by fine particulates and also see that a specified degree of cleanliness is being or has been achieved—and can record proof of this.

(377) At an enterprise level, management can be assured of the same things for multiple sites, machines or activities, and can store and access extensive data to enable monitoring of the time and costs involved, manage potential liability and industrial issues associated with cleaning and maintenance generally. Troublesome activities, machines or sites can be pinpointed and corrective action taken.

(378) Moreover, scheduling of cleaning activities can be improved by undertaking analysis of data logged during a sequence of such activities to determine intervals between cleans that contain overall costs to a desired level.

(379) Where cleaning activities are contracted to non-employees, it is possible to verify that the work is being done properly and cost-effectively.

(380) Data can be transmitted beyond the enterprise so that independent verification of work done and its standards may be carried out.

(381) The actual efficiency and effectiveness of different cleaning practices can be monitored using sensed data and used to identify improvements applicable not only to the particular place or activity from which the data came but to similar activities elsewhere. For example, for cleaning of a particular device or space, the required time, the best sequence for insertion of lances into port assemblies and the like can be determined and used to generate instructions (and/or computer programs where applicable) for similar activities elsewhere in the enterprise.

(382) Many enterprises do not have the capability to maintain sensitive equipment and instrumentation adequately. Anomalies in data can be watched for and where these are potentially attributable to the equipment itself, corrective action sought from the equipment supplier.

(383) Every system according to the invention has the capability to sample gas containing particulate material. It is possible to provide for inclusion of such system, or multiple such systems, into a data network so that such data is obtained and made available via that network whenever it is used, or remotely or automatically activate such system when it is not actually in use for the same purpose. When multiple sources of data at multiple locations (located by GPS data included in the sensed data) are provided over a data network, it can become possible through analysis to, for example, pinpoint sources of excessive particulate generation or predict where particulate matter is likely to be taken by wind.

(384) All of the above activities can to some degree be automated—for example through the generation of reports by appropriate computer applications, and doing so is a part of the invention. In particular, the analysis at one location of cleaning activities from data transmitted in digital form

from the actual site of the cleaning activity is a part of the invention, as is the computerized use of accumulated data over time to refine and even automate future activities.

(385) Cleaning in Zones of an Enclosed Space

(386) The use of gas jets to dislodge particulate matter in an enclosed space can have the effect that, after some cleaning has been done, application of a gas jet to a particular location in the space may disturb large quantities of particulates, so that locations already cleaned may be to some extent recontaminated by a cloud of particulate matter.

(387) To limit this effect, it is possible to isolate, at least in part, multiple zones within the enclosed space against recontamination.

(388) FIG. **63** shows schematically a section of an enclosure **2800** whose interior is to be cleaned according to the invention, using air as a cleaning medium (although the principle is applicable also where other gases are to be used). A cover **2802** sealingly covers an opening in the enclosure **2800** and is provided with port assemblies **2804** for insertion of a cleaning lance **2806** (eg any of lances **12**, **1160** or **2600**). Once a zone “A” in enclosure **2800** has received at least an initial cleaning using lance **2806**, an “air curtain” **2808a** is introduced through a nozzle **2810a**, the nozzle being elongate in a direction normal to the plane of the drawing, in known manner. Air for the air curtain **2808a** may be obtained from the atmosphere using a dedicated blower, or the same air supply used by the equipment of the invention, or air recirculated from the air being expelled from the enclosure **2800**. Air curtain **2808a** isolates to some degree zone “A” while cleaning proceeds in zones “B” and “C”. The process is repeated when zone “B” has been dealt with, by establishing a second air curtain **2808b** through nozzle **2810b**. Finally, zone “C” is cleaned.

(389) Depending on the particular enclosure **2800**, the particulate load therein, cleaning technique used, and the like, it may be desirable to complete the cleaning process with further use of the lance **2806** in all three zones, with or without switching off of the air curtains **2808a** and **2808b**.

(390) FIG. **64** shows a variation on the above approach, in which an enclosure **2900** is to be cleaned. Enclosure **2900** is fitted sealingly with a cover **2902**, having port assemblies **2904** for insertion of a lance (not shown) such as lance **2806**. The procedure is similar to that described in relation to enclosure **2800**, save that instead of actuating air curtains to at least partially isolate zones “A”, “B” and “C” the cover is provided with physical partitions **2906a** and **2906b** that can be slid inwardly and outwardly as required, through slots **2908** in cover **2902** and partitions **2906a** and **2906b** are slid inwardly to at least partially isolate the zones above them.

(391) Additional Information on Software

(392) There will now be provided a summary of software functionality adapted for cleaning applications of the invention where sophisticated control of pressure in a space being cleaned is not necessary, and not provided, and where a lance with onboard software functions such as lance **3500** is used.

(393) First, the software run by a microcontroller of block **200b** (FIG. **41**), consists of a start-up, a main loop and a series of interrupt driven events. On start-up, the software performs a scan of the ‘stack’ in which it is connected to determine what other layers of hardware are present. It uses this scan to enable/disable relevant sections of code accordingly. During the start up the software also uses the connected communication devices to search for and attempt to connect to other system peripherals so that they may communicate and share data. This pairing may occur in several ways, for instance, pressing a button on each device at the same time or may be set in software to automatically connect to a certain device with a given identification, if it is available. Should a connection not be established or a layer not found in the stack, the functions in the code relevant to those pieces of hardware are disabled.

(394) Furthermore, with regards to enabling or disabling functionality in the code, a configuration file may be used on the SD card to determine what functions are available. Should a functionality need to be disabled or enabled for any reason outside of the relevant hardware being present on the stack, it may be done so here. Sensor ranges, set points and thresholds, as well as the unique

identification of the hardware may also be found in this configuration file which is read in the start up of the device each time. This allows the same software to be loaded onto other systems according to the invention and having the functionality determined by the configuration file on the SD card which is inserted into the SD card slot on the motherboard. Authentication keys or certificates for secure transfer of data may also be stored and read from this configuration file.

(395) After start up the device enters a loop. This begins by first sampling each sensor it finds on the stack sequentially. Some sensors may be sampled many times while other sensors may be sampled less frequently, depending on the importance and how rapidly the sensor may be changing. These values are then compared against set points or threshold values which determine whether the system may be operating in a failure mode, under which conditions the software shuts off the compressed air and/or motor in order to prevent operator exposure or unsafe operating conditions. A wide range of communication protocols are used to interface with the sensors. These include analogue, digital, 4-20 mA, I2C/TWI, SPI, UART, USART and USB. After sampling the values are, if required, passed through a filter to reduce noise, typically this is done through the use of a moving point average. This is used to reduce noise of data shown on displays (reducing flickering of traffic light display). The data is then logged on a SD card, if an SD card is inserted. The data may also be uploaded via 4G/WiFi using HTTP or MQTT protocols (or similar secure protocols) to a remote server if those layers of stack are included.

(396) Any time during this loop, interrupt routines may occur, these are used for detecting important safety controls and button presses. For instance, the lance is able to send an interrupt if it detects a failure mode to quickly shut down the motor or the compressed air in the case of a dust leak. Accelerometers are used to detect falling or sudden impacts which may also necessitate a shut down, or, depending on magnitude of the accelerometer reading, be an indicator for mistreatment of the device. Interrupts may also be used for a microswitch which is triggered by opening the lid of the enclosure containing the main components of the system. If this switch is triggered, the software on the microcontroller switches off power to prevent potentially dangerous voltages being exposed. When this interrupt is triggered, it also sounds an alarm to indicate the hazard is present and bring the users attention to the fact that power has not been disconnected properly.

(397) The software also has functionality to calculate current in and out of a battery should one be attached, allowing for the battery or charge status to be estimated and displayed, recorded or transmitted to other devices.

(398) The software may also communicate with a GPS if it is found on the hardware stack. With this sensor, a 'Geo-Fence' may be implemented with boundaries set in the configuration file found on the SD card.

(399) Second, a cleaning lance such as lance **3500** may be capable of operating independently of the running software described above but also be able to communicate back and forth when paired with a system ("main system") such as that represented with FIGS. **41** and **48**. The lance may be used to display data from, such as, filter status or dust concentrations as well as allowing the operator to remotely control the main system, for instance, shutting down the motor in the main system from the lance. Communications may be performed using several communication protocols. These include radio (915 MHz), Bluetooth, Bluetooth LE, WiFi etc. These devices would also be found on the block **200b** hardware stack.

(400) The software on the lance is capable of producing a PWM signal of a given frequency which drives the compressed air valve. This allows for the 'pulsed' compressed air cleaning.

(401) The air quality sensors on the lance, which detect particulate matter may be to detect whether satisfactory sealing of the area being cleaned has been achieved. If high levels of dust are detected, this is a shutdown condition. The lance software first sends an electrical signal to the valve to stop the compressed air and also uses one of the connected communication devices to send a message to the main system indicating that a shutdown is required.

(402) The lance is able to capture and process images from a camera at the tip of lance. These

images may be displayed on the screen for the user to view immediately, or stored on an SD so that the images may be viewed later, perhaps to evaluate state of targeted area before and after cleaning. The software may perform some image processing on these captures.

(403) The lance is also able to automatically scan barcodes during use which indicate what is being cleaned at this time. This may be recorded so that any data logged at this time can be associated with the relevant truck/cabinet/motor etc.

(404) Similarly, to the lance implementation, the main system may also communicate to other peripherals, such as a compressed air quality measurement unit which may send messages to both the lance and main system which may be used to shut off the compressed air should the quality be insufficient

(405) The lance may similarly have accelerometers to detect dropping or sudden impacts, similarly to as described with the main system.

(406) In most applications, it is expected that data logged in use of the inventive system will be transmitted to a server remote from the space being cleaned and that may itself part of the system. The data may be received using various protocols (HTTP, MQTT as examples). The data may be processed and analysed to determine filter status and device status. The software running on this server is also capable of generating CSV files. This allows the data to be viewed in widely used software packages such as Excel. The analysis and processing software on the server may also be used to generate reports indicating cleaning performance and details of the cleans performed over a given timespan. This may be generated in the form of a PDF document. This report generation may be performed automatically at a given time or a manually executed process.

(407) The implementation of this software is also open, allowing for the software to be easily deployed on a physical or cloud-based server if desired.

COMBINATIONS OF FEATURES

(408) In the above description very many of the components, features of components, system arrangements, modes of operation and the like that have been stated to have alternatives that can be used in particular applications, or added optionally or not used or implemented. Where such alternatives are described, it is intended that they may be used in combinations other than the specific combinations described, where that is practicable, and where suited to a particular application.

(409) For example only, different port assemblies have been described and different cover assemblies have been described, but a port assembly described in association with a particular cover assembly may be used with another cover assembly if that is practicable.

Claims

1. An apparatus for removing particulate matter from an enclosure having an internal space and an opening into the internal space, comprising: a cover positionable adjacent the opening so that the cover covers the opening; a gas source external to the internal space; an inlet conduit that, when in use, extends through a specific first port in the cover and is adapted to direct gas from the gas source to at least one gas outlet within the internal space whereby particulate matter within the internal space is dislodged and entrained in gas within the internal space; and a blower that draws gas and particulate matter entrained therein from the internal space through a second port opening into the enclosure then successively through an outlet conduit, a particulate matter separation and collection means comprising at least one filter, and into an inlet of the blower; wherein: the specific first port is one of a plurality of first ports in the cover; the inlet conduit comprises an elongate lance having a first portion that includes the gas outlet and that a user in a workspace outside the enclosure can insert through the specific first port in the cover so that the gas outlet enters the internal space, the lance further having a second portion that then remains outside the internal space and is configured for manipulation by the user to move the gas outlet among locations within the

internal space and to withdraw the lance from the specific first port for insertion into a further one of the plurality of first ports; the apparatus further comprises a first sensor for sensing concentration of particulate matter in gas leaving the internal space; the apparatus further comprises a second sensor that is on the second portion of the lance for sensing concentration of particulate matter in air at a location in the workspace outside the internal space; and a visual display on the second portion of the lance; and wherein: the visual display is configured to display to the user in real time a concentration of particulate matter leaving the internal space sensed by the first sensor and is configured to display in real time a concentration of particulate matter in the workplace sensed by the second sensor while the apparatus is in use to alert the user in response to a detected excess value of particulate concentration in the workspace outside of the internal space while the lance is inserted into the internal space; and wherein the visual display is configured to display to the user, in real time, information on functioning of the apparatus derived from additional sensors comprised in the apparatus.

2. The apparatus according to claim 1, wherein the apparatus is automatically shut down if concentration of particulate matter sensed by the second sensor exceeds a specified level.
3. The apparatus according to claim 1, wherein alarm conditions indicating excessive particulate concentration sensed by the second sensor are signaled to the user by a warning light on the second portion of the lance or by the visual display.
4. The apparatus according to claim 1, wherein the visual display comprises a screen on the second portion of the lance.
5. The apparatus according to claim 1, wherein air from the workplace is drawn to the second sensor through an opening on the second portion of the lance.
6. The apparatus according to claim 5, wherein the second sensor is positioned on the second portion of the lance.
7. The apparatus according to claim 1, further comprising one or more pressure sensors on the lance configured to sense a difference in pressure between air in the workplace and gas at an opening in the first portion of the lance.
8. The apparatus according to claim 7, wherein gas flow from the gas outlet is automatically interrupted if gas pressure at the opening in the first portion of the lance exceeds the atmospheric pressure in the workspace.
9. The apparatus according to claim 1, wherein a light emitting device is positioned on the first portion of the lance for illumination of the internal space.
10. The apparatus according to claim 1, wherein the lance comprises a lance insertion sensor that detects insertion of the first portion of the lance into one of the plurality of first ports in the cover by sensing the presence of an element on the cover adjacent the said one of the plurality of first ports when the first portion is received therein.
11. The apparatus according to claim 10, wherein the element is one of a plurality of elements each of which is adjacent to one of the plurality of first ports and different from the elements adjacent to other ports of the plurality of first ports and wherein the lance insertion sensor that detects insertion of the first portion of the lance into a particular first port is configured to distinguish the particular element and accordingly a particular first port into which the first portion of the lance has been inserted.
12. The apparatus according to claim 1, wherein the inlet conduit comprises a valve configured when in use to interrupt gas flow in the inlet conduit periodically so that flow from the gas outlet is pulsatory.
13. The apparatus according to claim 1, further comprising a microprocessor configured to write to memory information derived from at least the first and second sensors.
14. The apparatus according to claim 13, configured to transmit information derived from at least the first and second sensors to a location remote from the apparatus under control of the microprocessor.

15. The apparatus according to claim 1, wherein the outlet conduit in use draws gas through an opening in the cover.
 16. The apparatus according to claim 1, wherein at least a portion of the gas leaving the blower is included in the gas supplied to the lance.
 17. The apparatus according to claim 1, wherein the cover comprises a sheet of transparent flexible material whereby the user can see into the internal space during use of the apparatus, and wherein the cover can be rolled up into a roll after use for storage.
 18. The apparatus according to claim 17, wherein the cover comprises at least one elongate stiffener that when the cover is in use extends from one side of the opening of the enclosure to an opposite side thereof whereby to limit bulging of the cover into the internal space.
 19. The apparatus according to claim 17, wherein the specific first port in the cover comprises a slit formed in the transparent flexible material.
 20. The apparatus according to claim 1, wherein the cover is held in place on the enclosure by one of: magnetic strip; adhesive tape; and individual magnets.
 21. A method for removing particulate matter from an enclosure having an internal space and an opening into the internal space, comprising the steps of: positioning a cover adjacent the opening so that the cover covers the opening; providing a gas source external to the internal space; providing an inlet conduit that comprises an elongate lance having a first portion with a gas outlet and that directs gas from the gas source to the gas outlet; by a user in a workspace outside the enclosure, inserting the first portion of the lance through a specific first port in the cover that is one of a plurality of first ports in the cover so that the gas outlet is within the internal space and particulate matter within the internal space is dislodged and entrained in gas within the internal space; by a blower, drawing gas and particulate matter entrained therein from the internal space firstly through a second port opening into the enclosure then successively through an outlet conduit, a particulate matter separation and collection means comprising at least one filter, and into an inlet of the blower; by the user manipulating a second portion of the lance that in use remains outside the enclosure, moving the gas outlet among positions within the internal space and relocating the lance among the plurality of first ports comprised in the cover; sensing concentration of particulate matter in gas leaving the internal space by a first sensor; sensing concentration of particulate matter in air at a location in the workspace outside the enclosure by a second sensor that is on the second portion of the lance; and displaying information derived from the first and second sensors to the user in real time by a visual display on the lance, and continuing operation of the apparatus while concentration of particulate matter in the workspace is below an unsafe level and until a satisfactory value of particulate concentration in gas leaving the internal space is achieved; and further displaying, by the visual display to the user in real time, information on functioning of the apparatus derived from additional sensors comprised in the apparatus.
 22. The apparatus according to claim 1, further comprising means for wireless communication between the lance and portions of the apparatus separate from the lance for exchange of signals relating to sensor outputs, alarms, control inputs, and the visual display.
 23. The apparatus according to claim 6, wherein the second sensor is one of two particulate concentration sensors on the lance.
 24. The apparatus according to claim 1, wherein the second port is positioned on in the cover.
-