

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402831
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Butterworth; Ian

Finger inserts for a nailfold imaging device

Abstract

A finger insert for use with a nailfold imaging device includes a housing to receive the user's finger and an immersion substance (e.g., immersion oil), and a deformable pad that holds the user's finger in place during imaging, as well as prevent bubble formation in the substance. The housing includes a transparent wall to facilitate imaging of the finger. The transparent wall includes multiple angled portions that prevent or reduce contact between the nailfold and the wall, to ensure sufficient blood flow through the nailfold region for imaging.

Inventors:	Butterworth; Ian (Somerville, MA)
Applicant:	Massachusetts Institute of Technology (Cambridge, MA)
Family ID:	74189551
Assignee:	Massachusetts Institute of Technology (Cambridge, MA)
Appl. No.:	17/516109
Filed:	November 01, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220192589 A1	Jun. 23, 2022

Related U.S. Application Data

continuation parent-doc US 16882966 20200526 US 11160492 child-doc US 17516109
us-provisional-application US 62878011 20190724

Publication Classification

Int. Cl.: A61B5/00 (20060101); **A61B5/022** (20060101); **A61B5/026** (20060101); **G06V40/12** (20220101)

U.S. Cl.:

CPC **A61B5/449** (20130101); **A61B5/0077** (20130101); **A61B5/0082** (20130101);
A61B5/02241 (20130101); **A61B5/0261** (20130101); **A61B5/6826** (20130101);
A61B5/702 (20130101); A61B2562/146 (20130101); A61B2562/16 (20130101);
A61B2562/164 (20130101); A61B2562/168 (20130101); G06V40/1341 (20220101)

Field of Classification Search

CPC: A61B (2562/168); A61B (2562/164); A61B (2562/16); A61B (2562/146); A61B (5/702);
A61B (5/6826); A61B (5/0261); A61B (5/02241); A61B (5/0082); A61B (5/0077); A61B
(5/449); G06V (40/1341)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
534211	12/1894	English	N/A	N/A
2548378	12/1950	Kleinfeld	N/A	N/A
2588528	12/1951	Howser	N/A	N/A
4425924	12/1983	Riva et al.	N/A	N/A
4694843	12/1986	Casenhiser	2/21	A45D 29/00
4998533	12/1990	Winkelman	N/A	N/A
5068536	12/1990	Rosenthal	N/A	N/A
5077476	12/1990	Rosenthal	N/A	N/A
5086229	12/1991	Rosenthal et al.	N/A	N/A
5204532	12/1992	Rosenthal	N/A	N/A
5218207	12/1992	Rosenthal	N/A	N/A
5237178	12/1992	Rosenthal et al.	N/A	N/A
5362966	12/1993	Rosenthal et al.	N/A	N/A
5365066	12/1993	Krueger, Jr. et al.	N/A	N/A
5436455	12/1994	Rosenthal et al.	N/A	N/A
5452717	12/1994	Branigan et al.	N/A	N/A
5582705	12/1995	Yeung et al.	N/A	N/A
5596987	12/1996	Chance	N/A	N/A
5598842	12/1996	Ishihara et al.	N/A	N/A
5676143	12/1996	Simonsen et al.	N/A	N/A
5782757	12/1997	Diab et al.	N/A	N/A
5791345	12/1997	Ishihara et al.	N/A	N/A
5855212	12/1998	Walker	132/73.5	A45D 29/007
5926261	12/1998	Hoshino	N/A	N/A
5934278	12/1998	Ishihara et al.	N/A	N/A
5983120	12/1998	Groner et al.	N/A	N/A
6041247	12/1999	Weckstrom et al.	N/A	N/A
6154285	12/1999	Teng	356/71	G06V 40/1324

6179159	12/2000	Gurley	N/A	N/A
6213952	12/2000	Finarov et al.	N/A	N/A
6246786	12/2000	Nishikiori et al.	N/A	N/A
6358208	12/2001	Lang et al.	N/A	N/A
6424851	12/2001	Berman et al.	N/A	N/A
6634367	12/2002	Abraham	132/285	A45D 29/004
6687521	12/2003	Sato	600/344	A61B 5/6838
7477924	12/2008	Chin	600/323	A61B 5/02438
8145286	12/2011	Arai et al.	N/A	N/A
8858429	12/2013	Mizuyoshi et al.	N/A	N/A
9556416	12/2016	Luscher et al.	N/A	N/A
9984277	12/2017	Castro-Gonzalez et al.	N/A	N/A
10433733	12/2018	Wang et al.	N/A	N/A
10485309	12/2018	Bonner	N/A	A44C 9/0061
10952622	12/2020	Fine et al.	N/A	N/A
11160492	12/2020	Butterworth	N/A	N/A
11244452	12/2021	Castro-Gonzalez et al.	N/A	N/A
11963750	12/2023	Castro-Gonzalez et al.	N/A	N/A
2001/0002431	12/2000	Gurley	N/A	N/A
2005/0209514	12/2004	Oshima et al.	N/A	N/A
2005/0268369	12/2004	Santiago	N/A	N/A
2006/0060770	12/2005	Page et al.	N/A	N/A
2006/0161063	12/2005	Shau	N/A	N/A
2007/0092115	12/2006	Usher et al.	N/A	N/A
2007/0116345	12/2006	Peterson et al.	N/A	N/A
2007/0161877	12/2006	Arai et al.	N/A	N/A
2007/0260129	12/2006	Chin	N/A	N/A
2008/0079723	12/2007	Hanson et al.	N/A	N/A
2009/0005693	12/2008	Brauner et al.	N/A	N/A
2009/0018417	12/2008	Wang	N/A	N/A
2009/0093970	12/2008	Lewy et al.	N/A	N/A
2009/0204044	12/2008	Benison	N/A	N/A
2010/0104169	12/2009	Yamada	N/A	N/A
2010/0254582	12/2009	Liu et al.	N/A	N/A
2010/0292629	12/2009	Dacey, Jr. et al.	N/A	N/A
2010/0324407	12/2009	Pichon et al.	N/A	N/A
2011/0081056	12/2010	Salafia	N/A	N/A
2011/0134426	12/2010	Kaduchak et al.	N/A	N/A
2011/0275908	12/2010	Baumann	N/A	N/A
2011/0299749	12/2010	Rauch	N/A	N/A
2012/0089031	12/2011	Ince	N/A	N/A
2012/0177257	12/2011	Maev	382/124	A61B 5/1172
2012/0269420	12/2011	Najarian et al.	N/A	N/A
2013/0011055	12/2012	You et al.	N/A	N/A
2013/0216119	12/2012	Baumgart	N/A	N/A
2013/0235949	12/2012	Jeckeln	N/A	N/A

2014/0018647	12/2013	Segman	N/A	N/A
2014/0038206	12/2013	Holmes et al.	N/A	N/A
2014/0068513	12/2013	Sakagawa	N/A	N/A
2014/0085482	12/2013	Teich et al.	N/A	N/A
2014/0092377	12/2013	Liu et al.	N/A	N/A
2014/0160481	12/2013	Ahner et al.	N/A	N/A
2014/0232869	12/2013	May et al.	N/A	N/A
2014/0240667	12/2013	Uji et al.	N/A	N/A
2014/0249784	12/2013	Sankaran et al.	N/A	N/A
2014/0273076	12/2013	Adams et al.	N/A	N/A
2015/0141766	12/2014	Fine	N/A	N/A
2015/0169641	12/2014	Alldrin et al.	N/A	N/A
2016/0014038	12/2015	Thyagarajan et al.	N/A	N/A
2016/0148038	12/2015	Castro-Gonzalez et al.	N/A	N/A
2017/0039714	12/2016	Small et al.	N/A	N/A
2017/0138849	12/2016	Tucker-Schwartz et al.	N/A	N/A
2017/0367459	12/2016	Yamasaki	N/A	B41J 29/02
2017/0367924	12/2016	Nan	N/A	N/A
2018/0012359	12/2017	Prentasic et al.	N/A	N/A
2018/0098683	12/2017	Kikuchi et al.	N/A	N/A
2018/0211380	12/2017	Tandon et al.	N/A	N/A
2018/0271382	12/2017	Bezemer et al.	N/A	N/A
2019/0139221	12/2018	Castro-Gonzalez et al.	N/A	N/A
2019/0228527	12/2018	Ramirez et al.	N/A	N/A
2020/0116698	12/2019	Zelmanovic et al.	N/A	N/A
2020/0237272	12/2019	Lin et al.	N/A	N/A
2021/0022665	12/2020	Butterworth	N/A	N/A
2021/0374963	12/2020	Gonzalez et al.	N/A	N/A
2022/0192589	12/2021	Butterworth	N/A	N/A
2022/0254024	12/2021	Castro-Gonzalez et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1108082	12/1994	CN	N/A
1228014	12/1998	CN	N/A
1342054	12/2001	CN	N/A
1399131	12/2002	CN	N/A
107115099	12/2016	CN	N/A
106803247	12/2020	CN	N/A
0641542	12/1994	EP	N/A
1685794	12/2005	EP	N/A
2007215951	12/2006	JP	N/A
2013169296	12/2012	JP	N/A
2012110373	12/2012	JP	N/A
2013545516	12/2012	JP	N/A
2014045868	12/2013	JP	N/A

2015515894	12/2014	JP	N/A
2015157071	12/2014	JP	N/A
2016509505	12/2015	JP	N/A
2016086842	12/2015	JP	N/A
2016202442	12/2015	JP	N/A
2017097711	12/2016	JP	N/A
100935455	12/2009	KR	N/A
20130028484	12/2012	KR	N/A
101273692	12/2012	KR	N/A
101452576	12/2013	KR	N/A
0027276	12/1999	WO	N/A
0122741	12/2000	WO	N/A
0207276	12/2001	WO	N/A
2012061078	12/2011	WO	N/A
2013167641	12/2012	WO	N/A
2013173446	12/2012	WO	N/A
2016086023	12/2015	WO	N/A
2017127732	12/2016	WO	N/A
2019079310	12/2018	WO	N/A
2021015843	12/2020	WO	N/A

OTHER PUBLICATIONS

Chen “The Research of Measurement and Recognition of the Human Microcirculatory Parameters Based on Image Processor Analysis” Thesis (with abstract), Nanjing Univ. of Aeronautics and Astronautics, 2012, 137 pages. cited by applicant

Chinese Notice of Allowance and Search Report with English Translation in Chinese Application No. 202080065336.X dated Oct. 19, 2022, 9 pages. cited by applicant

Decision of Refusal and English translation in Japanese Application No. 2020-542060 dated Nov. 21, 2022, 21 pages. cited by applicant

First Office Action and Search Report (with translation) in Chinese Application No.201880076372.9 dated Dec. 5, 2022, 17 pages. cited by applicant

Hu et al. Development of Image Analysing System of Nail Fold Microcirculation, Chinese Journal of Microcirculation, vol. 5, No. 2, 1995, 6 pages. cited by applicant

Notice of Acceptance in Australian Application No. 2018352526 dated Nov. 18, 2022, 3 pages. cited by applicant

U.S. Appl. No. 62/572,738, filed Oct. 16, 2017, Alvaro Sanchez Ferro. cited by applicant

U.S. Appl. No. 62/878,011, filed Jul. 24, 2019, Ian Butterworth. cited by applicant

Extended European Search Report in European Application No. 22172020.4 dated Mar. 20, 2023, 12 pages. cited by applicant

Partial European Search Report in European Application No. 22172020.4 dated Dec. 16, 2022, 14 pages. cited by applicant

USPTO e-Office Action: CTFR—Final Rejection in U.S. Appl. No. 17/666,461 dated Sep. 7, 2023. cited by applicant

USPTO e-Office Action: CTNF—Non-Final Rejection in U.S. Appl. No. 16/882,966 dated Feb. 19, 2021. cited by applicant

USPTO e-Office Action: CTNF—Non-Final Rejection in U.S. Appl. No. 14/951,260 dated Sep. 19, 2017. cited by applicant

USPTO e-Office Action: CTNF—Non-Final Rejection in U.S. Appl. No. 16/162,006 dated May 5, 2021. cited by applicant

USPTO e-Office Action: CTNF—Non-Final Rejection in U.S. Appl. No. 17/666,461 dated Mar. 15,

2023. cited by applicant
USPTO e-Office Action: NOA—Notice of Allowance and Fees Due (Ptol-85) in U.S. Appl. No. 16/882,966 dated Jun. 2, 2021. cited by applicant
USPTO e-Office Action: NOA—Notice of Allowance and Fees Due (Ptol-85) in U.S. Appl. No. 14/951,260 dated Feb. 1, 2018. cited by applicant
USPTO e-Office Action: NOA—Notice of Allowance and Fees Due in U.S. Appl. No. 16/162,006 dated Sep. 30, 2021. cited by applicant
Yap et al., “Mechanical deformation of neutrophils into narrow channels induces pseudopod projection and changes in biomechanical properties”, *Journal of Applied Physiology* 98.5 (2005): 1930-1939. cited by applicant
Extended European Search Report in European Application No. 20843851.5, dated Apr. 6, 2023, 14 pages. cited by applicant
Second Office Action (with translation) in Chinese Application No.201880076372.9 dated May 20, 2023, 11 pages. cited by applicant
International Search Report and Written Opinion in International Patent Application No. PCT/US2021/034455 mailed Sep. 21, 2021, 11 pages. cited by applicant
Decision of Refusal and English translation dated Jul. 24, 2023 in Japanese App. No. 2020-542060 29 pages. cited by applicant
First Australian Report in Australian App. No. 2023200739 dated Mar. 12, 2024, 5 pages. cited by applicant
Notice of Allowance with translation in Chinese Application No.201880076372.9 dated Apr. 5, 2024, 4 pages. cited by applicant
Office Action in Canadian App. No.3,079,209 dated Mar. 21, 2024, 4 pages. cited by applicant
Third Office Action with translation in Japanese App. No. 2020-542060 mailed Apr. 1, 2024, 9 pages. cited by applicant
Allen et al., “Computer based system for acquisition and analysis of nailfold capillary images,” *Medical Image Understanding & Analysis*, (2003): 1-4. cited by applicant
Anderson et al., “Computerized nailfold video capillaroscopy-a new tool for assessment of raynaud's phenomenon,” *J. Rheumatology* 32.5 (2005): 841-848. cited by applicant
Bezemer et al., “Validation of near-infrared laser speckle imaging for assessing microvascular (re) perfusion.” *Microvascular research* 79.2 (2010): 139-143. cited by applicant
Bourquard et al., “Non-invasive detection of severe neutropenia in chemotherapy patients by optical imaging of nailfold microcirculation.” *Scientific reports* 8.1 (2018): 1-12. cited by applicant
Bourquard, Aurelien, et al. “Analysis of white blood cell dynamics in nailfold capillaries.” 2015 37th Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC). IEEE, 2015, 11 pages. cited by applicant
Brown et al., “Rigidity of Circulating Lymphocytes is Primarily Conferred by Vimentin Intermediate Filaments”, *The Journal of Immunology*, 166.11 (2001): 6640-6646. cited by applicant
Cheng et al., “Non-invasive assessment of microvascular and endothelial function.” *JoVE (Journal of Visualized Experiments)* 71 (2013): e50008. 8 pages. cited by applicant
CS&E PCT Collaborative Search and Examination Pilot Upload Peer Contribution mailed Mar. 7, 2019, 58 pages. cited by applicant
Delgado-Gonzalo et al., “Spline-based framework for interactive segmentation in biomedical imaging,” *IRBM* 34.3 (2013): 235-243. cited by applicant
Deneux et al., “A processing work-flow for measuring erythrocytes velocity in extended vascular networks from wide field high-resolution optical imaging data.” *Neuroimage* 59.3 (2012): 2569-2588. cited by applicant
Dobbe et al., “Measurement of functional microcirculatory geometry and velocity distributions using automated image analysis.” *Medical & biological engineering & computing* 46.7 (2008):

659-670. cited by applicant

Doshi et al., "Computer-Aided Analysis of Nailfold Capillaroscopy Images." Handbook of Research on Trends in the Diagnosis and Treatment of Chronic Conditions. IGI Global, 2016. 146-158. cited by applicant

Drew, Patrick J., et al. "Rapid determination of particle velocity from space-time images using the Radon transform." Journal of computational neuroscience 29.1-2 (2010): 5-11. cited by applicant

Eden et al., "An automated method for analysis of flow characteristics of circulating particles from in vivo video microscopy," IEEE Transactions on Medical Imaging 24.8 (2005): 1011-1024. cited by applicant

Etehad Tavakol, Mahnaz, et al. "Nailfold capillaroscopy in rheumatic diseases: which parameters should be evaluated ?." BioMed research international 2015 (2015). cited by applicant

Extended European Search Report in European Patent Application No. 15862463.5 dated Sep. 11, 2018, 7 pages. cited by applicant

Extended European Search Report in European Patent Application No. 18867626.6 dated May 19, 2021, 8 pages. cited by applicant

Golan et al., "Noninvasive imaging of flowing blood cells using label-free spectrally encoded flow cytometry," Biomed Opt Express 3.6 (2012): 1455-1464. cited by applicant

Grassi et al., "Capillaroscopy: questions and answers." Clinical rheumatology 26.12 (2007): 2009. 8 pages. cited by applicant

Hofstee et al., "A multicentre study on the reliability of qualitative and quantitative nail-fold videocapillaroscopy assessment." Rheumatology 51.4 (2012): 749-755. cited by applicant

Hofstee et al., "A multicentre study on the reliability of qualitative and quantitative nail-fold videocapillaroscopy assessment," Rheumatology (2011): ker403. cited by applicant

Hollis et al., "Comparison of venous and capillary differential leukocyte counts using a standard hematology analyzer and a novel microfluidic impedance cytometer," PloS One 7.9 (2012): e43702. 8 pages. cited by applicant

Hou et al., "A computerized system of nail-fold capillaroscopy for dry eye disease diagnosis." Multidimensional Systems and Signal Processing 23.4 (2012): 515-524. cited by applicant

Huang et al., "A SR-based radon transform to extract weak lines from noise images," in Proceedings Int Conf on Image Processing, Barcelona, Spain 1 (2003): 849-852. cited by applicant

International Search Report and Written Opinion in International Patent Application No. PCT/US18/56100 mailed Mar. 7, 2019, 16 pages. cited by applicant

International Search Report and Written Opinion in International Patent Application No. PCT/US2020/034483 mailed Aug. 4, 2020, 11 pages. cited by applicant

International Search Report and Written Opinion issued for PCT/US15/62487, dated Feb. 5, 2016. 13 pages. cited by applicant

Kaur et al., "Nailfold Capillarscopy Techniques—A Review," IRACST—IJCSITS 2.2 (2012): 326-331. cited by applicant

Kim et al., "An original approach for quantification of blood vessels on the whole tumour section." Analytical cellular pathology 25.2 (2003): 63-75. cited by applicant

Lefford et al., "Nailfold capillary microscopy in connective tissue disease: a quantitative morphological analysis." Annals of the rheumatic diseases 45.9 (1986): 741-749. cited by applicant

MacLennan et al., "Finger-prick blood samples can be used interchangeably with venous samples for CD4 cell counting indicating their potential for use in CD4 rapid tests," AIDS 21.12 (2007): 1643-1645. cited by applicant

McKay et al., "Imaging human blood cells in vivo with oblique back-illumination capillaroscopy." Biomedical Optics Express 11.5 (2020): 2373-2382. cited by applicant

McKay et al., "Visualization of blood cell contrast in nailfold capillaries with high-speed reverse lens mobile phone microscopy." Biomedical Optics Express 11.4 (2020): 2268-2276. cited by applicant

Mengko et al., "Morphological characterization of nailfold capillaries." 2016 International Seminar on Intelligent Technology and Its Applications (ISITIA). IEEE, 2016. 6 pages. cited by applicant

Mercer et al., "Quantitative nailfold video capillaroscopy in patients with idiopathic inflammatory myopathy." *Rheumatology* 49.9 (2010): 1699-1705. cited by applicant

Moeini, Mohammad, et al. "Effects of anesthesia on the cerebral capillary blood flow in young and old mice." *Multiphoton Microscopy in the Biomedical Sciences XV*. vol. 9329. International Society for Optics and Photonics, 2015, 7 pages. cited by applicant

Mugii, et a., "Reduced red blood cell velocity in nail-fold capillaries as a sensitive and specific indicator of microcirculation injury in systemic sclerosis," *Rheumatology* 48.6 (2009): 696-703. cited by applicant

Murray et al., "The influence of measurement location on reliability of quantitative nailfold videocapillaroscopy in patients with SSc." *Rheumatology* 51.7 (2012): 1323-1330. cited by applicant

Nagy et al., "Nailfold digital capillaroscopy in 447 patients with connective tissue disease and Raynaud's disease." *Journal of the European Academy of Dermatology and Venereology* 18.1 (2004): 62-68. cited by applicant

Pablo-Trinidad et al., "Automated detection of neutropenia using noninvasive video microscopy of superficial capillaries." *American journal of hematology* 94.8 (2019): E219. 4 pages. cited by applicant

Pennarola et al., "Nailfold capillroscopic monitoring as preventive medicine in subjects exposed to ionising radiation." 11th International Congress of the international Radiation Protection Association. 2004. 6 pages. cited by applicant

Rao et al., "Evaluation of a new point of care automated complete blood count (CBC) analyzer in various clinical settings," *Clinica Chimica Acta* 389.1-2 (2008): 120-125. cited by applicant

Reif et al., "Label-free imaging of blood vessel morphology with capillary resolution using optical microangiography." *Quantitative imaging in medicine and surgery* 2.3 (2012): 207. 6 pages. cited by applicant

Riva et al., "Blue field entoptic phenomenon and blood velocity in the retinal capillaries," *JOSA* 70.10 (1980): 1234-1238. cited by applicant

Russcher et al., "Evaluation of the HemoCue WBC DIFF system for point-of-care counting of total and differential white cells in pediatric samples, " *Ned Tijdschr Klin Chem Labgeneesk* 38.3 (2013): 140-141. cited by applicant

Sainthillier et al., "Skin capillary network recognition and analysis by means of neural algorithms." *Skin Research and Technology* 11.1 (2005): 9-16. cited by applicant

Shore, "Capillaroscopy and the measurement of capillary pressure." *British journal of clinical pharmacology* 50.6 (2000): 501-513. cited by applicant

Uji et al., "The source of moving particles in parafoveal capillaries detected by adaptive optics scanning laser ophthalmoscopy," *Investigative Ophthalmology & Visual Science* 53.1 (2012): 171-178. cited by applicant

Winkelman et al., "Noninvasive Blood Cell Measurements by Imaging of the Microcirculation," *Am J Clin Pathol* 113 (2000): 479-483. cited by applicant

Wu, Chih-Chieh, et al. "Accuracy evaluation of RBC velocity measurement in nail-fold capillaries." *Microvascular research* 81.3 (2011): 252-260. cited by applicant

Chen et al. Deep learning in label-free cell classification. *Scientific reports*, 6.1 (2016): 21471, 16 pages. cited by applicant

Mudugamuwa, et al. "Review on Photomicrography Based Full Blood Count (FBC) Testing and Recent Advancements." *Adv. Tech.*, (2021), 33 pages. cited by applicant

Nitkunanantharajah, et al. "Three-dimensional optoacoustic imaging of nailfold capillaries in systemic sclerosis and its potential for disease differentiation using deep learning." *Scientific reports* 10.1 (2020): 16444, 9 pages. cited by applicant

PCT International Search and Written Opinion for International App. No. PCT/US2018/056100 dated Mar. 7, 2019, 11 pages. cited by applicant
PCT International Search and Written Opinion for International App. No. PCT/US2020/034483 dated Aug. 4, 2020, 10 pages. cited by applicant
WIPO International Preliminary report on Patentability Chapter 1, Sep. 21, 2021, PCT/US2021/034455 (Year 2021), 9 pages. cited by applicant
Written Opinion of the International Searching Authority for International App. No. PCT/US2021/034455, mailed Sep. 21, 2021, 8 pages. cited by applicant
Written Opinion of the International Searching Authority for International Application No. PCT/US2022/039000, dated Oct. 26, 2022, 8 pages. cited by applicant
Ye, et al. In-vivo full-field measurement of microcirculatory blood flow velocity based on intelligent object identification. Journal of biomedical optics 25.1 (2020): 016003-016003, 12 pages. cited by applicant
Notice of Allowance in European App. No. 20843851.5 dated Jan. 3, 2024, 8 pages. cited by applicant
Third Office Action (with translation) in Chinese Application No.201880076372.9 dated Jan. 11, 2024, 4 pages. cited by applicant
Examination Report in European Application No. 22172020.4 dated Dec. 11, 2024, 7 pages. cited by applicant
Notice of Allowance in European App. No. 20843851.5 dated Jul. 3, 2024, 7 pages. cited by applicant
Decision to Grant in European App. No. 20843851.5 dated Nov. 14, 2024, 2 pages. cited by applicant
Non-Final Office Action in U.S. Appl. No. 18/633,176 dated Dec. 4, 2024, 11 pages. cited by applicant
Extended European Search Report in European App. No. 23207252.0 dated Jun. 6, 2024, 12 pages. cited by applicant
Howlader et al: "Correlation of severity of chronic venous disease with capillary morphology assessed by capillary microscopy", Journal of Vascular Surgery, Elsevier, Amsterdam, NL, vol. 43, No. 3, Mar. 1, 2006 (Mar. 1, 2006), pp. 563-569, XP005314953, ISSN: 0741-5214, DOI: 10.1016/J.JVS.2005.10.077, 7 pages. cited by applicant
Australian Office Action (Acceptance) in Australian App. No. 2023200739 dated Sep. 30, 2024, 3 pages. cited by applicant
Decision to Grant with English translation in Japanese Application No. 2020-542060 mailed Sep. 17, 2024, 5 pages. cited by applicant
Bourquard et al., "Non-invasive detection of severe neutropenia in chemotherapy patients by optical imaging of nailfold microcirculation—Supplementary." Scientific reports 8.1 Nov. 1, 2018: 1-29, XP093035656, DOI: 10.1038/s41598-018-23591, 29 pages. cited by applicant
Extended European Search Report in European App. No. 24218887.8 dated Mar. 18, 2025, 15 pages. cited by applicant
Office Action in Chinese App. No. 202211658856.9 with Google Translation dated Jun. 19, 2025, 12 pages. cited by applicant

Primary Examiner: Buran; Ashley K

Assistant Examiner: Bor; Helene

Attorney, Agent or Firm: Smith Baluch LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of, and claims priority to, U.S. Non-Provisional application Ser. No. 16/882,966 titled “FINGER INSERTS FOR A NAILFOLD IMAGING DEVICE” filed May 26, 2020, which claims priority to U.S. Provisional Application No. 62/878,011 titled “FINGER INSERTS FOR A NAILFOLD IMAGING DEVICE” filed Jul. 24, 2019, the entire disclosure of which is incorporated by reference.

BACKGROUND

(1) White blood cells (WBCs, also referred to as leukocytes or leucocytes) are cells of the immune system that are involved in protecting the body against both infectious disease and foreign invaders. WBCs can exist not only in the blood, but also in the lymphatic system and tissues. Some conditions can trigger a response in the immune system and cause an increase in the number of WBCs (also referred to as WBC count). Other conditions can affect the production of WBCs by the bone marrow or the survival of existing WBCs in the circulation system. As these examples illustrate, various conditions can cause a change (either an increase or a decrease) of the number of circulating WBCs. Therefore, WBC count can be a relevant physiological parameter for the diagnosis, monitoring, and/or treatment of various conditions including, but not limited to, bacterial and viral infections (e.g., pneumonia or meningitis), bone marrow functionality associated with chemotherapy toxicity, and hematologic proliferative processes such as leukemia.

(2) In current clinical practice, most of the tests to derive WBC count are performed with large-scale equipment in central clinical laboratories. Generally, these ex vivo tests are still invasive because blood samples are collected from a patient (usually a full vial of blood is needed for each test). These blood samples are then transported, queued, and analyzed in laboratory tests, thereby taking several days to receive any results. This procedure can be burdensome for patients who need regular WBC counts or for patients with emergent conditions as well as their care. In addition, due to the ex vivo nature of conventional blood tests, there can be a certain bias of some parameters owing to the inherent differences between the measurements and the true physiological properties.

(3) Related U.S. patent publication nos. 2016/0148038 and 2019/0139221 generally disclose nailfold imaging devices that include a finger well, as illustrated in FIG. 1. The finger well **110** of the imaging device **100** accommodates the user's finger **120** in the imaging device **100** and contains optical immersion oil. The finger well **110** also includes a flat optical window **130**, to allow for illumination and for time-lapse microscopic imaging of the nailfold region of the user's finger **120** through the optical window **130**. In such a finger well design, the rigid housing that forms the finger well **110** can provide enough space to accommodate different finger sizes, but can leave a gap between the finger and the housing, allowing space for the finger to move easily. Even with the user's hand resting on the housing for stability, this can result in involuntary movement of the finger that can make video recordings and/or imaging difficult. One potential solution is to ‘under-size’ the finger well to reduce finger movement; however, this limits the range of finger sizes that the device can accommodate.

SUMMARY

(4) A finger insert for a finger imaging device includes a housing an opening to receive a finger of a subject. The housing defines a landing region abuts against a distal phalange of the finger of the subject when the finger is placed into the finger insert via the opening. The housing holds a liquid to facilitate imaging of a nailfold of the finger of the subject, such that at least the distal phalange of the finger is immersed in the liquid when the liquid is present in the finger insert and as the finger is placed into the finger insert via the opening. The housing includes a first wall and a second wall, with the second wall being optically transparent to facilitate imaging of the nailfold of

the finger. The finger insert further includes a deformable pad positioned on at least a portion of the first wall, to form an open-pore structure that fills a gap between the first wall and the finger of the user when the finger is inserted into the finger insert, and to reduce trapped air in the liquid when the liquid is present in the finger insert, during insertion and movement of the finger in the finger insert

(5) A system includes a finger imaging device including a light source, a detector, and a receptacle including an imaging window. The light source and the detector are optically coupled to the imaging window. The system also includes a finger insert, the finger insert being disposable in the receptacle. The finger insert includes a housing defining an opening an opening to receive a finger of a subject, and further defining a landing region that abuts against a distal phalange of the finger of the subject when the finger is placed into the finger insert via the opening, to hold a liquid to facilitate imaging of a nailfold of the finger of the subject. At least the distal phalange of the finger is immersed in the liquid when the liquid is present in the finger insert and as the finger is placed into the finger insert via the opening. The housing includes a first wall and a second wall, the second wall being optically transparent to facilitate imaging of the nailfold of the finger via the light source and detector. The finger insert further includes a deformable pad positioned on at least a portion of the first wall, to form an open-pore structure that fills a gap between the first wall and the finger of the user when the finger is inserted into the finger insert, and to reduce trapped air in the liquid when the liquid is present in the finger insert, during insertion and movement of the finger in the finger insert.

(6) A kit includes a finger imaging device including a light source, a detector, and a receptacle including an imaging window. The light source and the detector are optically coupled to the imaging window. The kit also includes a set of finger inserts, each finger insert of the set of finger inserts being disposable in the receptacle such that at least a section of the second wall of that finger insert is in optical communication with the imaging window when that finger insert is disposed in the receptacle. A first finger insert of the set of finger inserts is different from a finger insert apparatus of the set of finger inserts in one or more of a length of the housing along its longitudinal axis, and an average cross-sectional area of a curved portion of the first wall.

(7) A method includes receiving a finger of a user in a finger insert disposed in a finger imaging device. The finger insert includes a housing defining an opening an opening to receive a finger of a subject, and further defining a landing region abuts against a distal phalange of the finger of the subject when the finger is placed into the finger insert via the opening, to hold a liquid to facilitate imaging of a nailfold of the finger of the subject. At least the distal phalange of the finger is immersed in the liquid when the liquid is present in the finger insert and as the finger is placed into the finger insert via the opening. The housing including a first wall and a second wall, the second wall being optically transparent to facilitate imaging of the nailfold of the finger. The finger insert also includes a deformable pad positioned on at least a portion of the first wall, to form an open-pore structure that fills a gap between the first wall and the finger of the user when the finger is inserted into the finger insert, and to reduce trapped air in the liquid when the liquid is present in the finger insert, during insertion and movement of the finger in the finger insert. The method further includes imaging a nailfold portion of the finger via the wall portion of the finger insert using the finger imaging device.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The patent or application file contains at least one drawing executed in color. Copies of this patent or patent application publication with color drawing(s) will be provided by the Office upon request and payment of the necessary fee.

(2) The skilled artisan will understand that the drawings primarily are for illustrative purposes and are not intended to limit the scope of the inventive subject matter described herein. The drawings are not necessarily to scale; in some instances, various aspects of the inventive subject matter disclosed herein may be shown exaggerated or enlarged in the drawings to facilitate an understanding of different features. In the drawings, like reference characters generally refer to like features (e.g., functionally similar and/or structurally similar elements).

(3) FIG. 1 is an illustration of conventional nailfold imaging with a user's finger disposed in a finger well.

(4) FIG. 2 illustrates example aspects and/or considerations for designing of a finger insert.

(5) FIG. 3 illustrates an example finger insert.

(6) FIG. 4 illustrates the finger insert of FIG. 3 being inserted into a receptacle of a nailfold imaging device.

(7) FIG. 5 illustrates details of a nailfold imaging device.

(8) FIG. 6A shows the finger insert of FIG. 3 without spacers and without immersion oil.

(9) FIG. 6B shows the finger insert of FIG. 6A with some immersion oil added.

(10) FIG. 7A shows another finger insert and a nailfold imaging device for receiving that insert, according to the present disclosure.

(11) FIG. 7B shows the components of FIG. 7A with the insert positioned in the nailfold imaging device.

(12) FIG. 8A illustrates a perspective view of another example finger insert.

(13) FIG. 8B illustrates a front view of the finger insert of FIG. 8A.

(14) FIG. 8C illustrates a side view of the finger insert of FIG. 8A.

(15) FIG. 8D illustrates a top view of the finger insert of FIG. 8A.

(16) FIG. 9 illustrates a side view of the finger insert of FIG. 8A with a deformable pad, and with a user's finger inserted into the finger insert.

(17) FIG. 10A shows a top view of an example finger insert similar to the finger insert of FIG. 8A.

(18) FIG. 10B shows a front view of the finger insert of FIG. 10A.

(19) FIG. 11A shows an example finger insert with immersion oil and with a sealed opening.

(20) FIG. 11B is another view of the finger insert of FIG. 11A.

(21) FIG. 11C is another finger insert similar to that of FIG. 11A, but different in at least one aspect.

(22) FIG. 12 shows an example finger insert, similar to the finger insert of FIG. 8A, positioned in a nailfold imaging device.

(23) FIG. 13 illustrates a method for nailfold imaging.

(24) FIG. 14 shows how a user places their finger within a finger insert. The nailfold region is marked by a black dot placed at the center of the region.

(25) FIG. 15 illustrates an example of nailfold width and height calculation, done using the marked black dot as reference for the center of the nailfold.

(26) FIG. 16 is a plot demonstrating the variability between all subjects' nailfold ROI centers. The span is approximately 12 mm vertically and 5 mm horizontally.

(27) FIG. 17 illustrates an example data point from a particular subject's finger, with an approximate mapping of data distribution to an image of the finger in-place during one repeat.

(28) FIG. 18 is a plot illustrating five data points from each subject's ring finger on their right hand. It also illustrates the range of finger-tip lengths and slight asymmetries of each specific finger of a user, and the variation in movement between that one finger's repetitive insertion into the finger insert.

(29) FIG. 19 is a plot illustrating five data points from each subject's ring finger on their left hand. It also illustrates the range of finger-tip lengths and slight asymmetries of each specific finger of a user, and the variation in movement between that one finger's repetitive insertion into the finger insert.

(30) FIG. 20 is a plot illustrating all data points from the plots of FIGS. 18, 19, by subject. Intra-subject data shows the variation across different fingers of that subject.

(31) FIG. 21 illustrates the nailfold ROI of all the subjects overlaid on each other, while the black boxes are the different FoVs at the time. Specifically, the left plot illustrates the free positioning of the nailfolds ROIs, while the right plot illustrates a similar study where the vertical position of the finger insert in the receiving device was pre-calibrated by a measurement of the length of the finger-tip to nailfold, demonstrating a reduction in the variation in ROI positions across multiple users and fingers.

DETAILED DESCRIPTION

(32) Following below are more detailed descriptions of various concepts related to, and implementations of, kits, systems, devices, and methods that encompass finger inserts for nailfold imaging. It should be appreciated that various concepts introduced above and discussed in greater detail below may be implemented in numerous ways. Examples of specific implementations and applications are provided primarily for illustrative purposes to enable those skilled in the art to practice the implementations and alternatives apparent to those skilled in the art.

(33) The figures and example implementations described below are not meant to limit the scope of the present implementations to a single embodiment. Other implementations are possible by way of interchange of some or all of the described or illustrated elements. Moreover, where certain elements of the disclosed example implementations may be partially or fully implemented using known components, in some instances only those portions of such known components that are necessary for an understanding of the present implementations are described, and detailed descriptions of other portions of such known components are omitted so as not to obscure the present implementations.

(34) Generally, a finger insert as described herein can include and/or encompass a removable piece that is inserted into a nailfold imaging device before a measurement (e.g., imaging, video recording) starts, and is removed afterwards. In one aspect, the finger insert may be single-use and disposable, or reusable. In another aspect, the finger insert can be designed to engage with the nailfold imaging device ergonomically and securely, such that it provides a sturdy yet comfortable support for the finger while in use.

(35) As described in greater detail later, the finger insert can include an incorporated optical window to ensure that the optical path between the imaging and illumination optics is clean and transparent each time. Immersion oil can be pre-filled into the finger insert to prevent re-use and contamination of immersion oils with particulates. The insert accommodates different finger sizes through variable internal geometry, with different sized inserts available (e.g., small-long, small-short, medium-long, medium-short, large-long, large-short).

(36) In another aspect, the finger insert includes one or more flexible spacers to effectively and comfortably fill a gap that may be present between the rigid body of the finger insert and the finger of the subject. In one example discussed in further detail below, the flexible spacers may be implemented as rubber cylinders extruded from (and extending from) the walls of the body of the finger insert. In one aspect, the open-pore structure of the rubber cylinders significantly mitigates the trapping of air which would otherwise occur with semi-closed-pore structures like sponges, that would produce air bubbles in the immersion oil under the typical compression that occurs during inserting and movement of the finger.

(37) FIG. 2 illustrates aspects of finger geometry that can be considered when designing inventive finger inserts according to the present disclosure to accommodate various finger sizes. As a first example aspect, cross-sectional area and shape along the length of the finger (e.g., see the cross-sectional profiles 210, 220, 230 along the length of the finger) can affect how securely the finger fits into the opening in the finger insert, and also how much force is applied on the finger.

Excessive force on the finger can result in restriction of blood flow (that could in turn impede measurement made on the nailfold capillaries of that finger), and too little support or restriction

would reduce the necessary constraint for minimizing involuntary movement.

(38) A second example aspect can be the length of the finger from fingertip to nailfold (e.g., the length **240**), which is typically the same or similar to the fingernail length of that finger. The finger insert is designed such that the fingertip registers with the bottom of the insert, so that the distance between the end of the finger and the nailfold affects how high the nailfold sits in the well of the finger insert. This can be significant since the nailfold would need to fall within a region where the nailfold imaging device is able to image the nailfold region.

(39) FIG. 3 illustrates an example finger insert **310**. The insert **310** can include a housing **312**, a plate **330** (that may or may not be integrally formed with the housing), and multiple spacers **340** that are deformable by a user's finger when inserted into the insert **310**. The housing **312** and the plate **330** can be made from a substantially rigid, inelastic material such as a transparent thermoplastic (e.g. Poly(methyl methacrylate), or PMMA). The spacers can be made from an elastic, deformable material such as a silicone. In some cases, the material of the spacers can be optically transparent, while it can be absorbing in some other cases.

(40) The housing can include a top end **314** that has an opening to receive the user's finger, and a bottom end **316**. A body **318** of the housing **312** is disposed and/or otherwise formed between the top end **314** and the bottom end **316**, and can hold an immersion oil. The immersion oil can be selected to have a refractive index (e.g., a RI of about 1.51) that is similar to that of the housing and/or the dermis of the finger, to facilitate the nailfold imaging. The housing **312** can be sized to hold enough immersion oil such that at least the distal phalange of the finger is fully immersed in it. The housing **312** can include a curved portion **320** and a wall portion **322**. The wall portion **322** can be optically transparent and substantially flat to prevent spurious reflections that can arise due to the illumination. In some cases the wall portion **322** can be curved, or another suitable form to conform to the nailfold imaging device during use.

(41) The curved portion **320** can have a cross-sectional area (CSA) that (in at least a portion of the curved portion **320**) continuously or discontinuously changes from the top end **314** to the bottom end **316**. As explained above in connection with FIG. 2, such a CSA profile can accommodate for the typical changes in CSA of a user's finger along its length, towards the nailfold region. The curved portion **320** can be optically transparent, or absorbing to prevent reflection of a light beam from the light source of the nailfold imaging device.

(42) The CSA can vary from about 3 cm.^{sup.2} to about 1 cm.^{sup.2} from the top end **314** to the bottom end **316**. The depth of the housing from the top end **314** to the bottom end **316** can vary from about 10 mm to about 20 mm.

(43) The plate **330** is disposed, attached, coupled and/or otherwise present at the bottom end **316** of the housing **312** and can abut against a distal phalange of the finger of the subject to position the finger for imaging. The plate **330** and the bottom end **316** can form a fluid-tight seal to prevent the immersion oil from leaking.

(44) As also shown in FIG. 3, multiple, deformable spacers **340** can be positioned, attached, formed, and/or otherwise disposed on the curved portion **320**. The number, size, shape, and/or other aspects of the spacers **340** can be useful for forming an open-pore structure that can effectively and significantly fill a gap between the curved portion **320** and the finger of the user when inserted. Further, the spacers **340** can be designed to accommodate a variety of finger geometries, with the goal of providing support to minimize unintentional movement during the measurement. Additionally, the open-pore structure of the spacers **340**, even when deformed due to the pressure from the user's finger, significantly reduces or eliminates trapped air in the immersion oil when the user's finger is inserted into the insert, or moved around within the insert.

(45) FIG. 4 illustrates a system **400** that includes a finger insert **410**, which can be structurally and/or functionally similar to the insert **310**. The system also includes a nailfold imaging device **450**, which can be similar to such devices disclosed in the related U.S. patent publication nos. 2016/0148038 and 2019/0139221, the disclosures of which are incorporated herein by reference in

their entirety. The insert **410** is inserted into a receptacle **420** of the device **450** to achieve a firm mating to allow for rigid mechanical coupling of the insert **410** and device **450**, and to achieve a stable optical alignment for imaging the nailfold region of a finger in the insert **410**. FIG. 5 generally illustrates an example nailfold imaging device **1100** (also referred to as a “WBC detection and analysis system”) that includes a finger holder **1110** with a receptacle **1112** (also referred to as a “finger hold”). An imaging window **1114** is formed within the receptacle **1112** can be in optical communication with the interior of the insert **410** via its wall portion to permit nailfold imaging of the user's finger in the insert.

(46) The device **1100** can include an imager/imaging setup **1120** that includes a light source (not shown) to illuminate the user's nailfold region within the insert **410** via the window **1114**. The imager **1120** includes a focusing optic **1122** to collect light reflected or scattered from the finger and detector **1124** to receive the reflected or scattered light so as to form images of the finger. The device **1100** further includes a processor **1130** operably coupled to the imager **1120** and a memory **1140** operably coupled to the processor **1130**. The memory **1140** is encoded with processor-executable instructions, which, when executed by processor **1130**, may perform the methods described in the '038 and/or the '221 publications to analyze images received from the imager **1120**. The device **1100** also includes a display **1150**, which can display the images or videos taken by the imager **1120** and/or data associated with WBC events detected by the processor **1130**.

(47) FIG. 6A shows the insert **310** without the spacers and without any immersion oil, and illustrates the optical clarity of the insert **310**. FIG. 6B illustrates the insert of FIG. 3A with immersion oil added.

(48) FIG. 7A illustrates another insert design, where insert **710** does not include the wall portion of the insert **310**, and wherein the plate **730** has a relatively more rounded profile than the plate **330** to better conform to a user's fingertip, and to prevent inadvertent movement. In some cases, however, the plate **730** can be substantially flat.

(49) As illustrated in FIG. 7B, when the insert **710** is inserted into the nailfold imaging device **750** and immersion oil is added, the lack of the wall portion can provide for fewer coupling layers between the device and the user's finger, and a simplified design relative to that of the insert **310**. Such a setup can require removal and replacement of immersion oil within the receptacle of the device **750**, periodic cleaning to avoid accumulation of dirt and/or dust, and replacement of the imaging window (e.g., the window **1114**) due to potential scratching over time, which can deteriorate imaging.

(50) Aspects disclosed herein can also include a kit of finger inserts (e.g., the insert **310**, **710**, etc.). At least some of the inserts in the kit can be identical to each other, while in some cases, at least some of the inserts can be different in, for example, length of the housing, the cross-sectional profile of the curved portion, and so on. In this manner, the kit can include enough identical inserts for typical finger sizes and profiles, for repeated imaging thereof, and/or for varied finger sizes and profiles. In some cases, the kit can include the nailfold imaging device itself as well.

(51) FIGS. 8A-8D illustrates a housing **820** of another finger insert design. The housing **820** includes an opening **830** through which a user can insert their finger into the housing. Upon insertion, the distal phalange of the finger of the user can land on and/or abut against a landing region **840** of the housing **820**. The landing region **840**, can generally form, at least in part, a curved socket that conforms to the shape of the tip of a typical human finger. The curved socket can be positioned to ensure that the user's finger lands landed approximately centered about a longitudinal axis A-A' of the housing **820** in the view illustrated in FIG. 8B.

(52) Generally, the housing **820** can form a fluid-tight seal to hold a substance, e.g., an immersion oil or any other suitable liquid, to facilitate imaging. For example, the immersion oil can have a refractive index (e.g., a RI of about 1.51) that is similar to that of the housing **820** and/or the dermis of the finger, to facilitate the nailfold imaging. The housing **820** can be sized such that at least the distal phalange of the user's finger is within the housing **820**, and can be immersed in the substance,

to permit imaging of the nailfold region. For example, a length of the housing, such as along the axis A-A', can be from about 1 cm to about 7 cm, including all values and sub-ranges in between. The housing **820** can be wholly or partly formed of an inelastic material such as, for example such as an optically transparent thermoplastic (e.g. Poly(methyl methacrylate), or PMMA) glass (e.g., amorphous or crystalline), quartz (e.g., including Herkimer diamond, rock crystal, etc.), and/or the like. It is understood that imaging of the nailfold region can encompass imaging of at least some portion of the nailfold. For example, it is not required that the entire nailfold of the finger be exposed and/or otherwise available for imaging (e.g., due to the size of the imaging window of the imaging device), and imaging of the exposed portion of the nailfold can be sufficient for the purposes laid out herein, including for white blood cell measurements.

(53) The housing **820** can be formed of a first wall **850** and a second wall **855**, forming a fluid-tight seal as described above. The walls **855** can be integrally formed, or separately formed and fused, joined, glued, and/or otherwise combined together to yield the housing **820**. The second wall **855**, which can interface with imaging components (e.g., an illumination source, a detector, and/or the like) of a nailfold imaging device during use can be substantially optically transparent in the range of about 400 nm to about 800 nm, including all values and sub-ranges in between. In some cases, the first wall **850**, and/or a portion thereof, can be substantially optically transparent as well. As explained in greater detail below, the walls **850**, **855** can include various portions that accommodate a user's finger, and act in concert to maintain it in place, during use. The first wall **850** can be curved (e.g., round, elliptical, oval, parabolic, a curved spline, and/or the like) with respect to the axis A-A', as illustrated in FIGS. **8A-8C**. The second wall **855** can be flat (e.g., sheet-like) with respect to the axis A-A'.

(54) The first wall **850** can define a wall portion **860a**, a wall portion **860b** adjacent to the wall portion **860a**, and a wall portion **860c** adjacent to the wall portion **860b**. The second wall portion can define a wall portion **865a**, a wall portion **865b** adjacent to the wall portion **865a**, and a wall portion **865c** adjacent to the wall portion **865b**. These wall portions **865a**, **865b**, **865c**, **860a**, **860b**, and **860c** are sometimes also referred to here as a first wall portion, a second wall portion, a third wall portion, a fourth wall portion, a fifth wall portion, and a sixth wall portion, respectively. It is understood that while described as separate portions, any adjacent walls portions (e.g., the wall portions **865a**, **865b**) may be integrally formed such as, for example, via injection molding. In some cases, the entire housing **820** can be formed as a single piece via injection molding. In some cases, adjacent wall portions may be separately formed and fused, joined, glued, and/or otherwise combined together to form their respective wall.

(55) Referring to the second wall **855**, an edge/side of the wall portion **865a** can form a portion of the rim of the opening **830**, as best illustrated in FIG. **8A**. The wall portion **865a** can be substantially optically transparent to permit imaging of the nailfold region of the user's finger. The wall portion **865a** can be substantially flat in its entirety, or in part such as, for example, towards the wall portion **865b**. During use a knuckle of the user's finger, e.g., the distal interphalangeal joint, can abut or lie against the wall portion **865a**, as illustrated in FIG. **9** for the knuckle K, and described in greater detail later. The wall portion **865a** can be angled with respect to, and/or form an angle with, the wall portion **865b** at an angle α_1 , which can be about 10°, about 15°, about 20°, about 25°, about 30°, including all values and sub-ranges in between. The wall portion **865c**, in turn can be angled with respect to, and/or form an angle with, the wall portion **865b** at an angle α_2 , which can be about 10°, about 15°, about 20°, about 25°, about 30°, including all values and sub-ranges in between.

(56) Referring to the first wall **850**, an edge/side of the wall portion **860a** can form a remaining portion of the rim of the opening **830**, such that the wall portions **860a**, **860b** collective form and/or otherwise define the opening **830**. As illustrated in FIGS. **8A-8C**, the opening **830** can be generally circular, though in other cases (not shown), the opening **830** can be oval, elliptical, and/or the like. Factors affecting the shape of the opening **820** can include, but are not limited to, ease of holding,

inserting, and/or removing the housing **820**, ease of sealing the opening **820** with a fluid-tight seal, the shape of an opening of a receptacle in a finger insert device that receiving the insert **810**, ease of fabrication (e.g., during injection molding), and/or the like.

(57) As described above for the first wall **850** and as illustrated, the wall portion **860a** can be curved. The cross-sectional area defined by the wall portion **860a** can be substantially the same, or continuously decrease, from the opening **830** towards the wall portion **860b**. The cross-sectional area can be, for example, about 2 cm.sup.2 to about 4 cm.sup.2 at the opening **830**. In some cases, the cross-sectional area defined by the wall portion **860a** can decrease in a periodic or step-wise manner, such that the wall portion **860a** defines two or more different cross-sectional areas from the opening **830** towards the wall portion **860b**. The wall portion **860a** can be substantially optically transparent, e.g., similar to the wall portion **865a**. In some cases, the wall portion **860a** can be partially transparent, and/or composed of a light absorbing material, to prevent undesirable reflection of the excitation light during nailfold imaging. The wall portions **860b**, **860c** can collectively form and/or otherwise define the landing region that receives the end of the user's finger during use, as best illustrated in FIGS. **8A**, **8C**.

(58) FIG. **9** illustrates a finger insert **910**, which can be structurally and/or functionally similar to the finger insert **810**, and generally shows the insert **910** during use, with a finger F of a user inserted through an opening **920**. Unless expressly noted otherwise, similarly illustrated and labeled structures in FIG. **9** may be structurally and/or functionally similar to those in FIGS. **8A-8C** such as, for example, the wall portion **965a** can be similar to the wall portion **865a**, and so on.

(59) The insert **910** includes a pad **975** that is affixed, glued, and/or otherwise positioned on the first wall **850**, e.g., wholly, or at least partly on the wall portion **860a** of the first wall. The deformable pad **975** includes a base layer **985** and multiple spacers **980** formed on the base layer. In some cases, the base layer **985** can be absent, and the spacers **980** can be formed directly on the first wall **850**. The pad **975** can be wholly deformable, e.g., both the base layer **985** and the spacers **980** can be composed of a deformable material such as, for example, silicone or a silicone-based material. In some cases, the base layer **985** and the spacers **980** can be composed of different materials of different deformability such as, for example, a silicone, a nitrile, a neoprene and/or other rubbers, combinations thereof, and/or the like. In other cases, the pad **975** can be partially deformable such as, for example, having the base layer **985** be composed of a rigid, inelastic material while the spacers **980** are composed of a deformable material.

(60) The deformability of the spacers **980** can elastically deform upon insertion of the user's finger F, to press the finger F against the second wall **950**. Each spacer **980** can be suitably shaped, sized, and laid out in an open-pore structure to maintain separation between adjacent spacers in the absence of deformation. Further, the open-pore structure of the spacers **980** can reduce the formation of air bubbles and/or generally reduce/eliminate any trapped air in the immersion liquid that may have entered the insert **910** during insertion or movement of the user's finger. Such trapped air can interfere with nailfold imaging and lead to artifacts.

(61) The spacer **980** can be generally columnar or cylindrical in form, including forms such as, for example, right circular cylinders, oblique cylinders, cones, oblique cones, frustums (e.g., pyramidal, or conical), prismatic (e.g., elongated prisms, truncated elongated prisms, fin-like), and/or combinations thereof. As illustrated in FIG. **9**, in some cases the spacers **980** can be substantially frustoconical in form, having a larger cross-sectional radius towards the base layer **985**/the wall portion **975**. The number of spacers can be 2, 10, 20, 50, 100, 150, 200, or more than 200, including all values and sub-ranges in between.

(62) FIG. **9** also illustrates how the wall portions **960c**, **965c** cooperate to define and/or enclose a nail space **970** that can accommodate a nail N of the finger F. In this manner, the insert **910** can accommodate, i.e., receive in a secure fit manner, fingers of users with longer nails that extend beyond the distal end (i.e., the fingertip, also sometimes referred to as the distal phalange) of the user's finger.

(63) Upon insertion of the finger F into the insert **910**, the distal end DP of the finger lands and rests on the landing region **940**, and is pushed against the wall **950** by the pad **980**. By virtue of the angle $\alpha 1$ formed between the wall portions **965a**, **965b**, the knuckle/joint K of the finger lands on the wall portion **965a**, while the nail N of the finger lands on the region **965b**, resulting in a reduction or elimination of any interaction or contact between the wall portion **965a** and the nailfold region NF of the finger F. This ensures that there is little, or no pressure applied on the region NF by the wall portion **965a**, permitting blood to flow through the capillaries in the region NF, and in turn permitting imaging of the capillaries. In the absence of such angling between the wall portions **965a**, **965b**, the region NF would be compressed against the wall, resulting in blockage of flow in the capillaries of the region NF, and impeding nailfold imaging.

(64) Referring now to the angle $\alpha 2$ formed between the wall portions **965b**, **965c**, allowing an angle of 10° - 30° provides space for the lower extremity of the nail to protrude into nail space **970**.

(65) FIGS. **10A**, **10B** show a fabricated, example finger insert **1010** (e.g., structurally and/or functionally similar to the inserts **810**, **910**) with a deformable pad that includes both a base layer **1085** and spacers **1080** formed on the base layer. The base layer **1085** and the spacers **1080** here are integrally formed, of the same deformable material. The spacers **1080** are substantially conical in form. The finger insert **1010** is wholly transparent in this example, and the wall portion **1060a** is substantially frustoconical, i.e., it has a decreasing cross-section area from the opening inwards.

(66) FIGS. **11A-11C** show various views of finger inserts (e.g., structurally and/or functionally similar to any of the inserts described herein) having immersion oil disposed therein, and a fluid-tight seal at the opening. The labeling, shown in FIGS. **11A** and **11C**, can indicate unit numbers and/or a scale associated with, for example, variation in geometry of the structures of the finger insert and/or the pad, volume and/or nature of the liquid contained within, and/or the like.

(67) FIG. **12** shows a finger insert **1210** (e.g., structurally and/or functionally similar to the inserts described herein) during use with a nailfold imaging device **1205**, and with a user's finger inserted therein. A receptacle **1208** of the device **1205** can receive the insert **1210** in a mating-fit manner. The device **1205** can be configured to perform nailfold imaging of the user's finger as generally described in the '038, '221 publications.

(68) Aspects disclosed herein can be directed to kit that include multiple finger inserts (e.g., such as any finger insert described here). The finger inserts of the kit can be different from one other in any matter such as, but not limited to, a length of the housing along its longitudinal axis (e.g., along the axis A-A'), an average cross-sectional area of a curved wall portion (e.g., the wall portion **860a**), variations in the geometry and/or mechanical properties of the pad (e.g., the pad **975**). In some cases, each finger insert can have the liquid (e.g., a sterile immersion oil) already included therein, and a leak-proof covering over its opening, similar to shown in FIGS. **11A-11C**. In some cases, the kit can include the nailfold imaging device itself, such as the device **1205**, the device **1100** in FIG. **5**, and/or as generally described in the '038, '221 publications. Such an imaging device, similar to that illustrated in FIG. **5** for example can include a light source to illuminate the nailfold region through the second wall (e.g., the wall **855**), and a detector to receive the optical signal/beam from the nailfold region. The imaging device can also include a receptacle (e.g., the receptacle **1208**) sized and shaped to receive the finger inserts in any suitable mating manner. In some cases, a system can include one or more finger inserts, and a nailfold imaging device as described herein.

(69) FIG. **13** illustrates a method **1300**, such as for nailfold imaging. The method **1300** includes, at **1310**, receiving a finger of a user in a finger insert (e.g., structurally and the insert **810**, **910**, **1010**, and/or **1210**) disposed in a nailfold imaging device (e.g., the device of FIG. **5**, FIG. **12**, and/or as generally described in the '038, '221 publications). The finger insert can include a housing (e.g., the housing **820**) that defines an opening (e.g., the opening **830**) to receive a finger of a subject, and further defining a landing region (e.g., the region **840**) that abuts against a distal phalange of the finger of the subject when the finger is placed into the finger insert via the opening. The housing can hold a liquid (e.g., an immersion oil) to facilitate imaging of a nailfold of the finger of the

subject. In some cases, the method **1400** can encompass adding the liquid to the finger insert prior to step **1310**.

(70) At least the distal phalange of the finger is immersed in the liquid when the liquid is present in the finger insert and as the finger is placed into the finger insert via the opening. The housing including a first wall (e.g., the wall **850**) and a second wall (e.g., the wall **855**), the second wall being optically transparent to facilitate imaging of the nailfold of the finger. The method **1300** can also include inserting the finger insert into a receptacle of the nailfold imaging device. The nailfold imaging device includes a light source and a detector, and the receptacle includes an imaging window such that the light source and the detector are optically coupled to the imaging window.

(71) The method also includes, at step **1320**, imaging a nailfold portion of the finger via the wall portion of the finger insert using the nailfold imaging device. The imaging can include includes imaging the portion of the finger with the light source and detector via the imaging window and via the second wall of the finger insert.

(72) It is understood that while described for imaging of nailfold regions in fingers of a user, aspects disclosed herein can be useful for imaging other portions of the body such as, for example, toes of the feet. As a non-limiting example, an insert for imaging a human toe can be shaped and sized according to the considerations laid out herein, and accounting for the specific anatomy of the human toe. One such consideration could be, for example, that toes of the human feet do not splay out to the same extent that fingers do, so a toe insert will likely have to be sized to prevent excessive and painful separation between the user's toes. Another consideration can be, for example, that toes display wider variability in size than fingers, so a toe insert may need to be designed specifically for one or fewer than all toes of a user's foot.

(73) It is also understood that while described with respect to nailfold imaging, aspects disclosed herein can be useful for imaging other regions of a user's fingers outside the nailfold region (e.g., anywhere on the middle phalanx of the user's finger), other regions of a user's toes outside the nailfold region (e.g., anywhere on the middle phalanx of the user's finger or user's toe), and/or the like.

Example—Finger Positioning Study

(74) Patient's fingers can be used to perform a number of different physiological and healthcare tests, including, for example, the noninvasive measurement of a patient's white blood cell or neutrophil levels. These measurements often require or depend on stabilizing the finger for a certain period of time, and keeping it repeatedly within a predefined Region of Interest (ROI) in order to successfully carry out the measurement. Demonstrated here is how a custom, disposable “finger insert” can meet these needs. A series of studies were on a sample size of nine naive subjects to estimate the critical target ROI for such blood measurements, as well as the intra-subject and inter-subject variability in finger positioning within that ROI. The focus was on tracking one particular finger anatomical location, the nailfold, and it was confirmed that the finger insert disposable can repeatedly position within a 7 mm by 5 mm ROI for 85% of the users. These studies demonstrate that the finger insert disposable can successfully centralize the nailfold within this defined ROI, therefore allowing its imaging through an optical system designed to cover such Field Of View (FOV). Analysis of the presented data additionally shows the capacity to collect data in a range of finger locations beyond the nailfold.

Introduction

(75) The purpose of this study was to prove that an optical system with a FOV of 5 by 7 mm can consistently image the nailfold region (FIG. **14**) of a set of naive users, across a variety of finger sizes, by employing a finger insert disposable as shown and described in FIGS. **10A**, **10B**. To do this, the focus was on the variability of the nailfold geometries across a range of different subjects. Typically, the ring finger of the user's non-dominant hand is measured, both in conventional video capillaroscopy, which is employed for a wide range of clinical applications, as well as in other recent techniques to noninvasively measure white blood cells. However, this study incorporates

multiple fingers from each subject to replicate the geometric variability between fingers of a larger sample size. The goal was to prove successful imaging of nailfold ROIs across this larger sample size. Among the criteria for success was that naive users would be able to use the finger insert intuitively, that the finger can be placed comfortably into the finger insert, and that the nailfold should fall within the correct target zone or ROI for every measurement. To this end, the finger insert should guide the user's finger to the bottom extrusion within the finger insert as well as centering the finger and making the user comfortable. The knuckle of each finger measured should have minor contact with the inside face of the finger insert to stabilize the finger and avoid excessive pressure surrounding the nailfold, which could hinder blood flow and limit the ability to collect physiological and healthcare measurements from it. The ROI center should remain still to capture the measurement, so a padding in the finger insert was designed (the base layer **1085** and the spacers **1080** illustrated in FIGS. **10A**, **10B**) to secure the finger in place during the measurement with minimal vibration relative to the imaging system. The employed imaging system yields a 7 mm by 5 mm FOV, so the center of the ROI should be captured in this FOV.

(76) In summary, this study aims at: a. demonstrating an estimated range for the critical measurement ROI around a nailfold; b. demonstrating imaging of the nailfold within a defined FOV across a range of finger sizes; c. making the imaging and measurement work across all variations in finger geometry; d. demonstrating that the finger insert disposable can work in the hands of naive users.

(77) The criteria of a successful measurement considered here are: a. the finger can be placed comfortably into the finger insert b. the finger insert is intuitive to place the user's finger correctly (all the way down, touching the bottom/landing region, and centered) c. the finger insert improves the repeatability of finger placement d. the nailfold should fall within the specified ROI every time e. the finger insert padding prevents an upward force to minimize movement f. the finger knuckle is pressed up against the insert in a way that does not exert excess pressure in the nailfold region, that would in turn restrict blood flow but keeps the finger stable g. the center of the nailfold falls within a 5×7 mm ROI h. the finger stays still ± 1 mm during a measurement i. the finger insert provides for minimal vibration of the nailfold area relative to imaging system.

Methodology

(78) This study was conducted to calculate each user's average nailfold ROI based on the sample of subjects. These subjects range in gender and age from 20 to 40 years old. The subjects' index, middle, and ring finger were studied five times each in every test as a means to examine more finger size and geometry varieties. The finger insert and camera were kept in a constant location throughout every picture. Using a marker, a trained operator manually placed a dot just above the users' nailfolds to identify the nailfold ROI center where the measurement occurs (FIG. **14**). From these dot locations, the nailfold height and width were measured. Using ImageJ software, these ROI center locations were overlaid onto each other and graphed to better understand the range of finger sizes produced by the data (FIG. **15**). The finger insert of FIGS. **10A**, **10B** was tested across nine subjects.

Results

(79) Each dot on FIGS. **16**, **17** represents one data point from one finger of each subject where the ROI center falls. The maximum range of data falls between about 12 mm in the vertical direction and roughly 5 mm in the horizontal direction across all subjects.

(80) The data indicates that the finger insert condenses the nailfold ROI centers of the sample size to a range where one can take measurements with confidence. Based on measuring the center of the nailfold, it was found that each finger has roughly a 2 by 2 mm span for repeatability on the same location, as discernable from FIGS. **18**, **19**. By taking the center of the nailfold and measuring outwards until the end of the nailfold (FIG. **15**), the study found that the average width of nailfolds is 8.2 mm among the subjects. There is a minimal amount of translation in the vertical direction due to the geometry of the common nailfold.

(81) In conclusion, variability was present within the test, but the data condenses to approximately 2 mm by 1 mm (FIGS. 18, 19). Intra-subject data shows about a 4-5 mm variation in the Y-direction across the index, middle, and ring fingers (FIG. 20). The most dispersed data corresponded to the left middle finger of one particular subject, and all data points fall within 4 mm by 3 mm FoV. The largest ROI encompassing all finger positions from our data was about 9.5 mm by 5.5 mm, and the largest FoV where one could image the nailfold area was 8 mm by 6 mm (FIG. 21). By using pre-calibration, that is, by adjusting the Y position of the finger disposable beforehand to compensate for each user's finger length, we can image most nailfold areas within an 8 mm by 6 mm FoV.

CONCLUSION

(82) While various inventive embodiments have been described and illustrated herein, those of ordinary skill in the art will readily envision a variety of other means and/or structures for performing the function and/or obtaining the results and/or one or more of the advantages described herein, and each of such variations and/or modifications is deemed to be within the scope of the inventive embodiments described herein. More generally, those skilled in the art will readily appreciate that all parameters, dimensions, materials, and configurations described herein are meant to be exemplary and that the actual parameters, dimensions, materials, and/or configurations will depend upon the specific application or applications for which the inventive teachings is/are used. Those skilled in the art will recognize, or be able to ascertain using no more than routine experimentation, many equivalents to the specific inventive embodiments described herein. It is, therefore, to be understood that the foregoing embodiments are presented by way of example only and that, within the scope of the appended claims and equivalents thereto, inventive embodiments may be practiced otherwise than as specifically described and claimed. Inventive embodiments of the present disclosure are directed to each individual feature, system, article, material, kit, and/or method described herein. In addition, any combination of two or more such features, systems, articles, materials, kits, and/or methods, if such features, systems, articles, materials, kits, and/or methods are not mutually inconsistent, is included within the inventive scope of the present disclosure.

(83) Also, various inventive concepts may be embodied as one or more methods, of which an example has been provided. The acts performed as part of the method may be ordered in any suitable way. Accordingly, embodiments may be constructed in which acts are performed in an order different than illustrated, which may include performing some acts simultaneously, even though shown as sequential acts in illustrative embodiments.

(84) All publications, patent applications, patents, and other references mentioned herein are incorporated by reference in their entirety.

(85) All definitions, as defined and used herein, should be understood to control over dictionary definitions, definitions in documents incorporated by reference, and/or ordinary meanings of the defined terms.

(86) The indefinite articles “a” and “an,” as used herein in the specification and in the claims, unless clearly indicated to the contrary, should be understood to mean “at least one.”

(87) The phrase “and/or,” as used herein in the specification and in the claims, should be understood to mean “either or both” of the elements so conjoined, i.e., elements that are conjunctively present in some cases and disjunctively present in other cases. Multiple elements listed with “and/or” should be construed in the same fashion, i.e., “one or more” of the elements so conjoined. Other elements may optionally be present other than the elements specifically identified by the “and/or” clause, whether related or unrelated to those elements specifically identified. Thus, as a non-limiting example, a reference to “A and/or B”, when used in conjunction with open-ended language such as “comprising” can refer, in one embodiment, to A only (optionally including elements other than B); in another embodiment, to B only (optionally including elements other than A); in yet another embodiment, to both A and B (optionally including other elements); etc.

(88) As used herein in the specification and in the claims, “or” should be understood to have the same meaning as “and/or” as defined above. For example, when separating items in a list, “or” or “and/or” shall be interpreted as being inclusive, i.e., the inclusion of at least one, but also including more than one, of a number or list of elements, and, optionally, additional unlisted items. Only terms clearly indicated to the contrary, such as “only one of” or “exactly one of,” or, when used in the claims, “consisting of,” will refer to the inclusion of exactly one element of a number or list of elements. In general, the term “or” as used herein shall only be interpreted as indicating exclusive alternatives (i.e. “one or the other but not both”) when preceded by terms of exclusivity, such as “either,” “one of,” “only one of,” or “exactly one of.” “Consisting essentially of,” when used in the claims, shall have its ordinary meaning as used in the field of patent law.

(89) As used herein in the specification and in the claims, the phrase “at least one,” in reference to a list of one or more elements, should be understood to mean at least one element selected from any one or more of the elements in the list of elements, but not necessarily including at least one of each and every element specifically listed within the list of elements and not excluding any combinations of elements in the list of elements. This definition also allows that elements may optionally be present other than the elements specifically identified within the list of elements to which the phrase “at least one” refers, whether related or unrelated to those elements specifically identified. Thus, as a non-limiting example, “at least one of A and B” (or, equivalently, “at least one of A or B,” or, equivalently “at least one of A and/or B”) can refer, in one embodiment, to at least one, optionally including more than one, A, with no B present (and optionally including elements other than B); in another embodiment, to at least one, optionally including more than one, B, with no A present (and optionally including elements other than A); in yet another embodiment, to at least one, optionally including more than one, A, and at least one, optionally including more than one, B (and optionally including other elements); etc.

(90) In the claims, as well as in the specification above, all transitional phrases such as “comprising,” “including,” “carrying,” “having,” “containing,” “involving,” “holding,” “composed of,” and the like are to be understood to be open-ended, i.e., to mean including but not limited to. Only the transitional phrases “consisting of” and “consisting essentially of” shall be closed or semi-closed transitional phrases, respectively, as set forth in the United States Patent Office Manual of Patent Examining Procedures, Section 2111.03.

Claims

1. A finger insert for a finger imaging device, the finger insert comprising: a housing defining an opening, wherein the housing is adapted to receive a finger of a subject, the housing including: a first wall; a second wall, the second wall being optically transparent to facilitate imaging of capillaries in a nailfold of the finger by the finger imaging device when the finger insert is inserted in the finger imaging device, the second wall including a first wall portion, a second wall portion angled with respect to the first wall portion, and a third wall portion angled with respect to the first wall portion, wherein during use at least a portion of a nail of the finger is pressed against the second wall portion, the third wall portion, or both, and wherein a knuckle of the finger is pressed against the first wall portion; and a socket to abut against a distal phalange of the finger during use, the socket being curved to conform to a shape of the distal phalange of the finger; and a plurality of deformable spacers to elastically deform upon insertion of the finger into the finger insert, the plurality of deformable spacers positioned on at least a portion of the first wall to fill a gap between the first wall and the finger of the subject when the finger is inserted into the finger insert, and to press the finger towards the second wall, wherein the first wall portion, the second wall portion, and the socket are arranged such that when the distal phalange of the finger abuts against the socket and when the knuckle and nail of the finger are pressed against the second wall, contact between the nailfold of the finger and the second wall is prevented.

2. The finger insert of claim 1, wherein the socket is positioned such that the distal phalange of the finger of the subject lands on the socket as approximately centered about a longitudinal axis of the housing.

3. The finger insert of claim 1, wherein the second wall portion is angled with respect to the first wall portion by about 10 degrees to about 30 degrees.

4. The finger insert of claim 1, wherein the third wall portion is angled with respect to the second wall portion by about 10 degrees to about 30 degrees.

5. The finger insert of claim 1, wherein the housing is further configured to be fluid-tight to hold a liquid to facilitate imaging of the capillaries in the nailfold of the finger of the subject.

6. The finger insert of claim 1, wherein the housing is composed of an inelastic material.

7. The finger insert of claim 1, wherein the plurality of deformable spacers are attached to the first wall.

8. A finger insert for a finger imaging device, the finger insert comprising: a housing defining an opening adapted to receive a finger of a subject, the housing including: a first wall; a second wall, the second wall being optically transparent to facilitate imaging of capillaries in a nailfold of the finger by the finger imaging device when the finger insert is inserted in the finger imaging device, wherein during use at least a portion of a nail of the finger is pressed against the second wall and disposed in a nail space defined by the first wall and the second wall; and a landing region to abut against a distal phalange of the finger during use; and a plurality of deformable spacers positioned on at least a portion of the first wall, the plurality of deformable spacers arranged to fill a gap between the first wall and the finger of the subject when the finger is inserted into the finger insert and to press the finger towards the second wall, such that the nailfold of the finger is disposed in proximity of the second wall without contacting the second wall to facilitate imaging of the capillaries in the nailfold when at least a portion of the distal phalange of the finger abuts against the landing region and when at least the portion of the nail of the finger is pressed against the second wall.

9. The finger insert of claim 8, wherein the second wall further includes a first wall portion, a second wall portion angled with respect to the first wall portion, and a third wall portion angled with respect to the first wall portion, and wherein during use at least a portion of the nail of the finger is pressed against the second wall portion, the third wall portion, or both.

10. The finger insert of claim 9, wherein the second wall portion is angled with respect to the first wall portion by about 10 degrees to about 30 degrees towards a longitudinal axis of the housing to engage the nail of the finger.

11. The finger insert of claim 9, wherein the third wall portion is angled with respect to the second wall portion by about 10 degrees to about 30 degrees away from a longitudinal axis of the housing to at least partly define the nail space and to accommodate the nail of the finger.

12. The finger insert of claim 8, wherein the housing is further configured to be fluid-tight to hold a liquid to facilitate imaging of the capillaries in the nailfold of the finger of the subject.

13. The finger insert of claim 8, wherein the housing is composed of an inelastic material.

14. The finger insert of claim 8, wherein the plurality of deformable spacers are formed directly on the first wall.

15. A finger insert for a finger imaging device, the finger insert comprising: a housing defining an opening to receive a finger of a subject, the housing including: a first wall; a second wall, the second wall being optically transparent to facilitate imaging of capillaries in a nailfold of the finger by the finger imaging device when the finger insert is inserted in the finger imaging device, wherein during use a knuckle of the finger is pressed to abut against the second wall and be fixed in position with respect to the second wall; and a landing region comprising a curved socket to conform to a shape of a distal phalange of the finger and to abut against the distal phalange of the finger during use; and a plurality of deformable spacers positioned on at least a portion of the first wall, the plurality of deformable spacers arranged to fill a gap between the first wall and the finger

when the finger is inserted into the finger insert and to press the finger towards the second wall, such that the nailfold of the finger is disposed in proximity of the second wall without contacting the second wall to facilitate imaging of the capillaries when at least a portion of the distal phalange of the finger abuts against the landing region and when the knuckle and at least a portion of a nail of the finger are pressed to abut against the second wall and be fixed in position with respect to the second wall.

16. The finger insert of claim 15, wherein the second wall further includes a first wall portion, and a second wall portion angled with respect to the first wall portion, wherein during use the knuckle of the finger is wholly pressed against the first wall portion.

17. The finger insert of claim 16, wherein the second wall portion is angled with respect to the first wall portion by about 10 degrees to about 30 degrees towards a longitudinal axis of the housing.

18. The finger insert of claim 15, wherein the housing is further configured to be fluid-tight to hold a liquid to facilitate imaging of the capillaries in the nailfold of the finger of the subject.

19. The finger insert of claim 15, wherein the housing is composed of an inelastic material.

20. The finger insert of claim 15, further comprising a deformable pad formed on the first wall, wherein the deformable pad includes the plurality of deformable spacers formed thereon.
