

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12403009
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Kuo; Alfred

Femoral head arthroplasty system

Abstract

A femoral head arthroplasty system can comprise a femoral prosthesis comprising a mounting plate having a first side and an opposed second side. An adapter can extend from the second side of the mounting plate. An implant body can extend from the first side of the mounting plate. The implant body can extend from the mounting plate by a distance no greater than 90 mm. The femoral head arthroplasty system can further comprise a femoral head replacement having a generally spherical surface and comprising a recess that is shaped to complementarily receive the adapter of the femoral prosthesis.

Inventors: Kuo; Alfred (San Francisco, CA)

Applicant: United States Government as Represented by the Department of Veterans Affairs (Washington, DC)

Family ID: 73746439

Assignee: United States Government As Represented By The Department Of Veterans Affairs (Washington, DC)

Appl. No.: 16/899230

Filed: June 11, 2020

Prior Publication Data

Document Identifier	Publication Date
US 20200390559 A1	Dec. 17, 2020

Related U.S. Application Data

us-provisional-application US 62860549 20190612

Publication Classification

Int. Cl.: **A61F2/30** (20060101); **A61B17/00** (20060101); **A61B17/16** (20060101); **A61B90/00** (20160101); **A61F2/36** (20060101); **A61F2/40** (20060101)

U.S. Cl.:

CPC **A61F2/3609** (20130101); A61F2002/30433 (20130101); A61F2002/30784 (20130101); A61F2002/3093 (20130101); A61F2002/3611 (20130101); A61F2002/365 (20130101); A61F2310/00023 (20130101); A61F2310/00029 (20130101); A61F2310/00131 (20130101); A61F2310/00574 (20130101); A61F2310/00616 (20130101); A61F2310/00634 (20130101); A61F2310/00796 (20130101); A61F2310/0088 (20130101)

Field of Classification Search

CPC: A61F (2220/0016); A61F (2/4607); A61F (2/28); A61F (2/36); A61F (2/605); A61F (2/3609); A61F (2002/3093); A61F (2310/00131); A61F (2310/00023); A61F (2310/00029); A61F (2310/00796); A61F (2002/30433); A61F (2310/00634); A61F (2310/00574); A61F (2310/0088); A61F (2002/30784); A61F (2002/3611); A61F (2002/365); A61F (2310/00616); A61F (2310/0058); A61F (2002/30332); A61F (2002/3625); A61F (2002/3631); A61F (2002/3647); A61F (2002/3092); A61F (2310/00568); A61F (2310/00592)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3781917	12/1973	Mathys	N/A	N/A
4795473	12/1988	Grimes	623/23.11	A61B 17/746
4932974	12/1989	Pappas et al.	N/A	N/A
5112333	12/1991	Fixel	N/A	N/A
5167666	12/1991	Mattheck	N/A	N/A
5376126	12/1993	Lin	N/A	N/A
5458654	12/1994	Tepic	N/A	N/A
5571203	12/1995	Masini	623/22.46	A61F 2/3601
5601553	12/1996	Trebing	N/A	N/A
5800553	12/1997	Albrektsson	606/65	A61B 17/1721
6120544	12/1999	Grundeir	623/23.14	A61F 2/3601
6273915	12/2000	Grimes	623/23.11	A61F 2/367
6409768	12/2001	Tepic	N/A	N/A
6623486	12/2002	Weaver	N/A	N/A
6716250	12/2003	Ganjianpour	N/A	N/A
6740120	12/2003	Grimes	623/908	A61F 2/3601

6824568	12/2003	Albrektsson	623/23.15	A61F 2/3601
7063701	12/2005	Michelson	N/A	N/A
7094239	12/2005	Michelson	N/A	N/A
7137987	12/2005	Patterson	N/A	N/A
7569075	12/2008	Johnson	623/22.44	A61F 2/3601
7695502	12/2009	Orbay	N/A	N/A
7776076	12/2009	Grady, Jr.	N/A	N/A
7905909	12/2010	Orbay	N/A	N/A
7931691	12/2010	Li	N/A	N/A
7931840	12/2010	Michelson	N/A	N/A
8262707	12/2011	Huebner	N/A	N/A
8337535	12/2011	White	N/A	N/A
8388620	12/2012	Brunnarius	N/A	N/A
8398636	12/2012	Simon	N/A	N/A
8398690	12/2012	Bottlang	N/A	N/A
8403969	12/2012	Wallenstein	N/A	N/A
8470049	12/2012	Walter	623/23.15	A61F 2/3601
8496694	12/2012	Hashmi	N/A	N/A
8597334	12/2012	Mocanu	N/A	N/A
8632545	12/2013	Sarangapani	N/A	N/A
8632574	12/2013	Kortenbach	N/A	N/A
8641744	12/2013	Weaver	N/A	N/A
8734494	12/2013	Simon	N/A	N/A
8753402	12/2013	Winslow	623/22.17	A61F 2/4003
8777998	12/2013	Daniels	N/A	N/A
8840675	12/2013	Song	N/A	N/A
8845698	12/2013	Schneider	N/A	N/A
8870931	12/2013	Dahners	N/A	N/A
8906076	12/2013	Mocanu	N/A	N/A
8940029	12/2014	Leung	N/A	N/A
9005255	12/2014	Lewis	N/A	N/A
9060821	12/2014	Vennard	N/A	N/A
9066768	12/2014	Weiner	N/A	N/A
9101420	12/2014	Hansson	N/A	N/A
9211151	12/2014	Weaver	N/A	N/A
9265542	12/2015	Koay	N/A	N/A
9277947	12/2015	Koay	N/A	N/A
9295505	12/2015	Schneider	N/A	N/A
9295556	12/2015	Perez, III	N/A	A61F 2/3601
9387022	12/2015	Koay	N/A	N/A
9402728	12/2015	Liu	N/A	N/A
9427269	12/2015	Sinha	N/A	N/A
9427321	12/2015	Termanini	N/A	N/A
9468479	12/2015	Marotta	N/A	N/A
9474558	12/2015	Sixto, Jr.	N/A	N/A

9510880	12/2015	Terrill	N/A	N/A
9539040	12/2016	Vennard	N/A	N/A
9662156	12/2016	Overes	N/A	N/A
9687282	12/2016	Strnad	N/A	N/A
9687284	12/2016	Pancheco	N/A	N/A
9782208	12/2016	Martin	N/A	N/A
9867643	12/2017	Terrill	N/A	N/A
9895231	12/2017	Walter	N/A	A61F 2/3662
9931148	12/2017	Grady, Jr.	N/A	N/A
9974656	12/2017	Pappas	N/A	A61F 2/3601
9987061	12/2017	Sixto, Jr.	N/A	N/A
9999453	12/2017	Overes	N/A	N/A
10149708	12/2017	Kim	N/A	N/A
10179013	12/2018	Koay	N/A	N/A
10213236	12/2018	Lewis	N/A	N/A
10342586	12/2018	Schneider	N/A	N/A
10383668	12/2018	Rutledge	N/A	N/A
2002/0107520	12/2001	Hoffman	606/911	A61F 2/3601
2002/0111689	12/2001	Hyde, Jr.	N/A	N/A
2002/0120343	12/2001	Doubler	623/22.42	A61F 2/36
2002/0133234	12/2001	Sotereanos	623/23.26	A61F 2/3601
2004/0172138	12/2003	May	623/23.26	A61F 2/3607
2005/0197712	12/2004	Bigsby	623/23.27	A61F 2/3601
2005/0277937	12/2004	Leung	N/A	N/A
2006/0241606	12/2005	Vachtenberg	N/A	N/A
2007/0055248	12/2006	Zlowodzki	N/A	N/A
2007/0142922	12/2006	Lewis et al.	N/A	N/A
2007/0255420	12/2006	Johnson et al.	N/A	N/A
2008/0221700	12/2007	Howald et al.	N/A	N/A
2009/0118773	12/2008	James	N/A	N/A
2009/0192550	12/2008	Termanini	N/A	N/A
2009/0210067	12/2008	Meridew	N/A	N/A
2010/0168866	12/2009	Shih	N/A	N/A
2011/0288598	12/2010	Moed	N/A	N/A
2012/0004690	12/2011	Gonzalez- Hernandez	N/A	N/A
2012/0010722	12/2011	Walter	623/23.18	A61F 2/3609
2012/0203285	12/2011	Rotini	N/A	N/A
2012/0259422	12/2011	Pappas et al.	N/A	N/A
2013/0144397	12/2012	Smith et al.	N/A	N/A
2013/0158608	12/2012	Viola	N/A	N/A
2013/0204387	12/2012	Meridew et al.	N/A	N/A
2013/0261675	12/2012	Fritzinger	N/A	N/A

2013/0289630	12/2012	Fritzingner	N/A	N/A
2014/0066998	12/2013	Martin	N/A	N/A
2014/0094926	12/2013	Huff	623/23.18	A61F 2/3662
2014/0180289	12/2013	Lee	N/A	N/A
2014/0257512	12/2013	Liu	N/A	N/A
2015/0112355	12/2014	Dahners	N/A	N/A
2015/0272639	12/2014	Lewis	N/A	N/A
2016/0074081	12/2015	Weaver	N/A	N/A
2016/0331426	12/2015	Tao	N/A	N/A
2017/0095279	12/2016	Bare	N/A	N/A
2017/0181779	12/2016	Leither	N/A	N/A
2017/0319248	12/2016	Milella, Jr.	N/A	N/A
2018/0049783	12/2017	Gault	N/A	N/A
2018/0049785	12/2017	Langdale	N/A	N/A
2018/0049787	12/2017	Davison	N/A	N/A
2018/0064476	12/2017	Lopez	N/A	N/A
2018/0064477	12/2017	Lopez	N/A	N/A
2018/0064479	12/2017	Lopez	N/A	N/A
2018/0132913	12/2017	Davison	N/A	N/A
2018/0199966	12/2017	Grady, Jr.	N/A	N/A
2018/0256225	12/2017	Charkiewicz	N/A	N/A
2019/0000518	12/2018	Flint	N/A	N/A
2019/0046250	12/2018	Sylvestre	N/A	N/A
2019/0150994	12/2018	Lewis	N/A	N/A
2019/0150997	12/2018	Sixto	N/A	N/A
2019/0269445	12/2018	Singh	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2007/167660	12/2006	JP	N/A
2009/505762	12/2008	JP	N/A
WO-2005069810	12/2004	WO	A61F 2/36
WO 2006/004401	12/2005	WO	N/A
WO2010118894	12/2009	WO	N/A
WO 2013/103692	12/2012	WO	N/A
PCT			
US2020/037238	12/2019	WO	N/A

OTHER PUBLICATIONS

International Search Authority Search Report and Written Opinion for 37759.0172P1, dated Aug. 28, 2020. cited by applicant

U.S. Appl. No. 62/860,549, filed Jun. 12, 2019, Kuo. cited by applicant

Primary Examiner: Hu; Ann

Attorney, Agent or Firm: Ballard Spahr LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application claims priority to and the benefit of U.S. Provisional Patent Application No. 62/860,549, filed Jun. 12, 2019, the entirety of which is hereby incorporated by reference herein.

FIELD

(1) The disclosed invention relates to hip implants, and, more particularly, to systems for securing a femoral head replacement to the femur of a subject.

BACKGROUND

(2) Conventional hip implants are inserted into the femur about five to six inches. The use of such conventional hip implants requires removal of a significant quantity of a patient's bone, which can be undesirable. There is a need for hip implant systems that eliminate the need for removal of such significant quantities of bone.

SUMMARY

(3) Described herein, in various aspects, is a femoral head arthroplasty system. The femoral head arthroplasty system can comprise a femoral prosthesis. The femoral prosthesis can comprise a mounting plate having a first side and an opposed second side, an adapter extending from the second side of the mounting plate, and an implant body extending from the first side of the mounting plate. The implant body can extend from the mounting plate by a distance no greater than 90 mm. A femoral head replacement can have a generally spherical surface and can comprise a recess that is shaped to complementarily receive the adapter of the femoral prosthesis.

(4) A femoral head arthroplasty system can comprise a femoral prosthesis. The femoral prosthesis can comprise a mounting plate having a first side and an opposed second side, an adapter extending from the second side of the mounting plate, and an implant body extending from the first side of the mounting plate, wherein a distal end of the implant body has a planar face that is generally parallel to the mounting plate. A femoral head replacement can have a generally spherical surface and can comprise a recess that is shaped to complementarily receive the adapter of the femoral prosthesis.

(5) A femoral head arthroplasty system can comprise a femoral prosthesis. The femoral prosthesis can comprise a mounting plate having a first side and an opposed second side. An implant body can extend from the first side of the mounting plate. The implant body can extend from the mounting plate by a distance no greater than 90 mm. The mounting plate and the implant body can cooperate to define a recess. A femoral head replacement can have a generally spherical portion and an adapter extending distally from the generally spherical portion. The adapter can be configured for complementary receipt within the recess of the femoral prosthesis.

(6) The implant body can comprise at least one radially extending spline.

(7) The implant body can comprise a plurality of radially extending splines.

(8) The implant body can comprise a generally cylindrical portion.

(9) The implant body can define a hemi-cylindrical surface.

(10) The implant body can comprise mounting hardware. The mounting plate can define at least one opening configured to receive the mounting hardware.

(11) The mounting hardware can comprise at least one screw.

(12) The femoral prosthesis can comprise a porous or textured metal.

(13) The porous or textured metal can be at least one metal selected from the group consisting of cobalt chromium, titanium, and tantalum.

(14) The femoral prosthesis can comprise a coating.

(15) The coating can be one selected from the group consisting of hydroxyapatite, titanium oxide, titanium nitride, zirconium oxide, and pyrolytic carbon.

- (16) The coating can be configured to promote ingrowth or on-growth of bone.
- (17) The diameter of at least a portion of the implant body can range from about 10 mm to about 18 mm.
- (18) The implant body can have a variable outer diameter.
- (19) The adapter can have a Morse taper.
- (20) The femoral head replacement can be angularly offset from the femoral prosthesis.
- (21) A method can comprise: forming a prepared site within a femur; and implanting a femoral head arthroplasty system such that the implant body is received within the prepared site, wherein the prepared site extends no more than 30 mm distal to the lesser trochanter of the femur.
- (22) The mounting plate can have a major dimension that is greater than or equal to a major radial dimension of the femur. The mounting plate can abut cortical bone at a cut proximal end of the femur.
- (23) A kit can comprise: a femoral prosthesis comprising: a mounting plate having a first side and an opposed second side, an adapter extending from the second side of the mounting plate, and an implant body extending from the first side of the mounting plate, wherein the implant body extends from the mounting plate by a distance no greater than 90 mm. The kit can further comprise a plurality of femoral head replacements, each femoral head replacement having a generally spherical surface and comprising a recess that is shaped to complementarily receive the adapter of the femoral prosthesis, wherein each femoral head replacement of the plurality of femoral head replacements differs from every other femoral head replacement of the plurality of femoral head replacements in size or material.
- (24) Additional advantages of the invention will be set forth in part in the description that follows, and in part will be obvious from the description, or may be learned by practice of the invention. The advantages of the invention will be realized and attained by means of the elements and combinations particularly pointed out in the appended claims. It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory only and are not restrictive of the invention, as claimed.
-

Description

DESCRIPTION OF THE DRAWINGS

- (1) These and other features of the preferred embodiments of the invention will become more apparent in the detailed description in which reference is made to the appended drawings wherein:
- (2) FIG. 1 is a side view of a femoral prosthesis of a femoral head arthroplasty system, in accordance with embodiments disclosed herein.
- (3) FIG. 2 is the side view of the femoral prosthesis of FIG. 1 with dimensions for one exemplary embodiment.
- (4) FIG. 3 is a front view of the femoral prosthesis of FIG. 1.
- (5) FIG. 4 is the front view of the femoral prosthesis of FIG. 3 with dimensions for one exemplary embodiment.
- (6) FIG. 5 is a rear view of the femoral prosthesis of FIG. 1.
- (7) FIG. 6 is the rear view of the femoral prosthesis of FIG. 5 with dimensions for one exemplary embodiment.
- (8) FIG. 7 is a side view of a femoral head replacement of the femoral head arthroplasty system for use with the femoral prosthesis of FIG. 1.
- (9) FIG. 8 is a side view of another embodiment of a femoral head arthroplasty system.
- (10) FIG. 9 is a partial cutaway view of a femoral head arthroplasty system installed in a femur.
- (11) FIG. 10 is a rear perspective view of an exemplary femoral prosthesis in accordance with embodiments disclosed herein.

- (12) FIG. 11 is a front perspective view of the exemplary femoral prosthesis of FIG. 10.
- (13) FIG. 12 is a front view of the exemplary femoral prosthesis of FIG. 10.
- (14) FIG. 13 is a top view of the exemplary femoral prosthesis of FIG. 10.
- (15) FIG. 14 is a side view of the exemplary femoral prosthesis of FIG. 10.
- (16) FIG. 15 is a perspective view of an exemplary femoral prosthesis in accordance with embodiments disclosed herein.
- (17) FIG. 16 is a cross sectional view of the exemplary femoral prosthesis of FIG. 15.
- (18) FIG. 17 is a side view of a fixation screw for use with the femoral prosthesis.
- (19) FIG. 18 is a first end view of the fixation screw of FIG. 17.
- (20) FIG. 19 is a cross sectional view of the screw taken in the plane A-A of FIG. 18.
- (21) FIG. 20 is a detail view of the cross sectional view of the screw in FIG. 19 within the circle B.
- (22) FIG. 21 is a detail view of the cross sectional view of the screw in FIG. 19 within the circle C.
- (23) FIG. 22 is a second end view of the fixation screw of FIG. 17.

(24) It should be understood that any dimensions or other measurements indicated within the figures are merely exemplary and that other dimensions and measurements are contemplated.

DETAILED DESCRIPTION

- (25) The present invention now will be described more fully hereinafter with reference to the accompanying drawings, in which some, but not all embodiments of the invention, are shown. Indeed, this invention may be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will satisfy applicable legal requirements. Like numbers refer to like elements throughout. It is to be understood that this invention is not limited to the particular methodology and protocols described, as such may vary. It is also to be understood that the terminology used herein is for the purpose of describing particular embodiments only, and is not intended to limit the scope of the present invention.
- (26) Many modifications and other embodiments of the invention set forth herein will come to mind to one skilled in the art to which the invention pertains having the benefit of the teachings presented in the foregoing description and the associated drawings. Therefore, it is to be understood that the invention is not to be limited to the specific embodiments disclosed and that modifications and other embodiments are intended to be included within the scope of the appended claims. Although specific terms are employed herein, they are used in a generic and descriptive sense only and not for purposes of limitation.
- (27) As used herein the singular forms “a,” “an,” and “the” include plural referents unless the context clearly dictates otherwise. For example, use of the term “a screw” can refer to one or more of such screws, and so forth.
- (28) All technical and scientific terms used herein have the same meaning as commonly understood to one of ordinary skill in the art to which this invention belongs unless clearly indicated otherwise.
- (29) As used herein, the terms “optional” or “optionally” mean that the subsequently described event or circumstance may or may not occur, and that the description includes instances where said event or circumstance occurs and instances where it does not.
- (30) As used herein, the term “at least one of” is intended to be synonymous with “one or more of” For example, “at least one of A, B and C” explicitly includes only A, only B, only C, and combinations of each.
- (31) The word “or” as used herein means any one member of a particular list and also includes any combination of members of that list.
- (32) Ranges can be expressed herein as from “about” one particular value, and/or to “about” another particular value. When such a range is expressed, another aspect includes from the one particular value and/or to the other particular value. Similarly, when values are expressed as approximations, by use of the antecedent “about,” it will be understood that the particular value forms another aspect. It will be further understood that the endpoints of each of the ranges are

significant both in relation to the other endpoint, and independently of the other endpoint. Optionally, in some aspects, when values are approximated by use of the antecedent “about,” it is contemplated that values within up to 15%, up to 10%, up to 5%, or up to 1% (above or below) of the particularly stated value can be included within the scope of those aspects. Similarly, in some aspects, when values or characteristics are approximated by the use of the antecedent “approximately,” “generally,” or “substantially,” it is contemplated that values within up to 15%, up to 10%, up to 5%, or up to 1% (above or below) of the particularly stated value or characteristic can be included within the scope of those aspects.

(33) As used herein, the term “patient” can refer to a human or an animal that receives an implant as further disclosed herein. In exemplary aspects, a patient can be a human who has been determined to be in need of receiving an implant as disclosed herein.

(34) It is to be understood that unless otherwise expressly stated, it is in no way intended that any method set forth herein be construed as requiring that its steps be performed in a specific order. Accordingly, where a method claim does not actually recite an order to be followed by its steps or it is not otherwise specifically stated in the claims or descriptions that the steps are to be limited to a specific order, it is in no way intended that an order be inferred, in any respect. This holds for any possible non-express basis for interpretation, including: matters of logic with respect to arrangement of steps or operational flow; plain meaning derived from grammatical organization or punctuation; and the number or type of aspects described in the specification.

(35) The following description supplies specific details in order to provide a thorough understanding. Nevertheless, the skilled artisan would understand that the apparatus, system, and associated methods of using the apparatus can be implemented and used without employing these specific details. Indeed, the apparatus, system, and associated methods can be placed into practice by modifying the illustrated apparatus, system, and associated methods and can be used in conjunction with any other apparatus and techniques conventionally used in the industry.

(36) Disclosed herein, in various aspects and with reference to FIG. 1, is a femoral prosthesis **100** of a femoral head arthroplasty system. The femoral prosthesis **100** can comprise a mounting plate **110** having a first side **112** and an opposing second side **114**. The first side **112** of the mounting plate **110** can have a planar or substantially planar profile, and the mounting plate **110** can have a thickness **502** between about three and about seven millimeters (e.g., about five millimeters) in a first dimension (measured along a first axis **302**) that is perpendicular to the first side's planar or substantially planar surface. Within the planar or substantially planar surface of the first side **112**, the mounting plate **110** can extend about twenty-five to about forty millimeters (e.g., about thirty-four millimeters) in a second dimension (measured along a second axis **304**) and a length **504** of about sixteen to about twenty five millimeters (e.g., about twenty-two millimeters) in a third dimension (measured along a third axis **306**). The femoral prosthesis's mounting plate **110** can have a major dimension that is greater than the major radial dimension of the patient's femur so that, when implanted within the femur, the mounting plate abuts the femur's outer radial wall. A pair of top corners can define a radius **r1** (optionally, of about two millimeters), and a bottom of the mounting plate **110** can define a continuous arcuate profile (optionally, having a radius of eleven millimeters, or about half of the width of the mounting plate measured along the third axis **306**).

(37) The mounting plate **110** can define one or more through-holes **120** (e.g., a pair, as shown) that can receive mounting hardware for attaching the femoral prosthesis to a patient. The holes **122** can have respective diameters **d5** (optionally, a diameter ranging from about 4 millimeters to about 10 millimeters, or more preferably, being about seven millimeters). In some aspects, the holes **122** can be spaced from respective side edges of the mounting plate by distances **526** (e.g., at least one millimeter, between one and 4 millimeters, or, more preferably, about two millimeters). The pair of through holes **120** can optionally define female threads **122** therein for receiving male threads of mounting screws (see also FIGS. 15 and 16). In some optional aspects, the pair of through holes **120** can be centered along the third axis **306** so that the femoral prosthesis is symmetrical about a

plane that extends in the first and third dimensions (containing axes **302**, **306**) and bisects the femoral prosthesis **100**. Although embodiments described herein comprise features for attachment via screws, in further embodiments, other attachment means, such as wires, sutures, or cables, may be used.

(38) An implant body **130** can extend from the first side **112** of the mounting plate **110**. The implant body **130** can be disposed below (i.e., offset in the second dimension (along second axis **304**) from) the pair of through-holes **120**. The implant body **130** can comprise a first cylindrical or generally cylindrical protrusion **132** that extends perpendicularly to the face of the mounting plate's first side **112**. The first generally cylindrical protrusion **132** can extend less than ninety and greater than twenty millimeters, and optionally less than seventy-five and greater than thirty millimeters or between thirty-five and sixty millimeters, (e.g., about forty millimeters or about forty-five millimeters) from the first side **112** of the mounting plate along a first axis **134**. The first generally cylindrical protrusion **132** can optionally have a diameter d_1 between about ten and about eighteen millimeters (e.g., about fourteen millimeters). A distal end of the first generally cylindrical protrusion **132** (i.e., the end farthest away from the mounting plate **110**) can have an arcuate edge **136** that extends a length **512** in the first dimension **302** ranging from about three millimeters to about eight millimeters, or more preferably, being about five millimeters. The distal end of the first generally cylindrical protrusion **132** can optionally have a planar face **138** that is generally parallel to the mounting plate. The first generally cylindrical protrusion **132** can be spaced from the bottom of the mounting plate **110**, for example by about two millimeters. The first axis **134** of the first generally cylindrical protrusion **132** can optionally be spaced from the bottom of the mounting plate by a distance **530** (e.g., optionally, from about seven millimeters to about 12 millimeters, or about nine millimeters). In some optional aspects, the first generally cylindrical protrusion **132** can be spaced from the lower end of the mounting plate by a distance **506** (e.g., optionally, from about one millimeter to about four millimeters, or about two millimeters).

(39) The implant body **130** can further comprise a second cylindrical or generally cylindrical protrusion **150** that extends along a second axis **152** that is parallel to the first axis **134**. The second axis **152** can optionally be directly vertically above the first axis **134**. The second generally cylindrical portion **150** can extend a length **508** about ten to about forty millimeters (e.g., from about ten millimeters to about twenty millimeters, or about fifteen millimeters) from the first side **112** of the mounting plate **110**. The second generally cylindrical portion **150** can therefore have an end opposite the mounting plate **110** that is a length **516** (e.g., from about 25 millimeters to about 35 millimeters, or about thirty millimeters) from the end of the first generally cylindrical portion **130** opposite the mounting plate. The first and second axes **134**, **152** can be spaced by less than the sum of the respective radii of the first and second generally cylindrical portions so that the second generally cylindrical protrusion **150** overlaps the first generally cylindrical protrusion **132**. Accordingly, in a cross sectional plane perpendicular to the first axis **134**, the overlapping first and second generally cylindrical protrusions **132**, **150** can have a figure-eight shape. Optionally, the second axis **152** can extend along a top edge of the first generally cylindrical protrusion **132**. The second axis **152** can be spaced from the top of the mounting plate by a distance **532** (e.g., optionally, from about 15 millimeters to about 20 millimeters, or about eighteen millimeters) and can be spaced from the bottom of the mounting plate by a distance **534** (e.g., optionally, from about 13 millimeters to about 18 millimeters, or about sixteen millimeters). That is, the second axis **152** can be spaced from the first axis by the radius of the first generally cylindrical protrusion **132**. The second generally cylindrical protrusion **150** can have a radius r_3 of about five to about nine millimeters (e.g., about seven millimeters). The first and second generally cylindrical protrusions **132**, **150** can cooperate to provide an oblong cross section so that the implant body **130** is inhibited from rotation. Moreover, the combined cross sectional shape of the first and second generally cylindrical protrusions (e.g., a figure-eight shape) can cooperate with a bone preparation site that is easily prepared by a surgeon. In further embodiments, the implant body **130** can have various other

cross sectional profiles in planes perpendicular to the implant body's longitudinal dimension, including a generally cylindrical profile, an oval profile, a polygonal profile (e.g., a square or rectangular profile), or an oblong profile.

(40) Optionally, the implant body **130** can extend from the mounting plate by a distance of no greater than ninety millimeters, or no greater than seventy-five millimeters, or no greater than sixty millimeters, or no greater than fifty millimeters, or no greater than forty-five millimeters. As further disclosed herein, it is contemplated that the minimal length of the implant body **130** can reduce the amount of native bone of a subject that must be removed to accommodate the implant body.

(41) An adapter **160** can extend from, and be oriented perpendicularly or substantially perpendicularly to, the second side **114** of the mounting plate **110**. The adapter **160** can optionally have a central axis **161** that is collinear with the second axis **152**. Accordingly, the adapter **160** can be superiorly axially offset from (i.e. above) the axis **134** of the first generally cylindrical protrusion **132**. In this way, for some patients, a femoral head attached to the adapter **160** can most accurately recreate the patient's normal anatomy. In further embodiments, the adapter can have an axis offset from the axis **152**. Optionally, in some such embodiments, the adapter **160** can be axially aligned with the axis **134**. The adapter **160** can comprise a frustoconical portion **162** that attaches, via a neck portion **164**, to the mounting plate **110**. The neck portion can have a length **514** of from about three millimeters to about seven millimeters, or of about five millimeters. The frustoconical portion **162** can taper from a proximal end **166** to a distal end **168** (moving away from the mounting plate **110**). The frustoconical portion **162** can optionally have a Morse taper. The proximal end **166** can optionally have a diameter d_2 of about twelve to about sixteen millimeters (e.g., about fourteen millimeters), and the distal end **168** can optionally have a diameter d_3 of about ten millimeters to about fourteen millimeters (e.g., about twelve millimeters). The frustoconical portion **162** can extend axially a length **510** of about ten to about eighteen millimeters (e.g., about fourteen millimeters) from the proximal end **166** to the distal end **168**. In some aspects, the adapter's central axis can be spaced from the top of the mounting plate by a length **520** (optionally, from about 15 millimeters to about 20 millimeters, or about eighteen millimeters) and spaced from the bottom of the mounting plate by a length **522** (optionally, from about 13 millimeters to about 18 millimeters, or of sixteen millimeters). The adapter's radial-most surface can be spaced from the respective opposing side edges of the mounting plate in the third dimension **306** by a distance **524** (optionally, from about three millimeters to about six millimeters, or of about four millimeters). Optionally, at least a portion of the frustoconical portion's circumferential surface can comprise a texture. Said texture can improve frictional engagement between the adapter **160** and the femoral head replacement. In some optional aspects, a helical groove having a pitch of 0.5 millimeters can define said texture.

(42) The neck portion **164** of the adapter **160** can have a cross section that varies along its axis in an arcuate profile. At a halfway point along its axis, the neck portion **164** can have a minimum diameter d_4 , which, in some embodiments, can be about twelve millimeters. Opposing ends of the neck portion **164** can each have a diameter d_2 of about fourteen millimeters. Accordingly, the minimum diameter can be about two millimeters less than the maximum diameter of the neck portion **154**. The neck portion's narrowing diameter can provide a location to grip the femoral prosthesis during implantation and removal of the femoral prosthesis.

(43) Although shown extending parallel to the implant body **130**, in further embodiments, the adapter **160** can extend at various angles with respect to the implant body **130** in order to vary the varus/valgus angle of the femoral head with respect to the longitudinal dimension of the femur.

(44) Referring to FIG. 7, the adapter **160** can receive a femoral head replacement **200**. The femoral head replacement **200** can have a shape that cooperates with a hip socket of the patient's pelvis or an artificial hip socket. In some embodiments, the femoral head replacement **200** can have the shape of a natural femoral head. The femoral head replacement **200** can have a generally spherical profile. The femoral head replacement **200** can define a recess **210**. The recess **210** can have a

complementary shape to the adapter **160** (FIG. 1) of the femoral prosthesis **100** (FIG. 1). For example, the recess **210** can have a frustoconical profile. The prosthesis **200** can optionally be a conventional component known to those skilled in the art.

(45) The femoral prosthesis **100** can couple to the femoral head replacement **200** to create a femoral head arthroplasty system **250**. In some embodiments, the femoral prosthesis **100** and the femoral head replacement **200** can couple permanently, while in further embodiments, the pair can couple via a non-permanent means. The adapter **160** and femoral head replacement **200** can have an interference fit (e.g., via a Morse taper) so that the respective components frictionally engage each other. As stated above, at least one of the adapter **160** and the femoral head replacement **200** can optionally have a texture (i.e., surface texture) to improve the engagement between the respective components.

(46) Referring to FIG. 8, in further embodiments, a femoral head replacement **200'** can comprise a generally spherical portion **202'** and an adapter **160'** that extends distally from the generally spherical portion **202'**. A femoral prosthesis **100'** can comprise a recess **210'** and can otherwise have the same shape and dimensions as that of the femoral prosthesis **100** (FIG. 1). Although shown as a frustoconical protrusion, the adapter **160'** and recess **210'** can have profiles similar to that of the adapter **160** (FIG. 1) and the recess **210** (FIG. 7), respectively, or any other adapter profile known to those skilled in the art.

(47) In some embodiments, the femoral prosthesis can comprise at least one radially extending spline **180** or, as shown, a plurality of radially extending splines **180**. The radially extending spline(s) **180** can provide surfaces against which bone can grow as well as inhibit rotation of the femoral prosthesis about its axis of elongation.

(48) The femoral prosthesis **100** and/or the femoral head replacement **200** can comprise various materials known to those skilled in the art, such as, for example, porous, coated titanium, ceramics, tantalum, cobalt chromium alloy, or various other porous metals. The material(s) can be porous or textured in order to allow bone in-growth or on-growth. The material(s) can be strong enough to bear the weight of the patient without fracturing.

(49) The femoral prosthesis **100** and/or the femoral head replacement **200** can comprise a coating. Said coating can comprise one or more of the following: hydroxyapatite, titanium oxide, titanium nitride, zirconium oxide, and pyrolytic carbon. In further embodiments, the coating can comprise gold, ceramics, polymers (e.g., ultra-high molecular weight polyethylene), diamond-like carbon (DLC) coatings, oxidized zirconium, titanium nitride or various other coatings known to those skilled in the art. The coating(s) can optionally be low friction and can optionally be hydrophobic.

(50) Referring to FIGS. 10-14, in some aspects, the implant body **130** of the prosthesis **100** can have an elongate profile in the second dimension (along the second axis **304**). That is, in cross sections perpendicular to the first axis **302**, the implant body **130** can have a major dimension measured along the second axis **304** and a minor dimension measured along the third axis **306**. For example, the implant body **130** can define two hemi-cylindrical surfaces **190** that are spaced along the second axis **304** and connected via planar faces **192**. This or another non-axially symmetric profile can inhibit rotation of the implant body relative to the femur. In some aspects, the implant body can have a major dimension of between 18 and 25 millimeters (e.g., about 21 millimeters) measured along the second axis **304** and a minor dimension of between 12 and 18 (e.g., about 14 millimeters) measured along the third axis **306**.

(51) In some optional aspects, the centerline **194** of the implant body (i.e., the line extending through the centroid of the cross sections in planes perpendicular to the first dimension (first axis **302**)) can be collinear with the central axis **161** of the adapter **160**. In further optional aspects, as shown in FIGS. 15 and 16, the centerline **194** can be offset from the central axis **161** of the adapter **160** (optionally, offset from the central axis **161** in the second dimension (relative to the second axis **304**)).

(52) In some optional aspects, the distal end of the implant body **130** can optionally have a planar

face **138** that is parallel or generally parallel to the mounting plate. In further aspects, it is contemplated that the distal end of the implant body can define a rounded, oblong surface **139** or other non-planar surface that extends parallel to the mounting plate. For example, the implant body **130** can define first and second radii **141** (optionally, spherical surfaces) that are spaced relative to each other along the second dimension **304** (and that are measured in a plane containing the first and second axes).

(53) In some aspects, the centerline **194** of the implant body can extend perpendicularly to the mounting plate **110** along an entire length of the implant body. For example, within any plane that intersects the implant body and is perpendicular to the first axis **302**, a center point (which can optionally correspond to a center of mass) of the portion of the implant body within the plane will be intersected by the centerline **194**. In further aspects, it is contemplated that the apparatus can be symmetric about a plane that is perpendicular to the second dimension **304** and bisects the implant body (and, therefore, includes the centerline **194**). Optionally, in still further aspects, it is contemplated that the implant body can be symmetric about both (a) a first plane that is perpendicular to the second dimension **304** and bisects the implant body; and (b) a second plane that is perpendicular to the third dimension **306** and bisects the implant body. It is contemplated that the above-described configurations, by avoiding the need for providing an angled or asymmetric implant body (for example, as might be necessary to permit deeper advancement of an implant body within a native bone), can provide advantageous balance and force transmission properties while minimizing the amount of bone that is removed from the patient to accommodate the implant body.

(54) Referring to FIGS. **10-14**, it is further contemplated that in some aspects, the neck portion **164** can have a constant diameter (instead of the narrowing diameter as depicted in FIG. **1**) to increase the strength of the prosthesis.

(55) Referring to FIGS. **17-22**, a fixation screw **240** can have a head **241** defining a first thread (or plurality of threads) **242** and a body **243** defining a second thread (or plurality of threads) **244**. Optionally, the head of the screw can define a taper. Accordingly, the hole **120** (FIG. **16**) can define a corresponding taper. The fixation screw can comprise one or more (e.g., optionally, three equally circumferentially spaced) self-tapping features **246** for tapping the bone during insertion of the screw. The fixation screw can further comprise one or more (e.g., optionally, three equally circumferentially spaced) self-tapping features **247** for tapping the bone during removal of the screw. It should be understood that the dimensions (in millimeters) provided in the figures should be understood to be optional aspects.

(56) It is further contemplated that the prosthesis can be fixated to the femur, additionally or alternatively, with bone ingrowth and/or ongrowth and/or cemented fixation.

(57) A kit can comprise a femoral prosthesis **100** and a plurality of femoral head replacements **200**. Each of femoral head replacements **200** can differ from the others in at least one of size or material.

(58) Referring to FIG. **9**, a medical professional (e.g., an orthopedic surgeon) can form a prepared site within a femur **400**. For example, the medical professional can cut off a portion of the patient's natural femoral head. Optionally, the surgeon can use a patient-specific cutting guide that locates the optimal location and angle for removing the femoral head. According to one embodiment, the cutting guide can comprise a frame that defines a slot for guiding a cutting saw. The cutting guide can temporarily be fastened to the femur using pins or screws and subsequently be removed from the femur after cutting. The surgeon can drill/ream a pair of overlapping holes to receive the first and second cylindrical portions **132**, **150**. In further aspects, the overlapping holes can further be bored to provide an opening to receive the implant body **130** (e.g., for the embodiments shown in FIGS. **10-14**). The prepared site can be positioned further proximally along the neck of the femur (toward the original femoral head) than prepared sites of conventional femoral prostheses for hip replacement. The prepared site can optionally extend no more than thirty millimeters distal to the lesser trochanter **402** of the femur **400** (i.e., past the lesser trochanter along femoral shaft's

longitudinal axis in the direction toward the patient's foot). The medical professional can then implant the femoral prosthesis so that the implant body is received within the prepared site. The femoral prosthesis can be inserted so that the mounting plate abuts a superior end of the femur. The medical professional can drill holes in the patient's bone for receiving the screws or other fasteners. Screws **240** or other fasteners can be used to secure the femoral prosthesis in place. Optionally, the surgeon can drill holes into the femur to receive screws **240**. The femoral head replacement can then be attached to the femoral prosthesis.

(59) Compared to conventional implants, embodiments disclosed herein can enable hip implants that require less bone removal. That is, a shorter segment of bone can be removed, leaving a portion of the femoral neck through which the femoral prosthesis can extend. The disclosed embodiments can reduce blood loss during surgery and enable easier insertion for the surgeon, particularly in cases of anterior approach surgery. The disclosed embodiments can be associated with smaller incisions than conventional implants and can provide for easier re-do surgery if need arises.

EXEMPLARY ASPECTS

(60) In view of the described products, systems, and methods and variations thereof, herein below are described certain more particularly described aspects of the invention. These particularly recited aspects should not however be interpreted to have any limiting effect on any different claims containing different or more general teachings described herein, or that the “particular” aspects are somehow limited in some way other than the inherent meanings of the language literally used therein.

(61) Aspect 1: A femoral head arthroplasty system comprising: a femoral prosthesis comprising: a mounting plate having a first side and an opposed second side, an adapter extending from the second side of the mounting plate, and an implant body extending from the first side of the mounting plate, wherein the implant body extends from the mounting plate by a distance no greater than 90 mm; and a femoral head replacement having a generally spherical surface and comprising a recess that is shaped to complementarily receive the adapter of the femoral prosthesis.

(62) Aspect 2: A femoral head arthroplasty system comprising: a femoral prosthesis comprising: a mounting plate having a first side and an opposed second side, an adapter extending from the second side of the mounting plate, an implant body extending from the first side of the mounting plate, wherein the implant body has a distal end, wherein the distal end of the body defines a surface that extends generally parallel to the mounting plate; and a femoral head replacement comprising a recess that is shaped to complementarily receive the adapter of the femoral prosthesis.

(63) Aspect 3: A femoral head arthroplasty system comprising: a femoral prosthesis comprising: a mounting plate having a first side and an opposed second side; and an implant body extending from the first side of the mounting plate, wherein the implant body extends from the mounting plate by a distance no greater than 90 mm, wherein the mounting plate and the implant body cooperate to define a recess; and a femoral head replacement having a generally spherical portion and an adapter extending distally from the generally spherical portion, wherein the adapter is configured for complementary receipt within the recess of the femoral prosthesis.

(64) Aspect 4: The femoral head arthroplasty system of aspects 1-3, wherein the implant body comprises at least one radially extending spline.

(65) Aspect 5: The femoral head arthroplasty system of aspect 4, wherein the implant body comprises a plurality of radially extending splines.

(66) Aspect 6: The femoral head arthroplasty system of any of aspect 1-3, wherein the implant body defines a generally hemicylindrical surface.

(67) Aspect 7: The femoral head arthroplasty system of any of aspect 1-3, further comprising mounting hardware, and wherein the mounting plate defines at least one opening configured to receive the mounting hardware.

(68) Aspect 8: The femoral head arthroplasty system of aspect 7, wherein the mounting hardware

comprises at least one screw.

(69) Aspect 9: The femoral head arthroplasty system of any of aspect 1-3, wherein the femoral prosthesis comprises a porous or textured metal.

(70) Aspect 10: The femoral head arthroplasty system of aspect 9, wherein the porous or textured metal is at least one metal selected from the group consisting of cobalt chromium, titanium, and tantalum.

(71) Aspect 11: The femoral head arthroplasty system of any of aspect 1-3, wherein the femoral prosthesis comprises a coating.

(72) Aspect 12: The femoral head arthroplasty system of aspect 11, wherein the coating is one selected from the group consisting of hydroxyapatite, titanium oxide, titanium nitride, zirconium oxide, and pyrolytic carbon.

(73) Aspect 13: The femoral head arthroplasty system of aspect 11, wherein the coating is configured to promote ingrowth or on-growth of bone.

(74) Aspect 14: The femoral head arthroplasty system of any of aspect 1-3, wherein the diameter of at least a portion of the implant body ranges from about 10 mm to about 18 mm.

(75) Aspect 15: The femoral head arthroplasty system of any of aspect 1-3, wherein the implant body has a variable outer diameter.

(76) Aspect 16: The femoral head arthroplasty system of any of aspect 1-2, wherein the adapter has a Morse taper.

(77) Aspect 17: The femoral head arthroplasty system of any of aspect 1-2, wherein the femoral head replacement is angularly offset from the femoral prosthesis.

(78) Aspect 18: A method comprising: forming a prepared site within a femur; and implanting a femoral head arthroplasty system according to any one of aspect 1-17 such that the implant body is received within the prepared site, wherein the prepared site extends no more than 30 mm distal to the lesser trochanter of the femur.

(79) Aspect 19: The method of aspect 18, wherein the mounting plate has a major dimension that is greater than or equal to a major radial dimension of the femur, and wherein the mounting plate abuts cortical bone at a cut proximal end of the femur.

(80) Aspect 20: A kit comprising: a femoral prosthesis comprising: a mounting plate having a first side and an opposed second side, an adapter extending from the second side of the mounting plate, and an implant body extending from the first side of the mounting plate, wherein the implant body extends from the mounting plate by a distance no greater than 90 mm; and a plurality of femoral head replacements, each femoral head replacement having a generally spherical surface and comprising a recess that is shaped to complementarily receive the adapter of the femoral prosthesis, wherein each femoral head replacement of the plurality of femoral head replacements differs from every other femoral head replacement of the plurality of femoral head replacements in size or material.

(81) Although the foregoing invention has been described in some detail by way of illustration and example for purposes of clarity of understanding, certain changes and modifications may be practiced within the scope of the appended claims.

Claims

1. A femoral head arthroplasty system comprising: a femoral prosthesis comprising: a mounting plate having a first side and an opposed second side, wherein the first side of the mounting plate is configured to abut a cut surface of the femur, and an implant body extending from the first side of the mounting plate, wherein the implant body extends perpendicularly from the first side of the mounting plate along a first axis by a distance no greater than 90 mm, wherein, in cross section in a plane that is perpendicular to the first axis, the implant body has a major cross sectional dimension along a second axis and a minor cross sectional dimension along a third axis that is different than

the second axis, wherein the minor cross sectional dimension is less than the major cross sectional dimension, wherein the implant body is oblong in cross section in the plane that is perpendicular to the first axis, wherein the implant body has a distal end, wherein the implant body defines a continuous, uninterrupted circumferential surface extending from the mounting plate to the distal end, wherein the continuous, uninterrupted circumferential surface comprises two hemi-cylindrical surfaces having respective lengths, the two hemi-cylindrical surfaces being spaced along the second axis, and two parallel planar faces that are spaced along the third axis and extend between and to the two hemi-cylindrical surfaces along a respective entirety of each of the lengths of the two hemi-cylindrical surfaces, and wherein the implant body has a centerline that extends parallel to or is collinear with the first axis along an entire length of the implant body; and a femoral head replacement having a generally spherical surface, wherein one of the femoral prosthesis and the femoral head comprises an adapter, and wherein the other of the femoral prosthesis and the femoral head defines a recess that is complementarily shaped to receive the adapter.

2. The femoral head arthroplasty system of claim 1, wherein the femoral prosthesis comprises the adapter, wherein the adapter extends from the second side of the mounting plate.

3. The femoral head arthroplasty system of claim 1, further comprising mounting hardware, and wherein the mounting plate defines at least one opening configured to receive the mounting hardware.

4. The femoral head arthroplasty system of claim 3, wherein the mounting hardware comprises at least one screw.

5. The femoral head arthroplasty system of claim 4, wherein the at least one screw comprises a head and a body, wherein the head of the at least one screw defines a first thread, wherein the body of the at least one screw defines a second thread, wherein the mounting plate defines a threaded hole that is configured for complimentary receipt of the first thread of the head of the at least one screw.

6. The femoral head arthroplasty system of claim 1, wherein the femoral prosthesis comprises a porous or textured metal.

7. The femoral head arthroplasty system of claim 6, wherein the porous or textured metal is at least one metal selected from the group consisting of cobalt chromium, titanium, and tantalum.

8. The femoral head arthroplasty system of claim 1, wherein the femoral prosthesis comprises a coating.

9. The femoral head arthroplasty system of claim 8, wherein the coating is one selected from the group consisting of hydroxyapatite, titanium oxide, titanium nitride, zirconium oxide, and pyrolytic carbon.

10. The femoral head arthroplasty system of claim 8, wherein the coating is configured to promote ingrowth or on-growth of bone.

11. The femoral head arthroplasty system of claim 1, wherein the diameter of at least a portion of the implant body ranges from about 10 mm to about 18 mm.

12. The femoral head arthroplasty system of claim 1, wherein the adapter has a Morse taper.

13. The femoral head arthroplasty system of claim 1, wherein the femoral head replacement is angularly offset from the femoral prosthesis.

14. The femoral head arthroplasty system of claim 1, wherein the first side of the mounting plate has a planar or substantially planar profile, and wherein the second side of the mounting plate has a planar or substantially planar profile that is parallel to the first side.

15. The femoral head arthroplasty system of claim 1, wherein the major dimension of the implant body is between 18 mm and 25 mm, and wherein the minor dimension of the implant body is between 12 mm and 18 mm.

16. The femoral head arthroplasty system of claim 1, wherein the first side of the mounting plate is planar, and wherein the distal end of the implant body defines a surface that extends generally parallel to the first side of the mounting plate.

17. The femoral head arthroplasty system of claim 1, wherein the first side of the mounting plate is planar, and wherein the distal end of the implant body defines a surface that extends parallel to the first side of the mounting plate.
