

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12404131
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Samaras; Christopher J. et al.

Continuous dispensing reel system

Abstract

A generally continuous string of container carriers are positioned on a base (35) wherein container carriers are housed on multiple reels (40) and are spliced together between adjacent reels to form the generally continuous string and the multiple reels are arranged on at least one axle (55) for dispensing.

Inventors:	Samaras; Christopher J. (Tinley Park, IL), Erickson; Kevin D. (Glen Ellyn, IL)
Applicant:	ILLINOIS TOOL WORKS INC. (Glenview, IL)
Family ID:	73040313
Assignee:	ILLINOIS TOOL WORKS INC. (Glenview, IL)
Appl. No.:	17/778630
Filed (or PCT Filed):	October 12, 2020
PCT No.:	PCT/US2020/055192
PCT Pub. No.:	WO2021/118680
PCT Pub. Date:	June 17, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230028632 A1	Jan. 26, 2023

Related U.S. Application Data

us-provisional-application US 62947822 20191213

Publication Classification

Int. Cl.: **B65H16/02** (20060101); **B65D71/50** (20060101); **B65D85/67** (20060101); **B65H18/28** (20060101)

U.S. Cl.:

CPC **B65H16/021** (20130101); **B65D85/67** (20130101); **B65H18/28** (20130101); **B65D71/504** (20130101); **B65D2519/00631** (20130101); **B65H2301/412845** (20130101)

Field of Classification Search

CPC: B65H (16/005); B65H (16/021); B65H (16/04); B65H (18/28); B65H (75/02); B65H (75/08); B65H (75/10); B65H (75/362); B65H (75/364); B65H (75/4471); B65H (2301/4128); B65H (2301/41282); B65H (2301/41284); B65H (2301/412845); B65D (85/02); B65D (85/66); B65D (85/67); B65D (85/671); B65D (85/672); B65D (85/675); B65D (85/676); B65D (71/00); B65D (71/02); B65D (71/50); B65D (71/504); B65D (71/506)

USPC: 242/570; 242/570.2; 242/159; 242/160; 242/160.1; 242/160.2; 242/160.3; 242/571.2

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2650703	12/1952	Hagen	206/393	A47L 13/04
3285405	12/1965	Wanderer	N/A	N/A
3611656	12/1970	Chidsey, Jr.	206/145	B65D 71/50
3710535	12/1972	Walter	53/558	B65B 17/025
3878663	12/1974	Shelton	53/399	B65B 15/04
4022396	12/1976	Manchester	242/129	B65H 75/26
4033457	12/1976	Weaver	206/390	B65D 85/67
4267985	12/1980	Rogers	N/A	N/A
4741729	12/1987	Edwards	294/87.2	B65D 71/504
4844360	12/1988	Winter	211/171	B65H 16/021
4955471	12/1989	Hirose	N/A	B65H 18/28
5125506	12/1991	Galbierz	206/151	B65B 17/025
5303823	12/1993	Niles	N/A	B65D 43/162
5310056	12/1993	Ball	206/390	B65D 33/002
5551563	12/1995	Allen	206/394	B65H 49/38
5987851	12/1998	O'Connor	53/436	B65D 85/67
6068125	12/1999	Slaters, Jr. et al.	N/A	N/A
6209814	12/2000	Helton	242/531	B65H 55/04
8418844	12/2012	Slaters, Jr.	206/427	B65D 71/504
9139335	12/2014	Mansson	N/A	B65D 71/0096
9434521	12/2015	Olsen	N/A	B65D 85/67
10053321	12/2017	Erdem	N/A	B65H 18/28

10087027	12/2017	Takeda	N/A	B65H 21/00
11945631	12/2023	Cyr	N/A	B65D 65/466
2002/0144924	12/2001	Johnson	156/204	B65D 85/67
2003/0122008	12/2002	Abba	242/593	B65H 19/10
2003/0122009	12/2002	Abba	242/167	B65H 19/10
2009/0166235	12/2008	Mansson	206/391	B65D 71/04
2010/0140121	12/2009	Slaters, Jr.	206/223	B65D 71/504
2010/0320309	12/2009	Galgano	229/199	B65D 85/676
2011/0259767	12/2010	Olsen	206/150	B65D 85/67
2014/0196634	12/2013	Mansson	108/55.1	B65D 85/672
2016/0016351	12/2015	Siewert	264/163	B29C 53/02
2016/0280490	12/2015	Erdem	N/A	A61F 13/15764
2023/0087274	12/2022	Cyr	294/87.2	B65D 71/50
2024/0091972	12/2023	Hayter	N/A	B65D 71/50

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
37 02 595	12/1987	DE	N/A
0 960 833	12/1998	EP	N/A
727158	12/1954	GB	B65D 85/672
WO-2014173757	12/2013	WO	B65D 19/44
WO-2018230494	12/2017	WO	B65H 16/04
WO-2020115518	12/2019	WO	B65D 85/675

OTHER PUBLICATIONS

European Patent Office (EPO), Rijswijk, NL, International Search Report, Form PCT/ISA/210 for International Application No. PCT/US2020/055192, Feb. 18, 2021 (5 pp.). cited by applicant

European Patent Office (EPO), Rijswijk, NL, Written Opinion of the Int'l Searching Authority for Int'l Appln No. PCT/US2020/055192, Form PCT/ISA/237, Feb. 18, 2021 (7 pp.). cited by applicant

Primary Examiner: Momper; Anna M

Assistant Examiner: Dias; Raveen J

Attorney, Agent or Firm: Pauley Erickson & Swanson

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION (1) This application is a National Phase filing of PCT International Patent Application Number PCT/US2020/055192, filed on 12 Oct. 2020, which claims the priority of U.S. Provisional Patent Application Ser. No. 62/947,822, filed 13 Dec. 2019. (2) These applications are hereby incorporated by reference herein in their entirety and is made a part hereof, including but not limited to those portions which specifically appear hereinafter.

BACKGROUND OF THE INVENTION

Field of the Invention

(1) This invention relates to an apparatus and method for dispensing container carriers in a space-efficient manner.

Description of Prior Art

(2) Container carriers are used to unitize a plurality of containers. Typical containers are bottles, cans and other containers having a sidewall and a neck, chime or raised rib around an upper portion of the container. Container carriers typically connect two or more containers into a sturdy unitized package of containers. Container carriers are generally planar arrays of rings, sometimes referred to as "six-pack carriers," and may be formed from a thermoplastic sheet material.

(3) The thermoplastic sheet material is typically extruded and then punched so that large numbers of container carriers are formed end to end resulting in continuous elongated strings or strips of container carriers. Unless specified otherwise, container carriers as used in this specification are defined as the continuous elongated string of container carriers prior to application onto containers and subsequent division into individual container carriers.

(4) Prior art methods of packaging container carriers involve accumulating the elongated strings of container carriers onto reels. The reels of container carriers are unwound at a later time during application onto containers. The reel method of storing and applying the container carriers to containers requires splicing the end of one reel with the beginning of the following reel without interrupting the application process. In addition, the reel method of storing and applying carriers is generally limited to reels of a size which may be physically lifted and manipulated by the applying machine operator. Also, the reel unwinding equipment must accommodate the inertia and resultant backlash inherent in unwinding a wound strip of material. Further, the generally circular or octagonal shape of the reels limits the number of reels which may be assembled onto a single pallet for shipment between the production facility and the application facility.

(5) According to another prior art method of storing and dispensing container carriers, such as disclosed in Wanderer, U.S. Pat. No. 3,285,405, and Slaters Jr. et al., U.S. Pat. No. 6,068,125, incorporated by reference herein, elongated strings of container carriers are fan folded, similar to pin-feed computer paper, into boxes or cartons. The container carriers are dispensed from the boxes or cartons during the application process and successive boxes or cartons containing stacks of container carriers are spliced together as the boxes empty.

(6) However, such methods for storing and dispensing container carriers may lead to uneven accumulation of the container carriers at each end of the box or carton, specifically where the container carriers are folded over onto each other. As a result, cartons may suffer from uneven stacks of folded container carriers whereby a central portion of the carton is not filled to capacity and end portions of the carton include distinctly higher stacks of carriers. This problem is referred to as "birdsnesting" and may result in inefficiently packed cartons of container carriers and even tangling of the string of container carriers during the unwinding process. In addition, the equipment required to properly fan fold and stack container carriers into cartons is sophisticated and requires substantial investment and maintenance for continuous operation.

SUMMARY OF THE INVENTION

(7) It is one object of this invention to provide a package of container carriers which allows for space-efficient storage of reels of container carriers and permits uninterrupted removal of a mostly continuous elongated strip of container carriers.

(8) A package of container carriers for shipment and storage and subsequent application to groups of containers is constructed to contain reels of container carriers. Elongated strips of container carriers are preferably rolled into multiple reels and positioned and spliced within cartons for shipment and subsequent dispensing in a generally continuous manner.

(9) A resulting package of container carriers according to an embodiment of the invention

preferably includes a carton and a generally continuous string of container carriers rolled onto a plurality of reels in a generally continuous fashion wherein adjacent reels are separated by a splice.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The above-mentioned and other features and objects of this invention will be better understood from the following detailed description taken in conjunction with the drawings wherein:
- (2) FIG. 1 is a side elevational view of a string of container carriers according to the prior art;
- (3) FIG. 2 is a side perspective view of a carton or package of container carriers according to the prior art;
- (4) FIG. 3 is a side perspective view of a carton or package of container carriers according to one preferred embodiment of this invention;
- (5) FIG. 4 is a planogram of a carton or package of container carriers according to one preferred embodiment of this invention; and
- (6) FIG. 5 is a side perspective view of a carton or package of container carriers and a payoff system according to one preferred embodiment of this invention.

DESCRIPTION OF PREFERRED EMBODIMENTS

- (7) FIG. 1 shows a string of container carriers **10** as the term is used in the claimed invention. Container carriers **10** are preferably arranged in a generally continuous elongated string or strip having weakened areas between adjacent individual container carriers. Individual container carriers include two or more container receiving apertures **15** which are used to engage and unitize respective groups of containers into multipackages such as six packs, twelve packs, etc.
- (8) FIG. 2 shows a carton of fan folded stacks **20** of container carriers **10** according to the prior art. The elongated strip of container carriers **10** are preferably fan folded back and forth in alternating opposite directions resulting in horizontally extending rows of container carriers **10** forming vertically extending stacks **20**. Fan folding container carriers **10**, like pin-feed computer paper, preferably results in stacks **20** wherein a large amount of container carriers **10** are folded into a minimum amount of space. During the production process, container carriers **10** are preferably formed in the generally continuous, elongated string for shipment and storage in packaging, such as carton or package **15**. After shipment to an application facility, such as a soft drink bottler, container carriers **10** are preferably removed from the packaging and applied, on an applying machine, to groups of containers, such as cans, during which application container carriers **10** are separated from the elongated strip and into individual container carrier packages.
- (9) In a preferred embodiment of the invention shown in FIG. 3, package **30** comprises a carton or at least two or more rigid sidewalls **50**. The carton may contain two or more reels **40** of container carriers **10**. A method for assembling package **30** of container carriers **10** is required that results in an efficiently filled package **30** and permits uninterrupted removal of a mostly continuous elongated strip of container carriers **10**. In one preferred embodiment of this invention, package **30** is loaded with multiple reels **40** of container carriers **10**. Preferably, though not necessarily, each reel **40** of container carriers **10** is separated and/or positioned using one or more dividers **60** to maintain position of and spacing between the various reels **40** of container carriers **10**. This configuration helps prevent tangling and other problems encountered during loading and unloading of package **30**.
- (10) A system for dispensing a generally continuous string **10** of container carriers includes a base **35**. The base **35** may comprise a standard pallet or may be specifically adapted to the system herein.
- (11) At least two rigid sidewalls **50** preferably extend from the base **35**. The rigid sidewalls **50** may comprise corrugated load bearing cardboard or similar construction. Additional sidewalls may

extend between the two rigid sidewalls **50** that may be less structural but serve to protect the contents from contamination or intrusion. Alternatively, a carton may be formed of four similar sidewalls, each forming a structural rigid support for the system.

(12) One or more axles **55** may extend between the rigid sidewalls **50**. The axles **55** may comprise thick wall cardboard tubes or may comprise a more rigid and reusable solution including steel, plastic or other suitable material that can support the substantial weight of two or more reels **40** of container carrier.

(13) At least two reels **40** are preferably positioned around each axle **55**. The reels **40** as described each include a string **10** of container carriers. During production, the container carriers are preferably formed, such as through a punch press or rotary die, into generally continuous strings that are wound onto the reels **40** and then positioned within the subject system. Adjacent reels **40** are preferably are spliced together, so that a tail of reel A is connected to a head of reel B to form a generally continuous string **10** of container carriers.

(14) In a preferred embodiment of this invention, each additional reel **40** of container carriers **10** that is added to package **30** is connected to the previous reel **40** of container carriers **10**. Preferably, an end or tail of a container carrier at a bottom of a first reel **40** of container carriers **10** is connected with a head or beginning container carrier at a top of an additional reel **40** of container carriers **10**. The end container carrier is preferably connected or spliced with the beginning container carrier using a weld attachment or a heat seal. A planogram showing a preferred arrangement of reels **40** is shown in FIG. **4**. Adjacent reels **40** of container carriers **10** may also be connected using other methods known to those having skill in the art.

(15) Specifically, the system preferably comprises an array of reels **40**, each reel **40** of the array including a string of container carriers spliced to a string of container carriers of at least one adjacent reel **40**, such as shown in FIGS. **3** and **4**.

(16) In this specific embodiment, six reels **40** may be arranged in two rows, wherein two reels **40** along one rigid sidewall **50** include a spliced connection relative to each other and two reels **40** along another rigid sidewall include a spliced connection relative to each other. Further, the two reels **40** in a center of the axle **55** include a spliced connection relative to each other. As shown in FIG. **4**, a preferred arrangement includes connections among Reels A-B-C-D-E-F in that order head-to-tail. This arrangement encourages continuous runoff without tangling or interruption.

(17) In a preferred embodiment, each reel **40** is preferably fully “back wrapped” to enable continuous head-tail splicing. Specifically, each reel **40** is manufactured so that a mid-point of the carrier length is folded and wound at a core of the reel **40** so each turn of the reel pays off the length going to the application machine and a length to be pulled to the machine after the first half of the reel is depleted.

(18) The system may further include a divider **60** positioned between each adjacent reel **40**. The divider **60** may be positioned specifically between each adjacent reel that shares a common axle **55** and may prevent binding between the reels as they are unwound. Like the sidewalls **50**, the dividers **60** may also be corrugated cardboard and assist in the structural integrity of the system.

(19) In one embodiment, an additional layer of reels **40** may be positioned on top of the plurality of reels **40**. In this arrangement, at least one reel **40** of container carriers in the additional layer of reels is spliced to at least one reel **40** of container carriers in the plurality of reels below.

(20) According to one embodiment shown in FIG. **5**, a payoff system **80** may be integrated with the subject system to provide a powered pull system. The payoff system **80** according to this invention preferably pulls material from the reel **40** at a rate matched to a speed of the application machine. Such a powered feed system preferably acts as an isolation mechanism for the flow of carrier. As a result, the powered feed or pull system would keep upstream or downstream changes in tension from effecting proper application of the carrier to containers.

(21) While in the foregoing specification this invention has been described in relation to certain preferred embodiments thereof, and many details have been set forth for purposes of illustration, it

will be apparent to those skilled in the art that the apparatus is susceptible to additional embodiments and that certain of the details described herein can be varied considerably without departing from the basic principles of the invention.

Claims

1. A system for dispensing a generally continuous string of container carriers, each container carrier for unitizing a plurality of containers, the system comprising: a base; two rigid sidewalls extending from the base; an axle extending between the rigid sidewalls; and at least two reels positioned around the axle, each reel including a string of container carriers that are spliced together to form a generally continuous string of container carriers, wherein each reel is back-wrapped.
2. The system of claim 1 wherein the at least two reels comprise an array of reels, each reel of the array including the string of container carriers spliced to another string of container carriers of at least one adjacent reel of the array to form the generally continuous string of container carriers.
3. The system of claim 1 comprising an additional two axles, each axle supporting at least two reels.
4. The system of claim 1 comprising a divider positioned between each adjacent reel of the at least two reels.
5. The system of claim 1 comprising a divider positioned between each adjacent reel of the at least two reels that are positioned around the axle and that share that axle.
6. The system of claim 1 wherein the rigid sidewalls form a portion of a carton containing the generally continuous string of container carriers.
7. The system of claim 1 further comprising at least additional sidewalls forming a carton.
8. The system of claim 1 comprising six reels arranged in two rows, wherein two reels of the six reels along one rigid sidewall of the two rigid sidewalls include a spliced connection and two reels of the six reels along the other rigid sidewall of the two rigid sidewalls include a spliced connection.
9. The system of claim 8 wherein two reels of the six reels in a center of the axle include a spliced connection.
10. The system of claim 1 wherein the rigid sidewalls are corrugated.
11. The system of claim 1 wherein the axle comprises a cardboard tube.
12. The system of claim 1 wherein an additional layer of reels is positioned on top of the at least two reels.
13. The system of claim 12 wherein at least one reel of container carriers in the additional layer of reels is spliced to at least one reel of container carriers in the at least two reels below.
14. A generally continuous string of container carriers, each container carrier for unitizing a plurality of containers, the generally continuous string of container carriers comprising: a first reel having a string of container carriers; a second reel having a string of container carriers, the second reel connected to the first reel with a splice, wherein the first reel and the second reel are back-wrapped; an axle supporting at least one of the first reel and the second reel; and at least two sidewalls enclosing the first reel and the second reel.
15. A package of container carriers comprising: a carton; a generally continuous string of container carriers rolled onto a plurality of reels in a generally continuous fashion wherein adjacent reels are separated by a splice, wherein an additional layer of reels is positioned on top of the plurality of reels, and wherein at least one reel of container carriers in the additional layer of reels is spliced to at least one reel of container carriers in the plurality of reels below.
16. The system of claim 14 wherein each reel is back-wrapped.
17. The package of claim 15 further comprising a pair of axles, each axle supporting two or more reels of container carriers.
18. The package of claim 17 further comprising a divider positioned between each adjacent reel on

an each axle.

19. The package of claim 17 further comprising a pair of sidewalls between which each axle extends.

20. The package of claim 15 wherein the plurality of reels are arranged in a two by three array of reels within the carton.

21. A system for dispensing a generally continuous string of container carriers, each container carrier for unitizing a plurality of containers, the system comprising: a base; two rigid sidewalls extending from the base; at least one axle extending between the rigid sidewalls; and six reels arranged in two rows, wherein two reels of the six reels along one rigid sidewall of the two rigid sidewalls include a spliced connection and two reels of the six reels along the other rigid sidewall of the two rigid sidewalls include a spliced connection, wherein at least two reels are positioned around the at least one axle, each reel including a string of container carriers that are spliced together to form a generally continuous string of container carriers.
