

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12406249
Kind Code	B1
Date of Patent	September 02, 2025
Inventor(s)	Nolte; Matthew David et al.

Automated application workflows based on signal detection

Abstract

Techniques are described for automatically presenting workflow(s) in an application based at least partly on detected signal(s). A radio-frequency signal may be emitted from a transceiver and received by a transceiver of a user device when the transceiver is in proximity to the device. In response, an application including functionality to activate a payment card can launch.

Inventors: Nolte; Matthew David (San Antonio, TX), Webb; William Michael (San Antonio, TX), Huff; Shiloh (San Antonio, TX), London; Shane J. (San Antonio, TX)

Applicant: United Services Automobile Association (USAA) (San Antonio, TX)

Family ID: 73554599

Assignee: United Services Automobile Association (USAA) (San Antonio, TX)

Appl. No.: 18/430640

Filed: February 01, 2024

Related U.S. Application Data

continuation parent-doc US 16693116 20191122 US 11922401 child-doc US 18430640
continuation parent-doc US 15386358 20161221 US 10853796 20201201 child-doc US 16693116
us-provisional-application US 62270956 20151222

Publication Classification

Int. Cl.: G06Q40/00 (20230101); G06Q20/34 (20120101)

U.S. Cl.:

CPC G06Q20/354 (20130101); G06Q20/341 (20130101); G06Q20/352 (20130101);

Field of Classification Search

CPC: G06Q (40/10); G06Q (20/354); G06Q (20/341); G06Q (20/352)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5828044	12/1997	Jun	235/492	G06K 7/0008
8868458	12/2013	Starbuck	N/A	N/A
9734498	12/2016	Itwaru	N/A	N/A
10853796	12/2019	Nolte et al.	N/A	N/A
11538021	12/2021	Nolte et al.	N/A	N/A
2005/0187873	12/2004	Labrou et al.	N/A	N/A
2012/0101887	12/2011	Harvey	N/A	N/A
2014/0006194	12/2013	Xie	N/A	N/A
2014/0222670	12/2013	Concannon	705/41	G06Q 20/3263
2015/0302398	12/2014	Desai et al.	N/A	N/A
2016/0189142	12/2015	Chandru	N/A	N/A
2016/0253651	12/2015	Park	N/A	N/A
2017/0083882	12/2016	Kim	N/A	N/A
2018/0268403	12/2017	Guglani	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2012234372	12/2011	JP	N/A
2012234372	12/2011	JP	N/A
2010028266	12/2009	WO	N/A

OTHER PUBLICATIONS

“AOC Solutions Unveils EnCompass Mobile,” Business Wire; New York [New York]Feb. 27, 2013 (Year: 2013). cited by examiner

Unleashing the Wild Card for mobile payment, M Salajegheh, B Priyantha, J Liu—2014 IEEE International . . . , 2014—ieeexplore.ieee.org (Year: 2014). cited by applicant

U.S. Appl. No. 16/693,116, filed Nov. 22, 2019, Automated Application Workflows Based on Signal Detection. cited by applicant

U.S. Appl. No. 15/386,358, filed Dec. 21, 2016, now U.S. Pat. No. 10,853,796, Dec. 1, 2020, Automated Application Workflows Based on Signal Detection. cited by applicant

U.S. Appl. No. 62/270,956, filed Dec. 22, 2015, Automated Application Workflows Based on Signal Detection. cited by applicant

Primary Examiner: Akintola; Olabode

Attorney, Agent or Firm: Perkins Coie LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 16/693,116, filed on Nov. 22, 2019, entitled “AUTOMATED APPLICATION WORKFLOWS BASED ON SIGNAL DETECTION,” now allowed, which is a continuation of U.S. patent application Ser. No. 15/386,358, filed on Dec. 21, 2016, entitled “AUTOMATED APPLICATION WORKFLOWS BASED ON SIGNAL DETECTION,” issued as U.S. Pat. No. 10,853,796, which is a non-provisional of and claims priority to U.S. Provisional Application No. 62/270,956, filed on Dec. 22, 2015, entitled “AUTOMATED APPLICATION WORKFLOWS BASED ON SIGNAL DETECTION,” each of which are hereby incorporated by reference in their entireties for all purposes.

BACKGROUND

(1) Financial service providers such as banks, insurance companies, and so forth may provide a mobile application, through which customers can use a mobile device to access account data, request account activities, or view other information. However, applications designed for larger devices, such as desktop computers, may be difficult for users to view and manipulate on smaller, mobile devices with limited display size and/or limited interface functionality.

SUMMARY

(2) Implementations of the present disclosure are generally directed to the automated presentation of workflow(s) in an application based at least partly on detected signal(s). More particularly, implementations of the present disclosure are directed to the automated presentation of workflows for activating a payment card and/or viewing account information, based at least partly on detecting radio-frequency signal(s) that are emitted from a payment card and/or that identify the payment card.

(3) In general, innovative aspects of the subject matter described in this specification can be embodied in methods that includes actions of: receiving, through a transceiver component of a user device, a signal that includes a card identifier (ID) of a payment card; determining the card ID from the signal; determining a status of the payment card corresponding to the card ID; and based at least partly on the status of the payment card, presenting at least a portion of a workflow in an application executing on the user device.

(4) Implementations can include one or more of the following features: presenting the workflow further comprises presenting a card activation workflow responsive to the status of the payment card being currently inactive; presenting the workflow further comprises presenting an account information workflow responsive to the status of the payment card being currently active; determining the status of the payment card further comprises: sending a status request to a card service executing remotely, the status request including the card ID; and receiving the status from the card service in response to the status request; the signal is transmitted from a radio-frequency transmitter included in the payment card; the signal is transmitted from a near field communication (NFC) transmitter included in the payment card; sending an activation request to a card service executing remotely, the activation request including the card ID; receiving a notification from the card service in response to the request, the notification indicating that the payment card is activated for a period of time; or the payment card is inactive prior to sending the activation request, based on a determination that a location of the user device is outside a typical area of travel.

(5) Other implementations of any of the above aspects include corresponding systems, apparatus, and computer programs that are configured to perform the actions of the methods, encoded on computer storage devices.

(6) Implementations of the present disclosure provide one or more of the following technical advantages and/or improvements compared to traditional systems. By automatically launching workflow(s) in response to detected signals, implementations provide a user device that is less susceptible than traditional devices to errors in navigation in an application executing on the user device. Implementations also provide a better user experience for users using a user device (e.g., a

small, mobile device) to access information via an application executing on the user device. In some examples, implementations of the present disclosure enable device-based workflows to be executed even with devices with limited functionality (e.g., mobile devices having limited interface functionality as compared to larger devices). In some examples, implementations of the present disclosure enable device-based workflows to be executed even with devices with limited screen-size (e.g., mobile devices having limited display area as compared to larger devices). Moreover, implementations also enable application providers to create new access point(s) to surface deeply nested functionalities in the application. Such access point(s) are presented in response to detected signals, and the access point(s) enable to user to readily access the functionalities that may otherwise require multiple steps of navigation and/or knowledge of the application architecture. Accordingly, implementations provide for more efficient use of processing capacity, network bandwidth, storage space, active memory, and/or other computing resources compared to traditional systems which may consume such computing resources in recovering from errors in navigation and/or in performing a greater number of navigation steps compared to the implementations described herein.

(7) It is appreciated that methods in accordance with the present disclosure can include any combination of the aspects and features described herein. That is, methods in accordance with the present disclosure are not limited to the combinations of aspects and features specifically described herein, but also include any combination of the aspects and features provided.

(8) The details of one or more implementations of the present disclosure are set forth in the accompanying drawings and the description below. Other features and advantages of the present disclosure will be apparent from the description and drawings, and from the claims.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 depicts an example system for automatically launching an application workflow in response to detecting a signal, according to implementations of the present disclosure.

(2) FIG. 2 depicts an example system for automatically launching an application workflow in response to detecting a signal, according to implementations of the present disclosure.

(3) FIG. 3 depicts a flow diagram of an example process for automatically launching an application workflow in response to detecting a signal, according to implementations of the present disclosure.

(4) FIG. 4 depicts a flow diagram of an example process for payment card activation, according to implementations of the present disclosure.

(5) FIG. 5 depicts a flow diagram of an example process for automatically launching an application workflow in response to detecting a signal, according to implementations of the present disclosure.

(6) FIG. 6 depicts an example computing system, according to implementations of the present disclosure.

DETAILED DESCRIPTION

(7) Implementations of the present disclosure are directed to systems, devices, methods, and computer-readable media for automatically launching a workflow in an application executing on a computing device in response to detecting a signal at a transceiver of the computing device. In some implementations, an application such as a mobile application is configured to interface with a near field communication (NFC) transceiver or other radio-frequency transceiver on a computing device such as a mobile device (e.g., smartphone, tablet computer, wearable device, etc.). In some examples, the transceiver may receive a signal emitted by a radio-frequency transmitter included in a card such as a payment card. In some examples, the card is a credit card, debit card, bank card, business rewards card, gift card, or any other appropriate form of payment that enables the transfer of funds or other types of value. Implementations of the present disclosure also support the use of

cards other than payment cards.

(8) In response to receiving the signal, the transceiver of the computing device may provide the information in the signal to the mobile application. For example, the card may include a NFC chip that emits a signal, and the presence of the signal (e.g., at a detectable signal level) may indicate that the card is in proximity to the mobile device. In some examples, the card may be brought into proximity to (e.g., tapped against) the mobile device by a user. The transmitter may transmit an identifier (ID) of the card, which is received by the mobile application via the transceiver of the mobile device. The mobile application may automatically launch a particular workflow in the mobile application based on the presence of the signal and/or based on the particular card ID transmitted in the signal. In some implementations, the workflow is a device-based workflow requiring one or more devices to be executed. For example, at least a portion of the workflow may include any number of screens to perform card servicing functions or other customer services through the mobile application. For example, a tap of the card against the mobile device may cause the application to launch a card activation workflow, if the card is not already activated. If the card was previously activated, the tap may cause the application to launch a workflow to enable the user to view an account balance, transaction history, or other information associated with the card account.

(9) Using traditional computing systems, it may be cumbersome for a user to navigate an application to perform card servicing functions on smaller devices (e.g., wearable devices, smartphones, or other mobile devices with limited display capabilities and/or functionality as compared to laptop and/or desktop computers). For example, using a traditional system, the user may be required to navigate several levels deep into the application and have knowledge of the application's structure in order to perform financial services operations such as card activation and balance inquiries. Such navigation may be difficult on a wearable device or other mobile device with a small form factor. Implementations of the present disclosure enable execution of an application that is easier on such devices by, for example, automatically launching a workflow when the user taps a card against the device, reducing the number of steps and the need to navigate complex entry points on a small device.

(10) In some examples, a workflow may include one or more screens, windows, frames, or other containers for displaying elements in a user interface (UI) of an application. A workflow may also include any number of UI elements in any number of containers. The UI elements may present text, images, video, audio, graphics, or other types of content. The UI elements may also include controls that enable a user to interact with the application, such as text entry fields, selectable lists, menus, buttons, selectable images or graphics, or other types of controls. In some examples, a workflow is a single screen, window, frame, or other container that presents any number of UI elements. In some examples, a workflow includes multiple screens, windows, frames, or other containers, and at least some of the UI elements may enable a user to navigate from screen to screen within the application.

(11) An application may be a web application configured to execute at least partly in a web browser or in an object configured to present web content, such as an object instance of a WebView class or a UIWebView class. In some examples, the application may be a native application that is designed to execute within a hardware and/or software configuration of a computing device. The application may be configured according to any programming language, including compiled languages, interpreted languages, scripting languages, and so forth. The application may be configured to provide any type of service to the user. In some examples, the application is a financial services application provided by a financial institution such as a bank, credit union, investment brokerage, insurance company, and so forth.

(12) A tap of the card against the user device may include the card coming into physical contact with a portion of the user device. A tap may also include the card coming into proximity with the user device, such that the signal emitted by the transmitter in the card is detectable by a transceiver

of the user device. The proximity range for signal detection may depend on the strength or level of the signal emitted by the transmitter as well as the sensitivity or other characteristic(s) of the transceiver in the user device.

(13) FIG. 1 depicts an example system for automatically launching an application workflow in response to detecting a signal, according to implementations of the present disclosure. In the example of FIG. 1, a user **102** is wearing, carrying, or otherwise in the presence of a user device **106**. Although FIG. 1 depicts an example in which the user device **106** is a wearable computing device (e.g., a smartwatch), implementations support user devices **106** that are any type of computing device, such as a smartphone, tablet computer, laptop computer, in-vehicle computing system, and so forth. The user device **106** may be a mobile device or portable device such as a smartphone, tablet, wearable device, and so forth. The user device **106** may also be a less portable device such as a desktop computer, laptop computer, smart appliance, internet-of-things (IoT) device, and so forth. The user **102** may have a card **104** such as a payment card, and the card **104** may include a transmitter **108**. In some examples, the transmitter **108** is embedded in, affixed to, or otherwise (e.g., permanently) incorporated into the physical structure of the card **104**. In some examples, the transmitter **108** may be included in a sticker or other object that is affixed to the card **104** such that the user **102** may remove the transmitter **108** from the card **104**. In some examples, the transmitter **108** may be physically separate from, but associated with, the card **104**. For example, the card **104** may be mailed to the user **102** with various papers and the transmitter **108** may be included in the envelope with the card **104**.

(14) The transmitter **108** may be configured to emit a signal **110**. In some implementations, the signal **110** is a radio-frequency signal. The signal **110** may also be within any other frequency ranges of the electromagnetic (EM) spectrum, such as visible light, infrared, and so forth. Implementations also support signals **110** that are non-EM signals, such as audio emissions or other types of pressure waves. In some implementations, the transmitter **108** actively emits the signal **110** regardless of other signal(s) received at the transmitter **108**. In some implementations, the transmitter **108** may emit the signal **110** in response to detecting a radio-frequency signal or other type of input signal at the card **104**. For example, the transmitter **108** may emit a NFC signal **110** that is configured according to any version of a NFC specification. In another example, the transmitter **108** may emit a Bluetooth™ signal **110** that is arranged according to any version of a Bluetooth™ or Bluetooth™ Low Energy (LE) specification. In response to the detection of the signal **110** at the user device **106**, software executing on the user device **106** may alter its state, as described further with reference to FIG. 2. As shown in the example of FIG. 1, an application executing on the user device **106** has launched a new card activation workflow in response to the detected signal **110**.

(15) FIG. 2 depicts an example system for automatically launching an application workflow in response to detecting a signal **110**, according to implementations of the present disclosure. As shown in FIG. 2, the signal **110** may encode or otherwise include a card identifier (ID) **204**. In some implementations, the transmitter **108** may transmit a card ID **204** of the card **104** that is the card number itself (e.g., a 16 digit credit card number). In some implementations, the transmitter **108** may transmit a card ID **204** that is different than the card number but that corresponds (e.g., uniquely) to the card **104**. In some examples, the card ID **204** may be associated with the card number in a table or other data structure stored on a back-end server, such as the card service device(s) **208**.

(16) The user device **106** may include one or more network interface(s) **202**, which may also be described as a network interface controller (NIC) or transceiver. In some examples, the network interface(s) **202** may include a NFC receiver and/or transceiver. On receiving the signal **110** through the network interface(s) **202**, the application **206** may access the card ID **204** encoded in the signal **110**. The application **206** may cause another signal to be communicated to one or more card service(s) **210** executing on one or more card service device(s) **208**. In some implementations,

the application **206** may communicate the card ID **204** to the card service(s) **210**. Such communications may occur over one or more wired and/or wireless networks (not shown), such as the internet or other wide area network (WAN). The card service device(s) **208** may include any type of computing device(s), such as a server computer, a distributed computing device (e.g., cloud server), network server, and so forth.

(17) In some implementations, the application **206** may also communicate information identifying a user **102** who is currently logged into the application **206**. The card service(s) **210** may verify that the card ID **204** corresponds to a card **104** that is associated with the authenticated current user **102** of the application **206**. The card service(s) **210** may also verify that the communication is received from a user device **106** that is associated with the user **102**, to prevent fraudulent transactions. If the card ID **204** corresponds to a card **104** that is associated with the user **102**, and the user device **106** is known to be associated with the user **102**, the card service(s) **210** may respond to indicate that the application **206** may proceed to present an appropriate workflow. In some implementations, the card service(s) **210** may respond with a card status **212** indicating a current status of the card **104**, such as whether the card has been activated or has yet to be activated.

(18) In some implementations, the transmitter **108** may also emit other data or metadata in addition to the card ID **204** in the same signal **110** or other signal(s). For example, the transmitter **108** may be configured to emit a signal **110** that includes other information, such as a particular launch point. The launch point may be formatted as a uniform resource identifier (URI), such as a uniform resource locator (URL) or uniform resource name (URN). The application **206** may be configured to respond to a particular URI received at the network interface(s) **202**. For example, in response to detecting the URI, the application **206** may perform certain actions such as launching a workflow or sending a communication to the server to verify the card ID **204** and request instructions for which workflow to launch. In some examples, the application **206** may present content that is available at the URI, such as one or more particular web page(s).

(19) FIG. 3 depicts a flow diagram of an example process for automatically launching an application workflow in response to detecting a signal **110**, according to implementations of the present disclosure. Operations of the process may be performed by the network interface(s) **202**, the application **206**, the card service(s) **210**, or other software module(s) executing on the user device **106**, the card service device(s) **208**, or elsewhere.

(20) In some implementations, a user **102** is authenticated (**302**) to login and access information through the application **206**. Authentication may include verifying user-provided credentials such as one or more of a login name, password, personal identification number (PIN), answer(s) to knowledge-based questions (e.g., what is your maternal grandfather's middle name?), and so forth. Authentication may also include collecting biometric data from the user **102** and verifying that the collected biometric data corresponds to previously collected data from the user **102**. Biometric data may include fingerprint(s), image(s) or video of the user's face, audio recordings of the user's voice, and so forth. In some implementations, authentication may include one or more round trip communications with the card service device(s) **208** to verify the user's credential(s) and/or biometric data.

(21) A signal **110** may be received (**304**) at the user device **106**, by network interface(s) **202**. In some examples, the signal **110** may be emitted from a transmitter **108** associated with the card **104** as described above. The signal **110** may include a card ID **204**, and the card ID **204** may be extracted (**306**) from the signal **110** or otherwise determined based on the information in the signal **110**. On determining that the signal **110** has been received, the application **206** may request (**308**) a card status **212** from the card service(s) **210**. In some implementations, the application **206** may send a request to the card service(s) **210**, the request including the card ID **204**.

(22) In some implementations, the card service(s) **210** may perform (**310**) various fraud checking operation(s) based on the card ID **204** and/or other information included in the communication from the user device **106**. In some examples, the communication may include context information

such as a current location of the user device **106**, the current user **102** logged into the application **206**, and/or a device ID of the user device **106**. The fraud checking operations may check that the location is within a range of locations that is typical for the user **102** and/or the user device **106**. A current location that is outside the typical range may indicate a possible fraudulent use of the user device **106** and/or application **206**. Location may be determined based on a satellite-based navigation component of the user device **106**, such as a global positioning system (GPS) receiver, or using other techniques. The fraud checking operations may check that the device ID is that of a user device **106** previously registered or used by the user **102**. A different device ID may indicate possible fraud. The device ID may be a media access control (MAC) address or Ethernet Hardware Address (EHA) of the user device **106**, an internet protocol (IP) address of the user device **106**, or other device ID that (e.g., uniquely) identifies the user device **106** among multiple devices. If the card service(s) **210** determine possible fraud, the request for card status **212** may be denied and/or the user **102** may be prompted to provide further authentication information to ensure the user **102** is authorized to use the card **104**, the user device **106**, and/or the application **206**.

(23) The card status **212** of the card **104** may be determined (**312**) based on the card ID **204**. In some examples, the card status **212** may indicate that the card **104** is currently active, such that it may be used for transactions. Alternatively, the card status **212** may indicate that the card **104** is currently inactive, such that it may not yet be used for transactions. The card status **212** may be sent (**314**) to the application **206**. Based on the card status **212**, the application **206** may determine (**316**) whether the card **104** is already active. If not, the application **206** may present (**318**) a first workflow in the UI of the application **206**. The first workflow may be a card activation workflow that enables the user **102** to specify information to activate the card **104**. In some examples, the card activation workflow may automatically send a message to the card service(s) **210** to activate the card **104** without any further information provided by the user **102**. If it is determined that the card **104** is already active, the application **206** may present (**320**) a second workflow in the UI of the application **206**. The second workflow may enable the user **102** to view account information such as current account balance, recent transaction(s), and so forth.

(24) In some examples, the card service(s) **210** may determine that the card **104** is a new card **104** that has been sent to the user **102**, such that the card **104** needs to be activated for use by the user **102**. In such examples, the card service(s) **210** may respond with a card status message indicating that the application **206** is to launch the new card activation workflow to guide the user **102** through the process of activating the card. In some implementations, the tap of an un-activated card **104** on the user device **106** may prompt the application **206** to send a message to the card service(s) **210** to activate the card **104**, without any further interaction by the user **102**. If the card service(s) **210** determine that the card **104** has previously been activated, the card service(s) **210** may respond with a message indicating that the application **206** is to launch a different flow. For example, in response to the tap of an activated card **104**, the application **206** may present screens displaying the current balance of the card account, recent transaction(s), previous payment(s), next payment due, or other account information.

(25) In some implementations, the application **206** may include a feature to enable a user **102** to personalize the behavior of the application **206** in response to a tap of the card **104**. For example, the user **102** may personalize the application **206** to show account balance in response to a card tap. The application **206** may also enable the user to personalize (e.g., enable or disable) whether the application **206** launches a workflow automatically in response to detecting a signal **110**, or whether the user **102** is prompted to allow or disallow the workflow launch in response to the signal **110**. In some implementations, instead of making a call to the card service(s) **210** to determine which workflow to launch, the signal **110** may include a URL or other launch point to indicate which workflow to present in the application **206**.

(26) FIG. 4 depicts a flow diagram of an example process for card activation, according to implementations of the present disclosure. Operations of the process may be performed by the

network interface(s) **202**, the application **206**, the card service(s) **210**, or other software module(s) executing on the user device **106**, the card service device(s) **208**, or elsewhere.

(27) The user **102** may be authenticated (**402**) to access the application **206**, the signal **110** may be received (**404**), and the card ID **204** may be extracted (**406**) from the signal **110**, as described above with reference to **302**, **304**, and **306** respectively. The application **206** may send a communication to the card service(s) **210** to request (**408**) card activation. The communication may include the card ID **204**. On receiving the communication, the card service(s) **210** may perform (**410**) various fraud checking operations as described with reference to **310**. If the fraud checking operation(s) do not identify possible fraud, the card service(s) **210** may activate (**412**) the card **104** for a period of time, and send (**414**) a card activation message **416** to the user device **106**. The application **206** may present (**418**) the card activation message **416** in the UI of the application **206** to notify the user **102** that the card **104** may be used for the period of time.

(28) In some implementations, the workflow presented in the application **206** may be based at least partly on contextual information. For example, if the location of the user device **106** outside its normal range of locations or territory, the card service(s) **210** may instruct the application **206** to launch a travel notification workflow to enable the user **102** to indicate that they are travelling, their expected destination, the duration of the travel, or other information. As in the example of FIG. **4**, the determination that the user **102** is travelling may cause the card service(s) **210** to disable the card **104** by default. If the user **102** wishes to use the card **104** for a transaction while travelling, the user **102** may tap the card **104** against the user device **106**. This tap may cause the activation of the card **104** for a period of time (e.g., 5 minutes, 15 minutes, etc.) to enable the user **102** to complete the current transaction using the card **104**. Placing the card **104** into an inactive state by default, and activating the card **104** for a short period of time per transaction, may prevent the card **104** from being used if it is lost or stolen during the user's travels.

(29) The tap may allow the card service(s) **210** to determine that the card **104** is physically with the user **102**, and the card **104** may be activated for use for the period of time following the tap. The tap-to-use feature may be activated manually by the user **102**, or automatically activated under certain circumstances (e.g., when the user **102** is travelling). In some implementations, the user **102** may set preferences in the application **206** to determine when or under what circumstances the card **104** is generally disabled until tap, or generally enabled. The tap-to-use feature may also be automatically activated if possible fraud is detected (e.g., based on an unusual location, device, or usage pattern), to require the user **102** to prove that the card **104** is in their physical presence before authorizing a charge.

(30) As another example, if the current location of the user device **106** is determined to be at a store, the application **206** may respond to a tap by launching a workflow to present the current account balance instead of other information, to enable the user **102** to determine whether their account holds sufficient funds for a purchase. Location information may be stored on the card service device(s) **208**, and used subsequently to determine whether subsequent transactions are possibly fraudulent. For example, if the card **104** is tapped to the user device **106** in Texas, but a transaction request is detected from a store in New York, that transaction may be flagged as possibly fraudulent, assuming that the store location can be accurately determined based on the network address associated with the transaction.

(31) FIG. **5** depicts a flow diagram of an example process for automatically launching an application workflow in response to detecting a signal **110**, according to implementations of the present disclosure. Operations of the process may be performed by the network interface(s) **202**, the application **206**, the card service(s) **210**, or other software module(s) executing on the user device **106**, the card service device(s) **208**, or elsewhere.

(32) The signal **110** may be received (**502**) by the network interface(s) **202** of the user device **106**. In some examples, the signal **110** may be emitted from a transmitter **108** included in a piece of mail, such as an envelope, a parcel, a postcard, and so forth. A URL may be extracted (**504**) from

the signal **110**, and the application **206** may present (506) information associated with the URL. For example, the application **206** may navigate to the URL and load one or more pages of information available at the URL. In some examples, a letter or other piece of physical mail may be sent to user **102**, and the mail may include an iBeacon or other type of Bluetooth™ LE transmitter **108**. The Bluetooth™ transceiver or other network interface(s) **202** on the user device **106** may detect a signal **110** sent from the transmitter **108** and the application **206** may launch a workflow in response to the signal **110**. For example, an important or time-sensitive letter such as a new card mailer may include a transmitter chip, and the application **206** may respond to the signal **110** by presenting a screen to inform the user **102** that important new mail has been received. This may help the user **102** avoid throwing away letters that include a payment card, letters that require a customer signature, time-sensitive mail, or other important mail that may otherwise be perceived as junk mail by the user **102**. A letter may include a LE transmitter that has longer range or signal strength than a standard NFC transmitter, to enable signal detection even if the user device **106** is up to several meters away from the mail. In some examples, the signal **110** transmitted by the transmitter **108** included in the card **104** or a piece of mail may be encrypted or otherwise secured such that the application **206** is able to decrypt the signal **110** but other unauthorized processes are not able extract information from the signal **110**.

(33) In some implementations, the application **206** may be configured to detect and respond to the tap of another user's card to a user device **106**. For example, a funds transfer workflow from userA to userB may be launched in response to detecting the tap of userA's card to userB's user device **106**, if userB has configured their account to specify userA as a friend or contact for authorized funds transfers, and/or vice versa.

(34) FIG. 6 depicts an example computing system, according to implementations of the present disclosure. The system **600** may be used for any of the operations described with respect to the various implementations discussed herein. For example, the system **600** may be included, at least in part, in one or more of the user device **106** or the card service device(s) **208** described herein. The system **600** may include one or more processors **610**, a memory **620**, one or more storage devices **630**, and one or more input/output (I/O) devices **650** controllable via one or more I/O interfaces **640**. The various components **610**, **620**, **630**, **640**, or **650** may be interconnected via at least one system bus **660**, which may enable the transfer of data between the various modules and components of the system **600**.

(35) The processor(s) **610** may be configured to process instructions for execution within the system **600**. The processor(s) **610** may include single-threaded processor(s), multi-threaded processor(s), or both. The processor(s) **610** may be configured to process instructions stored in the memory **620** or on the storage device(s) **630**. The processor(s) **610** may include hardware-based processor(s) each including one or more cores. The processor(s) **610** may include general purpose processor(s), special purpose processor(s), or both.

(36) The memory **620** may store information within the system **600**. In some implementations, the memory **620** includes one or more computer-readable media. The memory **620** may include any number of volatile memory units, any number of non-volatile memory units, or both volatile and non-volatile memory units. The memory **620** may include read-only memory, random access memory, or both. In some examples, the memory **620** may be employed as active or physical memory by one or more executing software modules.

(37) The storage device(s) **630** may be configured to provide (e.g., persistent) mass storage for the system **600**. In some implementations, the storage device(s) **630** may include one or more computer-readable media. For example, the storage device(s) **630** may include a floppy disk device, a hard disk device, an optical disk device, or a tape device. The storage device(s) **630** may include read-only memory, random access memory, or both. The storage device(s) **630** may include one or more of an internal hard drive, an external hard drive, or a removable drive.

(38) One or both of the memory **620** or the storage device(s) **630** may include one or more

computer-readable storage media (CRSM). The CRSM may include one or more of an electronic storage medium, a magnetic storage medium, an optical storage medium, a magneto-optical storage medium, a quantum storage medium, a mechanical computer storage medium, and so forth. The CRSM may provide storage of computer-readable instructions describing data structures, processes, applications, programs, other modules, or other data for the operation of the system **600**. In some implementations, the CRSM may include a data store that provides storage of computer-readable instructions or other information in a non-transitory format. The CRSM may be incorporated into the system **600** or may be external with respect to the system **600**. The CRSM may include read-only memory, random access memory, or both. One or more CRSM suitable for tangibly embodying computer program instructions and data may include any type of non-volatile memory, including but not limited to: semiconductor memory devices, such as EPROM, EEPROM, and flash memory devices; magnetic disks such as internal hard disks and removable disks; magneto-optical disks; and CD-ROM and DVD-ROM disks. In some examples, the processor(s) **610** and the memory **620** may be supplemented by, or incorporated into, one or more application-specific integrated circuits (ASICs).

(39) The system **600** may include one or more I/O devices **650**. The I/O device(s) **650** may include one or more input devices such as a keyboard, a mouse, a pen, a game controller, a touch input device, an audio input device (e.g., a microphone), a gestural input device, a haptic input device, an image or video capture device (e.g., a camera), or other devices. In some examples, the I/O device(s) **650** may also include one or more output devices such as a display, LED(s), an audio output device (e.g., a speaker), a printer, a haptic output device, and so forth. The I/O device(s) **650** may be physically incorporated in one or more computing devices of the system **600**, or may be external with respect to one or more computing devices of the system **600**.

(40) The system **600** may include one or more I/O interfaces **640** to enable components or modules of the system **600** to control, interface with, or otherwise communicate with the I/O device(s) **650**. The I/O interface(s) **640** may enable information to be transferred in or out of the system **600**, or between components of the system **600**, through serial communication, parallel communication, or other types of communication. For example, the I/O interface(s) **640** may comply with a version of the RS-232 standard for serial ports, or with a version of the IEEE 1284 standard for parallel ports. As another example, the I/O interface(s) **640** may be configured to provide a connection over Universal Serial Bus (USB) or Ethernet. In some examples, the I/O interface(s) **640** may be configured to provide a serial connection that is compliant with a version of the IEEE 1394 standard.

(41) The I/O interface(s) **640** may also include one or more network interfaces, such as network interface(s) **202**, that enable communications between computing devices in the system **600**, or between the system **600** and other network-connected computing systems. The network interface(s) may include one or more network interface controllers (NICs) or other types of transceiver devices configured to send and receive communications over one or more networks using any network protocol.

(42) Computing devices of the system **600** may communicate with one another, or with other computing devices, using one or more networks. Such networks may include public networks such as the internet, private networks such as an institutional or personal intranet, or any combination of private and public networks. The networks may include any type of wired or wireless network, including but not limited to local area networks (LANs), wide area networks (WANs), wireless WANs (WWANs), wireless LANs (WLANs), mobile communications networks (e.g., 3G, 4G, Edge, etc.), and so forth. In some implementations, the communications between computing devices may be encrypted or otherwise secured. For example, communications may employ one or more public or private cryptographic keys, ciphers, digital certificates, or other credentials supported by a security protocol, such as any version of the Secure Sockets Layer (SSL) or the Transport Layer Security (TLS) protocol.

(43) The system 600 may include any number of computing devices of any type. The computing device(s) may include, but are not limited to: a personal computer, a smartphone, a tablet computer, a wearable computer, an implanted computer, a mobile gaming device, an electronic book reader, an automotive computer, a desktop computer, a laptop computer, a notebook computer, a game console, a home entertainment device, a network computer, a server computer, a mainframe computer, a distributed computing device (e.g., a cloud computing device), a microcomputer, a system on a chip (SoC), a system in a package (SiP), and so forth. Although examples herein may describe computing device(s) as physical device(s), implementations are not so limited. In some examples, a computing device may include one or more of a virtual computing environment, a hypervisor, an emulation, or a virtual machine executing on one or more physical computing devices. In some examples, two or more computing devices may include a cluster, cloud, farm, or other grouping of multiple devices that coordinate operations to provide load balancing, failover support, parallel processing capabilities, shared storage resources, shared networking capabilities, or other aspects.

(44) Implementations and all of the functional operations described in this specification may be realized in digital electronic circuitry, or in computer software, firmware, or hardware, including the structures disclosed in this specification and their structural equivalents, or in combinations of one or more of them. Implementations may be realized as one or more computer program products, i.e., one or more modules of computer program instructions encoded on a computer readable medium for execution by, or to control the operation of, data processing apparatus. The computer readable medium may be a machine-readable storage device, a machine-readable storage substrate, a memory device, a composition of matter effecting a machine-readable propagated signal, or a combination of one or more of them. The term “computing system” encompasses all apparatus, devices, and machines for processing data, including by way of example a programmable processor, a computer, or multiple processors or computers. The apparatus may include, in addition to hardware, code that creates an execution environment for the computer program in question, e.g., code that constitutes processor firmware, a protocol stack, a database management system, an operating system, or a combination of one or more of them. A propagated signal is an artificially generated signal, e.g., a machine-generated electrical, optical, or electromagnetic signal that is generated to encode information for transmission to suitable receiver apparatus.

(45) A computer program (also known as a program, software, software application, script, or code) may be written in any appropriate form of programming language, including compiled or interpreted languages, and it may be deployed in any appropriate form, including as a standalone program or as a module, component, subroutine, or other unit suitable for use in a computing environment. A computer program does not necessarily correspond to a file in a file system. A program may be stored in a portion of a file that holds other programs or data (e.g., one or more scripts stored in a markup language document), in a single file dedicated to the program in question, or in multiple coordinated files (e.g., files that store one or more modules, sub programs, or portions of code). A computer program may be deployed to be executed on one computer or on multiple computers that are located at one site or distributed across multiple sites and interconnected by a communication network.

(46) The processes and logic flows described in this specification may be performed by one or more programmable processors executing one or more computer programs to perform functions by operating on input data and generating output. The processes and logic flows may also be performed by, and apparatus may also be implemented as, special purpose logic circuitry, e.g., an FPGA (field programmable gate array) or an ASIC (application specific integrated circuit).

(47) Processors suitable for the execution of a computer program include, by way of example, both general and special purpose microprocessors, and any one or more processors of any appropriate kind of digital computer. Generally, a processor may receive instructions and data from a read only memory or a random access memory or both. Elements of a computer can include a processor for

performing instructions and one or more memory devices for storing instructions and data. Generally, a computer may also include, or be operatively coupled to receive data from or transfer data to, or both, one or more mass storage devices for storing data, e.g., magnetic, magneto optical disks, or optical disks. However, a computer need not have such devices. Moreover, a computer may be embedded in another device, e.g., a mobile telephone, a personal digital assistant (PDA), a mobile audio player, a Global Positioning System (GPS) receiver, to name just a few. Computer readable media suitable for storing computer program instructions and data include all forms of non-volatile memory, media and memory devices, including by way of example semiconductor memory devices, e.g., EPROM, EEPROM, and flash memory devices; magnetic disks, e.g., internal hard disks or removable disks; magneto optical disks; and CD ROM and DVD-ROM disks. The processor and the memory may be supplemented by, or incorporated in, special purpose logic circuitry.

(48) To provide for interaction with a user, implementations may be realized on a computer having a display device, e.g., a CRT (cathode ray tube) or LCD (liquid crystal display) monitor, for displaying information to the user and a keyboard and a pointing device, e.g., a mouse or a trackball, by which the user may provide input to the computer. Other kinds of devices may be used to provide for interaction with a user as well; for example, feedback provided to the user may be any appropriate form of sensory feedback, e.g., visual feedback, auditory feedback, or tactile feedback; and input from the user may be received in any appropriate form, including acoustic, speech, or tactile input.

(49) Implementations may be realized in a computing system that includes a back end component, e.g., as a data server, or that includes a middleware component, e.g., an application server, or that includes a front end component, e.g., a client computer having a graphical user interface or a web browser through which a user may interact with an implementation, or any appropriate combination of one or more such back end, middleware, or front end components. The components of the system may be interconnected by any appropriate form or medium of digital data communication, e.g., a communication network. Examples of communication networks include a local area network ("LAN") and a wide area network ("WAN"), e.g., the Internet.

(50) The computing system may include clients and servers. A client and server are generally remote from each other and typically interact through a communication network. The relationship of client and server arises by virtue of computer programs running on the respective computers and having a client-server relationship to each other.

(51) While this specification contains many specifics, these should not be construed as limitations on the scope of the disclosure or of what may be claimed, but rather as descriptions of features specific to particular implementations. Certain features that are described in this specification in the context of separate implementations may also be implemented in combination in a single implementation. Conversely, various features that are described in the context of a single implementation may also be implemented in multiple implementations separately or in any suitable sub-combination. Moreover, although features may be described above as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination may in some examples be excised from the combination, and the claimed combination may be directed to a sub-combination or variation of a sub-combination.

(52) Similarly, while operations are depicted in the drawings in a particular order, this should not be understood as requiring that such operations be performed in the particular order shown or in sequential order, or that all illustrated operations be performed, to achieve desirable results. In certain circumstances, multitasking and parallel processing may be advantageous. Moreover, the separation of various system components in the implementations described above should not be understood as requiring such separation in all implementations, and it should be understood that the described program components and systems may generally be integrated together in a single software product or packaged into multiple software products.

(53) A number of implementations have been described. Nevertheless, it will be understood that various modifications may be made without departing from the spirit and scope of the disclosure. For example, various forms of the flows shown above may be used, with steps re-ordered, added, or removed. Accordingly, other implementations are within the scope of the following claims.

Claims

1. A method comprising: detecting, by a user device associated with a user account, at least one wireless communication from a chip associated with a payment card with an inactive status, wherein the at least one wireless communication is transmitted from a radio-frequency transmitter included in the payment card or a container for the payment card; sending, to a card activation system, a request for activation of the payment card, wherein the request includes at least one of a card identifier or an account identifier from the at least one wireless communication from the radio-frequency transmitter; and in response to a verification that the card identifier or the account identifier is associated with the user account, receiving, by the user device, a card activation notification associated with the payment card, and presenting, in a user interface of the user device, a card activation workflow in an application executing on the user interface, wherein use of the card activation workflow causes transitioning of the payment card from the inactive status to an active status.
2. The method of claim 1, further comprising: sending, via the application on the user device, a communication to a card service associated with the payment card to request transition of the payment card from the inactive status to the active status; and receiving, by the user device, a notification from the card service indicating that the payment card is in the active status.
3. The method of claim 1, further comprising: receiving login credentials at the user device prior to detecting the at least one wireless communication.
4. The method of claim 1, further comprising: sending a status request to a card service executing remotely from the user device, wherein the status request is based on the at least one wireless communication, wherein a status of the payment card is provided by the card service in response to the status request.
5. The method of claim 1, wherein the at least one wireless communication indicates that the payment card is being activated for a first time, and wherein the card activation workflow is a new card activation workflow.
6. The method of claim 1, wherein the at least one wireless communication is received from the payment card or a container of the payment card, wherein the at least one wireless communication includes metadata associated with the user account.
7. A system comprising: one or more processors; and one or more memories storing instructions that, when executed by the one or more processors, cause the system to perform a process comprising: detecting, by a user device associated with a user account, at least one wireless communication from a chip associated with a payment card with an inactive status, wherein the at least one wireless communication is transmitted from a radio-frequency transmitter included in the payment card or a container for the payment card; sending, to a card activation system, a request for activation of the payment card, wherein the request includes at least one of a card identifier or an account identifier from the at least one wireless communication from the radio-frequency transmitter; and in response to a verification that the card identifier or the account identifier is associated with the user account, receiving, by the user device, a card activation notification associated with the payment card, and presenting, in a user interface of the user device, a card activation workflow in an application executing on the user interface, wherein use of the card activation workflow causes transitioning of the payment card from the inactive status to an active status.
8. The system according to claim 7, wherein the process further comprises: sending, via the

application on the user device, a communication to a card service associated with the payment card to request transition of the payment card from the inactive status to the active status; and receiving, by the user device, a notification from the card service indicating that the payment card is in the active status.

9. The system according to claim 7, wherein the process further comprises: receiving login credentials at the user device prior to detecting the at least one wireless communication.

10. The system according to claim 7, wherein the process further comprises: sending a status request to a card service executing remotely from the user device, wherein the status request is based on the at least one wireless communication, wherein a status of the payment card is provided by the card service in response to the status request.

11. The system according to claim 7, wherein the at least one wireless communication indicates that the payment card is being activated for a first time, and wherein the card activation workflow is a new card activation workflow.

12. The system according to claim 7, wherein the at least one wireless communication is received from the payment card or a container of the payment card, wherein the at least one wireless communication includes metadata associated with the user account.

13. A non-transitory computer-readable medium storing instructions that, when executed by a computing system, cause the computing system to perform operations comprising: detecting, by a user device associated with a user account, at least one wireless communication from a chip associated with a payment card with an inactive status, wherein the at least one wireless communication is transmitted from a radio-frequency transmitter included in the payment card or a container for the payment card; sending, to a card activation system, a request for activation of the payment card, wherein the request includes at least one of a card identifier or an account identifier from the at least one wireless communication from the radio-frequency transmitter; and in response to a verification that the card identifier or the account identifier is associated with the user account, receiving, by the user device, a card activation notification associated with the payment card, and presenting, in a user interface of the user device, a card activation workflow in an application executing on the user interface, wherein use of the card activation workflow causes transitioning of the payment card from the inactive status to an active status.

14. The non-transitory computer-readable medium of claim 13, wherein the operations further comprise: sending, via the application on the user device, a communication to a card service associated with the payment card to request transition of the payment card from the inactive status to the active status; and receiving, by the user device, a notification from the card service indicating that the payment card is in the active status.

15. The non-transitory computer-readable medium of claim 13, wherein the operations further comprise: receiving login credentials at the user device prior to detecting the at least one wireless communication.

16. The non-transitory computer-readable medium of claim 13, wherein the operations further comprise: sending a status request to a card service executing remotely from the user device, wherein the status request is based on the at least one wireless communication, wherein a status of the payment card is provided by the card service in response to the status request.

17. The non-transitory computer-readable medium of claim 13, wherein the at least one wireless communication indicates that the payment card is being activated for a first time, and wherein the card activation workflow is a new card activation workflow.
