

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396745
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Song; Youngjae et al.

Surgery instrument

Abstract

The present disclosure relates to an end tool of a surgical instrument, and more particularly, to an end tool of a surgical instrument capable of being mounted on a robot arm or operated manually for use in laparoscopic surgery or various surgeries, the multi-joint type surgical device capable of independently and smoothly performing a pitch motion and a yaw motion/actuation motion by compensating for jaw wire movement that occurs during the pitch motion.

Inventors: Song; Youngjae (Seongnam-si, KR), Lee; Jaeyeong (Seongnam-si, KR), Lee; Jung Joo (Seongnam-si, KR), Kim; Heejin (Seongnam-si, KR), Jang; Dongkyu (Seongnam-si, KR)

Applicant: LIVSMED INC. (Seongnam-si, KR)

Family ID: 1000008780019

Assignee: LIVSMED INC. (Seongnam-si, KR)

Appl. No.: 18/757036

Filed: June 27, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240350160 A1	Oct. 24, 2024

Foreign Application Priority Data

KR	10-2021-0191880	Dec. 29, 2021
----	-----------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/KR2022/021631 20221229 PENDING child-doc US 18757036

Publication Classification

Int. Cl.: **A61B17/29** (20060101); **A61B34/30** (20160101); **A61B34/37** (20160101); A61B17/00 (20060101)

U.S. Cl.:

CPC **A61B17/29** (20130101); **A61B34/37** (20160201); A61B2017/00199 (20130101); A61B2017/00212 (20130101); A61B2017/00398 (20130101); A61B2017/00477 (20130101); A61B2017/2903 (20130101); A61B2017/2929 (20130101); A61B2017/294 (20130101); A61B2017/2944 (20130101); A61B2034/302 (20160201); A61B2034/305 (20160201)

Field of Classification Search

CPC: A61B (34/71); A61B (34/70); A61B (34/30); A61B (34/37); A61B (2034/305); A61B (2017/00477)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6331181	12/2000	Tierney et al.	N/A	N/A
6783524	12/2003	Anderson et al.	N/A	N/A
2002/0111621	12/2001	Wallace et al.	N/A	N/A
2006/0079889	12/2005	Scott	N/A	N/A
2014/0350570	12/2013	Lee	N/A	N/A
2017/0172553	12/2016	Chaplin	N/A	A61B 34/30
2019/0328467	12/2018	Waterbury	N/A	A61B 34/30
2020/0305992	12/2019	Schuh et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
112043394	12/2019	CN	N/A
112617968	12/2020	CN	N/A
2004-301275	12/2003	JP	N/A
2011-200593	12/2010	JP	N/A
2018-538065	12/2017	JP	N/A
2021-153858	12/2020	JP	N/A
10-2308205	12/2020	KR	N/A
2022/231337	12/2021	WO	N/A

Primary Examiner: Schwiker; Katherine H

Attorney, Agent or Firm: Bridgeway IP Law Group, PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a continuation application of International Application No. PCT/KR2022/021631, filed on Dec. 29, 2022, and claims priority to Korean Application No. 10-2021-0191880, filed on Dec. 29, 2021, in the Korean Intellectual Property Office, the entire disclosures of which are incorporated herein by reference.

TECHNICAL FIELD

(1) The present disclosure relates to a surgical instrument, and more particularly, to a surgical instrument capable of being mounted on a robot arm or operated manually for use in laparoscopic surgery or various surgeries.

BACKGROUND ART

(2) Medically, surgery refers to the treatment of diseases by cutting, slitting, or manipulating the skin, mucous membranes, or other tissues using medical devices. In particular, open surgery in which the skin of the surgical site is incised and opened to treat, shape, remove organs or the like therein and the like cause problems such as bleeding, side effects, patient pain, scarring.

Accordingly, recently, surgery performed by inserting only a medical device, for example, laparoscopic surgical instrument, microsurgical microscope, and the like by forming a predetermined hole in the skin or surgery using a robot has been spotlighted as an alternative.

(3) Here, a surgical robot refers to a robot that has a function of replacing a surgical action performed by a surgeon. Advantageously, the surgical robot may operate more accurately and precisely as compared with a human and enable remote operation.

(4) Surgical robots that are currently being developed worldwide may include a bone surgical robot, a laparoscopic surgical robot, a stereotactic surgical robot, and the like. Here, the laparoscopic surgical robot is a robot that performs minimum invasive surgery using a laparoscope and small surgical instruments.

(5) Laparoscopic surgery is a cutting-edge surgery technique that involves perforating one or more small holes in the abdomen and inserting a laparoscope, which is an endoscope for looking inside the abdomen to perform the surgery, and is a field that is expected to advance in the future. Today's laparoscopes are mounted with computer chips and have been developed to the extent that magnified images, which are clearer than images seen with the naked eye, can be obtained and when used with specially-designed laparoscopic surgical tools while looking at a monitor screen, any type of surgery is possible.

(6) Moreover, laparoscopic surgery offers the same range of surgical procedures as open surgery, but with several advantages including fewer complications, the ability to initiate treatment shortly after the procedure, and the capability to maintain the patient's stamina and immune functions. As a result, laparoscopic surgery is becoming increasingly recognized as the standard surgery for treating colorectal cancer or the like in places such as the United States and Europe.

(7) Meanwhile, a surgical robot is generally composed of a master robot and a slave robot. When a surgical operator manipulates a control lever (e.g., a handle) equipped on the master robot, a surgical tool coupled to or held by a robot arm on the slave robot may be manipulated to perform surgery.

DESCRIPTION OF EMBODIMENTS

Technical Problem

(8) The present disclosure is directed to providing a multi-joint type surgical device capable of being mounted on a robot arm or operated manually for use in laparoscopic surgery or various surgeries, the multi-joint type surgical device capable of independently and smoothly performing a pitch motion and a yaw motion/actuation motion by compensating for jaw wire movement that occurs during the pitch motion.

Technical Solution to Problem

(9) One aspect of the present disclosure provides a surgical instrument comprising: an end tool including one or more jaws, and an end tool jaw pulley coupled to the jaws and formed to be

rotatable together with the jaws around a first shaft, the end tool being formed to allow at least a pitch rotation and a yaw rotation; a jaw wire coupled to the end tool jaw pulley and moved in response to rotation of the end tool jaw pulley; a connection part formed to extend in one direction, having the jaw wire passing therethrough, and having one end portion to which the end tool is coupled; and a driving part coupled to another end portion of the connection part and configured to control the pitch rotation and the yaw rotation of the end tool, wherein the driving part includes: a driving part jaw pulley formed to be rotatable around a second shaft and coupled to the jaw wire; and a driving part pitch pulley disposed adjacent to the driving part jaw pulley and formed to be rotatable around a third shaft different from the second shaft, and when the driving part pitch pulley is rotated for the pitch rotation of the end tool, the driving part jaw pulley is also rotated.

(10) In an embodiment of the present disclosure, a relative position of the driving part pitch pulley and the driving part jaw pulley remains constant.

(11) In an embodiment of the present disclosure, when the driving part pitch pulley is rotated around the third shaft, the driving part jaw pulley is rotated around the second shaft to change a length of the jaw wire in the driving part.

(12) In an embodiment of the present disclosure, as the length of the jaw wire in the driving part is changed due to the rotation of the driving part jaw pulley, a length of the jaw wire in the end tool is changed.

(13) In an embodiment of the present disclosure, even when the length of the jaw wire in the driving part is changed due to the rotation of the driving part jaw pulley, an overall length of the jaw wire remains constant.

(14) In an embodiment of the present disclosure, the jaws include a first jaw and a second jaw formed to face the first jaw, the end tool jaw pulley includes a first jaw pulley coupled to the first jaw and formed to be rotatable around the first shaft, and a second jaw pulley coupled to the second jaw and formed to be rotatable around a shaft substantially equal to or parallel to the first shaft and to face the first jaw pulley, the jaw wire includes a first jaw wire coupled to the first jaw pulley to rotate the first jaw pulley, and a second jaw wire coupled to the second jaw pulley to rotate the second jaw pulley, and the driving part jaw pulley includes a driving part first jaw pulley coupled to the first jaw wire to move the first jaw wire, and a driving part second jaw pulley coupled to the second jaw wire to move the second jaw wire.

(15) In an embodiment of the present disclosure, the end tool includes: a pair of first jaw pitch main pulleys formed on one side of the first jaw pulley and formed to be rotatable around a fourth shaft that forms a predetermined angle with the first shaft; a pair of second jaw pitch main pulleys formed on one side of the second jaw pulley and formed to be rotatable around a shaft substantially equal to or parallel to the fourth shaft; a first jaw pitch redundant pulley disposed between the first jaw pulley and the pair of first jaw pitch main pulleys and formed to be rotatable around a fifth shaft; and a second jaw pitch redundant pulley disposed between the second jaw pulley and the pair of second jaw pitch main pulleys and formed to be rotatable around a sixth shaft, wherein the first jaw wire is wound around at least some of the pair of first jaw pitch main pulleys, and the second jaw wire is wound around at least some of the pair of second jaw pitch main pulleys.

(16) In an embodiment of the present disclosure, while moving from a proximal end of the end tool toward a distal end of the end tool, of two strands of the first jaw wire coupled to the first jaw pulley, one strand of the first jaw wire is wound in one direction of a clockwise direction and a counterclockwise direction around the first jaw pitch main pulley, and another strand of the first jaw wire is wound in another direction of the clockwise direction and the counterclockwise direction around the first jaw pitch main pulley.

(17) In an embodiment of the present disclosure, based on a plane perpendicular to the first shaft and passing between the first jaw pulley and the second jaw pulley, of two strands of the first jaw wire coupled to the first jaw pulley, one strand of the first jaw wire comes into contact with an upper side of the first jaw pitch main pulley, and another strand of the first jaw wire comes into

contact with a lower side of the first jaw pitch main pulley.

(18) In an embodiment of the present disclosure, while moving from a proximal end of the end tool toward a distal end of the end tool, the first jaw wire sequentially comes into contact with the first jaw pitch main pulley and the first jaw pitch redundant pulley.

(19) In an embodiment of the present disclosure, based on a plane perpendicular to the first shaft and passing between the first jaw pulley and the second jaw pulley, of two strands of the first jaw wire coupled to the first jaw pulley, one strand of the first jaw wire sequentially comes into contact with a lower side of the first jaw pitch main pulley and a lower side of the first jaw pitch redundant pulley, and of the two strands of the first jaw wire coupled to the first jaw pulley, another strand of the first jaw wire sequentially comes into contact with an upper side of the first jaw pitch main pulley and an upper side of the first jaw pitch redundant pulley.

(20) In an embodiment of the present disclosure, a first jaw auxiliary pulley formed between the first jaw pulley and the first jaw pitch redundant pulley; and a second jaw auxiliary pulley formed between the second jaw pulley and the second jaw pitch redundant pulley.

(21) In an embodiment of the present disclosure, the first jaw wire is located on a common internal tangent of the first jaw pulley and the first jaw auxiliary pulley, and a rotation angle of the first jaw pulley is increased by the first jaw auxiliary pulley.

(22) In an embodiment of the present disclosure, further comprising: one or more first jaw pitch sub-pulleys formed on one side of the first jaw pitch main pulley and formed to be rotatable around a shaft substantially parallel to the fourth shaft; and one or more second jaw pitch sub-pulleys formed on one side of the second jaw pitch main pulley and formed to be rotatable around a shaft substantially parallel to the fourth shaft.

(23) In an embodiment of the present disclosure, the first jaw pitch sub-pulley or the second jaw pitch sub-pulley includes only one pulley.

(24) In an embodiment of the present disclosure, further comprising: an end tool hub formed to internally accommodate at least some of the first jaw and the second jaw; and a pitch hub formed to be rotatable relative to the end tool hub by being axially coupled to the end tool hub.

(25) In an embodiment of the present disclosure, the first jaw and the second jaw are rotated around the first shaft to perform a yaw motion, and the end tool hub is rotated around the fourth shaft to perform a pitch motion.

(26) In an embodiment of the present disclosure, further comprising: an end tool pitch pulley formed on an end portion of the end tool hub at a proximal end side; and a pitch wire coupled to the end tool pitch pulley to rotate the end tool pitch pulley.

(27) In an embodiment of the present disclosure, when the end tool pitch pulley is rotated by the pitch wire, the end tool hub is rotated as a whole together with the end tool pitch pulley to change a length of the first jaw wire wound around the first jaw pitch main pulley and the second jaw pitch main pulley.

(28) In an embodiment of the present disclosure, when the end tool pitch pulley is rotated by the pitch wire, the first jaw wire is moved to a certain degree by an external force in order to compensate for an amount of change in the length by which the first jaw wire is wound around the first jaw pitch main pulley and the second jaw pitch main pulley.

(29) In an embodiment of the present disclosure, the first jaw pitch redundant pulley or the second jaw pitch redundant pulley is integrally formed with the end tool hub.

(30) In an embodiment of the present disclosure, the fifth shaft and the sixth shaft are substantially parallel to the fourth shaft.

(31) In an embodiment of the present disclosure, the fifth shaft and the sixth shaft are formed to be inclined with respect to the first shaft and the fourth shaft, respectively.

(32) In an embodiment of the present disclosure, a groove of the first jaw pulley around which the first jaw wire is wound and a groove of the second jaw pulley around which the second jaw wire is wound are formed to be spaced apart from each other by a certain degree.

(33) In an embodiment of the present disclosure, a groove of the first jaw pulley around which the first jaw wire is wound and a groove of the second jaw pulley around which the second jaw wire is wound are formed to be adjacent to each other.

(34) In an embodiment of the present disclosure, the first jaw pitch redundant pulley or the second jaw pitch redundant pulley includes only one pulley.

(35) In an embodiment of the present disclosure, when the driving part pitch pulley of the driving part is rotated for a pitch motion, a driving part first jaw pulley and a driving part second jaw pulley of the driving part are rotated together to compensate for the pitch motion.

(36) In an embodiment of the present disclosure, an end tool hub formed to internally accommodate at least some of the first jaw and the second jaw; a pitch hub formed to be rotatable relative to the end tool hub by being axially coupled to the end tool hub; a first pin formed to be inserted through the end tool hub, and formed to extend in a first direction; a second pin inserted through the end tool hub, formed to be parallel to the first pin, and formed on one side of the first pin; a 2.5th pin inserted through the end tool hub, formed to extend in a second direction forming a predetermined angle with the first direction, and formed on one side of the second pin; a third pin inserted through the end tool hub and the pitch hub, formed to be parallel to the 2.5th pin, and formed on one side of the 2.5th pin; a fourth pin inserted through the pitch hub, formed to be parallel to the third pin, and formed on one side of the third pin; a first jaw auxiliary pulley formed on one side of the first jaw pulley, and formed to be rotatable around the second pin; a second jaw auxiliary pulley formed on one side of the second jaw pulley, and formed to be rotatable around the second pin; one or more first jaw pitch redundant pulleys formed on one side of the first jaw auxiliary pulley, and formed to be rotatable around the 2.5th pin; one or more second jaw pitch redundant pulleys formed on one side of the second jaw auxiliary pulley, and formed to be rotatable around the 2.5th pin; a pair of first jaw pitch main pulleys formed on one side of the first jaw pitch redundant pulley, and formed to be rotatable around the third pin; a pair of second jaw pitch main pulleys formed on one side of the second jaw pitch redundant pulley, and formed to be rotatable around the third pin; one or more first jaw pitch sub-pulleys formed on one side of the first jaw pitch main pulley, and formed to be rotatable around the fourth pin; and one or more second jaw pitch sub-pulleys formed on one side of the second jaw pitch main pulley, and formed to be rotatable around the fourth pin.

(37) In an embodiment of the present disclosure, an end tool hub formed to internally accommodate at least some of the first jaw and the second jaw; a pitch hub formed to be rotatable relative to the end tool hub by being axially coupled to the end tool hub; a first pin formed to be inserted through the end tool hub, and formed to extend in a first direction; a second pin inserted through the end tool hub, formed to extend in a second direction forming a predetermined angle with the first direction, and formed on one side of the first pin; a third pin inserted through the end tool hub and the pitch hub, formed to extend in a third direction forming a predetermined angle with the first direction and the second direction, and formed on one side of the second pin; a fourth pin inserted through the pitch hub, formed to be parallel to the third pin, and formed on one side of the third pin; a first jaw auxiliary pulley formed on one side of the first jaw pulley, and formed to be rotatable around the second pin; a second jaw auxiliary pulley formed on one side of the second jaw pulley, and formed to be rotatable around the second pin; a pair of first jaw pitch main pulleys formed on one side of the first jaw auxiliary pulley, and formed to be rotatable around the third pin; a pair of second jaw pitch main pulleys formed on one side of the second jaw auxiliary pulley, and formed to be rotatable around the third pin; one or more first jaw pitch sub-pulleys formed on one side of the first jaw pitch main pulley, and formed to be rotatable around the fourth pin; and one or more second jaw pitch sub-pulleys formed on one side of the second jaw pitch main pulley, and formed to be rotatable around the fourth pin.

Advantageous Effects of Disclosure

(38) According to the present disclosure, a pitch motion and a yaw motion/actuation motion can be

smoothly performed independently by compensating for jaw wire movement occurring during the pitch motion.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a conceptual view illustrating a surgical robot system to which a surgical instrument according to an embodiment of the present disclosure is mounted.
- (2) FIG. 2 is a block diagram illustrating an internal configuration of the surgical robot system of FIG. 1.
- (3) FIG. 3 is a perspective view illustrating a slave robot of the surgical robot system of FIG. 1.
- (4) FIG. 4 is a perspective view illustrating a surgical instrument mounted to the slave robot of FIG. 1.
- (5) FIGS. 5 and 6 are perspective views illustrating an end tool of a surgical instrument according to a first embodiment of the present disclosure.
- (6) FIGS. 7 and 8 are plan views of the end tool of FIG. 5.
- (7) FIGS. 9 and 10 are plan views of the end tool of FIG. 5.
- (8) FIG. 11 is a perspective view of the end tool of FIG. 5.
- (9) FIG. 12 is a perspective view of an end tool hub of the end tool of FIG. 5.
- (10) FIG. 13 is a perspective view illustrating a state in which the end tool of the surgical instrument of FIG. 5 is pitch-rotated by -90° .
- (11) FIG. 14 is a side view illustrating a state in which the end tool of the surgical instrument of FIG. 5 is pitch-rotated by $+90^{\circ}$.
- (12) FIG. 15 is a perspective view illustrating a state in which the end tool of the surgical instrument of FIG. 5 is yaw-rotated by $+90^{\circ}$.
- (13) FIG. 16 is a side view illustrating a state in which the end tool of the surgical instrument of FIG. 5 is yaw-rotated by -90° .
- (14) FIG. 17 is a perspective view of a driving part of the surgical instrument of FIG. 4.
- (15) FIG. 18 is a plan view of the driving part of the surgical instrument of FIG. 17.
- (16) FIG. 19 is a rear view of the driving part of the surgical instrument of FIG. 17.
- (17) FIG. 20 is a side view of the driving part of the surgical instrument of FIG. 17.
- (18) FIG. 21 is a view illustrating the configuration of pulleys and wires of the surgical instrument of FIG. 17 in detail.
- (19) FIGS. 22 and 23 are views illustrating the surgical instrument of FIG. 17 in a neutral state.
- (20) FIGS. 24, 25, 26A, and 26B are views illustrating the surgical instrument of FIG. 17 when pitch compensation is not performed.
- (21) FIGS. 27, 28, 29A, and 29B are views illustrating the surgical instrument shown in FIG. 17 when pitch compensation is performed.
- (22) FIG. 30 is a view illustrating a neutral state of a surgical instrument according to a comparative example of the present disclosure.
- (23) FIGS. 31, 32, and 33 are views illustrating the surgical instrument of FIG. 30 when pitch compensation is performed.
- (24) FIGS. 34 and 35 are perspective views illustrating an end tool of a surgical instrument according to a first modified example of the first embodiment of the present disclosure.
- (25) FIG. 36 is a plan view of the end tool of FIG. 34.
- (26) FIGS. 37 and 38 are plan views of the end tool of FIG. 34.
- (27) FIG. 39 is a perspective view of the end tool of FIG. 34.
- (28) FIG. 40 is a perspective view of an end tool hub of the end tool of FIG. 34.
- (29) FIGS. 41 and 42 are perspective views illustrating an end tool of a surgical instrument

according to a second modified example of the first embodiment of the present disclosure.

(30) FIG. **43** is a plan view of the end tool of FIG. **41**.

(31) FIGS. **44** and **45** are perspective views illustrating an end tool of a surgical instrument according to a third modified example of the first embodiment of the present disclosure.

(32) FIG. **46** is a coupled perspective view illustrating a second jaw of the end tool of FIG. **44**.

(33) FIG. **47** is an exploded perspective view illustrating the second jaw of the end tool of FIG. **44**.

(34) FIG. **48** is a coupled perspective view illustrating a first jaw of the end tool of FIG. **44**.

(35) FIG. **49** is an exploded perspective view illustrating the first jaw of the end tool of FIG. **44**.

(36) FIGS. **50** and **51** are perspective views illustrating an end tool hub of FIG. **44**.

(37) FIG. **52** is a plan view of the end tool of FIG. **44**.

(38) FIGS. **53** and **54** are side views of the end tool of FIG. **44**.

(39) FIGS. **55** and **56** are perspective views illustrating an end tool of a surgical instrument according to a fourth modified example of the first embodiment of the present disclosure.

(40) FIGS. **57** and **58** are plan views of the end tool of FIG. **55**.

(41) FIGS. **59**, **60**, and **61** are side views of the end tool of FIG. **55**.

(42) FIGS. **62** and **63** are plan views of the end tool of FIG. **55**.

(43) FIGS. **64** and **65** are perspective views illustrating an end tool of a surgical instrument according to a fifth modified example of the first embodiment of the present disclosure.

(44) FIG. **66** is a plan view of the end tool of FIG. **64**.

(45) FIG. **67** is a perspective view of an end tool hub of the end tool of FIG. **64**.

(46) FIG. **68** is a side view of the end tool of FIG. **64**.

(47) FIG. **69** is a perspective view illustrating a state in which the end tool of the surgical instrument of FIG. **64** is pitch-rotated by -90° .

(48) FIG. **70** is a side view illustrating a state in which the end tool of the surgical instrument of FIG. **64** is pitch-rotated by $+90^\circ$.

(49) FIG. **71** is a perspective view illustrating a state in which the end tool of the surgical instrument of FIG. **64** is yaw-rotated by $+90^\circ$.

(50) FIG. **72** is a side view illustrating a state in which the end tool of the surgical instrument of FIG. **64** is yaw-rotated by -90° .

(51) FIGS. **73** and **74** are perspective views illustrating an end tool of a surgical instrument according to a second embodiment of the present disclosure.

(52) FIGS. **75**, **76**, **77**, and **78** are plan views of the end tool of FIG. **73**.

(53) FIGS. **79**, **80**, and **81** are side views of the end tool of FIG. **73**.

(54) FIGS. **82** and **83** are perspective views illustrating an end tool of a surgical instrument according to a first modified example of the second embodiment of the present disclosure.

(55) FIGS. **84** and **85** are plan views of the end tool of FIG. **82**.

(56) FIGS. **86**, **87**, and **88** are side views of the end tool of FIG. **82**.

(57) FIGS. **89** and **90** are plan views of the end tool of FIG. **82**.

(58) FIGS. **91**, **92**, **93**, and **94** are perspective views illustrating an end tool of a surgical instrument according to a third embodiment of the present disclosure.

(59) FIGS. **95** and **96** are plan views of the end tool of FIG. **91**.

(60) FIGS. **97**, **98**, and **99** are side views of the end tool of FIG. **91**.

(61) FIGS. **100** and **101** are plan views of the end tool of FIG. **91**.

(62) FIG. **102** is a perspective view of an end tool hub of the end tool of FIG. **91**.

(63) FIG. **103** is a front view of the end tool hub of the end tool of FIG. **91**.

(64) FIG. **104** is a side view of the end tool hub of the end tool of FIG. **91**.

MODE OF DISCLOSURE

(65) While the present disclosure is susceptible to various modifications and alternative forms, specific embodiments thereof are shown by way of example in the drawings and will herein be described in detail. However, it should be understood that there is no intent to limit the present

disclosure to the particular forms disclosed herein, rather, the present disclosure should be construed to cover various modifications, equivalents, and alternatives of embodiments of the present disclosure. In describing the present disclosure, a detailed description of known related arts will be omitted when it is determined that the gist of the present disclosure may be unnecessarily obscured

(66) Although terms such as “first”, “second”, and the like may be used to describe various components, such components should not be limited to the above terms. The terms are only used to distinguish one component from another.

(67) The terms used herein are for the purpose of describing particular embodiments only and are not intended to be limiting to the present disclosure. Singular forms are intended to include plural forms as well, unless the context clearly indicates otherwise. In the present application, it will be further understood that the terms “comprise”, “comprising”, “include”, and/or “including”, when used in this specification, specify the presence of stated features, integers, steps, operations, elements, components and/or groups thereof but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components and/or groups thereof.

(68) Hereinafter, the embodiments of the present disclosure will be described below in detail with reference to the accompanying drawings, and when the embodiments of the present disclosure are described with reference to the drawings, the same or corresponding components are given the same reference numerals, and repetitive descriptions thereof will be omitted.

(69) Further, in describing the various embodiments of the present disclosure, it is to be understood that each embodiment is not intended to be interpreted or implemented independently, and that the technical ideas described in each embodiment may be interpreted or implemented in combination with other embodiments described separately.

(70) FIG. 1 is a conceptual diagram illustrating a surgical robot system to which a multi-joint type surgical device according to an embodiment of the present disclosure is mounted, FIG. 2 is a block diagram illustrating an internal configuration of the surgical robot system of FIG. 1, and FIG. 3 is a perspective view illustrating a slave robot of the surgical robot system of FIG. 1 and the multi-joint type surgical device mounted thereto.

(71) Referring to FIGS. 1 to 3, a surgical robot system 1 includes a master robot 10, a slave robot 20, and a multi-joint type surgical device 30.

(72) The master robot 10 includes manipulating members 10a and a display member 10b, and the slave robot 20 includes one or more robot arm units 21, 22, and 23.

(73) In detail, the master robot 10 includes the manipulating members 10a so that a surgical operator can grip and manipulate them respectively with both hands. The manipulating members 10a may be implemented as two or more handles as illustrated in FIG. 1, and manipulation signals according to the handle manipulation of the surgical operator are transmitted to the slave robot 20 through a wired or wireless communication network so that the robot arm units 21, 22, and 23 are controlled. That is, surgical motions such as positioning, rotation, and cutting operations of the robot arm units 21, 22, and 23 may be performed by the handle manipulation of the surgical operator.

(74) For example, the surgical operator may manipulate the robot arm units 21, 22, and 23 using manipulation levers in the form of a handle. The manipulation lever as described above may have various mechanical configurations according to the manipulate method thereof, and may be provided in various configurations for operating the robot arm units 21, 22, and 23 of the slave robot 20 and/or other surgical instruments, such as a master handle manipulating the motion of each of the robot arm units 21, 22, and 23 and various input tools added to the master robot 10 for manipulating the functions of the entire system such as joystick, keypad, trackball, foot pedal, and touch screen. Here, the manipulating member 10a is not limited to the shape of a handle and can be applied without any limitation as long as it can control motions of the robot arm units 21, 22, and 23 through a network such as a wired or wireless communication network.

(75) Alternatively, a voice input or a motion input may also be applied for user input. That is, a user may wear, on the head thereof, glasses or a head mount display (HMD), to which a sensor is attached, and a laparoscope **50** may move according to a direction in which the user's gaze. Alternatively, when the user issues a command with voice, such as "left", "right", "first arm", "second arm", and the like, the voice command may be recognized and the motion may be performed.

(76) An image captured through the laparoscope **50** to be described later is displayed as a screen image on the display member **10b** of the master robot **10**. In addition, a predetermined virtual manipulation plate may be displayed independently or displayed together with the image captured by the laparoscope **50** on the display member **10b**. A detailed description of the arrangement, configuration, and the like of such a virtual manipulation plate will be omitted.

(77) Here, the display member **10b** may include one or more monitors, each of which may individually display information necessary for surgery. The quantity of monitors may be variously determined depending on the type or kind of information that needs to be displayed.

(78) Meanwhile, the slave robot **20** may include one or more robot arm units **21**, **22**, and **23**. Here, each of the robot arm units **21**, **22**, and **23** may be provided in the form of a module that can operate independently of each other, and in this case, an algorithm for preventing a collision between the robot arm units **21**, **22**, and **23** may be applied to the surgical robot system **1**.

(79) In general, a robot arm refers to a device having a function similar to that of the arm and/or the wrist of a human being and having a wrist portion to which a predetermined tool may be attached. In the present specification, the robot arm units **21**, **22**, and **23** may each be defined as a concept encompassing all of the components such as an upper arm, a lower arm, a wrist, and an elbow, a multi-joint type surgical device coupled to the wrist portion, and the like. Alternatively, the robot arm unit may also be defined as a concept that includes only components for driving the multi-joint type surgical device, excluding the multi-joint type surgical device coupled to the wrist portion.

(80) The robot arm units **21**, **22**, and **23** of the slave robot **20** described above may be implemented to be driven with multiple degrees of freedom. The robot arm units **21**, **22**, and **23** may include, for example, a surgical instrument inserted into a surgical site of a patient, a yaw driving part for rotating the surgical instrument in a yaw direction according to a surgical position, a pitch driving part for rotating the surgical instrument in a pitch direction perpendicular to a rotational driving of the yaw driving part, a transfer driving part for moving the surgical instrument in a length direction, a rotation driving part for rotating the surgical instrument, and a surgical instrument driving part for incising or cutting the surgical lesion by driving an end effector at an end of the surgical instrument. However, the configuration of the robot arm units **21**, **22**, and **23** is not limited thereto, and it should be understood that this example does not limit the scope of the present disclosure. Here, a detailed description of the actual control process, such as rotation and movement of the robot arm units **21**, **22**, and **23** in a corresponding direction by the surgical operator manipulating the manipulating member **10a** will be omitted.

(81) Here, two of the robot arm units **21**, **22**, and **23** may have the multi-joint type surgical device **30** attached thereto, and one of the robot arm units **21**, **22**, and **23** may have the laparoscope **50** attached thereto. In addition, the surgical operator may select the robot arm unit **21**, **22**, or **23** to be controlled via the master robot **10**. As described above, by directly controlling a total of three or more surgical instruments through the master robot **10**, the surgical operator may accurately and freely control various tools according to the intention of the surgical operator without a surgical assistant.

(82) Meanwhile, one or more slave robots **20** may be provided to operate the patient, and the laparoscope **50** for allowing a surgical site to be displayed as a screen image through the display member **10b** may be implemented as an independent slave robot **20**. In addition, as described above, the embodiments of the present disclosure can be used universally for surgeries in which various surgical endoscopes other than laparoscopes (e.g., thoracoscopic, arthroscopic, rhinoscopic,

and the like) are used.

(83) Referring to FIG. 2, in an embodiment of the present disclosure, the master robot **10** may include an image input part **11**, a screen display part **12**, a user input part **13**, a manipulation signal generation part **14**, a control part **15**, a memory **16**, a storage part **17**, and a communication part **18**.

(84) The image input part **11** may receive an image captured by a camera provided in the laparoscope **50** of the slave robot **20** through a wired or wireless communication network.

(85) The screen display part **12** outputs a screen image corresponding to the image received through the image input part **11** as visual information. In addition, the screen display part **12** may further output information corresponding to biometric information of a subject to be treated, when the biometric information is input. In addition, the screen display part **12** may further output image data (e.g., an X-ray image, a CT image, an MRI image, or the like) associated with a patient for a surgical site. Here, the screen display part **12** may be implemented in the form of a display member (see **10b** of FIG. 1), and an image processing process for allowing the received image to be output as a screen image through the screen display part **12** may be performed by the control part **15**.

(86) In the embodiment illustrated in FIG. 2, the image input part and the screen display part are illustrated as being included in the master robot **10**, but the present disclosure is not limited thereto. That is, the display member may be provided as a separate member spaced apart from the master robot **10**. Alternatively, the display member may be provided as one component of the master robot **10**. In addition, in another embodiment, a plurality of display members may be provided, one of which may be disposed adjacent to the master robot **10**, and others thereof may be disposed at some distance from the master robot **10**.

(87) Here, the screen display part **12** (that is, the display member **10b** of FIG. 1) may be provided as a three-dimensional display device. In detail, the three-dimensional display device refers to an image display device in which depth information is added to a two-dimensional image by applying a stereoscopic technique, and this depth information is used to enable an observer to feel a three-dimensional living feeling and a sense of reality. The surgical robot system **1** according to an embodiment of the present disclosure may provide a more realistic virtual environment to a user by including a three-dimensional display device as the screen display part **12**.

(88) The user input part **13** is a member for allowing the surgical operator to manipulate the positions and functions of the robot arm units **21**, **22**, and **23** of the slave robot **20**. The user input part **13** may be formed in the form of a handle-shaped manipulation member (see **10a** of FIG. 1) as illustrated in FIG. 1, but the shape thereof is not limited thereto and may be implemented by being modified in various shapes to achieve the same purpose. In addition, for example, some of the user input part **13** may be formed in the shape of a handle, and the others may be formed in a different shape, such as a clutch button. In addition, a finger insertion tube or insertion ring may be further formed so as to allow the surgical operator's finger to be inserted therethrough and fixed to facilitate manipulation of the surgical tool.

(89) When the surgical operator manipulates the user input part **13** to move the positions of robot arm units **21**, **22**, and **23** or manipulate surgical operations thereof, the manipulation signal generation part **14** may generate a corresponding manipulation signal, and transmit the manipulation signal to the slave robot **20** through the communication part **18**. The manipulation signal may be transmitted and received via a wired or wireless communication network.

(90) The control part **15** is a kind of central processing device, and controls the operation of each component so that the above-described functions can be performed. In an example, the control part **15** may perform a function of converting an image input through the image input part **11** into a screen image to be displayed through the screen display part **12**.

(91) The memory **16** may perform a function of temporarily or permanently storing data processed by the control part **15**. Here, the memory **16** may include a magnetic storage medium or a flash storage medium, but the scope of the present disclosure is not limited thereto.

(92) The storage part **17** may store data received from the slave robot **20**. In addition, the storage

part **17** may store various pieces of input data (e.g., patient data, device data, surgery data, and the like).

(93) The communication part **18** interworks with a communication network **60** to provide a communication interface necessary for transmitting and receiving image data transmitted from the slave robot **20** and control data transmitted from the master robot **10**.

(94) The slave robot **20** includes a plurality of robot arm unit control parts **21a**, **22a**, and **23a**. In addition, the robot arm unit control part **21a** includes a robot arm control part **26**, an instrument control part **27**, and a communication part **29**. In addition, the robot arm unit control part **21a** may further include a rail control part **28**.

(95) The robot arm control part **26** may receive a manipulation signal generated by the manipulation signal generation part **14** of the master robot **10**, and may serve to control the robot arm units **21**, **22**, and **23** so as to operate according to the manipulation signal.

(96) The instrument control part **27** may receive a manipulation signal generated by the manipulation signal generation part **14** of the master robot **10**, and may serve to control the multi-joint type surgical device **30** so as to operate according to the manipulation signal.

(97) The communication part **29** interworks with the communication network **60** to provide a communication interface necessary for transmitting and receiving image data transmitted from the slave robot **20** and control data transmitted from the master robot **10**.

(98) Meanwhile, the communication network **60** serves to connect the master robot **10** and the slave robot **20**. That is, the communication network **60** refers to a communication network for providing an access path so that data can be transmitted and received between the master robot **10** and the slave robot **20** after the master robot **10** and the slave robot **20** are connected. The communication network **60** may be, for example, a wired network such as local area networks (LANs), wired area networks (WANs), metropolitan area networks (MANs), and integrated service digital networks (ISDNs), or a wireless network such as wireless LANs, code division multiple access (CDMA), Bluetooth, and satellite communication, but the scope of the present disclosure is not limited thereto.

(99) Continuing to refer to FIG. **4**, the surgical instrument **30** of the surgical robot system **1** may include an end tool **100**, a driving part **200**, and a connection part **400**.

(100) Here, the connection part **400** is formed in the shape of a hollow shaft, in which one or more wires (to be described later) may be accommodated, and may have one end portion to which the driving part **200** is coupled and another end portion to which the end tool **100** is coupled and serve to connect the driving part **200** and the end tool **100**.

(101) The driving part **200** is formed at one end portion of the connection part **400** and provides an interface capable of being coupled to the robot arm units **21**, **22**, and **23**. Accordingly, when a user operates the master robot **10**, a motor (not shown) of the robot arm units **21**, **22**, and **23** is operated so that the end tool **100** of the surgical instrument **30** can perform a motion corresponding thereto, and a driving force of the motor (not shown) is transmitted to the end tool **100** through the driving part **200**. In other words, it may be described that the driving part **200** itself becomes an interface that connects between the surgical instrument **30** and the slave robot **20**.

(102) The end tool **100** is formed on another end portion of the connection part **400**, and performs necessary motions for surgery by being inserted into a surgical site. The end tool **100** will be described in more detail later with reference to FIG. **5**.

(103) The surgical instrument according to an embodiment of the present disclosure may be provided in the surgical instrument of the surgical robot system shown in FIGS. **1** to **4**.

(104) Hereinafter, the surgical instrument that may be provided in the surgical robot system will be described in more detail.

(105) <First Embodiment of Surgical Instrument>

(106) FIGS. **5** and **6** are perspective views illustrating an end tool of a surgical instrument according to a first embodiment of the present disclosure. FIGS. **7** and **8** are plan views of the end

tool of FIG. 5. FIGS. 9 and 10 are plan views of the end tool of FIG. 5. FIG. 11 is a side perspective view of the end tool of FIG. 5. FIG. 12 is a perspective view of an end tool hub of the end tool of FIG. 5.

(107) In addition, FIG. 13 is a perspective view illustrating a state in which the end tool of the surgical instrument of FIG. 5 is pitch-rotated by -90° . FIG. 14 is a side view illustrating a state in which the end tool of the surgical instrument of FIG. 5 is pitch-rotated by $+90^\circ$. In addition, FIG. 15 is a perspective view illustrating a state in which the end tool of the surgical instrument of FIG. 5 is yaw-rotated by $+90^\circ$. FIG. 16 is a side view illustrating a state in which the end tool of the surgical instrument of FIG. 5 is yaw-rotated by -90° .

(108) Here, FIG. 6 illustrates a state in which an end tool hub 106 and a pitch hub 107 are removed from the end tool of FIG. 5, and FIG. 8 illustrates a state in which the end tool hub 106 and the pitch hub 107 are removed from the end tool of FIG. 7. In addition, FIG. 9 is a view illustrating the end tool of FIG. 5, with a focus on wires, and FIG. 10 is a view illustrating the end tool of FIG. 5, with a focus on pulleys. In addition, FIG. 11A illustrates a state in which the end tool hub 106 and the pitch hub 107 are mounted, FIG. 11B illustrates a path of a wire 301 in a state in which the end tool hub 106 and the pitch hub 107 are removed, and FIG. 11C illustrates a path of a wire 305 in the state in which the end tool hub 106 and the pitch hub 107 are removed.

(109) As described above with reference to FIGS. 1 to 4, a surgical instrument (see 30 of FIG. 4) according to the first embodiment of the present disclosure may include the end tool 100, a driving part (see 200 of FIG. 4), the power transmission part 300, and the connection part 400.

(110) Referring to FIGS. 5 to 16, the end tool 100 is formed at an end portion of the connection part 400 and performs necessary motions for surgery by being inserted into a surgical site. As an example of the above-described end tool 100, as shown in FIG. 5, a pair of jaws 101 and 102 for performing a grip motion may be used. However, the concept of the present disclosure is not limited thereto, and various devices for performing surgery may be used as the end tool 100. For example, a configuration such as a one-armed cautery may also be used as the end tool. The above-described end tool 100 is connected to the driving part (see 200 of FIG. 4) by the power transmission part 300 and receives a driving force of the driving part (see 200 of FIG. 4) through the power transmission part 300 to perform motions necessary for surgery, such as a gripping motion, a cutting motion, a suturing motion, or the like.

(111) Here, the end tool 100 of the surgical instrument 30 according to the first embodiment of the present disclosure is formed to be rotatable in at least two or more directions, for example, the end tool 100 may be formed to perform a pitch motion around a rotation shaft 143 of FIG. 5 and simultaneously perform a yaw motion and an actuation motion around a rotation shaft 141 of FIG. 5.

(112) Here, each of the pitch, yaw, and actuation motions used in the present disclosure are defined as follows.

(113) First, the pitch motion means a motion of the end tool 100 rotating in a vertical direction with respect to an extension direction of the connection part 400 (an X-axis direction of FIG. 5), that is, a motion rotating around a Y-axis of FIG. 5. In other words, the pitch motion means a motion of the end tool 100, which is formed to extend from the connection part 400, rotating vertically around the Y-axis with respect to the connection part 400.

(114) Next, the yaw motion means a motion of the end tool 100 rotating in the left and right directions, that is, a motion rotating around the Z-axis of FIG. 5, with respect to the extension direction of the connection part 400 (the X-axis direction of FIG. 5). In other words, the yaw motion means a motion of the end tool 100, which is formed to extend from the connection part 400, rotating horizontally around the Z-axis with respect to the connection part 400. That is, the yaw motion means rotating motions of two jaws 101 and 102, which are formed on the end tool 100, around the Z-axis in the same direction.

(115) Meanwhile, the actuation motion means a motion of the end tool 100 rotating around the

same rotation shaft as that of the yaw motion, while the two jaws **101** and **102** rotate in the opposite directions so as to be closed or opened. That is, the actuation motion means rotating motions of the two jaws **101** and **102**, which are formed on the end tool **100**, in the opposite directions around the Z-axis.

(116) Defining this from another perspective, the yaw rotation may be defined as a motion in which a jaw pulley to be described later is rotated around the rotation shaft **141**, which is a jaw pulley rotation shaft, and the pitch rotation may be defined as a motion in which the jaw pulley revolves around the rotation shaft **143**, which is a pitch main rotation shaft.

(117) The power transmission part **300** may connect the driving part (see **200** of FIG. **4**) to the end tool **100**, transmit the driving force from the driving part (see **200** of FIG. **4**) to the end tool **100**, and include a plurality of wires, pulleys, links, sections, gears, or the like.

(118) Hereinafter, the power transmission part **300** and the end tool **100** including the same will be described in more detail.

(119) (Power Transmission Part)

(120) Hereinafter, the power transmission part **300** of the end tool of the surgical instrument of FIG. **5** will be described in more detail.

(121) Referring to FIGS. **5**, **6**, and **10** and the like, the power transmission part **300** of the end tool **100** of the surgical instrument according to an embodiment of the present disclosure may include the wire **301**, a wire **302**, a wire **303**, a wire **304**, the wire **305**, and a wire **306**.

(122) Here, the wire **301** and the wire **305** may be paired to serve as first jaw wires. The wire **302** and the wire **306** may be paired to serve as second jaw wires. Here, the components encompassing the wire **301** and the wire **305**, which are first jaw wires, and the wire **302** and the wire **306**, which are second jaw wires, may be referred to as jaw wires. In addition, the wire **303** and the wire **304** may be paired to serve as pitch wires.

(123) Here, in the drawings, a pair of wires are illustrated as being associated with a rotational motion of a first jaw **101**, and a pair of wires are illustrated as being associated with a rotational motion of a second jaw **102**, but the concept of the present disclosure is not limited thereto. For example, a pair of wires may be associated with a yaw motion, and a pair of wires may be associated with an actuation motion.

(124) In addition, the power transmission part **300** of the surgical instrument according to an embodiment of the present disclosure may include a coupling member **321**, a coupling member **322**, a coupling member **323**, a coupling member **324**, a coupling member **325**, a coupling member **326**, a coupling member **327**, a coupling member **328**, a coupling member **329**, a coupling member **330**, and the like, which are coupled to respective end portions of wires to couple the wires to pulleys. Here, each of the coupling members may have various shapes as necessary, such as a ball shape, a tube shape, and the like.

(125) Here, the coupling member **321**, which is a pitch wire coupling member, may be coupled to the end portion of the wire **303**, which is a pitch wire, at the end tool **100** side, the coupling member **322**, which is a pitch wire coupling member, may be coupled to the end portion of the wire **304**, which is a pitch wire, at the end tool **100** side, and the coupling member **321** and the coupling member **322** may serve as pitch wire-end tool coupling members. Meanwhile, the coupling member **329**, which is a pitch wire-driving part coupling member, may be coupled to the end portion of the wire **303**, which is a pitch wire, at the driving part side (see **200** of FIG. **4**), and the coupling member **330**, which is a pitch wire-driving part coupling member, may be coupled to the end portion of the wire **304** at the driving part side (see **200** of FIG. **4**).

(126) Meanwhile, the coupling member **323**, which is a first jaw wire coupling member, may be coupled to the end portions of the wires **301** and **305**, which are first jaw wires, at the end tool **100** side to serve as a first jaw wire-end tool coupling member. Meanwhile, the coupling member **324**, which is a first jaw wire-driving part coupling member, may be coupled to the end portion of the wire **301**, which is a first jaw wire, at the driving part side (see **200** of FIG. **4**), and the coupling

member **325**, which is a first jaw wire-driving part coupling member, may be coupled to the end portion of the wire **305** at the driving part side (see **200** of FIG. **4**).

(127) Meanwhile, the coupling member **326**, which is a second jaw wire coupling member, may be coupled to the end portions of the wires **302** and **306**, which are second jaw wires, at the end tool **100** side to serve as a second jaw wire-end tool coupling member. Meanwhile, the coupling member **327**, which is a second jaw wire-driving part coupling member, may be coupled to the end portion of the wire **302**, which is a second jaw wire, at the driving part side (see **200** of FIG. **4**), and the coupling member **328**, which is a second jaw wire-driving part coupling member, may be coupled to the end portion of the wire **306** at the driving part side (see **200** of FIG. **4**).

(128) Here, each of the coupling members is classified as being included in the power transmission part **300**, but the coupling members may be classified such that the coupling member at the end tool **100** side may be included in the end tool **100**, and the coupling member at the driving part side (see **200** of FIG. **4**) may be included in the driving part (see **200** of FIG. **4**).

(129) The coupling relationship between the wires, the coupling members, and the respectively pulleys will be described in detail as follows.

(130) First, the wires **302** and **306**, which are second jaw wires, may be a single wire. The coupling member **326**, which is a second jaw wire-end tool coupling member, is inserted at an intermediate point of the second jaw wire, which is a single wire, and the coupling member **326** is crimped and fixed, and then, both strands of the second jaw wire centered on the coupling member **326** may be referred to as the wire **302** and the wire **306**, respectively.

(131) Alternatively, the wires **302** and **306**, which are second jaw wires, may also be formed as separate wires, and connected to each other by the coupling member **326**.

(132) In addition, by coupling the coupling member **326** to a pulley **121**, the wires **302** and **306** may be fixedly coupled to the pulley **121**. This allows the pulley **121** to rotate as the wires **302** and **306** are pulled and released.

(133) Meanwhile, the coupling member **327**, which is a second jaw wire-driving part coupling member, may be coupled to the end portion of the wire **302**, which is opposite to the end portion of the wire **302** to which the coupling member **326** is coupled, and the coupling member **328**, which is a second jaw wire-driving part coupling member may be coupled to the end portion of the wire **306**, which is opposite to the end portion of the wire **302** to which the coupling member **326** is coupled.

(134) In addition, by coupling the coupling member **327**, which is a second jaw wire-driving part coupling member coupled to the wire **302**, to a pulley **221**, and coupling the coupling member **328**, which is a second jaw wire-driving part coupling member coupled to the wire **306**, to a pulley **222**, the wire **302** and the wire **306** may be fixedly coupled to the pulley **221** and the pulley **222**, respectively. As a result, when the pulley **221** and the pulley **222** are rotated by a motor or a human force, the pulley **121** of the end tool **100** may be rotated as the wire **302** and the wire **306** are pulled or released.

(135) Here, as shown in the drawings, the driving part second jaw pulley may include two pulleys of the pulley **221** and the pulley **222**, the second jaw wire-driving part coupling member may also include the coupling member **327** and the coupling member **328**, the wire **302** may be coupled to the coupling member **327**, and the wire **306** may be coupled to the coupling member **328**.

Alternatively, although not shown in the drawings, the driving part second jaw pulley may include one pulley, the second jaw wire-driving part coupling member may also include one coupling member, and the wire **302** and the wire **306** may be coupled to one coupling member to be coupled to one driving part second jaw pulley.

(136) In the same manner, the wire **301**, which is a first jaw wire, is coupled to the first jaw wire-end tool coupling member **323** and the first jaw wire-driving part coupling member **324**, and the wire **305** is coupled to the first jaw wire-end tool coupling member **323** and the first jaw wire-driving part coupling member **325**. In addition, the first jaw wire-end tool coupling member **323** is

coupled to a pulley **111**, the first jaw wire-driving part coupling member **324** is coupled to a pulley **211**, and the first jaw wire-driving part coupling member **325** is coupled to a pulley **212**. As a result, when the pulley **211** and the pulley **212** are rotated by a motor or a human force, the pulley **111** of the end tool **100** may be rotated as the wire **301** and the wire **305** are pulled and released.

(137) In the same manner, one end portion of the wire **303**, which is a pitch wire, may be coupled to the coupling member **321**, which is a pitch wire-end tool coupling member, and one end portion of the wire **304**, which is a pitch wire, may be coupled the coupling member **322**, which is a pitch wire-end tool coupling member. In addition, another end portion of the wire **303** may be coupled to the coupling member **329**, which is a pitch wire-driving part coupling member, and another end portion of the wire **304** may be coupled to the coupling member **330**, which is a pitch wire-driving part coupling member. In addition, the coupling member **321** and the coupling member **322** are each coupled to the pulley **131**, and the coupling member **329** and the coupling member **330** are respectively coupled to the pulley **231**/pulley **232** that are driving part pitch pulleys. As a result, when the pulley **231**/pulley **232**, which is a driving part pitch pulley, is rotated by a motor or a human force, the pulley **131** of the end tool **100** may be rotated as the wire **303** and the wire **304** are pulled and released.

(138) As a result, the wire **301** and the wire **305**, which are both strands of the first jaw wire, are coupled to the coupling member **323**, which is a first jaw wire-end tool coupling member, and the coupling member **324**/coupling member **325**, which is a first jaw wire-driving part coupling member, to function as a closed loop as a whole. Similarly, the second jaw wire and the pitch wire may each be formed to function as a closed loop.

(139) (End Tool)

(140) Hereinafter, the end tool **100** of the surgical instrument of FIG. 5 will be described in more detail.

(141) Continuing to refer to FIGS. 5 to 16, the end tool **100** of the first embodiment of the present disclosure includes a pair of jaws for performing a grip motion, that is, the first jaw **101** and the second jaw **102**. Here, each of the first jaw **101** and the second jaw **102**, or a component encompassing the first jaw **101** and the second jaw **102** may be referred to as a jaw **103**.

(142) Further, the end tool **100** may include the pulley **111**, a pulley **112**, a pulley **113**, a pulley **114**, a pulley **115**, and a pulley **118** that are related to a rotational motion of the first jaw **101**. In addition, the end tool **100** may include the pulley **121**, a pulley **122**, a pulley **123**, a pulley **124**, a pulley **125**, and a pulley **128** that are related to a rotational motion of the second jaw **102**.

(143) Here, in the drawings, one group of pulleys is illustrated as being associated with a rotational motion of the first jaw **101**, and one group of pulleys is illustrated as being associated with a rotational motion of the second jaw **102**, but the concept of the present disclosure is not limited thereto. For example, one group of pulleys in the end tool may be associated with a yaw motion, and one group of pulleys in the end tool may be associated with an actuation motion. Here, the pulleys included in the end tool **100**, including the pulleys described above, may be collectively referred to as end tool pulleys.

(144) Here, the pulleys facing each other are illustrated in the drawings as being formed parallel to each other, but the concept of the present disclosure is not limited thereto, and each of the pulleys may be variously formed with a position and a size suitable for the configuration of the end tool.

(145) Further, the end tool **100** of the first embodiment of the present disclosure may include the end tool hub **106** and the pitch hub **107**.

(146) The rotation shaft **141**, a rotation shaft **142**, and a rotation shaft **145**, which will be described later, are inserted through the end tool hub **106**. In addition, the end tool hub **106** may internally accommodate at least some of the pulley **111** and the pulley **121** that are axially coupled to the rotation shaft **141**. In addition, the end tool hub **106** may internally accommodate at least some of the pulley **112** and the pulley **122** that are axially coupled to the rotation shaft **142**. In addition, the pulley **118** and the pulley **128**, which are axially coupled to the rotation shaft **145**, may be coupled

to the end tool hub **106**.

(147) In detail, referring to FIG. **12** or the like, the end tool hub **106** includes the first jaw pulley coupling part **106a**, the second jaw pulley coupling part **106b**, a guide part **106c**, a pitch redundant pulley accommodation part **106d**, and a pitch pulley coupling part **106e**.

(148) In detail, the first jaw pulley coupling part **106a** and the second jaw pulley coupling part **106b** are formed to face each other, and the pulley **111** and the pulley **121** are accommodated therein. In addition, a through hole is formed in each of the first jaw pulley coupling part **106a** and the second jaw pulley coupling part **106b** such that the rotation shaft **141** passes through and axially couples the first jaw pulley coupling part **106a**, the pulley **111**, the pulley **121**, and the second jaw pulley coupling part **106b**. In addition, the rotation shaft **142** passes through and axially couples the first jaw pulley coupling part **106a**, the pulley **112**, the pulley **122**, and the second jaw pulley coupling part **106b**.

(149) The first jaw pulley coupling part **106a** and the second jaw pulley coupling part **106b** are connected to each other by the guide part **106c**. That is, the first jaw pulley coupling part **106a** and the second jaw pulley coupling part **106b** parallel to each other are coupled to each other by the guide part **106c** formed in a direction substantially perpendicular thereto, so that the first jaw pulley coupling part **106a**, the second jaw pulley coupling part **106b**, and the guide part **106c** form a substantially “C-shape,” in which the pulley **111**, the pulley **112**, the pulley **121**, and the pulley **122** are accommodated.

(150) Here, the pulley **111**, which is a first jaw pulley, is disposed close to the first jaw pulley coupling part **106a** of the end tool hub **106**, and the pulley **121**, which is a second jaw pulley, is disposed close to the second jaw pulley coupling part **106b** of the end tool hub **106**, and thus a predetermined space may be formed between the wire **301**/wire **305**, which is a first jaw wire, and the wire **302**/wire **306**, which is a second jaw wire.

(151) Meanwhile, the pitch redundant pulley accommodation part **106d** may be formed on the guide part **106c** of the end tool hub **106** at the proximal end side. In addition, the pulley **118** and the pulley **128**, which are pitch redundant pulleys, may be accommodated in the pitch redundant pulley accommodation part **106d**, and these pitch redundant pulleys may be axially coupled to the end tool hub **106** by the rotation shaft **145**.

(152) Meanwhile, the pulley **131** serving as an end tool pitch pulley may be formed on the pitch pulley coupling part **106e** at one end portion of the end tool hub **106**. Here, the pulley **131** may be integrally formed with the end tool hub **106** as one body. That is, one end portion of the end tool hub **106** may be formed in a disk shape or a semi-circular shape, and a groove around which a wire may be wound may be formed on an outer circumferential surface of the end tool hub **106**, thereby forming a kind of guide channel. Alternatively, the pulley **131** may be formed as a separate member from the end tool hub **106** to be coupled to the end tool hub **106**. The wires **303** and **304** described above are coupled to the pulley **131** serving as an end tool pitch pulley, and a pitch motion is performed as the pulley **131** is rotated around the rotation shaft **143**.

(153) The rotation shaft **143** and a rotation shaft **144**, which will be described later, may be inserted through the pitch hub **107**, and the pitch hub **107** may be axially coupled to the end tool hub **106** and the pulley **131** by the rotation shaft **143**. Thus, the end tool hub **106** and the pulley **131** (coupled thereto) may be formed to be rotatable around the rotation shaft **143** with respect to the pitch hub **107**.

(154) Further, the pitch hub **107** may internally accommodate at least some of the pulley **113**, the pulley **114**, the pulley **123**, and the pulley **124** that are axially coupled to the rotation shaft **143**. In addition, the pitch hub **107** may internally accommodate at least some of the pulley **115** and the pulley **125** that are axially coupled to the rotation shaft **144**.

(155) Further, the end tool **100** of the first embodiment of the present disclosure may include the rotation shaft **141**, the rotation shaft **142**, the rotation shaft **145**, the rotation shaft **143**, and the rotation shaft **144**. As described above, the rotation shaft **141** and the rotation shaft **142** may be

inserted through the end tool hub **106**, and the rotation shaft **143** and the rotation shaft **144** may be inserted through the pitch hub **107**.

(156) The rotation shaft **141**, the rotation shaft **142**, the rotation shaft **145**, the rotation shaft **143**, and the rotation shaft **144** may be arranged sequentially from a distal end **104** of the end tool **100** toward a proximal end **105**. Accordingly, starting from the distal end **104**, the rotation shaft **141** may be referred to as a first pin, the rotation shaft **142** may be referred to as a second pin, the rotation shaft **145** may be referred to as a 2.5th pin, the rotation shaft **143** may be referred to as a third pin, and the rotation shaft **144** may be referred to as a fourth pin.

(157) Here, the rotation shaft **141** may function as a jaw pulley rotation shaft, the rotation shaft **142** may function as a jaw auxiliary pulley rotation shaft, the rotation shaft **143** may function as a pitch main rotation shaft, and the rotation shaft **144** may function as a pitch-serve rotation shaft of the end tool **100**. In addition, the rotation shaft **145** disposed between the rotation shaft **142** and the rotation shaft **143** may function as a pitch redundant rotation shaft of the end tool **100**.

(158) Each of the rotation shafts **141**, **142**, **143**, **144**, and **145** may be fitted into one or more pulleys, which will be described in detail later.

(159) The pulley **111** functions as a first jaw pulley, and the pulley **121** functions as a second jaw pulley, and these two components may be collectively referred to as jaw pulleys.

(160) The pulley **111** and the pulley **121**, which are jaw pulleys, are formed to face each other, and are formed to be rotatable independently of each other around the rotation shaft **141**, which is a jaw pulley rotation shaft. Here, in the drawings, it is illustrated that the pulley **111** and the pulley **121** are formed to rotate around one rotation shaft **141**, but it is of course possible that each jaw pulley may be formed to be rotatable around a separate shaft. Here, the first jaw **101** may be fixedly coupled to the pulley **111** and rotated together with the pulley **111**, and the second jaw **102** may be fixedly coupled to the pulley **121** and rotated together with the pulley **121**. Yaw and actuation motions of the end tool **100** are performed in response to the rotation the pulley **111** and the pulley **121**. That is, when the pulley **111** and the pulley **121** are rotated in the same direction around the rotation shaft **141**, the yaw motion is performed, and when the pulley **111** and the pulley **121** are rotated in opposite directions around the rotation shaft **141**, the actuation motion is performed.

(161) Here, the first jaw **101** and the pulley **111** may be formed as separate members and coupled to each other, or the first jaw **101** and the pulley **111** may be integrally formed as one body. Similarly, the second jaw **102** and the pulley **121** may be formed as separate members and coupled to each other, or the second jaw **102** and the pulley **121** may be integrally formed as one body.

(162) Here, a groove **111a** around which the wire **301**/wire **305**, which is a first wire, is wound is disposed in the pulley **111**, which is a first jaw pulley, to be adjacent to the first jaw pulley coupling part **106a** of the end tool hub **106**, and a groove **121a** around which the wire **302**/wire **306**, which is a second wire, is wound is disposed in the pulley **121**, which is a second jaw pulley, to be adjacent to the first jaw pulley coupling part **106a** of the end tool hub **106**. Accordingly, a predetermined space may be formed between the wire **301**/wire **305**, which is a first jaw wire, and the wire **302**/wire **306**, which is the second jaw wire. As described above, by disposing the wire **301**/wire **305**, which is a first jaw wire, and the wire **302**/wire **306**, which is a second jaw wire, to be spaced apart from each other, the wires may be wound around the respective pulleys while maintaining a straight line.

(163) The pulley **112** functions as a first jaw auxiliary pulley, and the pulley **122** functions as a second jaw auxiliary pulley, and these two components may be collectively referred to as jaw auxiliary pulleys.

(164) In detail, the pulley **112** and the pulley **122**, which are jaw auxiliary pulleys, may be additionally provided on one side of the pulley **111** and one side of the pulley **121**, respectively. In other words, the pulley **112**, which is a jaw auxiliary pulley, may be disposed between the pulley **111** and the pulley **113**/pulley **114**. In addition, the pulley **122**, which is a jaw auxiliary pulley, may be disposed between the pulley **121** and the pulley **123**/pulley **124**. The pulley **112** and the pulley

122 may be formed to be rotatable independently of each other around the rotation shaft **142**. Here, in the drawings, it is illustrated that the pulley **112** and the pulley **122** are formed to rotate around one rotation shaft **142**, but it is of course possible that each of the pulley **112** and the pulley **122** may be formed to be rotatable around a separate shaft. Such auxiliary pulleys will be described in more detail later.

(165) The pulley **113** and the pulley **114** function as first jaw pitch main pulleys, and the pulley **123** and the pulley **124** function as second jaw pitch main pulleys, and these two components may be collectively referred to as pitch main pulleys.

(166) The pulley **115** functions as a first jaw pitch sub-pulley, and the pulley **125** functions as a second jaw pitch sub-pulley, and these two components may be collectively referred to as pitch sub-pulleys.

(167) Meanwhile, in the present disclosure, the pulley **118** and the pulley **128**, which are pitch redundant pulleys, are further disposed between the pulleys **112** and **122**, which are jaw auxiliary pulleys, and the pulleys **113**, **114**, **123**, and **124**, which are pitch main pulleys.

(168) The pulley **118** functions as a first jaw pitch redundant pulley, and the pulley **128** functions as a second jaw pitch redundant pulley, and these two components may be collectively referred to as pitch redundant pulleys.

(169) In addition, the rotation shaft **145** functioning as a pitch redundant rotation shaft may be further provided, and the rotation shaft **145** may be inserted through the end tool hub **106**. Here, the rotation shaft **145** may be formed to be substantially parallel to the rotation shaft **143**, which is a pitch main rotation shaft, and the rotation shaft **144**, which is a pitch-serve rotation shaft. In this case, the rotation shaft **145** is disposed between the rotation shaft **142**, which is a second pin, and the rotation shaft **143**, which is a third pin, and thus may be referred to as a 2.5th pin due to a position thereof.

(170) Such a pitch redundant pulley may serve to change an entry/exit path of the jaw wire, through which the jaw wire enters from the proximal end of the end tool to the distal end or exits from the distal end to the proximal end. This will be described in more detail later.

(171) As a result, the rotation shaft **141**, the rotation shaft **142**, the rotation shaft **145**, the rotation shaft **143**, and the rotation shaft **144** may be arranged sequentially from the distal end **104** of the end tool **100** toward the proximal end **105**.

(172) In addition, the pulley **111**, the pulley **112**, the pulley **118**, the pulley **113**/pulley **114**, and the pulley **115**, which are pulleys associated with the rotation of the first jaw **101**, may be arranged sequentially from the distal end **104** of the end tool **100** toward the proximal end **105**.

(173) In addition, the pulley **121**, the pulley **122**, the pulley **128**, the pulley **123**/pulley **124**, and the pulley **125**, which are pulleys associated with the rotation of the second jaw **102**, may be arranged sequentially from the distal end **104** of the end tool **100** toward the proximal end **105**.

(174) Hereinafter, the pulley **112** and the pulley **122** serving as auxiliary pulleys will be described in more detail.

(175) The pulley **112** and the pulley **122** may serve to enlarge rotation angles of the first jaw **101** and the second jaw **102**, respectively, by coming into contact with the wire **305**, which is a first jaw wire, and the wire **302**, which is a second jaw wire, to change the arrangement path of the wires **305** and **302** to a certain extent.

(176) That is, when the auxiliary pulleys are not disposed, each of the first jaw and the second jaw may be rotated up to a right angle, but in an embodiment of the present disclosure, the pulley **112** and the pulley **122**, which are auxiliary pulleys, are additionally provided, so that the maximum rotation angle may be increased by θ as shown in FIG. **10**. This enables a motion of the two jaws of the end tool **120** being opened for an actuation motion while the two jaws are yaw-rotated by 90° in an L direction. This is because the second jaw **102** is rotated by the additional angle θ as shown in FIG. **10**. Similarly, an actuation motion is possible even when the two jaws are yaw-rotated in an R direction. In other words, a feature of increasing the range of a yaw rotation in which the actuation

motion is possible may be obtained through the pulley **112** and the pulley **122**.

(177) This will be described below in more detail.

(178) When the auxiliary pulleys are not disposed, since the first jaw wire is fixedly coupled to the first jaw pulley, and the second jaw wire is fixedly coupled to the second jaw pulley, each of the first jaw pulley and the second jaw pulley may be rotated up to 90°. In this case, when the actuation motion is performed while the first jaw and the second jaw are located at a 90° line, the first jaw may be spread, but the second jaw may not be rotated beyond 90°. Accordingly, when the first jaw and the second jaw perform a yaw motion over a certain angle, there was a problem that the actuation motion is not smoothly performed.

(179) In order to address such a problem, in the end tool **100** of the surgical instrument of the present disclosure, the pulley **112** and the pulley **122**, which are auxiliary pulleys, are additionally disposed on one side of the pulley **111** and one side of the pulley **121**, respectively. As described above, as the arrangement paths of the wire **305**, which is a first jaw wire, and the wire **302**, which is a second jaw wire, are changed to a certain extent by disposing the pulley **112** and the pulley **122**, a tangential direction of the wires **305** and **302** is changed, and accordingly, the coupling member **326** for coupling the wire **302** and the pulley **121** may be rotated up to a line N of FIG. **10**. That is, the coupling member **326**, which is a coupling part of the wire **302** and the pulley **121**, is rotatable until the coupling member **326** is located on a common internal tangent of the pulley **121** and the pulley **122**. Similarly, the coupling member **323**, which is a coupling part of the wire **305** and the pulley **111**, is rotatable until the coupling member **323** is located on a common internal tangent of the pulley **111** and the pulley **112**, so that the range of rotation in the L direction may be increased.

(180) In other words, due to the pulley **112**, the wires **301** and **305**, which are two strands of the first jaw wire wound around the pulley **111**, are disposed on one side with respect to a plane perpendicular to the Y-axis and passing through the X-axis. Simultaneously, due to the pulley **122**, the wires **302** and **306**, which are two strands of the second jaw wire wound around the pulley **121**, are disposed at another side with respect to the plane perpendicular to the Y-axis and passing through the X-axis.

(181) In other words, the pulley **113** and the pulley **114** are disposed on one side with respect to the plane perpendicular to the Y-axis and passing through the X-axis, and the pulley **123** and the pulley **124** are disposed at another side with respect to the plane perpendicular to the Y-axis and passing through the X-axis.

(182) In other words, the wire **305** is located on the internal tangent of the pulley **111** and the pulley **112**, and the rotation angle of the pulley **111** is increased by the pulley **112**. In addition, the wire **302** is located on the internal tangent of the pulley **121** and the pulley **122**, and a rotation angle of the pulley **121** is increased by the pulley **122**.

(183) As the rotation radii of the jaw **101** and the jaw **102** increase as described above according to the present disclosure, an effect of increasing a yaw motion range over which a normal opening/closing actuation motion is performed may be obtained.

(184) Hereinafter, components related to the rotation of the pulley **111** will be described.

(185) The pulley **113** and the pulley **114** are paired to function as first jaw pitch main pulleys. That is, the pulley **113** and the pulley **114** function as main rotation pulleys for a pitch motion of the first jaw **101**. Here, the wire **301**, which is a first jaw wire, is wound around the pulley **113**, and the wire **305**, which is a first jaw wire, is wound around the pulley **114**.

(186) The pulley **115** functions as a first jaw pitch sub-pulley. That is, the pulley **115** functions as a sub rotation pulley for a pitch motion of the first jaw **101**. Here, the wire **301**, which is a first jaw wire, is wound around the pulley **115**.

(187) The pulley **118** functions as a first jaw redundant pulley. That is, the pulley **118** function as a redundant rotation pulley for a pitch motion of the first jaw **101**. Here, the wire **305**, which is a first jaw wire, is wound around the pulley **118**.

(188) Here, the pulley **118** is disposed on one side of the pulley **111** and the pulley **112**. Here, the pulley **118** is formed to be rotatable around the rotation shaft **145**, which is a pitch redundant rotation shaft. Further, the pulley **113** and the pulley **114** are disposed on one side of the pulley **118** to face each other. Here, the pulley **113** and the pulley **114** are formed to be rotatable independently of each other around the rotation shaft **143** that is a pitch main rotation shaft. In addition, the pulley **115** are disposed on one side of each of the pulley **113** and the pulley **114**. Here, the pulley **115** is formed to be rotatable around the rotation shaft **144**, which is a pitch-serve rotation shaft. Here, in the drawings, it is illustrated that the pulley **118**, the pulley **113**, the pulley **114**, and the pulley **115** are all formed to be rotatable around the Y-axis direction, but the concept of the present disclosure is not limited thereto, and the rotation shafts of the respective pulleys may be formed in various directions according to configurations thereof.

(189) The wire **301**, which is a first jaw wire, is sequentially wound to make contact with at least portions of the pulley **115**, the pulley **113**, and the pulley **111**. In addition, the wire **305** connected to the wire **301** by the coupling member **323** is sequentially wound to make contact with at least portions of the pulley **111**, the pulley **112**, the pulley **118**, and the pulley **114**.

(190) In other words, the wire **301** and the wire **305**, which are first jaw wires, are sequentially wound to make contact with at least portions of the pulley **115**, the pulley **113**, the pulley **111**, the pulley **112**, the pulley **118**, and the pulley **114** and are formed to move along the above pulleys while rotating the above pulleys.

(191) Accordingly, when the wire **301** is pulled in the direction of an arrow **301** of FIG. 9, a coupling member **323** to which the wire **301** is coupled and the pulley **111** coupled to the coupling member **323** are rotated in an arrow L direction of FIG. 9. In contrast, when the wire **305** is pulled in the direction of an arrow **305** of FIG. 9, the coupling member **323** to which the wire **305** is coupled and the pulley **111** coupled to the coupling member **323** are rotated in an arrow R direction of FIG. 9.

(192) Next, components related to the rotation of the pulley **121** will be described.

(193) The pulley **123** and the pulley **124** are paired to function as second jaw pitch main pulleys. That is, the second jaw **102** functions as a main rotation pulley for a pitch motion of the second jaw **102**. Here, the wire **306**, which is a second jaw wire, is wound around the pulley **123**, and the wire **302**, which is a second jaw wire, is wound around the pulley **124**.

(194) The pulley **125** functions as a second jaw pitch sub-pulley. That is, the pulley **125** functions as a sub rotation pulley for a pitch motion of the second jaw **102**. Here, the wire **306**, which is a second jaw wire, is wound around the pulley **125**.

(195) The pulley **128** functions as a second jaw pitch redundant pulley. That is, the pulley **128** functions as a redundant rotation pulley for a pitch motion of the second jaw **102**. Here, the wire **302**, which is a second jaw wire, is wound around the pulley **128**.

(196) Here, the pulley **128** is disposed on one side of the pulley **121** and the pulley **122**. Here, the pulley **128** is formed to be rotatable around the rotation shaft **145**, which is a pitch redundant rotation shaft. Further, the pulley **123** and the pulley **124** are disposed on one side of the pulley **128** to face each other. Here, the pulley **123** and the pulley **124** are formed to be rotatable independently of each other around the rotation shaft **143** that is a pitch main rotation shaft. In addition, the pulley **125** is disposed on one side of each of the pulley **123** and the pulley **124**. Here, the pulley **125** is formed to be rotatable around the rotation shaft **144**, which is a pitch-serve rotation shaft. Here, in the drawings, it is illustrated that all of the pulley **128**, pulley **123**, the pulley **124**, and the pulley **125** are formed to be rotatable around the Y-axis direction, but the concept of the present disclosure is not limited thereto, and the rotation shafts of the respective pulleys may be formed in various directions according to configurations thereof.

(197) The wire **306**, which is a second jaw wire, is sequentially wound to make contact with at least portions of the pulley **125**, the pulley **123**, and the pulley **121**. In addition, the wire **302** connected to the wire **306** by the coupling member **326** is sequentially wound to make contact with at least

portions of the pulley **121**, the pulley **122**, the pulley **128**, and the pulley **124**.

(198) In other words, the wires **306** and **302**, which are second jaw wires, are sequentially wound to make contact with at least portions of the pulley **125**, the pulley **123**, the pulley **121**, the pulley **122**, the pulley **128**, and the pulley **124**, and are formed to move along the above pulleys while rotating the above pulleys.

(199) Accordingly, when the wire **306** is pulled in the direction of an arrow **306** of FIG. **9**, the coupling member **326** to which the wire **306** is coupled and the pulley **121** coupled to the coupling member **326** are rotated in the arrow R direction of FIG. **9**. In contrast, when the wire **302** is pulled in the direction of an arrow **302** of FIG. **9**, the coupling member **326** to which the wire **302** is coupled and the pulley **121** coupled to the coupling member **326** are rotated in the arrow L direction of FIG. **9**.

(200) Here, in the present disclosure, two strands of the jaw wire, which are wound around one jaw pulley, are wound around the pitch main pulley in opposite directions to each other, thereby facilitating control of the pitch motion.

(201) In detail, when defining a +Z-axis direction and a -Z-axis direction as upper and lower sides, respectively, based on a plane (i.e., an XY plane) passing between the pulley **111**, which is a first jaw pulley, and the pulley **121**, which is a second jaw pulley, of two strands of the first jaw wire, one strand (e.g., the wire **301**) may enter the pulley **113**, which is a first jaw pitch main pulley, at the lower side of the XY plane, and another strand (e.g., the wire **305**) may exit from the pulley **114**, which is a first jaw pitch main pulley, at the upper side of the XY plane. In other words, it may be said that the jaw wire is structured to enter the lower side of the first jaw pitch main pulley and exit the upper side of the first jaw pitch main pulley. (It is the structure in which the second jaw wire enters the upper side of the second jaw pitch main pulley and exits from the lower side thereof).

(202) In other words, the wire **301**, which is one strand of the first jaw wire sequentially comes into contact with an upper side of the pulley **115** and a lower side of the pulley **113**, and then comes into contact with the pulley **111**. Subsequently, the wire **305**, which is another strand of the first jaw wire, is wound around the pulley **111** and the pulley **112**, and then exits from the connection part **400** after sequentially coming into contact with an upper side of the pulley **114** and a lower side of the pulley **118**. As a result, the first jaw wire exits from the connection part **400**, enters the lower side of the pulley **113**, and then proceeds through each of the pulleys, and re-enters the connection part **400** via the upper side of the pulley **114**.

(203) Likewise, the wire **306**, which is one strand of the second jaw wire, sequentially come into contact with a lower side of the pulley **125** and an upper side of the pulley **123**, and then comes into contact with the pulley **121**. Subsequently, the wire **302**, which is another strand of the second jaw wire, is wound around the pulley **121** and the pulley **122**, and then exits from the connection part **400** after sequentially coming into contact with an upper side of the pulley **128** and a lower side of the pulley **124**. As a result, the second jaw wire exits from the connection part **400**, enters the upper side of the pulley **123**, and then proceeds through each of the pulleys, and re-enters the connection part **400** via the lower side of the pulley **124**.

(204) In other words, it may be expressed that, of the two strands of first jaw wire, one wire is wound around the first jaw pitch main pulley in one of the clockwise and counterclockwise directions, and another wire is wound around the first jaw pitch main pulley in the other one of the clockwise and counterclockwise directions. That is, when viewed in FIG. **11**, the wire **301** is wound in the clockwise direction while entering from the connection part **400** toward the end tool **100**, and the wire **305** is wound in the counterclockwise direction while entering from the connection part **400** toward the end tool **100**.

(205) Likewise, it may be expressed that, of the two strands of first second jaw wire, one wire is wound around the second jaw pitch main pulley in one of the clockwise and counterclockwise directions, and another wire is wound around the second jaw pitch main pulley in the other one of

the clockwise and counterclockwise directions. That is, when viewed in FIG. 10, the wire 302 is wound in the clockwise direction while entering from the connection part 400 toward the end tool 100, and the wire 306 is wound in the counterclockwise direction while entering from the connection part 400 toward the end tool 100.

(206) As described above, by winding two strands of the jaw wire, which are wound around one jaw pulley, around the pitch main pulley in opposite directions to each other, it is possible to easily control the pitch motion. This will be described in more detail later.

(207) Meanwhile, when viewed from the perspective of an XZ plane, the two strands of each jaw wire are disposed on the same side with respect to the XZ plane. In detail, when defining a +Y-axis direction and a -Y-axis direction with respect to a plane (i.e., the XZ plane) passing between the pulley 114, which is a first jaw pitch main pulley, and the pulley 124, which is a second jaw pitch main pulley, as a first side and a second side, respectively, of the two strands of the first jaw wire, one strand (e.g., the wire 301) may be disposed on the first side of the XZ plane, and another strand (e.g., the wire 305) may also be disposed on the same first side. Likewise, of the two strands of the second jaw wire, one strand (e.g., the wire 306) may be disposed on the second side of the XZ plane and another strand (e.g., the wire 302) may also be disposed on the same second side. That is, it may be said that it is structured so that one jaw wire enters the first side and exits from the first side. (In addition, it may be said that it is structured so that another jaw wire enters the second side and exits from the second side).

(208) (Driving Part)

(209) Hereinafter, the driving part 200 of the surgical instrument 30 of FIG. 4 will be described in more detail.

(210) FIG. 17 is a perspective view of the driving part of the surgical instrument of FIG. 4, FIG. 18 is a plan view of the driving part of the surgical instrument of FIG. 17, FIG. 19 is a rear view of the driving part of the surgical instrument of FIG. 17, and FIG. 20 is a side view of the driving part of the surgical instrument of FIG. 17.

(211) Referring to FIGS. 17 to 20, the driving part 200 of the surgical instrument 30 according to the first embodiment of the present disclosure may include the pulley 211, the pulley 212, a pulley 213, a pulley 214, a pulley 215, and a pulley 216, which are related to a rotational motion of the first jaw 101. In addition, the driving part 200 may include the pulley 221, the pulley 222, a pulley 223, a pulley 224, a pulley 225, and a pulley 226 that are related to a rotational motion of the second jaw 102.

(212) Here, the pulleys facing each other are illustrated in the drawings as being formed parallel to each other, but the concept of the present disclosure is not limited thereto, and each of the pulleys may be variously formed with a position and a size suitable for the configuration of the driving part.

(213) In addition, the driving part 200 of the surgical instrument 30 according to the first embodiment of the present disclosure may further include the pulley 231 and the pulley 232, which serve as driving part pitch pulleys.

(214) Further, the driving part 200 of the first embodiment of the present disclosure may include a rotation shaft 241, a rotation shaft 242, a rotation shaft 243, and a rotation shaft 244. Here, the rotation shaft 241 may function as a driving part first jaw rotation shaft, and the rotation shaft 242 may function as a driving part second jaw rotation shaft. In addition, the rotation shaft 243 may function as a driving part pitch rotation shaft, and the rotation shaft 244 may function as a driving part roll rotation shaft. Each of the rotation shafts 241, 242, 243, and 244 may be fitted into one or more pulleys, which will be described in detail later.

(215) In addition, the driving part 200 of the first embodiment of the present disclosure may include a motor coupling part 251, a motor coupling part 252, a motor coupling part 253, and a motor coupling part 254. Here, the motor coupling part 251 may function as a first jaw driving motor coupling part, the motor coupling part 252 may function as a second jaw driving motor

coupling part, the motor coupling part **253** may function as a pitch driving motor coupling part, and the motor coupling part **254** may function as a roll driving motor coupling part. Here, each of the motor coupling parts **251**, **252**, **253**, and **254** may be formed in the form of a rotatable flat plate, in which one or more coupling holes to which a motor (not shown) may be coupled may be formed. (216) The motor coupling parts **251**, **252**, **253**, and **254** of the driving part **200** described above are coupled to motors (not shown) formed in the robot arm units **21**, **22**, and **23**, respectively, so that the driving part **200** is operated by driving the motors (not shown).

(217) In addition, the driving part **200** of the first embodiment of the present disclosure may include a gear **263** and a gear **264**. Here, the gear **263** and the gear **264** may function as roll driving gears.

(218) Hereinafter, each component will be described in more detail.

(219) The pulley **211** and the pulley **212** may function as driving part first jaw pulleys, and the pulley **221** and the pulley **222** may function as driving part second jaw pulleys, and these components may be collectively referred to as driving part jaw pulleys.

(220) Here, it is illustrated in the drawings that the pulley **211** and the pulley **212** are associated with a rotational motion of the first jaw **101** of the end tool **100**, and the pulley **221** and the pulley **222** are associated with a rotational motion of the second jaw **102** of the end tool **100**, but the concept of the present disclosure is not limited thereto. For example, one group of pulleys in the driving part may be associated with a yaw motion, and one group of pulleys in the driving part may be associated with an actuation motion. Accordingly, the pulley **211**, the pulley **212**, the pulley **221**, and the pulley **222** may be collectively referred to as driving part driving pulleys. In addition, for the other pulleys, one group of pulleys may be associated with a yaw motion, and one group of pulleys may be associated with an actuation motion.

(221) The pulley **213**, the pulley **214**, the pulley **215**, and the pulley **216** may function as driving part first jaw auxiliary pulleys, and the pulley **223**, the pulley **224**, the pulley **225**, and the pulley **226** may function as driving part second jaw auxiliary pulley, and] these components may be collectively referred to as driving part jaw auxiliary pulleys.

(222) A plurality of rotation shafts including the rotation shaft **241**, the rotation shaft **242**, the rotation shaft **243**, and the rotation shaft **244** may be formed on a first surface of a base plate **201**. In addition, a plurality of relay pulleys **202** are formed on the first surface of the base plate **201**, and may serve to redirect the wires **301**, **302**, **303**, **304**, **305**, and **306** entering the driving part **200** via a shaft **410** toward the pulley **231**/pulley **232**.

(223) Further, the shaft **410** in the form of a shaft is coupled to a second surface of the base plate **201** opposite to the first surface, and the motor coupling part **251**, the motor coupling part **252**, the motor coupling part **253**, and the motor coupling part **254**, to which the motors (not shown) for driving the pulleys are coupled, may be formed on the second surface.

(224) Here, the rotation shaft may be connected to the respective motor coupling part either directly or indirectly via a gear.

(225) In an example, by directly coupling the motor coupling part **251**, which is a first jaw driving motor coupling part, to the rotation shaft **241** that is a driving part first jaw rotation shaft, when the motor coupling part **251** coupled to a first jaw driving motor (not shown) is rotated, the rotation shaft **241** directly coupled to the motor coupling part **251** may be rotated together with the motor coupling part **251**. Similarly, by directly coupling the motor coupling part **252**, which is a second jaw driving motor coupling part, to the rotation shaft **242** that is a driving part second jaw rotation shaft, when the motor coupling part **252** coupled to a second jaw driving motor (not shown) is rotated, the rotation shaft **242** directly coupled to the motor coupling part **252** may be rotated together with the motor coupling part **252**. Similarly, by directly coupling the motor coupling part **253**, which is a pitch driving motor coupling part, to the rotation shaft **243** that is a driving part pitch rotation shaft, when the motor coupling part **253** coupled to a pitch driving motor (not shown) is rotated, the rotation shaft **243** directly coupled to the motor coupling part **253** may be rotated

together with the motor coupling part **253**.

(226) In another example, when viewed from a plane perpendicular to the rotation shaft **244**, the motor coupling part **254**, which is a roll driving motor coupling part, and the rotation shaft **244**, which is a driving part roll rotation shaft, may be disposed to be spaced apart from each other by a certain degree. In addition, the motor coupling part **254** and the rotation shaft **244** may be connected by the gears **263** and **264**, which are roll driving gears.

(227) As such, some motor coupling parts are configured to be directly connected to the rotation shafts, respectively, and the remaining motor coupling parts are configured to be indirectly connected to the rotation shafts, respectively, because the coupling position and direction between the surgical instrument **30** and the slave robot **20** should be considered. That is, the rotation shaft unaffected by the coupling position with the slave robot **20** may be directly connected to the motor coupling part, while the rotation shaft that may interfere with the coupling position with the slave robot **20** may be indirectly connected to the motor coupling part.

(228) It is illustrated in the drawings that the motor coupling part **251**, the motor coupling part **252**, and the motor coupling part **253** are directly connected to the rotation shafts, respectively, and the motor coupling part **254** is indirectly connected, respectively, through the gears, but the concept of the present disclosure is not limited thereto, and various configurations are possible according to the coupling position and direction with the slave robot **20**.

(229) The pulleys **211** and **212**, which are driving part first jaw pulleys, may be coupled to the rotation shaft **241**, which is a driving part first jaw rotation shaft. Here, the pulleys **211** and **212** may be formed to rotate together with the rotation shaft **241**.

(230) Here, it is illustrated in the drawings that the driving part first jaw pulley is formed of two pulleys **211** and **212**, the wire **301** is coupled to one pulley **211**, and the wire **305** is coupled to the other pulley **212**. However, the concept of the present disclosure is not limited thereto, and the driving part first jaw pulley may be formed of one pulley, and both the wires **301** and **305** may be coupled to the one pulley.

(231) As described above, the rotation shaft **241** is coupled to the first jaw driving motor (not shown) by the motor coupling part **251**, and thus, when the first jaw driving motor (not shown) rotates for driving the first jaw **101**, the wires **301** and **305**, which are first jaw wires, are pulled or released as the pulleys **211** and **212**, which are driving part first jaw pulleys, are rotated together with the rotation shaft **241**.

(232) In addition, one or more driving part first jaw auxiliary rotation shafts may be disposed in a region adjacent to the rotation shaft **241**. In addition, to these rotation shafts, the pulley **213**, the pulley **214**, the pulley **215**, and the pulley **216** may be coupled. The pulley **213**, the pulley **214**, the pulley **215**, and the pulley **216** may serve to guide paths of the wires **301** and **305**, which are first jaw wires.

(233) The pulleys **221** and **222**, which are driving part second jaw rotation shafts, may be coupled to the rotation shaft **242** that is a driving part second jaw pulley. Here, the pulley **221** and the pulley **222** may be formed to rotate together with the rotation shaft **242**.

(234) Here, it is illustrated in the drawings that the driving part second jaw pulley is formed of two pulleys **221** and **222**, the wire **302** is coupled to one pulley **221**, and the wire **306** is coupled to the other pulley **222**. However, the concept of the present disclosure is not limited thereto, and the driving part second jaw pulley may be formed of one pulley, and both the wires **302** and **306** may be coupled to the one pulley.

(235) As described above, the rotation shaft **242** is coupled to the second jaw driving motor (not shown) by the motor coupling part **252**, and thus, when the second jaw driving motor (not shown) rotates for driving the second jaw **102**, that the wires **302** and **306**, which are second jaw wires, are pulled or released as the pulley **221** and the pulley **222**, which are driving part second jaw pulleys, are rotated together with the rotation shaft **242**.

(236) In addition, one or more driving part second jaw auxiliary rotation shafts may be disposed in

a region adjacent to the rotation shaft **242**. In addition, to these rotation shafts, the pulley **223**, the pulley **224**, the pulley **225**, and the pulley **226**, which are driving part second jaw auxiliary pulleys, may be coupled. The pulley **223**, the pulley **224**, the pulley **225**, and the pulley **226** may serve to guide paths of the wires **302** and **306**, which are second jaw wires.

(237) The pulley **231** and the pulley **232**, which are driving part pitch pulleys, may be coupled to the rotation shaft **243** that is a driving part pitch rotation shaft. Here, the pulley **231** and the pulley **232** may be formed to rotate together with the rotation shaft **243**.

(238) Here, it is illustrated in the drawings that the driving part pitch pulley is formed of two pulleys **231** and **232**, the wire **304** is coupled to one pulley **231**, and the wire **303** is coupled to the other pulley **232**. However, the concept of the present disclosure is not limited thereto, and the driving part pitch pulley may be formed of one pulley, and both the wire **303** and the wire **304** may be coupled to the one pulley.

(239) As described above, the rotation shaft **243** is coupled to a pitch driving motor (not shown) by the motor coupling part **253**, and thus, when the pitch driving motor (not shown) rotates for a pitch motion, the wires **303** and **304**, which are pitch wires, are pulled or released as the pulley **231** and the pulley **232**, which are driving part pitch pulleys, are rotated together with the rotation shaft **243**.

(240) In addition, one or more driving part pitch auxiliary rotation shafts may be disposed in a region adjacent to the rotation shaft **243**. In addition, a pulley **233** and a pulley **234**, which are driving part pitch auxiliary pulleys, may be coupled to the driving part pitch auxiliary rotation shafts. The pulley **233** and the pulley **234** may serve to guide paths of the wire **304** and the wire **303**, which are pitch wires.

(241) The wire **305**, which is a first jaw wire, is connected to the end tool **100** via the shaft **410** after being sequentially wound to make contact with at least portions of the pulley **211**, the pulley **213**, and the pulley **215** in a state in which one end portion of the wire **305** is coupled to the pulley **211** by the first jaw wire-driving part coupling member **325**.

(242) In other words, the wire **305**, which is a first jaw wire, sequentially passes through the driving part first jaw pulley **211**, the driving part first jaw auxiliary pulley **213**, and the driving part first jaw auxiliary pulley **215**, and then is connected to the end tool **100** via the shaft **410**.

(243) In other words, the wire **305**, which is a first jaw wire, enters the driving part **200** after passing through the end tool **100** and the shaft **410**, and then is fixedly coupled to the pulley **211**, which is a driving part first jaw pulley, after being sequentially wound around the pulley **215** and the pulley **213**.

(244) Meanwhile, the wire **301**, which is a first jaw wire, is connected to the end tool **100** through the shaft **410** after being sequentially wound to make contact with at least portions of the pulley **212**, the pulley **214**, and the pulley **216** in a state in which one end portion of the wire **301** is coupled to the pulley **212** by the first jaw wire-driving part coupling member **324**.

(245) The wire **306**, which is a second jaw wire, is connected to the end tool **100** via the shaft **410** after being sequentially wound to make contact with at least portions of the pulley **221**, the pulley **223**, and the pulley **225** in a state in which one end portion of the wire **306** is coupled to the pulley **221** by the second jaw wire-driving part coupling member **327**.

(246) Meanwhile, the wire **302**, which is a second jaw wire, is connected to the end tool **100** via the shaft **410** after being sequentially wound to make contact with at least portions of the pulley **222**, the pulley **224**, and the pulley **226** in a state in which one end portion of the wire **302** is coupled to the pulley **222** by the second jaw wire-driving part coupling member **328**.

(247) (Pitch Motion)

(248) The end tool **100** of the surgical instrument of the present disclosure may include the pulley **131**, which is an end tool pitch pulley, the driving part (see **200** of FIG. **17**) may include the pulley **231** and the pulley **232**, which are driving part pitch pulleys, and the power transmission part **300** may further include the wire **303** and the wire **304**, which are pitch wires.

(249) In detail, the pulley **131** of the end tool **100** is rotatable around the rotation shaft **143**, which

is a pitch main rotation shaft, and may be integrally formed with the end tool hub **106** (or fixedly coupled to the end tool hub **106**) as one body. In addition, the wire **303** and the wire **304** may serve to connect the pulley **131** of the end tool **100** to the pulley **231**/pulley **232**, which is a driving part pitch pulley, of the driving part (see **200** of FIG. **17**).

(250) Thus, when the pulley **231**/pulley **232**, which is a driving part pitch pulley, of the driving part (see **200** of FIG. **17**) rotates, the rotation of the pulley **231**/pulley **232**, which is a driving part pitch pulley, is transmitted to the pulley **131** of the end tool **100** through the wire **303** and the wire **304**, so that the pulley **131** is also rotated together with the pulley **231**/pulley **232**, and as a result, the end tool **100** perform a pitch motion while rotating.

(251) However, if the driving part does not perform separate pitch compensation for the jaw wire when the pulley **231**/pulley **232**, which is a driving part pitch pulley, is rotated to perform a pitch motion as described above, in the end tool, along with the pitch motion, the jaws are rotated around the rotation shaft **141**, which is a jaw pulley rotation shaft, and as a result, a pure pitch motion could not be performed.

(252) This pitch compensation will be described in more detail later.

(253) FIGS. **22** to **29** are conceptual views illustrating a pitch motion of the surgical instrument shown in FIG. **4**. In detail, FIGS. **22** and **23** are views illustrating the surgical instrument in a neutral state, FIGS. **24**, **25**, and **26** are views illustrating the surgical instrument when pitch compensation is not performed, and FIGS. **27**, **28**, and **29** are views illustrating the surgical instrument when pitch compensation is performed. Here, for convenience of description, the pulleys and the wires associated with the rotation of the first jaw are mainly shown in FIGS. **23A**, **26A**, and **29A**, and the pulleys and the wires associated with the rotation of the second jaw are mainly shown in FIGS. **23B**, **26B**, and **29B**.

(254) Here, in the surgical instrument according to an embodiment of the present disclosure, a pitch motion of the end tool **100** may be performed by rotating the pulley **211**/pulley **212**, which is a driving part first jaw pulley, and the pulley **221**/pulley **222**, which is a driving part second jaw pulley, to wind or unwind the jaw wires during the pitch motion.

(255) As described above, if the driving part does not perform separate pitch compensation for the jaw wire when the pulley **231**/pulley **232**, which is a driving part pitch pulley, is rotated to perform a pitch motion as described above, in the end tool, along with the pitch motion, the jaws are rotated around the rotation shaft **141**, which is a jaw pulley rotation shaft, and as a result, a pure pitch motion could not be performed.

(256) In detail, referring to FIGS. **22** to **26**, when the pulley **231**/pulley **232**, which is a driving part pitch pulley, of the driving part **200** is rotated to perform the pitch motion of the end tool, the rotation of the pulley **231**/pulley **232**, which is a driving part pitch pulley, is transmitted to the pulley **131** of the end tool **100** through the wire **303** and the wire **304**, so that the pulley **131** is rotated together with the pulley **231**/pulley **232**, and as a result, the end tool **100** performs the pitch motion while rotating.

(257) That is, when the pulley **231**/pulley **232**, which is a driving part pitch pulley, is rotated in the direction of an arrow **P1** of FIG. **26A**, the rotation of the pulley **231**/pulley **232**, which is a driving part pitch pulley, is transmitted to the pulley **131** of the end tool **100** through the wire **303** and the wire **304** so that the pulley **131** is rotated in the direction of an arrow **P2** of FIG. **26A**, and accordingly, the end tool hub (see **106** of FIG. **5**) is rotated with respect to the pitch hub (see **107** of FIG. **5**). In addition, the first jaw **101**, the second jaw **102**, the first jaw pulley **111**, the second jaw pulley **122**, the first jaw auxiliary pulley **112**, and the second jaw auxiliary pulley **122**, which are coupled to the end tool hub (see **106** of FIG. **5**), are also rotated together with the end tool hub (see **106** of FIG. **5**) with respect to the pitch hub (see **107** of FIG. **5**).

(258) However, in this case, the wire **301** and the wire **302**, which are jaw wires, are wound further around the pulley **113**/pulley **114** by $\Delta S_{\text{sub.pitch}}$, and the wire **305** and the wire **306** are unwound further around the pulley **114**/pulley **114** by $\Delta S_{\text{sub.pitch}}$.

(259) Thus, if this is not compensated for, the first jaw pulley **111** is rotated by a certain degree in the direction of an arrow **J1** of FIG. **26B**, and the second jaw pulley **121** is rotated by a certain degree in the direction of an arrow **J2** of FIG. **26A**.

(260) Thus, when the movement of the jaw wire is not compensated for, in the end tool, along with the pitch motion, the jaws are also rotated around the rotation shaft **141**, which is a jaw pulley rotation shaft, and as a result, the pure pitch motion may not be performed, and the pitch motion and a yaw motion may be mixed.

(261) In order to perform motion compensation for the pitch motion as described above, in the surgical instrument according to an embodiment of the present disclosure, during the pitch motion, the jaw wires are wound or unwound as the pulley **211**/pulley **212**, which is a driving part first jaw pulley, and the pulley **221**/pulley **222**, which is a driving part second jaw pulley, are rotated together with the driving part pitch pulley, so that a kind of compensation for the pitch motion is performed, allowing the pitch motion of the end tool **100** to be performed.

(262) That is, during the pitch motion, the pulley **211**/pulley **212**, which is a driving part first jaw pulley, is rotated by a certain degree in the direction of an arrow **A1** of FIG. **29B**. Then, the wire **301** is unwound from the pulley **211**/pulley **212**, which is a driving part first jaw pulley, by a certain degree (e.g., by $\Delta S_{\text{sub.pitch}}$), thereby being wound around the first jaw pitch main pulley **113** to the extent of the unwinding. At the same time, the wire **305** is wound around the pulley **211**/pulley **212**, which is a driving part first jaw pulley, by a certain degree (e.g., by $\Delta S_{\text{sub.pitch}}$), thereby being unwound from the first jaw pitch main pulley **114** to the extent of the winding.

(263) Likewise, during the pitch motion, the pulley **221**/pulley **222**, which is a driving part second jaw pulley, is rotated by a certain degree in the direction of an arrow **A2** of FIG. **29A**. Then, the wire **302** is unwound from the pulley **221**/pulley **222**, which is a driving part second jaw pulley, by a certain degree (e.g., by $\Delta P_{\text{sub.pitch}}$), thereby being wound around the second jaw pitch main pulley **123** to the extent of the unwinding. At the same time, the wire **306** is wound around the pulley **221**/pulley **222**, which is a driving part second jaw pulley, by a certain degree (e.g., by $\Delta S_{\text{sub.pitch}}$) thereby being unwound from the second jaw pitch main pulley **124** to the extent of the winding.

(264) In other words, when the pulley **231**/pulley **232**, which is a driving part pitch pulley, is rotated, the pulley **211**/pulley **212**, which is a driving part first jaw pulley, and the pulley **221**/pulley **222**, which is a driving part second jaw pulley, are also rotated, and accordingly, lengths of the jaw wires respectively wound around the pulley **211**/pulley **212**, which is a driving part first jaw pulley, and the pulley **221**/pulley **222**, which is a driving part second jaw pulley, are changed. That is, due to the rotation of the pulley **231**/pulley **232**, which is a driving part pitch pulley, the jaw wire wound at the end tool **100** side is unwound by the same amount at the driving part **200** side, and the jaw wire unwound at the end tool **100** side is wound by the same amount at the driving part **200** side, so that the pitch motion does not affect the yaw motion.

(265) In other words, due to the rotation of the pulley **231**/pulley **232**, which is a driving part pitch pulley, when the end tool **100** performs a pitch motion, the jaw wires (responsible for the yaw motion and the actuation motion) are also moved by the pitch motion. That is, as the pitch rotation is performed around the rotation shaft **143** of the end tool **100**, in the jaw wire coupled to one jaw, one strand is pulled and another strand is released. At the same time, in the jaw wire coupled to another jaw, one strand is pulled and another strand is released. Accordingly, it may be described that, in the present disclosure, in order to compensate for this movement of the jaw wire, when the pulley **231**/pulley **232**, which is a driving part pitch pulley, is rotated for a pitch motion of the end tool, the pulley **211**/pulley **212**, which is a driving part first jaw pulley, and the pulley **221**/pulley **222**, which is a driving part second jaw pulley, are also rotated to change the length of the respective jaw wire in the driving part, so that as much as the jaw wire is pulled (or released) at the end tool side, the jaw wire is released (or pulled) at the driving part side, thereby compensating for the movement of the jaw wire during the pitch motion of the end tool.

(266) As described above, the end tool **100** of the surgical instrument according to an embodiment of the present disclosure can easily control a pitch motion by winding the two strands of the jaw wire, which are wound around one jaw pulley, around the pitch main pulley in opposite directions. That is, during the pitch motion, the pulley **211**/pulley **212**, which is a driving part first jaw pulley, and the pulley **221**/pulley **222**, which is a driving part second jaw pulley, are rotated to wind and unwind the jaw wires, which enables a kind of compensation for the pitch motion, allowing the pitch motion of the end tool **100** to be performed.

(267) FIG. **30** is a view illustrating a neutral state of a surgical instrument according to a comparative example of the present disclosure, and FIGS. **31**, **32**, and **33** are views illustrating the surgical instrument of FIG. **30** when pitch compensation is performed.

(268) Here, for convenience of description, a state of an end tool to which an end tool hub and a pitch hub are coupled is shown in FIGS. **30A**, **31A**, and **32A**, and a state of the end tool from which the end tool hub and the pitch hub are removed is shown in FIGS. **30B**, **31B**, and **32B**, and a driving part corresponding to the state of the end tool is shown in FIGS. **30C**, **31C**, and **32C**.

(269) In the case of the surgical instrument according to the comparative example of the present disclosure shown in FIG. **30**, pitch redundant pulleys (see **118** and **128** of FIG. **6**) are not provided. Thus, two strands of the jaw wire wound around one jaw pulley are wound around a pitch main pulley in the same direction.

(270) For example, of two strands of the first jaw wire, one strand (e.g., a wire **701**) may enter a pulley **513**, which is a first jaw pitch main pulley, at a lower side of the XY plane, and another strand (e.g., a wire **705**) may exit from a pulley **514**, which is the first jaw pitch main pulley, at the lower side of the XY plane. In other words, it may be said that the first jaw wire is structured to enter a lower side of the first jaw pitch main pulley and exit from the lower side of the first jaw pitch main pulley. (It is the structure in which a second jaw wire enters an upper side of a second jaw pitch main pulley and exits from the upper side thereof).

(271) Accordingly, when a pitch motion is performed by rotating a pulley **631**/pulley **632**, which is a driving part pitch pulley, a wire **701** and a wire **705**, which are first jaw wires, move in the same direction.

(272) For example, as shown in FIGS. **31** and **33**, when the pulley **631**/pulley **632**, which is a driving part pitch pulley, is rotated in the direction of an arrow P of FIG. **31**, the wire **701** and the wire **705** are pulled by $\Delta S_{\text{sub.pitch}}$ shown in FIG. **33**.

(273) When the wire **701** and the wire **705** move in the same direction as described above, compensation for the pitch motion may not be performed just by rotating a pulley **611**/pulley **612**, which is a driving part first jaw pulley.

(274) Thus, as shown in FIGS. **31** and **33**, pitch compensation may be performed by moving the position of the pulley **611**/pulley **612**, which is driving part first jaw pulley, to change a path length of the first jaw wire in a driving part **600** and simultaneously moving the position of a pulley **621**/pulley **622**, which is a driving part second jaw pulley, to change a path length of the second jaw wire in the driving part **600**.

(275) That is, in order to compensate for the movement of the jaw wires during pitch driving, the pulley **611**/pulley **612**, which is a driving part first jaw pulley, is moved by a certain degree in the direction of an arrow J1. In addition, by the same principle, the pulley **621**/pulley **622**, which is a driving part second jaw pulley, is moved by a certain degree in the direction of an arrow J2.

(276) In this case, in order to move the positions of the driving part first jaw pulley and the driving part second jaw pulley for pitch compensation, various and complex instrument structures are required in the driving part.

(277) In comparison, the end tool **100** of the surgical instrument according to an embodiment of the present disclosure can easily control the pitch motion by winding the two strands of the jaw wire, which are wound around one jaw pulley, around the pitch main pulley in opposite directions.

(278) (Yaw Motion)

(279) FIGS. **15** and **16** are views illustrating a yaw motion of the surgical instrument shown in FIG. **4**.

(280) Referring to FIGS. **15**, **16**, **17**, and **21** and the like, when the pulley **211**/pulley **212**, which is a driving part first jaw pulley, is rotated in one direction for a yaw motion, one side of the wires **301** and **305**, which are first jaw wires, is wound around the pulley **211**/pulley **212** in response to the rotation of the pulley **211**/pulley **212**, and another side thereof is unwound from the pulley **211**/pulley **212**. Accordingly, the pulley **111**, which is an end tool first jaw pulley connected to the opposite side of the wires **301** and **305**, is rotated in one direction, so that the yaw motion is performed.

(281) At this time, the driving part pitch pulley **231**/pulley **232** is not rotated, and the wire **303** and the wire **304**, which are pitch wires, remain in their positions without being wound or unwound.

(282) Likewise, when the pulley **221**/pulley **222**, which is a driving part second jaw pulley, is rotated in one direction for the yaw motion, one side of the wire **302** and the wire **306**, which are second jaw wires, is wound around the pulley **221**/pulley **222** in response to the rotation the pulley **221**/pulley **222**, and another side thereof is unwound from the pulley **221**/pulley **222**. Accordingly, the pulley **121**, which is an end tool second jaw pulley connected to the opposite side of the wires **302** and **306**, is rotated in one direction, so that the yaw motion is performed.

(283) At this time, the driving part pitch pulley **231**/pulley **232** is not rotated, and the wire **303** and the wire **304**, which are pitch wires, remain in their positions without being wound or unwound.

(284) As a result, the overall lengths of the wire **301**, the wire **302**, the wire **305**, and the wire **306**, which are jaw wires, in the driving part **200** remain constant even when the pulley **211**/pulley **212** or the pulley **221**/pulley **222**, which are driving part jaw pulleys, are rotated for the yaw or actuation motion.

(285) As described above, in the surgical instrument **30** according to an embodiment of the present disclosure, when the driving part pitch pulley is rotated, the driving part jaw pulley is rotated together with the driving part pitch pulley to change the path length of the jaw wire wound around the driving part jaw pulley, so that the jaw wire is wound or unwound in response to the rotation of the driving part pitch pulley to offset or compensate for the movement of the jaw wire according to the pitch driving, thereby resulting in an effect of separating the pitch motion and the yaw motion.

MODES OF THE INVENTION

First Modified Example of First Embodiment

(286) Hereinafter, an end tool **100** of a surgical instrument according to a first modified example of the first embodiment of the present disclosure will be described. Here, the end tool **100** of the surgical instrument according to the first modified example of the first embodiment of the present disclosure is different from the end tool of the surgical instrument according to the first embodiment of the present disclosure described above in that some pulleys are added. Hereinafter, the configuration that is different from that of the first embodiment will be described in detail.

(287) FIGS. **34** and **35** are perspective views illustrating the end tool of the surgical instrument according to the first modified example of the first embodiment of the present disclosure. FIG. **36** is a plan view of the end tool of FIG. **34**. FIGS. **37** and **38** are plan views of the end tool of FIG. **34**. FIG. **39** is a perspective view of the end tool of FIG. **34**. FIG. **40** is a perspective view of an end tool hub of the end tool of FIG. **34**.

(288) Referring to FIGS. **34** to **40**, the end tool **100** according to the first modified example of the first embodiment of the present disclosure includes a pair of jaws for performing a grip motion, that is, a first jaw **101** and a second jaw **102**. Here, each of the first jaw **101** and the second jaw **102**, or a component encompassing the first jaw **101** and the second jaw **102** may be referred to as a jaw **103**.

(289) Further, the end tool **100** of the first embodiment of the present disclosure may include an end tool hub **106** and a pitch hub **107**.

(290) Further, the end tool **100** of the first modified example of the first embodiment of the present

disclosure may include a rotation shaft **141**, a rotation shaft **142**, a rotation shaft **145**, a rotation shaft **143**, and a rotation shaft **144**. As described above, the rotation shaft **141**, the rotation shaft **142**, and the rotation shaft **145** may be inserted through the end tool hub **106**, and the rotation shaft **143** and the rotation shaft **144** may be inserted through the pitch hub **107**.

(291) The end tool hub **106**, the pitch hub **107**, and each of the rotation shafts **141**, **142**, **143**, **144**, and **145** in the present modified example are substantially the same as the end tool hub **106**, pitch hub **107**, and each of the rotation shafts **141**, **142**, **143**, **144**, and **145** described in the first embodiment with reference to FIG. 5 or the like, and thus, detailed description thereof will be omitted herein.

(292) Meanwhile, the end tool **100** may include a pulley **111**, a pulley **112**, a pulley **113**, a pulley **114**, a pulley **115**, a pulley **116**, a pulley **117**, and a pulley **118** that are related to a rotational motion of the first jaw **101**. In addition, the end tool **100** may include a pulley **121**, a pulley **122**, a pulley **123**, a pulley **124**, a pulley **125**, a pulley **126**, a pulley **127**, and a pulley **128** that are related to a rotational motion of the second jaw **102**.

(293) Here, in the end tool **100** of the surgical instrument according to the first modified example of the first embodiment of the present disclosure, each of a first jaw pitch redundant pulley and a second jaw pitch redundant pulley includes two pulleys, and each of a first jaw pitch sub-pulley and a second jaw pitch sub-pulley includes two pulleys

(294) In detail, in the end tool **100** of the surgical instrument according to the first embodiment of the present disclosure shown in FIG. 6 or the like, one pulley **118** is provided as a first jaw pitch redundant pulley, and only one pulley **128** is provided as a second jaw pitch redundant pulley.

(295) In contrast, the end tool **100** of the surgical instrument according to the first modified example of the first embodiment of the present disclosure is different from the first embodiment of the present disclosure illustrated with reference to FIG. 6 or the like in that the end tool **100** of the surgical instrument according to the first modified example of the first embodiment of the present disclosure includes a pair of pulleys **117** and **118** as first jaw pitch redundant pulleys and a pair of pulleys **127** and **128** as second jaw pitch redundant pulleys.

(296) In addition, in the end tool **100** of the surgical instrument according to the first embodiment of the present disclosure illustrated with reference to FIG. 6 or the like, only one pulley **115** is provided as a first jaw pitch sub-pulley and only one pulley **125** as a second jaw pitch sub-pulley.

(297) In contrast, the end tool **100** of the surgical instrument according to the first modified example of the first embodiment of the present disclosure is different from the first embodiment of the present disclosure illustrated with reference to FIG. 6 or the like in that the end tool **100** of the surgical instrument according to the first modified example of the first embodiment of the present disclosure includes a pair of pulleys **115** and **116** as first jaw pitch sub-pulleys and a pair of pulleys **125** and **126** as second jaw pitch sub-pulleys.

(298) As a result, the pulley **111**, the pulley **112**, the pulley **117**/pulley **118**, the pulley **113**/pulley **114**, and the pulley **115**/pulley **116**, which are pulleys associated with the rotation of the first jaw **101**, may be arranged sequentially from a distal end **104** of the end tool **100** toward a proximal end **105**.

(299) In addition, the pulley **121**, the pulley **122**, the pulley **127**/pulley **128**, the pulley **123**/pulley **124**, and the pulley **125**/pulley **126**, which are pulleys associated with the rotation of the second jaw **102**, may be arranged sequentially from the distal end **104** of the end tool **100** toward the proximal end **105**.

(300) In other words, in the first embodiment of the present disclosure, the first jaw pitch redundant pulley and the second jaw pitch redundant pulley are each configured in one row, whereas, in the first modified example of the first embodiment of the present disclosure, the first jaw pitch redundant pulleys and the second jaw pitch redundant pulleys are each configured in two rows. In addition, in the first embodiment of the present disclosure, the first jaw pitch sub-pulley and the second jaw pitch sub-pulley are each configured in one row, whereas, in the first modified example

of the first embodiment of the present disclosure, the first jaw pitch sub-pulleys and the second jaw pitch sub-pulleys are each configured in two rows.

(301) Here, the pulley **117**/pulley **118** are disposed on one side of the pulley **111** and the pulley **112** to face each other. Here, the pulley **117** and the pulley **118** are formed to be rotatable independently of each other around the rotation shaft **145** that is a pitch redundant rotation shaft. In addition, the pulley **113** and the pulley **114** are disposed on one side of the pulley **117** and one side of the pulley **118**, respectively, to face each other. Here, the pulley **113** and the pulley **114** are formed to be rotatable independently of each other around the rotation shaft **143** that is a pitch main rotation shaft. In addition, the pulley **115** and the pulley **116** are disposed on one side of the pulley **113** and on one side of the pulley **114**, respectively, to face each other. Here, the pulley **115** and the pulley **116** are formed to be rotatable independently of each other around the rotation shaft **144** that is a pitch-serve rotation shaft. Here, in the drawings, it is illustrated that the pulley **117**, the pulley **118**, the pulley **113**, the pulley **114**, the pulley **115**, and the pulley **116** are all formed to be rotatable around a Y-axis direction, but the concept of the present disclosure is not limited thereto, and the rotation axes of the respective pulleys may be formed in various directions according to configurations thereof.

(302) The wire **301**, which is a first jaw wire, is sequentially wound to make contact with at least portions of the pulley **115**, the pulley **113**, the pulley **117**, and the pulley **111**. In addition, the wire **305** connected to the wire **301** by the coupling member **323** is sequentially wound to make contact with at least portions of the pulley **111**, the pulley **112**, the pulley **118**, the pulley **114**, and the pulley **116**.

(303) In other words, the wires **301** and **305**, which are first jaw wires, are sequentially wound to make contact with at least portions of the pulley **115**, the pulley **113**, the pulley **117**, the pulley **111**, the pulley **112**, the pulley **118**, the pulley **114**, and the pulley **116** and are formed to move along the above pulleys while rotating the above pulleys.

(304) Meanwhile, the pulley **127**/pulley **128** are disposed on one side of the pulley **121** and the pulley **122** to face each other. Here, the pulley **127** and the pulley **128** are formed to be rotatable independently of each other around the rotation shaft **145** which is a pitch redundant rotation shaft. Further, the pulley **123** and the pulley **124** are disposed on one side of the pulley **127** and the pulley **128**, respectively, to face each other. Here, the pulley **123** and the pulley **124** are formed to be rotatable independently of each other around the rotation shaft **143** that is a pitch main rotation shaft. In addition, the pulley **125** and the pulley **126** are disposed on one side of the pulley **123** and one side of the pulley **124**, respectively, to face each other. Here, the pulley **125** and the pulley **126** are formed to be rotatable independently of each other around the rotation shaft **144** that is a pitch-serve rotation shaft. Here, in the drawings, it is illustrated that all of the pulley **127**, the pulley **128**, the pulley **123**, the pulley **124**, the pulley **125**, and the pulley **126** are formed to be rotatable around the Y-axis direction, but the concept of the present disclosure is not limited thereto, and the rotation shafts of the respective pulleys may be formed in various directions according to configurations thereof.

(305) The wire **306**, which is a second jaw wire, is sequentially wound to make contact with at least portions of the pulley **125**, the pulley **123**, the pulley **127**, and the pulley **121**. In addition, the wire **302** connected to the wire **306** by the coupling member **326** is sequentially wound to make contact with at least portions of the pulley **121**, the pulley **122**, the pulley **128**, the pulley **124**, and the pulley **126**.

(306) In other words, the wire **306** and the wire **302**, which are second jaw wires, are sequentially wound to make contact with at least portions of the pulley **125**, the pulley **123**, the pulley **127**, the pulley **121**, the pulley **122**, the pulley **128**, the pulley **124**, and the pulley **126** are formed to move along the above pulleys while rotating the above pulleys.

(307) As a result, in the first embodiment of the present disclosure, the first jaw pitch redundant pulley, the second jaw pitch redundant pulley, the first jaw pitch sub-pulley, and the second jaw

pitch sub-pulley are each configured in one row, but in the first modified example of the first embodiment of the present disclosure, the first jaw pitch redundant pulleys, the second jaw pitch redundant pulleys, the first jaw pitch sub-pulleys, and the second jaw pitch sub-pulleys are each configured in two rows, so that the effect of supporting the wire more stably can be achieved.

Second Modified Example of First Embodiment

(308) Hereinafter, the end tool **100** of the surgical instrument according to a second modified example of the first embodiment of the present disclosure will be described. In this regard, the end tool **100** of the surgical instrument according to the second modified example of the first embodiment of the present disclosure is different from the end tool of the surgical instrument according to the first modified example of the first embodiment of the present disclosure described above in that some of the pulleys are omitted. Hereinafter, the configuration that is different from that the first modified example of the first embodiment will be described in detail.

(309) FIGS. **40** and **42** are perspective views illustrating an end tool of a surgical instrument according to a second modified example of the first embodiment of the present disclosure. FIG. **43** is a plan view of the end tool of FIG. **41**.

(310) Referring to FIGS. **41** to **43**, the end tool **100** according to the second modified example of the first embodiment of the present disclosure includes a pair of jaws for performing a grip motion, that is, the first jaw **101** and the second jaw **102**. In this regard, a component encompassing each of the first jaw **101** and the second jaw **102** or both the first jaw **101** and the second jaw **102** may be referred to as the jaw **103**.

(311) In addition, the end tool **100** of the first embodiment of the present disclosure may include the end tool hub **106** and the pitch hub **107**.

(312) In addition, the end tool **100** of the second modified example of the first embodiment of the present disclosure may include the rotation axis **141**, the rotation axis **142**, the rotation axis **145**, the rotation axis **143**, and the rotation axis **144**. As described above, the rotation axis **141**, the rotation axis **142**, and the rotation axis **145** may be inserted through the end tool hub **106**, and the rotation axis **143** and the rotation axis **144** may be inserted through the pitch hub **107**.

(313) In the present modified example, the end tool hub **106**, the pitch hub **107**, and the rotation axes **141**, **142**, **143**, **144**, and **145** are substantially the same as the end tool hub **106**, the pitch hub **107**, and the rotation axes **141**, **142**, **143**, **144**, and **145** that are described above with reference to FIG. **2** and the like, respectively, and thus, detailed descriptions thereof will be omitted.

(314) Meanwhile, the end tool **100** may include the pulley **111**, the pulley **112**, the pulley **113**, the pulley **114**, the pulley **115**, the pulley **116**, and the pulley **118**, which are associated with a rotational motion of the first jaw **101**. In addition, the end tool **100** may include the pulley **121**, the pulley **122**, the pulley **123**, the pulley **124**, the pulley **125**, the pulley **126**, and the pulley **128**, which are associated with a rotational motion of the second jaw **102**.

(315) In this regard, in the end tool **100** of the surgical instrument according to the second modified example of the first embodiment of the present disclosure, each of the first jaw pitch redundant pulley and the second jaw pitch redundant pulley includes only one pulley.

(316) In detail, the end tool **100** of the surgical instrument according to the first modified example of the first embodiment of the present disclosure illustrated in FIG. **34** and the like includes a pair of pulleys **117** and **118** as first jaw pitch redundant pulleys, and a pair of pulleys **127** and **128** as second jaw pitch redundant pulleys.

(317) On the contrary, the end tool **100** of the surgical instrument according to the second modified example of the first embodiment of the present disclosure is different from the first modified example of the first embodiment of the present disclosure illustrated in FIG. **34** and the like, in that it includes a single pulley **118** as a first jaw pitch redundant pulley, and a single pulley **128** as a second jaw pitch redundant pulley.

(318) Accordingly, the pulley **111**, the pulley **112**, the pulley **118**, the pulley **113**/pulley **114**, and the pulley **115**/pulley **116**, which are associated with rotation of the first jaw **101**, may be sequentially

arranged from the distal end **104** of the end tool **100** toward the proximal end **105**.

(319) In addition, the pulley **121**, the pulley **122**, the pulley **128**, the pulley **123**/pulley **124**, and the pulley **125**/pulley **126**, which are associated with rotation of the second jaw **102**, may be sequentially arranged from the distal end **104** of the end tool **100** toward the proximal end **105**.

(320) In this regard, the pulley **117** and pulley **127** of the end tool **100** of the first modified example of the first embodiment of the present disclosure illustrated in FIG. **34** and the like are not pulleys around which wires are wound, but pulleys through which the wires pass in a straight line, and thus may be omitted as in the present modified example.

(321) In other words, in the first modified example of the first embodiment of the present disclosure, two rows of first jaw pitch redundant pulleys and two rows of second jaw pitch redundant pulleys are provided, whereas in the second modified example of the first embodiment of the present disclosure, one row of a first jaw pitch redundant pulley and one row of a second jaw pitch redundant pulley are provided.

(322) In this regard, the pulley **118** is arranged on one side of the pulley **111** and the pulley **112**. In this regard, the pulley **118** is formed to be rotatable around the rotation axis **145**, which is a pitch redundant rotation axis. In addition, the pulley **113** and the pulley **114** are arranged on one side of the pulley **118** to face each other. In this regard, the pulley **113** and the pulley **114** are formed to be rotatable independently of each other around the rotation axis **143**, which is a pitch main rotation axis. In addition, the pulley **115** and the pulley **116** are arranged on one sides of the pulley **113** and the pulley **114**, respectively, to face each other. In this regard, the pulley **115** and the pulley **116** are formed to be rotatable independently of each other around the rotation axis **144**, which is a pitch sub-rotation axis. In this regard, the drawings illustrate that the pulley **118**, the pulley **113**, the pulley **114**, the pulley **115**, and the pulley **116** are formed to be rotatable around the Y-axis direction, but the concept of the present disclosure is not limited thereto, and the rotation axes of the respective pulleys may be formed in various directions according to their configurations.

(323) The wire **301**, which is a first jaw wire, is wound to sequentially come into contact with at least portions of the pulley **115**, the pulley **113**, and the pulley **111**. In addition, the wire **305** connected to the wire **301** by the coupling member **323** is wound to sequentially come into contact with at least portions of the pulley **111**, the pulley **112**, the pulley **118**, the pulley **114**, and the pulley **116**.

(324) In other words, the wire **301** and the wire **305**, which are first jaw wires, are wound to sequentially come into contact with at least portions of the pulley **115**, the pulley **113**, the pulley **111**, the pulley **112**, the pulley **118**, the pulley **114**, and the pulley **116**, and are formed to move along the above pulleys while rotating the above pulleys.

(325) Meanwhile, the pulley **128** is arranged on one side of the pulley **121** and the pulley **122**. In this regard, the pulley **128** is formed to be rotatable around the rotation axis **145**, which is a pitch redundant rotation axis. In addition, the pulley **123** and the pulley **124** are arranged on one side of the pulley **128** to face each other. In this regard, the pulley **123** and the pulley **124** are formed to be rotatable independently of each other around the rotation axis **143**, which is a pitch main rotation axis. In addition, the pulley **125** and the pulley **126** are arranged on one sides of the pulley **123** and the pulley **124**, respectively, to face each other. In this regard, the pulley **125** and the pulley **126** are formed to be rotatable independently of each other around the rotation axis **144**, which is a pitch sub-rotation axis. In this regard, the drawings illustrate that the pulley **128**, the pulley **123**, the pulley **124**, the pulley **125**, and the pulley **126** are formed to be rotatable around the Y-axis direction, but the concept of the present disclosure is not limited thereto, and the rotation axes of the respective pulleys may be formed in various directions according to their configurations.

(326) The wire **306**, which is a second jaw wire, is wound to sequentially come into contact with at least portions of the pulley **125**, the pulley **123**, and the pulley **121**. In addition, the wire **302** connected to the wire **306** by the coupling member **326** is wound to sequentially come into contact with at least portions of the pulley **121**, the pulley **122**, the pulley **128**, the pulley **124**, and the

pulley **126**.

(327) In other words, the wire **306** and the wire **302**, which are second jaw wires, are wound to sequentially come into contact with at least portions of the pulley **125**, the pulley **123**, the pulley **121**, the pulley **122**, the pulley **128**, the pulley **124**, and the pulley **126**, and are formed to move along the above pulleys while rotating the above pulleys.

(328) Accordingly, in the first modified example of the first embodiment of the present disclosure, two rows of first jaw pitch redundant pulleys and two rows of second jaw pitch redundant pulleys are provided, whereas in the second modified example of the first embodiment of the present disclosure, one row of a first jaw pitch redundant pulley and one row of a second jaw pitch redundant pulley are provided, and thus, an effect of reducing the number of parts and simplifying a manufacturing process may be achieved.

Third Modified Example of First Embodiment

(329) Hereinafter, the end tool **100** of the surgical instrument according to a third modified example of the first modified example of the first embodiment of the present disclosure will be described. In this regard, the end tool **100** of the surgical instrument according to the second modified example of the first embodiment of the present disclosure is different from the end tool of the surgical instrument according to the first embodiment of the present disclosure described above, in the configuration of the end tool hub. Hereinafter, the configuration that is different from that of the first modified example of the first embodiment will be described in detail.

(330) FIGS. **44** and **45** are perspective views illustrating the end tool of the surgical instrument according to the third modified example of the first embodiment of the present disclosure. FIG. **46** is a combined perspective view illustrating a second jaw of the end tool of FIG. **44**. FIG. **47** is an exploded perspective view illustrating the second jaw of the end tool of FIG. **44**. FIG. **48** is a combined perspective view illustrating a first jaw of the end tool of FIG. **44**. FIG. **49** is an exploded perspective view illustrating the first jaw of the end tool of FIG. **44**. FIGS. **50** and **51** are perspective views illustrating an end tool hub of the end tool of FIG. **44**. FIG. **52** is a plan view of the end tool of FIG. **44**. FIGS. **53** and **54** are side views of the end tool of FIG. **44**.

(331) Referring to FIGS. **44** to **54**, the end tool **100** according to the third modified example of the first embodiment of the present disclosure includes a pair of jaws for performing a grip motion, that is, the first jaw **101** and the second jaw **102**. In this regard, a component encompassing each of the first jaw **101** and the second jaw **102** or both the first jaw **101** and the second jaw **102** may be referred to as the jaw **103**.

(332) Meanwhile, an electric wire **411** may be coupled to the first jaw **101**, and an electric wire **412** may be coupled to the second jaw **102**.

(333) In addition, the end tool **100** of the third modified example of the first embodiment of the present disclosure may include an end tool hub **180** and the pitch hub **107**. The end tool hub **180** will be described in more detail below.

(334) In addition, the end tool **100** of the third modified example of the first embodiment of the present disclosure may include the rotation axis **141**, the rotation axis **142**, the rotation axis **143**, and the rotation axis **144**. As described above, the rotation axis **141** and the rotation axis **142** may be inserted through the end tool hub **106**, and the rotation axis **143** and the rotation axis **144** may be inserted through the pitch hub **107**.

(335) Meanwhile, the end tool **100** may include the pulley **111**, the pulley **112**, the pulley **113**, the pulley **114**, the pulley **115**, and the pulley **116**, which are associated with a rotational motion of the first jaw **101**. In addition, the end tool **100** may include the pulley **121**, the pulley **122**, the pulley **123**, the pulley **124**, the pulley **125**, and the pulley **126**, which are associated with a rotational motion of the second jaw **102**.

(336) In the present modified example, the first jaw **101**, the second jaw **102**, the pitch hub **107**, the respective pulleys, the respective rotation axes, and the like are substantially the same as those of the end tool **100** of the first embodiment described above with reference to FIG. **5** and the like, and

thus, detailed descriptions thereof will be omitted.

(337) Hereinafter, the end tool hub **180** of the third modified example of the first embodiment of the present disclosure will be described in more detail, and in particular, a first pitch redundant pulley part **183** and a second pitch redundant pulley part **184** of the end tool hub **180**, which serve as pitch redundant pulleys, will be mainly described.

(338) The end tool hub **180** includes a first jaw pulley coupling part **181**, a second jaw pulley coupling part **182**, the first pitch redundant pulley part **183**, the second pitch redundant pulley part **184**, and a pitch pulley coupling part **185**.

(339) In detail, the first jaw pulley coupling part **181** and the second jaw pulley coupling part **182** are formed to face each other such that the pulley **111**, the pulley **112**, the pulley **121**, and the pulley **122** are accommodated therein. In addition, a through hole is formed in each of the jaw pulley coupling parts **181** and **182** such that the rotation axis **141** passes through and axially couples the jaw pulley coupling parts **181** and **182**, the pulley **111**, and the pulley **121**. In addition, a through hole is formed in each of the jaw pulley coupling parts **181** and **182** such that the rotation axis **142** passes through and axially couples the jaw pulley coupling parts **181** and **182**, the pulley **112**, and the pulley **122**.

(340) The first jaw pulley coupling part **181** and the second jaw pulley coupling part **182** are connected to each other by a guide part **186**. That is, the first jaw pulley coupling part **181** and the second jaw pulley coupling part **182** parallel to each other are coupled by the guide part **186** formed in a direction substantially perpendicular thereto, such that the first jaw pulley coupling part **181**, the second jaw pulley coupling part **182**, and the guide part **186** form a substantially “C” shape in which the pulley **111**, the pulley **112**, the pulley **121**, and the pulley **122** are accommodated.

(341) In other words, it may also be described that the first jaw pulley coupling part **181** and the second jaw pulley coupling part **182** are formed to extend in the X-axis direction from both ends of the guide part **186** that is elongated in the Z-axis direction.

(342) The first pitch redundant pulley part **183** may be formed on one side surface of the guide part **186**, and the second pitch redundant pulley part **184** may be formed on the other side surface.

(343) In detail, the first pitch redundant pulley part **183** and the second pitch redundant pulley part **184**, each of which is formed in the shape of a disk like a pulley and has a groove formed on the outer circumferential surface thereof, around which a wire may be wound, may be formed on both side surfaces of the guide part **186**, respectively.

(344) In addition, the wire **305**, which is a first jaw wire, may be wound around the first pitch redundant pulley part **183**, and the wire **302**, which is a second jaw wire, may be wound around the second pitch redundant pulley part **184**.

(345) Meanwhile, the wire **301**, which is a first jaw wire, may pass through a side surface of the first pitch redundant pulley part **183**, and the wire **306**, which is a second jaw wire, may pass through a side surface of the second pitch redundant pulley part **184**.

(346) Meanwhile, the pulley **131** that serves as an end tool pitch pulley may be formed in the pitch pulley coupling part **185** at one end of the end tool hub **180**. In this regard, the pulley **131** may be formed with the end tool hub **180** as one body. That is, one end of the end tool hub **180** may be formed in a disk shape or a semicircular shape, and a groove around which a wire may be wound may be formed on an outer circumferential surface of the groove, such that a kind of guide channel is formed. Alternatively, the pulley **131** may be formed as a separate member from the end tool hub **180** and coupled to the end tool hub **180**. The wire **303** and the wire **304** described above are coupled to the pulley **131** serving as an end tool pitch pulley, and a pitch motion is performed as the pulley **131** is rotated around the rotation axis **143**.

(347) As such, as the first pitch redundant pulley part **183** and the second pitch redundant pulley part **184** is formed in the existing end tool hub **180** without adding a separate structure such as a pitch redundant pulley, it is possible to increase the range of rotation without adding additional

parts or manufacturing processes.

Fourth Modified Example of First Embodiment

(348) Hereinafter, the end tool **100** of the surgical instrument according to a fourth modified example of the first embodiment of the present disclosure will be described. In this regard, the end tool **100** of the surgical instrument according to the fourth modified example of the first embodiment of the present disclosure is different from the end tool of the surgical instrument according to the first modified example of the first embodiment of the present disclosure described above in that some of the pulleys are omitted. Hereinafter, the configuration that is different from that of the first modified example of the first embodiment will be described in detail.

(349) FIGS. **55** and **56** are perspective views illustrating the end tool of the surgical instrument according to the fourth modified example of the first embodiment of the present disclosure. FIGS. **57** and **58** are plan views of the end tool of FIG. **55**. FIGS. **59**, **60**, and **61** are side views of the end tool of FIG. **55**. FIGS. **62** and **63** are plan views of the end tool of FIG. **55**.

(350) Referring to FIGS. **55** to **63**, the end tool **100** according to the third modified example of the first embodiment of the present disclosure includes a pair of jaws for performing a grip motion, that is, the first jaw **101** and the second jaw **102**. In this regard, a component encompassing each of the first jaw **101** and the second jaw **102** or both the first jaw **101** and the second jaw **102** may be referred to as the jaw **103**.

(351) In addition, the end tool **100** of the fourth modified example of the first embodiment of the present disclosure may include the end tool hub **106** and the pitch hub **107**.

(352) In addition, the end tool **100** of the fourth modified example of the first embodiment of the present disclosure may include the rotation axis **141**, the rotation axis **142**, the rotation axis **145**, the rotation axis **143**, and the rotation axis **144**. As described above, the rotation axis **141**, the rotation axis **142**, and the rotation axis **145** may be inserted through the end tool hub **106**, and the rotation axis **143** and the rotation axis **144** may be inserted through the pitch hub **107**.

(353) In the present modified example, the end tool hub **106**, the pitch hub **107**, and the rotation axes **141**, **142**, **143**, **144**, and **145** are substantially the same as the end tool hub **106**, the pitch hub **107**, and the rotation axes **141**, **142**, **143**, **144**, and **145** that are described above with reference to FIG. **5** and the like, respectively, and thus, detailed descriptions thereof will be omitted.

(354) Meanwhile, the end tool **100** may include the pulley **111**, the pulley **112**, the pulley **113**, the pulley **114**, the pulley **115**, the pulley **117**, and the pulley **118**, which are associated with a rotational motion of the first jaw **101**. In addition, the end tool **100** may include the pulley **121**, the pulley **122**, the pulley **123**, the pulley **124**, the pulley **125**, the pulley **127**, and the pulley **128**, which are associated with a rotational motion of the second jaw **102**.

(355) In this regard, in the end tool **100** of the surgical instrument according to the fourth modified example of the first embodiment of the present disclosure, each of the first jaw pitch sub-pulley and the second jaw pitch sub-pulley includes only one pulley.

(356) In detail, the end tool **100** of the surgical instrument according to the first modified example of the first embodiment of the present disclosure illustrated in FIG. **34** and the like includes a pair of pulleys **115** and **116** as first jaw pitch sub-pulleys, and a pair of pulleys **125** and **126** as second jaw pitch sub-pulleys.

(357) On the contrary, the end tool **100** of the surgical instrument according to the fourth modified example of the first embodiment of the present disclosure is different from the first modified example of the first embodiment of the present disclosure illustrated in FIG. **34** and the like, in that it includes a single pulley **115** as a first jaw pitch sub-pulley, and a single pulley **125** as a second jaw pitch sub-pulley.

(358) Accordingly, the pulley **111**, the pulley **112**, the pulley **117/pulley 118**, the pulley **113/pulley 114**, and the pulley **115**, which are associated with rotation of the first jaw **101**, may be sequentially arranged from the distal end **104** of the end tool **100** toward the proximal end **105**.

(359) In addition, the pulley **121**, the pulley **122**, the pulley **127/pulley 128**, the pulley **123/pulley**

124, and the pulley **125**, which are associated with rotation of the second jaw **102**, may be sequentially arranged from the distal end **104** of the end tool **100** toward the proximal end **105**.

(360) In this regard, the pulley **116** and pulley **126** of the end tool **100** of the first modified example of the first embodiment of the present disclosure illustrated in FIG. **34** and the like are not pulleys around which wires are wound, but pulleys through which the wires pass in a straight line, and thus may be omitted as in the present modified example.

(361) In other words, in the first modified example of the first embodiment of the present disclosure, two rows of first jaw pitch sub-pulleys and two rows of second jaw pitch sub-pulleys are provided, whereas in the fourth modified example of the first embodiment of the present disclosure, one row of a first jaw pitch sub-pulley and one row of a second jaw pitch sub-pulley are provided.

(362) In this regard, the pulley **117**/pulley **118** are arranged on one side of the pulley **111** and the pulley **112**. In this regard, the pulley **117**/pulley **118** are formed to be rotatable around the rotation axis **145**, which is a pitch redundant rotation axis. In addition, the pulley **113** and the pulley **114** are arranged on one side of the pulley **117**/pulley **118** to face each other. In this regard, the pulley **113** and the pulley **114** are formed to be rotatable independently of each other around the rotation axis **143**, which is a pitch main rotation axis. In addition, the pulley **115** is arranged on one side of each of the pulley **113** and the pulley **114**. In this regard, the pulley **115** is formed to be rotatable around the rotation axis **144**, which is a pitch sub-rotation axis. In this regard, the drawings illustrate that the pulley **117**, the pulley **118**, the pulley **113**, the pulley **114**, and the pulley **115** are formed to be rotatable around the Y-axis direction, but the concept of the present disclosure is not limited thereto, and the rotation axes of the respective pulleys may be formed in various directions according to their configurations.

(363) The wire **301**, which is a first jaw wire, is wound to sequentially come into contact with at least portions of the pulley **115**, the pulley **113**, the pulley **117**, and the pulley **111**. In addition, the wire **305** connected to the wire **301** by the coupling member **323** is wound to sequentially come into contact with at least portions of the pulley **111**, the pulley **112**, the pulley **118**, and the pulley **114**.

(364) In other words, the wire **301** and the wire **305**, which are first jaw wires, are wound to sequentially come into contact with at least portions of the pulley **115**, the pulley **113**, the pulley **117**, the pulley **111**, the pulley **112**, the pulley **118**, and the pulley **114**, and are formed to move along the above pulleys while rotating the above pulleys.

(365) Meanwhile, the pulley **127**/pulley **128** are arranged on one side of the pulley **121** and the pulley **122**. In this regard, the pulley **127**/pulley **128** are formed to be rotatable around the rotation axis **145**, which is a pitch redundant rotation axis. In addition, the pulley **123** and the pulley **124** are arranged on one side of the pulley **127**/pulley **128** to face each other. In this regard, the pulley **123** and the pulley **124** are formed to be rotatable independently of each other around the rotation axis **143**, which is a pitch main rotation axis. In addition, the pulley **125** is arranged on one side of the pulley **123** and the pulley **124**. In this regard, the pulley **125** is formed to be rotatable around the rotation axis **144**, which is a pitch sub-rotation axis. In this regard, the drawings illustrate that the pulley **127**, the pulley **128**, the pulley **123**, the pulley **124**, the pulley **125**, and the pulley **126** are formed to be rotatable around the Y-axis direction, but the concept of the present disclosure is not limited thereto, and the rotation axes of the respective pulleys may be formed in various directions according to their configurations.

(366) The wire **306**, which is a second jaw wire, is wound to sequentially come into contact with at least portions of the pulley **125**, the pulley **123**, the pulley **127**, and the pulley **121**. In addition, the wire **302** connected to the wire **306** by the coupling member **326** is wound to sequentially come into contact with at least portions of the pulley **121**, the pulley **122**, the pulley **128**, and the pulley **124**.

(367) In other words, the wire **306** and the wire **302**, which are second jaw wires, are wound to

sequentially come into contact with at least portions of the pulley **125**, the pulley **123**, the pulley **127**, the pulley **121**, the pulley **122**, the pulley **128**, and the pulley **124**, and are formed to move along the above pulleys while rotating the above pulleys.

(368) Accordingly, in the first modified example of the first embodiment of the present disclosure, two rows of first jaw pitch sub-pulleys and two rows of second jaw pitch sub-pulleys are provided, whereas in the fourth modified example of the first embodiment of the present disclosure, one row of a first jaw pitch sub-pulley and one row of a second jaw pitch sub-pulley are provided, and thus, an effect of reducing the number of parts and simplifying a manufacturing process may be achieved.

Fifth Modified Example of First Embodiment

(369) Hereinafter, an end tool **100** of a surgical instrument according to a fifth modified example of the first embodiment of the present disclosure will be described. Here, the end tool **100** of the surgical instrument according to the fifth modified example of the first embodiment of the present disclosure is different from the end tool of the surgical instrument according to the first embodiment of the present disclosure described above in that the configuration of the end tool hub **180** serving as an auxiliary pulley is different. Such a configuration that is changed from that of the first embodiment will be described in detail later.

(370) FIGS. **64** and **65** are perspective views illustrating the end tool of the surgical instrument according to the fifth modified example of the first embodiment of the present disclosure. FIG. **66** is a plan view of the end tool of FIG. **64**. FIG. **67** is a perspective view of an end tool hub of the end tool of FIG. **64**. FIG. **68** is a side view of the end tool of FIG. **64**. FIG. **69** is a perspective view illustrating a state in which the end tool of the surgical instrument of FIG. **64** is pitch-rotated by -90° . FIG. **70** is a side view illustrating a state in which the end tool of the surgical instrument of FIG. **64** is pitch-rotated by $+90^\circ$. FIG. **71** is a perspective view illustrating a state in which the end tool of the surgical instrument of FIG. **64** is yaw-rotated by $+90^\circ$. FIG. **72** is a side view illustrating a state in which the end tool of the surgical instrument of FIG. **64** is yaw-rotated by -90° .

(371) Referring to FIGS. **64** to **72**, the end tool **100** of the first embodiment of the present disclosure includes a pair of jaws for performing a grip motion, that is, a first jaw **101** and a second jaw **102**. Here, each of the first jaw **101** and the second jaw **102**, or a component encompassing the first jaw **101** and the second jaw **102** may be referred to as a jaw **103**.

(372) Meanwhile, the end tool **100** includes a plurality of pulleys including a pulley **111** related to a rotational motion of the first jaw **101**. The pulleys related to the rotational motion of the first jaw **101** described in the present modified example are substantially the same as the pulley **111**, the pulley **112**, the pulley **113**, the pulley **114**, the pulley **115**, and the pulley **118** described with reference to FIG. **5** or the like of the first embodiment, and thus, detailed descriptions thereof will be omitted herein.

(373) Meanwhile, the end tool **100** includes a plurality of pulleys including a pulley **121** related to a rotational motion of the second jaw **102**. The pulleys related to the rotational motion of the second jaw **102** described in the present modified example are substantially the same as the pulley **121**, the pulley **122**, the pulley **123**, the pulley **124**, the pulley **125**, and the pulley **128** described with reference to FIG. **5** or the like of the first embodiment, and thus, detailed descriptions thereof will be omitted herein.

(374) Further, the end tool **100** of the first embodiment of the present disclosure may include an end tool hub **180** and a pitch hub **107**. The end tool hub **180** will be described in more detail later.

(375) Further, the end tool **100** of the fifth modified example of the first embodiment of the present disclosure may include a rotation shaft **141**, a rotation shaft **145**, a rotation shaft **143**, and a rotation shaft **144**. As described above, the rotation shaft **141** and the rotation shaft **145** may be inserted through the end tool hub **180**, and the rotation shaft **143** and the rotation shaft **144** may be inserted through the pitch hub **107**.

(376) In the present modified example, the pitch hub **107** and each of the rotation shafts **141**, **143**,

144, and **145** are substantially the same as the pitch hub **107** and each of the rotation shafts **141**, **143**, **144**, and **145** described in the first embodiment with reference to FIG. 5 or the like, and thus detailed descriptions thereof will be omitted herein.

(377) Also, the end tool **100** of the fifth modified example of the first embodiment of the present disclosure may include the end tool hub **180** and the pitch hub **107**.

(378) The rotation shaft **141** is inserted through the end tool hub **180**, and the pulley **111** and the pulley **121**, which are axially coupled to the rotation shaft **141**, and at least some of the first jaw **101** and the second jaw **102** coupled the pulley **111** and the pulley **121** may be accommodated inside the end tool hub **180**. Here, in an embodiment of the present disclosure, a guide part **183** serving as an auxiliary pulley is formed in the end tool hub **180**. That is, the guide part **183** configured to guide paths of wires **305** and **302** may be formed in the end tool hub **180**. The guide part **183** of the end tool hub **180** described above may serve as a kind of auxiliary pulley to reroute the wire, and the guide part **183** of the end tool hub **180** serving as an auxiliary pulley will be described in more detail later.

(379) Meanwhile, a pulley **131** serving as an end tool pitch pulley may be formed at one end portion of the end tool hub **180**. As shown in FIG. 64, the pulley **131** may be integrally formed with the end tool hub **180** as one body. In this case, the pulley **131** may be formed inside the end tool hub **180** in the form of a kind of guide channel to guide paths of the wire **303** and the wire **304**. Alternatively, the pulley **131** may be formed as a separate member from the end tool hub **180** to be coupled to the end tool hub **180**. In addition, the wire **303** and the wire **304** are coupled to the pulley **131** serving as an end tool pitch pulley, and a pitch motion is performed as the pulley **131** is rotated around the rotation shaft **143**.

(380) The rotation shaft **143** and the rotation shaft **144** are inserted through the pitch hub **107**, and the pitch hub **107** may be axially coupled to the end tool hub **180** and the pulley **131** by the rotation shaft **143**. Thus, the end tool hub **180** and the pulley **131** may be formed to be pitch-rotatable around the rotation shaft **143** with respect to the pitch hub **107**.

(381) Further, the pitch hub **107** may internally accommodate at least some of the pulley **113**, the pulley **114**, the pulley **123**, and the pulley **124** that are axially coupled to the rotation shaft **143**. In addition, the pitch hub **107** may internally accommodate at least some of the pulley **115** and the pulley **125** that are axially coupled to the rotation shaft **144**.

(382) Hereinafter, the end tool hub **180** of an embodiment of the present disclosure will be described in more detail, and in particular, the guide part **183** of the end tool hub **180** serving as an auxiliary pulley will be mainly described.

(383) The end tool hub **180** includes a pair of jaw pulley coupling parts **181** and **182**, the guide part **183**, a guide groove **184**, and a pitch pulley part **185**.

(384) In detail, the pair of jaw pulley coupling parts **181** and **182** are formed to face each other, and accommodate the pulley **111** and the pulley **121** therein. In addition, a through hole is formed in each of the jaw pulley coupling parts **181** and **182** such that the rotation shaft **141** passes through and axially couples the jaw pulley coupling parts **181** and **182**, the pulley **111**, and the pulley **121**.

(385) The pair of jaw pulley coupling parts **181** and **182** are connected to each other by the guide part **183**. That is, the pair of jaw pulley coupling parts **181** and **182** parallel to each other are coupled by the guide part **183** formed in a direction substantially perpendicular to the pair of jaw pulley coupling parts **181** and **182**, so that the pair of jaw pulley coupling parts **181** and **182** and the guide part **183** form a substantially C-shape, and accommodate the pulley **111** and the pulley **121** therein.

(386) In other words, it may be expressed that the pair of jaw pulley coupling parts **181** and **182** are formed to extend in the X-axis direction from both end portions of the guide part **183** formed to be elongated in the Z-axis direction.

(387) Here, the guide part **183** may be formed in a cylindrical shape with a cross section that is approximately semi-circular. In addition, the semi-circular portion may be disposed to protrude

toward the pulley **111** and the pulley **121**. In other words, it may be said that the guide part **183** is formed to protrude toward a space formed by the pair of jaw pulley coupling parts **181** and **182** and the guide part **183**. In other words, it may be said that a region of the guide part **183** adjacent to the jaw pulley coupling parts **181** and **182** is formed such that a cross section thereof is curved with a predetermined curvature.

(388) Alternatively, in other words, it may be also said that the wire guide part **183** serves as a kind of pulley member, which guides the paths of the wire **305** and the wire **302** by winding the wire **305** and the wire **302** around an outer circumferential surface thereof. However, here, the guide part **183** is not a member that is rotated around a predetermined axis like the original meaning pulley does, and it may be said that the guide part **183** is formed to be fixed as a portion of the end tool hub **180** and performs some similar functions of a pulley configured to guide a path of a wire by winding the wire therearound.

(389) Here, the guide part **183** is illustrated in the drawing as being formed in a cylindrical shape with a cross section that is approximately semi-circular. That is, at least a portion of the cross section of the guide part **183** on the XY plane is illustrated as having a certain arc shape. However, the concept of the present disclosure is not limited thereto, and the cross section may have a predetermined curvature like an elliptical shape or a parabola, or a corner of a polygonal column is rounded to a certain extent, so that the cross section may have various shapes and sizes suitable for guiding the paths of the wire **305** and the wire **302**.

(390) Here, the guide groove **184** for guiding the paths of the wire **305** and the wire **302** well may be further formed in a portion of the guide part **183**, which is in contact with the wire **305** and the wire **302**. The guide groove **184** may be formed in the form of a groove recessed to a certain extent from a protruding surface of the guide part **183**.

(391) Here, although the guide groove **184** is illustrated in the drawing as being formed in the entire arc surface of the guide part **183**, the concept of the present disclosure is not limited thereto, and the guide groove **184** may be formed only in a portion of the arc surface of the guide part **183** as necessary.

(392) As described above, by further forming the guide groove **184** in the guide part **183**, unnecessary friction between the wires is reduced, so that durability of the wires may be improved.

(393) The pitch pulley part **185** may be further formed in a direction opposite to a direction of formation of the jaw pulley coupling parts **181** and **182** in the guide part **183**. In addition, the pulley **131**, which is a pitch pulley around which the wire **303** and the wire **304** that are pitch wires may be wound, may be formed in the pitch pulley part **185**. However, here, the pulley **131** is not a member that is rotated around a predetermined axis like the original meaning pulley does, and it may be said that the pulley **131** is formed to be fixed as a portion of the end tool hub **180** and performs some similar functions of a pulley by winding a wire therearound. That is, the pulley **131** may be formed as a kind of groove in the pitch pulley part **185** of the end tool hub **180**, and the pulley **131** may serve as guide channels of the wire **303** and the wire **304**. Here, the pitch pulley part **185** may be formed on the XZ plane. In addition, a through hole through which the rotation shaft **143** may be inserted may be formed in the pitch pulley part **185**.

(394) Meanwhile, although not shown in the drawings, the pitch pulley part and the pitch pulley may be formed as separate members and may be coupled to each other, and the rotation shaft **143** may be formed to pass through the pitch pulley part and the pulley.

(395) Hereinafter, the role and function of the guide part **183** will be described in more detail.

(396) The guide part **183** may be in contact with the wire **305** and the wire **302** and may change the arrangement path of the wires **305** and **302** to a certain extent to serve to increase a rotation radius of each of the first jaw **101** and the second jaw **102**.

(397) That is, when the auxiliary pulley or the guide part **183** is not disposed, each of the pulley **111**, which is a first jaw pulley, and the pulley **121**, which is a second jaw pulley, may rotate up to a right angle, but in an embodiment of the present disclosure, by additionally providing the guide

part **183** in the end tool hub **180**, the maximum rotation angle of each pulley may be increased.

(398) This enables a motion that two jaws of the end tool **100** have to open for an actuation motion in a state in which the two jaws of the end tool **100** are yaw-rotated by 90°. In other words, a feature of increasing the range of a yaw rotation in which an actuation motion is possible may be obtained through the configuration of the guide part **183** of the end tool hub **180**.

(399) Furthermore, by forming the guide part **183** in the end tool hub **180**, which already exists, without adding a separate structure such as an auxiliary pulley, the range of rotation may be increased without adding a component and a manufacturing process.

(400) As described above, since there is no need to additionally dispose a separate structure for increasing the rotation angle, the number of components is decreased and the manufacturing process is simplified, and also, the length of the end tool is reduced by as much as the size of the auxiliary pulley, so that the length of the end tool is shortened during a pitch motion. Accordingly, a surgical motion may be more easily performed in a narrow space.

(401) This will be described below in more detail.

(402) In the end tool **100** of the surgical instrument according to an embodiment of the present disclosure, the arrangement path of the wires may be changed without a separate structure by forming the guide part **183** capable of changing the path of the wire on an inner side wall of the end tool hub **180**. As described above, as the arrangement path of the wire **305** and the wire **302** is changed to a certain degree by forming the guide part **183** in the end tool hub **180**, a tangential direction of the wire **305** and the wire **302** is changed, and accordingly, rotation angles of a coupling member **323** and a coupling member **326** that couple respective wires and pulleys may be increased.

(403) That is, the coupling member **326** that couples the wire **302** to the pulley **121** is rotatable until being located on a common internal tangent of the pulley **121** and the guide part **183**.

Similarly, a coupling member (see **323** of FIG. **11**) that couples the wire **305** to the pulley **111** is rotatable until being located on a common internal tangent of the pulley **111** and the guide part **183**, so that a rotation angle of the coupling member (see **323** of FIG. **11**) may be increased.

(404) In other words, due to the guide part **183**, the wire **301** and the wire **305** wound around the pulley **111** are disposed on one side with respect to a plane perpendicular to the Y-axis and passing through the X-axis. Simultaneously, due to the guide part **183**, the wires **302** and **306** wound around the pulley **121** are disposed on another side with respect to the plane perpendicular to the Y-axis and passing through the X-axis.

(405) In other words, the pulley **113** and the pulley **114** are disposed on one side with respect to the plane perpendicular to the Y-axis and passing through the X-axis, and the pulley **123** and the pulley **124** are disposed on another side with respect to the plane perpendicular to the Y-axis and passing through the X-axis.

(406) In other words, the wire **305** is located on the internal tangent of the pulley **111** and the guide part **183**, and the rotation angle of the pulley **111** is increased by the guide part **183**. In addition, the wire **302** is located on the internal tangent of the pulley **121** and the guide part **183**, and a rotation angle of the pulley **121** is increased by the guide part **183**.

(407) In the present embodiment in which an auxiliary pulley is not formed and the guide part **183** capable of changing the path of the wire is formed on the inner side wall of the end tool hub **180**, the length of the end tool of the surgical instrument may be reduced as compared to the surgical instrument in which a separate auxiliary pulley is formed. Since the length of the end tool is reduced as described above, a surgical operator may easily manipulate a surgical instrument, and side effects of surgery may be reduced when the surgery is performed in a narrow surgical space in the human body.

(408) According to the present disclosure as described above, the rotation radii of the pulley **111**, which is a first jaw pulley, and the pulley **121**, which is a second jaw pulley, increase, so that a yaw motion range in which a normal opening/closing actuation motion can be performed may be

increased.

(409) <Second Embodiment of End Tool of Surgical Instrument>

(410) Hereinafter, an end tool **1100** of a surgical instrument according to a second embodiment of the present disclosure will be described. In this regard, the end tool **1100** of the surgical instrument according to the second embodiment of the present disclosure is different from the end tool (see **100** of FIG. 5 and the like) of the surgical instrument according to the first embodiment of the present disclosure described above, in the arrangement of the jaw pulleys and the jaw wires. The configuration that is different from that of the first embodiment will be described in detail below.

(411) FIGS. 73 and 74 are perspective views illustrating the end tool of the surgical instrument according to the second embodiment of the present disclosure. FIGS. 75, 76, 77, and 78 are plan views of the end tool of FIG. 73. FIGS. 79, 80, and 81 are side views of the end tool of FIG. 73.

(412) Referring to FIGS. 73 to 81, a power transmission part **1300** of the end tool **1100** of the surgical instrument according to the second embodiment of the present disclosure may include a wire **1301**, a wire **1302**, a wire **1303**, a wire **1304**, a wire **1305**, and a wire **1306**. In the present embodiment, the wires are substantially the same as the wire **301**, the wire **302**, the wire **303**, the wire **304**, the wire **305**, and the wire **306** of the first embodiment described above with reference to FIG. 5 and the like, and thus, detailed descriptions thereof will be omitted.

(413) In addition, the power transmission part **1300** of the end tool **1100** of the surgical instrument according to the second embodiment of the present disclosure may include a coupling member **1321**, a coupling member **1322**, a coupling member **1323**, a coupling member **1324**, a coupling member **1326**, a coupling member **1327**, a coupling member **1329**, and the like, which are coupled to ends of the respective wires to combine the wires with the pulleys. In this regard, each of the coupling members may have various shapes as necessary, such as a ball shape, a tube shape, or the like. In the present embodiment, the coupling members are substantially the same as the coupling member **321**, the coupling member **322**, the coupling member **323**, the coupling member **324**, the coupling member **326**, and the coupling member **327** of the first embodiment described above with reference to FIG. 9 and the like, and thus, detailed descriptions thereof will be omitted.

(414) (End Tool)

(415) Hereinafter, the end tool **1100** of the surgical instrument of FIG. 73 will be described in more detail.

(416) Continuing to refer to FIGS. 73 to 81, the end tool **1100** of the second embodiment of the present disclosure includes a pair of jaws for performing a grip motion, that is, a first jaw **1101** and a second jaw **1102**. In this regard, a component encompassing each of the first jaw **1101** and the second jaw **1102** or both the first jaw **1101** and the second jaw **1102** may be referred to as a jaw **1103**.

(417) In addition, the end tool **1100** may include a pulley **1111**, a pulley **1112**, a pulley **1113**, a pulley **1114**, a pulley **1115**, a pulley **1116**, and a pulley **1118**, which are associated with a rotational motion of the first jaw **1101**. In addition, the end tool **1100** may include a pulley **1121**, a pulley **1122**, a pulley **1123**, a pulley **1124**, a pulley **1125**, a pulley **1126**, and a pulley **1128**, which are associated with a rotational motion of the second jaw **102**. These pulleys will be described in more detail below.

(418) In addition, the end tool **1100** of the second embodiment of the present disclosure may include an end tool hub **1106** and a pitch hub **1107**.

(419) A rotation axis **1141**, a rotation axis **1142**, and a rotation axis **1145** are inserted through the end tool hub **1106**. In addition, the end tool hub **1106** may internally accommodate at least portions of the pulley **1111** and the pulley **1121** that are axially coupled to the rotation axis **1141**. In addition, the end tool hub **1106** may internally accommodate at least portions of the pulley **1112** and the pulley **1122** that are axially coupled to the rotation axis **1142**. In addition, the pulley **1118** and the pulley **1128** that are axially coupled to the rotation axis **1145** may be coupled to the end tool hub **1106**.

(420) The rotation axis **1143** and a rotation axis **1144** may be inserted through the pitch hub **1107**, and the pitch hub **1107** may be axially coupled to the end tool hub **1106** and a pulley **1131** by the rotation axis **1143**. Thus, the end tool hub **1106** and the pulley **1131** (formed with the end tool hub **1106** as one body) may be formed to be rotatable around the rotation axis **1143** with respect to the pitch hub **1107**.

(421) In addition, the pitch hub **1107** may internally accommodate at least portions of the pulley **1113**, the pulley **1114**, the pulley **1123**, and the pulley **1124** that are axially coupled to the rotation axis **1143**. In addition, the pitch hub **1107** may internally accommodate at least portions of the pulley **1115**, the pulley **1116**, the pulley **1125**, and the pulley **1126** that are axially coupled to the rotation axis **1144**.

(422) In addition, the end tool **1100** of the second embodiment of the present disclosure may include the rotation axis **1141**, the rotation axis **1142**, the rotation axis **1145**, the rotation axis **1143**, and the rotation axis **1144**. As described above, the rotation axis **1141**, the rotation axis **1142**, and the rotation axis **1145** may be inserted through the end tool hub **1106**, and the rotation axis **1143** and the rotation axis **1144** may be inserted through the pitch hub **1107**.

(423) The rotation axis **1141**, the rotation axis **1142**, the rotation axis **1145**, the rotation axis **1143**, and the rotation axis **1144** may be arranged sequentially from a distal end **1104** of the end tool **1100** toward a proximal end **1105**. Accordingly, starting from the distal end **1104**, the rotation axis **1141** may be referred to as a first pin, the rotation axis **1142** may be referred to as a second pin, the rotation axis **1145** may be referred to as a two-and-a-halfth pin, the rotation axis **1143** may be referred to as a third pin, and the rotation axis **1144** may be referred to as a fourth pin.

(424) In this regard, the rotation axis **1141** may function as a jaw pulley rotation axis, the rotation axis **1142** may function as a jaw auxiliary pulley rotation axis, the rotation axis **1143** may function as a pitch main rotation axis, and the rotation axis **1144** may function as a pitch sub-rotation axis of the end tool **1100**. In addition, the rotation axis **1145** arranged between the rotation axis **1142** and the rotation axis **1143** may function as a pitch redundant rotation axis of the end tool **1100**.

(425) In the present embodiment, the end tool hub **1106**, the pitch hub **1107**, and the rotation axes **1141**, **1142**, **1143**, **1144**, and **1145** are substantially the same as the end tool hub **106**, the pitch hub **107**, and the rotation axes **141**, **142**, **143**, **144**, and **145** that are described above with reference to FIG. 5 and the like, respectively, and thus, detailed descriptions thereof will be omitted.

(426) Meanwhile, one or more pulleys may be fit into each of the rotation axes **1141**, **1142**, **1143**, **1144**, and **1145**, and this will be described in detail below.

(427) The pulley **1111** functions as a first jaw pulley, the pulley **1121** functions as a second jaw pulley, and these two components may be collectively referred to as a jaw pulley.

(428) The pulley **1111** and the pulley **1121**, which are jaw pulleys, are formed to face each other, and are formed to be rotatable independently of each other around the rotation axis **1141**, which is a jaw pulley rotation axis. In this regard, the drawings illustrate that the pulley **1111** and the pulley **1121** are formed to be rotated around one rotation axis **1141**, but it is needless to say that each jaw pulley may be formed to be rotatable around a separate shaft. In this regard, the first jaw **1101** may be fixedly coupled to the pulley **1111** to be rotated together with the pulley **1111**, and the second jaw **1102** may be fixedly coupled to the pulley **1121** to be rotated together with the pulley **1121**. Yaw and actuation motions of the end tool **1100** are performed according to rotation of the pulley **1111** and the pulley **1121**. That is, when the pulley **1111** and the pulley **1121** are rotated in the same direction around the rotation axis **1141**, the yaw motion is performed, and when the pulley **1111** and the pulley **1121** are rotated in opposite directions around the rotation axis **1141**, the actuation motion is performed.

(429) In this regard, the first jaw **1101** and the pulley **1111** may be formed as separate members and coupled to each other, or the first jaw **1101** and the pulley **1111** may be formed as one body. Similarly, the second jaw **1102** and the pulley **1121** may be formed as separate members and coupled to each other, or the second jaw **1102** and the pulley **1121** may be formed as one body.

(430) In this regard, a groove **1111a** around which the wire **1301**/wire **1305**, which are first wires, are wound in the pulley **1111**, which is a first jaw pulley, and a groove **1121a** around which the wire **1302**/wire **1306**, which are second wires, are wound in the pulley **1121**, which is a second jaw pulley, are arranged adjacent to each other. Thus, the wire **1301**/wire **1305**, which are first jaw wires, and the wire **1302** and the wire **1306**, which are second jaw wires, are arranged adjacent to each other in the Z-axis direction, and thus, there may not be a space in which a separate structure is to be arranged, between the first jaw wires and the second jaw wires.

(431) The pulley **1112** functions as a first jaw auxiliary pulley, the pulley **1122** functions as a second jaw auxiliary pulley, and these two components may be collectively referred to as a jaw auxiliary pulley.

(432) In detail, the pulley **1112** and the pulley **1122**, which are jaw auxiliary pulleys, may be additionally provided on one side of the pulley **1111** and the pulley **1121**. In other words, the pulley **1112**, which is a jaw auxiliary pulley, may be arranged between the pulley **1111** and the pulley **1113**/pulley **1114**. In addition, the pulley **1122**, which is a jaw auxiliary pulley, may be arranged between pulley **1121** and pulley **1123**/pulley **1124**. The pulley **1112** and the pulley **1122** may be formed to be rotatable independently of each other around the rotation axis **1142**. In this regard, the drawings illustrate that the pulley **1112** and the pulley **1122** are formed to be rotated around one rotation axis **1142**, but it is needless to say that the pulley **1112** and the pulley **1122** may be formed to be rotatable around separate shafts, respectively. Such an auxiliary pulley will be described below in more detail.

(433) The pulley **1113** and the pulley **1114** may function as first jaw pitch main pulleys, the pulley **1123** and the pulley **1124** may function as second jaw pitch main pulleys, and these two components may be collectively referred to as a pitch main pulley.

(434) The pulley **1115** and the pulley **1116** may function as first jaw pitch sub-pulleys, the pulley **1125** and the pulley **1126** may function as second jaw pitch sub-pulleys, and these two components may be collectively referred to as a pitch sub-pulley.

(435) Meanwhile, according to the present disclosure, the pulley **1118**, and the pulley **1128**, which are pitch redundant pulleys, are further arranged between the pulley **1112** and the pulley **1122**, which are jaw auxiliary pulleys, and the pulley **1113**, the pulley **1114**, the pulley **1123**, and the pulley **1124**, which are pitch main pulleys.

(436) The pulley **1118** may function as first jaw pitch redundant pulleys, the pulley **1128** may function as second jaw pitch redundant pulleys, and these two components may be collectively referred to as a pitch redundant pulley.

(437) In addition, the rotation axis **1145** functioning as a pitch redundant rotation axis may be further provided, and the rotation axis **1145** may be inserted through the end tool hub **1106**. In this regard, the rotation axis **1145** may be formed to be substantially parallel to the rotation axis **1143**, which is a pitch main rotation axis, and the rotation axis **1144**, which is a pitch sub-rotation axis. In this regard, the rotation axis **1145** is arranged between the rotation axis **1142**, which is the second pin, and the rotation axis **1143**, which is the third pin, and thus may be referred to as the two-and-a-halfth pin in terms of its position.

(438) The pitch redundant pulleys may serve to change insertion/withdrawal paths of jaw wires entering from the proximal end of the end tool to the distal end, or coming out from the distal end to the proximal end. This will be described in more detail below.

(439) Accordingly, the rotation axis **1141**, the rotation axis **1142**, the rotation axis **1145**, the rotation axis **1143**, and the rotation axis **1144** may be sequentially arranged from the distal end **1104** of the end tool **1100** toward the proximal end **1105**.

(440) In addition, the pulley **1111**, the pulley **1112**, the pulley **1118**, the pulley **1113**/pulley **1114**, and the pulley **1115**/pulley **1116**, which are associated with rotation of the first jaw **1101**, may be sequentially arranged from the distal end **1104** of the end tool **1100** toward the proximal end **1105**.

(441) In addition, the pulley **1121**, the pulley **1122**, the pulley **1128**, the pulley **1123**/pulley **1124**,

and the pulley **1125**/pulley **1126**, which are associated with rotation of the second jaw **1102**, may be sequentially arranged from the distal end **1104** of the end tool **1100** toward the proximal end **1105**.

(442) Hereinafter, components associated with the rotation of the pulley **1111** will be described.

(443) The pulley **1113** and the pulley **1114** are paired to function as first jaw pitch main pulleys. That is, the pulley **1113** and the pulley **1114** function as main rotation pulleys for a pitch motion of the first jaw **1101**. In this regard, the wire **1301**, which is a first jaw wire, is wound around the pulley **1113**, and the wire **1305**, which is a first jaw wire, is wound around the pulley **1114**.

(444) The pulley **1115** and the pulley **1116** are paired to function as first jaw pitch sub-pulleys. That is, the pulley **1115** and the pulley **1116** function as sub-rotation pulleys for a pitch motion of the first jaw **1101**. In this regard, the wire **1301**, which is a first jaw wire, is wound around the pulley **1115**, and the wire **1305**, which is a first jaw wire, is wound around the pulley **1116**.

(445) The pulley **1118** functions as first jaw redundant pulleys. That is, the pulley **1118** functions as redundant rotation pulleys for a pitch motion of the first jaw **1101**. In this regard, the wire **1305**, which is a first jaw wire, is wound around the pulley **1118**.

(446) In this regard, the pulley **1118** is arranged on one side of the pulley **1111** and the pulley **1112**. In this regard, the pulley **1118** is formed to be rotatable around the rotation axis **1145**, which is a pitch redundant rotation axis. In addition, the pulley **1113** and the pulley **1114** are arranged on one sides of the pulley **1118**, respectively, to face each other. In this regard, the pulley **1113** and the pulley **1114** are formed to be rotatable independently of each other around the rotation axis **1143**, which is a pitch main rotation axis. In addition, the pulley **1115** and the pulley **1116** are arranged on one sides of the pulley **1113** and the pulley **1114**, respectively, to face each other. In this regard, the pulley **1115** and the pulley **1116** are formed to be rotatable independently of each other around the rotation axis **1144**, which is a pitch sub-rotation axis. In this regard, the drawings illustrate that the pulley **1118**, the pulley **1113**, the pulley **1114**, the pulley **1115**, and the pulley **1116** are formed to be rotatable around the Y-axis direction, but the concept of the present disclosure is not limited thereto, and the rotation axes of the respective pulleys may be formed in various directions according to their configurations.

(447) The wire **1301**, which is a first jaw wire, is wound to sequentially come into contact with at least portions of the pulley **1115**, the pulley **1113**, and the pulley **1111**. In addition, the wire **1305** connected to the wire **1301** by the coupling member **1323** is wound to sequentially come into contact with at least portions of the pulley **1111**, the pulley **1112**, the pulley **1118**, the pulley **1114**, and the pulley **1116**.

(448) In other words, the wire **1301** and the wire **1305**, which are first jaw wires, are wound to sequentially come into contact with at least portions of the pulley **1115**, the pulley **1113**, the pulley **1111**, the pulley **1112**, the pulley **1118**, the pulley **1114**, and the pulley **1116**, and are formed to move along the above pulleys while rotating the above pulleys.

(449) Accordingly, when the wire **1301** is pulled in the direction of an arrow **1301** of FIG. 77, the coupling member **1323** to which the wire **1301** is coupled and the pulley **1111** coupled to the coupling member **1323** are rotated in the direction of an arrow L of FIG. 77. On the contrary, when the wire **1305** is pulled in the direction of an arrow **1305** of FIG. 64, the coupling member **1323** to which the wire **1305** is coupled and the pulley **1111** coupled to the coupling member **1323** are rotated in the direction of an arrow R of FIG. 77.

(450) Next, components associated with the rotation of the pulley **1121** will be described.

(451) The pulley **1123** and the pulley **1124** are paired to function as second jaw pitch main pulleys. That is, the pulley **1123** and the pulley **1124** function as main rotation pulleys for a pitch motion of the second jaw **1102**. In this regard, the wire **1306**, which is a second jaw wire, is wound around the pulley **1123**, and the wire **1302**, which is a second jaw wire, is wound around the pulley **1124**.

(452) The pulley **1125** and the pulley **1126** are paired to function as second jaw pitch sub-pulleys. That is, the pulley **1125** and the pulley **1126** may function as sub-rotation pulleys for a pitch motion of the second jaw **1102**. In this regard, the wire **1306**, which is a second jaw wire, is wound around

the pulley **1125**, and the wire **1302**, which is a second jaw wire, is wound around the pulley **1126**. (453) The pulley **1128** functions as second jaw pitch redundant pulleys. That is, the pulley **1128** functions as redundant rotation pulleys for a pitch motion of the second jaw **1102**. In this regard, the wire **1302**, which is a second jaw wire, is wound around the pulley **1128**.

(454) In this regard, the pulley **1128** is arranged on one side of the pulley **1121** and the pulley **1122**. In this regard, the pulley **1128** is formed to be rotatable around the rotation axis **1145**, which is a pitch redundant rotation axis. In addition, the pulley **1123** and the pulley **1124** are arranged on one sides of the pulley **1128**, respectively, to face each other. In this regard, the pulley **1123** and the pulley **1124** are formed to be rotatable independently of each other around the rotation axis **1143**, which is a pitch main rotation axis. In addition, the pulley **1125** and the pulley **1126** are arranged on one sides of the pulley **1123** and the pulley **1124**, respectively, to face each other. In this regard, the pulley **1125** and the pulley **1126** are formed to be rotatable independently of each other around the rotation axis **1144**, which is a pitch sub-rotation axis. In this regard, the drawings illustrate that the pulley **1128**, the pulley **1123**, the pulley **1124**, the pulley **1125**, and the pulley **1126** are formed to be rotatable around the Y-axis direction, but the concept of the present disclosure is not limited thereto, and the rotation axes of the respective pulleys may be formed in various directions according to their configurations.

(455) The wire **1306**, which is a second jaw wire, is wound to sequentially come into contact with at least portions of the pulley **1125**, the pulley **1123**, and the pulley **1121**. In addition, the wire **1302** connected to the wire **1306** by the coupling member **1326** is wound to sequentially come into contact with at least portions of the pulley **1121**, the pulley **1122**, the pulley **1128**, the pulley **1124**, and the pulley **1126**.

(456) In other words, the wire **1306** and the wire **1302**, which are second jaw wires, are wound to sequentially come into contact with at least portions of the pulley **1125**, the pulley **1123**, the pulley **1121**, the pulley **1122**, the pulley **1128**, the pulley **1124**, and the pulley **1126**, and are formed to move along the above pulleys while rotating the above pulleys.

(457) Accordingly, when the wire **1306** is pulled in the direction of an arrow **1306** of FIG. 77, the coupling member **1326** to which the wire **1306** is coupled and the pulley **1121** coupled to the coupling member **1326** are rotated in the direction of the arrow R of FIG. 77. On the contrary, when the wire **1302** is pulled in the direction of an arrow **302** of FIG. 77, the coupling member **1326** to which the wire **1302** is coupled and the pulley **1121** coupled to the coupling member **1326** are rotated in the direction of an arrow L of FIG. 64.

(458) In this regard, according to the present disclosure, two strands of jaw wires wound around one jaw pulley are wound around pitch main pulleys in opposite directions, such that a pitch motion is easily controlled.

(459) In detail, when the side above, in the +Z-axis direction, a plane passing between the pulley **1111**, which is a first jaw pulley, and the pulley **1121**, which is a second jaw pulley (i.e., an XY plane) is defined as an upper side and the side below the plane in the -Z-axis direction is defined as a lower side, any one (e.g., the wire **1301**) of the two strands of the first jaw wires may enter the pulley **1113**, which is a first jaw pitch main pulley, from the lower side of the XY plane, and the other strand (e.g., the wire **1305**) may come out of the pulley **1114**, which is a first jaw pitch main pulley, from the upper side of the XY plane. In other words, it may be described as a structure in which the jaw wire enters the first jaw pitch main pulley from the lower side and comes out from the upper side. (The second jaw wire enters the second jaw pitch main pulley from the upper side and comes out from the lower side)

(460) In other words, the wire **1301**, which is one strand of the first jaw wires, sequentially comes into contact with the upper side of the pulley **1115**, the lower side of the pulley **1113**, and then comes into contact with the pulley **1111**. Next, the wire **1305**, which is the other strand of the first jaw wires, is wound around the pulley **1111** and the pulley **1112**, and then sequentially comes into contact with the lower side of the pulley **1118**, the upper side of the pulley **1114**, and the lower side

of the pulley **1116**, and then comes out toward the connection part **400**. Accordingly, the first jaw wire comes out of the connection part **400**, enters the pulley **1113** from the lower side, then passes through each pulley, then passes through the upper side of the pulley **1114**, and then enters back the connection part **400**.

(461) Similarly, the wire **1306**, which is one strand of the second jaw wires, sequentially comes into contact with the lower side of the pulley **1125**, the upper side of the pulley **1123**, and then comes into contact with the pulley **1121**. Next, the wire **1302**, which is the other strand of the second jaw wires, is wound around the pulley **1121** and the pulley **1122**, and then sequentially comes into contact with the upper side of the pulley **1128**, the lower side of the pulley **1124**, and the upper side of the pulley **1126**, and then comes out toward the connection part **400**. Accordingly, the second jaw wire comes out of the connection part **400**, enters the pulley **1123** from the upper side, then passes through each pulley, then passes through the lower side of the pulley **1124**, and then enters back the connection part **400**.

(462) In other words, it may also be described that, any one wire of the two strands of the first jaw wires is wound around the first jaw pitch main pulley in any one of the clockwise direction and the counterclockwise direction while moving toward the end tool **1100** from a connection part **1400**, and the other wire is wound around the first jaw pitch main pulley in the other one of the clockwise direction and the counterclockwise direction while moving toward the end tool **1100** from the connection part **1400**. That is, as illustrated in FIGS. **79**, **80**, and **81**, the wire **1301** is wound in the clockwise direction while moving toward the end tool **1100** from the connection part **1400**, and the wire **1305** is wound in the counterclockwise direction while moving toward the end tool **1100** from the connection part **400**.

(463) Similarly, it may also be described that, any one wire of the two strands of the second jaw wires is wound around the second jaw pitch main pulley in any one of the clockwise direction and the counterclockwise direction while moving toward the end tool **1100** from the connection part **1400**, and the other wire is wound around the second jaw pitch main pulley in the other one of the clockwise direction and the counterclockwise direction while moving toward the end tool **1100** from the connection part **1400**. That is, as illustrated in FIGS. **66**, **67**, and **68**, the wire **1302** is wound in the clockwise direction while moving toward the end tool **1100** from the connection part **1400**, and the wire **1306** is wound in the counterclockwise direction while moving toward the end tool **1100** from the connection part **400**.

(464) As such, the end tool **1100** of the surgical instrument according to an embodiment of the present disclosure may obtain an effect of facilitating control of the pitch motion as the two strands of the jaw wires wound around one jaw pulley are wound around the pitch main pulleys in opposite directions. That is, during a pitch motion, the drive part first jaw pulley (see **211**, **212** of FIG. **21**) and the drive part second jaw pulley (see **221**, **222** of FIG. **21**) are rotated to wind or unwind the jaw wires, and thus perform a kind of compensation for the pitch motion, enabling the pitch motion of the end tool **1100**.

First Modified Example of Second Embodiment

(465) Hereinafter, the end tool **1100** of the surgical instrument according to a first modified example of the second embodiment of the present disclosure will be described. In this regard, the end tool **1100** of the surgical instrument according to the first modified example of the second embodiment of the present disclosure is different from the end tool of the surgical instrument according to the first embodiment of the present disclosure described above in that some of the pulleys are omitted. Hereinafter, the configuration that is different from that of the first embodiment will be described in detail.

(466) FIGS. **82** and **83** are perspective views illustrating an end tool of a surgical instrument according to the first modified example of the second embodiment of the present disclosure. FIGS. **84** and **85** are plan views of the end tool of FIG. **82**. FIGS. **86**, **87**, and **88** are side views of the end tool of FIG. **82**. FIGS. **89** and **90** are plan views of the end tool of FIG. **82**.

(467) Referring to FIGS. **82** to **90**, the end tool **1100** according to the first modified example of the second embodiment of the present disclosure includes a pair of jaws for performing a grip motion, that is, the first jaw **1101** and the second jaw **1102**. In this regard, a component encompassing each of the first jaw **1101** and the second jaw **1102** or both the first jaw **1101** and the second jaw **1102** may be referred to as the jaw **1103**.

(468) In addition, the end tool **1100** of the first modified example of the second embodiment of the present disclosure may include the end tool hub **1106** and the pitch hub **1107**.

(469) In addition, the end tool **1100** of the first modified example of the second embodiment of the present disclosure may include the rotation axis **1141**, the rotation axis **1142**, the rotation axis **1145**, the rotation axis **1143**, and the rotation axis **1144**. As described above, the rotation axis **1141**, the rotation axis **1142**, and the rotation axis **1145** may be inserted through the end tool hub **1106**, and the rotation axis **1143** and the rotation axis **1144** may be inserted through the pitch hub **1107**.

(470) In the present modified example, the end tool hub **1106**, the pitch hub **1107**, and the rotation axes **1141**, **1142**, **1143**, **1144**, and **1145** are substantially the same as the end tool hub **1106**, the pitch hub **1107**, and the respective rotation axes that are described above with reference to FIG. **73** and the like, respectively, and thus, detailed descriptions thereof will be omitted.

(471) Meanwhile, the end tool **1100** may include the pulley **1111**, the pulley **1112**, the pulley **1113**, the pulley **1114**, the pulley **1115**, and the pulley **1118**, which are associated with a rotational motion of the first jaw **1101**. In addition, the end tool **1100** may include the pulley **1121**, the pulley **1122**, the pulley **1123**, the pulley **1124**, the pulley **1125**, and the pulley **1128**, which are associated with a rotational motion of the second jaw **1102**.

(472) In this regard, in the end tool **1100** of the surgical instrument according to the first modified example of the second embodiment of the present disclosure, each of the first jaw pitch sub-pulley and the second jaw pitch sub-pulley includes only one pulley.

(473) In detail, the end tool **1100** of the surgical instrument according to the second embodiment of the present disclosure illustrated in FIG. **73** and the like includes a pair of pulleys **1115** and **1116** as first jaw pitch sub-pulleys, and a pair of pulleys **1125** and **1126** as second jaw pitch sub-pulleys.

(474) On the contrary, the end tool **1100** of the surgical instrument according to the first modified example of the second embodiment of the present disclosure is different from the second embodiment of the present disclosure illustrated in FIG. **60** and the like, in that it includes a single pulley **1115** as a first jaw pitch sub-pulley, and a single pulley **1125** as a second jaw pitch sub-pulley.

(475) Accordingly, the pulley **1111**, the pulley **1112**, the pulley **1118**, the pulley **1113**/pulley **1114**, and the pulley **1115**, which are associated with rotation of the first jaw **1101**, may be sequentially arranged from the distal end **1104** of the end tool **1100** toward the proximal end **1105**.

(476) In addition, the pulley **1121**, the pulley **1122**, the pulley **1128**, the pulley **1123**/pulley **1124**, and the pulley **1125**, which are associated with rotation of the second jaw **1102**, may be sequentially arranged from the distal end **1104** of the end tool **1100** toward the proximal end **1105**.

(477) In this regard, the pulley **1116** and pulley **1126** of the end tool **1100** of the second embodiment of the present disclosure illustrated in FIG. **73** and the like are not pulleys around which wires are wound, but pulleys through which the wires pass in a straight line, and thus may be omitted as in the present modified example.

(478) In other words, in the second embodiment of the present disclosure, two rows of first jaw pitch sub-pulleys and two rows of second jaw pitch sub-pulleys are provided, whereas in the first modified example of the second embodiment of the present disclosure, one row of a first jaw pitch sub-pulley and one row of a second jaw pitch sub-pulley are provided.

(479) In this regard, the pulley **1118** is arranged on one side of the pulley **1111** and the pulley **1112**. In this regard, the pulley **1118** are formed to be rotatable around the rotation axis **1145**, which is a pitch redundant rotation axis. In addition, the pulley **1113** and the pulley **1114** are arranged on one side of the pulley **1117**/pulley **1118** to face each other. In this regard, the pulley **1113** and the pulley

1114 are formed to be rotatable independently of each other around the rotation axis **1143**, which is a pitch main rotation axis. In addition, the pulley **1115** is arranged on one side of the pulley **1113** and the pulley **1114**. In this regard, the pulley **1115** is formed to be rotatable around the rotation axis **1144**, which is a pitch sub-rotation axis. In this regard, the drawings illustrate that the pulley **1118**, the pulley **1113**, the pulley **1114**, and the pulley **1115** are formed to be rotatable around the Y-axis direction, but the concept of the present disclosure is not limited thereto, and the rotation axes of the respective pulleys may be formed in various directions according to their configurations.

(480) The wire **1301**, which is a first jaw wire, is wound to sequentially come into contact with at least portions of the pulley **1115**, the pulley **1113**, and the pulley **1111**. In addition, the wire **1305** connected to the wire **1301** by the coupling member **1323** is wound to sequentially come into contact with at least portions of the pulley **1111**, the pulley **1112**, the pulley **1118**, and the pulley **1114**.

(481) In other words, the wire **1301** and the wire **1305**, which are first jaw wires, are wound to sequentially come into contact with at least portions of the pulley **1115**, the pulley **1113**, the pulley **1111**, the pulley **1112**, the pulley **1118**, and the pulley **1114**, and are formed to move along the above pulleys while rotating the above pulleys.

(482) Meanwhile, the pulley **1128** is arranged on one side of the pulley **1121** and the pulley **1122**. In this regard, the pulley **1128** are formed to be rotatable around the rotation axis **1145**, which is a pitch redundant rotation axis. In addition, the pulley **1123** and the pulley **1124** are arranged on one side of the pulley **1128** to face each other. In this regard, the pulley **1123** and the pulley **1124** are formed to be rotatable independently of each other around the rotation axis **1143**, which is a pitch main rotation axis. In addition, the pulley **1125** is arranged on one side of the pulley **1123** and the pulley **1124**. In this regard, the pulley **1125** is formed to be rotatable around the rotation axis **1144**, which is a pitch sub-rotation axis. In this regard, the drawings illustrate that the pulley **1128**, the pulley **1123**, the pulley **1124**, the pulley **1125**, and the pulley **1126** are formed to be rotatable around the Y-axis direction, but the concept of the present disclosure is not limited thereto, and the rotation axes of the respective pulleys may be formed in various directions according to their configurations.

(483) The wire **1306**, which is a second jaw wire, is wound to sequentially come into contact with at least portions of the pulley **1125**, the pulley **1123**, and the pulley **1121**. In addition, the wire **1302** connected to the wire **1306** by the coupling member **1326** is wound to sequentially come into contact with at least portions of the pulley **1121**, the pulley **1122**, the pulley **1128**, and the pulley **1124**.

(484) In other words, the wire **1306** and the wire **1302**, which are second jaw wires, are wound to sequentially come into contact with at least portions of the pulley **1125**, the pulley **1123**, the pulley **1121**, the pulley **1122**, the pulley **1128**, and the pulley **1124**, and are formed to move along the above pulleys while rotating the above pulleys.

(485) Accordingly, in the second embodiment of the present disclosure, two rows of first jaw pitch sub-pulleys and two rows of second jaw pitch sub-pulleys are provided, whereas in the first modified example of the second embodiment of the present disclosure, one row of a first jaw pitch sub-pulley and one row of a second jaw pitch sub-pulley are provided, and thus, an effect of reducing the number of parts and simplifying a manufacturing process may be achieved.

(486) <Third Embodiment of End Tool of Surgical Instrument>

(487) Hereinafter, an end tool **2100** of a surgical instrument according to a third embodiment of the present disclosure will be described. In this regard, the end tool **2100** of the surgical instrument according to the third embodiment of the present disclosure is different from the end tool (see **100** of FIG. 5 and the like) of the surgical instrument according to the first embodiment of the present disclosure described above, in the arrangement of the jaw pulleys and the jaw wires. The configuration that is different from that of the first embodiment will be described in detail below.

(488) FIGS. **91**, **92**, **93**, and **94** are perspective views illustrating an end tool of a surgical

instrument according to the third embodiment of the present disclosure. FIGS. **95** and **96** are plan views of the end tool of FIG. **91**. FIGS. **97**, **98**, and **99** are side views of the end tool of FIG. **91**. FIGS. **100** and **101** are plan views of the end tool of FIG. **91**. FIG. **102** is a perspective view of an end tool hub of the end tool of FIG. **91**, FIG. **103** is a front view of the end tool hub of the end tool of FIG. **91**, and FIG. **104** is a side view of the end tool hub of the end tool of FIG. **91**.

(489) Referring to FIGS. **91** to **104**, a power transmission part **2300** of the end tool **2100** of the surgical instrument according to the third embodiment of the present disclosure may include a wire **2301**, a wire **2302**, a wire **2303**, a wire **2304**, a wire **2305**, and a wire **2306**. In the present embodiment, the wires are substantially the same as the wire **301**, the wire **302**, the wire **303**, the wire **304**, the wire **305**, and the wire **306** of the first embodiment described above with reference to FIG. **9** and the like, and thus, detailed descriptions thereof will be omitted.

(490) In addition, the power transmission part **2300** of the end tool **2100** of the surgical instrument according to the third embodiment of the present disclosure may include a coupling member **2321**, a coupling member **2322**, a coupling member **2323**, a coupling member **2326**, and the like, which are coupled to ends of the respective wires to combine the wires with the pulleys. In this regard, each of the coupling members may have various shapes as necessary, such as a ball shape, a tube shape, or the like. In the present embodiment, the coupling members are substantially the same as the coupling member **321**, the coupling member **322**, the coupling member **323**, and the coupling member **326** of the first embodiment described above with reference to FIG. **9** and the like, and thus, detailed descriptions thereof will be omitted.

(491) (End Tool)

(492) Hereinafter, the end tool **2100** of the surgical instrument of FIG. **91** will be described in more detail.

(493) Continuing to refer to FIGS. **91** to **104**, the end tool **2100** of the third embodiment of the present disclosure includes a pair of jaws for performing a grip motion, that is, a first jaw **2101** and a second jaw **2102**. In this regard, a component encompassing each of the first jaw **2101** and the second jaw **2102** or both the first jaw **2101** and the second jaw **2102** may be referred to as a jaw **2103**.

(494) In addition, the end tool **2100** may include a pulley **2111**, a pulley **2112**, a pulley **2113**, a pulley **2114**, a pulley **2115**, and a pulley **2116**, which are associated with a rotational motion of the first jaw **2101**. In addition, the end tool **2100** may include a pulley **2121**, a pulley **2122**, a pulley **2123**, a pulley **2124**, a pulley **2125**, and a pulley **2126**, which are associated with a rotational motion of the second jaw **2102**. These pulleys will be described in more detail below.

(495) In addition, the end tool **2100** of the third embodiment of the present disclosure may include an end tool hub **2180** and a pitch hub **2107**. The end tool hub **2180** will be described in more detail below.

(496) In this regard, the end tool hub **2180** may internally accommodate at least portions of the pulley **2111** and the pulley **2121** that are axially coupled to a rotation axis **2141**. In addition, the end tool hub **2180** may internally accommodate at least portions of the pulley **2112** and the pulley **2122** that are axially coupled to a rotation axis **2142**.

(497) A rotation axis **2143** and a rotation axis **2144** may be inserted through the pitch hub **2107**, and the pitch hub **2107** may be axially coupled to the end tool hub **2180** and a pulley **2131** by the rotation axis **2143**. Thus, the end tool hub **2180** and the pulley **2131** (formed with the end tool hub **2180** as one body) may be formed to be rotatable around the rotation axis **2143** with respect to the pitch hub **2107**.

(498) In addition, the pitch hub **2107** may internally accommodate at least portions of the pulley **2113**, the pulley **2114**, the pulley **2123**, and the pulley **2124** that are axially coupled to the rotation axis **2143**. In addition, the pitch hub **2107** may internally accommodate at least portions of the pulley **2115**, the pulley **2116**, the pulley **2125**, and the pulley **2126** that are axially coupled to the rotation axis **2144**.

(499) In addition, the end tool **2100** of the third embodiment of the present disclosure may include the rotation axis **2141**, the rotation axis **2142**, the rotation axis **2143**, and the rotation axis **2144**.

(500) The rotation axis **2141**, the rotation axis **2142**, the rotation axis **2143**, and the rotation axis **2144** may be sequentially arranged from a distal end **2104** of the end tool **2100** toward a proximal end **2105**. Accordingly, starting from the distal end **2104**, the rotation axis **2141** may be referred to as a first pin, the rotation axis **2142** may be referred to as a second pin, the rotation axis **2143** may be referred to as a third pin, and the rotation axis **2144** may be referred to as a fourth pin.

(501) In this regard, the rotation axis **2141** may function as a jaw pulley rotation axis, the rotation axis **2142** may function as both a jaw auxiliary pulley rotation axis and a pitch redundant rotation axis, the rotation axis **2143** may function as a pitch main rotation axis, and the rotation axis **2144** may function as a pitch sub-rotation axis of the end tool **2100**.

(502) Hereinafter, the end tool hub **2180** of the third embodiment of the present disclosure will be described in more detail, and in particular, the rotation axis **2142** of the end tool hub **2180**, which serves as a jaw auxiliary pulley rotation axis, will be mainly described.

(503) Referring to FIGS. **102** to **104**, and the like, the end tool hub **2180** includes a first jaw pulley coupling part **2181**, a second jaw pulley coupling part **2182**, the rotation axis **2142**, a pitch pulley coupling part **2185**, and a guide part **2186**. In addition, the rotation axis **2142** may include a first sub-shaft **2142a** and a second sub-shaft **2142b**.

(504) In detail, the first jaw pulley coupling part **2181** and the second jaw pulley coupling part **2182** are formed to face each other such that the pulley **2111**, the pulley **2112**, the pulley **2121**, and the pulley **2122** are accommodated therein. In addition, a through hole is formed in each of the jaw pulley coupling parts **2181** and **2182** such that the rotation axis **2141** passes through and axially couples the jaw pulley coupling parts **2181** and **2182**, the pulley **2111**, and the pulley **2121**.

(505) The first jaw pulley coupling part **2181** and the second jaw pulley coupling part **2182** are connected to each other by the guide part **2186**. That is, the first jaw pulley coupling part **2181** and the second jaw pulley coupling part **2182** parallel to each other are coupled by the guide part **2186** formed in a direction substantially perpendicular thereto, such that the first jaw pulley coupling part **2181**, the second jaw pulley coupling part **2182**, and the guide part **2186** form a substantially “C” shape in which the pulley **2111**, the pulley **2112**, the pulley **2121**, and the pulley **2122** are accommodated.

(506) In other words, it may also be described that the first jaw pulley coupling part **2181** and the second jaw pulley coupling part **2182** are formed to extend in the X-axis direction from both ends of the guide part **2186** that is elongated in the Z-axis direction.

(507) The first sub-shaft **2142a** may be formed on an inner surface of the first jaw pulley coupling part **2181**, and the second sub-shaft **2142b** may be formed on the second jaw pulley coupling part **2182**. In other words, it may also be described that the second rotation axis **2142**, which is a jaw auxiliary pulley rotation axis, is formed by being divided into the first sub-shaft **2142a** and the second sub-shaft **2142b**.

(508) In detail, the first sub-shaft **2142a** and the second sub-shaft **2142b** may be formed to be inclined to a certain extent. In other words, the first sub-shaft **2142a** and the second sub-shaft **2142b** may be formed obliquely rather than parallel to any one of the X-axis, Y-axis, and Z-axis.

(509) In addition, the pulley **2112** may be coupled to the first sub-shaft **2142a**, and the pulley **2122** may be coupled to the second sub-shaft **2142b**. In this regard, the pulley **2112** may function as both a first jaw auxiliary pulley and a first pitch redundant pulley. In addition, the pulley **2122** may function as both a second jaw auxiliary pulley and a second pitch redundant pulley. This will be described in detail below.

(510) Meanwhile, the pulley **2131** that serves as an end tool pitch pulley may be formed in the pitch pulley coupling part **2185** at one end of the end tool hub **2180**. In this regard, the pulley **2131** may be formed with the end tool hub **2180** as one body. That is, one end of the end tool hub **2180** may be formed in a disk shape or a semicircular shape, and a groove around which a wire may be

wound may be formed on an outer circumferential surface of the groove, such that a kind of guide channel is formed. Alternatively, the pulley **2131** may be formed as a separate member from the end tool hub **2180** and coupled to the end tool hub **2180**. The wire **2303** and the wire **2304** described above are coupled to the pulley **2131** serving as an end tool pitch pulley, and a pitch motion is performed as the pulley **2131** is rotated around the rotation axis **2143**.

(511) Meanwhile, one or more pulleys may be fit into each of the rotation axes **2141**, **2142**, **2143**, and **2144**, and this will be described in detail below.

(512) The pulley **2111** functions as a first jaw pulley, the pulley **2121** functions as a second jaw pulley, and these two components may be collectively referred to as a jaw pulley.

(513) The pulley **2111** and the pulley **2121**, which are jaw pulleys, are formed to face each other, and are formed to be rotatable independently of each other around the rotation axis **2141**, which is a jaw pulley rotation axis. In this regard, the drawings illustrate that the pulley **2111** and the pulley **2121** are formed to be rotated around one rotation axis **2141**, but it is needless to say that each jaw pulley may be formed to be rotatable around a separate shaft. In this regard, the first jaw **2101** may be fixedly coupled to the pulley **2111** to be rotated together with the pulley **2111**, and the second jaw **2102** may be fixedly coupled to the pulley **2121** to be rotated together with the pulley **2121**. Yaw and actuation motions of the end tool **2100** are performed according to rotation of the pulley **2111** and the pulley **2121**. That is, when the pulley **2111** and the pulley **2121** are rotated in the same direction around the rotation axis **2141**, the yaw motion is performed, and when the pulley **2111** and the pulley **2121** are rotated in opposite directions around the rotation axis **2141**, the actuation motion is performed.

(514) In this regard, the first jaw **2101** and the pulley **2111** may be formed as separate members and coupled to each other, or the first jaw **2101** and the pulley **2111** may be formed as one body.

Similarly, the second jaw **2102** and the pulley **2121** may be formed as separate members and coupled to each other, or the second jaw **2102** and the pulley **2121** may be formed as one body.

(515) The pulley **2112** functions as a first jaw auxiliary pulley, the pulley **2122** functions as a second jaw auxiliary pulley, and these two components may be collectively referred to as a jaw auxiliary pulley. Simultaneously, the pulley **2112** may function as a first pitch redundant pulley, and the pulley **2122** may function as a second pitch redundant pulley.

(516) In detail, the pulley **2112** and the pulley **2122**, which are jaw auxiliary pulleys, may be additionally provided on one side of the pulley **2111** and the pulley **2121**. In other words, the pulley **2112**, which is a jaw auxiliary pulley, may be arranged between the pulley **2111** and the pulley **2113**/pulley **2114**. In addition, the pulley **2122**, which is a jaw auxiliary pulley, may be arranged between pulley **2121** and pulley **2123**/pulley **2124**. The pulley **2112** may be formed to be rotatable around the first sub-shaft **2142a** of the rotation axis **2142**, and the pulley **2122** may be formed to be rotatable around the second sub-shaft **2142b** of the rotation axis **2142**.

(517) The pulley **2113** and the pulley **2114** may function as first jaw pitch main pulleys, the pulley **2123** and the pulley **2124** may function as second jaw pitch main pulleys, and these two components may be collectively referred to as a pitch main pulley.

(518) The pulley **2115** and the pulley **2116** may function as first jaw pitch sub-pulleys, the pulley **2125** and the pulley **2126** may function as second jaw pitch sub-pulleys, and these two components may be collectively referred to as a pitch sub-pulley.

(519) Accordingly, the rotation axis **2141**, the rotation axis **2142**, the rotation axis **2143**, and the rotation axis **2144** may be sequentially arranged from the distal end **2104** of the end tool **2100** toward the proximal end **2105**.

(520) In addition, the pulley **2111**, the pulley **2112**, the pulley **2113**/pulley **2114**, and the pulley **2115**/pulley **2116**, which are associated with rotation of the first jaw **2101**, may be sequentially arranged from the distal end **2104** of the end tool **100** toward the proximal end **2105**.

(521) In addition, the pulley **2121**, the pulley **2122**, the pulley **2123**/pulley **2124**, and the pulley **2125**/pulley **2126**, which are associated with rotation of the second jaw **2102**, may be sequentially

arranged from the distal end **2104** of the end tool **100** toward the proximal end **2105**.

(522) Hereinafter, the pulley **2112** and the pulley **2122** will be described in more detail.

(523) First, the pulley **2112** may function as a first jaw auxiliary pulley, and the pulley **2122** may function as a second jaw auxiliary pulley. The pulley **2112** and the pulley **2122** may come into contact with the wire **2305**, which is a first jaw wire, and the wire **2302**, which is a second jaw wire to change the arrangement path of the wire **2305** and the wire **2302** to a certain extent, and thus perform a function of increasing a rotation angle of each of the first jaw **2101** and the second jaw **2102**. The role of the auxiliary pulley will be similar to that described in the first embodiment of the present disclosure.

(524) Simultaneously, the pulley **2112** may function as a first pitch redundant pulley, and the pulley **2122** may function as a second pitch redundant pulley. The pitch redundant pulleys may serve to change insertion/withdrawal paths of jaw wires entering from the proximal end of the end tool to the distal end, or coming out from the distal end to the proximal end.

(525) In this regard, a plane passing between the pulley **2111**, which is a first jaw pulley, and the pulley **2121**, which is a second jaw pulley, is defined as a first plane, the side above the first plane in the +Z-axis direction is defined as an upper side, and the side below the first plane in the -Z-axis direction is defined as a lower side.

(526) The wire **2305**, which is a first jaw wire, is located on the upper side of the first plane when passing through the pulley **2114**, which is a first jaw pitch main pulley, then the path of the wire **2305** is changed as the wire **2305** passes through the pulley **2112**, which is a first pitch redundant pulley, and when the wire **2305** passes through the pulley **2111**, which is a first jaw pulley, the wire **2305** is located on the lower side of the first plane.

(527) In this regard, the first sub-shaft **2142a** and the pulley **2112** coupled thereto are formed to be inclined with respect to the first plane, to serve to guide the path of the wire **2305** such that the wire **2305**, which is located on the upper side of the first plane when in contact with the pulley **2114**, is located on the lower side of the first plane when in contact with the pulley **2111**.

(528) That is, as illustrated in FIG. **103**, the first sub-shaft **2142a** and the pulley **2112** coupled thereto may be formed to be inclined to a certain extent on a YZ plane. In addition, as illustrated in FIG. **104**, the first sub-shaft **2142a** and the pulley **2112** coupled thereto may be formed to be inclined to a certain extent on an XZ plane.

(529) Similarly, the wire **2302**, which is a second jaw wire, is located on the lower side of the first plane when passing through the pulley **2124**, which is a second jaw pitch main pulley, then the path of the wire **2302** is changed as the wire **2302** passes through the pulley **2122**, which is a second pitch redundant pulley, and when the wire **2302** passes through the pulley **2121**, which is a second jaw pulley, the wire **2302** is located on the upper side of the first plane.

(530) In this regard, the second sub-shaft **2142b** and the pulley **2122** coupled thereto are formed to be inclined with respect to the first plane, to serve to guide the path of the wire **2302** such that the wire **2302**, which is located on the lower side of the first plane when in contact with the pulley **2124**, is located on the upper side of the first plane when in contact with the pulley **2121**.

(531) That is, as illustrated in FIG. **103**, the second sub-shaft **2142b** and the pulley **2122** coupled thereto may be formed to be inclined to a certain extent on a YZ plane. In addition, as illustrated in FIG. **104**, the second sub-shaft **2142b** and the pulley **2122** coupled thereto may be formed to be inclined to a certain extent on an XZ plane.

(532) Hereinafter, components associated with the rotation of the pulley **2111** will be described.

(533) The pulley **2113** and the pulley **2114** are paired to function as first jaw pitch main pulleys. That is, the pulley **2113** and the pulley **2114** function as main rotation pulleys for a pitch motion of the first jaw **2101**. In this regard, the wire **2301**, which is a first jaw wire, is wound around the pulley **2113**, and the wire **2305**, which is a first jaw wire, is wound around the pulley **2114**.

(534) The pulley **2115** and the pulley **2116** are paired to function as first jaw pitch sub-pulleys. That is, the pulley **2115** and the pulley **2116** function as sub-rotation pulleys for a pitch motion of the

first jaw **2101**. In this regard, the wire **2301**, which is a first jaw wire, is wound around the pulley **2115**, and the wire **2305**, which is a first jaw wire, is wound around the pulley **2116**.

(535) In this regard, the pulley **2113** and the pulley **2114** are arranged on one side of the pulley **2111** and the pulley **2112** to face each other. In this regard, the pulley **2113** and the pulley **2114** are formed to be rotatable independently of each other around the rotation axis **2143**, which is a pitch main rotation axis. In addition, the pulley **2115** and the pulley **2116** are arranged on one sides of the pulley **2113** and the pulley **2114**, respectively, to face each other. In this regard, the pulley **2115** and the pulley **2116** are formed to be rotatable independently of each other around the rotation axis **2144**, which is a pitch sub-rotation axis. In this regard, the drawings illustrate that the pulley **2113**, the pulley **2114**, the pulley **2115**, and the pulley **2116** are formed to be rotatable around the Y-axis direction, but the concept of the present disclosure is not limited thereto, and the rotation axes of the respective pulleys may be formed in various directions according to their configurations.

(536) The wire **2301**, which is a first jaw wire, is wound to sequentially come into contact with at least portions of the pulley **2115**, the pulley **2113**, and the pulley **2111**. In addition, the wire **2305** connected to the wire **2301** by the coupling member **2323** is wound to sequentially come into contact with at least portions of the pulley **2111**, the pulley **2112**, the pulley **2114**, and the pulley **2116**.

(537) In other words, the wire **2301** and the wire **2305**, which are first jaw wires, are wound to sequentially come into contact with at least portions of the pulley **2115**, the pulley **2113**, the pulley **2111**, the pulley **2112**, the pulley **2114**, and the pulley **2116**, and are formed to move along the above pulleys while rotating the above pulleys.

(538) Accordingly, when the wire **2301** is pulled in the direction of an arrow **2301** of FIG. **100**, the coupling member **2323** to which the wire **2301** is coupled and the pulley **2111** coupled to the coupling member **2323** are rotated in the direction of an arrow L of FIG. **100**. On the contrary when the wire **2305** is pulled in the direction of an arrow **2305** of FIG. **100**, the coupling member **2323** to which the wire **2305** is coupled and the pulley **2111** coupled to the coupling member **2323** are rotated in the direction of an arrow R of FIG. **100**.

(539) Next, components associated with the rotation of the pulley **2121** will be described.

(540) The pulley **2123** and the pulley **2124** are paired to function as second jaw pitch main pulleys. That is, the pulley **2123** and the pulley **2124** function as main rotation pulleys for a pitch motion of the second jaw **2102**. In this regard, the wire **2306**, which is a second jaw wire, is wound around the pulley **2123**, and the wire **2302**, which is a second jaw wire, is wound around the pulley **2124**.

(541) The pulley **2125** and the pulley **2126** are paired to function as second jaw pitch sub-pulleys. That is, the pulley **2125** and the pulley **2126** may function as sub-rotation pulleys for a pitch motion of the second jaw **2102**. In this regard, the wire **2306**, which is a second jaw wire, is wound around the pulley **2125**, and the wire **2302**, which is a second jaw wire, is wound around the pulley **2126**.

(542) In this regard, the pulley **2123** and the pulley **2124** are arranged on one side of the pulley **2121** and the pulley **2122** to face each other. In this regard, the pulley **2123** and the pulley **2124** are formed to be rotatable independently of each other around the rotation axis **2143**, which is a pitch main rotation axis. In addition, the pulley **2125** and the pulley **2126** are arranged on one sides of the pulley **2123** and the pulley **2124**, respectively, to face each other. In this regard, the pulley **2125** and the pulley **2126** are formed to be rotatable independently of each other around the rotation axis **2144**, which is a pitch sub-rotation axis. In this regard, the drawings illustrate that the pulley **2123**, the pulley **2124**, the pulley **2125**, and the pulley **2126** are formed to be rotatable around the Y-axis direction, but the concept of the present disclosure is not limited thereto, and the rotation axes of the respective pulleys may be formed in various directions according to their configurations.

(543) The wire **2306**, which is a second jaw wire, is wound to sequentially come into contact with at least portions of the pulley **2125**, the pulley **2123**, and the pulley **2121**. In addition, the wire **2302** connected to the wire **2306** by the coupling member **2326** is wound to sequentially come into

contact with at least portions of the pulley **2121**, the pulley **2122**, the pulley **2124**, and the pulley **2126**.

(544) In other words, the wire **2306** and the wire **2302**, which are second jaw wires, are wound to sequentially come into contact with at least portions of the pulley **2125**, the pulley **2123**, the pulley **2121**, the pulley **2122**, the pulley **2124**, and the pulley **2126**, and are formed to move along the above pulleys while rotating the above pulleys.

(545) Accordingly, when the wire **2306** is pulled in the direction of an arrow **2306** of FIG. **100**, the coupling member **2326** to which the wire **2306** is coupled and the pulley **2121** coupled to the coupling member **2326** are rotated in the direction of an arrow R of FIG. **100**. On the contrary, when the wire **2302** is pulled in the direction of an arrow **2302** of FIG. **100**, the coupling member **2326** to which the wire **2302** is coupled and the pulley **2121** coupled to the coupling member **2326** are rotated in the direction of an arrow L of FIG. **100**.

(546) In this regard, according to the present disclosure, two strands of jaw wires wound around one jaw pulley are wound around pitch main pulleys in opposite directions, such that a pitch motion is easily controlled.

(547) In detail, when the side above, in the +Z-axis direction, a plane passing between the pulley **2111**, which is a first jaw pulley, and the pulley **2121**, which is a second jaw pulley (i.e., an XY plane) is defined as an upper side and the side below the plane in the -Z-axis direction is defined as a lower side, any one (e.g., the wire **2301**) of the two strands of the first jaw wires may enter the pulley **2113**, which is a first jaw pitch main pulley, from the lower side of the XY plane, and the other strand (e.g., the wire **2305**) may come out of the pulley **2114**, which is a first jaw pitch main pulley, from the upper side of the XY plane. In other words, it may be described as a structure in which the first jaw wire enters the first jaw pitch main pulley from the lower side and comes out from the upper side. (The second jaw wire enters the second jaw pitch main pulley from the upper side and comes out from the lower side)

(548) In other words, the wire **2301**, which is one strand of the first jaw wires, sequentially comes into contact with the upper side of the pulley **2115** and the lower side of the pulley **2113**, and then comes into contact with the pulley **2111**. Next, the wire **2305**, which is the other strand of the first jaw wires, is wound around the pulley **2111** and the pulley **2112**, and then sequentially comes into contact with the upper side of the pulley **2114**, and the lower side of the pulley **2116**, and then comes out toward the connection part **400**. Accordingly, the first jaw wire comes out of a connection part **2400**, enters the pulley **2113** from the lower side, then passes through each pulley, then passes through the upper side of the pulley **2114**, and then enters back the connection part **400**.

(549) Similarly, the wire **2306**, which is one strand of the second jaw wires, sequentially comes into contact with the lower side of the pulley **2125** and the upper side of the pulley **2123**, and then comes into contact with the pulley **2121**. Next, the wire **2302**, which is the other strand of the second jaw wires, is wound around the pulley **2121** and the pulley **2122**, and then sequentially comes into contact with the lower side of the pulley **2124** and the upper side of the pulley **2126**, and then comes out toward the connection part **400**. Accordingly, the second jaw wire comes out of the connection part **400**, enters the pulley **2123** from the upper side, then passes through each pulley, then passes through the lower side of the pulley **2124**, and then enters back the connection part **2400**.

(550) In other words, it may also be described that, any one wire of the two strands of the first jaw wires is wound around the first jaw pitch main pulley in any one of the clockwise direction and the counterclockwise direction while moving toward the end tool **2100** from a connection part **2400**, and the other wire is wound around the first jaw pitch main pulley in the other one of the clockwise direction and the counterclockwise direction while moving toward the end tool **2100** from the connection part **2400**. That is, as illustrated in FIGS. **97**, **98**, and **99**, the wire **2301** is wound in the clockwise direction while moving toward the end tool **2100** from the connection part **2400**, and the wire **2305** is wound in the counterclockwise direction while moving toward the end tool **2100** from

the connection part **400**.

(551) Similarly, it may also be described that, any one wire of the two strands of the second jaw wires is wound around the second jaw pitch main pulley in any one of the clockwise direction and the counterclockwise direction while moving toward the end tool **2100** from the connection part **2400**, and the other wire is wound around the second jaw pitch main pulley in the other one of the clockwise direction and the counterclockwise direction while moving toward the end tool **2100** from the connection part **2400**. That is, as illustrated in FIGS. **97**, **98**, and **99**, the wire **2302** is wound in the clockwise direction while moving toward the end tool **2100** from the connection part **2400**, and the wire **2306** is wound in the counterclockwise direction while moving toward the end tool **2100** from the connection part **400**.

(552) As such, the end tool **2100** of the surgical instrument according to an embodiment of the present disclosure may obtain an effect of facilitating control of the pitch motion as the two strands of the jaw wires wound around one jaw pulley are wound around the pitch main pulleys in opposite directions. That is, during a pitch motion, the drive part first jaw pulley (see **211**, **212** of FIG. **21**) and the drive part second jaw pulley (see **221**, **222** of FIG. **21**) are rotated to wind or unwind the jaw wires, and thus perform a kind of compensation for the pitch motion, enabling the pitch motion of the end tool **2100**.

(553) As such, the present disclosure has been described with reference to one embodiment shown in the drawings, but it will be understood that this is merely exemplary, and those of ordinary skill in the art will understand that various modifications and variations of the embodiments are possible therefrom. Accordingly, the true technical protection scope of the present disclosure should be defined by the technical spirit of the appended claims.

INDUSTRIAL APPLICABILITY

(554) The present disclosure relates to a surgical instrument, and more particularly, may be used in a surgical instrument capable of being mounted on a robot arm or operated manually for use in laparoscopic surgery or various surgeries.

Claims

1. A surgical instrument comprising: an end tool configured to allow at least a pitch rotation and a yaw rotation, the end tool including: a first jaw, a second jaw disposed to face the first jaw, a first jaw pulley coupled to the first jaw and configured to be rotatable around a first shaft, and a second jaw pulley coupled to the second jaw and disposed to face the first jaw pulley and configured to be rotatable around the first shaft or around an axis that is parallel to the first shaft, a pair of first jaw pitch main pulleys configured to be rotatable around a fourth shaft that forms a predetermined angle with the first shaft, and disposed on one side with respect to a plane perpendicular to the fourth shaft, passing between the first jaw and the second jaw, and a pair of second jaw pitch main pulleys configured to be rotatable around the fourth shaft or around an axis that is parallel to the fourth shaft, and disposed on another side with respect to the plane; a jaw wire including a first jaw wire coupled to the first jaw pulley configured to rotate the first jaw pulley and a second jaw wire coupled to the second jaw pulley configured to rotate the second jaw pulley; a connection portion disposed to extend in one direction, having the first jaw wire and the second jaw wire passing therethrough, and having one end portion to which the end tool is coupled; and a driving part coupled to another end portion of the connection portion and configured to control the pitch rotation and the yaw rotation of the end tool, the driving part including: a driving part first jaw pulley coupled to the first jaw wire and configured to be rotatable around a second shaft and move the first jaw wire, a driving part second jaw pulley coupled to the second jaw wire and configured to be rotatable around the second shaft or an axis parallel to the second shaft and move the second jaw wire, and a driving part pitch pulley disposed adjacent to the driving part first jaw pulley and the driving part second jaw pulley and configured to be rotatable around a third shaft different from

the second shaft, wherein a relative position of the driving part first jaw pulley, the driving part second jaw pulley and the driving part pitch pulley remains constant, wherein two strands of the first jaw wire coupled to the first jaw pulley are wound in opposite directions around the pair of first jaw pitch main pulleys, wherein two strands of the second jaw wire coupled to the second jaw pulley are wound in opposite directions around the pair of second jaw pitch main pulleys, and wherein when the driving part pitch pulley is rotated for the pitch rotation of the end tool, the driving part first jaw pulley and the driving part second jaw pulley are also rotated to compensate a movement of the first jaw wire and the second jaw wire respectively.

2. The surgical instrument of claim 1, wherein when the driving part pitch pulley is rotated around the third shaft, the driving part first jaw pulley is rotated around the second shaft to change a length of the first jaw wire in the driving part.

3. The surgical instrument of claim 2, wherein as the length of the first jaw wire in the driving part is changed due to a rotation of the driving part first jaw pulley, a length of the first jaw wire in the end tool is changed.

4. The surgical instrument of claim 2, wherein even when the length of the first jaw wire in the driving part is changed due to a rotation of the driving part first jaw pulley, an overall length of the first jaw wire remains constant.

5. The surgical instrument of claim 1, wherein the end tool includes: a first jaw pitch redundant pulley disposed between the first jaw pulley and the pair of first jaw pitch main pulleys and configured to be rotatable around a fifth shaft; and a second jaw pitch redundant pulley disposed between the second jaw pulley and the pair of second jaw pitch main pulleys and configured to be rotatable around a sixth shaft.

6. The surgical instrument of claim 5, wherein while moving from a proximal end of the end tool toward a distal end of the end tool, the first jaw wire sequentially comes into contact with the pair of first jaw pitch main pulleys and the first jaw pitch redundant pulley.

7. The surgical instrument of claim 6, wherein based on a plane perpendicular to the first shaft and passing between the first jaw pulley and the second jaw pulley, among the two strands of the first jaw wire coupled to the first jaw pulley, one strand of the first jaw wire sequentially comes into contact with a lower side of one of the pair of first jaw pitch main pulleys and a lower side of the first jaw pitch redundant pulley, and among the two strands of the first jaw wire coupled to the first jaw pulley, another strand of the first jaw wire sequentially comes into contact with an upper side of another of pair of first jaw pitch main pulleys and an upper side of the first jaw pitch redundant pulley.

8. The surgical instrument of claim 5, further comprising: a first jaw auxiliary pulley disposed between the first jaw pulley and the first jaw pitch redundant pulley; and a second jaw auxiliary pulley disposed between the second jaw pulley and the second jaw pitch redundant pulley.

9. The surgical instrument of claim 8, wherein the first jaw wire is located on a common internal tangent of the first jaw pulley and the first jaw auxiliary pulley, and wherein a rotation angle of the first jaw pulley is increased by the first jaw auxiliary pulley.

10. The surgical instrument of claim 5, further comprising: an end tool hub formed to internally accommodate at least some of the first jaw and the second jaw; and a pitch hub configured to be rotatable relative to the end tool hub by being axially coupled to the end tool hub.

11. The surgical instrument of claim 10, wherein the first jaw and the second jaw are rotated around the first shaft to perform a yaw motion, and wherein the end tool hub is rotated around the fourth shaft to perform a pitch motion.

12. The surgical instrument of claim 10, further comprising: an end tool pitch pulley disposed on an end portion of the end tool hub at a proximal end side; and a pitch wire coupled to the end tool pitch pulley to rotate the end tool pitch pulley.

13. The surgical instrument of claim 12, wherein when the end tool pitch pulley is rotated by the pitch wire, the end tool hub is rotated as a whole together with the end tool pitch pulley to change a

length of the first jaw wire wound around the pair of first jaw pitch main pulleys and the pair of second jaw pitch main pulleys.

14. The surgical instrument of claim 13, wherein when the end tool pitch pulley is rotated by the pitch wire, the two strands of the first jaw wire is moved to a predetermined degree by an external force in order to compensate for an amount of change in the length by which the two strands of the first jaw wire is wound around each of the pair of first jaw pitch main pulleys, respectively.

15. The surgical instrument of claim 10, wherein the first jaw pitch redundant pulley or the second jaw pitch redundant pulley is integrally formed with the end tool hub.

16. The surgical instrument of claim 5, wherein the fifth shaft and the sixth shaft are substantially parallel to the fourth shaft.

17. The surgical instrument of claim 5, wherein the fifth shaft and the sixth shaft are formed to be inclined with respect to the first shaft and the fourth shaft, respectively.

18. The surgical instrument of claim 5, wherein the first jaw pitch redundant pulley or the second jaw pitch redundant pulley includes only one pulley.

19. The surgical instrument of claim 1, wherein while moving from a proximal end of the end tool toward a distal end of the end tool, among the two strands of the first jaw wire coupled to the first jaw pulley, one strand of the first jaw wire is wound in one direction of a clockwise direction and a counterclockwise direction around one of the pair of first jaw pitch main pulleys, and another strand of the first jaw wire is wound in another direction of the clockwise direction and the counterclockwise direction around another of the pair of first jaw pitch main pulleys.

20. The surgical instrument of claim 1, wherein based on a plane perpendicular to the first shaft and passing between the first jaw pulley and the second jaw pulley, among the two strands of the first jaw wire coupled to the first jaw pulley, one strand of the first jaw wire comes into contact with an upper side of one of the pair of first jaw pitch main pulleys, and another strand of the first jaw wire comes into contact with a lower side of another of the pair of first jaw pitch main pulleys.

21. The surgical instrument of claim 1, further comprising: one or more first jaw pitch sub-pulleys formed on one side of the pair of first jaw pitch main pulleys and configured to be rotatable around a shaft substantially parallel to the fourth shaft; and one or more second jaw pitch sub-pulleys formed on one side of the pair of second jaw pitch main pulleys and configured to be rotatable around a shaft substantially parallel to the fourth shaft.

22. The surgical instrument of claim 21, wherein the one or more first jaw pitch sub-pulleys or the one or more second jaw pitch sub-pulleys includes only one pulley.

23. The surgical instrument of claim 1, wherein a groove of the first jaw pulley around which the first jaw wire is wound and a groove of the second jaw pulley around which the second jaw wire is wound are formed to be spaced apart from each other by a predetermined degree.

24. The surgical instrument of claim 1, wherein a groove of the first jaw pulley around which the first jaw wire is wound and a groove of the second jaw pulley around which the second jaw wire is wound are formed to be adjacent to each other.

25. The surgical instrument of claim 1, wherein when the driving part pitch pulley of the driving part is rotated for a pitch motion, a driving part first jaw pulley and a driving part second jaw pulley of the driving part are rotated together to compensate for the pitch motion.

26. The surgical instrument of claim 1, comprising: an end tool hub configured to internally accommodate at least some of the first jaw and the second jaw; a pitch hub configured to be rotatable relative to the end tool hub by being axially coupled to the end tool hub; a first pin configured to be inserted through the end tool hub, and formed to be the first shaft extending in a first direction; a second pin configured to be inserted through the end tool hub, disposed to be parallel to the first pin, and disposed on one side of the first pin; a 2.5th pin configured to be inserted through the end tool hub, disposed to extend in a second direction forming a predetermined angle with the first direction, and disposed on one side of the second pin; a third pin configured to be inserted through the end tool hub and the pitch hub, disposed to be parallel to the 2.5th pin, and

disposed on one side of the 2.5th pin; a fourth pin configured to be inserted through the pitch hub, disposed to be parallel to the third pin, and formed to be the fourth shaft on one side of the third pin; a first jaw auxiliary pulley disposed on one side of the first jaw pulley, and configured to be rotatable around the second pin; a second jaw auxiliary pulley disposed on one side of the second jaw pulley, and configured to be rotatable around the second pin; one or more first jaw pitch redundant pulleys disposed on one side of the first jaw auxiliary pulley, and configured to be rotatable around the 2.5th pin; one or more second jaw pitch redundant pulleys disposed on one side of the second jaw auxiliary pulley, and configured to be rotatable around the 2.5th pin; the pair of first jaw pitch main pulleys disposed on one side of the one or more first jaw pitch redundant pulleys, and configured to be rotatable around the third pin; the pair of second jaw pitch main pulleys disposed on one side of the one or more second jaw pitch redundant pulleys, and configured to be rotatable around the third pin; one or more first jaw pitch sub-pulleys formed on one side of the pair of first jaw pitch main pulleys, and configured to be rotatable around the fourth pin; and one or more second jaw pitch sub-pulleys formed on one side of the pair of second jaw pitch main pulleys, and configured to be rotatable around the fourth pin.

27. The surgical instrument of claim 1, comprising: an end tool hub configured to internally accommodate at least some of the first jaw and the second jaw; a pitch hub configured to be rotatable relative to the end tool hub by being axially coupled to the end tool hub; a first pin configured to be inserted through the end tool hub, and formed to be the first shaft extending in a first direction; a second pin configured to be inserted through the end tool hub, disposed to extend in a second direction forming a predetermined angle with the first direction, and disposed on one side of the first pin; a third pin configured to be inserted through the end tool hub and the pitch hub, disposed to extend in a third direction forming a predetermined angle with the first direction and the second direction, and disposed on one side of the second pin; a fourth pin configured to be inserted through the pitch hub, disposed to be parallel to the third pin, and formed to be the fourth shaft on one side of the third pin; a first jaw auxiliary pulley disposed on one side of the first jaw pulley, and configured to be rotatable around the second pin; a second jaw auxiliary pulley disposed on one side of the second jaw pulley, and configured to be rotatable around the second pin; the pair of first jaw pitch main pulleys disposed on one side of the first jaw auxiliary pulley, and configured to be rotatable around the third pin; the pair of second jaw pitch main pulleys disposed on one side of the second jaw auxiliary pulley, and configured to be rotatable around the third pin; one or more first jaw pitch sub-pulleys formed on one side of the pair of first jaw pitch main pulleys, and configured to be rotatable around the fourth pin; and one or more second jaw pitch sub-pulleys formed on one side of the pair of second jaw pitch main pulleys, and configured to be rotatable around the fourth pin.
