

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397113
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Dobbles; John Michael et al.

Integrated insulin delivery system with continuous glucose sensor

Abstract

Systems and methods for integrating a continuous glucose sensor **12**, including a receiver **14**, a medicament delivery device **16**, a controller module, and optionally a single point glucose monitor **18** are provided. Integration may be manual, semi-automated and/or fully automated.

Inventors: Dobbles; John Michael (San Clemente, CA), Kamath; Apurv Ullas (San Diego, CA), Mahalingam; Aarthi (San Diego, CA), Brauker; James H. (Addison, MI)

Applicant: DexCom, Inc. (San Diego, CA)

Family ID: 1000008780036

Assignee: Dexcom, Inc. (San Diego, CA)

Appl. No.: 18/806797

Filed: August 16, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240399060 A1	Dec. 05, 2024

Related U.S. Application Data

continuation parent-doc US 17074490 20201019 PENDING child-doc US 18806797
continuation parent-doc US 16867476 20200505 US 10835672 20201117 child-doc US 17074490
continuation parent-doc US 15792038 20171024 US 10653835 20200519 child-doc US 16867476
continuation parent-doc US 15362571 20161128 US 9827372 20171128 child-doc US 15792038
continuation parent-doc US 14063811 20131025 US 9597453 20170321 child-doc US 15362571
continuation parent-doc US 13885604 US 9452258 20160927 WO PCT/US2007/080848 20071009
child-doc US 14063811

Publication Classification

Int. Cl.: **A61M5/172** (20060101); **A61B5/145** (20060101); **A61M5/142** (20060101); **A61M5/20** (20060101); **A61M11/00** (20060101); **A61M15/00** (20060101); **A61M35/00** (20060101); **G16H20/17** (20180101); **G16H40/63** (20180101); A61B5/00 (20060101); A61M5/00 (20060101); A61M5/178 (20060101); A61M5/30 (20060101)

U.S. Cl.:

CPC **A61M5/1723** (20130101); **A61B5/14532** (20130101); **A61B5/14546** (20130101); **A61M5/14244** (20130101); **A61M5/14276** (20130101); **A61M5/20** (20130101); **A61M11/00** (20130101); **A61M15/0065** (20130101); **A61M15/0068** (20140204); **A61M15/008** (20140204); **A61M15/0083** (20140204); **A61M35/00** (20130101); **G16H20/17** (20180101); **G16H40/63** (20180101); A61B5/0031 (20130101); A61M5/003 (20130101); A61M2005/14296 (20130101); A61M5/178 (20130101); A61M5/30 (20130101); A61M15/00 (20130101); A61M2205/3569 (20130101); A61M2205/50 (20130101); A61M2205/502 (20130101); A61M2205/52 (20130101); A61M2205/581 (20130101); A61M2205/582 (20130101); A61M2205/587 (20130101); A61M2205/8206 (20130101); A61M2230/201 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
52641	12/1865	Gates	N/A	N/A
62334	12/1866	Holmes	N/A	N/A
65604	12/1866	Reynolds	N/A	N/A
1954643	12/1933	Neuhaus	N/A	N/A
2719797	12/1954	Rosenblatt et al.	N/A	N/A
3210578	12/1964	Sherer	N/A	N/A
3219533	12/1964	Mullins	N/A	N/A
3381371	12/1967	Russell	N/A	N/A
3506032	12/1969	Eveleigh et al.	N/A	N/A
3556950	12/1970	Dahms et al.	N/A	N/A
3610226	12/1970	Albisser	N/A	N/A
3775182	12/1972	Patton et al.	N/A	N/A
3780727	12/1972	King	N/A	N/A
3826244	12/1973	Salcman et al.	N/A	N/A
3837339	12/1973	Aisenberg et al.	N/A	N/A
3838682	12/1973	Clark et al.	N/A	N/A
3874850	12/1974	Sorensen et al.	N/A	N/A
3898984	12/1974	Mandel et al.	N/A	N/A
3910256	12/1974	Clark et al.	N/A	N/A
3929971	12/1974	Roy	N/A	N/A
3933593	12/1975	Sternberg	N/A	N/A

3943918	12/1975	Lewis	N/A	N/A
3957613	12/1975	Macur	N/A	N/A
3964974	12/1975	Banauch et al.	N/A	N/A
3979274	12/1975	Newman	N/A	N/A
4008717	12/1976	Kowarski	N/A	N/A
4016866	12/1976	Lawton	N/A	N/A
4024312	12/1976	Korpman	N/A	N/A
4040908	12/1976	Clark, Jr.	N/A	N/A
4052754	12/1976	Homsy	N/A	N/A
4055175	12/1976	Clemens et al.	N/A	N/A
4073713	12/1977	Newman	N/A	N/A
4076656	12/1977	White et al.	N/A	N/A
4109505	12/1977	Clark et al.	N/A	N/A
4119406	12/1977	Clemens	N/A	N/A
4136250	12/1978	Mueller et al.	N/A	N/A
4151845	12/1978	Clemens	N/A	N/A
4172770	12/1978	Semersky et al.	N/A	N/A
4176659	12/1978	Rolfe	N/A	N/A
4197840	12/1979	Beck et al.	N/A	N/A
4197852	12/1979	Schindler et al.	N/A	N/A
4206755	12/1979	Klein	N/A	N/A
4215703	12/1979	Willson	N/A	N/A
4240438	12/1979	Updike et al.	N/A	N/A
4240889	12/1979	Yoda et al.	N/A	N/A
4245634	12/1980	Albisser et al.	N/A	N/A
4253469	12/1980	Aslan	N/A	N/A
4255500	12/1980	Hooke	N/A	N/A
4259540	12/1980	Sabia	N/A	N/A
4265249	12/1980	Schindler et al.	N/A	N/A
4319578	12/1981	Enger	N/A	N/A
4327725	12/1981	Cortese et al.	N/A	N/A
4366040	12/1981	Marsoner et al.	N/A	N/A
4369785	12/1982	Rehkopf et al.	N/A	N/A
4374013	12/1982	Enfors	N/A	N/A
4388166	12/1982	Suzuki et al.	N/A	N/A
4403984	12/1982	Ash et al.	N/A	N/A
4415666	12/1982	D'Orazio et al.	N/A	N/A
4431004	12/1983	Bessman et al.	N/A	N/A
4432366	12/1983	Margules	N/A	N/A
4436094	12/1983	Cerami	N/A	N/A
4442841	12/1983	Uehara et al.	N/A	N/A
4454295	12/1983	Wittmann et al.	N/A	N/A
4457339	12/1983	Juan et al.	N/A	N/A
4477314	12/1983	Richter et al.	N/A	N/A
4478222	12/1983	Koning et al.	N/A	N/A
4486290	12/1983	Cahalan et al.	N/A	N/A
4492575	12/1984	Mabille	N/A	N/A
4494950	12/1984	Fischell	N/A	N/A
4506680	12/1984	Stokes	N/A	N/A
4519973	12/1984	Cahalan et al.	N/A	N/A

RE31916	12/1984	Oswin et al.	N/A	N/A
4526569	12/1984	Bernardi	N/A	N/A
4534825	12/1984	Koning et al.	N/A	N/A
4535786	12/1984	Kater	N/A	N/A
4538616	12/1984	Rogoff	N/A	N/A
4545382	12/1984	Higgins et al.	N/A	N/A
4554927	12/1984	Fussell	N/A	N/A
4565665	12/1985	Fogt	N/A	N/A
4565666	12/1985	Cahalan et al.	N/A	N/A
4568444	12/1985	Nakamura et al.	N/A	N/A
4571292	12/1985	Liu et al.	N/A	N/A
4573968	12/1985	Parker	N/A	N/A
4577642	12/1985	Stokes	N/A	N/A
4583976	12/1985	Ferguson	N/A	N/A
4592824	12/1985	Smith et al.	N/A	N/A
4600495	12/1985	Fogt	N/A	N/A
4614514	12/1985	Carr et al.	N/A	N/A
4619793	12/1985	Lee	N/A	N/A
4625730	12/1985	Fountain et al.	N/A	N/A
4626104	12/1985	Pointon et al.	N/A	N/A
4632968	12/1985	Yokota et al.	N/A	N/A
RE32361	12/1986	Duggan	N/A	N/A
4655880	12/1986	Liu	N/A	N/A
4663824	12/1986	Kenmochi	N/A	N/A
4671288	12/1986	Gough	N/A	N/A
4672970	12/1986	Uchida et al.	N/A	N/A
4680268	12/1986	Clark, Jr.	N/A	N/A
4685463	12/1986	Williams	N/A	N/A
4685903	12/1986	Cable et al.	N/A	N/A
4694861	12/1986	Goodale et al.	N/A	N/A
4702732	12/1986	Powers et al.	N/A	N/A
4703756	12/1986	Gough et al.	N/A	N/A
4705503	12/1986	Dorman et al.	N/A	N/A
4711245	12/1986	Higgins et al.	N/A	N/A
4711251	12/1986	Stokes	N/A	N/A
4721677	12/1987	Clark, Jr.	N/A	N/A
4726381	12/1987	Jones	N/A	N/A
4731726	12/1987	Allen, III	N/A	N/A
4736748	12/1987	Nakamura et al.	N/A	N/A
4747822	12/1987	Peabody	N/A	N/A
4750496	12/1987	Reinhart et al.	N/A	N/A
4753652	12/1987	Langer et al.	N/A	N/A
4755168	12/1987	Romanelli et al.	N/A	N/A
4757022	12/1987	Shults et al.	N/A	N/A
4759828	12/1987	Young et al.	N/A	N/A
4763648	12/1987	Wyatt	N/A	N/A
4763658	12/1987	Jones	N/A	N/A
4777953	12/1987	Ash et al.	N/A	N/A
4781798	12/1987	Gough	N/A	N/A
4784157	12/1987	Halls et al.	N/A	N/A

4786394	12/1987	Enzer et al.	N/A	N/A
4787398	12/1987	Garcia et al.	N/A	N/A
4789467	12/1987	Lindsay et al.	N/A	N/A
4791932	12/1987	Margules	N/A	N/A
4803243	12/1988	Fujimoto et al.	N/A	N/A
4805624	12/1988	Yao et al.	N/A	N/A
4805625	12/1988	Wyler	N/A	N/A
4807632	12/1988	Liess et al.	N/A	N/A
4808089	12/1988	Buchholtz et al.	N/A	N/A
4808292	12/1988	Kessler et al.	N/A	N/A
4809704	12/1988	Sogawa et al.	N/A	N/A
4810243	12/1988	Howson	N/A	N/A
4810470	12/1988	Burkhardt et al.	N/A	N/A
4815471	12/1988	Stobie	N/A	N/A
4820281	12/1988	Lawler, Jr.	N/A	N/A
4822336	12/1988	DiTraglia	N/A	N/A
4823808	12/1988	Clegg et al.	N/A	N/A
4828544	12/1988	Lane et al.	N/A	N/A
4830013	12/1988	Maxwell	N/A	N/A
4831070	12/1988	McInally et al.	N/A	N/A
4832005	12/1988	Takamiya et al.	N/A	N/A
4832034	12/1988	Pizziconi et al.	N/A	N/A
4834101	12/1988	Collison et al.	N/A	N/A
4838281	12/1988	Rogers et al.	N/A	N/A
4841974	12/1988	Gumbrecht et al.	N/A	N/A
4849458	12/1988	Reed et al.	N/A	N/A
4852573	12/1988	Kennedy	N/A	N/A
4854322	12/1988	Ash et al.	N/A	N/A
4858615	12/1988	Meinema	N/A	N/A
4867741	12/1988	Portnoy	N/A	N/A
4871440	12/1988	Nagata et al.	N/A	N/A
4874363	12/1988	Abell	N/A	N/A
4883057	12/1988	Broderick	N/A	N/A
4883467	12/1988	Franetzki et al.	N/A	N/A
4889528	12/1988	Nadai et al.	N/A	N/A
4889744	12/1988	Quaid	N/A	N/A
4890620	12/1989	Gough	N/A	N/A
4890621	12/1989	Hakky	N/A	N/A
4900305	12/1989	Smith et al.	N/A	N/A
4902294	12/1989	Gosserez	N/A	N/A
4907857	12/1989	Giuliani et al.	N/A	N/A
4908208	12/1989	Lee et al.	N/A	N/A
4909786	12/1989	Gijssels et al.	N/A	N/A
4919114	12/1989	Miyazaki	N/A	N/A
4919141	12/1989	Zier et al.	N/A	N/A
4919649	12/1989	Timothy et al.	N/A	N/A
4921477	12/1989	Davis	N/A	N/A
4921480	12/1989	Sealfon	N/A	N/A
4925444	12/1989	Orkin et al.	N/A	N/A
4927407	12/1989	Dorman	N/A	N/A

4927516	12/1989	Yamaguchi et al.	N/A	N/A
4928694	12/1989	Maxwell	N/A	N/A
4934369	12/1989	Maxwell	N/A	N/A
4934375	12/1989	Cole et al.	N/A	N/A
4944299	12/1989	Silvian	N/A	N/A
4946439	12/1989	Eggers	N/A	N/A
4950246	12/1989	Muller	N/A	N/A
4951657	12/1989	Pfister et al.	N/A	N/A
4951669	12/1989	Maxwell et al.	N/A	N/A
4953552	12/1989	DeMarzo	N/A	N/A
4957483	12/1989	Gonser et al.	N/A	N/A
4963595	12/1989	Ward et al.	N/A	N/A
4966579	12/1989	Polaschegg	N/A	N/A
4967940	12/1989	Blette et al.	N/A	N/A
4970145	12/1989	Bennetto et al.	N/A	N/A
4973320	12/1989	Brenner et al.	N/A	N/A
4974592	12/1989	Branco	N/A	N/A
4974929	12/1989	Curry	N/A	N/A
4975636	12/1989	Desautels	N/A	N/A
4976687	12/1989	Martin	N/A	N/A
4979509	12/1989	Hakky	N/A	N/A
4984929	12/1990	Rock et al.	N/A	N/A
4986671	12/1990	Sun et al.	N/A	N/A
4988341	12/1990	Columbus et al.	N/A	N/A
4989607	12/1990	Keusch et al.	N/A	N/A
4992794	12/1990	Brouwers	N/A	N/A
4994026	12/1990	Fecondini	N/A	N/A
4994167	12/1990	Shults et al.	N/A	N/A
4997627	12/1990	Bergkuist et al.	N/A	N/A
5002055	12/1990	Merki et al.	N/A	N/A
5002572	12/1990	Picha	N/A	N/A
5006050	12/1990	Cooke et al.	N/A	N/A
5006111	12/1990	Inokuchi et al.	N/A	N/A
5007929	12/1990	Quaid	N/A	N/A
5009251	12/1990	Pike et al.	N/A	N/A
5019974	12/1990	Beckers	N/A	N/A
5026348	12/1990	Venegas	N/A	N/A
5030199	12/1990	Barwick et al.	N/A	N/A
5030333	12/1990	Clark, Jr.	N/A	N/A
5034112	12/1990	Murase et al.	N/A	N/A
5035711	12/1990	Aoki et al.	N/A	N/A
5041092	12/1990	Barwick	N/A	N/A
5045057	12/1990	Van Driessche et al.	N/A	N/A
5046496	12/1990	Betts et al.	N/A	N/A
5048525	12/1990	Maxwell	N/A	N/A
5050612	12/1990	Matsumura	N/A	N/A
5055171	12/1990	Peck	N/A	N/A
5055198	12/1990	Shettigar	N/A	N/A
5059654	12/1990	Hou et al.	N/A	N/A
5067491	12/1990	Taylor, II et al.	N/A	N/A

5068536	12/1990	Rosenthal	N/A	N/A
5070169	12/1990	Robertson et al.	N/A	N/A
5077476	12/1990	Rosenthal	N/A	N/A
5088981	12/1991	Howson et al.	N/A	N/A
5089421	12/1991	Dieffenbach	N/A	N/A
5096669	12/1991	Lauks et al.	N/A	N/A
5097834	12/1991	Skrabal	N/A	N/A
5098377	12/1991	Borsanyi et al.	N/A	N/A
5101814	12/1991	Palti	N/A	N/A
5108819	12/1991	Heller et al.	N/A	N/A
5109850	12/1991	Blanco et al.	N/A	N/A
5112301	12/1991	Fenton, Jr. et al.	N/A	N/A
5116313	12/1991	McGregor	N/A	N/A
5127405	12/1991	Alcala et al.	N/A	N/A
5137028	12/1991	Nishimura	N/A	N/A
5140985	12/1991	Schroeder et al.	N/A	N/A
5145565	12/1991	Kater et al.	N/A	N/A
5152746	12/1991	Atkinson et al.	N/A	N/A
5153827	12/1991	Coutre et al.	N/A	N/A
5160418	12/1991	Mullen	N/A	N/A
5161532	12/1991	Joseph	N/A	N/A
5165406	12/1991	Wong	N/A	N/A
5165407	12/1991	Wilson et al.	N/A	N/A
5174291	12/1991	Schoonen et al.	N/A	N/A
5176632	12/1992	Bernardi	N/A	N/A
5176658	12/1992	Ranford	N/A	N/A
5178142	12/1992	Harjunmaa et al.	N/A	N/A
5182004	12/1992	Kohno	N/A	N/A
5188591	12/1992	Dorsey, III	N/A	N/A
5190041	12/1992	Palti	N/A	N/A
5195963	12/1992	Yafuso et al.	N/A	N/A
5198771	12/1992	Fidler et al.	N/A	N/A
5208147	12/1992	Kagenow et al.	N/A	N/A
5208313	12/1992	Krishnan	N/A	N/A
5220917	12/1992	Cammilli et al.	N/A	N/A
5220920	12/1992	Gharib	N/A	N/A
5224929	12/1992	Remiszewski	N/A	N/A
5225063	12/1992	Gumbrecht et al.	N/A	N/A
5232434	12/1992	Inagaki et al.	N/A	N/A
5235003	12/1992	Ward et al.	N/A	N/A
5243982	12/1992	Mostl et al.	N/A	N/A
5243983	12/1992	Tarr et al.	N/A	N/A
5249576	12/1992	Goldberger et al.	N/A	N/A
5251126	12/1992	Kahn et al.	N/A	N/A
5254102	12/1992	Ogawa	N/A	N/A
5262305	12/1992	Heller et al.	N/A	N/A
5265594	12/1992	Olsson et al.	N/A	N/A
5266179	12/1992	Nankai et al.	N/A	N/A
5269891	12/1992	Colin	N/A	N/A
5271736	12/1992	Picha	N/A	N/A

5271815	12/1992	Wong	N/A	N/A
5279294	12/1993	Anderson et al.	N/A	N/A
5281319	12/1993	Kaneko et al.	N/A	N/A
5282848	12/1993	Schmitt	N/A	N/A
5284140	12/1993	Allen et al.	N/A	N/A
5284570	12/1993	Savage et al.	N/A	N/A
5285513	12/1993	Kaufman et al.	N/A	N/A
5287753	12/1993	Routh et al.	N/A	N/A
5298022	12/1993	Bernardi	N/A	N/A
5299571	12/1993	Mastrototaro	N/A	N/A
5302093	12/1993	Owens et al.	N/A	N/A
5304468	12/1993	Phillips et al.	N/A	N/A
5307263	12/1993	Brown	N/A	N/A
5310469	12/1993	Cunningham et al.	N/A	N/A
5311908	12/1993	Barone et al.	N/A	N/A
5312361	12/1993	Zadini et al.	N/A	N/A
5314471	12/1993	Brauker et al.	N/A	N/A
5316008	12/1993	Suga et al.	N/A	N/A
5316452	12/1993	Bogen et al.	N/A	N/A
5318511	12/1993	Riquier et al.	N/A	N/A
5322063	12/1993	Allen et al.	N/A	N/A
5324322	12/1993	Grill, Jr. et al.	N/A	N/A
5326356	12/1993	Della Valle et al.	N/A	N/A
5326449	12/1993	Cunningham	N/A	N/A
5330521	12/1993	Cohen	N/A	N/A
5330634	12/1993	Wong et al.	N/A	N/A
5331555	12/1993	Hashimoto et al.	N/A	N/A
5335658	12/1993	Bedingham	N/A	N/A
5337747	12/1993	Neftel	N/A	N/A
5342409	12/1993	Mullett	N/A	N/A
5342789	12/1993	Chick et al.	N/A	N/A
5343869	12/1993	Pross et al.	N/A	N/A
5344454	12/1993	Clarke et al.	N/A	N/A
5345932	12/1993	Yafuso et al.	N/A	N/A
5348788	12/1993	White	N/A	N/A
5352348	12/1993	Young et al.	N/A	N/A
5352351	12/1993	White et al.	N/A	N/A
5354272	12/1993	Swendson et al.	N/A	N/A
5354449	12/1993	Band et al.	N/A	N/A
5356375	12/1993	Higley	N/A	N/A
5356378	12/1993	Doan	N/A	N/A
5356786	12/1993	Heller et al.	N/A	N/A
5368028	12/1993	Palti	N/A	N/A
5368224	12/1993	Richardson et al.	N/A	N/A
5368562	12/1993	Blomquist et al.	N/A	N/A
5372133	12/1993	Hogen Esch	N/A	N/A
5372135	12/1993	Mendelson et al.	N/A	N/A
5372709	12/1993	Hood	N/A	N/A
5376070	12/1993	Purvis et al.	N/A	N/A
5378229	12/1994	Layer et al.	N/A	N/A

5380268	12/1994	Wheeler	N/A	N/A
5380491	12/1994	Carver, Jr. et al.	N/A	N/A
5380536	12/1994	Hubbell et al.	N/A	N/A
5380665	12/1994	Cusack et al.	N/A	N/A
5384028	12/1994	Ito	N/A	N/A
5390671	12/1994	Lord et al.	N/A	N/A
5391250	12/1994	Cheney, II et al.	N/A	N/A
5397848	12/1994	Yang et al.	N/A	N/A
5405510	12/1994	Betts et al.	N/A	N/A
5411052	12/1994	Murray	N/A	N/A
5411647	12/1994	Johnson et al.	N/A	N/A
5411866	12/1994	Luong et al.	N/A	N/A
5417206	12/1994	Kaneyoshi	N/A	N/A
5421328	12/1994	Bedingham	N/A	N/A
5421923	12/1994	Clarke et al.	N/A	N/A
5423738	12/1994	Robinson et al.	N/A	N/A
5423749	12/1994	Merte et al.	N/A	N/A
5428123	12/1994	Ward et al.	N/A	N/A
5429485	12/1994	Dodge	N/A	N/A
5429602	12/1994	Hauser	N/A	N/A
5429735	12/1994	Johnson et al.	N/A	N/A
5431160	12/1994	Wilkins	N/A	N/A
5431174	12/1994	Knute	N/A	N/A
5431921	12/1994	Thombre	N/A	N/A
5434412	12/1994	Sodickson et al.	N/A	N/A
5437635	12/1994	Fields et al.	N/A	N/A
5438984	12/1994	Schoendorfer	N/A	N/A
5443508	12/1994	Giampapa	N/A	N/A
5445610	12/1994	Evert	N/A	N/A
5448992	12/1994	Kupershmidt	N/A	N/A
5451260	12/1994	Versteeg et al.	N/A	N/A
5453278	12/1994	Chan et al.	N/A	N/A
5458631	12/1994	Xavier	N/A	N/A
5462051	12/1994	Oka et al.	N/A	N/A
5462064	12/1994	D'Angelo et al.	N/A	N/A
5466356	12/1994	Schneider et al.	N/A	N/A
5469846	12/1994	Khan	N/A	N/A
5474552	12/1994	Palti	N/A	N/A
5476776	12/1994	Wilkins	N/A	N/A
5482008	12/1995	Stafford et al.	N/A	N/A
5482446	12/1995	Williamson et al.	N/A	N/A
5482473	12/1995	Lord et al.	N/A	N/A
5484404	12/1995	Schulman et al.	N/A	N/A
5491474	12/1995	Suni et al.	N/A	N/A
5494562	12/1995	Maley et al.	N/A	N/A
5496453	12/1995	Uenoyama et al.	N/A	N/A
5497772	12/1995	Schulman et al.	N/A	N/A
5502396	12/1995	Desarzens et al.	N/A	N/A
5505828	12/1995	Wong et al.	N/A	N/A
5507288	12/1995	Bocker et al.	N/A	N/A

5508203	12/1995	Fuller et al.	N/A	N/A
5509888	12/1995	Miller	N/A	N/A
5512046	12/1995	Pusinelli et al.	N/A	N/A
5512055	12/1995	Domb et al.	N/A	N/A
5512248	12/1995	Van	N/A	N/A
5513636	12/1995	Palti	N/A	N/A
5514253	12/1995	Davis et al.	N/A	N/A
5515851	12/1995	Goldstein	N/A	N/A
5518601	12/1995	Foos et al.	N/A	N/A
5527288	12/1995	Gross et al.	N/A	N/A
5531679	12/1995	Schulman et al.	N/A	N/A
5531878	12/1995	Vadgama et al.	N/A	N/A
5536249	12/1995	Castellano et al.	N/A	N/A
5538511	12/1995	Van Antwerp	N/A	N/A
5540828	12/1995	Yacynych	N/A	N/A
5545220	12/1995	Andrews et al.	N/A	N/A
5545223	12/1995	Neuenfeldt et al.	N/A	N/A
5549547	12/1995	Cohen et al.	N/A	N/A
5549548	12/1995	Larsson	N/A	N/A
5549569	12/1995	Lynn et al.	N/A	N/A
5549651	12/1995	Lynn	N/A	N/A
5551850	12/1995	Williamson et al.	N/A	N/A
5553616	12/1995	Ham et al.	N/A	N/A
5554339	12/1995	Cozzette et al.	N/A	N/A
5561615	12/1995	Kuo et al.	N/A	N/A
5562614	12/1995	O'Donnell	N/A	N/A
5562615	12/1995	Nassif	N/A	N/A
5564439	12/1995	Picha	N/A	N/A
5568806	12/1995	Cheney, II et al.	N/A	N/A
5569186	12/1995	Lord et al.	N/A	N/A
5569188	12/1995	Mackool	N/A	N/A
5569219	12/1995	Hakki et al.	N/A	N/A
5569462	12/1995	Martinson et al.	N/A	N/A
5575293	12/1995	Miller et al.	N/A	N/A
5575930	12/1995	Tietje-Girault et al.	N/A	N/A
5577499	12/1995	Teves	N/A	N/A
5582184	12/1995	Erickson et al.	N/A	N/A
5582593	12/1995	Hultman	N/A	N/A
5584813	12/1995	Livingston et al.	N/A	N/A
5584876	12/1995	Bruchman et al.	N/A	N/A
5586553	12/1995	Halili et al.	N/A	N/A
5589133	12/1995	Suzuki	N/A	N/A
5590651	12/1996	Shaffer et al.	N/A	N/A
5593440	12/1996	Brauker et al.	N/A	N/A
5609572	12/1996	Lang	N/A	N/A
5611900	12/1996	Worden et al.	N/A	N/A
5624409	12/1996	Seale	N/A	N/A
5624537	12/1996	Turner et al.	N/A	N/A
5626563	12/1996	Dodge et al.	N/A	N/A
5628619	12/1996	Wilson	N/A	N/A

5628890	12/1996	Carter et al.	N/A	N/A
5637083	12/1996	Bertrand et al.	N/A	N/A
5640470	12/1996	Iyer et al.	N/A	N/A
5643195	12/1996	Drevet et al.	N/A	N/A
5651767	12/1996	Schulman et al.	N/A	N/A
5653756	12/1996	Clarke et al.	N/A	N/A
5653863	12/1996	Genshaw et al.	N/A	N/A
5658250	12/1996	Blomquist et al.	N/A	N/A
5660163	12/1996	Schulman et al.	N/A	N/A
5660565	12/1996	Williams	N/A	N/A
5665061	12/1996	Antwiler	N/A	N/A
5665065	12/1996	Colman et al.	N/A	N/A
5667504	12/1996	Baumann et al.	N/A	N/A
5673694	12/1996	Rivers	N/A	N/A
5674289	12/1996	Fournier et al.	N/A	N/A
5676651	12/1996	Larson, Jr. et al.	N/A	N/A
5676820	12/1996	Wang et al.	N/A	N/A
5681572	12/1996	Seare, Jr.	N/A	N/A
5682884	12/1996	Hill et al.	N/A	N/A
5683562	12/1996	Schaffar et al.	N/A	N/A
5686829	12/1996	Girault	N/A	N/A
5688239	12/1996	Walker	N/A	N/A
5688244	12/1996	Lang	N/A	N/A
5695623	12/1996	Michel et al.	N/A	N/A
5696314	12/1996	McCaffrey et al.	N/A	N/A
5697366	12/1996	Kimball et al.	N/A	N/A
5697899	12/1996	Hillman et al.	N/A	N/A
5704354	12/1997	Preidel et al.	N/A	N/A
5706807	12/1997	Picha	N/A	N/A
5711861	12/1997	Ward et al.	N/A	N/A
5713888	12/1997	Neuenfeldt et al.	N/A	N/A
5730654	12/1997	Brown	N/A	N/A
5733259	12/1997	Valcke et al.	N/A	N/A
5733336	12/1997	Neuenfeldt et al.	N/A	N/A
5743262	12/1997	Lepper, Jr. et al.	N/A	N/A
5749832	12/1997	Vadgama et al.	N/A	N/A
5749907	12/1997	Mann	N/A	N/A
5755692	12/1997	Manicom	N/A	N/A
5756632	12/1997	Ward et al.	N/A	N/A
5758643	12/1997	Wong et al.	N/A	N/A
5763760	12/1997	Gumbrecht et al.	N/A	N/A
5771890	12/1997	Tamada	N/A	N/A
5773286	12/1997	Dionne et al.	N/A	N/A
5776324	12/1997	Usala	N/A	N/A
5779665	12/1997	Mastrototaro et al.	N/A	N/A
5781455	12/1997	Hyodo	N/A	N/A
5782880	12/1997	Lahtinen et al.	N/A	N/A
5782912	12/1997	Brauker et al.	N/A	N/A
5787900	12/1997	Butler et al.	N/A	N/A
5791344	12/1997	Schulman et al.	N/A	N/A

5791880	12/1997	Wilson	N/A	N/A
5795453	12/1997	Gilmartin	N/A	N/A
5795774	12/1997	Matsumoto et al.	N/A	N/A
5798065	12/1997	Picha	N/A	N/A
5800383	12/1997	Chandler et al.	N/A	N/A
5800420	12/1997	Gross et al.	N/A	N/A
5800529	12/1997	Brauker et al.	N/A	N/A
5806517	12/1997	Gerhardt et al.	N/A	N/A
5807274	12/1997	Henning et al.	N/A	N/A
5807312	12/1997	Dzwonkiewicz	N/A	N/A
5807375	12/1997	Gross et al.	N/A	N/A
5807406	12/1997	Brauker et al.	N/A	N/A
5810770	12/1997	Chin et al.	N/A	N/A
5811487	12/1997	Schulz, Jr. et al.	N/A	N/A
5814599	12/1997	Mitragotri et al.	N/A	N/A
5820589	12/1997	Torgerson et al.	N/A	N/A
5820622	12/1997	Gross et al.	N/A	N/A
5822715	12/1997	Worthington et al.	N/A	N/A
5836887	12/1997	Oka et al.	N/A	N/A
5836989	12/1997	Shelton	N/A	N/A
5837454	12/1997	Cozzette et al.	N/A	N/A
5837728	12/1997	Purcell	N/A	N/A
5840026	12/1997	Uber, III et al.	N/A	N/A
5840148	12/1997	Campbell et al.	N/A	N/A
5848991	12/1997	Gross et al.	N/A	N/A
5851197	12/1997	Marano et al.	N/A	N/A
5851229	12/1997	Lentz et al.	N/A	N/A
5858365	12/1998	Faller	N/A	N/A
5858747	12/1998	Schinstine et al.	N/A	N/A
5861019	12/1998	Sun et al.	N/A	N/A
5863400	12/1998	Drummond et al.	N/A	N/A
5871514	12/1998	Wiklund et al.	N/A	N/A
5873862	12/1998	Lopez	N/A	N/A
5876370	12/1998	Blomquist	N/A	N/A
5879713	12/1998	Roth et al.	N/A	N/A
5882494	12/1998	Van Antwerp	N/A	N/A
5895235	12/1998	Droz	N/A	N/A
5897525	12/1998	Dey et al.	N/A	N/A
5897578	12/1998	Wiklund et al.	N/A	N/A
5899855	12/1998	Brown	N/A	N/A
5904666	12/1998	DeDecker et al.	N/A	N/A
5904708	12/1998	Goedeke	N/A	N/A
5911219	12/1998	Aylsworth et al.	N/A	N/A
5913998	12/1998	Butler et al.	N/A	N/A
5914026	12/1998	Blubaugh, Jr. et al.	N/A	N/A
5917346	12/1998	Gord	N/A	N/A
5919215	12/1998	Wiklund et al.	N/A	N/A
5919216	12/1998	Houben et al.	N/A	N/A
5921951	12/1998	Morris	N/A	N/A
5925021	12/1998	Castellano et al.	N/A	N/A

5928155	12/1998	Eggers et al.	N/A	N/A
5928182	12/1998	Kraus et al.	N/A	N/A
5928189	12/1998	Phillips et al.	N/A	N/A
5928195	12/1998	Malamud et al.	N/A	N/A
5931814	12/1998	Alex et al.	N/A	N/A
5932175	12/1998	Knute et al.	N/A	N/A
5933136	12/1998	Brown	N/A	N/A
5935785	12/1998	Reber et al.	N/A	N/A
5938636	12/1998	Kramer et al.	N/A	N/A
5944661	12/1998	Swette et al.	N/A	N/A
5947911	12/1998	Wong et al.	N/A	N/A
5954643	12/1998	VanAntwerp et al.	N/A	N/A
5954954	12/1998	Houck et al.	N/A	N/A
5957854	12/1998	Besson et al.	N/A	N/A
5957903	12/1998	Mirzaee et al.	N/A	N/A
5961451	12/1998	Reber et al.	N/A	N/A
5963132	12/1998	Yoakum	N/A	N/A
5964745	12/1998	Lyles et al.	N/A	N/A
5964993	12/1998	Blubaugh, Jr. et al.	N/A	N/A
5965125	12/1998	Mineau-Hanschke	N/A	N/A
5965380	12/1998	Heller et al.	N/A	N/A
5971922	12/1998	Arita et al.	N/A	N/A
5972369	12/1998	Roorda et al.	N/A	N/A
5976085	12/1998	Kimball et al.	N/A	N/A
5987352	12/1998	Klein et al.	N/A	N/A
5995208	12/1998	Sarge et al.	N/A	N/A
5995860	12/1998	Sun et al.	N/A	N/A
5997501	12/1998	Gross et al.	N/A	N/A
5999848	12/1998	Gord et al.	N/A	N/A
6001067	12/1998	Shults et al.	N/A	N/A
6001471	12/1998	Bries et al.	N/A	N/A
6002954	12/1998	Van Antwerp et al.	N/A	N/A
6007845	12/1998	Domb et al.	N/A	N/A
6011984	12/1999	Van Antwerp et al.	N/A	N/A
6014577	12/1999	Henning et al.	N/A	N/A
6016448	12/1999	Busacker et al.	N/A	N/A
6017435	12/1999	Hassard et al.	N/A	N/A
6023629	12/1999	Tamada	N/A	N/A
6024720	12/1999	Chandler et al.	N/A	N/A
6027445	12/1999	Von Bahr	N/A	N/A
6027479	12/1999	Alei et al.	N/A	N/A
6032059	12/1999	Henning et al.	N/A	N/A
6032667	12/1999	Heinonen	N/A	N/A
6036924	12/1999	Simons et al.	N/A	N/A
6043328	12/1999	Domschke et al.	N/A	N/A
6045671	12/1999	Wu et al.	N/A	N/A
6048691	12/1999	Maracas	N/A	N/A
6049727	12/1999	Crothall	N/A	N/A
6059946	12/1999	Yukawa et al.	N/A	N/A
6063637	12/1999	Arnold et al.	N/A	N/A

6066088	12/1999	Davis	N/A	N/A
6066448	12/1999	Wohlstadter et al.	N/A	N/A
6071391	12/1999	Gotoh et al.	N/A	N/A
6077299	12/1999	Adelberg et al.	N/A	N/A
6080583	12/1999	Von Bahr	N/A	N/A
6081735	12/1999	Diab et al.	N/A	N/A
6081736	12/1999	Colvin et al.	N/A	N/A
6083523	12/1999	Dionne et al.	N/A	N/A
6083710	12/1999	Heller et al.	N/A	N/A
6088608	12/1999	Schulman et al.	N/A	N/A
6090087	12/1999	Tsukada et al.	N/A	N/A
6091975	12/1999	Daddona et al.	N/A	N/A
6093172	12/1999	Funderburk et al.	N/A	N/A
6099511	12/1999	Devos et al.	N/A	N/A
6103033	12/1999	Say et al.	N/A	N/A
6103533	12/1999	Hassard et al.	N/A	N/A
6107083	12/1999	Collins et al.	N/A	N/A
6115634	12/1999	Donders et al.	N/A	N/A
6117290	12/1999	Say et al.	N/A	N/A
6120676	12/1999	Heller et al.	N/A	N/A
6121009	12/1999	Heller et al.	N/A	N/A
6122536	12/1999	Sun et al.	N/A	N/A
6123827	12/1999	Wong et al.	N/A	N/A
6127154	12/1999	Mosbach et al.	N/A	N/A
6128519	12/1999	Say	N/A	N/A
6129891	12/1999	Rolander et al.	N/A	N/A
6134461	12/1999	Say et al.	N/A	N/A
6135978	12/1999	Houben et al.	N/A	N/A
6142939	12/1999	Eppstein et al.	N/A	N/A
6144869	12/1999	Berner et al.	N/A	N/A
6159186	12/1999	Wickham et al.	N/A	N/A
6162201	12/1999	Cohen et al.	N/A	N/A
6162611	12/1999	Heller et al.	N/A	N/A
6163720	12/1999	Gyory et al.	N/A	N/A
6164921	12/1999	Moubayed et al.	N/A	N/A
6165154	12/1999	Gray et al.	N/A	N/A
6167614	12/2000	Tuttle et al.	N/A	N/A
6168568	12/2000	Gavriely	N/A	N/A
6169155	12/2000	Alvarez et al.	N/A	N/A
6171276	12/2000	Lippe et al.	N/A	N/A
6175752	12/2000	Say et al.	N/A	N/A
6180416	12/2000	Kurnik et al.	N/A	N/A
6183437	12/2000	Walker	N/A	N/A
6187062	12/2000	Oweis et al.	N/A	N/A
6189536	12/2000	Martinez et al.	N/A	N/A
6191860	12/2000	Klinger et al.	N/A	N/A
6192891	12/2000	Gravel et al.	N/A	N/A
6201980	12/2000	Darrow et al.	N/A	N/A
6201993	12/2000	Kruse et al.	N/A	N/A
6206856	12/2000	Mahurkar	N/A	N/A

6208894	12/2000	Schulman et al.	N/A	N/A
6212416	12/2000	Ward et al.	N/A	N/A
6212424	12/2000	Robinson	N/A	N/A
6213739	12/2000	Phallen et al.	N/A	N/A
6214185	12/2000	Offenbacher et al.	N/A	N/A
6219574	12/2000	Cormier et al.	N/A	N/A
6223080	12/2000	Thompson	N/A	N/A
6223083	12/2000	Rosar	N/A	N/A
6230059	12/2000	Duffin	N/A	N/A
6231879	12/2000	Li et al.	N/A	N/A
6232783	12/2000	Merrill	N/A	N/A
6233080	12/2000	Brenner et al.	N/A	N/A
6234964	12/2000	Iliff	N/A	N/A
6241863	12/2000	Monbouquette	N/A	N/A
6248067	12/2000	Causey, III et al.	N/A	N/A
6248077	12/2000	Elson et al.	N/A	N/A
6248093	12/2000	Moberg	N/A	N/A
6254586	12/2000	Mann et al.	N/A	N/A
6256522	12/2000	Schultz	N/A	N/A
6259937	12/2000	Schulman et al.	N/A	N/A
6263222	12/2000	Diab et al.	N/A	N/A
6264825	12/2000	Blackburn et al.	N/A	N/A
6270478	12/2000	Mernoee	N/A	N/A
6271332	12/2000	Lohmann et al.	N/A	N/A
6272364	12/2000	Kurnik	N/A	N/A
6272382	12/2000	Faltys et al.	N/A	N/A
6272480	12/2000	Tresp et al.	N/A	N/A
6274285	12/2000	Gries et al.	N/A	N/A
6275717	12/2000	Gross et al.	N/A	N/A
6280408	12/2000	Sipin	N/A	N/A
6281015	12/2000	Mooney et al.	N/A	N/A
6284478	12/2000	Heller et al.	N/A	N/A
6293925	12/2000	Safabash et al.	N/A	N/A
6298254	12/2000	Tamada	N/A	N/A
6299578	12/2000	Kurnik et al.	N/A	N/A
6299583	12/2000	Eggers et al.	N/A	N/A
6300002	12/2000	Webb et al.	N/A	N/A
6302855	12/2000	Lav et al.	N/A	N/A
6309351	12/2000	Kurnik et al.	N/A	N/A
6309384	12/2000	Harrington et al.	N/A	N/A
6309884	12/2000	Cooper et al.	N/A	N/A
6312388	12/2000	Marcovecchio et al.	N/A	N/A
6315738	12/2000	Nishikawa et al.	N/A	N/A
6325978	12/2000	Labuda et al.	N/A	N/A
6326160	12/2000	Dunn et al.	N/A	N/A
6329161	12/2000	Heller et al.	N/A	N/A
6329929	12/2000	Weijand et al.	N/A	N/A
6330464	12/2000	Colvin, Jr. et al.	N/A	N/A
6343225	12/2001	Clark, Jr.	N/A	N/A
6356776	12/2001	Berner et al.	N/A	N/A

6358225	12/2001	Butterfield	N/A	N/A
6365670	12/2001	Fry	N/A	N/A
6366794	12/2001	Moussy et al.	N/A	N/A
6368274	12/2001	Van Antwerp et al.	N/A	N/A
6370941	12/2001	Nakamura et al.	N/A	N/A
6372244	12/2001	Antanavich et al.	N/A	N/A
6379301	12/2001	Worthington et al.	N/A	N/A
6379317	12/2001	Kintzig et al.	N/A	N/A
6383478	12/2001	Prokop et al.	N/A	N/A
6387709	12/2001	Mason et al.	N/A	N/A
6391019	12/2001	Ito	N/A	N/A
6400974	12/2001	Lesho	N/A	N/A
6402703	12/2001	Kensey et al.	N/A	N/A
6403944	12/2001	MacKenzie et al.	N/A	N/A
6406066	12/2001	Uegane	N/A	N/A
6407195	12/2001	Sherman et al.	N/A	N/A
6409674	12/2001	Brockway et al.	N/A	N/A
6413393	12/2001	Van Antwerp et al.	N/A	N/A
6416651	12/2001	Millar	N/A	N/A
6424847	12/2001	Mastrototaro et al.	N/A	N/A
6430437	12/2001	Marro	N/A	N/A
6447448	12/2001	Ishikawa et al.	N/A	N/A
6447542	12/2001	Weadock	N/A	N/A
6459917	12/2001	Gowda et al.	N/A	N/A
6461331	12/2001	Van Antwerp	N/A	N/A
6461496	12/2001	Feldman et al.	N/A	N/A
6464849	12/2001	Say et al.	N/A	N/A
6466810	12/2001	Ward et al.	N/A	N/A
6467480	12/2001	Meier et al.	N/A	N/A
6471689	12/2001	Joseph et al.	N/A	N/A
6474360	12/2001	Ito	N/A	N/A
6475750	12/2001	Han et al.	N/A	N/A
6477392	12/2001	Honigs et al.	N/A	N/A
6477395	12/2001	Schulman et al.	N/A	N/A
6481440	12/2001	Gielen et al.	N/A	N/A
6484045	12/2001	Holker et al.	N/A	N/A
6484046	12/2001	Say et al.	N/A	N/A
6485449	12/2001	Ito	N/A	N/A
6488652	12/2001	Weijand et al.	N/A	N/A
6494830	12/2001	Wessel	N/A	N/A
6494879	12/2001	Lennox et al.	N/A	N/A
6497729	12/2001	Moussy et al.	N/A	N/A
6498043	12/2001	Schulman et al.	N/A	N/A
6498941	12/2001	Jackson	N/A	N/A
6501976	12/2001	Sohrab	N/A	N/A
6510239	12/2002	Wieres et al.	N/A	N/A
6510329	12/2002	Heckel	N/A	N/A
6512939	12/2002	Colvin et al.	N/A	N/A
6514718	12/2002	Heller et al.	N/A	N/A
6517508	12/2002	Utterberg et al.	N/A	N/A

6520326	12/2002	McIvor et al.	N/A	N/A
6520477	12/2002	Trimmer	N/A	N/A
6520937	12/2002	Hart et al.	N/A	N/A
6520997	12/2002	Pekkarinen et al.	N/A	N/A
6526298	12/2002	Khalil et al.	N/A	N/A
6527729	12/2002	Turcott	N/A	N/A
6534711	12/2002	Pollack	N/A	N/A
6536433	12/2002	Cewers	N/A	N/A
6537318	12/2002	Ita et al.	N/A	N/A
6541266	12/2002	Modzelewski et al.	N/A	N/A
6542765	12/2002	Guy et al.	N/A	N/A
6544212	12/2002	Galley	604/504	A61B 5/7275
6545085	12/2002	Kilgour et al.	N/A	N/A
6546268	12/2002	Ishikawa et al.	N/A	N/A
6546269	12/2002	Kurnik	N/A	N/A
6549796	12/2002	Sohrab	N/A	N/A
6551496	12/2002	Moles et al.	N/A	N/A
6553241	12/2002	Mannheimer et al.	N/A	N/A
6553244	12/2002	Lesho et al.	N/A	N/A
6554805	12/2002	Hiejima	N/A	N/A
6554822	12/2002	Holschneider et al.	N/A	N/A
6558320	12/2002	Causey, III et al.	N/A	N/A
6558321	12/2002	Burd et al.	N/A	N/A
6558347	12/2002	Jhuboo et al.	N/A	N/A
6558351	12/2002	Steil et al.	N/A	N/A
6558955	12/2002	Kristal et al.	N/A	N/A
6561978	12/2002	Conn et al.	N/A	N/A
6562001	12/2002	Lebel et al.	N/A	N/A
6565509	12/2002	Say et al.	N/A	N/A
6565535	12/2002	Zaias et al.	N/A	N/A
6565807	12/2002	Patterson et al.	N/A	N/A
6569195	12/2002	Yang et al.	N/A	N/A
6569521	12/2002	Sheridan et al.	N/A	N/A
6571128	12/2002	Lebel et al.	N/A	N/A
6572545	12/2002	Knobbe et al.	N/A	N/A
6572579	12/2002	Raghavan et al.	N/A	N/A
6574490	12/2002	Abbink et al.	N/A	N/A
6575905	12/2002	Knobbe et al.	N/A	N/A
6577899	12/2002	Lebel et al.	N/A	N/A
6579257	12/2002	Elgas et al.	N/A	N/A
6579498	12/2002	Eglise	N/A	N/A
6579690	12/2002	Bonnecaze et al.	N/A	N/A
6585644	12/2002	Lebel et al.	N/A	N/A
6585675	12/2002	O'Mahony et al.	N/A	N/A
6585763	12/2002	Keilman et al.	N/A	N/A
6587705	12/2002	Kim et al.	N/A	N/A
6589229	12/2002	Connelly et al.	N/A	N/A
6591125	12/2002	Buse et al.	N/A	N/A
6594514	12/2002	Berner et al.	N/A	N/A

6595756	12/2002	Gray et al.	N/A	N/A
6595919	12/2002	Berner et al.	N/A	N/A
6602221	12/2002	Saravia et al.	N/A	N/A
6605072	12/2002	Struys et al.	N/A	N/A
6607509	12/2002	Bobroff et al.	N/A	N/A
6609071	12/2002	Shapiro et al.	N/A	N/A
6612984	12/2002	Kerr, II	N/A	N/A
6613379	12/2002	Ward et al.	N/A	N/A
6615061	12/2002	Khalil et al.	N/A	N/A
6615078	12/2002	Burson et al.	N/A	N/A
6618603	12/2002	Varalli et al.	N/A	N/A
6618934	12/2002	Feldman et al.	N/A	N/A
6620138	12/2002	Marrgi et al.	N/A	N/A
6633772	12/2002	Ford et al.	N/A	N/A
6635014	12/2002	Starkweather et al.	N/A	N/A
6641533	12/2002	Causey, III et al.	N/A	N/A
6642015	12/2002	Vachon et al.	N/A	N/A
6645181	12/2002	Lavi et al.	N/A	N/A
6648821	12/2002	Lebel et al.	N/A	N/A
6653091	12/2002	Dunn et al.	N/A	N/A
6654625	12/2002	Say et al.	N/A	N/A
6656114	12/2002	Poulsen et al.	N/A	N/A
6656157	12/2002	Duchon et al.	N/A	N/A
6663615	12/2002	Madou et al.	N/A	N/A
6673022	12/2003	Bobo et al.	N/A	N/A
6673596	12/2003	Sayler et al.	N/A	N/A
6679865	12/2003	Shekalim	N/A	N/A
6679872	12/2003	Turovskiy et al.	N/A	N/A
6683535	12/2003	Utke	N/A	N/A
6684904	12/2003	Ito	N/A	N/A
6685668	12/2003	Cho et al.	N/A	N/A
6687522	12/2003	Tamada	N/A	N/A
6689089	12/2003	Tiedtke et al.	N/A	N/A
6689265	12/2003	Heller et al.	N/A	N/A
6694191	12/2003	Starkweather et al.	N/A	N/A
6695860	12/2003	Ward et al.	N/A	N/A
6699188	12/2003	Wessel	N/A	N/A
6699218	12/2003	Flaherty et al.	N/A	N/A
6699383	12/2003	Lemire et al.	N/A	N/A
6702249	12/2003	Ito	N/A	N/A
6702857	12/2003	Brauker et al.	N/A	N/A
6702972	12/2003	Markle	N/A	N/A
6711424	12/2003	Fine et al.	N/A	N/A
6712796	12/2003	Fentis et al.	N/A	N/A
6721587	12/2003	Gough	N/A	N/A
6723086	12/2003	Bassuk et al.	N/A	N/A
6731976	12/2003	Penn et al.	N/A	N/A
6736783	12/2003	Blake et al.	N/A	N/A
6740072	12/2003	Starkweather et al.	N/A	N/A
6740075	12/2003	Lebel et al.	N/A	N/A

6741877	12/2003	Shults et al.	N/A	N/A
6742635	12/2003	Hirshberg	N/A	N/A
6743635	12/2003	Neel et al.	N/A	N/A
6749587	12/2003	Flaherty	N/A	N/A
6750055	12/2003	Connelly et al.	N/A	N/A
6770030	12/2003	Schaupp et al.	N/A	N/A
6770067	12/2003	Lorenzen et al.	N/A	N/A
6773565	12/2003	Kunimoto et al.	N/A	N/A
6780297	12/2003	Matsumoto et al.	N/A	N/A
6793632	12/2003	Sohrab	N/A	N/A
6801041	12/2003	Karinka et al.	N/A	N/A
6802957	12/2003	Jung et al.	N/A	N/A
6804002	12/2003	Fine et al.	N/A	N/A
6805693	12/2003	Gray et al.	N/A	N/A
6809653	12/2003	Mann et al.	N/A	N/A
6810290	12/2003	Lebel et al.	N/A	N/A
6811548	12/2003	Jeffrey	N/A	N/A
6813519	12/2003	Lebel et al.	N/A	N/A
6832200	12/2003	Greeven et al.	N/A	N/A
6850790	12/2004	Berner et al.	N/A	N/A
6858020	12/2004	Rusnak	N/A	N/A
6862465	12/2004	Shults et al.	N/A	N/A
6869413	12/2004	Langley et al.	N/A	N/A
6875195	12/2004	Choi	N/A	N/A
6887228	12/2004	Mckay	N/A	N/A
6892085	12/2004	McIvor et al.	N/A	N/A
6893552	12/2004	Wang et al.	N/A	N/A
6895263	12/2004	Shin et al.	N/A	N/A
6895265	12/2004	Silver	N/A	N/A
6902544	12/2004	Ludin et al.	N/A	N/A
6925393	12/2004	Kalatz et al.	N/A	N/A
6926691	12/2004	Miethke	N/A	N/A
6931327	12/2004	Goode, Jr. et al.	N/A	N/A
6932584	12/2004	Gray et al.	N/A	N/A
6936006	12/2004	Sabra	N/A	N/A
6936029	12/2004	Mann et al.	N/A	N/A
6945965	12/2004	Whiting	N/A	N/A
6948492	12/2004	Wermeling et al.	N/A	N/A
6952604	12/2004	Denuzzio et al.	N/A	N/A
6954662	12/2004	Freger et al.	N/A	N/A
6960192	12/2004	Flaherty et al.	N/A	N/A
6965791	12/2004	Hitchcock et al.	N/A	N/A
6966325	12/2004	Erickson	N/A	N/A
6975893	12/2004	Say et al.	N/A	N/A
6979315	12/2004	Rogers et al.	N/A	N/A
6989891	12/2005	Braig et al.	N/A	N/A
6997921	12/2005	Gray et al.	N/A	N/A
6998247	12/2005	Monfre et al.	N/A	N/A
7008979	12/2005	Schottman et al.	N/A	N/A
7011630	12/2005	Desai et al.	N/A	N/A

7016713	12/2005	Gardner et al.	N/A	N/A
7022072	12/2005	Fox et al.	N/A	N/A
7022219	12/2005	Mansouri et al.	N/A	N/A
7025727	12/2005	Brockway et al.	N/A	N/A
7025743	12/2005	Mann et al.	N/A	N/A
7027848	12/2005	Robinson et al.	N/A	N/A
7029444	12/2005	Shin et al.	N/A	N/A
7033322	12/2005	Silver	N/A	N/A
7044911	12/2005	Drinan et al.	N/A	N/A
7048727	12/2005	Moss	N/A	N/A
7058437	12/2005	Buse et al.	N/A	N/A
7060059	12/2005	Keith et al.	N/A	N/A
7061593	12/2005	Braig et al.	N/A	N/A
7063086	12/2005	Shahbazpour et al.	N/A	N/A
7066884	12/2005	Custer et al.	N/A	N/A
7070577	12/2005	Haller et al.	N/A	N/A
7074307	12/2005	Simpson et al.	N/A	N/A
7081195	12/2005	Simpson et al.	N/A	N/A
7097775	12/2005	Greenberg et al.	N/A	N/A
7098803	12/2005	Mann et al.	N/A	N/A
7100628	12/2005	Izenson et al.	N/A	N/A
7108778	12/2005	Simpson et al.	N/A	N/A
7120483	12/2005	Russell et al.	N/A	N/A
7131967	12/2005	Gray et al.	N/A	N/A
7134999	12/2005	Brauker et al.	N/A	N/A
7136689	12/2005	Shults et al.	N/A	N/A
7146202	12/2005	Ward et al.	N/A	N/A
7150741	12/2005	Erickson et al.	N/A	N/A
7162290	12/2006	Levin	N/A	N/A
7166074	12/2006	Reghabi et al.	N/A	N/A
7168597	12/2006	Jones et al.	N/A	N/A
7169289	12/2006	Schuelein et al.	N/A	N/A
7183102	12/2006	Monfre et al.	N/A	N/A
7184810	12/2006	Caduff et al.	N/A	N/A
7207968	12/2006	Harcinske	N/A	N/A
7211074	12/2006	Sansoucy	N/A	N/A
7221970	12/2006	Parker	N/A	N/A
7223253	12/2006	Hogendijk	N/A	N/A
7225535	12/2006	Feldman et al.	N/A	N/A
7228162	12/2006	Ward et al.	N/A	N/A
7229288	12/2006	Stuart et al.	N/A	N/A
7238165	12/2006	Mncent et al.	N/A	N/A
7247138	12/2006	Reghabi et al.	N/A	N/A
7254450	12/2006	Christopherson et al.	N/A	N/A
7255690	12/2006	Gray et al.	N/A	N/A
7258681	12/2006	Houde	N/A	N/A
7261690	12/2006	Teller et al.	N/A	N/A
7266400	12/2006	Fine et al.	N/A	N/A
7267665	12/2006	Steil et al.	N/A	N/A
7276029	12/2006	Goode, Jr. et al.	N/A	N/A

7278983	12/2006	Ireland et al.	N/A	N/A
7279174	12/2006	Pacetti et al.	N/A	N/A
7282029	12/2006	Poulsen et al.	N/A	N/A
7288085	12/2006	Olsen	N/A	N/A
7291114	12/2006	Mault	N/A	N/A
7295867	12/2006	Berner et al.	N/A	N/A
7299082	12/2006	Feldman et al.	N/A	N/A
7311690	12/2006	Burnett	N/A	N/A
7313425	12/2006	Finarov et al.	N/A	N/A
7314452	12/2007	Madonia	N/A	N/A
7315767	12/2007	Caduff et al.	N/A	N/A
7316662	12/2007	Delnevo et al.	N/A	N/A
7317939	12/2007	Fine et al.	N/A	N/A
7318814	12/2007	Levine et al.	N/A	N/A
7327273	12/2007	Hung et al.	N/A	N/A
7329234	12/2007	Sansoucy	N/A	N/A
7334594	12/2007	Ludin	N/A	N/A
7335179	12/2007	Burnett	N/A	N/A
7335195	12/2007	Mehier	N/A	N/A
7338464	12/2007	Blischak et al.	N/A	N/A
7344500	12/2007	Talbot et al.	N/A	N/A
7354420	12/2007	Steil et al.	N/A	N/A
7357793	12/2007	Pacetti	N/A	N/A
7359723	12/2007	Jones	N/A	N/A
7361155	12/2007	Sage, Jr. et al.	N/A	N/A
7364562	12/2007	Braig et al.	N/A	N/A
7367942	12/2007	Grage et al.	N/A	N/A
7396353	12/2007	Lorenzen et al.	N/A	N/A
7399277	12/2007	Saidara et al.	N/A	N/A
7402153	12/2007	Steil et al.	N/A	N/A
7417164	12/2007	Suri	N/A	N/A
7426408	12/2007	DeNuzzio et al.	N/A	N/A
7433727	12/2007	Ward et al.	N/A	N/A
7519408	12/2008	Rasdal et al.	N/A	N/A
7519478	12/2008	Bartkowiak et al.	N/A	N/A
7523004	12/2008	Bartkowiak et al.	N/A	N/A
7534230	12/2008	Follman et al.	N/A	N/A
7569030	12/2008	Lebel et al.	N/A	N/A
7583990	12/2008	Goode, Jr. et al.	N/A	N/A
7591801	12/2008	Brauker et al.	N/A	N/A
7599726	12/2008	Goode, Jr. et al.	N/A	N/A
7604593	12/2008	Parris et al.	N/A	N/A
7615007	12/2008	Shults et al.	N/A	N/A
7618368	12/2008	Brown	N/A	N/A
7618369	12/2008	Hayter et al.	N/A	N/A
7624028	12/2008	Brown	N/A	N/A
7640032	12/2008	Jones	N/A	N/A
7640048	12/2008	Dobbles et al.	N/A	N/A
7647237	12/2009	Malave et al.	N/A	N/A
7654955	12/2009	Polidori et al.	N/A	N/A

7657297	12/2009	Simpson et al.	N/A	N/A
7670288	12/2009	Sher	N/A	N/A
7695434	12/2009	Malecha	N/A	N/A
7727147	12/2009	Osorio et al.	N/A	N/A
7731659	12/2009	Malecha	N/A	N/A
7761126	12/2009	Gardner et al.	N/A	N/A
7766830	12/2009	Fox et al.	N/A	N/A
7857760	12/2009	Brister et al.	N/A	N/A
7901394	12/2010	Ireland et al.	N/A	N/A
7905833	12/2010	Brister et al.	N/A	N/A
7927274	12/2010	Rasdal et al.	N/A	N/A
7946985	12/2010	Mastrototaro et al.	N/A	N/A
7976492	12/2010	Brauker et al.	N/A	N/A
8000901	12/2010	Brauker et al.	N/A	N/A
8005524	12/2010	Brauker et al.	N/A	N/A
8005525	12/2010	Goode, Jr. et al.	N/A	N/A
8010174	12/2010	Goode, Jr. et al.	N/A	N/A
8460231	12/2012	Brauker et al.	N/A	N/A
8512276	12/2012	Talbot et al.	N/A	N/A
8721585	12/2013	Brauker et al.	N/A	N/A
8808228	12/2013	Brister et al.	N/A	N/A
8882741	12/2013	Brauker et al.	N/A	N/A
8920401	12/2013	Brauker et al.	N/A	N/A
8926585	12/2014	Brauker et al.	N/A	N/A
9050413	12/2014	Brauker et al.	N/A	N/A
9155843	12/2014	Brauker et al.	N/A	N/A
9451908	12/2015	Kamath et al.	N/A	N/A
9452258	12/2015	Dobbles et al.	N/A	N/A
9452259	12/2015	Dobbles et al.	N/A	N/A
9457146	12/2015	Dobbles et al.	N/A	N/A
9463277	12/2015	Dobbles et al.	N/A	N/A
9498155	12/2015	Brauker et al.	N/A	N/A
9572935	12/2016	Dobbles et al.	N/A	N/A
9572936	12/2016	Dobbles et al.	N/A	N/A
9586004	12/2016	Dobbles et al.	N/A	N/A
9597453	12/2016	Dobbles et al.	N/A	N/A
9750441	12/2016	Brauker et al.	N/A	N/A
9827372	12/2016	Dobbles et al.	N/A	N/A
9937293	12/2017	Brauker et al.	N/A	N/A
10278580	12/2018	Brister et al.	N/A	N/A
10653835	12/2019	Dobbles et al.	N/A	N/A
10966609	12/2020	Brister et al.	N/A	N/A
11373347	12/2021	Kamath et al.	N/A	N/A
11744943	12/2022	Dobbles et al.	N/A	N/A
2001/0007950	12/2000	North et al.	N/A	N/A
2001/0016682	12/2000	Berner et al.	N/A	N/A
2001/0021817	12/2000	Brugger et al.	N/A	N/A
2001/0039053	12/2000	Liseo et al.	N/A	N/A
2001/0041830	12/2000	Varalli et al.	N/A	N/A
2001/0044588	12/2000	Mault	N/A	N/A

2001/0051768	12/2000	Schulman et al.	N/A	N/A
2002/0009810	12/2001	O'Connor et al.	N/A	N/A
2002/0016535	12/2001	Martin et al.	N/A	N/A
2002/0016719	12/2001	Nemeth et al.	N/A	N/A
2002/0018843	12/2001	Van Antwerp et al.	N/A	N/A
2002/0019022	12/2001	Dunn et al.	N/A	N/A
2002/0019330	12/2001	Murray et al.	N/A	N/A
2002/0022883	12/2001	Burg	N/A	N/A
2002/0023852	12/2001	McIvor et al.	N/A	N/A
2002/0026110	12/2001	Parris et al.	N/A	N/A
2002/0026111	12/2001	Ackerman	N/A	N/A
2002/0042090	12/2001	Heller et al.	N/A	N/A
2002/0042561	12/2001	Schulman et al.	N/A	N/A
2002/0043471	12/2001	Ikeda et al.	N/A	N/A
2002/0045808	12/2001	Ford et al.	N/A	N/A
2002/0060692	12/2001	Broemmelsiek	N/A	N/A
2002/0065453	12/2001	Lesho et al.	N/A	N/A
2002/0068860	12/2001	Clark	N/A	N/A
2002/0071776	12/2001	Bandis et al.	N/A	N/A
2002/0084196	12/2001	Liamos et al.	N/A	N/A
2002/0099282	12/2001	Knobbe et al.	N/A	N/A
2002/0099997	12/2001	Piret	N/A	N/A
2002/0111547	12/2001	Knobbe et al.	N/A	N/A
2002/0119711	12/2001	Vanantwerp et al.	N/A	N/A
2002/0123048	12/2001	Gau	N/A	N/A
2002/0133224	12/2001	Bajgar et al.	N/A	N/A
2002/0151796	12/2001	Koulik	N/A	N/A
2002/0155615	12/2001	Novikov et al.	N/A	N/A
2002/0161288	12/2001	Shin et al.	N/A	N/A
2002/0182241	12/2001	Borenstein et al.	N/A	N/A
2002/0188185	12/2001	Sohrab	N/A	N/A
2002/0193679	12/2001	Malave et al.	N/A	N/A
2002/0193885	12/2001	Legeay et al.	N/A	N/A
2002/0198513	12/2001	Lebel et al.	N/A	N/A
2003/0004432	12/2002	Assenheimer	N/A	N/A
2003/0006669	12/2002	Pei et al.	N/A	N/A
2003/0021729	12/2002	Moller et al.	N/A	N/A
2003/0023171	12/2002	Sato et al.	N/A	N/A
2003/0023317	12/2002	Brauker et al.	N/A	N/A
2003/0028089	12/2002	Galley et al.	N/A	N/A
2003/0031699	12/2002	Van Antwerp	N/A	N/A
2003/0032874	12/2002	Rhodes et al.	N/A	N/A
2003/0050546	12/2002	Desai et al.	N/A	N/A
2003/0054428	12/2002	Monfre et al.	N/A	N/A
2003/0060692	12/2002	L. Ruchti et al.	N/A	N/A
2003/0060753	12/2002	Starkweather et al.	N/A	N/A
2003/0060765	12/2002	Campbell et al.	N/A	N/A
2003/0070548	12/2002	Clausen	N/A	N/A
2003/0072741	12/2002	Berglund et al.	N/A	N/A
2003/0076082	12/2002	Morgan et al.	N/A	N/A

2003/0078481	12/2002	McIvor et al.	N/A	N/A
2003/0078560	12/2002	Miller et al.	N/A	N/A
2003/0088238	12/2002	Poulsen et al.	N/A	N/A
2003/0091433	12/2002	Tam et al.	N/A	N/A
2003/0097082	12/2002	Purdy et al.	N/A	N/A
2003/0099682	12/2002	Moussy et al.	N/A	N/A
2003/0100040	12/2002	Bonnecaze et al.	N/A	N/A
2003/0100821	12/2002	Heller et al.	N/A	N/A
2003/0114836	12/2002	Estes et al.	N/A	N/A
2003/0117296	12/2002	Seely	N/A	N/A
2003/0119208	12/2002	Yoon et al.	N/A	N/A
2003/0120152	12/2002	Omiya	N/A	N/A
2003/0125612	12/2002	Fox et al.	N/A	N/A
2003/0125613	12/2002	Enegren et al.	N/A	N/A
2003/0130616	12/2002	Steil et al.	N/A	N/A
2003/0132227	12/2002	Geisler et al.	N/A	N/A
2003/0134347	12/2002	Heller et al.	N/A	N/A
2003/0143746	12/2002	Sage	N/A	N/A
2003/0153821	12/2002	Berner et al.	N/A	N/A
2003/0176183	12/2002	Drucker et al.	N/A	N/A
2003/0187338	12/2002	Say et al.	N/A	N/A
2003/0188427	12/2002	Say et al.	N/A	N/A
2003/0199744	12/2002	Buse et al.	N/A	N/A
2003/0199745	12/2002	Burson et al.	N/A	N/A
2003/0208113	12/2002	Mault et al.	N/A	N/A
2003/0211050	12/2002	Majeti et al.	N/A	N/A
2003/0211625	12/2002	Cohan et al.	N/A	N/A
2003/0212317	12/2002	Kovatchev et al.	N/A	N/A
2003/0212346	12/2002	Yuzhakov et al.	N/A	N/A
2003/0212347	12/2002	Sohrab	N/A	N/A
2003/0212379	12/2002	Bylund et al.	N/A	N/A
2003/0225324	12/2002	Anderson et al.	N/A	N/A
2003/0225437	12/2002	Ferguson	N/A	N/A
2003/0231550	12/2002	MacFarlane	N/A	N/A
2003/0235817	12/2002	Bartkowiak et al.	N/A	N/A
2004/0006263	12/2003	Anderson et al.	N/A	N/A
2004/0010207	12/2003	Flaherty et al.	N/A	N/A
2004/0011671	12/2003	Shults et al.	N/A	N/A
2004/0015063	12/2003	DeNuzzio et al.	N/A	N/A
2004/0015134	12/2003	Lavi et al.	N/A	N/A
2004/0023253	12/2003	Kunwar et al.	N/A	N/A
2004/0023317	12/2003	Motamedi et al.	N/A	N/A
2004/0024327	12/2003	Brodnick	N/A	N/A
2004/0030285	12/2003	Lavi et al.	N/A	N/A
2004/0030294	12/2003	Mahurkar	N/A	N/A
2004/0039298	12/2003	Abreu	N/A	N/A
2004/0039406	12/2003	Jessen	N/A	N/A
2004/0040840	12/2003	Mao et al.	N/A	N/A
2004/0044272	12/2003	Moerman et al.	N/A	N/A
2004/0045879	12/2003	Shults et al.	N/A	N/A

2004/0052689	12/2003	Yao	N/A	N/A
2004/0054352	12/2003	Adams et al.	N/A	N/A
2004/0068230	12/2003	Estes et al.	N/A	N/A
2004/0074785	12/2003	Holker et al.	N/A	N/A
2004/0078219	12/2003	Kaylor et al.	N/A	N/A
2004/0106857	12/2003	Gough	N/A	N/A
2004/0122297	12/2003	Stahmann et al.	N/A	N/A
2004/0122353	12/2003	Shahmirian et al.	N/A	N/A
2004/0138543	12/2003	Russell et al.	N/A	N/A
2004/0143173	12/2003	Reghabi et al.	N/A	N/A
2004/0146909	12/2003	Duong et al.	N/A	N/A
2004/0152187	12/2003	Haight et al.	N/A	N/A
2004/0152622	12/2003	Keith et al.	N/A	N/A
2004/0162678	12/2003	Hetzel et al.	N/A	N/A
2004/0167801	12/2003	Say et al.	N/A	N/A
2004/0173472	12/2003	Jung et al.	N/A	N/A
2004/0176672	12/2003	Silver et al.	N/A	N/A
2004/0180391	12/2003	Gratzl et al.	N/A	N/A
2004/0186362	12/2003	Brauker et al.	N/A	N/A
2004/0186365	12/2003	Jin et al.	N/A	N/A
2004/0193025	12/2003	Steil et al.	N/A	N/A
2004/0199059	12/2003	Brauker et al.	N/A	N/A
2004/0204687	12/2003	Mogensen et al.	N/A	N/A
2004/0219664	12/2003	Heller et al.	N/A	N/A
2004/0220517	12/2003	Starkweather et al.	N/A	N/A
2004/0224001	12/2003	Pacetti et al.	N/A	N/A
2004/0248282	12/2003	Sobha M. et al.	N/A	N/A
2004/0253365	12/2003	Warren et al.	N/A	N/A
2004/0254433	12/2003	Bandis et al.	N/A	N/A
2005/0003399	12/2004	Blackburn et al.	N/A	N/A
2005/0010265	12/2004	Baru et al.	N/A	N/A
2005/0026689	12/2004	Marks	N/A	N/A
2005/0027180	12/2004	Goode et al.	N/A	N/A
2005/0027181	12/2004	Goode, Jr. et al.	N/A	N/A
2005/0027182	12/2004	Siddiqui et al.	N/A	N/A
2005/0027462	12/2004	Goode, Jr. et al.	N/A	N/A
2005/0027463	12/2004	Goode, Jr. et al.	N/A	N/A
2005/0031689	12/2004	Shults et al.	N/A	N/A
2005/0033132	12/2004	Shults et al.	N/A	N/A
2005/0038332	12/2004	Saidara et al.	N/A	N/A
2005/0043598	12/2004	Goode et al.	N/A	N/A
2005/0049472	12/2004	Manda et al.	N/A	N/A
2005/0051427	12/2004	Brauker et al.	N/A	N/A
2005/0051440	12/2004	Simpson et al.	N/A	N/A
2005/0054909	12/2004	Petisce et al.	N/A	N/A
2005/0056552	12/2004	Simpson et al.	N/A	N/A
2005/0065464	12/2004	Talbot et al.	N/A	N/A
2005/0077584	12/2004	Uhland et al.	N/A	N/A
2005/0090607	12/2004	Tapsak et al.	N/A	N/A
2005/0096519	12/2004	DeNuzzio et al.	N/A	N/A

2005/0101847	12/2004	Routt et al.	N/A	N/A
2005/0107677	12/2004	Ward et al.	N/A	N/A
2005/0112169	12/2004	Brauker et al.	N/A	N/A
2005/0113653	12/2004	Fox et al.	N/A	N/A
2005/0113744	12/2004	Donoghue et al.	N/A	N/A
2005/0115832	12/2004	Simpson et al.	N/A	N/A
2005/0118344	12/2004	Pacetti	N/A	N/A
2005/0119720	12/2004	Gale et al.	N/A	N/A
2005/0121322	12/2004	Say et al.	N/A	N/A
2005/0124873	12/2004	Shults et al.	N/A	N/A
2005/0131305	12/2004	Danielson et al.	N/A	N/A
2005/0139489	12/2004	Davies et al.	N/A	N/A
2005/0143635	12/2004	Kamath et al.	N/A	N/A
2005/0143675	12/2004	Neel et al.	N/A	N/A
2005/0154271	12/2004	Rasdal et al.	N/A	N/A
2005/0176136	12/2004	Burd et al.	N/A	N/A
2005/0177036	12/2004	Shults et al.	N/A	N/A
2005/0177398	12/2004	Watanabe et al.	N/A	N/A
2005/0181012	12/2004	Saint et al.	N/A	N/A
2005/0182451	12/2004	Griffin et al.	N/A	N/A
2005/0183954	12/2004	Hitchcock et al.	N/A	N/A
2005/0187720	12/2004	Goode, Jr. et al.	N/A	N/A
2005/0192557	12/2004	Brauker et al.	N/A	N/A
2005/0197553	12/2004	Cooper	N/A	N/A
2005/0197554	12/2004	Polcha	N/A	N/A
2005/0203360	12/2004	Brauker et al.	N/A	N/A
2005/0211571	12/2004	Schulein et al.	N/A	N/A
2005/0215871	12/2004	Feldman et al.	N/A	N/A
2005/0215872	12/2004	Berner et al.	N/A	N/A
2005/0239154	12/2004	Feldman et al.	N/A	N/A
2005/0242479	12/2004	Petisce et al.	N/A	N/A
2005/0245795	12/2004	Goode, Jr. et al.	N/A	N/A
2005/0245799	12/2004	Brauker et al.	N/A	N/A
2005/0245904	12/2004	Estes et al.	N/A	N/A
2005/0251083	12/2004	Carr-Brendel et al.	N/A	N/A
2005/0261563	12/2004	Zhou et al.	N/A	N/A
2005/0288596	12/2004	Eigler et al.	N/A	N/A
2006/0001550	12/2005	Mann et al.	N/A	N/A
2006/0015020	12/2005	Neale et al.	N/A	N/A
2006/0015024	12/2005	Brister et al.	N/A	N/A
2006/0016700	12/2005	Brister et al.	N/A	N/A
2006/0019327	12/2005	Brister et al.	N/A	N/A
2006/0020186	12/2005	Brister et al.	N/A	N/A
2006/0020187	12/2005	Brister et al.	N/A	N/A
2006/0020188	12/2005	Kamath et al.	N/A	N/A
2006/0020189	12/2005	Brister et al.	N/A	N/A
2006/0020190	12/2005	Kamath et al.	N/A	N/A
2006/0020191	12/2005	Brister et al.	N/A	N/A
2006/0020192	12/2005	Brister et al.	N/A	N/A
2006/0036139	12/2005	Brister et al.	N/A	N/A

2006/0036140	12/2005	Brister et al.	N/A	N/A
2006/0036141	12/2005	Kamath et al.	N/A	N/A
2006/0036142	12/2005	Brister et al.	N/A	N/A
2006/0036143	12/2005	Brister et al.	N/A	N/A
2006/0036144	12/2005	Brister et al.	N/A	N/A
2006/0036145	12/2005	Brister et al.	N/A	N/A
2006/0040402	12/2005	Brauker et al.	N/A	N/A
2006/0047095	12/2005	Pacetti	N/A	N/A
2006/0052745	12/2005	Van Antwerp et al.	N/A	N/A
2006/0067908	12/2005	Ding	N/A	N/A
2006/0078908	12/2005	Pitner et al.	N/A	N/A
2006/0079740	12/2005	Silver et al.	N/A	N/A
2006/0079809	12/2005	Goldberger et al.	N/A	N/A
2006/0094946	12/2005	Kellogg et al.	N/A	N/A
2006/0100588	12/2005	Brunnberg et al.	N/A	N/A
2006/0134165	12/2005	Pacetti	N/A	N/A
2006/0171980	12/2005	Helmus et al.	N/A	N/A
2006/0173406	12/2005	Hayes et al.	N/A	N/A
2006/0177379	12/2005	Asgari	N/A	N/A
2006/0183871	12/2005	Ward et al.	N/A	N/A
2006/0183984	12/2005	Dobbles et al.	N/A	N/A
2006/0183985	12/2005	Brister et al.	N/A	N/A
2006/0189863	12/2005	Peyser et al.	N/A	N/A
2006/0195029	12/2005	Shults et al.	N/A	N/A
2006/0222566	12/2005	Brauker et al.	N/A	N/A
2006/0224141	12/2005	Rush et al.	N/A	N/A
2006/0253085	12/2005	Geismar et al.	N/A	N/A
2006/0258929	12/2005	Goode et al.	N/A	N/A
2006/0263839	12/2005	Ward et al.	N/A	N/A
2006/0269586	12/2005	Pacetti	N/A	N/A
2006/0275857	12/2005	Naer et al.	N/A	N/A
2006/0281985	12/2005	Ward et al.	N/A	N/A
2007/0007133	12/2006	Mang et al.	N/A	N/A
2007/0016381	12/2006	Kamath et al.	N/A	N/A
2007/0027385	12/2006	Brister et al.	N/A	N/A
2007/0032706	12/2006	Kamath et al.	N/A	N/A
2007/0038044	12/2006	Dobbles et al.	N/A	N/A
2007/0049873	12/2006	Hansen et al.	N/A	N/A
2007/0066873	12/2006	Kamath et al.	N/A	N/A
2007/0066956	12/2006	Finkel	N/A	N/A
2007/0085995	12/2006	Pesach et al.	N/A	N/A
2007/0100222	12/2006	Mastrototaro et al.	N/A	N/A
2007/0106135	12/2006	Sloan et al.	N/A	N/A
2007/0112298	12/2006	Mueller, Jr. et al.	N/A	N/A
2007/0116600	12/2006	Kochar et al.	N/A	N/A
2007/0129619	12/2006	Ward et al.	N/A	N/A
2007/0129621	12/2006	Kellogg et al.	N/A	N/A
2007/0135698	12/2006	Shah et al.	N/A	N/A
2007/0135699	12/2006	Ward et al.	N/A	N/A
2007/0151869	12/2006	Heller et al.	N/A	N/A

2007/0173706	12/2006	Neinast et al.	N/A	N/A
2007/0173710	12/2006	Petisce et al.	N/A	N/A
2007/0173761	12/2006	Kanderian, Jr. et al.	N/A	N/A
2007/0179434	12/2006	Weinert et al.	N/A	N/A
2007/0197889	12/2006	Brister et al.	N/A	N/A
2007/0200254	12/2006	Curry	N/A	N/A
2007/0200267	12/2006	Tsai	N/A	N/A
2007/0203407	12/2006	Hoss et al.	N/A	N/A
2007/0203410	12/2006	Say et al.	N/A	N/A
2007/0203966	12/2006	Brauker et al.	N/A	N/A
2007/0206193	12/2006	Pesach	N/A	N/A
2007/0208244	12/2006	Brauker et al.	N/A	N/A
2007/0208245	12/2006	Brauker et al.	N/A	N/A
2007/0208246	12/2006	Brauker et al.	N/A	N/A
2007/0213610	12/2006	Say et al.	N/A	N/A
2007/0218097	12/2006	Heller et al.	N/A	N/A
2007/0219441	12/2006	Carlin et al.	N/A	N/A
2007/0225579	12/2006	Lucassen et al.	N/A	N/A
2007/0225675	12/2006	Robinson et al.	N/A	N/A
2007/0227907	12/2006	Shah et al.	N/A	N/A
2007/0233013	12/2006	Schoenberg	N/A	N/A
2007/0233051	12/2006	Hohl et al.	N/A	N/A
2007/0235331	12/2006	Simpson et al.	N/A	N/A
2007/0240497	12/2006	Robinson et al.	N/A	N/A
2007/0244381	12/2006	Robinson et al.	N/A	N/A
2007/0244382	12/2006	Robinson et al.	N/A	N/A
2007/0249916	12/2006	Pesach et al.	N/A	N/A
2007/0255126	12/2006	Moberg et al.	N/A	N/A
2007/0275193	12/2006	DeSimone et al.	N/A	N/A
2007/0293742	12/2006	Simonsen et al.	N/A	N/A
2007/0299409	12/2006	Whitbourne et al.	N/A	N/A
2008/0021666	12/2007	Goode et al.	N/A	N/A
2008/0021668	12/2007	Son	N/A	N/A
2008/0027301	12/2007	Ward et al.	N/A	N/A
2008/0029390	12/2007	Roche et al.	N/A	N/A
2008/0029391	12/2007	Mao et al.	N/A	N/A
2008/0033254	12/2007	Kamath et al.	N/A	N/A
2008/0034972	12/2007	Gough et al.	N/A	N/A
2008/0045824	12/2007	Tapsak et al.	N/A	N/A
2008/0071157	12/2007	McGarraugh et al.	N/A	N/A
2008/0071158	12/2007	McGarraugh et al.	N/A	N/A
2008/0072663	12/2007	Keenan et al.	N/A	N/A
2008/0086040	12/2007	Heller et al.	N/A	N/A
2008/0086041	12/2007	Heller et al.	N/A	N/A
2008/0086042	12/2007	Brister et al.	N/A	N/A
2008/0086043	12/2007	Heller et al.	N/A	N/A
2008/0086044	12/2007	Brister et al.	N/A	N/A
2008/0086273	12/2007	Shults et al.	N/A	N/A
2008/0091094	12/2007	Heller et al.	N/A	N/A
2008/0091095	12/2007	Heller et al.	N/A	N/A

2008/0097289	12/2007	Steil et al.	N/A	N/A
2008/0108942	12/2007	Brister et al.	N/A	N/A
2008/0119703	12/2007	Brister et al.	N/A	N/A
2008/0119704	12/2007	Brister et al.	N/A	N/A
2008/0119706	12/2007	Brister et al.	N/A	N/A
2008/0125751	12/2007	Fjield et al.	N/A	N/A
2008/0139910	12/2007	Mastrototaro et al.	N/A	N/A
2008/0154101	12/2007	Jain et al.	N/A	N/A
2008/0183061	12/2007	Goode et al.	N/A	N/A
2008/0183399	12/2007	Goode et al.	N/A	N/A
2008/0187655	12/2007	Markle et al.	N/A	N/A
2008/0188722	12/2007	Markle et al.	N/A	N/A
2008/0188725	12/2007	Markle et al.	N/A	N/A
2008/0188731	12/2007	Brister et al.	N/A	N/A
2008/0189051	12/2007	Goode et al.	N/A	N/A
2008/0193936	12/2007	Squirrell	N/A	N/A
2008/0194837	12/2007	Kim et al.	N/A	N/A
2008/0194935	12/2007	Brister et al.	N/A	N/A
2008/0194936	12/2007	Goode et al.	N/A	N/A
2008/0194937	12/2007	Goode et al.	N/A	N/A
2008/0195967	12/2007	Goode et al.	N/A	N/A
2008/0197024	12/2007	Simpson et al.	N/A	N/A
2008/0200788	12/2007	Brister et al.	N/A	N/A
2008/0200789	12/2007	Brister et al.	N/A	N/A
2008/0200791	12/2007	Simpson et al.	N/A	N/A
2008/0208025	12/2007	Shults et al.	N/A	N/A
2008/0210557	12/2007	Heller et al.	N/A	N/A
2008/0214915	12/2007	Brister et al.	N/A	N/A
2008/0262469	12/2007	Brister et al.	N/A	N/A
2008/0269723	12/2007	Mastrototaro et al.	N/A	N/A
2008/0287764	12/2007	Rasdal et al.	N/A	N/A
2008/0287765	12/2007	Rasdal et al.	N/A	N/A
2008/0287766	12/2007	Rasdal et al.	N/A	N/A
2008/0296155	12/2007	Shults et al.	N/A	N/A
2008/0300572	12/2007	Rankers et al.	N/A	N/A
2008/0305009	12/2007	Gamsey et al.	N/A	N/A
2008/0305506	12/2007	Suri	N/A	N/A
2008/0306368	12/2007	Goode, Jr. et al.	N/A	N/A
2008/0306433	12/2007	Cesaroni	N/A	N/A
2008/0306434	12/2007	Dobbles et al.	N/A	N/A
2008/0306435	12/2007	Kamath et al.	N/A	N/A
2008/0306444	12/2007	Brister et al.	N/A	N/A
2009/0005666	12/2008	Shin et al.	N/A	N/A
2009/0012379	12/2008	Goode, Jr. et al.	N/A	N/A
2009/0018418	12/2008	Markle et al.	N/A	N/A
2009/0018424	12/2008	Kamath et al.	N/A	N/A
2009/0018426	12/2008	Markle et al.	N/A	N/A
2009/0036758	12/2008	Brauker et al.	N/A	N/A
2009/0043181	12/2008	Brauker et al.	N/A	N/A
2009/0043182	12/2008	Brauker et al.	N/A	N/A

2009/0043525	12/2008	Brauker et al.	N/A	N/A
2009/0043541	12/2008	Brauker et al.	N/A	N/A
2009/0043542	12/2008	Brauker et al.	N/A	N/A
2009/0061528	12/2008	Suri	N/A	N/A
2009/0062635	12/2008	Brauker et al.	N/A	N/A
2009/0062645	12/2008	Fehre et al.	N/A	N/A
2009/0076356	12/2008	Simpson et al.	N/A	N/A
2009/0076360	12/2008	Brister et al.	N/A	N/A
2009/0076361	12/2008	Kamath et al.	N/A	N/A
2009/0081803	12/2008	Gamsey et al.	N/A	N/A
2009/0099434	12/2008	Liu et al.	N/A	N/A
2009/0124877	12/2008	Goode, Jr. et al.	N/A	N/A
2009/0124878	12/2008	Goode, Jr. et al.	N/A	N/A
2009/0124964	12/2008	Leach et al.	N/A	N/A
2009/0131768	12/2008	Simpson et al.	N/A	N/A
2009/0131769	12/2008	Leach et al.	N/A	N/A
2009/0131776	12/2008	Simpson et al.	N/A	N/A
2009/0131777	12/2008	Simpson et al.	N/A	N/A
2009/0137886	12/2008	Shariati et al.	N/A	N/A
2009/0137887	12/2008	Shariati et al.	N/A	N/A
2009/0143659	12/2008	Li et al.	N/A	N/A
2009/0156924	12/2008	Shariati et al.	N/A	N/A
2009/0177143	12/2008	Markle et al.	N/A	N/A
2009/0178459	12/2008	Li et al.	N/A	N/A
2009/0182217	12/2008	Li et al.	N/A	N/A
2009/0192366	12/2008	Mensingher et al.	N/A	N/A
2009/0192380	12/2008	Shariati et al.	N/A	N/A
2009/0192722	12/2008	Shariati et al.	N/A	N/A
2009/0192724	12/2008	Brauker et al.	N/A	N/A
2009/0192745	12/2008	Kamath et al.	N/A	N/A
2009/0192751	12/2008	Kamath et al.	N/A	N/A
2009/0203981	12/2008	Brauker et al.	N/A	N/A
2009/0204341	12/2008	Brauker et al.	N/A	N/A
2009/0216103	12/2008	Brister et al.	N/A	N/A
2009/0240120	12/2008	Mensingher et al.	N/A	N/A
2009/0240128	12/2008	Mensingher et al.	N/A	N/A
2009/0240193	12/2008	Mensingher et al.	N/A	N/A
2009/0242399	12/2008	Kamath et al.	N/A	N/A
2009/0242425	12/2008	Kamath et al.	N/A	N/A
2009/0264719	12/2008	Markle et al.	N/A	N/A
2009/0264856	12/2008	Lebel et al.	N/A	N/A
2009/0287074	12/2008	Shults et al.	N/A	N/A
2009/0299155	12/2008	Yang et al.	N/A	N/A
2009/0299156	12/2008	Simpson et al.	N/A	N/A
2009/0299162	12/2008	Brauker et al.	N/A	N/A
2009/0299276	12/2008	Brauker et al.	N/A	N/A
2010/0010324	12/2009	Brauker et al.	N/A	N/A
2010/0010331	12/2009	Brauker et al.	N/A	N/A
2010/0010332	12/2009	Brauker et al.	N/A	N/A
2010/0016687	12/2009	Brauker et al.	N/A	N/A

2010/0022855	12/2009	Brauker et al.	N/A	N/A
2010/0030053	12/2009	Goode, Jr. et al.	N/A	N/A
2010/0030484	12/2009	Brauker et al.	N/A	N/A
2010/0030485	12/2009	Brauker et al.	N/A	N/A
2010/0036215	12/2009	Goode, Jr. et al.	N/A	N/A
2010/0036216	12/2009	Goode, Jr. et al.	N/A	N/A
2010/0036222	12/2009	Goode, Jr. et al.	N/A	N/A
2010/0036223	12/2009	Goode, Jr. et al.	N/A	N/A
2010/0036224	12/2009	Goode, Jr. et al.	N/A	N/A
2010/0036225	12/2009	Goode, Jr. et al.	N/A	N/A
2010/0041971	12/2009	Goode, Jr. et al.	N/A	N/A
2010/0045465	12/2009	Brauker et al.	N/A	N/A
2010/0049024	12/2009	Saint et al.	N/A	N/A
2010/0076283	12/2009	Simpson et al.	N/A	N/A
2010/0081908	12/2009	Dobbles et al.	N/A	N/A
2010/0081910	12/2009	Brister et al.	N/A	N/A
2010/0161269	12/2009	Kamath et al.	N/A	N/A
2010/0179401	12/2009	Rasdal et al.	N/A	N/A
2010/0179407	12/2009	Goode, Jr. et al.	N/A	N/A
2010/0179408	12/2009	Kamath et al.	N/A	N/A
2010/0179409	12/2009	Kamath et al.	N/A	N/A
2010/0234707	12/2009	Goode, Jr. et al.	N/A	N/A
2010/0235106	12/2009	Kamath et al.	N/A	N/A
2010/0240975	12/2009	Goode, Jr. et al.	N/A	N/A
2010/0240976	12/2009	Goode, Jr. et al.	N/A	N/A
2010/0331656	12/2009	Mensing et al.	N/A	N/A
2010/0331657	12/2009	Mensing et al.	N/A	N/A
2011/0009727	12/2010	Mensing et al.	N/A	N/A
2011/0118579	12/2010	Goode, Jr. et al.	N/A	N/A
2011/0124997	12/2010	Goode, Jr. et al.	N/A	N/A
2011/0130970	12/2010	Goode, Jr. et al.	N/A	N/A
2011/0137601	12/2010	Goode, Jr. et al.	N/A	N/A
2011/0201910	12/2010	Rasdal et al.	N/A	N/A
2011/0218414	12/2010	Kamath et al.	N/A	N/A
2011/0231107	12/2010	Brauker et al.	N/A	N/A
2011/0231140	12/2010	Goode, Jr. et al.	N/A	N/A
2011/0231141	12/2010	Goode, Jr. et al.	N/A	N/A
2011/0231142	12/2010	Goode, Jr. et al.	N/A	N/A
2011/0257895	12/2010	Brauker et al.	N/A	N/A
2011/0270158	12/2010	Brauker et al.	N/A	N/A
2012/0059673	12/2011	Cohen et al.	N/A	N/A
2012/0097289	12/2011	Chun et al.	N/A	N/A
2012/0186581	12/2011	Brauker et al.	N/A	N/A
2012/0190953	12/2011	Brauker et al.	N/A	N/A
2012/0191063	12/2011	Brauker et al.	N/A	N/A
2012/0215201	12/2011	Brauker et al.	N/A	N/A
2012/0220979	12/2011	Brauker et al.	N/A	N/A
2012/0227737	12/2011	Mastrototaro et al.	N/A	N/A
2012/0238852	12/2011	Brauker et al.	N/A	N/A
2012/0259278	12/2011	Hayes et al.	N/A	N/A

2012/0296311	12/2011	Brauker et al.	N/A	N/A
2018/0043096	12/2017	Dobbles et al.	N/A	N/A
2018/0185587	12/2017	Brauker et al.	N/A	N/A
2019/0070360	12/2018	Sloan et al.	N/A	N/A
2019/0209009	12/2018	Brister et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2127172	12/1997	CA	N/A
10103803	12/2000	DE	N/A
0098592	12/1983	EP	N/A
0107634	12/1983	EP	N/A
0127958	12/1983	EP	N/A
0286118	12/1987	EP	N/A
0288793	12/1987	EP	N/A
0320109	12/1988	EP	N/A
0352610	12/1989	EP	N/A
0352631	12/1989	EP	N/A
0353328	12/1989	EP	N/A
0390390	12/1989	EP	N/A
0396788	12/1989	EP	N/A
0406473	12/1990	EP	N/A
0440044	12/1990	EP	N/A
0441252	12/1990	EP	N/A
0441394	12/1990	EP	N/A
0467078	12/1991	EP	N/A
0534074	12/1992	EP	N/A
0535898	12/1992	EP	N/A
0539751	12/1992	EP	N/A
0563795	12/1992	EP	N/A
0323605	12/1993	EP	N/A
0647849	12/1994	EP	N/A
0424633	12/1995	EP	N/A
0729366	12/1995	EP	N/A
0747069	12/1995	EP	N/A
0776628	12/1996	EP	N/A
0817809	12/1997	EP	N/A
0838230	12/1997	EP	N/A
0880936	12/1997	EP	N/A
0885932	12/1997	EP	N/A
0967788	12/1998	EP	N/A
0995805	12/1999	EP	N/A
1077634	12/2000	EP	N/A
1078258	12/2000	EP	N/A
1102194	12/2000	EP	N/A
0789540	12/2000	EP	N/A
1144028	12/2000	EP	N/A
1153571	12/2000	EP	N/A
0817809	12/2001	EP	N/A
1266607	12/2001	EP	N/A

1338295	12/2002	EP	N/A
1067862	12/2003	EP	N/A
1144028	12/2003	EP	N/A
1498067	12/2004	EP	N/A
1571582	12/2004	EP	N/A
2223710	12/2009	EP	N/A
2226086	12/2009	EP	N/A
2228642	12/2009	EP	N/A
2656423	12/1990	FR	N/A
2760962	12/1997	FR	N/A
1442303	12/1975	GB	N/A
2149918	12/1984	GB	N/A
S6283649	12/1986	JP	N/A
S6283849	12/1986	JP	N/A
H0783871	12/1994	JP	N/A
2000060826	12/1999	JP	N/A
2002515302	12/2001	JP	N/A
2002189015	12/2001	JP	N/A
2003079723	12/2002	JP	N/A
2003108679	12/2002	JP	N/A
2004000555	12/2003	JP	N/A
8902720	12/1988	WO	N/A
9000738	12/1989	WO	N/A
9010861	12/1989	WO	N/A
9013021	12/1989	WO	N/A
9116416	12/1990	WO	N/A
9213271	12/1991	WO	N/A
9314693	12/1992	WO	N/A
9323744	12/1992	WO	N/A
9422367	12/1993	WO	N/A
9507109	12/1994	WO	N/A
9513838	12/1994	WO	N/A
9601611	12/1995	WO	N/A
9603117	12/1995	WO	N/A
9614026	12/1995	WO	N/A
9625089	12/1995	WO	N/A
9630431	12/1995	WO	N/A
9632076	12/1995	WO	N/A
9637246	12/1995	WO	N/A
9701986	12/1996	WO	N/A
9706727	12/1996	WO	N/A
9719188	12/1996	WO	N/A
9728737	12/1996	WO	N/A
9743633	12/1996	WO	N/A
9824358	12/1997	WO	N/A
9838906	12/1997	WO	N/A
9948419	12/1998	WO	N/A
9956613	12/1998	WO	N/A
9958051	12/1998	WO	N/A
9958973	12/1998	WO	N/A

9959657	12/1998	WO	N/A
0012720	12/1999	WO	N/A
0013002	12/1999	WO	N/A
0013003	12/1999	WO	N/A
0019887	12/1999	WO	N/A
0032098	12/1999	WO	N/A
0033065	12/1999	WO	N/A
0049941	12/1999	WO	N/A
0059373	12/1999	WO	N/A
0074753	12/1999	WO	N/A
0078210	12/1999	WO	N/A
0112158	12/2000	WO	N/A
0116579	12/2000	WO	N/A
0120019	12/2000	WO	N/A
0120334	12/2000	WO	N/A
0134243	12/2000	WO	N/A
0143660	12/2000	WO	N/A
0152727	12/2000	WO	N/A
0158348	12/2000	WO	N/A
0168901	12/2000	WO	N/A
0169222	12/2000	WO	N/A
0188524	12/2000	WO	N/A
0188534	12/2000	WO	N/A
0205702	12/2001	WO	N/A
0224065	12/2001	WO	N/A
0078210	12/2001	WO	N/A
02082989	12/2001	WO	N/A
02089666	12/2001	WO	N/A
02100266	12/2001	WO	N/A
03000127	12/2002	WO	N/A
03022125	12/2002	WO	N/A
03022327	12/2002	WO	N/A
03047426	12/2002	WO	N/A
03063700	12/2002	WO	N/A
03072269	12/2002	WO	N/A
03101862	12/2002	WO	N/A
2004009161	12/2003	WO	N/A
2004110256	12/2003	WO	N/A
2005011489	12/2004	WO	N/A
2005012873	12/2004	WO	N/A
2005026689	12/2004	WO	N/A
2005032400	12/2004	WO	N/A
2005057168	12/2004	WO	N/A
2005057175	12/2004	WO	N/A
2005078424	12/2004	WO	N/A
2005026689	12/2004	WO	N/A
2005093629	12/2004	WO	N/A
2005106446	12/2004	WO	N/A
2006017358	12/2005	WO	N/A
2006021430	12/2005	WO	N/A

2006050405	12/2005	WO	N/A
2006105146	12/2005	WO	N/A
2006118713	12/2005	WO	N/A
2006131288	12/2005	WO	N/A
2007002209	12/2006	WO	N/A
2007002579	12/2006	WO	N/A
2007065285	12/2006	WO	N/A
2007097754	12/2006	WO	N/A
2007114943	12/2006	WO	N/A
2007127606	12/2006	WO	N/A
2007137286	12/2006	WO	N/A
2007143225	12/2006	WO	N/A
2008001091	12/2007	WO	N/A
2008076868	12/2007	WO	N/A

OTHER PUBLICATIONS

US 7,530,950 B2, 05/2009, Brister et al. (withdrawn) cited by applicant

Klonoff D., et al., "Performance Metrics for Continuous Interstitial Glucose Monitoring; Approved Guideline," Clinical and Laboratory Standards Institute, POCT05-A, vol. 28 (33), 2008, 72 pages. cited by applicant

Klonoff D.C., "Editorial: Current, Emerging, and Future Trends in Metabolic Monitoring," Diabetes Technology Therapeutics, vol. 4 (5), 2002, pp. 583-588. cited by applicant

Klueh U., et al., "Inflammation and Glucose Sensors: Use of Dexamethasone to Extend Glucose Sensor Function and Life Span in Vivo," Journal of Diabetes Science and Technology, vol. 1 (4), Jul. 2007, pp. 496-504. cited by applicant

Klueh U., et al., "Use of Vascular Endothelial Cell Growth Factor Gene Transfer to Enhance Implantable Sensor Function in Vivo," Biosensor Function and VEGF-Gene Transfer, vol. 67 (4), 2003, pp. 1072-1086. cited by applicant

Kondo T., et al., "A Miniature Glucose Sensor, Implantable in the Blood Stream," Diabetes Care, vol. 5 (3), May-Jun. 1982, 218-221. cited by applicant

Koschinsky T., et al., "Sensors for Glucose Monitoring: Technical And Clinical Aspects," Diabetes Metabolism Research and Reviews, vol. 17, No. 2, Jan. 1, 2001, pp. 113-123. cited by applicant

Koschinsky T., et al., "New Approach to Technical and Clinical Evaluation of Devices for Self-Monitoring of Blood Glucose," Diabetes Care, vol. 11 (8), Sep. 1988, pp. 619-629. cited by applicant

Koschinsky T., et al., "Review: Glucose Sensors and the Alternate Site Testing-like Phenomenon: Relationship Between Rapid Blood Glucose Changes and Glucose Sensor Signals," Diabetes Technology & Therapeutics, vol. 5 (5), 2003, pp. 829-842. cited by applicant

Kost J., et al., "Glucose-Sensitive Membranes Containing Glucose Oxidase: Activity, Swelling, and Permeability Studies," Journal of Biomedical Materials Research, vol. 19, 1985, pp. 1117-1133. cited by applicant

Koudelka M., et al., "In Vivo Response of Microfabricated Glucose Sensors to Glycemia Changes in Normal Rats," Biomed. Biochim. Acta, vol. 48 (11/12), Nov.-Dec. 1989, pp. 953-956. cited by applicant

Koudelka M., et al., "In-Vivo Behaviour of Hypodermically Implanted Microfabricated Glucose Sensors," Biosensors and Bioelectronics, vol. 6, 1991, pp. 31-36. cited by applicant

Kovatchev B.P., et al., "Evaluating the Accuracy of Continuous Glucose-Monitoring Sensors: Continuous Glucose-Error Grid Analysis Illustrated by TheraSense Freestyle Navigator Data," Diabetes Care, vol. 27 (8), Aug. 2004, pp. 1922-1928. cited by applicant

Kraver., et al., "A Mixed-Signal Sensor Interface Microinstrument," Sensors and Actuators A,

Physical 2001, vol. 91, pp. 266-277. cited by applicant

Krouwer U.S., "Setting Performance Goals and Evaluating Total Analytical Error for Diagnostic Assays," *Clinical Chemistry*, vol. 48 (6), 2002, pp. 919-927. cited by applicant

Kruger D., et al., "Psychological Motivation and Patient Education: A Role for Continuous Glucose Monitoring," *Diabetes Technology and Therapeutics*, vol. 2 (1), 2000, pp. S93-S97. cited by applicant

Kulys J., et al., "Carbon-Paste Biosensors Array for Long-Term Glucose Measurement," *Biosensors & Bioelectronics*, vol. 9, 1994, pp. 491-500. cited by applicant

Kunjan K., et al., "Automated Blood Sampling and Glucose Sensing in Critical Care Settings," *Journal of Diabetes Science and Technology*, vol. 2 (2), Mar. 2008, pp. 194-200. cited by applicant

Kunzler J., et al., "Hydrogels based on Hydrophilic Side Chain Siloxanes," *Poly Mat Sci and Eng*, 1993, vol. 69, pp. 226-227. cited by applicant

Kunzler J F., et al., "Contact Lens Materials," *Chemistry & Industry*, Aug. 21, 1995, pp. 651-655. cited by applicant

Kurnik R.T., et al., "Application of the Mixtures of Experts Algorithm for Signal Processing in a Noninvasive Glucose Monitoring System," *Sensors and Actuators B*, vol. 60, 1999, pp. 19-26. cited by applicant

Kurtz T.W., et al., "Recommendations for Blood Pressure Measurement in Humans and Experimental Animals, Part 2: Blood Pressure Measurement In Experimental Animals: A Statement for Professionals From the Subcommittee of Professional and Public Education of the American Heart Association Council on High Blood Pressure Research," *Hypertension*, Feb. 2005, vol. 45, pp. 299-310. cited by applicant

Lacourse W.R., et al., "Optimization of Waveforms for Pulsed Amperometric Detection of Carbohydrates Based on Pulsed Voltammetry," *Analytical Chemistry*, vol. 65, 1993, pp. 50-52. cited by applicant

Ladd M.F.C., et al., "Structure Determination by X-Ray Crystallography," 3rd Edition, Plenum Press, 1994, Ch. 1, pp. xxi-xxiv and 1-58. cited by applicant

Lee E., et al., "Effects of Pore Size, Void Volume and Pore Connectivity on Tissue Responses to Porous Silicone Implants," *Society for Biomaterials, 25th Annual Meeting*, 1999, p. 171. cited by applicant

Lee S.W., et al., "Combined Insulin Pump Therapy with Real-Time Continuous Glucose Monitoring Significantly Improves Glycemic Control Compared to Multiple Daily Injection Therapy in Pump Nave Patients with Type 1 Diabetes; Single Center Pilot Study Experience," *Journal of Diabetes Science and Technology*, vol. 1 (3), May 2007, pp. 400-404. cited by applicant

Lehmann E.D., et al., Retrospective Validation of a Physiological Model of Glucose-Insulin Interaction in Type 1 Diabetes Mellitus. *Medical Engineering & Physics*, vol. 16, May 1994, pp. 193-202. cited by applicant

Lerner., et al., "An Implantable Electrochemical Glucose Sensor," *Ann. N. Y. Acad. Sci.*, vol. 428, May 1984, pp. 263-278. cited by applicant

Lewandowski J.J., et al., "Evaluation of a Miniature Blood Glucose Sensor," *Transactions—American Society for Artificial Internal Organs*, vol. 34, 1988, pp. 255-258. cited by applicant

Leyboldt J.K., et al., "Model of a Two-Substrate Enzyme Electrode for Glucose," *Analytical Chemistry*, vol. 56, 1984, pp. 2896-2904. cited by applicant

Linke B., et al., "Amperometric Biosensor for In Vivo Glucose Sensing Based on Glucose Oxidase Immobilized in a Redox Hydrogel," *Biosensors and Bioelectronics*, vol. 9, 1994, pp. 151-158. cited by applicant

Loffler P., et al., "Separation and Determination of Traces of Ammonia in Air by Means of Chromatomembrane Cells," *Fresenius Journal of Analytical Chemistry*, 1995, vol. 352, pp. 613-614. cited by applicant

Lohn A., et al., "A Knowledge-Based System for Real-Time Validation of Calibrations and

Measurements,” *Chemometrics and Intelligent Laboratory Systems*, vol. 46, 1999, pp. 57-66. cited by applicant

Lowe C.R., “Biosensors,” *Trends in Biotechnology*, vol. 2 (3), 1984, pp. 59-65. cited by applicant

Luong J.H.T., et al., “Solubilization of Multiwall Carbon Nanotubes by 3-Aminopropyltriethoxysilane towards the Fabrication of Electrochemical Biosensors with Promoted Electron Transfer,” *Electroanalysis*, vol. 16 (1-2), 2004, pp. 132-139. cited by applicant

Lyandres O., et al. “Progress toward an In Vivo Surface-Enhanced Raman Spectroscopy Glucose Sensor,” *Diabetes Technology and Therapeutics*, vol. 10 (4), 2008, pp. 257-265. cited by applicant

Lyman D J., “Polyurethanes. I. The Solution Polymerization of Diisocyanates with Ethylene Glycol,” *Journal of Polymer Science*, 1960, vol. XLV, pp. 49-59. cited by applicant

Lynch S.M., et al., “Estimation-Based Model Predictive Control of Blood Glucose in Type I Diabetics: A Simulation Study,” *Proceedings of the IEEE 27th Annual Northeast Bioengineering Conference*, 2001, pp. 79-80. cited by applicant

Lynn P.A., “Recursive Digital Filters for Biological Signals,” *Med. Biol. Engineering*, vol. 9, 1971, pp. 37-43. cited by applicant

Madaras M B., et al., “Microfabricated Amperometric Creatine and Creatinine Biosensors,” *Analytica Chimica Acta*, 1996, vol. 319, pp. 335-345. cited by applicant

Maidan R., et al., “Elimination of Electrooxidizable Interferent-Produced Currents in Amperometric Biosensors,” *Analytical Chemistry*, vol. 64, 1992, pp. 2889-2896. cited by applicant

Makale M.T., et al., “Tissue Window Chamber System for Validation of Implanted Oxygen Sensors,” *American Journal of Physiology—Heart and Circulatory Physiology*, vol. 284, Feb. 21, 2003, pp. 1-27. cited by applicant

Malin S.F., et al., “Noninvasive Prediction of Glucose by Near-Infrared Diffuse Reflectance Spectroscopy,” *Clinical Chemistry*, vol. 45 (9), 1999, pp. 1651-1658. cited by applicant

Mancy K.H., et al., “A Galvanic Cell Oxygen Analyzer,” *Journal of Electroanalytical Chemistry*, vol. 4, 1962, pp. 65-92. cited by applicant

Maran A., et al., “Continuous Subcutaneous Glucose Monitoring in Diabetic Patients,” *A Multicenter Analysis*, *Diabetes Care*, vol. 25 (2), Feb. 2002, pp. 347-352. cited by applicant

March W.F., “Dealing with the Delay,” *Diabetes Technology & Therapeutics*, vol. 4 (1), 2002, pp. 49-50. cited by applicant

Marena S., et al., “The Artificial Endocrine Pancreas in Clinical Practice and Research,” *Panminerva Medica*, vol. 35 (2), 1993, pp. 67-74. cited by applicant

Martin R.F., “General Deming Regression for Estimating Systematic Bias and its Confidence Interval in Method-Comparison Studies,” *Clinical Chemistry*, vol. 46 (1), 2000, pp. 100-104. cited by applicant

Mascini M., et al., “Glucose Electrochemical Probe with Extended Linearity for Whole Blood,” *Journal Pharmaceutical and Biomedical Analysis*, vol. 7 (12), 1989, pp. 1507-1512. cited by applicant

Mastrototaro J.J., et al., “An Electroenzymatic Glucose Sensor Fabricated on a Flexible Substrate,” *Sensors and Actuators B*, vol. 5, 1991, pp. 139-144. cited by applicant

Mastrototaro J.J., et al., “Reproducibility of the Continuous Glucose Monitoring System Matches Previous Reports and the Intended Use of the Product,” *Diabetes Care*, vol. 26 (1), Jan. 2003, pp. 256-257. cited by applicant

Ernst H., et al., “Reliable Glucose Monitoring Through the Use of Microsystem Technology,” *Analytical Bioanalytical Chemistry*, vol. 373, 2002, pp. 758-761. cited by applicant

Fabietti P.G., et al., “Clinical Validation of a New Control-Oriented Model of Insulin and Glucose Dynamics in Subjects with Type 1 Diabetes,” *Diabetes Technology & Therapeutics*, vol. 9 (4), 2007, pp. 327-338. cited by applicant

Fahy B.G., et al., “An Analysis: Hyperglycemic Intensive Care Patients Need Continuous Glucose Monitoring—Easier Said Than Done,” *Journal of Diabetes Science and Technology*, *Diabetes*

Technology Society, vol. 2 (2), Mar. 2008, pp. 201-204. cited by applicant

Fare T.L., et al., "Functional Characterization of a Conducting Polymer-Based Immunoassay System," *Biosensors & Bioelectronics*, vol. 13 (3-4), 1998, pp. 459-470. cited by applicant

Feldman B., et al., "A Continuous Glucose Sensor Based on Wired Enzyme™ Technology—Results from a 3-Day Trial in Patients with Type 1 Diabetes," *Diabetes Technology & Therapeutics*, vol. 5 (5), 2003, pp. 769-779. cited by applicant

Fischer U., et al., "Assessment of Subcutaneous Glucose Concentration: Validation of the Wick Technique as a Reference for Implanted Electrochemical Sensors in Normal and Diabetic Dogs," *Diabetologia*, vol. 30, 1987, pp. 940-945. cited by applicant

Fischer U., et al., "Hypoglycaemia—Warning by Means of Subcutaneous Electrochemical Glucose Sensors: An Animal Study," *Horm. Metab. Res.*, vol. 27, 1995, p. 53. (Abstract Only). cited by applicant

Fischer U., et al., "Oxygen Tension at the Subcutaneous Implantation Site of Glucose Sensors," *Biomed. Biochim. Acta*, vol. 48 (11/12), 1989, pp. 965-971. cited by applicant

Freedman D., et al., "Statistics," Second Edition, W.W. Norton & Company, New York & London, 1991, p. 74 (3 pages). cited by applicant

Freiberger P., "Video Game Takes on Diabetes Superhero 'Captain Novolin' Offers Treatment Tips," Fourth Edition, Jun. 26, 1992, Business Section, 2 pages. cited by applicant

Frohnauer M.K., et al., "Graphical Human Insulin Time-Activity Profiles Using Standardized Definitions," *Diabetes Technology & Therapeutics*, vol. 3 (3), 2001, pp. 419-429. cited by applicant

Frost M.C., et al., "Implantable Chemical Sensors for Real-Time Clinical Monitoring: Progress and Challenges," *Current Opinion in Chemical Biology, Analytical Techniques*, vol. 6, 2002, pp. 633-641. cited by applicant

Gabby R.A., et al., "Optical Coherence Tomography-Based Continuous Noninvasive Glucose Monitoring in Patients with Diabetes," *Diabetes Technology & Therapeutics*, vol. 10, Nov. 3, 2008, pp. 188-193. cited by applicant

Ganesan N., et al., "Gold Layer-Based Dual Crosslinking Procedure of Glucose Oxidase with Ferrocene Monocarboxylic Acid Provides a Stable Biosensor," *Analytical Biochemistry, Notes & Tips*, vol. 343, 2005, pp. 188-191. cited by applicant

Ganesh A., et al., "Evaluation of the VIA Blood Chemistry Monitor for Glucose in Healthy and Diabetic Volunteers," *Journal of Diabetes Science and Technology*, vol. 2 (2), Mar. 2008, pp. 182-193. cited by applicant

Garg S.K., et al., "Correlation of Fingerstick Blood Glucose Measurements With GlucoWatch Biographer Glucose Results in Young Subjects With Type 1 Diabetes," *Emerging Treatments and Technologies, Diabetes Care*, vol. 22 (10), Oct. 1999, pp. 1708-1714. cited by applicant

Garg S.K., et al., "Improved Glucose Excursions Using an Implantable Real-Time Continuous Glucose Sensor in Adults With Type 1 Diabetes," *Emerging Treatments and Technologies, Diabetes Care*, vol. 27 (3), 2004, pp. 734-738. cited by applicant

Garg S.K., "New Insulin Analogues," *Diabetes Technology & Therapeutics*, vol. 7 (5), 2005, pp. 813-817. cited by applicant

Geller R.I., et al., "Use of an Immunoisolation Device for Cell Transplantation and Tumor Immunotherapy," *Annals of the New York Academy of Science*, 1997, vol. 831, pp. 438-451. cited by applicant

Gerritsen M., et al., "Influence of Inflammatory Cells and Serum on the Performance of Implantable Glucose Sensors," *Journal of Biomedical Material Research*, 2001, vol. 54, pp. 69-75. cited by applicant

Gerritsen M., et al., "Performance of Subcutaneously Implanted Glucose Sensors for Continuous Monitoring," *The Netherlands Journal of Medicine*, vol. 54, 1999, pp. 167-179. cited by applicant

Gerritsen M., et al., "Problems Associated with Subcutaneously Implanted Glucose Sensors,"

Diabetes Care, vol. 23 (2), Feb. 2000, pp. 143-145. cited by applicant

Gilligan B.J., et al., "Evaluation of a Subcutaneous Glucose Sensor Out to 3 Months in a Dog Model" Diabetes Care, vol. 17 (8), Aug. 1994, pp. 882-887. cited by applicant

Gilligan B.J., et al., "Feasibility of Continuous Long-Term Glucose Monitoring from a Subcutaneous Glucose Sensor in Humans," Diabetes Technology & Therapeutics, vol. 6 (3), 2004, pp. 378-386. cited by applicant

Godsland I.F., et al., "Maximizing the Success Rate of Minimal Model Insulin Sensitivity Measurement in Humans: The Importance of Basal Glucose Levels," The Biochemical Society and the Medical Research Society, Clinical Science, vol. 101, 2001, pp. 1-9. cited by applicant

Gouda M.D., et al., "Thermal Inactivation of Glucose Oxidase," The Journal of Biological Chemistry, vol. 278 (27), Issue of Jul. 4, 2003, pp. 24324-24333. cited by applicant

Gough D.A., et al., "Frequency Characterization of Blood Glucose Dynamics," Annals of Biomedical Engineering, vol. 31, 2003, pp. 91-97. cited by applicant

Gough D.A., et al., "Immobilized Glucose Oxidase in Implantable Glucose Sensor Technology," Diabetes Technology & Therapeutics, vol. 2 (3), 2000, pp. 377-380. cited by applicant

Gough D.A., "The implantable Glucose Sensor: An Example of Bioengineering Design," Introduction to Bioengineering, 2001, Chapter 3, pp. 57-66. cited by applicant

Gregg B A., et al., "Cross-Linked Redox Gels Containing Glucose Oxidase for Amperometric Biosensor Applications," Anal Chem, 1990, vol. 62, pp. 258-263. cited by applicant

Gross, et al., "Diabetes Technology & Therapeutics," Letters to the Editor, Diabetes Technology & Therapeutics, vol. 3 (1), 2001, pp. 129-131. cited by applicant

Gross T.M., et al., "Efficacy and Reliability of the Continuous Glucose Monitoring System," Diabetes Technology & Therapeutics, vol. 2, Supplement 1, 2000, pp. S19-S26. cited by applicant

Gross T.M., et al., "Performance Evaluation of the Minimed® Continuous Glucose Monitoring System During Patient Home Use," Diabetes Technology & Therapeutics, vol. 2(1), 2000, pp. 49-56. cited by applicant

Guerci B., et al., "Clinical Performance of CGMS in Type 1 Diabetic Patients Treated by Continuous Subcutaneous Insulin Infusion Using Insulin Analogs," Diabetes Care, vol. 26, 2003, pp. 582-589. cited by applicant

Hagvik J., "Glucose Measurement: Time for a Gold Standard," Journal of Diabetes Science and Technology, vol. 1 (2), Mar. 2007, pp. 169-172. cited by applicant

Hall S.B., et al., "Electrochemical Oxidation of Hydrogen Peroxide at Platinum Electrodes. Part 1. An Adsorption-controlled Mechanism," Electrochimica Acta, vol. 43, Nos. 5/6, 1998, pp. 579-588. cited by applicant

Hall S.B., et al., "Electrochemical Oxidation of Hydrogen Peroxide at Platinum Electrodes. Part II: Effect of potential," Electrochimica Acta, vol. 43 (14-15), 1998, pp. 2015-2024. cited by applicant

Hall S.B., et al., "Electrochemical Oxidation of Hydrogen Peroxide at Platinum Electrodes. Part III: Effect of Temperature," Electrochimica Acta, vol. 44, 1999, pp. 2455-2462. cited by applicant

Hall S.B., et al., "Electrochemical Oxidation of Hydrogen Peroxide at Platinum Electrodes. Part IV: Phosphate Buffer Dependence," Electrochimica Acta, vol. 44, 1999, pp. 4573-4582. cited by applicant

Hall S.B., et al., "Electrochemical Oxidation of Hydrogen Peroxide at Platinum Electrodes. Part V: Inhibition by Chloride," Electrochimica Acta, vol. 45, 2000, pp. 3573-3579. cited by applicant

Hamilton, "Complete Guide to Selecting the Right Hamilton Gastight, Microliter, and Specialty Syringe for your Application," Syringe Selection, www.hamiltoncompany.com 2006, 20 pages. cited by applicant

Harrison, et al., "Characterization of Perfluorosulfonic Acid Polymer Coated Enzyme Electrodes and a Miniaturized Integrated Potentiostat for Glucose Analysis in Whole Blood," Analytical Chemistry, 1988, vol. 60, pp. 2002-2007. cited by applicant

Hashiguchi Y., et al., "Development of a Miniaturized Glucose Monitoring System by Combining a Needle-Type Glucose Sensor with Microdialysis Sampling Method: Long-term subcutaneous tissue glucose monitoring in ambulatory diabetic patients," *Diabetes Care*, vol. 17, No. 5, May 1994, pp. 387-396. cited by applicant

Heinemann L., et al., "Review: Measurement of Insulin Absorption and Insulin Action," *Diabetes Technology & Therapeutics*, vol. 6 (5), 2004, pp. 698-718. cited by applicant

Heinemann L., "Measurement Quality of Blood Glucose Meters: Is There a Need for an Institution with an Unbiased View?," *Journal of Diabetes Science and Technology*, vol. 1 (2), Mar. 2007, pp. 178-180. cited by applicant

Heinemann L., "Review: Variability of Insulin Absorption and Insulin Action," *Diabetes Technology & Therapeutics*, vol. 4 (5), 2002, pp. 673-682. cited by applicant

Heise T., et al., "Hypoglycemia warning signal and glucose sensors: Requirements and concepts," *Diabetes Technology & Therapeutics*, vol. 5, No. 4, 2003, pp. 563-571. cited by applicant

Heller A., "Electrical Connection of Enzyme Redox Centers to Electrodes," *J. Phys. Chem.*, vol. 96, 1992, pp. 3579-3587. cited by applicant

Heller A., "Electrical Wiring of Redox Enzymes," *Ace. Chem. Res.*, vol. 23, 1990, pp. 128-134. cited by applicant

Heller A., "Implanted Electrochemical Glucose Sensors for the Management of Diabetes," *Annu. Rev., Biomed Eng.*, vol. 1, 1999, pp. 153-175. cited by applicant

Machine Translation of DE10103803A1, 2001, 1 page. cited by applicant

Machine Translation of JP2003079723A, 2003, 16 pages. cited by applicant

Patel H., et al., "Amperometric Glucose Sensors Based on Ferrocene Containing Polymeric Electron Transfer Systems—A Preliminary Report," *Biosensors & Bioelectronics*, vol. 18, 2003, pp. 1073-1076. cited by applicant

Peacock W.F., et al., "Cardiac Troponin and Outcome in Acute Heart Failure," *N. Engl. J. Med.*, vol. 358, 2008, pp. 2117-2126. cited by applicant

Peguin S., et al., "Pyruvate Oxidase and Oxaloacetate Decarboxylase Enzyme Electrodes—Simultaneous Determination of Transaminases with a Two-electrode-based Analyzer," *Analytica Chimica Acta*, vol. 222, 1989, pp. 83-93. cited by applicant

Pfeiffer E.F., et al., "On Line Continuous Monitoring of Subcutaneous Tissue Glucose is Feasible by Combining Portable Glucosensor with Microdialysis," *Horm. Metab. Res.*, vol. 25, 1993, pp. 121-124. cited by applicant

Pfeiffer E.F., "The Glucose Sensor: The Missing Link in Diabetes Therapy," *Horm Metab Res Suppl.*, vol. 24, 1990, pp. 154-164. cited by applicant

Phillips R.E., et al., "Biomedical Applications of Polyurethanes: Implications of Failure Mechanisms," *Journal of Biomedical application*, vol. 3, Oct. 1988, pp. 206-227. cited by applicant

Phillips R.P., "A High Capacity Transcutaneous Energy Transmission System," *ASIAO Journal*, vol. 41, 1995, pp. M259-M262. cited by applicant

Pichert J.W., et al., "Issues for the Coming Age of Continuous Glucose Monitoring," *Diabetes Educator*, vol. 26 (6), Nov.-Dec. 2000, pp. 969-980. cited by applicant

Pickup J.C., et al., "Developing Glucose Sensors for In Vivo Use," Elsevier Science Publishers Ltd (UK), *TIBTECH*, vol. 11, 1993, pp. 285-291. cited by applicant

Pickup J.C., et al., "Implantable Glucose Sensors: Choosing the Appropriate Sensor Strategy," *Biosensors*, vol. 3, (1987/1988), pp. 335-346. cited by applicant

Pickup J.C., et al., "In Vivo Molecular Sensing in Diabetes Mellitus: An Implantable Glucose Sensor with Direct Electron Transfer," *Diabetologia*, vol. 32, 1989, pp. 213-217. cited by applicant

Pickup J.C., et al., "Potentially-Implantable, Amperometric Glucose Sensors with Mediated Electron Transfer: Improving the Operating Stability," *Biosensors*, vol. 4, 1989, pp. 109-119. cited by applicant

Pickup J.C., et al., "Progress Towards in Vivo Glucose Sensing with a Ferrocene-Mediated

Amperometric Enzyme Electrode,” *Horm Metab Res Suppl*, vol. 20, 1988, pp. 34-36. cited by applicant

Pickup J.C., et al., “Responses and Calibration of Amperometric Glucose Sensors Implanted in the Subcutaneous Tissue of Man,” *ACTA Diabetol*, vol. 30, 1993, pp. 143-148. cited by applicant

Pineda L.M., et al., “Bone Regeneration with Resorbable Polymeric Membranes. III. Effect of Poly(L-lactide) Membrane Pore Size on the Bone Healing Process in Large Defects,” *Journal of Biomedical Materials Research*, vol. 31, 1996, pp. 385-394. cited by applicant

Pinner S.H., et al., “Cross-Linking of Cellulose Acetate by Ionizing Radiation,” *Nature*, vol. 184, Oct. 24, 1959, pp. 1303-1304. cited by applicant

Pishko M.V., et al., “Amperometric Glucose Microelectrodes Prepared Through Immobilization of Glucose Oxidase in Redox Hydrogels,” *Analytical Chemistry*, vol. 63 (20), 1991, pp. 2268-2272. cited by applicant

Pitzer K.R., et al., “Detection of Hypoglycemia with the Glucowatch Biographer,” *Diabetes Care*, vol. 24 (5), 2001, pp. 881-885. cited by applicant

Poirier J.Y., et al., “Clinical and Statistical Evaluation of Self-Monitoring Blood Glucose Meters,” *Diabetes Care*, vol. 21 (11), Nov. 1998, pp. 1919-1924. cited by applicant

Poitout V., et al., “A Glucose Monitoring System for on Line Estimation in Man of Blood Glucose Concentration Using a Miniaturized Glucose Sensor Implanted in the Subcutaneous Tissue and a Wearable Control Unit,” *Diabetologia*, vol. 36, 1993, pp. 658-663. cited by applicant

Poitout V., et al., “Development of a Glucose Sensor for Glucose Monitoring in Man: The Disposable Implant Concept,” *Clinical Materials*, vol. 15, 1994, pp. 241-246. cited by applicant

Poitout V., et al., “In Vitro and In Vivo Evaluation in Dogs of a Miniaturized Glucose Sensor,” *ASAIO Transactions*, vol. 37, 1991, pp. M298-M300. cited by applicant

Postlethwaite T.A., et al., “Interdigitated Array Electrode as an Alternative to the Rotated Ring-Disk Electrode for Determination of the Reaction Products of Dioxygen Reduction,” *Analytical Chemistry*, vol. 68 (17), Sep. 1996, pp. 2951-2958. cited by applicant

Prabhu V.G., et al., “Electrochemical Studies of Hydrogen Peroxide at a Platinum Disc Electrode,” *Electrochimica Acta*, vol. 26 (6), 1981, pp. 725-729. cited by applicant

Quinn C.A.P., et al., “Biocompatible, Glucose-Permeable Hydrogel for In situ Coating of Implantable Biosensors,” *Biomaterials*, vol. 18 (24), 1997, pp. 1665-1670. cited by applicant

Quinn C.P., et al., “Kinetics of Glucose Delivery to Subcutaneous Tissue in Rats Measured with 0.3-mm Amperometric Microsensors,” *The American Physiological Society*, vol. 269, 1995, pp. E155-E161. cited by applicant

Rabah M.A., et al., “Electrochemical Wear of Graphite Anodes During Electrolysis of Brine,” *Carbon*, vol. 29 (2), 1991, pp. 165-171. cited by applicant

Rafael E., “Cell Transplantation and Immunoisolation: Studies on a Macroencapsulation Device,” *Departments of Transplantation Surgery and Pathology, Karolinska Institutet, Huddinge Hospital, Stockholm, Sweden*, 1999, pp. 1-83. cited by applicant

Ratner B.D., “Reducing Capsular Thickness and Enhancing Angiogenesis around Implant Drug Release Systems,” *Journal of Controlled Release*, vol. 78, 2002, pp. 211-218. cited by applicant

Raya Systems Pioneers, “Raya Systems Pioneers Healthy Video Games,” *PlayRight*, Nov. 1993, pp. 14-15. cited by applicant

Reach G., “A Method for Evaluating in vivo the Functional Characteristics of Glucose Sensors,” *Biosensors*, vol. 2, 1986, pp. 211-220. cited by applicant

Reach G., et al., “Can Continuous Glucose Monitoring Be Used for the Treatment of Diabetes? ,” *Analytical Chemistry*, vol. 64 (6), Mar. 15, 1992, pp. 381A-386A. cited by applicant

Reach G., “Which Threshold to Detect Hypoglycemia? Value of Receiver-Operator Curve Analysis to Find a Compromise Between Sensitivity and Specificity,” *Diabetes Care*, vol. 24 (5), May 2001, pp. 803-804. cited by applicant

Rebrin K., et al., “Automated Feedback Control of Subcutaneous Glucose Concentration in

Diabetic Dogs,” *Diabetologia*, vol. 32, 1989, pp. 573-576. cited by applicant

Rebrin K., et al., “Subcutaneous Glucose Monitoring by Means of Electrochemical Sensors: Fiction or Reality?,” *Journal of Biomedical Engineering*, vol. 14, Jan. 1992, pp. 33-40. cited by applicant

Rebrin K., et al., “Subcutaneous Glucose Predicts Plasma Glucose Independent of Insulin: Implications for Continuous Monitoring,” *The American Physiological Society*, vol. 277, 1999, pp. E561-E571. cited by applicant

Renard E., “Implantable Closed-Loop Glucose Sensing and Insulin Delivery: The Future for Insulin Pump Therapy,” *Current Opinion in Pharmacology*, vol. 2 (6), 2002, pp. 708-716. cited by applicant

Reush, “Organometallic Compounds,” *Chemical Reactivity, Virtual Textbook of Organic Chemistry*, Retrieved from <http://www.cem.msu.edu/~reusch/VirtualText/orgmetal.htm> 2004, pp. 1-16. cited by applicant

Rhodes R.K., et al., “Prediction of Pocket-Portable and Implantable Glucose Enzyme Electrode Performance from Combined Species Permeability and Digital Simulation Analysis,” *Analytical Chemistry*, vol. 66 (9), May 1, 1994, pp. 1520-1529. cited by applicant

Rigla M., et al., “Real-Time Continuous Glucose Monitoring Together with Telemedical Assistance Improves Glycemic Control and Glucose Stability in Pump-Treated Patients,” *Diabetes Technology & Therapeutics*, vol. 10 (3), 2008, pp. 194-199. cited by applicant

Rinken T., et al., “Calibration of Glucose Biosensors by Using Pre-Steady State Kinetic Data,” *Biosensors & Bioelectronics*, vol. 13, 1998, pp. 801-807. cited by applicant

Ristic S., et al., “Review: Effects of Rapid-Acting Insulin Analogs on Overall Glycemic Control in Type 1 and Type 2 Diabetes Mellitus,” *Diabetes Technology & Therapeutics*, vol. 5 (1), 2003, pp. 57-66. cited by applicant

Rivers E.P., et al., “Central Venous Oxygen Saturation Monitoring in the Critically Ill Patient,” *Current Opinion in Critical Care*, 2001, vol. 7, pp. 204-211. cited by applicant

Sachlos E., et al., “Making Tissue Engineering Scaffolds Work Review on the Application of Solid Freeform Fabrication Technology to the Production of Tissue Engineering Scaffolds,” *European Cells and Materials*, vol. 5, 2003, pp. 29-40. cited by applicant

Sakakida M., et al., “Development of Ferrocene-Mediated Needle-Type Glucose Sensor as a Measure of True Subcutaneous Tissue Glucose Concentrations,” *Artif. Organs Today*, vol. 2 (2), 1992, pp. 145-158. cited by applicant

Sakakida M., et al., “Ferrocene-Mediated Needle Type Glucose Sensor Covered with Newly Designed Biocompatible Membrane,” *Sensors and Actuators B*, vol. 13-14, 1993, pp. 319-322. cited by applicant

Salardi S., et al., “The Glucose Area Under the Profiles Obtained with Continuous Glucose Monitoring System Relationships with HbA1C in Pediatric Type 1 Diabetic Patients,” *Diabetes Care*, vol. 25 (10), Oct. 2002, pp. 1840-1844. cited by applicant

Samuels M.P., “The Effects of Flight and Altitude,” *Arch Dis Child*, vol. 89, 2004, pp. 448-455. cited by applicant

San Diego Plastics Inc, “Polyethylene,” Datasheet, Retrieved from <http://www.sdplastics.com/polyeth.html> on Aug. 19, 2009, 7 pages. cited by applicant

Sanders E., et al., “Fibrous Encapsulation of Single Polymer Microfibers Depends on their Vertical Dimension in Subcutaneous Tissue Polymer Microfibers,” *Journal of Biomedical Material Research*, vol. 67A, 2003, pp. 1181-1187. cited by applicant

Mastrototaro J.J., “The MiniMed Continuous Glucose Monitoring System,” *Diabetes Technology & Therapeutics*, vol. 2, Supplement 1, 2000, pp. S13-S18. cited by applicant

Matsuki H., “Energy Transfer System Utilizing Amorphous Wires For Implantable Medical Devices,” *IEEE Transactions on Magnetics*, vol. 31 (2), 1994, pp. 1276-1282. cited by applicant

Matsumoto T., et al., “A long-Term Lifetime Amperometric Glucose Sensor with a Perfluorocarbon

Polymer Coating,” *Biosensors & Bioelectronics*, vol. 16, 2001, pp. 271-276. cited by applicant

Matsumoto T., et al., “A Micro-Planar Amperometric Glucose Sensor Unsusceptible to Interference Species,” *Sensors and Actuators B*, 49, 1998, pp. 68-72. cited by applicant

Matthews D.R., et al., “An Amperometric Needle-Type Glucose Sensor Testing in Rats and Man,” *Diabetic Medicine*, vol. 5, 1988, pp. 248-252. cited by applicant

Mazze R.S., et al., “Characterizing Glucose Exposure for Individuals with Normal Glucose Tolerance Using Continuous Glucose Monitoring and Ambulatory Glucose Profile Analysis,” *Diabetes Technology & Therapeutics*, vol. 10 (3), 2008, pp. 149-159. cited by applicant

Mazzola F., et al., “Video Diabetes: A Teaching Tool for Children with Insulin-Dependent Diabetes,” *IEEE, Proceedings 7th Annual Symposium on Computer Applications in Medical Care*, Oct. 1983, 1 page Abstract. cited by applicant

McCartney L.J., et al., “Near-Infrared Fluorescence Lifetime Assay for Serum Glucose Based on Allophycocyanin-Labeled Concanavalin A,” *Analytical Biochemistry*, vol. 292, 2001, pp. 216-221. cited by applicant

McGrath M.J., et al., “The Use of Differential Measurements with a Glucose Biosensor for Interference Compensation During Glucose Determinations by Flow Injection Analysis,” *Biosens Bioelectron*, vol. 10, 1995, pp. 937-943. cited by applicant

McKean B.D., et al., “A Telemetry Instrumentation System for Chronically Implanted Glucose and Oxygen Sensors,” *IEEE Transactions on Biomedical Engineering*, vol. 35 (7), Jul. 1988, pp. 526-532. cited by applicant

Memoli A., et al., “A Comparison between Different Immobilised Glucoseoxidase-Based Electrodes,” *Journal of Pharmaceutical and Biomedical Analysis*, vol. 29, 2002, pp. 1045-1052. cited by applicant

Merriam Webster Online Dictionary, Definition for “Aberrant,” retrieved from <https://www.merriam-webster.com/dictionary/aberrant> Aug. 19, 2008, 1 page. cited by applicant

Merriam-Webster Online Dictionary, Definition of “Acceleration” retrieved from <http://www.merriam-webster.com/dictionary/Acceleration> Jan. 11, 2010, 1 page. cited by applicant

Merriam-Webster Online Dictionary, Definition of “Nominal” retrieved from <http://www.merriam-webster.com/dictionary/nominal> Apr. 23, 2007, 1 page. cited by applicant

Merriam-Webster Online Dictionary, Definition of “System”. <http://www.merriamwebster.com/dictionary/System> Jan. 11, 2010, 2 pages. cited by applicant

Metzger M., et al., “Reproducibility of Glucose Measurements using the Glucose Sensor,” *Diabetes Care*, vol. 25 (6), Jul. 2002, pp. 1185-1191. cited by applicant

Meyerhoff C., et al., “On Line Continuous Monitoring of Subcutaneous Tissue Glucose in Men by Combining Portable Glucosensor With Microdialysis,” *Diabetologia*, vol. 35 (11), 1992, pp. 1087-1092. cited by applicant

Miller J.A., et al., “Development of an Autotuned Transcutaneous Energy Transfer System,” *ASAIO Journal*, vol. 39, 1993, pp. M706-M710. cited by applicant

Miller K.M., et al., “Generation of IL-1 like Activity in Response to Biomedical Polymer Implants: a Comparison of in Vitro and in Vivo Models,” *Journal of Biomedical Materials Research*, vol. 23(9), 1989, pp. 1007-1026. cited by applicant

Miller K.M., et al., “Human monocyte/macrophage activation and interleukin 1 generation by biomedical polymers,” *Journal of Biomedical Materials Research*, vol. 22 (8), 1988, pp. 713-731. cited by applicant

Miller K.M., et al., “In Vitro Stimulation of Fibroblast Activity by Factors Generated from Human Monocytes Activated by Biomedical Polymers,” *Journal of Biomedical Materials Research*, vol. 23(8), 1989, pp. 911-930. cited by applicant

Moatti-Sirat D., et al., “Evaluating In Vitro and In Vivo the Interference of Ascorbate and Acetaminophen on Glucose Detection by a Needle-Type Glucose Sensor,” *Biosensors and Bioelectronics*, vol. 7, 1992, pp. 345-352. cited by applicant

Moatti-Sirat D., et al., "Reduction of Acetaminophen Interference in Glucose Sensors by a Composite Nafion Membrane: Demonstration in Rats and Man," *Diabetologia*, vol. 37 (6), Jun. 1994, pp. 610-616. cited by applicant

Moatti-Sirat., et al., "Towards Continuous Glucose Monitoring: In Vivo Evaluation of a Miniaturized Glucose Sensor Implanted for Several Days in Rat Subcutaneous Tissue," *Diabetologia*, vol. 35, 1992, pp. 224-230. cited by applicant

Monsod T.P., et al., "Do Sensor Glucose Levels Accurately Predict Plasma Glucose Concentrations During Hypoglycemia and Hyperinsulinemia?," *Diabetes Care*, vol. 25 (5), 2002, pp. 889-893. cited by applicant

Morff R.J., et al., "Microfabrication of Reproducible, Economical, Electroenzymatic Glucose Sensors," *Annual International Conference of the IEEE Engineering in Medicine and Biology Society*, vol. 12 (2), 1990, pp. 0483-0484. cited by applicant

Mosbach K., et al., "Determination of Heat Changes in the Proximity of Immobilized Enzymes with an Enzyme Thermistor and its Use for the Assay of Metabolites," *Biochimica Biophysica Acta*, vol. 403, 1975, pp. 256-265. cited by applicant

Motonaka J., et al., "Determination of Cholesterol and Cholesterol Ester with Novel enzyme Microsensors," *Anal. Chem.*, vol. 65, 1993, pp. 3258-3261. cited by applicant

Moussy F., et al., "A Miniaturized Nafion-Based Glucose Sensor: In Vitro and In Vivo Evaluation in Dogs," *International Journals of Artificial Organs*, vol. 17 (2), 1994, pp. 88-94. cited by applicant

Moussy F., et al., "Biomaterials community examines biosensor biocompatibility," *Diabetes Technology & Therapeutics*, vol. 2(3), 2000, pp. 473-477. cited by applicant

Moussy F., et al., "Performance of Subcutaneously Implanted Needle-Type Glucose Sensors Employing a Novel Trilayer Coating," *Analytical Chemistry*, vol. 65, Aug. 1, 1993, pp. 2072-2077. cited by applicant

Moussy F., "Implantable Glucose Sensor: Progress and Problems," *IEEE*, Nov. 2002, pp. 270-273. cited by applicant

Mowery K.A., et al., "Preparation and Characterization by Hydrophobic Polymeric Films that are Thromboresistant via Nitric Oxide Release," *Biomaterials*, vol. 21, 2000, pp. 9-21. cited by applicant

Murphy S.M., et al., "Polymer Membranes in Clinical Sensor Applications, II. The Design and Fabrication of Permselective Hydrogels for Electrochemical Devices," *Biomaterials*, 1992, vol. 13 (14), pp. 979-990. cited by applicant

Muslu, "Trickling Filter Performance," *Applied Biochemistry and Biotechnology*, vol. 37, 1992, pp. 211-224. cited by applicant

Myler S., et al., "Ultra-Thin-Polysiloxane-Film-Composite Membranes for the Optimisation of Amperometric Oxidase Enzyme Electrodes," *Biosensors & Bioelectronics*, vol. 17, 2002, pp. 35-43. cited by applicant

Nakayama Y., et al., "Surface Fixation of Hydrogels: Heparin and Glucose Oxidase Hydrogelated Surfaces" *ASAIO Journal*, 1992, pp. M421-M424. cited by applicant

Nam Y.S., et al., "A Novel Fabrication Method of Macroporous Biodegradable Polymer Scaffolds Using Gas Foaming Salt as a Porogen Additive," *J Biomed Mater Res*, 2000, vol. 53, pp. 1-7. cited by applicant

Neuburger G.G., et al., "Pulsed Amperometric Detection of Carbohydrates at Gold Electrodes with a Two-Step Potential Waveform," *Anal. Chem.*, vol. 59, 1987, pp. 150-154. cited by applicant

Newsrx, "Glucose Monitoring: FDA OKs New Device to Manage Diabetes," *Medical Letter on the CDC & FDA via NewsRx.com*, Aug. 3, 2003, 1 page. cited by applicant

Nintendo Healthcare, *Wired*, Dec. 1993, 1 page. cited by applicant

Novo Nordisk Pharmaceuticals Inc., "Diabetes Educational Video Game Recognized by Software Publishers Association," *Press Release*, Mar. 14, 1994, 4 pages. cited by applicant

Ohara T.J., et al., "Glucose Electrodes Based on Cross-Linked [Os(bpy)₂Cl](+/2+) Complexed Poly(1-Vinylimidazole) Films," *Analytical Chemistry*, vol. 65, Dec. 1993, pp. 3512-3517. cited by applicant

Ohara T.J., et al., "'Wired' Enzyme Electrodes for Amperometric Determination of Glucose or Lactate in the Presence of Interfering Substances," *Anal Chem*, vol. 66, 1994, pp. 2451-2457. cited by applicant

Okuda, et al., "Mutarotase Effect on Micro Determinations of D-Glucose and its Anomers with β D-Glucose Oxidase," *Anal Biochem*, vol. 43 (1), 1971, pp. 312-315. cited by applicant

Oxford English Dictionary Online, Definition of "Impending," http://www.askoxford.com/results/?view=devdict&field-12668446_Impending&branch Jan. 11, 2010, 1 page. cited by applicant

Palmisano F., et al., "Simultaneous Monitoring of Glucose and Lactate by an Interference and Cross-Talk Free Dual Electrode Amperometric Biosensor Based on Electropolymerized Thin Films," *Biosensors & Bioelectronics*, vol. 15, 2000, pp. 531-539. cited by applicant

Panetti T.S., "Differential Effects of Sphingosine 1-Phosphate and Lysophosphatidic Acid on Endothelial Cells," *Biochimica et Biophysica Acta*, vol. 1582, 2002, pp. 190-196. cited by applicant

Panteleon A.E., et al., "The Role of the Independent Variable to Glucose Sensor Calibration," *Diabetes Technology & Therapeutics*, vol. 5 (3), 2003, pp. 401-410. cited by applicant

Parker R.S., et al., "A Model-Based Algorithm for Blood Glucose Control In Type I Diabetic Patients," *IEEE Trans Biomed Engg (BME)*, vol. 46(2), 1999, pp. 148-157. cited by applicant

Heller A., "Plugging Metal Connectors into Enzymes," *Nature Biotechnology*, vol. 21, No. 6, Jun. 2003, pp. 631-632. cited by applicant

Hicks J.M., "In Situ Monitoring," *Clinical Chemistry*, vol. 31 (12), 1985, pp. 1931-1935. cited by applicant

Hitchman M.L., "Measurement of Dissolved Oxygen," Edited by Elving P.J et al., *Chemical Analysis*, New York, John Wiley & Sons, vol. 49, Chapter 3, 1978, pp. 34-49 and 59-123. cited by applicant

Hoel P.G., "Elementary Statistics," Fourth Edition, John Wiley & Sons, Inc., 1976, pp. 113-114. cited by applicant

Houghton Mifflin Company, "American Heritage Dictionary," 4th Edition, 2000, pp. 82. cited by applicant

Houghton Mifflin Company, "Xenogenic, the American Heritage Stedman's Medical Dictionary," 2002, Answers.Com, retrieved from <http://www.answers.com/topic/xenogenic>, on Nov. 7, 2006, 2 Pages. cited by applicant

Hovorka R., et al., "Closing the Loop: The Adicol Experience," *Diabetes Technology & Therapeutics*, vol. 6 (3), 2004, pp. 307-318. cited by applicant

Hrapovic S., et al., "Picoamperometric Detection of Glucose at Ultrasmall Platinum-Based Biosensors Preparation and Characterization," *Anal. Chem*, vol. 75, 2003, pp. 3308-3315. cited by applicant

Hu Y., et al., "A Needle-Type Enzyme-Based Lactate Sensor for In Vivo Monitoring," *Analytica Chimica Acta*, vol. 281, 1993, pp. 503-511. cited by applicant

Huang C., et al., "Electrochemical Generation of Oxygen. 1: The Effects of Anions and Cations on Hydrogen Chemisorption and Anodic Oxide Film Formation on Platinum Electrode. 2: The Effects of Anions and Cations on Oxygen Generation on Platinum Electrode," U.S. Department of Commerce/NTIS, 1975, 126 pages. cited by applicant

Huang Q., et al., "A 0.5mW Passive Telemetry IC for Biomedical Applications," *Proceedings of the 23rd European Solid-State Circuits Conference (ESSCIRC '97)*, Southampton, UK, Sep. 16-18, 1997, pp. 172-175. cited by applicant

Hunsley B., et al.. "Whole Blood Glucose Standard Is Key to Accurate Insulin Dosages," *Journal*

of Diabetes Science and Technology, vol. 1 (2), Mar. 2007, pp. 173-177. cited by applicant

Hunter I., et al., "Minimally Invasive Glucose Sensor and Insulin Delivery System," MIT Home Automation and Healthcare Consortium, Mar. 31, 2000, Progress Report No. 25, 17 pages. cited by applicant

International Preliminary Report on Patentability for Application No. PCT/US2005/006301, mailed Aug. 30, 2006, 4 pages. cited by applicant

International Preliminary Report on Patentability for Application No. PCT/US2007/080848 mailed Apr. 13, 2010, 6 pages. cited by applicant

International Preliminary Report on Patentability for Application No. PCT/US2008/058158, mailed Sep. 29, 2009, 9 pages. cited by applicant

International Preliminary Report on Patentability for Application No. PCT/US2008/065978 mailed Jun. 19, 2008, 14 pages. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2005/006301, mailed Jun. 22, 2005, 4 pages. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2007/080848 mailed Aug. 28, 2008, 6 pages. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2008/058158, mailed Aug. 8, 2008, 10 pages. cited by applicant

International Search Report and Written opinion for Application No. PCT/US2008/065978 mailed Oct. 2, 2008, 14 pages. cited by applicant

Ishikawa M., et al., "Initial Evaluation of a 290-Mm Diameter Subcutaneous Glucose Sensor: Glucose Monitoring With a Biocompatible, Flexible-Wire, Enzyme-Based Amperometric Microsensor in Diabetic and Nondiabetic Humans," Journal of Diabetes and Its Complications, vol. 12, 1998, pp. 295-301. cited by applicant

Jablecki M., et al., "Simulations of the Frequency Response of Implantable Glucose Sensors," Analytical Chemistry, vol. 72, 2000, 1853-1859. cited by applicant

Jaffari S.A., et al., "Recent Advances in Amperometric Glucose Biosensors for In Vivo Monitoring," Physiological Measurement, 1995, vol. 16, pp. 1-15. cited by applicant

Jaremko J., et al., "Advances Toward the Implantable Artificial Pancreas for Treatment of Diabetes," Diabetes Care, vol. 21 (3), Mar. 1998, pp. 444-450. cited by applicant

Jensen M.B., et al., "Fast Wave Forms for Pulsed Electrochemical Detection of Glucose by Incorporation of Reductive Desorption of Oxidation Products," Analytical Chemistry, vol. 69 (9), May 1997, pp. 1776-1781. cited by applicant

Jeong R.A., et al., "In Vivo Calibration of the Subcutaneous Amperometric Glucose Sensors Using a Non-Enzyme Electrode," Biosensors and Bioelectronics, Elsevier, vol. 19, 2003, pp. 313-319. cited by applicant

Jeutter D.C., "A Transcutaneous Implanted Battery Recharging and Biotelemetry Power Switching System," IEEE Transactions on Biomedical Engineering, vol. BME-29 (5), May 1982, pp. 314-321. cited by applicant

Jeutter D.C., et al., "Design of a Radio-Linked Implantable Cochlear Prosthesis Using Surface Acoustic Wave Devices," IEEE Transactions on Ultrasonics, Ferroelectrics and Frequency Control, vol. 40 (5), Sep. 1993, pp. 469-477. cited by applicant

Jobst G., et al., "Thin-Film Microbiosensors for Glucose-Lactate Monitoring," Anal Chem, Sep. 15, 1996, vol. 68(18), pp. 3173-3179. cited by applicant

Johnson K.W., et al., "In Vivo Evaluation of an Electroenzymatic Glucose Sensor Implanted in Subcutaneous Tissue," Biosensors and Bioelectronics, 1992, vol. 7, pp. 709-714. cited by applicant

Johnson K.W., "Reproducible Electrodeposition of Biomolecules for the Fabrication of Miniature Electroenzymatic Biosensors," Sensors and Actuators B, vol. 5, 1991, pp. 85-89. cited by applicant

Jones S.M., et al., "Optimal Insulin Pump Dosing and Postprandial Glycemia Following a Pizza Meal Using the Continuous Glucose Monitoring System," Diabetes Technology &

Therapeutics, vol. 7 (2), Apr. 2005, pp. 233-240. cited by applicant

Joung G.B., et al., "An Energy Transmission System for an Artificial Heart Using Leakage Inductance Compensation of Transcutaneous Transformer," IEEE Transactions on Power Electronics, vol. 13 (6), Nov. 1998, pp. 1013-1022. cited by applicant

Jovanovic L.M.D., "The Role of Continuous Glucose Monitoring in Gestational Diabetes Mellitus," Diabetes Technology and Therapeutics, vol. 2 (1), 2000, pp. S67-S71. cited by applicant

Kacaniklic V., et al., "Amperometric Biosensors for Detection of L- and D-Amino Acids Based on Coimmobilized Peroxidase and L- and D-Amino Acid Oxidases in Carbon Paste Electrodes," Electroanalysis, vol. 6, May-Jun. 1994, pp. 381-390. cited by applicant

Kamath A., et al., "Calibration of a Continuous Glucose Monitor: Effect of Glucose Rate of Change," Eighth Annual Diabetes Technology Meeting, Nov. 13-15, 2008, pp. A88 (2 pages). cited by applicant

Kang S.K., et al., "In Vitro and Short-Term in Vivo Characteristics of a Kel-F Thin Film Modified Glucose Sensor," Analytical Sciences, vol. 19, Nov. 2003, pp. 1481-1486. cited by applicant

Kaplan S.M., "Wiley Electrical and Electronics Engineering Dictionary," IEEE Press, John Wiley & Sons, Inc., 2004, pp. 141, 142, 548 549. cited by applicant

Kargol M., et al., "Studies on the Structural Properties of Porous Membranes: Measurement of Linear Dimensions of Solutes," Biophysical Chemistry, 2001, vol. 91, pp. 263-271. cited by applicant

Karube I., et al., "Microbiosensors for Acetylcholine and Glucose," Biosensors & Bioelectronics, 1993, vol. 8, pp. 219-228. cited by applicant

Kaufman F.R., et al., "A Pilot Study of the Continuous Glucose Monitoring System," Diabetes Care, vol. 24 (12), Dec. 2001, pp. 2030-2034. cited by applicant

Kaufman F.R., "Role of the Continuous Glucose Monitoring System in Pediatric Patients," Diabetes Technology and Therapeutics, vol. 2 (1), 2000, S49-S52. cited by applicant

Kawagoe J.L., et al., "Enzyme-Modified Organic Conducting Salt Microelectrode," Analytical Chemistry, vol. 63, 1991, pp. 2961-2965. cited by applicant

Keedy F.H., et al., "Determination of Urate in Undiluted Whole Blood by Enzyme Electrode," Biosensors and Bioelectronics, vol. 6, 1991, pp. 491-499. cited by applicant

Kerner, et al., "A Potentially Implantable Enzyme Electrode for Amperometric Measurement of Glucose," Hormone and Metabolic Research Supplement, vol. 20, 1988, pp. 8-13. cited by applicant

Kerner W., et al., "The Function of a Hydrogen Peroxide-Detecting Electroenzymatic Glucose Electrode is Markedly Impaired in Human Sub-Cutaneous Tissue and Plasma," Biosensors and Bioelectronics, vol. 8, 1993, pp. 473-482. cited by applicant

Kerner W., "Implantable Glucose Sensors: Present Status and Future Developments," Experimental and Clinical Endocrinol Diabetes, vol. 109 (2), 2001, pp. S341-S346. cited by applicant

Kiechle F.L., "The Impact of Continuous Glucose Monitoring on Hospital Point-of-Care Testing Programs," Diabetes Technology and Therapeutics, vol. 3 (4), 2001, pp. 647-649. cited by applicant

Kizilel S., et al., "Review: The Bioartificial Pancreas: Progress and Challenges," Diabetes Technology & Therapeutics, vol. 7 (6), 2005, pp. 968-985. cited by applicant

Tang, et al., "Mast Cells Mediate Acute Inflammatory Responses to Implanted Biomaterials," Proceedings of the National Academy of Sciences of the USA, 1998, vol. 95, pp. 8841-8846. cited by applicant

Tang, et al., "Molecular Determinants of Acute Inflammatory Responses to Biomaterials," J Clin Invest, 1996, vol. 97, pp. 1329-1334. cited by applicant

Tatsuma T., et al., "Oxidase/Peroxidase Bilayer-Modified Electrodes as Sensors for Lactate, Pyruvate, Cholesterol and Uric Acid," Analytica Chimica Acta, vol. 242, 1991, pp. 85-89. cited by applicant

Thennadil S.N., et al., "Comparison of Glucose Concentration in Interstitial Fluid, and Capillary and Venous Blood During Rapid Changes in Blood Glucose Levels," *Diabetes Technology & Therapeutics*, vol. 3 (3), 2001, pp. 357-365. cited by applicant

Thijssen, et al., "A Kalman Filter for Calibration, Evaluation of Unknown Samples and Quality Control in Drifting Systems," Part 1, Theory and Simulations, *Analytica chimica Acta*, 1984, vol. 156, pp. 87-101. cited by applicant

Thijssen, et al., "A Kalman Filter for Calibration, Evaluation of Unknown Samples and Quality Control in Drifting Systems," Part 3, Variance Reduction, *Analytica chimica Acta*, 1985, vol. 173, pp. 265-272. cited by applicant

Thijssen, et al., "A Kalman Filter for Calibration, Evaluation of Unknown Samples and Quality Control in Drifting Systems," Part 4, Flow Injection Analysis, *Analytica chimica Acta*, 1985, vol. 174, pp. 27-40. cited by applicant

Thijssen P.C., "A Kalman Filter for Calibration, Evaluation of Unknown Samples and Quality Control in Drifting Systems," Part 2, Optimal Designs, *Analytica chimica Acta*, vol. 162, 1984, pp. 253-262. cited by applicant

Thome V., et al., "(Abstract) Can the Decrease in Subcutaneous Glucose Concentration Precede the Decrease in Blood Glucose Level? Proposition for a Push-Pull Kinetics Hypothesis," *Horm. metab. Res.*, vol. 27, 1995, p. 53. cited by applicant

Thome-Duret V., et al., "Continuous Glucose Monitoring in the Free-Moving Rat," *Metabolism*, vol. 47 (7), Jul. 1998, pp. 799-803. cited by applicant

Thome-Duret V., et al., "Modification of the Sensitivity of Glucose Sensor Implanted into Subcutaneous Tissue," *Diabetes Metabolism*, vol. 22, 1996, pp. 174-178. cited by applicant

Thome-Duret V., et al., "Use of a Subcutaneous Glucose Sensor to Detect Decreases in Glucose Concentration Prior to Observation in Blood," *Analytical Chemistry*, vol. 68 (21), Nov. 1, 1996, pp. 3822-3826. cited by applicant

Thompson M., et al., "In Vivo Probes: Problems and Perspectives," *Clinical Biochemistry*, vol. 19 (5), Oct. 1986, pp. 255-261. cited by applicant

Tibell, et al., "Survival of Macroencapsulated Allogeneic Parathyroid Tissue One Year after Transplantation in Nonimmunosuppressed Humans," *Cell Transplantation*, 2001, vol. 10, pp. 591-599. cited by applicant

Tierney M.J., et al., "Effect of Acetaminophen on the Accuracy of Glucose Measurements Obtained with the GlucoWatch Biographer," *Diabetes Technology & Therapeutics*, vol. 2 (2), 2000, pp. 199-207. cited by applicant

Tierney M.J., et al., "The Gluco Watch® Biographer: A Frequent, Automatic and Noninvasive Glucose Monitor," *Annals of Medicine*, vol. 32, 2000, pp. 632-641. cited by applicant

Tilbury J.B., et al., "Receiver Operating Characteristic Analysis for Intelligent Medical Systems—A New Approach for Finding Confidence Intervals," *IEEE Transactions on Biomedical Engineering*, vol. 47 (7), Jul. 2000, pp. 952-963. cited by applicant

Torjman M.C., et al., "Glucose Monitoring in Acute Care: Technologies on the Horizon," *Journal of Diabetes Science and Technology*, vol. 2 (2), Mar. 2008, pp. 178-181. cited by applicant

Trajanoski Z., et al., "Neural Predictive Controller For Insulin Delivery Using The Subcutaneous Route," *IEEE Transactions on Biomedical Engineering*, vol. 45(9), 1998, pp. 1122-1134. cited by applicant

Trecroci D., "A Glimpse into the Future-Continuous Monitoring of Glucose with a Microfiber," *Diabetes Interview*, Jul. 2002, pp. 42-43. cited by applicant

Tse P.S.H., et al., "Time-Dependent Inactivation of Immobilized Glucose Oxidase and Catalase," *Biotechnology & Bioengineering*, vol. 29, 1987, pp. 705-713. cited by applicant

Turner A.P.F., "Amperometric Biosensor based on Mediator-Modified Electrodes," *Methods in Enzymology*, 1988, vol. 137, pp. 90-103. cited by applicant

Turner A.P.F., et al., "Carbon Monoxide: Acceptor Oxidoreductase from *Pseudomonas*

Thermocarboxydovorans Strain C2 and its Use in a Carbon Monoxide Sensor,” *Analytica Chimica Acta*, vol. 163, 1984, pp. 161-174. cited by applicant

Turner A.P.F., et al., “Diabetes Mellitus: Biosensors for Research and Management,” *Biosensors*, vol. 1, 1985, pp. 85-115. cited by applicant

Unger J., et al., “Glucose Control in the Hospitalized Patient,” *Emergency Medicine*, vol. 36 (9), 2004, pp. 12-18. cited by applicant

Udpike S.J., et al., “A Subcutaneous Glucose Sensor with Improved Longevity, Dynamic Range, and Stability of Calibration,” *Diabetes Care*, vol. 23 (2), Feb. 2000, pp. 208-214. cited by applicant

Udpike S.J., et al., “Continuous Glucose Monitor Based on an Immobilized Enzyme Electrode Detector,” *Journal of Laboratory and Clinical Medicine*, vol. 93(4), 1979, pp. 518-527. cited by applicant

Udpike S.J., et al., “Enzymatic Glucose Sensor: Improved Long-Term Performance in Vitro and In Vivo,” *ASAIO Journal*, vol. 40 (2), Apr.-Jun. 1994, pp. 157-163. cited by applicant

Udpike S.J., et al., “Implanting the Glucose Enzyme Electrode: Problems, Progress, and Alternative Solutions,” *Diabetes Care*, vol. 5 (3), May-Jun. 1982, pp. 207-212. cited by applicant

Udpike S.J., et al., “Laboratory Evaluation of New Reusable Blood Glucose Sensor,” *Diabetes Care*, vol. 11 (10), Nov.-Dec. 1988, pp. 801-807. cited by applicant

Udpike S.J., et al., “Principles of Long-Term Fully Implanted Sensors with Emphasis on Radiotelemetric Monitoring of Blood Glucose Form Inside a Subcutaneous Foreign Body Capsule (FBC),” Edited by Fraser D M, *Biosensors in the Body: Continuous in vivo Monitoring*, John Wiley & Sons Ltd., New York, 1997, Chapter 4, pp. 117-137. cited by applicant

Udpike S.J., et al., “The Enzyme Electrode,” *Nature*, vol. 214, Jun. 3, 1967, pp. 986-988. cited by applicant

Utah Medical Products Inc., “Deltran—Disposable Blood Pressure Transducers,” *Product Specifications*, 2003-2006, 6 pages. cited by applicant

Vadgama P., “Diffusion Limited Enzyme Electrodes,” *NATO ASI Series: Series C, Math and Phys. Sci*, vol. 226, 1988, pp. 359-377. cited by applicant

Vadgama P., “Enzyme Electrodes as Practical Biosensors,” *Journal of Medical Engineering Technology*, vol. 5 (6), Nov. 1981, pp. 293-298. cited by applicant

Valdes T.I., et al., “In Vitro and In Vivo Degradation of Glucose Oxidase Enzyme used for an Implantable Glucose Biosensor,” *Diabetes Technology & Therapeutics*, vol. 2 (3), 2000, pp. 367-376. cited by applicant

Van Den Berghe, “Tight Blood Glucose Control with Insulin in “Real-Life” Intensive Care,” *Mayo Clinic Proceedings*, vol. 79 (8), Aug. 2004, pp. 977-978. cited by applicant

Velho G., et al., “In Vitro and In Vivo Stability of Electrode Potentials in Needle-Type Glucose Sensors,” *Influence of Needle Material*, *Diabetes*, vol. 38, Feb. 1989, pp. 164-171. cited by applicant

Velho G., et al., “Strategies for Calibrating a Subcutaneous Glucose Sensor,” *Biomed Biochim Acta*, vol. 48 (11/12), 1989, pp. 957-964. cited by applicant

Vesper H.W., et al., “Assessment of Trueness of a Glucose Monitor Using Interstitial Fluid and Whole Blood as Specimen Matrix,” *Diabetes Technology & Therapeutics*, vol. 8 (1), 2006, pp. 76-80. cited by applicant

Von Woedtke T., et al., “In Situ Calibration of Implanted Electrochemical Glucose Sensors,” *Biomed. Biochim. Acta* 48 vol. 11/12, 1989, pp. 943-952. cited by applicant

Wade L.G., “Reactions of Aromatic Compounds,” *Organic Chemistry*, Chapter 17, 5th edition, 2003, pp. 762-763. cited by applicant

Wagner, et al., “Continuous Amperometric Monitoring of Glucose in a Brittle Diabetic Chimpanzee with a Miniature Subcutaneous Electrode,” *Proc. Natl. Acad. Sci. USA*, vol. 95, May 1998, pp. 6379-6382. cited by applicant

Wang J., et al., “Highly Selective Membrane-Free Mediator-Free Glucose Biosensor,” *Analytical*

Chemistry, vol. 66 (21), Nov. 1, 1994, pp. 3600-3603. cited by applicant

Wang X., et al., "Improved Ruggedness for Membrane-Based Amperometric Sensors using a Pulsed Amperometric Method," *Analytical Chemistry*, vol. 69 (21), Nov. 1, 1997, pp. 4482-4489. cited by applicant

Ward W.K., et al., "A New Amperometric Glucose Microsensor: In Vitro and Short-Term In Vivo Evaluation," *Biosensors & Bioelectronics*, vol. 17, 2002, pp. 181-189. cited by applicant

Ward W.K., et al., "Assessment of Chronically Subcutaneous Glucose Sensors in Dogs: The Effect of Surrounding Fluid Masses," *ASAIO Journal*, 1999, vol. 45 (6), pp. 555-561. cited by applicant

Ward W.K., et al., "Rise in Background Current Over Time in a Subcutaneous Glucose Sensor in the Rabbit," *Relevance to Calibration and Accuracy, Biosensors & Bioelectronics*, vol. 15, 2000, pp. 53-61. cited by applicant

Ward W.K., et al., "Understanding Spontaneous Output Fluctuations of an Amperometric Glucose Sensor: Effect of Inhalation Anesthesia and Use of a Nonenzyme Containing Electrode," *ASAIO Journal*, 2000, pp. 540-546. cited by applicant

Wentholt I.M.E., et al., "Relationship between Interstitial and Blood Glucose in Type 1 Diabetes Patients: Delay and the Push-pull Phenomenon Revisited," *Diabetes Technology & Therapeutics*, vol. 9 (2), 2007, pp. 169-175. cited by applicant

Aalders, et al., "Development of a Wearable Glucose Sensor; Studies in Healthy Volunteers and in Diabetic Patients," *The International Journal of Artificial Organs*, 1991, vol. 14, No. 2, pp. 102-108. cited by applicant

Abe, et al., "Characterization of Glucose Microsensors for Intracellular Measurements," *Analytical Chemistry*, 1992, vol. 64, No. 18, pp. 2160-2163. cited by applicant

Abel, et al., "Biosensors for in Vivo Glucose Measurements: Can We Cross the Experimental Stage," *Biosensors & Bioelectronics*, 2002, vol. 17, pp. 1059-1070. cited by applicant

Abel, et al., "Experience With an Implantable Glucose Sensor as a Prerequisite of an Artificial Beta Cell," *Biomed. Biochim. Acta*, 1984, vol. 43, No. 5, pp. 577-584. cited by applicant

Adilman, et al., "Videogames: Knowing The Score, Creative Computing," Dec. 1983, *Dialog: File 148; IAC Trade & Industry Database*, vol. 9, p. 224(5) (9 pages). cited by applicant

Alcock S.J., et al., "Continuous Analyte Monitoring to Aid Clinical Practice," *IEEE Engineering in Medicine Biology*, 1994, vol. 13, pp. 319-325. cited by applicant

Amer M.M.B., "An Accurate Amperometric Glucose Sensor Based Glucometer with Eliminated Cross-Sensitivity," *Journal of Medical Engineering & Technology*, vol. 26 (5), Sep./Oct. 2002, pp. 208-213. cited by applicant

American Diabetes Association., "Position Statement: Diagnosis and Classification of Diabetes Mellitus," *Diabetes Care*, vol. 30, Supplement 01, Jan. 2007, pp. S42-S47. cited by applicant

American Diabetes Association., "Position Statement: Standards of Medical Care in Diabetes," *Diabetes Care*, vol. 30, Supplement 01, Jan. 2007, pp. S4-S41. cited by applicant

American Diabetes Association., "Summary of Revisions for the 2007 Clinical Practice Recommendations," *Diabetes Care*, vol. 30, Supplement 01, Jan. 2007, pp. S3. cited by applicant

Amin R., et al., "Hypoglycemia Prevalence in Prepubertal Children With Type 1 Diabetes on Standard Insulin Regimen: Use of Continuous Glucose Monitoring System," *Diabetes Care*, 2003, vol. 26, No. 3, pp. 662-667. cited by applicant

Armour J.C., et al., "Application of Chronic Intravascular Blood Glucose Sensor in Dogs," *Diabetes*, Dec. 1990, vol. 39, pp. 1519-1526. cited by applicant

Asberg P., et al., "Hydrogels of a Conducting Conjugated Polymer as 3-D Enzyme Electrode," *Biosensors Bioelectronics*, 2003, vol. 19, pp. 199-207. cited by applicant

Assolant-Vinet C.H., et al., "New Immobilized Enzyme Membranes for Tailor-Made Biosensors," *Analytical Letters*, 1986, vol. 19(78), pp. 875-885. cited by applicant

Atanasov P., et al., "Biosensor for Continuous Glucose Monitoring," *Biotechnology and Bioengineering*, John Wiley & sons Inc, 1994, vol. 43, pp. 262-266. cited by applicant

Atanasov P., et al., "Implantation of a Refillable Glucose Monitoring-Telemetry Device," *Biosensors and Bioelectronics*, vol. 12 (7), 1997, pp. 669-680. cited by applicant

Aussedat B., et al., "A User-Friendly Method For Calibrating a Subcutaneous Glucose Sensor-Based Hypoglycaemic Alarm," Elsevier Science Limited, *Biosensors & Bioelectronic*, 1997, vol. 12, No. 11, pp. 1061-1071. cited by applicant

Aussedat B., et al., "Interstitial Glucose Concentration and Glycemia: Implications for Continuous Subcutaneous Glucose Monitoring," *American Journal of Physiology—Endocrinology and Metabolism*, vol. 278 (4), Apr. 1, 2000, pp. E716-E728. cited by applicant

Bailey T.S., et al., "Reduction in Hemoglobin A1C with Real-Time Continuous Glucose Monitoring: Results from a 12-Week Observational Study," *Diabetes Technology Therapeutics*, vol. 9 (3), 2007, pp. 203-210. cited by applicant

Baker D.A., et al., "Dynamic Concentration Challenges for Biosensor Characterization," *Biosensors & Bioelectronics*, vol. 8, 1993, pp. 433-441. cited by applicant

Baker D.A., et al., "Dynamic Delay and Maximal Dynamic Error in Continuous Biosensors," *Analytical Chemistry*, vol. 68 (8), Apr. 15, 1996, pp. 1292-1297. cited by applicant

Bard A.J., et al., "Electrochemical Methods," *Fundamentals and Applications*, John Wiley & Sons, New York, 1980, pp. 173-175. cited by applicant

Bardeletti G., et al., "A Reliable L-Lactate Electrode with a New Membrane for Enzyme Immobilization for Amperometric Assay of Lactate," *Analytica Chimica Acta*, vol. 187, 1986, pp. 47-54. cited by applicant

Beach R.D., et al., "Subminiature Implantable Potentiostat and Modified Commercial Telemetry Device for Remote Glucose Monitoring," *IEEE Transactions on Instrumentation and Measurement*, vol. 48 (6), Dec. 1999, pp. 1239-1245. cited by applicant

Bellucci F., et al., "Electrochemical Behaviour of Graphite-Epoxy Composite Materials (GECM) in Aqueous Salt Solutions," *Journal of Applied Electrochemistry*, vol. 16 (1), Jan. 1986, pp. 15-22. cited by applicant

Berger M., et al., "Computer Programs to Assist the Physician in the Analysis of Self-Monitored Blood Glucose Data," *Proceedings of the Annual Symposium on Computer Applications in Medical Care*, 1988, pp. 52-57. cited by applicant

Bertrand C., et al., "Multipurpose Electrode with Different Enzyme Systems Bound to Collagen Films," *Analytica Chimica Acta*, 1981, vol. 126, pp. 23-34. cited by applicant

Bessman S.P., et al., "Progress toward a Glucose Sensor for the Artificial Pancreas," *Proceedings of a Workshop on Ion-Selective Microelectrodes*, Jun. 4-5, 1973, Boston University, 1973, pp. 189-197. cited by applicant

Biermann E., et al., "How Would Patients Behave if they were Continually Informed of their Blood Glucose Levels? A Simulation Study Using a "Virtual" Patient," *Diabetes Technology & Therapeutics*, vol. 10 (3), 2008, pp. 178-187. cited by applicant

Bindra D.S., et al., "Design and in Vitro Studies of a Needle-Type Glucose Sensor for Subcutaneous Monitoring," *Analytical Chemistry*, vol. 63, Sep. 1, 1991, pp. 1692-1696. cited by applicant

Bindra D.S., et al., "Pulsed Amperometric Detection of Glucose in Biological Fluids at a Surface-Modified Gold Electrode," *Analytical Chemistry*, vol. 61 (22), Nov. 15, 1989, pp. 2566-2570. cited by applicant

Bisenberger M., et al., "A Triple-Step Potential Waveform at Enzyme Multisensors with Thick-Film Gold Electrodes for Detection of Glucose and Sucrose," *Sensors and Actuators B*, vol. 28, 1995, pp. 181-189. cited by applicant

Bland J.M., et al., "A Note on the Use of the Intraclass Correlation Coefficient in the Evaluation of Agreement between Two Methods of Measurement," *Computers in Biology and Medicine*, vol. 20 (5), 1990, pp. 337-340. cited by applicant

Bland J.M., et al., "Statistical Methods for Assessing Agreement Between Two Methods of Clinical

Measurement," *The Lancet*, Feb. 8, 1986, pp. 307-310. cited by applicant

Bobbioni-Harsch E., et al., "Lifespan of Subcutaneous Glucose Sensors and their Performances during Dynamic Glycaemia Changes in Rats," *J. Biomed. Eng.*, vol. 15, 1993, pp. 457-463. cited by applicant

Bode B.W., "Clinical Utility of the Continuous Glucose Monitoring System," *Diabetes Technology & Therapeutics*, vol. 2, Supplement 1, 2000, pp. S35-S41. cited by applicant

Bode B.W., et al., "Continuous Glucose Monitoring Used to Adjust Diabetes Therapy Improves Glycosylated Hemoglobin: A Pilot Study," *Diabetes Research and Clinical Practice*, vol. 46, 1999, pp. 183-190. cited by applicant

Bode B.W., et al., "Using the Continuous Glucose Monitoring System to Improve the Management of Type 1 Diabetes," *Diabetes Technology & Therapeutics*, vol. 2, Supplement 1, 2000, pp. S43-S48. cited by applicant

Boedeker Plastics Inc, "Polyethylene Specifications," Polyethylene Data Sheet, Retrieved from <http://www.boedeker.com/polye.sub.--p.htm> on Aug. 19, 2009, 4 pages. cited by applicant

Boland E., et al., "Limitations of Conventional Methods of Self-Monitoring of Blood Glucose," *Diabetes Care*, vol. 24 (11), Nov. 2001, pp. 1858-1862. cited by applicant

Bolinder J., et al., "Self-Monitoring of Blood Glucose in Type I Diabetic Patients: Comparison with Continuous Microdialysis Measurements of Glucose in Subcutaneous Adipose Tissue during Ordinary Life Conditions," *Diabetes Care*, vol. 20 (1), Jan. 1997, pp. 64-70. cited by applicant

Bolinder J., et al., "Microdialysis Measurement of the Absolute Glucose Concentration in Subcutaneous Adipose Tissue Allowing Glucose Monitoring in Diabetic Patients," *Rapid Communication, Diabetologia*, vol. 35, 1992, pp. 1177-1180. cited by applicant

Bott A.W., "A Comparison of Cyclic Voltammetry and Cyclic Staircase Voltammetry," *Current Separations*, vol. 16 (1), 1997, pp. 23-26. cited by applicant

Bott A.W., "Electrochemical Methods for the Determination of Glucose," *Current Separations*, vol. 17 (1), 1998, pp. 25-31. cited by applicant

Bowman L., et al., "The Packaging of Implantable Integrated Sensors," *IEEE Transactions in Biomedical Engineering*, vol. BME-33 (2), Feb. 1986, pp. 248-255. cited by applicant

Brauker, et al., "Sustained Expression of High Levels of Human Factor IX from Human Cells Implanted within an Immunoisolation Device into Athymic Rodents," *Human Gene Therapy*, Apr. 10, 1998, vol. 9, pp. 879-888. cited by applicant

Brauker J., et al., "Local Inflammatory Response Around Diffusion Chambers Containing Xenografts," *Transplantation*, vol. 61 (12), Jun. 27, 1996, pp. 1671-1677. cited by applicant

Brauker J H., et al., "Neovascularization of Synthetic Membranes Directed by Membrane Microarchitecture," *Journal of Biomedical Material Research*, 1995, vol. 29, pp. 1517-1524. cited by applicant

Brauker J., "Unraveling Mysteries at the Biointerface: Molecular Mediator of Inhibition of Blood Vessel Formation in the Foreign Body Capsule Revealed," *SurFACTS in Biomaterials*, vol. 6 (3), 2001, pp. 1,5. cited by applicant

Braunwald E., "Biomarkers in Heart Failure," *Medical Progress, The New England Journal of Medicine*, vol. 358, May 15, 2008, pp. 2148-2159. cited by applicant

Bremer T., et al., "Is Blood Glucose Predictable from Previous Values? A Solicitation for Data," *Perspectives in Diabetes*, vol. 48, Mar. 1999, pp. 445-451. cited by applicant

Bremer T.M., et al., "Benchmark Data from the Literature for Evaluation of New Glucose Sensing Technologies," *Diabetes Technology Therapeutics*, vol. 3 (3), 2001, pp. 409-418. cited by applicant

Brooks S.L., et al., "Development of an On-line Glucose Sensor for Fermentation Monitoring," *Biosensors*, vol. 3, 1987/1988, pp. 45-56. cited by applicant

Bruckel J., et al., "In Vivo Measurement of Subcutaneous Glucose Concentrations with an Enzymatic Glucose Sensor and a Wick Method," *Klin Wochenschr*, vol. 67, 1989, pp. 491-495. cited by applicant

Brunner G.A., et al., "Validation of Home Blood Glucose Meters with Respect to Clinical and Analytical Approaches," *Diabetes Care*, vol. 21, No. 4, Apr. 1998, pp. 585-590. cited by applicant

Brunstein E., et al., "Preparation and Validation of Implantable Electrodes for the Measurement of Oxygen and Glucose," *Biomed Biochim. Acta*, vol. 48 (11/12), 1989, pp. 911-917. cited by applicant

Cai Q., et al., "A Wireless, Remote Query Glucose Biosensor Based on a pH-Sensitive Polymer," *Analytical Chemistry*, vol. 76 (14), Jul. 15, 2004, pp. 4038-4043. cited by applicant

Cameron T., et al., "Micromodular Implants to Provide Electrical Stimulation of Paralyzed Muscles and Limbs," *IEEE Transactions on Biomedical Engineering*, vol. 44 (9), Sep. 1997, pp. 781-790. cited by applicant

Campanella L., et al., "Biosensor for Direct Determination of Glucose and Lactate in Undiluted Biological Fluids," *Biosensors & Bioelectronics*, vol. 8, 1993, pp. 307-314. cited by applicant

Candas B., et al., "An Adaptive Plasma Glucose Controller Based on a Nonlinear Insulin/Glucose Model," *IEEE Transactions on Biomedical Engineering*, vol. 41 (2), Feb. 1994, pp. 116-124. cited by applicant

Cass A.E.G., et al., "Ferrocene-Mediated Enzyme Electrodes for Amperometric Determination of Glucose," *Analytical Chemistry*, vol. 56 (4), Apr. 1984, pp. 667-671. cited by applicant

Cassidy J.F., et al., "Novel Electrochemical Device for the Detection of Cholesterol or Glucose," *Analyst*, vol. 118, Apr. 1993, pp. 415-418. cited by applicant

Chase H.P., et al., "Continuous Subcutaneous Glucose Monitoring in Children with Type 1 Diabetes," *Pediatrics*, vol. 107 (2), Feb. 2001, pp. 222-226. cited by applicant

Chase J.G., et al., "Targeted Glycemic Reduction in Critical Care Using Closed-Loop Control," *Diabetes Technology & Therapeutics*, vol. 7 (2), 2005, pp. 274-282. cited by applicant

Chen C., et al., "A Noninterference Polypyrrole Glucose Biosensor," *Biosensors and Bioelectronics*, vol. 22, 2006, pp. 639-643. cited by applicant

Chen T., et al., "Defining the Period of Recovery of the Glucose Concentration after its Local Perturbation by the Implantation of a Miniature Sensor," *Clinical Chemistry and Laboratory Medicine*, vol. 40 (8), 2002, pp. 786-789. cited by applicant

Chia C.W., et al., "Glucose Sensors: Toward Closed Loop Insulin Delivery," *Endocrinology and Metabolism Clinics of North America*, vol. 33, 2004, pp. 175-195. cited by applicant

Choleau C., et al., "Calibration of a Subcutaneous Amperometric Glucose Sensor Implanted for 7 Days in Diabetic Patients Part 2. Superiority of the One-point Calibration Method," *Biosensors and Bioelectronics*, vol. 17 (8), 2002, pp. 647-654. cited by applicant

Choleau C., et al., "Calibration of a Subcutaneous Amperometric Glucose Sensor Part 1. Effect of Measurement Uncertainties on the Determination of Sensor Sensitivity and Background Current," *Biosensors and Bioelectronics*, vol. 17, 2002, pp. 641-646. cited by applicant

Ciba Specialty Chemicals, "Ciba® IRGACURE® 2959," Coating Effects Segment, Photoinitiator Product Description, Basel Switzerland, Apr. 2, 1998, 3 pages. cited by applicant

Claremont D.J., et al., "Potentially-Implantable, Ferrocene-Mediated Glucose Sensor," *Journal of Biomedical Engineering*, vol. 8, Jul. 1986, pp. 272-274. cited by applicant

Claremont D.J., et al., "Subcutaneous Implantation of a Ferrocene-Mediated Glucose Sensor in Pigs," *Diabetologia*, vol. 29, 1986, pp. 817-821. cited by applicant

Clark L.C., et al., "Configurational Cyclic Voltammetry: Increasing the Specificity and Reliability of Implanted Electrodes," *IEEE/Ninth Annual Conference of the Engineering in Medicine and Biology Society*, 1987, pp. 0782-0783. cited by applicant

Clark L.C., et al., "Long-Term Stability of Electroenzymatic Glucose Sensors Implanted in Mice," vol. XXXIV, *Transactions—American Society for Artificial Internal Organs*, 1988, vol. 34, pp. 259-265. cited by applicant

Clark L.C., et al., "One-Minute Electrochemical Enzymic Assay for Cholesterol in Biological Materials," *Clinical Chemistry*, vol. 27 (12), 1981, pp. 1978-1982. cited by applicant

Clarke W.L., et al., "Evaluating Clinical Accuracy of Systems for Self Monitoring of Blood Glucose," Technical Articles, Diabetes Care, vol. 10 (5), Sep.-Oct. 1987, pp. 622-628. cited by applicant

Colangelo V.J., et al., "Corrosion Rate Measurements in Vivo," Journal of Biomedical Materials Research, vol. 1, 1967, pp. 405-414. cited by applicant

Colowick S.P., et al., "Methods in Enzymology," vol. XLIV, Immobilized Enzymes, Edited by Mosbach K, New York Academic Press, 1976, 11 pages. cited by applicant

Coulet P.R., et al., "Enzymes Immobilized on Collagen Membranes: A Tool for Fundamental Research and Enzyme Engineering," Journal of Chromatography, vol. 215, 1981, pp. 65-72. cited by applicant

Coulet P.R., "Polymeric Membranes and Coupled Enzymes in the Design of Biosensors," Journal of Membrane Science, 1992, vol. 68, pp. 217-228. cited by applicant

Cox D.J., et al., "Accuracy of Perceiving Blood Glucose in IDDM," Diabetes Care, vol. 8 (6), Nov.-Dec. 1985, pp. 529-536. cited by applicant

Csoregi E., et al., "Amperometric Microbiosensors for Detection of Hydrogen Peroxide and Glucose Based on Peroxidase-Modified Carbon Fibers," Electroanalysis, vol. 6, 1994, pp. 925-933. cited by applicant

Csoregi E., et al., "Design, Characterization and One-Point in Vivo Calibration of a Subcutaneously Implanted Glucose Electrode," American Chemical Society, Analytical Chemistry, vol. 66 (19), Oct. 1, 1994, pp. 3131-3138. cited by applicant

Currie J.F., et al., "Novel Non-Intrusive Trans-Dermal Remote Wireless Micro-Fluidic Monitoring System Applied to Continuous Glucose and Lactate Assays for Casualty Care and Combat Readiness Assessment," RTO HFM Symposium, RTO-MP-HFM-109, Aug. 16-18, 2004, pp. 24-1-24-18. cited by applicant

Dai W.S., et al., "Hydrogel Membranes with Mesh Size Asymmetry based on the Gradient Crosslinking of Poly(Vinyl Alcohol)," Journal of Membrane Science, 1999, vol. 156, pp. 67-79. cited by applicant

Danielsson B., et al., "Enzyme Thermistors," Methods in Enzymology, vol. 137, 1988, pp. 181-197. cited by applicant

D'Arrigo G., et al., "Porous-Si Based Bio Reactors for Glucose Monitoring and Drugs Production," Proceedings of SPIE, 2003, vol. 4982, pp. 178-184. cited by applicant

Dassau E., et al., "In Silico Evaluation Platform for Artificial Pancreatic β -Cell Development—A Dynamic Simulator for Closed-Loop Control with Hardware-in-the-loop," Diabetes Technology & Therapeutics, vol. 11 (3), 2009, pp. 1-8. cited by applicant

Davies M.L., et al., "Polymer Membranes in Clinical Sensor Applications," An overview of membrane function, Biomaterials, vol. 13 (14), 1992, pp. 971-978. cited by applicant

Davis G., et al., "Bioelectrochemical Fuel Cell and Sensor Based on a Quinoprotein, Alcohol Dehydrogenase," Enzyme and Microbial Technology, vol. 5 (5), Sep. 1983, pp. 383-388. cited by applicant

De Vos P., et al., "Considerations for Successful Transplantation of Encapsulated Pancreatic Islets," Diabetologia, vol. 45, 2002, pp. 159-173. cited by applicant

Deutsch T., et al., "Time Series Analysis and Control of Blood Glucose Levels in Diabetic Patients," Computer Methods and Programs in Biomedicine, Elsevier Scientific Publishers, vol. 41, 1994, pp. 167-182. cited by applicant

Dixon B.M., et al., "Characterization in Vitro and in Vivo of the Oxygen Dependence of an Enzyme/Polymer Biosensor for Monitoring Brain Glucose," Journal of Neuroscience Methods, vol. 119, 2002, pp. 135-142. cited by applicant

DuPont, "Dimension® AR Clinical Chemistry System," The Chemistry Analyzer that Makes the most of your Time, Money and Effort, Dade International, Chemistry Systems, Newark, 1998, 18 pages. cited by applicant

Durliat H., et al., "Spectrophotometric and Electrochemical Determinations of L(+)-Lactate in Blood by Use of Lactate Dehydrogenase from Yeast," *Clinical Chemistry*, vol. 22 (11), 1976, pp. 1802-1805. cited by applicant

Edwards Lifesciences, "Accuracy for You and Your Patients," Marketing materials, 2002, 4 pages. cited by applicant

El Degheidy M.M., et al., "Optimization of an Implantable Coated Wire Glucose Sensor," *Journal of Biomedical Engineering*, vol. 8, Apr. 1986, pp. 121-129. cited by applicant

ELCO Diagnostics Company, "Direct 30/30® Blood Glucose Sensor," Markwell Medical Catalog, 1990, 1 page. cited by applicant

El-Khatib F.H., et al., "Adaptive Closed-Loop Control Provides Blood-Glucose Regulation Using Dual Subcutaneous Insulin and Glucagon Infusion in Diabetic Swine," *Journal of Diabetes Science and Technology*, Diabetes Technology Society, vol. 1 (2), 2007, pp. 181-192. cited by applicant

El-Sa'ad L., et al., "Moisture Absorption by Epoxy Resins: The Reverse Thermal Effect," *Journal of Materials Science*, vol. 25, 1990, pp. 3577-3582. cited by applicant

Sansen W., et al., "A Smart Sensor for the Voltammetric Measurement of Oxygen or Glucose Concentrations," *Sensors and Actuators B1*, 1990, pp. 298-302. cited by applicant

Sansen W., et al., "Glucose Sensor with Telemetry System," In *Implantable Sensors for Closed Loop Prosthetic Systems* edited by Ko W.H, Chapter 12, 1985, pp. 167-175. cited by applicant

Schaffar B.P.H., "Thick Film Biosensors for Metabolites in Undiluted Whole Blood and Plasma Samples," *Analytical Bioanalytical Chemistry*, Dec. 2001, vol. 372, pp. 254-260. cited by applicant

Schmidt F.J., et al., "Calibration of a Wearable Glucose Sensor," *The International Journal of Artificial Organs*, Wichtig Publishing, IT, vol. 15 (1), Jan. 1, 1992, pp. 55-61. cited by applicant

Schmidt F.J., et al., "Glucose Concentration in Subcutaneous Extracellular Space," *Diabetes Care*, vol. 16 (5), May 1993, pp. 695-700. cited by applicant

Schmidtke D.W., et al., "Accuracy of the One-Point in Vivo Calibration of "Wired" Glucose Oxidase Electrodes Implanted in Jugular Veins of Rats in Periods of Rapid Rise and Decline of the Glucose Concentration," *Analytical Chemistry*, vol. 70 (10), May 15, 1998, pp. 2149-2155. cited by applicant

Schmidtke D.W., et al., "Measurement and Modeling of the Transient Difference Between Blood and Subcutaneous Glucose Concentrations in the Rat After Injection of Insulin," *Proceedings of the National Academy of Sciences*, vol. 95, Jan. 1998, pp. 294-299. cited by applicant

Schoemaker M., et al., "The SCGMI System: Subcutaneous Continuous Glucose Monitoring Based on Microdialysis Technique," *Diabetes Technology & Therapeutics*, vol. 5 (4), 2003, pp. 599-608. cited by applicant

Schoonen A.J.M., et al., "Development of a Potentially Wearable Glucose Sensor for Patients with Diabetes Mellitus: Design and In-vitro Evaluation," *Biosensors & Bioelectronics*, vol. 5, 1990, pp. 37-46. cited by applicant

Schuler, et al., "Modified Gas-Permeable Silicone Rubber Membranes for Covalent Immobilisation of Enzymes and their Use in Biosensor Development," *Analyst*, 1999, vol. 124, pp. 1181-1184. cited by applicant

Selam J.L., "Management of Diabetes with Glucose Sensors and Implantable Insulin Pumps," *From the Dream of the 60s to the Realities of the 90s*, *ASAIO Journal* 1997, vol. 43, pp. 137-142. cited by applicant

Service F.J., et al., "Mean Amplitude of Glycemic Excursions, A Measure of Diabetic Instability," *Diabetes*, vol. 19 (9), Sep. 1970, pp. 644-655. cited by applicant

Service F.J., et al., "Measurements of Glucose Control," *Diabetes Care*, vol. 10 (2), Mar.-Apr. 1987, pp. 225-237. cited by applicant

Service R.F., "Can Sensors Make a Home in the Body?," *Science, Materials Science: Soft Surface*, vol. 297, Aug. 9, 2002, pp. 962-963. cited by applicant

Sharkawy A.A., et al., "Engineering the Tissue Which Encapsulates Subcutaneous Implants. I.

Diffusion Properties,” *Journal of Biomedical Materials Research*, vol. 37, 1996, pp. 401-412. cited by applicant

Shaw G.W., et al., “In Vitro Testing of a Simply Constructed, Highly Stable Glucose Sensor Suitable for Implantation in Diabetic Patients,” *Biosensors & Bioelectronics*, vol. 6, 1991, pp. 401-406. cited by applicant

Shichiri M., et al., “Glycaemic Control in Pancreatectomized Dogs with a Wearable Artificial Endocrine Pancreas,” *Diabetologia*, vol. 24, 1983, pp. 179-184. cited by applicant

Shichiri M., et al., “Membrane Design for Extending the Long-Life of an Implantable Glucose Sensor,” *Diabetes Nutrition & Metabolism*, vol. 2 (4), 1989, pp. 309-313. cited by applicant

Shichiri M., et al., “Needle Type Glucose Sensor for Wearable Artificial Endocrine Pancreas,” In *Implantable Sensors for Closed-Loop Prosthetic Systems* edited by Ko W.H, Chapter 15, 1985, pp. 197-210. cited by applicant

Shichiri M., et al., “Telemetry Glucose Monitoring Device with Needle-Type Glucose Sensor: A Useful Tool for Blood Glucose Monitoring in Diabetic Individuals,” *Diabetes Care*, vol. 9 (3), May-Jun. 1986, pp. 298-301. cited by applicant

Shichiri M., et al., “Wearable Artificial Endocrine Pancreas with Needle-Type Glucose Sensor,” Preliminary Communication, *Lancet*, vol. 2, Nov. 20, 1982, pp. 1129-1131. cited by applicant

Shults M.C., et al., “A Telemetry-Instrumentation System for Monitoring Multiple Subcutaneously Implanted Glucose Sensors,” *IEEE Transactions on Biomedical Engineering*, vol. 41 (10), Oct. 1994, pp. 937-942. cited by applicant

Sieminski, et al., “Biomaterial-Microvasculature Interactions,” *Biomaterials*, 2000, vol. 21, pp. 2233-2241. cited by applicant

Sigma-Aldrich Corp., “Cellulose Acetate,” Product Description, Product No. 419028, St. Louis, MO, 2005, 1 page. cited by applicant

Sigma-Aldrich Corp. “Nafion® 117 Solution Product Description, Product No. 70160,” retrieved from <https://www.sigmaaldrich.com/cgi-bin/hsrun/Suite7/Suite/HAHTpage/Suite.HsExternalProd> on Apr. 7, 2005, 1 page. cited by applicant

Skyler J.S., “The Economic Burden of Diabetes and the Benefits of Improved Glycemic Control: The Potential Role of a Continuous Glucose Monitoring System,” *Diabetes Technology & Therapeutics*, vol. 2, Supplement 1, 2000, pp. S7-S12. cited by applicant

Slater-Maclean L., et al., “Accuracy of Glycemic Measurements in the Critically Ill,” *Diabetes Technology and Therapeutics*, vol. 10 (3), 2008, pp. 169-177. cited by applicant

Smith B., et al., “An Externally Powered, Multichannel, Implantable Stimulator-Telemeter for Control of Paralyzed Muscle,” *IEEE Transactions on Biomedical Engineering*, vol. 45 (4), Apr. 1998, pp. 463-475. cited by applicant

Smith, et al., “A Comparison of Islet Transplantation and Subcutaneous Insulin Injections for the Treatment of Diabetes Mellitus,” *Computers in Biology and Medicine*, 1991, vol. 21 (6), pp. 417-427. cited by applicant

Sokol L., et al., “Immobilized-Enzyme Rate-Determination Method for Glucose Analysis,” *Clinical Chemistry*, vol. 26 (1), 1980, pp. 89-92. cited by applicant

Sokolov S., et al., “Metrological Opportunities of the Dynamic Mode of Operating an Enzyme Amperometric Biosensor,” *Medical Engineering & Physics*, vol. 17 (6), 1995, pp. 471-476. cited by applicant

Sparacino G., et al., “Continuous Glucose Monitoring Time Series and Hypo-Hyperglycemia Prevention: Requirements, Methods, Open Problems,” *Current Diabetes Reviews*, vol. 4 (3), 2008, pp. 181-192. cited by applicant

Sproule B.A., et al., “Fuzzy Pharmacology: Theory and Applications,” *Trends in Pharmacological Sciences*, vol. 23 (9), Sep. 2002, pp. 412-417. cited by applicant

Sriyudthsak M., et al., “Enzyme-Epoxy Membrane Based Glucose Analyzing System and Medical Applications,” *Biosensors & Bioelectronics*, vol. 11 (8), 1996, pp. 735-742. cited by applicant

Steil G.M., et al., "Determination of Plasma Glucose During Rapid Glucose Excursions with a Subcutaneous Glucose Sensor," *Diabetes Technology & Therapeutics*, vol. 5 (1), 2003, pp. 27-31. cited by applicant

Stern M., et al., "Electrochemical Polarization: I. A Theoretical Analysis of the Shape of Polarization Curves," *Journal of the Electrochemical Society*, vol. 104 (1), Jan. 1957, pp. 56-63. cited by applicant

Sternberg, et al., "Covalent Enzyme Coupling on Cellulose Acetate Membranes for Glucose Sensor Development," *Anal Chem*, Dec. 1988, vol. 60(24), pp. 2781-2786. cited by applicant

Sternberg F., et al., "Does Fall in Tissue Glucose Precede Fall in Blood Glucose?," *Diabetologia*, vol. 39, 1996, pp. 609-612. cited by applicant

Sternberg R., et al., "Study and Development of Multilayer Needle-type Enzyme Based Glucose Microsensors," *Biosensors*, Mar. 20, 1988, vol. 4 (1), pp. 27-40. cited by applicant

Stokes, "Polyether Polyurethanes: Biostable or Not," *Journal of Biomaterials Applications*, Oct. 1988, vol. 3, pp. 228-259. cited by applicant

Street, et al., "Islet Graft Assessment in the Edmonton Protocol: Implications for Predicting Long-Term Clinical Outcome," *Diabetes*, 2004, vol. 53, pp. 3107-3114. cited by applicant

Street J.O., et al., "A Note on Computing Robust Regression Estimates via Iteratively Reweighted Least Squares," *The American Statistician*, vol. 42 (2), May 1988, pp. 152-154. cited by applicant

Suh, et al., "Behavior of Fibroblasts on a Porous Hyaluronic Acid Incorporated Collagen Matrix," *Yonsei Medical Journal*, 2002, vol. 43 (2), pp. 193-202. cited by applicant

Sumino T., et al., "Preliminary Study of Continuous Glucose Monitoring with a Microdialysis Technique," *Proceedings of the 20th Annual International Conference of the IEEE Engineering in Medicine and Biology Society*, vol. 20 (4), 1998, pp. 1775-1778. cited by applicant

Takatsu I., et al., "Solid State Biosensors Using Thin-Film Electrodes," *Sensors and Actuators*, 1987, vol. 11, pp. 309-317. cited by applicant

Takegami S., et al., "Pervaporation of Ethanol/Water Mixtures Using Novel Hydrophobic Membranes Containing Polydimethylsiloxane," *Journal of Membrane Science*, vol. 75, 1992, pp. 93-105. cited by applicant

Tamura T., et al., "Preliminary Study of Continuous Glucose Monitoring with a Microdialysis Technique and a Null Method—A Numerical Analysis," *Frontiers of Medical Biological Engineering*, vol. 10 (2), 2000, pp. 147-156. cited by applicant

Tanenberg R.J., et al., "Continuous Glucose Monitoring System: A New Approach to the Diagnosis of Diabetic Gastroparesis," *Diabetes Technology Therapeutics*, vol. 2, Supplement 1, 2000, pp. S73-S80. cited by applicant

Tang, et al., "Fibrin(ogen) Mediates Acute Inflammatory Responses to Biomaterials," *J.Exp.Med*, 1993, vol. 178, pp. 2147-2156. cited by applicant

Tang, et al., "Inflammatory Responses to Biomaterials," *Am J Clin Pathol*, 1995, vol. 103, pp. 466-471. cited by applicant

Wientjes K.J.C., "Development of a Glucose Sensor for Diabetic Patients," (Ph.D. Thesis), 2000, 212 pages. cited by applicant

Wikipedia., "Intravenous Therapy," http://en.wikipedia.org/wiki/Intravenous_therapy, Aug. 15, 2006, 6 pages. cited by applicant

Wilkins E., et al., "Glucose Monitoring: State of the Art and Future Possibilities," *Med. Eng. Phys.*, vol. 18 (4), 1996, pp. 273-288. cited by applicant

Wilkins E., et al., "Integrated Implantable Device for Long-Term Glucose Monitoring," *Biosensors & Bioelectronics*, vol. 10, 1995, pp. 485-494. cited by applicant

Wilkins E.S., et al., "The Coated Wire Electrode Glucose Sensor," *Horm Metab Res Suppl.*, vol. 20, 1988, pp. 50-55. cited by applicant

Wilson G.S., et al., "Enzyme-Based Biosensors for In Vivo Measurements," *Chem. Rev.*, vol. 100, 2000, pp. 2693-2704. cited by applicant

Wilson G.S., et al., "Progress Toward the Development of an Implantable Sensor for Glucose," *Clinical Chemistry*, vol. 38 (9), 1992, pp. 1613-1617. cited by applicant

Wolpert H., "Establishing a Continuous Glucose Monitoring Program," *Journal of Diabetes Science and Technology*, Mar. 2008, vol. 2 (2), pp. 307-310. cited by applicant

Wolpert H.A., "Commentary: A Clinician's Perspective on Some of the Challenges in Closed Loop," *Diabetes Technology & Therapeutics*, vol. 5 (5), 2003, pp. 843-846. cited by applicant

Wood W D., et al., "Hermetic Sealing with Epoxy," *Pave Technology—Mechanical Engineering*, Mar. 1990, 3 pages. cited by applicant

Woodward S.C., "How Fibroblasts and Giant Cells Encapsulate Implants: Considerations in Design of Glucose Sensors," *Diabetes Care*, vol. 5 (3) May-Jun. 1982, pp. 278-281. cited by applicant

Worsley G.J et al., "Measurement of Glucose in Blood with a Phenylboronic Acid Optical Sensor," *Journal of Diabetes Science and Technology*, vol. 2 (2), Mar. 2008, pp. 213-220. cited by applicant

Wright M., et al., "Bioelectrochemical Dehalogenations via Direct Electrochemistry of Poly(ethylene oxide)-Modified Myoglobin," *Electrochemistry Communications*, vol. 1, 1999, pp. 609-613. cited by applicant

Wu H., et al., "In Situ Electrochemical Oxygen Generation with an Immunoisolation Device," *Annals New York Academy of Sciences*, vol. 875, 1999, pp. 105-125. cited by applicant

Yamasaki Y., et al., "Direct Measurement of Whole Blood Glucose by a Needle-Type Sensor," *Clinica Chimica Acta*. 93, 1989, pp. 93-98. cited by applicant

Yamasaki Y., "The Development of a Needle-Type Glucose Sensor for Wearable Artificial Endocrine Pancreas," *Medical Journal of Osaka University*, vol. 35 (1-2), Sep. 1984, pp. 25-34. cited by applicant

Yang C., et al., "A Comparison of Physical Properties and Fuel Cell Performance of Nafion and Zirconium Phosphate/Nafion Composite Membranes," *Journal of Membrane Science*, vol. 237, 2004, pp. 145-161. cited by applicant

Yang Q., et al., "Development of Needle-Type Glucose Sensor with High Selectivity," *Science and Actuators B*, vol. 46, 1998, pp. 249-256. cited by applicant

Yang S., et al., "A Glucose Biosensor Based on an Oxygen Electrode: In-Vitro Performances in a Model Buffer Solution and in Blood Plasma," *Biomedical Instrumentation & Technology*, vol. 30 (1), 1996, pp. 55-61. cited by applicant

Yang S., et al., "Glucose Biosensors with Enzyme Entrapped in Polymer Coating," *Biomedical Instrument and Technology*, Mar./Apr. 1995, vol. 29 (2), pp. 125-133. cited by applicant

Ye L., et al., "High Current Density Wired Quinoprotein Glucose Dehydrogenase Electrode," *Analytical Chemistry*, vol. 65, 1993, pp. 238-241. cited by applicant

Zamzow K.L., et al., "Development and Evaluation of a Wearable Blood Glucose Monitor," *ASAIO Transactions*, vol. 36 (3), 1990, pp. M588-M591. cited by applicant

Zavalkoff S.R., et al., "Evaluation of Conventional Blood Glucose Monitoring as an Indicator of Integrated Glucose Values Using a Continuous Subcutaneous Sensor," *Diabetes Care*, vol. 25(9), 2002, pp. 1603-1606. cited by applicant

Zethelius B., et al., "Use of Multiple Biomarkers to Improve the Prediction of Death From Cardiovascular Causes," *N. Engl. J. Med.*, vol. 358, May 2008, pp. 2107-2116. cited by applicant

Zhang, et al., "Elimination of the Acetaminophen Interference in an Implantable Glucose Sensor," *Analytical Chemistry*, 1994, vol. 66 (7), pp. 1183-1188. cited by applicant

Zhang Y., et al., "Electrochemical Oxidation of H₂O₂ on Pt and Pt + Ir Electrodes in Physiological Buffer and its Applicability to H₂O₂-Based Biosensors," *J. Electro Analytical Chemistry*, vol. 345, 1993, pp. 253-271. cited by applicant

Zhang Y., et al., "In Vitro and In Vivo Evaluation of Oxygen Effects on a Glucose Oxidase Based Implantable Glucose Sensor," *Analytica Chimica Acta*, vol. 281, 1993, pp. 513-520. cited by applicant

Zhu, et al., "Fabrication and Characterization of Glucose Sensors Based on a Microarray H₂O₂

Electrode,” Biosensors & Bioelectronics, 1994, vol. 9, pp. 295-300. cited by applicant
Zhu, et al., “Planar Amperometric Glucose Sensor Based on Glucose Oxidase Immobilized by Chitosan Film on Prussian blue Layer,” Sensors, 2002, vol. 2, pp. 127-136. cited by applicant
Ziaie, et al., “A Single-Channel Implantable Microstimulator for Functional Neuromuscular Stimulation,” IEEE Transactions on Biomedical Engineering, 1997, vol. 44(10), pp. 909-920. cited by applicant
Machine Translation of EP1144028B1, 2004, 32 Pages. cited by applicant

Primary Examiner: Mendez; Manuel A

Attorney, Agent or Firm: Kaplan Breyer Schwarz LLP

Background/Summary

INCORPORATION BY REFERENCE TO RELATED APPLICATIONS (1) Any and all priority claims identified in the Application Data Sheet, or any correction thereto, are hereby incorporated by reference under 37 CFR 1.57. This application is a continuation of U.S. application Ser. No. 17/074,490, filed Oct. 19, 2020, which is a continuation of U.S. application Ser. No. 16/867,476, filed May 5, 2020, which is a continuation of U.S. application Ser. No. 15/792,038, filed Oct. 24, 2017, now U.S. Pat. No. 10,653,835, which is a continuation of U.S. application Ser. No. 15/362,571, filed Nov. 28, 2016, now U.S. Pat. No. 9,827,372, which is a continuation of U.S. application Ser. No. 14/063,811, filed Oct. 25, 2013, now U.S. Pat. No. 9,597,453, which is a continuation of U.S. application Ser. No. 13/885,604, filed on Sep. 11, 2013, now U.S. Pat. No. 9,452,258, which is the national phase under 35 U.S.C. § 371 of prior PCT International Application No. PCT/US2007/080848 filed on Oct. 9, 2007. Each of the aforementioned applications is incorporated by reference herein in its entirety, and each is hereby expressly made a part of this specification.

FIELD OF THE INVENTION

(1) The present invention relates generally to systems and methods monitoring glucose in a host. More particularly, the present invention relates to an integrated medicament delivery device and continuous glucose sensor.

BACKGROUND OF THE INVENTION

(2) Diabetes mellitus is a disorder in which the pancreas cannot create sufficient insulin (Type I or insulin dependent) and/or in which insulin is not effective (Type 2 or non-insulin dependent). In the diabetic state, the victim suffers from high glucose, which may cause an array of physiological derangements (for example, kidney failure, skin ulcers, or bleeding into the vitreous of the eye) associated with the deterioration of small blood vessels. A hypoglycemic reaction (low glucose) may be induced by an inadvertent overdose of insulin, or after a normal dose of insulin or glucose-lowering agent accompanied by extraordinary exercise or insufficient food intake.

(3) Conventionally, a diabetic person carries a self-monitoring blood glucose (SMBG) monitor, which typically comprises uncomfortable finger pricking methods. Due to the lack of comfort and convenience, a diabetic generally measures his glucose level only two to four times per day. Unfortunately, these time intervals are spread so far apart that the diabetic will likely find out too late that he has entered a hyper- or hypo-glycemic condition, sometimes incurring dangerous side effects. In fact, it is not only unlikely that a diabetic will take a timely SMBG value, but he will not know if his blood glucose is going up (higher) or down (lower), which inhibits his ability to make educated insulin therapy decisions.

(4) Home diabetes therapy requires personal discipline of the user, appropriate education from a

doctor, proactive behavior under sometimes-adverse situations, patient calculations to determine appropriate therapy decisions, including types and amounts of administration of insulin and glucose into his or her system, and is subject to human error. Technologies are needed that ease the burdens faced by diabetic patients, simplify the processes involved in treating the disease, and minimize user error which may cause unnecessarily dangerous situations in some circumstances.

SUMMARY OF THE INVENTION

(5) In a first aspect, an integrated system for monitoring a glucose concentration in a host and for delivering insulin to a host is provided, the system comprising a continuous glucose sensor, wherein the continuous glucose sensor is configured to substantially continuously measure a glucose concentration in a host, and to provide sensor data associated with the glucose concentration in the host; an electronics module comprising an on/off controller module configured to iteratively determine an insulin therapy instruction in response to an evaluation of a relationship of internally derived data and a glucose boundary, wherein the insulin therapy instruction comprises an instruction selected from the group consisting of on and off; and an insulin delivery device configured to deliver insulin to the host, wherein the insulin delivery device is at least one of physically connected to a receiver and operably connected to a receiver, wherein the insulin delivery device is configured to receive the insulin therapy instruction from the controller.

(6) In an embodiment of the first aspect, the insulin therapy instruction is determined solely on internally derived data and the glucose boundary.

(7) In an embodiment of the first aspect, the glucose boundary is programmable by at least one of the host, a caretaker of the host, the on/off controller module, and a manufacturer of the integrated system.

(8) In an embodiment of the first aspect, the glucose boundary is a glucose concentration of from about 70 mg/dl to about 160 mg/dl.

(9) In an embodiment of the first aspect, an on insulin therapy instruction is determined when the glucose concentration exceeds the glucose boundary.

(10) In an embodiment of the first aspect, the insulin delivery device is configured to deliver insulin automatically in response to selection of the on insulin therapy instruction.

(11) In an embodiment of the first aspect, the insulin is flash insulin.

(12) In an embodiment of the first aspect, the insulin delivery device is further configured to deliver insulin at a programmable delivery rate, wherein the delivery rate is programmable by at least one of the host, a caretaker of the host, the on/off controller module, and a manufacturer of the system.

(13) In an embodiment of the first aspect, the insulin delivery device is further configured to deliver insulin at a programmed delivery rate and wherein the on/off controller module is configured to iteratively determine the insulin therapy instruction in response to internally derived data and the glucose boundary, wherein the on/off controller module comprises programming configured to adjust an insulin delivery rate in response to internally derived data and the glucose boundary.

(14) In an embodiment of the first aspect, the on/off controller module is further configured to iteratively determine the insulin therapy instruction in response to a host's metabolic response to an insulin therapy, wherein the on/off controller module comprises programming configured to adjust an insulin delivery rate in response to the host's metabolic response.

(15) In an embodiment of the first aspect, the off insulin therapy instruction is selected when the glucose concentration falls below the glucose boundary.

(16) In an embodiment of the first aspect, the insulin delivery device is configured to automatically terminate insulin delivery in response to selection of the off insulin therapy instruction.

(17) In an embodiment of the first aspect, the insulin delivery device is configured to provide delivery device data associated with insulin delivery.

(18) In an embodiment of the first aspect, the internally derived data comprises at least one of

sensor data, processed sensor data, delivery device data, and processed delivery device data.

(19) The integrated system of Claim **14**, wherein the internally derived data further comprises at least one of a glucose concentration, a glucose concentration range, a change in glucose concentration, a glucose concentration rate of change, an acceleration of a glucose concentration rate of change, a host insulin sensitivity, a change in host insulin sensitivity, a host metabolic response to insulin therapy, an amount of insulin delivered, a time of insulin delivery, an insulin on board, and a time.

(20) In an embodiment of the first aspect, the integrated system further comprises an auxiliary sensor configured to provide auxiliary sensor data associated with at least one measurement made by the auxiliary sensor in the host, wherein the internally derived data further comprises auxiliary sensor data.

(21) In an embodiment of the first aspect, the auxiliary sensor comprises at least one of an accelerometer, a pressure sensor, a pH sensor, a temperature sensor, an oxygen sensor, an auxiliary glucose sensor, an analyte sensor configured to measure an analyte other than glucose, a proximity sensor, and an orientation sensor.

(22) In a second aspect, an integrated system for monitoring a glucose concentration in a host and for delivering insulin to a host is provided, the system comprising a continuous glucose sensor, wherein the continuous glucose sensor is configured to substantially continuously measure a glucose concentration in a host, and to provide sensor data associated with a glucose concentration of the host; an electronics module comprising a basal controller module configured to iteratively determine an insulin therapy instruction in response to an evaluation of a relationship of internally derived data and a basal profile, wherein the basal profile comprises at least one time block associated with a maximum insulin delivery rate; and an insulin delivery device configured to deliver insulin to the host, wherein the insulin delivery device is at least one of physically connected to a receiver and operably connected to a receiver, wherein the insulin delivery device is configured to receive the insulin therapy instruction from the controller module, wherein the insulin therapy instruction is constrained by a maximum insulin delivery rate associated with a current time block.

(23) In an embodiment of the second aspect, the insulin therapy instruction is determined solely on internally derived data and the basal profile.

(24) In an embodiment of the second aspect, the maximum insulin delivery rate is an insulin delivery rate of from about 0.01 U/hour to about 6.0 U/hour.

(25) In an embodiment of the second aspect, the insulin delivery device is configured to deliver insulin automatically in response to receiving the insulin therapy instruction.

(26) In an embodiment of the second aspect, the insulin therapy instruction instructs delivery of insulin at less than the maximum insulin delivery rate associated with the current time block.

(27) In an embodiment of the second aspect, the basal profile is programmable by at least one of the host and a caretaker of the host.

(28) In an embodiment of the second aspect, the basal profile is programmable by at least one of the basal controller module and a manufacturer of the integrated system.

(29) In an embodiment of the second aspect, the basal controller module is configured to iteratively determine the insulin therapy instruction in response to internally derived data and the basal profile, wherein the basal controller module comprises programming to adjust the basal profile in response to internally derived data.

(30) In an embodiment of the second aspect, the basal controller module is further configured to iteratively determine the insulin therapy instruction in response to a host's metabolic response to an insulin therapy, wherein the basal controller module comprises programming to adjust the basal profile in response to the host's metabolic response.

(31) In an embodiment of the second aspect, the insulin delivery device is configured to provide delivery device data associated with insulin delivery.

(32) In an embodiment of the second aspect, the internally derived data comprises at least one of sensor data, processed sensor data, delivery device data, and processed delivery device data.

(33) In an embodiment of the second aspect, the internally derived data further comprises at least one of a glucose concentration, a glucose concentration range, a change in glucose concentration, a glucose concentration rate of change, an acceleration of the glucose concentration rate of change, a host insulin sensitivity, a change in host insulin sensitivity, a host metabolic response to insulin therapy, an amount of insulin delivered, a time of insulin delivery, an insulin on board, and a time.

(34) In an embodiment of the second aspect, the integrated system further comprises an auxiliary sensor configured to provide auxiliary sensor data associated with at least one measurement made by the auxiliary sensor in the host, wherein the internally derived data further comprises auxiliary sensor data.

(35) In an embodiment of the second aspect, the auxiliary sensor comprises at least one of an accelerometer, a pressure sensor, a pH sensor, a temperature sensor, an oxygen sensor, an auxiliary glucose sensor, an analyte sensor configured to measure an analyte other than glucose, a proximity sensor, and an orientation sensor.

(36) In a third embodiment, an integrated system for monitoring a glucose concentration in a host and for delivering insulin to a host is provided, the system comprising a continuous glucose sensor, wherein the continuous glucose sensor is configured to substantially continuously measure a glucose concentration in a host, and to provide sensor data associated with the glucose concentration of the host; an electronics module comprising a bolus controller module configured to iteratively determine an insulin therapy instruction in response to an evaluation of a relationship of internally derived data and an engageable bolus constraint, wherein a relationship of internally derived data to the bolus constraint is evaluated in response to engagement of the bolus constraint, and wherein the bolus constraint comprises a maximum total insulin dose that can be delivered within a predefined time period in response to engagement of the bolus constraint; and an insulin delivery device configured to deliver insulin to the host, wherein the insulin delivery device is at least one of physically connected to a receiver and operably connected to a receiver, wherein the insulin delivery device is configured to receive the insulin therapy from the controller module.

(37) In an embodiment of the third aspect, the insulin therapy instruction is determined solely on internally derived data and the bolus constraint.

(38) In an embodiment of the third aspect, the system further comprises at least one of a selectable button configured to allow a user to engage the engageable bolus constraint, a scroll wheel configured to allow a user to engage the engageable bolus constraint, and a menu selection configured to allow a user to engage the engageable bolus constraint.

(39) In an embodiment of the third aspect, the insulin therapy instruction comprises an instruction to deliver a portion of the maximum total insulin dose.

(40) In an embodiment of the third aspect, the insulin delivery device is configured to deliver insulin automatically in response to receiving the insulin therapy instruction.

(41) In an embodiment of the third aspect, the bolus constraint is programmable by at least one of the host and a caretaker of the host.

(42) In an embodiment of the third aspect, the bolus constraint is programmable by at least one of the bolus controller module and a manufacturer of the integrated system.

(43) In an embodiment of the third aspect, the bolus controller module is configured to iteratively determine an insulin therapy instruction in response to internally derived data and an engaged bolus constraint, wherein the bolus controller module comprises programming to adjust the bolus constraint in response to internally derived data.

(44) In an embodiment of the third aspect, the bolus controller module is further configured to calculate insulin therapy in response to a host's metabolic response to an insulin therapy, wherein the controller module comprises programming to adjust the bolus constraint in response to the host's metabolic response.

- (45) In an embodiment of the third aspect, the insulin delivery device is configured to provide delivery device data associated with insulin delivery.
- (46) In an embodiment of the third aspect, the internally derived data comprises at least one of sensor data, processed sensor data, delivery device data and processed delivery device data.
- (47) In an embodiment of the third aspect, the internally derived data further comprises at least one of a glucose concentration, a glucose concentration range, a change in glucose concentration, a glucose concentration rate of change, an acceleration of the glucose concentration rate of change, a host insulin sensitivity, a change in host insulin sensitivity, a host metabolic response to insulin therapy, an amount of insulin delivered, a time of insulin delivery, an insulin on board, and a time.
- (48) In an embodiment of the third aspect, the integrated system further comprises an auxiliary sensor configured to provide auxiliary sensor data associated with at least one measurement taken by the auxiliary sensor in the host, wherein the internally derived data further comprises auxiliary sensor data.
- (49) In an embodiment of the third aspect, the auxiliary sensor comprises at least one of an accelerometer, a pressure sensor, a pH sensor, a temperature sensor, an oxygen sensor, an auxiliary glucose sensor, an analyte sensor configured to measure an analyte other than glucose, a proximity sensor, and an orientation sensor.
-

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a block diagram of an integrated system of the preferred embodiments, including a continuous glucose sensor, a receiver for processing and displaying sensor data, a medicament delivery device, and an optional single point glucose-monitoring device.
- (2) FIG. 2A is a perspective view of a continuous glucose sensor in one embodiment.
- (3) FIG. 2B is a perspective view of an in vivo portion of a transcutaneous continuous glucose sensor in one embodiment.
- (4) FIG. 2C is a cross-section of the portion of a transcutaneous continuous glucose sensor, of FIG. 2B, taken along line 2C-2C, in one embodiment.
- (5) FIG. 3 is a block diagram of the electronics associated with a continuous glucose sensor in one embodiment.
- (6) FIG. 4 is a graph comparing the time-activity profiles of some exemplary flash insulins (FI-1, FI2, FI3) to the time-activity profile of Humulin R, as taken from Frohnauer, et al. 2001, in "Graphical Human Insulin Time-Activity Profiles Using Standardized Definitions," *Diab. Tech. & Therap.* 3(3):419-429.
- (7) FIGS. 5A and 5B are perspective views of an integrated system **10** in one embodiment, wherein a receiver is integrated with a medicament delivery device in the form of a manual syringe, and optionally includes a single point glucose monitor.
- (8) FIGS. 6A to 6C are perspective views of an integrated system in one embodiment, wherein a receiver is integrated with a medicament delivery device in the form of one or more transdermal patches housed within a holder, and optionally includes a single point glucose monitor.
- (9) FIGS. 7A and 7B are perspective views of an integrated system in one embodiment, wherein a receiver is integrated with a medicament delivery device in the form of a pen or jet-type injector, and optionally includes a single point glucose monitor.
- (10) FIGS. 8A to 8C are perspective views of an integrated system in one embodiment, wherein a sensor and delivery pump, which are implanted or transdermally inserted into the patient, are operably connected to an integrated receiver, and optionally include a single point glucose monitor.
- (11) FIG. 9 is a block diagram that illustrates integrated system electronics in one embodiment.
- (12) FIG. 10 is a flow chart that illustrates the process of validating therapy instructions prior to

medicament delivery in one embodiment.

(13) FIG. 11 is a flow chart that illustrates the process of providing adaptive metabolic control using an integrated sensor and medicament delivery device in one embodiment.

(14) FIG. 12 is a flow chart that illustrates the process of glucose signal estimation using the integrated sensor and medicament delivery device in one embodiment.

(15) FIG. 13 is a flow chart that illustrates the process of determining medicament delivery in one embodiment.

(16) FIG. 14 is a flow chart that illustrates the process of calculating a medicament therapy based on internally derived data in one embodiment.

(17) FIG. 15 is a flow chart that illustrates the process of calculating a medicament therapy based on internally derived data, using an on/off controller module, in one embodiment.

(18) FIG. 16 is a flow chart that illustrates the process of calculating a medicament therapy based on internally derived data, using a dynamic basal controller module, in one embodiment.

(19) FIG. 17 is a flow chart that illustrates the process of calculating a medicament therapy based on internally derived data, using a dynamic bolus module, in one embodiment.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

(20) The following description and examples illustrate some exemplary embodiments of the disclosed invention in detail. Those of skill in the art will recognize that there are numerous variations and modifications of this invention that are encompassed by its scope. Accordingly, the description of a certain exemplary embodiment should not be deemed to limit the scope of the present invention.

Definitions

(21) In order to facilitate an understanding of the disclosed invention, a number of terms are defined below.

(22) The term “continuous glucose sensor,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to a device that continuously or continually measures the glucose concentration of a bodily fluid (e.g., blood, plasma, interstitial fluid and the like), for example, at time intervals ranging from fractions of a second up to, for example, 1, 2, or 5 minutes, or longer. It should be understood that continual or continuous glucose sensors can continually measure glucose concentration without requiring user initiation and/or interaction for each measurement, such as described with reference to U.S. Pat. No. 6,001,067, for example.

(23) The phrase “continuous glucose sensing,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to the period in which monitoring of the glucose concentration of a host's bodily fluid (e.g., blood, serum, plasma, extracellular fluid, etc.) is continuously or continually performed, for example, at time intervals ranging from fractions of a second up to, for example, 1, 2, or 5 minutes, or longer. In one exemplary embodiment, the glucose concentration of a host's extracellular fluid is measured every 1, 2, 5, 10, 20, 30, 40, 50 or 60-seconds.

(24) The term “biological sample,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to sample of a host body, for example, blood, interstitial fluid, spinal fluid, saliva, urine, tears, sweat, or the like.

(25) The term “host,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to mammals such as humans.

(26) The term “biointerface membrane,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a

special or customized meaning), and refers without limitation to a permeable or semi-permeable membrane that can include two or more domains and is typically constructed of materials of a few microns thickness or more, which can be placed over the sensing region to keep host cells (for example, macrophages) from gaining proximity to, and thereby damaging the sensing membrane or forming a barrier cell layer and interfering with the transport of glucose across the tissue-device interface.

(27) The term “sensing membrane,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to a permeable or semi-permeable membrane that can be comprised of two or more domains and is typically constructed of materials of a few microns thickness or more, which are permeable to oxygen and are optionally permeable to glucose. In one example, the sensing membrane comprises an immobilized glucose oxidase enzyme, which enables an electrochemical reaction to occur to measure a concentration of glucose.

(28) The term “domain,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to regions of a membrane that can be layers, uniform or non-uniform gradients (for example, anisotropic), functional aspects of a material, or provided as portions of the membrane.

(29) As used herein, the term “copolymer,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to polymers having two or more different repeat units and includes copolymers, terpolymers, tetrapolymers, etc.

(30) The term “sensing region,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to the region of a monitoring device (e.g., an analyte sensor) responsible for the detection of a particular analyte, such as but not limited to glucose. In one embodiment, the sensing region generally comprises a non-conductive body, a working electrode (anode), a reference electrode and a counter electrode (cathode) passing through and secured within the body forming an electrochemically reactive surface at one location on the body and an electronic connection at another location on the body, and a sensing membrane affixed to the body and covering the electrochemically reactive surface. The counter electrode typically has a greater electrochemically reactive surface area than the working electrode. During general operation of the sensor a biological sample (for example, blood or interstitial fluid) or a portion thereof contacts (for example, directly or after passage through one or more domains of the sensing membrane) an enzyme (for example, glucose oxidase, GOx); the reaction of the biological sample (or portion thereof) results in the formation of reaction products that allow a determination of the glucose level in the biological sample. In one exemplary embodiment, the sensing region includes at least one working electrode and a second electrode, which can function as a reference and/or counter electrode. In another exemplary embodiment, the sensing region includes a plurality of working electrodes, a counter electrode and a reference electrode.

(31) The term “electrochemically reactive surface,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to the surface of an electrode where an electrochemical reaction takes place. In the case of the working electrode, the hydrogen peroxide produced by the enzyme catalyzed reaction of the glucose being detected reacts creating a measurable electronic current (for example, detection of glucose utilizing glucose oxidase produces H_2O_2 as a by product, H_2O_2 reacts with the surface of the working electrode producing two protons (2H^+), two electrons ($2e^-$) and one molecule of oxygen (O_2) which produces the electronic current being detected). In the case of the counter electrode, a reducible species (for example, O_2) is reduced at the electrode surface in order to

balance the current being generated by the working electrode.

(32) The term “electrochemical cell,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to a device in which chemical energy is converted to electrical energy. Such a cell typically consists of two or more electrodes held apart from each other and in contact with an electrolyte solution. Connection of the electrodes to a source of direct electric current renders one of them negatively charged and the other positively charged. Positive ions in the electrolyte migrate to the negative electrode (cathode) and there combine with one or more electrons, losing part or all of their charge and becoming new ions having lower charge or neutral atoms or molecules; at the same time, negative ions migrate to the positive electrode (anode) and transfer one or more electrons to it, also becoming new ions or neutral particles. The overall effect of the two processes is the transfer of electrons from the negative ions to the positive ions, a chemical reaction.

(33) The term “proximal” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to near to a point of reference such as an origin or a point of attachment. For example, in some embodiments of a sensing membrane that covers an electrochemically reactive surface, the electrolyte domain is located more proximal to the electrochemically reactive surface than the interference domain.

(34) The term “distal” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to spaced relatively far from a point of reference, such as an origin or a point of attachment. For example, in some embodiments of a sensing membrane that covers an electrochemically reactive surface, a resistance domain is located more distal to the electrochemically reactive surfaces than the enzyme domain.

(35) The term “substantially” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to being largely but not necessarily wholly that which is specified, which may include an amount greater than 50 percent, an amount greater than 60 percent, an amount greater than 70 percent, an amount greater than 80 percent, an amount greater than 90 percent or more.

(36) The terms “processor” and “processor module,” as used herein are a broad terms, and are to be given their ordinary and customary meaning to a person of ordinary skill in the art (and are not to be limited to a special or customized meaning), and refer without limitation to a computer system, state machine, processor, or the like designed to perform arithmetic or logic operations using logic circuitry that responds to and processes the basic instructions that drive a computer. In some embodiments, the terms can include ROM and/or RAM associated therewith.

(37) The term “ROM,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to read-only memory, which is a type of data storage device manufactured with fixed contents. ROM is broad enough to include EEPROM, for example, which is electrically erasable programmable read-only memory (ROM).

(38) The term “RAM,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to a data storage device for which the order of access to different locations does not affect the speed of access. RAM is broad enough to include SRAM, for example, which is static random access memory that retains data bits in its memory as long as power is being supplied.

(39) The term “A/D Converter,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or

customized meaning), and refers without limitation to hardware and/or software that converts analog electrical signals into corresponding digital signals.

(40) The term “RF module,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to a radio frequency transmitter and/or receiver for transmitting and/or receiving signals.

(41) The terms “raw data stream” and “data stream,” as used herein are broad terms, and are to be given their ordinary and customary meaning to a person of ordinary skill in the art (and are not to be limited to a special or customized meaning), and refer without limitation to an analog or digital signal directly related to the analyte concentration measured by the analyte sensor. In one example, the raw data stream is digital data in “counts” converted by an A/D converter from an analog signal (for example, voltage or amps) representative of an analyte concentration. The terms broadly encompass a plurality of time spaced data points from a substantially continuous analyte sensor, which comprises individual measurements taken at time intervals ranging from fractions of a second up to, for example, 1, 2, or 5 minutes or longer.

(42) The term “counts,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to a unit of measurement of a digital signal. In one example, a raw data stream measured in counts is directly related to a voltage (for example, converted by an A/D converter), which is directly related to current from a working electrode.

(43) The term “electronic circuitry,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to the components (for example, hardware and/or software) of a device configured to process data. In the case of an analyte sensor, the data includes biological information obtained by a sensor regarding the concentration of the analyte in a biological fluid. U.S. Pat. Nos. 4,757,022, 5,497,772 and 4,787,398, which are hereby incorporated by reference in their entirety, describe suitable electronic circuits that can be utilized with devices of certain embodiments.

(44) The term “potentiostat,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to an electrical system that controls the potential between the working and reference electrodes of a three-electrode cell at a preset value. The potentiostat forces whatever current is necessary to flow between the working and counter electrodes to keep the desired potential, as long as the needed cell voltage and current do not exceed the compliance limits of the potentiostat.

(45) The terms “operably connected” and “operably linked,” as used herein are broad terms, and are to be given their ordinary and customary meaning to a person of ordinary skill in the art (and are not to be limited to a special or customized meaning), and refer without limitation to one or more components being linked to another component(s) in a manner that allows transmission of signals between the components. For example, one or more electrodes can be used to detect the amount of glucose in a sample and convert that information into a signal; the signal can then be transmitted to an electronic circuit. In this case, the electrode is “operably linked” to the electronic circuit. These terms are broad enough to include wired and wireless connectivity.

(46) The term “algorithmically smoothed,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to modification of a set of data to make it smoother and more continuous and remove or diminish outlying points, for example, by performing a moving average of the raw data stream.

(47) The term “algorithm,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or

customized meaning), and refers without limitation to the computational processes (for example, programs) involved in transforming information from one state to another, for example using computer processing.

(48) The term “regression,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to finding a line in which a set of data has a minimal measurement (for example, deviation) from that line. Regression can be linear, non-linear, first order, second order, and so forth. One example of regression is least squares regression.

(49) The terms “recursive filter” and “auto-regressive algorithm,” as used herein are broad terms, and are to be given their ordinary and customary meaning to a person of ordinary skill in the art (and are not to be limited to a special or customized meaning), and refer without limitation to an equation in which previous averages are part of the next filtered output. More particularly, the generation of a series of observations whereby the value of each observation is partly dependent on the values of those that have immediately preceded it. One example is a regression structure in which lagged response values assume the role of the independent variables.

(50) The terms “velocity” and “rate of change,” as used herein are broad terms, and are to be given their ordinary and customary meaning to a person of ordinary skill in the art (and are not to be limited to a special or customized meaning), and refer without limitation to time rate of change; the amount of change divided by the time required for the change. In one embodiment, these terms refer to the rate of increase or decrease in an analyte for a certain time period.

(51) The term “acceleration” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to the rate of change of velocity with respect to time. This term is broad enough to include deceleration.

(52) The term “clinical risk,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to an identified danger or potential risk to the health of a host based on a measured or estimated analyte concentration, its rate of change, and/or its acceleration.

(53) The term “clinically acceptable,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to an analyte concentration, rate of change, and/or acceleration associated with that measured analyte that is considered to be safe for a host.

(54) The term “time period,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to an amount of time including a single point in time and a path (for example, range of time) that extends from a first point in time to a second point in time.

(55) The term “measured analyte values,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to an analyte value or set of analyte values for a time period for which analyte data has been measured by an analyte sensor. The term is broad enough to include data from the analyte sensor before or after data processing in the sensor and/or receiver (for example, data smoothing, calibration, or the like).

(56) The term “alarm,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to audible, visual, or tactile signal that are triggered in response to detection of clinical risk to a host. In one embodiment, hyperglycemic and hypoglycemic alarms are triggered when present or future clinical danger is assessed based on continuous analyte data.

(57) The term “computer,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to a machine that can be programmed to manipulate data.

(58) The term “modem,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to an electronic device for converting between serial data from a computer and an audio signal suitable for transmission over a telecommunications connection to another modem.

(59) The term “intelligent,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to systems and methods programmed to be able to adjust to changes in the current conditions and make deductions from information being processed.

(60) The term “adaptive,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to an ability (e.g., systems and methods able to) to be adjusted for use in different conditions; to change something to suit different conditions. In some embodiments, an adaptive controller module can be configured to adjust the medicament delivery rate, the medicament volume, the time of delivery, and the like, based on evaluation of internally derived data and the host metabolic response to therapy.

(61) The term “condition,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to a mode or state of being; the physical status of the body as a whole or of one of its parts. For example, a host's condition can refer to his state of health, his metabolic state and the like.

(62) The term “glucose boundary,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to a glucose concentration or range of glucose concentrations. In some embodiments, the system is configured to compare and/or evaluate internally derived data with a glucose boundary. In some embodiments, a glucose boundary can include a maximum glucose concentration.

(63) The term “on/off controller module,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to a mechanism configured to select between two instructions, namely either “on” or “off.” An on/off controller module can include a device, such as a switch, programming or a combination thereof, that can actuate and/or de-actuate an insulin delivery device, such that the device is either delivering insulin or not delivering insulin. In some embodiments, the on instruction is sent to the insulin delivery device, which is configured to deliver the insulin, such as to automatically deliver the insulin; similarly, the off instruction can be sent to the insulin delivery device, which terminates insulin delivery upon receipt of the off instruction.

(64) The term “basal,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to the minimum required rate or other value for something to function. For example, in the case of insulin therapy, the term “basal rate” can refer to a regular (e.g., in accordance with fixed order or procedure, such as regularly scheduled for/at a fixed time), periodic or continuous delivery of low levels of insulin, such as but not limited to throughout a 24-hour period.

(65) The term “basal profile,” as used herein is a broad term, and is to be given its ordinary and

customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to an insulin delivery schedule that includes one or more blocks of time (e.g., time blocks), wherein each block is associated with a maximum insulin delivery rate.

(66) The term “dynamic basal controller module,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to a controller module configured to intelligently and adaptively evaluate internally derived data relative to a basal profile and to determine a basal insulin therapy (e.g., an insulin delivery rate) based thereon, wherein the insulin therapy can include a delivery rate of up to the maximum delivery rate associated with a time block of the basal profile.

(67) The term “bolus,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to a single dose of insulin, usually given over a short, defined period of time, that has been calculated and/or estimated to be sufficient to cover an expected rise in blood glucose, such as the rise that generally occurs during/after a meal.

(68) The term “bolus constraint,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to an engageable (e.g., selectable) maximum total insulin therapy (e.g., maximum total dose) that can be delivered during a defined period of time. In some embodiments, the bolus constraint has been calculated/estimated to be sufficient to cover an expected rise in glucose, such as an average glucose increase associated with consumption of a meal. In some embodiments, the host, a caretaker of the host, and/or the manufacturer can program a bolus constraint. In some circumstances, a bolus constraint can be programmed by an intelligent/adaptive controller module.

(69) The term “dynamic bolus controller module,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to a controller module configured to intelligently and adaptively evaluate internally derived data against (e.g., relative to) an engaged bolus constraint and to calculate an therapy based thereon, wherein the calculations are constrained by the engaged bolus constraint. A dynamic bolus controller module can include one or more instructions for calculation and/or delivery of a dynamic basal insulin therapy, such as but not limited to instructions to the insulin delivery device to deliver the bolus therapy automatically.

(70) The term “range,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to a sequence, series, or scale between limits (e.g., maximum and minimum values). For example, a range of glucose concentrations can include glucose concentrations from 60 mg/dl to 200 mg/dl. In another example, a range of insulin delivery rates can include rates from about 0.01 U/hr to about 40 U/hr. In some embodiments, a range is a single value.

(71) The terms “programmed” and “programmable,” as used herein are broad terms, and are to be given their ordinary and customary meaning to a person of ordinary skill in the art (and are not to be limited to a special or customized meaning), and refer without limitation to being or able to be arranged, as in a series of steps and/or instructions to be carried out, such as by a computer. As used herein, the terms programmed and programmable includes “pre-programmed,” “pre-programmable,” “re-programmed” and “re-programmable.” In one example, a constraint can be programmed prior to use and/or reprogrammed at a later time.

(72) The term “internally derived data,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to data measured and/or processed by

the integrated system, or a component thereof. Internally derived data can include data from a system component, such as but not limited to an analyte sensor (e.g., continuous glucose sensor), an auxiliary sensor, and/or an insulin delivery device. Internally derived data can include data derived (e.g., by processing and/or algorithmic evaluation) from the data received from a system component, such as but not limited to processed data, evaluated raw and/or processed data, host insulin sensitivity, host metabolic response, relationship of insulin sensitivity and/or metabolic response to each other, time, activity level, tracking of internally derived data to establish trends, insulin delivered and/or on-board, and the like. In some circumstances, internally derived data can include older and/or new data, such as but not limited to data received in the past (e.g., minutes, hours, days, weeks or months) and/or recently received data (e.g., currently received, instant, such as but not limited to within the previous 1-15 minutes). In some embodiments, a controller module can evaluate the internally derived data as it is received.

(73) The term “insulin therapy,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to an amount and/or schedule of the insulin to be delivered to the host. An insulin therapy can include one or more doses of insulin, up to the maximum (e.g., dose, therapy) associated with a constraint, such as but not limited to a basal profile and/or a bolus constraint. In some circumstances, the insulin therapy calculated and/or delivered can include a one or more partial doses that sum to an amount less than or equal to the maximum (e.g., dose, therapy) associated with a constraint. In some circumstances, the user can override the insulin therapy calculated by a controller module and/or associated with a constraint, such as, for example, to command the integrated system to deliver a manually entered insulin therapy.

(74) The term “target range,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to a range of glucose concentrations within which a host is to try to maintain his blood sugar. In general, a target range is a range of glucose concentrations considered to be euglycemic. Euglycemic glucose concentrations are discussed in detail in the section entitled “Programming and Processing.”

(75) The term “meal,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to an amount of food or beverage consumed by the host. In some circumstances, a meal is associated with a time of day, during which that meal is generally consumed, such as but not limited to breakfast, lunch, dinner, supper, snack, and the like. In some circumstances, a meal is associated with a particular type of food or beverage, such as one that a host consumes only occasionally, such as but not limited to a high fat meal (e.g., pizza) or a high carbohydrate meal (e.g., cake, cookies, candy, ice cream, and the like).

(76) The term “auxiliary sensor,” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to a sensor other than the continuous glucose sensor, which is configured to sense glucose or an analyte other than glucose, or to sense a condition, such as but not limited to temperature, pH, host activity level, orientation, pressure, proximity and the like.

Overview

(77) FIG. 1 is a block diagram of an integrated system **10** of the preferred embodiments, including a continuous glucose sensor **12**, a receiver **14** for processing and displaying sensor data, a medicament delivery device **16**, and optionally a single point glucose-monitoring device **18**. The integrated diabetes management system **10** of the preferred embodiments provides improved convenience and accuracy thus affording a diabetic host **8** with improved convenience, functionality, and safety in the care of their disease.

(78) FIG. 1 shows a continuous glucose sensor **12** that measures a concentration of glucose or a substance indicative of the concentration or presence of the glucose. In some embodiments, the glucose sensor **12** is an invasive, minimally invasive, or non-invasive device, for example a subcutaneous, transdermal, intravascular or extracorporeal device. In some embodiments, the sensor **12** can analyze a plurality of intermittent biological samples. The glucose sensor can use any method of glucose-measurement, including enzymatic, chemical, physical, electrochemical, spectrophotometric, polarimetric, calorimetric, radiometric, or the like. In alternative embodiments, the sensor **12** can be any sensor capable of determining the level of an analyte in the body, for example oxygen, lactase, insulin, hormones, cholesterol, medicaments, viruses, or the like. The glucose sensor **12** uses any known method to provide an output signal indicative of the concentration of the glucose. The output signal is typically a raw data stream that is used to provide a useful value of the measured glucose concentration to a host or doctor, for example.

(79) Accordingly, a receiver **14** is provided that receives and processes the raw data stream, including calibrating, validating, and displaying meaningful glucose values to a host, such as described in more detail below. A medicament delivery device **16** is further provided as a part of the integrated system **10**. In some embodiments, the medicament delivery device **16** is a manual delivery device, for example a syringe, inhaler, or transdermal patch, which is manually integrated with the receiver **14**. In some embodiments, the medicament delivery device **16** is a semi-automated delivery device, for example a pen or jet-type injector, an inhaler, a spray, or pump, which provides a semi-automated integration with the receiver **14**. In some embodiments, the medicament delivery device **16** is an automated delivery device, for example a transcutaneous or implantable pump system, which provides an automated integration with the receiver **14**. In some embodiments, an optional single point glucose monitor **18** is further provided as a part of the integrated system **10**, for example a self-monitoring blood glucose meter (SMBG), non-invasive glucose meter, or the like.

(80) Conventionally, each of these devices separately provides valuable information and or services to diabetic hosts. Thus, a typical diabetic host has numerous individual devices, which they track and consider separately. In some cases, the amount of information provided by these individual devices may require complex understanding of the nuances and implications of each device, for example types and amounts of insulin to deliver. Typically, each individual device is a silo of information that functions as well as the data provided therein, therefore when the devices are able to communicate with each other, enhanced functionality and safety can be realized. For example, when a continuous glucose monitor functions alone (for example, without data other than that which was gathered by the device), sudden changes in glucose level are tracked, but may not be fully understood, predicted, preempted, or otherwise considered in the processing of the sensor data; however, if the continuous glucose sensor were provided with information about time, amount, and type of insulin injections, calories consumed, time or day, meal time, or like, more meaningful, accurate and useful glucose estimation, prediction, and other such processing can be provided, such as described in more detail herein. By integrating these devices, the information from each component can be leveraged to increase the intelligence, benefit provided, convenience, safety, and functionality of the continuous glucose sensor and other integrated components. Therefore, it would be advantageous to provide a device that aids the diabetic host in integrating these individual devices in the treatment of his/her disease.

(81) In the non-diabetic host, pancreatic β -cells generally respond quickly to spikes in blood glucose by releasing stored insulin (e.g., within about 10-minutes). In preferred embodiments, the integrated system **10** is configured to mimic pancreatic β -cells, and thereby to provide substantially physiological detection of glucose levels and/or insulin response. Accordingly, the system **10** includes a continuous analyte sensor, a medicament delivery device (e.g., an infusion pump, a pen, a syringe, an inhaler, a medicament patch, and the like), and associated electronics, as described elsewhere herein. In various embodiments, the electronics include one or more of an on/off

controller module, a dynamic basal controller module and/or a dynamic bolus controller module, as described elsewhere herein. In some embodiments, the electronics include two or more controller modules configured to work in concert. The system **10** is configured for use with regular, rapid-acting, fast-acting and/or flash-acting insulins, which are described elsewhere herein. In one exemplary embodiment, the system **10** is configured to determine a medicament dose (e.g., an insulin dose) using solely internally derived data.

(82) Glucose Sensor

(83) FIG. 2A is a perspective view of one embodiment of a wholly implantable continuous glucose sensor **12** (e.g., the primary analyte sensor). In this embodiment, a body **20** and a sensing region **22** house the electrodes and sensor electronics (FIG. 3). The three electrodes within the sensing region are operably connected to the sensor electronics (FIG. 3) and are covered by a sensing membrane and a biointerface membrane (not shown), which are described in more detail below.

(84) The body **20** is preferably formed from epoxy molded around the sensor electronics, however the body can be formed from a variety of materials, including metals, ceramics, plastics, or composites thereof. U.S. Pat. No. 7,134,999 discloses suitable configurations suitable for the body **20**, and is incorporated by reference in its entirety.

(85) In one embodiment, the sensing region **22** comprises three electrodes including a platinum working electrode, a platinum counter electrode, and a silver/silver chloride reference electrode, for example. However a variety of electrode materials and configurations can be used with the implantable glucose sensor of the preferred embodiments. The top ends of the electrodes are in contact with an electrolyte phase (not shown), which is a free-flowing fluid phase disposed between the sensing membrane and the electrodes. In one embodiment, the counter electrode is provided to balance the current generated by the species being measured at the working electrode. In the case of a glucose oxidase based glucose sensor, the species being measured at the working electrode is H.sub.2O.sub.2. Glucose oxidase catalyzes the conversion of oxygen and glucose to hydrogen peroxide and gluconate according to the following reaction:

Glucose+O.sub.2→Gluconate+H.sub.2O.sub.2

(86) The change in H.sub.2O.sub.2 can be monitored to determine glucose concentration because for each glucose molecule metabolized, there is a proportional change in the product H.sub.2O.sub.2. Oxidation of H.sub.2O.sub.2 by the working electrode is balanced by reduction of ambient oxygen, enzyme generated H.sub.2O.sub.2, or other reducible species at the counter electrode. The H.sub.2O.sub.2 produced from the glucose oxidase reaction further reacts at the surface of working electrode and produces two protons (2H.sup.+), two electrons (2e.sup.-), and one oxygen molecule (**02**).

(87) In one embodiment, a potentiostat (FIG. 3) is employed to monitor the electrochemical reaction at the electroactive surface(s). The potentiostat applies a constant potential to the working and reference electrodes to determine a current value. The current that is produced at the working electrode (and flows through the circuitry to the counter electrode) is substantially proportional to the amount of H.sub.2O.sub.2 that diffuses to the working electrode. Accordingly, a raw signal can be produced that is representative of the concentration of glucose in the user's body, and therefore can be utilized to estimate a meaningful glucose value.

(88) In some embodiments, the sensing membrane includes an enzyme, for example, glucose oxidase, and covers the electrolyte phase. In one embodiment, the sensing membrane generally includes a resistance domain most distal from the electrochemically reactive surfaces, an enzyme domain less distal from the electrochemically reactive surfaces than the resistance domain, and an electrolyte domain adjacent to the electrochemically reactive surfaces. However, it is understood that a sensing membrane modified for other devices, for example, by including fewer or additional domains, is within the scope of the preferred embodiments. U.S. Patent Publication No. US-2003-0032874-A1 describes membranes that can be used in some embodiments of the sensing membrane. It is noted that in some embodiments, the sensing membrane can additionally include

an interference domain that blocks some interfering species; such as described in the above-cited co-pending patent application. U.S. Patent Publication No. US-2005-0090607-A1 also describes membranes that can be used for the sensing membrane of the preferred embodiments, and is incorporated herein by reference in its entirety.

(89) Preferably, the biointerface membrane supports tissue ingrowth, serves to interfere with the formation of a barrier cell layer, and protects the sensitive regions of the device from host inflammatory response. In one embodiment, the biointerface membrane generally includes a cell disruptive domain most distal from the electrochemically reactive surfaces and a cell impermeable domain less distal from the electrochemically reactive surfaces than the cell disruptive domain. The cell disruptive domain is preferably designed to support tissue ingrowth, disrupt contractile forces typically found in a foreign body response, encourage vascularity within the membrane, and disrupt the formation of a barrier cell layer. The cell impermeable domain is preferably resistant to cellular attachment, impermeable to cells, and composed of a biostable material. U.S. Pat. Nos. 6,702,857, 7,192,450, and U.S. Patent Publication No. US-2005-0251083-A1 describe biointerface membranes that can be used in conjunction with the preferred embodiments, and are incorporated herein by reference in their entirety. It is noted that the preferred embodiments can be used with a short term (for example, 1 to 7 day sensor), in which case a biointerface membrane may not be required. It is noted that the biointerface membranes described herein provide a continuous glucose sensor that has a useable life of greater than about one week, greater than about one month, greater than about three months, or greater than about one year, herein after referred to as “long-term.”

(90) In some embodiments, the domains of the biointerface and sensing membranes are formed from materials such as silicone, polytetrafluoroethylene, polyethylene-co-tetrafluoroethylene, polyolefin, polyester, polycarbonate, biostable polytetrafluoroethylene, homopolymers, copolymers and/or terpolymers of polyurethanes, polypropylene (PP), polyvinylchloride (PVC), polyvinylidene fluoride (PVDF), polybutylene terephthalate (PBT), polymethylmethacrylate (PMMA), polyether ether ketone (PEEK), polyurethanes, cellulosic polymers, polysulfones and block copolymers thereof including, for example, di-block, tri-block, alternating, random and graft copolymers.

(91) FIG. 2B is a perspective view of an in vivo portion of a transcutaneous continuous glucose sensor **12**, in one embodiment. In this embodiment, the in vivo portion of the sensor includes at least one working electrode **12a** and a reference electrode **12b** and a sensing membrane **12c**.

(92) FIG. 2C is a cross-section of the sensor shown in FIG. 2B, taken on line 2C-2C. In preferred embodiments, the sensing membrane **12c** (e.g., a biointerface and/or sensing membrane) includes at least an enzyme domain **12f** having an enzyme configured to detect the analyte, such as but not limited to glucose oxidase, as described elsewhere herein. In some preferred embodiments, the sensing membrane **12c** can include one or more additional domains, such as but not limited to an electrode domain **12d**, an interference domain **12e**, a resistance domain **12j**, a cell disruptive domain and a cell impermeable domain, for example. Additional sensor and sensing membrane configurations can be found in U.S. Patent Publication No. US-2006-0020187-A1, U.S. Patent Publication No. US-2005-0031689-A1, U.S. Patent Publication No. 2007-0027370-A1, U.S. Patent Publication No. 2006-0229512-A1, U.S. Patent Publication No. 2006-0253012-A1, U.S. Patent Publication No. US-2007-0197890-A1, U.S. application Ser. No. 11/404,417 filed on Apr. 14, 2006 and entitled “SILICONE BASED MEMBRANES FOR USE IN IMPLANTABLE GLUCOSE SENSORS,” and U.S. application Ser. No. 11/750,907 filed on May 18, 2007 and entitled “ANALYTE SENSORS HAVING AN OPTIMIZED SIGNAL-TO-NOISE RATIO,” each of which is incorporated herein by reference in its entirety.

(93) In preferred embodiments, the analyte sensor **12** is configured to provide response to changes in host glucose concentration, such as but not limited to a sensor response time of about 20-minutes or less. The term “sensor response time” as used herein is a broad term, and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (and is not to be limited to a special or customized meaning), and refers without limitation to the time required for the sensor to

measure a stable signal value associated with a change in glucose concentration, from a first concentration to a second concentration. The sensor response time can be measured by in vitro experimentation. For example, sensor response time can be measured by first placing a continuous glucose sensor in a first glucose solution (e.g., 100 mg/dl glucose); then moving the sensor to a second glucose solution (e.g., 200 mg/dl glucose) and allowing the sensor to equilibrate. In some embodiments, the sensor response time is less than about 10-minutes. In preferred embodiments, the sensor response time is less than 1, 2, 3, 4, or 5-minutes. In more preferred embodiments, the sensor response time is less than about 30-seconds. In some alternative embodiments, sensor response time includes an additional period of time required to process the measured glucose concentration change and provide a numerical output to the user (e.g., via a receiver).

(94) FIG. 3 is a block diagram that illustrates the electronics associated with a continuous glucose sensor **12** in one embodiment. In this embodiment, a potentiostat **24** is shown, operably connected to an electrode system (such as described above) and provides a voltage to the electrodes (FIG. 2), which biases the sensor to enable measurement of a current signal indicative of the analyte concentration in the host (also referred to as the analog portion). In some embodiments, the potentiostat includes a resistor (not shown) that translates the current into voltage. In some alternative embodiments, a current to frequency converter is provided that is configured to continuously integrate the measured current, for example, using a charge counting device. An A/D converter **26** digitizes the analog signal into a digital signal, also referred to as “counts” in some embodiments for processing. Accordingly, the resulting raw data stream in counts, also referred to as raw sensor data, is directly related to the current measured by the potentiostat **24**.

(95) A processor module **28** includes the central control unit (houses ROM **30** and RAM **32**) that controls the processing of the sensor electronics. In some embodiments, the processor module includes a microprocessor, however a computer system other than a microprocessor can be used to process data as described herein, for example an ASIC can be used for some or all of the sensor's central processing. The processor typically provides semi-permanent storage of data, for example, storing data such as sensor identifier (ID) and programming to process data streams (for example, programming for data smoothing and/or replacement of signal artifacts such as is described in U.S. Publication No. US-2005-0043598-A1). The processor additionally can be used for the system's cache memory, for example for temporarily storing recent sensor data. In some embodiments, the processor module comprises memory storage components such as ROM **30**, RAM **32**, dynamic-RAM, static-RAM, non-static RAM, EEPROM, rewritable ROMs, flash memory, or the like.

(96) In some embodiments, the processor module comprises a digital filter, for example, an infinite impulse response (IIR) or finite impulse response (FIR) filter, configured to smooth the raw data stream from the A/D converter. Generally, digital filters are programmed to filter data sampled at a predetermined time interval (also referred to as a sample rate). In some embodiments, wherein the potentiostat is configured to measure the analyte at discrete time intervals, these time intervals determine the sample rate of the digital filter. In some alternative embodiments, wherein the potentiostat is configured to continuously measure the analyte, for example, using a current-to-frequency converter as described above, the processor module can be programmed to request a digital value from the A/D converter at a predetermined time interval, also referred to as the acquisition time. In these alternative embodiments, the values obtained by the processor are advantageously averaged over the acquisition time due the continuity of the current measurement. Accordingly, the acquisition time determines the sample rate of the digital filter. In preferred embodiments, the processor module is configured with a programmable acquisition time, namely, the predetermined time interval for requesting the digital value from the A/D converter is programmable by a user within the digital circuitry of the processor module. An acquisition time of from about 2 seconds to about 512 seconds is preferred; however any acquisition time can be programmed into the processor module. A programmable acquisition time is advantageous in optimizing noise filtration, time lag, and processing/battery power.

(97) Preferably, the processor module **28** is configured to build the data packet for transmission to an outside source, for example, a Radio Frequency (RF) transmission (e.g., via RF module **38**) to a receiver as described in more detail below. Generally, the data packet comprises a plurality of bits that can include a preamble, a unique identifier identifying the electronics unit, the receiver, or both, (e.g., sensor ID code), data (e.g., raw data, filtered data, and/or an integrated value) and/or error detection or correction. Preferably, the data (transmission) packet has a length of from about 8 bits to about 128 bits, preferably about 48 bits; however, larger or smaller packets can be desirable in certain embodiments. The processor module **28** can be configured to transmit any combination of raw and/or filtered data. In one exemplary embodiment, the transmission packet contains a fixed preamble, a unique ID of the electronics unit, a single five-minute average (e.g., integrated) sensor data value, and a cyclic redundancy code (CRC).

(98) In some embodiments, the processor module **28** further comprises a transmitter portion that determines the transmission interval of the sensor data to a receiver, or the like. In some embodiments, the transmitter portion, which determines the interval of transmission, is configured to be programmable. In one such embodiment, a coefficient can be chosen (e.g., a number of from about 1 to about 100, or more), wherein the coefficient is multiplied by the acquisition time (or sampling rate), such as described above, to define the transmission interval of the data packet. Thus, in some embodiments, the transmission interval is programmable from about 2 seconds to about 850 minutes, more preferably from about 30 second to about 5 minutes; however, any transmission interval can be programmable or programmed into the processor module. However, a variety of alternative systems and methods for providing a programmable transmission interval can also be employed. By providing a programmable transmission interval, data transmission can be customized to meet a variety of design criteria (e.g., reduced battery consumption, timeliness of reporting sensor values, etc.).

(99) Conventional glucose sensors measure current in the nanoAmp range. In contrast to conventional glucose sensors, the preferred embodiments are configured to measure the current flow in the picoAmp range, and in some embodiments, femtoAmps. Namely, for every unit (mg/dL) of glucose measured, at least one picoAmp of current is measured. Preferably, the analog portion of the A/D converter **26** is configured to continuously measure the current flowing at the working electrode and to convert the current measurement to digital values representative of the current. In one embodiment, the current flow is measured by a charge counting device (e.g., a capacitor). Preferably, a charge counting device provides a value (e.g., digital value) representative of the current flow integrated over time (e.g., integrated value). In some embodiments, the value is integrated over a few seconds, a few minutes, or longer. In one exemplary embodiment, the value is integrated over 5 minutes; however, other integration periods can be chosen. Thus, a signal is provided, whereby a high sensitivity maximizes the signal received by a minimal amount of measured hydrogen peroxide (e.g., minimal glucose requirements without sacrificing accuracy even in low glucose ranges), reducing the sensitivity to oxygen limitations in vivo (e.g., in oxygen-dependent glucose sensors).

(100) In some embodiments, the electronics unit is programmed with a specific ID, which is programmed (automatically or by the user) into a receiver to establish a secure wireless communication link between the electronics unit and the receiver. Preferably, the transmission packet is Manchester encoded; however, a variety of known encoding techniques can also be employed.

(101) A battery **34** is operably connected to the sensor electronics and provides the power for the sensor **12**. In one embodiment, the battery is a lithium manganese dioxide battery; however, any appropriately sized and powered battery can be used (for example, AAA, nickel-cadmium, zinc-carbon, alkaline, lithium, nickel-metal hydride, lithium-ion, zinc-air, zinc-mercury oxide, silver-zinc, and/or hermetically-sealed). In some embodiments, the battery is rechargeable, and/or a plurality of batteries can be used to power the system. The sensor can be transcutaneously powered

via an inductive coupling, for example. In some embodiments, a quartz crystal **36** is operably connected to the processor **28** and maintains system time for the computer system as a whole, for example for the programmable acquisition time within the processor module.

(102) An RF module **38** is operably connected to the processor **28** and transmits the sensor data from the sensor **12** to a receiver within a wireless transmission **40** via antenna **42**. In some embodiments, a second quartz crystal **44** provides the time base for the RF carrier frequency used for data transmissions from the RF module **38**. In some alternative embodiments, however, other mechanisms, such as optical, infrared radiation (IR), ultrasonic, or the like, can be used to transmit and/or receive data.

(103) In the RF telemetry module of the preferred embodiments, the hardware and software are designed for low power requirements to increase the longevity of the device (for example, to enable a life of from about 3 to about 24 months, or more) with maximum RF transmittance from the in vivo environment to the ex vivo environment for wholly implantable sensors (for example, a distance of from about one to ten meters or more). Preferably, a high frequency carrier signal of from about 402 MHz to about 433 MHz is employed in order to maintain lower power requirements. In some embodiments, the RF module employs a one-way RF communication link to provide a simplified ultra low power data transmission and receiving scheme. The RF transmission can be OOK or FSK modulated, preferably with a radiated transmission power (EIRP) fixed at a single power level of typically less than about 100 microwatts, preferably less than about 75 microwatts, more preferably less than about 50 microwatts, and most preferably less than about 25 microwatts.

(104) In one alternative embodiment, the continuous glucose sensor comprises a transcutaneous sensor such as described in U.S. Pat. No. 6,565,509 to Say et al. In another alternative embodiment, the continuous glucose sensor comprises a subcutaneous sensor such as described with reference to U.S. Pat. No. 6,579,690 to Bonnez et al. and U.S. Pat. No. 6,484,046 to Say et al. In another alternative embodiment, the continuous glucose sensor comprises a refillable subcutaneous sensor such as described with reference to U.S. Pat. No. 6,512,939 to Colvin et al. In another alternative embodiment, the continuous glucose sensor comprises an intravascular sensor such as described with reference to U.S. Pat. No. 6,477,395 to Schulman et al. In another alternative embodiment, the continuous glucose sensor comprises an intravascular sensor such as described with reference to U.S. Pat. No. 6,424,847 to Mastrototaro et al. All of the above patents are incorporated in their entirety herein by reference. In general, it should be understood that the disclosed embodiments are applicable to a variety of continuous glucose sensor configurations.

(105) Receiver

(106) The preferred embodiments provide an integrated system, which includes a receiver **14** that receives and processes the raw data stream from the continuous glucose sensor **12**. The receiver can perform all or some of the following operations: a calibration, converting sensor data, updating the calibration, evaluating received reference and sensor data, evaluating the calibration for the analyte sensor, validating received reference and sensor data, displaying a meaningful glucose value to a user, calculating therapy recommendations, validating recommended therapy, adaptive programming for learning individual metabolic patterns, and prediction of glucose values, for example. Some complementary systems and methods associated with the receiver are described in more detail with reference to U.S. Patent Publication No. US-2005-0027463-A1 which is incorporated herein by reference in its entirety. FIGS. **9** to **11** describe some processes that can be programmed into the receiver. Additionally, the receiver **14** of the preferred embodiments works together with the other components of the system (for example, the medicament delivery device **16** and the single point glucose monitor **18**) to provide enhanced functionality, convenience, and safety, such as described in more detail herein. FIGS. **4** to **7** are illustrates of a few exemplary integrated systems of the preferred embodiments, each of which include the receiver, such as described in more detail herein.

(107) In some embodiments, the receiver **14** is a PDA- or pager-sized housing **46**, for example, and comprises a user interface **48** that has a plurality of buttons **50** and a liquid crystal display (LCD) screen, which can include a backlight. In some embodiments, the receiver can take other forms, for example a computer, server, or other such device capable of receiving and processing the data such as described herein. In some embodiments the user interface can also include a keyboard, a speaker, and a vibrator such as described with reference to FIG. **8**. The receiver **46** comprises systems (for example, electronics) necessary to receive, process, and display sensor data from the glucose sensor **12**, such as described in more detail with reference to FIG. **8**. The receiver **14** processes data from the continuous glucose sensor **12** and additionally processes data associated with at least one of the medicament delivery device **16**, single point glucose meter **16**, and user **8**.

(108) In some embodiments, the receiver **14** is integrally formed with at least one of the medicament delivery device **16**, and single point glucose monitor **18**. In some embodiments, the receiver **14**, medicament delivery device **16** and/or single point glucose monitor **18** are detachably connected, so that one or more of the components can be individually detached and attached at the user's convenience. In some embodiments, the receiver **14**, medicament delivery device **16**, and/or single point glucose monitor **18** are separate from, detachably connectable to, or integral with each other; and one or more of the components are operably connected through a wired or wireless connection, allowing data transfer and thus integration between the components. In some embodiments, one or more of the components are operably linked as described above, while another one or more components (for example, the syringe or patch) are provided as a physical part of the system for convenience to the user and as a reminder to enter data for manual integration of the component with the system. Some exemplary embodiments are described with reference to FIGS. **4** to **7**, however suffice it to say that each of the components of the integrated system can be manually, semi-automatically, or automatically integrated with each other, and each component can be in physical and/or data communication with another component, which can include wireless connection, wired connection (for example, via cables or electrical contacts), or the like. In some embodiments, the receiver is configured to process data from the glucose sensor, an auxiliary sensor and/or the medicament delivery device, and can include a controller module.

(109) Medicament Delivery Device

(110) The preferred embodiments provide an integrated system **10**, which includes a medicament delivery device **16** for administering a medicament to the host **8**. The integrated medicament delivery device can be designed for bolus injection/infusion, basal injection/infusion, continuous injection/infusion, inhalation, transdermal absorption, other method for administering medicament, or any combinations thereof. In one exemplary embodiment, the medicament delivery device is an infusion pump configured for transcutaneous (e.g., injection/infusion and absorption into the subcutaneous tissue), intraperitoneal or intravenous infusion. In some embodiments, the infusion device is wholly implantable. In other embodiments, the infusion device is worn outside of the body, with infusion via a catheter. In some embodiments, the infusion device is configured for one or more maintenance functions, such as but not limited to checking for catheter clogs or monitoring the rate of insulin leaving the infusion device or the remaining volume of insulin within the pump. In some embodiments, the medicament delivery device is an insulin pump configured to deliver insulin to the host. In some embodiments, the insulin pump is further configured to receive and process instructions for delivery of an insulin therapy from a controller module.

(111) In some embodiments, the medicament delivery device is an injection pen configured to inject insulin transcutaneously. In some embodiments, the medicament delivery device is an inhaler that delivers an inhalable insulin formulation. In other embodiments, the medicament delivery device is an oral medicament, such as an insulin preparation formulated for buccal absorption. In still other embodiments, the medicament delivery device is configured for transdermal delivery, such as a transdermal patch. In some embodiments, the at least two insulin delivery devices are used in conjunction with each other. For example, delivery of insulin by an infusion device (e.g., a

pump) can be supplemented with delivery of another medicament (e.g., either the same or different types of insulin, or another medicament such as glucagon) with a second medicament delivery device, such as but not limited to a pen, a transdermal patch or an inhaler. For example, in some circumstances, a host can use an infusion pump to deliver rapid acting insulin and a patch to constantly deliver a slow-acting insulin. In another exemplary circumstance, a transcutaneous insulin pump can provide the insulin therapy, which can be supplemented by instructions to provide a therapeutic dose of glucagon via an inhaler or an oral preparation. The term medicament includes any substance used in therapy for a host using the system **10**, for example, insulin, glucagon, or derivatives thereof. PCT International Publication No. WO02/43566-A1 describes glucose, glucagon, and vitamins A, C, or D that can be used with the preferred embodiments. U.S. Pat. Nos. 6,051,551 and 6,024,090 describe types of insulin suitable for inhalation that can be used with the preferred embodiments. U.S. Pat. No. 5,234,906, 6,319,893, and European Patent No. EP-760677-B1 describe various derivatives of glucagon that can be used with the preferred embodiments. U.S. Pat. No. 6,653,332 describes a combination therapy that can be used with the preferred embodiments. U.S. Pat. No. 6,471,689 and PCT International Publication No. WO81/01794-A1 describe insulin useful for delivery pumps that can be used with the preferred embodiments. U.S. Pat. No. 5,226,895 describes a method of providing more than one type of insulin that can be used with the preferred embodiments. Each of the above references is incorporated herein by reference in its entirety and the medicaments and methods disclosed can be useful in the preferred embodiments.

(112) As described elsewhere herein, in preferred embodiments, the system is configured to substantially mimic the body's metabolic response to changes in glucose (e.g., the host's blood sugar concentration), similar to the response of a pancreatic 3-cell to changes in glucose concentration. As is understood by one skilled in the art, insulin activity can be influenced by a variety of factors, such as but not limited to method/location of delivery (e.g., injected transcutaneously, infused IV or intraperitoneally, inhaled, etc.), the host's insulin sensitivity, method of insulin preparation, and the like. However, it is possible to compare different insulins by comparing their time-activity profiles (TAP), as defined by methods of Frohnauer, et al. 2001, in "Graphical Human Insulin Time-Activity Profiles Using Standardized Definitions," *Diab. Tech. & Therap.* 3(3):419-429. Table 1 presents the TAPs of some purified human insulins (e.g., wild type and/or analogs) and one exemplary flash insulin (described elsewhere herein).

(113) TABLE-US-00001

	TABLE 1	Duration	Insulin Formulation	Onset (hrs)	T.sub.i50 (hrs)	Peak (hrs)	T.sub.d50 (hrs)
Humulin R	Plasma Insulin Level	0.08-1.0	0.5-3.25	4.0-12.0			
Glucose Infusion Rate	0.25-1.0	0.6-1.25	1.5-4.0	4.0-7.0	9.5-12.0		
NPH	Plasma Insulin Level	0.08-1.5	1.0-8.0	6.0-28.0			
Glucose Infusion Rate	0.25-2.0	1.25-3.25	3.5-10.0	8.5-18.0	14.0-27.0		
Lente	Plasma Insulin Level	0.5-2.25	4.0-6.5	21.0-24.0			
Glucose Infusion Rate	0.75-2.0	3.0-4.5	9.4-12.0	19.25-23.5	21.0-24.0		
Ultralente	Plasma Insulin Level	0.5-3.0	4.0-16.0	9.0-28.0			
Glucose Infusion Rate	0.75-3.0	3.5-8.0	5.0-14.5	17.0-22.0	22.5-36.6		
Insulin lispro	Plasma Insulin Level	0.08-0.25	0.6-1.0	3.0-8.0			
Glucose Infusion Rate	0.16-0.5	0.6-0.75	1.25-2.0	2.5-4.25	5.0-7.0		
Flash Insulin	Plasma Insulin Level	≤0.08-≤0.25	≤0.6-≤1.0	≤3.0-≤8.0			
Glucose Infusion Rate	≤0.25-≤0.5	≤0.6-≤0.75	≤1.25-≤2.0	≤2.5-≤4.25	≤5.0-≤7.0		

Humulin R = a purified wild type human insulin; NPH = a purified human insulin analog (Humulin N) Lente = another purified human insulin analog (Humulin L) Ultralente = yet another purified human insulin analog (Humulin U) T.sub.i50 = the time point at which insulin activity is half of the maximal activity, as the level increases. T.sub.d50 = the time point at which the insulin activity is half of the maximal activity, as the level decreases.

(114) FIG. 4 illustrates the TAP of Humulin R (according to Frohnauer, et al. 2001, in "Graphical Human Insulin Time-Activity Profiles Using Standardized Definitions," *Diab. Tech. & Therap.* 3(3):419-429) and three possible TAPs for a "Flash Insulin," which is described below. As is known to those skilled in the art, the times of onset, peak and duration of an insulin's activity can

be determined by conducting glucose clamp studies (e.g., on human volunteers) and examining the pharmacokinetics of the insulin (e.g., by examining the plasma insulin level or the glucose infusion rate during glucose clamp studies). According to the methods of Frohnauer, et al., “onset” of an insulin's activity can be determined by graphing the insulin's activity over an extended period of time (e.g., about 24- to 38-hours). On a graph of an insulin's activity (see FIG. 4), onset occurs at a time point between last baseline measurement and the first measurement above the baseline. In some circumstances, onset of an insulin's activity can be very abrupt or sharp, occurring within a few minutes. In other circumstances, onset can be prolonged, taking up to several hours. The peak of insulin activity occurs at a time point between the first maximum activity measurement and the last maximum activity measurement. In some circumstances, the peak of activity is very brief, such as a single time point. In other circumstances, the peak is prolonged (e.g., lasts a period of minutes or hours) and falls within a range of consecutive time points. The duration of an insulin's activity is the length of time during which the insulin has been active (e.g., functioning, working in the body), up to the termination of activity. At termination, the insulin's activity generally declines, tapers off and/or plateaus out (e.g., flattens out). On a graph of the insulin's activity, activity termination occurs between the last point above horizontal and the first point on the horizontal. In some circumstances, an insulin's termination can be abrupt, such as at a single point. In other circumstances, an insulin's termination can be extended over a period of several minutes or a few hours.

(115) In some embodiments, the insulin used in conjunction with the integrated system **10** is configured such that the system mimics the function of a pancreatic β -cell, with a substantially immediate onset of activity, a very rapid peak and a very brief duration (as determined by plasma insulin concentration according to the methods of Frohnauer et al). In some embodiments, the insulin is configured to have an onset time of about 5-minutes to about 10-minutes or less and a peak of activity of about 5-minutes to about 1.25-hours. Additionally, the insulin is configured to have a substantially short (e.g., brief) duration of about 3-hours or less.

(116) In some embodiments, a very rapid-acting insulin is preferred, such that the insulin can be delivered by a system having an on/off controller, as described elsewhere herein. Such an insulin is referred to herein as a “Flash Insulin.” In FIG. 4, three possible TAPs, of an exemplary flash insulin, are denoted by the curves labeled FI-1, FI-2 and FI-3. Depending upon the flash insulin developed, other TAPs are possible. In preferred embodiments, a flash insulin is configured to have a substantially “instant on” onset, such that the flash insulin reaches its peak of activity within a short time after delivery. For example, in some embodiments, a flash insulin's onset can occur within about 10-minutes or less (e.g., after delivery), preferably within about 6-minutes or less. In another example, in some embodiments, the flash insulin's peak of activity can occur within about 2-minutes to about 30-minutes, preferably within about 5-minutes to about 15-minutes. In another example, in some embodiments, the flash insulin's duration is substantially short, such as less than about 3, 2 or 1-hours. In some preferred embodiments, the flash insulin's activity peaks within about 4, 5, 8, 10, 15 or 20-minutes of the insulin's onset of activity and/or infusion of the insulin into the host. In some more preferred embodiments, the flash insulin's duration is sufficiently brief that “dose stacking” (e.g., from sequential doses) has substantially no effect on the host's glucose concentration. For example, in some embodiments, the flash insulin's duration is about 10, 20, 30 or 40-minutes, preferably less than about 20-minutes. In some embodiments, the flash insulin is configured for use with an on/off controller (discussed elsewhere herein), such that when the on instruction is selected, the flash insulin is delivered at substantially constant rate.

(117) Manual Integration

(118) In some embodiments, the medicament delivery device **16** is a manual delivery device, for example a syringe, inhaler, transdermal patch, cell transplantation device, and/or manual pump for manual integration with the receiver. Manual integration includes medicament delivery devices wherein a user (for example, host or doctor) manually selects the amount, type, and/or time of

delivery. In some embodiments, the medicament delivery device **16** is any syringe suitable for injecting a medicament, as is appreciated by one skilled in the art. One example of a syringe suitable for the medicament delivery device of the preferred embodiments is described in U.S. Pat. No. 5,137,511, which is incorporated herein by reference in its entirety.

(119) FIGS. 5A and 5B are perspective views of an integrated system **10** in one embodiment, wherein a receiver **14** is integrated with a medicament delivery device **16** in the form of a manual syringe **54**, and optionally includes a single point glucose monitor **18**, which will be described in more detail elsewhere herein. The receiver **14** receives, processes, and displays data from the continuous glucose monitor **12**, such as described in more detail above, and can also receive, process, and display data manually entered by the user. In some embodiments, the receiver includes algorithms that use parameters provided by the continuous glucose sensor, such as glucose concentration, rate-of-change of the glucose concentration, and acceleration of the glucose concentration to more particularly determine the type, amount, and time of medicament administration. The medicament delivery device **16** is in the form of a syringe **54**, which can comprise any known syringe configuration, such as described in more detail above. In some embodiments, the syringe **54** includes a housing, which is designed to hold a syringe as well as a plurality of types and amounts of medicament, for example fast-acting insulin, slow-acting insulin, and glucagon. In some embodiments, the syringe is detachably connectable to the receiver **14**, and the receiver **14** provides and receives information to and from the host associated with the time, type, and amount of medicament administered. In some embodiments, the syringe is stored in a holder that is integral with or detachably connected to the receiver **14**. In some embodiments, the syringe **54** can be detachably connected directly to the receiver, provided in a kit with the receiver, or other configuration, which provides easy association between the syringe and the receiver.

(120) Referring now to the integration between the syringe and the receiver, it is noted that the receiver can be programmed with information about the time, amount, and types of medicament that can be administered with the syringe, for example. In some embodiments during set-up of the system, the host and/or doctor manually enters information about the amounts and types of medicament available via the syringe of the integrated system. In some alternative embodiments, manufacturer-provided data can be downloaded to the receiver so that the host and/or doctor can select appropriate information from menus on the screen, for example, to provide easy and accurate data entry. Thus, by knowing the available medicaments, the receiver can be programmed to customize the host's therapy recommendations considering available types and amounts of medicaments in combination with concentration, rate-of-change, and/or acceleration of the host's glucose. While not wishing to be bound by theory, it is believed that by storing available medicament therapies, the receiver is able to customize medicament calculations and recommend appropriate therapy based glucose on trend information and the preferred types and the amounts of medicament available to the host.

(121) Subsequently in some embodiments, once the host has administered a medicament (including via the syringe and or by other means), the amount, type, and/or time of medicament administration are input into the receiver by the host. Similarly, the receiver can be programmed with standard medicaments and dosages for easy selection by the host (for example, menus on the user interface). This information can be used by the receiver to increase the intelligence of the algorithms used in determining the glucose trends and patterns that can be useful in predicting and analyzing present, past, and future glucose trends, and in providing therapy recommendations, which will be described in more detail below. Additionally, by continuously monitoring the glucose concentration over time, the receiver provides valuable information about how a host responds to a particular medicament, which information can be used by a doctor, host, or by the algorithms within the receiver, to determine patterns and provide more personalized therapy recommendations. In other words, in some embodiments, the receiver includes programming that learns the patterns (for example, an individual's metabolic response to certain medicament deliveries and host behavior)

and to determine an optimum time, amount, and type of medicament to delivery in a variety of conditions (e.g., glucose concentration, rate-of-change, and acceleration). While not wishing to be bound by theory, it is believed that by continuously monitoring an individual's response to various medicaments, the host's glucose levels can be more proactively treated, keeping the diabetic host within safe glucose ranges substantially all the time.

(122) In some embodiments, the receiver includes programming to predict glucose trends, such as described in U.S. Patent Publication No. US-2005-0203360-A1, which is incorporated herein by reference in its entirety. In some embodiments, the predictive algorithms consider the amount, type, and time of medicament delivery in predicting glucose values. For example, a predictive algorithm that predicts a glucose value or trend for the upcoming 15 to 20 minutes uses a mathematical algorithm (for example, regression, smoothing, or the like) such as described in the above-cited U.S. Patent Publication No. US-2005-0203360-A1 to project a glucose value. However outside influences, including medicament delivery can cause this projection to be inaccurate. Therefore, some embodiments provide programming in the receiver that uses the medicament delivery information received from the delivery device **14**, in addition to other mathematical equations, to more accurately predict glucose values in the future.

(123) In some alternative embodiments, the medicament delivery device **16** includes one or more transdermal patches **58** suitable for administering medicaments as is appreciated by one skilled in the art. PCT International Publication No. WO02/43566 describes one such transdermal patch, which can be used in the preferred embodiments. Although the above-cited reference and description associated with the FIGS. **6A** to **6C** describe a medicament (for example, glucagon) useful for treating hypoglycemia, it is understood that transdermal patches that release a medicament (for example, insulin) useful for treating hyperglycemia are also contemplated within the scope of the preferred embodiments.

(124) FIGS. **6A** to **6C** are perspective views of an integrated system **10** in one embodiment, wherein a receiver **14** is integrated with a medicament delivery device **16** in the form of one or more transdermal patches **58** housed within a holder **56**, and optionally includes a single point glucose monitor **18**, which will be described in more detail elsewhere herein. The receiver **14** receives, processes, and displays data from the continuous glucose monitor **12**, such as described in more detail above. The medicament delivery device **16** is in the form of one or more transdermal patches **58** held in a holder **56**, which can comprise any known patch configuration.

(125) The integration of the patches **58** with the receiver **14** includes similar functionality and provides similar advantages as described with reference to other manual integrations including manual medicament delivery devices (for example, syringe and inhaler). However, a unique advantage can be seen in the integration of a continuous glucose sensor with a glucagon-type patch. Namely, a continuous glucose sensor, such as described in the preferred embodiments, provides more than single point glucose readings. In fact, because the continuous glucose sensor **12** knows the concentration, rate-of-change, acceleration, the amount of insulin administered (in some embodiments), and/or individual patterns associated with a host's glucose trends (learned over time as described in more detail elsewhere herein), the use of the glucagon patch can be iteratively optimized (inputting its usage into the receiver and monitoring the individual's metabolic response) to proactively preempt hypoglycemic events and maintain a more controlled range of glucose values. This can be particularly advantageous for nighttime hypoglycemia by enabling the diabetic host (and his/her caretakers) to improve overall nighttime diabetic health. While not wishing to be bound by theory, the integration of the continuous glucose sensor and transdermal glucagon-type patch can provide diabetic hosts with a long-term solution to reduce or avoid hypoglycemic events.

(126) In some embodiments, the holder **58** is detachably connectable to the receiver **14** (for example on the side opposite the LCD), which enables convenient availability of the patch to the host when the receiver indicates that a medicament (for example, glucose or glucagon) is recommended. It is further noted that although this holder is shown without another medicament

delivery device **16** in the illustrations of FIGS. **6A** to **6C**, other medicaments (for example, insulin pen, insulin pump, such as described with reference to FIGS. **7** and **8**) can be integrated into the system in combination with the medicament patch illustrated herein. While not wishing to be bound by theory, it is believed that by combining medicaments that aid the diabetic host in different ways (for example, medicaments for treating hyper- and hypo-glycemic events, or, fast-acting and slow-acting medicaments), a simplified comprehensive solution for treating diabetes can be provided.

(127) Manual integration of delivery devices with the continuous glucose sensor **12** of the preferred embodiments can additionally be advantageous because the continuous device of the preferred embodiments is able to track glucose levels long-term (for example weeks to months) and adaptively improve therapy decisions based on the host's response over time.

(128) In some alternative embodiments, the medicament delivery device **16** includes an inhaler or spray device suitable for administering a medicament into the circulatory system, as is appreciated by one skilled in the art. Some examples of inhalers suitable for use with the preferred embodiments include U.S. Pat. Nos. 6,167,880, 6,051,551, and 6,024,090, which are incorporated herein by reference in their entirety. In some embodiments, the inhaler or spray device is considered a manual medicament delivery device, such as described with reference to FIGS. **5** and **6**, wherein the inhaler or spray is manually administered by a host, and wherein the host manually enters data into the continuous receiver about the time, amount, and types of therapy. However, it is also possible that the inhaler or spray device used for administering the medicament can also comprise a processor module and operable connection to the receiver (for example, RF), such that data is sent and received between the receiver and inhaler or spray device, making it a semi-automated integration, which is described in more detail with reference to the integrated insulin pen below, for example.

(129) In some embodiments, the inhaler or spray device is integrally housed within, detachably connected to, or otherwise physically associated with (for example, in a kit) to the receiver. The functionality and advantages of the integrated inhaler or spray device are similar to those described with reference to the syringe and/or patch integration, above. It is noted that the inhaler or spray device can be provided in combination with any other of the medicament delivery devices of the preferred embodiments, for example, a fast-acting insulin inhaler and a slow acting insulin pump can be advantageously integrated into the system of the preferred embodiments and utilized at the appropriate time as is appreciated by one skilled in the art. In some embodiments, wherein the inhaler or spray device includes a semi-automated integration with the receiver, the inhaler or spray device can be physically integrated with receiver such as described above and also operably connected to the receiver, for example via a wired (for example, via electrical contacts) or wireless (for example, via RF) connection.

(130) In one alternative embodiment, a manual medicament delivery pump is implanted such as described in U.S. Pat. No. 6,283,944, which is incorporated herein by reference in its entirety. In this alternative embodiment, the host-controlled implantable pump allows the host to press on the device (through the skin) to administer a bolus injection of a medicament when needed. It is believed that providing glucagon or other medicament for treating hypoglycemia within this device will provide the ease and convenience that can be easily released by the host and/or his or her caretaker when the continuous glucose sensor indicates severe hypoglycemia, for example. In some alternative embodiments, the manual implantable pump is filled with insulin, or other medicament for treating hyperglycemia. In either case, the manual pump and continuous glucose sensor will benefit from manual integrations described in more detail above.

(131) In another alternative embodiment, a cell transplantation device, such as described in U.S. Pat. Nos. 6,015,572, 5,964,745, and 6,083,523, which are incorporated herein by reference in their entirety, is manually integrated with the continuous sensor of the preferred embodiments. In this alternative embodiment, a host would be implanted with beta islet cells, which provide insulin

secretion responsive to glucose levels in the body. The receiver associated with the implantable glucose sensor can be programmed with information about the cell transplantation (for example, time, amount, type, etc). In this way, the long-term continuous glucose sensor can be used to monitor the body's response to the beta islet cells. This can be particularly advantageous when a host has been using the continuous glucose sensor for some amount of time prior to the cell transplantation, and the change in the individual's metabolic patterns associated with the transplantation of the cells can be monitored and quantified. Because of the long-term continuous nature of the glucose sensor of the preferred embodiments, the long-term continuous effects of the cell transplantation can be consistently and reliably monitored. This integration can be advantageous to monitor any person's response to cell transplantation before and/or after the implantation of the cells, which can be helpful in providing data to justify the implantation of islet cells in the treatment of diabetes.

(132) It is noted that any of the manual medicament delivery devices can be provided with an RF ID tag or other communication-type device, which allows semi-automated integration with that manual delivery device, such as described in more detail below.

(133) Semi-Automated Integration

(134) Semi-automated integration of medicament delivery devices **16** in the preferred embodiments includes any integration wherein an operable connection between the integrated components aids the user (for example, host or doctor) in selecting, inputting, or calculating the amount, type, or time of medicament delivery of glucose values, for example, by transmitting data to another component and thereby reducing the amount of user input required. In the preferred embodiments, semi-automated can also refer to a fully automated device (for example, one that does not require user interaction), wherein the fully automated device requires a validation or other user interaction, for example to validate or confirm medicament delivery amounts. In some embodiments, the semi-automated medicament delivery device is an inhaler or spray device, a pen or jet-type injector, or a transdermal or implantable pump.

(135) FIGS. 7A and 7B are perspective views of an integrated system **10** in one embodiment, wherein a receiver **14** is integrated with a medicament delivery device **16** in the form of a pen or jet-type injector, hereinafter referred to as a pen **60**, and optionally includes a single point glucose monitor **18**, which will be described in more detail elsewhere herein. The receiver **14** receives, processes, and displays data from the continuous glucose monitor **12**, such as described in more detail above. The medicament delivery pen **60** of the preferred embodiments includes any pen-type injector, such as is appreciated by one skilled in the art. A few examples of medicament pens that can be used with the preferred embodiments, include U.S. Pat. Nos. 5,226,895, 4,865,591, 6,192,891, and 5,536,249, each of which are incorporated herein by reference in its entirety.

(136) FIG. 7A is a perspective view of an integrated system **10** in embodiment. The integrated system **10** is shown in an attached state, wherein the various elements are held by a mechanical means, as is appreciated by one skilled in the art. The components **14**, **16**, and **18** (optional) are also in operable connection with each other, which can include a wired or wireless connection. In some embodiments, the components include electrical contacts that operably connect the components together when in the attached state. In some embodiments, the components are operably connected via wireless connection (for example, RF), and wherein the components may or may not be detachably connectable to each other. FIG. 7B shows the components in an unattached state, which can be useful when the host would like to carry minimal components and/or when the components are integrated via a wireless connection, for example.

(137) Medicament delivery pen **60** includes at least a processor module and a wired or wireless connection to the receiver **14**, which are described in more detail with reference to FIG. 9. In some embodiments, the pen **60** includes programming that receives instructions sent from the receiver **14** regarding type and amount of medicament to administer. In some embodiments, wherein the pen includes more than one type of medicament, the receiver provides the necessary instructions to

determine which type or types of medicament to administer, and can provide instructions necessary for mixing the one or more medicaments. In some embodiments, the receiver provides the glucose trend information (for example, concentration, rate-of-change, acceleration, or other user input information) and pen **60** includes programming necessary to determine appropriate medicament delivery.

(138) Subsequently, the pen **60** includes programming to send information regarding the amount, type, and time of medicament delivery to the receiver **14** for processing. The receiver **14** can use this information received from the pen **60**, in combination with the continuous glucose data obtained from the sensor, to monitor and determine the host's glucose patterns to measure their response to each medicament delivery. Knowing the host's individual response to each type and amount of medicament delivery can be useful in adjusting or optimizing the host's therapy. It is noted that individual metabolic profiles (for example, insulin sensitivity) are variable from host to host. While not wishing to be bound by theory, it is believed that once the receiver has learned (for example, monitored and determined) the individual's metabolic patterns, including glucose trends and associated medicament deliveries, the receiver can be programmed to adjust and optimize the therapy recommendations for the host's individual physiology to maintain their glucose levels within a desired target range. In alternative embodiments, the pen **60** can be manually integrated with the receiver.

(139) In some embodiments, the receiver includes algorithms that use parameters (e.g., data) provided by the continuous glucose sensor, such as glucose concentration, rate-of-change of the glucose concentration, and acceleration of the glucose concentration to more particularly determine the type, amount, and time of medicament administration. In fact, all of the functionality of the above-described manual and semi-automated integrated systems, including therapy recommendations, adaptive programming for learning individual metabolic patterns, and prediction of glucose values, can be applied to the semi-automated integrated system **10**, such as described herein. However, the semi-automated integrated sensing and delivery system additionally provides convenience by automation (for example, data transfer through operable connection) and reduced opportunity for human error than can be experienced with the manual integration.

(140) In some alternative embodiments, the semi-automated integration provides programming that requires at least one of the receiver **14**, single point glucose monitor **18**, and medicament delivery device **16** to be validated or confirmed by another of the components to provide a fail safe accuracy check; in these embodiments, the validation includes algorithms programmed into any one or more of the components. In some alternative embodiments, the semi-automated integration provides programming that requires at least one of the receiver **14** and medicament delivery device **16** to be validated or confirmed by a human (for example, confirm the amount and/or type of medicament). In these embodiments, validation provides a means by which the receiver can be used adjunctively, when the host or doctor would like to have more control over the host's therapy decisions, for example. See FIGS. **10** to **12** for processes that can be implemented herein.

(141) Although the above description of semi-automated medicament delivery is mostly directed to an integrated delivery pen, the same or similar integration can be accomplished between a semi-automated inhaler or spray device, and/or a semi-automated transdermal or implantable pump device. Additionally, any combination of the above semi-automated medicament delivery devices can be combined with other manual and/or automated medicament delivery device within the scope of the preferred embodiments as is appreciated by one skilled in the art.

(142) In some embodiments, the semi-automated integrated system **10** includes a dynamic bolus controller module that is configured to intelligently evaluate an engaged (e.g., selectable) bolus constraint (e.g., pre-set and/or programmable) and internally derived data, and to calculate an insulin therapy (e.g., dose) less than or equal to the maximum total insulin dose associated with the engaged bolus constraint, in response to the host engaging the bolus constraint, such as described in more detail elsewhere herein. Preferably, the determination of the insulin therapy is based solely on

the internally derived data and the engaged bolus constraint. In some preferred embodiments, the evaluation and/or calculation of therapy are performed iteratively. In some embodiments, a bolus constraint can be engaged (e.g., selected, initiated, activated) by pressing a programmable button or key, actuating a switch, selecting from a menu (e.g., scroll, pop-up or tab) and the like. In some embodiments, the system includes two or more bolus constraints, such as constraints associated with different types of meals and/or with different events. For example, one or more bolus constraint buttons can be programmed by the user (e.g., the host or a caretaker of the host) for insulin therapies sufficient to cover an average breakfast, lunch or dinner, to cover a high carbohydrate or high fat meal, or as a corrective insulin dose and the like. In a further embodiment, the system is configured to request host validation of the calculated bolus insulin therapy (e.g., by selecting yes or no, OK).

(143) In some embodiments, the system is configured to include an on/off controller module and/or a dynamic basal controller module. On/off and dynamic basal controller modules are discussed in detail elsewhere herein.

(144) Automated Integration

(145) Automated integration medicament delivery devices **16** in the preferred embodiments are any delivery devices wherein an operable connection between the integrated components provides for full control of the system without required user interaction. Transdermal and implantable pumps are examples of medicament delivery devices that can be used with the preferred embodiments of the integrated system **10** to provide automated control of the medicament delivery device **16** and continuous glucose sensor **12**. Some examples of medicament pumps that can be used with the preferred embodiments include, U.S. Pat. No. 6,471,689, PCT International Publication No. WO81/01794, and European Patent No. EP-1281351-B, each of which is incorporated herein by reference in its entirety.

(146) FIGS. **8A** to **8C** are perspective views of an integrated system in one embodiment, wherein a sensor and delivery pump, which are implanted or transdermally inserted into the host, are operably connected to an integrated receiver, and optionally include a single point glucose monitor. FIG. **8A** is a perspective view of a host **8**, in which is implanted or transdermally inserted a sensor **12** and a pump **70**. FIGS. **8B** and **8C** are perspective views of the integrated receiver and optional single point glucose monitor in attached and unattached states. The pump **70** can be of any configuration known in the art, for example, such as cited above.

(147) The receiver **14** receives, processes, and displays data associated with the continuous glucose monitor **12**, data associated with the pump **70**, and data manually entered by the host **8**. In some embodiments, the receiver includes algorithms that use parameters provided by the continuous glucose sensor, such as glucose concentration, rate-of-change of the glucose concentration, and acceleration of the glucose concentration to determine the type, amount, and time of medicament administration. In fact, all of the functionality of the above-described manual and semi-automated integrated systems, including therapy recommendations, confirmation or validation of medicament delivery, adaptive programming for learning individual metabolic patterns, and prediction of glucose values, can be applied to the fully automated integrated system **10**, such as described herein with reference to FIGS. **8A** to **8C**. However, the fully automated sensing and delivery system can run with or without user interaction. U.S. Patent Publication No. US-2003-0028089-A1 provides some systems and methods for providing control of insulin, which can be used with the preferred embodiments, and is incorporated herein by reference in its entirety.

(148) In some embodiments of the automated integrated system **10**, a fail-safe mode is provided, wherein the system is programmed with conditions whereby when anomalies or potentially clinically risky situations arise, for example when a reference glucose value (for example, from an SMBG) indicates a discrepancy from the continuous sensor that could cause risk to the host if incorrect therapy is administered. Another example of a situation that may benefit from a validation includes when a glucose values are showing a trend in a first direction that shows a possibility of

“turn around,” namely, the host may be able to reverse the trend with a particular behavior within a few minutes to an hour, for example. In such situations, the automated system can be programmed to revert to a semi-automated system requiring user validation or other user interaction to validate the therapy in view of the situation.

(149) It is noted that in the illustrated embodiment, only one receiver **14** is shown, which houses the electronics for both the medicament delivery pump **70** and the continuous sensor **12**. Although it is possible to house the electronics in two different receiver housings, providing one integrated housing **14** increases host convenience and minimizes confusion or errors. In some embodiments, the sensor receiver electronics and pump electronics are separate, but integrated. In some alternative embodiments, the sensor and pump share the same electronics.

(150) Additionally, the integrated receiver for the sensor and pump, can be further integrated with any combination with the above-described integrated medicament delivery devices, including syringe, patch, inhaler, and pen, as is appreciated by one skilled in the art.

(151) In some embodiments, the fully automated integrated system **10** includes an on/off controller module, as described elsewhere herein. Preferably, the on/off controller module is configured to intelligently and adaptively evaluate only internally derived data relative to a pre-programmed glucose boundary (e.g., about 70, 80, 90, 100, 110, 120, 130, 140, 150, or 160 mg/dl glucose) and to select between on and off instructions that actuate the system's integrated insulin delivery device. In one embodiment, integrated system **10** is configured to automatically (e.g., iteratively, continually or continuously) monitor and manage the host's glucose level in real-time, similarly to the glucose regulation by the pancreatic β -cells of a non-diabetic person. In generally, the glucose boundary is selected based on when insulin is, or is not, to be delivered to the host.

(152) In some embodiments, the automated system includes an on/off controller and is configured for use with a flash insulin (e.g., an insulin having a substantially “instant on,” rapid peak and short duration TAP, as described in the section entitled “Medicament Delivery Device”), such that the on/off controller can iteratively (e.g., automatically, periodically, or continually) evaluate the internally derived data, calculate and deliver flash insulin doses over a period of time (e.g., minutes, hours, days, etc.) and the effect of insulin dose stacking (e.g., to the host) is substantially negligible and/or can be algorithmically accounted for. On/off controller modules are described in greater detail in the section entitled “On/off Controller Module,” and, for example, with reference to FIG. **15**.

(153) In some embodiments, the automated integrated system **10** includes a dynamic basal controller module configured to intelligently and adaptively evaluate solely internally derived data relative to a basal profile, and to calculate an insulin therapy within the basal profile, such that the host's glucose is substantially maintained within a target range over a period of hours, days or weeks, with the exception of expected increases in glucose associated with meals and the like. In general, the target range is a range of euglycemic glucose concentrations. Two exemplary target ranges are glucose concentrations from about 80 mg/dl to about 140 mg/dl and from about 100-mg-dl to about 160 mg/dl. Dynamic basal controller modules are described in greater detail in the section entitled “Dynamic Basal Controller Module,” and, for example, with reference to FIG. **16**.

(154) In some embodiments, the fully automated integrated system is configured to continuously (e.g., intermittently, iteratively, periodically, or automatically) adaptively monitor and evaluate the host's metabolic profile and to determine (e.g., calculate) an insulin therapy. As is known to one skilled in the art, the host's metabolic profile can fluctuate over a period of days or weeks, depending upon the host's activity level and state of health, the types of foods the host is consuming, medications, and the like. Preferably, the controller module (e.g., on/off, basal and/or bolus controller modules) is configured to adaptively and intelligently adjust one or more system parameters (e.g., glucose boundary, basal profile, bolus constraint, insulin delivery rate, and the like) in response to internally derived data and the host's metabolic profile. While not wishing to be bound by theory, it is believed that configuring the fully automated integrated system to adaptively

monitor and evaluate the user's metabolic profile promotes optimal insulin dosing, improves system accuracy and reduces the number of host hypoglycemic episodes, which ultimately promotes improved host health and safety.

(155) Single Point Glucose Monitor

(156) In the illustrated embodiments (FIGS. 5 to 8), the single point glucose monitor includes a meter for measuring glucose within a biological sample including a sensing region that has a sensing membrane impregnated with an enzyme, similar to the sensing membrane described with reference to U.S. Pat. Nos. 4,994,167 and 4,757,022, each which is incorporated herein in its entirety by reference. However, in alternative embodiments, the single point glucose monitor can use other measurement techniques such as conventional finger stick/test strip meters, optical devices, and the like. It is noted that the meter is optional in that a separate meter can be used and the glucose data downloaded or input by a user into the receiver. However the illustrated embodiments show an integrated system that exploits the advantages associated with integration of the single point glucose monitor with the receiver **14** and delivery device **16**.

(157) FIGS. 5 to 8 are perspective views of integrated receivers including a single point glucose monitor. It is noted that the integrated single point glucose monitor can be integral with, detachably connected to, and/or operably connected (wired or wireless) to the receiver **14** and medicament delivery device **16**. The single point glucose monitor **18** integrates rapid and accurate measurement of the amount of glucose in a biological fluid and its associated processing with the calibration, validation, other processes associated with the continuous receiver **14**, such as described in more detail with reference to U.S. Patent Publication No. US-2005-0154271-A1 which is incorporated herein by reference in its entirety.

(158) In the illustrated embodiments, the single point glucose monitor **18**, such as described in the above-cited U.S. Patent Publication No. US-2005-0154271-A1, includes a body **62** that houses a sensing region **64**, which includes a sensing membrane located within a port. A shuttle mechanism **66** can be provided that preferably feeds a single-use disposable bioprotective film that can be placed over the sensing region **64** to provide protection from contamination. The sensing region includes electrodes, the top ends of which are in contact with an electrolyte phase (not shown), which is a free-flowing fluid phase disposed between the sensing membrane and the electrodes. The sensing region measures glucose in the biological sample in a manner such as described in more detail above, with reference the continuous glucose sensor, and as described in U.S. Pat. Nos. 4,994,167 and 4,757,022. The similarity of the measurement technologies used for the continuous glucose sensor and the single point glucose sensor provides an internal control that creates increased reliability by nature of consistency and decreased error potential that can otherwise be increased due to combining dissimilar measurement techniques. Additionally, the disclosed sensing membrane is known to provide longevity, repeatability, and cost effectiveness, for example as compared to single use strips, or the like. However, other single point glucose monitors can be used with the preferred embodiments.

(159) In one alternative embodiment, the single point glucose monitor comprises an integrated lancing and measurement device such as described in U.S. Pat. No. 6,607,658. In another alternative embodiment, the single point glucose monitor comprises a near infrared device such as described in U.S. Pat. No. 5,068,536. In another alternative embodiment, the single point glucose monitor comprises a reflectance reading apparatus such as described in U.S. Pat. No. 5,426,032. In another alternative embodiment, the single point glucose monitor comprises a spectroscopic transfectance device such as described in U.S. Pat. No. 6,309,884. Each of the above patents and patent applications is incorporated in its entirety herein by reference.

(160) In some embodiments, the single point glucose meter further comprises a user interface that includes a display **72** and a button **74**; however, some embodiments utilize the display **48** and buttons **50** of the receiver **14** rather than providing a separate user interface for the monitor **18**. In some embodiments the single point glucose monitor measured glucose concentration, prompts,

and/or messages can be displayed on the user interface **48** or **72** to guide the user through the calibration and sample measurement procedures, or the like. In addition, prompts can be displayed to inform the user about necessary maintenance procedures, such as “Replace Sensor” or “Replace Battery.” The button **74** preferably initiates the operation and calibration sequences. The button can be used to refresh, calibrate, or otherwise interface with the single point glucose monitor **18** as is appreciated by one skilled in the art.

(161) Integrated Electronics

(162) FIG. **9** is a block diagram that illustrates integrated system electronics in one embodiment. One embodiment is described wherein the processor module within the receiver performs much of the processing, however it is understood that all or some of the programming and processing described herein can be accomplished within the continuous glucose sensor, the receiver, the single point glucose monitor, and/or the delivery device, or any combination thereof. Similarly, displays, alarms, and other user interface functions can be incorporated into any of the individual components of the integrated delivery device.

(163) A quartz crystal **76** is operably connected to an RF module **78** that together function to receive and synchronize data streams via an antenna **80** (for example, transmission **40** from the RF module **44** shown in FIG. **3**). Once received, a processor module **82** processes the signals, such as described below. However, other methods of wired or wireless communication can be substituted for the RF communication described herein.

(164) The processor module **82** is the central control unit that provides the processing for the receiver, such as storing data, analyzing continuous glucose sensor data stream, analyzing single point glucose values, accuracy checking, checking clinical acceptability, calibrating sensor data, downloading data, recommending therapy instructions, calculating medicament delivery amount, type and time, learning individual metabolic patterns, and controlling the user interface by providing prompts, messages, warnings and alarms, or the like. The processor module **82** can include all or part of the controller module, as described elsewhere herein, and with reference to FIGS. **13** to **17**, for example. The processor module **82** can include hardware and software that performs the processing described herein, including for example, read only memory **84** (ROM), such as flash memory, provides permanent or semi-permanent storage of data, storing data such as sensor ID, receiver ID, and programming to process data streams (for example, programming for performing estimation and other algorithms described elsewhere herein), and random access memory **88** (RAM) stores the system's cache memory and is helpful in data processing. For example, the RAM **88** stores information from the continuous glucose sensor, delivery device, and/or single point glucose monitor for later recall by the user or a doctor; a user or doctor can transcribe the stored information at a later time to determine compliance with the medical regimen or evaluation of glucose response to medication administration (for example, this can be accomplished by downloading the information through the pc com port **90**). In addition, the RAM **88** can also store updated program instructions and/or host specific information. FIGS. **10** and **11** describe more detail about programming that is preferably processed by the processor module **82**. In some alternative embodiments, memory storage components comparable to ROM and RAM can be used instead of or in addition to the preferred hardware, such as SRAM, EEPROM, dynamic RAM, non-static RAM, rewritable ROMs, flash memory, or the like.

(165) In some embodiments, the processor module **82** monitors the internally derived data (e.g., the continuous glucose sensor data stream) **40** to determine a preferable time for capturing glucose concentration values using the single point glucose monitor electronics **116** for calibration of the continuous sensor data stream. For example, when sensor glucose data (for example, observed from the data stream) changes too rapidly, a single point glucose monitor reading may not be sufficiently reliable for calibration during unstable glucose changes in the host; in contrast, when sensor glucose data are relatively stable (for example, relatively low rate of change), a single point glucose monitor reading can be taken for a reliable calibration. In some additional embodiments, the

processor module can prompt the user via the user interface to obtain a single point glucose value for calibration at predetermined intervals. In some additional embodiments, the user interface can prompt the user to obtain a single point glucose monitor value for calibration based upon certain events, such as meals, exercise, large excursions in glucose levels, faulty or interrupted data readings, or the like. In some embodiments, certain acceptability parameters can be set for reference values received from the single point glucose monitor. For example, in one embodiment, the receiver only accepts reference glucose data between about 40 and about 400 mg/dL.

(166) In some embodiments, the processor module **82** monitors the internally derived data, such as but not limited to the continuous glucose sensor data stream, to determine a preferable time for medicament delivery, including type, amount, and time. In some embodiments, the processor module is programmed to detect impending clinical risk and can request data input, a reference glucose value from the single point glucose monitor, or the like, in order to confirm a therapy recommendation. In some embodiments, the processor module is programmed to process internally derived data and medicament therapies to adaptive adjust to an individual's metabolic patterns. In some embodiments, the processor module is programmed to project glucose trends based on data from the integrated system (for example, medicament delivery information, user input, or the like). In some embodiments, the processor module is programmed to calibrate the continuous glucose sensor based on the integrated single point glucose monitor. Numerous other programming can be incorporated into the processor module, as is appreciated by one skilled in the art, as is described in cited patents and patent applications here, and as is described with reference to flowcharts of FIGS. **10** to **12**.

(167) It is noted that one advantage of integrated system of the preferred embodiments can be seen in the time stamp of the sensor glucose data, medicament delivery data, and reference glucose data. Namely, typical implementations of the continuous glucose sensor **12**, wherein the medicament delivery **16** and/or single point glucose monitor **18** is not integral with the receiver **14**, the reference glucose data or medicament delivery data can be obtained at a time that is different from the time that the data is input into the receiver **14**. Thus, the user may not accurately input the “time stamp” of the delivery or, for example, the time or obtaining reference glucose value or administering the medicament, at the time of reference data input into the receiver. Therefore, the accuracy of the calibration of the continuous sensor, prediction of glucose values, therapy recommendations, and other processing is subject to human error (for example, due to inconsistencies in entering the actual time of the single point glucose test). In contrast, the preferred embodiments of the integrated system advantageously do not suffer from this potential inaccuracy when the time stamp is automatically and accurately obtained at the time of the event. Additionally, the processes of obtaining reference data and administering the medicament can be simplified and made convenient using the integrated receiver because of fewer loose parts (for example, cable, test strips, etc.) and less required manual data entry.

(168) A battery **92** is operably connected to the processor module **82** and provides power for the receiver. In one embodiment, the battery is a standard AAA alkaline battery, however any appropriately sized and powered battery can be used. In some embodiments, a plurality of batteries can be used to power the system. In some embodiments, a power port (not shown) is provided permit recharging of rechargeable batteries. A quartz crystal **94** is operably connected to the processor module **168** and maintains system time for the computer system as a whole.

(169) A PC communication (com) port **90** can be provided to enable communication with systems, for example, a serial communications port, allows for communicating with another computer system (for example, PC, PDA, server, and the like). In one exemplary embodiment, the receiver is able to download historical data to a physician's PC for retrospective analysis by the physician. The PC communication port **90** can also be used to interface with other medical devices, for example pacemakers, implanted analyte sensor patches, infusion devices, telemetry devices, and the like.

(170) A user interface **96** comprises a keyboard **98**, speaker **100**, vibrator **102**, backlight **104**, liquid

crystal display (LCD) **106**, one or more buttons **108**, and/or a scroll wheel (not shown). The components that comprise the user interface **96** provide controls to interact with the user. The keyboard **98** can allow, for example, input of user information about himself/herself, such as mealtime, exercise, insulin administration, and reference glucose values. The speaker **100** can provide, for example, audible signals or alerts for conditions such as present and/or predicted hyper- and hypoglycemic conditions. The vibrator **102** can provide, for example, tactile signals or alerts for reasons such as described with reference to the speaker, above. The backlight **104** can be provided, for example, to aid the user in reading the LCD in low light conditions. The LCD **106** can be provided, for example, to provide the user with visual data output. In some embodiments, the LCD is a touch-activated screen. The buttons **108** can provide for toggle, menu selection, option selection, mode selection, and reset, for example. In some alternative embodiments, a microphone can be provided to allow for voice-activated control.

(171) The user interface **96**, which is operably connected to the processor module **82**, serves to provide data input and output for both the continuous glucose sensor, delivery mechanism, and/or for the single point glucose monitor. Data output includes a numeric estimated analyte value, an indication of directional trend of analyte concentration, a graphical representation of the measured analyte data over a period of time, alarms/alerts, therapy recommendations, actual therapy administered, event markers, and the like. In some embodiments, the integrated electronics are configured to display a representation of a target glucose value or target glucose range on the user interface. Some additional data representations are disclosed in U.S. Patent Publication No. US-2005-0203360-A1, which is incorporated herein by reference in its entirety.

(172) In some embodiments, prompts or messages can be displayed on the user interface to guide the user through the initial calibration and sample measurement procedures for the single point glucose monitor. Additionally, prompts can be displayed to inform the user about necessary maintenance procedures, such as “Replace Sensing Membrane” or “Replace Battery.” Even more, the glucose concentration value measured from the single point glucose monitor can be individually displayed.

(173) In some embodiments, prompts or messages can be displayed on the user interface to convey information to the user, such as malfunction, outlier values, missed data transmissions, or the like, for the continuous glucose sensor. Additionally, prompts can be displayed to guide the user through calibration of the continuous glucose sensor. Even more, calibrated sensor glucose data can be displayed, which is described in more detail with reference to U.S. Patent Publication No. US-2005-0027463-A1 and U.S. Patent Publication No. US-2005-0203360-A1, each of which is incorporated herein by reference in its entirety.

(174) In some embodiments, prompts or messages about the medicament delivery device can be displayed on the user interface to inform or confirm to the user type, amount, and time of medicament delivery. In some embodiments, the user interface provides historical data and analytes pattern information about the medicament delivery, and the host's metabolic response to that delivery, which may be useful to a host or doctor in determining the level of effect of various medicaments.

(175) Electronics **110** associated with the delivery device **16** (namely, the semi-automated and automated delivery devices) are operably connected to the processor module **82** and include a processor module **112** for processing data associated with the delivery device **16** and include at least a wired or wireless connection (for example, RF module) **114** for transmission of data between the processor module **82** of the receiver **14** and the processor module **112** of the delivery device **16**. Other electronics associated with any of the delivery devices cited herein, or other known delivery devices, may be implemented with the delivery device electronics **110** described herein, as is appreciated by one skilled in the art.

(176) In some embodiments, the processor module **112** comprises programming for processing the delivery information in combination with the internally derived data (e.g., continuous sensor

information). In some embodiments, the processor module **112** includes all or part of the controller module, as described elsewhere herein. In some alternative embodiments, the processor module **82** comprises programming for processing the delivery information in combination with the internally derived data. In some embodiments, both processor modules **82** and **112** mutually process information related to each component.

(177) In some embodiments, the medicament delivery device **16** further includes a user interface (not shown), which may include a display and/or buttons, for example. U.S. Pat. Nos. 6,192,891, 5,536,249, and 6,471,689 describe some examples of incorporation of a user interface into a medicament delivery device, as is appreciated by one skilled in the art.

(178) Electronics **116** associated with the single point glucose monitor **18** are operably connected to the processor module **120** and include a potentiostat **118** in one embodiment that measures a current flow produced at the working electrode when a biological sample is placed on the sensing membrane, such as described above. The current is then converted into an analog signal by a current to voltage converter, which can be inverted, level-shifted, and sent to an A/D converter. The processor module can set the analog gain via a control port (not shown). The A/D converter is preferably activated at one-second intervals. The processor module evaluates the converter output with any number of pattern recognition algorithms known to those skilled in the art until a glucose peak is identified. A timer is then preferably activated for about 30 seconds at the end of which time the difference between the first and last electrode current values is calculated. This difference is then divided by the value stored in the memory during instrument calibration and is then multiplied by the calibration glucose concentration. The glucose value in milligram per deciliter, millimoles per liter, or the like, is then stored in the processor module, displayed on the user interface, used to calibrate of the glucose sensor data stream, downloaded, etc.

(179) Programming and Processing

(180) FIG. **10** is a flow chart that illustrates the process **130** of validating therapy instructions prior to medicament delivery in one embodiment. In some embodiments, the therapy recommendations include a suggestion on the user interface of time, amount, and type of medicament to delivery. In some embodiments, therapy instructions include calculating a time, amount, and/or type of medicament delivery to administer, and optionally transmitting those instructions to the delivery device. In some embodiments, therapy instructions include that portion of a closed loop system wherein the determination and delivery of medicament is accomplished, as is appreciated by one skilled in the art.

(181) Although computing and processing of data is increasingly complex and reliable, there are circumstances by which the therapy recommendations necessitate human intervention. Some examples include when a user is about to alter his/her metabolic state, for example due to behavior such as exercise, meal, pending manual medicament delivery, or the like. In such examples, the therapy recommendations determined by the programming may not have considered present or upcoming behavior, which may change the recommended therapy. Numerous such circumstances can be contrived; suffice it to say that a validation may be advantageous in order to ensure that therapy recommendations are appropriately administered.

(182) At block **132**, a sensor data receiving module, also referred to as the sensor data module, receives sensor data (e.g., a data stream), including one or more time-spaced sensor data points, from a sensor via the receiver, which may be in wired or wireless communication with the sensor. The sensor data point(s) may be raw or smoothed, such as described in U.S. Patent Publication No. US-2005-0043598-A1 which is incorporated herein by reference in its entirety.

(183) At block **134**, a medicament calculation module, which is a part of a processor module, calculates a recommended medicament therapy based on the received sensor data. A variety of algorithms may be used to calculate a recommended therapy as is appreciated by one skilled in the art.

(184) At block **136**, a validation module, which is a part of the processor module, optionally

validates the recommended therapy. The validation may include a request from the user, or from another component of the integrated system **10**, for additional data to ensure safe and accurate medicament recommendation or delivery. In some embodiments, the validation requests and/or considers additional input, such as time of day, meals, sleep, calories, exercise, sickness, or the like. In some embodiments, the validation module is configured to request this information from the user. In some embodiments, the validation module is responsive to a user inputting such information.

(185) In some embodiments, when the integrated system **10** is in fully automated mode, the validation module is triggered when a potential risk is evaluated. For example, when a clinically risky discrepancy is evaluated, when the acceleration of the glucose value is changing or is low (indicative of a significant change in glucose trend), when it is near a normal meal, exercise or sleep time, when a medicament delivery is expected based on an individual's dosing patterns, and/or a variety of other such situations, wherein outside influences (meal time, exercise, regular medicament delivery, or the like) may deem consideration in the therapy instructions. These conditions for triggering the validation module may be pre-programmed and/or may be learned over time, for example, as the processor module monitors and patterns an individual's behavior patterns.

(186) In some embodiments, when the integrated system **10** is in semi-automated mode, the system may be programmed to request additional information from the user regarding outside influences unknown to the integrated system prior to validation. For example, exercise, food or medicament intake, rest, or the like may input into the receiver for incorporation into a parameter of the programming (algorithms) that processing the therapy recommendations.

(187) At block **138**, the receiver confirms and sends (for example, displays, transmits and/or delivers) the therapy recommendations. In manual integrations, the receiver may simply confirm and display the recommended therapy, for example. In semi-automated integrations, the receiver may confirm, transmit, and optionally delivery instructions to the delivery device regarding the recommended therapy, for example. In automated integrations the receiver may confirm and ensure the delivery of the recommended therapy, for example. It is noted that these examples are not meant to be limiting and there are a variety of methods by which the receiver may confirm, display, transmit, and/or deliver the recommended therapy within the scope of the preferred embodiments.

(188) FIG. **11** is a flow chart **140** that illustrates the process of providing adaptive metabolic control using an integrated system in one embodiment. In this embodiment, the integrated system is programmed to learn the patterns of the individual's metabolisms, including metabolic response to medicament delivery.

(189) At block **142**, a medicament data receiving module, which may be programmed within the receiver **14** and/or medicament delivery device **16**, receives medicament delivery data, including time, amount, and/or type. In some embodiments, the user is prompted to input medicament delivery information into the user interface. In some embodiments, the medicament delivery device **16** sends the medicament delivery data to the medicament data-receiving module.

(190) At block **144**, a sensor data receiving module, also referred to as the sensor data module, receives sensor data (e.g., a data stream), including one or more time-spaced sensor data points, from a sensor via the receiver, which may be in wired or wireless communication with the sensor.

(191) At block **146**, the processor module, which may be programmed into the receiver **14** and/or the delivery device **16** is programmed to monitor the sensor data from the sensor data module **142** and medicament delivery from the medicament delivery module **144** to determine an individual's metabolic profile, including their response to various times, amounts, and/or types of medicaments. The processor module uses any pattern recognition-type algorithm as is appreciated by one skilled in the art to quantify the individual's metabolic profile.

(192) At block **148**, a medicament calculation module, which is a part of a processor module, calculates the recommended medicament based on the sensor glucose data, medicament delivery

data, and/or individual's metabolic profile. In some embodiments, the recommended therapy is validated such as described with reference to FIG. 10 above. In some embodiments, the recommended therapy is manually, semi-automatically, or automatically delivered to the host.

(193) At block 150, the process of monitoring and evaluation a host's metabolic profile is repeated with new medicament delivery data, wherein the processor monitors the sensor data with the associated medicament delivery data to determine the individual's metabolic response in order to adaptively adjust, if necessary, to newly determined metabolic profile or patterns. This process may be continuous throughout the life of the integrated system, may be initiated based on conditions met by the continuous glucose sensor, may be triggered by a host or doctor, or may be provided during a start-up or learning phase.

(194) While not wishing to be bound by theory, it is believed that by adaptively adjusting the medicament delivery based on an individual's metabolic profile, including response to medicaments, improved long-term host care and overall health can be achieved.

(195) FIG. 12 is a flow chart 152 that illustrates the process of glucose signal estimation using the integrated sensor and medicament delivery device in one embodiment. It is noted that glucose estimation and/or prediction are described in U.S. Patent Publication No. US-2005-0027463-A1 and U.S. Patent Publication No. US-2005-0203360-A1, each of which has been incorporated herein by reference in its entirety. However, the preferred embodiments described herein, further incorporated additional data of medicament delivery in estimating or predicting glucose trends.

(196) At block 154, a sensor data receiving module, also referred to as the sensor data module, receives sensor data (e.g., a data stream), including one or more time-spaced sensor data points, from a sensor via the receiver, which may be in wired or wireless communication with the sensor.

(197) At block 156, the medicament data receiving module, which may be programmed within the receiver 14 and/or medicament delivery device 16, receives medicament delivery data, including time, amount, and/or type.

(198) At block 158, the processor module evaluates medicament delivery data with substantially time corresponding glucose sensor data to determine individual metabolic patterns associated with medicament delivery. "Substantially time corresponding data" refers to that time period during which the medicament is delivered and its period of release in the host.

(199) At block 160, the processor module estimates glucose values responsive to individual metabolic patterns associated with the medicament delivery. Namely, the individual metabolic patterns associated with the medicament delivery are incorporated into the algorithms that estimate present and future glucose values, which are believed to increase accuracy of long-term glucose estimation.

(200) FIG. 13 is a flow chart 200 that illustrates the process of determining medicament delivery using an integrated system 10, in one embodiment. In preferred embodiments, medicament (e.g., insulin or another drug) delivery is calculated to maintain the host substantially at and/or within a target range. In the case of insulin therapy, the target range is generally a range of preferred glucose concentrations within which the host is to maintain (at least to try) his blood sugar, as is discussed below. For example, in some circumstances, the target range is a range of euglycemic glucose concentrations. As is understood by those skilled in the art, glycemic ranges can vary, depending upon the therapy goals and the morbidity/mortality associated with a given glucose level (e.g., concentration). For example, according to the American Diabetes Association, a preferred target range is a euglycemic range that provides tight glucose control and substantially reduces diabetic morbidity and mortality, namely a fasting glucose of from 90 mg/dl to 130 mg/dl. Alternative target ranges can be used, such as from about 70, 80, 90, 100, 110 or 120 mg/dl to about 110, 120, 130, 140, 150 or 160 mg/dl or more. In some circumstances, the target range can be very wide (e.g., from about 80 mg/dl to about 160 mg/dl) or very narrow (e.g., 90 mg/dl to 120 mg/dl) or even a single glucose concentration. In some embodiments, the host and/or his health care professional select a target range. In some embodiments, the target range is programmable (e.g., pre-

programmable, re-programmable), such as by the host, a caretaker of the host or the manufacturer. In some embodiments, the integrated system includes two or more target ranges. In some embodiments, the controller module is configured to adaptively/intelligently program (e.g., re-program) the target range, such as after evaluation of the internally derived data and the host's metabolic response to insulin therapy.

(201) At block **202**, the processor module is configured to receive and process internally derived data. Internally derived data can include but it not limited to continuous glucose sensor data, continuous glucose processed sensor data, auxiliary sensor data, processed auxiliary sensor data, delivery device data and processed delivery device data, including glucose concentration, glucose concentration range, change in glucose concentration, glucose concentration rate of change, acceleration of the glucose concentration rate of change, host insulin sensitivity, change in host insulin sensitivity, host metabolic response to insulin therapy, amount of insulin delivered, time of insulin delivery, insulin on board, time, acceleration, host activity level, pressure, a pH, a temperature, an oxygen level, the level of an analyte other than glucose, a proximity and orientation. In some embodiments, internally derived data can include data derived from algorithmic processing of continuous analyte sensor data and/or auxiliary sensor data and/or medicament delivery device data. In some embodiments, the system is configured to further received external data (e.g., meal occurrence/content, exercise, units of insulin delivered, time of insulin delivery, etc.) such as for historical purposes (e.g., as a diary or log).

(202) At block **204**, the system is configured to calculate (e.g., determine) a medicament therapy (e.g., insulin therapy) based solely on internally derived data and any constraint (e.g., range, boundary, profile and the like). In general, calculation of the medicament therapy is conducted by the system's controller module (e.g., on/off, dynamic basal and/or dynamic bolus controller module), as described elsewhere herein. In some embodiments, evaluation and calculation is iterative. In some embodiments, the calculated insulin therapy includes an instruction for delivery of the insulin therapy to the host.

(203) At block **206**, the system is optionally configured to validate the calculated therapy based on patient (e.g., host) input. For example, in some embodiments, the host must accept the calculated medicament therapy before the system can proceed to providing (e.g., delivering) the medicament therapy at block **208**, and the system can return to block **202**. If the host accepts calculated the medicament therapy (e.g., the dose is validated), the medicament therapy will be provided/delivered. Similarly, if the host does not accept the medicament therapy, no medicament will be given. In some embodiments, the system is configured such that the host can command the system to provide a manually calculated dose (e.g., calculated by the host). In some embodiments, the system is further configured to allow the system to adaptively and intelligently determine an appropriate and/or optimal delivery schedule for the commanded manually calculated dose.

(204) At block **208**, the system is configured to deliver the calculated insulin therapy, as described elsewhere herein. In some embodiments, the insulin delivery device is configured to deliver the calculated insulin therapy automatically upon receipt of an instruction from the controller module. After delivering the insulin therapy, the system is configured to return to block **202**.

(205) FIG. **14** is a flow chart **204** that illustrates calculation of a medicament therapy based on the internally derived data, in one embodiment. Generally, the system **10** is configured to use at least one controller module (all or in part) to calculate the insulin therapy, such as but not limited to an on/off controller module **210**, a dynamic basal controller module **212** and a dynamic bolus controller module **214**. In some embodiments, the system is configured with only one controller module. In other embodiments, the system is configured with two or all three of the controller modules. In one embodiment, the system includes two or more controller modules configured to work in concert (e.g., in conjunction, together, in combination). In some embodiments, the controller module is configured to provide all or some of the processing for block **204** of FIG. **13**. The controller module can be incorporated into any portion of the integrated system, such as but

not limited to the receiver, the medicament delivery device, a component separate from the receiver and the delivery device, or a combination thereof (e.g., integrated electronics, such as a processor module). In some embodiments, a controller module is included in processor module **82** and/or in processor module **112**.

(206) On/Off Controller Module

(207) FIG. **15** is a flow chart that illustrates an on/off controller module **210**, in one embodiment.

(208) At block **216**, the on/off controller module is configured to intelligently, adaptively and iteratively evaluate the internally derived data (e.g., raw and/or processed glucose sensor data) relative to a target range and/or a glucose boundary. In some embodiments, a glucose boundary is a host glucose concentration at which the system is configured to deliver insulin. In some embodiments, the target range and the glucose boundary are associated with each other. For example, the glucose boundary can be the upper limit of the target range. In some embodiments, the host does not validate either data or a calculated medicament therapy. In preferred embodiments, the system includes a continuous analyte sensor, and can include one or more auxiliary sensors, such as described elsewhere herein. In some embodiments, the glucose boundary can be programmable, such as by the host, a caretaker of the host and/or the manufacturer. In some embodiments, the glucose boundary is programmable by an intelligent/adaptive controller module.

(209) At block **218**, the on/off controller module is configured to actuate medicament delivery, such as by selecting between on and off instructions. The point at which the selection is made can be referred to as a setpoint. In some embodiments, the set point is the glucose boundary. In one exemplary embodiment, the system includes programming to select between the on and off instructions. When evaluation of the internally derived data indicates that the host's glucose is (or has) surpassing (or surpassed) a glucose boundary, the controller module selects the on instruction, which directs actuation of the insulin delivery device (e.g., turns on delivery). Conversely, when the host's glucose falls below a glucose boundary (as determined by evaluation of the internally derived data), the off instruction is selected and insulin delivery is terminated (e.g., turned off). In preferred embodiments, the insulin will be delivered at a programmable rate, which can be programmed by the host, a caretaker of the host, or the manufacturer, for example. In some embodiments, the on/off controller can include more than one setpoint, such as but not limited to a first set point to select the on instruction and a second setpoint to select the off instruction.

(210) In some embodiments, the on/off controller module is configured to adjust the insulin delivery rate in response to evaluation of internally derived data and the host's metabolic response to insulin delivery (e.g., metabolic state). For example, the insulin can be delivered at relatively faster or slower rates, depending upon the evaluation of the internal data. In some circumstances, when the on instruction is selected, the medicament can be delivered substantially continuously and/or intermittently, such as but not limited to at a single rate (e.g., about 0.05 U, 0.1 U, 0.2 U, 0.3 U, 0.4 U, 0.5 U, 0.6 U, 0.7 U, 0.8 U or 0.9 U per hour or more).

(211) In one exemplary embodiment, the integrated system **10** includes an on/off controller module configured to intelligently and adaptively evaluate the internally derived data relative to a programmed glucose boundary and then select between the on and off instructions. For example, if the glucose boundary is 140 mg/dl, then the controller module evaluates the internally derived data against the 140 mg/dl glucose boundary (block **216**). If the host's glucose is above the 140 mg/dl glucose boundary, then the controller module selects the on instruction, which leads to actuation of insulin delivery at box **218**. If the host's glucose is above the 140 mg/dl glucose boundary and insulin is currently being delivered (e.g., the on instruction was selected at an earlier time), then the controller module does nothing (e.g., insulin continues to be delivered). If the host's glucose is 140 mg/dl or less, the off instruction is selected (or the on instruction is de-selected/terminated), whereby insulin delivery is ceased. In some embodiments, the insulin is delivered (e.g., infused) substantially continuously, such as at a given rate (e.g., U/min), or substantially intermittently, such as small volumes every few minutes (e.g., 0.5-U every 6-minutes). In preferred embodiments, the

system is configured, such that data evaluation and/or insulin delivery are iterative (e.g., cyclic, periodic, continuous, automatic, and the like). Because the system is configured to function intelligently and adaptively, in some embodiments, the system can modify (e.g., adjust, either with or without host validation) the glucose boundary and/or the insulin infusion rate, such that maintenance of the host within the target range is optimized.

(212) In another exemplary embodiment, the system **10** includes an on/off controller module configured for use in combination with flash insulin. The flash insulin therapy can be delivered automatically, periodically, intermittently and/or substantially continually, in response to the on/off controller, such that the host is maintained substantially at and/or within the target range. For example, in some embodiments, the system is configured to intermittently deliver small doses of flash insulin when (while) the host's glucose is above the glucose boundary. The rate of flash insulin delivery is programmed such that when the host's glucose is rising and surpasses the glucose boundary, the on instruction is selected and a small amount of flash insulin is delivered. After delivery, the controller module can be configured to wait a brief period (e.g., a few minutes), and then evaluate the internally derived data relative to the glucose boundary. If the internally derived data indicates that the host's glucose is still above the glucose boundary, then another small dose of flash insulin can be delivered. Alternatively, the system can be configured to wait until the delivered insulin has had a predetermined effect (e.g., time sufficient for the activity of about 50, 60, 70, 80, 90 or 95% of the delivered insulin to peak, or for the activity of about 50, 60, 70, 80, 90 or 95% of the delivered insulin to terminate), prior to returning to block **202** (FIG. **13**). As is appreciated by one skilled in the art, the system can be configured to proceed through several cycles of these steps (e.g., iteratively evaluate and provide insulin doses using the on/off controller module), until the host's glucose level falls to/below the glucose boundary. When the host's glucose level falls to/below the glucose boundary, the on/off controller is configured to select the off instruction, which results in termination of insulin delivery. While not wishing to be bound by theory, it is believed that use of flash insulin in combination with an on/off controller module advantageously substantially prevents stacking of insulin doses and substantially avoids hypoglycemic episodes. Accordingly, improved host health and safety are promoted while diabetic complications are avoided or delayed during the host's lifetime.

(213) In some embodiments, the integrated system is configured arranged for use with other insulins (e.g., regular (e.g., wild type), fast-acting or rapid-acting human insulin analogs, etc.), such that the on/off controller evaluates/tracks "insulin on-board" (e.g., the total amount of active insulin currently in the host's body).

(214) Dynamic Basal Controller Module

(215) As is understood by one skilled in the art, insulin needs vary between individuals and throughout the day, both during and between meals. To take care of between meal glucose fluctuations, diabetic hosts generally employ a basal schedule (e.g., basal profile) for continuous delivery of low levels of insulin, such that, between meals, the host's glucose is relatively steady (e.g., remains within a target (e.g., euglycemic) range). Accordingly, in preferred embodiments, the integrated system **10** includes a dynamic basal controller module configured to iteratively evaluate internally derived data relative to a programmable basal profile and iteratively calculate a dynamic basal insulin therapy within the basal profile.

(216) FIG. **16** is a flow chart that illustrates a dynamic basal controller module **212**, in one embodiment. In preferred embodiments, the dynamic basal controller module can be part of the electronics module and is configured to evaluate internally derived data relative to a basal profile **220** and to intelligently and adaptively calculate a dynamic basal medicament therapy **222**, based on that evaluation. In preferred embodiments, the insulin therapy is determined solely on internally derived data and the basal profile.

(217) A basal profile generally includes a schedule of time blocks, each block being associated with an insulin delivery rate. In general, a diabetic host can determine his basal profile by

experimentation. For example, the basal insulin delivery rate for a particular time period can be determined by fasting while periodically evaluating the glucose level. Neither food nor bolus insulin can be taken for 4-hours prior to or during the evaluation period. If the blood sugar level changes dramatically during evaluation, then the basal rate can be adjusted to increase or decrease insulin delivery to keep the blood sugar level approximately steady. For instance, to determine the host's morning basal requirement, he must skip breakfast. On waking, he would test his glucose level periodically until lunch. Changes in blood glucose level are compensated with adjustments in the morning basal rate. The process is repeated over several days, varying the fasting period, until a 24-hour basal profile (which keeps fasting blood sugar levels relatively steady) has been built up. As used herein, a basal profile includes a schedule of one or more time blocks, wherein each time block is associated with a maximum insulin delivery rate. As is described herein, in some embodiments, the dynamic basal controller module is constrained by the basal profile. Accordingly, in some embodiments, the controller module is configured to evaluate internally derived data (e.g., including re-evaluate internally derived data as it is received) and to iteratively calculate an insulin delivery rate (e.g., insulin therapy) up to the maximum rate of a current time block. Accordingly, the insulin therapy can include a delivery rate less than the maximum insulin delivery rate associated with the current time block. In some embodiments, the basal profile includes a 24-hour schedule. In some embodiments, the schedule can be shorter or longer than 24-hours. In some embodiments, the schedule is repeatable and/or cyclic (e.g., iterative). In some embodiments, the host, a caretaker of the host, and/or the manufacturer can program a basal profile. In some circumstances, an intelligent/adaptive controller module can be configured to program the basal profile.

(218) At block **220**, in preferred embodiments, the dynamic basal controller module is configured to evaluate solely internally derived data (e.g., from an operably connect continuous glucose sensor, from an auxiliary sensor and/or an insulin delivery device) relative to a programmed basal profile. Internally derived data includes but is not limited to glucose concentration, change in concentration, rate of change of concentration, acceleration (or deceleration) of the change, direction of the change, predicted analyte concentration for a future time, estimated analyte concentration, possible variations of analyte data (e.g., based on maximum possible error), trend information and the like. For example, in some circumstances, a low rate of change (in glucose concentration/level) is from about ± 0 mg/dl/min to about 1 mg/dl/min, a moderate rate of change is from about 1 mg/dl/min to about 2 mg/dl/min, and a high rate of change is from about 3 mg/dl/min to about 6 mg/dl/min. In some embodiments, the calculation can include evaluation of the host's metabolic response to insulin therapy, which can depend upon a variety of factors, such as but not limited to the type of insulin delivered, the mode and/or location of delivery, and the like.

(219) In some embodiments, internally derived data can include data received from one or more auxiliary sensors, such as but not limited to sensors for glucose, an analyte other than glucose, pH, temperature, pressure, host movement, host body position, proximity, and the like. For example, an accelerometer can provide data regarding the host's activity level (e.g., sedentary versus exercising versus sleeping), which can affect the host's insulin requirement. In one exemplary embodiment, the dynamic basal controller module is configured to evaluate accelerometer data in conjunction with internally derived data, depending upon if the accelerometer data is within or without a programmed range (e.g., whether or not the host is very active). For example, the system can be configured such that if the accelerometer data is above a setpoint (e.g., indicates that the host is very active or exercising), then the accelerometer data is considered by the controller module; if the accelerometer data is below the set point, the accelerometer is not considered. In one exemplary embodiment, the system is configured such that the basal controller module intelligently monitors the host's activity level (e.g., over a period of days and/or weeks) and adaptively adjusts the basal profile to maintain the host substantially within the target range during both active and inactive periods of the day. For example, in some embodiments, the controller module is configured to

intelligently determine when the host is generally very active (e.g., exercising), less active (e.g., working at the computer) or sedentary (e.g., sleeping). Some hosts will tend to be more active than others. Advantageously, because the controller module responds to changes in the host's metabolic state, each host can have a basal profile optimized to his personal needs.

(220) At block **222**, in some embodiments, the dynamic basal controller module is configured to calculate (e.g., determine) a dynamic basal medicament therapy (also referred to as the “insulin therapy”) based solely on the internally derived data and the basal profile (e.g., the evaluation thereof), wherein the calculated insulin therapy falls within the basal profile. The insulin therapy calculated by the dynamic basal controller module is a rate of insulin delivery less than or equal to the insulin delivery rate associated with the basal profile (e.g., at the current block of time). Preferably, the delivery rate is sufficient to bring the host's glucose concentration substantially within a pre-programmed target range (e.g., a euglycemic range). Over time, the insulin therapy can include a plurality of delivery rates at different time blocks calculated to maintain the host within the target range. In some embodiments, the maximum insulin therapy (e.g., delivery rate) is from about 0.01 U/hour or less to about 6.0 U/hour or more. For example, in some embodiments, the maximum insulin therapy is from about 0.01 U/hr to about 0.2 U/hr. In some embodiments, the maximum insulin therapy is from about 0.21 U/hr to about 0.3 U/hr. In some embodiments, the maximum insulin therapy is from about 0.31 U/hr to about 0.4 U/hr. In some embodiments, the maximum insulin therapy is from about 0.41 U/hr to about 0.5 U/hr. In some embodiments, the maximum insulin therapy is from about 0.51 U/hr to about 1.0 U/hr. In some embodiments, the maximum insulin therapy is about 1.5 U/hr, 2.0 U/hr, 2.5 U/hr, 3.0 U/hr, 3.5 U/hr, 4.0 U/hr, 4.5 U/hr, 5.0 U/hr, or 5.5 U/hr. In preferred embodiments, instructions for delivery of the calculated insulin therapy are sent to the insulin delivery device, which then automatically delivers the instructed insulin therapy. In some embodiments, dynamic basal controller module can include one or more instructions for calculation and/or delivery of the basal insulin therapy. The calculated insulin delivery rate can be an instruction provided to an insulin delivery device to deliver the insulin therapy, such as to automatically deliver the therapy.

(221) In preferred embodiments, the system **10** is configured to iteratively (e.g., cyclic, periodic, and the like) evaluate the internally derived data (e.g., including past and newly/more recently received internally derived data) and to iteratively calculate an insulin delivery rate. Because the system is configured to function intelligently and adaptively, in some embodiments, the system can respond to changes in the host's metabolic state by modifying (e.g., adjusting, programming, re-programming, either with or without host validation) the basal profile, such that maintenance of the host within the selected target range is optimized. In some embodiments, the controller module includes programming to adjust the basal profile in response to internally derived data and the host's metabolic response. In some embodiments, the insulin therapy substantially maintains the host's glucose concentration within the target range without driving the host into a hyper- or hypoglycemic range. In some embodiments, the dynamic basal controller module includes one or more instructions configured to process the internally derived data and iteratively provide the therapy instructions. In a further embodiment, these instructions include instructions for evaluating the internally derived data and calculating the insulin therapy based solely on the internally derived data.

(222) In one exemplary embodiment, the integrated system includes a dynamic basal controller module configured to iteratively (continually, automatically, periodically, or intermittently) evaluate the internally derived data relative to a programmable basal profile and calculate an insulin therapy that falls within the basal profile. For example, if the current time block of the basal profile specifies 2U of insulin per hour, then the controller module can calculate an insulin therapy up to that amount. Preferably, the calculated insulin therapy is optimal for maintaining the host within the selected (e.g., preferred, engaged, programmed) target range. As the system receives additional internal data, it is configured to adjust the insulin delivery rate in an intelligent and

adaptive manner. For example, if the evaluation of currently received internal data indicates that for optimal control (e.g., of blood sugar) the insulin delivery rate should be increased from 0.5 U/hr to 1 U/hr, then the controller module can both send instructions to the integrated insulin delivery device to do so and reprogram the basal profile with the new delivery rate for that time block. In another example, if the evaluation might indicates that the delivery rate should be reduced to maintain optimal control, and then the controller module can calculate a new insulin therapy and instruct the delivery device accordingly. Internally derived data can include trend information, such as but not limited to changes in the host's insulin needs (e.g., response to delivered insulin, insulin sensitivity, or metabolic profile) over time. Accordingly, in preferred embodiments, the dynamic basal controller module is configured to evaluate this trend information and make intelligent adjustments to (e.g., re-program) the insulin therapy and/or the basal profile, such that between meal glucose control can be optimized (e.g., continually). In some embodiments, the system is configured to request validation of such a change (e.g., re-programming) in insulin therapy and/or the basal profile.

(223) In some embodiments, the dynamic basal controller module can be configured to evaluate the internally derived data **220** with respect to one or more target ranges (which can overlap) to intelligently and adaptively direct calculation of the dynamic basal medicament therapy. For example, in one exemplary embodiment, as a first step, the dynamic basal controller module evaluates the internally derived data with respect to glycemic ranges (e.g., hypoglycemic, euglycemic, hyperglycemic or very hyperglycemic). If, for example, the host is euglycemic, a first calculation can be made; if the host is hyperglycemic a second calculation can be made; and if the host is hypoglycemic a third calculation can be made. In some embodiments, the controller evaluates the rate and/or direction of glucose concentration change and/or acceleration of the change (e.g., if glucose concentration has changed, if it is going up or down, if it is changing slowly or rapidly, etc.). For example, if the glucose level is very hyperglycemic and increasing rapidly, a first dynamic basal insulin dose (e.g., dose #1) can be calculated. If the glucose level is very hyperglycemic and decreasing slowly, a second dynamic basal insulin dose (e.g., dose #2), which might be smaller than dose #1, can be calculated. If the glucose level is slightly hyperglycemic and increasing slowly, a third dynamic basal insulin dose (dose #3) can be calculated. Dose #3 may be smaller than both dose #1 and dose #2. If, on the other hand, the glucose level is in the euglycemic range and decreasing slowly, insulin delivery can be terminated (e.g., until the glucose level was again above the euglycemic range). In another example, if the glucose level is in euglycemic range and decreasing rapidly, or in the hypoglycemic range, the controller can be configured to alert the host, such as by an alarm, for example so that he can eat some sugar to raise his glucose level.

(224) In some embodiments, the dynamic basal controller module is configured for use in conjunction with a flash-acting insulin, as described elsewhere herein. In one exemplary embodiment, the onset of activity of the flash insulin is less than about 5-minutes as determined by plasma insulin concentration according to the methods of Frohnauer et al). In some embodiments, the flash insulin's activity peaks within about 10 to 30-minutes. In some embodiments, the flash insulin's duration of activity is about 30-minutes or less and up to about 1-hour. In some embodiments, the flash insulin's activity peaks within about 5-minutes of delivery and terminates within about 10-20 minutes.

(225) In some embodiments, the dynamic basal controller module is configured for use in conjunction with a regular, rapid-acting or fast-acting insulin (including analogs), as described elsewhere herein. In a further embodiment, the dynamic basal controller module is configured to track the amount of insulin "on board" (e.g., the total amount of active insulin currently within the host and the insulin activity associated with that amount), and to evaluate the insulin on board when calculating a dynamic basal therapy.

(226) Dynamic Bolus Controller Module

(227) Conventionally, when a host is going to eat a meal, he calculates a bolus insulin dose that should be sufficient to cover the glucose increase anticipated due to consumption of the meal. He then gives himself the calculated bolus dose and eats the meal. Without careful measurement of carbohydrate and fat content of the meal and the host's insulin sensitivity, the calculated bolus dose can only estimate the amount of insulin to be taken for that meal. Thus, in general, the calculated bolus dose will not be the optimal dose to cover the actual glucose increase that occurs when the meal is eaten. The host's sugar may increase more than he thought it would, in which case the calculated bolus dose could be too small, which could lead to hyperglycemia. Alternatively, the host's sugar might not rise as high as he thought it would, in which case the calculated bolus dose may be too large, and could lead to hypoglycemia. Accordingly, in preferred embodiments, the integrated system **10** includes a dynamic bolus controller module configured to iteratively evaluate internally derived data relative to a programmable bolus constraint and iteratively calculate a dynamic bolus insulin therapy, upon host activation of the programmable bolus constraint.

(228) FIG. **17** is a flow chart illustrating a dynamic bolus controller module **214**, in one embodiment. In preferred embodiments, the dynamic bolus controller module is included in the electronics module and is configured to evaluate an engageable constraint **224** as well as internally derived data **226**. In some embodiments, the dynamic bolus controller module is configured to intelligently provide a dynamic bolus medicament therapy (e.g., insulin therapy) within a pre-set (e.g., programmable) constraint **228**, such as in response to the host engaging the bolus constraint. Preferably, the dynamic bolus controller module is configured to iteratively calculate an insulin therapy based solely on evaluation of internally derived data (e.g., re-evaluation of internally derived data as it is received) and the bolus constraint. In some embodiments, the dynamic bolus controller module **214** allows host validation of the dynamic bolus medicament therapy (e.g., FIG. **13**, box **206**), which is believed to promote increased user confidence, increased host compliance and improved health status. Advantageously, the dynamic bolus controller module **214** can be configured to use a variety of insulins, including but not limited to regular or rapid/quick-acting insulins (e.g., slower onset and peak of activity, longer duration of activity) and flash insulins, described elsewhere herein.

(229) In preferred embodiments, an engageable bolus constraint is associated with a programmable dynamic bolus insulin therapy. In preferred embodiments, the dynamic bolus insulin therapy is the maximum total insulin that can be delivered to the host over a specified period of time, in response to the host engaging (e.g., selecting) the bolus constraint associated with the insulin therapy. In some embodiments, the insulin therapy comprises one or more portions of the maximum total insulin dose, as described below. In some embodiments, the bolus constraint can be programmed (e.g., pre-programmed and/or pre-set), programmable and/or re-programmable. In some embodiments, the host and/or a caretaker of the host can program the bolus constraint. In some embodiments, the bolus constraint can be programmed by the manufacturer or the dynamic bolus controller module.

(230) At block **224**, the dynamic bolus controller module is configured to evaluate a bolus constraint (e.g., engageable/selectable, and programmable, re-programmable and/or pre-set limit), such as one that has been engaged by the host. In general, a bolus constraint is associated with an insulin therapy that has been calculated and/or estimated to be sufficient to cover an average expected rise in blood sugar, such as an increase in glucose that occurs (on average) when a host eats a given meal, such as but not limited to breakfast, lunch, dinner and the like. For example, on most days, the host may eat very similar breakfasts (e.g., an average (e.g., usual) breakfast), which can cause very similar glucose increases (e.g., an average increase in glucose). Accordingly, a "breakfast" bolus constraint can be calculated to cover the average rise in glucose associated with an average breakfast. In some embodiments, a bolus constraint can be associated with a host activity (e.g., to cover the glucose rise associated with host performance of about 30-minutes of vigorous exercise) or condition (e.g., a corrective bolus for when the insulin delivered is

insufficient to cover an actual rise in glucose). In preferred embodiments, the system includes one or more selectable bolus constraints. The constraints can be selected by any means known in the art, such as by pushing a pre-programmed push-button or scrolling through a menu of selectable constraints with a slider or a scroll wheel.

(231) In some embodiments, the controller module is configured (e.g., includes programming) to intelligently evaluate the internally derived data and the host's metabolic response to insulin therapy, and to adjust the bolus constraint based on that evaluation. Advantageously, a calculated insulin therapy is based on internally derived data, an engaged bolus constraint and the host's metabolic response to insulin therapy, which enables the system to optimize the insulin therapy to the host, who's metabolic response varies over time, depending upon a variety of factors, such as but not limited to changes in the host's activity level, dietary changes, medications (e.g., insulin-sensitizing agents, new insulin type), and the like. Depending upon the circumstances, the controller module can re-program a bolus constraint by adjusting the rate of insulin delivery, the amount of insulin that can be delivered and/or the time period over which the insulin can be delivered.

(232) At block **226**, in preferred embodiments, the dynamic bolus controller module is configured to evaluate the internally derived data. The internally derived data is evaluated in the context of (e.g., relative to) a selected bolus constraint and in response to selection (activation, engagement) of the bolus constraint. Returning to the example of the "Breakfast" bolus constraint, in general, the host will engage the breakfast bolus constraint (e.g., by pressing a pre-programmed button that is labeled "Breakfast") at the beginning of a breakfast meal. In general, as the host consumes his breakfast, his glucose will begin to change (e.g., rise), which the integrated system's continuous glucose sensor detects (e.g., measures, senses). Internally derived data will be generated as the system's continuous glucose sensor monitors the changes in the host's glucose level. The dynamic bolus controller module evaluates the sensor data (e.g., internally derived data) against (e.g., in the context of, relative to) the engaged breakfast constraint.

(233) At block **228**, the dynamic bolus controller module calculates a dynamic bolus medicament (e.g., insulin) therapy within the selected bolus constraint. Preferably, the dynamic bolus controller module adaptively determines a substantially optimal insulin therapy, such as for example, delivery of all or a portion (e.g., in one large dose or a plurality of smaller doses) of the maximum total insulin dose (associated with the engaged constraint) over the specified time period. For example, if the breakfast constraint is associated with a maximum of 10 U of insulin to be delivered over 30-minutes, then, when the host engages the breakfast constraint, the controller module evaluates the internally derived data and determines an insulin therapy (including instructions sent to the insulin delivery device, which automatically delivers the instructed insulin therapy). For example, in some circumstances, the calculated insulin therapy can include delivery of the entire total dose (e.g., 10 U) within the specified 30-minutes (or a shorter length of time). In other circumstances, the calculated insulin therapy can include dividing the total insulin therapy into two or more partial (e.g., smaller) doses, some or all of which can be delivered over the 30-minute period. Delivery of a partial dose depends upon the controller module's evaluation of internally derived data. For example, as the 30-minutes progress, the controller module continually (e.g., continuously, iteratively, intermittently, automatically) receives and iteratively re-evaluates internally derived data (e.g., as it becomes available) and determines, based thereon, if additional partial doses are needed to handle the rise (e.g., the actual rise) in glucose (e.g., up until the maximum dose has been delivered). In preferred embodiments, the system is configured to slow and/or stop insulin delivery in circumstances wherein the host is entering a severely hypoglycemic range (e.g., programmable, such as less than about 70 mg/dl).

(234) In one exemplary embodiment, the dynamic bolus controller module is configured to calculate a percentage (e.g., portion, fraction) of the engaged bolus constraint (e.g., total insulin therapy) associated with a meal. For example, if the engaged bolus constraint is programmed for a

total insulin dose (e.g., D.sub.0) of 10 U in 1-hour: the controller module can calculate a first dose, such as about 7 U of insulin (e.g., dose D.sub.1 at time T.sub.1), based on the controller module's evaluation of the internally derived data relative to the engaged constraint. Instructions are sent to the integrated insulin delivery device and the partial dose is automatically delivered to the host. After an appropriate waiting period (e.g., depending upon the insulin's TAP), the controller module evaluates internally derived data (e.g., at time T.sub.2, data more recent than data used to initially calculate D.sub.1) and determines an additional insulin dose (e.g., dose D.sub.2) required to bring the host's glucose concentration into a target range (at time T.sub.2). For example, in some circumstances, an additional insulin dose may be necessary to bring the host's glucose concentration into the target range. In some other circumstances, no additional doses may be required (e.g., D.sub.2=0). Suppose that, in this example, additional insulin is required, then the controller module can calculate and instruct delivery of up to 2 more units of insulin (e.g., D.sub.0–D.sub.1–D.sub.2=2 U insulin remaining). In preferred embodiments, the insulin therapy delivered to the host is smallest total insulin dose necessary to maintain the host substantially within the target range (e.g., an euglycemic range).

(235) In some embodiments, the system is configured for user validation of the dynamic bolus therapy, such as before delivery of the insulin (e.g., FIG. 13, box 206). In one exemplary embodiment, the system is configured to alert the host (e.g., that a dynamic bolus therapy has been calculated) and request host validation (e.g., that the host accepts the dynamic bolus therapy, such as a maximum amount of insulin to be delivered over a given period of time). Upon host validation, the calculated therapy is delivered.

(236) In one exemplary embodiment, semi-automated integrated system 10 is configured such that the host can select a bolus constraint associated with a meal, such as by pressing one of a plurality of labeled, pre-programmed buttons or making a selection from a menu. For example, in this embodiment, each button is labeled with an icon of a food (e.g., cereal bowl, sandwich, slice of pizza, ice cream cone) and is associated with an insulin therapy calculated to be sufficient to cover that food (e.g., a meal) on average. For example, the sandwich bolus constraint is associated with an insulin dose that is generally sufficient to cover the glucose rise associated with host consumption of an average sandwich (e.g., a maximum total of up to 10 U of insulin to be delivered over 1-hour). When the host presses the sandwich button, the dynamic bolus controller module evaluates internally derived data and intelligently and adaptively determines a substantially optimal way (e.g., schedule of one or more insulin doses) to deliver a bolus insulin therapy (e.g., constrained by the sandwich constraint), preferably such that the host will not substantially enter a dangerous hypoglycemic state (e.g., glucose less than about 70 mg/dl) when the therapy is delivered. In preferred embodiments, the bolus controller module is configured to substantially continuously (e.g., constantly, automatically, iteratively, periodically, and/or intermittently) receive and evaluate internal data and to iteratively (e.g., automatically, periodically, and/or intermittently) determine an insulin therapy. For example, in some embodiments, the bolus controller module is configured to calculate a bolus therapy (e.g., based on solely the internally derived data) every about 5, 10, 15, 20, 30, 40 or 50-minutes. In some embodiments, the bolus controller module calculates a bolus therapy about every hour or longer. The calculated insulin therapy is then delivered (e.g., administered, such as automatically) to the host. In some embodiments, the insulin therapy associated with the engaged bolus constraint can be divided into portions (e.g., a total therapy of 10 U to be delivered in 1-hour is divided into two 5 U portions, five 2 U portions, or a 5 U portion, two 2 U portions and one 1 U portion) that can be delivered over time period associated with the engaged bolus constraint. In general, if portions of the total bolus therapy are delivered, the controller module is configured to wait a period of time for the delivered insulin to become active and to lower the host's blood sugar a pre-determined amount. The length of wait varies, depending upon the insulin's TAP and mode of delivery (e.g., injected subcutaneously by a pump versus by a syringe, inhaled, and the like) or the location of delivery, the type of meal being

consumed, the host's insulin sensitivity and metabolic state, and the like. After the wait time, the controller module again evaluates the internally derived data and determines if additional insulin is required. For example, if the host's glucose is still increasing, another partial dose can be delivered. This cycle can be repeated until either the total bolus therapy has been delivered the delivery time has expired. In some embodiments, the system is further configured to request host validation of the therapy, such as by selection of either a YES or NO button, and the like, as is appreciated by one skilled in the art.

(237) In some embodiments, the system is configured such that the host can manually enter a bolus insulin dose and the dynamic bolus controller module can evaluate the internally derived data and determine an insulin therapy within the entered bolus dose. For example, suppose the host wants to eat something for which there is no pre-programmed bolus constraint, such as a candy bar. In this circumstance, the host can calculate a bolus dose to cover the glucose increase that will probably occur when he eats that candy bar. He can enter the bolus dose he calculated and then have the system monitor his glucose and deliver the entered bolus dose as necessary (e.g., based upon evaluation of the internally derived data; to maintain and/or return the host within/to a target range). Preferably, the calculated therapy is substantially optimal for handling the glucose rise that will likely occur upon consumption of the meal for which the host calculated the bolus dose.

(238) In some circumstances, a selected constraint may be insufficient to handle a meal that the host has consumed. For example, a meal can have more carbohydrates than the average meal the engaged constraint was pre-programmed to handle. Accordingly, the controller module can be configured to alert the host to a need for additional insulin. As is understood by one in the art, a number of alerts and/or alarms can be built into the system, such as but not limited to safety alarms. The system can be configured to allow the selection of an additional meal constraint or a corrective bolus constraint and/or to allow the host to enter a manually calculated and enter a corrective bolus dose.

(239) In preferred embodiments, the dynamic bolus controller module is configured to evaluate trend information (e.g., derived from the internally derived data; the host's metabolic response to delivered insulin) and to adapt accordingly, such as by adjusting (e.g., re-programming) the time and/or amount of an insulin therapy associated with a bolus constraint. As is understood by one skilled in the art, trend information can fluctuate over time, depending upon the host's health, activity level, medications consumed, and the like. In one exemplary embodiment, the controller module is configured to evaluate the host's insulin sensitivity over time, and to re-program a bolus constraint such that a substantially optimal insulin therapy can be delivered to the host upon engagement of the bolus constraint. For example, suppose the host is relatively insulin resistant and has a correction factor of 10:1 (e.g., 1 U of insulin will lower glucose by 10 mg/dl). Accordingly, 10 U of insulin would be required to lower the glucose level by 100 mg/dl. Suppose the host becomes more insulin sensitive, such as by increasing exercise, which would change his insulin needs. The controller module monitors these metabolic changes and adjusts calculation of the insulin therapy accordingly, such as by modifying the correction factor (e.g., increase to 20:1) during insulin therapy calculation, for example. In preferred embodiments, intelligent and dynamic tracking of trends and calculation of bolus insulin therapies enables the dynamic bolus controller module to substantially minimize the risk of driving the host into a potentially dangerous state, such as but not limited to a severely hypoglycemic state (e.g., glucose concentration less than about 60 mg/dl).

(240) In one exemplary embodiment, the controller module continually receives information (e.g., internally derived data) related to the host's glucose level and iteratively evaluates the data relative to a target glycemic range (e.g., a euglycemic range pre-set by the host, a caretaker of the host, or by the manufacturer, such as 80-120 mg/dl or 100-140 mg/dl). When the host selects a bolus constraint (e.g., 15 U to be delivered over the next hour, selected at the start of a meal), the controller module evaluates the internally derived data relative to the engaged constraint and

calculates an insulin therapy that both 1) is sufficient to lower the host's glucose level to and/or within the target range and 2) is within the therapy associated with the engaged bolus constraint (e.g., will not exceed 15 U to be delivered over the next hour). If the calculated dose is less than or equal to the dose associated with the engaged constraint, the system delivers the calculated dose (e.g., a portion of the bolus dose). Generally, it will take some time for the insulin to have its effect (e.g., related to the insulin's TAP). In this embodiment, the controller module is configured to wait the appropriate period of time and then evaluate the host's response to the delivered insulin dose. In some circumstances, the host's response to the delivered insulin therapy may be insufficient (e.g., his glucose was not lowered to and/or maintained within the target range), so, the controller module will calculate and deliver an additional insulin dose (e.g., another portion of the dynamic bolus dose), based upon evaluation of the internally derived data. This iterative process continues until the time defined by the engaged bolus constraint expires (e.g., the 1-hour has passed). In some circumstances, the host's response to the initial insulin dose may be sufficient to maintain the host's blood glucose within the target range and additional insulin doses will not be calculated/delivered. While not wishing to be bound by theory, it is believed that the dynamic bolus controller module enables the use of less insulin while at the same time reducing the number of host hypoglycemic events than is possible using model-based systems or manual bolus calculation.

(241) In one exemplary embodiment, the controller module of the system **10** is configured to continuously (e.g., continually, iteratively, intermittently, automatically, periodically) collect and/or evaluate internally derived data, including trend data, such as but not limited to the host's insulin sensitivity and metabolic profile. The controller module can be an on/off, dynamic basal and/or dynamic bolus controller module, and is configured to adaptively adjust to a newly determined metabolic profile when calculating an insulin therapy. In some embodiments, the system is configured to adjust the target range, the set point, the basal profile and/or the bolus constraint, so as to improve the accuracy of host glucose control. In some embodiments, the system (e.g., the electronics module) includes one controller module. In other embodiments, the system includes two controller modules, which are configured to work in concert with each other. For example, the system can include an on/off controller module and either the dynamic basal or dynamic bolus controller modules. In another example, the system can include the dynamic basal and dynamic bolus controller modules. In yet another embodiment, the system includes all three controller modules, which are configured to work in concert with each other.

(242) In some embodiments, the system is configured such that the user can enter an insulin dose to be delivered. In some further embodiments, the system can be configured such that the controller module evaluates the internally derived data and calculates an appropriate and/or optimal delivery schedule for the entered dose. In some further embodiments, the system can be configured to deliver the entered dose substantially immediately.

(243) Intelligent and Adaptive Data Evaluation and Therapy Calculation

(244) A host's insulin requirements can fluctuate over time, due to changes in a variety of factors, such as but not limited to changes in the host's health, weight and/or exercise routine, changes in the type of insulin used and medications, dietary changes, and the like. Additionally, the condition of some components of the integrated system **10** can vary, either over time or from lot to lot. For example, many glucose sensors have some error in their function. This error can vary through out the sensor's lifetime and/or from manufacturing lot to manufacturing lot. Similarly, insulin formulations can vary between manufacturing lots, such as due to small variations in dilution or activity. In yet another example, the insulin deliver device can have some amount of error in measurement of insulin being delivered and/or remaining. Accordingly, in some embodiments, the system is configured to intelligently and adaptively adjust to changing circumstances (e.g., account for error in different system components when determining an insulin therapy), such that the host can be continuously provided with substantially optimum glucose control.

(245) In some circumstances, one or more of the system **10** components have some amount of

error. For example, in some circumstances, glucose data from a continuous glucose sensor may include some sensor error, such as about 1%, 2%, 5%, 10%, 15%, 20% or more error. In another example, in some circumstances, an insulin infusion device can have some error in measurement of the amount of insulin delivered (e.g., number of units, rate, volume, and the like) such as about 1%, 2%, 5%, 10%, 15%, 20% or more error. In yet another example, there can be small errors made when the insulin is formulated, such that it can have a slightly different activity or concentration than as labeled. Such system error can make it more difficult to control and host's glucose concentration, unless the system is configured to handle this error.

(246) Accordingly, in some embodiments, the system **10** is configured such that the controller module (e.g., on/off, dynamic basal or dynamic bolus controller module) considers system error (e.g., sensor error, insulin activity/delivery errors) when calculating an insulin therapy (e.g., an insulin delivery rate, an insulin dose, selecting between the on and off instructions). In one exemplary embodiment, if an average sensor error is initially $\pm 20\%$, then the controller module is configured to adjust the target glucose range by a similar amount up or down. Accordingly, if the original target range is 100-150 mg/dl, then the target range can be increased by 20% to about 120-180-gm/dl. This can prevent inadvertently driving the host too low (e.g., wherein the host's blood sugar is too close to a dangerous hypoglycemic level), such as by overshooting the target range (e.g., 100- to 150 mg/dl reduced by 20% would be 80- to 130 mg/dl). In another exemplary embodiment, the controller module is configured to track and/or evaluate system error (e.g., over time) and adjust one or more system parameters (e.g., target range, glucose boundary, bolus constraint, basal profile, rate of insulin delivery, time of insulin delivery and the like) such that the host is maintained substantially within the target range a substantial portion of the time the system **10** is in use (e.g., 50, 60, 70, 80, 90, or 99% of the time). For example, if sensor error increases to 30% on day-3 of use, the controller module is configured to adjust the target range a corresponding amount (e.g., increase the target range by 30%).

(247) In some embodiments, the system **10** includes two or all three controller modules which are configured to work in concert (e.g., switch therebetween), such that the host is maintained substantially within the target range a substantial portion of the time (e.g., 50%, 60%, 70%, 80%, 90%, 95% or more of the time) that the system is in use by the host. For example, in some embodiments, the system includes an on/off controller module and either a dynamic bolus controller module or a dynamic basal controller module. In some embodiments, the system includes both the dynamic basal and dynamic bolus controller modules, but not an on/off controller module. In some embodiments, the system includes the on/off controller module as well as both the dynamic basal and dynamic bolus controller modules.

(248) In one exemplary embodiment, the system includes on/off and basal controller modules, and is configured such that determination of insulin therapy occurs in at least two steps. In a first step, the on/off controller module evaluates the internally derived data relative to a glucose boundary, and selects between the on and off instructions. If the on instruction is selected, the dynamic basal controller module evaluated the internally derived data relative to a programmed basal profile and calculated/determines an insulin therapy within the current time block of the basal profile. If the off instruction is selected, then insulin delivery is terminated. In a further exemplary embodiment, the system also includes a dynamic bolus controller module. In general, the on/off and basal controller modules can be configured to function automatically (e.g., perform their functions automatically and in concert with each other) until the user engages a programmable bolus constraint. When the user engages the bolus constraint, the bolus controller module calculates an insulin therapy within the engaged constraint. The system can be further configured to return to operation by the on/off and basal controller modules, until such time that the user again engages a bolus constraint. While not wishing to be bound by theory, it is believed that an intelligent, adaptive integrated system, which can switch between controller modules, can substantially improve consistency and accuracy of glucose control, which enables tight control by the host, and thereby improving the host's health

and delaying diabetic complications.

(249) In an exemplary embodiment of a fully automated integrated system **10**, the system includes on/off, dynamic basal and dynamic bolus controller modules, is configured for use in conjunction with a flash insulin, and is configured to adaptively and intelligently switch (e.g., automatically, as described herein) between controller modules, depending upon evaluation of the internally derived data, system parameters (e.g., glucose boundary, target range, basal profile, bolus constraints, and the like) and system constraints, such that the host is maintained substantially at within a programmed target range at least 50% of the time the system is in use. In preferred embodiments, the host is maintained within the target range at least 60, 70, 80, 90, or 99% of the time the system is in use. More preferably, the system is further configured to maintain the host within the programmed target range regardless of the host's activity level, metabolic state and/or meal consumption. In such a system, a substantial portion of the host's day, he may experience only moderate increases/decreases in glucose. During these portions of his day, the on/off controller can select either the on or off instructions (e.g., to turn insulin delivery on and off), and when the on instruction is selected, the basal controller module can calculate delivery of basal levels of insulin. A portion of the host's day, an unexpected rapid rise in glucose concentration (e.g., the internally derived data) may occur, which may indicate that a meal is being or has been consumed. Generally, the host would require a bolus insulin therapy to handle the increased glucose that can result from meal consumption. Accordingly, the system can be configured such that the on/off controller can select the on instruction (e.g., turns on insulin delivery) and then the dynamic bolus controller module can calculate an appropriate bolus insulin therapy (e.g., within pre-programmed bolus constraints, non-host engageable). Similarly, as the glucose concentration is brought into the target range, the system can intelligently recognize a decreased requirement for insulin, and can switch from the dynamic bolus controller module, back to the dynamic basal controller module, which can calculate a basal insulin therapy (e.g., for the host's current needs). If the glucose is brought within the target range, the on/off controller can select the off instruction to terminate insulin delivery.

Examples

(250) In one exemplary implementation of the preferred embodiments, the continuous glucose sensor (and its receiver) comprises programming to track a host during hypoglycemic or near-hypoglycemic conditions. In this implementation, the processor (e.g., controller module) includes programming that sends instructions to administer a hypoglycemic treating medicament, such as glucagon, via an implantable pump or the like, when the glucose level and rate of change surpass a predetermined threshold (for example, 80 mg/dL and 2 mg/dL/min). In this situation, the sensor waits a predetermined amount of time (for example, 40 minutes), while monitoring the glucose level, rate of change of glucose, and/or acceleration/deceleration of glucose in the host, wherein if the rate of change and/or acceleration shows a changing trend away from hypoglycemia (for example, decreased deceleration of glucose levels to non-hypoglycemia, then the host need not be alarmed. In this way, the automated glucagon delivery device can proactively preempt hypoglycemic conditions without alerting or awaking the host.

(251) In one exemplary implementation of the preferred embodiments, a continuous glucose sensor is integrated with a continuous medicament delivery device (for example, an insulin pump) and a bolus medicament delivery device (for example, and insulin pen) and a controller module. In this embodiment, the integration exploits the benefits of automated and semi-automated device, for example, providing an automated integration with an infusion pump, while provide semi-automated integration with an insulin pen as necessary.

(252) In one exemplary implementation of the preferred embodiments, a medicament delivery device is provided that includes reservoirs of both fast acting insulin and slow acting insulin. The medicament delivery device is integrated with a controller module as described elsewhere herein, however in this implementation, the controller module determines an amount of fast acting insulin and an amount of slow acting insulin, wherein the medicament delivery device is configured to

deliver the two insulins separately and/or in combination, such that the host is maintained substantially at and/or within the target range. In this way, the receiver and medicament delivery device can work together in a feedback loop to iteratively optimize amounts of slow and fast acting insulin for a variety of situations (for example, based on glucose level, rate of change, acceleration, and behavioral factors such as diet, exercise, time of day, etc.) adapted to the individual host's metabolic profile.

(253) In one exemplary implementation of the preferred embodiments, an integrated hypo- and hyper-glycemic treating system is provided. In this implementation, a manual-, semi-automated, or automated integration of an insulin delivery device is combined with a manual-, semi-automated, or automated integration of a glucose or glucagon delivery device. These devices are integrated with the receiver for the continuous glucose sensor and a controller module in any manner described elsewhere herein. While not wishing to be bound by theory, it is believed that the combination of a continuous glucose sensor, integrated insulin device, and integrated glucose or glucagon device provides a simplified, comprehensive, user friendly, convenient, long-term and continuous method of monitoring, treating, and optimizing comprehensive care for diabetes.

(254) In one exemplary implementation of the preferred embodiments, an integrated hypo- and hyper-glycemic treating system is provided, including a continuous glucose sensor, an insulin infusion device and a dynamic controller module, wherein the system is configured to adaptively and intelligently evaluate the host's metabolic state (e.g., historical profile) and adjust the insulin therapy accordingly, in response to an unexpected increase in glucose above a programmed target range. In some circumstances, the boundaries between low, target and high glucose levels, between slow and fast rates of change, and between small and large insulin dose adjustments can be substantially sharp. Accordingly, in this embodiment, the dynamic controller module is configured to evaluate weighted sums (e.g., derived by processing the data collected from the continuous glucose sensor, use of a Kalman filter) to provide a suggested dynamic insulin therapy that is substantially adjusted for the host's current glucose profile (e.g., concentration, rate of change, acceleration, etc.). One skilled in the art understands that, generally, the weighting of a control action depends upon the degree to which its input condition is true. Thus, at the present time (T.sub.1), the condition that best describes the glucose level and rate of change (e.g., at T.sub.1) will have the largest influence on the control action (e.g., the amount of insulin to be calculated). For exemplary purposes, suppose the following conditions are defined: a very high glucose concentration is greater than 140 mg/dl; a moderately high glucose concentration is from 110 mg/dl to 140 mg/dl; a slow rise in glucose concentration is from 0.5 mg/dl/min to 1.0 mg/dl/min; and a stable glucose concentration is from -0.5-mg/dl/min to 0.5 mg/dl/min. Thus, if the measured glucose concentration is 140 mg/dl and it is rising at a rate of 0.5=mg/dl/min, then the host's current glucose profile falls on the boundary between very high and a little high glucose concentrations, as well as between rising slowly and stable rates. Accordingly, if a large insulin dose increase is defined as from 1-U/h to 2-U/h; a moderate dose increase as from 0.5-U/h to 1-U/h; and small dose increase as from 0.1-U/h to 0.5-U/h; then an optimal increase in insulin dose (e.g., to maintain the host in the target range) may be about 1.2-U/h, for example. Similarly, if the host is relatively insulin insensitive (e.g., resistant), a larger dose can be calculated; and if the host is relatively insulin sensitive, then a smaller dose can be calculated. Thus, the dynamic controller module is configured to adapt (e.g., adjust, modify, re-program) insulin therapy (e.g., dosing) to a given host and his current metabolic conditions. For example, the dynamic controller module can be configured to monitor (e.g., learn) the host's insulin sensitivity by comparing substantially more recent (prior minutes to hours) changes in glucose and insulin dose, and adjust the current dose boundaries accordingly. In a further example, the system can consider system error (e.g., sensor error, drug delivery error and the like) as a weighted sum, when determining the dynamic insulin therapy. For example, if the sensor error is very high and the rate of change is rising slowly, then the insulin therapy can be adjusted by a large increase; if the sensor error is very high and the rate

of change is stable, then the insulin therapy can be adjusted by a medium increase; if the sensor error is a little high and the rate of change is stable, then the insulin therapy can be adjusted by a small increase. Advantageously, because any definition of boundaries between low, target and high glucose levels, between slow and fast rates of change, and between small and large insulin therapy adjustments is artificially sharp, the weighted sum provides a graded dose adjustment. Because the dynamic controller module is configured adaptively learn and track trends, the dose boundaries can be intelligently adjusted accordingly. While not wishing to be bound by theory, it is believed that due to its non-model-based nature, smooth transitions between ranges and adaptive learning, the dynamic controller module substantially increases accuracy for each host, which leads to a higher level of safety and improved host health.

(255) In one exemplary implementation of the preferred embodiments, an integrated hypo- and hyper-glycemic treating system is provided, including a continuous glucose sensor, an insulin infusion device and a controller module (on/off, dynamic basal, dynamic bolus) configured to monitor and evaluate system error (e.g., errors in sensor readings and/or evaluation of the internally derived data) and to titrate the insulin therapy, such that the host substantially does not overshoot the euglycemic range (e.g., enter the hypoglycemic range) during delivery of the calculated dose. For example, if the sensor readings include a $\pm 30\%$ error, the target range is set an equivalent percent (e.g., $\pm 30\%$) above the target range. For example, in some circumstances, if the preferred target range is 80-100 mg/dl, the target can be increased by 30%, to 110-140 mg/dl glucose. In other circumstances, the internally derived data can indicate that the target range should be lowered. Accordingly, the target range can be adjusted up or down, depending upon the error of the system, such that the host substantially does not enter a hypoglycemic (e.g., unsafe) glucose range.

(256) In one exemplary implementation of the preferred embodiments, an integrated hypo- and hyper-glycemic treating system is provided, including a continuous glucose sensor, an insulin infusion device and a controller module configured to provide and/or evaluate trending information. Trend information can include changes in glucose concentration (increasing or decreasing), the rate of change, and the acceleration. Generally, consideration of trend information in insulin therapy calculation can direct relative increases and/or decreases in the calculated therapy and its delivery. For example, in a first exemplary circumstance, the host's glucose concentration is 200 mg/dl and slowly increasing; 5 U of insulin might be insufficient to bring his glucose down to the target level (e.g., 100 mg/dl). In a second exemplary circumstance, in contrast, if the host's glucose concentration is 200 mg/dl and rapidly decreasing, that same insulin dose (e.g., 5 U) might be too large and cause him to overshoot the target range (e.g., become hypoglycemic). In still another example, if the host's glucose concentration is 200 mg/dl and increasing rapidly, a larger insulin dose (e.g., 6, 7, 8, 9 or 10 U or more) may be required to bring his glucose substantially to the target range, relative to the dose required in the first exemplary circumstance. Accordingly, the controller module is configured to evaluate the trend information when calculating a medicament therapy.

(257) In one exemplary implementation of the preferred embodiments, an integrated hypo- and hyper-glycemic treating system is provided, including a continuous glucose sensor, an insulin infusion device and a controller module, wherein the target range is a euglycemic glucose range (e.g., about 90 mg/dl to 140 mg/dl), a dynamic insulin therapy is an amount of a given insulin required to lower a hyperglycemic host's glucose concentration substantially to within about 90 mg/dl to 140 mg/dl glucose (e.g., at the time of calculation), substantially without reducing the host's glucose to a hypoglycemic range. Suppose the target range is 100-140 mg/dl, the host's current glucose concentration is 120 mg/dl and he has just consumed a meal (e.g., including an amount of carbohydrate). Generally, in response to the meal, the host's glucose will begin to rise. Preferably, the integrated system monitor's the host's glucose substantially continuously. If the host's glucose exceeds 140 mg/dl (e.g., at T.sub.1), then the dynamic controller module will calculate a dynamic insulin dose (e.g., D.sub.1) sufficient (at time T.sub.1) to lower the host's

glucose to at least 140 mg/dl. After delivery of D.sub.1, the system will continue to monitor the host's glucose. Generally, a period of time sufficient for the insulin to act (e.g., depending upon the insulin's TAP) is allowed to pass. If, at a later time (e.g., T.sub.2), the host's glucose exceeds 140 mg/dl, the dynamic controller module can calculate another dynamic insulin dose (e.g., D.sub.2), sufficient (at time T.sub.2) to lower the host's glucose to at least 140 mg/dl. If, at T.sub.2, the host's glucose is within the target range, then no additional dynamic insulin doses will be calculated and/or delivered. This process can be repeated (e.g., iteratively), such that the host's glucose is maintained substantially within the target range (e.g., 100-140 mg/dl in this example). In preferred embodiments, the system is configured to stop insulin delivery and/or sound an alarm, if the host's glucose falls below the target range and/or within a dangerous range (e.g., hypoglycemic, such as less than 70 mg/dl).

(258) In one exemplary implementation of the preferred embodiments, an integrated hypo- and hyper-glycemic treating system is provided, including a continuous glucose sensor, an insulin infusion device and a controller module, the dynamic controller module is configured to calculate an insulin therapy that, in a worst-case scenario, is not sufficient (e.g., insufficient) to drive the host into a severely hypoglycemic state (e.g., less than about 65 mg/dl). For exemplary purposes, let's suppose that the host's target glucose is 110 mg/dl, and his glucose level is currently increasing at ≥ 1 mg/dl/min and is projected to rise (based on the internally derived data) to 170 mg/dl. The dynamic controller module can be programmed such that at a programmed threshold level (e.g., 140 mg/dl), it calculates an insulin therapy that will be sufficient to lower the host's glucose concentration from the expected 170 mg/dl down to the target range (110 mg/dl; lowered by ~60 mg/dl). Suppose that the host's glucose actually does not rise above 140 mg/dl. In this circumstance, the 60-point correction will lower glucose to about 80 mg/dl, which is still about 20-30 mg/dl above what would be a dangerously hypoglycemic glucose concentration. On the other hand, in a best-case scenario, the dynamic controller module can anticipate and correct/prevent an expected rise in glucose concentration, such that the host is substantially maintained within a target blood glucose range, such as a euglycemic range. If the host's glucose concentration continues to rise after delivery of the insulin therapy (e.g., to 200 mg/dl), the dynamic controller module can calculate an additional insulin therapy sufficient to lower the host's glucose concentration the additional amount (e.g., 30-points). In some embodiments, the dynamic controller module is configured to divide the insulin therapy into two or more portions to be delivered over a given period of time. For example, if the insulin therapy is divided into two portions, the first portion can be delivered, and the host's response monitored. If, after the monitoring period has passed, the host's glucose concentration is still above the target, the second portion (all or a part thereof) can be delivered. If, on the other hand, the host's glucose concentration has been lowered to within a threshold (e.g., 110-140 mg/dl) or to the target range (e.g., 110 mg/dl), the second portion can be not delivered.

(259) Methods and devices that are suitable for use in conjunction with aspects of the preferred embodiments are disclosed in U.S. Pat. Nos. 4,994,167; 4,757,022; 6,001,067; 6,741,877; 6,702,857; 6,558,321; 6,931,327; 6,862,465; 7,074,307; 7,081,195; 7,108,778; and 7,110,803.

(260) Methods and devices that are suitable for use in conjunction with aspects of the preferred embodiments are disclosed in U.S. Patent Publication No. US-2005-0176136-A1; U.S. Patent Publication No. US-2005-0251083-A1; U.S. Patent Publication No. US-2005-0143635-A1; U.S. Patent Publication No. US-2005-0181012-A1; U.S. Patent Publication No. US-2005-0177036-A1; U.S. Patent Publication No. US-2005-0124873-A1; U.S. Patent Publication No. US-2005-0115832-A1; U.S. Patent Publication No. US-2005-0245799-A1; U.S. Patent Publication No. US-2005-0245795-A1; U.S. Patent Publication No. US-2005-0242479-A1; U.S. Patent Publication No. US-2005-0182451-A1; U.S. Patent Publication No. US-2005-0056552-A1; U.S. Patent Publication No. US-2005-0192557-A1; U.S. Patent Publication No. US-2005-0154271-A1; U.S. Patent Publication No. US-2004-0199059-A1; U.S. Patent Publication No. US-2005-0054909-A1; U.S. Patent

Publication No. US-2005-0112169-A1; U.S. Patent Publication No. US-2005-0051427-A1; U.S. Patent Publication No. US-2003-0032874-A1; U.S. Patent Publication No. US-2005-0103625-A1; U.S. Patent Publication No. US-2005-0203360-A1; U.S. Patent Publication No. US-2005-0090607-A1; U.S. Patent Publication No. US-2005-0187720-A1; U.S. Patent Publication No. US-2005-0161346-A1; U.S. Patent Publication No. US-2006-0015020-A1; U.S. Patent Publication No. US-2005-0043598-A1; U.S. Patent Publication No. US-2003-0217966-A1; U.S. Patent Publication No. US-2005-0033132-A1; U.S. Patent Publication No. US-2005-0031689-A1; U.S. Patent Publication No. US-2004-0186362-A1; U.S. Patent Publication No. US-2005-0027463-A1; U.S. Patent Publication No. US-2005-0027181-A1; U.S. Patent Publication No. US-2005-0027180-A1; U.S. Patent Publication No. US-2006-0020187-A1; U.S. Patent Publication No. US-2006-0036142-A1; U.S. Patent Publication No. US-2006-0020192-A1; U.S. Patent Publication No. US-2006-0036143-A1; U.S. Patent Publication No. US-2006-0036140-A1; U.S. Patent Publication No. US-2006-0019327-A1; U.S. Patent Publication No. US-2006-0020186-A1; U.S. Patent Publication No. US-2006-0020189-A1; U.S. Patent Publication No. US-2006-0036139-A1; U.S. Patent Publication No. US-2006-0020191-A1; U.S. Patent Publication No. US-2006-0020188-A1; U.S. Patent Publication No. US-2006-0036141-A1; U.S. Patent Publication No. US-2006-0020190-A1; U.S. Patent Publication No. US-2006-0036145-A1; U.S. Patent Publication No. US-2006-0036144-A1; U.S. Patent Publication No. US-2006-0016700-A1; U.S. Patent Publication No. US-2006-0142651-A1; U.S. Patent Publication No. US-2006-0086624-A1; U.S. Patent Publication No. US-2006-0068208-A1; U.S. Patent Publication No. US-2006-0040402-A1; U.S. Patent Publication No. US-2006-0036142-A1; U.S. Patent Publication No. US-2006-0036141-A1; U.S. Patent Publication No. US-2006-0036143-A1; U.S. Patent Publication No. US-2006-0036140-A1; U.S. Patent Publication No. US-2006-0036139-A1; U.S. Patent Publication No. US-2006-0142651-A1; U.S. Patent Publication No. US-2006-0036145-A1; U.S. Patent Publication No. US-2006-0036144-A1; U.S. Patent Publication No. US-2006-0200022-A1; U.S. Patent Publication No. US-2006-0198864-A1; U.S. Patent Publication No. US-2006-0200019-A1; U.S. Patent Publication No. US-2006-0189856-A1; U.S. Patent Publication No. US-2006-0200020-A1; U.S. Patent Publication No. US-2006-0200970-A1; U.S. Patent Publication No. US-2006-0183984-A1; U.S. Patent Publication No. US-2006-0183985-A1; U.S. Patent Publication No. US-2006-0195029-A1; U.S. Patent Publication No. US-2006-0229512-A1; U.S. Patent Publication No. US-2006-0222566-A1; U.S. Patent Publication No. US-2007-0032706-A1; U.S. Patent Publication No. US-2007-0016381-A1; U.S. Patent Publication No. US-2007-0027370-A1; U.S. Patent Publication No. US-2007-0027384-A1; U.S. Patent Publication No. US-2007-0032717-A1; and U.S. Patent Publication No. US-2007-0032718 A1.

(261) Methods and devices that are suitable for use in conjunction with aspects of the preferred embodiments are disclosed in U.S. application Ser. No. 09/447,227 filed Nov. 22, 1999 and entitled "DEVICE AND METHOD FOR DETERMINING ANALYTE LEVELS"; U.S. application Ser. No. 11/515,342 filed Sep. 1, 2006 and entitled "SYSTEMS AND METHODS FOR PROCESSING ANALYTE SENSOR DATA"; U.S. application Ser. No. 11/654,135 filed Jan. 17, 2007 and entitled "POROUS MEMBRANES FOR USE WITH IMPLANTABLE DEVICES"; U.S. application Ser. No. 11/675,063 filed Feb. 14, 2007 and entitled "ANALYTE SENSOR"; U.S. application Ser. No. 11/543,734 filed Oct. 4, 2006 and entitled "DUAL ELECTRODE SYSTEM FOR A CONTINUOUS ANALYTE SENSOR"; U.S. application Ser. No. 11/654,140 filed Jan. 17, 2007 and entitled "MEMBRANES FOR AN ANALYTE SENSOR"; U.S. application Ser. No. 11/654,327 filed Jan. 17, 2007 and entitled "MEMBRANES FOR AN ANALYTE SENSOR"; U.S. application Ser. No. 11/543,396 filed Oct. 4, 2006 and entitled "ANALYTE SENSOR"; U.S. application Ser. No. 11/543,490 filed Oct. 4, 2006 and entitled "ANALYTE SENSOR"; U.S. application Ser. No. 11/543,404 filed Oct. 4, 2006 and entitled "ANALYTE SENSOR"; U.S. application Ser. No. 11/681,145 filed Mar. 1, 2007 and entitled "ANALYTE SENSOR"; and U.S. application Ser. No. 11/690,752 filed Mar. 23, 2007 and entitled "TRANSCUTANEOUS ANALYTE SENSOR".

(262) All references cited herein, including but not limited to published and unpublished applications, patents, and literature references, are incorporated herein by reference in their entirety and are hereby made a part of this specification. To the extent publications and patents or patent applications incorporated by reference contradict the disclosure contained in the specification, the specification is intended to supersede and/or take precedence over any such contradictory material.

(263) The term “comprising” as used herein is synonymous with “including,” “containing,” or “characterized by,” and is inclusive or open-ended and does not exclude additional, unrecited elements or method steps.

(264) All numbers expressing quantities of ingredients, reaction conditions, and so forth used in the specification are to be understood as being modified in all instances by the term “about.”

Accordingly, unless indicated to the contrary, the numerical parameters set forth herein are approximations that may vary depending upon the desired properties sought to be obtained. At the very least, and not as an attempt to limit the application of the doctrine of equivalents to the scope of any claims in any application claiming priority to the present application, each numerical parameter should be construed in light of the number of significant digits and ordinary rounding approaches.

(265) The above description discloses several methods and materials of the present invention. This invention is susceptible to modifications in the methods and materials, as well as alterations in the fabrication methods and equipment. Such modifications will become apparent to those skilled in the art from a consideration of this disclosure or practice of the invention disclosed herein.

Consequently, it is not intended that this invention be limited to the specific embodiments disclosed herein, but that it cover all modifications and alternatives coming within the true scope and spirit of the invention.

Claims

1. A method for determining insulin therapy for a patient, the method comprising: receiving, by a user interface of a receiver device that comprises the user interface, a display, and one or more processor modules, input from a user, wherein the input from the user sets a selectable glucose target; generating, by the one or more processor modules of the receiver device, glucose trend information, wherein the glucose trend information is based at least in part on sensor glucose data from a data stream comprising time-spaced sensor data points measured in a bodily fluid of the patient by a continuous glucose sensor; generating a predicted glucose concentration, wherein the predicted glucose concentration comprises a prediction of a future glucose concentration, wherein the prediction is generated based at least in part on an algorithm; generating, by the one or more processor modules of the receiver device, patient data, wherein the patient data comprises one or more of: an insulin sensitivity of the patient, a change in insulin sensitivity of the patient, a metabolic response of the patient to insulin therapy, an amount of insulin delivered to the patient, a time of insulin delivery to the patient, and/or an insulin on board of the patient; generating, by the one or more processor modules of the receiver device, a series of insulin therapy instructions by evaluating at least the glucose trend information, the patient data, and the selectable glucose target; and transmitting the series of insulin therapy instructions for use by an insulin delivery device, wherein a glucose concentration measured in a bodily fluid of the patient by the continuous glucose sensor following administration of insulin in accordance with the series of insulin therapy instructions is at or within the selectable glucose target.
2. The method of claim 1, wherein the selectable glucose target is a single glucose concentration.
3. The method of claim 1, wherein the selectable glucose target is a range of glucose concentrations.
4. The method of claim 1, wherein the selectable glucose target is selected from a predefined list of selectable glucose target options.

5. The method of claim 1, wherein calculating an insulin therapy instruction is based solely on evaluating the glucose trend information, the patient data, and the selectable glucose target.
 6. The method of claim 1, wherein the selectable glucose target is set for a first specified time period.
 7. The method of claim 6, wherein a second selectable glucose target is set for a second specified time period that is different from the first specified time period.
 8. The method of claim 7, wherein subsequent glucose concentrations measured in a bodily fluid of the patient by the continuous glucose sensor following administration of insulin in accordance with the series of insulin therapy instructions is at or within the selectable glucose target 70% or more of time that the method is in use for the patient.
 9. The method of claim 1, wherein subsequent glucose concentrations measured in a bodily fluid of the patient by the continuous glucose sensor following administration of insulin in accordance with the series of insulin therapy instructions is at or within the selectable glucose target 50% or more of time that the method is in use for the patient.
 10. The method of claim 1, wherein the selectable glucose target is adaptively re-programmed based on evaluation of the patient data and/or an external input.
 11. The method of claim 10, wherein the patient data comprises data associated with a metabolic response of the patient to insulin therapy.
 12. The method of claim 10, wherein the external input is associated with an activity level of the patient.
 13. The method of claim 1, wherein the selectable glucose target is displayed by the display of the receiver device.
 14. The method of claim 1, wherein information associated with at least one insulin therapy instruction from the series of insulin therapy instructions is displayed by the display of the receiver device.
 15. The method of claim 1, wherein the receiver device is integrally formed with the insulin delivery device.
 16. The method of claim 1, wherein the insulin delivery device is an infusion pump and the series of insulin therapy instructions is transmitted by radio frequency wireless communication.
 17. The method of claim 16, wherein at least one insulin therapy instruction in the series of insulin therapy instructions terminates insulin delivery when glucose trend information indicates a glucose level of the patient is in a euglycemic range and decreasing.
 18. The method of claim 1, wherein the user is the patient.
-