

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12398812
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Fang; Shih-Yao et al.

Inflating connector

Abstract

An inflating connector includes a base, a pressure valve, a gas bottle connecting seat, and a throttling valve. The base has an assembling passageway, a first gas passageway communicating with the assembling passageway, and a second gas passageway communicating with the assembling passageway, a gas nozzle to be connected with the second gas passageway. The pressure valve has an elastic member and a piston, which are accommodated in the first gas passageway. The elastic member acts on the piston to make it close up the first gas passageway. The gas bottle is disposed on a side of the assembling passageway, and has a gas inlet passageway for being connected with a gas bottle and a gas outlet passageway communicating with the gas inlet passageway. The throttling valve has an operation unit and a throttling member capable of being driven by the operation unit to displace along the gas outlet passageway.

Inventors: Fang; Shih-Yao (Taichung, TW), Hung; Jung-Lung (Taichung, TW)

Applicant: TALLGUY AND MARK PRECISION CO., LTD. (Taichung, TW); CIRCUM AVANTI CO., LTD. (Taichung, TW)

Family ID: 1000008780055

Assignee: TALLGUY AND MARK PRECISION CO., LTD. (Taichung, TW); CIRCUM AVANTI CO., LTD. (Taichung, TW)

Appl. No.: 18/518812

Filed: November 24, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240288078 A1	Aug. 29, 2024

Foreign Application Priority Data

TW	112106816	Feb. 23, 2023
----	-----------	---------------

Publication Classification

Int. Cl.: F16K5/16 (20060101); F16K1/30 (20060101); F16K17/08 (20060101)

U.S. Cl.:

CPC F16K5/16 (20130101); F16K1/306 (20130101); F16K17/082 (20130101);

Field of Classification Search

CPC: F16K (5/16); F16K (1/306); F16K (1/04); F16K (1/385); F16K (17/082); F16K (17/04); F16K (17/168); F17C (13/04); F04B (39/123); F04B (41/02)

USPC: 137/226; 137/224; 137/234

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1699378	12/1928	Smith	137/227	B60S 5/043
3451416	12/1968	Nyberg	137/115.18	F16K 17/0473
3648893	12/1971	Whiting	222/397	F16K 1/307
4077422	12/1977	Brinkley	137/68.14	F17C 13/12
4350176	12/1981	Lace	137/554	F16K 17/04
4911403	12/1989	Lockwood, Jr.	251/210	F16K 1/305
5048554	12/1990	Kremer	137/69	F16K 1/305
5671775	12/1996	Miller	137/557	F16K 41/12
5678602	12/1996	Cannet	137/500	G05D 7/0186

Primary Examiner: Schneider; Craig M

Assistant Examiner: Rost; Andrew J

Attorney, Agent or Firm: Muncy, Geissler, Olds & Lowe, P.C.

Background/Summary

BACKGROUND OF THE INVENTION

1. Field of the Invention

(1) The present invention relates to inflating connectors and more particularly, to an inflating connector which can change the intake gas quantity and intake gas pressure of the gas flowing into a bicycle tire from a gas bottle.

2. Description of the Related Art

(2) The common bicycle tire inflating manners almost adopt an air pump to inflate by applying force for pressurized pumping. The presently commercially available air pumps are already smaller and smaller in size for the convenience of being carried by the user, but the reduced size causes the air pumps reduced gas quantity for inflating when applying force for pressurized pumping, so it requires the user relatively more effort and time to complete the bicycle tire inflating. Therefore,

the bicycle tire inflating now changes to adopt the combination of a gas bottle filled with high-pressure gas with an inflating connector.

(3) However, the current inflating connectors cannot adjust the intake gas quantity and intake gas pressure of the gas flowing into the bicycle tire from the gas bottle, resulting in that the bicycle tires often burst due to the over large intake gas quantity or over high intake gas pressure of the gas. Besides, if the user has the demand for measuring the intake gas pressure, the user has to additionally use a pressure gauge or use an air pump having a pressure gauge, that is very inconvenient for the user. Therefore, the current inflating connectors still need improvement.

SUMMARY OF THE INVENTION

(4) The present invention has been accomplished in view of the above-noted circumstances. The present invention provides an inflating connector which can change the intake gas quantity and intake gas pressure of the gas flowing into the bicycle tire from the gas bottle.

(5) To attain the above objective, the inflating connector of the present invention includes a base, a pressure valve, a gas bottle connecting seat, and a throttling valve. The base has a first rod portion, a second rod portion opposite to the first rod portion, an assembling passageway located between the first and second rod portions, a first gas passageway penetrating through the first rod portion axially and communicating with the assembling passageway, and a second gas passageway penetrating through the second rod portion axially and communicating with the assembling passageway. The first gas passageway has an entrance section communicating with the assembling passageway, an accommodating section communicating with the entrance section, and an exit located at the accommodating section. The second gas passageway is arranged for being connected with a gas nozzle. The pressure valve has a cover screwingly connected to the first rod portion, and an elastic member and a piston, which are accommodated in the accommodating section. The cover has an opening communicating with the exit. The piston is movably disposed in the accommodating section, and has a plug portion capable of closing up the entrance section and a rod portion connected with the plug portion. The elastic member acts on the piston to make the plug portion close up the entrance section. The gas bottle connecting seat is installed on a side of the assembling passageway. The gas bottle connecting seat has a gas inlet passageway, a gas outlet passageway communicating with the gas inlet passageway, a first connecting passageway communicating with the gas outlet passageway and the entrance section, and a second connecting passageway communicating with the gas outlet passageway and the second gas passageway. The gas inlet passageway is arranged for being connected with a gas bottle to enable gas in the gas bottle to flow to the gas outlet passageway. The throttling valve is installed on another side of the assembling passageway. The throttling valve has an operation unit, and a throttling member connected with the operation unit and accommodated in the gas outlet passageway. The operation unit is arranged for driving the throttling member to displace back and forth along an axis of the gas outlet passageway to change the size of a communication space between the gas outlet passageway and the first connecting passageway, the second connecting passageway and the gas inlet passageway.

(6) By the above-described technical features, the inflating connector of the present invention changes the intake gas quantity and intake gas pressure of the gas by the adjustments of the throttling valve and the pressure valve, thereby preventing the bicycle tire from burst due to the over large intake gas quantity or over high intake gas pressure of the gas. Besides, the pressure valve can pre-set the magnitude of the intake gas pressure to make the intake gas pressure of the gas flowing into the bicycle tire smaller than the pre-set intake gas pressure, so that the user doesn't need to additionally use a pressure gauge or use an air pump having a pressure gauge to measure if the intake gas pressure is over high, that is very convenient for the user.

(7) Preferably, it is not completely gastight between the plug portion of the piston and a wall of the accommodating section of the first gas passageway.

(8) Preferably, it is completely gastight between the plug portion of the piston and a wall of the

accommodating section of the first gas passageway, and the rod portion of the piston is inserted through the exit of the first gas passageway and the opening of the cover.

(9) Preferably, it is not completely gastight between the plug portion of the piston and a wall of the accommodating section of the first gas passageway, and the rod portion of the piston is inserted through the exit of the first gas passageway and the opening of the cover; the base has a third gas passageway penetrating through the first rod portion radially and communicating with the accommodating section; the pressure valve has a switch sleeved onto the first rod portion; the switch is slidable relative to the first rod portion back and forth to close up or not close up the third gas passageway.

(10) Preferably, the base has a fourth gas passageway penetrating through the first rod portion radially and communicating with the accommodating section; the fourth gas passageway is arranged apart from the third gas passageway; when the third gas passageway is not closed up by the switch of the pressure valve, the gas in the gas bottle flows to the fourth gas passageway through the third gas passageway; when the third gas passageway is closed up by the switch of the pressure valve, the gas in the gas bottle is disabled from flowing to the fourth gas passageway through the third gas passageway.

(11) Preferably, the operation unit of the throttling valve includes a sleeve sleeved onto the throttling member, an elastic member accommodated in the sleeve, and a pin inserted in the throttling member; the elastic member acts on the throttling member to make the throttling member partially close up the communication space; the throttling member has an external thread; a wall of the gas outlet passageway of the gas bottle connecting seat has an internal thread; the pin is pivotable relative to the sleeve to drive the throttling member in a way that the external thread of the throttling member is guided by the internal thread of the gas outlet passageway to make the throttling member displace back and forth along the axis of the gas outlet passageway.

(12) Preferably, the gas inlet passageway of the gas bottle connecting seat has a connecting path and an installation path communicating with the connecting path, and a wall of the installation path has an internal thread; the gas bottle connecting seat has an inserting member accommodated in the installation path; the internal thread of the installation path is arranged for being screwingly connected with a bottleneck of the gas bottle so that the inserting member is inserted in the bottleneck of the gas bottle. In this way, the inserting member is inserted in the bottleneck of the gas bottle to allow the gas in the gas bottle to flow into the gas inlet passageway.

(13) The detailed structure, features, assembly or usage of the inflating connector provided by the present invention will be described in the following detailed description of embodiments. However, those skilled in the field of the present invention should understand that the detailed descriptions and specific embodiments instanced for implementing the present invention are given by way of illustration only, not intended to limit the scope of the claims of the present invention.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The inflating connector of the present invention will be further described in the following embodiments and the accompanying drawings, and wherein:

(2) FIG. 1 is an assembled perspective view of an inflating connector according to a first embodiment of the present invention;

(3) FIG. 2 is a partially exploded sectional view of the inflating connector according to the first embodiment of the present invention;

(4) FIG. 3 is a perspective view of a base of the inflating connector according to the first embodiment of the present invention;

(5) FIG. 4 is an axially sectional view of the inflating connector according to the first embodiment

- of the present invention, showing the status that a gas bottle is connected to a gas bottle connecting seat;
- (6) FIG. 5 is a partial enlarged view of FIG. 4, showing the status that a throttling member approaches a connecting path;
- (7) FIG. 6 is similar to FIG. 5, showing the status that the throttling member moves away from the connecting path;
- (8) FIG. 7 is a partial enlarged view of FIG. 4, showing the status that a piston is displaced upwardly;
- (9) FIG. 8 is similar to FIG. 7, showing the status that an entrance section is closed up by a plug portion of the piston;
- (10) FIG. 9 is an axially sectional view of an inflating connector according to a second embodiment of the present invention, showing the status that a gas bottle is connected to a gas bottle connecting seat;
- (11) FIG. 10 is a partial enlarged view of FIG. 9, showing the status that a piston is displaced upwardly;
- (12) FIG. 11 is similar to FIG. 10, showing the status that an entrance section is closed up by a plug portion of a piston;
- (13) FIG. 12 is an axially sectional view of an inflating connector according to a third embodiment of the present invention, showing the status that a gas bottle is connected to a gas bottle connecting seat;
- (14) FIG. 13 is a partial enlarged view of FIG. 12, showing the status that a third gas passageway is not closed up by a switch and a piston is displaced upwardly; and
- (15) FIG. 14 is similar to FIG. 13, showing the status that the third gas passageway is closed up by the switch.

DETAILED DESCRIPTION OF THE INVENTION

- (16) First of all, it is to be mentioned that the technical features provided by the present invention are unlimited to the specific structure, usage and application thereof described in the detailed description of the invention. It should be understood by those skilled in the related art that all the terms used in the contents of the specification are for illustrative description. The directional terms mentioned in this specification, such as 'front, upper, lower, rear, left, right, top, bottom, in, and out', are also just for illustrative description on the basis of normal usage direction, not intended to limit the claimed scope.
- (17) Referring to FIG. 1, an inflating connector 1 according to a first embodiment of the present invention includes a base 10, a pressure valve 20, a gas bottle connecting seat 30, and a throttling valve 41.
- (18) Referring to FIG. 2 and FIG. 3, the base 10 has a first rod portion 11, and a second rod portion 12 opposite to the first rod portion 11. The outer peripheral surfaces of the first and second rod portions 11 and 12 each have an external thread 111 or 121. The base 10 further has an assembling passageway 13 located between the first and second rod portions 11 and 12, a first gas passageway 14 penetrating through the first rod portion 11 axially and communicating with the assembling passageway 13, and a second gas passageway 15 penetrating through the second rod portion 12 axially and communicating with the assembling passageway 13. The wall of the assembling passageway 13 has an internal thread 131. The first gas passageway 14 has an entrance section 141 communicating with the assembling passageway 13, an accommodating section 142 communicating with the entrance section 141, and an exit 143 located at the upper end of the accommodating section 142. There are an O-ring 16, a spacer 17 and a clamber 18 disposed in the second gas passageway 15 in order. The spacer 17 is abutted against the O-ring 16 for preventing the O-ring 16 from dropping off the second gas passageway 15, and an end cover 19 is screwed onto the external thread 121 of the second rod portion 12 in a way that the end cover 19 is abutted against the clamber 18 for preventing the clamber 18 from dropping off the second gas passageway

15. In this way, when the base **10** is connected with a gas nozzle, which may be but unlimited to an American valve, French valve or English valve, the clamber **18** can make the gas nozzle inserted in the second gas passageway **15** relatively more stably. Besides, the O-ring **16** prevents the gas from leaking along the wall of the second gas passageway **15**.

(19) Referring to FIG. 2 and FIG. 4, in this embodiment, the pressure valve **20** includes a cover **21**, a piston **24**, and an elastic member **28**.

(20) The cover **21** has a head portion **22**, and an annular body portion **23** connected with the head portion **22**. The head portion **22** has an opening **221**. The inner peripheral surface of the head portion **22** has an inner flange **222** protruding along radial direction of the opening **221**. The annular body portion **23** has a cover accommodating space **231**. The wall of the cover accommodating space **231** has an internal thread **232**. In practical assembly, the cover **21** is screwed onto the external thread **111** of the first rod portion **11** as shown in FIG. 3 by the internal thread **232** so that the first rod portion **11** is accommodated in the cover accommodating space **231**, and the opening **221** communicates with the exit **143** of the first gas passageway **14**.

(21) The piston **24** is movably accommodated in the accommodating section **142** of the first gas passageway **14**. The piston **24** has a rod portion **25**, a plug portion **26** connected with the rod portion **25**, and an outer flange **27** connected between the rod portion **25** and the plug portion **26**.

(22) The elastic member **28** is implemented by a coil spring. The elastic member **28** is accommodated in the accommodating section **142** of the first gas passageway **14**. An end of the elastic member **28** is abutted against the inner flange **222** of the cover **21**, and the other end is abutted against the outer flange **27** of the piston **24**. In this way, the elastic member **28** can provide an elastic restoring force acted on the piston **24** to enable the plug portion **26** of the piston **24** to close up the entrance section **141** of the first gas passageway **14**.

(23) As shown in FIG. 2 and FIG. 4, the gas bottle connecting seat **30** has an installation portion **31**, and a joining portion **36** connected with the installation portion **31**. The installation portion **31** has a gas inlet passageway **32**. The gas inlet passageway **32** includes a connecting path **33**, and an installation path **34** communicating with the connecting path **33**. As shown in FIG. 4 and FIG. 5, the wall of the installation path **34** has an internal thread **341**, and an inserting member **35** is accommodated in the installation path **34**. The outer peripheral surface of the joining portion **36** has a first external thread **361** and a second external thread **362**. The first external thread **361** and the second external thread **362** are arranged apart from each other. The joining portion **36** further has a gas outlet passageway **37** communicating with the gas inlet passageway **32**, a first connecting passageway **38** communicating with the gas outlet passageway **37**, and a second connecting passageway **39** communicating with the gas outlet passageway **37**. A communication space **40** as shown in FIG. 5 is formed between the gas outlet passageway **37**, the first and second connecting passageways **38** and **39** and the gas inlet passageway **32**. Besides, as shown in FIG. 5, the wall of the gas outlet passageway **37** has an internal thread **371**. In practical application, the gas bottle connecting seat **30** is installed on the right side of the assembling passageway **13** of the base **10** in a way that the second external thread **362** of the joining portion **36** is screwingly connected with the internal thread **131** of the assembling passageway **13** of the base **10**, making the first connecting passageway **38** and the second connecting passageway **39** communicate with the entrance section **141** of the first gas passageway **14** and the second gas passageway **15** respectively. Besides, as shown in FIG. 5, the gas bottle connecting seat **30** is screwed onto a bottleneck **5** of a gas bottle **4** by the internal thread **341** of the installation path **34**, and the inserting member **35** is inserted in the bottleneck **5** of the gas bottle **4**, thereby allowing the gas in the gas bottle **4** to flow to the gas outlet passageway **37** through the gas inlet passageway **32**.

(24) Referring to FIG. 2 and FIG. 4, in this embodiment, the throttling valve **41** includes a throttling member **42** and an operation unit **46**. The throttling member **42** has a rod-shaped body portion **43**, and a gas blocking portion **44** connected with the rod-shaped body portion **43**. As shown in FIG. 2, the right end of the rod-shaped body portion **43** has an abutted flange **431**, and an

external thread **432** arranged apart from the abutted flange **431**. The left end of the rod-shaped body portion **43** has a pivot hole **433**. In this way, as shown in FIG. 5, the rod-shaped body portion **43** of the throttling member **42** is inserted in the gas outlet passageway **37** of the gas bottle connecting seat **30**, and the external thread **432** of the rod-shaped body portion **43** is screwingly connected with the internal thread **371** of the gas outlet passageway **37** of the gas bottle connecting seat **30**.

(25) Referring to FIG. 2, the operation unit **46** includes a sleeve **47**, an elastic member **51**, a swivel cap **52**, and a pin **54**.

(26) As shown in FIG. 5, the sleeve **47** is sleeved onto the throttling member **42** and screwed onto the joining portion **36** of the gas bottle connecting seat **30**. The sleeve **47** has a bottom plate **48**, a tube-shaped body portion **49** extending from the bottom plate **48**, and a tube-shaped accommodating space **50** formed by the bottom plate **48** and the tube-shaped body portion **49**. The tube-shaped body portion **49** has an end wall **491**, and a through hole **492** penetrating through the end wall **491** and communicating with the tube-shaped accommodating space **50**. The wall of the tube-shaped accommodating space **50** has an internal thread **501**. In practical application, as shown in FIG. 4 and FIG. 5, the tube-shaped body portion **49** of the sleeve **47** is sleeved onto the throttling member **42** in a way that the rod-shaped body portion **43** of the throttling member **42** is inserted through the through hole **492**, and the internal thread **501** of the tube-shaped accommodating space **50** is screwingly connected with the first external thread **361** of the joining portion **36** of the gas bottle connecting seat **30**, making the bottom plate **48** abutted against the left side of the assembling passageway **13**.

(27) As shown in FIG. 5, the elastic member **51** is accommodated in the tube-shaped accommodating space **50** of the sleeve **47**. An end of the elastic member **51** is abutted against the end wall **491** of the tube-shaped body portion **49** of the sleeve **47**, and the other end is abutted against the abutted flange **431** of the throttling member **42**. In this way, the elastic member **51** provides an elastic restoring force acted on the throttling member **42** to enable the gas blocking portion **44** of the throttling member **42** to partially cover the connecting path **33** of the gas inlet passageway **32**.

(28) As shown in FIG. 4 and FIG. 5, the swivel cap **52** is sleeved onto the tube-shaped body portion **49** of the sleeve **47**, and the swivel cap **52** has a through hole **53**. The pin **54** is inserted through the pivot hole **433** of the throttling member **42** and the through hole **53** of the swivel cap **52**.

(29) In practical operation, as shown in FIG. 5, when the swivel cap **52** is applied with force to rotate clockwise, the pin **54** is pivoted relative to the sleeve **47** to drive the rod-shaped body portion **43** of the throttling member **42** to displace to the right along the axis of the gas outlet passageway **37**, making the gas blocking portion **44** of the throttling member **42** approach the connecting path **33** of the gas inlet passageway **32** to reduce the size of the communication space **40**. On the contrary, as shown in FIG. 6, when the swivel cap **52** is applied with force to rotate counterclockwise, the pin **54** is pivoted relative to the sleeve **47** to drive the rod-shaped body portion **43** of the throttling member **42** to displace to the left along the axis of the gas outlet passageway **37**, making the gas blocking portion **44** of the throttling member **42** move away from the connecting path **33** of the gas inlet passageway **32** to increase the size of the communication space **40**.

(30) The structures of the components of the inflating connector **1** according to the first embodiment of the present invention are described above. The usage manner of the inflating connector **1** according to the first embodiment of the present invention will be further introduced hereinafter.

(31) The user can adjust the throttling valve **41** to change the intake gas quantity of the gas. Further speaking, as shown in FIG. 5, at first the bottleneck **5** of the gas bottle **4** is screwed into the installation path **34** of the gas bottle connecting seat **30** to make the gas in the gas bottle **4** flow into the gas outlet passageway **37** through the gas inlet passageway **32**. If the intake gas quantity of the gas is over large, as shown in FIG. 5, the user has to rotate the swivel cap **52** clockwise to make the

swivel cap 52 and the pin 54 pivot clockwise relative to the sleeve 47 to drive the rod-shaped body portion 43 of the throttling member 42 to displace to the right along the axis of the gas outlet passageway 37, causing the gas blocking portion 44 of the throttling member 42 to approach the connecting path 33 of the gas inlet passageway 32, thereby reducing the size of the communication space 40, so as to reduce the intake gas quantity of the gas. If the intake gas quantity of the gas is too small, as shown in FIG. 6, the user has to rotate the swivel cap 52 counterclockwise to make the swivel cap 52 and the pin 54 pivot counterclockwise relative to the sleeve 47 and drive the rod-shaped body portion 43 of the throttling member 42 to displace to the left along the axis of the gas outlet passageway 37, causing the gas blocking portion 44 of the throttling member 42 to move away from the connecting path 33 of the gas inlet passageway 32, thereby increasing the size of the communication space 40, so as to increase the intake gas quantity of the gas.

(32) Besides, the user can adjust the pressure valve 20 to change the intake gas pressure of the gas. Further speaking, as shown in FIG. 4, at first the cover 21 is rotated downwardly relative to the first rod portion 11, and the elastic member 28 is compressed by the inner flange 222, thereby setting a predetermined pressure. In this embodiment, the cover 21 is screwingly disposed at the most bottom end of the external thread 111 of the first rod portion 11 as shown in FIG. 3. After that, the bottleneck 5 of the gas bottle 4 is screwed into the installation path 34 of the gas bottle connecting seat 30. As shown in FIG. 7, the gas flows into the gas inlet passageway 32, and flows into the entrance section 141 of the first gas passageway 14 through the first connecting passageway 38. In this embodiment, there is a gap between the plug portion 26 of the piston 24 and the wall of the accommodating section 142 of the first gas passageway 14, so it cannot be completely gastight there. At this time, if the intake gas pressure of the gas is larger than the predetermined pressure, the plug portion 26 of the piston 24 is pushed upwardly by the gas, so that the piston 24 is moved upwardly. At this time, the elastic member 28 is pushed by the piston 24 upwardly and thereby stores the elastic restoring force, so that a gap is produced between the plug portion 26 of the piston 24 and the accommodating section 142 of the first gas passageway 14, and the gas can flow out through the exit 143 of the first gas passageway 14 and the opening 221 of the cover 21 to reduce the intake gas pressure of the gas. Once the intake gas pressure of the gas is smaller than the predetermined pressure, the gas cannot push the plug portion 26 of the piston 24 upwardly anymore. At this time, the elastic restoring force stored by the elastic member 28 acts on the piston 24 to make the piston 24 move downwardly from the position as shown in FIG. 7 to the position as shown in FIG. 8, causing the plug portion 26 of the piston 24 to close up the entrance section 141 of the first gas passageway 14 again.

(33) In addition, the cover 21 can be rotated upwardly to different positions for setting different predetermined pressures. Besides, the rod portion 25 of the piston 24 may be configured to be inserted through the exit 143 of the first gas passageway 14 and the opening 221 of the cover 21, and the rod portion 25 is marked with several graduations (not shown). At this time, if the intake gas pressure of the gas is larger than the predetermined pressure, the plug portion 26 of the piston 24 is pushed by the gas upwardly, so that the piston 24 is moved upwardly. The rod portion 25 of the piston 24 protrudes out of the head portion 22 of the cover 21. The user can know about the current intake gas pressure of the gas through the graduations on the rod portion 25.

(34) However, the present invention is unlimited to that disclosed in this embodiment. Referring to FIG. 9, an inflating connector 2 according to a second embodiment of the present invention is approximately the same in structure and operation manner with the first embodiment. The primary difference is that it is completely gastight between the plug portion 26 of the piston 24 and the wall of the accommodating section 142 of the first gas passageway 14. Therefore, the gas cannot flow out along the wall of the accommodating section 142 of the first gas passageway 14. The gas all flows into the second gas passageway 15 through the second connecting passageway 39. Besides, the rod portion 25 of the piston 24 is marked with several graduations (not shown) and inserted through the exit 143 of the first gas passageway 14 and the opening 221 of the cover 21. As shown

in FIG. 10, at this time, if the intake gas pressure of the gas is larger than the predetermined pressure, the plug portion 26 of the piston 24 is pushed by the gas upwardly, so that the piston 24 is moved upwardly. At this time, the elastic member 28 is pushed by the piston 24 upwardly and thereby stores the elastic restoring force, causing the rod portion 25 of the piston 24 to protrude out of the head portion 22 of the cover 21. At this time, the user can know about the current intake gas pressure of the gas through the graduations on the rod portion 25. At this time, if the intake gas pressure of the gas is smaller than the predetermined pressure, as shown in FIG. 11, the gas cannot push the plug portion 26 of the piston 24, so that the entrance section 141 of the first gas passageway 14 is closed up by the plug portion 26 of the piston 24. In addition, the adjusting manner of the throttling valve 41 provided by this embodiment is completely the same with that of the inflating connector 1 according to the first embodiment of the present invention, thereby not repeatedly described.

(35) Referring to FIG. 12, an inflating connector 3 according to a third embodiment of the present invention is approximately the same in structure and operation manner with the second embodiment. The primary difference is that the base 10 further has a third gas passageway 112 and a fourth gas passageway 113, which penetrate through the first rod portion 11 radially. The third gas passageway 112 and the fourth gas passageway 113 are arranged apart from each other. In this embodiment, there is a gap between the plug portion 26 of the piston 24 and the wall of the accommodating section 142 of the first gas passageway 14, so it cannot be completely gastight there. The rod portion 25 of the piston 24 further has a through hole 251 penetrating therethrough, and the rod portion 25 is inserted through the exit 143 of the first gas passageway 14 and the opening 221 of the cover 21. The pressure valve 20 further includes a switch 29 sleeved onto the first rod portion 11. As shown in FIG. 13, at first the third gas passageway 112 is not closed up by the switch 29, so the gas flows into the third gas passageway 112 through the through hole 251 of the rod portion 25 of the piston 24 and flows to the fourth gas passageway 113. At this time, if the intake gas pressure of the gas is larger than the predetermined pressure, the gas flows to the accommodating section 142 of the first gas passageway 14 from the fourth gas passageway 113, flows upwardly along the wall of the accommodating section 142 of the first gas passageway 14, and then pushes the plug portion 26 of the piston 24 upwardly, so that the plug portion 26 of the piston 24 is moved upwardly. At this time, the elastic member 28 is pushed by the plug portion 26 of the piston 24 upwardly and thereby stores the elastic restoring force, so that a gap is produced between the plug portion 26 of the piston 24 and the accommodating section 142 of the first gas passageway 14. Therefore, the gas can flow out through the exit 143 of the first gas passageway 14 and the opening 221 of the cover 21, or flow out through the gap between the cover accommodating space 231 of the cover 21 and the first rod portion 11, thereby reducing the intake gas pressure of the gas. Once the intake gas pressure of the gas is smaller than the predetermined pressure, the gas cannot push the plug portion 26 of the piston 24 upwardly anymore. At this time, the elastic restoring force stored by the elastic member 28 acts on the plug portion 26 of the piston 24 to make the plug portion 26 of the piston 24 move downwardly from the position as shown in FIG. 13 to the position as shown in FIG. 14. The user can apply force to move the switch 29 downwardly relative to the first rod portion 11 from the position as shown in FIG. 13 to the position as shown in FIG. 14 to make the third gas passageway 112 closed up by the switch 29. At this time, the gas cannot flow to the fourth gas passageway 113 through the third gas passageway 112, so the gas all flows into the second gas passageway 15 through the second connecting passageway 39 and flows into the gas nozzle, so that the inflating of the bicycle tire (not shown) installed with the gas nozzle can be accomplished quickly. In addition, the adjusting manner of the throttling valve 41 provided by this embodiment is completely the same with that of the inflating connector 1 according to the first embodiment of the present invention, thereby not repeatedly described.

(36) In conclusion, the inflating connector 1, 2, 3 of the present invention changes the intake gas

quantity and intake gas pressure of the gas by the adjustments of the throttling valve **41** and the pressure valve **20**, thereby preventing the bicycle tire from burst due to the over large intake gas quantity or the over high intake gas pressure of the gas. Besides, the pressure valve **20** of the inflating connector **1**, **2**, **3** of the present invention can pre-set the intake gas pressure of the gas to make the intake gas pressure of the gas flowing into the bicycle tire smaller than the pre-set intake gas pressure, so that the user doesn't need to additionally use a pressure gauge or use an air pump having a pressure gauge to measure if the intake gas pressure is over high, that is very convenient for the user.

Claims

1. An inflating connector, which is adapted for being detachably combined with a gas bottle and a gas nozzle, the inflating connector being characterized in comprising: a base having a first rod portion, a second rod portion opposite to the first rod portion, an assembling passageway located between the first and second rod portions, a first gas passageway penetrating through the first rod portion axially and communicating with the assembling passageway, and a second gas passageway penetrating through the second rod portion axially and communicating with the assembling passageway, the first gas passageway having an entrance section communicating with the assembling passageway, an accommodating section communicating with the entrance section, and an exit located at the accommodating section, the second gas passageway being arranged for being connected with the gas nozzle; a pressure valve having a cover screwingly connected to the first rod portion, and an elastic member and a piston, which are accommodated in the accommodating section, the cover having an opening communicating with the exit, the piston being movably disposed in the accommodating section and having a plug portion capable of closing up the entrance section and a rod portion connected with the plug portion, the elastic member acting on the piston to make the plug portion close up the entrance section; a gas bottle connecting seat installed on a side of the assembling passageway, the gas bottle connecting seat having a gas inlet passageway, a gas outlet passageway communicating with the gas inlet passageway, a first connecting passageway communicating with the gas outlet passageway and the entrance section, and a second connecting passageway communicating with the gas outlet passageway and the second gas passageway, the gas inlet passageway being arranged for being connected with the gas bottle to enable gas in the gas bottle to flow to the gas outlet passageway; and a throttling valve installed on another side of the assembling passageway, the throttling valve having an operation unit and a throttling member connected with the operation unit and accommodated in the gas outlet passageway, the operation unit being arranged for driving the throttling member to displace back and forth along an axis of the gas outlet passageway to change size of a communication space between the gas outlet passageway and the first connecting passageway, the second connecting passageway and the gas inlet passageway.

2. The inflating connector as claimed in claim 1, which is characterized in that it is not completely gastight between the plug portion of the piston and a wall of the accommodating section of the first gas passageway.

3. The inflating connector as claimed in claim 1, which is characterized in that it is completely gastight between the plug portion of the piston and a wall of the accommodating section of the first gas passageway, and the rod portion of the piston is inserted through the exit of the first gas passageway and the opening of the cover.

4. The inflating connector as claimed in claim 1, which is characterized in that it is not completely gastight between the plug portion of the piston and a wall of the accommodating section of the first gas passageway, and the rod portion of the piston is inserted through the exit of the first gas passageway and the opening of the cover; the base has a third gas passageway penetrating through the first rod portion radially and communicating with the accommodating section; the pressure

valve has a switch sleeved onto the first rod portion; the switch is slidable back and forth relative to the first rod portion to close up or not close up the third gas passageway.

5. The inflating connector as claimed in claim 4, which is characterized in that the base has a fourth gas passageway penetrating through the first rod portion radially and communicating with the accommodating section, and the fourth gas passageway is arranged apart from the third gas passageway; when the third gas passageway is not closed up by the switch of the pressure valve, the gas in the gas bottle flows to the fourth gas passageway through the third gas passageway; when the third gas passageway is closed up by the switch of the pressure valve, the gas in the gas bottle is disabled from flowing to the fourth gas passageway through the third gas passageway.

6. The inflating connector as claimed in claim 1, which is characterized in that the operation unit of the throttling valve comprises a sleeve sleeved onto the throttling member, an elastic member accommodated in the sleeve, and a pin inserted in the throttling member; the elastic member acts on the throttling member to make the throttling member partially close up the communication space; the throttling member has an external thread; a wall of the gas outlet passageway of the gas bottle connecting seat has an internal thread; the pin is pivotable relative to the sleeve to drive the throttling member in a way that the external thread of the throttling member is guided by the internal thread of the gas outlet passageway to make the throttling member displace back and forth along the axis of the gas outlet passageway.

7. The inflating connector as claimed in claim 1, which is characterized in that the gas inlet passageway of the gas bottle connecting seat has a connecting path and an installation path communicating with the connecting path, and a wall of the installation path has an internal thread; the gas bottle connecting seat has an inserting member accommodated in the installation path; the internal thread of the installation path is arranged for being screwingly connected with a bottleneck of the gas bottle so that the inserting member is inserted in the bottleneck of the gas bottle.
