

# US Patent & Trademark Office

## Patent Public Search | Text View

---

|                      |                    |
|----------------------|--------------------|
| United States Patent | 12399215           |
| Kind Code            | B2                 |
| Date of Patent       | August 26, 2025    |
| Inventor(s)          | Nagashima; Hideaki |

---

### Housing and prober

---

#### Abstract

A housing for a prober having a multi-layer structure in which measuring parts are stacked includes: floor bases configured to floor surfaces of respective layers of the multi-layer structure; and at least one side frame body which is arranged between a floor base of one layer and a floor base of another layer positioned above the one layer among the plurality of layers, and which is positioned in both side parts of the measuring parts, wherein the side frame body includes: a first side frame which is erected on the floor base of the one layer and which supports a lower surface side of the floor base of the another layer; and a second side frame which is erected on the floor base of the one layer at a position different from that of the first side frame, and supports a measuring part constituent member arranged in the measuring part.

---

|                   |                                             |
|-------------------|---------------------------------------------|
| <b>Inventors:</b> | <b>Nagashima; Hideaki (Tokyo, JP)</b>       |
| <b>Applicant:</b> | <b>Tokyo Seimitsu Co., Ltd. (Tokyo, JP)</b> |
| <b>Family ID:</b> | <b>1000008779992</b>                        |
| <b>Assignee:</b>  | <b>TOKYO SEIMITSU CO., LTD. (Tokyo, JP)</b> |
| <b>Appl. No.:</b> | <b>18/731040</b>                            |
| <b>Filed:</b>     | <b>May 31, 2024</b>                         |

#### Prior Publication Data

|                            |                         |
|----------------------------|-------------------------|
| <b>Document Identifier</b> | <b>Publication Date</b> |
| US 20240319264 A1          | Sep. 26, 2024           |

#### Foreign Application Priority Data

|    |             |               |
|----|-------------|---------------|
| JP | 2021-196404 | Dec. 02, 2021 |
|----|-------------|---------------|

#### Related U.S. Application Data

## Publication Classification

**Int. Cl.:** G01R31/28 (20060101)

**U.S. Cl.:**

**CPC** G01R31/2893 (20130101);

## Field of Classification Search

**CPC:** G01R (31/2887); G01R (1/06722); G01R (1/07314); G01R (1/07342); G01R (31/26); G01R (31/2867); G01R (31/2893); G01R (31/318511); G01R (1/0491); G01R (31/2862); G01R (31/2863); G01R (31/2886); G01R (31/2891); G01R (31/31907); H01L (21/67242); H01L (21/67253); H01L (21/67259); H01L (22/14); H01L (22/20); H01L (22/30)

**USPC:** 324/757.03

---

## References Cited

### U.S. PATENT DOCUMENTS

| Patent No.   | Issued Date | Patentee Name | U.S. Cl. | CPC |
|--------------|-------------|---------------|----------|-----|
| 2018/0017594 | 12/2017     | Tamura        | N/A      | N/A |
| 2021/0088588 | 12/2020     | Endo          | N/A      | N/A |

### FOREIGN PATENT DOCUMENTS

| Patent No.      | Application Date | Country | CPC          |
|-----------------|------------------|---------|--------------|
| 108470690       | 12/2017          | CN      | N/A          |
| 2016-181639     | 12/2015          | JP      | N/A          |
| 2016-181690     | 12/2015          | JP      | N/A          |
| 2017-28296      | 12/2016          | JP      | N/A          |
| 2019109242      | 12/2018          | JP      | G01R 31/28   |
| 2021-52065      | 12/2020          | JP      | N/A          |
| 10-2021-0019193 | 12/2020          | KR      | N/A          |
| 20210019193     | 12/2020          | KR      | G01R 31/2893 |

### OTHER PUBLICATIONS

Espacenet English translation of JP 2019109242 A (Year: 2019). cited by examiner  
 Espacenet English translation of KR 20210019193 A (Year: 2021). cited by examiner  
 Espacenet translation of Nagashima JP2019109242A Enclosure (Year: 2019). cited by examiner  
 International Preliminary Report on Patentability for PCT/JP2022/036737 (PCT/IPEA/409) dated Jul. 13, 2023. cited by applicant  
 International Search Report for PCT/JP2022/036737 (PCT/ISA/210) mailed on Dec. 20, 2022. cited by applicant  
 Written Opinion for PCT/JP2022/036737 (PCT/ISA/237) dated Dec. 20, 2022. cited by applicant  
 Chinese Office Action and Search Report for corresponding Chinese Application No. 202280079960.4, dated Oct. 12, 2024, with an English translation. cited by applicant

*Primary Examiner:* Alkafawi; Eman A

*Assistant Examiner:* McDonnough; Courtney G

*Attorney, Agent or Firm:* Birch, Stewart, Kolasch & Birch, LLP

---

## **Background/Summary**

CROSS-REFERENCE TO RELATED APPLICATIONS (1) The present application is a Continuation of PCT International Application No. PCT/JP2022/036737 filed on Sep. 30, 2022 claiming priority under 35 U.S.C § 119(a) to Japanese Patent Application No. 2021-196404 filed on Dec. 2, 2021. Each of the above applications is hereby expressly incorporated by reference, in their entirety, into the present application.

## **BACKGROUND OF THE INVENTION**

### **Field of the Invention**

(1) The present invention relates to a prober for an inspection of electrical characteristics of semiconductor devices (chips) formed on a semiconductor wafer and, particularly, to a housing for a prober including a plurality of measuring parts stacked in multiple stages and to a prober to which the housing is applied.

### **Description of the Related Art**

(2) A semiconductor manufacturing process includes a large number of steps and various inspections are performed in various manufacturing steps in order to guarantee product quality and improve production yield. For example, in a stage where chips of semiconductor devices have been formed on a semiconductor wafer, a wafer-level inspection is performed in which an electrode pad of a semiconductor device of each chip is connected to a test head, power and a test signal are supplied from the test head, and a signal outputted from the semiconductor device is measured by the test head to electrically inspect whether or not the semiconductor device operates properly.

(3) The wafer-level inspection is performed using a prober which brings a probe into close contact with the electrode pad of each chip on the wafer. The probe is electrically connected to a terminal of the test head. Then, power and a test signal are supplied to each chip from the test head via the probe, and output signal from each chip are detected by the test head to measure whether or not each chip operates properly.

(4) In semiconductor manufacturing processes, upsizing of wafers and further micronizing (integration) are being promoted in order to reduce manufacturing costs, and there has been a significant increase in the number of chips to be formed on one wafer. Accordingly, given that a period of time required to inspect one wafer with a prober is becoming longer, there is a need for improvements in throughput.

(5) Hence, in order to improve throughput, a large number of probes are provided to perform multi-probing so that a plurality of chips may be simultaneously inspected. Recently, the number of chips to be simultaneously inspected has been more and more increased, and attempts have even been made to simultaneously inspect all of the chips on a wafer. To this end, an allowable error of alignment when bringing an electrode pad and a probe into contact with each other is becoming smaller and, consequently, higher positional accuracy in movement of probes is required.

(6) While increasing the number of probers is conceivable as the simplest method of increasing throughput, increasing the number of probers also creates a problem in that an installation area of

probers on a production line also increases. In addition, increasing the number of probers also results in proportionally increasing device cost. Therefore, there is a need to increase throughput while suppressing the increase in the installation area and the increase in device cost.

(7) To address such problems, probers having a plurality of measuring parts stacked in multiple stages are being proposed (for example, refer to Patent Literature 1 and Patent Literature 2). Since these probers have a multi-layer structure (multi-stage structure) in which the measuring parts are stacked in multiple stages, a wafer-level inspection can be performed by each measuring part so that throughput may be improved while suppressing the increase in installation area and the increase in device cost.

(8) On the other hand, Patent Literature 3 relates to an inspection device in which a plurality of testers are arranged in a multi-layer structure, and a conveyance stage which conveys a wafer to a tester is provided to each layer. Patent Literature 3 discloses a technique to suppress an effect of vibration created by the operation of the conveyance stages of other layers. In Patent Literature 3, when the conveyance stage of one layer among the multi-layer structure is in operation, a controller which controls movement of the conveyance stage of each layer perform control so as to restrict operations of the conveyance stages of other layers in order to suppress an effect of vibration created by the operation of the conveyance stages of other layers.

#### CITATION LIST

(9) Patent Literature 1: Japanese Patent Application Laid-Open No. 2017-028296 Patent Literature 2: Japanese Patent Application Laid-Open No. 2016-181690 Patent Literature 3: Japanese Patent Application Laid-Open No. 2021-052065

#### SUMMARY OF THE INVENTION

(10) Each of the probers disclosed in Patent Literature 1 and Patent Literature 2 includes an alignment device (moving stage) for each layer, which detachably holds a wafer chuck and performs relative positioning (alignment) between a wafer held by the wafer chuck and a probe card. The alignment device is configured to be movable among measuring parts arranged on each layer. When such a prober is constructed using a housing (an integrated housing) in which a plurality of frames that form a plurality of compartments are combined and integrated with each other, the following problem arises.

(11) In the probers described above, since the alignment device capable of moving among measuring parts is provided on each layer, the probers are structured in such a manner that when the alignment device is moved on one layer, vibration caused by the movement of the alignment device readily propagates to a measuring part arranged on other layers via the frames that make up the housing. As a result, there is a risk that due to a decline in accuracy of alignment, sufficient contact accuracy between the wafer and probes of a probe card may no longer be secured so that inspection accuracy may deteriorate.

(12) On the other hand, with the technology disclosed in Patent Literature 3, since the movement of the conveyance stage on other layers is restricted when the conveyance stage on one layer among the plurality of layers is in operation, there is a risk that a period of time required for the movement of the conveyance stage may increase so that throughput of the inspection may decline.

(13) In addition, the technique disclosed in Patent Literature 3 also has a problem in that the technique is only effective to vibration due to a movement of a conveyance stage and is ineffective to vibration constantly generated due to other factors such as vibration caused by an abnormality of a test head of another layer.

(14) The present invention has been made in consideration of the circumstances described above, and aims to provide, a housing for a prober having a multi-layer structure in which a plurality of measuring parts are stacked in multiple stages, the housing capable of effectively reducing adverse effect of vibration generated on each layer without deterioration in throughput of inspection, and a prober to which the housing is applied.

(15) The following invention is provided in order to solve the problems described above.

- (16) A housing for a prober according to a first aspect is a housing for a prober having a multi-layer structure in which a plurality of measuring parts are stacked in multiple stages. The housing for a prober includes: floor bases configured to constitute floor surfaces of respective layers of the multi-layer structure; and at least one side frame body which is arranged between a floor base of one layer and a floor base of another layer positioned above the one layer among the plurality of layers, and positioned in both side parts of the measuring parts, wherein the side frame body includes: a first side frame which is erected on the floor base of the one layer and supports a lower surface side of the floor base of the another layer; and a second side frame which is erected on the floor base of the one layer at a position different from that of the first side frame, and supports a measuring part constituent member arranged in each measuring part.
- (17) According to a second aspect, in the housing for a prober according to the first aspect, the side frame body is arranged on a layer other than an uppermost layer among the plurality of layers. Making the configuration of the uppermost layer to be simpler than the layers other than the uppermost layer, enables the uppermost layer to be lighter so that a structure of the entire housing may be stabilized.
- (18) According to a third aspect, the housing for a prober according to the second aspect further includes a head plate having a holding unit configured to hold the measuring part constituent member, wherein a lower surface side of the head plate is supported by the second side frame.
- (19) According to a fourth aspect, in the housing for a prober according to any one of the first to third aspects, the second side frame is juxtaposed to the first side frame at a position adjacent to the first side frame.
- (20) According to a fifth aspect, in the housing for a prober according to any one of the first to fourth aspects, the measuring part constituent member is one of a pogo frame, a probe card and a test head.
- (21) A prober according to a sixth aspect includes the housing for a prober according to any one of the first to fifth aspects, wherein at least two or more measuring parts are provided on the one layer, and the prober includes a moving stage capable of moving a wafer to be inspected to each of the measuring parts arranged on the one layer.
- (22) According to the present invention, in a housing for a prober having a multi-layer structure in which a plurality of measuring parts are stacked in multiple stages, an effect of vibration generated on each layer may be effectively reduced, without deterioration in throughput of inspection.
- 

## **Description**

### **BRIEF DESCRIPTION OF THE DRAWINGS**

- (1) FIG. 1 is an external view showing an overall configuration of a prober according to a present embodiment.
- (2) FIG. 2 is a plan view of the prober shown in FIG. 1.
- (3) FIG. 3 is a diagram (front view) showing an internal structure of a measurement unit shown in FIG. 1.
- (4) FIG. 4 is a diagram (side view) showing an internal structure of a measurement unit shown in FIG. 1.
- (5) FIG. 5 is a schematic diagram showing a configuration of a measuring part.
- (6) FIG. 6 is a diagram showing a state where a test head, a pogo frame, a probe card, and a wafer chuck are integrated.
- (7) FIG. 7 is a diagram (front view) showing another configuration example (comparative example) of a housing.
- (8) FIG. 8 is a diagram (side view) showing another configuration example (comparative example) of a housing.

(9) FIG. **9** is a diagram for explaining an effect of a housing according to the present embodiment.  
(10) FIG. **10** is a diagram for explaining an effect of the housing according to the present embodiment.

(11) FIG. **11** is a diagram (side view) showing a modification example of the housing according to the present embodiment.

## DESCRIPTION OF THE EMBODIMENTS

(12) Hereinafter, a preferred embodiment of the present invention will be described with reference to the accompanying drawings. Firstly, a prober **100** according to the present embodiment will be described, then a housing **1** to be applied to the prober **100** will be described.

(13) [Prober]

(14) First, a configuration of the prober **100** will be described with reference to FIGS. **1** and **2**. FIG. **1** is an external view showing an overall configuration of the prober **100**. FIG. **2** is a plan view of the prober **100** shown in FIG. **1**.

(15) As shown in FIGS. **1** and **2**, the prober **100** according to the present embodiment includes a loader unit **114** which supplies and collects a wafer **W** (refer to FIG. **5**) to be inspected, and a measurement unit **112** which is arranged adjacent to the loader unit **114**. The measurement unit **112** includes measuring parts **30** and when the wafer **W** (inspection object) is supplied to each measuring part **30** from the loader unit **114**, an inspection (wafer-level inspection) of electrical characteristics is respectively performed for each chip of the wafer **W** in each measuring part **30**. Then, the wafer **W** inspected in each measuring part **30** is collected by the loader unit **114**. Note that the prober **100** is also equipped with an operating panel **121**, a control device (not illustrated) for controlling the respective units, and the like.

(16) The loader unit **114** has a load port **118** on which a wafer cassette **120** is placed and a conveyance unit **122** which conveys the wafer **W** between each measuring part **30** of the measurement unit **112** and the wafer cassette **120**. The conveyance unit **122** is equipped with a conveyance unit drive mechanism (not illustrated) and is configured to be movable in X and Z directions and rotatable in a  $\theta$  direction (around the Z direction). In addition, the conveyance unit **122** is equipped with a conveyance arm **124** and is capable of stretching and contracting the conveyance arm **124** in the Y direction with the conveyance unit drive mechanism. A suction pad (not illustrated) is provided in an upper surface part of the conveyance arm **124**, and the conveyance arm **124** holds the wafer **W** by subjecting a rear surface of the wafer **W** to vacuum suction with the suction pad. Accordingly, the wafer **W** inside the wafer cassette **120** is extracted by the conveyance arm **124** of the conveyance unit **122** and conveyed to each measuring part **30** of the measurement unit **112** in a state of being held by the upper surface of the conveyance arm **124**. In addition, the inspected wafer **W** for which the inspection has been finished is returned to the wafer cassette **120** from each measuring part **30** via a reverse route.

(17) FIGS. **3** and **4** are diagrams showing an internal structure of the measurement unit **112** shown in FIG. **1**. FIG. **3** is a diagram of the measurement unit **112** as viewed from a front surface side (side of the loader unit **114**) and FIG. **4** is a diagram of the measurement unit **112** as viewed from a side surface side.

(18) As shown in FIGS. **3** and **4**, the measurement unit **112** has a multi-layer structure (multi-stage structure) in which the measuring parts **30** are stacked in multiple stages, and the respective measuring parts **30** are two-dimensionally arrayed in the X direction and the Z direction. In the present embodiment, as an example, four measuring parts **30** arranged in the X direction, are stacked in three stages in the Z direction.

(19) The measurement unit **112** is equipped with the housing **1** which partitions the measuring unit **112** to form the measuring parts **30**. The housing **1** has a grid shape in which frames are combined in a grid pattern. A configuration of the housing **1** will be described in detail later.

(20) The respective measuring parts **30** have the same configuration. As shown in FIG. **5**, the measuring parts **30** includes a head plate **44**, a test head **43**, a probe card **42**, and a pogo frame **41**

interposed between the test head **43** and the probe card **42**.

(21) The test head **43** is supported above the head plate **44** by a test head holding part (not illustrated). The test head **43** is electrically connected to probes **66** of the probe card **42**. The test head **43** supplies each chip with power and a test signal for an electrical inspection, and detects an output signal from each chip to measure whether or not each chip operates properly.

(22) The head plate **44** is supported by the housing **1**, and includes a pogo frame mounting part **53**. The pogo frame mounting part **53** has a circular opening that corresponds to a planar shape of the pogo frame **41**. The pogo frame mounting part **53** has a positioning pin **63** and the pogo frame **41** is fixed to the pogo frame mounting part **53** in a state of being positioned by the positioning pin **63**. A fixing method of the pogo frame **41** is not particularly limited. For example, as a method of fixing the pogo frame **41**, a method of causing the pogo frame **41** to be sucked by vacuum suction on a support surface (suction surface) of the pogo frame mounting part **53** using suction means (not illustrated), may be preferably used. As fixing means other than vacuum suction, mechanical fixing means such as screws may be used.

(23) The pogo frame **41** has a large number of pogo pins (not illustrated) which electrically connect each terminal formed on a lower surface (a surface opposing the pogo frame **41**) of the test head **43** to each terminal formed on an upper surface (a surface opposing the pogo frame **41**) of the probe card **42**. In addition, sealing members **60** and **62** respectively having ring shapes are formed in outer circumferential parts of an upper surface (a surface opposing the test head **43**) and a lower surface (a surface opposing the probe card **42**) of the pogo frame **41**. Furthermore, the test head **43**, the pogo frame **41**, and the probe card **42** are integrated in a case where a space enclosed by the test head **43**, the pogo frame **41** and the sealing member **60**, and a space enclosed by the probe card **42**, the pogo frame **41** and the sealing member **62** are depressurized by suction means (not illustrated).

(24) The probe card **42** includes a large number of probes **66** corresponding to electrodes of the respective chips of the wafer **W**. Each probe **66** is formed so as to protrude downward from a lower surface (a surface opposing a wafer chuck **150**) of the probe card **42** and is electrically connected to each terminal provided on the upper surface (the surface opposing the pogo frame **41**) of the probe card **42**. Therefore, when the test head **43**, the pogo frame **41**, and the probe card **42** are integrated, each probe **66** is electrically connected to each terminal of the test head **43** via the pogo frame **41**. Note that the probe card **42** in the present example is equipped with the large number of probes **66** corresponding to electrodes of all of the chips of the wafer **W** to be inspected, and simultaneous inspections are performed for the chips on the wafer **W** held by the wafer chuck **150**, in the respective measuring parts **30**.

(25) The wafer chuck **150** sucks and fixes the wafer **W** by vacuum suction or the like. The wafer chuck **150** is detachably supported by an alignment device **13** to be described later and is configured to be movable in the X, Y, Z, and  $\theta$  directions by the alignment device **13**. In addition, a ring-shaped sealing member **64** is provided in an outer circumferential part of an upper surface (wafer placement surface) of the wafer chuck **150**. A space enclosed by the probe card **42**, the wafer chuck **150** and the sealing member **64** is depressurized by suction means (not illustrated) so that the wafer chuck **150** is drawn towards the probe card **42**. Accordingly, each probe **66** of the probe card **42** comes into contact with an electrode pad of each chip of the wafer **W** so that an inspection may be started.

(26) A heating/cooling mechanism (not illustrated) as a heating/cooling source is provided inside the wafer chuck **150** so that electrical characteristics of the chips may be inspected in a high-temperature state (for example, 150° C. at maximum) or in a low-temperature state (for example, -40° C. at minimum). An appropriate known heater/cooler may be adopted as the heating/cooling mechanism, and various heating/cooling mechanisms are conceivable. For example, the heating/cooling mechanism may be a mechanism having a double layer structure of: a heating layer with planer heater; and a cooling layer with a pathway for a cooling fluid. For further example, the heating/cooling mechanism may be a heating/cooling device with a single layer structure of a

thermal conductor embedded with a cooling tube around which a heating heater is wound. In addition, instead of electrical heating, a thermal fluid may be circulated or a Peltier element may be used.

(27) The measurement unit **112** is further equipped with the alignment device **13** which detachably supports the wafer chuck **150**. The alignment device **13** is provided on each stage and is configured to be mutually movable among measuring parts **30** arranged on the each layer (each stage) by an alignment device drive mechanism (not illustrated). In other words, the alignment device **13** is shared by measuring parts **30** (in the present example, four measuring parts **30**) which are arranged on the same layer (stage) as the alignment device **13**, and moves among the measuring parts **30** arranged on the same layer. Note that the alignment device **13** is an example of the “moving stage” according to the present invention. In addition, once the alignment device **13** moves to each measuring part **30**, the alignment device **13** is fixed by a positioning/fixing device (not illustrated), and then the wafer chuck **150** is moved in the X, Y, Z, and  $\theta$  directions by the alignment device drive mechanism described above so as to perform relative positioning between the wafer W being held by the wafer chuck **150** and the probe card **42**. Although not illustrated, the alignment device **13** is equipped with a probe tip position detection camera and a wafer alignment camera in order to detect a relative positional relationship between electrodes of chips of the wafer W held by the wafer chuck **150** and the probes **66**.

(28) While the alignment device **13** sucks and fixes the wafer chuck **150** by vacuum suction or the like, fixing means other than vacuum suction may be adopted as long as the wafer chuck **150** may be fixed. For example, the wafer chuck **150** may be fixed by mechanical means or the like. In addition, the alignment device **13** is provided with positioning means (not illustrated) so that the definite relative positional relationship with the wafer chuck **150** may be maintained.

(29) Next, an inspection method using the prober **100** according to the present embodiment will be described.

(30) When an inspection is performed using the prober **100** according to the present embodiment, in the loader unit **114**, the wafer W inside the wafer cassette **120** is extracted by the conveyance arm **124** of the conveyance unit **122** and conveyed to each measuring part **30** of the measurement unit **112** in a state of being held by the upper surface of the conveyance arm **124**.

(31) On the other hand, in the measurement unit **112**, the alignment device **13** provided for each layer (each stage) moves to a predetermined measuring part **30** and the wafer chuck **150** is positioned on an upper surface of the alignment device **13** and fixed by suction.

(32) Subsequently, the alignment device **13** moves the wafer chuck **150** to a predetermined delivery position. In addition, once the wafer W is delivered by the conveyance unit **122** of the loader unit **114**, the wafer W is held on the upper surface of the wafer chuck **150**.

(33) Next, the alignment device **13** moves the wafer chuck **150** holding the wafer W thereon, to a predetermined alignment position, and detects relative positional relationship between the electrodes of the chips of the wafer W held by the wafer chuck **150** and the probes **66** using the probe tip position detection camera and the wafer alignment camera (both not illustrated). Then, the alignment device **13** moves the wafer chuck **150** in the X, Y, Z, and  $\theta$  directions based on the detected positional relationship to perform relative positioning between the wafer W held by the wafer chuck **150** and the probe card **42**.

(34) After the positioning is performed, the alignment device **13** moves the wafer chuck **150** to a predetermined measurement position (a position opposing the probe card **42**) and moves the wafer chuck **150** upward until a height of the wafer chuck **150** equals a predetermined height (specifically, a height at which the sealing member **64** formed on the upper surface of the wafer chuck **150** comes into contact with the lower surface (the surface opposing the wafer chuck **150**) of the probe card **42**). At this point, preferably, suction by suction means (not illustrated) is started before the sealing member **64** comes into contact with the lower surface of the probe card **42** (in other words, before the space enclosed by the probe card **42**, the wafer chuck **150**, and the sealing



member **64** becomes a sealed space). Accordingly, since suction is being performed by the suction means, an effect of a reactive force (counterforce) due to compression of the space can be prevented even if the wafer chuck **150** is moved upward. Note that the suction by the suction means may be started at the same timing when the sealing member **64** comes into contact with the lower surface of the probe card **42**.

(35) Subsequently, the alignment device **13** releases the fixing of the wafer chuck **150**. Accordingly, the wafer chuck **150** detaches from the alignment device **13**. In addition, because the space enclosed by the probe card **42**, the wafer chuck **150** and the scaling member **64** is depressurized due to suction by the suction means, the wafer chuck **150** is drawn towards the probe card **42** so as to be brought into close contact with the probe card **42**. and the wafer chuck **150** As a result, the respective probes **66** of the probe card **42** come into contact with the electrode pads of the respective chips on the wafer W with uniform contact pressure.

(36) Thus, as shown in FIG. **6**, the measuring part **30** assumes a state where the test head **43**, the pogo frame **41**, the probe card **42**, and the wafer chuck **150** are integrated so that a wafer-level inspection may be started.

(37) Subsequently, power and a test signal are supplied to each chip on the wafer W from the test head **43**, and the inspection of an electrical operation is performed by detecting a signal outputted from each chip.

(38) Thereafter, with respect to other measuring parts **30**, the wafer W is supplied onto the wafer chuck **150**, and after an alignment operation and a contact operation are completed simultaneous inspections of the respective chips on the wafer W are sequentially performed in each measuring part **30**, according to a similar procedure. In other words, in each measuring part **30**, power and a test signal are supplied to each chip on the wafer W from the test head **43** and an inspection of an electrical operation is performed by detecting a signal outputted from each chip.

(39) Once the inspection is completed in the respective measuring parts **30**, the alignment device **13** is sequentially moved to the respective measuring parts **30** and the wafer chuck **150** holding the inspected wafer W is collected.

(40) Specifically, when the alignment device **13** moves to the measuring part **30** where the inspection has been finished, the alignment device **13** is moved upward to a position where the upper surface of the alignment device **13** abuts with the wafer chuck **150** and the depressurization of the space enclosed by the probe card **42**, the wafer chuck **150** and the scaling member **64** is released. In addition, the alignment device **13** positions and fixes the wafer chuck **150** to the upper surface of the alignment device **13**. Furthermore, the alignment device **13** moves the wafer chuck **150** to a predetermined delivery position, unfixes the inspected wafer W from the wafer chuck **150**, and delivers the inspected wafer W to the conveyance unit **122**. The inspected wafer W delivered to the conveyance unit **122** is held by the conveyance arm **124** and returned to the wafer cassette **120** arranged in the loader unit **114**.

(41) While one wafer chuck **150** is respectively assigned to each measuring part **30** in the present embodiment as shown in FIGS. **3** and **4**, the wafer chuck **150** may be shared among measuring parts **30**. In this case, the alignment device **13** moves the wafer chuck **150** among the measuring parts **30** which share the wafer chuck **150**.

(42) [Housing]

(43) Next, a configuration of the housing **1** applied to the prober **100** according to the present embodiment will be described in detail. The housing **1** is an example of the "housing for a prober" according to the present invention.

(44) As shown in FIGS. **3** and **4**, in the housing **1** according to the present embodiment, frames are combined to have a grid pattern so as to form compartments corresponding to the measuring parts **30** on each layer. In the housing **1**, in order to effectively suppress vibration generated in the prober **100** (such as vibration created by a movement of the alignment device **13** and vibration constantly generated in each measuring part **30**), a frame (the side frame body **20**) arranged on each layer (in

the present embodiment, with the exception of the uppermost layer) has a divided frame structure. While details will be provided later, the side frame body **20** arranged on one layer is configured so as to include: a first side frame **21** which supports another layer arranged above the one layer; and a second side frame **22** which supports a measuring part constituent member (which includes the head plate **44**, the pogo frame **41**, the probe card **42**, and the test head **43**) arranged in the measuring parts **30** in the one layer. In the following description, the respective layers in FIGS. **3** and **4** will be referred to as a first layer, a second layer, and a third layer, from bottom to top. In the example shown in FIGS. **3** and **4**, the first layer is a lowermost layer and the third layer is an uppermost layer.

(45) First, in the housing **1** according to the present embodiment, a configuration of the uppermost layer differs from a configuration of layers other than the uppermost layer due to reasons to be described later. Firstly, the configuration of layers other than the uppermost layer or, in other words, a configuration of the first and second layers in FIGS. **3** and **4** will be described.

(46) Each layer other than the uppermost layer includes: a floor base **10** which constitutes a floor surface of each layer of the multi-layer structure; and side frame bodies **20** which are provided between the floor bases **10** of the respective layers. The floor base **10** has a flat plate shape which is elongated in the X direction (that is, a longitudinal direction of the floor base **10** is the X direction) and which is parallel to the XY plane. Preferably, the floor base **10** is formed so as to be shared among the measuring parts **30** (compartments) provided on one layer.

(47) In addition, preferably, on layers other than the uppermost layer, a ceiling of the floor base **10** of a given layer doubles (serves) as a floor base **10** of another layer immediately below the given layer. For example, in FIGS. **3** and **4**, the floor base **10** of the third layer doubles as a ceiling of the floor base **10** of the second layer.

(48) Preferably, an upper surface of the floor base **10** of each layer is provided with a guide rail (or guide rails) (not illustrated) which guides a movement of the alignment device **13** in the X direction.

(49) The side frame bodies **20** are arranged between the floor base **10** of a given layer and the floor base **10** of another layer positioned above the given layer, and arranged in both end parts in the Y direction (both side parts in the Y direction) of the floor base **10**.

(50) There are two types of the side frame bodies **20**: a first side frame **21** and a second side frame **22** which is provided separately from the first side frame **21**.

(51) For example, the first side frame **21** has a columnar shape that extends in the Z direction. In addition, one end of the first side frame **21** is arranged at, for example, an end in the Y direction of an upper surface of the floor base **10** of a given layer and another end of the first side frame **21** is arranged at, for example, an end in the Y direction of a lower surface of the floor base **10** of another layer positioned above the given layer.

(52) In other words, the first side frame **21** is erected on a side of the upper surface (a surface on which the guide rail is formed) of the floor base **10** of a given layer and supports a side of the lower surface (a surface on an opposite side to the surface on which the guide rail is formed) of the floor base **10** of another layer positioned above the given layer.

(53) According to FIG. **4**, for example, the first side frame **21** of the second layer supports the floor base **10** of the third layer (uppermost layer). By coupling the floor bases **10** in the Z direction by the first side frames **21**, a multi-layer structure in which multiple stages are stacked in the Z direction is formed.

(54) The second side frame **22** is erected on the upper surface of the floor base **10** of each layer at a position which differs from that of the first side frame **21**. For example, as shown in FIG. **4**, the second side frame **22** is juxtaposed (parallelly arranged) to the first side frame **21** at a position adjacent to the first side frame **21**. In addition, the second side frames **22** are preferably arranged at constant intervals in the X direction. Specifically, the second side frames **22** are respectively arranged between the measuring parts **30**, and on outer sides of the measuring parts **30** at both ends

in the X direction.

(55) For example, each second side frame **22** has an approximately gate-like shape. Each second side frame **22** includes: two column parts **221** which extend in the Z direction; and a beam part **222** which spans between the two column parts **221** and extends in the Y direction. Note that the shape of the beam part **222** is not necessarily a straight rod shape. The shape of the beam part **222** may be appropriately changed or modified according to a shape and desirable arrangement of the measuring part constituent member (to be described later). For example, the two column parts **221** of the second side frames **22** are arranged in the vicinity of both ends in the Y direction of the respective measuring parts **30**.

(56) The measuring part constituent member arranged in each measuring part **30** on each layer other than the uppermost layer includes the head plate **44**, the pogo frame **41**, the probe card **42**, and the test head **43**. The head plate **44** is a flat plate-shaped member arranged in the measuring part **30** and, as described above, includes the pogo frame mounting part **53** (refer to FIG. 5). The pogo frame **41** is fixed to the pogo frame mounting part **53** of the head plate **44**. In addition, the pogo frame **41** is configured such that the test head **43** and the probe card **42** are respectively integrated on upper surface and lower surface of the pogo frame **41** by suction means (not illustrated). In other words, the head plate **44** is a member which directly or indirectly supports the pogo frame **41**, the probe card **42**, and the test head **43** which constitute the measuring part constituent member.

(57) The head plate **44** configured in this manner is supported by the second side frame **22** (more specifically, the beam part **222**). Preferably, a position (support position) where the head plate **44** is supported by the second side frame **22** is the lower surface of the head plate **44**. However, the support position is not necessarily limited thereto, and may be another position (for example, a side surface of the head plate **44**). Accordingly, the measuring part constituent member arranged in each measuring part **30** of each layer other than the uppermost layer is respectively directly or indirectly supported by the second side frame **22** and the inspection described above is to be performed in each measuring part **30**.

(58) As described above, on each of the layers other than the uppermost layer, the first side frame **21** which supports the floor base **10** of an upper layer is separately provided from the second side frame **22** which supports the measuring part constituent member arranged on the own layer.

(59) Next, a configuration of the uppermost layer will be described. The uppermost layer includes the floor base **10**, uppermost layer side frame bodies **23**, and a frame part **24**. In the uppermost layer (the third layer in FIGS. 3 and 4), while the uppermost layer side frame bodies **23** may have a same configuration as the side frame bodies **20** of the other layers as in a modification (refer to FIG. 11) to be described later, since there is no need to support the floor base **10** of an upper layer, the side frame body **20** need not be configured to have two mutually different types of frames (the first side frame **21** and the second side frames **22**) as in each of the layers other than the uppermost layer. In addition, when the uppermost layer has a simpler configuration to reduce its weight, the overall configuration of the housing **1** may be made more stable.

(60) Due to these reasons, in the uppermost layer, the uppermost layer side frame bodies **23** have a simpler configuration than the side frame bodies **20** of the other layers. More specifically, the uppermost layer side frame bodies **23** have both functions of supporting a ceiling (not illustrated) and supporting the measuring part constituent member. In other words, the uppermost layer side frame bodies **23** function as the first side frame **21** and the second side frame **22** in the side frame bodies **20** of the other layers.

(61) As shown in FIGS. 3 and 4, the uppermost layer side frame bodies **23** are arranged at positions that almost correspond to the second side frames **22** and have approximately the same shape as the second side frames **22**. In other words, the uppermost layer side frame bodies **23** are erected on the upper surface of the floor base **10** of the uppermost layer in a similar manner to the second side frames **22**. Furthermore, the uppermost layer side frame bodies **23** are arranged at constant intervals

in the X direction. Specifically, the uppermost layer side frame bodies **23** are respectively arranged between the measuring parts **30**, and on outer sides of the measuring parts **30** at both ends in the X direction.

(62) The uppermost layer side frame bodies **23** have an approximately gate-like shape. The uppermost layer side frame bodies **23** includes: two column parts **231** which extend in the Z direction; and a beam part **232** which spans between the two column parts **231** and extends in the Y direction. Upper end sides of the column parts **231** exceed the beam part **232** and extend to the frame part **24** which constitutes a ceiling of the uppermost layer.

(63) The shape of the beam part **232** may be appropriately changed or modified according to a shape and desirable arrangement of the measuring part constituent member. For example, the two column parts **231** of the uppermost layer side frame bodies **23** are arranged in the vicinity of both ends in the Y direction of the respective measuring parts **30**.

(64) The measuring part constituent member arranged in each measuring part **30** on the uppermost layer includes the head plate **44**, the pogo frame **41**, the probe card **42**, and the test head **43** in a similar manner to the layers other than the uppermost layer. In addition, the head plate **44** of the uppermost layer is a member which directly or indirectly supports the pogo frame **41**, the probe card **42**, and the test head **43** which constitute the measuring part constituent member in a similar manner to the layers other than the uppermost layer.

(65) The head plate **44** of the uppermost layer is supported by the uppermost layer side frame bodies **23** (more specifically, the beam part **232**). While a support position of the head plate **44** by the uppermost layer side frame bodies **23** is preferably the lower surface of the head plate **44**, the support position is not necessarily limited thereto and may be another position (for example, a side surface of the head plate **44**). Accordingly, the measuring part constituent member arranged in each measuring part **30** of the uppermost layer is respectively directly or indirectly supported by the uppermost layer side frame bodies **23**.

(66) The frame part **24** connects the upper end parts of the uppermost layer side frame bodies **23** in the Z direction, and the ceiling (not illustrated) is fixed to the frame part **24**.

(67) FIGS. **7** and **8** are diagrams showing another configuration example (comparative example) of a housing applied to a prober. FIG. **7** is a front view of the housing according to the comparative example and FIG. **8** is a side view of the housing according to the comparative example. In the housing according to the comparative example shown in FIGS. **7** and **8**, a side frame **50** of each layer has an integrated frame structure with both functions of supporting the floor base **10** of an upper layer and supporting the measuring part constituent member.

(68) Therefore, in the housing according to the comparative example, when the alignment device **13** moves on a given layer and vibration is generated on the floor base **10**, the vibration is transmitted through the side frame **50** and readily propagates to the floor base **10** of other layers positioned above and below the layer. As a result, there is a problem in that even if the movement of the alignment device **13** ends, a long settling time is required until the vibration caused by the movement of the alignment device **13** settles.

(69) In addition, in the housing according to the comparative example, since the vibration of the floor base **10** of a given layer directly propagates to the side frame **50** of other layers positioned above and below the given layer, there is a problem in that the measuring part constituent member supported by the side frame **50** of other layers vibrates so as to deteriorate alignment accuracy and adversely affect results of wafer-level inspections.

(70) On the other hand, the housing **1** according to the present embodiment adopts a divided frame structure in which the first side frame **21** which supports the floor base **10** of an upper layer and the second side frame **22** which supports the measuring part constituent member are separately constructed. Therefore, in a case where the alignment device **13** moves on a given layer and vibration is generated on the floor base **10**, even if the vibration is transmitted through the first side frame **21** and propagates to the floor base **10** of other layers, the vibration is less likely to propagate

to the measuring part constituent member supported by the second side frame **22** which is separated from the first side frame **21**.

(71) Accordingly, it is possible to suppress an adverse effect of vibration generated by the movement of the alignment device **13** on a given layer to a result of a wafer-level inspection and alignment accuracy on other layers positioned above and below the given layer.

(72) In addition, with the housing **1** according to the present embodiment, since there is no need to restrict the movement of the alignment device **13** of other layers during an operation of the alignment device **13** of one layer among the alignment devices **13** arranged on the respective layers, an effect of vibration generated by the movement of the alignment devices **13** can be effectively suppressed without disadvantageously reducing throughput of the wafer-level inspection.

(73) Furthermore, with the housing **1** according to the present embodiment, because the divided frame structure is adopted to the housing **1** as described above, even when vibration is generated due to a factor other than the movement of the alignment device **13** such as an abnormality of each component (for example, the test head **43**) which constitutes the measuring parts **30**, the vibration can be prevented from affecting the measuring parts **30** of other layers.

(74) Next, an advantageous effect realized by the housing **1** according to the present embodiment will be described more specifically with reference to FIGS. **9** and **10**. FIG. **9** is a graph schematically showing how the side frame **50** of a layer positioned below a given layer vibrates, when vibration of a given constant amplitude is applied to the floor base **10** of the given layer for a certain period of time, in the housing according to the comparative example shown in FIGS. **7** and **8**. FIG. **10** is a graph schematically showing how the second side frame **22** of a layer positioned below a given layer vibrates, when vibration of a given constant amplitude is applied to the floor base **10** for a certain period of time in the housing **1** according to the present embodiment, in a similar manner to the comparative example. The graphs in FIGS. **9** and **10** represent output waveforms of a vibration meter. In each graph, an axis of abscissa represents time in units of seconds and an axis of ordinate represents output voltage (corresponding to an amplitude of vibration) in units of mV.

(75) In the graphs shown in FIGS. **9** and **10**, a difference between a maximum value and a minimum value of output voltage corresponds to an amplitude of vibration generated on the measuring part constituent member of a layer positioned below the given layer due to propagation of vibration generated on the given layer.

(76) In the graph shown in FIG. **9**, the difference between the maximum value and the minimum value of output voltage of the vibration meter is approximately 129 mV which is a value corresponding to the amplitude of vibration in the second side frame **22** of a layer positioned below in the housing according to the comparative example. On the other hand, in the graph shown in FIG. **10**, the difference between the maximum value and the minimum value of output voltage of the vibration meter is approximately 71.656 mV which is a value corresponding to the amplitude of vibration in the second side frame **22** of a layer positioned below in the housing **1** according to the present embodiment. A comparison between both amplitudes reveals that with the housing **1** according to the present embodiment, amplitude (in other words, a magnitude of vibration) can be reduced by over 40 percent, as compared to the housing according to the comparative example.

#### Modifications

(77) In the embodiment described above, explanation is made about a case where the configuration of the uppermost layer is simplified compared to layers other than the uppermost layer in order to make the uppermost layer lighter and stabilize the structure of the entire housing **1**. However, the configuration of the uppermost layer may be the same as the configuration of other layers. FIG. **11** shows, as a modification example, a schematic configuration diagram (side view) of the measurement unit **112** whose housing **2** has the uppermost layer with the same configuration as other layers. Illustration of a front view of the housing **2** according to the modification example is

omitted because it is the same as FIG. 3. Naturally, the housing 2 according to the modification example can also realize the advantageous effect described above.

(78) In addition, in the embodiment described above, the number of layers and the number of the measuring parts 30 in the measurement unit 112 are not limited to the example shown in FIGS. 3 and 4.

#### Advantageous Effects

(79) As described above, in the housing 1 according to the present embodiment, the side frame body 20 has a divided frame structure in which the first side frame 21 that supports the floor base 10 of an upper layer and the second side frame 22 that supports the measuring part constituent member, are constructed separately from each other. Accordingly, even when the alignment device 13 moves on a given layer to generate vibration on the floor base 10 and the vibration propagates to the floor base 10 of upper and lower layers through the first side frame 21, the vibration is less likely to propagate to the measuring part constituent member supported by the second side frame 22 which is separate from the first side frame 21 on the upper and lower layers.

(80) Thus, vibration generated by the movement of the alignment device 13 on a given layer, is suppressed from adversely affecting alignment accuracy and a result of a wafer-layer inspection on other layers positioned above and below the given layer.

(81) With the housing 1 according to the present embodiment, since the movement of the alignment device 13 is not restricted, throughput of a wafer-level inspection by a prober may be favorably maintained while suppressing adverse effect of vibration on alignment accuracy and a result of the wafer-level inspection.

(82) With the housing 1 according to the present embodiment, since the divided frame structure reduces effects caused by vibration, even when vibration is generated due to a factor other than the movement of the alignment device 13 such as an abnormality of the measuring parts 30, the advantageous effect described above may be realized.

(83) While the embodiment of the present invention has been described, the present invention is not limited to the examples described above. It is obvious that various improvements and modifications may be made without departing from the scope of the invention.

#### REFERENCE SIGNS LIST

(84) 1,2 housing 10 floor base 13 alignment device 20 side frame body 21 first side frame 22 second side frame 23 uppermost layer side frame body 24 frame part 30 measuring part 41 pogo frame 42 probe card 43 test head 44 head plate 50 side frame 53 pogo frame mounting part 60, 62, 64 sealing member 63 positioning pin 66 probe 22 column part 222 beam part 231 column part 232 beam part 100 prober 112 measurement unit 114 loader unit 118 load port 120 wafer cassette 121 operating panel 122 conveyance unit 124 conveyance arm 150 wafer chuck W wafer

#### Claims

1. A housing for a prober having a multi-layer structure in which a plurality of measuring parts are stacked in multiple stages and a moving stage is configured to be movable among two or more measuring parts arranged on a same layer, the housing for a prober comprising: floor bases configured to constitute floor surfaces of respective layers of the multi-layer structure; and a side frame body which is arranged between a floor base of one layer and a floor base of another layer positioned above the one layer among the plurality of layers, and positioned in both side parts of the measuring parts, wherein the side frame body includes: a first side frame which is erected on the floor base of the one layer and supports a lower surface side of the floor base of the another layer; and a second side frame which is erected on the floor base of the one layer at a position different from that of the first side frame, and supports a measuring part constituent member arranged in each measuring part, and the second side frame has a gate form comprising two column parts and a beam part which spans between the two column parts, in such a manner that the moving

stage is movable among two or more measuring parts on the one layer.

2. The housing for a prober according to claim 1, wherein the side frame body is arranged on a layer other than an uppermost layer among the plurality of layers.

3. The housing for a prober according to claim 2, further comprising a head plate having a holding unit configured to hold the measuring part constituent member, wherein a lower surface side of the head plate is supported by the second side frame.

4. The housing for a prober according to claim 1, wherein the second side frame is juxtaposed to the first side frame at a position adjacent to the first side frame.

5. The housing for a prober according to claim 1, wherein the measuring part constituent member is one of a pogo frame, a probe card and a test head.

6. A prober comprising the housing for a prober according to claim 1, wherein at least two or more measuring parts are provided on the one layer, and the prober comprises a moving stage capable of moving a wafer to be inspected to each of the measuring parts arranged on the one layer.

7. The housing for a prober according to claim 1, wherein the floor base of the one layer has a flat plate shape which is elongated in a first direction and parallel to a horizontal plane, the moving stage is movable in the first direction on the one layer, and in the second side frame, the beam part extends in a second direction different from the first direction on the horizontal plane.

---