

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12401315
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Huang; Yu-Chia et al.

GPS positioning stake with solar panel adjustable in angle

Abstract

A GPS positioning stake includes a supporting pole, a base connected with the supporting pole and having a GPS positioning module and a rotation axle, an adjustment board having an axle sleeving portion pivotably connected with the rotation axle and a solar panel providing electric energy for the operation of the GPS positioning module, and an angle adjusting device including a first gear fixedly sleeved onto the rotation axle, a second gear sleeved onto the rotation axle and located in the axle sleeving portion, an elastic member, and an operation member. The first and second gears engage when the operation member locks, disabling the adjustment board from rotation relative to the rotation axle, and separate when the operation member unlocks, enabling the adjustment board to drive the second gear to rotate relative to the rotation axle for adjusting the solar panel's light receiving angle for better energy conversion efficiency.

Inventors:	Huang; Yu-Chia (Taichung, TW), Chou; Fu-Peng (Taichung, TW)
Applicant:	DURQ MACHINERY CORP. (Taichung, TW)
Family ID:	1000008780105
Assignee:	DURQ MACHINERY CORP. (Taichung, TW)
Appl. No.:	18/654363
Filed:	May 03, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240380358 A1	Nov. 14, 2024

Foreign Application Priority Data

DE	102023112556.7	May. 12, 2023
----	----------------	---------------

Publication Classification

Int. Cl.: H02S20/32 (20140101); A01D34/00 (20060101); G01S19/13 (20100101); A01D101/00 (20060101)

U.S. Cl.:

CPC H02S20/32 (20141201); G01S19/13 (20130101); A01D34/008 (20130101); A01D2101/00 (20130101)

Field of Classification Search

CPC: H02S (20/32); H02S (20/30); G01S (19/13); A01D (34/008)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2011/0120523	12/2010	Silver	136/246	F24S 30/452
2012/0227788	12/2011	Lundahl	136/246	H02S 20/30
2014/0174499	12/2013	Fitzgerald	136/246	H02S 20/32
2014/0283894	12/2013	Silver	136/246	F24S 25/70

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
215345883	12/2020	CN	N/A
215345883	12/2020	CN	N/A

Primary Examiner: Mershon; Jayne L

Attorney, Agent or Firm: Muncy, Geissler, Olds & Lowe, P.C.

Background/Summary

BACKGROUND OF THE INVENTION

1. Field of the Invention

(1) The present invention relates to GPS positioning stakes and more particularly, to a GPS positioning stake with a solar panel adjustable in angle.

2. Description of the Related Art

(2) The utility model patent CN215345883U disclosed a lawn mower positioning system which includes a base station and a lawn mower main body. The base station has a first GPS module and a first communication module. The lawn mower main body has a second GPS module, a second communication module and a control device. The lawn mower positioning system creates communication by the first and second communication modules, and uses the control device to receive signal obtained by the first and second GPS modules, so as to obtain positioning information of the lawn mower main body, that is simple in operation and easy in maintenance. However, the base station adopts a wired charging device (e.g. electric wire and charging socket) to provide electric energy for the operation of the first GPS module, so that the position of the

placement of the base station is limited by the wired charging device. Therefore, the lawn mower positioning system disclosed by the aforementioned patent still needs improvement.

SUMMARY OF THE INVENTION

(3) The present invention has been accomplished in view of the above-noted circumstances. The present invention provides a GPS positioning stake, which is self-powered by a solar panel, so the position of placement thereof is unlimited by the environment. Besides, the light receiving angle of the solar panel is adjustable for obtaining relatively better energy conversion efficiency.

(4) To attain the above objective, the present invention provides a GPS positioning stake which includes a supporting pole, a base, an adjustment board, and an angle adjusting device. The base is connected with the supporting pole, and the base has a GPS positioning module and a rotation axle. The adjustment board has an axle sleeving portion and a solar panel. The axle sleeving portion is pivotably connected with the rotation axle. The solar panel provides electric energy for the operation of the GPS positioning module. The angle adjusting device includes a first gear, a second gear, an elastic member, and an operation member. The first gear is fixedly sleeved onto the rotation axle, and the first gear has a first teeth portion. The second gear is sleeved onto the rotation axle and located in the axle sleeving portion. The second gear is arranged in a way that the second gear is slidable along an axial direction of the rotation axle relative to the rotation axle and the axle sleeving portion, and able to be driven by the axle sleeving portion to rotate relative to the rotation axle. The second gear has a second teeth portion facing toward the first teeth portion. The elastic member provides an elastic force acted on the second gear to make the second gear displace toward the first gear. The operation member is sleeved onto the rotation axle in a way that the operation member is displaceable between a lock position and an unlock position. The operation member has a pushing portion located in the axle sleeving portion, and a force receiving portion exposed out of the axle sleeving portion. The force receiving portion is adapted to be pressed so that the operation member is displaced relative to the rotation axle from the lock position to the unlock position. When the operation member is located at the lock position, the second teeth portion is engaged with the first teeth portion to disable the axle sleeving portion of the adjustment board from rotation relative to the rotation axle. When the operation member is located at the unlock position, the pushing portion is inserted between the second teeth portion and the first teeth portion to separate the second teeth portion from the first teeth portion to enable the axle sleeving portion of the adjustment board to drive the second gear to rotate relative to the rotation axle.

(5) By the above-described technical features, the GPS positioning stake of the present invention provides the electric energy for the operation of the GPS positioning module by the illumination of the sun on the solar panel, and the GPS positioning stake of the present invention allows the user to adjust the angle of the adjustment board to increase the probability of the solar panel being illuminated by the sun, so as to obtain relatively better energy conversion efficiency.

(6) Preferably, the operation member is a pressed rod or a pulled rod; the pressed rod or the pulled rod is sleeved onto the rotation axle in a way that the pressed rod or the pulled rod is displaceable along a radial direction of the rotation axle. The pressed rod or the pulled rod of such design is reduced in volume.

(7) Preferably, the second gear has a first slope; when the operation member is the pressed rod, the pushing portion of the pressed rod has a second slope, and the first slope is abutted on the second slope; when the operation member is the pulled rod, the pushing portion of the pulled rod has a third slope, and the first slope is abutted on the third slope. In this way, when the pressed rod is displaced from the lock position to the unlock position, the second slope of the pressed rod pushes the first slope of the second gear to make the second gear move along the axial direction of the rotation axle toward the direction away from the first gear, so as to separate the second teeth portion of the second gear from the first teeth portion of the first gear. When the pulled rod is displaced from the lock position to the unlock position, the third slope of the pulled rod pushes the first slope of the second gear to make the second gear move along the axial direction of the rotation

axle toward the direction away from the first gear, so as to separate the second teeth portion of the second gear from the first teeth portion of the first gear.

(8) Preferably, the base has a position limiting block; the first gear has a position limiting hole; when the first gear is sleeved onto the rotation axle, the position limiting block fits in the position limiting hole so that the first gear is fixedly sleeved onto the rotation axle firmly.

(9) Preferably, the angle adjusting device includes a protecting cover fixedly disposed in the axle sleeving portion; the protecting cover has a bottom plate, an annular body portion extending from the bottom plate, an accommodating space formed by the bottom plate and the annular body portion, and a fixed pipe extending from the bottom plate and located in the annular body portion; the rotation axle of the base has a connecting portion; the fixed pipe is sleeved onto the connecting portion so that the axle sleeving portion is pivotable relative to the rotation axle.

(10) Preferably, the protecting cover has two embedded protrusions located in the annular body portion; the second gear has two embedded recesses provided separately; the embedded protrusions are embedded in the embedded recesses, so that the second gear is displaceable relative to the protecting cover along the axial direction of the rotation axle, and also able to be driven by the protecting cover to rotate relative to the rotation axle.

(11) Preferably, the second gear has a supporting portion; the elastic member is a coil spring and placed in the accommodating space of the protecting cover; an end of the elastic member is sleeved onto the supporting portion; another end of the elastic member is abutted on the bottom plate of the protecting cover.

(12) Preferably, the adjustment board has a first end portion and a second end portion; the adjustment board is rotatable until the first end portion is abutted against the base, or the adjustment board is rotatable until the second end portion is abutted against the base. In this way, the first end portion and the second end portion can limit the angle, for which the adjustment board is rotatable.

(13) To attain the above objective, the present invention provides another GPS positioning stake, which includes a supporting pole, a base, an adjustment board and an angle adjusting device. The base is connected with the supporting pole, and the base has a GPS positioning module and a rotation axle. The adjustment board has an axle sleeving portion and a solar panel. The axle sleeving portion is pivotable relative to the rotation axle, and an inner peripheral surface of the axle sleeving portion has a teeth portion. The solar panel provides electric energy for the operation of the GPS positioning module. The angle adjusting device includes an engaging gear, an elastic member, and an operation member. The engaging gear is sleeved onto the rotation axle and located in the axle sleeving portion. The engaging gear is arranged in a way that the engaging gear is slidable relative to the rotation axle along an axial direction of the rotation axle, and the engaging gear has an engaging teeth portion facing toward the teeth portion of the axle sleeving portion. The elastic member provides an elastic force acted on the engaging gear to make the engaging gear displace toward the teeth portion of the axle sleeving portion. The operation member is inserted in the axle sleeving portion in a way that the operation member is displaceable between a lock position and an unlock position. When the operation member is located at the lock position, the engaging teeth portion is engaged with the teeth portion of the axle sleeving portion to disable the adjustment board from rotation relative to the rotation axle. When the operation member is located at the unlock position, the operation member pushes the engaging gear to separate the engaging teeth portion from the teeth portion of the axle sleeving portion to enable the adjustment board to rotate relative to the rotation axle.

(14) Preferably, the operation member is a button or a knob; the button or the knob is inserted in the axle sleeving portion in a way that the button or the knob is displaceable along an axial direction of the rotation axle.

(15) Preferably, when the operation member is the knob, an outer peripheral surface of the knob has a thread, the inner peripheral surface of the axle sleeving portion has an annular flange, and the

thread is abutted against the annular flange. In this way, the thread of the knob is guided by the annular flange of the axle sleeving portion to displace along the axial direction of the rotation axle. (16) Preferably, the engaging gear has a supporting portion; the elastic member is a coil spring; an end of the elastic member is sleeved onto the supporting portion; another end of the elastic member is sleeved onto the rotation axle and abutted against the base.

(17) Further scope of applicability of the present invention will become apparent from the detailed description given hereinafter. However, it should be understood that the detailed description and specific examples, while indicating preferred embodiments of the invention, are given by way of illustration only, since various changes and modifications within the spirit and scope of the invention will become apparent to those skilled in the art from this detailed description.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a perspective view of a GPS positioning stake of a first embodiment of the present invention;
- (2) FIG. 2 is a partial exploded perspective view of the GPS positioning stake of the first embodiment of the present invention;
- (3) FIG. 3 is a system block diagram showing an operating mode between a GPS positioning module and a solar panel;
- (4) FIG. 4 is an enlarged view of the part A in FIG. 2;
- (5) FIG. 5 is an enlarged view of the part B in FIG. 2;
- (6) FIG. 6 is a radially directional partial sectional view of the GPS positioning stake of the first embodiment of the present invention, showing a first gear is fixedly sleeved onto a rotation axle;
- (7) FIG. 7 is a radially directional partial sectional view of the GPS positioning stake of the first embodiment of the present invention, showing a protecting cover is sleeved onto a second gear;
- (8) FIG. 8 is an axially directional partial sectional view of the GPS positioning stake of the first embodiment of the present invention, showing a pressed rod is located at a lock position;
- (9) FIG. 9 is similar to FIG. 8, showing the pressed rod is located at an unlock position;
- (10) FIG. 10 is an assembled perspective view of a pulled rod and a second gear of a second embodiment of the present invention;
- (11) FIG. 11 is an axially directional partial sectional view of a GPS positioning stake of the second embodiment of the present invention, showing the pulled rod is located at a lock position;
- (12) FIG. 12 is similar to FIG. 11, showing the pulled rod is located at an unlock position;
- (13) FIG. 13 is a partial exploded perspective view of a GPS positioning stake of a third embodiment of the present invention, showing an engaging teeth portion of an engaging gear is engaged with a teeth portion of an axle sleeving portion;
- (14) FIG. 14 is an axially directional partial sectional view of the GPS positioning stake of the third embodiment of the present invention, showing a button is located at a lock position;
- (15) FIG. 15 is similar to FIG. 14, showing the button is located at an unlock position;
- (16) FIG. 16 is a partial exploded perspective view of a GPS positioning stake of a fourth embodiment of the present invention, showing an engaging teeth portion of an engaging gear is engaged with a teeth portion of an axle sleeving portion;
- (17) FIG. 17 is an axially directional partial sectional view of a GPS positioning stake of the fourth embodiment of the present invention, showing a knob is located at a lock position;
- (18) FIG. 18 is similar to FIG. 17, showing the knob is located at an unlock position;
- (19) FIG. 19 is a side view of the GPS positioning stake of the present invention, showing the status that an adjustment board is not adjusted;
- (20) FIG. 20 is similar to FIG. 19, showing the status that a first end portion of the adjustment

board is abutted against a base; and

(21) FIG. 21 is similar to FIG. 20, showing the status that a second end portion of the adjustment board is abutted against the base.

DETAILED DESCRIPTION OF THE INVENTION

(22) First of all, it is to be mentioned that the technical features provided by the present invention are unlimited to the specific structure, usage and application thereof described in the detailed description of the invention. It should be understood by those skilled in the related art that all the terms used in the contents of the specification are for illustrative description. The directional terms mentioned in this specification, such as 'front, upper, lower, rear, left, right, top, bottom, in, and out', are also just for illustrative description on the basis of normal usage direction, not intended to limit the claimed scope.

(23) Referring to FIG. 1 and FIG. 2, a GPS positioning stake 1 of a first embodiment of the present invention includes a supporting pole 10, a base 20, an adjustment board 30, and two angle adjusting devices 40. In practice, it may include only one angle adjusting device 40.

(24) The supporting pole 10 is a telescopic rod, the bottom end of which has a trident seat 11 and an inserting portion 12 located below the trident seat 11. The inserting portion 12 can be inserted into a predetermined inserting hole (not shown) or directly inserted into the ground. Then, the trident seat 11 is stably supported on the ground to make the supporting effect of the supporting pole 10 better.

(25) Referring to FIG. 2 to FIG. 4, the bottom end of the base 20 has a connecting portion 21 connected with the supporting pole 10. Two opposite outsides of the base 20 each have a fixed seat 22. Each fixed seat 22 has a rotation axle 23 and a position limiting block 231 fixedly disposed on the rotation axle 23. The rotation axle 23 is provided at the free end thereof with a connecting portion 232. The inside of the base 20 has a GPS positioning module 24 as shown in FIG. 3. The GPS positioning module 24 is arranged to provide satellite positioning signal to a robotic lawn mower (not shown).

(26) The adjustment board 30 includes an upper covering plate 31 and a lower covering plate 32. The upper covering plate 31 has an upper adjustment section 311, an upper slot 312 penetrating through the upper adjustment section 311, and an upper bearing section 313 connected with the upper adjustment section 311 and inclined downwardly. The upper bearing section 313 is arranged for the placement of a solar panel 314. As shown in FIG. 3, the solar panel 314 receives sunlight, then convert direct current into alternating current by a photoelectric converter 33, and stores the power produced thereby into a storage battery 34 for providing electric energy for the operation of the GPS positioning module 24 of the base 20. The lower covering plate 32 has a lower adjustment section 321, a lower slot 322 penetrating through the lower adjustment section 321, two axle sleeving portions 323 oppositely provided on the lower adjustment section 321, and a lower bearing section 324 connected with the lower adjustment section 321 and inclined downwardly. The lower adjustment section 321 of the lower covering plate 32 is combined with the upper adjustment section 311 of the upper covering plate 31, and the lower bearing section 324 of the lower covering plate 32 is combined with the upper bearing section 313 of the upper covering plate 31, so that the lower slot 322 of the lower covering plate 32 communicates with the upper slot 312 of the upper covering plate 31. The adjustment board 30 is sleeved onto the base 20 by the upper and lower slots 312 and 322. Besides, the adjustment board 30 is pivotably sleeved onto the fixed seats 22 of the base 20 by the two axle sleeving portions 323 of the lower covering plate 32, and accommodates the rotation axles 23 of the base 20 therein.

(27) The angle adjusting devices 40 are accommodated in the axle sleeving portions 323 of the adjustment board 30, and each angle adjusting device 40 includes a first gear 42, a second gear 44, a protecting cover 46, an elastic member 50 and an operation member 51.

(28) Referring to FIG. 4 and FIG. 5, the first gear 42 has a first teeth portion 421, and the position limiting block 231 of the rotation axle 23 fits in a position limiting hole 422 of the first gear 42, so

that the first gear **42** is fixedly sleeved onto the rotation axle **23** and placed in the fixed seat **22** (as shown in FIG. **6**).

(29) The second gear **44** is sleeved onto the rotation axle **23** by an axial hole **441**, and an end of the axial hole **441** has two supporting portions **442**. The second gear **44** has a second teeth portion **443** facing toward the first teeth portion **421**, and a first slope **444** surrounded by the second teeth portion **443** (as shown in FIG. **5**). The outer peripheral edge of the second gear **44** has two embedded recesses **445** provided oppositely.

(30) The protecting cover **46** is fixedly disposed on the upper adjustment section **311** of the upper covering plate **31** and located in the axle sleeving portion **323** of the lower covering plate **32**. As shown in FIG. **4** and FIG. **5**, the protecting cover **46** has a bottom plate **461**, an annular body portion **462** extending from the bottom plate **461**, an accommodating space **463** formed by the bottom plate **461** and the annular body portion **462**, two embedded protrusions **464** oppositely provided on the inner wall surface of the annular body portion **462**, and a fixed pipe **465** extending from the bottom plate **461** and located in the annular body portion **462**. An end of the fixed pipe **465** has a flange **466**. As shown in FIG. **7** and FIG. **8**, the embedded protrusions **464** of the protecting cover **46** are embedded in the embedded recesses **445** of the second gear **44**, and the fixed pipe **465** is inserted through the axial hole **441** of the second gear **44** as shown in FIG. **4** and sleeved onto the connecting portion **232** of the rotation axle **23** by the flange **466**. The fixed pipe **465** and the rotation axle **23** are pivotably connected with each other by a bolt **47**, a spacer **48** and a nut **49**, so that through the protecting cover **46**, the axle sleeving portion **323** can drive the second gear **44** to rotate relative to the rotation axle **23** and allow the second gear **44** to displace along the axial direction of the rotation axle **23** relative to the rotation axle **23**, the axle sleeving portion **323** and the protecting cover **46**.

(31) As shown in FIG. **4**, the elastic member **50** is implemented by a coil spring. The elastic member **50** is accommodated in the accommodating space **463** of the protecting cover **46**. An end of the elastic member **50** is sleeved onto the supporting portions **442** of the second gear **44**, and then another end of the elastic member **50** is abutted on the bottom plate **461** of the protecting cover **46**. In this way, the elastic member **50** provides an elastic restoring force acted on the second gear **44** to make the second gear **44** displace toward the first gear **42** (as shown in FIG. **8** and FIG. **9**).

(32) As shown in FIG. **4** and FIG. **5**, in this embodiment, the operation member **51** is a pressed rod. The pressed rod has a pushing portion **52** and a force receiving portion **53**, wherein the pushing portion **52** is located in the axle sleeving portion **323** and sleeved onto the rotation axle **23** by an elongated hole **521**, so that the pressed rod is displaceable upwardly and downwardly relative to the rotation axle **23** along the radial direction of the rotation axle **23**. The pushing portion **52** further has a second slope **522**. The second slope **522** of the pushing portion **52** is abutted on the first slope **444** of the second gear **44**. The force receiving portion **53** is exposed out of the axle sleeving portion **323** for being pressed by an external force, so that the pressed rod acted by the external force is displaceable relative to the rotation axle **23** along the radial direction of the rotation axle **23** from a lock position **P1** (as shown in FIG. **8**) to an unlock position **P2** (as shown in FIG. **9**). When the pressed rod is located at the lock position **P1** as shown in FIG. **8**, the second teeth portion **443** of the second gear **44** is engaged with the first teeth portion **421** of the first gear **42** to disable the axle sleeving portion **323** of the adjustment board **30** from driving the second gear **44** to rotate relative to the rotation axle **23**. In the process that the pressed rod is moved from the lock position **P1** as shown in FIG. **8** toward the unlock position **P2** as shown in FIG. **9**, the second slope **522** of the pushing portion **52** of the pressed rod pushes the first slope **444** of the second gear **44** to make the second gear **44** move along the axial direction of the rotation axle **23** toward the direction away from the first gear **42**. When the pressed rod arrives at the unlock position **P2** as shown in FIG. **9**, the pushing portion **52** of the pressed rod is inserted between the second teeth portion **443** and the first teeth portion **421** to separate the second teeth portion **443** of the second gear **44** from the first

teeth portion **421** of the first gear **42** to enable the axle sleeving portion **323** of the adjustment board **30** to drive the second gear **44** to rotate relative to the rotation axle **23**.

(33) It can be known from the above description that for the GPS positioning stake **1** of the first embodiment of the present invention, when the angle adjustment of the adjustment board **30** is to be performed, at first, a pressing force has to be applied to the force receiving portion **53** of the pressed rod to displace the pressed rod from the lock position **P1** as shown in FIG. **8** to the unlock position **P2** as shown in FIG. **9**. At this time, the pressed rod forces the second teeth portion **443** of the second gear **44** to separate from the first teeth portion **421** of the first gear **42**, so that through the axle sleeving portion **323** and the protecting cover **46**, the adjustment board **30** can drive the second gear **44** to rotate relative to the rotation axle **23**. Thus, the adjustment board **30** is allowed to be rotated relative to the rotation axle **23** for the adjustment of the light receiving angle of the solar panel **314**. At this time, the elastic member **50** is compressed by the second gear **44** and thereby stores the elastic restoring force. Once the adjustment board **30** is adjusted to the proper angle, the pressing force applied to the force receiving portion **53** of the pressed rod can be released. At this time, the elastic restoring force released by the elastic member **50** is acted on the second gear **44**, and the first slope **444** of the second gear **44** pushes the second slope **522** of the pushing portion **52** of the pressed rod to make the pressed rod move from the unlock position **P2** as shown in FIG. **9** back to the lock position **P1** as shown in FIG. **8**. At this time, the second teeth portion **443** of the second gear **44** is engaged with the first teeth portion **421** of the first gear **42** again, and thus the adjustment board **30** is disabled from rotation relative to the rotation axle **23**, and the adjustment of the light receiving angle of the solar panel **314** is accomplished.

(34) However, the GPS positioning stake **1** is unlimited to that disclosed in this embodiment. Referring to FIG. **10**, a GPS positioning stake **2** of a second embodiment of the present invention is approximately the same in structure with the first embodiment, but the primary difference therebetween is that another second gear **44a** is provided in this embodiment. The second gear **44a** in this embodiment is approximately the same in structure with the second gear **44** in the above-described first embodiment, but the primary difference therebetween is that the second gear **44a** in this embodiment has two second teeth portions **44a1**, a first slope **44a2** surrounded by the second teeth portion **44a1**, and a breach **44a3** located between the second teeth portions **44a1**. The second teeth portions **44a1** face toward the first teeth portion **421** of the first gear **42**. The operation member **54** in this embodiment is a pulled rod. The pulled rod has a pushing portion **55**, an embedded portion **56** connected with the pushing portion **55**, and a force receiving portion **57** connected with the embedded portion **56**. As shown in FIG. **11**, the pushing portion **55** is located in the axle sleeving portion **323** and sleeved onto the rotation axle **23** by an elongated hole **551**, so that the pulled rod is displaceable upwardly and downwardly relative to the rotation axle **23** along the radial direction of the rotation axle **23**. The pushing portion **55** further has a third slope **552**. The third slope **552** is abutted on the first slope **44a2** of the second gear **44a**. The embedded portion **56** is embedded in the breach **44a3** of the second gear **44a** (as shown in FIG. **10**). The force receiving portion **57** is exposed out of the axle sleeving portion **323** for being pulled by an external force so that the pulled rod acted by the external force is displaceable relative to the rotation axle **23** along the radial direction of the rotation axle **23** from a lock position **P1** (as shown in FIG. **11**) to an unlock position **P2** (as shown in FIG. **12**).

(35) When the pulled rod is located at the lock position **P1** as shown in FIG. **11**, the second teeth portions **44a1** of the second gear **44a** as shown in FIG. **10** are engaged with the first teeth portion **421** of the first gear **42** to disable the axle sleeving portion **323** of the adjustment board **30** from driving the second gear **44a** to rotate relative to the rotation axle **23**. In the process that the pulled rod is moved from the lock position **P1** as shown in FIG. **11** toward the unlock position **P2** as shown in FIG. **12**, the third slope **552** of the pushing portion **55** of the pulled rod pushes the first slope **44a2** of the second gear **44a** to make the second gear **44a** move along the axial direction of the rotation axle **23** toward the direction away from the first gear **42**. When the pulled rod arrives at

the unlock position P2 as shown in FIG. 12, the pushing portion 55 of the pulled rod is inserted between the second teeth portion 44a1 and the first teeth portion 421 to separate the second teeth portion 44a1 of the second gear 44a from the first teeth portion 421 of the first gear 42 to enable the axle sleeving portion 323 of the adjustment board 30 to drive the second gear 44a to rotate relative to the rotation axle 23.

(36) Referring to FIG. 11 and FIG. 12, for the GPS positioning stake 2 of the second embodiment of the present invention, when the angle adjustment of the adjustment board 30 is to be performed, at first, a pulling force has to be applied to the force receiving portion 57 of the pulled rod to displace the pulled rod from the lock position P1 as shown in FIG. 11 to the unlock position P2 as shown in FIG. 12. At this time, the pulled rod forces the second teeth portion 44a1 of the second gear 44a to separate from the first teeth portion 421 of the first gear 42, so that through the axle sleeving portion 323 and the protecting cover 46, the adjustment board 30 can drive the second gear 44a to rotate relative to the rotation axle 23. Thus, the adjustment board 30 is allowed to be rotated relative to the rotation axle 23 for the adjustment of the light receiving angle of the solar panel 314. At this time, the elastic member 50 is compressed by the second gear 44a and thereby stores the elastic restoring force. Once the adjustment board 30 is adjusted to the proper angle, the pulling force applied to the force receiving portion 57 of the pulled rod can be released. At this time, the elastic restoring force released by the elastic member 50 is acted on the second gear 44a, and the first slope 44a2 of the second gear 44a pushes the third slope 552 of the pushing portion 55 of the pulled rod to make the pulled rod move from the unlock position P2 as shown in FIG. 12 back to the lock position P1 as shown in FIG. 11. At this time, the second teeth portions 44a1 of the second gear 44a (as shown in FIG. 10) are engaged with the first teeth portion 421 of the first gear 42 again, and thus the adjustment board 30 is disabled from rotation relative to the rotation axle 23, and the adjustment of the light receiving angle of the solar panel 314 is accomplished.

(37) Referring to FIG. 13 to FIG. 15, a GPS positioning stake 3 of a third embodiment of the present invention is approximately the same in structure with the above-described first embodiment, but the primary difference therebetween is that the angle adjusting devices 40 thereof are different in structure. As shown in FIG. 13, in this embodiment, an inner peripheral surface of the axle sleeving portion 323 has a teeth portion 323a, which is completely the same in structure with the first teeth portion 421 of the first gear 42. In addition, in this embodiment, the angle adjusting device 40 provides an engaging gear 45, as shown in FIG. 13 and FIG. 14. The engaging gear 45 is approximately the same in structure with the second gear 44 in the above-described first embodiment, but the primary difference therebetween is that the engaging gear 45 has a flat plate portion 451, an engaging teeth portion 452 located on the outer peripheral edge of the flat plate portion 451, and two supporting portions 453 located at another end of the flat plate portion 451. An end of the elastic member 50 is sleeved onto the supporting portions 453 of the engaging gear 45, and the other end is sleeved onto the rotation axle 23 and abutted against the fixed seat 22 of the base 20. In this embodiment, the operation member 58 is a button. A part of the button is inserted in the axle sleeving portion 323, and another part is exposed out of the axle sleeving portion 323 for being pressed by an external force so that the button acted by the external force is displaceable relative to the rotation axle 23 along the axial direction of the rotation axle 23 from a lock position P3 (as shown in FIG. 14) to an unlock position P4 (as shown in FIG. 15). When the button is located at the lock position P3 as shown in FIG. 14, the engaging teeth portion 452 of the engaging gear 45 is engaged with the teeth portion 323a of the axle sleeving portion 323 to disable the adjustment board 30 from rotation relative to the rotation axle 23. In the process that the button is moved from the lock position P3 as shown in FIG. 14 toward the unlock position P4 as shown in FIG. 15, an end of the button is abutted against the flat plate portion 451 of the engaging gear 45 to make the engaging gear 45 move along the axial direction of the rotation axle 23 toward the direction away from the teeth portion 323a of the axle sleeving portion 323. When the button arrives at the unlock position P4 as shown in FIG. 15, the engaging teeth portion 452 of the

engaging gear **45** is separated from the teeth portion **323a** of the axle sleeving portion **323** to enable the adjustment board **30** to rotate relative to the rotation axle **23**.

(38) Referring to FIG. **14** and FIG. **15**, for the GPS positioning stake **3** of the third embodiment of the present invention, when the angle adjustment of the adjustment board **30** is to be performed, at first, a pressing force has to be applied to the button (operation member **58**) to displace the button from the lock position **P3** as shown in FIG. **14** to the unlock position **P4** as shown in FIG. **15**. At this time, the button is abutted against the flat plate portion **451** of the engaging gear **45** and pushes the engaging gear **45** to separate the engaging teeth portion **452** of the engaging gear **45** from the teeth portion **323a** of the axle sleeving portion **323**, so that the user can stir the adjustment board **30**. Thus, the adjustment board **30** is allowed to be rotated relative to the rotation axle **23** for the adjustment of the light receiving angle of the solar panel **314**. At this time, the elastic member **50** is compressed by the engaging gear **45** and thereby stores the elastic restoring force. Once the adjustment board **30** is adjusted to the proper angle, the pressing force applied to the button can be released. At this time, the elastic restoring force released by the elastic member **50** is acted on the engaging gear **45**, and the flat plate portion **451** of the engaging gear **45** pushes the button to make the button move from the unlock position **P4** as shown in FIG. **15** back to the lock position **P3** as shown in FIG. **14**. At this time, the engaging teeth portion **452** of the engaging gear **45** is engaged with the teeth portion **323a** of the axle sleeving portion **323** again, and thus the adjustment board **30** is disabled from rotation relative to the rotation axle **23**, and the adjustment of the light receiving angle of the solar panel **314** is accomplished.

(39) Referring to FIG. **16** to FIG. **18**, a GPS positioning stake **4** of a fourth embodiment of the present invention is approximately the same in structure with the GPS positioning stake **3** of the third embodiment, but the primary difference therebetween is that the angle adjusting devices **40** thereof are different in structure. As shown in FIG. **17** and FIG. **18**, in this embodiment, the inner peripheral surface of the axle sleeving portion **323** has an annular flange **323b**. The operation member **59** is a knob, and an outer peripheral surface of the knob has a thread **591**. A part of the knob is inserted in the axle sleeving portion **323**, and the thread **591** is abutted against the annular flange **323b** of the axle sleeving portion **323**. Another part of the knob is exposed out of the axle sleeving portion **323** for being rotated so that the thread **591** of the knob is guided by the annular flange **323b** to displace along the axial direction of the rotation axle **23** from a lock position **P3** (as shown in FIG. **17**) to an unlock position **P4** (as shown in FIG. **18**). When the knob is located at the lock position **P3** as shown in FIG. **17**, the engaging teeth portion **452** of the engaging gear **45** is engaged with the teeth portion **323a** of the axle sleeving portion **323** (as shown in FIG. **16**) to disable the adjustment board **30** from rotation relative to the rotation axle **23**. In the process that the knob is moved from the lock position **P3** as shown in FIG. **17** toward the unlock position **P4** as shown in FIG. **18**, an end of the knob is abutted against the flat plate portion **451** of the engaging gear **45** to make the engaging gear **45** move along the axial direction of the rotation axle **23** toward the direction away from the teeth portion **323a** of the axle sleeving portion **323**. When the knob arrives at the unlock position **P4** as shown in FIG. **18**, the engaging teeth portion **452** of the engaging gear **45** is separated from the teeth portion **323a** of the axle sleeving portion **323** to enable the adjustment board **30** to rotate relative to the rotation axle **23**.

(40) Referring to FIG. **17** and FIG. **18**, for the GPS positioning stake **4** of the fourth embodiment of the present invention, when the angle adjustment of the adjustment board **30** is to be performed, at first, a rotating force has to be applied to the knob (operation member **59**) to displace the knob from the lock position **P3** as shown in FIG. **17** to the unlock position **P4** as shown in FIG. **18**. At this time, the knob is abutted against the flat plate portion **451** of the engaging gear **45** and pushes the engaging gear **45** to separate the engaging teeth portion **452** of the engaging gear **45** from the teeth portion **323a** of the axle sleeving portion **323** as shown in FIG. **16**, so that the user can stir the adjustment board **30**. Thus, the adjustment board **30** is allowed to be rotated relative to the rotation axle **23** for the adjustment of the light receiving angle of the solar panel **314**. At this time, the

elastic member **50** is compressed by the engaging gear **45** and thereby stores the elastic restoring force. Once the adjustment board **30** is adjusted to the proper angle, the user can rotate the knob reversely. At this time, the elastic restoring force released by the elastic member **50** is acted on the engaging gear **45**, and the flat plate portion **451** of the engaging gear **45** pushes the knob to make the knob move from the unlock position **P4** as shown in FIG. **18** back to the lock position **P3** as shown in FIG. **17**. At this time, the engaging teeth portion **452** of the engaging gear **45** is engaged with the teeth portion **323a** of the axle sleeving portion **323** (as shown in FIG. **16**) again, and thus the adjustment board **30** is disabled from rotation relative to the rotation axle **23**, and the adjustment of the light receiving angle of the solar panel **314** is accomplished.

(41) It should be supplementarily noted here that the adjustment board **30** of the GPS positioning stake **1, 2, 3, 4** of the present invention is provided at two ends of the upper and lower adjustment sections **311** and **321** as shown in FIG. **2** with a first end portion **30a** and a second end portion **30b** (as shown in FIG. **19**) respectively. In the process of the angle adjustment, the adjustment board **30** is allowed to be at farthest rotated to let the first end portion **30a** abutted against the base **20** (as shown in FIG. **20**), or rotated to let the second end portion **30b** abutted against the base **20** (as shown in FIG. **21**), such that the angle, for which the adjustment board **30** can be rotated, is limited.

(42) In conclusion, the GPS positioning stake **1, 2, 3, 4** of the present invention is self-powered by the solar panel **314** for the operation of the GPS positioning module **24**, which solves the problem of the limited position of the placement of the GPS positioning stake **1**, allowing the user to insert the GPS positioning stake **1** of the present invention at any location for positioning the robotic lawn mower. Therefore, the GPS positioning stake **1, 2, 3, 4** of the present invention has relatively higher flexibility in use. Further speaking, the GPS positioning stake **1, 2, 3, 4** of the present invention allows the user to adjust the angle of the adjustment board **30** to increase the probability of the solar panel **314** being illuminated by the sun, so as to increase the energy conversion efficiency.

(43) The invention being thus described, it will be obvious that the same may be varied in many ways. Such variations are not to be regarded as a departure from the spirit and scope of the invention, and all such modifications as would be obvious to one skilled in the art are intended to be included within the scope of the following claims.

Claims

1. A GPS positioning stake, which is characterized in comprising: a supporting pole; a base connected with the supporting pole, the base having a GPS positioning module and a rotation axle; an adjustment board having an axle sleeving portion and a solar panel, the axle sleeving portion being pivotably connected with the rotation axle, the solar panel providing electric energy for operation of the GPS positioning module; and an angle adjusting device comprising: a first gear fixedly sleeved onto the rotation axle, the first gear having a first teeth portion; a second gear sleeved onto the rotation axle and located in the axle sleeving portion, the second gear being arranged in a way that the second gear is slidable along an axial direction of the rotation axle relative to the rotation axle and the axle sleeving portion and able to be driven by the axle sleeving portion to rotate relative to the rotation axle, the second gear having a second teeth portion facing toward the first teeth portion; an elastic member providing an elastic force acted on the second gear to make the second gear displace toward the first gear; and an operation member sleeved onto the rotation axle in a way that the operation member is displaceable between a lock position and an unlock position, the operation member having a pushing portion located in the axle sleeving portion and a force receiving portion exposed out of the axle sleeving portion, the force receiving portion being adapted for receiving an external force so that the operation member is displaced relative to the rotation axle from the lock position to the unlock position, when the operation member is located at the lock position, the second teeth portion being engaged with the first teeth portion to disable the axle sleeving portion of the adjustment board from rotation relative to the

rotation axle, when the operation member is located at the unlock position, the pushing portion being inserted between the second teeth portion and the first teeth portion to separate the second teeth portion from the first teeth portion to enable the axle sleeving portion of the adjustment board to drive the second gear to rotate relative to the rotation axle.

2. The GPS positioning stake as claimed in claim 1, which is characterized in that the operation member is a pressed rod or a pulled rod; the pressed rod or the pulled rod is sleeved onto the rotation axle in a way that the pressed rod or the pulled rod is displaceable along a radial direction of the rotation axle.

3. The GPS positioning stake as claimed in claim 2, which is characterized in that the second gear has a first slope; when the operation member is the pressed rod, the pushing portion of the pressed rod has a second slope, and the first slope is abutted on the second slope; when the operation member is the pulled rod, the pushing portion of the pulled rod has a third slope, and the first slope is abutted on the third slope.

4. The GPS positioning stake as claimed in claim 1, which is characterized in that the base has a position limiting block; the first gear has a position limiting hole; when the first gear is sleeved onto the rotation axle, the position limiting block fits in the position limiting hole so that the first gear is fixed to the rotation axle.

5. The GPS positioning stake as claimed in claim 1, which is characterized in that the angle adjusting device comprises a protecting cover fixedly disposed in the axle sleeving portion; the protecting cover has a bottom plate, an annular body portion extending from the bottom plate, an accommodating space formed by the bottom plate and the annular body portion, and a fixed pipe extending from the bottom plate and located in the annular body portion; the rotation axle of the base has a connecting portion; the fixed pipe is sleeved onto the connecting portion so that the axle sleeving portion is pivotable relative to the rotation axle.

6. The GPS positioning stake as claimed in claim 5, which is characterized in that the protecting cover has two embedded protrusions located in the annular body portion; the second gear has two embedded recesses provided separately; the embedded protrusions are embedded in the embedded recesses.

7. The GPS positioning stake as claimed in claim 6, which is characterized in that the second gear has a supporting portion; the elastic member is a coil spring and placed in the accommodating space of the protecting cover; an end of the elastic member is sleeved onto the supporting portion; another end of the elastic member is abutted on the bottom plate of the protecting cover.

8. The GPS positioning stake as claimed in claim 1, which is characterized in that the adjustment board has a first end portion and a second end portion; the adjustment board is rotatable until the first end portion is abutted against the base, or the adjustment board is rotatable until the second end portion is abutted against the base.

9. A GPS positioning stake, which is characterized in comprising: a supporting pole; a base connected with the supporting pole, the base having a GPS positioning module and a rotation axle; an adjustment board having an axle sleeving portion and a solar panel, the axle sleeving portion being pivotable relative to the rotation axle, an inner peripheral surface of the axle sleeving portion having a teeth portion, the solar panel providing electric energy for operation of the GPS positioning module; and an angle adjusting device comprising: an engaging gear sleeved onto the rotation axle and located in the axle sleeving portion, the engaging gear being arranged in a way that the engaging gear is slidable along an axial direction of the rotation axle relative to the rotation axle, the engaging gear having an engaging teeth portion facing toward the teeth portion of the axle sleeving portion; an elastic member providing an elastic force acted on the engaging gear to make the engaging gear displace toward the teeth portion of the axle sleeving portion; and an operation member inserted in the axle sleeving portion in a way that the operation member is displaceable between a lock position and an unlock position, when the operation member is located at the lock position, the engaging teeth portion of the engaging gear being engaged with the teeth portion of

the axle sleeving portion to disable the adjustment board from rotation relative to the rotation axle; when the operation member is located at the unlock position, the operation member pushing the engaging gear to separate the engaging teeth portion of the engaging gear from the teeth portion of the axle sleeving portion to enable the adjustment board to rotate relative to the rotation axle.

10. The GPS positioning stake as claimed in claim 9, which is characterized in that the operation member is a button or a knob; the button or the knob is inserted in the axle sleeving portion in a way that the button or the knob is displaceable along an axial direction of the rotation axle.

11. The GPS positioning stake as claimed in claim 10, which is characterized in that when the operation member is the knob, an outer peripheral surface of the knob has a thread, the inner peripheral surface of the axle sleeving portion has an annular flange, and the thread is abutted against the annular flange.

12. The GPS positioning stake as claimed in claim 9, which is characterized in that the engaging gear has a supporting portion; the elastic member is a coil spring; an end of the elastic member is sleeved onto the supporting portion of the engaging gear; another end of the elastic member is sleeved onto the rotation axle and abutted against the base.

13. The GPS positioning stake as claimed in claim 9, which is characterized in that the adjustment board has a first end portion and a second end portion; the adjustment board is rotatable until the first end portion is abutted against the base, or the adjustment board is rotatable until the second end portion is abutted against the base.
