

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250275626

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Jenkins; Zachary William et al.

Picnic Table Assembly

Abstract

The table having a top portion and a frame positioned under the top portion. The table further having a pair of planks, each plank coupled to a leg of a pair of legs. A joint transitions each of the planks to rotate inwards towards a central inner surface of the top portion. An inner surface of the plank and the inner surface of the top portion become adjacent permitting the table to be in a closed position.

Inventors: Jenkins; Zachary William (Douglassville, PA), Gehman; Rebecca (Lititz, PA), Nagle; Trevin (Mount Joy, PA)

Applicant: Clark Core Services, LLC (Lancaster, PA)

Family ID: 96881384

Assignee: Clark Core Services, LLC (Lancaster, PA)

Appl. No.: 18/909139

Filed: October 08, 2024

Related U.S. Application Data

us-provisional-application US 63560372 20240301

Publication Classification

Int. Cl.: A47B3/14 (20060101)

U.S. Cl.:

CPC A47B3/14 (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application claims priority under 35 U.S.C. § 119 to U.S. Provisional Patent Application No. 63/560,372 filed on Mar. 1, 2024.

FIELD OF THE INVENTION

[0002] The present invention pertains to a picnic table and, more particularly, to an improved folding picnic table.

BACKGROUND

[0003] Presently, designs for folding picnic tables are in the public space, however, the existing units provide a common nuisance. Specifically, the current designs of the folding picnic table make the unit nearly impossible to transport with one person without causing undue stress and strain. Therefore, there is a need for a folding picnic table that allows a single person to easily transport the picnic table without additional assistant.

SUMMARY

[0004] A table includes a top portion. The table further includes a frame positioned under the top portion. The table further includes a stabilizing structure coupled to the frame and having a pair of legs, each leg having a joint. The table further includes a pair of planks, each plank coupled to a leg of the pair of legs. The joint transitions each of the planks to rotate inwards towards a central inner surface of the top portion. An inner surface of the plank and the inner surface of the top portion become adjacent permitting the table to be in a closed position.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0005] In the following, the present invention is described in more detail with references to the drawings in which:

[0006] FIG. 1 illustrates a top perspective view of the picnic table assembly unfolded;

[0007] FIG. 2 illustrates a bottom perspective view of the picnic table assembly unfolded;

[0008] FIG. 3 illustrates another top perspective view of an exemplary embodiment;

[0009] FIG. 4 illustrates another bottom perspective view of an exemplary embodiment;

[0010] FIG. 5 illustrates another top perspective view of an exemplary embodiment;

[0011] FIG. 6 illustrates another bottom perspective view of an exemplary embodiment;

[0012] FIG. 7 illustrates a top, front, right side perspective view of an exemplary embodiment;

[0013] FIG. 8 illustrates an enlarged perspective view;

[0014] FIG. 9 illustrates a top perspective view of the picnic table assembly in a first folded position; and

[0015] FIG. 10 illustrates a bottom perspective view of the picnic table assembly in a second folded position.

DETAILED DESCRIPTION OF THE EMBODIMENT(S)

[0016] With reference to the Figures, a picnic table assembly 1 according to the invention is shown.

[0017] In an exemplary embodiment shown, a picnic table assembly 1 according to the invention generally includes a structure. The structure generally includes a top portion 2, a frame 4, a stabilizing structure 6, a pair of planks 8 and a side frame 10.

[0018] In the exemplary embodiment and as shown in FIG. 1, the top portion 2 is a rectangular planar member. One skilled in the art would understand the applicant's design is not the exclusive embodiment. The top portion 2 further includes an outer surface 20 and an inner surface 22. The top portion 2 further includes a passageway 24 extending through the top portion 2, specifically, through a central area of both the outer surface 20 and the inner surface 22. One skilled in the art

would understand the applicant's design is not the exclusive embodiment.

[0019] In the exemplary embodiment, the top portion **2** further includes an edging **26**. The edging **26** is an elongated member extending downwards from a perimeter of the top portion **2**. One skilled in the art would understand the applicant's design is not the exclusive embodiment. The edging **26** includes a thickness, the same thickness as a thickness of the top portion **2**.

[0020] In the exemplary embodiment, the top portion **2** and the edging **26** form a cradle **28**. The cradle **28** is formulated on the inner surface **22** of the top portion **2**. The cradle **28** permits the frame **4** to rest and abut against the top portion **2** and the edging **26**. One skilled in the art would understand the applicant's design is not the exclusive embodiment.

[0021] In the exemplary embodiment and as shown in FIG. **2**, the frame **4** is octagon shaped. One skilled in the art would understand the applicant's design is not the exclusive embodiment. The frame **4** is positioned within the cradle **28**.

[0022] The frame **4** further includes a plurality of braces **30**. The at least four braces **30** extend across a width side of the frame **4**. One skilled in the art would understand the applicant's design is not the exclusive embodiment. Each brace **30** is a cylindrical member with a partial curvature at each end of the brace **30**.

[0023] In the exemplary embodiment, the stabilizing structure **6** includes a pair of legs **40**. The at least two pairs of legs **40** each extend from at least one brace **30**. Each pair of legs **40** include a plurality of horizontal members and vertical members. The stabilizing structure **6** further includes a joint bracket **42**. The joint bracket **42** permits locking and unlocking of each leg **40** and providing each leg **40** with rotational movement. The at least four joint brackets **42** are positioned on each horizontal member of the leg **40**. One skilled in the art would understand the applicant's design is not the exclusive embodiment.

[0024] In the exemplary embodiment and as shown in FIGS. **1-4**, each plank **8** is an elongated planar member. One skilled in the art would understand the applicant's design is not the exclusive embodiment. Each plank **8** further includes an outer surface **50** and an inner surface **52**.

[0025] In the exemplary embodiment, each plank **8** further includes a plank edging **54**. The plank edging **54** is an elongated member extending downwards from a perimeter of each of the planks **8**. One skilled in the art would understand the applicant's design is not the exclusive embodiment. The plank edging **54** includes a thickness, the same thickness as a thickness of the plank **8**.

[0026] In the exemplary embodiment, each plank **8** and the plank edging **54** form a side cradle **56**. The side cradle **56** is formulated on the inner surface **52** of each of the planks **8**. The side cradle **56** permits the side frame **10** to rest and abut against the plank **8** and the plank edging **54**. One skilled in the art would understand the applicant's design is not the exclusive embodiment.

[0027] In the exemplary embodiment, the side frame **10** is rectangular shaped and positioned within the side cradle **56**. One skilled in the art would understand the applicant's design is not the exclusive embodiment.

[0028] In another exemplary embodiment, with reference to the FIGS. **5-6**, a picnic table assembly **1'** according to the invention is shown.

[0029] In an exemplary embodiment shown, a picnic table assembly **1'** according to the invention generally includes a structure. The structure generally includes a top portion **2'**, a frame **4'**, a stabilizing structure **6'**, a pair of planks **8'** and a side frame **10'**.

[0030] In the exemplary embodiment and as shown in FIG. **5**, the top portion **2'** is a rectangular planar member. One skilled in the art would understand the applicant's design is not the exclusive embodiment. The top portion **2'** further includes an outer surface **20'** and an inner surface **22'**. The top portion **2'** further includes a passageway **24'** extending through the top portion **2'**, specifically, through a central area of both the outer surface **20'** and the inner surface **22'**. One skilled in the art would understand the applicant's design is not the exclusive embodiment.

[0031] In the exemplary embodiment, the top portion **2'** further includes an edging **26'**. The edging **26'** is an elongated member extending downwards from a perimeter of the top portion **2'**. One

skilled in the art would understand the applicant's design is not the exclusive embodiment. The edging **26'** includes a thickness, the same thickness as a thickness of the top portion **2'**.

[0032] In the exemplary embodiment, the top portion **2'** and the edging **26'** form a cradle **28'**. The cradle **28'** is formulated on the inner surface **22'** of the top portion **2'**. The cradle **28'** permits the frame **4'** to rest and abut against the top portion **2'** and the edging **26'**. One skilled in the art would understand the applicant's design is not the exclusive embodiment.

[0033] In the exemplary embodiment and as shown in FIG. 6, the frame **4'** is a plurality of horizontal and vertical members. One skilled in the art would understand the applicant's design is not the exclusive embodiment. The frame **4'** is positioned within the cradle **28'**.

[0034] The frame **4'** further includes a plurality of braces **30'**. The at least four braces **30'** extend across a width side of the frame **4'**. One skilled in the art would understand the applicant's design is not the exclusive embodiment. A pair of braces **32'** include a curvature extending away from the top portion **2'**. A second pair of braces **34'** includes an additional member extending towards the edging **26'** and away from the passageway **24'**.

[0035] In the exemplary embodiment, the stabilizing structure **6'** includes a pair of legs **40'**. The at least two pairs of legs **40'** each extend from at least one brace **30'**. Each pair of legs **40'** include a plurality of horizontal members and vertical members with a slight curvature. One skilled in the art would understand the applicant's design is not the exclusive embodiment.

[0036] In the exemplary embodiment, the stabilizing structure **6'** further includes a joint bracket **42'**. The joint bracket **42'** permits locking and unlocking of each leg **40'** and providing each leg **40'** with rotational movement. The at least four joint brackets **42'** are positioned on each horizontal member of the leg **40'**. One skilled in the art would understand the applicant's design is not the exclusive embodiment.

[0037] In the exemplary embodiment and as shown in FIGS. 5-6, each plank **8'** is an elongated planar member. One skilled in the art would understand the applicant's design is not the exclusive embodiment. Each plank **8'** further includes an outer surface **50'** and an inner surface **52'**.

[0038] In the exemplary embodiment, each plank **8'** further includes a plank edging **54'**. The plank edging **54'** is an elongated member extending downwards from a perimeter of each of the planks **8'**. One skilled in the art would understand the applicant's design is not the exclusive embodiment. The plank edging **54'** includes a thickness, the same thickness as a thickness of the plank **8'**.

[0039] In the exemplary embodiment, each plank **8'** and the plank edging **54'** permits the side frame **10'** to rest and abut against the plank **8'** and the plank edging **54'**. One skilled in the art would understand the applicant's design is not the exclusive embodiment.

[0040] In the exemplary embodiment, the side frame **10'** is curvature shaped and positioned against each plank **8'**. One skilled in the art would understand the applicant's design is not the exclusive embodiment.

[0041] In the exemplary embodiment, the picnic table assembly **1'** further includes a plurality a handles **60'**. The at least four handles each include a strap **62'** and a grip **64'**. The strap **62'** couples to each end of the grip **64'**. The strap **62'** is further fixed to the edging **26'**. One skilled in the art would understand the applicant's design is not the exclusive embodiment.

[0042] In the exemplary embodiment and as shown in FIGS. 1-10, a user utilizing the picnic table assembly **1**, **1'** is shown in an open position. Each pair of legs **40**, **40'** is rotated along the brace **30**, **30'** where a portion of the leg **40**, **40'** is positioned within the side cradle **56** of the inner surface **52** of the plank **8** or abutting against the inner surface **52'** of the plank **8'**. As shown in FIG. 9, each plank **8**, **8'** is positioned parallel to the edging **26**, **26'** of the top portion **2**, **2'**. As shown in FIG. 10, each of the joint brackets **42**, **42'** are switched from a locked state to an unlocked state to permit each of the planks **8**, **8'** to rotate inwards towards a central inner surface **22**, **22'** of the top portion **2**, **2'**. The inner surface **52**, **52'** of the plank **8**, **8'** and the inner surface **22**, **22'** of the top portion **2**, **2'** become adjacently positioned providing the picnic table assembly **1**, **1'** in a closed position.

[0043] It should be noted that various changes and modifications to the embodiments described

herein will be apparent to those skilled in the art. Such changes and modifications may be made without departing from the spirit and scope of the present invention and without diminishing its intended advantages. For example, various embodiments of the systems and methods may be provided based on various combinations of the features and functions from the subject matter provided herein.

Claims

1. A table comprising: a top portion; a frame positioned under the top portion; a stabilizing structure coupled to the frame and having a pair of legs, each leg having a joint; and a pair of planks, each plank coupled to a leg of the pair of legs, the joint transitions each of the planks to rotate inwards towards a central inner surface of the top portion, an inner surface of the plank and the inner surface of the top portion become adjacent permitting the table to be in a closed position.
 2. The table of claim 1, wherein the top portion includes a cradle formed on the inner surface of the top portion.
 3. The table of claim 2, wherein the frame is positioned within the cradle.
 4. The table of claim 3, wherein the frame further includes at least one brace.
 5. The table of claim 4, wherein the at least one brace extends across a width of the frame.
 6. The table of claim 5, wherein the pair of legs extend from the brace.
 7. The table of claim 6, wherein each leg includes a horizontal member and a vertical member.
 8. The table of claim 7, wherein each joint is positioned on the horizontal member of the leg.
 9. The table of claim 8, wherein each plank includes a cradle formed on the inner surface of the plank.
 10. The table of claim 9, wherein each plank includes a frame positioned within the cradle.
 11. A table comprising: a planar member having a frame coupled to an inner surface of the planar member; a pair of planks; a pair of legs, each leg coupled at one end to the frame and at a second end to a plank of the pair of planks, each leg having a joint, the joint permitting rotation of the plank from an open position to a closed position, in the open position each plank extends away from the planar member, in the closed position, an inner surface of the plank and the inner surface of the planar member are adjacent.
 12. The table of claim 11, wherein in the closed position, a portion of the leg is positioned within a cradle of the planar member and within a cradle of the plank.
 13. The table of claim 12, wherein the frame includes a plurality of braces extending across its width.
 14. The table of claim 13, wherein the plank further includes a frame positioned within the cradle of the plank.
 15. The table of claim 14, wherein the planar member further includes a plurality of handles.
-