

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250275638

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Barber; Karen

STRUCTURED BED SKIRT FOR AN ADJUSTABLE BED

Abstract

A bed skirt for an adjustable bed is provided. The bed skirt has a fitted base configured to at least partially wrap around a foundation of the adjustable bed and a top portion configured to cover a top portion of the foundation. An cut-out has a plurality of horizontally positioned elastic strips that define a series of sections located on the top panel and a plurality of vertically integrated fasteners positioned proximate each of the left side and the right side of the fitted base a horizontally integrated fastener positioned proximate the foot portion, and has adjustable right, left and foot drop panels.

Inventors: Barber; Karen (Palmetto, FL)

Applicant: Barber; Karen (Palmetto, FL)

Family ID: 96881361

Appl. No.: 18/593174

Filed: March 01, 2024

Publication Classification

Int. Cl.: A47G9/02 (20060101)

U.S. Cl.:

CPC A47G9/0292 (20130101);

Background/Summary

TECHNICAL FIELD

[0001] The present disclosure relates generally to bedding accessories. More specifically, the

present disclosure relates to a structured bed skirt for an adjustable bed that prevents bunching and is height adjustable.

BACKGROUND OF THE INVENTION

[0002] Bed skirts and dust ruffles are common bedding accessories. They are both utilitarian and decorative. They are utilitarian because they assist in preventing dust and other foreign objects from settling beneath a bed while also hiding items that may be stored under a bed, and they are decorative in that they are designed to be aesthetically pleasing and complement bedroom decor and other bed accessories including sheets, comforters, quilts, and bedspreads. A conventional bed skirt is made of different materials such as linen, cotton, or a cotton/polyester blend. The bed skirt is placed between the mattress and the box spring of a bed.

[0003] Adjustable beds, also referred to as adjustable bases or adjustable frames, have become increasingly popular. In terms of revenue, the adjustable beds product segment was valued at USD 6.24 billion in 2021 and has since expanded at a compound annual growth rate (CAGR) of 8.8% from 2022 to 2030. The increasing global population, rapid urbanization, and growing disposable income levels are boosting product adoption. Increasing sales of trending products also boost the potential of this market. In addition, the growing trend of smart homes will contribute to industry expansion over the forecast period. While adjustable beds are best suitable for the elderly or those with mobility issues, they are now being used by people of all ages for health and lifestyle benefits as these beds can help ease chronic pains related to arthritis, sciatica, etc., and can provide when a user is watching television or eating in bed. With adjustable beds, however, due to the adjustability of the bed, base and mattress, bed skirts often experience a “bunching” or “gap” problem that make them aesthetically unpleasing.

[0004] Conventional bed skirts for adjustable beds have a cut to allow for separation of the skirt when the adjustable bed is in an upright position. However, as the bed adjusts and changes position, the bed skirt still flows downwardly due to gravity, thus leaving an aesthetically unpleasing visual.

[0005] Furthermore, drop length or “height” may be problematic because conventional bed skirts are manufactured with a fixed drop length. However, the distance from the top of a bed platform to the floor is not a standardized distance, so the bottom of the bed skirt may hang a few inches above the floor or puddle on the floor if it is too long and dragging on the floor collecting dirt, or they are too short thus exposing the metal legs and under-bed storage, as well as allowing dust to collect under the bed, especially in the case of a tailored bed skirt. Further, most bed skirts are manufactured using one solid piece of material, which makes it incredibly challenging to maintain and clean. Usually, the bed skirts have pleats (gathered bed skirt) at the corners and in the middle section of each side that are difficult to iron and/or clean.

[0006] Therefore, there is a need for a bed skirt for an adjustable bed or base that obviates the above recited drawbacks.

SUMMARY OF THE INVENTION

[0007] The disclosure relates generally to a structured an adjustable bed skirt for an adjustable bed. In one embodiment, the bed skirt is adjustable to different heights according to the height of the adjustable bed foundation to user preference. The adjustable bed foundation may comprise the foundation, the box spring, or the mattress, each, together or separate, encompassing the foundation depending upon the adjustable bed design. In one embodiment, the bed skirt is made of a material, but not limited to, linen, cotton, a cotton/polyester blend, and a polyester upholstery fabric. In one embodiment, the bed skirt is formed with a tailored fit that may be easily adaptable for use with any size of adjustable bed including but not limited to twin beds, full beds, and, optionally, queen and/or king beds, slipcover sofas, chairs, and other furniture. The bed skirt may provide comfort for the consumer or user to utilize and provide a stylish appearance to the bed platform.

[0008] In one embodiment, a bed skirt for an adjustable bed is disclosed. The bed skirt comprises a fitted base configured to at least partially wrap around a foundation of the adjustable bed, wherein the fitted base comprises a head portion, a foot portion, a left side and a right side, and wherein the

fitted base comprises a top panel configured to cover a top portion of the foundation, wherein the top panel comprises a cut-out having a plurality of horizontally positioned elastic strips that define a series of sections on the foundation of the adjustable bed located on the top panel, wherein the elastic straps are configured to provide pliability during adjustment of the adjustable bed; a plurality of vertically integrated fasteners positioned proximate each of the left side and the right side of the fitted base, wherein the vertically integrated fasteners are spaced apart at a predetermined distance on the left side and the right side; a horizontally integrated fastener positioned proximate the foot portion; a right drop panel configured to connect to one of the vertically integrated fasteners on the right side; a left drop panel configured to connect to one of the vertically integrated fasteners on the right side; a foot drop panel configured to connect to the horizontally integrated fastener foot portion; wherein each of the right drop panel, left drop panel and foot drop panel are height adjustable.

[0009] In one embodiment, the foot panel is configured to cover a bottom side portion of the bed platform. In one embodiment, the foot panel includes at least one fabric layer and one or more fastener strips. In one embodiment, the fastener strips are sewn along a width of a top edge of the foot panel. The foot panel is further configured to be removably and adjustably fastened to the left panel and the right panel by mating the one or more fastener strips along the bottom edge of the right panel and the left panel, thereby allowing the bed skirt to be adjusted to a desired height according to the height of the bed platform by the user.

[0010] In one embodiment, the fabric layer of each panel of the bed skirt is folded inwardly and sewn to create at least one sleeve with an open end. In one embodiment, the bed skirt further comprises a foldable structured insert/panel. In one embodiment, the structured insert/panel is securely positioned into the sleeves via the open ends of each fabric layer of the left panel, right panel, and the foot panel to encase the outer surface of the bed platform. In one embodiment, the structured insert/panel is a collapsible and foldable core board.

[0011] This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter. The claimed subject matter is not limited to implementations that solve any or all disadvantages noted in the Background.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0012] Aspects of the present disclosure are illustrated by way of example and are not limited by the accompanying figures for which like references indicate like elements.

[0013] FIG. 1 illustrates a top right side perspective view of the adjustable bed skirt for the adjustable bed showing the panel drop, according to an embodiment;

[0014] FIG. 2 illustrates a top right side perspective view of the adjustable bed skirt for the adjustable bed without the panel drops, according to an embodiment;

[0015] FIG. 3 illustrates a front view of a structured foot panel for of the adjustable bed skirt for the adjustable bed, according to one embodiment;

[0016] FIG. 4 illustrates a front view of a structured right panel for of the adjustable bed skirt for the adjustable bed, according to one embodiment;

[0017] FIG. 5 illustrates a front view of a structured left panel for of the adjustable bed skirt for the adjustable bed, according to one embodiment;

[0018] FIG. 6 illustrates a top right left perspective view of the top wrap and bottom wrap the adjustable bed skirt for the adjustable bed according to an embodiment;

[0019] FIG. 7 illustrates a series of a top right side perspective views showing the drop panels in

different positions according to an embodiment.

DETAILED DESCRIPTION OF THE INVENTION

[0020] Exemplary embodiments are discussed below with reference to the Figures.

[0021] In the descriptions above and in the claims, phrases such as “at least one of” or “one or more of” may occur followed by a conjunctive list of elements or features. The term “and/or” may also occur in a list of two or more elements or features. Unless otherwise implicitly or explicitly contradicted by the context in which it used, such a phrase is intended to mean any of the listed elements or features individually or any of the recited elements or features in combination with any of the other recited elements or features. For example, the phrases “at least one of A and B;” “one or more of A and B;” and “A and/or B” are each intended to mean “A alone, B alone, or A and B together.” A similar interpretation is also intended for lists including three or more items. For example, the phrases “at least one of A, B, and C;” “one or more of A, B, and C;” and “A, B, and/or C” are each intended to mean “A alone, B alone, C alone, A and B together, A and C together, B and C together, or A and B and C together.” Use of the term “based on,” above and in the claims is intended to mean, “based at least in part on,” such that an unrecited feature or element is also permissible.

[0022] The subject matter described herein can be embodied in systems, apparatus, methods, and/or articles depending on the desired configuration. The implementations set forth in the foregoing description do not represent all implementations consistent with the subject matter described herein. Instead, they are merely some examples consistent with aspects related to the described subject matter. Although a few variations have been described in detail above, other modifications or additions are possible. In particular, further features and/or variations can be provided in addition to those set forth herein. For example, the implementations described above can be directed to various combinations and sub-combinations of the disclosed features and/or combinations and sub combinations of several further features disclosed above. In addition, the logic flows depicted in the accompanying figures and/or described herein do not necessarily require the particular order shown, or sequential order, to achieve desirable results. Other implementations may be within the scope of the following claims.

[0023] The described embodiments are to be considered in all respects only as illustrative and not restrictive. The scope is, therefore, indicated by the appended claims rather than by the foregoing description. All changes that come within the meaning and range of equivalency of the claims are to be embraced within their scope.

[0024] Referring now to FIG. 1, a top right side perspective view of the adjustable bed skirt for the adjustable bed showing the panel drop shown generally at **100**. The bed skirt **100** is formed with at least three structured drop panels, but in optional embodiments, may have as many as six. The structuring of each panel using inserts or cores is important aesthetically, as it gives the skirt a clean drop, and the gaps therebetween provide the ability to the adjustable bed to adjust.

[0025] As shown, the adjustable bed skirt **100** comprises a fitted base **102** configured to at least partially wrap around a foundation (shown in FIG. 2) of the adjustable bed. The fitted base **102** comprises a head portion **101**, a foot portion **103**, a left side **105** and a right side **107**. A top portion **120** is provided and is configured to cover a top portion of the foundation. Top portion **120** comprises cut-out **104**, which allows the foundation of the be seen, and form sections **108**. The fitted base may be formed of a material with elasticity and stickiness.

[0026] The cut-out **104** has a plurality of horizontally positioned elastic strips **106a**, **106b**, **106c** that define a series of sections **108a**, **108b** and **108c** located on the top portion **120**. The elastic straps **108a**, **108b** and **108c** are configured to provide pliability during adjustment of the adjustable bed. While three elastic straps are shown, any number of elastic straps may be employed based on the points of motion of the adjustable bed. Furthermore, the straps are located in flat sections of the adjustable bed rather than the points of motion in embodiments so that the stretch. The plurality of horizontally positioned elastic strips are attached to an end of each section on one side of the elastic

strip, and an end of the subsequent section on another side of the elastic strip.

[0027] In FIG. 1, right panels **114a-d**, and foot panel **110** are shown fully constructed, with the bed in a semi-upright position. While fasteners are shown in this FIG. 1, they are shown in detail in FIG. 2, showing the actual attachment of the panels. In embodiments, the drop panels **110** and **114** (left drop panels not being shown in this FIG. 5 may be formed of an aesthetically pleasing material and fabrics. In one embodiment, the drop panels may be folded inwardly and sewn on a fold line to create a seam or a sleeve, described in greater details in FIGS. 3-5.

[0028] In operation, in embodiments, the top portion **120** is positioned on the foundation and under the mattress, and the drop panels hang approximately to the floor. To provide adjustability as it relates to the drop to the floor, the bed skirt comprises may comprise hook and loop type fasteners, magnetic strips, fastener strips and socket snaps or eyelets.

[0029] In optional embodiments, horizontal flexible piping may be attached where the top portion and side portions meet, and where the side portion and foot portions. The horizontal piping may be configured to connect the panels to the base.

[0030] With reference now to FIG. 2, a top right side perspective view of the adjustable bed skirt for the adjustable bed without the panel drops is shown generally at **200**. In this embodiment, the foundation **210** and legs **212** of the adjustable bed can be seen. For reference, the fitted base **102**, top portion **120**, cut-out **104**, horizontally positioned elastic strips **106a**, **106b**, **106c**, and series of sections **108a**, **108b** and **108c** located on the top portion **120** is shown. Again the foundation can also be seen via cut out **104** and the series of sections **108**.

[0031] In this perspective view, a plurality of right side vertically integrated fasteners **202** and a plurality of left side vertically integrated fasteners **206** are shown positioned proximate each of the left side **105** and the right side **107** of the fitted base **102**. The vertically integrated fasteners **202** and **206** are spaced apart at a predetermined distance on the left side **105** and the right side **107**, leaving right spaces **204** and left spaces **208** positioned in between vertically integrated fasteners **202** and **206**, respectively. As shown, there are three spaces on each side, but more or less spaces may be provided depending upon the points of motion of the adjustable bed. Each of the vertically integrated fasteners **202** and **206** are configured to connect to each of the right drop panels **114a-d** and the left drop panels (now shown in this view, but analogous to the right drop panels).

[0032] A horizontally integrated fastener **214** is positioned proximate the foot portion **103**. Because there are no points of vertical motion in adjustable beds, the horizontally integrated fastener **214** may be positioned across the entire length of the foot portion without gaps. However, in embodiments, spaces may be provided should the user want multiple drop panels at the foot portion **103** for aesthetic purposes. The horizontally integrated fastener **214** is configured to connect the foot drop panel **110**. Each of the drop panels described herein are height adjustable.

[0033] With reference now to FIG. 3, a deconstructed front view of the foot drop panel is shown generally at **300**. As can be seen in FIG. 3, view **301**, a front side of the foot panel **110** can be seen. Foot drop panel comprises an attachment a fold that forms an internal pocket **304**. The **304** is configured to accept a re-sizable structured insert **306** shown in view **303** to provide rigidity to the drop panel **110** thereby improving the aesthetics of the bed skirt **100** whilst also protecting the user's legs from the structure of the bed foundation should the user happen to run into the bed, and also making the skirt more easily ironable or pressable. Panels **308** are provided so that the user can appropriately size the drop panel **110**. The structured insert **306** may be provided for each of the drop portions of the left panel, right panel, and foot panel, and may comprise foam core for example as shown in FIGS. 4 and 5. The back side of the foot drop panel **310** shown in view **305** comprises an attachment portion **312** configured to attach to the fasteners **214**. In this way, fasteners **214** and **312** may comprise male fasteners and female fasteners, the male may be on the drop panel and the female may be on the fitted based, or vice versa. Rows of fasteners may be positioned on the foot drop panel **110** to adjust the height of the panel **110**.

[0034] With reference now to FIG. 3, a deconstructed front view of the foot drop panel is shown

generally at **300**. As can be seen in FIG. 3, view **301**, a front side of the foot panel **110** can be seen. Foot drop panel comprises an attachment a fold that forms an internal pocket **304**. The **304** is configured to accept a re-sizable structured insert **306** shown in view **303** to provide rigidity to the drop panel **110** thereby improving the aesthetics of the bed skirt **100** whilst also protecting the user's legs from the structure of the bed foundation should the user happen to run into the bed, and also making the skirt more easily ironable or pressable. Panels **308** are provided so that the user can appropriately size the drop panel **110**. The structured insert **306** may be provided for each of the drop portions of the left panel, right panel, and foot panel, and may comprise foam core for example as shown in FIGS. 4 and 5. The back side of the foot drop panel **310** shown in view **305** comprises an attachment portion **312** configured to attach to the fasteners **214**. In this way, fasteners **214** and **312** may comprise male fasteners and female fasteners, the male may be on the drop panel and the female may be on the fitted based, or vice versa. Rows of fasteners may be positioned on the foot drop panel **110** to adjust the height of the panel **110**.

[0035] With reference now to FIG. 4, a deconstructed front view of the right drop panel is shown generally at **400**. As can be seen in FIG. 4, view **401**, a front side of the right panel **112** can be seen. Right drop panel **112** comprises a fold that forms an internal pockets **416** that are shown in greater detail in view **405**. Separate panels **114a-d** are provided so that small gaps exist to allow for motion of the bed. In embodiments, elastic material **412a-c** provided in between panels **114a-d** so that no gaps show. The material may have the same aesthetic quality has the panels themselves to form a continuous panel. View **403** shows each insert **406** separately as they are sized to fit in each of the pockets shown in view **405**.

[0036] In embodiments, material **412a-c** may be additional material that is configured to fold inwardly when the adjustable bed is flat, but when the bed is in motion or in a non-flat position, the additional material (or fabric) provides a polished flat look so that the user cannot see any gaps between panel. This additional material provides an allowance for motion. Of course, in embodiments, such as those shown in FIG. 7, there can be gaps such that each panel is entirely separate. This applies to each of the right drop panel, left drop panel and foot drop panel.

[0037] The back view of the right panel is shown at **405**. Openings **414a-d** for pockets **416a-d** accept a re-sizable structured insert **406** shown in view **405** to provide rigidity to the drop panel **112** thereby improving the aesthetics of the bed skirt **100** whilst also protecting the user's legs from the structure of the bed foundation should the user happen to run into the bed, and also making the skirt more easily ironable or pressable. Panels **308** are provided so that the user can appropriately size the drop panel **112**. The back side of the right drop panel **112** shown in view **305** comprises an attachment portion **420** configured to attach to the fasteners **418**. In this way, fasteners **418** and **202** may comprise male fasteners and female fasteners, the male may be on the drop panel and the female may be on the fitted based, or vice versa. Rows of fasteners may be positioned on the right drop panel **112** to adjust the height of the panel **112**. The right drop panel **112** comprises female fasteners that are spaced apart congruently to the predetermined distances of the male fasteners of the right side of the fitted base or vice versa.

[0038] Referring now to FIG. 5, a deconstructed front view of the left drop panel is shown generally at **500**. As can be seen in FIG. 5, view **501**, a front side of the right panel **504** can be seen. Right drop panel **504** comprises a fold that forms an internal pockets **516** that are shown in greater detail in view **505**. Separate panels **516a-d** are provided so that small gaps exist to allow for motion of the bed. In embodiments, elastic material **512a-c** provided in between panels **514a-d** so that no gaps show. The material may have the same aesthetic quality has the panels themselves to form a continuous panel. View **503** shows each insert **506** separately as they are sized to fit in each of the pockets shown in view **505**.

[0039] The back view of the left panel is shown at **505**. Openings **514a-d** for pockets **516a-d** accept a re-sizable structured insert **506** shown in view **505** to provide rigidity to the drop panel **506** thereby improving the aesthetics of the bed skirt **100** whilst also protecting the user's legs from the

structure of the bed foundation should the user happen to run into the bed, and also making the skirt more easily ironable or pressable. Panels **508** are provided so that the user can appropriately size the left drop panel **506**. The back side of the left drop panel **112** shown in view **505** comprises an attachment portion **420** configured to attach to the fasteners **518**. In this way, fasteners **518** and **506** may comprise male fasteners and female fasteners, the male may be on the drop panel and the female may be on the fitted based, or vice versa. Rows of fasteners may be positioned on the left drop panel **506** to adjust the height of the panel **506**. The right drop panel **506** comprises female fasteners that are spaced apart congruently to the predetermined distances of the male fasteners of the right side of the fitted base or vice versa.

[0040] Referring to FIGS. **3-5**, the structured inserts are in the form of a foam core board insert/panel of the bed skirt **100**. The structured insert is dimensioned by the user to fit into the pockets for each panel to provide a structured aesthetic appearance. In embodiments, the inserts may be sized based on known standards (King, Queen, Full, Twin). Other materials that the panel may be made of is cardboard or plastic and may be telescoping rather than foldable or cuttable—meaning rather than they have panels fold they telescope into themselves, or may be accordion in nature. The structured inserts comprise a plurality of pre-folds or pre-cuts so that a user using either scissors or by folding the panel over on itself, can change the height of the insert. The number of panels may vary.

[0041] With reference now to FIG. **6**, illustrates, top and right left perspective view of the fitted base is shown wrapped around the foundation of the adjustable bed skirt for the adjustable bed. The bottom side **602** is shown as is the bottom side **604** of the panel **102**.

[0042] FIG. **7** illustrates a series of a top right side perspective views showing the drop panels in different positions according to embodiments at **702**, **704**, **706** and **708**.

[0043] In one embodiment, the bed skirt **100** is made of a material such as linen, cotton, a cotton/polyester blend, and/or a polyester upholstery fabric, though may be formed of other materials. In one embodiment, the bed skirt **100** is sewn to a piece of lightweight mesh fabric. In one embodiment, the bed skirt **100** is formed with a tailored fit that may be easily adaptable for use with any size of the adjustable bed, twin beds, full beds, and, optionally, queen and/or king beds.

[0044] In embodiments, the fasteners may comprise hook and loop (H&L) fasteners, snap tape fasteners or magnets (e.g., magnetic strips, or sockets and a plurality of eyelets).

[0045] As it relates to height adjustability, in operation, drop portion or each fastener strip on the fitted based may be multiple fastener strips. For example, should the panels be fastened at a first row, the side drop length is X. Should the panels be fastened at a second row, the length of the side drop is Y.

[0046] In one embodiment, the drop portions may be, but not limited to, linen fabric. In one embodiment, the drop portion may be folded inwardly and sewn on a fold line to create a seam or a sleeve having a dimension of about, but not limited to, 80" length and 14" height. Further, the fold line shown view **303** enables the user to easily fold the fabric layer for easy carrying and storage of bed skirt during not in use.

[0047] Preferred embodiments are described herein, including the best mode known to the inventors. It should be understood that the illustrated embodiments are exemplary only and should not be taken as limiting.

[0048] Although specific features of various embodiments may be shown in some drawings and not in others, this is for convenience only. In accordance with the principles described herein, the feature(s) of one drawing may be combined with any or all of the features in any of the other drawings. The words "including," "comprising," "having," and "with" as used herein are to be interpreted broadly and comprehensively, and are not limited to any physical interconnection. Moreover, any embodiments disclosed herein are not to be interpreted as the only possible embodiments. Rather, modifications and other embodiments are intended to be included within the scope of the appended claims.

Claims

1. A bed skirt for an adjustable bed, the bed skirt comprising: a fitted base configured to at least partially wrap around a foundation of the adjustable bed, wherein the fitted base comprises a head portion, a foot portion, a left side and a right side, and wherein the fitted based comprises: a top portion configured to cover a top portion of the foundation, wherein the top panel comprises a cut-out having a plurality of horizontally positioned elastic strips that define a series of sections located on the foundation, wherein the elastic straps are configured to provide pliability during adjustment of the adjustable bed; a plurality of vertically integrated fasteners positioned proximate each of the left side and the right side of the fitted base, wherein the vertically integrated fasteners are spaced apart at a predetermined distance on the left side and the right side; a horizontally integrated fastener positioned proximate the foot portion; a right drop panel configured to connect to one of the vertically integrated fasteners on the right side; a left drop panel configured to connect to one of the vertically integrated fasteners on the right side; a foot drop panel configured to connect to the horizontally integrated fastener foot portion; wherein each of the right drop panel, left drop panel and foot drop panel are height adjustable.
 2. The bed skirt of claim 1, wherein the fasteners comprise male fasteners on the fitted base, and female fasteners on the panels, and wherein: the right drop panel comprises female fasteners that are spaced apart congruently to the predetermined distances of the male fasteners of the right side of the fitted base; the left drop panel comprises female fasteners that are spaced apart congruently to the predetermined distances of the male fasteners of the right side of the fitted base.
 3. The bed skirt of claim 1, wherein each of the plurality of horizontally positioned elastic strips are attached to an end of each section on one side of the elastic strip, and an end of the subsequent section on another side of the elastic strip.
 4. The bed skirt of claim 3, wherein the elastic straps are positioned on a flat portion of the adjustable bed.
 5. The bed skirt of claim 1, wherein the plurality of vertically integrated fasteners comprises at least two rows of fasteners configured to attach to the other of the left panel or right panel on a first of the two rows or the second of the two rows to adjust a height of the left panel drop portion or the right panel drop portion, and wherein the horizontally integrated fastener comprise at least two rows of fasteners configured to adjust a height of the foot panel drop portion.
 6. The bed skirt of claim 1, wherein the left panel, right panel, and foot panel drop portions further comprise at least one pocket; a plurality of structured panels dimensioned to fit within the at least one pocket of the left panel, right panel, and foot panel drop portions; wherein a fabric layer on the left panel, the right panel and the foot panel is foldable inwardly and to create the at least one pocket in each of the left panel, the right panel and the foot panel drop portions.
 7. The bed skirt of claim 6, wherein the plurality of structured panels comprises seams to allow a user to adjust a size of the structured panels.
 8. The bed skirt of claim 1, wherein the structured panel is formed of a foam core board.
 9. The bed skirt of claim 1, wherein the first plurality of fasteners, second plurality of fasteners, or both, are fastener are hook and loop fasteners.
 10. The bed skirt of claim 5, wherein the at least one pockets comprises an open end configured to encase the structured panel.
-