



US 20250277554A1

(19) **United States**

(12) **Patent Application Publication**
Bapu et al.

(10) **Pub. No.: US 2025/0277554 A1**

(43) **Pub. Date: Sep. 4, 2025**

(54) **LOW-VIBRATION CRYOGEN DELIVERY
SYSTEM AND METHOD**

Publication Classification

(71) Applicant: **Lake Shore Cryotronics, Inc.**,
Westerville, OH (US)

(51) **Int. Cl.**
F16L 55/04 (2006.01)
B33Y 80/00 (2015.01)
G01N 1/42 (2006.01)

(72) Inventors: **Thomas Bapu**, Lewis Center, OH (US);
Eric King, Dublin, OH (US); **Robert**
William Scites, IV, Columbus, OH
(US)

(52) **U.S. Cl.**
CPC **F16L 55/041** (2013.01); **G01N 1/42**
(2013.01); **B33Y 80/00** (2014.12)

(21) Appl. No.: **19/068,168**


(57) **ABSTRACT**

(22) Filed: **Mar. 3, 2025**

Related U.S. Application Data

(60) Provisional application No. 63/560,620, filed on Mar.
1, 2024.

A cooling system. The system includes a conduit configured
to carry a cryogenic fluid to a cooling target and a support
supporting the conduit. The support includes a first clamp
for clamping the conduit in place and a first weight for
dampening vibrations in the conduit, wherein the support
dampens nm-scale vibrations.






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D




FIG. 6E




FIG. 7A




FIG. 7B

735





FIG. 7C






FIG. 8




FIG. 9






FIG. 10





LOW-VIBRATION CRYOGEN DELIVERY SYSTEM AND METHOD

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application claims the benefit of U.S. Provisional Patent Application Ser. No. 63/560,620, filed Mar. 1, 2024 and entitled “LOW-VIBRATION CRYOGEN DELIVERY SYSTEM AND METHOD,” the priority of which is hereby claimed and the disclosure of which is incorporated herein by reference in its entirety.

FIELD OF DISCLOSURE

[0002] The subject disclosure relates to cooling systems that may be used for various purposes, including for cooling material samples to measure properties (e.g., electronic, optical, physical, etc.). The subject disclosure also relates to systems that perform vibration-sensitive measurements, particularly those that obtain measurements from a sample under cooled or cryogenic conditions.

BACKGROUND

[0003] Materials properties measured under cryogenic conditions are useful in a number of fields, such as semiconductor materials and device testing. Reasons for performing measurements under these conditions are many. For example, extremely low temperatures may be necessary for certain important device or materials properties to manifest in ways that are measurable by analytical equipment. Low temperatures can also reduce or remove stray vibrations or signals that can interfere with measurements of those properties.

[0004] More generally, cryogenic temperatures mean lower thermal noise, lower thermal energy, and reduced random motion of charge carriers. This can improve precision and observation of electronic properties, particularly in superconductive materials. For similar reasons, it can allow measurements of semiconductor properties (e.g., bandgaps) with a high level of precision. At cryogenic temperatures, quantum effects become more prominent and can be studied more readily. This facilitates study of quantum dots, quantum wells, and other nanoscale semiconductor structures. Some semiconductor experiments involve the interaction of semiconductors with other materials or external fields that can be more precisely controlled and studied at cryogenic temperatures. Still other measurements, such as radiation detection, improve under cryogenic conditions. For at least the reasons described above, cryogenic conditions can provide a more stable environment for a variety of applications. All of these and other related applications, whether expressly mentioned herein or not, are to be considered within the scope of the present disclosure.

[0005] Unfortunately, the logistics of cooling samples to cryogenic temperatures can introduce vibrations large enough to confound the very measurements the cooling is meant to facilitate. This is at least in part because most cryogenic systems cool by physically circulating a cooling liquid (cryogen) throughout the measurement (and related) systems. Fluid flow through pipes during cryogen delivery and circulation can vibrate components mechanically coupled to the pipes. Active components needed to drive the fluid through the pipes (e.g., compressors) also introduce potentially problematic vibrations. Similar issues may be

caused by circulation of suitable cryogenic liquid (e.g., liquid helium (He), liquid nitrogen (N₂), liquid hydrogen (H₂), liquid oxygen (LOX), liquid argon (Ar), liquid neon (Ne), carbon monoxide (CO), carbon dioxide (CO₂), and liquid xenon (Xe)).

[0006] These problems become even more acute when the cryogenic fluid is recycled instead of discarded after being used to cool the sample. Traditional systems simply dispose of spent cryogen (e.g., by flushing it out of the system). In that case, disposal can require little flow of spent cryogen through the measurement system. Less flow means less opportunity to cause vibrations. For the opposite reason, systems that recycle cryogen (e.g., liquid He) compound and exacerbate vibrational issues. This is because recycling requires circulating spent or used cryogen back to the cooling system from the sample to re-cool the cryogen. In this way, recycling increases, and may even double, cryogen flow through the measurement system. This necessarily increases vibrations. Moreover, additional use of pumps and conduits may be needed to send the spent cryogen back to the compressor. In some cases, new active components may even need to be added. All this introduces more vibration sources to the system. In fact, any additional circulation of cryogen in the system for any reason, whether related to recycling or not, can potentially introduce vibrations that may interfere with the measurements.

[0007] Moreover, even very small vibrations on the scale of nm can be problematic with regard to the materials measurements described above. Most vibration dampening techniques are effective at damping only larger scale vibrations that are at least tens of nm in amplitude. However, some measurements require information extraction from atomic scale features that would be “washed out” by much smaller-scale, even nm-scale, vibrations. Others will be rendered ambiguous by those same vibrations. Therefore, there is a need to develop a system that can dampen vibrations on very small size scales having very small vibrational amplitudes (e.g., nm).

SUMMARY

[0008] Disclosed herein is a cooling system. The system includes a conduit configured to carry a cryogenic fluid to a cooling target and a support supporting the conduit. The support includes a first clamp for clamping the conduit in place and a first weight for dampening vibrations in the conduit, wherein the support dampens nm-scale vibrations.

[0009] The system may be configured to decrease the amplitude of nm-scale vibrations induced by the coolant supply by greater than 99% before reaching the sample. The system may be configured to decrease an amplitude of nm-scale vibrations induced by a pump by greater than 80% before reaching a sample. The system may be configured to decrease the amplitude of nm-scale vibrations induced by the pump by greater than 92% before reaching the sample.

[0010] The support may include a second clamp for clamping the conduit in place and a second weight for dampening vibrations in the conduit. The first weight may be vibrationally isolated from the second weight. The first weight may be vibrationally isolated from a floor on which the cooling system rests. The first weight may be vibrationally connected to a floor on which the cooling system rests. The second weight may be vibrationally isolated from a floor on which the cooling system rests.

[0011] The system may include a sub-system for recycling the cryogenic fluid. The sub-system may include a vacuum pump and a line to the vacuum pump. The line to the vacuum pump may be coupled to a mass to dampen vibrations. The mass may be vibrationally de-coupled from the first weight. The mass may be vibrationally de-coupled from any other weights in the cooling system. The line to the vacuum pump may be coupled to a vibration-dampening table via a third clamp. The third clamp may be molded to the lines bellows.

[0012] At least one of the first clamp and the second clamp may be 3D printed. An inner surface of the at least one clamp may conform to an outer surface of a bellows. The bellows may be on the conduit.

[0013] Also disclosed herein is a measurement system including the cooling system. The measurement system may include a sample, wherein the sample is vibrationally isolated from the cooling system. The measurement system may include an analytical device for performing at least one of Energy Dispersive X-ray Spectroscopy (EDS or EDX), X-ray Fluorescence Spectroscopy (XRF), X-ray Photoelectron Spectroscopy (XPS or ESCA), Extended X-ray Absorption Fine Structure (EXAFS), X-ray Absorption Near Edge Structure (XANES), X-ray Emission Spectroscopy (XES), and X-ray Diffraction (XRD). The measurement system may include an analytical device for performing at least one of Auger Electron Spectroscopy (AES), Photoemission Spectroscopy (PES), Inverse Photoelectron Spectroscopy (IPES), Angle-Resolved Photoemission Spectroscopy (ARPES), X-ray Photoelectron Spectroscopy (XPS or ESCA), Electron Energy Loss Spectroscopy (EELS), and Cathodoluminescence Spectroscopy (CL).

[0014] The cooling system may include at least one of a coolant supply and a pump, wherein the at least one of a coolant supply and a pump comprises support feet. The support feet may have at least one of a pad, matt, and a coating. The at least one of a pad, matt, and a coating may include at least one of rubber, foam, and tape.

[0015] Also disclosed herein is a method of cooling a sample for testing using a cooling system. The method includes supplying a cryogenic fluid to a cooling target via a conduit, dampening nm-scale vibration in the cooling system via a support supporting the conduit. The support includes a first clamp for clamping the conduit in place and a first weight for dampening vibrations in the conduit.

[0016] The dampening nm-scale vibration in the cooling system may decrease an amplitude of nm-scale vibrations induced by a coolant supply by greater than 90% before reaching a sample. The dampening nm-scale vibration in the cooling system may decrease the amplitude of nm-scale vibrations induced by the coolant supply by greater than 99% before reaching the sample. The dampening nm-scale vibration may decrease an amplitude of nm-scale vibrations induced by a pump by greater than 80% before reaching a sample. The dampening nm-scale vibration in the cooling system may decrease the amplitude of nm-scale vibrations induced by the pump by greater than 92% before reaching the sample.

[0017] The support may include a second clamp for clamping the conduit in place and a second weight for dampening vibrations in the conduit. The testing may include at least one of Energy Dispersive X-ray Spectroscopy (EDS or EDX), X-ray Fluorescence Spectroscopy (XRF), X-ray Photoelectron Spectroscopy (XPS or ESCA), Extended X-ray Absorption Fine Structure (EXAFS), X-ray

Absorption Near Edge Structure (XANES), X-ray Emission Spectroscopy (XES), and X-ray Diffraction (XRD). The testing may include at least one of Auger Electron Spectroscopy (AES), Photoemission Spectroscopy (PES), Inverse Photoelectron Spectroscopy (IPES), Angle-Resolved Photoemission Spectroscopy (ARPES), X-ray Photoelectron Spectroscopy (XPS or ESCA), Electron Energy Loss Spectroscopy (EELS), and Cathodoluminescence Spectroscopy (CL).

BRIEF DESCRIPTION OF DRAWINGS

[0018] FIG. 1 shows an exemplary setup 100 where vibrations can be problematic.

[0019] FIG. 2 shows an alternative embodiment system 200 to setup 100, according to aspects of the present disclosure.

[0020] FIG. 3 shows an alternative embodiment system 300, according to aspects of the present disclosure.

[0021] FIG. 4 shows an alternative embodiment system 400, according to aspects of the present disclosure.

[0022] FIG. 5A shows an exemplary design for a vibration dampening foot.

[0023] FIG. 5B shows another exemplary design for a vibration dampening foot.

[0024] FIG. 6A shows an exemplary bellows design for a cooling line.

[0025] FIG. 6B is a cross-sectional drawing that illustrates of how the molded clamp fits with line B1 bellows.

[0026] FIG. 6C is a cross-sectional drawing that illustrates details of molded clamps mating structure designed to fit with line B1 bellows.

[0027] FIG. 6D is a drawing that illustrates how the molded clamp can be used in conjunction with a vibrational damping table.

[0028] FIG. 6E is a drawing that illustrates how the molded clamp can mount a cooling line to the table of FIG. 6D.

[0029] FIG. 7A shows an experimental setup 700 for testing vibration mediating designs, including those disclosed herein.

[0030] FIG. 7B shows an alternative mass dampener 735.

[0031] FIG. 7C shows another view of mass dampener 735.

[0032] FIG. 7D shows another view of mass dampener 735.

[0033] FIG. 8 is a schematic showing the essential components of setup 700 for data acquisition.

[0034] FIG. 9 shows the results of the vibration RMS measurement by component for system 700.

[0035] FIG. 10 is a schematic showing a cryostat and various directions for vibrational testing.

[0036] FIG. 11 shows the laser position in the experimental setup 700 for x or y direction vibrational measurements.

DETAILED DESCRIPTION

[0037] Several illustrative embodiments will be described in detail with the understanding that the present disclosure merely exemplifies the general inventive concepts. Embodiments encompassing the general inventive concepts may take various forms and the general inventive concepts are not intended to be limited to the specific embodiments described herein.

[0038] FIG. 1 shows an exemplary setup **100** where vibrations of the kind discussed above can be problematic. Measurement system **100** includes at least one material sample for taking cryogenic measurements. Sample **5** identified in FIG. 1 is a chamber or component of measurement system **100** that houses the actual material sample (not shown). That said, herein, the sample and its chamber will be referred to collectively as “the sample **5**.”

[0039] System **100** further includes analytics **10a** and **10b**. They are mounted proximally to sample **5** so that they may obtain measurements. Analytics **10a** and **10b** may include any known measurement, including measurements expressly mentioned herein and those that are not expressly mentioned. Examples include scanning electron microscopy, X-ray spectroscopy, and other analytical techniques (e.g., Energy Dispersive X-ray Spectroscopy (EDS or EDX), X-ray Fluorescence Spectroscopy (XRF), X-ray Photoelectron Spectroscopy (XPS or ESCA), Extended X-ray Absorption Fine Structure (EXAFS), X-ray Absorption Near Edge Structure (XANES), X-ray Emission Spectroscopy (XES), X-ray Diffraction (XRD), Auger Electron Spectroscopy (AES), Photoemission Spectroscopy (PES), Inverse Photoelectron Spectroscopy (IPES), Angle-Resolved Photoemission Spectroscopy (ARPES), X-ray Photoelectron Spectroscopy (XPS or ESCA), Electron Energy Loss Spectroscopy (EELS), and Cathodoluminescence Spectroscopy (CL)).

[0040] In addition, FIG. 1 shows a cryostat **15** included in system **100** that may manage delivery of coolant and/or cooling to sample **5** and analytics **10a** and **10b**. Cryostat **15** can maintain low temperatures for scientific experiments, materials research, superconductivity studies, and medical and other applications. Cryostat **15** can include an insulated chamber, temperature control mechanisms, and other components to manage and monitor the cryogenic environment.

[0041] Although FIG. 1 shows cryostat **15** and other components of the Coolant Delivery System as a focus of the disclosure, it is to be understood that applications of concepts disclosed herein may go beyond system **100**. The concepts may more generally apply to systems that do not actually include cryostats. For example, vibration mitigation (and other) solutions disclosed herein may be applied to probe stations, experiment inserts, optical stations, and/or electromagnets.

[0042] FIG. 1 further shows the Coolant Delivery System including a compressor **30** that may work in conjunction with cryostat **15**. Compressor **30** is primarily a circulation pump that could include a compressor and/or a vacuum pump. Compressor **30** can be any component that circulates and/or manages flow of the cryogenic fluid or refrigerant within system **100**. Compressor **30** may distribute cryogen within system **100** in conjunction with other components, such as pipes, valves, an expansion device (not shown), etc. For example, compressor **30** may provide coolant (e.g., liquid He) through hose **35a** and flexible hose **35b** to cryostat **15**. Doing so may maintain the required pressure and temperature conditions of the cryogenic fluid for a refrigeration cycle sufficient to cool sample **5**.

[0043] FIG. 1 also shows that system **100** further includes return hose **40**. Return hose **40** removes spent coolant from cryostat **15** for recycling (e.g., re-pressurization and redistribution to cryostat **15** via hoses **35a** and **35b**) through the Coolant Delivery System. As discussed in more detail below, the systems and methods disclosed herein can obtain and maintain measurement accuracy while recycling cryo-

gen, such as liquid He. Recycling cryogen is increasingly common, frequently driven by cost and environmental considerations.

[0044] It is to be understood that the Coolant Delivery System shown in FIG. 1, and system **100** more generally, is merely exemplary. It is meant to illustrate certain principles described herein without being limiting. Significant changes may be made to system **100** and still be within the scope of the present disclosure. For example, the Coolant Delivery System may include more hoses **35a** and **35b**, valves, and/or other conduits beyond those shown (implied or suggested) in FIG. 1 or other figures herein. In another example, not all systems **100** necessarily include return hose **40** or the capability to recycle cryogen. It is to be understood that still other variations are possible and within the scope of the present disclosure.

[0045] As shown in FIG. 1, the above-mentioned components (e.g., sample **5**, analytics **10a** and **10b**, and cryostat **15**, for example) may be mounted on a common base **35** that is fixed to a Table T. Although not expressly shown in FIG. 1, Table T (as well as any other table described or suggested herein) may be a “floating” pneumatic table for dampening vibrations. This is a table that incorporates pneumatic elements for height adjustment. For example, Table T may be a laboratory-type (or other) air table that uses pneumatics (compressed air) to generate mechanical motion of its top surface (not shown). In that context, Table T can allow the top surface to stay fairly level despite vibrations produced by system **100** (e.g., by the Coolant Delivery System). In this way, Table T can also dampen vibrations in system **100** to, for example, improve measurement quality as described above.

[0046] Other types of Tables T that may be used with system **100** or the other systems described herein include mechanically adjustable tables. These are tables with mechanical height-adjustment mechanisms that may use automatic (e.g., computer-driven) systems and/or hand cranks or gears to change the table height. Others use electric motors to adjust the height. Still other options include hydraulically adjustable tables. These are similar to pneumatic tables but use fluid (usually oil) to enable height adjustments. All of these table types may be used to dampen vibrations in system **100** to some degree. In addition, fixed-height tables and mobile workstations (e.g., tables on wheels) may also be used. Table T may be fitted with a vibration and/or noise-dampening system that is separate and apart from its internal construction. Table T may also rest on a vibration and/or noise-dampening system or platform. Any suitable vibration and/or noise-dampening system may be used for this purpose, including any described, suggested, or implied herein.

[0047] Multiple noise and vibration mitigation measures can be employed simultaneously in system **100**. For example, Table T may dampen vibrations from the sample **5** side of system **100**. Vibrations from the Coolant Delivery System side of system **100** may also be dampened similarly by Table T or another vibration-dampening device (not shown). Yet even with Table T and other noise/vibration dampening systems, excessive vibrations can still confound measurements taken by system **100**. For example, the multiple dampening systems described above (and more generally) may not prevent vibrations from the Coolant Delivery System from being transmitted to the sample via hoses **35a**, **35b**, and **40**. In fact, system **100** as shown in FIG. 1 has no

way to dampen such vibrations before they reach sample 5. Some vibrations (e.g., those caused by the Coolant Delivery System, and specifically compressor 15) may have extremely small amplitude (e.g., 5 nm amplitude or even 1 nm amplitude). Such small vibrations may not be effectively mitigated by Table T or the other conventional systems.

[0048] Therefore, there is a need to dampen vibrations from the Coolant Delivery System before they can be transmitted to sample 5. This need is heightened by additional vibrations caused by recycling cryogen in a closed-loop system (i.e., via hose 40, as described above). As one example, it may be advantageous for vibrations/noise in the Coolant Delivery System to be decreased independently (i.e., in vibrational isolation) of vibration dampening in other parts of system 100, etc.

[0049] Several solutions to the above-described problems are presented herein. Each solution and its related aspects may be applied separately or together in combinations. Moreover, it is to be understood that each of the solutions described below and more generally herein may be applied to system 100 of FIG. 1. This is true even if system 100 has not been redrawn in this disclosure to expressly include features or components that are described as part of the solution. More generally, it is to be understood that the discussion that follows may be directly applied to system 100 and suitable variations, whether described above or not.

[0050] One exemplary solution to the problem of vibrations being transmitted from the Coolant Delivery System to sample 5 involves multiple mass dampeners and connection points beyond those shown in FIG. 1. This alternative embodiment system 200 is shown in FIG. 2.

[0051] It is to be understood that embodiment 200 may also be applicable to system 100 above. Toward that end, components in embodiment 200 (and in other embodiments described herein, such as variations 300 and 400) that have the same names or designations of components in system 100 may take on the same form. They may take on any form discussed in the context of system 100 above. For example, the cryostat in embodiment 200 may correspond to cryostat 15, the table may correspond to Table T, and the bellow flex line B1 may correspond to flexible hose 35b and/or hose 35a. It is to be understood that sample 5 in embodiment 200 may be located in part of the cryostat.

[0052] One difference between system 100 and system 200 is that system 200 rests fewer components on Table T. In fact, Table T dampens only vibrations from the cryostat and/or sample portion of system 200, not its Coolant Delivery System portion. For example, the vacuum pump of system 200's recycling system is resting on the Ground, rather than on Table T. This allows vacuum pump to be vibrationally isolated from cryostat 15, sample 5, and other components. Cryogen reservoir and compressor can also be vibrationally isolated for the same reasons. Therefore, although fewer components in system 200 benefit from Table T's noise dampening, this allows vibrations generated by these (active) components to be vibrationally isolated from sample 5.

[0053] Although certain components are shown in FIG. 2 as being supported directly by the ground (e.g., the cryogen reservoir and compressor), it is to be understood that this is merely exemplary. These same components may be supported by another table (e.g., a different but similar vibration-dampening table as Table T of FIG. 1) to, for example, dampen vibrations. However, in system 200, for the reasons

discussed above, these components are not supported by the same table that supports the cryostat and sample 5.

[0054] Another difference is that system 200 includes an additional bellow flex line B2 to the right of the table that may, for example, correspond to return hose 40 in FIG. 1. Line B2 is part of the recycling system, i.e., the system that processes "spent" or used coolant pumped by the compressor of system 200 (located near the cryogen reservoir, though not shown in FIG. 2).

[0055] System 200 also includes two arm structures 210a and 210b that are attached to a mass. Arms 210a and 210b are fixed to bellow flex line B1 via clamps 220a and 220b, respectively. One purpose of this configuration is to hold line B1 via mass to dampen vibrations imparted to B1 before they reach sample 5. Such vibrations may be imparted to line B1, for example, by the compressor (located near the cryogen reservoir). The vibrations may also be caused by flow of coolant through B1 and other parts of system 200. One cause of vibrations, for example, is cavitation or gas in the coolant flowing through B1. In any event, fixing line B1 to the mass via clamps 220a and 220b dampens vibrations. Because clamps 220a and 220b mechanically couple line B1 to the mass, vibrational energy is dissipated by moving the mass up or down against gravity.

[0056] The mass shown in FIG. 2 can have any suitable weight for its vibration-dampening purpose. For example, masses of several g, several kg, tens of kg, and even hundreds of kg may be used. Moreover, any material with these weights may be used. For example, steel blocks may be used. Sand, concrete, iron filings, and ball bearings may be used. In certain variations, liquid containers may be filled with liquid and used as the mass. Although the mass may appear to be a monolithic component in FIG. 2, it is to be understood that this is merely exemplary. The mass could be anything having sufficient weight. For example, the mass could be heavy equipment or devices (e.g., electronic equipment, etc.).

[0057] Arms 210a and 210b can take on any suitable structure that will allow the mass to dampen vibrations in line B1. One possibility is for arms 210a and 210b to be pieces of metal (or other material with sufficient structural integrity) that mechanically couple clamps 220a and 220b with the mass or other components (not shown). Another is for arms 210a and 210b themselves to include substantial mass and, therefore, mass-dampening capabilities. In general, it is advantageous for arms 210a and 210b to be made from stiff material to prevent unnecessary vibrations. Many metals are suitable for this purpose including steel and aluminum. Certain plastics may also be useful. In addition, use of materials like aluminum increases the ability to adjust clamp positions and attach more components.

[0058] Bellow flex lines B1 and B2 can take on any suitable form. One exemplary form is shown in FIG. 6A below. However, the presentation in FIG. 6A and the corresponding discussion is not meant to be limiting. In other examples, one or more of bellow flex lines B1 and B2 may include regions (or consist entirely) of straight-walled pipe without bellows. In other variations, one or more of lines B1 and B2 may have corrugated metal bellows such that these lines can vibrate in one or more directions. For example, lines B1 and B2 may be configured with bellows (not shown) such that they can vibrate along (or in opposite direction of) the direction of cryogen fluid flow in the line (see, e.g., FIG. 6B). Lines B1 and B2 may also be configured

with bellows such that they can flex in a direction perpendicular to this flow. They may be further configured to flex in still more directions.

[0059] Clamps **220a** and **220b** may take on any suitable form, including those discussed in more detail below in the context of FIGS. **6C** and **6D**. As discussed below, an inventive clamp/hose mating system may help accomplish clamping and increase the efficacy of vibration damping. This is because the tightness with which clamps **220a** and **220b** hold their respective line **B1** and **B2** affects their efficacy of vibration damping. Increasing that tightness increases efficacy. On the other hand, loose clamps not only render the mass ineffective at damping line **B1**'s vibrations but may also introduce additional problems, such as additional unwanted vibrations resulting from movement of the loose clamps. For this reason, as described in more detail below, it was found that clamps with ridges matching the form of ridges on line **B1** (see, e.g., FIG. **6C**) are advantageous in creating a tight clamp. This shape may be formed, for example, via 3D printing (e.g., metal or plastic). In addition, clamps **220a** and **220b** can be advantageously formed of rigid, non-elastic materials such as steel.

[0060] That said, in some embodiments, it may be advantageous for clamps **220a** and **220b** to substantially clamp the entire periphery of lines **B1** or **B2** (respectively), as shown in FIG. **2**. In this configuration, lines **B1** and **B2** may be relatively smooth or retain ridges. Interior surfaces of clamps **220a** and **220b** may be relatively smooth or include ridges, corresponding (or not) to the shape of the lines. It is to be appreciated that many different configurations are possible to give clamps **220a** and **220b** a tight grip on their respective lines **B1** and **B2**. All should be considered within the context of this disclosure whether expressly represented herein or not.

[0061] As shown in FIG. **2**, system **200** includes two additional clamps **220c** and **220d**. These clamps are optionally included, e.g., in cases where system **200** includes a cryogen recycling (or disposal) system. They may be of the same type as clamps **220a** and **220b**. Clamps **220c** and **220d** dampen vibrations of their corresponding portions of lines **B1** and **B2**, respectively. In the configuration shown in FIG. **2**, the clamps do this by vibrationally coupling these lines to the mass of Table T. In other words, the clamps dampen portions of lines **B1** and **B2** closest to sample **5** using Table T, the same vibration damping mechanism used to dampen vibrations from sample **5** and cryostat. Alternatively, the clamps may couple the portions of lines **B1** and **B2** closest to Table T to different masses or vibration-dampening systems (not shown) that may not be part of Table T. In either case, clamps **220c** and **220d** maintain their respective portions of lines **B1** and **B2** as somewhat vibrationally independent of the Coolant Delivery System, thus further vibrationally isolating Table T (and components resting thereon) from that system.

[0062] FIG. **2** also shows a Mass 2, which is a mass to be used with the "Vacuum pump" that is also shown in the figure. This is an optional mass similar to that fixed to line **B1** via arms **210a** and **210b**. The purpose of Mass 2 is to dampen vibrations occurring on line **B2** between clamp **220d** and the vacuum pump. Such vibrations may be caused, for example, by the vacuum pump, a cryogenic fluid recycling system, and/or a cryogenic fluid disposal system.

[0063] FIG. **2** shows system **200** having two arms **210a** and **210b**. This is merely exemplary. Any suitable number of

arms **210** is possible. However, multiple arms might be advantageous in the sense that each provides a new vibrational node to line **B1**. Using multiple arms reduces materials and space. Each arm has a consecutive drop in transmission. This is helpful in commonly tight areas like this application.

[0064] Another exemplary system embodiment **300** is shown in FIG. **3**. System **300** is similar to system **200** but also includes of a vibration isolator ("ISOLATOR" in FIG. **3**, referred to herein as "isolator") and an additional mass for arm **210b** that is separate and apart from the mass used to dampen arm **210a**.

[0065] System **300** has all of the advantages of system **200** described above. Additionally, having isolator dampen vibrations from arm **210b** close to Table T allows for less vibration (and energy) transfer from line **B1** to Table T and the components thereon. This is because arms **210a** and **210b** are effectively independently damping different portions of line **B1**. Arm **210a** is essentially dedicated to damping vibrations from the compressor/cryogen reservoir side of line **B1**. At the same time, arm **210b** is essentially dedicated to damping vibrations on the side of **B1** that is closer to Table T. Therefore, system **300** provides additional protection for sample **5** from vibrations emanating from the compressor. Isolator can be made of elastomeric material and/or a spring-like dampener. One example is rubber. Another is resin.

[0066] Another exemplary embodiment system **400** is shown in FIG. **4**. System **400** is similar to system **300** apart from two modifications. The first is an additional vibration isolator on arm **210a** in addition to the isolator for arm **210b**. The second modification is that the mass formerly used to dampen arms **210a** and **210b** in system **200** is now used to dampen vibrations in bellow flex line **B2**.

[0067] System **400** has advantages of systems **200** and **300** described above. Additionally, having isolator dampen vibrations from arm **210a** enhances the effect discussed above, namely that both arms **210a** and **210b** receive separate damping. This provides greater damping and vibration isolation for Table T from line **B1** and the compressor. In addition, both arms **210a** and **210b** are separately damped from line **B2**. This provides for a similar vibration-isolating effect. It also conserves space and materials by locating three separate mass dampeners in the same structure, which also facilitates easy transfer and movement of this portion of system **400**.

Modifications of Systems **200**, **300**, and **400** Not Expressly Shown in FIGS. **2-4**

[0068] Several additional modifications to systems **200**, **300**, and **400** are contemplated herein. A brief description follows. It is to be understood that these modifications may be applied to any of the variations described, implied, or suggested by this disclosure.

[0069] Additional modifications include adding wheels to the components (e.g., to the components including various masses and/or the component including arms **220a** and **220b** and the three mass dampeners in system **400**). Such wheels would enhance the facility of movement of the entire system. Moreover, they would allow the repositioning of various mass dampeners (masses) as needed, increasing the flexibility of noise dampening in the system. In addition, active noise/vibration cancellation may be added to any of

the noise-dampening mechanisms herein (e.g., on Table T, clamps **220a-220d**, arms **210a** and **210b**, and lines **B1** and **B2**).

[0070] In addition, isolator padding (e.g., of the same or different type as isolator described above in the context of FIG. 3) or “feet” may be placed at the bottom of any of the components (e.g., vacuum pump, various masses including the component having arms **210a** and **210b**, the compressor/cryogen reservoir, and Table T, etc.). This can be done to, among other things, further dampen and isolate vibrations.

[0071] Feet variations are shown in FIGS. 5A and 5B below. Variations contemplated include feet made of steel or other metal (e.g., as shown in FIG. 5B), metal feet with a rubber pad, and metal feet with a pad comprising a spring mass dampener or elastomer system. Variations include feet with rigid/fixed connections or anchors to the ground. Variations include “lag bolts” that allow components a limited degree of lateral movement and vibration dampening. Variations also include various types of adhesive. Variations with no feet are also contemplated.

[0072] Active noise dampening may also be added to the active components (e.g., the compressor/cryogen reservoir). This can be done to improve vibration mitigation generally. It can also help improve dampening of the exterior (e.g., building vibrations). The active dampener could be assisted via any number of vibration sensors located throughout variations **200**, **300**, and **400**. In one example, sensors could be placed on lines **B1** and **B2** to determine the amplitude of their vibrations. In another, a vibration sensor may be added to Table T. In the latter case, the active dampener may be used to reduce a difference in vibrations of the Floor, **B1**, **B2**, or other components and Table T.

[0073] It is contemplated to extend mass dampening (passive and active, as discussed above) to other features not shown in FIGS. 1-4. For example, laboratory hard piping, braided flex lines, electrical cables, and pneumatic lines (not shown) are all vibration pathways. Each of these components can be independently isolated and mass-damped in much the same way lines **B1** and **B2** are in FIGS. 2-4.

Variations of Clamps **220a-220d**

[0074] As discussed briefly above in the context of FIG. 2, vibration mitigation effectiveness can be impacted by the clamp shape, material, and holding force on the transfer line. To maximize interlocking force and interaction with lines **B1** and **B2**, the interior shape of the clamps **220a-220d** on the external (ridged, bellowed) shape of lines **B1/B2** as shown in FIG. 6A was modeled.

[0075] More specifically, clamps were molded to mate with the ridges on the line **B1/B2** bellows shown in FIG. 6A. Such molding can interlock portions of the clamp with the ridged portions of the bellows to potentially control (and substantially decrease) vibrational motion in multiple axes/directions. Although clamps holding only to the outer diameter of the line (outer bellows) can effectively dampen transverse vibrations, such clamps were shown to have difficulty damping vibrations perpendicular to the flow of coolant in lines **B1/B2**. In contrast, clamps molded to conform to or otherwise interlock with the bellows of **B1/B2**, as described above, can dampen these transverse vibrations.

[0076] FIG. 6B is a cross-sectional drawing that illustrates how the molded clamp fits with line **B1** bellows. The direction of coolant flow is given in FIG. 6B. The 3D-printed clamp design is shown in FIGS. 6C and 6D. Clamp **220a-**

220d materials can encompass any suitable, moldable or printable via additive manufacturing materials. These include 3D printable metals and plastics.

Examples

[0077] FIG. 7A shows an experimental setup **700** for testing vibration mediating designs disclosed herein. The components shown in FIG. 7A are described below. Here we apply a testing technique designed to measure vibrations having amplitude on the nm scale to show the effectiveness of noise dampening capabilities of system **700**.

[0078] Cryocooler **710** supplies liquid helium to system **700**. In general, such coolers **710** can contribute substantially to vibrational noise. In one example embodiment, cooler **710** is an infinite helium cryocooler made by Lakeshore Cryotronics of Westerville, Ohio. However, it is to be understood that cryocooler **710** can be any suitable cryocooler that can supply any suitable cooling liquid to system **700**. For example, any of the Coolant Delivery Systems shown in FIGS. 1-4 may be represented by Cryocooler **710**. Transfer line **720** carries liquid coolant from cryocooler **710** through the system **700**. As shown in FIG. 7A, transfer line **720** may comprise flexible vacuum hose systems used cryogenic measurements. In particular, it may represent bellow flex lines **B1** and **B2** shown in FIG. 4. It may comprise stainless steel and or other components described herein.

[0079] As shown in FIG. 7A, system **700** may include mass dampener **730**. Mass dampener **730** may include any combination of Masses 1-7 shown in FIGS. 1-4, or similar masses. FIG. 7A shows mass dampener **730** as weights configured within a vessel or bucket. This is a common configuration. It may be used to hold several mass dampeners and/or mass isolators such as those discussed above in the context of FIGS. 1-4. The masses may be held in place by any suitable means, including sand or adhesive material. That said, it should be understood that alternative configurations are possible.

[0080] For example, FIGS. 7B-7D show an alternative to mass dampener **730** in the form of mass dampener **735**. Dampener **735** includes a weight (Mass 7) that may be the same as the weight in dampener **730**. It further includes arms **730a** and **730b**, as well as clamps **220a-220d**. The main difference is that dampener **735** also includes housing **736** (including housing components **736a-736e**). Housing **736** may serve to shield the interior components of dampener **735** from dust and/or contamination. Housing **736** may also have a noise dampening effect. It is to be understood that housing **736** may be applied to any of the variations described herein. Moreover, it is to be further understood that the design, shape, and form of housing **736** shown in FIGS. 7B-7D is merely exemplary. Modifications of this design, as well as other housing designs, are possible and within the scope of the present disclosure.

[0081] Turning back to FIG. 7A, the figure also shows various other aspects of system **700** including table clamp **740**. Table clamp **740** is similar to the cable clamps discussed above, most notably table clamp **220c** of FIG. 2 (shown in the figure as clamping flex line **B1** to the table). FIG. 700 shows table clamp **760** next to the cryostat **750** for mounting to table **795**. It also shows return line **770**, which is part of the **B1/B2** line. In addition it has a return mass dampener **780** similar to the mass described above (i.e., Mass 1-7). FIG. 7A also shows circulation pump **790**. Pump

790 circulates coolant fluid in the system **700** through the transfer line **720**. Circulation pump **790** can be, for example, any of the pumps shown in FIGS. 1-4 including the “vacuum pump.”

Data Acquisition

[0082] As shown in FIG. 7A, vibrations were measured using a laser vibrometer setup including laser vibrometer **791** and vibrometer controller **792**. Vibrometer **791** was a Polytec Vibrometer. Cryostat **750** was a Lake Shore ST-500 series microscopy cryostat. During data acquisition, cryostat **750** was mounted on floating optical table **795**. Cryocooler **710** was mounted on top of a rolling table. Vibration amplitude measurements from vibrometer **791** were collected and analyzed by a Lake Shore M81 Synchronous Source Measure System **793** in communication with computer **794**. However, it is to be understood that other measurement systems and components known in the art may be used to acquire similar data under similar conditions.

[0083] FIG. 8 is a schematic showing the essential components of setup **700** for data acquisition. The two major vibration sources are the cryocooler **710** and the return pump **790**. Vibration data was acquired with vibrometer **791** set to a gain of 0.5 $\mu\text{m}/\text{V}$. The data streaming rate was 1000 Hz with 0.06 power line cycles (NPLC) for 120 seconds.

Data Processing

[0084] The vibration data was processed as follows. The data was broken into 24 segments of five second duration. Fast Fourier Transform (FFT) analysis was then performed on each data segment. A Hanning window was used to average and smooth the data. More specifically, the Hanning window averaged all 24 FFTs together to reduce the noise. This analysis produced noise density ($\text{m}/\sqrt{\text{Hz}}$) vs frequency with a bandwidth of 0.2 Hz. This noise density is independent of bandwidth. This is in contrast with other measurable quantities (e.g., amplitude (m)) that are bandwidth dependent.

[0085] Vibration root mean square (RMS) amplitude was calculated as follows. The RMS amplitude was taken as the square root of the integral of the squared noise density vs frequency. The integral was evaluated from high to low frequency, specifically from 500 Hz down to a particular lower frequency f . Integrating from high to low frequency can decrease the contribution of drift.

Results

[0086] System **700** was used to measure the vibration RMS amplitude at the location of each of the components shown in FIG. 8. In particular, RMS was measured for the components likely to be the source of most, if not all, of the significant vibrations. These components are cryocooler **710** and pump **790**. Such measurements established vibration baselines. Propagation of vibrations made by these components through system **700** was measured at seven other locations. These were the locations of the following components: arm **730a**, arm **730b**, transfer line **720**, cryostat **750**, table **795**, return line **770**, return mass dampener **780**, and circulation pump **790**. These measurements, taken together, give an overview of how vibrations travel within system **700**.

[0087] FIG. 9 shows the results of the vibration RMS measurement by component. The individual numerical results are shown below in Table 1 in terms of vibration in the lateral (x) direction.

TABLE 1

Measured RMS Vibrational Amplitude in Setup 700 by Component		
Element	Name	Measured Vibrational RMS (nm)
710	Cryocooler	1712
730a	Arm 1	505
730b	Arm 2	354
740	Transfer Line	166
750	Cryostat	4.8
795	Table	2
770	Cryo Line Return	159
780	Return Mass Dampener	648
790	Pump	2093

[0088] In particular, FIG. 9 confirms the highest measured vibration amplitudes, 1712 nm and 2093 nm vibration RMS, are measured at the locations of cooler **710** and pump **790**, respectively. FIG. 9 further shows how vibration amplitude decreases systematically as one travels along the cooling lines from either end (i.e., from the cooler **710** end or from the pump **790** end) to the interior of system **700**. This is likely why the lowest vibration amplitudes (4.5 nm and 2 nm) are measured at and near the relatively central location of the cryostat **750**. This low measured vibration amplitude at the cryostat **750** likely results from its relatively central location and the collective work of the noise/vibration dampening mechanisms of system **700** discussed above. The decrease in relative RMS amplitude as the vibration dampening mechanisms are changed (as described above) provides a measure of the effectiveness of vibration dampening.

[0089] FIG. 9 shows that arms **730a** and **730b**, significantly dampen vibrations as they travel through the system. For example, the vibration amplitude produced by cryocooler **710** has already decreased by 90% when measured at transfer line **720**. This is after the vibrations have passed through arms **730a** and **730b** and been mitigated by their mass dampening effects, as described above. However, it is before the vibrations have been dampened by pneumatic table **795**. In fact, the vibration amplitude is essentially zero to within experimental error when measured on experimental table **795** (e.g., vibrations measured at cryostat **750** mounted on table **795** or on table **795** itself). This represents more than a 99% decrease in amplitude of vibrations as they travel from cryocooler **710**, through the noise dampening mechanisms, to sample **5** in cryostat **750**.

[0090] FIG. 9 shows a similar result with respect to vibrations created by pump **790**. More specifically, the measured RMS vibration amplitude at the pump **790** vibration source (i.e., 2093 nm) decreases by 92% before it reaches the cryo line return **770**. This shows the noise dampening effect of return mass dampener **780**. As pointed out above, any vibrations from pump **790** have been essentially dampened to zero amplitude to within experimental error before they reach cryostat **750**. Together these results support the conclusions that the mass dampening setup in system **700** (e.g., mass dampening through arms **730a** and **730b** as well as dampener **780**) can decrease more than 90% of the amplitude of the nm-scale vibrations prior to pneumatic mitigation by table **795**.

Variations in Noise Dampening Setup

[0091] In addition to the above-described setup, several alterations of system **700** were independently tested for vibration dampening. Table 2 below summarizes the results. We note here that a variation in the setup shown in FIG. 7A was used to test vibrational amplitude in both x and y directions as defined with respect to cryostat **750** in FIG. 10. As shown in FIG. 10, the cryostat **750** includes a window **752** that allows laser light to illuminate sample **5**. Window **752** also allows reflected laser light to be collected in x, y, and z directions. FIG. 11 shows the laser **791** position in the actual experimental setup. Measurements of z-direction vibrations are also possible with modifications to the setup shown in FIG. 11.

TABLE 2

Effect of multiple arms 730 on mass dampening applied between cryocooler 710 and cryostat 750	
Setup Components	Measured Vibrational RMS (nm)
One arm (730a) only	8.485
Two arms (730a and 730b)	4.822

[0092] As shown in Table 2, one test varied the number of arms **730a** and **730b** in the dampening system between cryocooler **710** and cryostat **750**. It was found that adding a second arm to the dampening, as shown in FIG. 7A, had a significant effect on vibration dampening. In fact adding a second arm without adding additional weight decreased the noise amplitude by around 43%.

[0093] Having established that adding more than one arm (**730**) to the mass dampening system of the cryocooler **710** substantially decreases vibrations, a number of two arm variations were tested. These changed other aspects, such as the feet **510a**. The results of the most consequential variations are shown below in Table 3.

TABLE 3

Effect of varying feet 510a on noise dampening	
Variation	Measured Vibrational RMS (nm)
Feet 510a omitted from system 700	15.001
Metal feet 510a only	4.926
Metal feet 510a on a rubber mat	7.783
Metal Feet 510a, each with a rubber pad	4.130
Conically shaped metal feet 510a	6.165
Floor-anchored, conically shaped metal feet 510a	5.440

[0094] As shown in Table 3, the composition of metal feet in system **700** (e.g., foot **510a** on cryocooler **510** shown in FIG. 5B) had an impact on vibration amplitude of hundreds of percent. Metal feet **510a** were found to be generally effective noise dampeners. Including feet of some kind was far better than having no feet at all. Table 3 also shows that noise dampening effectiveness of the metal feet generally does not improve when those feet were placed on rubber matting material. Results also show that certain variations in the shape of the feet seem to make a lesser contribution to noise mitigation. However, they also show substantially increased noise dampening when rubber pads are included.

[0095] Also tested was how the surface of the laboratory floor contacted by the feet (e.g., feet **510a**), referred to herein as the “feet landing surface,” affects noise dampening. The alternative surfaces to bare metal/floor contact included 1) “A tape” (also known as nano tape or gecko tape, is a double-sided, commercially available and reusable tape that can stick to many surfaces without the use of screws or anchors), 2) thin red” tape (another commercially available double-sided, pressure-sensitive adhesive tape), and 3) VHB “Foam” tape (a commercially available tape in the form of a white foam).

TABLE 4

Effect on noise dampening of varying the feet landing surface	
Variation	Measured Vibrational RMS (nm)
Bare floor (metal feet 510a touching bare floor)	4.822
Metal feet 510a touching A tape	4.679
Metal feet 510a touching thin red tape	4.321
Metal feet 510a touching foam tape	4.015

[0096] The results in Table 4 suggest that the surface contacted by feet **510a** does, in fact, have an impact on vibration damping. In particular, the foam tape seemed to perform best as the contact surface. That said, each of the three types of tape (A, thin red, and foam) offer some form of vibration damping improvement over bare metal.

[0097] The effect on vibration damping of other variables in system **700** was also explored. For example, clamping torque was varied from 6-36 in-lbs. The weight of the bucket holding mass dampening arms **730a** and **730b** was also varied from 60-136 pounds. Surprisingly, the variables showing the most impact on noise dampening were the number of mass damping arms (Table 2), the feet composition (Table 3), and the feet landing surface (Table 4).

[0098] While various inventive aspects, concepts, and features of the inventions have been described and illustrated herein as embodied in certain exemplary embodiments, these various aspects, concepts, and features may be used in many alternative embodiments, either individually or in various combinations and sub-combinations thereof. Unless expressly excluded herein all such combinations and sub-combinations are intended to be within the scope of the present inventions. Still further, while various alternative embodiments as to the various aspects, concepts and features of the inventions—such as alternative materials, structures, configurations, methods, circuits, devices and components, software, hardware, control logic, alternatives as to form, fit and function, and so on—may be described herein, such descriptions are not intended to be a complete or exhaustive list of available alternative embodiments, whether presently known or later developed. Those skilled in the art may readily adopt one or more of the inventive aspects, concepts or features into additional embodiments and uses within the scope of the present inventions even if such embodiments are not expressly disclosed herein. Additionally, even though some features, concepts or aspects of the inventions may be described herein as being a preferred arrangement or method, such description is not intended to suggest that such feature is required or necessary unless expressly so stated. Still further, exemplary or representative values and ranges may be included to assist in understanding the present disclosure, however, such values and ranges are

not to be construed in a limiting sense and are intended to be critical values or ranges only if so expressly stated. Still further, exemplary or representative values and ranges may be included to assist in understanding the present disclosure, however, such values and ranges are not to be construed in a limiting sense and are intended to be critical values or ranges only if so expressly stated. Parameters identified as “approximate” or “about” a specified value are intended to include both the specified value and values within 10% of the specified value, unless expressly stated otherwise. Further, it is to be understood that the drawings accompanying the present application may, but need not, be to scale, and therefore may be understood as teaching various ratios and proportions evident in the drawings. Moreover, while various aspects, features and concepts may be expressly identified herein as being inventive or forming part of an invention, such identification is not intended to be exclusive, but rather there may be inventive aspects, concepts and features that are fully described herein without being expressly identified as such or as part of a specific invention, the inventions instead being set forth in the appended claims. Descriptions of exemplary methods or processes are not limited to inclusion of all steps as being required in all cases, nor is the order that the steps are presented to be construed as required or necessary unless expressly so stated.

We claim:

1. A cooling system comprising:
 - a conduit configured to carry a cryogenic fluid to a cooling target;
 - a support supporting the conduit, wherein the support comprises:
 - a first clamp for clamping the conduit in place; and
 - a first weight for dampening vibrations in the conduit,
 wherein the support dampens nm-scale vibrations.
2. The cooling system of claim 1, wherein the system is configured to decrease an amplitude of nm-scale vibrations induced by a coolant supply by greater than 90% before reaching a sample.
3. The cooling system of claim 2, wherein the system is configured to decrease the amplitude of nm-scale vibrations induced by the coolant supply by greater than 99% before reaching the sample.
4. The cooling system of claim 1, wherein the system is configured to decrease an amplitude of nm-scale vibrations induced by a pump by greater than 80% before reaching a sample.
5. The cooling system of claim 4, wherein the system is configured to decrease the amplitude of nm-scale vibrations induced by the pump by greater than 92% before reaching the sample.

6. The cooling system of claim 1, wherein the support further comprises:

- a second clamp for clamping the conduit in place; and
- a second weight for dampening vibrations in the conduit.

7. The cooling system of claim 6, wherein the first weight is vibrationally isolated from the second weight.

8. The cooling system of claim 1, wherein the first weight is vibrationally isolated from a floor on which the cooling system rests.

9. The cooling system of claim 1, wherein the first weight is vibrationally connected to a floor on which the cooling system rests.

10. The cooling system of claim 6, wherein the second weight is vibrationally isolated from a floor on which the cooling system rests.

11. The cooling system of claim 1, further comprising a sub-system for recycling the cryogenic fluid.

12. The cooling system of claim 11, wherein the sub-system comprises a vacuum pump and a line to the vacuum pump.

13. The cooling system of claim 12, wherein the line to the vacuum pump is coupled to a mass to dampen vibrations.

14. The cooling system of claim 13, wherein the mass is vibrationally de-coupled from the first weight.

15. The cooling system of claim 14, wherein the mass is vibrationally de-coupled from any other weights in the cooling system.

16. The cooling system of claim 1, wherein the first clamp is 3D printed.

17. A measurement system comprising the cooling system of claim 1.

18. The measurement system of claim 17 comprising an analytical device for performing at least one of Energy Dispersive X-ray Spectroscopy (EDS or EDX), X-ray Fluorescence Spectroscopy (XRF), X-ray Photoelectron Spectroscopy (XPS or ESCA), Extended X-ray Absorption Fine Structure (EXAFS), X-ray Absorption Near Edge Structure (XANES), X-ray Emission Spectroscopy (XES), and X-ray Diffraction (XRD).

19. The measurement system of claim 17 comprising an analytical device for performing at least one of Auger Electron Spectroscopy (AES), Photoemission Spectroscopy (PES), Inverse Photoelectron Spectroscopy (IPES), Angle-Resolved Photoemission Spectroscopy (ARPES), X-ray Photoelectron Spectroscopy (XPS or ESCA), Electron Energy Loss Spectroscopy (EELS), and Cathodoluminescence Spectroscopy (CL).

20. A method of cooling a sample for testing using a cooling system, the method comprising:

- supplying a cryogenic fluid to a cooling target via a conduit;

- dampening nm-scale vibration in the cooling system via a support supporting the conduit, the support comprising:
 - a clamp for clamping the conduit in place; and
 - a weight for dampening vibrations in the conduit.

* * * * *