

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250277590

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Nelson; Nathan Ernell

ADJUSTMENT BRACKET FOR A COOKING APPLIANCE

Abstract

An adjustment bracket for a cooking appliance defining a vertical direction, a lateral direction, and a transverse direction. The cooking appliance may include a front frame. The front frame may include a frame sill and a side member. The side member may extend along the vertical direction from the frame sill. The frame sill and the side member may define a bottom corner. The adjustment bracket may include a main body extended between a top and a bottom along the vertical direction, an inner edge and an outer edge along the lateral direction, and a front side and a rear side along the transverse direction. The adjustment bracket may also include a second body disposed at the top and the inner edge of the main body. The second body may be wrapped around a portion of the bottom corner to protect the bottom corner.

Inventors: Nelson; Nathan Ernell (Louisville, KY)

Applicant: Haier US Appliance Solutions, Inc. (Wilmington, DE)

Family ID: 96881031

Appl. No.: 18/591694

Filed: February 29, 2024

Publication Classification

Int. Cl.: F24C15/08 (20060101); F24C15/00 (20060101)

U.S. Cl.:

CPC F24C15/086 (20130101); F24C15/005 (20130101)

Background/Summary

FIELD OF THE DISCLOSURE

[0001] The present subject matter relates generally to a cooking appliance and more particularly to an adjustment bracket for a cooking appliance.

BACKGROUND OF THE DISCLOSURE

[0002] Conventional residential and commercial oven appliances generally include a cabinet that includes a cooking chamber for receipt of food items for cooking. Multiple heating elements are positioned within the cooking chamber to provide heat to food items located therein. In addition, conventional oven appliances include a cooktop positioned on a top of the appliance that includes one or more heating elements, such as electric heaters, gas burners, or induction heating elements. Cooking appliances that include both an oven and a cooktop are commonly referred to as “ranges.”

[0003] Some cooking appliances can include a frame or a chassis that defines the cooking chamber or a drawer recess of the cooking appliance. The frame or chassis can be enameled, for instance, to increase durability or provide a preferred finish to the frame. However, challenges related to the enameled coating a cooking appliance frame can exist. For example, during shipping or handling of the cooking appliance, the portions of the enameled coating may be susceptible to chipping.

[0004] Accordingly, a cooking appliance with features for obviating one or more of the aforementioned drawbacks would be useful.

BRIEF DESCRIPTION OF THE DISCLOSURE

[0005] Aspects and advantages of the invention will be set forth in part in the following description, or may be obvious from the description, or may be learned through practice of the invention.

[0006] In one exemplary aspect of the present disclosure, a cooking appliance is provided. The cooking appliance may define a vertical direction, a lateral direction, and a transverse direction. The cooking appliance may include a cabinet defining a cooking chamber and a drawer recess positioned below the cooking chamber. The cooking appliance may also include a front frame defining a chamber opening for the cooking chamber and a drawer opening for the drawer recess. The front frame may include a frame sill and a side member. The frame sill may extend between a first side and a second side along the lateral direction. The side member may extend along the vertical direction from the first side of the frame sill to form a bottom corner of the front frame. The cooking appliance may further include an adjustment bracket attached to the bottom corner of the front frame. The adjustment bracket may include a main body extended between a top and a bottom along the vertical direction, an inner edge and an outer edge along the lateral direction, and a front side and a rear side along the transverse direction. The adjustment bracket may also include a second body disposed at the top and the inner edge of the main body.

[0007] In another exemplary aspect of the present disclosure, an adjustment bracket for a cooking appliance is provided. The cooking appliance may define a vertical direction, a lateral direction, and a transverse direction. The cooking appliance may include a front frame. The front frame of the cooking appliance may include a frame sill and a side member. The side member may extend along the vertical direction from the frame sill. The frame sill and the side member may define a bottom corner. The adjustment bracket may include a main body extended between a top and a bottom along the vertical direction, an inner edge and an outer edge along the lateral direction, and a front side and a rear side along the transverse direction. The adjustment bracket may also include a second body disposed at the top and the inner edge of the main body. The second body may be wrapped around a portion of the bottom corner to protect the bottom corner.

[0008] These and other features, aspects and advantages of the present invention will become better understood with reference to the following description and appended claims. The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and, together with the description, serve to explain the principles of the invention.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] A full and enabling disclosure of the present invention, including the best mode thereof, directed to one of ordinary skill in the art, is set forth in the specification, which makes reference to the appended figures.

[0010] FIG. 1 provides a front perspective view of a cooking appliance according to one or more exemplary embodiments of the present subject matter.

[0011] FIG. 2 provides a side cross-sectional view of the exemplary cooking appliance of FIG. 1 according to one or more exemplary embodiments of the present subject matter.

[0012] FIG. 3 provides a perspective view of a bottom portion of the exemplary cooking appliance of FIG. 1 with a drawer face and a portion of a first side wall removed.

[0013] FIG. 4 provides a close-up perspective view of a front corner of a housing assembly of the exemplary cooking appliance of FIG. 1.

[0014] FIG. 5 provides a close-up perspective view of a front corner of a housing assembly of the exemplary cooking appliance of FIG. 1 with a front adjustment bracket and a front leveling leg removed.

[0015] FIG. 6 provides a perspective view of a front adjustment bracket according to an exemplary embodiment of the present disclosure.

[0016] Repeat use of reference characters in the present specification and drawings is intended to represent the same or analogous features or elements of the present invention.

DETAILED DESCRIPTION

[0017] Reference now will be made in detail to embodiments of the invention, one or more examples of which are illustrated in the drawings. Each example is provided by way of explanation of the invention, not limitation of the invention. In fact, it will be apparent to those skilled in the art that various modifications and variations can be made in the present invention without departing from the scope of the invention. For instance, features illustrated or described as part of one embodiment can be used with another embodiment to yield a still further embodiment. Thus, it is intended that the present invention covers such modifications and variations as come within the scope of the appended claims and their equivalents.

[0018] As used herein, the terms “first,” “second,” and “third” may be used interchangeably to distinguish one component from another and are not intended to signify location or importance of the individual components. The terms “includes” and “including” are intended to be inclusive in a manner similar to the term “comprising.” Similarly, the term “or” is generally intended to be inclusive (i.e., “A or B” is intended to mean “A or B or both”). The term “at least one of” in the context of, e.g., “at least one of A, B, and C” refers to only A, only B, only C, or any combination of A, B, and C. In addition, here and throughout the specification and claims, range limitations may be combined or interchanged. Such ranges are identified and include all the sub-ranges contained therein unless context or language indicates otherwise. For example, all ranges disclosed herein are inclusive of the endpoints, and the endpoints are independently combinable with each other. The singular forms “a,” “an,” and “the” include plural references unless the context clearly dictates otherwise.

[0019] Approximating language, as used herein throughout the specification and claims, may be applied to modify any quantitative representation that could permissibly vary without resulting in a change in the basic function to which it is related. Accordingly, a value modified by a term or terms, such as “generally,” “about,” “approximately,” and “substantially,” are not to be limited to the precise value specified. In at least some instances, the approximating language may correspond to the precision of an instrument for measuring the value, or the precision of the methods or machines for constructing or manufacturing the components or systems. For example, the

approximating language may refer to being within a 10 percent margin, i.e., including values within ten percent greater or less than the stated value. In this regard, for example, when used in the context of an angle or direction, such terms include within ten degrees greater or less than the stated angle or direction, e.g., “generally vertical” includes forming an angle of up to ten degrees in any direction, e.g., clockwise or counterclockwise, with the vertical direction V.

[0020] The word “exemplary” is used herein to mean “serving as an example, instance, or illustration.” In addition, references to “an embodiment” or “one embodiment” does not necessarily refer to the same embodiment, although it may. Any implementation described herein as “exemplary” or “an embodiment” is not necessarily to be construed as preferred or advantageous over other implementations.

[0021] Referring now to the figures, FIG. 1 provides a perspective view of a range appliance **100** including a cooktop **102** and FIG. 2 provides a side cut-away view of the range appliance **100**. Range appliance **100** is provided by way of example only and is not intended to limit the present subject matter to the arrangement shown in FIGS. 1 and 2. Thus, the present subject matter may be used with other range appliance **100** or cooktop **102** configurations, e.g., double oven range appliances, gas cooktops, etc. As illustrated, range appliance **100** generally defines a vertical direction V, a lateral direction L, and a transverse direction T, each of which is mutually perpendicular, such that an orthogonal coordinate system is generally defined.

[0022] The range appliance **100** may include a cabinet **101**. The cabinet **101** may extend between a top **103** and a bottom **105** along the vertical direction V. The cabinet **101** may extend, between a left side **107** and a right side **109** along the lateral direction, and between a front **111** and a rear **113** along the transverse direction T. The cabinet **101** may include a first side wall **115** and a second side wall **117**. The first side wall **115** may be positioned at the left side **107** of the cabinet **101**. The second side wall **117** may be positioned at the right side **109** of the cabinet **101**. A cooking surface **104** of cooktop **102** includes a plurality of heating elements **106**. For the embodiment depicted, the cooktop **102** includes five heating elements **106** spaced along cooking surface **104**. Moreover, for the embodiment depicted, the heating elements **106** are generally electric heating elements and are positioned at, e.g., on or proximate to, the cooking surface **104**.

[0023] However, in other embodiments, the cooktop **102** may include any other suitable shape, configuration, or number of heating elements **106**. For example, the cooktop **102** may include one or more heating elements **106** spaced along the cooking surface **104**, such as three or more heating elements **106** spaced along the cooking surface **104**, such as six or more heating elements **106** spaced along the cooking surface **104**. As another example, in certain exemplary embodiments, the cooktop **102** may be a gas-powered cooktop. For instance, in such embodiments, the cooktop **102** may include one or more gas burners mounted below or through the cooking surface **104**.

[0024] As shown in FIG. 1, a cooking utensil **108**, such as a pot, pan, or the like, may be placed on a heating element **106** to heat the cooking utensil **108** and cook or heat food items placed in cooking utensil **108**. Range appliance **100** also includes a door **120** that permits access to a cooking chamber **164** of range appliance **100**, e.g., for cooking or baking of food items therein. A control panel **122** having controls **124** permits a user to make selections for cooking of food items. Although shown on a backsplash or back panel **126** of range appliance **100**, control panel **122** may be positioned in any suitable location. Controls **124** may include buttons, knobs, and the like, as well as combinations thereof, or controls **124** may be implemented on a remote user interface device such as a smartphone, as described below. As an example, a user may manipulate one or more controls **124** to select a temperature or a heat or power output for each heating element **106** and the cooking chamber **164**. The selected temperature or heat output of heating element **106** affects the heat transferred to cooking utensil **108** placed on heating element **106**.

[0025] In some embodiments, the range appliance **100** includes a control system **150** for controlling one or more of the plurality of heating elements **106** and the cooking chamber **164**. Specifically, the control system **150** may include a controller **152** operably connected to the control

panel **122** and controls **124**. The controller **152** may be operably connected to each of the plurality of heating elements **106** for controlling a power supply to each of the plurality of heating elements **106** in response to one or more user inputs received through the control panel **122** and controls **124**. [0026] Referring now to FIG. **3**, a perspective view of a bottom portion of the range appliance **100** is provided. The bottom portion of the range appliance **100** may define a drawer recess **160** for receiving a drawer assembly **162**. In some embodiments, the range appliance **100** includes a housing assembly **200**. The housing assembly **200** may generally be provided as a chassis or a supporting frame for the cabinet **101**. For instance, portions of the cabinet **101**, such as a first side wall **115** or the second side wall **117** may be attached to or mounted to (e.g., via welds, mechanical fasteners, etc.) the housing assembly **200** to form the cabinet **101**. In addition, the housing assembly **200** may generally include a rear frame **202**, a front frame **204**, a first base rail **206**, and a second base rail **208**. The front frame **204** and the rear frame **202** may be spaced apart along the transverse direction T. For instance, the front frame **204** and the rear frame **202** may be positioned at the front **111** and the rear **113** of the range appliance **100**, respectively. In some embodiments, the front frame **204** and rear frame **202** define the front **111** or the rear **113** of the cabinet **101**, respectively. The front frame **204** may extend between the top **103** (e.g., the top of the cooking chamber) and the bottom **105** of the range appliance **100**.

[0027] In some embodiments, the front frame **204** includes a frame sill **210**, a first side member **212**, and a second side member **214**. The frame sill **210** may be positioned at the bottom of the front frame **204**. In addition, the frame sill **210** may be positioned at or proximate the front **111** of the range appliance **100**. The frame sill **210** may generally extend along the lateral direction L between the first side member **212** and the second side member **214**. The first side member **212** may be extended along the vertical direction V from the frame sill **210** at the left side **107** of the range appliance **100**. The second side member **214** may be extended along the vertical direction V from the frame sill **210** at the right side **109** of the range appliance **100**. In some embodiments, the front frame **204**, and the components thereof (e.g., the first side member **212**, the second side member **214**, or the frame sill **210**) may include an enameled coating. For instance, a substantially vitreous or glassy inorganic coating may be bonded to the front frame **204** (e.g., by thermal fusion) to provide durability or a glossy appearance to the front frame **204**.

[0028] In some embodiments, the front frame **204** may define the opening for the drawer recess **160**. For instance, the frame sill **210**, the first side member **212**, and the second side member **214** may together define the opening for the drawer recess **160**. In such embodiments, the frame sill **210** is positioned at the bottom of the front frame **204**. In addition, the frame sill **210** may be positioned at or proximate the front **111** of the range appliance **100**. The frame sill **210** may generally extend along the lateral direction L between the first side member **212** and the second side member **214**. The first side member **212** may be extended along the vertical direction V from the frame sill **210** at the left side **107** of the range appliance **100**. The second side member **214** may be extended along the vertical direction V from the frame sill **210** at the right side **109** of the range appliance **100**.

[0029] In some embodiments, a height adjustment assembly **230** may be attached to the housing assembly **200**. The height adjustment assembly **230** may be configured to adjust a cooktop height of the range appliance **100**. For instance, the height adjustment assembly **230** may be capable of increasing or decreasing the total distance between the cooktop **102** and a predetermined ground surface that the range appliance **100** may be positioned on. In some embodiments, the height adjustment assembly **230** includes a first front leveling leg **232**, a first rear leveling leg **234**, a second front leveling leg **236**, a second rear leveling leg **238**. As will be appreciated in more detail below, one or more (e.g., each) of the first front leveling leg **232**, the first rear leveling leg **234**, the second front leveling leg **236**, or the second rear leveling leg **238** may be movably mounted to the housing assembly **200** to adjust the cooktop height of the range appliance **100**.

[0030] In some embodiments, the drawer recess **160** may be provided underneath a cooking

chamber **164**, for example. A user may store various items (e.g., cooking utensils **108** or the like) within drawer recess **160**. Additionally or alternatively, drawer recess **160** may be used as a temporary storage area for food (e.g., as a warming zone or area). According to some embodiments, drawer recess **160** may be an additional cooking or baking zone, in which food items may be cooked or baked. It should be noted that drawer recess **160** may be used for any suitable purposes, and the disclosure is not limited to those examples given herein. The opening to drawer recess **160** may be defined in the lateral direction L and vertical direction V. In detail, drawer recess **160** may be configured such that drawer assembly **162** is withdrawn in the transverse direction T from drawer recess **160**.

[0031] Drawer assembly **162** may include a main panel **166**, a rear panel **168**, a first side panel **170**, and a second side panel **172**. Accordingly, main panel **166**, rear panel **168**, first side panel **170**, and second side panel **172** may form a drawer body **174** having a cuboid shape into which various items may be placed. It should be noted that drawer body **174** may be formed from a single piece and bent into the cuboid shape according to certain embodiments. Drawer assembly **162** may include a front panel or door face **176** including a handle **178** (see e.g., FIG. 1) used to withdraw and insert drawer assembly **162** into drawer recess **160**. When assembled, first side panel **170** and second side panel **172** may be defined in the transverse direction T and the vertical direction V. Rear panel **168** may be defined in the lateral direction L and the vertical direction V. Main panel **166** may be defined in the lateral direction L and the transverse direction T. A rear portion of each of first side panel **170** and second side panel **172** may extend further in the transverse direction T than a position of rear panel **168**. In other words, each of first side panel **170** and second side panel **172** may define an overhang or extension in the transverse direction T (e.g., behind rear panel **168** in the transverse direction T).

[0032] Referring now specifically to FIGS. 4 and 5, close-up perspective views of a bottom portion of the right side **109** of the range appliance **100** are provided. As should be appreciated, for the purposes of clarity and brevity, only the bottom portion of the right side **109** of the range appliance **100**, and components positioned at or proximate to the bottom portion of the right side **109** of range appliance **100** are illustrated and described in more detail below. One of ordinary skill in the art would recognize that the structure, configuration, or function of the components illustrated and described below may be mirrored or identical to the structure, configuration, or function of components positioned at or proximate to the first side of the range appliance **100**. For instance, the structure, function, or configuration of the second base rail **208** described below may mirror or may be identical to the structure, function, or configuration of the first base rail **206**. For example, the second base rail **208** may include a top surface **251** and a bottom surface **253** spaced apart along the vertical direction V. The first base rail **206** may include a top surface and a bottom surface that mirror or are identical to the top surface **251** and the bottom surface **253** of the second base rail **208**.

[0033] In some embodiments, the frame sill **210** includes a first portion **240**, a second portion **242**, and a jog **244**. The first portion **240** may be the main body of the frame sill **210**. For instance, the first portion **240** may extend along the lateral direction L across the majority of housing assembly **200**. The jog **244** may be positioned between the first portion **240** and the second portion **242**. The jog **244** may define an offset or displacement of the bottom edge of the frame sill **210**. For instance, the jog **244** may raise or lift the second portion **242** along the vertical direction V by a predetermined amount **248**. Particularly, the jog **244** may raise or lift a bottom edge **246** of the frame sill **210** by a predetermined amount **248**. As will be appreciated, this offset, or displacement, may be utilized to accommodate the second base rail **208**. In particular, the jog **244** may allow the second base rail **208** to sit within the housing assembly **200**. As illustrated, in FIG. 5, the second side member **214** may be extended along the vertical direction V from the second portion **242** of the frame sill **210**. The second portion **242** of the frame sill **210** and the second side member **214** may together define a bottom corner **250** of the front frame **204**.

[0034] In some embodiments, when the second base rail **208** is attached to the second portion **242** of the frame sill **210**, the second base rail **208** may be positioned within the housing assembly **200** (e.g., due to the vertical positioning of the second portion **242** of the frame sill **210**). That is, the bottom surface **253** of the second base rail **208** may be, at least in part, positioned at or vertically above, the bottom edge **246** of the second portion **242** of the frame sill **210**. In this regard, the second base rail **208** may be elevated above the bottom most point of the frame sill **210** (e.g., the bottom edge **246** of the first portion **240** of the frame sill **210**) such that the second base rail **208** is positioned “within” the housing assembly **200**.

[0035] As briefly mentioned above, the height adjustment assembly **230** may include a second front leveling leg **236** and a second rear leveling leg **238**. The second front leveling leg **236** may be movably mounted to the front frame **204** to adjust the cooktop height defined by a cooktop of the range appliance **100**. Particularly, second front leveling leg **236** may be movably mounted to the front frame **204** within a front adjustment bracket **252**. The front adjustment bracket **252** may generally include a main body **254** and a leg mount **256**. The main body **254** may be mounted to the front face of the front frame **204** at the bottom corner **250**. The leg mount **256** may be extended from the main body **254** along the transverse direction T. The leg mount **256** may define a leg aperture (e.g., FIG. **6**). The second front leveling leg **236** may be movably mounted within the leg mount **256** to adjust the cooktop height. For instance, the second front leveling leg **236** may include a threaded portion that is movably mounted within a complementary threaded portion within the leg aperture.

[0036] The transverse extension of the leg mount **256** may advantageously position the second front leveling leg **236** in front of the front frame **204**. The second front leveling leg **236** may include an axis of rotation. The axis of rotation may extend axially through a center of the second front leveling leg **236**. The axis of rotation of the second front leveling leg **236** may be positioned in front of the second side member **214** (e.g., along the transverse direction T). Moreover, the positioning of the second front leveling leg **236** may advantageously allow the range appliance **100** to minimize the use of counterweight, for instance, counterweight that may be utilized to reduce or mitigate tipping of the range appliance **100**.

[0037] The second rear leveling leg **238** may be movably mounted within the second base rail **208** to adjust the cooktop height. For instance, the second rear leveling leg **238** may include a threaded portion that is movably mounted within a complementary threaded aperture defined at a rear portion **260** of the second base rail **208**. The rear portion **260** of the second base rail **208** may be positioned at, or proximate to, the rear end **220** of the second base rail **208**. That is, the rear portion **260** of the second base rail **208** may be positioned closer to the rear end **220** of the second base rail **208** than the front end **222** of the second base rail **208**, such as within the rear twenty five percent of the transverse length of the second base rail **208**, within the rear fifteen percent of the transverse length of the second base rail **208**, or within the rear five percent of the transverse length of the second base rail **208**.

[0038] As an illustrative example, a user may rotate the second front leveling leg **236** or the second rear leveling leg **238** within the respective complementary threaded aperture to raise or lower the cooktop height. In some exemplary embodiments, the second front leveling leg **236** or the second rear leveling leg **238** can be raised or lowered independently of each other to “level” the range appliance **100** and more particularly, the cooktop **102** of the range appliance **100**. In some other embodiments, the second front leveling leg **236** or the second rear leveling leg **238** can be raised or lowered together raise or lower the cooktop height.

[0039] As should be appreciated, the first front leveling leg **232** or the first rear leveling leg **234** may also be raised or lower independently to “level” the range appliance **100**, and more particularly, the cooktop **102** of the range appliance **100**. In this regard, first front leveling leg **232**, the first rear leveling leg **234**, the second front leveling leg **236**, or the second rear leveling leg **238** may be raised or lowered independently of each other to “level” the range appliance **100**, and more

particularly, the cooktop **102** of the range appliance **100**. Moreover, the first front leveling leg **232** or the first rear leveling leg **234** may be raised or lowered together to raise or lower the cooktop height. In this regard, first front leveling leg **232**, the first rear leveling leg **234**, the second front leveling leg **236**, or the second rear leveling leg **238** may be raised or lowered together to raise or lower the cooktop height.

[0040] Referring now to FIG. **6**, a perspective view of the front adjustment bracket **252** is provided. As briefly mentioned above the front adjustment bracket **252** may generally include a main body **254** and a leg mount **256**. The main body **254** may be generally rectangular in shape, extending along the vertical direction V and the lateral direction L. For instance, the main body **254** may be extended between a top **258** and a bottom **261** along the vertical direction V, an inner edge **262** and an outer edge **264** along the lateral direction L, and a front side **266** and a rear side **268** along the transverse direction T. Front side **266** may face a front of range appliance **100**. Accordingly, rear side **268** may be provided opposite front side **266** and thus face a rear of range appliance **100**.

[0041] The front adjustment bracket **252** may include a second body **270** extended from the main body **254**. The second body **270** may be provided to protect a portion of the front frame **204**. Specifically, the second body **270** may be provided to protect a portion of the bottom corner **250** of the front frame **304**. For example, referring briefly to FIG. **5**, the bottom corner **250** may include a front trim **205** and a side trim **207**. The front trim **205** may be positioned at an inner portion of the second side member **214**. The side trim **207** may be positioned at the jog **244** (e.g., between the first portion **240** of the frame sill **210** and the second portion **242** of the frame sill **210**). The front trim **205** and the side trim **207** may be relatively thin portions of the front frame **204** (e.g., when compared to other portions of the front frame **204** such as the frame sill **210**). For example, a lateral width of the front trim **205** may be thinner than surrounding portions of the front frame **204**, for instance, may be thinner than the vertical length of the first portion **240** of the frame sill **210**. As another example, the transverse width of the side trim **207** may be thinner than the surrounding portions of the front frame **204**, for instance, may be thinner than the transverse width of the first portion **240** of the frame sill **210**.

[0042] The second body **270** may cover and obscure visibility of (e.g., to a user of the range appliance **100**), at least a portion of the front trim **205** or the side trim **207** of the front frame **204**. For instance, the second body **270** may be positioned in front of (e.g., along the transverse direction T) or beside (e.g., along the lateral direction L) the front frame **204**. In this regard, the second body **270** may be configured to obscure the visibility of areas of the front trim **205** or the side trim **207** where chipping or cracking of the enameled coating may occur. For instance, during shipping or handling of the range appliance **100**, the range appliance **100** may experience a severe shock (e.g., a drop or a hit). The severe shock experienced by the range appliance **100** may cause chipping or cracking of the enameled coating at portions of the front trim **205** or the side trim **207**. The second body **270** is positioned to obscure visibility of areas where chipping or cracking of the enameled coating (e.g., to a user of the range appliance **100**) is prone to occur. Thus, the second body **270** may maintain an acceptable appearance of the front frame **204** to a user of the range appliance **100**.

[0043] In some embodiments, the second body **270** includes a front guard **272** and a side guard **274** for protecting a portion of the bottom corner **250** of the front frame **204**. The front guard **272** may be provided to protect the front trim **205** of the front frame **204**. The side guard **274** may be provided to obscure visibility (e.g., to a user of the range appliance **100**) of at least a portion the side trim **207** of the front frame **204**. The front guard **272** may be extended along the vertical direction V from the top **258** of the main body **254**. Specifically, the front guard **272** may be extended along the vertical direction V from the top **258** of the main body **254** proximity to the front side **266** of the main body **254**. In addition, the front guard **272** may be disposed at the inner edge **262** of the main body **254**. The front guard **272** may be extended between a first side **276** and a second side **278** along the lateral direction L. The first side **276** may be disposed at the inner edge **262** of the main body **254**.

[0044] The side guard **274** may be extended along the vertical direction V from the inner edge **262** of the main body **254**. The side guard **274** may be extended along the transverse direction T from the first side **276** of the front guard **272**, for instance, toward a rear of the range appliance **100**. In this regard, the side guard **274** may be positioned approximately perpendicular to the front guard **272**. When the front adjustment bracket **252** is attached to the front frame **204**, the front guard **272** and the side guard **274** may wrap around the front trim **205** or the side trim **207** of the front frame **204**. In this regard, during a shipping or handling operation, the second body **270** may be capable of protecting the front frame **204**, and more particularly, the front guard **272** may be capable of protecting the enamel coating on the front trim **205** or side guard **274** may be capable of protecting enamel coating on the side trim **207**, from chipping. Additionally or alternatively, the front adjustment bracket **252** may include a drawer guide **280** extended from the main body **254**. For instance, the drawer guide **280** may be extended from the inner edge **262** of the main body **254** along the lateral direction L. The drawer guide **280** may be provided to guide the drawer assembly **162**, for instance, into or out of the drawer recess **160**.

[0045] Front adjustment bracket **252** may also define may include a plurality of fastener apertures **282**. In detail, the plurality of fastener apertures **282** may be defined through main body **254** along the transverse direction T. The plurality of fastener apertures **282** may extend from front side **266** to rear side **268** (e.g., along the transverse direction T). Further, the plurality of fastener apertures **282** may be spaced apart along each of the vertical direction V and the lateral direction L. As shown in the figures, three fastener apertures **282** may be provided, however it should be understood that the number of fastener apertures **282** shown is by way of example only, and that any suitable number of fastener apertures **282** may be provided. Accordingly, front adjustment bracket **252** may be selectively fastened to range appliance **100** via one or more fasteners (such as screws, bolts, pins, rivets, or the like).

[0046] The leg aperture **290** may be defined as a through hole through leg mount **256**. For instance, leg aperture **290** may be defined axially along the vertical direction V. Leg aperture **290** may be a threaded hole. For instance, leg aperture **290** may include features for receiving a threaded portion of the second front leveling leg **236**. In this regard, the second front leveling leg **236** may be movably mounted within leg aperture **290** via threaded engagement to adjust the cooktop height of range appliance.

[0047] Although aspects of the present subject matter are described herein in the context of a single oven appliance, it should be appreciated that range appliance **100** is provided by way of example only. Other oven or range appliances having different configurations, different appearances, or different features may also be utilized with the present subject matter, e.g., double ovens, standalone cooktops, etc.

[0048] This written description uses examples to disclose the invention, including the best mode, and also to enable any person skilled in the art to practice the invention, including making and using any devices or systems and performing any incorporated methods. The patentable scope of the invention is defined by the claims, and may include other examples that occur to those skilled in the art. Such other examples are intended to be within the scope of the claims if they include structural elements that do not differ from the literal language of the claims, or if they include equivalent structural elements with insubstantial differences from the literal languages of the claims.

Claims

1. A cooking appliance defining a vertical direction, a lateral direction, and a transverse direction, the cooking appliance comprising: a cabinet defining a cooking chamber and a drawer recess positioned below the cooking chamber; a front frame defining a chamber opening for the cooking chamber and a drawer opening for the drawer recess, the front frame comprising a frame sill and a

side member, the frame sill extending between a first side and a second side along the lateral direction, the side member extending along the vertical direction from the first side of the frame sill to form a bottom corner of the front frame; and an adjustment bracket attached to the bottom corner of the front frame, the adjustment bracket comprising: a main body extended between a top and a bottom along the vertical direction, an inner edge and an outer edge along the lateral direction, and a front side and a rear side along the transverse direction; and a second body disposed at the top and the inner edge of the main body.

2. The cooking appliance of claim 1, wherein the frame sill comprises a first portion, a jog, and a second portion, wherein the jog is positioned between the first portion and the second portion to raise the second portion along the vertical direction by a predetermined amount, wherein the second portion is positioned at the first side of the frame sill, and wherein the side member extends along the vertical direction from the second portion of the frame sill to form a bottom corner of the front frame.

3. The cooking appliance of claim 1, wherein the second body comprises a front guard for protecting a front trim of the bottom corner, wherein the front guard is extended along the vertical direction from the top of the main body, and wherein the front guard is disposed at the inner edge of the main body.

4. The cooking appliance of claim 3, wherein the front guard is extended between a first side and a second side along the lateral direction, wherein the first side is disposed at the inner edge of the main body.

5. The cooking appliance of claim 4, wherein the second body further comprises a second guard for protecting a side trim of the bottom corner, wherein the second guard is extended along the vertical direction from the inner edge of the main body, and wherein the second guard is extended along the transverse direction from the first side of the front guard toward a rear of the cabinet.

6. The cooking appliance of claim 5, wherein the front frame comprises an enamel coating, and wherein the enamel coating of the bottom corner of the front frame is protected by the second body.

7. The cooking appliance of claim 1, wherein the adjustment bracket further comprises a leg mount, wherein the leg mount extends along the transverse direction from the front side of the main body.

8. The cooking appliance of claim 7, wherein the leg mount defines a leg aperture for movably receiving a leveling leg, and wherein a cooktop height of the cooking appliance is adjusted by rotating the leveling leg within the leg aperture.

9. The cooking appliance of claim 1, wherein the main body defines one or more fastener apertures for receiving one or more mechanical fasteners, and wherein the main body is fastened to the bottom corner of the front frame via the one or more mechanical fasteners.

10. The cooking appliance of claim 1, wherein the side member is a first side member, wherein the first side member is extended along the vertical direction from the first side of the frame sill, wherein the front frame further comprises a second side member, wherein the second side member is extended along the vertical direction from the second side of the frame sill, wherein the bottom corner is a first bottom corner at the first side of the frame sill, and wherein the second side of the frame sill and the second side member define a second bottom corner at the second side of the frame sill.

11. The cooking appliance of claim 10, wherein the adjustment bracket is a first adjustment bracket, wherein the first adjustment bracket is attached to the first bottom corner, wherein the cooking appliance further comprises: a second adjustment bracket attached to the second bottom corner, the second adjustment bracket defining a leg aperture for movably receiving a second leveling leg, wherein a cooktop height of the cooking appliance is adjusted by rotating the second leveling leg within the leg aperture of the second adjustment bracket.

12. An adjustment bracket for a cooking appliance, the cooking appliance defining a vertical direction, a lateral direction, and a transverse direction, the cooking appliance comprising a front frame, the front frame comprising a frame sill and a side member extending along the vertical

direction from the frame sill, the frame sill and the side member defining a bottom corner, the adjustment bracket comprising: a main body extended between a top and a bottom along the vertical direction, an inner edge and an outer edge along the lateral direction, and a front side and a rear side along the transverse direction; and a second body disposed at the top and the inner edge of the main body, wherein the second body is wrapped around a portion of the bottom corner to protect the bottom corner.

13. The adjustment bracket of claim 12, wherein the second body comprises a front guard for protecting a front trim of the bottom corner, wherein the front guard extends along the vertical direction from the top of the main body, and wherein the front guard is disposed at the inner edge of the main body.

14. The adjustment bracket of claim 13, wherein the front guard is extended between a first side and a second side along the lateral direction, wherein the first side is disposed at the inner edge of the main body.

15. The adjustment bracket of claim 14, wherein the second body further comprises a second guard for protecting a side trim of the bottom corner, wherein the second guard is extended along the vertical direction from the inner edge of the main body, and wherein the second guard is extended along the transverse direction from the first side of the front guard toward a rear of the cooking appliance.

16. The adjustment bracket of claim 15, wherein the front frame includes an enamel coating, and wherein the enamel coating of the bottom corner of the front frame is protected by the second body.

17. The adjustment bracket of claim 1, wherein the adjustment bracket further comprises a leg mount, wherein the leg mount is extended along the transverse direction from the front side of the main body.

18. The adjustment bracket of claim 17, wherein the leg mount defines a leg aperture for movably receiving a leveling leg, and wherein a cooktop height of the cooking appliance is adjusted by rotating the leveling leg within the leg aperture.

19. The adjustment bracket of claim 1, wherein the main body defines one or more fastener apertures for receiving one or more mechanical fasteners, and wherein the main body is fastened to the bottom corner of the front frame via the one or more mechanical fasteners.
