

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250277606

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Primbas; George

AIR CONDITIONING SYSTEM AND TRANSPORTATION SYSTEM INCLUDING SAME

Abstract

An air conditioning system includes a rotation driving device, an energy storage device for powering the rotation driving device, a generator electrically connected to the energy storage device, and a turboexpander. The turboexpander includes a drive shaft coupled to both the generator and the rotation driving device, and configured to be rotated by the rotation driving device. The turboexpander also includes a compressor wheel and an expander wheel. The compressor wheel is configured to pull in ambient air and generate pressurized air from the ambient air responsive to rotation of the drive shaft. The expander wheel is fluidly coupled to the compressor wheel such that the pressurized air from the compressor wheel is configured to be received in the expander wheel and converted into expanded and cooled air by the expander wheel for delivery to an environment.

Inventors: Primbas; George (Concord Township, OH)

Applicant: Thevu LLC (Concord Township, OH)

Family ID: 96881048

Assignee: Thevu LLC (Concord Township, OH)

Appl. No.: 19/171566

Filed: April 07, 2025

Related U.S. Application Data

parent US continuation 18816006 20240827 parent-grant-document US 12215908 child US 19003031

parent US continuation-in-part 19003031 20241227 PENDING child US 19171566

parent US continuation-in-part 18612010 20240321 parent-grant-document US 12103354 child US

Publication Classification

Int. Cl.: **F25B9/06** (20060101); **F24F5/00** (20060101); **F25B9/00** (20060101); **F25B43/00** (20060101)

U.S. Cl.:

CPC **F25B9/06** (20130101); **F24F5/0085** (20130101); **F25B43/00** (20130101); **F25B9/004** (20130101)

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation-in-part of U.S. patent application Ser. No. 19/003,031, filed Dec. 27, 2024, and entitled “AIR CONDITIONING SYSTEM AND TRANSPORTATION SYSTEM INCLUDING SAME”, which is a continuation of U.S. patent application Ser. No. 18/816,006, filed Aug. 27, 2024, now U.S. Pat. No. 12,215,908, and entitled “AIR CONDITIONING SYSTEM AND TRANSPORTATION SYSTEM INCLUDING SAME”, which is a continuation-in-part of U.S. patent application Ser. No. 18/612,010, filed Mar. 21, 2024, now U.S. Pat. No. 12,103,354, and entitled “AIR CONDITIONING SYSTEM, TRANSPORTATION SYSTEM INCLUDING THE SAME, AND ASSOCIATED METHOD”, which claims priority to and claims the benefit of U.S. Patent Application Ser. No. 63/559,466, filed Feb. 29, 2024, the contents of which are incorporated herein in by reference.

BACKGROUND

[0002] Air conditioning (A/C) systems have been known for many years. Generally, it can be said that A/C systems provide cooled air into an environment (e.g., a residential or commercial building) by removing heat from indoor air. As the A/C system is performing this function, it returns the cooled air to the indoor space, and expels hot air outside of the building. Today, known A/C systems use a coolant, such as freon, ammonia, propane, and the like, and circulates this coolant to generate the cooled air. Furthermore, today's A/C systems, such as the prior art A/C system **2** of FIG. **1**, include a compressor **4**, a condenser **6**, and an evaporator **8**. In operation, these components of the A/C system work to change the coolant from gas to liquid and back to a gas.

[0003] More specifically, the compressor **4** increases the pressure and temperature of the coolant gas and delivers it to the condenser **6**, where it is converted to a liquid, before it is sent back to the evaporator **8**. In the evaporator **8**, the liquid coolant (e.g., freon, ammonia etc.) evaporates and cools the coil of the evaporator **8**. Subsequent to this cooling of the coil of the evaporator **8**, a fan **10** blows air across the cold coil of the evaporator **8** in order to cool the building (e.g., residence, commercial, or otherwise). Additionally, after being blown into the building, the cooled air is then circulated throughout the building while the heated evaporated gas is sent back outside the compressor. In other words, the A/C system **2** is a closed loop system, and as such, the heat is then released into the outdoor air as the coolant returns to a liquid state. In operation, this sequence is repeated until the building reaches a desired temperature.

[0004] The above-described system/process has a number of drawbacks. First, coolant in A/C systems, such as freon (e.g., refrigerant), is becoming more and more regulated. As a result, the coolant is becoming extremely expensive and inefficient for users, who may be homeowners or

commercial building owners, to use in their A/C systems. Second, performing maintenance on today's A/C systems is rather difficult. For example, maintenance technicians who have to replace coolant of a given A/C system with new coolant are forced to turn off an entire A/C system, syphon out the old coolant, and introduce the new coolant. This process can take significant time to perform, costing users money. Third, because the cost of various coolants has gotten so high, owners are often forced to replace entire A/C systems when they have leaks in their coils, rather than simply introduce new coolant. This is not desirable. Fourth, because coolant and today's A/C systems (e.g., evaporators and condensers) are so expensive, many places in the world, such as hot desert regions, are unable to afford the same, thereby making withstanding the heat rather difficult. Fifth because powering air compressors requires users to draw power from a power grid, regions of the world with less sophisticated electric power capabilities are undesirably deprived of air conditioning. Finally, because today's A/C systems are closed loop systems, users are forced to keep their windows and doors closed, in order to prevent cooled air from escaping, and/or to minimize A/C bills.

[0005] Other systems which cause gases to move between states, besides the A/C system 2, include air separation systems at air separation plants. These systems have been known for a long time. However, the primary purpose of most all if not all air separation systems at these plants is to liquify gases (e.g., nitrogen, oxygen, etc.) for refrigeration purposes. Accordingly, equipment in these plants is uniquely tailored for the purpose of, for example, liquifying oxygen and nitrogen. Furthermore, gases in such plants, such as nitrogen gas, are lethal if breathed in by a human.

[0006] It is with respect to these and other considerations that the instant disclosure is concerned.

SUMMARY

[0007] In one aspect of the disclosed concept, an air conditioning system is provided. The air conditioning system comprises a rotation driving device; an energy storage device for powering the rotation driving device; a generator electrically connected to the energy storage device; and a turboexpander, comprising: a drive shaft coupled to both the generator and the rotation driving device, and configured to be rotated by the rotation driving device, a compressor wheel coupled to the drive shaft and configured to pull in ambient air and generate pressurized air from the ambient air responsive to rotation of the drive shaft in a manner wherein the rotation driving device provides a source of kinetic energy to cause the compressor wheel to rotate and generate the pressurized air, and an expander wheel coupled to the drive shaft and fluidly coupled to the compressor wheel such that the pressurized air from the compressor wheel is configured to be received in the expander wheel and converted into expanded and cooled air by the expander wheel for delivery to an environment. The expander wheel and the generator are configured to convert both the source of kinetic energy and energy in the ambient air into mechanical energy of the drive shaft, and then convert the mechanical energy of the drive shaft into electrical energy in the generator for charging the energy storage device, and thereby powering the rotation driving device.

[0008] In another aspect, a transportation system comprises an electric motor; at least one element coupled to and configured to be driven by the electric motor in order to move the transportation system between an IDLING state corresponding to the transportation system being turned on and not moving, and an OPERATING state corresponding to the transportation system being turned on and moving; and air conditioning system, comprising a rotation driving device, an energy storage device for powering the rotation driving device and the electric motor, a generator electrically connected to the energy storage device, and a turboexpander, comprising a drive shaft coupled to both the generator and the rotation driving device, and configured to be rotated by the rotation driving device, a compressor wheel coupled to the drive shaft and configured to pull in ambient air and generate pressurized air from the ambient air responsive to rotation of the drive shaft in a manner wherein the rotation driving device provides a source of kinetic energy to cause the compressor wheel to rotate and generate the pressurized air, and an expander wheel coupled to the drive shaft and fluidly coupled to the compressor wheel such that the pressurized air from the

compressor wheel is configured to be received in the expander wheel and converted into expanded and cooled air by the expander wheel for delivery to an environment. The expander wheel and the generator are configured to convert both the source of kinetic energy and energy in the ambient air into mechanical energy of the drive shaft, and then convert the mechanical energy of the drive shaft into electrical energy in the generator for charging the energy storage device, and thereby powering the rotation driving device.

[0009] In another aspect, a transportation system comprises an electric motor; at least one element coupled to and configured to be driven by the electric motor in order to move the transportation system between an IDLING state corresponding to the transportation system being turned on and not moving, and an OPERATING state corresponding to the transportation system being turned on and moving; and an air conditioning system, comprising a rotation driving device, an energy storage device for powering both the rotation driving device and the electric motor, a generator electrically connected to the energy storage device, and a turboexpander, comprising a drive shaft coupled to both the generator and the rotation driving device, and configured to be rotated by the rotation driving device, a compressor wheel coupled to the drive shaft and configured to pull in ambient air and generate pressurized air from the ambient air responsive to rotation of the drive shaft in a manner wherein the rotation driving device provides a source of kinetic energy to cause the compressor wheel to rotate and generate the pressurized air, and an expander wheel coupled to the drive shaft and fluidly coupled to the compressor wheel such that the pressurized air from the compressor wheel is configured to be received in the expander wheel and converted into expanded and cooled air by the expander wheel for delivery to an environment. The expander wheel and the generator are configured to convert both the source of kinetic energy and energy in the ambient air into mechanical energy of the drive shaft, and then convert the mechanical energy of the drive shaft into electrical energy in the generator for charging the energy storage device, and thereby powering the rotation driving device.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] FIG. 1 is a schematic of a prior art A/C system.

[0011] FIG. 2 is a simplified view of an A/C system in accordance with the disclosed concept, shown as employed with an electrical apparatus, an additional power source, a vent stack, and ductwork, each of which is illustrated in dashed line drawing, and wherein double line connections between components in FIG. 2 denote electrical connections and single line connections between components in FIG. 2 generally denote conduits (e.g., without limitation, pipes) through which fluids may flow.

[0012] FIGS. 3 and 4 are front and simplified views, respectively, of a transportation system including the A/C system of FIG. 2, in accordance with one non-limiting embodiment of the disclosed concept.

[0013] FIG. 5 is a simplified view of another A/C system in accordance with the disclosed concept, wherein double line connections between components in FIG. 5 denote electrical connections and single line connections between components in FIG. 5 generally denote conduits (e.g., without limitation, pipes) through which fluids may flow.

[0014] FIG. 6 is a simplified view of a transportation system including the A/C system of FIG. 5, in accordance with one non-limiting embodiment of the disclosed concept.

DETAILED DESCRIPTION

[0015] As employed herein, the term “coupled” shall mean connected together either directly or via one or more intermediate parts or components.

[0016] As employed herein, the term “number” shall mean one or an integer greater than one (i.e., a

plurality).

[0017] As employed herein, the term “air compressor” shall mean a device which generates pressurized air from ambient air, and delivers the pressurized air at an outlet at a pressure greater than the pressure of the ambient air entering the inlet. Air compressors in accordance with the disclosed concept may use electrical energy in order to generate a flow of pressurized gas. Air compressors may include an electric air compressor motor. Air compressors in accordance with the disclosed concept, unlike nitrogen compressors (or compressors configured for other gases besides air), may not have gas coolers, inlet and outlet dampers, and asynchronous motors.

[0018] As employed herein, the term “blower” shall mean an apparatus configured to produce air movement to a space.

[0019] As employed herein, the term “generator” shall mean a device configured to convert mechanical energy obtained from an external source into electrical energy as an output. Generators in accordance with the disclosed concept may convert mechanical energy from rotation of a drive shaft of a turboexpander into electrical energy, and may do so by moving at least one electrical conductor in a magnetic field in order to create a voltage difference between two ends of the electrical conductor.

[0020] As employed herein, the term “coolant” shall mean a substance configured to change states between liquid and gas, and as employed in a coil of an evaporator of an A/C system, such as the A/C system 2. Non-limiting examples of coolants include freon, propane, and ammonia.

[0021] As used herein, the term “air” shall mean an atmospheric gas comprised of Nitrogen, Oxygen, and Argon. Air in accordance with the disclosed concept preferably includes indoor and outdoor air, as well as both purified and non-purified air, wherein purified air includes, but is not limited to, air in which moisture and/or carbon dioxide have been removed. In one non-limiting example, air in accordance with the disclosed concept is non-toxic (e.g., breathable) to human beings.

[0022] As employed herein, the term “valve” shall mean a device for causing an opening area of a region of a conduit to be changeable as the valve opens and closes. Valves in accordance with disclosed concept may include guide vanes, as well as devices which move between FULLY OPEN states and FULLY CLOSED states.

[0023] As employed herein, the terms “inlet” and “outlet” shall each correspond to a “conduit”, whether a metallic or non-metallic pipe, or other type of conduit.

[0024] As employed herein, the term “control system” shall mean a system for directing the flow of air in an air conditioning system by causing any number of valves to independently move to predetermined positions, including fully open positions, fully closed positions, and positions therebetween. Control systems in accordance with the disclosed concept include programmable logic control systems.

[0025] As employed herein, the phrase “combustion reaction involving burning of fuel” shall mean a reaction involving an explosion between a gas, such as air, and a combustible fuel (e.g., oil including byproducts such as gasoline and aviation fuel, and natural gas including byproducts such as hydrogen fuel). A “combustion reaction involving burning of fuel” does not include the discharge of energy from an energy storage device such as a battery, and associated powering of an air compressor motor therewith.

[0026] As employed herein, the phrase “sole source of kinetic energy” shall mean a source of kinetic energy, such as a flow of pressurized air, in whose absence another object, such as a compressor wheel of a turboexpander, is configured to be in a static state (e.g., at rest), with respect to a ground.

[0027] As employed herein, the term “turboexpander” shall mean a device comprising a drive shaft, and first and second wheels coupled to the drive shaft, wherein the first wheel is configured to compress a gas and the second wheel is configured to expand the gas.

[0028] FIG. 2 shows an example A/C system **100**, in accordance with one non-limiting

embodiment of the disclosed concept. The A/C system **100** in one example is preferably a coolant-free air conditioning system such that it functions without circulating coolant into a coil of an evaporator or other device. This is highly beneficial, as compared to the A/C system **2** (FIG. **1**), which is required to use coolant to cool buildings and the like. More specifically, by being coolant-free, the A/C system **100** can, among other advantages, save users money and minimize maintenance. That is, large evaporators and the like do not have to be replaced, and expensive coolant does not have to be employed in order to cool a building.

[0029] The A/C system **100** will now be discussed in detail, and the aforementioned advantages as well as others will be made apparent. As shown in FIG. **2**, the system **100** includes an air compressor **110**, a turboexpander **120**, a generator **140** coupled to the turboexpander **120**, an energy storage device **145** (e.g., without limitation, a battery, a capacitor, or another different type of energy storage device) electrically connected to the generator **140**, and a blower **150**. The turboexpander **120** is coupled to the air compressor **110**, the generator **140**, and the blower **150**. In one non-limiting example, the A/C system **100** is configured to deliver expanded and cooled air to ductwork **160**, which may be coupled to the blower **150** and configured to deliver the expanded and cooled air from the turboexpander **120** throughout a building.

[0030] In operation, aspects of the A/C system **100** comprising the air compressor **110**, the turboexpander **120**, the generator **140**, the energy storage device **145**, and the blower **150** may be located outside of a building, and may be fluidly coupled to the ductwork **160**, which may extend throughout the interior of the building. In a suitable alternative example, the air compressor **110**, the turboexpander **120**, the generator **140**, and the blower **150** may all be located in an interior of a building and be a self-contained subassembly that is configured to pull indoor air into the air compressor **110** for cooling, wherein the cooled air may be delivered back into the indoor environment.

[0031] The turboexpander **120** includes a drive shaft **122**, a compressor wheel **124** coupled to the drive shaft **122**, an expander wheel **126** coupled to the drive shaft **122** and the compressor wheel **124** (e.g., via the drive shaft **122**), a first inlet **128** and a first outlet **130** each associated with the compressor wheel **124**, and a second inlet **132** and a second outlet **134** each associated with the expander wheel **126**. Furthermore, as shown, the generator **140** includes a rotor (“R”) **142** coupled to the drive shaft **122** of the turboexpander **120** and configured to be rotated during operation of the turboexpander **120**.

[0032] Moreover, the air compressor **110** may include an air compressor motor **119**, which may be an electric motor. Additionally, the generator **140** is preferably electrically connected to the air compressor motor **119** in order to power the air compressor **110**, and/or is configured to be electrically connected to an electrical apparatus **180** (shown in dashed line drawing in FIG. **2**) in order to power the electrical apparatus **180**. The electrical apparatus **180** may be an operating system of a building (e.g., a restaurant, hospital, and the like), such as a lighting system, refrigeration system, freezer system, etc., in a manner wherein the A/C system **100** is configured to deliver air conditioning to the building, and also supply power to the lighting, refrigeration, and/or freezer system, as well as various other systems within the building. Furthermore, the generator **140** may be configured to power, e.g., fully power, the electrical apparatus **180** (e.g., the operating system of the building) while the blower **150** is delivering the expanded and cooled air to the building. After discussion of the operation of the A/C system **100**, below will be discussion of an example implementation of the A/C system **100**, wherein an electrical apparatus is in the form of an electric motor **280** (FIG. **4**) of a transportation system (e.g., vehicle **200**, shown in FIGS. **3** and **4**), such that the vehicle **200** includes the A/C system **100** as an integral operating system.

[0033] Continuing to refer to FIG. **2**, the energy storage device **145** is electrically connected to the air compressor motor **119**, the generator **140**, and the electrical apparatus **180**. Additionally, in non-limiting examples of the disclosed concept, the A/C system **100** does have the capability to receive power from a grid (e.g., from a power source **145-1**, shown in dashed line drawing in FIG. **2**),

should the need arise.

[0034] In operation, the generator **140** reliably supplies power to a number of devices. For example, the energy storage device **145** is electrically connected to and configured to be charged by the generator **140** of the A/C system **100**. Moreover, the energy storage device **145** is also configured to power the air compressor motor **119**. Specifically, during operation of the A/C system **100**, power may first be drawn by the air compressor motor **119** from the energy storage device **145**.

[0035] In one non-limiting example, the A/C system **100** further includes a moisture separator (“MS”) **114**, which may be a filter, fluidly coupled to an outlet **113** of the air compressor **110** and the first inlet **128** of the turboexpander **120** in order for moisture (e.g., water) to be removed from the pressurized air before the pressurized air is delivered to the turboexpander **120**. As such, the air compressor **110** may be configured to pull in ambient air at an inlet **111** of the air compressor **110** from the atmosphere, generate pressurized air from the ambient air, and cause the pressurized air to exit via the outlet **113** before being passed through the moisture separator **114**. It will be appreciated that the ambient air may be pressurized to any number of different pressure ranges, depending on the environment for the A/C system **100**. In one example, the ambient air is pressurized to between 130-180 psi. In an alternative example, an air compressor is configured to generate higher or lower pressures higher than 130-180 psi, provided suitable materials are employed, such as thicker and higher-grade steels for higher pressures.

[0036] Continuing to refer to FIG. 2, it will be appreciated that the air compressor **110** may, in one example, be fluidly coupled to the turboexpander **120** without any intermediate air processing apparatuses (e.g., a heat exchanger, distillation column, etc.) therebetween, such that the pressurized air flows directly from the air compressor **110** into the turboexpander **120**. As used herein, the moisture separator **114** is not considered an air processing apparatus. In a further example, the outlet **113** of the air compressor **110** is directly coupled to and engaged with the first inlet **128**, such that air flows directly from the outlet **113** through the moisture separator **114** and into the first inlet **128** of the turboexpander **120**, without passing through any other intermediate parts or components. It will also be appreciated that the blower **150** may be fluidly coupled to the second outlet **134** without any intermediate air processing apparatuses (e.g., a heat exchanger, distillation column, etc.) being located therebetween. In other words, the blower **150** may have an inlet **137** that is directly coupled with and engaged with the second outlet **134**.

[0037] In one example, a suitable alternative air compressor (not shown) may be fluidly coupled to the first inlet **128** of the turboexpander via a side stream **115**, shown in FIG. 2. In such an embodiment, the alternative air compressor (not shown) may be an existing air compressor at a garage, air separation facility, or the like. In such an example embodiment of the disclosed concept, the side stream **115**, and a valve **115-1** coupled to the side stream **115**, may be one of a plurality of streams of the air compressor (not shown), wherein other of the streams may separately be configured to be directed to, for example, a fork-lift (not shown) in a garage or other location. Accordingly, it will be appreciated that air from the alternative air compressor (not shown) may likewise not be processed (e.g., in a heat exchanger, distillation column, or the like) when passing through the valve **115-1** of the side stream **115** to the first inlet **128**. Furthermore, in such an example of the disclosed concept, an air conditioning system preferably includes the turboexpander **120**, the generator **140**, the energy storage device **145**, and the blower **150**, which are configured to receive the pressurized air from the separate air compressor (not shown) via the side stream **115** and valve **115-1**.

[0038] Continuing to refer to FIG. 2, coupled to the outlet **113** of the air compressor **110** is a valve **113-1**, and coupled to the first inlet **128** of the turboexpander **120** is another valve **128-1**. In operation, the valves **113-1**, **128-1** function to control the volume and speed of air both exiting the air compressor **110** and entering the first inlet **128** of the turboexpander **120**. As a result, volume flow of air moving through the A/C system **100** is configured to be reliably controlled by opening

and closing the valves **113-1,128-1**.

[0039] More specifically, the A/C system **100** may further include a control system **190**. In one example, the control system **190** is wirelessly connected and/or electrically connected to the air compressor **110** and the valves **113-1,128-1**, such that responsive to actuation of the control system **190** (e.g., wherein a user presses a button on a control panel or sends a signal to the control system **190** with a wireless device), the air compressor **110** is configured to generate the pressurized air at a predetermined first pressure, thereby causing the turboexpander **120** to generate expanded and cooled air at a predetermined second temperature. This is achieved by the valves **113-1,128-1** being opened and closed to predetermined opening areas by the control system **190**.

[0040] Once inside the turboexpander **120**, the compressor wheel **124** may generate boosted air from the pressurized air from the air compressor **110**, and the expander wheel **126** may generate expanded and cooled air from the boosted air, as will be discussed below. For example, the compressor wheel **124** boosts the pressurized air from the air compressor **110** to an even greater pressure. As such, by employing the compressor wheel **124**, a size of the air compressor **110** is advantageously able to be relatively small. In one example, the compressor wheel **124** receives the pressurized ambient air at 130-180 psi and boosts the pressurized ambient air to a pressure even greater than 180 psi. After being boosted by the compressor wheel **124**, the even higher pressurized air exits the compressor wheel **124** via the first outlet **130**, which is fluidly coupled to the second inlet **132** of the expander wheel **126**.

[0041] Accordingly, after exiting through the first outlet **130**, the boosted air enters the expander wheel **126** via the second inlet **132**. Once inside the expander wheel **126**, the boosted air is expanded by volume, which causes a relatively large pressure and temperature drop in the air. In other words, the expander wheel **126** generates expanded and cooled air from the boosted air. In one example, the air is configured to exit the turboexpander at between 3-20 psi of pressure, as well as between 33-45 degrees Fahrenheit. It will be appreciated that inlet and outlet temperatures associated with the turboexpander **120** may readily be varied.

[0042] However, in accordance with the disclosed concept, air is preferably not being liquified during operation of the A/C system **100** (e.g., other than at the moisture separator **114**), and operation of the A/C system **100** includes directing the air above a freezing temperature of water. That is, the air compressor **110** and the turboexpander **120** are together configured to change the ambient air to the expanded and cooled air without causing any of the ambient, pressurized, boosted, and expanded and cooled air to change states between a gas and a liquid. This includes embodiments where air undergoes a purification process corresponding to moisture and carbon dioxide being removed from the air between the air compressor **110** and the first inlet **128**.

[0043] Furthermore, it will be appreciated that the gas which is compressed by the air compressor **110** and the compressor wheel **124**, and then expanded and cooled by the expander wheel **126**, is the same gas which is delivered to the blower **150**. That is, unlike existing systems (e.g., the A/C system **2**) in which coolant changes from liquid to gas in the evaporator in order to cool an entirely separate and distinct gas (e.g., air) which is passed over the coil of the evaporator, the A/C system **100** is preferably coolant-free. As such, the same air which is pressurized, boosted, and expanded and cooled is also the air that is delivered to the blower **150**, such that the blower receives the expanded and cooled air in order to deliver the expanded and cooled air to an environment. Put another way, substantially all of the air associated with the A/C system **100** enters and passes through each of the compressor **110**, the turboexpander **120**, and the blower **150** such that coolant (e.g., being located in coils) is preferably not employed to cool the air. As such, the A/C system **100** readily provides tremendous advantages over the prior art A/C system **2** (FIG. 1) and improves over the prior art A/C system **2** in most and/or all of the respects discussed above in connection with the A/C system **2** (FIG. 1).

[0044] Continuing to refer to FIG. 2, as the expander wheel **126** is dropping the pressure and temperature of the air, the drive shaft **122** is rotating, which in turn powers the windings of the

generator **140** via the coupling between the rotor **142** and the drive shaft **122**. The purpose of this functionality will be described below. Additionally, once the pressure and temperature of the air have been dropped by the expander wheel **126**, the expanded and cooled (e.g., and also low pressure) air is caused to exit the turboexpander **120** via the second outlet **134**. In turn, this cool and low-pressure air is advantageously used to cool a building, the cabin of the vehicle **200** (FIGS. **3** and **4**), and/or other environments. More specifically, and continuing to refer to FIG. **2**, the inlet **137** of the blower **150** is fluidly coupled to the second outlet **134**. As such, when the cool and low-pressure air is received at the blower **150**, a fan of the blower **150** can cause that cool and low-pressure air to be excited (e.g., made more turbulent), thereby allowing it to be delivered more effectively to a building.

[0045] Furthermore, because the air is rather cold, in one example the A/C system **100** is configured to be employed with a valve system in the form of a vent stack **152** coupled to the outlet of the blower **150**. The vent stack **152** may open and close to an outside environment automatically or from a user. In one example, the control system **190** is wirelessly connected to the vent stack **152** in order to better control the temperature of cooled air being delivered to a building. For example, a smaller opening of the vent stack **152** via the control system **190** is configured cause colder temperatures in a given building. Accordingly, the vent stack **152** may be a way for the A/C system to regulate temperature in a building. In one example, the vent stack **152** could be open one at an initial time one hundred percent and then can close in a gradual manner in order to efficiently regulate temperature in a building.

[0046] Continuing to refer to FIG. **2**, the ductwork **160**, which is coupled to the A/C system **100**, may include a primary branch **162** and a plurality of secondary branches **164,166,168** fluidly coupled to the primary branch **162**. Additionally, coupled to, located on, and/or provided with an end of each of the secondary branches **164,166,168** may be a corresponding vent **165,167,169** (e.g., one which may be positioned adjacent a wall of a room of a commercial building or house). As such, it will be appreciated that the cool and low-pressure air, which has been excited by the blower **150**, will enter the primary branch **162** (e.g., the primary branch **162** is fluidly coupled to the blower **150**) and be forced through each of the secondary branches **164,166,168**, where it will exit the ductwork **160** through the corresponding vents **165,167,169**, thereby adequately delivering the cooled and low-pressure air throughout a large number of regions of a building.

[0047] In addition to delivering cooled and low-pressure air to an environment, the A/C system **100** is also provided with a power generation capability in tandem with the air conditioning capability. More specifically, as stated above, as the drive shaft **122** of the turboexpander **120** is caused to rotate, the rotor **142** of the generator **140** is rotated, thus generating power. As shown in FIG. **2**, a first electrical line **170** is electrically connected to the generator **140**, and a number of branch electrical lines **172,174,176** are each directly or indirectly electrically connected to the first electrical line **170**. In one example, the electrical lines **170,172,174,176** allow electrical power from the generator **140** to be directed to any combination or all of the air compressor motor **119**, the energy storage device **145**, and the electrical apparatus **180**.

[0048] In one example, electric power from the generator **140** is directed back into the air compressor motor **119** via the electrical lines **170,172**, which may be one single electrical line. In another example, the A/C system **100** further is configured to deliver power to the electrical apparatus **180**, wherein electric power from the generator **140** is directed to the electrical apparatus **180** via the electrical lines **170,174**, which may be one single electrical line. In yet a further example, electric power from the generator **140** is directed to the energy storage device **145** via the electrical lines **170,172,176**, which may be one single electrical line, in order that the energy storage device **145** may be charged by the generator **140**. Accordingly, the A/C system **100**, unlike the A/C system **2** (FIG. **1**), is advantageously configured to deliver cool and low-pressure air to an environment and simultaneously (e.g., at the same time) deliver electric power to electrical apparatuses, including the air compressor motor **119**, the energy storage device **145**, and/or the

electrical apparatus **180**.

[0049] Continuing to refer to FIG. 2, the air compressor **110** includes the inlet **111** for receiving the ambient air, and the inlet **137** of the blower is configured to receive the expanded and cooled air from the second outlet **134** of the turboexpander **120**. Furthermore, as shown in FIG. 2, the A/C system **100** further includes a recirculation conduit **139** fluidly coupled to each of the second outlet **134** of the turboexpander **120**, the inlet **137** of the blower **150**, and the inlet **111** of the air compressor **110** in order to recirculate a first amount of the expanded and cooled air back into the inlet **111** of the air compressor after the first amount has exited the turboexpander **120**. In one example, the air compressor **110** is fluidly coupled between the recirculation conduit **139** and the compressor wheel **124** such that the first amount is configured to flow directly from the recirculation conduit **139** into the inlet **111** of the air compressor **110** to be pressurized before flowing into and being boosted by the compressor wheel **124**. In other words, the recirculation conduit **139** is preferably spaced from the inlet **128** associated with the compressor wheel **124**.

[0050] To illustrate, and with continued reference to FIG. 2, the A/C system **100** may further include a vent conduit **138**, as well as a plurality of valves **111-1,137-1,138-1,139-1** each coupled to a corresponding one of the inlet **111** of the air compressor **110**, the inlet **137** of the blower **150**, the vent conduit **138**, and the recirculation conduit **139**. The valves **111-1,137-1,138-1,139-1** are preferably each wirelessly connected and/or electrically connected to the control system **190**, and function to control the flow of the expanded and cooled air in the system. For example, responsive to actuation of the control system **190**, the valve **138-1** may move between fully open and fully closed states, thus causing either large amounts or none, respectively, of the expanded and cooled air to exit the A/C system to an atmosphere via the vent conduit **138**. Similarly, the valves **137-1,139-1,111-1** control airflow into the blower **150**, through the recirculation conduit **139**, and into the air compressor **110**.

[0051] In one example, the valves **137-1,139-1** function to control the first amount of the expanded and cooled air flowing into the inlet **111** of the air compressor **110** and a second amount of the expanded and cooled air flowing into the blower **150**. In one example, the vent conduit **138** is fluidly coupled to each of the second outlet **134** of the turboexpander **120**, the inlet **137** of the blower **150**, and the recirculation conduit **139**, such that the vent conduit **138** is configured to vent a second amount of the expanded and cooled air to an atmosphere. It will thus be appreciated that the valve **138-1** is configured to control the second amount of the expanded and cooled air being vented to the atmosphere. In one example, responsive to actuation of the control system **190**, such as a user pressing a button on the control system **190** or the control system **190** receiving a signal from a smart device (e.g., mobile phone, tablet, vehicle, etc.), the amount of the expanded and cooled air passing through the recirculation conduit **139** may be a predetermined amount.

[0052] Continuing to refer to FIG. 2, the air compressor is further configured to startup in a reliable manner. More specifically, the air compressor **110** preferably further includes a vent conduit **117**, the outlet **113**, a valve **117-1** coupled to the vent conduit **117**, and the valve **113-1** coupled to the outlet **113** of the air compressor **110**. Furthermore, the vent conduit **117** is configured to vent an amount of the pressurized air to an atmosphere, and the valve **117-1** is configured to control the amount of the pressurized air being vented to the atmosphere. Moreover, the valve **113-1** is configured to control an amount of the pressurized air exiting the air compressor **110** before being delivered to the turboexpander **120**. In turn, responsive to the A/C system **100** moving from an INITIAL STATE to an OPERATING state, the amount of pressurized air vented to the atmosphere decreases as the amount of air passing through the outlet **113** increases. Put another way, the vent conduit **117** may close gradually or entirely after the air compressor **110** gets going, in order to allow for maximum delivery of the pressurized air to the turboexpander **120**.

[0053] In another example embodiment of the disclosed concept, and as shown in FIGS. 3 and 4, the vehicle **200** includes the A/C system **100**, a vehicle body or frame **203**, a pair of wheels **204**, at least one element (e.g., first and second axles **207,209**) each coupled to the frame **203** as well as to

one of the pair of wheels **204**, and an electrical apparatus in the form of the electric motor **280**. In operation the electric motor **280** is configured to drive (e.g., cause to rotate) at least one of the first and second axles **207,209**, thereby allowing the first, second, third and fourth wheels **204** to roll when the vehicle **200** is in an OPERATING state. Furthermore, the electric motor **280** is advantageously configured to draw power from each of the generator **140** (FIG. 2) and the energy storage device **145** (FIG. 2).

[0054] Continuing to refer to FIG. 4, it will be appreciated that the generator **140** (FIG. 2) and the energy storage device **145** of the A/C system **100** are each electrically connected to and configured to supply power to the electric motor **280**. Accordingly, operation of the A/C system **100** as discussed above is configured to deliver cool air to an environment (e.g., a cabin of the vehicle **200**) and also generate electric power in the generator **140** in order to charge the energy storage device **145** as well as power the electric motor **280**. As the electric motor **280** is powered by the generator **140** and/or the energy storage device **145** (FIG. 2), the body or frame **203** and associated wheels **204** can thus be moved along a road, parking lot, or elsewhere. In other words, the vehicle **200** can be powered and caused to drive by the power from the generator **140** being delivered to the electric motor **280**.

[0055] Additionally, in the example of FIG. 4 the energy storage device **145** for powering the air compressor motor **119** may be configured to supply power to the electric motor **280** in the form of a backup power supply to the electric motor **280** and/or in order to start the electric motor **280**. Accordingly, the generator **140** is configured to power the electric motor **280** and function as a power source during operation of the vehicle **200**. As such, the vehicle **200** may be powered with either relatively little electric charging and/or filling up of a gas tank (for hybrid vehicles). That is, the generator **140** may significantly supplement the power capabilities of the vehicle **200**.

[0056] More specifically, the vehicle **200** may have an OFF state corresponding to the vehicle **200** being turned off and not moving, an IDLING state corresponding to the vehicle **200** being turned on and not moving, and an OPERATING state corresponding to the vehicle **200** being turned on and moving. In one example, the electric motor **280** is configured to draw a first amount of power from the energy storage device **145** (FIG. 2) in order to move the vehicle **200** from the OFF state to the IDLING state. That is, the energy storage device **145** can get the vehicle **200** started, and then once the vehicle **200** is running, the generator **140** (FIG. 2) can charge the energy storage device **145** (FIG. 2) as well as power the electric motor **280**.

[0057] For example, when the vehicle **200** is in the OPERATING state, the electric motor **280** is configured to draw a second amount of power from the generator **140** (FIG. 2). In other words, the electric motor **280** may draw power from each of the energy storage device **145** and the generator **140**, and the generator **140** may be configured to power and charge the energy storage device **145** during operation of the A/C system **100**. It will also be appreciated that when the vehicle **200** moves from the IDLING state to the OPERATING state, the first amount of power from the energy storage device **145** decreases as the second amount of power from the generator **140** increases.

[0058] Accordingly, the vehicle **200** is configured such that the energy storage device **145** may be employed to start the vehicle **200**, and during operation of the vehicle **200**, more power may be drawn from the generator **140** than the energy storage device **145**. As such, when the vehicle **200** is in the OPERATING state, the first amount of power from the energy storage device **145** is configured to be less than the second amount of power from the generator **140**. As a result, the energy storage device **145** may be substantially smaller than batteries associated with today's electric and hybrid vehicles, wherein these batteries (not shown) are typically required to be relatively large and expensive because they are mostly the sole power sources for the vehicles.

[0059] Furthermore, by employing the A/C system **100** in the vehicle **200**, a tremendous cost and material savings to businesses and consumers can be realized. More specifically, known transportation systems which employ relatively large batteries can advantageously be provided with the relatively small energy storage device **145** instead, due to the generator **140** harnessing

energy from the air. As a result, the cost of the vehicle **200** can be relatively low, and the vehicle **200** can also operate in a clean-energy manner wherein material use associated with batteries can be largely minimized.

[0060] More specifically, in one example the air compressor **110** is configured to pull in ambient air having a first amount X_1 of energy, the air compressor **110** is configured to add a second amount X_2 of energy to the ambient air that is being pressurized therein via compression, and during expansion of the air in the expander wheel **126**, energy is removed from the air, such that the expanded and cooled air may be generated for air conditioning. Simultaneously, the expander wheel **126** is configured to create mechanical work in the generator **140** in order to generate electricity for powering the air compressor **110** and/or an electrical apparatus (e.g., the electrical apparatus **180** or the electric motor **280**). As a result, apart from any friction associated losses in the system, a first fraction of the (X_1+X_2) energy may be provided as the expanded and cooled air for air conditioning, and a second fraction, which may be a larger fraction, of the (X_1+X_2) energy may be routed back from the generator **140** in the form of electricity to the air compressor motor **119**, the energy storage device **145**, and/or the electric motor **280**.

[0061] Additionally, because warmer air has more energy than colder air, the air conditioning system **100** preferably further has a heating element (e.g., heating coil **139-2**) coupled to the recirculation conduit **139**. This is optimal for cold weather conditions. More specifically, the heating coil **139-2** is preferably electrically connected to the generator **140** via the electrical line **178** and is preferably configured to be powered by the generator **140** during operation of the air conditioning system **100**. As a result, the vehicle **200** is optimally configured to be powered by the air conditioning system **100** in cold weather, where the energy from the air is relatively low, as well as warm weather, where the energy from the air is relatively high. That is, the expanded and cooled air entering the recirculation conduit **139** after exiting the second outlet **134** may be heated with the heating coil **139-2** as it is passed through the recirculation conduit **139**, thus increasing an amount of energy supplied to the turboexpander **120** from the air compressor **110**.

[0062] Additionally, as shown in FIG. 4, the energy storage device **145** (FIG. 2) of the A/C system **100** may, if the need arises, also be separately charged by connecting the vehicle **200** to a power source **250**, which may be a charging station or plug extending from a building to a charging port of the vehicle **200**.

[0063] It will thus be appreciated that the electric motor **280** may be configured to consume a first amount of power per mile during use, and the generator **140** (FIG. 2) of A/C system **100** may be configured to deliver a relatively large fraction of the first amount of power to the electric motor **280**. In one example, the first amount of power consumed by the electric motor **280** is between 150-400 watt-hours per mile (e.g., 0.15-0.4 kWh/mile) during use.

[0064] Additionally, by powering the electric motor **280** with the air conditioning system **100**, operation of the vehicle **200** can be said to be safer than known methods of powering a vehicle. For example, accidents involving gasoline powered vehicles may result in fuel tanks exploding, accidents involving vehicles powered by relatively large batteries may result in non-dry portions of the relatively large batteries igniting, and more recent but known technologies involving liquid hydrogen to power a vehicle may be dangerous in that liquid hydrogen is often rather difficult to contain and work with. In accordance with the disclosed concept, by way of contrast, the air conditioning system **100** obviates these challenges by powering the vehicle **200**, in one example, without an explosion between air (e.g., any of the ambient, pressurized, boosted, and expanded and cooled air) and other gases, liquids, or solids. Rather, the disclosed concept relies on a safe heat exchange between energy in the air and electricity.

[0065] Although the disclosed concept has been described in association with the transportation system being in the form of the vehicle **200**, which is an automobile, it will be appreciated that suitable alternative transportation systems are within the scope of the disclosed concept, including non-sedan automobiles such as sports-utility-vehicles and trucks, as well as buses, trains, large or

small ships, and the like, wherein each of these transportation systems may have an electric motor electrically connected to the A/C system **100**, and elements coupled to and configured to be driven by the electric motor.

[0066] Accordingly, it will be appreciated that one method of delivering expanded and cooled air to an environment with the A/C system comprises the steps of pulling in ambient air and generating pressurized air from the ambient air, with the air compressor **110**; delivering the pressurized air to a turboexpander **120** of the A/C system **100**; generating boosted air with the turboexpander from the pressurized air from the air compressor **110**; after the boosted air has been generated by the turboexpander **120**, generating the expanded and cooled air from the boosted air with the turboexpander **120**, and also creating mechanical work in a generator **140** of the air conditioning system **100** which is coupled to the turboexpander **120**, in order to generate electricity for powering the air compressor **110** and/or an electrical apparatus **180**; and at the blower **150**, receiving the expanded and cooled air from the turboexpander **120** and delivering the expanded and cooled air to the environment.

[0067] It will also be appreciated that the method may further comprise providing with the air compressor **110** the inlet **111** for receiving the ambient air; providing with the turboexpander **120** the outlet **134** through which the expanded and cooled air exits the turboexpander **120**; providing with the blower **150** an inlet for receiving the expanded and cooled air from the outlet **134** of the turboexpander **120**; and providing the A/C system with a recirculation conduit **139** fluidly coupled to each of the outlet **134** of the turboexpander **120**, the inlet **137** of the blower **150**, and the inlet **111** of the air compressor **110**; and recirculating a first amount of the expanded and cooled air back into the inlet **111** of the air compressor **110** after the first amount has exited the turboexpander **120**. The method may further include powering the operating system (e.g., the electrical apparatus **180**) of a building with the generator **140** while the blower **150** is delivering the expanded and cooled air to the interior of the building.

[0068] Referring again to FIG. 2, and also FIGS. 3 and 4 which include the A/C system **100**, additional operation of the A/C system **100** will now be described. In one example, it will be appreciated that the compressor wheel **124** is coupled to the drive shaft **122** and is fluidly coupled to the air compressor **110** such that the pressurized air from the air compressor **110** is configured to be forced through a conduit **112** (e.g., wherein the conduit **112** includes the outlet **113** and the inlet **128**, and may be a pipe, such as a closed pipe or continuous closed pipe, which has one single lumen extending from a first open end to a second open end) extending between the air compressor **110** and the compressor wheel **124**, and into the compressor wheel **124**, thereby providing a source of kinetic energy, optionally a sole source of kinetic energy, to directly cause the compressor wheel **124** to rotate and generate the boosted air from the pressurized air.

[0069] The conduit **112** is different than arrangements of known technologies in that it allows for the pressurized air to provide this source of kinetic energy. In accordance with the disclosed concept, the conduit **112** advantageously is configured to receive at least 98 percent of the pressurized air therethrough for delivery to the compressor wheel **124**. Additionally, the air compressor **110** may be configured to discharge the pressurized air at a first pressure, and the pressurized air is preferably configured to be received at the compressor wheel **124** at a second pressure equal to at least 95 percent of the first pressure (e.g., due to the conduit **112**).

[0070] Furthermore, and continuing to refer to FIG. 2, the expander wheel **126** is preferably coupled to the drive shaft **122** and fluidly coupled to both the compressor wheel **124** and the blower **150** such that the boosted air from the compressor wheel **124** is configured to be received in the expander wheel **126** and directly cause the expander wheel **126** and the drive shaft **122** to rotate together with the compressor wheel **124** (e.g., the drive shaft **122** and the wheels **124,126** all rotate at the same angular velocity), thereby generating expanded and cooled air in the expander wheel **126**.

[0071] It will also be appreciated that the air conditioning system is configured such that the

expander wheel **126** and the drive shaft **122** rotate together with the compressor wheel **124** via the pressurized air, and the mechanical work is created in the generator **140**, without the turboexpander **120** being driven by a combustion reaction involving burning of fuel by an apparatus directly connected to the turboexpander **120** or by an apparatus indirectly connected thereto via intermediate components. For example, the pressurized air is configured to provide the source of kinetic energy to directly cause the compressor wheel **124** to rotate and generate the boosted air from the pressurized air without the pressurized air being mixed with fuel from a combustion reaction before being received in the turboexpander **120**. As a result, it is contemplated that all of the pressurized, boosted, and expanded and cooled air are non-toxic to humans and are thus breathable. This is distinct from many known technologies employing turboexpanders, such as in airplanes, in which air is mixed with fuel for directly or indirectly driving the turboexpander. Additionally, it will be appreciated that the turboexpander **120** of the air conditioning system **100** is preferably not configured to be driven by any gases other than air.

[0072] Additionally, as stated above, the expander wheel **126** is configured to create mechanical work in the generator **140** responsive to rotation of the drive shaft **122** in order to generate electricity for charging the energy storage device **145** and thereby powering at least one of the air compressor motor **119** and a separate electrical apparatus (e.g., the electric motor **280**). Thus, the energy storage device **145** is configured to be charged by recycled energy from both the energy storage device **145** and the ambient air after the ambient air has been pressurized by the air compressor **110** and boosted by the compressor wheel **124**.

[0073] Additionally, in one example the A/C system **100** includes desirable apparatus to allow the A/C system **100** to operate at relatively low temperatures. These apparatus include the moisture separator **114**, discussed above, and a carbon dioxide removal system (“CO₂ RS”) **116**. The moisture separator **114** is fluidly coupled to the conduit **112** and is configured to remove moisture from the pressurized air before the pressurized air is delivered to the compressor wheel **124**, thereby allowing the A/C system **100** to generate the expanded and cooled air at a temperature below a freezing temperature of water. Moreover, the carbon dioxide removal system **116** is preferably coupled to the conduit **112** after the moisture separator **114** and is configured to remove carbon dioxide from the pressurized air after the moisture has been removed by the moisture separator **114**, and before the pressurized air is delivered to the compressor wheel **124**, thereby allowing the A/C system **100** to generate the expanded and cooled air at another temperature below a freezing temperature of carbon dioxide. Because the moisture separator **114** and the carbon dioxide removal system **116** are uniquely configured to allow the expanded and cooled air to exit the expander wheel **126** at low temperatures, these two elements also advantageously allow the A/C system **100** to operate with a relatively large pressure drop across the expander wheel **126**.

[0074] Continuing to refer to FIG. 2, it will be appreciated that the A/C system **100** further includes an additional conduit **131**, one including the outlet **130** associated with the compressor wheel **124** and the inlet **132** associated with the expander wheel **126**, such that the conduit **131**, which may be a pipe, preferably has a first open end at the compressor wheel **124**, a second open end at the expander wheel **126**, and a closed portion extending therebetween such that the pipe has one single lumen extending from at the compressor wheel **124** to at the expander wheel **126**. As a result of the conduit **131**, the boosted air is allowed to flow directly from the compressor wheel **124** into the expander wheel **130**.

[0075] FIG. 5 depicts another A/C system **300** similar to the A/C system **100** (FIG. 2), shown without a vent stack, ductwork, or control system for ease of illustration and economy of disclosure, and wherein like numbers represent like features. For example, the A/C system **300** preferably includes a moisture separator **314**, a carbon dioxide removal system **316**, a turboexpander **120** (e.g., and drive shaft **322**, and associated compressor and expander wheels **324,326** coupled to the drive shaft **322**), outlets **330,334**, inlets **328,332,337**, a vent conduit **338**, a recirculation conduit **339**, a heating element **339-2**, a generator **340**, an energy storage device **345**

(e.g., without limitation, a battery, a capacitor, or another type of energy storage device), a blower **350**, and is configured such that energy storage device **345** may separately charge/power an electrical apparatus **380** (e.g., an electric motor of a transportation system). These elements function in a similar manner as like components described in association with the A/C system **100**, and as such, for economy of disclosure, not all functionality of the A/C system **300** will be described herein.

[0076] In accordance with the disclosed concept, the A/C system **300** preferably also includes a rotation driving device **400** coupled to the drive shaft **322**, and configured to cause (e.g., without limitation, directly cause) the drive shaft **322** to rotate. The rotation driving device **400** preferably engages the drive shaft **322** (e.g., is directly connected thereto), but other arrangements are contemplated (e.g., wherein a suitable alternative rotation driving device is coupled to a suitable alternative drive shaft via a belt). In one example, the drive shaft **322** is a unitary component, optionally made of a single piece of material, and the generator **340** and the rotation driving device **400** may both be directly coupled to the drive shaft **322**, and may also be indirectly coupled to the drive shaft **322**. As a result of the coupling between the drive shaft **322**, the generator **340**, and the rotation driving device **400**, benefits of the disclosed concept, including efficient operation as caused by imparting of kinetic energy from the rotation driving device **400** to the turboexpander **320**, and simultaneous generation of power and air conditioning, are configured to be realized.

[0077] Continuing to refer to FIG. 5, the rotation driving device **400** is preferably an electric motor that is configured to be powered by the energy storage device **345**, although it will be appreciated herein that alternative rotation driving devices are contemplated. The rotation driving device **400** can be understood as providing a source of kinetic energy to cause the compressor wheel **324** to rotate and generate pressurized air. Further yet, the source of kinetic energy of the rotation driving device **400** (e.g., an electric motor) is configured to cause the expander wheel **326** to rotate together with the compressor wheel **324** independent of an impact of the pressurized air.

[0078] When the compressor wheel **324** rotates, it pulls in ambient air via the inlet **328**. In other words, the A/C system **300** preferably is configured such that the ambient air is pulled in through the inlet **328**, which is associated with the compressor wheel **324** such that the ambient air directly enters the compressor wheel **324**. As the ambient air is being pulled in through the inlet **328**, the ambient air preferably passes through an air filter **329** (shown in simplified form in FIG. 5) of the A/C system **300** that is coupled to the inlet **328**. In this manner, the ambient air preferably enters the compressor wheel **324** at a pressure and temperature that is the same as the pressure and temperature of the ambient air at a distal end of the inlet **328** where the ambient air first enters the A/C system **300**.

[0079] In the example of FIG. 5, the inlet **328**, which preferably has a valve on it (shown but not labeled), is configured to be in an open state, thereby allowing the ambient air to be received therethrough, and passed into the compressor wheel **324**. As such, unlike the A/C system **100** (FIG. 2) in which the air compressor **110** (FIG. 2) pulls in ambient air, in the A/C system **100** (FIG. 2) the compressor wheel **324** is configured to pull in ambient air and generate pressurized air from the ambient air responsive to rotation of the drive shaft **322** (e.g., as caused by the rotation driving device **400**).

[0080] As such, the A/C system **300** subsequently works as follows. The expander wheel **326**, which is coupled to the drive shaft **322** and fluidly coupled to the compressor wheel **324**, is configured such that the pressurized air from the compressor wheel **324** is configured to be received in the expander wheel **326** and converted into expanded and cooled air by the expander wheel **326** for delivery to an environment. Furthermore, the expander wheel **326** and the generator **340** (e.g., which is electrically connected to the energy storage device **345**) are configured to convert both the source of kinetic and energy in the ambient air into mechanical energy of the drive shaft **322**, and then convert the mechanical energy of the drive shaft **322** into electrical energy in the generator **340** for charging the energy storage device **345**, and thereby powering (e.g., charging)

the rotation driving device **400** (e.g., and also the other electrical apparatus **380**, which may be an electric motor **580**, as shown in FIG. 6).

[0081] Accordingly, the rest of the A/C system **300**, as discussed above, functions similar to the A/C system **100** (FIG. 2). That is, the turboexpander **320** does not rotate due to a combustion reaction involving burning of fuel by an apparatus indirectly connected to the turboexpander **320** via intermediate components, and the turboexpander **320** does not rotate due to a combustion reaction involving burning of fuel by an apparatus directly connected to the turboexpander **320**. Additionally, the source of kinetic energy applied to the drive shaft **322** by the rotation driving device **400** may be a sole source of kinetic energy to directly cause the compressor wheel **324** to rotate, the A/C system **300** is preferably a coolant-free A/C system **300** like the A/C system **100** (FIG. 2), and the energy storage device **345** is preferably configured to be charged by recycled energy from both the energy storage device **345** and the energy in the ambient air after the ambient air has been pressurized by the compressor wheel **324**. The conduit **331**, which is fluidly coupled to the compressor wheel **324** and the expander wheel **326**, preferably extends from at the compressor wheel **324** to at the expander wheel **326**, thus allowing the pressurized air to flow directly from the compressor wheel **324** into the expander wheel **326**, and the conduit **331** may include a pipe having a first open end at the compressor wheel **324**, a second open end at the expander wheel **326**, and a closed portion extending therebetween such that the pipe has a single lumen extending between the first and second open ends.

[0082] However, unlike the A/C system **100** (FIG. 2), the A/C system **300** is configured with different positioning for the moisture separator **314** and the carbon dioxide removal system **316**, namely because the A/C system **300** is preferably devoid of an air compressor other than the compressor wheel **324**. That is, the compressor wheel **324** may be configured to act as a sole air compressor for the A/C system **300**. As such, the moisture separator **314** is preferably fluidly coupled to the conduit **331** and configured to remove moisture from the pressurized air before the pressurized air is delivered to the expander wheel **326**, thereby allowing the A/C system **300** to generate the expanded and cooled air at a temperature below a freezing temperature of water. Additionally, the carbon dioxide removal system **316** is preferably fluidly coupled to the conduit **331** after the moisture separator **314** and is configured to remove carbon dioxide from the pressurized air after the moisture has been removed by the moisture separator **314** and before the pressurized air is delivered to the expander wheel **326**, thereby allowing the A/C system **300** to generate the expanded and cooled air at a temperature below a freezing temperature of carbon dioxide.

[0083] Moreover, as the A/C system **300** is preferably devoid of a separate air compressor other than the compressor wheel **324**, the recirculation conduit **339** is configured differently than in the A/C system **100** (FIG. 2). For example, the recirculation conduit **339** is preferably configured to discharge directly into the compressor wheel **324**.

[0084] More specifically, as shown in FIG. 4, the blower **350** is fluidly coupled to the expander wheel **326** and configured to receive the expanded and cooled air from the expander wheel **326** and deliver the expanded and cooled air to an environment. The inlet **328** associated with the compressor wheel **324** is configured to receive the ambient air before the ambient air is pulled into the compressor wheel **324**. Additionally, the recirculation conduit **339** is preferably fluidly coupled to each of the outlet **334** of the turboexpander **320**, the inlet **337** of the blower **350**, and the inlet **328** associated with the compressor wheel **324** in order to recirculate a first amount of the expanded and cooled air back into the inlet **328** associated with the compressor wheel **324** after the first amount has exited the turboexpander **320**.

[0085] FIG. 6 is an example transportation system **500**, according to one embodiment of the disclosed concept. The transportation system **500** is configured similar to the transportation system **200** (FIG. 4), and like numbers represent like features. Specifically, the transportation system **500** includes an electric motor **580**, at least one element (shown but not labeled) coupled to and

configured to be driven by the electric motor **580** in order to move the transportation system **500** between an IDLING state corresponding to the transportation system **500** being turned on and not moving, and an OPERATING state corresponding to the transportation system **500** being turned on and moving. Additionally, the transportation system **500** preferably also includes the A/C system **300**, wherein the energy storage device **345** (FIG. 5) of the A/C system **300** may be a primary energy storage device, such as a battery, of the transportation system **500**. In this manner, the transportation system **500** can be understood as including a plurality of different rotation driving devices (e.g., the rotation driving device **400**, which may be an electric motor, and the electric motor **580**), each of which may be powered by the energy storage device **345**, and wherein the generator **340** may be configured to re-charge the energy storage device **345** with recycled energy from both the energy storage device **345** and additional energy in the ambient air.

[0086] Accordingly, it will be appreciated that one method of delivering expanded and cooled air to an environment with the A/C system **300** comprises the steps of pulling in ambient air and generating pressurized air from the ambient air, with the air compressor wheel **324** of the turboexpander **320**; delivering the pressurized air to the expander wheel **326** via the conduit **331**; generating expanded and cooled air from the pressurized air with the expander wheel **326**, and also creating mechanical work in the generator **340**, in order to generate electricity for powering the rotation generating device **400** and/or the electrical apparatus **380** (e.g., via the energy storage device **345**); and optionally, at the blower **350**, receiving the expanded and cooled air from the turboexpander **320** and delivering the expanded and cooled air to the environment.

[0087] While the present disclosure has been described with reference to various implementations, it will be understood that these implementations are illustrative and that the scope of the disclosure is not limited to them. Many variations, modifications, additions, and improvements are possible. More generally, implementations in accordance with the present disclosure have been described in the context of particular implementations. Functionality can be separated or combined in blocks differently in various implementations of the disclosure or described with different terminology. These and other variations, modifications, additions, and improvements can fall within the scope of the disclosure as defined in the claims that follow.

Claims

1. (canceled)
2. The air conditioning system according to claim **21**, wherein the rotation driving device is an electric motor.
3. The air conditioning system according to claim 2, wherein the turboexpander does not rotate due to a combustion reaction involving burning of fuel by an apparatus indirectly connected to the turboexpander via intermediate components, and wherein the turboexpander does not rotate due to a combustion reaction involving burning of fuel by an apparatus directly connected to the turboexpander.
4. The air conditioning system according to claim 2, wherein the electric motor engages the drive shaft.
5. (canceled)
6. The air conditioning system according to claim 2, further comprising a moisture separator, a carbon dioxide removal system, and a conduit, wherein the conduit is fluidly coupled to the compressor wheel and the expander wheel, wherein the moisture separator is fluidly coupled to the conduit and configured to remove moisture from the second air before the second air is delivered to the expander wheel, thereby allowing the air conditioning system to generate the third, expanded and cooled air at a temperature below a freezing temperature of water, and wherein the carbon dioxide removal system is fluidly coupled to the conduit after the moisture separator and is configured to remove carbon dioxide from the second air after the moisture has been removed by

the moisture separator and before the second air is delivered to the expander wheel, thereby allowing the air conditioning system to generate the third, expanded and cooled air at a temperature below a freezing temperature of carbon dioxide.

7. (canceled)

8. (canceled)

9. The air conditioning system according to claim 2, further comprising an inlet associated with the compressor wheel, a recirculation conduit, and a blower, wherein the blower is fluidly coupled to the expander wheel and configured to receive the third, expanded and cooled air from the expander wheel and deliver the third, expanded and cooled air to the environment, wherein the turboexpander further comprises an outlet through which the third, expanded and cooled air exits the expander wheel, wherein the blower has an inlet for receiving the third, expanded and cooled air from the outlet of the turboexpander, wherein the recirculation conduit is fluidly coupled to each of the outlet of the turboexpander, the inlet of the blower, and the inlet associated with the compressor wheel in order to recirculate a first amount of the third, expanded and cooled air back into the inlet associated with the compressor wheel after the first amount has exited the turboexpander.

10. (canceled)

11. (canceled)

12. (canceled)

13. (canceled)

14. (canceled)

15. (canceled)

16. (canceled)

17. The transportation system according to claim 28, wherein the electric motor is a first electric motor, and wherein the rotation driving device is a second electric motor.

18. The transportation system according to claim 17, wherein the at least one element comprises a first axle and a second axle, wherein the transportation system further comprises a first pair of wheels coupled to the first axle, and a second pair of wheels coupled to the second axle, and wherein the first electric motor is coupled to and configured to drive the first and second axles, thereby allowing the first and second pairs of wheels to roll when the transportation system is in the OPERATING state.

19. The transportation system according to claim 17, wherein the turboexpander does not rotate due to a combustion reaction involving burning of fuel by an apparatus indirectly connected to the turboexpander via intermediate components, and wherein the turboexpander does not rotate due to a combustion reaction involving burning of fuel by an apparatus directly connected to the turboexpander.

20. The transportation system according to claim 17, wherein the second electric motor engages the drive shaft.

21. An air conditioning system, comprising: a rotation driving device; and a turboexpander, comprising: a drive shaft coupled to the rotation driving device, and configured to be rotated by the rotation driving device, a compressor wheel coupled to the drive shaft and configured to receive first air and generate second air from the first air in a manner wherein the rotation driving device provides a source of kinetic energy to cause the compressor wheel to rotate and pressurize the first air, and an expander wheel coupled to the drive shaft such that the source of kinetic energy is configured to cause the expander wheel to rotate together with the compressor wheel, wherein the expander wheel is fluidly coupled to the compressor wheel, thereby allowing the second air from the compressor wheel to be received in the expander wheel and, responsive to energy being removed from the second air, converted into third, expanded and cooled air by the expander wheel for delivery to an environment.

22. The air conditioning system according to claim 21, further comprising a conduit comprising an

outlet associated with the compressor wheel and an inlet associated with the expander wheel, such that the conduit extends from at the compressor wheel to at the expander wheel, thus allowing the second air to flow directly from the compressor wheel into the expander wheel.

23. The air conditioning system according to claim 22, wherein the air conditioning system is a coolant-free air conditioning system.

24. The air conditioning system according to claim 23, wherein the turboexpander does not rotate due to a combustion reaction involving burning of fuel by an apparatus indirectly connected to the turboexpander via intermediate components, and wherein the turboexpander does not rotate due to a combustion reaction involving burning of fuel by an apparatus directly connected to the turboexpander.

25. The air conditioning system according to claim 22, wherein the conduit comprises a pipe having a first open end at the compressor wheel and a second open end at the expander wheel such that the pipe has a single lumen extending between the first and second open ends.

26. The air conditioning system according to claim 22, wherein the second air is configured to exit the compressor wheel at a first temperature and enter the expander wheel at a second temperature substantially the same as the first temperature.

27. The air conditioning system according to claim 21, further comprising an energy storage device for powering the rotation driving device, and a generator electrically connected to the energy storage device, wherein the drive shaft is coupled to the generator, and wherein the expander wheel and the generator are configured to convert both the source of kinetic energy and energy in the first air into mechanical energy of the drive shaft, and then convert the mechanical energy of the drive shaft into electrical energy in the generator for charging the energy storage device, and thereby powering the rotation driving device.

28. A transportation system, comprising: an electric motor; at least one element coupled to and configured to be driven by the electric motor in order to move the transportation system between an IDLING state corresponding to the transportation system being turned on and not moving, and an OPERATING state corresponding to the transportation system being turned on and moving; and air conditioning system, comprising: a rotation driving device, an energy storage device for powering both the rotation driving device and the electric motor, a generator electrically connected to the energy storage device, and a turboexpander, comprising: a drive shaft coupled to both the generator and the rotation driving device, and configured to be rotated by the rotation driving device, a compressor wheel coupled to the drive shaft and configured to receive first air and generate second air from the first air in a manner wherein the rotation driving device provides a source of kinetic energy to cause the compressor wheel to rotate and pressurize the first air, and an expander wheel coupled to the drive shaft such that the source of kinetic energy is configured to cause the expander wheel to rotate together with the compressor wheel, wherein the expander wheel is fluidly coupled to the compressor wheel, thereby allowing the second air from the compressor wheel to be received in the expander wheel and, responsive to energy being removed from the second air, converted into third, expanded and cooled air by the expander wheel for delivery to an environment, and wherein the expander wheel and the generator are configured to convert both the source of kinetic energy and energy in the first air into mechanical energy of the drive shaft, and then convert the mechanical energy of the drive shaft into electrical energy in the generator for charging the energy storage device, and thereby powering the rotation driving device.
