

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12384562
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Guo; Jinsheng et al.

System and method for capturing space target

Abstract

Disclosed are a system and a method for capturing a space target. The system includes a plurality of capturing devices, a delivery device, a launching device, and a deceleration and recovery device, each of the plurality of capturing devices is configured to be launched into a target orbit to capture a defunct space target, the delivery device is configured to deliver, along a preset delivery trajectory, each of the plurality of capturing devices to a first preset location in the launching device, the launching device is configured to launch each of the plurality of capturing devices located at the first preset location into the target orbit to capture the defunct space target, and the deceleration and recovery device is configured to decelerate each of the plurality of capturing devices after it is launched and flies a preset distance.

Inventors: Guo; Jinsheng (Harbin, CN), Wu; Fan (Harbin, CN), Qiu; Shi (Harbin, CN), Chen; Jian (Harbin, CN), Wei; Cheng (Harbin, CN), Wang; Hongxu (Harbin, CN)

Applicant: Harbin Institute of Technology (Harbin, CN)

Family ID: 82076729

Assignee: Harbin Institute of Technology (Harbin, CN)

Appl. No.: 18/390259

Filed: December 20, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240116655 A1	Apr. 11, 2024

Foreign Application Priority Data

CN	202210302809.4	Mar. 24, 2022
----	----------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/CN2023/081155 20230313 PENDING child-doc US 18390259

Publication Classification

Int. Cl.: **B64G1/10** (20060101)

U.S. Cl.:

CPC **B64G1/1081** (20230801);

Field of Classification Search

CPC: B64G (1/1081); B64G (1/1078); B64G (1/222)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6789536	12/2003	Summers	N/A	N/A
2002/0079407	12/2001	Lounge et al.	N/A	N/A
2014/0367523	12/2013	Kitazawa	244/158.4	B64G 1/6462

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102991731	12/2012	CN	N/A
103072142	12/2012	CN	N/A
103863583	12/2013	CN	N/A
109353550	12/2018	CN	N/A
109969433	12/2018	CN	N/A
110435927	12/2018	CN	N/A
110450989	12/2018	CN	N/A
112455731	12/2020	CN	N/A
113895662	12/2021	CN	N/A
114674179	12/2021	CN	N/A
2014210572	12/2013	JP	N/A

OTHER PUBLICATIONS

First Office Action issued in counterpart Chinese Patent Application No. 202210302809.4, dated Nov. 23, 2023. cited by applicant

International Search Report and Written Opinion issued in corresponding PCT Application No. PCT/CN2023/081155, dated May 29, 2023. cited by applicant

Primary Examiner: Berona; Kimberly S

Assistant Examiner: Aleksic; Nevena

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) The present application is a continuation of International Patent Application No. PCT/CN2023/081155, filed on Mar. 13, 2023, which claims priority to Chinese Patent Application No. 202210302809.4, filed on Mar. 24, 2022. The disclosures of these applications are hereby incorporated by reference in their entireties.

TECHNICAL FIELD

(1) The present application relates to the technical field of aerospace, and particularly to a system and a method for capturing a space target.

BACKGROUND

(2) With the rapid increase in the number of space crafts in space orbit, the number of defunct space crafts in space orbit has also surged. It is urgent to capture and remove these defunct space crafts in the field of aerospace. The defunct space crafts in space orbit may be captured by space webs, a space robotic arm, or a space harpoon. Moreover, the defunct space crafts in space orbit may be captured through rendezvous and docking (RVD) with a tracking spacecraft. When the defunct space crafts are captured by the space webs, an onboard spacecraft can only carry a limited number of the space webs and thus the capturing efficiency is relatively low. When the defunct space crafts are captured by the space robotic arm, the space robotic arm has a large mass and thus the onboard spacecraft needs a large overload, and the cost of the space robotic arm is also significant. Moreover, when the defunct space crafts are captured by the space robotic arm, orbit control may be performed in a high precision and the reliability of the onboard spacecraft may be affected by the reliability of the space robotic arm. Due to strict technical requirements, it is difficult to capture the defunct space crafts in space orbit through rendezvous and docking (RVD) with the tracking spacecraft. Although it is simple and reliable to capture the defunct space crafts by the space harpoons, lightweight design of the space harpoons may be considered. The space harpoons may be prevented to rebound and damage the onboard spacecraft. Multiple of the space harpoons may be prevented to repeatedly capture the same defunct spacecraft.

SUMMARY

(3) The disclosure provides a system and a method for capturing a space target. According to the system and method, defunct space targets are captured and then towed to a decay orbit with low capturing cost and high capturing efficiency.

(4) The technical solution of the disclosure is implemented as follows.

(5) According to a first aspect of the disclosure, a system for capturing a space target is provided. The system includes a plurality of capturing devices, a delivery device, a launching device, and a deceleration and recovery device.

(6) Each of the plurality of capturing devices is configured to be launched into a target orbit to capture a defunct space target.

(7) The delivery device is configured to deliver, along a preset delivery trajectory, each of the plurality of capturing devices to a first preset location in the launching device.

(8) The launching device is configured to launch each of the plurality of capturing devices located at the first preset location into the target orbit to capture the defunct space target.

(9) The deceleration and recovery device is configured to decelerate each of the plurality of capturing devices after it is launched and flies a preset distance.

(10) According to a second aspect of the disclosure, a method for capturing a space target is provided. The method may be applied to the system according to the first aspect. The method includes the followings operations: delivering, by the delivery device, along a preset delivery

trajectory, each of the plurality of capturing devices to the first preset location in the launching device; launching, by the launching device, each of the plurality of capturing devices located at the first preset location into the target orbit to capture the defunct space target; and decelerating, by the deceleration and recovery device, each of the plurality of capturing devices after it is launched and flies a preset distance.

(11) According to the disclosure, a system and a method for capturing a space target is provided. The delivery device delivers the plurality of capturing devices to the first preset location in the launching device along the preset delivery trajectory. The launching device may launch the capturing device located at the first preset location to capture the defunct space target. After the capturing device is launched and flies the preset distance, the deceleration and recovery device decelerates the capturing device and prevents the capturing device from rebounding to cause damage to an onboard spacecraft. The system according to the disclosure may capture the defunct space targets of different sizes and types, including the defunct space targets that are difficult to capture using traditional space robotic arm or space-webs. The system according to the disclosure has strong adaptability and high capturing efficiency.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) To better explain the disclosure, the figures referred in the description of the disclosure will be briefly introduced. The figures in the following description are only examples of the disclosure.
- (2) FIG. 1 is a diagram of the structure of a system for capturing a space target according to the disclosure.
- (3) FIG. 2 is atop view of the structure of the system for capturing the space target according to the disclosure.
- (4) FIG. 3 is a side view of the structure of the system for capturing the space target according to the disclosure.
- (5) FIG. 4 is a diagram of the structure of a capturing device according to the disclosure.
- (6) FIG. 5 is a diagram of the structure of a deceleration axis with an internal heating device according to the disclosure.
- (7) FIG. 6 is a diagram of the structure of a delivery device according to the disclosure.
- (8) FIG. 7 is a partial enlarged diagram of part I shown in FIG. 6.
- (9) FIG. 8 is a diagram of the structure of a launching device according to the disclosure.
- (10) FIG. 9 is a diagram of the internal structure of the launching device according to the disclosure.
- (11) FIG. 10 is a diagram of the structure of a second transmission gear according to the disclosure.
- (12) FIG. 11 is a diagram of the structure of a deceleration and recovery device according to the disclosure.
- (13) FIG. 12 is a diagram of a partial structure in the deceleration and recovery device according to the disclosure.
- (14) FIG. 13 is a schematic diagram of the process of a method for capturing the space target according to the disclosure.

DETAILED DESCRIPTION OF THE EMBODIMENTS

(15) To make the objectives, technical solutions, and advantages of the disclosure more apparent, the following will describe in detail the example embodiments according to the disclosure, with reference to the accompanying drawings. Obviously, the described embodiments are just part of the embodiments of the disclosure, not all of the embodiments. It should be understood that the disclosure is not limited by the example embodiments described here.

(16) FIG. 1 is a diagram of a structure of a system 1 for capturing a space target according to the

disclosure. The system **1** includes a plurality of capturing devices **11**, a delivery device **12**, a launching device **13**, and a deceleration and recovery device **14**.

(17) Each of the plurality of capturing devices **11** is configured to be launched into a target orbit to capture a defunct space target.

(18) The delivery device **12** is configured to deliver each of the plurality of capturing devices **11** to a first preset location in the launching device **13** along a preset delivery trajectory.

(19) The launching device **13** is configured to launch each of the plurality of capturing devices **11** located at the first preset location into the target orbit to capture the defunct space target.

(20) The deceleration and recovery device **14** is configured to decelerate each of the plurality of the capturing devices **11** after it is launched and flies a preset distance.

(21) In an embodiment of the disclosure, the defunct space targets are not limited to the defunct space crafts, but also include space debris.

(22) Moreover, the shape of the preset delivery trajectory is not limited to a coiled shape shown in FIGS. **1** and **2**. Other forms or shapes of the delivery trajectories may also be applied to the system **1** of the disclosure.

(23) For the system **1** shown in FIG. **1**, the delivery device **12** delivers the plurality of capturing devices **11** to the first preset location in the launching device **13** along the preset delivery trajectory. The launching device **13** may launch the capturing device **11** located at the first preset location to capture the defunct space target. After the capturing device **11** is launched and flies the preset distance, the deceleration and recovery device **14** decelerates the capturing device **11** and prevents the capturing device **11** from rebounding to cause damage to an onboard spacecraft. The system **1** according to the disclosure may capture the defunct space targets of different sizes and types, including the defunct space targets that are difficult to capture using traditional space robotic arm or space-webs. The system **1** according to the disclosure has strong adaptability and high capturing efficiency.

(24) The components of the capturing devices **11** are made of a biodegradable material. Therefore, in the case that the capturing devices **11** and the defunct space targets are towed into the predetermined decay orbit, the capturing devices **11** can be fully degraded.

(25) In an embodiment of the disclosure, the system **1** shown in FIG. **1** may be mounted on the surface of other space crafts (not shown in FIG. **1**), such as a satellite, and thus the system **1** may fly into a predetermined space orbit by mounting on the satellite and execute a capturing task.

(26) When the capturing device **11** hits the defunct space target, the defunct space target travels with the onboard spacecraft to the predetermined decay orbit. The capturing task of towing the defunct space target from an initial space orbit to the predetermined decay orbit is accomplished.

(27) The system **1** shown in FIG. **1** can carry **200** capturing devices **11** to execute **200** capturing tasks, which saves launching cost by avoiding repeatedly launching the system **1** from a ground station. Moreover, the system **1** in an embodiment of the disclosure may fly into the space orbit by mounting on the satellite weighing up to 300 kilograms to execute the capturing tasks in space orbit with low capturing cost and high capturing efficiency. According to another embodiment of the disclosure, the number of the capturing device **11** may be adjusted according to the actual requirements, and the number of the capturing device is not limited to 200.

(28) When the assembly of the system **1** is completed, as shown in FIGS. **2** and **3**, the maximum radial diameter of the system **1** does not exceed 1000 millimeters, and maximum height of the system **1** does not exceed 210 millimeters. Hence, the system **1** is small in size and light in mass, realizing a lightweight design.

(29) For the system **1** shown in FIG. **1**, in some possible implementations, the deceleration and recovery device **14** is further configured to recover the capturing device **11** into the launching device **13** when the capturing device **11** fails to hit the defunct space target. When the capturing device **11** does not hit the defunct space target, the capturing device **11** may be decelerated and recovered into the launching device **13** by the deceleration and recovery device **14**. The capturing

device **11** is re-launched to another target orbit to continue capturing other defunct space target.

(30) For the system **1** shown in FIG. **1**, in some possible implementations, as shown in FIG. **4**, each of the capturing devices **11** includes a head **111**, at least one barb unit **112**, a location unit **113**, a first rope **114** wound inside of the capturing device **11**, a deceleration shaft **115**, and a second rope **116** wound on the deceleration shaft **115**.

(31) The head **111** is pointed for piercing and inserting into the defunct space target.

(32) The barb unit **112** is configured to prevent the defunct space target from falling off when the defunct space target is towed.

(33) The location unit **113** is configured to acquire real-time location of the capturing device **11** to assist the capturing device **11** in moving to the first preset location.

(34) The second rope **116** is connected to the first rope **114**, and the second rope **116** decelerates the capturing device **11** to zero by gradually unwinding from the deceleration shaft **115** when the first rope **114** is fully unwound.

(35) In the specific implementation process, the components of the capturing device **11**, for example, the head **111**, the barb unit **112**, and the location unit **113**, can be detached from the system **1** and all be launched into the target orbit. In addition, when the capturing device **11** has been launched, the first rope **114** can gradually leave from the capturing device **11** and gradually unwound. When the capturing device **11** hits the defunct space target before the first rope **114** is fully unwound, the capturing device **11** will continue driving the first rope **114** to fly forward until the first rope **114** is fully unwound. When the first rope **114** is fully unwound, the first rope **114** will pull the second rope **116** to gradually unwind to decelerate the capturing device **11**. Naturally, when the first rope **114** is fully unwound and the capturing device **11** has not captured the defunct space target, the first rope **114** can also pull the second rope **116** to gradually unwind to decelerate the capturing device **11**. The first rope **114** and the second rope **116** may be the same rope, which are designed in segments. The first rope **114** is wound within the capturing device **11**, and the second rope **116** is wound on the deceleration shaft **115**. Such a design not only helps the capturing device **11** capture the defunct space target but also effectively decelerates the capturing device **11** to prevent the capturing device **11** from rebounding and damaging the onboard satellite.

(36) According to an embodiment of the disclosure, each of the capturing devices **11** has a weight of 0.5 kilograms, which is beneficial for the lightweight design of the system **1**. The length of the first rope **114** being 50 meters indicates that the system **1** can capture the defunct space target at a distance of 50 meters. Additionally, the length of the first rope **114** also determines the preset distance that the capturing device **11** can fly mentioned in the technical scheme.

(37) In some examples, as shown in FIG. **5**, a heating device **1151** is installed inside the deceleration shaft **115**, and the heating device **1151** is configured to heat the second rope **116** to fuse the second rope **116** when the defunct space target has been towed to the predetermined decay orbit. The heating device **1151** may be a power resistor.

(38) For the system **1** shown in FIG. **1**, in some possible implementations, as shown in FIG. **6**, the delivery device **12** includes a first frame **121**, a plurality of mounting brackets **122**, a plurality pairs of deceleration shaft holes **123**, a first transmission gear **124**, a first driving mechanism **125** connected to the first transmission gear **124**, a plurality of power contacts **126**, and a plurality of switch contacts **127**.

(39) The plurality of mounting brackets **122** are uniformly set on the upper side of the first frame **121**, and each of the capturing devices **11** is mounted on the corresponding mounting bracket **122**.

(40) The plurality pairs of deceleration shaft holes **123** are uniformly formed in the first frame **121** in a manner that each pair of deceleration shaft holes **123** are arranged on two lateral sides of the first frame **121**, and the deceleration shaft **115** is rotatably installed within the corresponding pair of deceleration shaft holes **123**.

(41) A bottom of the first frame **121** has an inverted T-shaped guide rail **1211**, as shown in FIG. **7**, and both transverse ends of the T-shaped guide rail **1211** are respectively provided with a first

transmission rack **128** engaging with the first transmission gear **124**.

(42) The first driving mechanism **125** is configured to rotate the first transmission gear **124** to translate the first transmission rack **128**, so that the plurality of capturing devices **11** may move along the preset delivery trajectory.

(43) The plurality of power contacts **126** are uniformly arranged on both sides of the first frame **121**, and the plurality of power contacts **126** provide electrical energy during the launching and deceleration and recovery process of the capturing device **11**.

(44) The plurality of switch contacts **127** are uniformly arranged on one side of the first frame **121**.

(45) In the detailed implementation process, the first driving mechanism **125** drives the first transmission gear **124** to engage with the first transmission rack **128**, thereby enabling the plurality of capturing devices **11** to sequentially advance until arriving at the first preset location in the launching device **13**. During the advancing movement of the capturing device **11**, the first driving mechanism **125** and the first transmission gear **124** remain stationary. The first frame **121** and other components mounted on the first frame **121**, such as the mounting bracket **122**, the deceleration shaft hole **123**, the power contact **126**, and the switch contact **127**, will move with the capturing device **11**. Additionally, the delivery device **12** is assembled in conjunction with the onboard satellite by the T-shaped guide rail **1211**.

(46) According to an embodiment of the disclosure, the delivery device **12** includes a plurality of transmission units. Each of the transmission units includes a mounting bracket **122**, two deceleration shaft holes **123** for installing the deceleration shaft **115**, two power contacts **126**, and a switch contact **127**. Each capturing device **11** corresponds to a transmission unit. During transmission process, each transmission unit moves with the corresponding capturing device **11**, cooperating to complete the launching tasks, decelerating and recovering the capturing device **11**.

(47) On the one hand, the first driving mechanism **125** is a stepper motor.

(48) On the other hand, the transmission path of the capturing device **11** depends on the shape of the first frame **121**, such as the coiled shape shown in FIG. 1.

(49) For the system **1** shown in FIG. 1, in some possible implementations as shown in FIGS. 8 and 9, the launching device **13** includes a second frame **131**, a launching chamber **132**, a launching bracket **133**, a second driving mechanism **134**, a second transmission mechanism **135**, a first elastic mechanism **136**, a guide rail **137**, a first travel switch **138**, a second travel switch **139**, and a conductive piece **140**.

(50) The launching chamber **132** having a semi-cylindrical shape, placed within the second frame **131**.

(51) The launching bracket **133** passes through the launching chamber **132**, and the launching bracket **133** is fixedly connected to the launching chamber **132**.

(52) The second driving mechanism **134** is configured to drive the second transmission mechanism **135**. When the capturing device **11** has not yet been delivered to the first preset location, the second driving mechanism **134** drives the second transmission mechanism **135** so that the launching bracket **133** and the launching chamber **132** move downwards along the guide rail **137** to the second preset location and compress the first elastic mechanism **136**. And when the capturing device **11** has been delivered to the first preset location, the second driving mechanism **134** continues to drive the second transmission mechanism **135** so that the first elastic mechanism **136** is released and the launching bracket **133** and the launching chamber **132** move upwards along the guide rail **137** under the action of the first elastic mechanism **136** and launch the capturing device **11**.

(53) The first travel switch **138** is configured to send a command to stop the transmission of the second transmission mechanism **135** when the launching bracket **133** and the launching chamber **132** have moved down to the second preset location so that the launching bracket **133** remains the stationary in the second preset location.

(54) The second travel switch **139** is configured to electrically connect with the switch contact **127**

to send a command to stop the advancing movement of the capturing device **11** when the capturing device **11** has been advanced to the first preset location, so that the capturing device **11** remains stationary in the first preset location.

(55) The conductive piece **140** is arranged on both sides of the second frame **131**, and the conductive piece is electrically connected to the power contacts **126** to supply electrical energy.

(56) Moreover, in an embodiment, the second driving mechanism **134** may be a stepper motor and it is connected to the power supply device of the onboard satellite (not shown in the figures).

(57) The first elastic mechanism **136** may be a spring that passes through the launching bracket **133**. The first elastic mechanism **136** is compressed during the downward movement of the launching bracket **133** and launching chamber **132**. After the capturing device **11** advances the first preset location, the bottom of the first elastic mechanism **136** can abut against the top of the mounting bracket **122**.

(58) For the aforementioned embodiments, in some examples, the second transmission mechanism **135** includes a second transmission gear **1351** and a second transmission rack **1352** engaging with the second transmission gear **1351**. And the second transmission gear **1351** is a semi-toothed structure. According to an embodiment of the disclosure, as shown in FIG. 8, the second transmission gear **1351** is connected to the second driving mechanism **134**, and the second transmission rack **1352** is fixedly set on one side of the launching bracket **133**. Therefore, when the capturing device **11** reaches the first preset location and aims at the defunct space target, the second driving mechanism **134** drives the second transmission mechanism **135** to deliver. And since the second transmission gear **1351** is the semi-toothed structure, the second transmission rack **1352** will be released during the transmission process, and then the launching bracket **133** and the launching chamber **132** move upwards under the elastic force of the first elastic mechanism **136**, thereby pushing the capturing device **11** out of the launching device **13** to complete the launching action. The spring force of the first elastic mechanism **136** is 2000 N, which allows the capturing device **11** weighting 0.5 kilograms to fly at a speed of 20 m/s. Therefore, the capturing device **11** may penetrate and insert into the defunct space target at high speed, such as the honeycomb sandwich structure of a defunct spacecraft.

(59) For the aforementioned embodiments, in some examples, as shown in FIG. 10, the second transmission mechanism **135** also includes a ratchet **1353** and a pawl **1354**. The ratchet **1353** is set inside the second transmission gear **1351**, and the pawl **1354** is connected to the second driving mechanism **134**. When the capturing device **11** has not been advanced to the first preset location, the power supply device on the satellite provides electrical energy to the second driving mechanism **134**, which in turn drives the second driving gear **1351** to engage with the second transmission rack **1352** for transmission, whereby the launching bracket **133** and the launching chamber **132** are lowered to the second preset location and compress the first elastic mechanism **136**, so that the first travel switch **138** is triggered. When the first travel switch **138** is triggered, the second driving mechanism **134** stops operating, at which time the pawl **1354** abuts against the outer peripheral wall of the ratchet **1353** to cause the transmission of the second transmission gear **1351** to stop driving and remain stationary in the current transmission location. Eventually, the launching bracket **133** and the launching chamber **132** remain stationary in the second preset location.

(60) When the capturing device **11** advances to the first preset location and the capturing device **11** is ready to launch, the location unit **113** in the capturing device **11** can abut against the launching chamber **132**. Therefore, under the action of elastic force of the first elastic mechanism **136**, the capturing device **11** is launched into the target orbit.

(61) Moreover, after the capturing device **11** located at the first preset location in the launching device **13** is launched, the delivery device **12** continues moving along the preset delivery trajectory. On the one hand, the mounting components corresponding to the launched capturing device **11** and other components, such as the mounting bracket **122** and the deceleration shaft **115**, are delivered out of the launching device **13**. On the other hand, the next capturing device **11** and its

corresponding mounting components are delivered to the launching device **13** to execute a next capturing task.

(62) For the system **1** shown in FIG. **1**, in some possible implementations, as shown in FIGS. **11** and **12**, the deceleration and recovery device **14** includes an electromagnetic valve **141**, a driving shaft **142**, a second elastic mechanism **143** wound on the driving shaft **142**, a magnetic damper **144**, and a third driving mechanism **145**.

(63) The electromagnetic valve **141** is configured to stop working when the capturing device **11** is delivered to the first preset location, allowing the second elastic mechanism **143** to push the driving shaft **142** to connect with the deceleration shaft **115**, and after the capturing device **11** is launched, the electromagnetic valve **141** attracts the driving shaft **142** to separate it from the deceleration shaft **115** after the capturing device **11** is launched. The driving shaft **142** is connected to the deceleration shaft **115** via a gear coupling **146**.

(64) The magnetic damper **144** is configured to generate damping force to damp the gradual unwinding process of the first rope **114** and the second rope **116** is unwound, so as to decelerate the capturing device **11**.

(65) The third driving mechanism **145** is connected to the magnetic damper **144**, and the third driving mechanism **145** is configured to pull the second rope **116** so that the deceleration shaft **115** rotate reversely, so as to recover the capturing device **11**.

(66) When the capturing device **11** advances to the first preset location and triggers the second travel switch **139**, the capturing device **11** stops advancing, and the electromagnetic valve **141** also stops working. At this time, the second elastic mechanism **143** pushes the driving shaft **142** so that the driving shaft **142** connects with the deceleration shaft **115**, and the damping torque is delivered between the driving shaft **142** and the deceleration shaft **115** through the gear coupling **146**. It should be understood that after the capturing device **11** is launched, the first rope **114** gradually unwinds and fully detaches from the capturing device **11**. When the first rope **114** continues to pull the second rope **116**, since the second rope **116** is wound on the deceleration shaft **115**, the deceleration shaft **115** rotates during the process of pulling the second rope **116**. Additionally, the deceleration shaft **115** is connected to the driving shaft **142** through the gear coupling **146**. Thus, when the magnetic damper **144** generates the damping force, its damping torque can be delivered to the deceleration shaft **115** via the driving shaft **142**. Hence, the magnitude of the damping torque can be obtained by measuring the real-time angular velocity of the deceleration shaft **115**, so as to decelerate flight speed of the capturing device **11** to zero before the second rope **116** is fully unwound. When the capturing device **11** hits the defunct space target, the defunct space target is towed to the decay orbit by the onboard spacecraft equipped with the system **1**. The heating device **117** on the deceleration shaft **115** can heat the second rope **116** to fuse the second rope **116** when the defunct space target has been towed to the predetermined decay orbit.

(67) For the above embodiments, in some examples, the gear coupling **146** includes a conical friction gear **1461** and a driven helical gear **1462**.

(68) In the specific implementation process, the third driving mechanism **145** may be a stepper motor. Furthermore, the connection method of the third driving mechanism **145** and the magnetic damper **144** is not limited to the series connection shown in FIG. **10**. And the connection method of the third driving mechanism **145** and the magnetic damper **144** may also be an integrated design.

(69) FIG. **13** is a schematic diagram of the process of a method for capturing the space target according to the disclosure. The method may be applied in the system **1** described in the aforementioned technical scheme. The method according to the embodiment includes operations **S1301** to **S1303**.

(70) In the operation **S1301**, the delivery device delivers, along a preset delivery trajectory, each of the plurality of capturing devices to the first preset location in the launching device.

(71) In the operation **S1302**, the launching device launches each of the plurality of capturing devices located at the first preset location into the target orbit to capture the defunct space target.

(72) In the operation S1303, the deceleration and recovery device decelerates each of the plurality of capturing devices after it is launched and flies a preset distance.

(73) Since the method illustrated in FIG. 13 may be applied to the system 1 described in the aforementioned technical scheme, the specific details of the method may refer to the detailed description of each component in the system 1 mentioned in the aforementioned technical scheme, which are not be elaborated here.

(74) Exemplarily, for the method shown in FIG. 13, in some possible implementations, the method also includes the following step.

(75) When the capturing device fails to hit the defunct space target, the capturing device may be recovered to the launching device.

(76) The above description is only specific embodiments of the disclosure, but the protection scope of the disclosure is not limited to this. Any alterations or substitutions that can be readily thought of by any person skilled in the art within the technical scope disclosed by the disclosure should all be covered within the protection scope of the disclosure. Therefore, the protection scope of the disclosure should be based on the protection scope of the claims.

Claims

1. A system for capturing a space target, comprising a plurality of capturing devices, a delivery device, a launching device, and a deceleration and recovery device, wherein each of the plurality of capturing devices is configured to be launched into a target orbit to capture a defunct space target; the delivery device is configured to deliver, along a preset delivery trajectory, each of the plurality of capturing devices to a first preset location in the launching device; the launching device is configured to launch each of the plurality of capturing devices located at the first preset location into the target orbit to capture the defunct space target; and the deceleration and recovery device is configured to decelerate each of the plurality of capturing devices after the capturing device is launched and flies a preset distance, wherein the capturing device comprises a head, at least one barb unit, a location unit, a first rope wound inside of the capturing device, a deceleration shaft, and a second rope wound on the deceleration shaft, wherein the head is pointed for piercing and inserting into the defunct space target; the barb unit is configured to prevent the defunct space target from falling off when the defunct space target is towed; the location unit is configured to acquire real-time location of the capturing device to assist the capturing device in moving to the first preset location; and the second rope is connected to the first rope, and the second rope decelerates a flight speed of the capturing device to zero by gradually unwinding from the deceleration shaft when the first rope is fully unwound, wherein the deceleration shaft further comprises a heating device, and the heating device is configured to heat the second rope to fuse the second rope when the defunct space target has been towed to a predetermined decay orbit.
2. The system according to claim 1, wherein the deceleration and recovery device is further configured to recover the capturing device into the launching device when the capturing device fails to hit the defunct space target.
3. The system according to claim 1, wherein the delivery device comprises a first frame, a plurality of mounting brackets, a plurality pairs of deceleration shaft holes, a first transmission gear, a first driving mechanism connected to the first transmission gear, a plurality of power contacts, and a plurality of switch contacts, wherein the plurality of mounting brackets are uniformly arranged on an upper side of the first frame, and each of the capturing devices is mounted on a corresponding one of the plurality of mounting brackets; the plurality pairs of deceleration shaft holes are uniformly formed in the first frame in a manner that each pair of deceleration shaft holes are arranged on two lateral sides of the first frame respectively, and the deceleration shaft is rotatably installed within the corresponding pair of deceleration shaft holes; a bottom of the first frame has an inverted T-shaped guide rail, and both transverse ends of the inverted T-shaped guide rail are

respectively provided with a first transmission rack engaging with the first transmission gear; the first driving mechanism is configured to rotate the first transmission gear to translate the first transmission rack, so that the plurality of capturing devices move along the preset delivery trajectory; the plurality of power contacts are uniformly arranged on both sides of the first frame, and the plurality of power contacts provide electrical energy during the launching and deceleration recovery process of the capturing device; and the plurality of switch contacts are uniformly arranged on one side of the first frame.

4. The system according to claim 3, wherein the launching device comprises a second frame, a launching chamber, a launching bracket, a second driving mechanism, a second transmission mechanism, a first elastic mechanism, a guide rail, a first travel switch, a second travel switch, and a conductive piece; the launching chamber having a semi-cylindrical shape, and is placed within the second frame; the launching bracket passes through the launching chamber, and the launching bracket is fixedly connected to the launching chamber; the second driving mechanism is configured to drive the second transmission mechanism, wherein, when the capturing device has not yet been delivered to the first preset location, the second driving mechanism drives the second transmission mechanism so that the launching bracket and the launching chamber move downwards along the guide rail to the second preset location and compress the first elastic mechanism, and when the capturing device has been delivered to the first preset location, the second driving mechanism continues to drive the second transmission mechanism so that the first elastic mechanism is released and the launching bracket and the launching chamber move upwards along the guide rail under the action of the first elastic mechanism and launch the capturing device; the first travel switch is configured to send a command to stop the transmission of the second transmission mechanism when the launching bracket and the launching chamber have moved down to the second preset location so that the launching bracket stops at the second preset location; the second travel switch is configured to electrically connect with the switch contact point to send a command to stop the advancing movement of the capturing device when the capturing device has been advanced to the first preset location, so that the capturing device stops at the first preset location; and the conductive piece is arranged on two sides of the second frame, and the conductive piece is electrically connected to the power contacts to supply electrical energy.

5. The system according to claim 4, wherein the second transmission mechanism comprises a second transmission gear and a second transmission rack engaged with the second transmission gear, and the second transmission gear has a semi-toothed structure.

6. The system according to claim 4, wherein the second transmission mechanism comprises a ratchet and a pawl, the ratchet is arranged inside the second transmission gear, and the pawl is connected to the second driving mechanism.

7. The system according to claim 1, wherein the deceleration and recovery device comprises an electromagnetic valve, a driving shaft, a second elastic mechanism wound on the driving shaft, a magnetic damper, and a third driving mechanism, wherein the electromagnetic valve is configured to: stop working when the capturing device is delivered to the first preset location, allowing the second elastic mechanism to push the driving shaft to connect with the deceleration shaft, and attract the driving shaft to separate the driving shaft from the deceleration shaft after the capturing device is launched, wherein the driving shaft is connected to the deceleration shaft via a gear coupling; the magnetic damper is configured to generate damping force to damp the gradual unwinding process of the first rope and the second rope is unwound, so as to decelerate the capturing device; and the third driving mechanism is connected to the magnetic damper, and is configured to pull the second rope so that the deceleration shaft rotate reversely, so as to recover the capturing device.

8. A method for capturing a space target, the method being applied to a system for capturing a space target, the system comprising a plurality of capturing devices, a delivery device, a launching device, and a deceleration and recovery device, wherein the method comprises: delivering, by the

delivery device, along a preset delivery trajectory, each of the plurality of capturing devices to a first preset location in the launching device; launching, by the launching device, each of the plurality of capturing devices located at the first preset location into a target orbit to capture a defunct space target; and decelerating, by the deceleration and recovery device, each of the plurality of capturing devices after the capturing device is launched and flies a preset distance, wherein the capturing device comprises a head, at least one barb unit, a location unit, a first rope wound inside of the capturing device, a deceleration shaft, and a second rope wound on the deceleration shaft, wherein the head is pointed for piercing and inserting into the defunct space target; the barb unit is configured to prevent the defunct space target from falling off when the defunct space target is towed; the location unit is configured to acquire real-time location of the capturing device to assist the capturing device in moving to the first preset location; and the second rope is connected to the first rope, and the second rope decelerates a flight speed of the capturing device to zero by gradually unwinding from the deceleration shaft when the first rope is fully unwound, wherein the deceleration shaft further comprises a heating device, and the heating device is configured to heat the second rope to fuse the second rope when the defunct space target has been towed to a predetermined decay orbit.

9. The method according to claim 8, wherein the deceleration and recovery device is configured to recover the capturing device into the launching device when the capturing device fails to hit the defunct space target.

10. The method according to claim 8, wherein the delivery device comprises a first frame, a plurality of mounting brackets, a plurality pairs of deceleration shaft holes, a first transmission gear, a first driving mechanism connected to the first transmission gear, a plurality of power contacts, and a plurality of switch contacts, wherein the plurality of mounting brackets are uniformly arranged on an upper side of the first frame, and each of the capturing devices is mounted on a corresponding one of the plurality of mounting brackets; the plurality pairs of deceleration shaft holes are uniformly formed in the first frame in a manner that each pair of deceleration shaft holes are arranged on two lateral sides of the first frame respectively, and the deceleration shaft is rotatably installed within the corresponding pair of deceleration shaft holes; a bottom of the first frame has an inverted T-shaped guide rail, and both transverse ends of the inverted T-shaped guide rail are respectively provided with a first transmission rack engaging with the first transmission gear; the first driving mechanism is configured to rotate the first transmission gear to translate the first transmission rack, so that the plurality of capturing devices move along the preset delivery trajectory; the plurality of power contacts are uniformly arranged on both sides of the first frame, and the plurality of power contacts provide electrical energy during the launching and deceleration recovery process of the capturing device; and the plurality of switch contacts are uniformly arranged on one side of the first frame.

11. The method according to claim 10, wherein the launching device comprises a second frame, a launching chamber, a launching bracket, a second driving mechanism, a second transmission mechanism, a first elastic mechanism, a guide rail, a first travel switch, a second travel switch, and a conductive piece; the launching chamber having a semi-cylindrical shape, and is placed within the second frame; the launching bracket passes through the launching chamber, and the launching bracket is fixedly connected to the launching chamber; the second driving mechanism is configured to drive the second transmission mechanism, wherein, when the capturing device has not yet been delivered to the first preset location, the second driving mechanism drives the second transmission mechanism so that the launching bracket and the launching chamber move downwards along the guide rail to the second preset location and compress the first elastic mechanism, and when the capturing device has been delivered to the first preset location, the second driving mechanism continues to drive the second transmission mechanism so that the first elastic mechanism is released and the launching bracket and the launching chamber move upwards along the guide rail under the action of the first elastic mechanism and launch the capturing device; the first travel

switch is configured to send a command to stop the transmission of the second transmission mechanism when the launching bracket and the launching chamber have moved down to the second preset location so that the launching bracket stops at the second preset location; the second travel switch is configured to electrically connect with the switch contact point to send a command to stop the advancing movement of the capturing device when the capturing device has been advanced to the first preset location, so that the capturing device stops at the first preset location; and the conductive piece is arranged on two sides of the second frame, and the conductive piece is electrically connected to the power contacts to supply electrical energy.

12. The method according to claim 11, wherein the second transmission mechanism comprises a second transmission gear and a second transmission rack engaged with the second transmission gear, and the second transmission gear has a semi-toothed structure.

13. The method according to claim 11, wherein the second transmission mechanism comprises a ratchet and a pawl, the ratchet is arranged inside the second transmission gear, and the pawl is connected to the second driving mechanism.

14. The method according to claim 8, wherein the deceleration and recovery device comprises an electromagnetic valve, a driving shaft, a second elastic mechanism wound on the driving shaft, a magnetic damper, and a third driving mechanism, wherein the electromagnetic valve is configured to: stop working when the capturing device is delivered to the first preset location, allowing the second elastic mechanism to push the driving shaft to connect with the deceleration shaft, and attract the driving shaft to separate the driving shaft from the deceleration shaft after the capturing device is launched, wherein the driving shaft is connected to the deceleration shaft via a gear coupling; the magnetic damper is configured to generate damping force to damp the gradual unwinding process of the first rope and the second rope is unwound, so as to decelerate the capturing device; and the third driving mechanism is connected to the magnetic damper, and is configured to pull the second rope so that the deceleration shaft rotate reversely, so as to recover the capturing device.
