

(12) **United States Patent**
Anderton et al.

(10) **Patent No.:** **US 12,388,892 B2**
(45) **Date of Patent:** ***Aug. 12, 2025**

(54) **GUIDED PERSONAL IDENTITY BASED ACTIONS**

(71) Applicant: **Snap Inc.**, Santa Monica, CA (US)

(72) Inventors: **Landon Anderton**, Salt Lake City, UT (US); **Garrett Gee**, Los Angeles, CA (US); **Ryan Hornberger**, Playa Vista, CA (US); **Kirk Ouimet**, Orem, UT (US); **Kameron Sheffield**, South Jordan, UT (US); **Benjamin Turley**, Lehi, UT (US)

(73) Assignee: **SNAP INC.**, Santa Monica, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **18/604,075**

(22) Filed: **Mar. 13, 2024**

(65) **Prior Publication Data**

US 2024/0223651 A1 Jul. 4, 2024

Related U.S. Application Data

(63) Continuation of application No. 17/830,839, filed on Jun. 2, 2022, now Pat. No. 11,962,645, which is a (Continued)

(51) **Int. Cl.**
G06F 17/00 (2019.01)
G06F 3/0484 (2022.01)
(Continued)

(52) **U.S. Cl.**
CPC **H04L 67/104** (2013.01); **G06F 3/0484** (2013.01); **H04L 67/02** (2013.01)

(58) **Field of Classification Search**
CPC H04L 67/104; H04L 67/02; H04L 63/08; G06F 3/0484; G06Q 10/10; G06Q 30/01;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

666,223 A 1/1901 Shedlock
4,581,634 A 4/1986 Williams
(Continued)

FOREIGN PATENT DOCUMENTS

CA 2887596 A1 7/2015
EP 2051480 A1 4/2009
(Continued)

OTHER PUBLICATIONS

"A Whole New Story", Snap, Inc., [Online] Retrieved from the Internet: <URL: <https://www.snap.com/en-US/news/>>, (2017), 13 pgs.

(Continued)


Primary Examiner — Andrew T McIntosh

(74) Attorney, Agent, or Firm — SCHWEGMAN LUNDBERG & WOESSNER, P.A.

(57) **ABSTRACT**

Systems and methods for guided personal identity based actions are provided. In example embodiments, a user-specified action from a first user device of a first user is received. The user-specified action pertains to the first user and uses data of the first user when performed. The user-specified action is linked to an identifier. An indication of the identifier is received from a second user device of a second user. In response to receiving the indication of the identifier, the user-specified action linked to the identifier is identified, the data of the first user is accessed, a user interface that includes an option to perform the user-specified action using the data of the first user is generated, and the generated user interface is presented on the second user device.

19 Claims, 14 Drawing Sheets



Related U.S. Application Data

continuation of application No. 15/991,660, filed on May 29, 2018, now Pat. No. 11,388,226, which is a continuation of application No. 14/595,712, filed on Jan. 13, 2015, now abandoned.

(51) **Int. Cl.**

H04L 67/02 (2022.01)

H04L 67/104 (2022.01)

(58) **Field of Classification Search**

CPC G06Q 50/01; H04M 1/2755; H04M 1/72469; H04M 1/27453

See application file for complete search history.

(56)

References Cited

U.S. PATENT DOCUMENTS

4,975,690	A	12/1990	Torres	7,020,494	B2	3/2006	Spriestersbach et al.
5,072,412	A	12/1991	Henderson, Jr. et al.	7,027,124	B2	4/2006	Foote et al.
5,493,692	A	2/1996	Theimer et al.	7,072,963	B2	7/2006	Anderson et al.
5,713,073	A	1/1998	Warsta	7,085,571	B2	8/2006	Kalhan et al.
5,754,939	A	5/1998	Herz et al.	7,110,744	B2	9/2006	Freeny, Jr.
5,855,008	A	12/1998	Goldhaber et al.	7,124,164	B1	10/2006	Chemtob
5,883,639	A	3/1999	Walton et al.	7,149,893	B1	12/2006	Leonard et al.
5,999,932	A	12/1999	Paul	7,173,651	B1	2/2007	Knowles
6,012,098	A	1/2000	Bayeh et al.	7,188,143	B2	3/2007	Szeto
6,014,090	A	1/2000	Rosen et al.	7,203,380	B2	4/2007	Chiu et al.
6,029,141	A	2/2000	Bezos et al.	7,206,568	B2	4/2007	Sudit
6,038,295	A	3/2000	Mattes	7,227,937	B1	6/2007	Yoakum et al.
6,049,711	A	4/2000	Yehezkel et al.	7,237,002	B1	6/2007	Estrada et al.
6,154,764	A	11/2000	Nitta et al.	7,240,089	B2	7/2007	Boudreau
6,167,435	A	12/2000	Druckenmiller et al.	7,269,426	B2	9/2007	Kokkonen et al.
6,204,840	B1	3/2001	Petelycky et al.	7,280,658	B2	10/2007	Amini et al.
6,205,432	B1	3/2001	Gabbard et al.	7,315,823	B2	1/2008	Brondrup
6,216,141	B1	4/2001	Straub et al.	7,349,768	B2	3/2008	Bruce et al.
6,285,381	B1	9/2001	Sawano et al.	7,356,564	B2	4/2008	Hartselle et al.
6,285,987	B1	9/2001	Roth et al.	7,394,345	B1	7/2008	Ehlinger et al.
6,310,694	B1	10/2001	Okimoto et al.	7,411,493	B2	8/2008	Smith
6,317,789	B1	11/2001	Rakavy et al.	7,423,580	B2	9/2008	Markhovsky et al.
6,334,149	B1	12/2001	Davis, Jr. et al.	7,454,442	B2	11/2008	Cobleigh et al.
6,349,203	B1	2/2002	Asaoka et al.	7,508,419	B2	3/2009	Toyama et al.
6,353,170	B1	3/2002	Eyzaguirre et al.	7,512,649	B2	3/2009	Faybishenko et al.
6,446,004	B1	9/2002	Cao et al.	7,519,670	B2	4/2009	Hagale et al.
6,449,657	B2	9/2002	Stanbach et al.	7,535,890	B2	5/2009	Rojas
6,456,852	B2	9/2002	Bar et al.	7,546,554	B2	6/2009	Chiu et al.
6,484,196	B1	11/2002	Maurille	7,607,096	B2	10/2009	Oreizy et al.
6,487,601	B1	11/2002	Hubacher et al.	7,639,943	B1	12/2009	Kalajan
6,523,008	B1	2/2003	Avrunin	7,650,231	B2	1/2010	Gadler
6,542,749	B2	4/2003	Tanaka et al.	7,668,537	B2	2/2010	DeVries
6,549,768	B1	4/2003	Fraccaroli	7,770,137	B2	8/2010	Forbes et al.
6,618,593	B1	9/2003	Drutman et al.	7,778,973	B2	8/2010	Choi
6,622,174	B1	9/2003	Ukita et al.	7,779,444	B2	8/2010	Glad
6,631,463	B1	10/2003	Floyd et al.	7,787,886	B2	8/2010	Markhovsky et al.
6,636,247	B1	10/2003	Hamzy et al.	7,796,946	B2	9/2010	Eisenbach
6,636,855	B2	10/2003	Holloway et al.	7,801,954	B2	9/2010	Cadiz et al.
6,643,684	B1	11/2003	Malkin et al.	7,856,360	B2	12/2010	Kramer et al.
6,658,095	B1	12/2003	Yoakum et al.	8,001,204	B2	8/2011	Burtner et al.
6,665,531	B1	12/2003	Soderbacka et al.	8,032,586	B2	10/2011	Challenger et al.
6,668,173	B2	12/2003	Greene	8,082,255	B1	12/2011	Carlson, Jr. et al.
6,684,238	B1	1/2004	Dutta	8,090,351	B2	1/2012	Klein
6,684,257	B1	1/2004	Camut et al.	8,098,904	B2	1/2012	Ioffe et al.
6,698,020	B1	2/2004	Zigmond et al.	8,099,109	B2	1/2012	Altman et al.
6,700,506	B1	3/2004	Winkler	8,112,716	B2	2/2012	Kobayashi
6,720,860	B1	4/2004	Narayanaswami	8,131,597	B2	3/2012	Hudetz
6,724,403	B1	4/2004	Santoro et al.	8,135,166	B2	3/2012	Rhoads
6,757,713	B1	6/2004	Ogilvie et al.	8,136,028	B1	3/2012	Loeb et al.
6,832,222	B1	12/2004	Zimowski	8,146,001	B1	3/2012	Reese
6,834,195	B2	12/2004	Brandenberg et al.	8,161,115	B2	4/2012	Yamamoto
6,836,792	B1	12/2004	Chen	8,161,417	B1	4/2012	Lee
6,898,626	B2	5/2005	Ohashi	8,195,203	B1	6/2012	Tseng
6,959,324	B1	10/2005	Kubik et al.	8,199,747	B2	6/2012	Rojas et al.
6,970,088	B2	11/2005	Kovach	8,208,943	B2	6/2012	Petersen
6,970,907	B1	11/2005	Ullmann et al.	8,214,443	B2	7/2012	Hamburg
6,980,909	B2	12/2005	Root et al.	8,234,350	B1	7/2012	Gu et al.
6,981,040	B1	12/2005	Konig et al.	8,276,092	B1	9/2012	Narayanan et al.
				8,279,319	B2	10/2012	Date
				8,280,406	B2	10/2012	Ziskind et al.
				8,285,199	B2	10/2012	Hsu et al.
				8,287,380	B2	10/2012	Nguyen et al.
				8,301,159	B2	10/2012	Hamynen et al.
				8,306,922	B1	11/2012	Kunal et al.
				8,312,086	B2	11/2012	Velusamy et al.
				8,312,097	B1	11/2012	Siegel et al.
				8,326,315	B2	12/2012	Phillips et al.
				8,326,327	B2	12/2012	Hymel et al.
				8,332,475	B2	12/2012	Rosen et al.
				8,352,546	B1	1/2013	Dollard
				8,379,130	B2	2/2013	Forutanpour et al.
				8,385,950	B1	2/2013	Wagner et al.
				8,402,097	B2	3/2013	Szeto
				8,405,773	B2	3/2013	Hayashi et al.
				8,418,067	B2	4/2013	Cheng et al.
				8,423,409	B2	4/2013	Rao
				8,471,914	B2	6/2013	Sakiyama et al.
				8,472,935	B1	6/2013	Fujisaki
				8,510,383	B2	8/2013	Hurley et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,527,345 B2	9/2013	Rothschild et al.	2002/0144154 A1	10/2002	Tomkow
8,554,627 B2	10/2013	Svensden et al.	2003/0001846 A1	1/2003	Davis et al.
8,560,612 B2	10/2013	Kilmer et al.	2003/0016247 A1	1/2003	Lai et al.
8,594,680 B2	11/2013	Ledlie et al.	2003/0017823 A1	1/2003	Mager et al.
8,613,089 B1	12/2013	Holloway et al.	2003/0020623 A1	1/2003	Cao et al.
8,639,621 B1	1/2014	Ellis	2003/0023874 A1	1/2003	Prokupets et al.
8,660,358 B1	2/2014	Bergboer et al.	2003/0037124 A1	2/2003	Yamaura et al.
8,660,369 B2	2/2014	Llano et al.	2003/0052925 A1	3/2003	Daimon et al.
8,660,793 B2	2/2014	Ngo et al.	2003/0101230 A1	5/2003	Benschoter et al.
8,682,350 B2	3/2014	Altman et al.	2003/0110503 A1	6/2003	Perkes
8,718,333 B2	5/2014	Wolf et al.	2003/0126215 A1	7/2003	Udell
8,724,622 B2	5/2014	Rojas	2003/0148773 A1	8/2003	Spiestersbach et al.
8,732,168 B2	5/2014	Johnson	2003/0164856 A1	9/2003	Prager et al.
8,744,523 B2	6/2014	Fan et al.	2003/0229607 A1	12/2003	Zellweger et al.
8,745,132 B2	6/2014	Obradovich	2004/0027371 A1	2/2004	Jaeger
8,761,800 B2	6/2014	Kuwahara	2004/0064429 A1	4/2004	Hirstius et al.
8,768,876 B2	7/2014	Shim et al.	2004/0078367 A1	4/2004	Anderson et al.
8,775,972 B2	7/2014	Spiegel	2004/0111467 A1	6/2004	Willis
8,788,680 B1	7/2014	Naik	2004/0158739 A1	8/2004	Wakai et al.
8,790,187 B2	7/2014	Walker et al.	2004/0189465 A1	9/2004	Capobianco et al.
8,797,415 B2	8/2014	Arnold	2004/0203959 A1	10/2004	Coombes
8,798,646 B1	8/2014	Wang et al.	2004/0215625 A1	10/2004	Svensden et al.
8,856,349 B2	10/2014	Jain et al.	2004/0243531 A1	12/2004	Dean
8,874,677 B2	10/2014	Rosen et al.	2004/0243688 A1	12/2004	Wugofski
8,886,227 B2	11/2014	Schmidt et al.	2005/0021444 A1	1/2005	Bauer et al.
8,909,679 B2	12/2014	Root et al.	2005/0022211 A1	1/2005	Veselov et al.
8,909,725 B1	12/2014	Sehn	2005/0048989 A1	3/2005	Jung
8,939,363 B2	1/2015	Powell et al.	2005/0078804 A1	4/2005	Yomoda
8,970,592 B1	3/2015	Petterson	2005/0097176 A1	5/2005	Schatz et al.
8,972,357 B2	3/2015	Shim et al.	2005/0102381 A1	5/2005	Jiang et al.
8,995,433 B2	3/2015	Rojas	2005/0104976 A1	5/2005	Currans
9,015,285 B1	4/2015	Ebsen et al.	2005/0114783 A1	5/2005	Szeto
9,020,745 B2	4/2015	Johnston et al.	2005/0119936 A1	6/2005	Buchanan et al.
9,040,574 B2	5/2015	Wang et al.	2005/0122405 A1	6/2005	Voss et al.
9,055,416 B2	6/2015	Rosen et al.	2005/0193340 A1	9/2005	Amburgey et al.
9,094,137 B1	7/2015	Sehn et al.	2005/0193345 A1	9/2005	Klassen et al.
9,100,806 B2	8/2015	Rosen et al.	2005/0198128 A1	9/2005	Anderson
9,100,807 B2	8/2015	Rosen et al.	2005/0223066 A1	10/2005	Buchheit et al.
9,113,301 B1	8/2015	Spiegel et al.	2005/0288954 A1	12/2005	McCarthy et al.
9,119,027 B2	8/2015	Sharon et al.	2006/0026067 A1	2/2006	Nicholas et al.
9,123,074 B2	9/2015	Jacobs et al.	2006/0107297 A1	5/2006	Toyama et al.
9,143,382 B2	9/2015	Bhagal et al.	2006/0114338 A1	6/2006	Rothschild
9,143,681 B1	9/2015	Ebsen et al.	2006/0119882 A1	6/2006	Harris et al.
9,152,477 B1	10/2015	Campbell et al.	2006/0242239 A1	10/2006	Morishima et al.
9,191,776 B2	11/2015	Root et al.	2006/0252438 A1	11/2006	Ansamaa et al.
9,204,252 B2	12/2015	Root	2006/0265417 A1	11/2006	Amato et al.
9,225,897 B1	12/2015	Sehn et al.	2006/0270419 A1	11/2006	Crowley et al.
9,258,459 B2	2/2016	Hartley	2006/0287878 A1	12/2006	Wadhwa et al.
9,344,606 B2	5/2016	Hartley et al.	2007/0004426 A1	1/2007	Pfleging et al.
9,378,386 B1*	6/2016	Saylor G06F 21/6209	2007/0038715 A1	2/2007	Collins et al.
9,385,983 B1	7/2016	Sehn	2007/0040931 A1	2/2007	Nishizawa
9,396,354 B1	7/2016	Murphy et al.	2007/0073517 A1	3/2007	Panje
9,407,712 B1	8/2016	Sehn	2007/0073823 A1	3/2007	Cohen et al.
9,407,816 B1	8/2016	Sehn	2007/0075898 A1	4/2007	Markhovsky et al.
9,430,783 B1	8/2016	Sehn	2007/0082707 A1	4/2007	Flynt et al.
9,439,041 B2	9/2016	Parvizi et al.	2007/0136228 A1	6/2007	Petersen
9,443,227 B2	9/2016	Evans et al.	2007/0192128 A1	8/2007	Celestini
9,450,907 B2	9/2016	Pridmore et al.	2007/0198340 A1	8/2007	Lucovsky et al.
9,459,778 B2	10/2016	Hogeg et al.	2007/0198495 A1	8/2007	Buron et al.
9,489,661 B2	11/2016	Evans et al.	2007/0208751 A1	9/2007	Cowan et al.
9,491,134 B2	11/2016	Rosen et al.	2007/0210936 A1	9/2007	Nicholson
9,532,171 B2	12/2016	Allen et al.	2007/0214180 A1	9/2007	Crawford
9,537,811 B2	1/2017	Allen et al.	2007/0214216 A1	9/2007	Carrer et al.
9,560,617 B2	1/2017	Liu et al.	2007/0233556 A1	10/2007	Koningstein
9,628,950 B1	4/2017	Noeth et al.	2007/0233801 A1	10/2007	Eren et al.
9,710,821 B2	7/2017	Heath	2007/0233859 A1	10/2007	Zhao et al.
9,854,219 B2	12/2017	Sehn	2007/0243887 A1	10/2007	Bandhole et al.
10,621,570 B2	4/2020	Meere et al.	2007/0244750 A1	10/2007	Grannan et al.
11,388,226 B1	7/2022	Anderton et al.	2007/0255456 A1	11/2007	Funayama
2002/0047868 A1	4/2002	Miyazawa	2007/0281690 A1	12/2007	Altman et al.
2002/0078456 A1	6/2002	Hudson et al.	2008/0022329 A1	1/2008	Glad
2002/0087631 A1	7/2002	Sharma	2008/0025701 A1	1/2008	Ikeda
2002/0097257 A1	7/2002	Miller et al.	2008/0032703 A1	2/2008	Krumm et al.
2002/0122659 A1	9/2002	Mcgrath et al.	2008/0033930 A1	2/2008	Warren
2002/0128047 A1	9/2002	Gates	2008/0043041 A2	2/2008	Hedenstroem et al.
			2008/0049704 A1	2/2008	Wittman et al.
			2008/0062141 A1	3/2008	Chandhri
			2008/0076505 A1	3/2008	Ngyen et al.
			2008/0092233 A1	4/2008	Tian et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2008/0094387	A1	4/2008	Chen	2010/0185552	A1	7/2010	Deluca et al.
2008/0104503	A1	5/2008	Beall et al.	2010/0185665	A1	7/2010	Horn et al.
2008/0109844	A1	5/2008	Baldeschweiler et al.	2010/0191631	A1	7/2010	Weidmann
2008/0120409	A1	5/2008	Sun et al.	2010/0197318	A1	8/2010	Petersen et al.
2008/0147730	A1	6/2008	Lee et al.	2010/0197319	A1	8/2010	Petersen et al.
2008/0148150	A1	6/2008	Mall	2010/0198683	A1	8/2010	Aarabi
2008/0158230	A1	7/2008	Sharma et al.	2010/0198694	A1	8/2010	Muthukrishnan
2008/0168033	A1	7/2008	Ott et al.	2010/0198826	A1	8/2010	Petersen et al.
2008/0168489	A1	7/2008	Schrage	2010/0198828	A1	8/2010	Petersen et al.
2008/0189177	A1	8/2008	Anderton et al.	2010/0198862	A1	8/2010	Jennings et al.
2008/0207176	A1	8/2008	Brackbill et al.	2010/0198870	A1	8/2010	Petersen et al.
2008/0208692	A1	8/2008	Garaventi et al.	2010/0198917	A1	8/2010	Petersen et al.
2008/0214210	A1	9/2008	Rasanen et al.	2010/0201482	A1	8/2010	Robertson et al.
2008/0222545	A1	9/2008	Lemay	2010/0201536	A1	8/2010	Robertson et al.
2008/0255976	A1	10/2008	Altberg et al.	2010/0214436	A1	8/2010	Kim et al.
2008/0256446	A1	10/2008	Yamamoto	2010/0223128	A1	9/2010	Dukellis et al.
2008/0256577	A1	10/2008	Funaki et al.	2010/0223343	A1	9/2010	Bosan et al.
2008/0266421	A1	10/2008	Takahata et al.	2010/0250109	A1	9/2010	Johnston et al.
2008/0270938	A1	10/2008	Carlson	2010/0257196	A1	10/2010	Waters et al.
2008/0288338	A1	11/2008	Wiseman et al.	2010/0259386	A1	10/2010	Holley et al.
2008/0306826	A1	12/2008	Kramer et al.	2010/0273509	A1	10/2010	Sweeney et al.
2008/0313329	A1	12/2008	Wang et al.	2010/0281045	A1	11/2010	Dean
2008/0313346	A1	12/2008	Kujawa et al.	2010/0306669	A1	12/2010	Della Pasqua
2008/0318616	A1	12/2008	Chipalkatti et al.	2011/0004071	A1	1/2011	Faiola et al.
2009/0006191	A1	1/2009	Arankalle et al.	2011/0010205	A1	1/2011	Richards
2009/0006565	A1	1/2009	Velusamy et al.	2011/0029512	A1	2/2011	Folgnier et al.
2009/0015703	A1	1/2009	Kim et al.	2011/0040783	A1	2/2011	Uemichi et al.
2009/0024956	A1	1/2009	Kobayashi	2011/0040804	A1	2/2011	Peirce et al.
2009/0030774	A1	1/2009	Rothschild et al.	2011/0043858	A1	2/2011	Jetter
2009/0030999	A1	1/2009	Gatzke et al.	2011/0050909	A1	3/2011	Ellenby et al.
2009/0040324	A1	2/2009	Nonaka	2011/0050915	A1	3/2011	Wang et al.
2009/0042588	A1	2/2009	Lottin et al.	2011/0064388	A1	3/2011	Brown et al.
2009/0058822	A1	3/2009	Chaudhri	2011/0066743	A1	3/2011	Hurley et al.
2009/0079846	A1	3/2009	Chou	2011/0083101	A1	4/2011	Sharon et al.
2009/0089678	A1	4/2009	Sacco et al.	2011/0102630	A1	5/2011	Rukes
2009/0089710	A1	4/2009	Wood et al.	2011/0119133	A1	5/2011	Igelman et al.
2009/0093261	A1	4/2009	Ziskind	2011/0137881	A1	6/2011	Cheng et al.
2009/0132341	A1	5/2009	Klinger	2011/0145564	A1	6/2011	Moshir et al.
2009/0132453	A1	5/2009	Hangartner et al.	2011/0159890	A1	6/2011	Fortescue et al.
2009/0132665	A1	5/2009	Thomsen et al.	2011/0164163	A1	7/2011	Bilbrey et al.
2009/0148045	A1	6/2009	Lee et al.	2011/0197194	A1	8/2011	D'Angelo et al.
2009/0153492	A1	6/2009	Popp	2011/0202598	A1	8/2011	Evans et al.
2009/0157450	A1	6/2009	Athsani et al.	2011/0202968	A1	8/2011	Nurmi
2009/0157752	A1	6/2009	Gonzalez	2011/0211534	A1	9/2011	Schmidt et al.
2009/0160970	A1	6/2009	Fredlund et al.	2011/0213845	A1	9/2011	Logan et al.
2009/0163182	A1	6/2009	Gatti et al.	2011/0215966	A1	9/2011	Kim et al.
2009/0177299	A1	7/2009	Van De Sluis	2011/0225048	A1	9/2011	Nair
2009/0192900	A1	7/2009	Collision	2011/0238763	A1	9/2011	Shin et al.
2009/0199242	A1	8/2009	Johnson et al.	2011/0255736	A1	10/2011	Thompson et al.
2009/0215469	A1	8/2009	Fisher et al.	2011/0273575	A1	11/2011	Lee
2009/0232354	A1	9/2009	Camp, Jr. et al.	2011/0282799	A1	11/2011	Huston
2009/0234815	A1	9/2009	Boerries et al.	2011/0283188	A1	11/2011	Farrenkopf
2009/0239552	A1	9/2009	Churchill et al.	2011/0314419	A1	12/2011	Dunn et al.
2009/0249222	A1	10/2009	Schmidt et al.	2011/0320373	A1	12/2011	Lee et al.
2009/0249244	A1	10/2009	Robinson et al.	2012/0028659	A1	2/2012	Whitney et al.
2009/0265647	A1	10/2009	Martin et al.	2012/0033718	A1	2/2012	Kauffman et al.
2009/0288022	A1	11/2009	Almstrand et al.	2012/0036015	A1	2/2012	Sheikh
2009/0291672	A1	11/2009	Treves et al.	2012/0036443	A1	2/2012	Ohmori et al.
2009/0292608	A1	11/2009	Polachek	2012/0054797	A1	3/2012	Skog et al.
2009/0319607	A1	12/2009	Belz et al.	2012/0059722	A1	3/2012	Rao
2009/0327073	A1	12/2009	Li	2012/0062805	A1	3/2012	Candelore
2010/0062794	A1	3/2010	Han	2012/0084731	A1	4/2012	Filman et al.
2010/0082427	A1	4/2010	Burgener et al.	2012/0084835	A1	4/2012	Thomas et al.
2010/0082693	A1	4/2010	Hugg et al.	2012/0085829	A1	4/2012	Ziegler
2010/0100568	A1	4/2010	Papin et al.	2012/0099800	A1	4/2012	Llano et al.
2010/0113065	A1	5/2010	Narayan et al.	2012/0108293	A1	5/2012	Law et al.
2010/0130233	A1	5/2010	Parker	2012/0110096	A1	5/2012	Smarr et al.
2010/0131880	A1	5/2010	Lee et al.	2012/0113143	A1	5/2012	Adhikari et al.
2010/0131895	A1	5/2010	Wohlert	2012/0113272	A1	5/2012	Hata
2010/0153144	A1	6/2010	Miller et al.	2012/0123830	A1	5/2012	Svendsen et al.
2010/0159944	A1	6/2010	Pascal et al.	2012/0123871	A1	5/2012	Svendsen et al.
2010/0161658	A1	6/2010	Hamynen et al.	2012/0123875	A1	5/2012	Svendsen et al.
2010/0161831	A1	6/2010	Haas et al.	2012/0124126	A1	5/2012	Alcazar et al.
2010/0162149	A1	6/2010	Sheleheda et al.	2012/0124176	A1	5/2012	Curtis et al.
2010/0183280	A1	7/2010	Beauregard et al.	2012/0124458	A1	5/2012	Cruzada
				2012/0131507	A1	5/2012	Sparandara et al.
				2012/0131512	A1	5/2012	Takeuchi et al.
				2012/0143760	A1	6/2012	Abulafia et al.
				2012/0150978	A1	6/2012	Monaco

(56)

References Cited

U.S. PATENT DOCUMENTS

2012/0165100 A1	6/2012	Lalancette et al.	2013/0219479 A1	8/2013	DeSoto et al.
2012/0166971 A1	6/2012	Sachson et al.	2013/0222323 A1	8/2013	Mckenzie
2012/0169855 A1	7/2012	Oh	2013/0227476 A1	8/2013	Frey
2012/0172062 A1	7/2012	Altman et al.	2013/0228615 A1	9/2013	Gates et al.
2012/0173991 A1	7/2012	Roberts et al.	2013/0232194 A1	9/2013	Knapp et al.
2012/0176401 A1	7/2012	Hayward et al.	2013/0238979 A1	9/2013	Sayers, III et al.
2012/0184248 A1	7/2012	Speede	2013/0263031 A1	10/2013	Oshiro et al.
2012/0197724 A1	8/2012	Kendall	2013/0265450 A1	10/2013	Barnes, Jr.
2012/0200743 A1	8/2012	Blanchflower et al.	2013/0267253 A1	10/2013	Case et al.
2012/0209924 A1	8/2012	Evans et al.	2013/0275505 A1	10/2013	Gauglitz et al.
2012/0210244 A1	8/2012	De Francisco Lopez et al.	2013/0282819 A1	10/2013	Mehta
2012/0212632 A1	8/2012	Mate et al.	2013/0290443 A1	10/2013	Collins et al.
2012/0220264 A1	8/2012	Kawabata	2013/0304646 A1	11/2013	De Geer
2012/0226748 A1	9/2012	Bosworth et al.	2013/0311255 A1	11/2013	Cummins et al.
2012/0233000 A1	9/2012	Fisher et al.	2013/0314334 A1	11/2013	Leica et al.
2012/0234907 A1	9/2012	Clark et al.	2013/0325964 A1	12/2013	Berberat
2012/0236162 A1	9/2012	Imamura	2013/0344896 A1	12/2013	Kirmse et al.
2012/0239761 A1	9/2012	Linner et al.	2013/0346869 A1	12/2013	Asver et al.
2012/0250951 A1	10/2012	Chen	2013/0346877 A1	12/2013	Borovoy et al.
2012/0252418 A1	10/2012	Kandekar et al.	2014/0006129 A1	1/2014	Heath
2012/0254325 A1	10/2012	Majeti et al.	2014/0011538 A1	1/2014	Mulcahy et al.
2012/0278387 A1	11/2012	Garcia et al.	2014/0019264 A1	1/2014	Wachman et al.
2012/0278692 A1	11/2012	Shi	2014/0032682 A1	1/2014	Prado et al.
2012/0290637 A1	11/2012	Perantatos et al.	2014/0043204 A1	2/2014	Basnayake et al.
2012/0299954 A1	11/2012	Wada et al.	2014/0045530 A1	2/2014	Gordon et al.
2012/0300087 A1	11/2012	Shore et al.	2014/0047016 A1	2/2014	Rao
2012/0304052 A1	11/2012	Tanaka et al.	2014/0047045 A1	2/2014	Baldwin et al.
2012/0304080 A1	11/2012	Wormald et al.	2014/0047335 A1	2/2014	Lewis et al.
2012/0307096 A1	12/2012	Ford et al.	2014/0049652 A1	2/2014	Moon et al.
2012/0307112 A1	12/2012	Kunishige et al.	2014/0052485 A1	2/2014	Shidfar
2012/0319904 A1	12/2012	Lee et al.	2014/0052633 A1	2/2014	Gandhi
2012/0323933 A1	12/2012	He et al.	2014/0057660 A1	2/2014	Wager
2012/0324018 A1	12/2012	Metcalf et al.	2014/0059124 A1	2/2014	Sonog et al.
2013/0006759 A1	1/2013	Srivastava et al.	2014/0082651 A1	3/2014	Sharifi
2013/0018726 A1	1/2013	Ionescu et al.	2014/0092130 A1	4/2014	Anderson et al.
2013/0024757 A1	1/2013	Doll et al.	2014/0092813 A1	4/2014	Jaakkola
2013/0036364 A1	2/2013	Johnson	2014/0096029 A1	4/2014	Schultz
2013/0041610 A1 *	2/2013	Waters G06K 7/10792	2014/0110468 A1	4/2014	Kandregula
		702/93	2014/0114565 A1	4/2014	Aziz et al.
2013/0043302 A1 *	2/2013	Powlen G06Q 50/01	2014/0122585 A1	5/2014	Delong
		235/494	2014/0122658 A1	5/2014	Haeger et al.
2013/0045753 A1	2/2013	Obermeyer et al.	2014/0122787 A1	5/2014	Shalvi et al.
2013/0050260 A1	2/2013	Reitan	2014/0129428 A1	5/2014	Tyler et al.
2013/0055083 A1	2/2013	Fino	2014/0129733 A1	5/2014	Klais
2013/0057587 A1	3/2013	Leonard et al.	2014/0129953 A1	5/2014	Spiegel
2013/0059607 A1	3/2013	Herz et al.	2014/0143143 A1	5/2014	Fasoli et al.
2013/0060690 A1	3/2013	Oskolkov et al.	2014/0149519 A1	5/2014	Redfern et al.
2013/0063369 A1	3/2013	Malhotra et al.	2014/0155102 A1	6/2014	Cooper et al.
2013/0067027 A1	3/2013	Song et al.	2014/0157114 A1	6/2014	Halme et al.
2013/0071093 A1	3/2013	Hanks et al.	2014/0172531 A1	6/2014	Liberty et al.
2013/0080254 A1	3/2013	Thramann	2014/0173424 A1	6/2014	Hogeg et al.
2013/0085790 A1	4/2013	Palmer et al.	2014/0173457 A1	6/2014	Wang et al.
2013/0086072 A1	4/2013	Peng et al.	2014/0189592 A1	7/2014	Benchenaa et al.
2013/0090171 A1	4/2013	Holton et al.	2014/0197234 A1	7/2014	Hammad
2013/0095857 A1	4/2013	Garcia et al.	2014/0207679 A1	7/2014	Cho
2013/0104053 A1	4/2013	Thornton et al.	2014/0214471 A1	7/2014	Schreiner, III
2013/0110885 A1	5/2013	Brundrett, III	2014/0222564 A1	8/2014	Kranendonk et al.
2013/0111514 A1	5/2013	Slavin et al.	2014/0229251 A1	8/2014	Lim et al.
2013/0128059 A1	5/2013	Kristensson	2014/0230071 A1	8/2014	Adam et al.
2013/0129252 A1	5/2013	Lauper	2014/0258405 A1	9/2014	Perkin
2013/0132477 A1	5/2013	Bosworth et al.	2014/0265359 A1	9/2014	Cheng et al.
2013/0145286 A1	6/2013	Feng et al.	2014/0266703 A1	9/2014	Dalley, Jr. et al.
2013/0159110 A1	6/2013	Rajaram et al.	2014/0278978 A1	9/2014	O'connor et al.
2013/0159919 A1	6/2013	Leydon	2014/0279061 A1	9/2014	Elimeliah et al.
2013/0169822 A1	7/2013	Zhu et al.	2014/0279436 A1	9/2014	Dorsey et al.
2013/0173729 A1	7/2013	Starenky et al.	2014/0279540 A1	9/2014	Jackson
2013/0182133 A1	7/2013	Tanabe	2014/0280537 A1	9/2014	Pridmore et al.
2013/0185131 A1	7/2013	Sinha et al.	2014/0282096 A1	9/2014	Rubinstein et al.
2013/0191198 A1	7/2013	Carlson et al.	2014/0287779 A1	9/2014	O'keefe et al.
2013/0191394 A1 *	7/2013	Bradley G06Q 50/01	2014/0289833 A1	9/2014	Briceno
		707/738	2014/0306986 A1	10/2014	Gottesman et al.
2013/0194301 A1	8/2013	Robbins et al.	2014/0317302 A1	10/2014	Naik
2013/0198176 A1	8/2013	Kim	2014/0324627 A1	10/2014	Haver et al.
2013/0218965 A1	8/2013	Abrol et al.	2014/0324629 A1	10/2014	Jacobs
2013/0218968 A1	8/2013	Mceevilly et al.	2014/0325383 A1	10/2014	Brown et al.
			2014/0326793 A1	11/2014	Windmueller et al.
			2015/0006672 A1 *	1/2015	Morel G06Q 30/0269
					709/217
			2015/0020086 A1	1/2015	Chen et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2015/0046278	A1	2/2015	Pei et al.	
2015/0071619	A1	3/2015	Brough	
2015/0087263	A1	3/2015	Branscomb et al.	
2015/0088622	A1	3/2015	Ganschow et al.	
2015/0095020	A1	4/2015	Leydon	
2015/0095989	A1	4/2015	An	
2015/0096042	A1	4/2015	Mizrachi	
2015/0116529	A1	4/2015	Wu et al.	
2015/0124791	A1	5/2015	Mazandarany et al.	
2015/0169827	A1	6/2015	Laborde	
2015/0172534	A1	6/2015	Miyakawa et al.	
2015/0178260	A1	6/2015	Brunson	
2015/0211861	A1	7/2015	Ingerman et al.	
2015/0222814	A1	8/2015	Li et al.	
2015/0248663	A1 *	9/2015	Meere	G06Q 20/10 705/17
2015/0254486	A1	9/2015	Shigemitsu	
2015/0261917	A1	9/2015	Smith	
2015/0312184	A1	10/2015	Langholz et al.	
2015/0350136	A1	12/2015	Flynn, III et al.	
2015/0350910	A1	12/2015	Eramian	
2015/0365795	A1	12/2015	Allen et al.	
2015/0378502	A1	12/2015	Hu et al.	
2016/0006927	A1	1/2016	Sehn	
2016/0014063	A1	1/2016	Hogeg et al.	
2016/0021233	A1 *	1/2016	Savage	G06Q 10/1093 455/414.1
2016/0085773	A1	3/2016	Chang et al.	
2016/0085863	A1	3/2016	Allen et al.	
2016/0099901	A1	4/2016	Allen et al.	
2016/0156719	A1	6/2016	Mobarak et al.	
2016/0180887	A1	6/2016	Sehn	
2016/0182422	A1	6/2016	Sehn et al.	
2016/0182875	A1	6/2016	Sehn	
2016/0239248	A1	8/2016	Sehn	
2016/0277419	A1	9/2016	Allen et al.	
2016/0321708	A1	11/2016	Sehn	
2017/0006094	A1	1/2017	Abou Mahmoud et al.	
2017/0061308	A1	3/2017	Chen et al.	
2017/0287006	A1	10/2017	Azmooodeh et al.	
2022/0303336	A1	9/2022	Anderton et al.	

FOREIGN PATENT DOCUMENTS

EP	2151797	A1	2/2010
GB	2399928	A	9/2004
KR	19990073076	A	10/1999
KR	20010078417	A	8/2001
WO	WO-1996024213	A1	8/1996
WO	WO-1999063453	A1	12/1999
WO	WO-2000058882	A1	10/2000
WO	WO-2001029642	A1	4/2001
WO	WO-2001050703	A3	7/2001
WO	WO-2006118755	A2	11/2006
WO	WO-2007092668	A2	8/2007
WO	WO-2009043020	A2	4/2009
WO	WO-2011040821	A1	4/2011
WO	WO-2011119407	A1	9/2011
WO	WO-2013008238	A1	1/2013
WO	WO-2013045753	A1	4/2013
WO	WO-2014006129	A1	1/2014
WO	WO-2014068573	A1	5/2014
WO	WO-2014115136	A1	7/2014
WO	WO-2014194262	A2	12/2014
WO	WO-2015192026	A1	12/2015
WO	WO-2016044424	A1	3/2016
WO	WO-2016054562	A1	4/2016
WO	WO-2016065131	A1	4/2016
WO	WO-2016100318	A2	6/2016
WO	WO-2016100318	A3	6/2016
WO	WO-2016100342	A1	6/2016
WO	WO-2016149594	A1	9/2016
WO	WO-2016179166	A1	11/2016

OTHER PUBLICATIONS

"Adding photos to your listing", eBay, [Online] Retrieved from the Internet: <URL: <http://pages.ebay.com/help/sell/pictures.html>>, (accessed May 24, 2017), 4 pgs.

"U.S. Appl. No. 14/595,712, Advisory Action mailed Apr. 11, 2018", 3 pgs.

"U.S. Appl. No. 14/595,712, Examiner Interview Summary mailed Oct. 26, 2015", 3 pgs.

"U.S. Appl. No. 14/595,712, Final Office Action mailed May 5, 2017", 14 pgs.

"U.S. Appl. No. 14/595,712, Final Office Action mailed May 5, 2017", 13 pgs.

"U.S. Appl. No. 14/595,712, Final Office Action mailed Oct. 8, 2015", 18 pgs.

"U.S. Appl. No. 14/595,712, Final Office Action mailed Dec. 29, 2017", 29 pgs.

"U.S. Appl. No. 14/595,712, Non Final Office Action mailed May 8, 2015", 16 pgs.

"U.S. Appl. No. 14/595,712, Non Final Office Action mailed Jun. 9, 2016", 14 pgs.

"U.S. Appl. No. 14/595,712, Non Final Office Action mailed Aug. 3, 2017", 28 pgs.

"U.S. Appl. No. 14/595,712, Response filed Jan. 7, 2016 to Final Office Action mailed Oct. 8, 2015", 16 pgs.

"U.S. Appl. No. 14/595,712, Response filed Feb. 28, 2018 to Final Office Action mailed Dec. 29, 2017", 20 pgs.

"U.S. Appl. No. 14/595,712, Response filed Jun. 16, 2015 to Non Final Office Action mailed May 8, 2015", 14 pgs.

"U.S. Appl. No. 14/595,712, Response filed Sep. 7, 2016 to Non Final Office Action mailed Jun. 9, 2016", 12 pgs.

"U.S. Appl. No. 15/991,660, Advisory Action mailed Jan. 26, 2022", 3 pgs.

"U.S. Appl. No. 15/991,660, Advisory Action mailed May 13, 2021", 2 pgs.

"U.S. Appl. No. 15/991,660, Corrected Notice of Allowability mailed Apr. 1, 2022".

"U.S. Appl. No. 15/991,660, Final Office Action mailed Mar. 31, 2021", 15 pgs.

"U.S. Appl. No. 15/991,660, Final Office Action mailed Nov. 10, 2021", 19 pgs.

"U.S. Appl. No. 15/991,660, Non Final Office Action mailed Jan. 8, 2020", 12 pgs.

"U.S. Appl. No. 15/991,660, Non Final Office Action mailed Jul. 20, 2021", 18 pgs.

"U.S. Appl. No. 15/991,660, Notice of Allowance mailed Mar. 7, 2022", 12 pgs.

"U.S. Appl. No. 15/991,660, Response filed Jan. 5, 2022 to Final Office Action mailed Nov. 10, 2021", 12 pgs.

"U.S. Appl. No. 15/991,660, Response filed Apr. 2, 2020 to Non Final Office Action mailed Jan. 8, 2020", 11 pgs.

"U.S. Appl. No. 15/991,660, Response filed May 5, 2021 to Final Office Action mailed Mar. 31, 2021", 12 pgs.

"U.S. Appl. No. 15/991,660, Response filed Aug. 5, 2020 to Restriction Requirement mailed Jul. 6, 2020", 2 pgs.

"U.S. Appl. No. 15/991,660, Response filed Oct. 20, 2021 to Non Final Office Action mailed Jul. 20, 2021", 13 pgs.

"U.S. Appl. No. 15/991,660, Restriction Requirement mailed Jul. 6, 2020", 7 pgs.

"U.S. Appl. No. 17/830,839, Final Office Action mailed Oct. 2, 2023", 26 pgs.

"U.S. Appl. No. 17/830,839, Non Final Office Action mailed May 4, 2023", 28 pgs.

"U.S. Appl. No. 17/830,839, Notice of Allowance mailed Dec. 13, 2023", 11 pgs.

"U.S. Appl. No. 17/830,839, Response filed Jun. 29, 2023 to Non Final Office Action mailed May 4, 2023", 10 pgs.

"U.S. Appl. No. 17/830,839, Response filed Nov. 14, 2023 to Final Office Action mailed Oct. 2, 2023", 10 pgs.

"BlogStomp", StompSoftware, [Online] Retrieved from the Internet: <URL: <http://stompsoftware.com/blogstomp>>, (accessed May 24, 2017), 12 pgs.

(56)

References Cited**OTHER PUBLICATIONS**

"Cup Magic Starbucks Holiday Red Cups come to life with AR app", Blast Radius, [Online] Retrieved from the Internet: <URL: <https://web.archive.org/web/20160711202454/http://www.blastradius.com/work/cup-magic/>>, (2016), 7 pgs.

"Daily App: InstaPlace (iOS/Android): Give Pictures a Sense of Place", TechPP, [Online] Retrieved from the Internet: <URL: <http://techpp.com/2013/02/15/instaplace-app-review/>>, (2013), 13 pgs.

"InstaPlace Photo App Tell the Whole Story", [Online] Retrieved from the Internet: <URL: youtu.be/uF_gFkg1hBM>, (Nov. 8, 2013), 113 pgs., 1:02 min.

"International Application Serial No. PCT/US2015/037251, International Search Report mailed Sep. 29, 2015", 2 pgs.

"Introducing Snapchat Stories", [Online] Retrieved from the Internet: <URL: <https://web.archive.org/web/20131026084921/https://www.youtube.com/watch?v=88Cu3yN-LIM>>, (Oct. 3, 2013), 92 pgs.; 00:47 min.

"Macy's Believe-o-Magic", [Online] Retrieved from the Internet: <URL: <https://web.archive.org/web/20190422101854/https://www.youtube.com/watch?v=xvzRXy3J0Z0&feature=youtu.be>>, (Nov. 7, 2011), 102 pgs.; 00:51 min.

"Macy's Introduces Augmented Reality Experience in Stores across Country as Part of Its 2011 Believe Campaign", Business Wire, [Online] Retrieved from the Internet: <URL: <https://www.businesswire.com/news/home/20111102006759/en/Macys-Introduces-Augmented-Reality-Experience-Stores-Country>>, (Nov. 2, 2011), 6 pgs.

"Starbucks Cup Magic", [Online] Retrieved from the Internet: <URL: <https://www.youtube.com/watch?v=RWwQXi9RG0w>>, (Nov. 8, 2011), 87 pgs.; 00:47 min.

"Starbucks Cup Magic for Valentine's Day", [Online] Retrieved from the Internet: <URL: <https://www.youtube.com/watch?v=8nvqOzjq10w>>, (Feb. 6, 2012), 88 pgs.; 00:45 min.

"Starbucks Holiday Red Cups Come to Life, Signaling the Return of the Merriest Season", Business Wire, [Online] Retrieved from the Internet: <URL: <http://www.businesswire.com/news/home/20111115005744/en/2479513/Starbucks-Holiday-Red-Cups-Life-Signaling-Return>>, (Nov. 15, 2011), 5 pgs.

Aniruddh, "Facebook Integrates QR codes for Profiles in Apps", hackerSPACE (Online), URL: <https://hackerspace.kinja.com/facebook-integrates-qr-codes-for-profiles-in-apps-1564650292>, (accessed Aug. 2, 2018), 2 pgs.

Carthy, Roi, "Dear All Photo Apps: Mobli Just Won Filters", TechCrunch, [Online] Retrieved from the Internet: <URL: <https://techcrunch.com/2011/09/08/mobli-filters/>>, (Sep. 8, 2011), 10 pgs.

Dou, Xue Hairong, et al., "Creative use of QR codes in consumer communication", International journal of mobile marketing 3.2, (2008), 61-67.

Janthong, Isaranu, "Instaplace ready on Android Google Play store", Android App Review Thailand, [Online] Retrieved from the Internet: <URL: <http://www.android-free-app-review.com/2013/01/instaplace-android-google-play-store.html>>, (Jan. 23, 2013), 9 pgs.

Kane, Russell, "How to Combine QR Codes with the Power of Facebook", Social Media Examiner (Online), URL: <https://www.socialmediaexaminer.com/how-to-combine-qr-codes-with-the-power-of-facebook/>, (accessed Aug. 2, 2018), 7 pgs.

Korhan, Jeff, "QR Codes Like Your Facebook Page", URL: <http://www.jeffkorhan.com/2010/10/qr-codes-like-your-facebook-page.html>, (accessed Aug. 2, 2018), 3 pgs.

Law, Bobby, "Interactive lectures: encouraging student interaction using Quick Response codes", International Journal on Advances in Intelligent Systems 7. 3-4, (2014), 349-360.

Leyden, John, "This SMS will self-destruct in 40 seconds", [Online] Retrieved from the Internet: <URL: <http://www.theregister.co.uk/2005/12/12/stealthtext/>>, (Dec. 12, 2005), 1 pg.

MacLeod, Duncan, "Macys Believe-o-Magic App", [Online] Retrieved from the Internet: <URL: <http://theinspirationroom.com/daily/2011/macys-believe-o-magic-app/>>, (Nov. 14, 2011), 10 pgs.

MacLeod, Duncan, "Starbucks Cup Magic Lets Merry", [Online] Retrieved from the Internet: <URL: <http://theinspirationroom.com/daily/2011/starbucks-cup-magic/>>, (Nov. 12, 2011), 8 pgs.

McPherson, Frank, "Scan to Add a Facebook Friend on Android Phones", Adweek (Online), URL: <https://www.adweek.com/digital/scan-to-add-a-facebook-friend-on-android-phones/>, (accessed Aug. 2, 2018), 1 pg.

Notopoulos, Katie, "A Guide To The New Snapchat Filters and Big Fonts", [Online] Retrieved from the Internet: <URL: https://www.buzzfeed.com/katienotopoulos/a-guide-to-the-new-snapchat-filters-and-big-fonts?utm_term=.bkQ9qVZWw#nv58YXpkV>, (Dec. 22, 2013), 13 pgs.

Panzarino, Matthew, "Snapchat Adds Filters, A Replay Function and for Whatever Reason, Time, Temperature and Speed Overlays", TechCrunch, [Online] Retrieved from the Internet: <URL: <https://techcrunch.com/2013/12/20/snapchat-adds-filters-new-font-and-for-some-reason-time-temperature-and-speed-overlays/>>, (Dec. 20, 2013), 12 pgs.

Summerson, Cameron, "InstaWiFi Lets You Easily Share Your Wi-Fi Password Through NFC or QR Codes", Android Police (Online), URL: <https://www.androidpolice.com/2012/07/24/new-app-instawifi-lets-you-easily-share-your-wi-fi-password-through-nfc-or-qr-codes/>, (accessed Aug. 2, 2018), 2 pgs.

Trapani, Gina, "How to Make Your Personal QR Code", URL: <https://lifehacker.com/5488323/how-to-make-your-personal-qr-code>, (accessed Aug. 2, 2018), 2 pgs.

Tripathi, Rohit, "Watermark Images in PHP and Save File on Server", [Online] Retrieved from the Internet: <URL: <http://code.rohitink.com/2012/12/28/watermark-images-in-php-and-save-file-on-server>>, (Dec. 28, 2012), 4 pgs.

Vazquez, Briseno Mabel, et al., "Using RFID/NFC and QR-code in mobile phones to link the physical and the digital world", Interactive Multimedia 12, (2012), 219-242.

Yarden, "Animate your Advertising with Animation QR Codes", Visuallead Blog, [Online] Retrieved from the Internet: <URL: <http://blog.visuallead.com/animate-advertising-animation-qr-codes/>>, (Dec. 10, 2014), 3 pgs.

* cited by examiner




FIG. 1


200


FIG. 2




FIG. 3




FIG. 4




FIG. 6




FIG. 5





FIG. 7A






FIG. 9




FIG. 8




FIG. 11




FIG. 10




FIG. 12




FIG. 13





FIG. 15

FIG. 14






FIG. 17




FIG. 18

1

GUIDED PERSONAL IDENTITY BASED ACTIONS

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 17/830,839, filed Jun. 2, 2022, and entitled “GUIDED PERSONAL IDENTITY BASED ACTIONS”, now issued as U.S. Pat. No. 11,962,645, which is a continuation of U.S. patent application Ser. No. 15/991,660, filed May 29, 2018, and entitled “GUIDED PERSONAL IDENTITY BASED ACTIONS,” now issued as U.S. Pat. No. 11,388,226, which is a continuation of U.S. patent application Ser. No. 14/595,712, filed Jan. 13, 2015, and entitled “GUIDED PERSONAL IDENTITY BASED ACTIONS.” The contents of these prior applications are considered part of this application and are hereby incorporated by reference in their entirety.

TECHNICAL FIELD

Embodiments of the present disclosure relate generally to mobile computing technology and, more particularly, but not by way of limitation, to guided personal identity based actions.

BACKGROUND

Automated identification techniques, such as Quick Response (QR) codes, are a popular way to share and provide small pieces of information to users of mobile devices, wearable devices, and other smart devices. Many automated identification techniques are limited to one-way communication and store a limited amount of data that is often static and non-executable. These characteristics can curb the usefulness of automated identification for tasks involving two-way communication, frequently updated data, or data transfers that exceed a capacity of an automated identification scheme.

BRIEF DESCRIPTION OF THE DRAWINGS

Various ones of the appended drawings merely illustrate example embodiments of the present disclosure and should not be considered as limiting its scope.

FIG. 1 is a block diagram illustrating a networked system, according to some example embodiments.

FIG. 2 is a block diagram illustrating an example embodiment of a personal identity system, according to some example embodiments.

FIG. 3 is a diagram illustrating an example of guided personal identity based actions, according to some example embodiments.

FIG. 4 is a flow diagram illustrating an example method for guided personal identity based actions, according to some example embodiments.

FIGS. 5 and 6 are example user interface diagrams depicting example user interfaces for providing an option to perform guided personal identity based actions, according to some example embodiments.

FIGS. 7A and 7B are swim-lane diagrams illustrating various communications between devices performing a method for guided personal identity based actions, according to some example embodiments.

2

FIG. 8 is a flow diagram illustrating further example operations for guided personal identity based actions, according to some example embodiments.

FIG. 9 is a user interface diagram depicting an example user interface for displaying a machine-readable visual representation that encodes an identifier, according to some example embodiments.

FIG. 10 is a flow diagram illustrating further example operations for configuring guided personal identity based actions, according to some example embodiments.

FIG. 11 is a user interface diagram depicting an example user interface for configuration of guided personal identity based actions, according to some example embodiments.

FIGS. 12 and 13 are flow diagrams illustrating further example operations for performing analytics associated with guided personal identity based actions, according to some example embodiments.

FIGS. 14 and 15 are user interface diagrams depicting an example user interface for presenting analytics associated with guided personal identity based actions, according to some example embodiments.

FIG. 16 is a user interface diagram depicting an example mobile device and mobile operating system interface, according to some example embodiments.

FIG. 17 is a block diagram illustrating an example of a software architecture that may be installed on a machine, according to some example embodiments.

FIG. 18 is a block diagram presenting a diagrammatic representation of a machine in the form of a computer system within which a set of instructions may be executed for causing the machine to perform any of the methodologies discussed herein, according to an example embodiment.

The headings provided herein are merely for convenience and do not necessarily affect the scope or meaning of the terms used.

DETAILED DESCRIPTION

The description that follows includes systems, methods, techniques, instruction sequences, and computing machine program products that embody illustrative embodiments of the disclosure. In the following description, for the purposes of explanation, numerous specific details are set forth in order to provide an understanding of various embodiments of the inventive subject matter. It will be evident, however, to those skilled in the art, that embodiments of the inventive subject matter may be practiced without these specific details. In general, well-known instruction instances, protocols, structures, and techniques are not necessarily shown in detail.

Automated identification techniques offer a convenient way for users of smart devices to access small pieces of information. For example, QR codes are two-dimensional optical bar codes that encode information readable by a device (e.g., a smart phone) equipped with a camera sensor. In a common scenario, a website address is encoded into a QR code and a smart device scans the QR code to access the website address. In this scenario, a user is directed to a website without guidance or direction as to performing a particular action or task associated with the website or a particular entity associated with the QR code. This aimlessness can diminish the likelihood of the user achieving a purpose of the QR code. According to various example embodiments, a guided, focused objective for a QR code, or similar automated identification scheme, can improve both user experience and the chances of the user completing an action associated with the QR code.

To assist users in providing guided personal identity based actions to other users, in various example embodiments, an application server provides a user interface for a first user to configure an action, task, or other instruction that uses data associated with the first user or entity (e.g., a business, organization, or individual). The application server receives a user-specified action and links the user-specified action to an identifier that can be encoded into a QR code or another type of automated identification tag (e.g., Radio Frequency Identification (RFID) tags, Near Field Communication (NFC) tags, smart tags, or audio based tags). The application server stores the configuration of the action to be accessed in association with the identifier.

Subsequently, a second user scans the QR code to trigger communication of an indication of the identifier encoded in the QR code to the application server that is storing or can facilitate retrieval of the configuration of the user-specified action. The application server identifies the user-specified action linked to the identifier and accesses the data of the first user to be used when performing the user-specified action. The application server uses the data of the first user to facilitate performing the user-specified action (e.g., the data of first user can include a member identification on a social network service used to facilitate a particular social network action such as friending the first user). In some embodiments, the first user can provide the data during configuration or a specification of the data to be retrieved dynamically by the application server. For instance, the application server can dynamically retrieve or access the data when the user-specified action is performed. This may be desirable in situations where the data is subject to change (e.g., a current geolocation of a food truck that is frequently in different locations). In some instances, the application server can automatically perform, on behalf of the second user, the user-specified action using the data of the first user. In other instances, the application server generates a user interface including an option to perform the user-specified action using the data of the first user and the user interface is presented to the second user.

The user-specified action can comprise a wide variety of actions that pertain to the first user or another entity. For example, the user-specified action can include providing certain data (e.g., directions to a particular geolocation specified by the first user or network login information), sending a text message to a certain number with a certain message content, placing a phone call to a certain number, adding an event to a calendar of the second user and the first user, downloading a particular media file (e.g., a song or an app), providing payment information to facilitate a payment to the first user, establishing a peer-to-peer communication link between a device of the first user and a device of the second user in real time (e.g., BLUETOOTH® pairing of devices), automatically logging into an online account, automatically becoming a member of an online service, a social network action (e.g., like, favorite, connect, friend, follow, post, tag, or check-in), or any suitable combination thereof.

FIG. 1 is a network diagram depicting a network system 100 having a client-server architecture configured for exchanging data over a network, according to one embodiment. For example, the network system 100 may be a messaging system where clients communicate and exchange data within the network system 100. The data may pertain to various functions (e.g., sending and receiving text and media communication, determining geolocation, etc.) and aspects (e.g., guided personal identity based actions) associated with the network system 100 and its users. Although illustrated

herein as client-server architecture, other embodiments may include other network architectures, such as peer-to-peer or distributed network environments.

As shown in FIG. 1, the network system 100 includes a social messaging system 130. The social messaging system 130 is generally based on a three-tiered architecture, consisting of an interface layer 124, an application logic layer 126, and a data layer 128. As is understood by skilled artisans in the relevant computer and Internet-related arts, each module or engine shown in FIG. 1 represents a set of executable software instructions and the corresponding hardware (e.g., memory and processor) for executing the instructions. To avoid obscuring the inventive subject matter with unnecessary detail, various functional modules and engines that are not germane to conveying an understanding of the inventive subject matter have been omitted from FIG. 1. Of course, additional functional modules and engines may be used with a social messaging system, such as that illustrated in FIG. 1, to facilitate additional functionality that is not specifically described herein. Furthermore, the various functional modules and engines depicted in FIG. 1 may reside on a single server computer, or may be distributed across several server computers in various arrangements. Moreover, although the social messaging system 130 is depicted in FIG. 1 as a three-tiered architecture, the inventive subject matter is by no means limited to such an architecture.

As shown in FIG. 1, the interface layer 124 consists of interface module(s) (e.g., a web server) 140, which receive requests from various client-computing devices and servers, such as client device(s) 110 executing client application(s) 112, and third party server(s) 120 executing third party application(s) 122. In response to received requests, the interface module(s) 140 communicate appropriate responses to requesting devices via a network 104. For example, the interface module(s) 140 can receive requests such as Hypertext Transfer Protocol (HTTP) requests, or other web-based Application Programming Interface (API) requests.

The client device(s) 110 can execute conventional web browser applications or applications (also referred to as “apps”) that have been developed for a specific platform to include any of a wide variety of mobile computing devices and mobile-specific operating systems (e.g., IOS™, ANDROID™, WINDOWS® PHONE). In an example, the client device(s) 110 are executing the client application(s) 112. The client application(s) 112 can provide functionality to present information to a user 106 and communicate via the network 104 to exchange information with the social messaging system 130. Each of the client device(s) 110 can comprise a computing device that includes at least a display and communication capabilities with the network 104 to access the social messaging system 130. The client device(s) 110 comprise, but are not limited to, remote devices, work stations, computers, general purpose computers, Internet appliances, hand-held devices, wireless devices, portable devices, wearable computers, cellular or mobile phones, personal digital assistants (PDAs), smart phones, tablets, ultrabooks, netbooks, laptops, desktops, multi-processor systems, microprocessor-based or programmable consumer electronics, game consoles, set-top boxes, network PCs, mini-computers, and the like. User(s) 106 can be a person, a machine, or other means of interacting with the client device(s) 110. In some embodiments, the user(s) 106 interact with the social messaging system 130 via the client device(s) 110.

As shown in FIG. 1, the data layer 128 has database server(s) 132 that facilitate access to information storage

repositories or database(s) **134**. The database(s) **134** are storage devices that store data such as member profile data, social graph data (e.g., relationships between members of the social messaging system **130**), and other user data.

An individual can register with the social messaging system **130** to become a member of the social messaging system **130**. Once registered, a member can form social network relationships (e.g., friends, followers, or contacts) on the social messaging system **130** and interact with a broad range of applications provided by the social messaging system **130**.

The application logic layer **126** includes various application logic module(s) **150**, which, in conjunction with the interface module(s) **140**, generate various user interfaces with data retrieved from various data sources or data services in the data layer **128**. Individual application logic module(s) **150** may be used to implement the functionality associated with various applications, services, and features of the social messaging system **130**. For instance, a social messaging application can be implemented with one or more of the application logic module(s) **150**. The social messaging application provides a messaging mechanism for users of the client device(s) **110** to send and receive messages that include text and media content such as pictures and video. The client device(s) **110** may access and view the messages from the social messaging application for a specified period of time (e.g., limited or unlimited). In an example, a particular message is accessible to a message recipient for a predefined duration (e.g., specified by a message sender) that begins when the particular message is first accessed. After the predefined duration elapses, the message is deleted and is no longer accessible to the message recipient. Of course, other applications and services may be separately embodied in their own application server module(s) **150**.

As illustrated in FIG. 1, the social messaging system **130** includes a personal identity system **160**. In various embodiments, the personal identity system **160** can be implemented as a standalone system and is not necessarily included in the social messaging system **130**. In some embodiments, the client device(s) **110** include a portion of the personal identity system **160** (e.g., a portion of the personal identity system **160** included independently or in the client application(s) **112**). In embodiments where the client device(s) **110** includes a portion of the personal identity system **160**, the client device(s) **110** can work alone or in conjunction with the portion of the personal identity system **160** included in a particular application server or included in the social messaging system **130**.

FIG. 2 is a block diagram **200** of the personal identity system **160**. The personal identity system **160** is shown to include a communication module **210**, a presentation module **220**, a configuration module **230**, an instruction module **240**, a data module **250**, and an analytics module **260**. All, or some, of the modules **210-260** communicate with each other, for example, via a network coupling, shared memory, and the like. Each module of the modules can be implemented as a single module, combined into other modules, or further subdivided into multiple modules. Other modules not pertinent to example embodiments can also be included, but are not shown.

The communication module **210** provides various communications functionality. For example, the communication module **210** receives an indication of an identifier linked to a particular user-specified action. In a specific example, when the client device(s) **110** scan a QR code, the client device(s) **110** communicate an indication of the identifier extracted from the QR code to the communication module

210. The communication module **210** exchanges network communications with the database server(s) **132**, the client device(s) **110**, and the third party server(s) **120**. The information retrieved by the communication module **210** includes data associated with the user (e.g., member profile data from an online account or social network service data) or other data to facilitate the functionality described herein.

The presentation module **220** provides various presentation and user interface functionality operable to interactively present and receive information to and from the user. For instance, the presentation module **220** is utilizable to present machine-readable visual representations of an identifier (e.g., a QR code), a user interface configured to receive guided personal identity based action configuration data, or a user interface configured to provide an option to perform a guided personal identity based action. In various embodiments, the presentation module **220** presents or causes presentation of information (e.g., visually displaying information on a screen, acoustic output, haptic feedback). The process of interactively presenting information is intended to include the exchange of information between a particular device and the user. The user may provide input to interact with the user interface in many possible manners, such as alphanumeric, point based (e.g., cursor), tactile, or other input (e.g., touch screen, tactile sensor, light sensor, infrared sensor, biometric sensor, microphone, gyroscope, accelerometer, or other sensors). The presentation module **220** provides many other user interfaces to facilitate functionality described herein. The term “presenting” as used herein is intended to include communicating information or instructions to a particular device that is operable to perform presentation based on the communicated information or instructions.

The configuration module **230** provides functionality that allows users to upload configuration data for guided personal identity based actions such as user-specified actions and data for the user-specified actions. For example, the configuration module **230** can cause presentation of a user interface that includes multiple action options on the client device(s) **110**. In this example, a user specifies a particular action by selecting one of the multiple action options included in the user interface. The user can also specify data associated with the user-specified action. In this way, the configuration module **230** facilitates configuration and upload of user-specified actions and data for the user-specified actions.

The instruction module **240** provides functionality associated with performing the user-specified action. For example, the instruction module **240** identifies the user-specified action linked to a particular identifier (e.g., via a lookup of the user-specified action using the identifier). The instruction module **240** can perform or cause another device to perform the user-specified action. In further embodiments, the instruction module **240** modifies, alters, or otherwise augments the user-specified action based on a variety of data. For instance, the instruction module **240** determines a device capability to perform certain actions based on user data (e.g., determining that the user is a member of a particular social network service prior to performing an action associated with the particular social network service). In still further embodiments, the instruction module **240** can infer a preference of the user based on the user data (e.g., identifying a most frequently or recently used social network service indicates a preference for actions associated with the most frequently or recently used social network service). In various embodiments, the instruction module **240** can exchange network communications with the third party

server(s) 120, the client device(s) 110, or various components of the social messaging system 130 to facilitate performing or causing performance of the user-specified action.

The data module 250 provides various data functionality such as exchanging information with databases or servers. For example, the data module 250 accesses data from the third party server(s) 120, the database(s) 134, and the client device(s) 110. In a specific example, the data module 250 accesses data used by the instruction module 240 to perform or cause performance of the user-specified action. In some instances, the data module 250 accesses the data for the user-specified action that is stored with the user-specified action (e.g., stored in the database(s) 134). In other instances, the data module 250 retrieves the data for the user-specified action from the client device(s) 110, the third party server(s) 120, or other storage devices.

The analytics module 260 provides functionality to generate various analytics data associated with a particular identifier linked to the user-specified action. For example, the analytics module 260 can identify a characteristic corresponding to a particular identifier by analyzing context attributes associated with the identifier. For instance, the context attributes include attributes associated with a context corresponding to receiving an indication of a particular identifier (e.g., a geolocation of where a particular identifier was detected, a device type that detected the particular identifier). In some embodiments, the analytics module 260 updates, maintains, or otherwise manages data associated with the context associated with receiving indications. For instance, the analytics module 260 increments an access count each time an indication is received at the communication module 210.

Turning now to FIG. 3, a diagram 300 illustrating an example of guided personal identity based actions is shown. FIG. 3 is an overview of a particular example implementation of the personal identity system 160 facilitating a guided personal identity based action. Additional details and alternative implementations are discussed in connection with the figures to follow. In the diagram 300, a scene 302 illustrates a first user 304 and a second user 306. A scene 308 portrays an enlarged view of a portion of the scene 302. The scene 308 shows a first user device 312 of the first user 304 and a second user device 316 of the second user 306. The first user device 312 is displaying a code 310 (e.g., a machine-readable visual representation such as a QR code) that encodes an identifier detectable by the second user device 316. The second user device 316 employs a camera sensor, or another optical sensor, to detect or scan a signal 314 (e.g., a camera sensor capturing an optical signal) corresponding to the code 310. After scanning the code 310, the second user device 316 decodes the identifier encoded in the code 310. The second user device 316 is communicatively coupled to the network 104 and the social messaging system 130 via a communication link 318, allowing for an exchange of data between the personal identity system 160 and the second user device 316.

In an example scenario, the first user 304 has previously provided configuration data to the personal identity system 160 for a guided personal identity based action. For instance, the first user 304 provided a specification of an action that performs a social network action such as forming a relationship with another member on a social network service. In this instance, the user-specified action uses a member identification of the first user 304 on the social network service to perform the social network action. Subsequent to the first user 304 providing the user-specified action, the

personal identity system 160 links the user-specified action to an identifier (e.g., an identifier corresponding to the first user 304 or a unique identifier to distinguish the user-specified action from among other user-specified actions). The personal identity system 160 can also generate the code 310 that encodes the identifier. The first user device 312 stores the code 310 that encodes the identifier corresponding to the user-specified action provided by the first user. After configuration of the guided personal identity based action is complete, the first user 304 can display and share the code 310 with other users such as the second user 306. For example, the code 310 can be physically printed and distributed (e.g., on a billboard, in a newspaper publication, or on a business card), displayed on a display screen of the first user device 312, or displayed on another device.

Continuing with the example scenario, the first user 304 displays the code 310 on a display screen of the first user device 312 and the second user 306 operates a camera sensor of the second user device 316 to physically detect the code 310. Once the second user device 316 detects and decodes the identifier from the code 310, the second user device 316 provides an indication of the identifier to the personal identity system 160. In response to receiving the indication of the identifier, the personal identity system 160 identifies the user-specified action previously linked to the identifier during configuration of the guided personal identity based action, generates a user interface that includes an option to perform the user-specified action using the data of the first user 304, and causes presentation of the generated user interface on the second user device 316. As shown in the diagram 300, the second user device 316 is displaying a user interface that includes a user interface element that, when activated by an operator of the second user device 316, performs (or causes to be performed) the user-specified action. In this scenario, the personal identity system 160 performs the user-specified action by identifying the first user 304 and the second user 306 on a particular social network service and forming a relationship between the first user 304 and the second user 306 on the social network service. In some embodiments, no action aside from receiving the identifier is required before performing the user-specified action (i.e., an action commences immediately upon scanning). In some of these instances, a user interface may be displayed merely to inform a user that the user-specified action has occurred. Thus, FIG. 3 illustrates an example implementation of the personal identity system 160 facilitating a guided personal identity based action configured by the first user 304 and provided to the second user 306.

FIG. 4 is a flow diagram illustrating an example method 400 for guided personal identity based actions. The operations of the method 400 may be performed by components of the personal identity system 160, and are so described below for the purposes of illustration.

At operation 410, the configuration module 230 receives a user-specified action from a first user device of a first user. The user-specified action pertains to the first user and uses data of the first user when performed. In some embodiments, the user-specified action comprises multiple user-specified actions received from the first user device, each of the multiple user-specified actions pertaining to the first user and using data of the first user when performed.

The instruction module 240 uses the data of the first user to facilitate performing the user-specified action. For instance, the data of the first user comprises a member identification operable to identify the first user on a social network service. In this instance, the user-specified action

can comprise a social network action of the social network service such as liking, friending, favoriting, posting, and so forth. The personal identity system **160** can perform (or cause performance of) the social network action by the instruction module **240** identifying the first user (using the data of the first user) and a second user on the social network service and sending a request to the social network service to perform the social network action involving the first user and the second user.

In various embodiments, the first user specifies rules or conditions associated with the user-specified action. In these embodiments, the instruction module **240** determines satisfaction of the condition prior to performing the user-specified action (e.g., if the condition is satisfied perform the user-specified action, and if the condition is not satisfied do not perform the user-specified action). In a specific example, if the user-specified action is a post or message, the first user can provide a rule for generating the message content to the configuration module **230** (e.g., automatically include a current geolocation of the second user in the message content). In other examples, the user-specified action is not available during a particular time period, or a particular user-specified action is not available to the second user unless the second user has a social network relationship with the first user such as being contacts or connected on the social network service.

In further embodiments, the user-specified action comprises sending a text message, such as a Short Message Service (SMS) message, a Multimedia Messaging Service (MMS) message, an Enhanced Messaging Service (EMS) message, and so forth. In some embodiments, the first user provides a message content for the text message to the personal identity system **160** along with the user-specified action (sending a text message in this example). In other embodiments, the message content is provided by the second user when the user-specified action is performed on the second user device of the second user.

In still further embodiments, the user-specified action comprises providing or sharing information such as contact information, WI-FI® settings, payment information (e.g., to allow for the second user to send a payment to the first user), availability based on the first user's calendar entries, and so forth. In a specific example, the user-specified action comprises providing WI-FI® settings to the second user to allow the second user to establish a connection with a WI-FI® network. In some instances, the first user provides the WI-FI® settings (e.g., a password, network name, and so on) to the configuration module **230** when configuring the user-specified action. In other instances, the instruction module **240**, upon performing the user-specific action (in this example providing WI-FI® settings to another user), retrieves the WI-FI® settings and communicates the retrieved WI-FI® settings to the second user device (e.g., retrieved from the first user device in real time and communicated to the second user device). In this way, the first user does not have to manually provide the WI-FI® settings when configuring the user-specified action.

At operation **420**, the configuration module **230** links the user-specified action to an identifier. For example, the configuration module **230** stores the user-specified action in association with the identifier such that provided the identifier, the instruction module **240**, or another module, can identify the user-specified action using the identifier (e.g., via a lookup in a database). In further example embodiments, the configuration module **230** can generate a machine-readable visual representation (e.g., a QR code) that encodes the identifier (discussed further below in con-

nection with FIG. **8**). In other embodiments, the configuration module **230** can encode the identifier using other automated identification schemes (e.g., RFID tags, NFC tags, smart tags, or audio based tags).

At operation **430**, the communication module **210** receives an indication of the identifier from the second user device of the second user. In some embodiments, the operation **410** and the operation **420** are performed at a first time and the operation **430** and subsequent operations are performed at a second time occurring after the first time. That is to say, the first user can configure the user-specified action in advance of the second user device providing an indication of the identifier corresponding to the user-specified action.

In various embodiments, the second user device includes components operable to detect a variety of identifiers. In various embodiments, the second user device includes RFID tag reader components, NFC smart tag detection components, optical reader components (e.g., an optical sensor to detect one-dimensional bar codes such as Universal Product Code (UPC) bar codes, multi-dimensional bar codes such as a QR code, Aztec code, Data Matrix, Dataglyph, MaxiCode, PDF417, Ultra Code, Uniform Commercial Code Reduced Space Symbology (UCC RSS)-2D bar code, and other optical codes), acoustic detection components (e.g., microphones to identify tagged audio signals), or a suitable combination thereof. In a specific example, the second user uses the second user device to scan a QR code being displayed on the first user device. Once the second user device extracts the identifier from the QR code, the second user device transmits an indication of the identifier, such as a network message including the identifier, to the communication module **210**.

In response, after the communication module **210** receives the indication of the identifier, at operation **440**, the instruction module **240** identifies the user-specified action linked to the identifier. For instance, the instruction module **240** performs a lookup of the user-specified action using the identifier.

At operation **450**, the data module **250** accesses the data of the first user to be used when the user-specified action is performed. As discussed above, in some instances, the first user provides data associated with the user-specified action when configuring the user-specified action and the data module **250** simply accesses the data along with the user-specified action. In other instances, the first user provides instructions for retrieving data associated with the user-specified action when configuring the user-specified action. In these instances, the data module **250** retrieves the data associated with the user-specified action according to the instructions provided by the first user. For example, the instructions can comprise a particular type of data to access such as a current geolocation of the user. In this example, the data module **250** queries the first user device, or another specified storage location, to retrieve the data to be used when performing the user-specified action.

At operation **460**, the presentation module **220** or the instruction module **240** generates a user interface that includes an option to perform the user-specified action using the data of the first user. In alternative embodiments, the instruction module **240** automatically performs the user-specified action on behalf of the second user in response to receiving the indication of the identifier. In various embodiments, the instruction module **240** augments, adapts, or otherwise modifies the option to perform the user-specified action according to various analyses and according to user-specified rules or conditions provided by the first user during the configuration of the user-specified action.

11

In an embodiment, the data module **250** accesses user data of the second user stored on the second user device or another storage location (e.g., a third party server such as a server hosting a social network service). For instance, the user data can comprise device type, device model, data download or upload speeds, demographic information of the second user (e.g., age, gender, marital status, or socioeconomic status), social networks the second user is a member of, frequently used apps, browser history, and so forth. In these embodiments, the instruction module **240** augments the options (e.g., makes certain options unavailable to the second user) or the user interface including the options (e.g., emphasize a particular option over other options) based on an analysis of the user data of the second user. For instance, the instruction module **240** modifies the user interface or the option to perform the user-specified action according to the user-specified rules or conditions corresponding to the user-specified action. In a specific example, the instruction module **240** can provide access or restrict access to certain user-specified actions based on a social network relationship between the first user and the second user on a particular social networking site (e.g., certain actions are accessible to friends of the first user and unavailable to other users).

In a specific example, the instruction module **240** determines a device capability to perform certain actions based on the user data of the second user. The instruction module **240** identifies a particular user-specified action from among the multiple user-specified actions according to the device capability. The instruction module **240** or the presentation module **220** generates the user interface to include an option to perform the particular user-specified action. As a concrete example, if the user data indicates that the second user is a member of a particular social network service, the instruction module **240** identifies a particular user-specified action associated with the particular social network service and an option to perform the particular user-specified action is included in the user interface. In this way, the instruction module **240** dynamically adapts the user interface according to the device capability of the second user device.

In another example, the instruction module **240** infers a user preference based on an analysis of the user data of the second user, the user preference being indicative of a preference to perform certain actions. The instruction module **240** identifies a particular user-specified action from among the multiple user-specified actions according to the user preference. Subsequently, the instruction module **240** generates the user interface to include an option to perform the particular user-specified action. As a concrete example, if the user data indicates that the second user frequently uses a particular app, the instruction module **240** identifies a particular user-specified action associated with the particular app and an option to perform the particular user-specified action is included in the user interface. As such, the instruction module **240** augments the user interface according to inferred preferences of the second user.

Turning now to FIGS. 5 and 6, example user interface diagrams depicting example user interfaces for providing an option to perform guided personal identity based actions are shown. Although user interfaces described herein (e.g., FIGS. 5, 6, 9, 11, 14, and 15) depict specific example user interfaces and user interface elements, these are merely non-limiting examples, and many other alternate user interfaces and user interface elements can be generated by the presentation module **220** and presented to the user. It will be noted that alternate presentations of the displays described herein include additional information, graphics, options, and

12

so forth; other presentations include less information, or provide abridged information for easy use by the user.

FIG. 5 depicts an example user interface **500** that includes user interface elements **510** and **520** that cause a particular user-specified action to be performed when activated (e.g., clicked or tapped on a touch screen display). In some embodiments, the user interface **500** is a browser user interface operating on a computer or mobile device. Similarly, FIG. 6 depicts an example user device **600** (e.g., smart phone) displaying an example user interface **610** that includes user interface elements **620** and **630** that cause a particular user-specified action to be performed when activated (e.g., clicked or tapped on a touch screen display).

Referring back to FIG. 4, at operation **470**, the presentation module **220** causes presentation of the generated user interface on the second user device. For instance, the presentation module **220** can transmit the user interface and an instruction to present the user interface to the second user device.

In further embodiments, the communication module **210** receives a selection of the option to perform the user-specified action from the second user device. The instruction module **240** performs (or causes performance of) the user-specified action in response to receiving the selection of the option from the second user device. The data module **250** stores an indication of the selection of the option in association with the second user device and the identifier (e.g., stored in the database(s) **134**). At a later time, the communication module **210** receives a subsequent indication of the identifier from the second user device. The presentation module **220** generates the user interface, in part, according to the stored indication of the selection. For instance, if a particular user-specified action has previously been performed, the instruction module **240** can omit an option to perform the user-specified action from subsequent user interface presentations.

In still further embodiments, the data module **250** stores a history of identifiers for a particular user. For example, for each indication of an identifier the communication module **210** receives, the data module **250** stores the identifier in association with an identification of the second user. The data module **250** accesses a history of identifiers for a particular user and the presentation module **220** can generate a user interface including the history of identifiers for the particular user. In these embodiments, the user interface is operable to perform the user-specified action corresponding to respective identifiers included in the history of identifiers. In this way, a particular user can revisit particular user-specified actions previously performed or stored.

In yet further embodiments, the instruction module **240** determines that the second user device is detecting the identifier from a machine-readable visual representation of the identifier being displayed on the first user device in real time. For instance, the first user device can communicate an indication, to the communication module **210**, indicating that the first user device is currently displaying a particular machine-readable visual representation.

In some embodiments, the first user device and the second user device are geo-enabled devices operable to communicate a geolocation to the communication module **210**. In other embodiments, the instruction module **240** derives an approximate location using an Internet Protocol (IP) location service or another similar service. The instruction module **240** can then infer that the second user device is detecting the machine-readable visual representation from the first user device by comparing the geolocations of the first user device and the second user device to determine that the

13

devices are within a distance of each other (e.g., a distance short enough for the second user device to detect the machine-readable visual representation being displayed on the first user device).

Based on the determination that the second user device is detecting the identifier from a machine-readable visual representation of the identifier being displayed on the first user device in real time, the instruction module 240 causes an interaction between the second user device and the first user device in real time. In an example, the interaction comprises automatically establishing a peer-to-peer communication session between the first user device and the second user device (e.g., a WI-FI® peer-to-peer session or a BLUETOOTH® pairing).

FIGS. 7A and 7B are swim-lane diagrams illustrating various communications between devices performing a method for guided personal identity based actions. At operation 710, a first user device 702 provides configuration data for a guided personal identity based action to the personal identity system 160. The configuration data can comprise a user specification of an action and data to be used when the action is performed.

As described above, at the operation 410, the configuration module 230 receives a user-specified action from the first user device 702. For instance, the configuration data includes the user-specified action. In various embodiments, the personal identity system 160 provides user interfaces configured to receive the configuration data to the first user device 702.

At the operation 420, the configuration module 230 links the user-specified action to an identifier. As further described in connection with FIGS. 8 and 9, the personal identity system 160 can generate a machine-readable visual representation that encodes the identifier. In some embodiments, the machine-readable visual representation is generated at the first user device 702.

Subsequently, at operation 712, the first user device 702 receives and stores the identifier representation. Although FIG. 7A shows the first user device 702 providing the configuration data, another device of the first user can provide the configuration data to the personal identity system 160 and a different device of the first user can store the identifier representation. That is to say, in some embodiments, the device that provides the configuration data can be different from the device that stores the identifier representation.

In various embodiments, the above operations of FIG. 7A are performed at a first time and subsequent operations of FIGS. 7A and 7B are performed at a second time after the first time (e.g., the identifier representation is configured during a first session and subsequently displayed during a later session). At operation 714, the first user device 702 displays the identifier representation. For instance, the identifier representation is displayed on a display screen of the first user device 702 such that another device can detect the identifier representation.

At operation 716, a second user device 704 detects the identifier from the identifier representation. For instance, the identifier representation comprises a QR code and a camera sensor of the second user device 704 detects and decodes the signal corresponding to the identifier representation being displayed on the first user device 702.

At operation 718, the second user device 704 provides an indication of the identifier to the personal identity system 160. For instance, once the second user device 704 decodes the identifier representation to extract the identifier, the

14

second user device 704 sends a request for the user-specified action corresponding with the identifier to the personal identity system 160.

As described above in connection with FIG. 4, at the operation 430, the communication module 210 receives an indication of the identifier from the second user device 704. At the operation 440, the instruction module 240 identifies the user-specified action linked to the identifier (e.g., via a lookup).

In continuing with the discussion in connection with FIG. 7A, FIG. 7B shows additional operations. At operation 450, the data module 250 accesses the data of the first user to be used when the user-specified action is performed.

At operation 720, the first user device 702 provides data to the personal identity system 160. In other embodiments, the data for the user-specified action is stored by the personal identity system 160 (e.g., stored in the database(s) 134).

As described above in connection with FIG. 4, at the operation 460, the presentation module 220 or the instruction module 240 generates a user interface that includes an option to perform the user-specified action using the data of the first user. At the operation 470, the presentation module 220 causes presentation of the generated user interface on the second user device 704.

At operation 722, the second user device 704 presents the generated user interface. The presentation of the generated user interface on the second user device 704 is an interactive presentation allowing the user of the second user device 704 to provide input, such as by selecting an option to perform the user-specified action.

At operation 724, the second user device 704 receives a selection of an option to perform the user-specified action. In some instances, the second user device 704 receives multiple selections of options to perform multiple user-specified actions.

At operation 726, the communication module 210 or the instruction module 240 receives an indication of the selection to perform the user-specified action. For instance, the second user device 704 sends a request to the personal identity system 160 to perform a particular user-specified action. In other embodiments, the user-specified action is performed locally on the second user device 704 without further communication with the personal identity system 160.

At operation 728, the instruction module 240 performs the selected action. In performing the selected action the instruction module 240 can cause the exchange of data between any of the first user device 702 at operation 730, the second user device 704 at operation 732, the personal identity system 160, or a third party server (not shown).

FIG. 8 is a flow diagram illustrating further example operations for guided personal identity based actions. After the communication module 210 receives the user-specified action at the operation 410 and the configuration module 230 links the user-specified action to the identifier at the operation 420, the additional example operations of FIG. 8 are performed in some example embodiments.

At operation 810, the configuration module 230 generates a machine-readable visual representation (e.g., a QR code) that encodes the identifier. For instance, the configuration module 230 generates an image file that includes the machine-readable visual representation.

At operation 820, the configuration module 230 transmits the generated machine-readable visual representation (e.g., an image file) to the first user device to be stored by the first user device and subsequently displayed on a user interface of the first user device. For example, the first user device

15

stores multiple machine-readable visual representations corresponding to different user-specified actions or sets of user-specified actions. The first user of the first user device can display a particular machine-readable visual representation when the first user desires another user to perform the user-specified actions corresponding to the particular machine-readable visual representation.

Similar to the operation 430 discussed above, at operation 830, the communication module 210 receives the indication of the identifier in response to the second user device physically detecting in real time the identifier from the machine-readable visual representation being displayed on the first user device. For instance, the second user device scans a QR code being displayed by the first user device. Subsequently, the personal identity system 160 performs the operation 440 and subsequent operations of the example method 400 as discussed in connection with FIG. 4 above.

FIG. 9 is a user interface diagram 900 depicting an example user interface 910 for displaying a machine-readable visual representation 920 (e.g., a QR code) that encodes an identifier. In some embodiments, the machine-readable visual representation 920 includes text, an image, or an animation, such as element 930, representative of the user-specified action associated with the machine-readable visual representation 920. In an embodiment, multiple machine-readable visual representations are stored on a particular user device. In this embodiment, a user 940 can scroll through or otherwise navigate the multiple machine-readable visual representations via a touch-based gesture 950 (e.g., a swipe performed by sliding a finger or pointing instrument in a particular direction across a display).

The following discussion in connection with FIGS. 10 and 11 is again directed to configuration of a particular guided personal identity based action. FIG. 10 is a flow diagram illustrating further example operations for configuring guided personal identity based actions. Prior to the operations of the method 400 discussed above, the personal identity system 160 performs the operations of FIG. 10 in some example embodiments. At operation 1010, the configuration module 230 or the presentation module 220 causes presentation of multiple action options on a user interface of the first user device. For instance, the personal identity system 160 can provide a user interface that includes predefined actions and includes fields for inputting data associated with the predefined actions.

In further embodiments, the configuration module 230 determines the action options to include in the user interface based on user data of the first user. For instance, the configuration module 230 can retrieve data indicating a particular social network service the first user is a member of from the user device, a third party server, or another source. Based on the data of the first user indicating the first user is a member of the particular social network service, the configuration module 230 determines a particular action option associated with the particular social network service and includes the particular action option in the user interface to be presented on the first user device.

At operation 1020, the communication module 210 receives a selection of an action option from among the multiple action options. The first user, or another operator configuring a particular guided personal identity based action, can provide selections of action options along with data associated with the action option to configure the particular guided personal identity based action. Subsequently, at the operation 410, the communication module 210 receives the user-specified action (e.g., the user-speci-

16

fied action indicated by the selection of the action option receive at the operation 1020).

FIG. 11 is a user interface diagram 1100 depicting an example user interface 1110 for configuration of guided personal identity based actions. A user interface element 1120 allows the user to provide data associated with a particular action. In this example, the user can provide WI-FI® settings data for an action directed to establishing a WI-FI® connection (e.g., network login credentials). In further embodiments, the user can specify conditions or rules (discussed above in connection with FIG. 4) for the action (e.g., a condition of being a contact of the user on a social network server prior performing the action). A user interface element 1130 allows the user to generate and save a QR code for the user-specified action configured using the user interface 1110. A user interface element 1140 allows the user to share the QR code with other users (e.g., via a social messaging service communication, an email, or an SMS message). A user interface element 1150 provides the user an option to generate additional QR codes for additional user-specified actions.

The following discussion in connection with FIGS. 12-15 is directed to analytics associated with guided personal identity based actions. At the operation 430, the communication module 210 receives the indication of the identifier from the second user device. Subsequently, the additional operations of FIGS. 12 and 13 are performed in some example embodiments as discussed below.

FIG. 12 is a flow diagram illustrating example operations for performing analytics in association with a particular identifier. At operation 1210, the analytics module 260 updates an identifier metric corresponding to the identifier. The identifier metric may include an access count incremented each time an indication of the identifier is received. For instance, each time a QR code is scanned, the access count is incremented. In some embodiments, as further discussed in connection with FIG. 13, contextual data associated with instances of a scan are stored and can be subsequently used for various analyses (e.g., scans from a particular country or region, scans during a particular time of day, scans from particular device types, or scans from users with particular demographics).

At operation 1220, the presentation module 220 causes presentation of the identifier metric on a user interface of the first user device. The identifier metric or other metrics calculated by the analytics module 260 can be presented using a variety of visual and textual formats.

FIG. 13 is a flow diagram illustrating example operations for performing analytics in association with a particular identifier. In response to receiving the indication of the identifier from the second user device, at operation 1310, the data module 250 retrieves context attributes from the second user device. For example, the context attributes comprise device type, device model, a time stamp, geolocation, or other sensor data of the second user device.

At operation 1320, the data module 250 stores the context attributes in association with the identifier. For instance, the data module 250 can store the context attributes in the database(s) 134.

At operation 1330, the analytics module 260 identifies a characteristic corresponding to the identifier by analyzing the context attributes stored in association with the identifier. For instance, the analytics module 260 can identify a particular characteristic comprising a high density clustering of scans with a certain geolocation (e.g., many scans in a particular geographic vicinity). Such a characteristic can be of interest to the user who configured the scan. In some

embodiments, the first user can specify rules or conditions based on the characteristics associated with analytics generated by the analytics module 260. For example, once a particular number of scans within a certain geographic boundary is exceeded, the user-specified action is no longer available to users within the geographic boundary.

At operation 1340, the presentation module 220 causes presentation of the characteristic on a user interface of the first user device. The presentation module 220 can generate a variety of text, graphics, images, and animations for presentation of the characteristic.

FIG. 14 is a user interface diagram 1400 depicting an example user interface 1410 for displaying a various analytics generated by the analytics module 260. In this example, the user interface 1410 is displaying scan history data, such as history data 1420, over time. The scan history data can include a variety of information such as a count of scans for a particular identifier for a particular date and platform.

FIG. 15 is a user interface diagram 1500 depicting an example user interface 1510 for displaying various analytics generated by the analytics module 260. In this example, the user interface 1510 is displaying geolocation data associated with scans, such as geolocation data 1520 (e.g., latitude, longitude, altitude, and time stamp), for a particular time period.

Modules, Components, and Logic

Certain embodiments are described herein as including logic or a number of components, modules, or mechanisms. Modules can constitute either software modules (e.g., code embodied on a machine-readable medium or in a transmission signal) or hardware modules. A “hardware module” is a tangible unit capable of performing certain operations and can be configured or arranged in a certain physical manner. In various example embodiments, one or more computer systems (e.g., a standalone computer system, a client computer system, or a server computer system) or one or more hardware modules of a computer system (e.g., a processor or a group of processors) is configured by software (e.g., an application or application portion) as a hardware module that operates to perform certain operations as described herein.

In some embodiments, a hardware module is implemented mechanically, electronically, or any suitable combination thereof. For example, a hardware module can include dedicated circuitry or logic that is permanently configured to perform certain operations. For example, a hardware module can be a special-purpose processor, such as a Field-Programmable Gate Array (FPGA) or an Application Specific Integrated Circuit (ASIC). A hardware module may also include programmable logic or circuitry that is temporarily configured by software to perform certain operations. For example, a hardware module can include software encompassed within a general-purpose processor or other programmable processor. It will be appreciated that the decision to implement a hardware module mechanically, in dedicated and permanently configured circuitry, or in temporarily configured circuitry (e.g., configured by software) can be driven by cost and time considerations.

Accordingly, the phrase “hardware module” should be understood to encompass a tangible entity, be that an entity that is physically constructed, permanently configured (e.g., hardwired), or temporarily configured (e.g., programmed) to operate in a certain manner or to perform certain operations described herein. As used herein, “hardware-implemented module” refers to a hardware module. Considering embodiments in which hardware modules are temporarily config-

ured (e.g., programmed), each of the hardware modules need not be configured or instantiated at any one instance in time. For example, where a hardware module comprises a general-purpose processor configured by software to become a special-purpose processor, the general-purpose processor may be configured as respectively different special-purpose processors (e.g., comprising different hardware modules) at different times. Software can accordingly configure a particular processor or processors, for example, to constitute a particular hardware module at one instance of time and to constitute a different hardware module at a different instance of time.

Hardware modules can provide information to, and receive information from, other hardware modules. Accordingly, the described hardware modules can be regarded as being communicatively coupled. Where multiple hardware modules exist contemporaneously, communications can be achieved through signal transmission (e.g., over appropriate circuits and buses) between or among two or more of the hardware modules. In embodiments in which multiple hardware modules are configured or instantiated at different times, communications between such hardware modules may be achieved, for example, through the storage and retrieval of information in memory structures to which the multiple hardware modules have access. For example, one hardware module performs an operation and stores the output of that operation in a memory device to which it is communicatively coupled. A further hardware module can then, at a later time, access the memory device to retrieve and process the stored output. Hardware modules can also initiate communications with input or output devices, and can operate on a resource (e.g., a collection of information).

The various operations of example methods described herein can be performed, at least partially, by one or more processors that are temporarily configured (e.g., by software) or permanently configured to perform the relevant operations. Whether temporarily or permanently configured, such processors constitute processor-implemented modules that operate to perform one or more operations or functions described herein. As used herein, “processor-implemented module” refers to a hardware module implemented using one or more processors.

Similarly, the methods described herein can be at least partially processor-implemented, with a particular processor or processors being an example of hardware. For example, at least some of the operations of a method can be performed by one or more processors or processor-implemented modules. Moreover, the one or more processors may also operate to support performance of the relevant operations in a “cloud computing” environment or as a “software as a service” (SaaS). For example, at least some of the operations may be performed by a group of computers (as examples of machines including processors), with these operations being accessible via a network (e.g., the Internet) and via one or more appropriate interfaces (e.g., an Application Program Interface (API)).

The performance of certain of the operations may be distributed among the processors, not only residing within a single machine, but deployed across a number of machines. In some example embodiments, the processors or processor-implemented modules are located in a single geographic location (e.g., within a home environment, an office environment, or a server farm). In other example embodiments, the processors or processor-implemented modules are distributed across a number of geographic locations.

Applications

FIG. 16 illustrates an example mobile device 1600 executing a mobile operating system (e.g., IOS™, ANDROID™, WINDOWS® Phone, or other mobile operating systems), consistent with some embodiments. In one embodiment, the mobile device 1600 includes a touch screen operable to receive tactile data from a user 1602. For instance, the user 1602 may physically touch 1604 the mobile device 1600, and in response to the touch 1604, the mobile device 1600 may determine tactile data such as touch location, touch force, or gesture motion. In various example embodiments, the mobile device 1600 displays a home screen 1606 (e.g., Springboard on IOS™) operable to launch applications or otherwise manage various aspects of the mobile device 1600. In some example embodiments, the home screen 1606 provides status information such as battery life, connectivity, or other hardware statuses. The user 1602 can activate user interface elements by touching an area occupied by a respective user interface element. In this manner, the user 1602 interacts with the applications of the mobile device 1600. For example, touching the area occupied by a particular icon included in the home screen 1606 causes launching of an application corresponding to the particular icon.

Many varieties of applications (also referred to as “apps”) can be executed on the mobile device 1600, such as native applications (e.g., applications programmed in Objective-C, Swift, or another suitable language running on IOS™, or applications programmed in Java running on ANDROID™), mobile web applications (e.g., applications written in Hypertext Markup Language-5 (HTML5)), or hybrid applications (e.g., a native shell application that launches an HTML5 session). For example, the mobile device 1600 includes a messaging app, an audio recording app, a camera app, a book reader app, a media app, a fitness app, a file management app, a location app, a browser app, a settings app, a contacts app, a telephone call app, or other apps (e.g., gaming apps, social networking apps, biometric monitoring apps). In another example, the mobile device 1600 includes a social messaging app 1608 such as SNAPCHAT® that, consistent with some embodiments, allows users to exchange ephemeral messages that include media content. In this example, the social messaging app 1608 can incorporate aspects of embodiments described herein.

Software Architecture

FIG. 17 is a block diagram 1700 illustrating an architecture of software 1702, which can be installed on any one or more of the devices described above. FIG. 17 is merely a non-limiting example of a software architecture, and it will be appreciated that many other architectures can be implemented to facilitate the functionality described herein. In various embodiments, the software 1702 is implemented by hardware such as a machine 1800 of FIG. 18 that includes processors 1810, memory 1830, and I/O components 1850. In this example architecture, the software 1702 can be conceptualized as a stack of layers where each layer may provide a particular functionality. For example, the software 1702 includes layers such as an operating system 1704, libraries 1706, frameworks 1708, and applications 1710. Operationally, the applications 1710 invoke application programming interface (API) calls 1712 through the software stack and receive messages 1714 in response to the API calls 1712, consistent with some embodiments.

In various implementations, the operating system 1704 manages hardware resources and provides common services. The operating system 1704 includes, for example, a kernel 1720, services 1722, and drivers 1724. The kernel

1720 acts as an abstraction layer between the hardware and the other software layers consistent with some embodiments. For example, the kernel 1720 provides memory management, processor management (e.g., scheduling), component management, networking, and security settings, among other functionality. The services 1722 can provide other common services for the other software layers. The drivers 1724 are responsible for controlling or interfacing with the underlying hardware, according to some embodiments. For instance, the drivers 1724 can include display drivers, camera drivers, BLUETOOTH® drivers, flash memory drivers, serial communication drivers (e.g., Universal Serial Bus (USB) drivers), WI-FI® drivers, audio drivers, power management drivers, and so forth.

In some embodiments, the libraries 1706 provide a low-level common infrastructure utilized by the applications 1710. The libraries 1706 can include system libraries 1730 (e.g., C standard library) that can provide functions such as memory allocation functions, string manipulation functions, mathematic functions, and the like. In addition, the libraries 1706 can include API libraries 1732 such as media libraries (e.g., libraries to support presentation and manipulation of various media formats such as Moving Picture Experts Group-4 (MPEG4), Advanced Video Coding (H.264 or AVC), Moving Picture Experts Group Layer-3 (MP3), Advanced Audio Coding (AAC), Adaptive Multi-Rate (AMR) audio codec, Joint Photographic Experts Group (JPEG or JPG), or Portable Network Graphics (PNG)), graphics libraries (e.g., an OpenGL framework used to render in two dimensions (2D) and three dimensions (3D) in a graphic context on a display), database libraries (e.g., SQLite to provide various relational database functions), web libraries (e.g., WebKit to provide web browsing functionality), and the like. The libraries 1706 can also include a wide variety of other libraries 1734 to provide many other APIs to the applications 1710.

The frameworks 1708 provide a high-level common infrastructure that can be utilized by the applications 1710, according to some embodiments. For example, the frameworks 1708 provide various graphic user interface (GUI) functions, high-level resource management, high-level location services, and so forth. The frameworks 1708 can provide a broad spectrum of other APIs that can be utilized by the applications 1710, some of which may be specific to a particular operating system or platform.

In an example embodiment, the applications 1710 include a home application 1750, a contacts application 1752, a browser application 1754, a book reader application 1756, a location application 1758, a media application 1760, a messaging application 1762, a game application 1764, and a broad assortment of other applications such as a third party application 1766. According to some embodiments, the applications 1710 are programs that execute functions defined in the programs. Various programming languages can be employed to create one or more of the applications 1710, structured in a variety of manners, such as object-oriented programming languages (e.g., Objective-C, Java, or C++) or procedural programming languages (e.g., C or assembly language). In a specific example, the third party application 1766 (e.g., an application developed using the ANDROID™ or IOS™ software development kit (SDK) by an entity other than the vendor of the particular platform) may be mobile software running on a mobile operating system such as IOS™, ANDROID™, WINDOWS® PHONE, or another mobile operating system. In this example, the third party application 1766 can invoke the API

calls **1712** provided by the operating system **1704** to facilitate functionality described herein.
Example Machine Architecture and Machine-Readable Medium

FIG. **18** is a block diagram illustrating components of a machine **1800**, according to some embodiments, able to read instructions from a machine-readable medium (e.g., a machine-readable storage medium) and perform any one or more of the methodologies discussed herein. Specifically, FIG. **18** shows a diagrammatic representation of the machine **1800** in the example form of a computer system, within which instructions **1816** (e.g., software, a program, an application, an applet, an app, or other executable code) for causing the machine **1800** to perform any one or more of the methodologies discussed herein can be executed. In alternative embodiments, the machine **1800** operates as a standalone device or can be coupled (e.g., networked) to other machines. In a networked deployment, the machine **1800** may operate in the capacity of a server machine or a client machine in a server-client network environment, or as a peer machine in a peer-to-peer (or distributed) network environment. The machine **1800** can comprise, but not be limited to, a server computer, a client computer, a personal computer (PC), a tablet computer, a laptop computer, a netbook, a set-top box (STB), a personal digital assistant (PDA), an entertainment media system, a cellular telephone, a smart phone, a mobile device, a wearable device (e.g., a smart watch), a smart home device (e.g., a smart appliance), other smart devices, a web appliance, a network router, a network switch, a network bridge, or any machine capable of executing the instructions **1816**, sequentially or otherwise, that specify actions to be taken by the machine **1800**. Further, while only a single machine **1800** is illustrated, the term “machine” shall also be taken to include a collection of machines **1800** that individually or jointly execute the instructions **1816** to perform any one or more of the methodologies discussed herein.

In various embodiments, the machine **1800** comprises processors **1810**, memory **1830**, and I/O components **1850**, which can be configured to communicate with each other via a bus **1802**. In an example embodiment, the processors **1810** (e.g., a Central Processing Unit (CPU), a Reduced Instruction Set Computing (RISC) processor, a Complex Instruction Set Computing (CISC) processor, a Graphics Processing Unit (GPU), a Digital Signal Processor (DSP), an Application Specific Integrated Circuit (ASIC), a Radio-Frequency Integrated Circuit (RFIC), another processor, or any suitable combination thereof) include, for example, a processor **1812** and a processor **1814** that may execute the instructions **1816**. The term “processor” is intended to include multi-core processors that may comprise two or more independent processors (also referred to as “cores”) that can execute instructions contemporaneously. Although FIG. **18** shows multiple processors, the machine **1800** may include a single processor with a single core, a single processor with multiple cores (e.g., a multi-core processor), multiple processors with a single core, multiple processors with multiples cores, or any combination thereof.

The memory **1830** comprises a main memory **1832**, a static memory **1834**, and a storage unit **1836** accessible to the processors **1810** via the bus **1802**, according to some embodiments. The storage unit **1836** can include a machine-readable medium **1838** on which are stored the instructions **1816** embodying any one or more of the methodologies or functions described herein. The instructions **1816** can also reside, completely or at least partially, within the main memory **1832**, within the static memory **1834**, within at least

one of the processors **1810** (e.g., within the processor's cache memory), or any suitable combination thereof, during execution thereof by the machine **1800**. Accordingly, in various embodiments, the main memory **1832**, the static memory **1834**, and the processors **1810** are considered machine-readable media **1838**.

As used herein, the term “memory” refers to a machine-readable medium **1838** able to store data temporarily or permanently and may be taken to include, but not be limited to, random-access memory (RAM), read-only memory (ROM), buffer memory, flash memory, and cache memory. While the machine-readable medium **1838** is shown in an example embodiment to be a single medium, the term “machine-readable medium” should be taken to include a single medium or multiple media (e.g., a centralized or distributed database, or associated caches and servers) able to store the instructions **1816**. The term “machine-readable medium” shall also be taken to include any medium, or combination of multiple media, that is capable of storing instructions (e.g., instructions **1816**) for execution by a machine (e.g., machine **1800**), such that the instructions, when executed by one or more processors of the machine **1800** (e.g., processors **1810**), cause the machine **1800** to perform any one or more of the methodologies described herein. Accordingly, a “machine-readable medium” refers to a single storage apparatus or device, as well as “cloud-based” storage systems or storage networks that include multiple storage apparatus or devices. The term “machine-readable medium” shall accordingly be taken to include, but not be limited to, one or more data repositories in the form of a solid-state memory (e.g., flash memory), an optical medium, a magnetic medium, other non-volatile memory (e.g., Erasable Programmable Read-Only Memory (EPROM)), or any suitable combination thereof. The term “machine-readable medium” specifically excludes non-statutory signals per se.

The I/O components **1850** include a wide variety of components to receive input, provide output, produce output, transmit information, exchange information, capture measurements, and so on. In general, it will be appreciated that the I/O components **1850** can include many other components that are not shown in FIG. **18**. The I/O components **1850** are grouped according to functionality merely for simplifying the following discussion, and the grouping is in no way limiting. In various example embodiments, the I/O components **1850** include output components **1852** and input components **1854**. The output components **1852** include visual components (e.g., a display such as a plasma display panel (PDP), a light emitting diode (LED) display, a liquid crystal display (LCD), a projector, or a cathode ray tube (CRT)), acoustic components (e.g., speakers), haptic components (e.g., a vibratory motor), other signal generators, and so forth. The input components **1854** include alphanumeric input components (e.g., a keyboard, a touch screen configured to receive alphanumeric input, a photo-optical keyboard, or other alphanumeric input components), point based input components (e.g., a mouse, a touchpad, a trackball, a joystick, a motion sensor, or other pointing instruments), tactile input components (e.g., a physical button, a touch screen that provides location and force of touches or touch gestures, or other tactile input components), audio input components (e.g., a microphone), and the like.

In some further example embodiments, the I/O components **1850** include biometric components **1856**, motion components **1858**, environmental components **1860**, or position components **1862**, among a wide array of other com-

ponents. For example, the biometric components **1856** include components to detect expressions (e.g., hand expressions, facial expressions, vocal expressions, body gestures, or eye tracking), measure biosignals (e.g., blood pressure, heart rate, body temperature, perspiration, or brain waves), identify a person (e.g., voice identification, retinal identification, facial identification, fingerprint identification, or electroencephalogram based identification), and the like. The motion components **1858** include acceleration sensor components (e.g., an accelerometer), gravitation sensor components, rotation sensor components (e.g., a gyroscope), and so forth. The environmental components **1860** include, for example, illumination sensor components (e.g., a photometer), temperature sensor components (e.g., one or more thermometers that detect ambient temperature), humidity sensor components, pressure sensor components (e.g., a barometer), acoustic sensor components (e.g., one or more microphones that detect background noise), proximity sensor components (e.g., infrared sensors that detect nearby objects), gas sensor components (e.g., machine olfaction detection sensors, gas detection sensors to detect concentrations of hazardous gases for safety or to measure pollutants in the atmosphere), or other components that may provide indications, measurements, or signals corresponding to a surrounding physical environment. The position components **1862** include location sensor components (e.g., a Global Positioning System (GPS) receiver component), altitude sensor components (e.g., altimeters or barometers that detect air pressure from which altitude may be derived), orientation sensor components (e.g., magnetometers), and the like.

Communication can be implemented using a wide variety of technologies. The I/O components **1850** may include communication components **1864** operable to couple the machine **1800** to a network **1880** or devices **1870** via a coupling **1882** and a coupling **1872**, respectively. For example, the communication components **1864** include a network interface component or another suitable device to interface with the network **1880**. In further examples, communication components **1864** include wired communication components, wireless communication components, cellular communication components, Near Field Communication (NFC) components, BLUETOOTH® components (e.g., BLUETOOTH® Low Energy), WI-FI® components, and other communication components to provide communication via other modalities. The devices **1870** may be another machine or any of a wide variety of peripheral devices (e.g., a peripheral device coupled via a Universal Serial Bus (USB)).

Moreover, in some embodiments, the communication components **1864** detect identifiers or include components operable to detect identifiers. For example, the communication components **1864** include Radio Frequency Identification (RFID) tag reader components, NFC smart tag detection components, optical reader components (e.g., an optical sensor to detect one-dimensional bar codes such as a Universal Product Code (UPC) bar code, multi-dimensional bar codes such as a Quick Response (QR) code, Aztec Code, Data Matrix, Dataglyph, MaxiCode, PDF417, Ultra Code, Uniform Commercial Code Reduced Space Symbology (UCC RSS)-2D bar codes, and other optical codes), acoustic detection components (e.g., microphones to identify tagged audio signals), or any suitable combination thereof. In addition, a variety of information can be derived via the communication components **1864**, such as location via Internet Protocol (IP) geolocation, location via WI-FI® signal triangulation, location via detecting a BLU-

ETOOTH® or NFC beacon signal that may indicate a particular location, and so forth.

Transmission Medium

In various example embodiments, one or more portions of the network **1880** can be an ad hoc network, an intranet, an extranet, a virtual private network (VPN), a local area network (LAN), a wireless LAN (WLAN), a wide area network (WAN), a wireless WAN (WWAN), a metropolitan area network (MAN), the Internet, a portion of the Internet, a portion of the Public Switched Telephone Network (PSTN), a plain old telephone service (POTS) network, a cellular telephone network, a wireless network, a WI-FI® network, another type of network, or a combination of two or more such networks. For example, the network **1880** or a portion of the network **1880** may include a wireless or cellular network, and the coupling **1882** may be a Code Division Multiple Access (CDMA) connection, a Global System for Mobile communications (GSM) connection, or another type of cellular or wireless coupling. In this example, the coupling **1882** can implement any of a variety of types of data transfer technology, such as Single Carrier Radio Transmission Technology (1xRTT), Evolution-Data Optimized (EVDO) technology, General Packet Radio Service (GPRS) technology, Enhanced Data rates for GSM Evolution (EDGE) technology, third Generation Partnership Project (3GPP) including 3G, fourth generation wireless (4G) networks, Universal Mobile Telecommunications System (UMTS), High Speed Packet Access (HSPA), Worldwide Interoperability for Microwave Access (WiMAX), Long Term Evolution (LTE) standard, others defined by various standard-setting organizations, other long range protocols, or other data transfer technology.

In example embodiments, the instructions **1816** are transmitted or received over the network **1880** using a transmission medium via a network interface device (e.g., a network interface component included in the communication components **1864**) and utilizing any one of a number of well-known transfer protocols (e.g., Hypertext Transfer Protocol (HTTP)). Similarly, in other example embodiments, the instructions **1816** are transmitted or received using a transmission medium via the coupling **1872** (e.g., a peer-to-peer coupling) to the devices **1870**. The term “transmission medium” shall be taken to include any intangible medium that is capable of storing, encoding, or carrying the instructions **1816** for execution by the machine **1800**, and includes digital or analog communications signals or other intangible media to facilitate communication of such software.

Furthermore, the machine-readable medium **1838** is non-transitory (in other words, not having any transitory signals) in that it does not embody a propagating signal. However, labeling the machine-readable medium **1838** “non-transitory” should not be construed to mean that the medium is incapable of movement; the medium should be considered as being transportable from one physical location to another. Additionally, since the machine-readable medium **1838** is tangible, the medium may be considered to be a machine-readable device.

Language

Throughout this specification, plural instances may implement components, operations, or structures described as a single instance. Although individual operations of one or more methods are illustrated and described as separate operations, one or more of the individual operations may be performed concurrently, and nothing requires that the operations be performed in the order illustrated. Structures and functionality presented as separate components in example configurations may be implemented as a combined structure

25

or component. Similarly, structures and functionality presented as a single component may be implemented as separate components. These and other variations, modifications, additions, and improvements fall within the scope of the subject matter herein.

Although an overview of the inventive subject matter has been described with reference to specific example embodiments, various modifications and changes may be made to these embodiments without departing from the broader scope of embodiments of the present disclosure. Such embodiments of the inventive subject matter may be referred to herein, individually or collectively, by the term “invention” merely for convenience and without intending to voluntarily limit the scope of this application to any single disclosure or inventive concept if more than one is, in fact, disclosed.

The embodiments illustrated herein are described in sufficient detail to enable those skilled in the art to practice the teachings disclosed. Other embodiments may be used and derived therefrom, such that structural and logical substitutions and changes may be made without departing from the scope of this disclosure. The Detailed Description, therefore, is not to be taken in a limiting sense, and the scope of various embodiments is defined only by the appended claims, along with the full range of equivalents to which such claims are entitled.

As used herein, the term “or” may be construed in either an inclusive or exclusive sense. Moreover, plural instances may be provided for resources, operations, or structures described herein as a single instance. Additionally, boundaries between various resources, operations, modules, engines, and data stores are somewhat arbitrary, and particular operations are illustrated in a context of specific illustrative configurations. Other allocations of functionality are envisioned and may fall within a scope of various embodiments of the present disclosure. In general, structures and functionality presented as separate resources in the example configurations may be implemented as a combined structure or resource. Similarly, structures and functionality presented as a single resource may be implemented as separate resources. These and other variations, modifications, additions, and improvements fall within a scope of embodiments of the present disclosure as represented by the appended claims. The specification and drawings are, accordingly, to be regarded in an illustrative rather than a restrictive sense.

What is claimed is:

1. A system comprising:

hardware processing circuitry configured to perform operations comprising:

receiving an action from a first device of a first user; generating a machine-readable code that visually represents an identifier of the action and includes a graphical element representing the action;

causing presentation of the machine-readable code on the first device;

determining that a second device of a second user has interacted with the machine-readable code presented on the first device; and

in response to determining that the second device has interacted with the machine-readable code presented on the first device:

analyzing one or more preferences of the second user to determine that the second user frequently uses a particular application;

in response to determining that the second user frequently uses the particular application based on the one or more

26

preferences, identifying a particular user-specified action from among multiple user-specified actions associated with the particular application;

generating a user interface on the second device to include an additional option to perform the particular user-specified action; and

emphasizing a first of one or more options presented in the user interface over a second option of the one or more options based on a device type or device model of the second device.

2. The system of claim 1, the operations comprising: presenting, in the user interface, an option to automatically include a current location of the second device in a message transmitted to the first device; and

disabling one or more options presented in the user interface to make one or more options unavailable to the second user based on a device type or device model of the second device.

3. The system of claim 1, wherein the operations further comprise:

causing the machine-readable code to be presented on the first device in response to detecting a swipe gesture along a particular direction across a display of the first device that navigates through multiple machine-readable codes.

4. The system of claim 1, wherein the operations further comprise:

determining a device type or device model of the second device.

5. The system of claim 4, wherein the operations further comprise:

emphasizing a first of one or more options presented in the user interface over a second option of the one or more options based on the device type or device model of the second device.

6. The system of claim 1, wherein the operations further comprise:

updating a metric corresponding to the machine-readable code in response to determining that the second device of the second user has interacted with the machine-readable code presented on the first device; and causing the metric to be presented on the first device of the first user.

7. The system of claim 1, wherein the particular user-specified action comprises multiple user-specified actions received from the first device, each of the multiple user-specified actions pertains to the first user and uses data of the first user when performed, the operations further comprising identifying the first user and the second user on a social network and forming a relationship between the first user and the second user on the social network in response to determining based on the data that the first user and the second user are not connected on the social network.

8. The system of claim 1, wherein the operations further comprise:

generating a metric that includes an access count incremented each time an interaction with the machine-readable code is detected.

9. The system of claim 1, wherein the operations further comprise:

associating contextual data with each instance of an interaction with the machine-readable code, the contextual data comprising a representation of a geographical location from which the interaction is detected, a time of day during which the interaction is detected, or a device type used to interact with the machine-readable code.

27

10. The system of claim 1, wherein the operations further comprise:

identifying a characteristic corresponding to the identifier by analyzing contextual data associated with each instance of an interaction with the machine-readable code; and

causing presentation of the identified characteristic on the first device of the first user.

11. The system of claim 1, wherein the operations further comprise:

identifying a density of clusterings of scans within a certain geolocation based on contextual data comprising a representation of a geographical location from which an interaction with the machine-readable code is detected;

based on the density, determining that a number of scans within the certain geolocation has reached a threshold; and

in response to determining that the number of scans within the certain geolocation has reached a threshold, disabling performance of the action in the certain geolocation.

12. The system of claim 1, wherein the operations further comprise displaying a geographical location from which an interaction with the machine-readable code is detected including a latitude, longitude, altitude and time stamp for a particular time period on the first device of the first user.

13. A method comprising:

receiving an action from a first device of a first user;

generating a machine-readable code that visually represents an identifier of the action and includes a graphical element representing the action;

causing presentation of the machine-readable code on the first device;

determining that a second device of a second user has interacted with the machine-readable code presented on the first device; and

in response to determining that the second device has interacted with the machine-readable code presented on the first device:

in response to determining that the second device has interacted with the machine-readable code presented on the first device:

analyzing one or more preferences of the second user to determine that the second user frequently uses a particular application;

in response to determining that the second user frequently uses the particular application based on the one or more preferences, identifying a particular user-specified action from among multiple user-specified actions associated with the particular application;

generating a user interface on the second device to include an additional option to perform the particular user-specified action; and

emphasizing a first of one or more options presented in the user interface over a second option of the one or more options based on a device type or device model of the second device.

14. A non-transitory computer readable storage medium comprising instructions that when executed by hardware processing circuitry cause the hardware processing circuitry to perform operations, the operations comprising:

receiving an action from a first device of a first user;

generating a machine-readable code that visually represents an identifier of the action and includes a graphical element representing the action;

28

causing presentation of the machine-readable code on the first device;

determining that a second device of a second user has interacted with the machine-readable code presented on the first device; and

in response to determining that the second device has interacted with the machine-readable code presented on the first device:

analyzing one or more preferences of the second user to determine that the second user frequently uses a particular application;

in response to determining that the second user frequently uses the particular application based on the one or more preferences, identifying a particular user-specified action from among multiple user-specified actions associated with the particular application;

generating a user interface on the second device to include an additional option to perform the particular user-specified action; and

emphasizing a first of one or more options presented in the user interface over a second option of the one or more options based on a device type or device model of the second device.

15. The non-transitory computer readable storage medium of claim 14, wherein the operations further comprise:

presenting, in the user interface, an option to automatically include a current location of the second device in a message transmitted to the first device; and

disabling one or more options presented in the user interface to make one or more options unavailable to the second user based on a device type or device model of the second device.

16. The non-transitory computer readable storage medium of claim 14, wherein the operations further comprise:

disabling one or more options presented in the user interface to make one or more options unavailable to the second user based on a device type or device model of the second device.

17. The non-transitory computer readable storage medium of claim 14, wherein the operations further comprise:

presenting, in the user interface, an option to automatically include a current location of the second device in a message transmitted to the first device.

18. The non-transitory computer readable storage medium of claim 14, wherein the operations further comprise:

updating a metric corresponding to the machine-readable code in response to determining that the second device of the second user has interacted with the machine-readable code presented on the first device; and

causing the metric to be presented on the first device of the first user.

19. The non-transitory computer readable storage medium of claim 14, wherein the particular user-specified action comprises multiple user-specified actions received from the first device, each of the multiple user-specified actions pertains to the first user and uses data of the first user when performed, the operations further comprising identifying the first user and the second user on a social network and forming a relationship between the first user and the second user on the social network in response to determining based on the data that the first user and the second user are not connected on the social network.

* * * * *