

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12386305
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Ding; Geming et al.

Developing cartridge and electronic imaging apparatus

Abstract

A developing cartridge includes: a cartridge containing a developer and including a first side wall and a second side wall positioned opposite to each other along a first direction; a power reception member configured to receive a driving power and positioned at the first side wall; a developing roller rotatable about a first axis extending in the first direction; and an activation member including a movable member and a detection protrusion positioned at the second side wall. The movable member rotates around a second axis in a second direction, the first direction and the second direction intersect with each other, and the detection protrusion moves as the movable member moves.

Inventors:	Ding; Geming (Zhuhai, CN), Peng; Tiansheng (Zhuhai, CN), Yang; Hao (Zhuhai, CN), Dai; Shuchun (Zhuhai, CN), Zeng; Likun (Zhuhai, CN)
Applicant:	Zhuhai Ninestar Information Technology Co. , Ltd. (Zhuhai, CN)
Family ID:	74684540
Assignee:	Zhuhai Ninestar Information Technology Co., Ltd. (Zhuhai, CN)
Appl. No.:	18/735370
Filed:	June 06, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240402644 A1	Dec. 05, 2024

Foreign Application Priority Data

CN	201921406009.7	Aug. 27, 2019
CN	201921418173.X	Aug. 28, 2019
CN	201921466131.3	Sep. 04, 2019
CN	201921477153.X	Sep. 05, 2019
CN	201921516810.7	Sep. 11, 2019

CN	201921557007.8	Sep. 18, 2019
CN	201921580821.1	Sep. 21, 2019
CN	201921720541.6	Oct. 14, 2019
CN	201921747615.5	Oct. 17, 2019
CN	201921784211.3	Oct. 22, 2019
CN	201921863944.6	Oct. 31, 2019

Related U.S. Application Data

continuation parent-doc US 18183751 20230314 US 12038714 child-doc US 18735370
continuation parent-doc US 17671541 20220214 US 11635728 20230402 child-doc US 18183751
continuation parent-doc WO PCT/CN2020/111148 20200825 PENDING child-doc US 17671541

Publication Classification

Int. Cl.: G03G21/16 (20060101); G03G21/18 (20060101)

U.S. Cl.:

CPC G03G21/1647 (20130101); G03G21/1821 (20130101); G03G21/1857 (20130101);
G03G21/186 (20130101); G03G21/1864 (20130101); G03G2221/1657 (20130101)

Field of Classification Search

CPC: G03G (21/1647); G03G (21/186); G03G (21/1864); G03G (2221/1657); G03G (21/1896)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6298202	12/2000	Fushiya	399/113	G03G 21/1896
9535396	12/2016	Shimizu	N/A	G03G 21/1647
2012/0207501	12/2011	Funamoto	399/68	G03G 15/5008
2015/0277353	12/2014	Fukamachi	399/119	G03G 21/1647
2017/0315467	12/2016	Bryant	N/A	B41J 2/442
2022/0171324	12/2021	Ding	N/A	G03G 21/186

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
201514542	12/2009	CN	N/A
205003445	12/2015	CN	N/A
108089417	12/2017	CN	N/A
108983567	12/2017	CN	N/A

201170839	12/2017	CN	N/A
111240168	12/2019	CN	N/A
107885053	12/2020	CN	G03G 15/0863
3382466	12/2017	EP	G03G 15/0863
S62134654	12/1986	JP	N/A

OTHER PUBLICATIONS

The World Intellectual Property Organization (WIPO) International Search Report for PCT/CN2020/111148 Nov. 11, 2020 4 Pages (including translation). cited by applicant
 Notice of Allowance of CN202021065051X. cited by applicant
 Notice of Allowance of CN2020202540804. cited by applicant

Primary Examiner: Gray; Francis C

Attorney, Agent or Firm: Anova Law Group, PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 18/183,751 filed on Mar. 14, 2023, which in turn is a continuation of U.S. patent application Ser. No. 17/671,541 filed on Feb. 14, 2022, which in turn is a continuation of International Application No. PCT/CN2020/111148, filed on Aug. 25, 2020, which in turn claims priority to Chinese Patent Application No. 201921406009.7, filed on Aug. 27, 2019, Chinese Patent Application No. 201921418173.X, filed on Aug. 28, 2019, Chinese Patent Application No. 201921466131.3, filed on Sep. 4, 2019, Chinese Patent Application No. 201921477153.X, filed on Sep. 5, 2019, Chinese Patent Application No. 201921516810.7, filed on Sep. 11, 2019, Chinese Patent Application No. 201921557007.8, filed on Sep. 18, 2019, Chinese Patent Application No. 201921580821.1, filed on Sep. 21, 2019, Chinese Patent Application No. 201921720541.6, filed on Oct. 14, 2019, Chinese Patent Application No. 201921747615.5, filed on Oct. 17, 2019, Chinese Patent Application No. 201921784211.3, filed on Oct. 22, 2019, and Chinese Patent Application No. 201921863944.6, filed on Oct. 31, 2019. All of the applications are hereby incorporated by reference in their entireties.

TECHNICAL FIELD

(1) The present application relates to the technical field of electronic imaging and, in particular, to a developing cartridge and an electronic imaging apparatus.

BACKGROUND

(2) A developing cartridge is a detachable part widely used in an electronic imaging apparatus. The electronic imaging apparatus is provided with a driving member, for providing power to the developing cartridge; and a detect gear is further provided on the developing cartridge. When a new developing cartridge is mounted on the electronic imaging apparatus, the electronic imaging apparatus is recognized as a specific developing cartridge via an action of the detect gear and the electronic imaging apparatus, and capacity of the developing cartridge is recognized according to predetermined information in the electronic imaging apparatus, so as to remind a user to replace the new developing cartridge when a printing life of the developing cartridge is about to expire.

(3) For example, there has been a specific developing cartridge. FIG. 1 is a developing cartridge in the prior art, a power reception member **110** is provided with one end of the developing cartridge in

a length direction, for receiving power from a driving member of the electronic imaging apparatus; and a detect gear part **150** is provided with the other end of the developing cartridge in the length direction. The developing cartridge further includes a developing roller **160**, for outputting developer stored in the developing cartridge.

(4) However, the structure of activation assemblies on the developing cartridge in the prior art is complicated.

SUMMARY

(5) In view of the above problem, the present applicant provides a developing cartridge, which is used for an electronic imaging apparatus to detect and identify the developing cartridge.

(6) For achieving the above purpose, embodiments of the present application provide the following technical solutions: a developing cartridge including: a cartridge configured to accommodate developer therein, where the cartridge includes a first side wall and a second side wall, and the first side wall and the second side wall are provided opposite to each other along a first direction; a power reception member, configured to receive driving power transmitted from the electronic imaging apparatus, where the power reception member is located on the first side wall; a rotary member, installed between the first side wall and the second side wall, where one end of the rotary member is provided with a first gear, and the other end of the rotary member is provided with a second gear; the first gear is located at the first side wall, and configured to receive driving power transmitted from the power reception member; and the second gear is located at the second side wall, and configured to receive driving power transmitted from the rotary member; and an activation member, located on the second side wall which can receive driving power transmitted from the second gear; and the activation member includes a movable member and a trigger part provided on the movable member, the trigger part can trigger a detection part of the electronic imaging apparatus to recognize the developing cartridge by controlling the movable member, and the movable member moves in a translational motion or rotatable manner about the rotation axis that is not parallel to the first direction.

(7) The movable member is a rack, and the trigger part is a protrusion provided on the rack.

(8) A guide rail is provided on the cartridge, and the rack can move along the guide rail to enable the trigger part to trigger the detection part.

(9) The guide rail has a bent section, and the rack is a bendable flexible rack.

(10) The cartridge further includes an end cover and a holding member provided on the second side wall, and the end cover at least partly the second gear; the holding member has a first guide rail and a second guide rail, and the end cover has a third guide rail corresponding to the first guide rail and a fourth guide rail corresponding to the second guide rail; and a rack cover is provided on an upper cover of the rack, one side of the rack is located in the second guide rail, and the other side of the rack is located in the fourth guide rail; and one side of the rack cover is located in the first guide rail, and the other side of the rack cover is located in the third guide rail.

(11) The rack can move along the second guide rail and the fourth guide rail under an action of the driving power; and the rack cover can move along the first guide rail and the third guide rail to make the rack cover to be installed in place.

(12) The rack can move along the second guide rail and the fourth guide rail under an action of the driving power; and the rack cover can move along the first guide rail and the third guide rail to make the rack cover to be installed in place.

(13) The holding member has a first groove constructing the first guide rail and a second groove constructing the second guide rail; and the end cover has a third groove constructing the third guide rail and a fourth groove constructing the fourth guide rail; the second groove and/or the fourth groove has a tailing edge used to restrict the rack, and the rack can move to abut the tailing edge under the action of the driving power; and the tailing edge can be a reference datum when the rack is at the initial position.

(14) The rack cover is clamped with the cartridge; and/or, the rack cover is threaded with the

cartridge.

(15) A cantilevered buckle is provided on the second guide rail and/or the fourth guide rail, the rack is provided with a card slot matching with the buckle, when the card slot abuts with the buckle, the rack is in the initial position; and the buckle can be a reference datum when the rack is at the initial position.

(16) The rack at least includes a first rack and a second rack, the first rack is juxtaposed in and the second rack, and the first rack and the second rack change between an unfolded state and a folded state in response to the driving power.

(17) The first rack and the second rack are in sliding connection, the first rack is lagging behind the second rack, the second rack moves under the driving power, and then the second rack drive the first rack to connect with second gear

(18) The second gear can successively engage with the first rack and the second rack, an engaging groove and an engaging protrusion are provided between the first rack and the second rack, and the second gear drives the second rack to enable the engaging protrusion to move along the engaging groove until the engaging groove interferes with the engaging protrusion.

(19) The movable member is a bevel gear, and the trigger part is a protrusion provided on the bevel gear.

(20) The cartridge is provided with an intermediate transmitting member, and the trigger part can push the intermediate transmitting member under the driving of the movable member to enable the intermediate transmitting member to push the detection part.

(21) The cartridge is further provided with a first elastic member, one end of the first elastic member is relatively fixed to the cartridge, and the other end of the first elastic member is relatively fixed to the intermediate transmitting member; and under an action of the elastic power of the first elastic member, the intermediate transmitting member moves toward a direction away from the detection part.

(22) The intermediate transmitting member is a swing lever or a push block.

(23) A transmission structure is provided between the second gear and the movable member, and the second gear transmits the driving force to the movable member by the transmission structure.

(24) The transmission structure includes a first transmission part and a second transmission part, the first transmission part is configured to connect with the movable member in a transmission manner, the second transmission part is configured to connect with the second gear in a transmission manner, and the first transmission part and the second transmission part are configured to be suitable for delaying transmitting driving power transmitted to the second transmission part to the first transmission part.

(25) The first transmission part includes a hysteresis gear provided with a first protrusion in an axial direction, the second transmission part includes a first idle gear provided with the engaging groove in the axial direction, the engaging groove is configured to form a sector with a center of a circle of the first idle gear, and the first protrusion reaches into the engaging groove and moves along a length direction of the engaging groove.

(26) The transmission structure further includes a third transmission part used to accelerate in movement of the movable member, a transmission ratio of the third transmission part is greater than a transmission ratio of the second transmission part; and one of the second transmission part and the third transmission part is controllably connected to the second gear.

(27) The second transmission part includes a second idle gear, the third transmission part includes a third idle gear, the second idle gear and the third idle gear are configured to rotate coaxially, and a pitch circle diameter of the second idle gear is smaller than a pitch circle diameter of the third idle gear; and the hysteresis gear is provided with a pinion portion, the pinion portion is a missing gear, the pinion portion and the hysteresis gear are provided coaxially, a pitch circle diameter of the pinion portion is smaller than a pitch circle diameter of the hysteresis gear, the pinion portion connects with the third idle gear, and the second idle gear connects with the first idle gear.

- (28) At least one of the transmission structure and the movable member includes the bevel gear.
 - (29) The power reception member directly engages with the first gear.
 - (30) The electronic imaging apparatus includes the developing cartridge.
 - (31) Compared with the prior art, the developing cartridge provided by the embodiment of the present application has the following advantages:
 - (32) The developing cartridge of the embodiments of the present application drives the detection part to move by the movable member moving or rotating around the rotation axis in the direction that is not parallel to the first direction, thereby enabling the activation member to satisfy developing cartridges with diversified structures.
 - (33) In addition to the technical problems solved, the technical features constituting the technical solutions, and the beneficial effects brought by the technical features of these technical solutions in the embodiments of application described above, other technical problems solved by the developing cartridge, other technical features contained in the technical solutions, and the beneficial effects brought by these technical features provided by the embodiments of the present application will be described in further detail in the specific implementation.
-

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) In order to explain the technical solutions of the embodiments of the present application more clearly, the accompanying drawings, which need to be used in the embodiments, are briefly introduced below. Obviously, the drawings described below are only some embodiments of the present application. Other drawings can also be obtained by ordinary technicians in the art according to these drawings without paying creative efforts.
- (2) FIG. 1 is a stereoscopic view of a developing cartridge in the prior art;
- (3) FIG. 2 is a schematic structural diagram of a transmission part;
- (4) FIG. 3 is a stereoscopic view of a developing cartridge after removing an end cover in Embodiment 2;
- (5) FIG. 4 is a schematic diagram of an end A of the developing cartridge viewed from a length direction of the developing cartridge in Embodiment 2;
- (6) FIG. 5 is an enlarged view of an end B of the developing cartridge in Embodiment 2;
- (7) FIG. 6 and FIG. 7 are schematic diagrams of main components of the end B of the developing cartridge viewed from the length direction of the developing cartridge in Embodiment 2;
- (8) FIG. 8 is a schematic diagram of a rack when resetting in Embodiment 2;
- (9) FIG. 9 and FIG. 10 are schematic structural diagrams of an end B of a developing cartridge in Embodiment 3;
- (10) FIG. 11 and FIG. 12 are schematic structural diagrams of an activation member in Embodiment 4;
- (11) FIG. 13 and FIG. 14 are schematic structural diagrams of an activation member in Embodiment 5;
- (12) FIG. 15 is a stereoscopic view of a developing cartridge in Embodiment 6;
- (13) FIG. 16 is a stereoscopic view of an activation member of the developing cartridge after removing an end cover at one end in Embodiment 6;
- (14) FIG. 17 to FIG. 19 are schematic diagrams of position changes of a rack in Embodiment 6;
- (15) FIG. 20 is a stereoscopic view of a transmission structure in Embodiment 6;
- (16) FIG. 21 is a stereoscopic view of an activation member of a developing cartridge after removing an end cover at one end in Embodiment 7;
- (17) FIG. 22 is a schematic diagram of a working state of an activation member in Embodiment 7;
- (18) FIG. 23 is an exploded view of a movable member in Embodiment 7;

(19) FIG. 24 is an exploded view of a swing lever and a conductive portion in Embodiment 7;

(20) FIG. 25 is a cross-sectional view of a developing cartridge cut along a plane perpendicular to a length direction of the developing cartridge in Embodiment 8;

(21) FIG. 26 is an exploded view of the developing cartridge in Embodiment 8;

(22) FIG. 27 is an exploded view of an activation member and a guide rail in Embodiment 8;

(23) FIG. 28 is a stereoscopic view of an activation member of a developing cartridge after removing an end cover at one end in Embodiment 9;

(24) FIG. 29 is a stereoscopic view of a rack in Embodiment 9;

(25) FIG. 30 is a stereoscopic structural diagram of one end of an activation member of a developing cartridge in Embodiment 10;

(26) FIG. 31 is a stereoscopic structural diagram of the activation member of the developing cartridge after removing an end cover at one end in Embodiment 10;

(27) FIG. 32 is an exploded view of a relationship between a movable member and a transmission gear in Embodiment 10;

(28) FIG. 33A is an exploded view of an installation of an end cover in Embodiment 11;

(29) FIG. 33B is a schematic structural diagram of an end cover in Embodiment 11;

(30) FIG. 34 is a schematic diagram of a structure of a guide rail after removing an end cover in Embodiment 11;

(31) FIG. 35 is an exploded view of installation locations of the guide rail and an activation member in Embodiment 11;

(32) FIG. 36 is a schematic structural diagram of a developing cartridge after removing the guide rail, the rack and the end cover in Embodiment 11;

(33) FIG. 37 is an exploded view of an assembly of parts of the developing cartridge after removing the guide rail, the rack and the end cover in Embodiment 11;

(34) FIG. 38 and FIG. 39 are stereoscopic views of the rack with different viewing angles in Embodiment 11;

(35) FIG. 40 to FIG. 44 are schematic diagrams of a movement process between the rack and the swing lever during a detection process of the electronic imaging apparatus in Embodiment 11;

(36) FIG. 45A and FIG. 45B are stereoscopic views of a developing cartridge in Embodiment 12;

(37) FIG. 46 to FIG. 49 are schematic structural diagrams with different positions and different viewing angles during movement of a guide rail protecting cover in Embodiment 12;

(38) FIG. 50 and FIG. 51 are exploded views with different viewing angles during a process of the end cover being installing to the developing cartridge in Embodiment 12;

(39) FIG. 52 is a schematic structural diagram of a swing lever part in Embodiment 12;

(40) FIG. 53 and FIG. 54 are exploded views with different angles of installation of a conductive portion in Embodiment 12;

(41) FIG. 55 is a stereoscopic view of a structure of a gear set at one end of an activation member in Embodiment 13;

(42) FIG. 56 is a schematic structural diagram of a gear set at one end of a power reception member in Embodiment 14;

(43) FIG. 57 is a stereoscopic view of a developing cartridge in Embodiment 15;

(44) FIG. 58 is a schematic structural diagram of a transmission part after removing a protecting cover from the developing cartridge in Embodiment 15;

(45) FIG. 59 is a stereoscopic view of an end B of the developing cartridge in Embodiment 15;

(46) FIG. 60 is a schematic structural diagram of a gear set after removing an end cover from the developing cartridge in Embodiment 15;

(47) FIG. 61 is a stereoscopic view of a hysteresis gear of the developing cartridge in Embodiment 15;

(48) FIG. 62 is a stereoscopic view of a fourth gear of the developing cartridge in Embodiment 15;

(49) FIG. 63 is a stereoscopic view of a first rack of the developing cartridge in Embodiment 15;

(50) FIG. **64** is a stereoscopic view of a second rack of the developing cartridge in Embodiment 15;
(51) FIG. **65** is a schematic structural diagram of a rack in an initial position in Embodiment 15;
(52) FIG. **66** is a schematic structural diagram of the rack in the initial position engaging with a transmission gear in Embodiment 15;
(53) FIG. **67** is a schematic structural diagram of the rack in a middle position in Embodiment 15;
(54) FIG. **68** is a schematic structural diagram of the rack in the middle position engaging with the transmission gear in Embodiment 15;
(55) FIG. **69** is a schematic structural diagram of the second rack in a last position in Embodiment 15; and
(56) FIG. **70** is a schematic structural diagram of the second rack in the last position engaging with the transmission gear in Embodiment 15.

DESCRIPTION OF EMBODIMENTS

(57) In order to better understand the technical solutions of the present application, the embodiments of the present application will be described in detail as follows in conjunction with the accompanying drawing.

(58) It should be illustrated that the embodiments described are only a part of the embodiments of the present application, rather than all of the embodiments thereof. All the other embodiments obtained by ordinary technicians in the art based on the embodiments of the present application without creative efforts shall fall within (belong to) the protection scope of the present application.

(59) The developing cartridge of the present application will be introduced in detail below through specific embodiments.

Embodiment 1

(60) FIG. **2** is a schematic diagram of a transmission structure of a developing cartridge in FIG. **1**. For convenient display, a frame (shell) portion of the developing cartridge is removed in FIG. **1**.

(61) As shown in FIG. **2**, the developing cartridge receives rotational driving power from an electronic imaging apparatus through a power reception member **110**, and transmits the power to an agitator member **130** through one gear set **120** at receiving end. The agitator member **130** is located inside cartridge of the developing cartridge, rotary agitator to prevent the developer from being clumping. The agitator member **130** then transmits the rotational driving power to another gear set **140** at counting end located in the other side of the agitator member **130**, and further to a detect gear **150**.

(62) In the present embodiment, the developing cartridge is divided into two parts which are an activating part and a printing part. A frame of the activating part may be provided to be similar with the structure of the developing cartridge in the prior art in FIG. **1**. However, compared to the developing cartridge in the prior art, the frame of the activating part does not need to be installed with a developing roller or and does not need to store developer, it only needs to at least contain a power reception member for receiving power from the electronic imaging apparatus, a detect gear used to activate an electronic imaging apparatus to check a new developing cartridge, and a transmission part for transmitting the power from the power reception member to the detect gear. Preferably, it is possible to use the existing developing cartridge without providing the developing roller and storing the developer, and only the frame and the transmission structure in FIG. **2** are retained as the activating part.

(63) The activating part is taken out after the activating part is activated in the electronic imaging apparatus, and a printing part is installed in the electronic imaging apparatus. The printing part does not have the detect gear **150** for activating compared with the developing cartridge in the prior art. The other part of the printing part may be set as that in the prior art. At this time, the electronic imaging apparatus recognizes the developing cartridge after being activated by the activating part, and replaces the printing part and performs a normal printing. This can avoid poor printing effect caused by the interference of the counting gear in the printing process.

(64) When the electronic imaging apparatus prompts to replace the developing cartridge, at this

time, developer remaining in the printing part is also at a low level, a new activating part and a new printing part are replaced, and it continues to follow the process of firstly activating the electronic imaging apparatus by using the activating part and then performing electronic imaging by using the printing part.

(65) Preferably, in order to save resources, it may further design a structure of a reusable activating part, thereby selling a combination product of the activating part and the printing part as well as a product of a separate printing part.

Embodiment 2

(66) As shown in the FIG. 3 to FIG. 7, the present embodiment provides a developing cartridge, where the developing cartridge is installed detachable in an electronic imaging apparatus, and includes a cartridge, a power reception member **210**, a rotary member and an activation member.

(67) The cartridge includes a first side wall A and a second side wall B, and the first side wall A and the second side wall B are oppositely provided along a first direction. Where the first direction is a length direction of the developing cartridge, developer accommodated in the cartridge; the power reception member **210** is positioned on the first side wall A, and used to receive driving power transmitted from the electronic imaging apparatus; the rotary member is installed between the first side wall A and the second side wall B, one end of the rotary member is provided with a first gear **221**, and the other end of the rotary member is provided with a second gear **241**, the first gear **221** is positioned on the first side wall A, for receiving the driving power transmitted from the power reception member **210**, the second gear **241** is positioned on the second side wall B, for receiving the driving power transmitted from the rotary member; and the activation member is positioned on the second side wall B, which moves under the driving power transmitted from the second gear **241**, and is detected by a detection part of the electronic imaging apparatus to recognize the developing cartridge.

(68) The activation member includes a movable member **251** and a trigger part provided on the movable member **251**, and the trigger part is driven by the movable member **251** to trigger the detection part **999** of the electronic imaging apparatus, so that the electronic imaging apparatus recognizes the developing cartridge. The movable member is a rack, the trigger part is a protrusion provided on the rack, and the structure of the rack is simple and easily to be processed. On the one hand, the structure of the activation member has been simplified, on the other hand, it is convenient to adjust the rack and the trigger part provided on the rack, so that the activation member can be adapted to different electronic imaging apparatuses.

(69) The developing cartridge of the present embodiment is installed in the electronic imaging apparatus, the power reception member **210** receives the driving power transmitted from the electronic imaging apparatus, and sequentially transmits the driving power to the activation member through the first gear **221**, the rotary member and the second gear **241**, thereby driving the movable member **251** of the activation member to move, so that the trigger part provided on the movable member **251** triggers the detection part **999** of the electronic imaging apparatus and then the developing cartridge is recognized by the electronic imaging apparatus.

(70) The trigger part may be a protrusion **252** provided on the rack, and the protrusion **252** may be integrally formed with the rack, or may also be assembled together after being separately processed; number and height of the protrusion may be set according to predetermined content in the electronic imaging apparatus to satisfy the detection requirements of the detection part of the electronic imaging apparatus; and when the number of the protrusion is at least two, the protrusions may be spaced from one another along the length direction of the rack, and the distance between adjacent two protrusions may also be set according to the predetermined content in the electronic imaging apparatus.

(71) In other embodiments, the trigger part may further be other structure provided on the rack, as long as the detection part of the electronic imaging apparatus can be triggered under the driving of the rack, so that the developing cartridge is recognized by the electronic imaging apparatus.

(72) The rotary member may be an agitator member, and the agitator member is used to stir the developer in the cartridge; and in the other embodiments, the rotary member may further be a developing roller, the developing roller is used to output the developer in the cartridge, or, the rotary member may further be a powder feeding roller, and the powder feeding roller is used to output the developer for the developing roller.

(73) As shown in FIG. 4, the power reception member **210** of the present embodiment directly engages with the first gear **221** located on the first side wall A, and the first gear **221** receives the driving power from the power reception member **210** and rotates about a third axis **2211** extending in the first direction. The power reception member may directly engage with the first gear, thereby not only saving the material cost, but also reducing the assembly difficulty and saving the assembly time.

(74) It needs to illustrate that the electronic imaging apparatus of the present embodiment may be a structure that not only can provide electrical energy for the developing cartridge, but also perform detection on the developing cartridge. A conductive part, which can be in contact with the detection part, is provided on the cartridge, and the trigger part may trigger the detection part under the driving of the movable member **251** to separate the detection part from the conductive part.

(75) As shown in FIG. 6 and FIG. 7, the movable member **251** of the present embodiment may locate between the conductive part **253** and the detection part **999**, the trigger part is provided on a side of the movable member **251** facing the detection part **999**, and may push the detection part **999** under the driving of the movable member **251** to separate the detection part **999** from the conductive part **253**.

(76) Specifically, one side of the movable member **251** having a tooth part may directly engage with the second gear **241**, the other side is provided with a protrusion **252** which can push the detection part **999**, and the conductive part **253** receive the electrical energy transmitted from the electronic imaging apparatus through contacting with the detection part **999**. Before the electronic imaging apparatus detects the developing cartridge, the positions of the movable member **251** and other components are shown in FIG. 6, at this time, at least a part of the detection part **999** is in contact with the conductive part **253** to transmit the electrical energy. When the electronic imaging apparatus starts to detect the developing cartridge, the movable member **251** is driven by the second gear **241** to move toward an upper right direction in FIG. 6, so that the protrusion **252** can push the detecting portion **999** to be separated from the conductive portion **253**. As the continued movement of the movable member **251**, as shown in FIG. 7, the protrusion **252** leaves the position where the detecting portion **999** separates from the conductive portion **253**, so as to restore contact between the detecting portion **999** and the conductive portion **253**, during this process, the movement of the detection part **999** can generate a pulse for recognition by the electronic imaging apparatus.

(77) In the present embodiment, in order to enable the rack **251** to be more stable, have a better directionality, and not easy to fall out during the moving process. On the one hand, a groove **254** for accommodating the movable member **251** may be provided at a free end of the conductive part **253**, so that a part of the movable member **251** is located in the groove **254**; and on the other hand, a guide rail may be provided on the cartridge, and the movable member may move along the guide rail, so that the trigger part triggers the detection part.

(78) The position of the rack and the protrusions on the rack may further have other settings according to actual needs, which will be described here again.

(79) In the use of the developing cartridge of the present embodiment, there may be some situations in which the movable member **251** needs to be reset, for example, after the developer in the developing cartridge is exhausted and before refilling and putting into use, the rack needs to be reset, for example, in the process of production, the movable member **251** of the developing cartridge after being tested needs to be reset. For facilitate resetting the movable member **251** to enable the movable member **251** to restore the initial position before the detection part of the

electronic imaging apparatus is triggered, an elastic member **242** may be provided on the cartridge. As shown in FIG. **5**, one end of the elastic member **242** is relatively fixed to cartridge, the other end of the elastic member **242** is relatively fixed to the second gear **241**, and the elastic member **242** may enable the second gear **241** to move along the axial direction.

(80) As shown in FIG. **8**, when resetting the activation member, the second gear **241** is firstly pressed in the direction of the cartridge to enable the second gear **241** to move toward the direction closing to the cartridge, so as to disengage with the movable member **251**; and then the movable member **251** is pulled toward the opposite direction that the detection part **999** may be triggered, so that the movable member **251** is restored to the initial position and the second gear **241** is released. Under the pushing of the elastic member **242**, the second gear **241** may restore to the position of engaging with the movable member **251**, so as to complete the reset of the movable member **251**. The resetting solution is simple and does not require tearing down the activation member.

Embodiment 3

(81) The present embodiment provides a developing cartridge, and unspecified parts are the same as the structure of the developing cartridge in Embodiment 2.

(82) As shown in FIG. **9** and FIG. **10**, the developing cartridge includes a second gear **341** and a movable member **351** engaged with the second gear **341**. A bevel gear part **354** is provided at one end of the movable member **351** closing to the second gear **341**, so as to receive the power from the second gear **341**, that is, the movable member **351** is the bevel gear. A conducting pillar **353** restrains the movable member **351** to enable the movable member **351** to rotate around a rotation shaft (also known as a rotation axis or an axis B-B) that is not parallel to the length direction (first direction A-A) of the developing cartridge, especially rotate around a rotation shaft that is perpendicular to the first direction. A trigger part **352** is further provided at the side of the movable member **351** closing to the detection part **999**. The second gear **341** is installed at a shaft end of the agitator member and rotates together with the agitator member.

(83) After receiving the power transmitted through the agitator member, through engaging with the bevel gear part **354**, the second gear **341** enables the movable member **351** to rotate. The movable member **351** may be a flexible member. The movable member **351** may be made of conductive material or insulating material. As shown in FIG. **10**, with the rotation of the movable member **351**, the trigger part **352** contacts and interferes with the detection part **999**, to enable the detection part **999** to move and recognize the trigger part, and then the movable member **351** continues to rotate to enable the detection part **999** to avoid the trigger part **352**.

(84) Preferably, a missing tooth structure is provided on the bevel gear part **354** of the movable member **351**, when rotating to a missing tooth position, the agitator bevel gear **341** may no longer drive the movable member **351**. Such a design may prevent the movable member **351** from rotating all the time after the developing cartridge is recognized by the electronic imaging apparatus.

Embodiment 4

(85) The present embodiment discloses an activation member portion located on an end B of the developing cartridge. FIG. **11** and FIG. **12** are schematic structural diagrams of an activation member in the present embodiment, and reveal a working principle of the structure in the present embodiment. All illustrated parts in the present embodiment are the same as the contents in the above embodiments, which will not be repeated for the sake of simplicity.

(86) As shown in FIG. **11** and FIG. **12**, a movable member **451** is provided with a trigger part **452** with a cam, and the trigger part **452** may push an intermediate transmitting member **454** of a push rod structure to push the detection part **999** of the electronic imaging apparatus to move. A first elastic member **455** is further provided on the intermediate transmitting member **454**, one end of the first elastic member **455** is connected with a fixed end **456** fixed on the developing cartridge, and the other end is connected to the intermediate transmitting member **454**.

(87) When the trigger part **452** rotates counterclockwise as shown in the drawing, the trigger part **452** pushes the intermediate transmitting member **454** to move in a direction closing to the

detection part **999**, and the intermediate transmitting member **454** pushes the detection part **999** to enable the detection part **999** to move, that is, changing from a first state in the FIG. **11** to a second state in the FIG. **12**. After that, the trigger part **452** continues rotating without pushing the intermediate transmitting member **454**, and the elastic member **455** pushes the intermediate transmitting member **454** away from the detection part **999**, since the elastic structure or the action of gravity inside the electronic imaging apparatus, the detection part **999** is moved back to the first state. The whole processes generate a pulse that the electronic imaging apparatus can recognize the developing cartridge.

(88) Preferably, the movable member **451** of the present embodiment may imitate the detect gear **150** in FIG. **2** to provide with a structure that a rotation axis is parallel to the length direction of the developing cartridge, or may imitate the bevel gear part **354** in FIG. **9** to provide with a structure that a rotation axis is not parallel to the length direction of the developing cartridge.

Embodiment 5

(89) The present embodiment provides another structure of an activation member.

(90) FIG. **13** and FIG. **14** are schematic structural diagrams of an activation member in the present embodiment. The activation member includes a mounting gear **651**, a protrusion **652**, a hollow push rod **654**, and a fixed supporting point **655**. The mounting gear **651** receives power from the developing cartridge and rotates, the protrusion **652** is fixed on a non-rotation axis position of the mounting gear **651**, and the rotation of the mounting gear **651** changes the position of the protrusion **652**. The protrusion **652** is fixedly connected with the hollow push rod **654** in a rotatable way, that is, a relative rotation, rather than a relative translation, may occur between the protrusion **652** and the hollow push rod **654**. Preferably, one end of the hollow push rod **654** in the length direction is fixedly connected with the protrusion **652** in a rotatable way. The hollow push rod **654** has an “O”-shaped ring structure, and the fixed supporting point **655** is further provided inside the hollow push rod **654**. The fixed supporting point **655** is fixed on the developing cartridge, and when the protrusion **652** drives the hollow push rod **654** to rotate, a relative movement occurs between the hollow push rod **654** and the fixed supporting point **655**. FIG. **13** shows a first state when the detection part **999** is not lifted off from the conducting pillar by the hollow push rod **654**; and FIG. **14** shows a second state when the detection part **999** is lifted off from the conducting pillar by the hollow push rod **654**. When the mounting gear **651** rotates, the detection part **999** can move. By setting the features, such as different rotating speed and height of mounting gear **651**, and a length of the hollow push rod **654**, a predetermined pulse may be generated to enable the electronic imaging apparatus to recognize the developing cartridge.

(91) In the present embodiment, the mounting gear **651** is the movable member, the protrusion **652** is the trigger part, and the hollow push rod **654** is the intermediate transmitting member.

Embodiment 6

(92) The present embodiment is an improvement and deformation of the Embodiment 1.

(93) A developing cartridge of the present embodiment adds an intermediate transmitting member on the basis of Embodiment 2, the trigger part may push the intermediate transmitting member under the driving of the movable member to enable the intermediate transmitting member to push the detection part to move.

(94) As shown in FIG. **15**, a power reception member **710** is provided on the first side wall of the developing cartridge in the first direction, and an activation member **750** is provided on the second side wall of the developing cartridge in the first direction. The transmission relationship between the power reception member **710** and the activation member **750** is the same as that in Embodiment 2, which can be transmitted through the rotation member and the gear set.

(95) As shown in FIG. **16**, the intermediate transmitting member in the present embodiment is a push block **752**, when the push block **752** moves along a straight line under the action of the push of the trigger part, the push block **752** may push the detection part to separate from the conductive part **753**. The cartridge is also provided with a first elastic member **754**, where one end of the first

elastic member **754** is relatively fixed with the cartridge, and another end of the first elastic member **754** is relatively fixed with the push block **752**, so that the push block **752** moves toward a direction away from the detection part under the elastic action of the first elastic member **754**.

(96) FIG. **17** to FIG. **19** are schematic diagrams of position changing relationships of a movable member in Embodiment 6. When the movable member is at an initial position, as shown in FIG. **17**, one side of the movable member **751** closing to the push block **752** is provided with one or more protrusions, the protrusion is provided with a pushing inclined surface **7511**, the push block **752** is provided with a pushed inclined surface **7521**, the pushing inclined surface **7511** may push the push block **752** to move through the pushed inclined surface **7521**. More preferably, after being pushed, the push block **752** in the present embodiment moves toward the direction away from the cartridge, so that a forced separation slope **7522** provided on the push block **752** pushes the detection part to separate from the conductive part.

(97) As shown in FIG. **18**, when the movable member **751** moves and pushes the push block **752**, the forced separation slope **7522** provided on the push block **752** can push the detection part to separate from the conductive part. After that, the movable member **751** continues to move and no longer interferes with the push block **752**, at this time, the first elastic member **754** pushes the push block **752** to restore the position closing to the cartridge, as shown in FIG. **19**. At this time, the detection part returns back to the position contacting the conductive part, and in the process, the pulse which can be recognized by the electronic imaging apparatus is generated.

(98) FIG. **20** is a stereoscopic view of the transmission structure. In order to set a suitable transmission ratio, an idler **742** may further be provided between a second gear **741** and the movable member **751**, so that the second gear **741** transmits the driving power to the movable member **751** by the idler **742**. The number of the idler may be set according to actual requirements; on the one hand, the idler can enable less vibration during transmission is transmitted to the detection part of the electronic imaging apparatus, so as not to generate negative effects for the normal detection of the detection part, on the other hand, it enables the force of the whole gear set more reasonable.

Embodiment 7

(99) The present embodiment is a further refinement and optimization of the solution in Embodiment 3. Unexplained structures are the same as those in Embodiment 3.

(100) FIG. **21** is a stereoscopic view of an activation member of a developing cartridge. A second gear **841** is a bevel gear rotatable about an axis C-C extending in the first direction, which transmits the rotational driving power to a movable member **851**, a protrusion of one end of the movable member **851** toggles a swing lever **852** again, and the swing lever constitutes an intermediate transmitting member that rotates about an axis D-D.

(101) As shown in FIG. **22** and FIG. **23**, the movable member **851** includes a bevel gear part **8511**, a shaft **8512**, a holding member **8513**, a bearing **8514**, a fixed part **8515** and a protrusion **8516**. The bevel gear part **8511** is engaged with the second gear **841** to receive power and transmits it to the shaft **8512**. The holding member **8513** is fixed on the developing cartridge, and includes the bearing **8514** for supporting the shaft **8512**. Preferably, the holding member **8513** is fixed on the developing cartridge by screwing. The fixed part **8515** is fixed on the shaft **8512**, so as to prevent the shaft **8512** from falling off from the bearing **8514**. The fixed part **8515** is further provided with the protrusion **8516**, so as to contact with the swing lever **852**. When the shaft **8512** rotates, the fixed part **8515** drives the protrusion **8516** to move together.

(102) As shown in FIG. **24**, a conductive part **853** includes a contacting surface **8531**, for contacting with the detection part. There is also provided a protruding shaft **8532** beside it. The swing lever **852** includes a first end **8523** which is used to separate the power part from the contacting surface **8531**, a ring **8521** fixed on the protruding shaft **8532**, and a second end **8522** pushed by the protrusion **8516**. Preferably, the ring **8521** is fixed rotatably to the conductive part **853** through a screw **8534**. Preferably, the first elastic member is further provided to enable the

swing lever **852**, when not interfered by the protrusion **8516**, to return to a position which does not affect the electronic energy transmitting by the power supply part and the contacting surface **8531**. The first elastic member may set as a torsion spring whose ring structure passes through the protruding shaft **8532**, one end is fixed to the conductive part and another end is fixed to the swing lever **852**.

(103) In the present embodiment, a transmission structure, for example, a transmission structure composed of at least one gear, may be provided between the second gear and the movable member, and at least one of the second gear, the transmission structure and the movable member is provided with the bevel gear structure, that is, at least one of the second gear, the transmission structure and the movable member is provided with the bevel gear part.

Embodiment 8

(104) The thought of the present embodiment is same as that of Embodiment 2, however, the present embodiment shows another type of developing cartridge, which is matched with another type of electronic imaging apparatus. Considering a unified design concept and similar reliability tests of different types, similar solutions are also adopted. A guide rail of the present embodiment has a bending section, and a movable member **951** is a bendable flexible rack.

(105) It should be noted that, the detection part of the electronic imaging apparatus, corresponding to the developing cartridge of the present embodiment, may be only used to detect the developing cartridge, and the electronic imaging apparatus may have a structure dedicated to supply power to the developing cartridge. The electronic imaging apparatus, corresponding to developing cartridge of the present embodiment, detects the developing cartridge through the detection part being pushed by the developing cartridge to locate at different positions.

(106) As shown in FIG. **26**, an electrode **953** is used to receive power from the electronic imaging apparatus, a movable member **951** is used to enable the electronic imaging apparatus to recognize the developing cartridge.

(107) As shown in FIG. **25**, the developing cartridge is provided with a plurality of rotation members along the first direction thereof, such as an agitator member **931**, a developing supply roller **932** and a developing roller **933**. All these rotation members obtain the rotational driving power from the gear set connected with the power reception member and rotate. Therefore, in the present embodiment and the above embodiments, any one of these rotation members may be selected to complete the power transmission process from one end to the other end of the developing cartridge. More preferably, the agitator member may be used as an example in above embodiments, the developing supply roller **932** is selected to as an example in the present embodiment.

(108) As shown in FIG. **26**, the gear set **940** receives the rotational driving power from the developing supply roller **932** and transmits it to drive the movable member **951**. The electrode **953** is located on the side wall of the developing cartridge. The movable member **951** is installed in a guide rail **954** to prevent it from falling out, more preferably, the guide rail **954** is fixed to the developing cartridge. In order to prevent the movable member **951** from protruding too much after the developing cartridge is installed in the electronic imaging apparatus, which interferes with other structures in the electronic imaging apparatus, for example, interferes with a door cover of the electronic imaging apparatus where the developing cartridge is installed, thereby affecting normal use of the electronic imaging apparatus or causing damage of the electronic imaging apparatus, the movable member **951** in the present embodiment is set as a bendable flexible rack, for example, a rack made of nylon material, and a bending section is provided on the guide rail **954** at the same time, so that when moving along the guide rail **954** with the bending section, the flexible rack can avoid other structures in the electronic imaging apparatus, thereby preventing the movable member **951** from adversely affecting the electronic imaging apparatus. The rack also has a certain degree of hardness to receive the driving power.

(109) As shown in FIG. **27**, the movable member **951** is provided with a predetermined number of

protrusions **952** along a predetermined separation distance, by setting different numbers and separation distances of the protrusions **952**, that is, the detection part of the electronic imaging apparatus can be pushed at different time intervals and different times to generate different signals, and the electronic imaging apparatus can learn the specific information of the developing cartridge through processing these signals. More preferably, the guide rail **954** is provided on the side wall of the cartridge, and not is parallel to the first direction of the cartridge.

(110) Other technical features are the same as that of Embodiment 2, and can achieve the same or similar technical effects, which will not be repeated here. For details, please refer to the description of Embodiment 2.

Embodiment 9

(111) The difference between the present embodiment and Embodiment 2 is that an intermediate transmitting member in the present embodiment is a swing lever.

(112) As shown in the FIG. **28** and FIG. **29**, a connecting shaft **A532** is provided on a conductive part **A53**, and the swing lever **A55** is sleeved on the connecting shaft **A532** and rotates around the connecting shaft **A532**; and the swing lever **A55** has a first end **A552** and a second end **A553**, where the first end **A552** is used to drive the swing lever **A55** to rotate under the push of the trigger part, so that the second end **A553** pushes the detection part away from the conductive part **A53**.

(113) The cartridge is also provided with a first elastic member (not shown in the figure), where one end of the first elastic member is relatively fixed with the swing lever **A55**, and the other end is relatively fixed with the cartridge. The first elastic member is used to drive the swing lever **A55** to reset after the first end **A552** is away from the trigger part, that is, the first elastic member has a tendency of driving the swing lever **A55** to return a position where it does not block the conduction.

(114) In implementation, after receiving power from the second gear, a rack **A51** drives a protrusion **A52** to move along a guide rail **A54**, more preferably, the guiding of the guide rail **A54** is not parallel to the first direction. The conductive part **A53** includes a conductive contact surface **A531** and the connecting shaft **A532**, and the swing lever **A55** is rotatably sleeved on the connecting shaft **A532**. The first end **A552** of the swing lever may drive the swing lever **A55** to rotate under the push of the protrusion **A52**, so that the second end **A553** pushes the detection part away from the conductive contact surface **A531**. The arrangement of the first elastic member keeps the swing lever **A55** in the position where it does not block the conduction when it is not under force, or enables the swing lever **A55** to restore the position where it does not block the conduction, after the external force on the swing lever **A55** disappears. More preferably, the first elastic member may be a torsion spring, whose one end is connected with the swing lever **A55** and another end is connected with the cartridge, and which is coaxial with the rotation axis of the swing lever **A55**.

(115) As shown in FIG. **29**, the rack **A51** includes a tooth part **A511**, the tooth part **A511** is used to engaged with the gear set to push the rack **A51** to move, the protrusion **A52** is used to abut with the first end **A552** of the swing lever **A55** to push the swing lever **A55**, and the second end **A553** of the swing lever **A55** abuts with the detection part of the electronic imaging apparatus to push the detection part away from the conductive contact face **A531**, so that the developing cartridge is recognized by the electronic imaging apparatus. More preferably, the protrusion **A52** has two parts which are a pushing inclined surface **A521** and a plane **A522**, and the first end **A552** of the swing lever has a pushed inclined surface abutting with the pushing inclined surface **A521**, so as to enable the contact between the protrusion **A52** and the swing lever **A55** more smooth. The plane **A522** is used to keep the swing lever **A55** in the position where the detection part is pushed away from the conductive contact surface **A531** in the process that the protrusion **A52** pushes the swing lever **A55**. Specifically, all the length of the plane **A522** and the number of the protrusion **A52** may be set according to the predetermined content in the electronic imaging apparatus.

(116) Top of the connecting shaft **A532** is provided with an undercut, there is no need to perform

complicated screwing work during assembly. It only needs to directly install the swing lever A55 into the connecting shaft A532, and the undercut on the connecting shaft A532 can ensure that the swing lever A55 will not fall off.

(117) It should be illustrated that the intermediate transmitting member may further provide other implementations according to actual deeds, in addition to the two implementations of the push block in Embodiment 6 and the swing lever in the present embodiment, which will not be repeated here. Other technical features are same as that of Embodiment 2, and can achieve the same or similar technical effects, which will not be repeated here. For details, please refer to the description of Embodiment 2.

Embodiment 10

(118) FIG. 30 is a stereoscopic structure of one end of an activation member of a developing cartridge in Embodiment 10. The developing cartridge of the present embodiment includes a rack B51, a protrusion B52 provided on the rack B51, a conductive part B53 and a guide rail B54 for mounting the rack B51. The guide rail B54 is provided on an end cover of the cartridge, and the end cover is fixed on the cartridge by screws or other ways to protect the internal parts. One end of the elastic member B55 connects with the rack B51, and the other end connects with the guide rail B54. The first elastic member B55 has the function of keeping the rack B51 in a first position, so as to enable the rack B51 to return back to the first position which is the position before the rack starts to detect after completing the action detected by detection part of the electronic imaging apparatus.

(119) FIG. 31 is a stereoscopic structural diagram of the activation member of the developing cartridge after removing an end cover at one end in Embodiment 10. The activation member of the present embodiment further includes a gear set, the gear set at least includes a hysteresis gear B41, the hysteresis gear B41 is used to receive the driving power transmitted by a second intermediate gear B42, the rack B51 engages with the hysteresis gear B41 to enable the rack B51 to move driven by the hysteresis gear B41, and the hysteresis gear B41 is provided with at least one first missing tooth part. The first elastic member B55 is used to drive the rack to move toward the direction away from the detection part, when the rack B51 moves to the first missing tooth part.

(120) gear set further includes a first idle gear B40 engaged with the second intermediate gear B42, where the first idle gear B40 and the hysteresis gear B41 are coaxially provided, and the first idle gear B40 may drive the hysteresis gear B41 to rotate; and a second missing tooth part is provided on the first idle gear B40, which is used to enable the first idle gear B40 to disengage with the second intermediate gear B42.

(121) The second intermediate gear B42 transmits the power to the first idle gear B40, and the first idle gear B40 transmits the power to the hysteresis gear B41 coaxial with the first idle gear B40 through the connecting structure. The hysteresis gear B41 may engage with rack B51 through the tooth on its surface to transmit the power, and drive the rack B51 to move from a first position on the one side of detection part of electronic imaging apparatus to the direction closing to the detection part. At this time, both the first idle gear B40 and the hysteresis gear B41 move along a direction as shown in FIG. 31 and FIG. 32. The state shown in the FIG. 31 is also the state before the developing cartridge is installed in the electronic imaging apparatus for detection, that is, the state of the rack B51 is in the first position.

(122) As shown in FIG. 32, a transmitting column B401 is provided at one side of the first idle gear B40 which is opposite to the hysteresis gear B41, and a transmitting groove B415 is provided at one side of the hysteresis gear B41 which is opposite to the first idle gear B40. The transmitting column B401 may move along the transmitting groove B415, and when moving to the predetermined position in the transmitting groove B415, the transmitting column B401 drives the hysteresis gear B41 to move, for example, the transmitting groove has a first side and a second side, when the transmitting column moves and abuts the second side of the transmitting groove, the transmitting column may drive a third gear to move.

(123) Before the developing cartridge is detected, the transmitting column B401 is installed in the

first side **B416** of the transmitting groove **B415**, when the electronic imaging apparatus starts to transmit to the developing cartridge and drive the first idle gear **B40** to rotate, the transmitting column **B401** rotates from the first side **B416** to the second side **B417** and drives the hysteresis gear **B41** to rotate. A detection of such an arrangement may be performed after the electronic imaging apparatus has been running for a short period of time, thereby preventing the data of the first collision process from not being collected by the electronic imaging apparatus when the insufficient respond of the electronic imaging apparatus is not fast enough.

(124) The present embodiment takes the protrusion of the rack colliding the detection part three times as an example for detailed description, the hysteresis gear **B41** includes a first tooth **B411**, a second tooth **B412**, a third tooth **B413** and a fourth tooth **B414**. When the electronic imaging apparatus and developing cartridge are detected and recognized, the hysteresis gear **B41** rotates in the a direction and drives the rack **B51** to move. When the protrusion **B52** has not reached the second position of colliding the detection part, the hysteresis gear **B41** rotates to enable the first missing tooth part between the first tooth **B411** and the second tooth **B412** towards the rack **B51**, so as to enable an fourth elastic member **B55** to pull the rack **B51** back to the first position. The hysteresis gear **B41** continues to rotate in the a direction, the second tooth **B412** engages with the rack **B51** and drives the rack **B51** to move from the first position to the second position until it moves to the second position, so that the protrusion **B52** completes the first collision with the detection part. And then the hysteresis gear **B41** rotates to enables the first missing tooth part between the second tooth **B412** and the third tooth **B413** towards the rack **B51**, so as to enable the fourth elastic member **B55** to pull the rack **B51** back to the first position. similarly, the third tooth **B413** drives the rack **B51** and the protrusion **B52** to complete the second collision with the detection part, the fourth elastic member **B55** pulls the rack **B51** back to the first position; and the fourth tooth **B414** continues to drive the rack **B51** and the protrusion **B52** to complete the third collision with the detection part. Due to the fourth tooth has no missing tooth after rotating in a direction, the rack **B51** and the protrusion **B52** continue to move along the guide rail **B54** after completing the third collision with the detection part, until moving to the other side of the detection apparatus. At this time, the other side of the detection apparatus where the protrusion **B52** is located is a third position. In this process, the protrusion located on the rack pushes the detection part of the electronic imaging apparatus three times to enable the detection part is in different positions, therefore, it is convenient for the electronic imaging apparatus to recognize the developing cartridge.

(125) In other embodiments, it may further set the number of the first missing tooth part according to the actual number of collisions required for detection, for example, when one collision is required, there is no need to provide the first missing tooth part, and the rack **B51** may directly move from the first position to the third position. When it requires two collisions, two first missing tooth parts are provided; and when it requires four collisions, four first missing tooth parts are provided. Besides, it may further provide that the first tooth **B412** directly drives the rack **B51** and the protrusion **B52** to the second position.

(126) More preferably, for the sake of the hysteresis gear **B41** and the first idle gear **B40** no longer continue to rotate after completing the detection, refer to FIG. 31, the second missing tooth part **B402** may be provided on the first idle gear **B40**, so that after completing the detection, the first idle gear **B40** disengages with the second intermediate gear **B42**, so that the first idle gear **B40** and the hysteresis gear **B41** no longer rotate.

(127) According the actual production needs, the present embodiment further refines the transmission structure in the gear and rack solution. All the parts that are not described in the present embodiment can be set with reference to the foregoing embodiments.

Embodiment 11

(128) The developing cartridge of the present embodiment is further refined on the basis of Embodiment 9. All the parts that are not described in the present embodiment can be set with

reference to the foregoing embodiments.

(129) As shown in FIG. 33A, FIG. 33B and FIG. 34 to FIG. 36, the cartridge of the developing cartridge of the present embodiment further includes an end cover C70 and a holding member C60 provided on the second side wall, and the end cover C70 at least covers part of the second gear; the holding member C60 has a first guide rail C601 and a second guide rail C602, and the end cover C70 has a third guide rail C74 corresponding to the first guide rail C601 and a fourth guide rail C75 corresponding to the second guide rail C602; a rack cover C51 is provided above the rack C52, one side of the rack C52 is located in the second guide rail C602, and the other side is located in the fourth guide rail C75; and one side of the rack cover C51 is located in the first guide rail C601, and the other side is located in the third guide rail C74.

(130) The holding member C60 has a first groove constructing the first guide rail C601 and a second groove constructing the second guide rail C602, and the end cover C70 has a third groove constructing the third guide rail C74 and a fourth groove constructing the fourth guide rail C75. The second groove or the fourth groove has a tailing edge that limits the rack C52, or both the second groove and the fourth groove have a tailing edge that limits the rack C52, and the rack C52 may be moved to abut with the tailing edge under the action of the driving power. The tailing edge can be used as a reference datum when the rack C52 is in the initial position.

(131) The rack C52 moves along the second guide rail C602 and the fourth guide rail C75 under the action of the driving power. The rack cover C51 may move along the first guide rail C601 and the third guide rail C74, so that the rack cover C51 is installed in place.

(132) The rack cover C51 is detachable installed at the cartridge, to enable the rack C52, after the rack cover C51 is removed from the cartridge, to be removed from the second guide rail C602 and the fourth guide rail C75 and reinstalled to the initial position.

(133) Specifically, the power reception member and the second gear of the present embodiment are still respectively provided on the first side wall and the second side wall of the cartridge, in the present embodiment, more preferably, the rotation member transmitted power from one end of the power reception member to one end of the second gear is the agitator member.

(134) As shown in FIG. 33A and FIG. 33B, the end cover C70 is used to protect various parts provided on the second side wall of the cartridge, such as the gear set C40, the activation member C50 and the holding member C60. The end cover C70 is relatively fixed with the second side wall of the cartridge after the developing cartridge is installed.

(135) The end cover C70 is provided with an undercut C71, a first screw hole C72, a second screw hole C73, a third guide rail C74 and a fourth guide rail C75. The undercut C71 is hooked through a predetermined corresponding position on the cartridge, and the first screw hole C72 and the second screw hole C73 are connected with the predetermined screw hole on the cartridge by screwing, so as to enable the end cover C70 to fixedly connect to the cartridge. The third guide rail C74 is used to support the rack cover C51, and the fourth guide rail C75 is used to support the rack C52.

(136) As shown in FIG. 34 and FIG. 35, the rack cover C51 is fixed on the second side wall of cartridge by the third screw hole C512, and the rack cover C51 is provided with a rail inside to accommodate the rack C52 which moves along a corresponding rail. A swing lever C53 may be toggled by the protrusion on the rack C52. An elastic member C54 maintains the swing lever C53 at the first position of the swing lever C53. There is a side surface C511 on the rack cover C51, and after the rack cover C70 is assembled, the side surface C511 may contact with the end cover C70, so as to further restrict the movement of the rack cover C51. After the rack cover C51 is restricted by the end cover C70, even if the screw in the third screw hole C512 is removed, the rack cover C51 may only be installed or taken out along a specific location perpendicular to the first direction. In this way, when the rack C52 requires to be reset after completing a printing detection, only the rack cover C51 needs to be taken out along the specific position to change the position of the rack C52 to complete the reset. Further, it may also install the screw in the third screw hole C512 in place after the printing detection is completed and the rack C52 is reset, in the previous production

process, only an abutment between the end cover C70 and the side surface C511 can be used to limit and restrict the rack cover C51.

(137) As shown in FIG. 36 and FIG. 37, the gear set C40 includes a fourth gear C41, a second gear C42 and a third gear C43. The second gear C42 is connected and rotates coaxially with the agitator member C31. The fourth gear C41 is a two-stage gear, one layer of which engages with the second gear C42, and the other layer of which engages with the third gear C43. The third gear C43 is used to engage with the rack C52, so that the third gear C43 transmits the power received from the fourth gear C41 to the rack C52, and drive the rack C52 to move. The second gear C42 is closer to the main of the developing cartridge than the holding member C60. The third gear C43 is farther away from the main of the developing cartridge than the holding member C60. The third gear C43 is rotatable supported by the holding member C60, that is, the shaft of the third gear C43 may reach into a shaft sleeve hole C64 of the holding member C60 to obtain a rotatable support. The holding member C60 has a first guide rail C601 used to support the rack cover C51 and a second guide rail C602 used to support the rack C52.

(138) The holding member C60 has an undercut C66 fixedly connected with the cartridge and a fourth screw hole C65. More preferably, during the assembly process of the developing cartridge, the fourth screw hole C65 coincides with the second screw hole C73 on the end cover C70 (as shown in FIG. 28), and a screw that passes through the fourth screw hole C65 and the second screw C73 may be used to fix the holding member and the end cover on the cartridge to save space and material. The holding member C60 is provided with a developing supply roller conductive part C67 and a developing roller conductive part C68 which respectively transmit electrical energy to the developing supply roller C32 and the developing roller C33. In the present embodiment, the conductive part is provided on the holding member C60, the conductive part includes a conductive contact surface C61 connected with the electronic imaging apparatus to receive the electrical energy, and a connecting shaft C62 provided closing to the conductive contact surface C61. More preferably, a centerline of the connecting shaft C62 is parallel to the conductive contact surface C61, and a free end of the connecting shaft C62 is provided with a detachment prevention structure. The swing lever C53 is sleeved on the connecting shaft C62. The holding member C60 is further provided with a support surface C63 supporting the first elastic member C54.

(139) As shown in FIG. 38 and FIG. 39, a convex tooth part C525 is provided on the rack C52, and used to engage with the third gear C43 and receive the power, and the rack C52 is further provided with a protrusion connected with the swing lever C53. In the present embodiment, the number of the protrusion is two, that is, a first protrusion C521 and a second protrusion C522. Further, in order to enable the process of the protrusion contacting with the swing lever C53 smoother, the first protrusion C521 is provided with a pushing inclined surface C523, and the second protrusion C523 is provided with a pushing inclined surface C524.

(140) As shown in FIG. 40 to FIG. 44, the swing lever C53 has a first end C532, a second end C533 and a ring C531. In the present embodiment, another setting method of the first elastic member is provided, that is, one end of the first elastic member C54 connects with the first end C532 of the swing lever, and the other end of the first elastic member C54 connects with the support surface C63, so that the swing lever C53 keeps in the first position without external force, and after the swing lever C53 moves to the second position, it has a tendency of pushing the swing lever C53 back to the first position.

(141) When assembling the developing cartridge, one side of the rack C52 is located in the second guide rail C602, and the other side is located in the fourth guide rail C75, and it may move along the second guide rail C602 and the fourth guide rail C75 to install in place; and one side of the rack cover C51 is located in the first guide rail C601 and the other side is located in the third guide rail C74, and it may move along the first guide rail C601 and the third guide rail C74 to install in place.

(142) As shown in FIG. 40, when the electronic imaging apparatus does not start to drive the developing cartridge, the rack C52 is not in contact with the first end C532, at this time, the rack

C52 is at the initial position, the swing lever C53 is at the first position, and the second end C533 does not prevent the electronic imaging apparatus from transmitting electrical energy to the developing cartridge.

(143) As shown in FIG. 41, after the electronic imaging apparatus drives the developing cartridge by the power reception member and transmits driving power to the rack C52, the rack C52 receives the driving power and moves along the second guide rail C602 and the fourth guide rail C75. The first protrusion C521 is in contact with the first end C532, and the second end C533 prevents the electronic imaging apparatus from transmitting electrical energy to the developing cartridge, at this time, the swing lever C53 is at the second position.

(144) As shown in FIG. 42, the rack C52 continues to move forward, when the first protrusion C521 is no longer in contact with the first end C532, the first elastic member C54 pushes the swing lever C53 from the second position back to the first position, at this time, the second end C533 does not prevent the electronic imaging apparatus from transmitting electrical energy to the developing cartridge.

(145) As shown in FIG. 43, the rack C52 then continues to move forward until the second protrusion C522 is in contact with the first end C532, and the second end C533 prevents the electronic imaging apparatus from transmitting electrical energy to the developing cartridge, at this time, the swing lever C53 is at the second position.

(146) As shown in FIG. 44, when the rack continues to drive forward and the second protrusion C522 is no longer in contact with the first end C532, at this time, the rack C52 is at a last position, and the first elastic member C54 pushes the swing lever C53 from the second position back to the first position, at this time, the second end C533 does not prevent the electronic imaging apparatus from transmitting electrical energy to the developing cartridge. In the whole movement process of the rack, the electronic imaging apparatus is pushed twice by the swing lever and receives pulse information twice, so that the specific developing cartridge can be recognized.

(147) After the rack C52 moves from the initial position to the last position, firstly, the rack cover C51 is removed from the developing cartridge; then, the rack C52 is removed from the second guide rail and the fourth guide rail, and reinstalled at the initial position; finally, the rack cover C51 is installed back to the developing cartridge, thereby completing the reset of the rack C52.

(148) Other technical features are same as those of Embodiment 2, and can achieve the same or similar technical effects, which will not be repeated here. For details, please refer to the description of Embodiment 2.

Embodiment 12

(149) The present embodiment is similar to that in Embodiment 11, and parts not described are regarded as the same as those of Embodiment 11.

(150) A rack cover D51 is clamped with the cartridge; and/or, the rack cover C51 is threaded with the cartridge.

(151) A cantilevered buckle (not shown in figure) is provided at a second guide rail D602 and/or a fourth guide rail, the rack C52 is provided with a card slot (not shown in figure) matching with the buckle, when the card slot abuts the buckle, the rack D52 is at the initial position; and the buckle can be used to be a reference datum when the rack D52 is at the initial position.

(152) As shown in FIG. 45A and FIG. 45B, the developing cartridge includes a rack cover D51, an end cover D70, a holding member D60 and other components. Among them, the rack cover D51 may be removed from the developing cartridge without removing other parts. More preferably, the rack cover D51 may be connected to the cartridge by the buckle, and may be removed from the cartridge by hand along the predetermined direction, or, the rack cover D51 may be fixed on the cartridge by screws.

(153) FIG. 46 and FIG. 48 are a position before the rack D51 is installed in place, and FIG. 47 and FIG. 49 are a position after the rack D51 is installed in place; and FIG. 46 and FIG. 47 are schematic structural diagrams viewed from the direction outside of the developing cartridge, FIG.

48 and **FIG. 49** are schematic structural diagrams viewed from the direction inside the developing cartridge, and viewed angles of the direction outside and the direction inside are roughly opposite (that is, an angle between the two is about 180 degrees).

(154) As shown in **FIG. 46** to **FIG. 49**, the rack cover **D51** has a first fixed point **D511**, a second fixed point **D512** and a third fixed point **D513**. Among them, the first fixed point **D511** is located in front of a movement direction of the rack cover **D51** during the installation process, and the first fixed point **D511** is clamped in the specific fixed position **D69** on the holding member **D60** by a card convex way. The second fixed point **D512** is used to prevent the rack cover **D51** from falling off along the installation direction perpendicular to the rack cover **D51**, and the second fixed point **D512** reaches into a first depression **D71** provided at the end cover during the movement process of the rack cover **D51** along the installation direction, so as to prevent the rack cover **D51** from falling off. The third fixed point **D513** is located behind the movement direction of the rack cover **D51** during the installation process. More preferably, the third fixed point **D513** is a card convex provided at the rack cover **D51**, and the card convex may reach into a second depression **D72** of the end cover **D70**, so that the rack cover **D51** may only be taken out along a specific direction.

(155) As shown in **FIG. 50** and **FIG. 51**, the end cover **D70** is provided with a first buckle **D74**, a second buckle **D75** and a screw hole **D76** for fixing the end cover **D70** on the cartridge; and the end cover **D70** is further provided with a third guide rail **D78** used to support the rack cover **D51**, and a fourth guide rail **D79** used to support the rack **D52**. The developing cartridge includes a gear set with a similar structure and transmission relationship to that of Embodiment 10, however, in the present embodiment, the holding member **D60** no longer divides the gear set in two different areas, a third gear **D43** is rotatably fixed on the end cover **D70**. Through providing a third gear shaft **D77** on the end cover **D70**, and providing an anti-falling undercut at the top of the third gear shaft **D77**, the third gear **D43** may be rotatably fixed on the end cover **D70**. To enable the assembly process much easier, a second gear half-shaft **D73** may further be provided on the end cover **D70**, the second gear half-shaft **D73** is docked with another second gear half-shaft on the cartridge to form as a completed second gear shaft. During assembly, it may first insert the second gear **D42** into the second gear half-shaft **D73**, through reasonably setting the position of the second gear half-shaft and the position of the first buckle **D74**, the protruding part of a free end of the first buckle **D74** can restrain the second gear **D42**, so that the second gear **D42** does not fall off from the end cover **D70** without the action of external force. Therefore, the second gear **D42** may be installed at the cartridge together with the end cover **D70** during assembly, thereby inducing work hours of workers and risk of possible loss gears.

(156) As shown in **FIG. 52**, in the present embodiment, the positions of the swing lever **D53** and the first elastic member **D54** are adaptively designed according to the specific structure and the space position of the developing cartridge, principles of the swing lever in two embodiments are the same and may all be pushed by the rack, which are two specific implementation of the swing lever.

(157) As shown in **FIG. 53** and **FIG. 54**, the holding member **D60** is fixed on the cartridge by a third buckle **D66** and a screw hole **D65**, and the projection of the holding member **D60** on a plane perpendicular to the first direction of the cartridge does not coincide with the gear set **D40**, especially, does not coincide with the fourth gear **D41** and the second gear **D42**.

(158) The motion rail of the rack **D52** may be set as: one side is achieved by the holding member **D60** and the other side is achieved by the end cover **D70**. One side of the rack is located in a second guide rail **D602** of the holding member **D60**, and the other side is located in a fourth guide rail **D79** of the end cover **D70**. One side of the rack cover **D51** is located in a first guide rail **D601** of the holding member **D60**, and the other side is located in a third guide rail **D78** of the end cover **D70**, after the rack cover **D51** is installed at the developing cartridge, a guide rail structure which is complete and may restrain simultaneously the upper and lower portions of the rack **D52** is formed on one side of the end cover **D70**. A cantilevered buckle (not shown in figure) may be provided on

the second guide rail **D602** or the fourth guide rail **D79**, at the same time, a card slot (not shown in figure) that can abut with the buckle is provided on the rack **D52**, so as to restrain the rack **D52** at the initial position, and the buckle may be a reference datum when the rack **D52** is at the initial position.

(159) Other technical features are same as those of Embodiment 11, and can achieve the same or similar technical effects, which will not be repeated here. For details, please refer to the description of Embodiment 2.

Embodiment 13

(160) The present embodiment discloses a gear set structure at one end of an activation member of a developing cartridge.

(161) As shown in FIG. 55, the developing cartridge includes a developing supply roller **E32** and a developing roller **E33**, and all these rotating rollers may receive power from the one end of the two ends of the developing cartridge in the length direction and transmit it to the other end. Preferably, in the present embodiment, a second gear **E42** and the developing supply roller **E32** are coaxially provided and fixed on the developing supply roller **E32**. A third gear **E42**, a fourth gear **E43** and a fifth gear **E44** are two-stage gears, and the third gear **E42** engages with the second gear **E41** and the fourth gear **E43**, the fourth gear **E43** engages with the third gear **E42** as well as the fifth gear **E44**, and the fifth gear **E44** engages with the fourth gear **E43**, at the same time, engages with a detection gear **E51**. When the power is transmitted from the developing supply roller **E32**, it passes through the second gear **E41**, the third gear **E42**, the fourth gear **E43** and the fifth gear **E44**, and finally transmitted to a detect gear **E51**. In the present embodiment, the detect gear is the activation member, and the third gear, the fourth gear and the fifth gear are the transmission structure.

Embodiment 14

(162) The present embodiment is a further improvement based on Embodiment 13, and mainly optimizes the gear set at one end of the power reception member of the developing cartridge, and reduces the number of parts, thereby reducing the cost.

(163) As shown in FIG. 56, the driving of the agitator member from the gear set at one end of the power reception member is eliminated in the present embodiment, so as to achieve the effect of reducing parts and saving assembly time.

(164) In the present embodiment, the transmission process of the developing cartridge is as follows: first, the power reception member **F10** receives the rotational driving power from the electronic imaging apparatus; next, the power reception member **F10** drives the developing roller and the developing supply roller to rotate by engaging with a developing roller gear **F21** and a first gear **F22**; then, the developing supply roller transmits power to the gear set at one end of the detect gear, and transmits power to the fifth gear **E41** (see FIG. 55) and the detect gear (see FIG. 55). The fifth gear **E44** is connected with the agitator member through a shaft, so as to achieve a function of driving the agitator member to rotate. Therefore, even if the number of the gear is reduced and the process and time of the assembly is reduced, the whole function of the developing cartridge is completed.

Embodiment 15

(165) Unspecified parts in the present embodiment are the same as those of the foregoing embodiments. The present embodiment relates two technical solutions as follows: one technical solution is that, in order to solve the problem that the rack is too long, the rack is made into two parts that can be extended, and the other technical solution is that, in order to solve the problem that when some type of the developing cartridge is detected by the electronic imaging apparatus, the transmission structure is designed to accelerate the rack forward.

(166) As shown in FIG. 58, the developing cartridge includes two ends in the length direction, which are an A end and a B end. The developing cartridge **1** includes: a cartridge **10**, a developing roller **11**, a developing supply roller **12**, an end cover **18**, a protecting cover **19** and a power reception member **20**. The end cover **18** may be independently and detachably connected with the

protecting cover **19**. Among them, the A end is provided with the power reception member **20** used to receive power from the electronic imaging apparatus; and the B end is provided with a first rack **30** and a second rack **40**, which are used to contact with the detection part in the electronic imaging apparatus.

(167) As shown in FIG. **58**, the developing cartridge receives the rotational power from the electronic imaging apparatus through the power reception member **20**, and transmits the power to the developing supply roller through a first gear **121** which is clamped at one end of the shaft of the developing supply roller **12**, and then drives a second gear **122** which is clamped at the other end of the shaft of the developing supply roller **12** to rotate.

(168) As shown in FIG. **59** and FIG. **60**, the end cover **18** is provided with a guide rail **181**, and the first rack **30** and the second rack **40** are both provided in the guide rail **181**. A side wall **101** at the B end of the cartridge is provided with a first positioning pillar **1011** and a second poisoning pillar **1012**; and the developing cartridge **1** includes: a first intermediate gear **13**, a third idle gear **14a**, a second idle gear **14b**, a hysteresis gear **15**, a first idle gear **16** and a driving gear **17**. Among them, the third idle gear **14a** is coaxially provided with the second idle gear **14b**.

(169) As shown in FIG. **61** and FIG. **62**, the hysteresis gear **15** includes: a first through hole **150**, a first protrusion **151**, a pinion portion **152** and a large gear portion **153**; and the first idle gear **16** includes: a second through hole **160**, a second protrusion **161**, an engaging groove **162** and a first gear portion **163**. Among them, the first gear portion **163** of the first idle gear **16** engages with the second idle gear **14b**.

(170) Where the first through hole **150** and the second through hole **160** are clamped at the first positioning pillar **1011** in turn, the driving gear **17** is installed in the second positioning pillar **1012**, so as to enable the hysteresis gear **15**, the first idle gear **16** and the driving gear **17** to be fixedly connected on the cartridge **10**.

(171) As shown in FIG. **63** and FIG. **64**, the first rack **30** includes: a first detection protrusion **301**, a second detection protrusion **302**, a third protrusion **303** and a first tooth portion **304**. The second rack **40** includes: a third detection protrusion **401**, a fourth detection protrusion **402**, a transmission groove **403** and a second tooth portion **404**. Among them, the third protrusion **303** is clamped in the transmission groove **403** and may move in the transmission groove **403** to enable the first rack **30** and the second rack **40** to move relatively. The positions of the transmission groove and the third protrusion can be interchanged.

(172) As shown in FIG. **65** and FIG. **66**, the rack is at the initial position, when the developing cartridge dose not receive the rotational driving power, the third protrusion **303** is located in the transmission groove **403**, the first tooth portion **304** of the first rack **30** does not engage with the driving gear **17**, and a part of the second tooth portion **404** of the second rack **40** engages with the driving gear **17**.

(173) The developing cartridge receives the rotational driving power from the electronic imaging apparatus by the power reception member **20**, and transmits the power to the gear set of the B end of the developing cartridge by the second gear **122** of the developing supply roller **12**. The second gear **122** transmits the rotational driving power to the first idle gear **13** engaged therewith, and further transmits the rotational driving power to the second idle gear **14b** engaged with the first idle gear **13**. The second idle gear **14b** transmits the rotational driving power received from the first idle gear **13** to the first idle gear **16**, and drives the first idle gear **16** to rotate.

(174) When the first idle gear **16** rotates, the second protrusion **161** also rotates, gradually rotates to a position where it is in contact with the first protrusion **151** of the hysteresis gear **15** clamped in the engaging groove **162**, and then drives the hysteresis gear **15** to rotate. Due to the process needs certain buffer time, the hysteresis gear **15** rotates lagging relative to the first idle gear **16**. When the hysteresis gear rotates, the driving gear **17** engaged therewith also rotates, so as to drive the second rack **40** to move, at this time, the first rack **30** dose not move relative to the driving gear **17**.

(175) The first rack **30** and the second rack **40** are connected in a sliding way, the first rack **30** lags

behind the second rack **40**, the second rack **40** moves under the drive of the driving gear **17**, and then the second rack **40** drives the first rack **30** to connect with a driving gear **1730**, so that the first rack **30** may directly receive driving power from the driving gear **17** to move in a translation way instead of being driven by the second rack **40**.

(176) As shown in FIG. **67** and FIG. **68**, when the rack is at a middle position, an end of the transmission groove **403** moves to a position abutted with the third protrusion **303**, meanwhile the second tooth portion **404** of the second rack **40** moves a certain distance relative to the driving gear **17**, and the first tooth portion **304** of the first rack **30** is still in a state not engaged with the driving gear **17**.

(177) During the second rack **40** moves from the initial position to the middle position, the detection part of the electronic imaging apparatus is in contact with the third detection protrusion **401** and the fourth detection protrusion **402** of the second rack **40**, and continuously goes through the process of contact, separation, re-contact, and re-separation between the detection part and the detection protrusion.

(178) When the rack is at the middle position, the second rack **40** no longer receives driving power and stops moving, and the first rack **30** is still connected with the driving gear **17**, that is, the first rack **30** may still receive the driving power to move.

(179) As shown in FIG. **69** and FIG. **70**, after the hysteresis gear **15** receives the rotational driving power from first idle gear **16**, the pinion portion **152** of the hysteresis gear **15** gradually rotates to engage with the third idle gear **14a**, so as to drive the hysteresis gear **15** to rotate in an accelerated way, so as to further drive both the hysteresis gear **15** and the driving gear **17** engaged therewith to rotate in an accelerated way.

(180) Due to the accelerated rotation of the driving gear **17**, the first rack **30** gradually moves from the position engaged with the driving gear **17** to the position disengaged with the driving gear **17**, at this time, the first rack also stops to move, and the rack reaches to the last position. After the driving gear **17** completes the acceleration, the first rack **30** completely disengages with the driving gear **17**, that is, a last tooth of the first tooth portion **304** of the first rack **30** is flushed with a last tooth of the second tooth portion **404** of the second rack **40**, the first rack **30** and the second rack **40** are both disengaged with the driving gear **17** at the same time. Meanwhile, the third protrusion **303** moves to the position abutted against the front end of the transmission groove **403**. When the rack is at the last position, the swing lever of the electronic imaging apparatus is always in contact with the detection protrusion.

(181) The first rack **30** and the second rack **40** are overlapped and in a folded state, and the first rack **30** and the second rack **40** move in the same direction sequentially, so that the first rack **30** and the second rack **40** are in a unfolded state, and the unfolded first rack may also be driven in the same direction, thus the first rack **30** and the second rack **40** are in the folded state again, thereby reducing the size of the developing cartridge **1**, and further reducing the cost.

(182) Finally, it should be noted that the above embodiments are only used to illustrate the technical solutions of the present application, rather than limiting them; Although the application has been described in detail with reference to the foregoing embodiments, those of ordinary skilled in the art should understand that they can still modify the technical solutions described in the foregoing embodiments, or equivalently replace some or all of the technical features. And these modifications or replacements do not cause the essence of the corresponding technical solutions to deviate from the scope of the technical solutions of the embodiments of the present application.

Claims

1. A developing cartridge, comprising: a cartridge containing a developer and including a first side wall and a second side wall positioned opposite to each other along a first direction; a power reception member configured to receive a driving power and positioned at the first side wall; a

- developing roller rotatable about a first axis extending in the first direction; and an activation member including a movable member and a detection protrusion positioned at the second side wall, wherein the movable member rotates around a second axis in a second direction, the first direction and the second direction intersect with each other, and the detection protrusion moves as the movable member moves.
2. The developing cartridge according to claim 1, further comprising: a first gear positioned at the first side wall and driven by the driving power received by the power reception member to rotate about a third axis extending in the first direction.
 3. The developing cartridge according to claim 1, further comprising: a second gear rotatable about a fourth axis extending in the first direction, the second gear including a bevel gear part.
 4. The developing cartridge according to claim 3, wherein: the movable member as is rotated by the second gear.
 5. The developing cartridge according to claim 1, further comprising: an intermediate transmitting member positioned at the second side wall and moves as the movable member rotates.
 6. The developing cartridge according to claim 5, wherein: the intermediate transmitting member rotates about a fifth axis that is not parallel with the first direction.
 7. The developing cartridge according to claim 6, wherein: the intermediate transmitting member is a swing lever.
 8. The developing cartridge according to claim 5, further comprising: an elastic member, wherein one end of the first elastic member is connected to the intermediate transmitting member.
 9. The developing cartridge according to claim 1, wherein: the movable member includes a missing tooth part and a protrusion.
 10. The developing cartridge according to claim 1, further comprising: a conductive part positioned at the second side wall.
 11. The developing cartridge according to claim 10, wherein: the movable member is made of conductive material.
 12. The developing cartridge according to claim 10, wherein: the movable member is made of insulating material.
 13. A developing cartridge, comprising: a cartridge containing a developer and including a first side wall and a second side wall positioned opposite to each other along a first direction; a power reception member configured to receive a driving power and positioned at the first side wall; a developing roller rotatable about a first axis extending in the first direction; and an activation member including a movable member and a detection protrusion positioned at the second side wall; wherein the detection protrusion moves as the movable member moves, and the movable member is a flexible member.
 14. The developing cartridge according to claim 13, further comprising: at least a portion of the movable member is located closer to the second side wall than the power reception member in the first direction.
 15. The developing cartridge according to claim 13, further comprising: a guide rail along which the movable member moves.
 16. The developing cartridge according to claim 13, further comprising: an electrode positioned at the second side wall.
-