

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397993
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Chen; Yeguang et al.

Loading or unloading apparatus, system, and method

Abstract

A loading or unloading apparatus configured to convey goods to a transport robot or unload goods on the transport robot. The loading or unloading apparatus includes an upright frame, a plurality of goods loading or unloading assemblies and a second driving structure. The upright frame is extending along a vertical direction. The plurality of goods loading or unloading assemblies are arranged on the upright frame at intervals along the vertical direction and capable of separately conveying, at different heights, the goods to the transport robot or unloading the goods on the transport robot. The second driving structure is configured to drive the upright frame to approach or move away from the transport robot along a loading or unloading direction, such that the plurality of goods loading or unloading assemblies convey the goods to the transport robot or unload the goods on the transport robot.

Inventors:	Chen; Yeguang (Guangdong, CN), Kong; Zhe (Guangdong, CN)
Applicant:	HAI ROBOTICS CO., LTD. (Guangdong, CN)
Family ID:	1000008781209
Assignee:	HAI ROBOTICS CO., LTD. (Guangdong, CN)
Appl. No.:	17/939647
Filed:	September 07, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230034430 A1	Feb. 02, 2023

Foreign Application Priority Data

CN	202010157383.9	Mar. 09, 2020
CN	202010157413.6	Mar. 09, 2020
CN	202020280361.7	Mar. 09, 2020
CN	202020281007.6	Mar. 09, 2020

CN	202020281070.X	Mar. 09, 2020
CN	202020281542.1	Mar. 09, 2020
CN	202020281558.2	Mar. 09, 2020
CN	202020282274.5	Mar. 09, 2020
CN	202020283790.X	Mar. 09, 2020
CN	202010520140.7	Jun. 09, 2020

Related U.S. Application Data

continuation parent-doc WO PCT/CN2021/079173 20210304 PENDING child-doc US 17939647

Publication Classification

Int. Cl.: B65G1/137 (20060101); B65G1/06 (20060101)

U.S. Cl.:

CPC B65G1/1375 (20130101); B65G1/06 (20130101);

Field of Classification Search

CPC: B65G (1/1375); B65G (1/02); B65G (1/06); B65G (65/00)

USPC: 700/213; 700/214; 700/218

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5379229	12/1994	Parsons et al.	N/A	N/A
5895195	12/1998	Simmons et al.	N/A	N/A
6755322	12/2003	Herzog et al.	N/A	N/A
9008829	12/2014	Worsley	N/A	B65G 1/10
9663292	12/2016	Brazeau et al.	N/A	N/A
11180069	12/2020	Jarvis et al.	N/A	B60P 3/007
2006/0245862	12/2005	Hansl et al.	N/A	N/A
2007/0140817	12/2006	Hansl	N/A	N/A
2017/0174431	12/2016	Borders et al.	N/A	B65G 1/0421
2019/0352092	12/2018	Zheng et al.	N/A	N/A
2020/0048005	12/2019	Kraetsch et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
108190341	12/2017	CA	N/A
102627179	12/2011	CN	N/A
103350850	12/2012	CN	N/A
203544918	12/2013	CN	N/A
105593143	12/2015	CN	N/A
106064386	12/2015	CN	N/A

107000934	12/2016	CN	N/A
206569571	12/2016	CN	N/A
206665475	12/2016	CN	N/A
207158372	12/2017	CN	N/A
107922119	12/2017	CN	N/A
108069180	12/2017	CN	N/A
207536599	12/2017	CN	N/A
207580635	12/2017	CN	N/A
208008400	12/2017	CN	N/A
108861283	12/2017	CN	N/A
208249076	12/2017	CN	N/A
208307644	12/2018	CN	N/A
109592280	12/2018	CN	N/A
208761426	12/2018	CN	N/A
208761427	12/2018	CN	N/A
109748027	12/2018	CN	N/A
109760981	12/2018	CN	N/A
209023571	12/2018	CN	N/A
110239870	12/2018	CN	N/A
209522319	12/2018	CN	N/A
110537189	12/2018	CN	N/A
209871392	12/2018	CN	N/A
210028821	12/2019	CN	N/A
111634597	12/2019	CN	N/A
212244808	12/2019	CN	N/A
212244809	12/2019	CN	N/A
212244811	12/2019	CN	N/A
212638694	12/2020	CN	N/A
102017112658	12/2017	DE	N/A
0235488	12/1986	EP	N/A
2018163415	12/2017	JP	N/A
101470741	12/2013	KR	N/A
20150142729	12/2014	KR	N/A
WO2016151504	12/2015	WO	N/A
WO2017090108	12/2016	WO	N/A

OTHER PUBLICATIONS

International search report of PCT/CN2021/079173 mailed Jun. 9, 2021 with English translation. cited by applicant

Notice of Allowance of Chinese Application No. 202111027600.3, issued on Feb. 27, 2025. cited by applicant

First Office Action of Chinese Application No. 202111027460.X, dated Apr. 1, 2025, and search report, and its English translation. cited by applicant

Primary Examiner: Crawford; Gene O

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) The present disclosure is a continuation of International Patent Application No. PCT/CN2021/079173 filed on Mar. 4, 2021, which claims priority to Chinese Patent Application No. 202010520140.7, entitled “LOADING OR UNLOADING APPARATUS AND LOADING OR UNLOADING METHOD” and filed with the China National Intellectual Property Administration on Jun. 9, 2020; Chinese Patent Application No. 202010157383.9, entitled “LOADING OR UNLOADING APPARATUS AND LOADING OR UNLOADING METHOD” and filed with the China National Intellectual Property Administration on Mar. 9, 2020; Chinese Patent Application No. 202020281542.1, entitled “LOADING OR UNLOADING APPARATUS AND LOADING OR UNLOADING SYSTEM” and filed with the China National Intellectual Property Administration on Mar. 9, 2020; Chinese Patent Application No. 202020281007.6, entitled “TRANSPORT ROBOT AND TRANSPORT SYSTEM HAVING SAME” and filed with the China National Intellectual Property Administration on Mar. 9, 2020; Chinese Patent Application No. 202010157413.6, entitled “TRANSPORT ROBOT, TRANSPORT SYSTEM, AND TRANSPORT METHOD THEREOF” and filed with the China National Intellectual Property Administration on Mar. 9, 2020; Chinese Patent Application No. 202020280361.7, entitled “TRANSPORT ROBOT AND TRANSPORT SYSTEM HAVING SAME” and filed with the China National Intellectual Property Administration on Mar. 9, 2020; Chinese Patent Application No. 202020281070.X, entitled “TRANSPORT ROBOT AND TRANSPORT SYSTEM HAVING SAME” and filed with the China National Intellectual Property Administration on Mar. 9, 2020; Chinese Patent Application No. 202020282274.5, entitled “LOADING OR UNLOADING APPARATUS AND LOADING OR UNLOADING SYSTEM” and filed with the China National Intellectual Property Administration on Mar. 9, 2020; Chinese Patent Application No. 202020283790.X, entitled “LOADING OR UNLOADING APPARATUS AND LOADING OR UNLOADING SYSTEM” and filed with the China National Intellectual Property Administration on Mar. 9, 2020; and Chinese Patent Application No. 202020281558.2, entitled “TRANSPORT ROBOT AND TRANSPORT SYSTEM HAVING SAME” and filed with the China National Intellectual Property Administration on Mar. 9, 2020, which are incorporated herein by reference in their entireties.

TECHNICAL FIELD

(1) The present disclosure relates to the technical field of warehousing and logistics, and in particular, to a loading or unloading apparatus, system, and method for same.

BACKGROUND

(2) Intelligent warehousing is a step in the logistics process. The application of intelligent warehousing ensures the speed and accuracy of data input in various steps of warehouse management of goods, so as to ensure that enterprises can accurately grasp the real data of the inventory in a timely and accurately manner, and reasonably maintain and control the enterprise inventory. Through scientific coding, batches and shelf life of inventory goods can also be conveniently managed. By using the storage location management function, current locations of all inventory goods can be grasped in time, which is conducive to improving the efficiency of warehouse management.

(3) The transport robot plays an important role in intelligent warehousing, and replaces the manual transport of goods. However, the overall working efficiency of an existing transport robot is low.

SUMMARY

(4) To resolve the foregoing technical problems, embodiments of the present disclosure provide a transport robot, system, and method, and a loading or unloading apparatus, system, and method, which are used for improving the overall working efficiency of the transport robot.

(5) To resolve the foregoing technical problems, the embodiments of the present disclosure provide the following technical solutions:

(6) According to a first aspect, the present disclosure provides a transport robot, including: a

vertical frame arranged along a vertical direction; and a storage mechanism including a plurality of storage assemblies configured to store to-be-transported goods and arranged on the vertical frame at equal intervals along the vertical direction.

(7) Optionally, an interval between two adjacent storage assemblies is equal; and when the transport robot is unloading, the plurality of storage assemblies are capable of moving synchronously to perform a synchronous unloading action.

(8) Optionally, the transport robot further includes: a chassis capable of moving on a ground; a lifting mechanism arranged on the vertical frame and capable of ascending or descending relative to the vertical frame along the vertical direction; and a carrying mechanism configured to carry goods, movably arranged on the vertical frame along the vertical direction, connected to the lifting mechanism, and capable of ascending or descending along the vertical direction under driving of the lifting mechanism, so as to deliver goods in the carrying mechanism to corresponding storage assemblies.

(9) Optionally, the transport robot further includes a blocking mechanism capable of switching between a blocking position and an avoidance position, where when the blocking mechanism is at the blocking position, the blocking mechanism is configured to block goods in the plurality of storage assemblies from sliding out; and when the blocking mechanism is at the avoidance position, goods are capable of being moved into or moved out of the plurality of storage assemblies.

(10) Optionally, the transport robot further includes: a lifting mechanism arranged on the vertical frame and capable of ascending or descending relative to the vertical frame along the vertical direction; and a carrying mechanism configured to carry goods, movably arranged on the vertical frame along the vertical direction, connected to the lifting mechanism, and capable of ascending or descending along the vertical direction under driving of the lifting mechanism, so as to deliver, at different heights, goods in the carrying mechanism to corresponding storage assemblies.

(11) Optionally, the transport robot further includes: a chassis movable on a ground; a lifting mechanism arranged on the vertical frame and capable of ascending or descending relative to the vertical frame along the vertical direction; a carrying mechanism configured to carry goods, movably arranged on the vertical frame along the vertical direction, connected to the lifting mechanism, and capable of ascending or descending along the vertical direction under driving of the lifting mechanism, so as to deliver goods in the carrying mechanism to corresponding storage assemblies; and a controller electrically connected to the chassis, the lifting mechanism, and the carrying mechanism and configured to control the chassis, the lifting mechanism, and the carrying mechanism to individually or jointly perform an action.

(12) According to a second aspect, the present disclosure further provides a transport system, including an auxiliary apparatus and the transport robot according to the first aspect.

(13) According to a third aspect, the present disclosure further provides a transport system, including a control center and the transport robot according to the first aspect.

(14) According to a fourth aspect, the present disclosure further provides a transport system, including a loading or unloading apparatus and the transport robot according to the first aspect.

(15) According to a fifth aspect, the present disclosure further provides a loading or unloading apparatus configured to convey goods to a transport robot or unload goods on the transport robot.

The loading or unloading apparatus includes an upright frame, a plurality of goods loading or unloading assemblies and a second driving structure. The upright frame is extending along a vertical direction. The plurality of goods loading or unloading assemblies are arranged on the upright frame at intervals along the vertical direction and capable of separately conveying, at different heights, the goods to the transport robot or unloading the goods on the transport robot. The second driving structure is configured to drive the upright frame to approach or move away from the transport robot along a loading or unloading direction, wherein when the second driving structure drives the upright frame to approach or move away from the transport robot, the plurality

of goods loading or unloading assemblies convey the goods to the transport robot or unload the goods on the transport robot.

(16) Optionally, each of the plurality of goods loading or unloading assemblies includes a bracket, a loading or unloading structure, and a first driving structure. A plurality of brackets of the plurality of goods loading or unloading assemblies are arranged on the upright frame at intervals along the vertical direction. The first driving structure and the loading or unloading structure are respectively arranged on corresponding brackets, and the loading or unloading structure is in driving connection with the first driving structure and is configured to convey the goods to the transport robot or unload the goods on the transport robot.

(17) Optionally, the loading or unloading structure includes a chain and a protrusion. The chain is rotatably arranged on the bracket along a loading or unloading direction, and the protrusion is fixedly arranged on the chain. The first driving structure includes a driving motor in driving connection with the chain; and the chain is capable of carrying goods, and when the chain rotates, the protrusion pushes a bottom portion of goods, so that the goods are pushed to the transport robot, or the protrusion pulls a bottom portion of goods, so that the goods are pulled from the transport robot to the chain.

(18) Optionally, each of the plurality of goods loading or unloading assemblies includes a separate driving structure.

(19) Optionally, the loading or unloading apparatus further includes a second driving structure configured to drive the upright frame to approach or move away from the transport robot along a loading or unloading direction, where when the second driving structure drives the upright frame to approach or move away from the transport robot, the plurality of goods loading or unloading assemblies convey the goods to the transport robot or unload the goods on the transport robot.

(20) According to a sixth aspect, the present disclosure further provides a loading or unloading system, including a transport robot and the loading or unloading apparatus according to the fifth aspect, where the loading or unloading apparatus is configured to convey goods to the transport robot or unload goods on the transport robot.

(21) According to a seventh aspect, the present disclosure further provides a loading or unloading method, applied to the loading or unloading apparatus according to the fifth aspect. The loading or unloading method includes: receiving a second loading or unloading instruction; and controlling, according to the second loading or unloading instruction, the second driving structure to drive the upright frame to approach or move away from the transport robot along a loading or unloading direction, and controlling the plurality of goods loading or unloading assemblies to convey the goods to the transport robot or unload the goods on the transport robot.

(22) After adopting the foregoing technical solutions, the present disclosure has at least the following technical effects:

(23) In the transport robot provided in the present disclosure, when unloading, a plurality of storage assemblies of a storage mechanism may move synchronously to perform a synchronous unloading action, so that the synchronous unloading of goods in the plurality of storage assemblies is implemented. The current problem of a low unloading efficiency caused by the layer-by-layer unloading of goods is effectively resolved, goods in the transport robot can be unloaded at one time, the unloading efficiency is improved, the unloading time is reduced, and the overall working efficiency of the transport robot is improved.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a three-dimensional view of a transport robot viewed from an angle according to an embodiment of the present disclosure;

- (2) FIG. 2 is a three-dimensional view of the transport robot shown in FIG. 1 viewed from another angle;
- (3) FIG. 3 is a schematic partial view of the transport robot shown in FIG. 1 at A;
- (4) FIG. 4 is a three-dimensional view of the transport robot shown in FIG. 1 with a base, a vertical frame, and a lifting mechanism removed;
- (5) FIG. 5 is a three-dimensional view of a storage assembly shown in FIG. 2;
- (6) FIG. 6 is a three-dimensional view of a transport system of the transport robot shown in FIG. 1;
- (7) FIG. 7 is a three-dimensional view of an auxiliary apparatus in the transport system shown in FIG. 6;
- (8) FIG. 8 is a three-dimensional view of a lifting apparatus in the transport system shown in FIG. 6;
- (9) FIG. 9 is a three-dimensional view of a transport robot according to another embodiment of the present disclosure;
- (10) FIG. 10 is a partial enlarged view of the transport robot shown in FIG. 9;
- (11) FIG. 11 is a three-dimensional view of the transport robot shown in FIG. 10 applied to a transport system;
- (12) FIG. 12 is a three-dimensional view of a loading or unloading apparatus in an implementation of the transport system shown in FIG. 9;
- (13) FIG. 13 is a partial schematic view of the loading or unloading apparatus shown in FIG. 12;
- (14) FIG. 14 is a three-dimensional view of a loading or unloading apparatus in another implementation of the transport system shown in FIG. 11;
- (15) FIG. 15 is a partial schematic view of the loading or unloading apparatus shown in FIG. 14;
- (16) FIG. 16 is a three-dimensional view of a loading or unloading apparatus provided in still another implementation of the present disclosure;
- (17) FIG. 17 is a three-dimensional view of a cooperation between the loading or unloading apparatus shown in FIG. 14 and a transport robot;
- (18) FIG. 18 is a schematic structural diagram of a loading or unloading apparatus according to an embodiment of the present disclosure;
- (19) FIG. 19 is an enlarged schematic view of a partial structure in FIG. 18;
- (20) FIG. 20 is a schematic structural diagram of a transport robot corresponding to the loading or unloading apparatus in FIG. 18 according to an embodiment of the present disclosure;
- (21) FIG. 21 is an enlarged schematic view of a partial structure in FIG. 20;
- (22) FIG. 22 is a schematic structural diagram of a loading or unloading system according to an embodiment of the present disclosure;
- (23) FIG. 23 is a schematic structural diagram of a loading or unloading apparatus according to another embodiment of the present disclosure;
- (24) FIG. 24 is an enlarged schematic view of a partial structure in FIG. 23;
- (25) FIG. 25 is a schematic structural diagram of a loading or unloading apparatus according to still another embodiment of the present disclosure;
- (26) FIG. 26 is a schematic structural diagram of a loading or unloading system according to another embodiment of the present disclosure;
- (27) FIG. 27 is a schematic structural diagram of a loading or unloading method according to an embodiment of the present disclosure;
- (28) FIG. 28 is a schematic diagram of specific operations of an operation S40 according to an embodiment of the present disclosure; and
- (29) FIG. 29 is a schematic diagram of specific operations of an operation S40 according to another embodiment of the present disclosure.

DETAILED DESCRIPTION

Embodiment 1

- (30) Referring to FIG. 1, FIG. 3, and FIG. 6, the present disclosure provides a transport robot **100**.

The transport robot **100** is applied to a transport system, and can transport goods **200**. It can be understood that the goods **200** may be goods with a bracket, and the transport robot **100** transports the goods **200** through the bracket. Certainly, the goods may alternatively be goods placed in a container, and the transport robot **100** transports the goods **200** through the container. The goods **200** described below are goods placed in the container, and the container may be loaded with the goods **200**, so as to implement the transport of the goods **200**. The transport robot **100** transports the container to an unloading position, and after unloading the goods **200** in the container, the container may be transported back to the transport robot **100**, so as to reuse the container and reduce the cost. Alternatively, reference sign **200** refers to a container with goods, and the transport robot **100** transports the container to the unloading position, and unloads the container with goods through an unloading apparatus.

(31) The transport robot **100** plays an important role in intelligent warehousing, transports goods **200**, ensures a transport speed of the goods **200**, improves the transport efficiency of the goods **200**, and reduces the consumption of labor resources. The transport robot **100** of the present disclosure can unload synchronously, so that goods **200** in the transport robot **100** can be unloaded at one time, thereby improving the unloading efficiency, reducing the unloading time, and improving the overall working efficiency of the transport robot **100**.

(32) Referring to FIG. 1 and FIG. 3, in an embodiment, the transport robot **100** includes a vertical frame **110** and a storage mechanism **120**. The vertical frame **110** is arranged along a vertical direction. The storage mechanism **120** includes a plurality of storage assemblies **121** configured to store to-be-transported goods **200** and movably arranged on the vertical frame **110** at intervals along the vertical direction. An interval between two adjacent storage assemblies **121** is equal. When the transport robot **100** is unloading, the plurality of storage assemblies **121** are capable of moving synchronously to perform a synchronous unloading action.

(33) The vertical frame **110** plays a bearing role, and various components of the transport robot **100** are mounted thereon. When the transport robot **100** transports the goods **200**, the vertical frame **110** may drive synchronous movement of the components on the transport robot **100**, so as to implement the transport of the goods **200**. The storage mechanism **120** is located on the vertical frame **110**, is configured to store the goods **200**, and is capable of moving synchronously with the vertical frame **110**, so as to implement the transport of the goods **200**. The transport robot **100** moves to a loading position, and the to-be-transported goods **200** are transported to the storage mechanism **120** for storage. Then, the transport robot **100** moves from the loading position to an unloading position. Correspondingly, the storage mechanism **120** moves to the unloading position along with the vertical frame **110**. At this time, the goods **200** in the storage mechanism **120** can be unloaded. The storage mechanism **120** can temporarily store the to-be-transported goods **200**, thereby improving the capability of the transport robot **100** to carry the goods **200**.

(34) In addition, the storage mechanism **120** includes a plurality of storage assemblies **121** arranged on the vertical frame **110** at intervals, and an interval between two adjacent storage assemblies **121** is equal. Each of the plurality of storage assemblies **121** can carry goods **200** of a container to ensure a storage capacity of the transport robot **100**. That is, the plurality of storage assemblies **121** are evenly distributed on the vertical frame **110** along the vertical direction. The to-be-transported goods **200** may be transported to the plurality of storage assemblies **121**, and the transport robot **100** drives the goods **200** in the plurality of storage assemblies **121** to be transported to the unloading position.

(35) To further improve the transport efficiency of the transport robot **100**, the transport robot **100** of the present disclosure can implement synchronous unloading at the unloading position. Specifically, during unloading, the plurality of storage assemblies **121** may move synchronously, so that the goods **200** are moved out of the plurality of storage assemblies **121**, and a synchronous unloading action is performed in real time. In this way, the goods **200** in the plurality of storage assemblies **121** can be unloaded synchronously, which shortens the unloading time and improves

the unloading efficiency of the transport robot **100**. After the unloading is completed, the transport robot **100** may return to the loading position to continue loading, which improves the working efficiency of the transport robot **100**.

(36) In this embodiment described above, when the transport robot **100** is unloading, a plurality of storage assemblies **121** of a storage mechanism **120** may move synchronously to perform a synchronous unloading action, so that the synchronous unloading of goods **200** in the plurality of storage assemblies **121** is implemented, the current problem of a low unloading efficiency caused by the layer-by-layer unloading of goods is effectively resolved, goods **200** in the transport robot **100** can be unloaded at one time, the unloading efficiency is improved, the unloading time is reduced, and the overall working efficiency of the transport robot **100** is improved.

(37) In an embodiment, the transport robot **100** further includes a movable chassis **160** arranged at a bottom portion of the vertical frame **110**. The movable chassis **160** can drive the transport robot **100** to move, which greatly improves the adaptability of the transport robot **100** to actual working conditions. Specifically, the chassis **160** includes a chassis frame **161**, a travel drive assembly, and a plurality of rotating wheels **162**. The vertical frame **110** is arranged on an upper portion of the chassis frame **161**, the plurality of rotating wheels **162** are arranged on a bottom portion of the chassis frame **161**, the travel drive assembly is arranged on the chassis frame **161**, and at least one of the plurality of rotating wheels **162** is in driving connection with the travel drive assembly. Further, at least two of the plurality of rotating wheels **162** are separately in driving connection with the travel drive assembly, and the at least two of the plurality of rotating wheels **162** being separately in driving connection with the travel drive assembly are distributed on two sides of the chassis frame **161** along a traveling direction, thereby achieving a steering function of the chassis **160**. The travel drive assembly includes at least two wheel drive motors, and the at least two of the plurality of rotating wheels **162** distributed on the two sides of the chassis frame **161** along the traveling direction are respectively driven by separate wheel drive motors. That the at least two of the plurality of rotating wheels **162** distributed on the two sides of the chassis frame **161** along the traveling direction are respectively driven by separate wheel drive motors can simplify a transmission structure on the chassis **160**.

(38) In an embodiment, each of the plurality of rotating wheels **162** includes a driving wheel and a driven wheel. The driving wheel and the driven wheel are mounted on a bottom portion of the chassis **160**, may separately rotate relative to the chassis **160**, and jointly support the chassis **160**. The driving wheel is driven by a wheel drive motor to enable the chassis **160** to move. By configuring the movable chassis **160**, the transport robot **100** can transport the goods **200** between the loading position and the unloading position. There are two driving wheels, and the two driving wheels are symmetrically distributed. Correspondingly, there are two wheel drive motors, and the two driving wheels are respectively driven by the two wheel drive motors, so that rotational speeds of the two driving wheels could be different, thereby implementing the steering of the chassis **160**. There are four driven wheels, and the four driven wheels are distributed in a rectangular shape. The four driven wheels may be universal wheels or may be of other wheel structures with a steering function. According to actual situations, a quantity of the driven wheel is not limited to four, but may also be six, three, or the like.

(39) In this embodiment, the chassis **160** is also mounted with a guiding apparatus, and the guiding apparatus may be a camera configured to identify a graphic code attached to a ground, so that the chassis **160** travels along a preset path. The graphic code may be a two-dimensional code, a barcode, or some customized identification codes. In some other embodiments, the guiding apparatus may be a laser guiding apparatus configured to guide the chassis **160** to travel along a laser beam, or the guiding apparatus may be a short-wave receiving apparatus configured to receive a preset short-wave signal to guide the chassis **160** to travel along a preset path. It should be noted that, in some other embodiments, the chassis **160** may be omitted, and the vertical frame **110** is directly and fixedly mounted on the ground or another platform, and is only configured to carry the

goods **200** between the loading position and the unloading position around the vertical frame.

(40) Referring to FIG. **1** to FIG. **4**, in an embodiment, the transport robot **100** further includes at least one linkage mechanism **130**, and each of the at least one linkage mechanism **130** is connected to at least two storage assemblies **121** and is configured to drive the at least two storage assemblies **121** to move synchronously relative to the vertical frame **110** to perform a synchronous unloading action. When the at least one linkage mechanism **130** moves, a synchronous movement of the at least two storage assemblies **121** may be implemented. It can be understood that one linkage mechanism **130** may be connected to all storage assemblies **121**, and alternatively, among a plurality of linkage mechanisms **130**, each of the plurality of linkage mechanisms **130** may be connected to a plurality of storage assemblies **121**. Exemplarily, there are two linkage mechanisms **130**, where one of the two linkage mechanisms **130** is connected to storage assemblies **121** of first to third layers, and the other one of the two linkage mechanisms **130** is connected to storage assemblies **121** of fourth to sixth layers. Certainly, in another implementation of the transport robot and the transport system having same, there may be more linkage mechanisms **130**. The transport robot and the transport system having the same are only described by taking an example in which one linkage mechanism **130** is connected to all storage assemblies **121**. A working principle of a plurality of linkage mechanisms **130** is substantially the same as that of the one linkage mechanism **130**, and details are not described herein again.

(41) The storage mechanism **120** may be rotatably mounted on the vertical frame **110**, and may further be connected to the linkage mechanism **130**. When moving, the linkage mechanism **130** drives the plurality of storage assemblies **121** to rotate relative to the vertical frame **110**, so that the plurality of storage assemblies **121** can undergo a pitching motion. It can be understood that one end of the linkage mechanism **130** may be mounted on the vertical frame **110** or the chassis **160**, as long as the linkage mechanism **130** can drive the plurality of storage assemblies **121** to undergo a pitching motion.

(42) When the linkage mechanism **130** drives the plurality of storage assemblies **121** to move upward, one ends of the plurality of storage assemblies **121** are lifted up, and other ends rotate relative to the vertical frame **110**, so as to stay at initial positions. At this time, the plurality of storage assemblies **121** are lifted up, and goods **200** thereon may slide out of the plurality of storage assemblies **121** under an action of gravity thereof, so as to implement the unloading of the goods **200**. Because the linkage mechanism **130** simultaneously drives the plurality of storage assemblies **121** to move upward, the plurality of storage assemblies **121** can be simultaneously lifted up, thereby simultaneously performing an unloading operation to implement the unloading. After the unloading is completed, the linkage mechanism **130** drives the plurality of storage assemblies **121** to descend, and the plurality of storage assemblies **121** return to horizontal initial positions.

(43) When the linkage mechanism **130** drives the plurality of storage assemblies **121** to move downward, and after external goods **200** are simultaneously conveyed to the plurality of storage assemblies **121**, the goods **200** can slide into the plurality of storage assemblies **121** under the action of gravity to implement synchronous loading. It should be noted that the synchronous loading of the transport robot **100** needs to be implemented in cooperation with an auxiliary apparatus **300** of the transport system, a specific implementation process is described in detail in the following specification, and only the synchronous unloading of the transport robot **100** is described in detail in this embodiment.

(44) After the transport robot **100** loads the goods **200** into the plurality of storage assemblies **121** at the loading position, the transport robot **100** moves from the loading position to the unloading position. At this time, the linkage mechanism **130** drives the plurality of storage assemblies **121** to move upward, so that the plurality of storage assemblies **121** are lifted up. In this way, the goods **200** in the plurality of storage assemblies **121** can slide out of the plurality of storage assemblies **121** under the action of gravity thereof, and be stored in a specified apparatus such as the auxiliary

apparatus **300**, so as to implement the synchronous unloading of the transport robot **100**. After the unloading is completed, the transport robot **100** returns to the loading position to load goods, and in this way, a transport function of the transport robot **100** is achieved.

(45) In an embodiment, the linkage mechanism **130** includes a linkage connector **131** simultaneously connected to at least two storage assemblies **121** and capable of synchronously driving the at least two storage assemblies **121** to synchronously undergo a pitching motion. It can be understood that the pitching motion herein may be a pitching rotational motion, or a curved motion, and certainly, may also be in other forms that can generate the pitching motion. One ends of the at least two storage assemblies **121** are rotatably connected to the vertical frame **110**, and the at least two storage assemblies **121** are also connected to the linkage connector **131**. The linkage connector **131** can ascend or descend. When ascending or descending, the linkage connector **131** may drive the at least two storage assemblies **121** to ascend or descend, so that the at least two storage assemblies **121** rotate relative to the vertical frame **110**, that is, the at least two storage assemblies **121** undergo a pitching motion. It can be understood that, when one of the at least two storage assemblies **121** undergo a pitching motion, the linkage connector **131** is driven to ascend or descend, and the remaining storage assemblies **121** may be driven to move through the linkage connector **131**; or the linkage connector **131** ascends or descends, and then the at least two storage assemblies **121** are driven to move.

(46) As shown in FIG. 1 and FIG. 2, optionally, the linkage connector **131** and the at least two storage assemblies **121** may be rotatably connected or fixedly connected. When the linkage connector **131** and the at least two storage assemblies **121** are rotatably connected, the at least two storage assemblies **121** may have a rotary shaft, and the at least two storage assemblies **121** may be rotatably mounted on the linkage connector **131** through the rotary shaft. Alternatively, the linkage connector **131** may have a rotary shaft, and the linkage connector **131** may be rotatably mounted on the at least two storage assemblies **121** through the rotary shaft. Alternatively, a connection between the linkage connector **131** and the at least two storage assemblies **121** is similar to an olecranon engagement structure. In addition, the rotary shaft may be replaced with a hinge or another component that can implement a rotatable connection.

(47) Optionally, the linkage connector **131** may be a connecting rod connected to the at least two storage assemblies **121**. Further optionally, the linkage member may include a plurality of connecting rods, and two adjacent storage assemblies **121** are connected by one of the plurality of connecting rods. In this case, when one of the at least two storage assemblies **121** moves, adjacent connecting rods may drive the remaining storage assemblies **121** to move. It can be understood that a specific structure of the linkage connector **131** is not limited to the connecting rod, but may also be a connecting piece or the like.

(48) It should be noted that, the essential spirit of the present disclosure lies in the linkage between the linkage connector **131** and the at least two storage assemblies **121**, and the linkage connector **131** can implement the synchronous movement of the at least two storage assemblies **121**, thereby performing a synchronous unloading operation. In this embodiment, the connection of connectors is implemented by connecting rods, and there may be one or more connecting rods. In addition, there are various arrangements of the linkage connector **131**, which cannot all be listed herein, and a linkage manner in the present disclosure is not limited to being implemented by the foregoing specific structures.

(49) Referring to FIG. 1 and FIG. 3, in an embodiment, in a same horizontal direction, a distance between the linkage connector **131** and the vertical frame **110** is less than or equal to a length of each of the plurality of storage assemblies **121**. It can be understood that a length at a connection position between the linkage connector **131** and the plurality of storage assemblies **121** may be equal to the length of each of the plurality of storage assemblies **121**. In this case, the linkage connector **131** and the vertical frame **110** are respectively located at two ends of the plurality of storage assemblies **121**. The length at the connection position between the linkage connector **131**

and the plurality of storage assemblies **121** may be less than the length of each of the plurality of storage assemblies **121**, and the connection position between the linkage connector **131** and the plurality of storage assemblies **121** is located on side surfaces of the plurality of storage assemblies **121**. That is, the linkage connector **131** may be located at any position on a peripheral side of each of the plurality of storage assemblies **121**. In this way, the linkage connector **131** can drive the plurality of storage assemblies **121** to synchronously ascend or descend when the linkage connector **131** ascends or descends, so as to perform the synchronous unloading operation of the transport robot **100**.

(50) In an embodiment, there may be at least one linkage connector **131**. In a case that there is one linkage connector **131**, the cooperation between the linkage connector with the vertical frame **110** can ensure that the plurality of storage assemblies **121** are fixed and reliable, and simultaneously implement the driving of the movement of the plurality of storage assemblies **121**. In a case that there are a plurality of linkage connectors **131**, the plurality of linkage connectors **131** can further improve the linkage of the plurality of storage assemblies **121** and ensure that the plurality of storage assemblies **121** move in a consistent manner.

(51) In a case that there is one linkage connector **131**, the linkage connector **131** and the vertical frame **110** are respectively arranged at two ends of the plurality of storage assemblies **121**. That is, the connection position between the linkage connector **131** and the plurality of storage assemblies **121** and the vertical frame **110** are respectively located at the two ends of the plurality of storage assemblies **121**, and a distance between the connection position and the vertical frame **110** is equal to a size of each of the plurality of storage assemblies **121** along a horizontal direction. In this way, the plurality of storage assemblies **121** can be reliably supported by the linkage connector **131** and the vertical frame **110**, to prevent the plurality of storage assemblies **121** from falling and dropping, so that the plurality of storage assemblies **121** can reliably store the goods **200**.

(52) In a case that there are a plurality of linkage connectors **131**, the plurality of linkage connectors **131** are arranged at intervals along the peripheral side of the storage assembly **121**. The plurality of linkage connectors **131** are distributed at intervals along the peripheral side of each of the plurality of storage assemblies **121**, and may be distributed uniformly, non-uniformly, or symmetrically. The plurality of storage assemblies **121** can be reliably supported by the plurality of linkage connectors **131** and the vertical frame **110**, to prevent the plurality of storage assemblies **121** from falling and dropping, so that the plurality of storage assemblies **121** can reliably store the goods **200**.

(53) Referring to FIG. 1, FIG. 3, and FIG. 4, in an embodiment, the linkage mechanism **130** further includes a linkage driving member **132** configured to cooperate with the linkage connector **131**, so as to drive the plurality of storage assemblies **121** to implement synchronous unloading. The linkage driving member **132** is a power source for the movement of the linkage mechanism **130**, and implements the driving of the movement of a linkage moving member. In addition, the linkage driving member **132** outputs linear motion, so that the linkage connector **131** can ascend or descend, and the plurality of storage assemblies **121** can undergo a pitching motion. Optionally, the linkage driving member **132** includes, but is not limited to, an air cylinder, a hydraulic cylinder, a linear motor, or an electric push rod, and may also be another linear driving unit capable of outputting the linear motion. Exemplarily, the linkage driving member **132** is a linear motor. Exemplarily, one end of the linkage driving member **132** is arranged on the chassis **160**. Certainly, one end of the linkage driving member **132** may also be arranged on the vertical frame **110**.

(54) Optionally, the linkage driving member **132** may be connected to the plurality of storage assemblies **121**. In an embodiment, an output end of the linkage driving member **132** is connected to one of the plurality of storage assemblies **121**. One end of the linkage driving member **132** is mounted on the vertical frame **110**, and an other end is connected to the plurality of storage assemblies **121**. After outputting the linear motion, the linkage driving member **132** may drive the plurality of storage assemblies **121** connected thereto to move, and then the plurality of storage

assemblies **121** may drive the linkage connector **131** to ascend or descend. At this time, the linkage connector **131** may drive the remaining storage assemblies **121** to move synchronously, so that the plurality of storage assemblies **121** rotate relative to the vertical frame **110**, the plurality of storage assemblies **121** are lifted up, and the synchronous unloading operation of the plurality of storage assemblies **121** is performed.

(55) Further, the output end of the linkage driving member **132** is connected to a bottom portion or a top portion of one of the plurality of storage assemblies **121**. In a case that the linkage driving member **132** is connected to the top portion of the plurality of storage assemblies **121**, the linkage driving member **132** may retract to drive the plurality of storage assemblies **121** to move upward, and the linkage driving member **132** may extend to drive the plurality of storage assemblies **121** to move downward. In a case that the linkage driving member **132** is connected to the bottom portion of the plurality of storage assemblies **121**, the linkage driving member **132** may extend to drive the plurality of storage assemblies **121** to move upward, and the linkage driving member **132** may retract to drive the plurality of storage assemblies **121** to move downward. Exemplarily, the linkage driving member **132** is connected to the bottom portion of the plurality of storage assemblies **121**. Still further, the linkage driving member **132** is located and connected to a bottom portion of a lowermost storage assembly **121**, and the output end of the linkage driving member **132** is in abutment with a middle region of the bottom portion of the storage assembly **121**. In this way, the linkage driving member **132** does not affect the loading or unloading of goods **200** of a carrying component, so as to avoid interference.

(56) Further optionally, the output end of the linkage driving member **132** is connected to the linkage connector **131**. The linkage driving member **132** may directly drive the linkage connector **131** to ascend or descend, and then the linkage connector **131** may drive the plurality of storage assemblies **121** to move synchronously. Further, the linkage driving member **132** may be located at the bottom portion of the lowermost storage assembly **121** and arranged on the chassis **160**, and the output end of the linkage driving member **132** is connected to the linkage connector **131**. Certainly, the linkage driving member **132** may also be located at the top portion of the plurality of storage assemblies **121**.

(57) The linkage mechanism **130** in this embodiment can implement the simultaneous unloading of a plurality of storage assemblies **121**, the plurality of storage assemblies **121** are connected by a same linkage connector **131**, and an output end of a linkage driving member **132** is connected to a lowermost storage assembly **121**. When the linkage driving member **132** extends, the linkage driving member **132** may push the plurality of storage assemblies **121** upward, so that the plurality of storage assemblies **121** rotate relative to the vertical frame **110**. When rotating, the plurality of storage assemblies **121** may drive the linkage connector **131** to move synchronously, and then the linkage connector **131** drives the remaining storage assemblies **121** to move synchronously, so as to implement the synchronous driving of all storage assemblies **121** to move upward, thereby performing the synchronous unloading operation.

(58) It is worth noting that there are various rotational driving forms in which the plurality of storage assemblies **121** rotate relative to the vertical frame **110** to undergo a pitching motion. In this embodiment, only the linkage driving member **132** capable of outputting the linear motion is configured to drive the movement of the plurality of storage assemblies **121**, and other driving components that can implement the pitching motion of the plurality of storage assemblies **121** should be considered as falling within the protection scope of the present disclosure.

(59) Referring to FIG. 1, FIG. 3, and FIG. 5, in an embodiment, each of the plurality of storage assemblies **121** includes a carrier body **1211** configured to carry the goods **200** and rotatably connected to the linkage connector **131** and the vertical frame **110** separately. The carrier body **1211** is a main body configured to carry the goods **200**, one end of the carrier body **1211** is rotatably connected to the vertical frame **110**, and an other end is rotatably connected to the linkage connector **131**. The end of the carrier body **1211** connected to the vertical frame **110** is a head end,

and the end of the carrier body **1211** connected to the linkage connector **131** is a tail end. When the linkage connector **131** drives the carrier body **1211** to ascend or descend, the tail end of the carrier body **1211** rotates around the head end of the carrier body **1211**, so that the carrier body **1211** undergoes a pitching motion. Optionally, an edge of the carrier body **1211** is rotatably connected to the linkage connector **131** and the vertical frame **110** separately, and certainly, a middle region of the carrier body **1211** may also be rotatably connected to the linkage connector **131** and the vertical frame **110** separately.

(60) It can be understood that the rotatable connection between the carrier body **1211** and the vertical frame **110** may be that the carrier body **1211** has a rotary shaft, and the carrier body **1211** is also rotatably mounted on the vertical frame **110** through the rotary shaft, or the vertical frame **110** has a rotary shaft, and the carrier body **1211** may be rotatably mounted on the rotary shaft, or the like. In addition, the foregoing manner of the rotatable connection which is implemented through the rotary shaft may also be replaced by a hinged connection or other forms of rotatable connection.

(61) Optionally, the carrier body **1211** is arranged in a flat plate shape, and a container of the goods **200** may be transferred to the carrier body **1211**. Further, the edge of the carrier body **1211** has three sides of flanges, and the three sides of flanges form a loading or unloading port at the vertical frame **110**, and the goods **200** are mounted in the carrier body **1211** through the loading or unloading port. In addition, the flanges can limit the displacement of the goods **200** on the carrier body **1211**, prevent the goods **200** from falling out of the carrier body **1211**, and ensure that the carrier body **1211** can store the goods **200** accurately.

(62) In an embodiment, each of the plurality of storage assemblies **121** further includes a rolling member **1212** arranged on the carrier body **1211** in a rolling manner and configured to be in a rolling contact with the goods **200** in the carrier body **1211**. The rolling member **1212** can reduce a frictional force between the goods **200** and the carrier body **1211**, so as to facilitate the loading or unloading of the goods **200**. When the goods **200** are loaded, a bottom portion of the goods **200** is in contact with the rolling member **1212** under the action of gravity thereof. During the movement of the goods **200** into the carrier body **1211**, the goods **200** may drive rollers to rotate, so that the frictional force between the goods **200** and the carrier body **1211** is reduced, and the loading of the goods **200** is facilitated. When the goods **200** are unloaded, the linkage connector **131** drives the carrier body **1211** to move upward. At this time, the tail end of the carrier body **1211** is higher than a top end of the carrier body **1211**, and the goods **200** in the carrier body **1211** slide out of the carrier body **1211** under the action of gravity. In addition, during a sliding process of the goods **200** along the carrier body **1211**, the bottom portion of the goods **200** drives the rolling member **1212** to roll, so that the goods **200** slide out of the carrier body **1211** more easily, and the unloading of the goods **200** is facilitated.

(63) Optionally, the carrier body **1211** is provided with a rolling groove, the rolling member **1212** may be rotatably mounted in the rolling groove, and a top surface of the rolling member **1212** is slightly higher than a top surface of the carrier body **1211**, so as to ensure that the rolling member **1212** can be in contact with the bottom portion of the goods **200**. In addition, the bottom portion of the carrier body **1211** also includes a protection cover covering the rolling member **1212** on the bottom portion of the carrier body **1211**, so as to avoid interference between a bottom portion of the rolling member **1212** and other components.

(64) Optionally, the rolling member **1212** includes, but is not limited to, rollers, rolling shafts, rolling balls, or other components capable of rolling. In addition, there are a plurality of rolling members **1212**, and the plurality of rolling members **1212** may be arranged in one row, or may be arranged in a plurality of rows. Exemplarily, the rolling member **1212** is rollers arranged in three rows.

(65) Referring to FIG. 1 and FIG. 3, in an embodiment, the transport robot **100** further includes a lifting mechanism **140** capable of ascending or descending relative to the vertical frame **110** along

the vertical direction and a carrying mechanism **150** configured to carry the goods **200**, where the carrying mechanism **150** is movably arranged on the vertical frame **110** along the vertical direction, is connected to the lifting mechanism **140**, and is capable of ascending or descending along the vertical direction under driving of the lifting mechanism **140**, so as to deliver goods **200** in the carrying mechanism **150** to a corresponding storage mechanism **120**.

(66) The carrying mechanism **150** is a terminal configured to perform an action of the transport robot **100**. At the loading position, the carrying mechanism **150** may carry the to-be-transported goods **200**, and transport the goods **200** into the carrier body **1211**. Certainly, in some occasions, in a case that the goods **200** in the plurality of storage assemblies **121** need to be unloaded separately, the carrying mechanism **150** may also take out the goods **200** in the carrier body **1211**. Optionally, the carrying mechanism **150** includes, but is not limited to, a mechanical arm, an actionable tow bar, or a plane with a conveying function, and the like. The lifting mechanism **140** is configured to implement the ascending or descending movement of the carrying mechanism **150**, and is capable of driving the carrying mechanism **150** to ascend or descend along the vertical direction.

(67) At the loading position, there is a shelving unit with a plurality of layers configured to carry the goods **200**. When the transport robot **100** loads goods at the loading position, the lifting mechanism **140** drives the carrying mechanism **150** to ascend or descend, so that the carrying mechanism **150** can pick goods on the shelving unit. Then, a lifting assembly drives the carrying mechanism **150** to ascend or descend, so as to transfer the goods **200** in the carrying mechanism **150** to the plurality of storage assemblies **121**. This process is repeated until the plurality of storage assemblies **121** store the goods **200**. After the loading is completed, the transport robot **100** moves from the loading position to the unloading position, and the linkage mechanism **130** enables the plurality of storage assemblies **121** to perform a synchronous unloading operation, so as to complete one-time unloading. After the unloading is completed, the transport robot **100** returns to the loading position, so that continuous transport of the goods **200** can be implemented by repeating the process, thereby improving the transport efficiency.

(68) The function of the lifting mechanism **140** is to drive the carrying mechanism **150** to ascend or descend along the vertical direction. In an embodiment, the lifting mechanism **140** includes a lifting power source and a lifting transmission component, and the lifting power source and the lifting transmission component are separately arranged on the vertical frame **110**. The lifting transmission component is in driving connection with the lifting power source and the carrying mechanism **150**. Specifically, an output end of the lifting power source is in driving connection with an input end of the lifting transmission component, and an output end of the lifting transmission component is in driving connection with the carrying mechanism **150**. That the lifting power source and the lifting transmission component are separately arranged on the vertical frame **110**, and the driving connection between the lifting power source and the lifting transmission component facilitate the disassembly or assembly of the lifting mechanism **140** on the vertical frame **110**. Optionally, a power output from the lifting power source is in a form of rotation and linear motion, or in any other form of motion, and a final output of the lifting transmission component in driving connection with the lifting power source is movement along the vertical direction. Optionally, the lifting power source includes a driving motor in driving connection with the input end of the lifting transmission component. The lifting power source in a form of a motor runs more stably. Further, the driving motor can rotate forwardly or reversely, which facilitates the control of an ascending or descending process of the lifting mechanism **140**.

(69) Optionally, the lifting transmission component may be of a telescopic rod structure, a chain transmission structure, a driving transmission structure, or the like, and may also be of another structure capable of enabling the carrying mechanism **150** to ascend or descend. Exemplarily, the lifting transmission component is of a chain transmission structure, including a sprocket and a chain, the chain is connected to the carrying mechanism **150**, and the chain is arranged on the vertical frame **110** along the vertical direction. When the output end of the lifting power source

drives the sprocket to rotate, the chain ascends or descends along the vertical frame **110**, which may further drive the carrying mechanism **150** to ascend or descend.

(70) It should be noted that, the essence of the lifting transmission component is to output the ascending or descending motion to drive the carrying mechanism **150** to ascend or descend, thereby implementing the loading of the goods **200**. In this embodiment, the lifting transmission component is implemented by a chain transmission structure. In addition, there are various structures that can implement ascending or descending, which cannot all be listed herein, and the manner of the ascending or descending motion in the present disclosure is not limited to being implemented by the foregoing specific structures.

(71) In an embodiment, the transport robot **100** further includes a rotary mechanism arranged between the carrying mechanism **150** and the lifting mechanism **140** and configured to drive the carrying mechanism **150** to rotate relative to the lifting mechanism **140**, so that the carrying mechanism **150** is aligned with a corresponding storage mechanism **120**. The rotary mechanism is rotatably connected to the carrying mechanism **150**, and the carrying mechanism **150** is rotatable relative to the rotary mechanism. When the carrying mechanism **150** is rotated by the rotary mechanism, a direction of the carrying mechanism **150** may be adjusted, so that the loading or unloading port of the carrying mechanism **150** can be adjusted. The carrying mechanism **150** implements the loading or unloading of the goods **200** through the loading or unloading port. When the transport robot **100** is at the loading position, the rotary mechanism may drive the carrying mechanism **150** to rotate, so that the loading or unloading port of the carrying mechanism **150** faces a shelving unit, and the goods **200** can be loaded into the carrying mechanism **150**. When the carrying mechanism **150** transfers the goods **200** to the plurality of storage assemblies **121**, the rotary mechanism may drive the carrying mechanism **150** to rotate, so that the loading or unloading port of the carrying mechanism **150** faces the plurality of storage assemblies **121**. At this time, the goods **200** in the carrying mechanism **150** can be transferred to the plurality of storage assemblies **121**.

(72) Optionally, the rotary mechanism includes a carrying bracket, an autorotation gear arranged on the carrying bracket, and an autorotation motor fixedly mounted on the carrying bracket. An output end of the autorotation motor is connected to the autorotation gear, the carrying mechanism **150** is mounted on the autorotation gear, and the carrying bracket is mounted on the lifting mechanism **140**. The autorotation motor may drive the autorotation gear to rotate, which may further drive the carrying mechanism **150** to rotate.

(73) It should be noted that, the essence of the rotary mechanism is to output a rotation motion, so as to drive the carrying mechanism **150** to rotate, thereby implementing the loading or unloading of the goods **200**. In this embodiment, the rotary mechanism is implemented by an autorotation motor and an autorotation gear. In addition, there are various structures that can implement rotation, which cannot all be listed herein, and the manner of the rotation motion in the present disclosure is not limited to being implemented by the foregoing specific structures.

(74) Referring to FIG. 1 and FIG. 3, in an embodiment, the carrying mechanism **150** includes a transition member **151** and a pick-or-place member **152** that is telescopically arranged on the transition member **151**, and the pick-or-place member **152** is capable of taking out goods **200** and storing the goods in the transition member **151**, and is further capable of pushing out goods **200** in the transition member **151**. The pick-or-place member **152** is telescopically arranged in the transition member **151**. At the loading position, the pick-or-place member **152** extends out of the transition member **151** to take out goods **200** on a shelving unit, and then the pick-or-place member **152** retracts into the transition member **151** to temporarily store the goods **200** in the transition member **151**. Subsequently, the lifting mechanism **140** and the rotary mechanism drive the carrying mechanism **150** to move, so that the carrying mechanism **150** moves to a plurality of storage assemblies **121** in which the goods are to be placed. At this time, the pick-or-place member **152** extends out of the transition member **151**, moves the goods **200** out of the transition member **151**,

and transfers the goods to the plurality of storage assemblies **121**. After the transfer, the pick-or-place member **152** retracts into the transition member **151**. Optionally, the transition member **151** includes, but is not limited to, a transition box, and the pick-or-place member **152** includes, but is not limited to, a structure in which a telescopic motor cooperates with a telescopic rod, a mechanical arm mechanism, and the like.

(75) In an embodiment, the transport robot **100** further includes a controller electrically connected to the chassis **160**, the carrying mechanism **150**, the lifting mechanism **140**, and the rotary mechanism separately, so as to control the synchronous movement of components or control the movement of at least one component, to achieve a function of automatic goods carrying.

(76) Referring to FIG. 1, FIG. 3, FIG. 6, and FIG. 7, the present disclosure further provides a transport system including an auxiliary apparatus **300** and the transport robot **100** in the foregoing embodiments. The auxiliary apparatus **300** includes a support frame **310** and a plurality of transport mechanisms **320** arranged on the support frame **310** at intervals along a vertical direction, and a manner in which the plurality of transport mechanisms **320** are arranged at intervals is the same as a manner in which a plurality of storage assemblies **121** are arranged at intervals. When the transport robot **100** moves to the auxiliary apparatus **300**, goods **200** on the plurality of storage assemblies **121** are capable of being simultaneously transferred to corresponding transport mechanisms **320** to implement synchronous unloading; or goods **200** on the plurality of transport mechanisms **320** are capable of being simultaneously transferred to corresponding storage assemblies **121** to implement synchronous loading.

(77) The auxiliary apparatus **300** can implement the synchronous unloading or synchronous loading of the goods **200**. The auxiliary apparatus **300** is arranged at an unloading position or a loading position. In a case that the auxiliary apparatus **300** is unloaded, the auxiliary apparatus **300** is at the unloading position; and in a case that the auxiliary apparatus **300** is loaded, the auxiliary apparatus **300** is at the loading position. In the present disclosure, only an example in which the auxiliary apparatus **300** is at the unloading position is used for description. The auxiliary apparatus **300** is located at the unloading position. After the transport robot **100** completes loading at the loading position, the transport robot **100** moves to the unloading position. At this time, the transport robot **100** is docked with the auxiliary apparatus **300**, and the auxiliary apparatus **300** may receive and pick the goods **200** in the plurality of storage assemblies **121** in the transport robot **100**.

(78) Specifically, the mounting frame **321** functions as a support, which is configured to support a plurality of transport mechanisms **320** configured to transport the goods **200**. The auxiliary apparatus **300** includes a same quantity of transport mechanisms **320** as the plurality of storage assemblies **121**, and heights at which the plurality of transport mechanisms **320** are located are consistent with heights at which corresponding storage assemblies **121** are located. After the transport robot **100** is docked with the auxiliary apparatus **300**, the plurality of storage assemblies **121** and the plurality of transport mechanisms **320** are at same levels and heights. When unloading, the linkage driving member **132** of the linkage mechanism **130** extends to drive one end of a lowermost storage assembly **121** to be lifted up. During a lifting process of the storage assembly **121**, the linkage connector **131** may be driven to ascend, and the linkage connector **131** may drive the remaining storage assemblies **121** to be lifted up during the lifting process. In this way, the plurality of storage assemblies **121** can be simultaneously lifted up, the goods **200** in the plurality of storage assemblies **121** slide out of the plurality of storage assemblies **121** under the action of gravity and the action of the rolling member **1212**, and move to corresponding transport mechanisms **320**, and the transport mechanisms **320** transport the goods **200** thereon away to implement the unloading of the goods **200**.

(79) The auxiliary apparatus **300** may also implement the loading of the goods **200**. Specifically, transport mechanisms **320** of different layers drive the goods **200** to move toward corresponding storage assemblies **121**, and transfer the goods **200** to the corresponding storage assemblies **121**. It can be understood that when loading the goods **200**, the linkage mechanism **130** may drive ends of

the plurality of storage assemblies **121** to descend, and at the same time, the plurality of transport mechanisms **320** simultaneously transfer the goods **200** to the corresponding storage assemblies **121**. After the goods **200** are gradually transferred into the carrier body **1211** and come into contact with the rolling member **1212**, the goods **200** may slide into the plurality of storage assemblies **121** under the action of gravity thereof and through the cooperation with the rolling member **1212**. Certainly, the plurality of storage assemblies **121** may also be stationary, and the goods **200** may also be moved into the plurality of storage assemblies **121** by a pushing force of the plurality of transport mechanisms **320** in cooperation with the rolling member **1212**.

(80) Referring to FIG. 6 and FIG. 7, in an embodiment, each of the plurality of transport mechanisms **320** includes a mounting frame **321** arranged on the support frame **310** and a transport portion **322** movably arranged on the mounting frame **321**, and the transport portion **322** may drive the goods **200** to move. The mounting frame **321** is of a frame structure, which carries the transport portion **322** and is configured to implement the mounting of the transport portion **322**. The transport portion **322** is a main component that implements the transport of the goods **200**. When the goods **200** are in the transport portion **322**, the transport portion **322** may drive the goods **200** to move toward or away from the plurality of storage assemblies **121**.

(81) Optionally, the transport portion **322** is of a structure that can implement horizontal transport, such as a conveyor belt structure, an assembly line, a conveyor roller structure, a roller structure, or the like. Exemplarily, the transport portion **322** is of a roller structure, and specifically includes a plurality of rollers, and each of the plurality of rollers includes a built-in rolling motor to drive the each of the plurality of rollers to rotate, thereby implementing the transport of the goods **200**. It should be noted that, there are various structures that can implement the horizontal transport of the goods **200**, which cannot all be listed herein, and the transport portion **322** in the present disclosure is not limited to being implemented by the foregoing specific structures.

(82) In an embodiment, the auxiliary apparatus **300** further includes a movable base arranged at a bottom portion of the support frame **310**. The movable base can drive the auxiliary apparatus **300** to move, which greatly improves the adaptation of the auxiliary apparatus **300** to actual working conditions. In this way, the auxiliary apparatus **300** can easily move to the loading position, the unloading position, or any other position, to work with the transport robot **100**. Optionally, a structure of the base is exactly the same as that of the chassis **160** of the transport robot **100**, and details are not described herein again.

(83) Referring to FIG. 1, FIG. 6, and FIG. 8, in an embodiment, the transport system further includes a conveying apparatus **500** and a lifting apparatus **400** that is arranged between the auxiliary apparatus **300** and the conveying apparatus **500**, and the lifting apparatus **400** is configured to ascend or descend along the vertical direction, so as to be docked with each of the plurality of transport mechanisms **320** and the conveying apparatus **500**. The lifting apparatus **400** is capable of receiving and picking goods **200** of the plurality of transport mechanisms **320** and transferring the goods to the conveying apparatus **500**; or the lifting apparatus **400** is capable of receiving and picking goods **200** of the conveying apparatus **500** and transferring the goods to the plurality of transport mechanisms **320**.

(84) The lifting apparatus **400** is configured to receive and pick the goods **200** of the plurality of transport mechanisms **320** or transport the goods **200** to the plurality of transport mechanisms **320**. Because the plurality of transport mechanisms **320** are arranged at intervals along the vertical direction, to facilitate the goods loading or unloading of the auxiliary apparatus **300**, the lifting apparatus **400** needs to move to a transport mechanism **320** at a corresponding position, so as to perform a corresponding operation. The conveying apparatus **500** is configured to convey the goods **200**, may transport away goods **200** unloaded by the lifting apparatus **400**, and may also transport to-be-loaded goods **200** to the lifting apparatus **400**. Optionally, the conveying apparatus **500** may be of a structure that can implement the horizontal transport, such as a conveyor belt structure, an assembly line, a conveying roller structure, or a roller structure, or the like.

Exemplarily, the conveying apparatus **500** is of an assembly line structure, and (85) Specifically, when unloading, the lifting apparatus **400** ascends to one side of a transport mechanism **320**, after receiving the goods **200** of the transport mechanism **320**, the lifting apparatus **400** descends, and transfers the goods **200** to the conveying apparatus **500**, and the goods are transported away by the conveying apparatus **500**. Subsequently, the lifting apparatus **400** further ascends to another transport mechanism **320**, and this process is repeated until all the goods **200** on the plurality of transport mechanisms **320** are transported away. When loading, after the lifting apparatus **400** descends and receives and picks the goods **200** conveyed by the conveying apparatus **500**, the lifting apparatus **400** ascends to one side of a transport mechanism **320** and transfers the goods **200** to the transport mechanism **320**; and subsequently, the lifting apparatus **400** further descends to the conveying apparatus **500**, and this process is repeated until the plurality of transport mechanisms **320** are loaded with the goods **200**.

(86) In an embodiment, the lifting apparatus **400** includes a lifting frame **410** along the vertical direction, a moving mechanism **420** arranged on the lifting frame **410**, and a transfer mechanism **430** with at least one layer arranged on the moving mechanism **420**. The moving mechanism **420** may ascend or descend along the lifting frame **410** and drive the transfer mechanism **430** with at least one layer to move, so as to receive and pick goods from or transfer goods **200** to the plurality of transport mechanisms **320**. The lifting frame **410** has a bearing function, and is configured to bear the moving mechanism **420** and the transfer mechanism **430** with at least one layer. Optionally, a bottom portion of the lifting frame **410** may also be provided with rotating wheels, so as to adapt to different applications. The transfer mechanism **430** with at least one layer is configured to carry the goods **200** and implement the transfer of the goods **200** between a high position such as a transport mechanism **320** and a low position such as the conveying apparatus **500**. The moving mechanism **420** is arranged on the lifting frame **410** along the vertical direction, and may output movement in the vertical direction, so as to drive the transfer mechanism **430** with at least one layer to ascend or descend.

(87) It can be understood that the moving mechanism **420** is configured to implement the ascending or descending motion of the transfer mechanism **430** with at least one layer along the vertical direction. A specific structure of the moving mechanism **420** may be a telescopic rod structure, a chain transmission structure, a driving transmission structure, or the like, and may also be another structure capable of enabling the carrying mechanism **150** to ascend or descend. Exemplarily, a specific structure of the moving mechanism **420** is the same as a structure of the lifting mechanism **140** of the transport robot **100**, and details are not described herein again. Certainly, the specific structure of the moving mechanism **420** may also be different from the structure of the lifting mechanism **140** of the transport robot **100**, as long as the moving mechanism **420** can implement the ascending or descending motion.

(88) Exemplarily, there is a transfer mechanism **430** with one layer, and the transfer mechanism **430** with one layer receives and picks goods from one transport mechanism **320** at one time, or transfers goods to one transport mechanism **320** at one time. Certainly, in another implementation of the transport robot and the transport system having the same, in a case that there is a transfer mechanism **430** with at least two layers, the transfer mechanism **430** with at least two layers may remove goods on at least two transport mechanisms **320** at one time, or transfer goods to at least two transport mechanisms **320**, so as to improve the efficiency of goods turnover.

(89) In an embodiment, the transfer mechanism **430** with at least one layer includes a transfer base **431** arranged on the moving mechanism **420** and a transfer portion **432** movably arranged on the transfer base **431**, and the transfer portion **432** may drive goods **200** to move, and may receive and pick goods from or transfer goods **200** to at least one of the plurality of transport mechanisms **320**. The transfer base **431** plays a bearing role and is configured to carry the transfer portion **432**, so as to mount the transfer portion **432** on the moving mechanism **420**. When the moving mechanism **420** ascends or descends, the transfer base **431** may drive the transfer portion **432** to ascend or

descend synchronously, so as to implement the loading or unloading of the goods **200**.

(90) Optionally, the transfer portion **432** is of a structure that can implement horizontal transport, such as a conveyor belt structure, an assembly line, a conveyor roller structure, a roller structure, or the like. Exemplarily, the transfer portion **432** is of a rolling shaft structure, and specifically includes a plurality of rolling shafts, and each of the plurality of rolling shafts includes a built-in rolling motor to drive the each of the plurality of rolling shafts to rotate, thereby implementing the transport of the goods **200**. It should be noted that, there are various structures that can implement the horizontal transport of the goods **200**, which cannot all be listed herein, and the transfer portion **432** in the present disclosure is not limited to being implemented by the foregoing specific structures.

(91) The transfer portion **432** may receive and pick the goods **200** of one transport mechanism **320** at one time, as mentioned above. The transfer portion **432** may also receive and pick the goods **200** of a plurality of transport mechanisms **320** at one time, and the moving mechanism **420** may receive and pick the goods **200** of the plurality of transport mechanisms **320** layer by layer, and then convey the goods to the conveying apparatus **500** together for transport after receiving and picking the goods. Exemplarily, the moving mechanism **420** drives the transfer portion **432** to ascend to a top portion. After receiving and picking goods **200** of one transport mechanism **320**, the transfer portion **432** descends one layer to receive and pick goods **200** of one transport mechanism **320**. After the transfer portion **432** is full or the goods **200** of the plurality of transport mechanisms **320** are received, the moving mechanism **420** drives the transfer portion **432** to descend to a position of the conveying apparatus **500**, and the transfer portion **432** transfers all the goods **200** thereon to the conveying apparatus **500**. Certainly, the moving mechanism **420** may move layer by layer from bottom to top, a principle thereof is substantially the same as a principle from top to bottom, and details are not described herein again.

(92) Certainly, the transfer portion **432** may also receive and pick a plurality of goods **200** transferred by the conveying apparatus **500** at one time, and then transfer the goods to the plurality of transport mechanisms **320** layer by layer, a principle thereof is substantially the same as a foregoing principle of goods unloading, and details are not described herein again.

(93) In the transport robot **100** and the transport system in the present disclosure, when unloading, a plurality of storage assemblies **121** of a storage mechanism **120** may move synchronously to perform a synchronous unloading action, so that the synchronous unloading of goods **200** in the plurality of storage assemblies **121** is implemented, goods **200** in the transport robot **100** can be unloaded at one time, the unloading efficiency is improved, the unloading time is reduced, and the overall working efficiency of the transport robot **100** is improved. In addition, after the transport robot **100** is used in cooperation with the auxiliary apparatus **300**, the loading or unloading can be simultaneously implemented, thereby improving the working efficiency of the transport system.

Embodiment 2

(94) Referring to FIG. 1, FIG. 3, FIG. 6, FIG. 9, and FIG. 11, the present disclosure provides a transport robot **100**. The transport robot **100** is applied to a transport system, and can transport goods **200**. It can be understood that the goods **200** may be goods with a bracket, and the transport robot **100** transports the goods **200** through the bracket; and certainly, the goods may alternatively be goods placed in a container, and the transport robot **100** transports the goods **200** through a container. The goods **200** described below are goods placed in the container, and the container may be loaded with the goods **200**, so as to implement the transport of the goods **200**. The transport robot **100** transports the container to an unloading position, and after unloading the goods **200** in the container, the container may be transported back to the transport robot **100**, so as to reuse the container and reduce the cost. Alternatively, the goods **200** is a box with goods, and the transport robot **100** transports the container to the unloading position, and unloads the container with goods through an unloading apparatus.

(95) The transport robot **100** plays an important role in intelligent warehousing, transports goods

200, ensures a transport speed of the goods **200**, improves the transport efficiency of the goods **200**, and reduces the consumption of labor resources. The transport robot **100** of the present disclosure can unload synchronously, so that goods **200** in the transport robot **100** can be unloaded at one time, thereby improving the unloading efficiency, reducing the unloading time, and improving the overall working efficiency of the transport robot **100**.

(96) Referring to FIG. 1 and FIG. 3, in an embodiment, the transport robot **100** includes a vertical frame **110** and a storage mechanism **120**. The vertical frame **110** is arranged along a vertical direction. The storage mechanism **120** includes a plurality of storage assemblies **121** configured to store to-be-transported goods **200** and arranged on the vertical frame **110** at equal intervals along the vertical direction.

(97) The vertical frame **110** plays a bearing role, and various components of the transport robot **100** are mounted thereon. When the transport robot **100** transports the goods **200**, the vertical frame **110** may drive synchronous movement of the components on the transport robot **100**, so as to implement the transport of the goods **200**. The storage mechanism **120** is located on the vertical frame **110**, is configured to store the goods **200**, and is capable of moving synchronously with the vertical frame **110**, so as to implement the transport of the goods **200**. The transport robot **100** moves to a loading position, and the to-be-transported goods **200** are transported to the storage mechanism **120** for storage. Then, the transport robot **100** moves from the loading position to an unloading position. Correspondingly, the storage mechanism **120** moves to the unloading position along with the vertical frame **110**. At this time, the goods **200** in the storage mechanism **120** can be unloaded. The storage mechanism **120** can temporarily store the to-be-transported goods **200**, thereby improving the capability of the transport robot **100** to carry the goods **200**.

(98) In addition, the storage mechanism **120** includes a plurality of storage assemblies **121** arranged on the vertical frame **110** at intervals. Each of the plurality of storage assemblies **121** can carry goods **200** of a box to ensure a storage capacity of the transport robot **100**. Optionally, a distance between two adjacent storage assemblies **121** may be equal or not equal. Exemplarily, the plurality of storage assemblies **121** are evenly distributed on the vertical frame **110** along the vertical direction. The to-be-transported goods **200** may be transported to the plurality of storage assemblies **121**, and the transport robot **100** drives the goods **200** in the plurality of storage assemblies **121** to be transported to the unloading position.

(99) Referring to FIG. 1 and FIG. 3, in an embodiment, the transport robot **100** further includes a lifting mechanism **140** capable of ascending or descending relative to the vertical frame **110** along the vertical direction and a carrying mechanism **150** configured to carry the goods **200**, where the carrying mechanism **150** is movably arranged on the vertical frame **110** along the vertical direction, is connected to the lifting mechanism **140**, and is capable of ascending or descending along the vertical direction under driving of the lifting mechanism **140**, so as to deliver goods **200** in the carrying mechanism **150** to a corresponding storage mechanism **120**.

(100) The carrying mechanism **150** is a terminal configured to perform an action of the transport robot **100**. At the loading position, the carrying mechanism **150** may carry the to-be-transported goods **200**, and transport the goods **200** into the plurality of storage assemblies **121**. Certainly, in some occasions, in a case that the goods **200** in the plurality of storage assemblies **121** need to be unloaded separately, the carrying mechanism **150** may also take out the goods **200** in the plurality of storage assemblies **121**. Optionally, the carrying mechanism **150** includes, but is not limited to, a mechanical arm, an actionable tow bar, or a plane with a conveying function, and the like. The lifting mechanism **140** is configured to implement the ascending or descending movement of the carrying mechanism **150**, and is capable of driving the carrying mechanism **150** to ascend or descend along the vertical direction.

(101) At the loading position, there is a shelving unit with a plurality of layers configured to carry goods **200**. When loading goods at the loading position of the transport robot **100**, the lifting mechanism **140** drives the carrying mechanism **150** to ascend or descend, so that the carrying

mechanism **150** can pick goods on the shelving unit. Then, the lifting mechanism **140** drives the carrying mechanism **150** to ascend or descend, so as to transfer the goods **200** in the carrying mechanism **150** to the plurality of storage assemblies **121**. This process is repeated until the plurality of storage assemblies **121** store the goods **200**. After the loading is completed, the transport robot **100** moves from the loading position to the unloading position, and the plurality of storage assemblies **121** may perform a synchronous unloading operation. After the unloading is completed, the transport robot **100** returns to the loading position, so that continuous transport of the goods **200** can be implemented by repeating the process, thereby improving the transport efficiency.

(102) The function of the lifting mechanism **140** is to drive the carrying mechanism **150** to ascend or descend along the vertical direction. In an embodiment, the lifting mechanism **140** includes a lifting power source and a lifting transmission component, and the lifting power source and the lifting transmission component are separately arranged on the vertical frame **110**. The lifting transmission component is in driving connection with the lifting power source and the carrying mechanism **150**. Specifically, an output end of the lifting power source is in driving connection with an input end of the lifting transmission component, and an output end of the lifting transmission component is in driving connection with the carrying mechanism **150**. That the lifting power source and the lifting transmission component are separately arranged on the vertical frame **110**, and the driving connection between the lifting power source and the lifting transmission component facilitate the disassembly or assembly of the lifting mechanism **140** on the vertical frame **110**. Optionally, a power output from the lifting power source is in a form of rotation and linear motion, or in any other form of motion, and a final output of the lifting transmission component in driving connection with the lifting power source is movement along the vertical direction. Optionally, the lifting power source includes a driving motor in driving connection with the input end of the lifting transmission component. The lifting power source in a form of a motor runs more stably. Further, the driving motor can rotate forwardly or reversely, which facilitates the control of an ascending or descending process of the lifting mechanism **140**.

(103) Optionally, the lifting transmission component may be of a telescopic rod structure, a chain transmission structure, a driving transmission structure, or the like, and may also be of another structure capable of enabling the carrying mechanism **150** to ascend or descend. Exemplarily, the lifting transmission component is of a chain transmission structure, including a sprocket and a chain, the chain is connected to the carrying mechanism **150**, and the chain is arranged on the vertical frame **110** along the vertical direction. When the output end of the lifting power source drives the sprocket to rotate, the chain ascends or descends along the vertical frame **110**, which may further drive the carrying mechanism **150** to ascend or descend.

(104) It should be noted that, the essence of the lifting transmission component is to output the ascending or descending motion to drive the carrying mechanism **150** to ascend or descend, thereby implementing the loading of the goods **200**. In this embodiment, the lifting transmission component is implemented by a chain transmission structure. In addition, there are various structures that can implement ascending or descending, which cannot all be listed herein, and the manner of the ascending or descending motion in the present disclosure is not limited to being implemented by the foregoing specific structures.

(105) In an embodiment, the transport robot **100** further includes a rotary mechanism arranged between the carrying mechanism **150** and the lifting mechanism **140** and configured to drive the carrying mechanism **150** to rotate relative to the lifting mechanism **140**, so that the carrying mechanism **150** is aligned with a corresponding storage mechanism **120**. The rotary mechanism is rotatably connected to the carrying mechanism **150**, and the carrying mechanism **150** is rotatable relative to the rotary mechanism. When the carrying mechanism **150** is rotated by the rotary mechanism, a direction of the carrying mechanism **150** may be adjusted, so that the loading or unloading port of the carrying mechanism **150** can be adjusted. The carrying mechanism **150**

implements the loading or unloading of the goods **200** through the loading or unloading port. When the transport robot **100** is at the loading position, the rotary mechanism may drive the carrying mechanism **150** to rotate, so that the loading or unloading port of the carrying mechanism **150** faces a shelving unit, and the goods **200** can be loaded into the carrying mechanism **150**. When the carrying mechanism **150** transfers the goods **200** to the plurality of storage assemblies **121**, the rotary mechanism may drive the carrying mechanism **150** to rotate, so that the loading or unloading port of the carrying mechanism **150** faces the plurality of storage assemblies **121**. At this time, the goods **200** in the carrying mechanism **150** can be transferred to the plurality of storage assemblies **121**.

(106) Optionally, the rotary mechanism includes a carrying bracket, an autorotation gear arranged on the carrying bracket, and an autorotation motor fixedly mounted on the carrying bracket. An output end of the autorotation motor is connected to the autorotation gear, the carrying mechanism **150** is mounted on the autorotation gear, and the carrying bracket is mounted on the lifting mechanism **140**. The autorotation motor may drive the autorotation gear to rotate, which may further drive the carrying mechanism **150** to rotate.

(107) It should be noted that, the essence of the rotary mechanism is to output a rotation motion, so as to drive the carrying mechanism **150** to rotate, thereby implementing the loading or unloading of the goods **200**. In this embodiment, the rotary mechanism is implemented by an autorotation motor and an autorotation gear. In addition, there are various structures that can implement rotation, which cannot all be listed herein, and the manner of the rotation motion in the present disclosure is not limited to being implemented by the foregoing specific structures.

(108) When the transport robot **100** in the foregoing embodiment loads goods, the lifting mechanism **140** drives the carrying mechanism **150** to transfer the goods **200** to a plurality of storage assemblies **121** at corresponding heights in the storage mechanism **120**. When unloading, the lifting mechanism **140** drives the carrying mechanism **150** to take out the goods **200** in a plurality of storage assemblies **121** at corresponding heights in the storage mechanism **120**. Through the cooperation between the lifting mechanism **140** and the carrying mechanism **150**, the automation of loading or unloading of the goods **200** is implemented, a problem of high cost and low efficiency in a current transport method is effectively resolved, the cost of the loading or unloading of the goods is reduced, and the efficiency of the loading or unloading of the goods **200** is greatly improved. In addition, the carrying mechanism **150** moves to different heights under the driving of the lifting mechanism **140**, so that the to-be-transported goods **200** can be delivered to a plurality of storage assemblies **121** at different heights in the storage mechanism **120**, which has strong versatility and reduces the floor space.

(109) Referring to FIG. 1 and FIG. 3, in an embodiment, the carrying mechanism **150** includes a transition member **151** and a pick-or-place member **152** that is telescopically arranged on the transition member **151**, and the pick-or-place member **152** is capable of taking out goods **200** and storing the goods in the transition member **151**, and is further capable of pushing out goods **200** in the transition member **151**. The pick-or-place member **152** is telescopically arranged in the transition member **151**. At the loading position, the pick-or-place member **152** extends out of the transition member **151** to take out goods **200** on a shelving unit, and then the pick-or-place member **152** retracts into the transition member **151** to temporarily store the goods **200** in the transition member **151**. Subsequently, the lifting mechanism **140** and the rotary mechanism drive the carrying mechanism **150** to move, so that the carrying mechanism **150** moves to a plurality of storage assemblies **121** in which the goods are to be placed. At this time, the pick-or-place member **152** extends out of the transition member **151**, moves the goods **200** out of the transition member **151**, and transfers the goods to the plurality of storage assemblies **121**. After the transfer, the pick-or-place member **152** retracts into the transition member **151**. Optionally, the transition member **151** includes, but is not limited to, a transition box, and the pick-or-place member **152** includes, but is not limited to, a structure in which a telescopic motor cooperates with a telescopic rod, a

mechanical arm mechanism, and the like.

(110) In an embodiment, the transport robot **100** further includes a movable chassis **160** arranged at a bottom portion of the vertical frame **110**. The movable chassis **160** can drive the transport robot **100** to move, which greatly improves the adaptability of the transport robot **100** to actual working conditions. Specifically, the chassis **160** includes a chassis frame **161**, a travel drive assembly, and a plurality of rotating wheels **162**, the vertical frame **110** is arranged on an upper portion of the chassis frame **161**, the plurality of rotating wheels **162** are arranged on a bottom portion of the chassis frame **161**, the travel drive assembly is arranged on the chassis frame **161**, and at least one of the plurality of rotating wheels **162** is in driving connection with the travel drive assembly. Further, at least two of the plurality of rotating wheels **162** are separately in driving connection with the travel drive assembly, and the at least two of the plurality of rotating wheels **162** being separately in driving connection with the travel drive assembly are distributed on two sides of the chassis frame **161** along a traveling direction, thereby achieving a steering function of the chassis **160**. The travel drive assembly includes at least two wheel drive motors, and the at least two of the plurality of rotating wheels **162** distributed on the two sides of the chassis frame **161** along the traveling direction are respectively driven by separate wheel drive motors. That the at least two of the plurality of rotating wheels **162** distributed on the two sides of the chassis frame **161** along the traveling direction are respectively driven by separate wheel drive motors can simplify a transmission structure on the chassis **160**.

(111) In an embodiment, each of the plurality of rotating wheels **162** includes a driving wheel and a driven wheel. The driving wheel and the driven wheel are mounted on a bottom portion of the chassis **160**, may separately rotate relative to the chassis **160**, and jointly support the chassis **160**. The driving wheel is driven by a wheel drive motor to enable the chassis **160** to move. By configuring the movable chassis **160**, the transport robot **100** can transport the goods **200** between the loading position and the unloading position. There are two driving wheels, and the two driving wheels are symmetrically distributed. Correspondingly, there are two wheel drive motors, and the two driving wheels are respectively driven by the two wheel drive motors, so that rotational speeds of the two driving wheels are different, thereby implementing the steering of the chassis **160**. There are four driven wheels, and the four driven wheels are distributed in a rectangular shape. The four driven wheels may be universal wheels or may be of other wheel structures with a steering function. According to actual situations, a quantity of the driven wheel is not limited to four, but may also be six, three, or the like.

(112) In this embodiment, the chassis **160** is also mounted with a guiding apparatus, and the guiding apparatus is a camera configured to identify a graphic code attached to a ground, so that the chassis **160** travels along a preset path. The graphic code may be a two-dimensional code, a barcode, or some customized identification codes. In some other embodiments, the guiding apparatus is a laser guiding apparatus configured to guide the chassis **160** to travel along a laser beam, or the guiding apparatus is a short-wave receiving apparatus configured to receive a preset short-wave signal to guide the chassis **160** to travel along a preset path. It should be noted that, in some other embodiments, the chassis **160** may be omitted, and the vertical frame **110** is directly and fixedly mounted on the ground or another platform, and is only configured to carry the goods **200** between the loading position and the unloading position around the vertical frame.

(113) In an embodiment, the transport robot **100** further includes a controller electrically connected to the chassis **160**, the carrying mechanism **150**, the lifting mechanism **140**, and the rotary mechanism separately, so as to control the synchronous movement of components or control the movement of at least one component, to achieve a function of automatic goods carrying.

First Embodiment

(114) Referring to FIG. 1 to FIG. 8, in the first embodiment of the present disclosure, when a transport robot **100** is unloading, a plurality of storage assemblies **121** are capable of moving synchronously to perform a synchronous unloading action.

(115) To further improve the transport efficiency of the transport robot **100**, the transport robot **100** of the present disclosure can implement synchronous unloading at the unloading position. Specifically, during unloading, a plurality of storage assemblies **121** may move synchronously, so that the goods **200** are moved out of the plurality of storage assemblies **121**, and a synchronous unloading action is performed in real time. In this way, the goods **200** in the plurality of storage assemblies **121** can be unloaded synchronously, which shortens the unloading time and improves the unloading efficiency of the transport robot **100**. After the unloading is completed, the transport robot **100** may return to the loading position to continue loading, which improves the working efficiency of the transport robot **100**.

(116) In this embodiment described above, when the transport robot **100** is unloading, a plurality of storage assemblies **121** of a storage mechanism **120** may move synchronously to perform a synchronous unloading action, so that the synchronous unloading of goods **200** in the plurality of storage assemblies **121** is implemented, the current problem of a low unloading efficiency caused by the layer-by-layer unloading of goods is effectively resolved, goods **200** in the transport robot **100** can be unloaded at one time, the unloading efficiency is improved, the unloading time is reduced, and the overall working efficiency of the transport robot **100** is improved.

(117) Referring to FIG. 1 to FIG. 4, in an embodiment, the transport robot **100** further includes at least one linkage mechanism **130**, and each of the at least one linkage mechanism **130** is connected to at least two storage assemblies **121** and is configured to drive the at least two storage assemblies **121** to move synchronously relative to the vertical frame **110** to perform a synchronous unloading action. When the at least one linkage mechanism **130** moves, a synchronous movement of the at least two storage assemblies **121** may be implemented. It can be understood that one linkage mechanism **130** may be connected to all storage assemblies **121**, and alternatively, among a plurality of linkage mechanisms **130**, each of the plurality of linkage mechanisms **130** may be connected to a plurality of storage assemblies **121**. Exemplarily, there are two linkage mechanisms **130**, where one of the two linkage mechanisms **130** is connected to storage assemblies **121** of first to third layers, and the other one of the two linkage mechanisms **130** is connected to storage assemblies **121** of fourth to sixth layers. Certainly, in another implementation of the present disclosure, there may be more linkage mechanisms **130**. The present disclosure is only described by taking an example in which one linkage mechanism **130** is connected to all storage assemblies **121**. A working principle of a plurality of linkage mechanisms **130** is substantially the same as that of the one linkage mechanism **130**, and details are not described herein again.

(118) The storage mechanism **120** may be rotatably mounted on the vertical frame **110**, and may further be connected to the linkage mechanism **130**. When moving, the linkage mechanism **130** drives the plurality of storage assemblies **121** to rotate relative to the vertical frame **110**, so that the plurality of storage assemblies **121** can undergo a pitching motion. It can be understood that one end of the linkage mechanism **130** may be mounted on the vertical frame **110** or the chassis **160**, as long as the linkage mechanism **130** can drive the plurality of storage assemblies **121** to undergo a pitching motion.

(119) When the linkage mechanism **130** drives the plurality of storage assemblies **121** to move upward, one ends of the plurality of storage assemblies **121** are lifted up, and other ends rotate relative to the vertical frame **110**, so as to stay at initial positions. At this time, the plurality of storage assemblies **121** are lifted up, and goods **200** thereon may slide out of the plurality of storage assemblies **121** under an action of gravity thereof, so as to implement the unloading of the goods **200**. Because the linkage mechanism **130** simultaneously drives the plurality of storage assemblies **121** to move upward, the plurality of storage assemblies **121** can be simultaneously lifted up, thereby simultaneously performing an unloading operation to implement the unloading. After the unloading is completed, the linkage mechanism **130** drives the plurality of storage assemblies **121** to descend, and the plurality of storage assemblies **121** return to horizontal initial positions.

(120) When the linkage mechanism **130** drives the plurality of storage assemblies **121** to move downward, and after external goods **200** are simultaneously conveyed to the plurality of storage assemblies **121**, the goods **200** can slide into the plurality of storage assemblies **121** under the action of gravity to implement synchronous loading. It should be noted that the synchronous loading of the transport robot **100** needs to be implemented in cooperation with an auxiliary apparatus **300** of the transport system, a specific implementation process is described in detail in the following specification, and only the synchronous unloading of the transport robot **100** is described in detail in this embodiment.

(121) After the transport robot **100** loads the goods **200** into the plurality of storage assemblies **121** at the loading position, the transport robot **100** moves from the loading position to the unloading position. At this time, the linkage mechanism **130** drives the plurality of storage assemblies **121** to move upward, so that the plurality of storage assemblies **121** are lifted up. In this way, the goods **200** in the plurality of storage assemblies **121** can slide out of the plurality of storage assemblies **121** under the action of gravity thereof, and be stored in a specified apparatus such as the auxiliary apparatus **300**, so as to implement the synchronous unloading of the transport robot **100**. After the unloading is completed, the transport robot **100** returns to the loading position to load goods, and in this way, a transport function of the transport robot **100** is achieved.

(122) In an embodiment, the linkage mechanism **130** includes a linkage connector **131** simultaneously connected to at least two storage assemblies **121** and capable of synchronously driving the at least two storage assemblies **121** to synchronously undergo a pitching motion. It can be understood that the pitching motion herein may be a pitching rotational motion, or a curved motion, and certainly, may also be in other forms that can generate the pitching motion. One ends of the at least two storage assemblies **121** are rotatably connected to the vertical frame **110**, and the at least two storage assemblies **121** are also connected to the linkage connector **131**. The linkage connector **131** can ascend or descend. When ascending or descending, the linkage connector **131** may drive the at least two storage assemblies **121** to ascend or descend, so that the at least two storage assemblies **121** rotate relative to the vertical frame **110**, that is, the at least two storage assemblies **121** undergo a pitching motion. It can be understood that, when one of the at least two storage assemblies **121** undergo a pitching motion, the linkage connector **131** is driven to ascend or descend, and the remaining storage assemblies **121** may be driven to move through the linkage connector **131**; or the linkage connector **131** ascends or descends, and then the at least two storage assemblies **121** are driven to move.

(123) As shown in FIG. 1 and FIG. 2, optionally, the linkage connector **131** and the at least two storage assemblies **121** may be rotatably connected or fixedly connected. When the linkage connector **131** and the at least two storage assemblies **121** are rotatably connected, the at least two storage assemblies **121** may have a rotary shaft, and the at least two storage assemblies **121** may be rotatably mounted on the linkage connector **131** through the rotary shaft. Alternatively, the linkage connector **131** may have a rotary shaft, and the linkage connector **131** may be rotatably mounted on the at least two storage assemblies **121** through the rotary shaft. Alternatively, a connection between the linkage connector **131** and the at least two storage assemblies **121** is similar to an olecranon engagement structure. In addition, the rotary shaft may be replaced with a hinge or another component that can implement a rotatable connection.

(124) Optionally, the linkage connector **131** may be a connecting rod connected to the at least two storage assemblies **121**. Further optionally, the linkage member may include a plurality of connecting rods, and two adjacent linkage members are connected by the plurality of connecting rods. In this case, when one of the at least two storage assemblies **121** moves, adjacent connecting rods may drive the remaining storage assemblies **121** to move. It can be understood that a specific structure of the linkage connector **131** is not limited to the connecting rod, but may also be a connecting piece or the like.

(125) It should be noted that, the essential spirit of the present disclosure lies in the linkage

between the linkage connector **131** and the at least two storage assemblies **121**, and the linkage connector **131** can implement the synchronous movement of the at least two storage assemblies **121**, thereby performing a synchronous unloading operation. In this embodiment, the connection of connectors is implemented by connecting rods, and there may be one or more connecting rods. In addition, there are various arrangements of the linkage connector **131**, which cannot all be listed herein, and a linkage manner in the present disclosure is not limited to being implemented by the foregoing specific structures.

(126) Referring to FIG. 1 and FIG. 3, in an embodiment, in a same horizontal direction, a distance between the linkage connector **131** and the vertical frame **110** is less than or equal to a length of each of the plurality of storage assemblies **121**. It can be understood that a length at a connection position between the linkage connector **131** and the plurality of storage assemblies **121** may be equal to the length of each of the plurality of storage assemblies **121**. In this case, the linkage connector **131** and the vertical frame **110** are respectively located at two ends of the plurality of storage assemblies **121**. The length at the connection position between the linkage connector **131** and the plurality of storage assemblies **121** may be less than the length of each of the plurality of storage assemblies **121**, and the connection position between the linkage connector **131** and the plurality of storage assemblies **121** is located on side surfaces of the plurality of storage assemblies **121**. That is, the linkage connector **131** may be located at any position on a peripheral side of each of the plurality of storage assemblies **121**. In this way, the linkage connector **131** can drive the plurality of storage assemblies **121** to synchronously ascend or descend when the linkage connector **131** ascends or descends, so as to perform the synchronous unloading operation of the transport robot **100**.

(127) In an embodiment, there may be at least one linkage connector **131**. In a case that there is one linkage connector **131**, the cooperation between the linkage connector with the vertical frame **110** can ensure that the plurality of storage assemblies **121** are fixed and reliable, and simultaneously implement the driving of the movement of the plurality of storage assemblies **121**. In a case that there are a plurality of linkage connectors **131**, the plurality of linkage connectors **131** can further improve the linkage of the plurality of storage assemblies **121** and ensure that the plurality of storage assemblies **121** move in a consistent manner.

(128) In a case that there is one linkage connector **131**, the linkage connector **131** and the vertical frame **110** are respectively arranged at two ends of the plurality of storage assemblies **121**. That is, the connection position between the linkage connector **131** and the plurality of storage assemblies **121** and the vertical frame **110** are respectively located at the two ends of the plurality of storage assemblies **121**, and a distance between the connection position and the vertical frame **110** is equal to a size of each of the plurality of storage assemblies **121** along a horizontal direction. In this way, the plurality of storage assemblies **121** can be reliably supported by the linkage connector **131** and the vertical frame **110**, to prevent the plurality of storage assemblies **121** from falling and dropping, so that the plurality of storage assemblies **121** can reliably store the goods **200**.

(129) In a case that there are a plurality of linkage connectors **131**, the plurality of linkage connectors **131** are arranged at intervals along the peripheral side of the storage assembly **121**. The plurality of linkage connectors **131** are distributed at intervals along the peripheral side of each of the plurality of storage assemblies **121**, and may be distributed uniformly, non-uniformly, or symmetrically. The plurality of storage assemblies **121** can be reliably supported by the plurality of linkage connectors **131** and the vertical frame **110**, to prevent the plurality of storage assemblies **121** from falling and dropping, so that the plurality of storage assemblies **121** can reliably store the goods **200**.

(130) Referring to FIG. 1, FIG. 3, and FIG. 4, in an embodiment, the linkage mechanism **130** further includes a linkage driving member **132** configured to cooperate with the linkage connector **131**, so as to drive the plurality of storage assemblies **121** to implement synchronous unloading. The linkage driving member **132** is a power source for the movement of the linkage mechanism

130, and implements the driving of the movement of a linkage moving member. In addition, the linkage driving member **132** outputs linear motion, so that the linkage connector **131** can ascend or descend, and the plurality of storage assemblies **121** can undergo a pitching motion. Optionally, the linkage driving member **132** includes, but is not limited to, an air cylinder, a hydraulic cylinder, a linear motor, or an electric push rod, and may also be another linear driving unit capable of outputting the linear motion. Exemplarily, the linkage driving member **132** is a linear motor. Exemplarily, one end of the linkage driving member **132** is arranged on the chassis **160**. Certainly, one end of the linkage driving member **132** may also be arranged on the vertical frame **110**.

(131) Optionally, the linkage driving member **132** may be connected to the plurality of storage assemblies **121**. In an embodiment, an output end of the linkage driving member **132** is connected to one of the plurality of storage assemblies **121**. One end of the linkage driving member **132** is mounted on the vertical frame **110**, and an other end is connected to the plurality of storage assemblies **121**. After outputting the linear motion, the linkage driving member **132** may drive a plurality of storage assemblies **121** connected thereto to move, and then the plurality of storage assemblies **121** may drive the linkage connector **131** to ascend or descend. At this time, the linkage connector **131** may drive the remaining storage assemblies **121** to move synchronously, so that the plurality of storage assemblies **121** rotate relative to the vertical frame **110**, the plurality of storage assemblies **121** are lifted up, and the synchronous unloading operation of the plurality of storage assemblies **121** is performed.

(132) Further, the output end of the linkage driving member **132** is connected to a bottom portion or a top portion of one of the plurality of storage assemblies **121**. In a case that the linkage driving member **132** is connected to the top portion of the plurality of storage assemblies **121**, the linkage driving member **132** may retract to drive the plurality of storage assemblies **121** to move upward, and the linkage driving member **132** may extend to drive the plurality of storage assemblies **121** to move downward. In a case that the linkage driving member **132** is connected to the bottom portion of the plurality of storage assemblies **121**, the linkage driving member **132** may extend to drive the plurality of storage assemblies **121** to move upward, and the linkage driving member **132** may retract to drive the plurality of storage assemblies **121** to move downward. Exemplarily, the linkage driving member **132** is connected to the bottom portion of the plurality of storage assemblies **121**. Still further, the linkage driving member **132** is located and connected to a bottom portion of a lowermost storage assembly **121**, and the output end of the linkage driving member **132** is in abutment with a middle region of the bottom portion of the storage assembly **121**. In this way, the linkage driving member **132** does not affect the loading or unloading of goods **200** of a carrying component, so as to avoid interference.

(133) Further optionally, the output end of the linkage driving member **132** is connected to the linkage connector **131**. The linkage driving member **132** may directly drive the linkage connector **131** to ascend or descend, and then the linkage connector **131** may drive the plurality of storage assemblies **121** to move synchronously. Further, the linkage driving member **132** may be located at the bottom portion of the lowermost storage assembly **121** and arranged on the chassis **160**, and the output end of the linkage driving member **132** is connected to the linkage connector **131**. Certainly, the linkage driving member **132** may also be located at the top portion of the plurality of storage assemblies **121**.

(134) The linkage mechanism **130** in this embodiment can implement the simultaneous unloading of a plurality of storage assemblies **121**, the plurality of storage assemblies **121** are connected by a same linkage connector **131**, and an output end of a linkage driving member **132** is connected to a lowermost storage assembly **121**. When the linkage driving member **132** extends, the linkage driving member **132** may push the plurality of storage assemblies **121** upward, so that the plurality of storage assemblies **121** rotate relative to the vertical frame **110**. When rotating, the plurality of storage assemblies **121** may drive the linkage connector **131** to move synchronously, and then the linkage connector **131** drives the remaining storage assemblies **121** to move synchronously, so as to

implement the synchronous driving of all storage assemblies **121** to move upward, thereby performing the synchronous unloading operation.

(135) It is worth noting that there are various rotational driving forms in which the plurality of storage assemblies **121** rotate relative to the vertical frame **110** to undergo a pitching motion. In this embodiment, only the linkage driving member **132** capable of outputting the linear motion is configured to drive the movement of the plurality of storage assemblies **121**, and other driving components that can implement the pitching motion of the plurality of storage assemblies **121** should be considered as falling within the protection scope of the present disclosure.

(136) Referring to FIG. 1, FIG. 3, and FIG. 5, in an embodiment, each of the plurality of storage assemblies **121** includes a carrier body **1211** configured to carry the goods **200** and rotatably connected to the linkage connector **131** and the vertical frame **110** separately. The carrier body **1211** is a main body configured to carry the goods **200**, one end of the carrier body **1211** is rotatably connected to the vertical frame **110**, and an other end is rotatably connected to the linkage connector **131**. One end of the carrier body **1211** connected to the vertical frame **110** is a head end, and one end of the carrier body **1211** connected to the linkage connector **131** is a tail end. When the linkage connector **131** drives the carrier body **1211** to ascend or descend, the tail end of the carrier body **1211** rotates around the head end of the carrier body **1211**, so that the carrier body **1211** undergoes a pitching motion. Optionally, an edge of the carrier body **1211** is rotatably connected to the linkage connector **131** and the vertical frame **110** separately, and certainly, a middle region of the carrier body **1211** may also be rotatably connected to the linkage connector **131** and the vertical frame **110** separately.

(137) It can be understood that the rotatable connection between the carrier body **1211** and the vertical frame **110** may be that the carrier body **1211** has a rotary shaft, and the carrier body **1211** is also rotatably mounted on the vertical frame **110** through the rotary shaft, or the vertical frame **110** has a rotary shaft, and the carrier body **1211** may be rotatably mounted on the rotary shaft, or the like. In addition, the foregoing manner of the rotatable connection which is implemented through the rotary shaft may also be replaced by a hinged connection or other forms of rotatable connection.

(138) Optionally, the carrier body **1211** is arranged in a flat plate shape, and a container of the goods **200** may be transferred to the carrier body **1211**. Further, the edge of the carrier body **1211** has three sides of flanges, and the three sides of flanges form a loading or unloading port at the vertical frame **110**, and the goods **200** are mounted in the carrier body **1211** through the loading or unloading port. In addition, the flanges can limit the displacement of the goods **200** on the carrier body **1211**, prevent the goods **200** from falling out of the carrier body **1211**, and ensure that the carrier body **1211** can store the goods **200** accurately. It can be understood that the loading or unloading port herein is the loading or unloading end **1215** in the second embodiment.

(139) In an embodiment, each of the plurality of storage assemblies **121** further includes a rolling member **1212** arranged on the carrier body **1211** in a rolling manner and configured to be in a rolling contact with the goods **200** in the carrier body **1211**. The rolling member **1212** can reduce a frictional force between the goods **200** and the carrier body **1211**, so as to facilitate the loading or unloading of the goods **200**. When the goods **200** are loaded, a bottom portion of the goods **200** is in contact with the rolling member **1212** under the action of gravity thereof. During the movement of the goods **200** into the carrier body **1211**, the goods **200** may drive rollers to rotate, so that the frictional force between the goods **200** and the carrier body **1211** is reduced, and the loading of the goods **200** is facilitated. When the goods **200** are unloaded, the linkage connector **131** drives the carrier body **1211** to move upward. At this time, the tail end of the carrier body **1211** is higher than a top end of the carrier body **1211**, and the goods **200** in the carrier body **1211** slide out of the carrier body **1211** under the action of gravity. In addition, during a sliding process of the goods **200** along the carrier body **1211**, the bottom portion of the goods **200** drives the rolling member **1212** to roll, so that the goods **200** slide out of the carrier body **1211** more easily, and the unloading of the

goods **200** is facilitated.

(140) Optionally, the carrier body **1211** is provided with a rolling groove, the rolling member **1212** may be rotatably mounted in the rolling groove, and a top surface of the rolling member **1212** is slightly higher than a top surface of the carrier body **1211**, so as to ensure that the rolling member **1212** can be in contact with the bottom portion of the goods **200**. In addition, the bottom portion of the carrier body **1211** also includes a protection cover covering the rolling member **1212** on the bottom portion of the carrier body **1211**, so as to avoid interference between a bottom portion of the rolling member **1212** and other components.

(141) Optionally, the rolling member **1212** includes, but is not limited to, rollers, rolling shafts, rolling balls, or other components capable of rolling. In addition, there are a plurality of rolling members **1212**, and the plurality of rolling members **1212** may be arranged in one row, or may be arranged in a plurality of rows. Exemplarily, the rolling member **1212** is rollers arranged in three rows.

(142) Referring to FIG. 1, FIG. 3, FIG. 6, and FIG. 7, the first embodiment of the present disclosure further provides a transport system including an auxiliary apparatus **300** and the transport robot **100** in the foregoing embodiment. The auxiliary apparatus **300** includes a support frame **310** and a plurality of transport mechanisms **320** arranged on the support frame **310** at intervals along a vertical direction, and a manner in which the plurality of transport mechanisms **320** are arranged at intervals is the same as a manner in which a plurality of storage assemblies **121** are arranged at intervals. When the transport robot **100** moves to the auxiliary apparatus **300**, goods **200** on the plurality of storage assemblies **121** are capable of being simultaneously transferred to corresponding transport mechanisms **320** to implement synchronous unloading; or goods **200** on the plurality of transport mechanisms **320** are capable of being simultaneously transferred to corresponding storage assemblies **121** to implement synchronous loading.

(143) The auxiliary apparatus **300** can implement the synchronous unloading or synchronous loading of the goods **200**. The auxiliary apparatus **300** is arranged at an unloading position or a loading position. In a case that the auxiliary apparatus **300** is unloaded, the auxiliary apparatus **300** is at the unloading position; and in a case that the auxiliary apparatus **300** is loaded, the auxiliary apparatus **300** is at the loading position. In the present disclosure, only an example in which the auxiliary apparatus **300** is at the unloading position is used for description. The auxiliary apparatus **300** is located at the unloading position. After the transport robot **100** completes loading at the loading position, the transport robot **100** moves to the unloading position. At this time, the transport robot **100** is docked with the auxiliary apparatus **300**, and the auxiliary apparatus **300** may receive and pick the goods **200** in the plurality of storage assemblies **121** in the transport robot **100**.

(144) Specifically, the mounting frame **321** functions as a support, which is configured to support a plurality of transport mechanisms **320** configured to transport the goods **200**. The auxiliary apparatus **300** includes a same quantity of transport mechanisms **320** as the plurality of storage assemblies **121**, and heights at which the plurality of transport mechanisms **320** are located are consistent with heights at which corresponding storage assemblies **121** are located. After the transport robot **100** is docked with the auxiliary apparatus **300**, the plurality of storage assemblies **121** and the plurality of transport mechanisms **320** are at same levels and heights. When unloading, the linkage driving member **132** of the linkage mechanism **130** extends to drive one end of a lowermost storage assembly **121** to be lifted up. During a lifting process of the storage assembly **121**, the linkage connector **131** may be driven to ascend, and the linkage connector **131** may drive the remaining storage assemblies **121** to be lifted up during the lifting process. In this way, the plurality of storage assemblies **121** can be simultaneously lifted up, the goods **200** in the plurality of storage assemblies **121** slide out of the plurality of storage assemblies **121** under the action of gravity and the action of the rolling member **1212**, and move to corresponding transport mechanisms **320**, and the transport mechanisms **320** transport the goods **200** thereon away to implement the unloading of the goods **200**.

(145) The auxiliary apparatus **300** may also implement the loading of the goods **200**. Specifically, transport mechanisms **320** of different layers drive the goods **200** to move toward corresponding storage assemblies **121**, and transfer the goods **200** to the corresponding storage assemblies **121**. It can be understood that when loading the goods **200**, the linkage mechanism **130** may drive ends of the plurality of storage assemblies **121** to descend, and at the same time, the plurality of transport mechanisms **320** simultaneously transfer the goods **200** to the corresponding storage assemblies **121**. After the goods **200** are gradually transferred into the carrier body **1211** and come into contact with the rolling member **1212**, the goods **200** may slide into the plurality of storage assemblies **121** under the action of gravity thereof and through the cooperation with the rolling member **1212**. Certainly, the plurality of storage assemblies **121** may also be stationary, and the goods **200** may also be moved into the plurality of storage assemblies **121** by a pushing force of the plurality of transport mechanisms **320** in cooperation with the rolling member **1212**.

(146) Referring to FIG. 6 and FIG. 7, in an embodiment, each of the plurality of transport mechanisms **320** includes a mounting frame **321** arranged on the support frame **310** and a transport portion **322** movably arranged on the mounting frame **321**, and the transport portion **322** may drive the goods **200** to move. The mounting frame **321** is of a frame structure, which carries the transport portion **322** and is configured to implement the mounting of the transport portion **322**. The transport portion **322** is a main component that implements the transport of the goods **200**. When the goods **200** are in the transport portion **322**, the transport portion **322** may drive the goods **200** to move toward or away from the plurality of storage assemblies **121**.

(147) Optionally, the transport portion **322** is of a structure that can implement horizontal transport, such as a conveyor belt structure, an assembly line, a conveyor roller structure, a roller structure, or the like. Exemplarily, the transport portion **322** is of a roller structure, and specifically includes a plurality of rollers, and each of the plurality of rollers includes a built-in rolling motor to drive the each of the plurality of rollers to rotate, thereby implementing the transport of the goods **200**. It should be noted that, there are various structures that can implement the horizontal transport of the goods **200**, which cannot all be listed herein, and the transport portion **322** in the present disclosure is not limited to being implemented by the foregoing specific structures.

(148) In an embodiment, the auxiliary apparatus **300** further includes a movable base arranged at a bottom portion of the support frame **310**. The movable base can drive the auxiliary apparatus **300** to move, which greatly improves the adaptation of the auxiliary apparatus **300** to actual working conditions. In this way, the auxiliary apparatus **300** can easily move to the loading position, the unloading position, or any other position, to work with the transport robot **100**. Optionally, a structure of the base is exactly the same as that of the chassis **160** of the transport robot **100**, and details are not described herein again.

(149) Referring to FIG. 1, FIG. 6, and FIG. 8, in an embodiment, the transport system further includes a conveying apparatus **500** and a lifting apparatus **400** that is arranged between the auxiliary apparatus **300** and the conveying apparatus **500**, and the lifting apparatus **400** is configured to ascend or descend along the vertical direction, so as to be docked with each of the plurality of transport mechanisms **320** and the conveying apparatus **500**. The lifting apparatus **400** is capable of receiving and picking goods **200** of the plurality of transport mechanisms **320** and transferring the goods to the conveying apparatus **500**; or the lifting apparatus **400** is capable of receiving and picking goods **200** of the conveying apparatus **500** and transferring the goods to the plurality of transport mechanisms **320**.

(150) The lifting apparatus **400** is configured to receive and pick the goods **200** of the plurality of transport mechanisms **320** or transport the goods **200** to the plurality of transport mechanisms **320**. Because the plurality of transport mechanisms **320** are arranged at intervals along the vertical direction, to facilitate the goods loading or unloading of the auxiliary apparatus **300**, the lifting apparatus **400** needs to move to a transport mechanism **320** at a corresponding position, so as to perform a corresponding operation. The conveying apparatus **500** is configured to convey the

goods **200**, may transport away goods **200** unloaded by the lifting apparatus **400**, and may also transport to-be-loaded goods **200** to the lifting apparatus **400**. Optionally, the conveying apparatus **500** may be of a structure that can implement the horizontal transport, such as a conveyor belt structure, an assembly line, a conveying roller structure, or a roller structure, or the like. Exemplarily, the conveying apparatus **500** is of an assembly line structure, and specifically, when unloading, the lifting apparatus **400** ascends to one side of a transport mechanism **320**, after receiving the goods **200** of the transport mechanism **320**, the lifting apparatus **400** descends, and transfers the goods **200** to the conveying apparatus **500**, and the goods are transported away by the conveying apparatus **500**. Subsequently, the lifting apparatus **400** further ascends to another transport mechanism **320**, and this process is repeated until all the goods **200** on the plurality of transport mechanisms **320** are transported away. When loading, after the lifting apparatus **400** descends and receives and picks the goods **200** conveyed by the conveying apparatus **500**, the lifting apparatus **400** ascends to one side of a transport mechanism **320** and transfers the goods **200** to the transport mechanism **320**; and subsequently, the lifting apparatus **400** further descends to the conveying apparatus **500**, and this process is repeated until the plurality of transport mechanisms **320** are loaded with the goods **200**.

(151) In an embodiment, the lifting apparatus **400** includes a lifting frame **410** along the vertical direction, a moving mechanism **420** arranged on the lifting frame **410**, and a transfer mechanism **430** with at least one layer arranged on the moving mechanism **420**. The moving mechanism **420** may ascend or descend along the lifting frame **410** and drive the transfer mechanism **430** with at least one layer to move, so as to receive and pick goods from or transfer goods **200** to the plurality of transport mechanisms **320**. The lifting frame **410** has a bearing function, and is configured to bear the moving mechanism **420** and the transfer mechanism **430** with at least one layer. Optionally, a bottom portion of the lifting frame **410** may also be provided with rotating wheels, so as to adapt to different applications. The transfer mechanism **430** with at least one layer is configured to carry the goods **200** and implement the transfer of the goods **200** between a high position such as a transport mechanism **320** and a low position such as the conveying apparatus **500**. The moving mechanism **420** is arranged on the lifting frame **410** along the vertical direction, and may output movement in the vertical direction, so as to drive the transfer mechanism **430** with at least one layer to ascend or descend.

(152) It can be understood that the moving mechanism **420** is configured to implement the ascending or descending motion of the transfer mechanism **430** with at least one layer along the vertical direction. A specific structure of the moving mechanism **420** may be a telescopic rod structure, a chain transmission structure, a driving transmission structure, or the like, and may also be another structure capable of enabling the carrying mechanism **150** to ascend or descend. Exemplarily, a specific structure of the moving mechanism **420** is the same as a structure of the lifting mechanism **140** of the transport robot **100**, and details are not described herein again. Certainly, the specific structure of the moving mechanism **420** may also be different from the structure of the lifting mechanism **140** of the transport robot **100**, as long as the moving mechanism **420** can implement the ascending or descending motion.

(153) Exemplarily, there is a transfer mechanism **430** with one layer, and the transfer mechanism **430** with one layer receives and picks goods from one transport mechanism **320** at one time, or transfers goods to one transport mechanism **320** at one time. Certainly, in another implementation of the present disclosure, in a case that there is a transfer mechanism **430** with at least two layers, the transfer mechanism **430** with at least two layers may remove goods on at least two transport mechanisms **320** at one time, or transfer goods to at least two transport mechanisms **320**, so as to improve the efficiency of goods turnover.

(154) In an embodiment, the transfer mechanism **430** with at least one layer includes a transfer base **431** arranged on the moving mechanism **420** and a transfer portion **432** movably arranged on the transfer base **431**, and the transfer portion **432** may drive goods **200** to move, and may receive and

pick goods from or transfer goods **200** to at least one of the plurality of transport mechanisms **320**. The transfer base **431** plays a bearing role and is configured to carry the transfer portion **432**, so as to mount the transfer portion **432** on the moving mechanism **420**. When the moving mechanism **420** ascends or descends, the transfer base **431** may drive the transfer portion **432** to ascend or descend synchronously, so as to implement the loading or unloading of the goods **200**.

(155) Optionally, the transfer portion **432** is of a structure that can implement horizontal transport, such as a conveyor belt structure, an assembly line, a conveyor roller structure, a roller structure, or the like. Exemplarily, the transfer portion **432** is of a rolling shaft structure, and specifically includes a plurality of rolling shafts, and each of the plurality of rolling shafts includes a built-in rolling motor to drive the each of the plurality of rolling shafts to rotate, thereby implementing the transport of the goods **200**. It should be noted that, there are various structures that can implement the horizontal transport of the goods **200**, which cannot all be listed herein, and the transfer portion **432** in the present disclosure is not limited to being implemented by the foregoing specific structures.

(156) The transfer portion **432** may receive and pick the goods **200** of one transport mechanism **320** at one time, as mentioned above. The transfer portion **432** may also receive and pick the goods **200** of a plurality of transport mechanisms **320** at one time, and the moving mechanism **420** may receive and pick the goods **200** of the plurality of transport mechanisms **320** layer by layer, and then convey the goods to the conveying apparatus **500** together for transport after receiving and picking the goods. Exemplarily, the moving mechanism **420** drives the transfer portion **432** to ascend to a top portion. After receiving and picking goods **200** of one transport mechanism **320**, the transfer portion **432** descends one layer to receive and pick goods **200** of one transport mechanism **320**. After the transfer portion **432** is full or the goods **200** of the plurality of transport mechanisms **320** are received, the moving mechanism **420** drives the transfer portion **432** to descend to a position of the conveying apparatus **500**, and the transfer portion **432** transfers all the goods **200** thereon to the conveying apparatus **500**. Certainly, the moving mechanism **420** may move layer by layer from bottom to top, a principle thereof is substantially the same as a principle from top to bottom, and details are not described herein again.

(157) Certainly, the transfer portion **432** may also receive and pick a plurality of goods **200** transferred by the conveying apparatus **500** at one time, and then transfer the goods to the plurality of transport mechanisms **320** layer by layer, a principle thereof is substantially the same as a foregoing principle of goods unloading, and details are not described herein again.

(158) In an embodiment, the transport system further includes a control center, components of the transport system perform a coordinated action under the control of the control center, and the control center of the transport system maintains a communication connection with an external server. The control center may identify information of the to-be-transported goods **200**, and the control center may obtain information of a loading position and an unloading position corresponding to each piece of the to-be-transported goods **200**. The control center coordinates and controls the components according to the obtained information, so as to efficiently complete the transport of the goods **200**.

(159) In the transport robot **100** and the transport system in this embodiment, when unloading, a plurality of storage assemblies **121** of a storage mechanism **120** may move synchronously to perform a synchronous unloading action, so that the synchronous unloading of goods **200** in the plurality of storage assemblies **121** is implemented, goods **200** in the transport robot **100** can be unloaded at one time, the unloading efficiency is improved, the unloading time is reduced, and the overall working efficiency of the transport robot **100** is improved. In addition, after the transport robot **100** is used in cooperation with the auxiliary apparatus **300**, the loading or unloading can be simultaneously implemented, thereby improving the working efficiency of the transport system.

Second Embodiment

(160) Referring to FIG. 9 and FIG. 17, in the second embodiment of the present disclosure, the

transport robot **100** further includes a blocking mechanism **170** capable of switching between a blocking position and an avoidance position, where when the blocking mechanism **170** is at the blocking position, the blocking mechanism **170** is configured to block goods **200** in the storage assemblies **121** from sliding out, and when the blocking mechanism **170** is at the avoidance position, goods **200** are capable of being moved into or moved out of the plurality of storage assemblies **121**.

(161) It can be understood that after the plurality of storage assemblies **121** store the to-be-transported goods **200**, during the movement of the transport robot **100** from the loading position to the unloading position, the transport robot **100** travels a specific distance, and the goods **200** stored in the plurality of storage assemblies **121** may be at a risk of falling. Once the goods **200** in the plurality of storage assemblies **121** fall, on the one hand, the goods **200** are damaged, resulting in economic losses; and on the other hand, a manual or intelligent picking apparatus is required to pick the goods **200** and place the goods in the plurality of storage assemblies **121** again for transport, which affects the transport efficiency of the goods **200**.

(162) In view of the foregoing description, the transport robot **100** of the present disclosure further includes a blocking mechanism **170**, and the goods **200** in the plurality of storage assemblies **121** are blocked by the blocking mechanism **170**. In this way, the goods **200** in the plurality of storage assemblies **121** can be prevented from sliding out. Specifically, the blocking mechanism **170** capable of switching between a blocking position and an avoidance position. When the blocking mechanism **170** is at the avoidance position, the goods **200** may be loaded into the plurality of storage assemblies **121** or the goods **200** may be taken out from the plurality of storage assemblies **121**. When the blocking mechanism **170** is at the blocking position, the goods **200** in the plurality of storage assemblies **121** are in abutment with the blocking mechanism **170**, and the blocking mechanism **170** may restrict the goods **200** in the plurality of storage assemblies **121** from sliding out and prevent the goods **200** from falling.

(163) Specifically, when the transport robot **100** is at the loading position, the blocking mechanism **170** is at the avoidance position, and at this time, the goods **200** may be loaded into the plurality of storage assemblies **121**; after the loading is completed, the blocking mechanism **170** moves to the blocking position, and at this time, the blocking mechanism **170** may be in abutment with the goods **200** in the plurality of storage assemblies **121** to restrict the goods **200** from sliding out of the plurality of storage assemblies **121**; subsequently, the transport robot **100** may move from the loading position to the unloading position, and the blocking mechanism **170** is always at the blocking position during this process; and when the blocking mechanism **170** is at the unloading position, the blocking mechanism **170** moves from the blocking position to the avoidance position, and at this time, the goods **200** in the plurality of storage assemblies **121** may be taken out. In addition, the transport robot **100** reciprocates in this way. It can be understood that the blocking mechanism **170** may play a blocking role during the movement of the transport robot **100** regardless of whether there are goods in the plurality of storage assemblies **121**, or may only play a blocking role during goods transport in a case that there are goods in the plurality of storage assemblies **121**.

(164) When the transport robot **100** of the foregoing embodiment transports goods, the blocking mechanism **170** moves to the blocking position and may be in abutment with the goods **200** in the plurality of storage assemblies **121**, so as to restrict the goods **200** from sliding out of the plurality of storage assemblies **121**. Therefore, a current problem that the goods easily slide out of a storage rack of the transport robot during goods transport is effectively resolved, the goods **200** are prevented from sliding out of the plurality of storage assemblies **121** during a transport process of the transport robot **100**, the safety of the goods **200** is ensured, a risk of sliding out is avoided, and the transport efficiency is improved. In addition, when the transport robot **100** loads or unloads goods, the blocking mechanism **170** moves to the avoidance position. At this time, the goods **200** may be loaded into the plurality of storage assemblies **121**, and the goods **200** in the plurality of

storage assemblies **121** may also be removed, which does not hinder a loading or unloading operation of the transport robot **100**, and is convenient for use.

(165) In an embodiment, the blocking mechanism **170** may simultaneously block the goods **200** in the plurality of storage assemblies **121**. That is, the blocking mechanism **170** may simultaneously move to the blocking position, so as to block the goods **200** in the plurality of storage assemblies **121**, and the blocking mechanism **170** may also simultaneously move to the avoidance position, so that the plurality of storage assemblies **121** can perform a loading or unloading operation.

Certainly, in another implementation of the present disclosure, there are a plurality of blocking mechanisms **170**, and each of the plurality of blocking mechanisms **170** may simultaneously block the goods **200** in at least two of the plurality of storage assemblies **121**. It can be understood that one blocking mechanism **170** may simultaneously act on goods **200** of all storage assemblies **121**, or a plurality of blocking mechanisms **170** may act on a plurality of storage assemblies **121**.

Exemplarily, there are two blocking mechanisms **170**, where one of the two blocking mechanisms **170** is configured to block goods **200** of storage assemblies **121** of first to third layers, and the other one of the two blocking mechanisms **170** is configured to block goods **200** of storage assemblies **121** of fourth to sixth layers. Certainly, in another implementation of the present disclosure, there may be more blocking mechanisms **170**. In the present disclosure, only an example in which one blocking mechanism **170** blocks the goods **200** of all storage assemblies **121** is used for description. A working principle of a plurality of blocking mechanisms **170** is substantially the same as that of the one blocking mechanism **170**, and details are not described herein again.

(166) It is worth noting that an arrangement position of the blocking mechanism **170** is not limited in principle. The blocking mechanism may be movably arranged on the vertical frame **110**, may be movably arranged on the chassis **160**, and may also be movably arranged on the plurality of storage assemblies **121**, as long as it is ensured that the blocking mechanism **170** can move to the avoidance position or the blocking position. In this embodiment, only an example in which the blocking mechanism **170** is movably arranged on the chassis **160** is used for description. A working principle of the blocking mechanism **170** arranged at another position is substantially the same as a working principle of the blocking mechanism **170** movably arranged on the chassis **160**, and details are not described herein again. Specifically, when the blocking mechanism **170** moves relative to the chassis **160**, the blocking mechanism **170** may move to the blocking position or the avoidance position. After the blocking mechanism **170** can move to the blocking position, the blocking mechanism **170** may block the goods **200** in the plurality of storage assemblies **121**; and after the blocking mechanism **170** can move to the avoidance position, the blocking mechanism **170** no longer blocks the plurality of storage assemblies **121**, and the goods **200** may freely enter or exit the plurality of storage assemblies **121**.

(167) In an embodiment, the plurality of storage assemblies **121** includes a loading or unloading end **1215** that faces away from the vertical frame **110**. The goods **200** are loaded or unloaded from the loading or unloading end **1215** of the plurality of storage assemblies **121** to complete the loading or unloading of the goods **200**. Exemplarily, as shown in FIG. **10**, one ends of the plurality of storage assemblies **121** away from the vertical frame **110** is provided with the loading or unloading end **1215**. During loading, the goods **200** are moved from the loading or unloading end **1215** into the plurality of storage assemblies **121**, and during unloading, the goods **200** are moved from the loading or unloading end **1215** out of the plurality of storage assemblies **121**. Optionally, the loading or unloading end **1215** is an end opening of the plurality of storage assemblies **121**, or another entrance or exit through which the goods **200** can enter or exit. Certainly, in another implementation of the present disclosure, the loading or unloading end **1215** may also be arranged at one ends of the plurality of storage assemblies **121** close to the vertical frame **110**. In this way, the loading or unloading of the goods **200** in the plurality of storage assemblies **121** can also be implemented.

(168) Optionally, the loading or unloading end **1215** is arranged on a same side as the carrying

mechanism **150**. When the loading or unloading end **1215** performs a loading or unloading operation, the carrying mechanism **150** needs to avoid the loading or unloading end **1215**, so as to avoid interference between the carrying mechanism **1215** and a loading or unloading apparatus **600**, and ensure reliable loading or unloading. In this case, the carrying mechanism **150** may ascend to a highest position of the transport robot **100** or a position higher than the loading or unloading apparatus **600**, or move to an other side of the transport robot **100**. Further optionally, the loading or unloading end **1215** is arranged on an opposite side of the carrying mechanism **150**. The goods loading or unloading at the loading or unloading end **1215** is not affected by the carrying mechanism **150**, and when the plurality of storage assemblies **121** are loaded or unloaded, the carrying mechanism **150** does not interfere with the loading or unloading apparatus **600**.

(169) Referring to FIG. **9** and FIG. **10**, in an embodiment, the blocking mechanism **170** may move into or move out of the loading or unloading end **1215**. That is, when the blocking mechanism **170** moves into the loading or unloading end **1215**, the blocking mechanism **170** is at the blocking position. At this time, an end portion of the goods **200** is in abutment with the blocking mechanism **170**, and the blocking mechanism **170** blocks the goods **200** to restrict the goods **200** from sliding out of the loading or unloading end **1215**. When the blocking mechanism **170** moves out of the loading or unloading end **1215**, the blocking mechanism **170** is at the avoidance position. At this time, the loading or unloading end **1215** is unobstructed, the goods **200** may be loaded into the plurality of storage assemblies **121** through the loading or unloading end **1215**, and the goods **200** in the plurality of storage assemblies **121** may also be unloaded through the loading or unloading end **1215**.

(170) In an embodiment, when the blocking mechanism **170** is at the blocking position, the blocking mechanism **170** is in abutment with a side wall or a bottom surface of the goods **200**. That is, the blocking position of the blocking mechanism **170** may be located on a bottom surface or a side surface of the plurality of storage assemblies **121**. When the blocking mechanism **170** moves to the blocking position, the blocking mechanism **170** may be in abutment with the goods **200** in the plurality of storage assemblies **121** at a side surface or a bottom surface. At this time, the movement of the goods **200** in the plurality of storage assemblies **121** is restricted due to an abutting force of the blocking mechanism **170**, so that the goods **200** are prevented from sliding out of the plurality of storage assemblies **121**. After the blocking mechanism **170** moves to the avoidance position, the blocking mechanism **170** is separated from the side surface or the bottom surface of the goods **200** of the plurality of storage assemblies **121**, and the goods **200** may move in the plurality of storage assemblies **121**, so as to perform the loading or unloading operation of the plurality of storage assemblies **121**.

(171) In an embodiment, the blocking mechanism **170** is arranged on at least one side of the plurality of storage assemblies **121**. It can be understood that the blocking mechanism **170** may be arranged on one side of the plurality of storage assemblies **121**, as shown in FIG. **9** and FIG. **10**, and in this case, the blocking mechanism **170** may block the goods **200** in the plurality of storage assemblies **121** at the blocking position. Certainly, in another implementation of the present disclosure, blocking mechanisms **170** may also be located on two sides of the plurality of storage assemblies **121** respectively. In this way, the goods **200** in the plurality of storage assemblies **121** can be further blocked. Further, two blocking mechanisms **170** may be arranged symmetrically or asymmetrically, as long as the blocking mechanisms can block the goods **200** in the plurality of storage assemblies **121**.

(172) Exemplarily, in this embodiment, only an example in which the blocking mechanism **170** can move into or move out of the loading or unloading end **1215** is used for description. In addition, the blocking mechanism **170** is arranged on one side of the plurality of storage assemblies **121**, working principles of blocking mechanisms **170** with different layouts mentioned in other embodiments are substantially the same as that of the blocking mechanism **170** in this embodiment, and details are not described herein again. In this case, the blocking position of the blocking

mechanism **170** is located at the loading or unloading end **1215**. After the blocking mechanism **170** moves to the loading or unloading end **1215**, the blocking mechanism **170** is at the loading or unloading end **1215** and faces the goods **200**, so as to block the goods **200**.

(173) In an embodiment, the blocking mechanism **170** includes a movable blocking connector **171** and a plurality of blocking assemblies **172** separately connected to the blocking connector **171**, and at least one of the plurality of blocking assemblies **172** corresponds to a same storage assembly **121**. The blocking connector **171** is capable of driving the plurality of blocking assemblies **172** to move into the loading or unloading end **1215**, so as to block the goods **200** in the plurality of storage assemblies **121**. The blocking connector **171** functions as a connection, and is configured to connect the plurality of blocking assemblies **172**. When moving, the blocking connector **171** may synchronously drive the plurality of blocking assemblies **172** to move, so that the plurality of blocking assemblies **172** can move to a loading or unloading end **1215** of a corresponding storage assembly **121** or move out of the loading or unloading end **1215** of the plurality of storage assemblies **121**. Optionally, the blocking connector **171** includes, but is not limited to, a connecting rod or a longboard, and the like.

(174) The plurality of blocking assemblies **172** function as a blocking, and is configured to implement blocking of the goods **200**. When the blocking connector **171** drives the plurality of blocking assemblies **172** to move to the blocking position, the plurality of blocking assemblies **172** are located at the loading or unloading end **1215**. At this time, the end portion of the goods **200** faces the plurality of blocking assemblies **172**, and the plurality of blocking assemblies **172** restrict the goods **200** from moving out of the plurality of storage assemblies **121**. When the blocking connector **171** drives the plurality of blocking assemblies **172** to move to the avoidance position, the plurality of blocking assemblies **172** are separated from the loading or unloading end **1215**. At this time, there is no object to block the end portion of the goods **200**, and the plurality of storage assemblies **121** may be loaded or unloaded.

(175) It can be understood that the avoidance position may be located outside the plurality of blocking assemblies **172**, or may be located at a bottom portion of the plurality of storage assemblies **121**, or at a position flush with the plurality of storage assemblies **121**. The avoidance position is located at the bottom portion of the plurality of storage assemblies **121**, as long as the plurality of blocking assemblies **172** are at a position that does not affect the moving in or moving out of goods **200** of a next layer.

(176) Optionally, the blocking connector **171** may ascend or descend, and when ascending or descending, the blocking connector **171** may drive the plurality of blocking assemblies **172** to ascend or descend synchronously, so that the plurality of blocking assemblies **172** are located at the loading or unloading end **1215** or move out of the loading or unloading end **1215**. In this case, the avoidance position may be located at the bottom portion of the plurality of storage assemblies **121** or the position flush with the plurality of storage assemblies **121**. Certainly, the blocking connector **171** may also move horizontally. When moving horizontally, the blocking connector **171** may drive the plurality of blocking assemblies **172** to move horizontally and synchronously, so that the plurality of blocking assemblies **172** are located at the loading or unloading end **1215** or move out of the loading or unloading end **1215**. In this case, the avoidance position may be located outside the plurality of blocking assemblies **172**. Certainly, the blocking connector **171** may also perform another form of movement, such as one or a combination of rotating motion, swinging motion, moving motion, and the like, as long as the plurality of blocking assemblies **172** can move into or move out of the loading or unloading end **1215**. Exemplarily, in the present disclosure, only an example in which the blocking connector **171** ascends or descends and displaces is used for description. In addition, the avoidance position is located at the bottom portion of the plurality of storage assemblies **121** or the position flush with the plurality of storage assemblies **121**.

(177) In an embodiment, each of the plurality of blocking assemblies **172** includes a stopping member fixedly arranged on the blocking connector **171**, and movement of the blocking connector

171 is capable of driving the stopping member to move into or move out of the loading or unloading end **1215**. In this embodiment, the stopping member is fixedly arranged on the blocking connector **171**, and the movement of the blocking connector **171** may directly drive the stopping member to move, so that the stopping member moves to the blocking position or the avoidance position. For example, when the blocking connector **171** drives the stopping member to ascend, the stopping member may move to the loading or unloading end **1215**, so as to block the goods **200**; and when the blocking connector **171** drives the stopping member to descend, the stopping member may move to the avoidance position, so as to no longer block the goods **200**. Optionally, the stopping member may be a baffle plate, a stopper, a limit post, or another component capable of blocking.

(178) Referring to FIG. **9** and FIG. **10**, in an embodiment, each of the plurality of blocking assemblies **172** includes a swing member **1721** and a blocking member **1722**, one end of the swing member **1721** is rotatably connected to the blocking connector **171**, an other end of the swing member **1721** is mounted with the blocking member **1722**, and a middle portion of the swing member **1721** is rotatably mounted at the loading or unloading end **1215** of the plurality of storage assemblies **121**. When ascending or descending, the blocking connector **171** is capable of driving the swing member **1721** to swing, so that the swing member **1721** drives the blocking member **1722** to move into or move out of the loading or unloading end **1215**.

(179) That is, the blocking connector **171** implements the switching between the blocking position and the avoidance position through the indirect movement of the plurality of blocking assemblies **172**, such as a swinging motion. Specifically, when the blocking connector **171** moves, one end of the swing member **1721** may be driven to move relative to the plurality of storage assemblies **121**, and then an other end of the swing member **1721** may drive the blocking member **1722** to move, so that the blocking member **1722** moves to the avoidance position or the blocking position. A head portion of the swing member **1721** is rotatably connected to the blocking connector **171**, the middle portion of the swing member **1721** is rotatably connected to the plurality of storage assemblies **121**, and a tail portion of the swing member **1721** is connected to the blocking member **1722**. The blocking member **1722** may move to the avoidance position or the blocking position.

(180) Exemplarily, when the blocking connector **171** moves upward along the vertical direction, the blocking connector **171** may drive the blocking member **1722** to move to the blocking position through the swing member **1721**, and when the blocking connector **171** moves downward along the vertical direction, the blocking connector **171** may drive the blocking member **1722** to move to the avoidance position through the swing member **1721**. Optionally, the swing member **1721** is a swing rod, and the blocking member **1722** is a blocking rod.

(181) It should be noted that, the essential spirit of the present disclosure lies in the movement of the blocking connector **171** and the plurality of blocking assemblies **172**, so that the plurality of blocking assemblies **172** respectively move to avoidance positions or blocking positions corresponding to the plurality of storage assemblies **121**. In the foregoing two embodiment, two forms of each of the plurality of blocking assemblies **172** are separately described; and in addition, there are various arrangements of the plurality of blocking assemblies **172**, which cannot all be listed herein, and a linkage manner in the present disclosure is not limited to being implemented by the foregoing specific structures.

(182) In an embodiment, the blocking mechanism **170** further includes a blocking driving member, and an output end of the blocking driving member is connected to the blocking connector **171**, so as to drive the plurality of blocking assemblies **172** to move into or move out of the loading or unloading end **1215**. The blocking driving member is a power source for the movement of the blocking mechanism **170**, and implements the driving of the movement of a blocking moving member. In addition, the blocking driving member outputs linear motion, so that the blocking connector **171** can ascend or descend, and then the blocking connector **171** may drive the plurality of blocking assemblies **172** to move, so that the plurality of blocking assemblies **172** move to the

avoidance position or the blocking position. Optionally, the blocking driving member includes, but is not limited to, an air cylinder, a hydraulic cylinder, a linear motor, or an electric push rod, and may also be another linear driving unit capable of outputting the linear motion. Exemplarily, the blocking driving member is a linear motor. Exemplarily, one end of the blocking driving member is arranged on the chassis **160**. Certainly, in another implementation of the present disclosure, a rotation motor cooperates with a protrusion member to drive.

(183) In an embodiment, a bottom portion of each of the plurality of storage assemblies **121** is provided with a movement space used for a loading or unloading mechanism **620** of a transport system to move into, so as to load goods into or take goods out of the plurality of storage assemblies **121**. Because the plurality of storage assemblies **121** cannot move during loading or unloading, other components such as the carrying mechanism **150** or a matching structure of the loading or unloading apparatus **600** are required to move the goods **200** into the plurality of storage assemblies **121** or take the goods out of the plurality of storage assemblies **121** during loading or unloading. Therefore, a bottom portion of each of the plurality of storage assemblies **121** needs to include a space used for the carrying mechanism **150** and the auxiliary apparatus **300** to extend into, so as to facilitate the goods loading or unloading of the plurality of storage assemblies **121**. When loading goods to the plurality of storage assemblies **121**, the carrying mechanism **150** or the loading or unloading apparatus **600** may extend into the movement space to place the goods **200** on the plurality of storage assemblies **121**, and then exit the movement space; and when unloading goods from the plurality of storage assemblies **121**, the carrying mechanism **150** or the loading or unloading apparatus **600** may extend into the movement space to hold the goods **200** in the plurality of storage assemblies **121** and drive the goods **200** to move out of the plurality of storage assemblies **121**.

(184) In an embodiment, each of the plurality of storage assemblies **121** include a first side plate **1213** and a second side plate **1214** that are arranged on the vertical frame **110**, and the first side plate **1213** and the second side plate **1214** are opposite to each other and surround the movement space. The first side plate **1213** and the second side plate **1214** are arranged at a same height of the vertical frame **110**, and are arranged in parallel. In this way, the first side plate **1213** and the second side plate **1214** can be configured to respectively hold bottom portions of two sides of the goods **200**, so that the goods **200** is flat, and deflection is avoided. A portion between the first side plate **1213** and the second side plate **1214** is a gap, that is, the foregoing movement space, which allows the carrying mechanism **150** or the loading or unloading apparatus **600** to extend into, so as to perform a loading or unloading operation.

(185) Certainly, in another implementation of the present disclosure, each of the plurality of storage assemblies **121** includes a carrier body configured to carry the goods **200** and being provided with a movement space along an entrance or exit direction of the goods **200**, and a size of the movement space along the entrance or exit direction of the goods **200** is less than a size of the carrier body along the entrance or exit direction of the goods **200**. That is, the movement space in this case is an opening of the carrier body. The goods **200** are carried by the carrier body, and the movement space of the carrier body may also allow the carrying mechanism **150** or the loading or unloading apparatus **600** to extend into, so as to perform the loading or unloading operation.

(186) Referring to FIG. 9 and FIG. 11, the second embodiment of the present disclosure further provides a transport system including a loading or unloading apparatus **600** and the transport robot **100** in the foregoing embodiment. The loading or unloading apparatus **600** is configured to convey the goods **200** to the transport robot **100** or unload the goods **200** on the transport robot **100**. The loading or unloading apparatus **600** includes an upright frame **610** extending along a vertical direction and a plurality of loading or unloading mechanisms **620** arranged on the upright frame **610** at intervals along the vertical direction, and a manner in which the plurality of loading or unloading mechanisms **620** are arranged at intervals is the same as a manner in which a plurality of storage assemblies **121** are arranged at intervals. After the transport robot **100** is docked with the

loading or unloading apparatus **600**, the plurality of loading or unloading mechanisms **620** are capable of respectively conveying, at different heights, the goods **200** to the plurality of storage assemblies **121** or unloading the goods **200** in the plurality of storage assemblies **121**.

(187) The loading or unloading apparatus **600** can implement synchronous unloading or synchronous loading of the goods **200**. The loading or unloading apparatus **600** is mounted at an unloading position or a loading position. In a case that the loading or unloading apparatus **600** is unloaded, the loading or unloading apparatus **600** is at the unloading position; and in a case that the loading or unloading apparatus **600** is loaded, the loading or unloading apparatus **600** is at the loading position. In the present disclosure, only an example in which the loading or unloading apparatus **600** is at the unloading position is used for description. The loading or unloading apparatus **600** is located at the unloading position. After the transport robot **100** completes loading at the loading position, the transport robot **100** moves to the unloading position. At this time, the transport robot **100** is docked with the loading or unloading apparatus **600**, and the loading or unloading apparatus **600** may receive and pick the goods **200** in the plurality of storage assemblies **121** in the transport robot **100**. Certainly, the reverse transport of the goods **200** may also be implemented at this position, that is, after the transport robot **100** is docked with the loading or unloading apparatus **600**, the loading or unloading apparatus **600** may transfer the goods **200** to the plurality of storage assemblies **121**.

(188) Specifically, the upright frame **610** plays a supporting role, and is configured to support the plurality of loading or unloading mechanisms **620** configured to transport the goods **200**. The loading or unloading apparatus **600** includes a same quantity of loading or unloading mechanisms **620** as the plurality of storage assemblies **121**. The plurality of loading or unloading mechanisms **620** may separately convey, at different heights, the goods **200** to the transport robot **100**, or unload the goods **200** on the transport robot **100**, which greatly shortens the waiting time of the transport robot **100** during a loading or unloading process. In addition, heights at which the plurality of loading or unloading mechanisms **620** are located are consistent with heights at which corresponding storage assemblies **121** are located. After the transport robot **100** is docked with the loading or unloading apparatus **600**, the plurality of storage assemblies **121** and the plurality of loading or unloading mechanisms **620** are at same heights, and the plurality of loading or unloading mechanisms **620** may convey the goods **200** to all storage assemblies **121** on the transport robot **100** at one time, or the plurality of loading or unloading mechanisms **620** may implement one-time removal of goods **200** from all storage assemblies **121** on the transport robot **100**. Certainly, in specific working conditions, one or more loading or unloading mechanisms **620** in the loading or unloading apparatus **600** may simultaneously convey the goods **200** to the transport robot **100** or unload the goods **200** on the transport robot **100**.

(189) Each of the plurality of loading or unloading mechanisms **620** may act independently to convey the goods **200** to the transport robot **100** or unload the goods **200** on the transport robot **100**. Referring to FIG. 10, FIG. 11, FIG. 12, and FIG. 13, in an embodiment, each of the plurality of loading or unloading mechanisms **620** includes a bracket **621**, a loading or unloading assembly **622**, and a loading or unloading driving member **623**, a plurality of brackets **621** are arranged on the upright frame **610** at intervals along the vertical direction, the loading or unloading driving member **623** and the loading or unloading assembly **622** are respectively arranged on corresponding brackets **621**, the loading or unloading assembly **622** is connected to the loading or unloading driving member **623**, and the loading or unloading assembly **622** is configured to convey the goods **200** to the plurality of storage assemblies **121** or unload the goods **200** in the plurality of storage assemblies **121**. The loading or unloading driving member **623** may allow a corresponding loading or unloading assembly **622** to individually convey the goods **200** to the transport robot **100** or unload the goods **200** on the transport robot **100**.

(190) Further, as shown in FIG. 10 to FIG. 13, the loading or unloading assembly **622** includes a chain **6221** and a protrusion **6222**, the chain **6221** is rotatably arranged on the bracket **621** along a

loading or unloading direction, and the protrusion **6222** is fixedly arranged on the chain **6221**. The loading or unloading driving member **623** includes a driving motor in driving connection with the chain **6221**; and the chain **6221** may carry the goods **200**. When the driving motor drives the chain **6221** to rotate, the protrusion **6222** pushes a bottom portion of the goods **200**, so as to push the goods **200** to the transport robot **100**, or the protrusion **6222** pulls a bottom portion of the goods **200**, so as to pull the goods **200** from the transport robot **100** to the chain **6221**, or the protrusion **6222** blocks the bottom portion of the goods **200**, and the goods **200** are transferred to the chain **6221** when the transport robot **100** moves away from the loading or unloading apparatus **600**. Specifically, the chain **6221** is arranged on two sprockets arranged at intervals along the loading or unloading direction, and an output shaft of the driving motor is in driving connection with one of the two sprockets. When rotating, the driving motor drives the chain **6221** to operate, and the protrusion **6222** pushes the bottom portion of the goods **200**, so as to push the goods **200** to the transport robot **100**, or the protrusion **6222** pulls the bottom portion of the goods **200**, so as to pull the goods **200** from the transport robot **100** to the chain **6221**. Furthermore, each of the plurality of loading or unloading mechanisms **620** includes two sets of loading or unloading assemblies **622**, the two sets of loading or unloading assemblies **622** are arranged on the bracket **621** in parallel and at intervals, and the driving motor is in driving connection with two chains **6221**. The two sets of loading or unloading assemblies **622** can increase the stability during the loading or unloading of the goods **200**. In an embodiment of the present disclosure, as shown in FIG. 13, each of the plurality of loading or unloading mechanisms **620** further includes a synchronization rod **624**, the two chains **6221** are separately in driving connection with the synchronization rod **624**, and the driving motor is in driving connection with one of the two chains **6221**. Specifically, the synchronization rod **624** connects two sprockets arranged at intervals along a horizontal direction perpendicular to the loading or unloading direction, thereby ensuring that the two chains **6221** rotate synchronously. It can be understood that the chain **6221** in the foregoing embodiment only plays a role of driving and carrying goods. In another embodiment of the present disclosure, a belt, a timing belt, or the like, are used to replace the chain.

(191) In another embodiment, as shown in FIG. 10, FIG. 11, FIG. 14, and FIG. 15, each of the plurality of loading or unloading mechanisms **620** includes a loading or unloading cross arm **625** and a push-pull assembly **626**, one ends of a plurality of loading or unloading cross arms **625** are arranged on the upright frame **610** at intervals along the vertical direction, and the push-pull assembly **626** is rotatably arranged at other ends corresponding to the plurality of loading or unloading cross arms **625**. When rotating, the push-pull assembly **626** includes a push-pull position and an avoidance position, and when rotating to the push-pull position, push-pull assembly **626** conveys the goods **200** to the transport robot **100** or pulls down the goods **200** on the transport robot **100**. When the push-pull assembly **626** rotates to the avoidance position, the push-pull assembly **626** avoids the goods **200**. It can be understood that when pushing or pulling the goods **200**, the push-pull assembly **626** may push or pull a top portion, a middle portion, or a bottom portion of the goods **200**. In an embodiment of the present disclosure, two loading or unloading assemblies **620** are arranged at intervals in a same horizontal direction of the upright frame **610**, and two push-pull assemblies **626** in the same horizontal direction separately rotate to the push-pull position or the avoidance position. The two push-pull assemblies **626** in the same horizontal direction respectively drive two sides of the goods **200** along the loading or unloading direction. The two push-pull assemblies **626** push or pull the two sides of the goods **200** synchronously, which can effectively ensure the stability of a push-pull process of the goods **200**. Further, the two push-pull assemblies **626** in the same horizontal direction push/pull two sides of the middle portion of the goods **200** synchronously along the loading or unloading direction. It can be understood that the two push-pull assemblies **626** in the same horizontal direction rotate to the push-pull position or the avoidance position synchronously, or rotate to the push-pull position or the avoidance position successively. In another embodiment of the present disclosure, only one loading or unloading

mechanism **620** is arranged in a same height direction of the upright frame **610**, and the one loading or unloading mechanism **620** pushes or pulls the top portion or the bottom portion of the goods **200** when pushing or pulling the goods **200**.

(192) In an implementation, as shown in FIG. **14** and FIG. **15**, the push-pull assembly **626** includes a push-pull rod **6261** and a push-pull motor **6262**, the push-pull motor **6262** is arranged at one ends of the plurality of loading or unloading cross arms **625** away from the upright frame **610**, the push-pull rod **6261** is arranged on an output shaft of the push-pull motor **6262**, and the push-pull motor **6262** is configured to drive the push-pull rod **6261** to rotate to the push-pull position or the avoidance position. Two push-pull rods **6261** may separately be rotated to the push-pull position under the driving of the push-pull motor **6262**, so as to pull the goods **200** out of the transport robot **100** or push the goods **200** to the transport robot **100**. It can be understood that the function of the push-pull motor **6262** is to drive the push-pull rod **6261** to rotate, and the push-pull rod **6261** is directly arranged on the output shaft of the push-pull motor **6262**, or the push-pull rod **6261** is connected to the output shaft of the push-pull motor **6262** through a transmission mechanism, as long as the push-pull motor **6262** can drive the push-pull rod **6261** to rotate to the push-pull position or the avoidance position.

(193) In an embodiment, all loading or unloading mechanisms **620** in the loading or unloading apparatus **600** act synchronously to convey, at different heights, the goods **200** to the transport robot **100** or unload the goods **200** on the transport robot **100**, or some of the plurality of loading or unloading mechanisms **620** in the loading or unloading apparatus **600** act independently to convey, at specified heights, the goods **200** to the transport robot **100** or unload the goods **200** on the transport robot **100**. As shown in FIG. **16** and FIG. **17**, in an implementation, the loading or unloading apparatus **600** further includes an adjustment drive mechanism **630** configured to drive the upright frame **610** to approach or move away from the transport robot **100** along the loading or unloading direction, and when the adjustment drive mechanism **630** drives the upright frame **610** to approach or move away from the transport robot **100**, the plurality of loading or unloading mechanisms **620** convey the goods **200** to the transport robot **100** or unload the goods **200** on the transport robot **100**. The loading or unloading apparatus **600** provided in this embodiment can remove all the goods **200** or specified goods **200** on the transport robot **100** at one time, or simultaneously convey a plurality of goods **200** to the transport robot **100**. In an implementation, the adjustment drive mechanism **630** adopts a driving structure in the form of a motor and a belt.

(194) In an embodiment of the present disclosure, the loading or unloading apparatus **600** further includes a temporary storage shelving unit **640**, the upright frame **610** is movably arranged on the temporary storage shelving unit **640** along a horizontal direction, and the adjustment drive mechanism **630** is configured to drive the upright frame **610** to move relative to the temporary storage shelving unit **640** along the horizontal direction. The temporary storage shelving unit **640** includes a shelving unit with a plurality of layers along the vertical direction, and the plurality of loading or unloading mechanisms **620** are configured to pull goods **200** at different heights on the transport robot **100** to corresponding layers of the shelving unit on the temporary storage shelving unit **640**, or the plurality of loading or unloading mechanisms **620** are configured to push goods **200** on the plurality of layers of the shelving unit to the transport robot **100**. The temporary storage shelving unit **640** can temporarily store the goods **200** unloaded from the transport robot **100** by the loading or unloading apparatus **600**, or temporarily store the to-be-transported goods **200** which are transported to the transport robot **100**. In an implementation, the temporary storage shelving unit **640** includes a temporary storage roller **641** with a plurality of layers arranged along the vertical direction, and each layer of the temporary storage roller **641** is capable of individually transporting the goods **200** along the loading or unloading direction. Optionally, each layer of the temporary storage roller **641** can simultaneously carry a plurality of goods **200**.

(195) In an embodiment, the loading or unloading apparatus **600** further includes a movable base arranged at a bottom portion of the upright frame **610**. The loading or unloading apparatus **600**

further includes a movable base arranged at the bottom portion of the upright frame **610**. The movable base can drive the loading or unloading apparatus **600** to move, which greatly improves the adaptability of the loading or unloading apparatus **600** to actual working conditions. In this way, the loading or unloading apparatus **600** can easily move to the loading position, the unloading position, or any other position, to work with the transport robot **100**. Optionally, a structure of the base is exactly the same as that of the chassis **160** of the transport robot **100**, and details are not described herein again.

(196) Referring to FIG. **9** and FIG. **11**, in an embodiment, the transport system further includes a conveying apparatus **500** and a lifting apparatus **400** that is arranged between the loading or unloading apparatus **600** and the conveying apparatus **500**, and the lifting apparatus **400** is configured to ascend or descend along the vertical direction, so as to be docked with each of the plurality of loading or unloading mechanisms **620** and the conveying apparatus **500**. The lifting apparatus **400** is capable of receiving and picking the goods **200** of the plurality of loading or unloading mechanisms **620** and transferring the goods to the conveying apparatus **500**; or the lifting apparatus **400** is capable of receiving and picking goods **200** of the conveying apparatus **500** and transferring the goods to the plurality of loading or unloading mechanisms **620**.

(197) The lifting apparatus **400** is configured to receive and pick the goods **200** of the plurality of loading or unloading mechanisms **620** or transport the goods **200** to the plurality of loading or unloading mechanisms **620**. Because the plurality of loading or unloading mechanisms **620** are arranged at intervals along the vertical direction, to facilitate the goods loading or unloading of the loading or unloading apparatus **600**, the lifting apparatus **400** needs to move to a loading or unloading mechanism **620** at a corresponding position, so as to perform a corresponding operation. The conveying apparatus **500** is configured to convey the goods **200**, may transport away goods **200** unloaded by the lifting apparatus **400**, and may also transport to-be-loaded goods **200** to the lifting apparatus **400**. Optionally, the conveying apparatus **500** may be of a structure that can implement the horizontal transport, such as a conveyor belt structure, an assembly line, a conveying roller structure, or a roller structure, or the like. Exemplarily, the conveying apparatus **500** is of an assembly line structure, and specifically, when unloading, the lifting apparatus **400** ascends to one side of a loading or unloading mechanism **620**, after receiving the goods **200** of the loading or unloading mechanism **620**, the lifting apparatus **400** descends, and transfers the goods **200** to the conveying apparatus **500**, and the goods are transported away by the conveying apparatus **500**. Subsequently, the lifting apparatus **400** further ascends to another loading or unloading mechanism **620**, and this process is repeated until all the goods **200** on the plurality of loading or unloading mechanisms **620** are transported away. When loading, after the lifting apparatus **400** descends and receives and picks the goods **200** conveyed by the conveying apparatus **500**, the lifting apparatus **400** ascends to one side of a loading or unloading mechanism **620** and transfers the goods **200** to the loading or unloading mechanism **620**; and subsequently, the lifting apparatus **400** further descends to the conveying apparatus **500**, and this process is repeated until the plurality of loading or unloading mechanisms **620** are loaded with the goods **200**.

(198) In an embodiment, the lifting apparatus **400** includes a lifting frame **410** along the vertical direction, a moving mechanism **420** arranged on the lifting frame **410**, and a transfer mechanism **430** with at least one layer arranged on the moving mechanism **420**, and the moving mechanism **420** may ascend or descend along the lifting frame **410** and drive the transfer mechanism **430** with at least one layer to move, so as to receive and pick or transfer the goods **200** to the plurality of loading or unloading mechanisms **620**. The lifting frame **410** has a bearing function, and is configured to bear the moving mechanism **420** and the transfer mechanism **430** with at least one layer. Optionally, a bottom portion of the lifting frame **410** may also be provided with rotating wheels, so as to adapt to different applications. The transfer mechanism **430** with at least one layer is configured to carry the goods **200** and implement the transfer of the goods **200** between a high position such as a loading or unloading mechanism **620** and a low position such as the conveying

apparatus **500**. The moving mechanism **420** is arranged on the lifting frame **410** along the vertical direction, and may output movement in the vertical direction, so as to drive the transfer mechanism **430** with at least one layer to ascend or descend.

(199) It can be understood that the moving mechanism **420** is configured to implement the ascending or descending motion of the transfer mechanism **430** with at least one layer along the vertical direction. A specific structure of the moving mechanism **420** may be a telescopic rod structure, a chain transmission structure, a driving transmission structure, or the like, and may also be another structure capable of enabling the carrying mechanism **150** to ascend or descend. Exemplarily, a specific structure of the moving mechanism **420** is the same as a structure of the lifting mechanism **140** of the transport robot **100**, and details are not described herein again. Certainly, the specific structure of the moving mechanism **420** may also be different from the structure of the lifting mechanism **140** of the transport robot **100**, as long as the moving mechanism **420** can implement the ascending or descending motion.

(200) Exemplarily, there is a transfer mechanism **430** with one layer, and the transfer mechanism **430** with one layer receives and picks goods **200** from one loading or unloading mechanism **620** at one time, or transfers goods **200** to one loading or unloading mechanism **620** at one time. Certainly, in another implementation of the present disclosure, in a case that there is a transfer mechanism **430** with at least two layers, the transfer mechanism **430** with at least two layers may remove goods **200** of at least two loading or unloading mechanisms **620** at one time, or transfer goods **200** to at least two loading or unloading mechanisms **620**, so as to improve the efficiency of turnover of the goods **200**.

(201) In an embodiment, the transfer mechanism **430** with at least one layer includes a transfer base **431** arranged on the moving mechanism **420** and a transfer portion **432** movably arranged on the transfer base **431**, and the transfer portion **432** may drive the goods **200** to move, and may receive and pick or transfer the goods **200** to at least one of the plurality of loading or unloading mechanisms **620**. The transfer base **431** plays a bearing role and is configured to carry the transfer portion **432**, so as to mount the transfer portion **432** on the moving mechanism **420**. When the moving mechanism **420** ascends or descends, the transfer base **431** may drive the transfer portion **432** to ascend or descend synchronously, so as to implement the loading or unloading of the goods **200**.

(202) Optionally, the transfer portion **432** is of a structure that can implement horizontal transport, such as a conveyor belt structure, an assembly line, a conveyor roller structure, a roller structure, or the like. Exemplarily, the transfer portion **432** is of a rolling shaft structure, and specifically includes a plurality of rolling shafts, and each of the plurality of rolling shafts includes a built-in rolling motor to drive the each of the plurality of rolling shafts to rotate, thereby implementing the transport of the goods **200**. It should be noted that, there are various structures that can implement the horizontal transport of the goods **200**, which cannot all be listed herein, and the transfer portion **432** in the present disclosure is not limited to being implemented by the foregoing specific structures.

(203) The transfer portion **432** may receive and pick the goods **200** of one loading or unloading mechanism **620** at one time, as mentioned above. The transfer portion **432** may also receive and pick the goods **200** of a plurality of loading or unloading mechanisms **620** at one time, and the moving mechanism **420** may receive and pick the goods **200** of the plurality of loading or unloading mechanisms **620** layer by layer, and then convey the goods to the conveying apparatus **500** together for transport after receiving and picking the goods. Exemplarily, the moving mechanism **420** drives the transfer portion **432** to ascend to a top portion. After receiving and picking goods **200** of one loading or unloading mechanism **620**, the transfer portion **432** descends one layer to receive and pick goods **200** of one loading or unloading mechanism **620**. After the transfer portion **432** is full or the goods **200** of the plurality of loading or unloading mechanisms **620** are received, the moving mechanism **420** drives the transfer portion **432** to descend to a

position of the conveying apparatus **500**, and the transfer portion **432** transfers all the goods **200** thereon to the conveying apparatus **500**. Certainly, the moving mechanism **420** may move layer by layer from bottom to top, a principle thereof is substantially the same as a principle from top to bottom, and details are not described herein again.

(204) Certainly, the transfer portion **432** may also receive and pick a plurality of goods **200** transferred by the conveying apparatus **500** at one time, and then transfer the goods to the plurality of loading or unloading mechanisms **620** layer by layer, a principle thereof is substantially the same as the foregoing principle of goods unloading, and details are not described herein again.

(205) In an embodiment, the transport system further includes a control center, components of the transport system perform a coordinated action under the control of the control center, and the control center of the transport system maintains a communication connection with an external server. The control center may identify information of the to-be-transported goods **200**, and the control center may obtain information of a loading position and an unloading position corresponding to each piece of the to-be-transported goods **200**. The control center coordinates and controls the components according to the obtained information, so as to efficiently complete the transport of the goods **200**.

(206) In the transport robot **100** and the transport system in this embodiment, when transporting goods, a blocking mechanism **170** moves to a blocking position and may be in abutment with goods **200** in a plurality of storage assemblies **121**, so as to restrict the goods **200** from sliding out of the plurality of storage assemblies **121**. Therefore, the goods **200** are prevented from sliding out of the plurality of storage assemblies **121** during a transport process of the transport robot **100**, the safety of the goods **200** is ensured, a risk of sliding out is avoided, and the transport efficiency is improved. In addition, when the transport robot **100** loads or unloads goods, the blocking mechanism **170** moves to an avoidance position. At this time, goods **200** may be loaded into the plurality of storage assemblies **121**, and the goods **200** in the plurality of storage assemblies **121** may also be removed, which does not hinder a loading or unloading operation of the transport robot **100**, and is convenient for use.

(207) Based on the transport robot **100** of the foregoing two embodiments, the present disclosure further provides a transport method of the transport robot **100**, which is applicable to the transport robot **100** in the foregoing two embodiments. The transport method includes the following operations: a controller receives a first loading or unloading instruction; the controller controls the transport robot **100** to move to a first loading or unloading position according to the first loading or unloading instruction; in a case that the controller confirms that the first loading or unloading position is a loading position, the controller controls a carrying mechanism **150** to transfer goods **200** to the plurality of storage assemblies **121** of a storage mechanism **120**; and in a case that the controller confirms that the first loading or unloading position is an unloading position, the controller controls the transport robot **100** to unload goods at the unloading position.

(208) Components of the transport robot **100** perform a coordinated action under the control of the controller, and the controller of the transport robot **100** maintains a communication connection with a control center of the transport system or an external server. The transport robot **100** may identify information of to-be-transported goods **200**, and the transport robot **100** may obtain information of a loading position and an unloading position corresponding to each piece of the to-be-transported goods **200**. The transport robot **100** coordinates and controls the components according to the obtained information, so as to efficiently complete the transport of the goods **200**. Optionally, the controller includes, but is not limited to, a CPU, and may also be another component that can implement control.

(209) When loading or unloading is required, the controller receives the first loading or unloading instruction, and then the controller controls, according to the first loading or unloading instruction, the transport robot **100** to move, so that the transport robot **100** moves at the first loading or unloading position. The first loading or unloading position includes a loading position and an

unloading position, the loading position is defined as a position at which a shelving unit is located, and the unloading position is at which a plurality of transport mechanisms **320** or a plurality of loading or unloading mechanisms **620** are located. It can be understood that the loading position and the unloading position may be interchanged, that is, the transport robot **100** may load at the unloading position and unload at the loading position.

(210) Generally, the transport robot **100** may be loaded by the carrying mechanism **150** at the loading position, and unloaded by the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620** at the unloading position. After the controller controls, according to the first loading or unloading instruction, the transport robot **100** to move to the loading position, the controller may control the lifting mechanism **140** to drive the carrying mechanism **150** to ascend or descend, so that the carrying mechanism **150** can pick goods on the shelving unit. Then, the lifting mechanism **140** drives the carrying mechanism **150** to ascend or descend, so as to transfer the goods **200** in the carrying mechanism **150** to the plurality of storage assemblies **121**, and implement the loading of the goods **200**. This process is repeated until the plurality of storage assemblies **121** store the goods **200**. After the controller moves from the loading position to the unloading position according to the first unloading instruction, the controller controls the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620** to receive and pick the goods **200** in the plurality of storage assemblies **121**, so as to implement the unloading of the goods **200**.

(211) Certainly, the loading or unloading process may also be performed in a reverse direction, that is, the transport robot **100** is loaded at the unloading position by the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620** at the unloading position, and is unloaded by the carrying mechanism **150** at the loading position. After the controller controls, according to the first loading or unloading instruction, the transport robot **100** to move to the unloading position, the controller controls the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620** to transfer the goods **200** thereon to corresponding storage assemblies **121**, so as to implement the loading of the goods **200**. After the transport robot **100** is filled with the goods **200**, the controller moves from the unloading position to the loading position according to the first unloading instruction, the controller may control the lifting mechanism **140** to drive the carrying mechanism **150** to ascend or descend, so that the carrying mechanism **150** can pick goods in the plurality of storage assemblies **121**, and then the lifting mechanism **140** drives the carrying mechanism **150** to ascend or descend, so as to remove the goods **200** in the carrying mechanism **150**. This process is repeated until the goods **200** of the plurality of storage assemblies **121** are taken away, and the unloading of the goods **200** is implemented.

(212) It is worth noting that after controlling the transport robot **100** to move to the first loading or unloading position, the controller needs to determine whether the first loading or unloading position is the loading position or the unloading position. For example, in a case that there are no goods **200** in the transport robot **100**, after the transport robot **100** moves to the first loading or unloading position, in a case that the first loading or unloading position is the loading position, the carrying mechanism **150** loads the goods into the plurality of storage assemblies **121** in this case; and in a case that there are goods **200** in the transport robot **100**, after the transport robot **100** moves to the first loading or unloading position, in a case that the first loading or unloading position is the unloading position, the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620** unload the goods in this case.

(213) In this embodiment described above, the transport method can implement the automatic transport of the goods **200**, so that a problem of high cost and low efficiency in a current transport method is effectively resolved, the cost of the loading or unloading of the goods **200** is reduced, and the efficiency of the loading or unloading of the goods **200** is greatly improved. In addition, the carrying mechanism **150** moves to different heights under the driving of the lifting mechanism **140**,

so that the to-be-transported goods **200** can be delivered to a plurality of storage assemblies **121** at different heights in the storage mechanism **120**, which has strong versatility and reduces the floor space.

(214) In an embodiment, when the transport robot **100** is unloading, a plurality of storage assemblies **121** are capable of moving synchronously to perform a synchronous unloading action, and the first loading or unloading instruction includes a first unloading instruction; and that the controller controls the transport robot **100** to unload goods at the unloading position includes the following operation: the controller receives the first unloading instruction, and the controller controls, according to the first unloading instruction, at least two of the plurality of storage assemblies **121** to simultaneously unload goods.

(215) In a case that the transport robot **100** is the transport robot **100** in the first embodiment, the plurality of storage assemblies **121** in the transport robot **100** can implement synchronous unloading. Specifically, in a case that the first loading or unloading instruction received by the controller is the first unloading instruction, the controller controls, according to the first unloading instruction, the transport robot **100** to move from the loading position to the unloading position. The unloading position in this case corresponds to the auxiliary apparatus **300** of the transport system. In addition, the plurality of storage assemblies **121** are respectively docked with the plurality of transport mechanisms **320**. When the controller controls at least two of the plurality of storage assemblies **121** to unload simultaneously, at least two of the plurality of transport mechanisms **320** corresponding to the at least two of the plurality of storage assemblies **121** may receive and pick the goods **200** removed from the at least two of the plurality of storage assemblies **121**, so as to complete the unloading operation of the transport robot **100**.

(216) In an embodiment, when the transport robot **100** is loading, a plurality of storage assemblies **121** are capable of moving synchronously to perform a synchronous loading action, and the first loading or unloading instruction includes a first loading instruction; and that the controller controls the transport robot **100** to load goods at the loading position includes the following operation: the controller receives the first loading instruction, and the controller controls, according to the first loading instruction, the auxiliary apparatus **300** to simultaneously load goods to at least two of the plurality of storage assemblies **121**.

(217) In a case that the transport robot **100** is the transport robot **100** in the first embodiment, the plurality of storage assemblies **121** in the transport robot **100** can implement synchronous loading. In a case that the transport robot **100** needs to load goods, a loading operation is performed by the auxiliary apparatus **300**. Specifically, in a case that the first loading or unloading instruction received by the controller is the first loading instruction, the controller controls, according to the first loading instruction, the transport robot **100** to move from the unloading position to the loading position. In this case, the loading position is opposite to that in the foregoing embodiments, and the unloading position is opposite to that in the foregoing embodiments. It indicates that the loading position in this case corresponds to the auxiliary apparatus **300** of the transport system. In addition, the plurality of storage assemblies **121** are respectively docked with the plurality of transport mechanisms **320**. The controller controls a plurality of transport mechanisms **320** of the auxiliary apparatus **300** to move goods into a plurality of storage assemblies **121** at corresponding positions, so that the synchronous loading of the plurality of storage assemblies **121** is implemented, and the loading operation of the transport robot **100** is completed.

(218) In an embodiment, the transport robot **100** includes a linkage mechanism **130** electrically connected to the controller, and that the controller controls, according to the first unloading instruction, at least two of the plurality of storage assemblies **121** to simultaneously unload goods includes the following operation: the controller controls, according to the first unloading instruction, the linkage mechanism **130** to drive the at least two of the plurality of storage assemblies **121** to simultaneously move.

(219) The controller is electrically connected to the linkage mechanism **130**, and is further

electrically connected to a linkage driving member **132** of the linkage mechanism **130**. The controller may control the movement of the linkage driving member **132**, so that the linkage mechanism **130** can drive the at least two of the plurality of storage assemblies **121** to move synchronously to perform an unloading action. It can be understood that, after the controller receives the first unloading instruction, and after the plurality of storage assemblies **121** of the transport robot **100** are docked with the plurality of transport mechanisms **320** of the auxiliary apparatus **300**, the controller controls, through the linkage driving member **132**, the linkage mechanism **130** to drive the at least two of the plurality of storage assemblies **121** to be lifted up synchronously, so that the goods **200** in the plurality of storage assemblies **121** slide out of the plurality of storage assemblies **121** and move to corresponding transport mechanisms **320**, and an unloading operation of the transport robot **100** is completed.

(220) In an embodiment, the transport robot **100** further includes a blocking mechanism **170** electrically connected to the controller and capable of switching between a blocking position and an avoidance position, and the first loading or unloading instruction includes a first unloading instruction; and that the controller controls the transport robot **100** to unload goods at the unloading position further includes the following operation: the controller receives the first unloading instruction, and the controller controls, according to the first unloading instruction, the blocking mechanism **170** to move to the avoidance position, so that the plurality of storage assemblies **121** are in an unloadable state.

(221) In a case that the transport robot **100** is the transport robot **100** in the second embodiment, the transport robot **100** may block the goods **200** in the plurality of storage assemblies **121**, to prevent the goods **200** from sliding out of the plurality of storage assemblies **121** during a process of transporting the goods **200** by the transport robot **100**, so as to protect the goods **200** in the plurality of storage assemblies **121** and prevent the goods **200** from being damaged. Specifically, the transport robot **100** of the present disclosure blocks the goods **200** in the plurality of storage assemblies **121** by the blocking mechanism **170** at the blocking position during a transport process. When unloading is required, the blocking mechanism **170** moves from the blocking position to the avoidance position, and at this time, the loading or unloading apparatus **600** may perform an unloading operation on the plurality of storage assemblies **121**.

(222) Because a structure and a working principle of the blocking mechanism **170** have been described in detail in the second embodiment, details are not described herein again, and the description herein is only from a perspective of a control method. Specifically, after the controller receives the first unloading instruction, the controller controls, according to the first unloading instruction, the transport robot **100** to move to the unloading position. Subsequently, the controller controls the blocking mechanism **170** to move from the blocking position to the avoidance position, the blocking mechanism **170** no longer blocks the goods **200** in the plurality of storage assemblies **121**, and the goods **200** in the plurality of storage assemblies **121** may be moved out and are in the unloadable state, which is specifically implemented by the plurality of loading or unloading mechanisms **620** of the loading or unloading apparatus **600**. Specifically, the transport robot **100** is at the unloading position. At this time, the transport robot **100** approaches the loading or unloading apparatus **600**, and the plurality of storage assemblies **121** are respectively docked with the plurality of loading or unloading mechanisms **620**. Subsequently, the controller controls the blocking mechanism **170** to move from the blocking position to the avoidance position, the blocking mechanism **170** no longer blocks the goods **200** in the plurality of storage assemblies **121**, and the plurality of loading or unloading mechanisms **620** may extend into the plurality of storage assemblies **121**, and receive and pick and remove the goods **200** in the plurality of storage assemblies **121**, so that the unloading operation of the transport robot **100** is performed.

(223) In an embodiment, the transport robot **100** further includes a blocking mechanism **170** electrically connected to the controller and capable of switching between a blocking position and an avoidance position, and the first loading or unloading instruction includes a first loading

instruction; and the transport method further includes the following operation: the controller receives the first loading instruction, and the controller controls, according to the first loading instruction, the blocking mechanism **170** to move to the avoidance position, so that the plurality of storage assemblies **121** are in a loadable state.

(224) In a case that the transport robot **100** is the transport robot **100** in the second embodiment, the transport robot **100** may block the goods **200** in the plurality of storage assemblies **121**, to prevent the goods **200** from sliding out of the plurality of storage assemblies **121** during a process of transporting the goods **200** by the transport robot **100**, so as to protect the goods **200** in the plurality of storage assemblies **121** and prevent the goods **200** from being damaged. Specifically, during a loading process of the transport robot **100** of the present disclosure, the blocking mechanism **170** moves from the blocking position to the avoidance position. At this time, the plurality of loading or unloading mechanisms **620** may perform a loading operation on the plurality of storage assemblies **121**. Specifically, the to-be-transported goods **200** are placed on the plurality of loading or unloading mechanisms **620**, and then the blocking mechanism **170** moves from the blocking position to the avoidance position, so that the plurality of loading or unloading mechanisms **620** can extend into the plurality of storage assemblies **121**. Subsequently, the goods **200** are placed in the plurality of storage assemblies **121** by the plurality of loading or unloading mechanisms **620** and then removed from the plurality of storage assemblies **121**.

(225) In an embodiment, the blocking mechanism **170** includes a plurality of blocking assemblies **172** respectively corresponding to a plurality of storage assemblies **121**, and that the controller controls, according to the first unloading instruction, the blocking mechanism **170** to move to the avoidance position includes the following operation: the controller controls, according to the first unloading instruction, a blocking assembly **172** at a specified position to move to a corresponding avoidance position, so that a storage assembly **121** at the specified position is in the unloadable state; or the controller controls, according to the first unloading instruction, the plurality of blocking assemblies **172** to respectively move into corresponding avoidance positions, so that at least two of the plurality of storage assemblies **121** are in the unloadable state.

(226) The controller is electrically connected to the blocking mechanism **170**, and is further electrically connected to a blocking driving member of the blocking mechanism **170**. The controller may control the movement of the blocking driving member, thereby causing at least one of the plurality of blocking assemblies **172** in the blocking mechanism **170** to move. It can be understood that in a case that the controller controls the movement of one or more specified blocking assemblies **172** in the blocking mechanism **170**, blocking assemblies **172** at storage assemblies **121** corresponding to the one or more specified blocking assemblies **172** move from the blocking position to the avoidance position, so that the storage assemblies **121** corresponding to the one or more specified blocking assemblies **172** are in the unloadable state. In this case, the plurality of loading or unloading mechanisms **620** may receive and pick the goods **200** in the storage assemblies **121** corresponding to the one or more specified blocking assemblies **172**. Certainly, the controller may also control all blocking assemblies **172** in the blocking mechanism **170** to move from the blocking position to the avoidance position, so that the plurality of storage assemblies **121** are in the unloadable state. In this case, the plurality of loading or unloading mechanisms **620** may receive and pick the goods **200** in corresponding storage assemblies **121**.

(227) In an embodiment, the plurality of storage assemblies **121** include a loading or unloading end **1215** configured to load or unload the goods **200**, and the transport method further includes the following operation: after the controller receives the first unloading instruction, the controller controls the carrying mechanism **150** to avoid the loading or unloading end **1215**.

(228) That is, after the controller receives the first unloading instruction, the controller controls the carrying mechanism **150** to move to a specified position, so that the carrying mechanism **150** moves away from the loading or unloading end, so as to avoid the loading or unloading of the goods **200** by the plurality of transport mechanisms **320** or the plurality of loading or unloading

mechanisms **620**. It can be understood that the loading or unloading end **1215** is an opening used for loading or unloading the goods **200**, a specific form thereof has been mentioned above, and details are not described herein again. In a case that the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620** are configured to unload goods, the carrying mechanism **150** needs to avoid the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620**, so as to avoid interference. Specifically, the controller may control the carrying mechanism **150** to move to a specified position. The specified position herein may be a topmost position of the transport robot **100** or a position higher than the plurality of transport mechanisms **320** and the plurality of loading or unloading mechanisms **620**, or may be a position different from the loading or unloading end **1215**.

(229) Specifically, in a case that the loading or unloading end **1215** is arranged on a same side as the carrying mechanism **150**, the controller may control the carrying mechanism **150** to ascend to a top end of the transport robot **100**, and may also control the carrying mechanism **150** to ascend to a position higher than the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620** or to move to an other side of the vertical frame **110**, so that the loading or unloading end **1215** is arranged away from the carrying mechanism **150**. In this way, the carrying mechanism **150** can move away from the loading or unloading end **1215**, and the interference between the carrying mechanism **150** and the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620** at the loading or unloading end **1215** can be avoided. In a case that the loading or unloading end **1215** and the carrying mechanism **150** are arranged on opposite sides, the carrying mechanism **150** does not block the loading or unloading end **1215**, and in this case, the carrying mechanism **150** may move to a specified position or may not move, as long as the loading or unloading is not affected.

(230) In an embodiment, the plurality of storage assemblies **121** include a loading or unloading end **1215** configured to load or unload the goods **200**, and the transport method further includes the following operation: after the controller receives the first loading instruction, the controller controls the carrying mechanism **150** to avoid the loading or unloading end **1215**.

(231) It can be understood that, whether loading or unloading from the loading or unloading end **1215**, the controller needs to control the carrying mechanism **150** to avoid the loading or unloading end **1215**, so as to avoid interference between the carrying mechanism **150** and the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620** at the loading or unloading end **1215**. An avoidance principle is the same as that in the foregoing embodiments, and details are not described herein again. Exemplarily, when loading or unloading the goods **200** from one end close to the carrying mechanism **150**, the carrying mechanism **150** first ascend to a highest position, thereby leaving a space for the transport robot **100** to be docked with the auxiliary apparatus **300** or the loading or unloading apparatus **600**.

(232) Based on the transport system of the foregoing two embodiments, the present disclosure further provides a transport method of the transport system, which is applicable to the transport system in the foregoing two embodiments. The transport method includes the following operations: a control center receives a second loading or unloading instruction; the control center controls the transport robot **100** to move to a second loading or unloading position according to the second loading or unloading instruction; and the control center confirms that the second loading or unloading position is a loading position or an unloading position, and controls the transport robot **100** to perform a loading or unloading operation.

(233) Components of the transport system perform a coordinated action under the control of the control center, and the control center of the transport system maintains a communication connection with an external server. The control center may identify information of the to-be-transported goods **200**, and the control center may obtain information of a loading position and an unloading position corresponding to each piece of the to-be-transported goods **200**. The control center coordinates and controls the components according to the obtained information, so as to

efficiently complete the transport of the goods **200**.

(234) When loading or unloading is required, the control center receives the second loading or unloading instruction, and then the control center controls, according to the second loading or unloading instruction, the transport robot **100** to move, so that the transport robot **100** moves at the second loading or unloading position. The second loading or unloading position also includes a loading position and an unloading position, which is substantially the same as the first loading or unloading position, and is only used for distinction. It can be understood that the loading position and the unloading position may be interchanged, that is, the transport robot **100** may load at the unloading position and unload at the loading position.

(235) Generally, the transport robot **100** may be loaded by the carrying mechanism **150** at the loading position, and unloaded by the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620** at the unloading position. After the control center controls, according to the second loading or unloading instruction, the transport robot **100** to move to the loading position, the control center may control the lifting mechanism **140** to drive the carrying mechanism **150** to ascend or descend, so that the carrying mechanism **150** can pick goods on a shelving unit. Then, the lifting mechanism **140** drives the carrying mechanism **150** to ascend or descend, so as to transfer the goods **200** in the carrying mechanism **150** to the plurality of storage assemblies **121**, and implement the loading of the goods **200**. This process is repeated until the plurality of storage assemblies **121** store the goods **200**. After the control center moves from the loading position to the unloading position according to the second unloading instruction, the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620** may receive and pick the goods **200** in the plurality of storage assemblies **121**, so as to implement the unloading of the goods **200**.

(236) Certainly, the loading or unloading process may also be performed in a reverse direction, that is, the transport robot **100** is loaded at the unloading position by the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620** at the unloading position, and is unloaded by the carrying mechanism **150** at the loading position. After the control center controls, according to the second loading or unloading instruction, the transport robot **100** to move to the unloading position, the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620** may transfer the goods **200** thereon to corresponding storage assemblies **121**, so as to implement the loading of the goods **200**. After the transport robot **100** is filled with the goods **200**, the control center moves from the unloading position to the loading position according to the second unloading instruction, the control center may control the lifting mechanism **140** to drive the carrying mechanism **150** to ascend or descend, so that the carrying mechanism **150** can pick the goods in the plurality of storage assemblies **121**, and then the lifting mechanism **140** drives the carrying mechanism **150** to ascend or descend, so as to remove the goods **200** in the carrying mechanism **150**. This process is repeated until the goods **200** of the plurality of storage assemblies **121** are taken away, and the unloading of the goods **200** is implemented.

(237) It is worth noting that after controlling the transport robot **100** to move to the second loading or unloading position, the control center needs to determine whether the second loading or unloading position is the loading position or the unloading position. For example, in a case that there are no goods **200** in the transport robot **100**, after the transport robot **100** moves to the second loading or unloading position, in a case that the second loading or unloading position is the loading position, the carrying mechanism **150** loads the goods into the plurality of storage assemblies **121** in this case; and in a case that there are goods **200** in the transport robot **100**, after the transport robot **100** moves to the second loading or unloading position, in a case that the second loading or unloading position is the unloading position, the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620** unload the goods in this case.

(238) In this embodiment described above, the transport method can implement the automatic

transport of the goods **200**, so that a problem of high cost and low efficiency in a current transport method is effectively resolved, the cost of the loading or unloading of the goods **200** is reduced, and the efficiency of the loading or unloading of the goods **200** is greatly improved. In addition, the carrying mechanism **150** moves to different heights under the driving of the lifting mechanism **140**, so that the to-be-transported goods **200** can be delivered to a plurality of storage assemblies **121** at different heights in the storage mechanism **120**, which has strong versatility and reduces the floor space.

(239) In an embodiment, that the control center confirms that the second loading or unloading position is a loading position or an unloading position, and controls the transport robot **100** to perform a loading or unloading operation includes the following operations: the control center obtains goods information in the plurality of storage assemblies **121**; in a case that there are goods in the plurality of storage assemblies **121** and the control center confirms that the second loading or unloading position is the unloading position, the control center controls the transport robot **100** to unload goods at the unloading position; and in a case that there are no goods in the plurality of storage assemblies **121** and the control center confirms that the second loading or unloading position is the loading position, the control center controls the transport robot **100** to load goods at the loading position.

(240) That is, whether the plurality of storage assemblies **121** perform the loading operation or the unloading operation is determined according to whether or not there are goods **200** therein. In a case that there are goods **200** in the plurality of storage assemblies **121**, it indicates that the plurality of storage assemblies **121** do not need to be loaded but need to be unloaded. In this case, after the transport robot **100** moves to the second loading or unloading position, the second loading or unloading position is the unloading position. At this time, the control center may control the transport robot **100** to unload at the loading position. Specifically, the plurality of storage assemblies **121** correspond to the plurality of transport mechanisms **320** of the auxiliary apparatus **300**, and the goods in the plurality of storage assemblies **121** may be unloaded to corresponding transport mechanisms **320** synchronously. In a case that there are no goods **200** in the plurality of storage assemblies **121**, it indicates that the plurality of storage assemblies **121** do not need to be unloaded but need to be loaded. In this case, after the transport robot **100** moves to the second loading or unloading position, the second loading or unloading position is the loading position. At this time, the control center may control the transport robot **100** to load at the loading position. Specifically, the plurality of storage assemblies **121** correspond to the plurality of transport mechanisms **320** of the auxiliary apparatus **300**, and the goods in the plurality of transport mechanisms **320** may be loaded to corresponding storage assemblies **121** synchronously.

(241) In an embodiment, the second loading or unloading instruction includes a second loading instruction, and that the control center controls the transport robot to load goods at the loading position includes the following operations: the control center receives the second loading instruction; the control center controls the transport robot **100** to move to the second loading or unloading position according to the second loading instruction; the control center confirms that the second loading or unloading position is a loading or unloading position, and the control center controls a carrying mechanism **150** to transfer goods **200** to storage assemblies **121** of a storage mechanism **120**; and the control center confirms that the second loading or unloading position is an unloading position, and the control center controls at least one of the plurality of loading or unloading mechanisms **620** or at least one of the plurality of transport mechanisms **320** to transfer goods **200** to corresponding storage assemblies **121**.

(242) When the transport robot **100** is loading goods, the control center receives the second loading instruction. Optionally, the control center controls, according to the second loading instruction, the transport robot **100** to move to the loading position, and then the control center may control the lifting mechanism **140** to drive the carrying mechanism **150** to ascend or descend, so that the carrying mechanism **150** can pick goods on a shelving unit. Then, the lifting assembly drives the

carrying mechanism **150** to ascend or descend, so as to transfer the goods **200** in the carrying mechanism **150** to the plurality of storage assemblies **121**, and implement the loading of the goods **200**. This process is repeated until the plurality of storage assemblies **121** store the goods **200**. Further optionally, the control center controls, according to the second loading instruction, the transport robot **100** to move to the unloading position. After the plurality of storage assemblies **121** are docked with the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620**, the control center controls at least one of the plurality of transport mechanisms **320** or at least one of the plurality of loading or unloading mechanisms **620** to transfer the goods **200** thereon to corresponding storage assemblies **121**. It can be understood that one or several transport mechanisms **320** or loading or unloading mechanisms **620** may be specified to perform a loading action, or all transport mechanisms **320** or loading or unloading mechanisms **620** may perform the loading action.

(243) In an embodiment, when the transport robot **100** is unloading, a plurality of storage assemblies **121** are capable of moving synchronously to perform a synchronous unloading action, and the second loading or unloading instruction includes a second unloading instruction; the transport system further includes an auxiliary apparatus **300** comprising a plurality of transport mechanisms **320** arranged at intervals along a vertical direction; and that the control center controls the transport robot **100** to unload goods at the unloading position includes the following operations: the control center receives the second unloading instruction; the control center controls the transport robot **100** to move to the unloading position, and the plurality of storage assemblies **121** of the transport robot **100** respectively correspond to the plurality of transport mechanisms **320**; and the control center controls at least two of the plurality of storage assemblies **121** to simultaneously unload, so that goods **200** in the at least two of the plurality of storage assemblies **121** can be transferred to corresponding transport mechanisms **320**.

(244) In a case that the transport system includes the transport robot **100** in the first embodiment, the plurality of storage assemblies **121** in the transport robot **100** can implement synchronous unloading. Specifically, in a case that the second loading or unloading instruction received by the control center is the second unloading instruction, the control center controls, according to the second unloading instruction, the transport robot **100** to move from the loading position to the unloading position. The unloading position in this case corresponds to the auxiliary apparatus **300** of the transport system. In addition, the plurality of storage assemblies **121** are respectively docked with the plurality of transport mechanisms **320**. When the controller controls at least two of the plurality of storage assemblies **121** to unload simultaneously, at least two of the plurality of transport mechanisms **320** corresponding to the at least two of the plurality of storage assemblies **121** may receive and pick the goods **200** removed from the at least two of the plurality of storage assemblies **121**, so as to complete the unloading operation of the transport robot **100**.

(245) In an embodiment, when the transport robot **100** is loading, a plurality of storage assemblies **121** are capable of moving synchronously to perform a synchronous loading action, and the second loading or unloading instruction includes a second loading instruction; the transport system further includes an auxiliary apparatus **300** including a plurality of transport mechanisms **320** arranged at intervals along a vertical direction; and that the control center controls the transport robot **100** to load goods at the loading position includes the following operations: the control center receives the second loading instruction; the control center controls the transport robot **100** to move to the loading position, and the plurality of storage assemblies **121** of the transport robot **100** respectively correspond to the plurality of transport mechanisms **320**; and the control center controls at least two of the plurality of transport mechanisms **320** to simultaneously load goods to at least two of the plurality of storage assemblies **121**.

(246) In a case that the transport robot **100** is the transport robot **100** in the first embodiment, the plurality of storage assemblies **121** in the transport robot **100** can implement synchronous loading. In a case that the transport robot **100** needs to load goods, a loading operation is performed by the

auxiliary apparatus **300**. Specifically, in a case that the second loading or unloading instruction received by the controller is the second loading instruction, the controller controls, according to the second loading instruction, the transport robot **100** to move from the unloading position to the loading position. In this case, the loading position is opposite to that in the foregoing embodiments, and the unloading position is opposite to that in the foregoing embodiments. It indicates that the loading position in this case corresponds to the auxiliary apparatus **300** of the transport system. In addition, the plurality of storage assemblies **121** are respectively docked with the plurality of transport mechanisms **320**. The controller controls a plurality of transport mechanisms **320** of the auxiliary apparatus **300** to move goods into a plurality of storage assemblies **121** at corresponding positions, so that the synchronous loading of the plurality of storage assemblies **121** is implemented, and the loading operation of the transport robot **100** is completed.

(247) In an embodiment, the transport robot **100** includes a linkage mechanism **130** electrically connected to the control center, and that the control center controls, according to the second unloading instruction, at least two of the plurality of storage assemblies **121** to simultaneously unload includes the following operation:

(248) the control center controls, according to the second unloading instruction, the linkage mechanism **130** to drive the at least two of the plurality of storage assemblies **121** to move simultaneously, so as to transfer the goods **200** to the corresponding transport mechanisms **320**.

(249) The control center is electrically connected to the linkage mechanism **130**, and is further electrically connected to a linkage driving member **132** of the linkage mechanism **130**. The control center may control the movement of the linkage driving member **132**, so that the linkage mechanism **130** can drive the at least two of the plurality of storage assemblies **121** to move synchronously to perform an unloading action. It can be understood that, after the control center receives the second unloading instruction, and after the plurality of storage assemblies **121** of the transport robot **100** are docked with the plurality of transport mechanisms **320** of the auxiliary apparatus **300**, the controller controls, through the linkage driving member **132**, the linkage mechanism **130** to drive the at least two of the plurality of storage assemblies **121** to be lifted up synchronously, so that the goods **200** in the plurality of storage assemblies **121** slide out of the plurality of storage assemblies **121** and move to corresponding transport mechanisms **320**, and an unloading operation of the transport robot **100** is completed.

(250) In an embodiment, the transport robot **100** further includes a blocking mechanism **170** electrically connected to the control center and capable of switching between a blocking position and an avoidance position, and the second loading or unloading instruction includes a second unloading instruction; and the transport system further includes a loading or unloading apparatus **600** electrically connected to the control center and including a plurality of loading or unloading mechanisms **620** arranged at intervals along a vertical direction, and that the control center controls the transport robot **100** to unload goods at the unloading position includes the following operations: the control center receives the second unloading instruction; the control center controls the transport robot **100** to move to the unloading position, and the plurality of storage assemblies **121** of the transport robot **100** respectively correspond to the plurality of loading or unloading mechanisms **620**; the control center controls, according to the second unloading instruction, the blocking mechanism **170** to move to the avoidance position, so that the plurality of storage assemblies **121** are in an unloadable state; and the control center controls the plurality of loading or unloading mechanisms **620** to extend into the plurality of storage assemblies **121** to receive and pick and remove goods **200** of the plurality of storage assemblies **121**.

(251) In a case that the transport system includes the transport robot **100** in the second embodiment, the transport robot **100** may block the goods **200** in the plurality of storage assemblies **121**, to prevent the goods **200** from sliding out of the plurality of storage assemblies **121** during a process of transporting the goods **200** by the transport robot **100**, so as to protect the goods **200** in the plurality of storage assemblies **121** and prevent the goods **200** from being damaged.

Specifically, the transport robot **100** of the present disclosure blocks the goods **200** in the plurality of storage assemblies **121** by the blocking mechanism **170** at the blocking position during a transport process. When unloading is required, the blocking mechanism **170** moves from the blocking position to the avoidance position, and at this time, the loading or unloading apparatus **600** may perform an unloading operation on the plurality of storage assemblies **121**.

(252) Because a structure and a working principle of the blocking mechanism **170** have been described in detail in the second embodiment, details are not described herein again, and the description herein is only from a perspective of a control method. Specifically, after the control center receives the second unloading instruction, the control center controls, according to the second unloading instruction, the transport robot **100** to move to the unloading position. At this time, the transport robot **100** approaches the loading or unloading apparatus **600**, and the plurality of storage assemblies **121** are respectively docked with the plurality of loading or unloading mechanisms **620**. Subsequently, the control center controls the blocking mechanism **170** to move from the blocking position to the avoidance position, the blocking mechanism **170** no longer blocks the goods **200** in the plurality of storage assemblies **121**, and the control center controls the plurality of loading or unloading mechanisms **620** to extend into the plurality of storage assemblies **121**, and receive and pick and remove the goods **200** in the plurality of storage assemblies **121**, so that the unloading operation of the transport robot **100** is implemented.

(253) In an embodiment, the transport robot **100** further includes a blocking mechanism **170** electrically connected to the control center and capable of switching between a blocking position and an avoidance position, and the second loading or unloading instruction includes a second loading instruction; and the transport system further includes a loading or unloading apparatus **600** electrically connected to the control center and including a plurality of loading or unloading mechanisms **620** arranged at intervals along a vertical direction, and that the control center controls the transport robot **100** to load goods at the unloading position includes the following operations: the control center receives the second loading instruction; the control center controls the transport robot **100** to move to the loading position, and the plurality of storage assemblies **121** of the transport robot **100** respectively correspond to the plurality of loading or unloading mechanisms **620**; the control center controls, according to the second loading instruction, the blocking mechanism **170** to move to the avoidance position, so that the plurality of storage assemblies **121** are in a loadable state; and the control center controls the plurality of loading or unloading mechanisms **620** to carry the goods **200** and extend into the plurality of storage assemblies **121** to place the goods **200** in the plurality of storage assemblies **121**.

(254) In a case that the transport system includes the transport robot **100** in the second embodiment, the transport robot **100** may block the goods **200** in the plurality of storage assemblies **121**, to prevent the goods **200** from sliding out of the plurality of storage assemblies **121** during a process of transporting the goods **200** by the transport robot **100**, so as to protect the goods **200** in the plurality of storage assemblies **121** and prevent the goods **200** from being damaged.

Specifically, during a loading process of the transport robot **100** of the present disclosure, the blocking mechanism **170** moves from the blocking position to the avoidance position. At this time, the plurality of loading or unloading mechanisms **620** may perform a loading operation on the plurality of storage assemblies **121**. Specifically, the to-be-transported goods **200** are placed on the plurality of loading or unloading mechanisms **620**, and then the blocking mechanism **170** moves from the blocking position to the avoidance position, so that the plurality of loading or unloading mechanisms **620** can extend into the plurality of storage assemblies **121**. Subsequently, the goods **200** are placed in the plurality of storage assemblies **121** by the plurality of loading or unloading mechanisms **620** and then removed from the plurality of storage assemblies **121**.

(255) In an embodiment, that the control center confirms that the second loading or unloading position is an unloading position includes the following operation: the control center obtains first relative position information corresponding to an unloading identifier, and in a case that a deviation

between a current position of the transport robot **100** and the first relative position information is less than a first threshold, the transport robot **100** is at the unloading position; or the control center obtains second relative position information corresponding to the auxiliary apparatus **300** or the loading or unloading apparatus **600**, and in a case that a deviation between the current position of the transport robot **100** and the second relative position information is less than a second threshold, the transport robot **100** is at the unloading position.

(256) Optionally, an unloading identifier is arranged near the auxiliary apparatus **300** or the loading or unloading apparatus **600**. The unloading identifier is arranged corresponding to the auxiliary apparatus **300** or the loading or unloading apparatus **600**, and is used for indicating the unloading position at which the auxiliary apparatus **300** or the loading or unloading apparatus **600** is located. In a case that the transport robot **100** moves to a position indicated by the unloading identifier, it indicates that the transport robot **100** moves in place, and an unloading operation may be performed. That is, position information corresponding to the unloading identifier is the first relative position information, and the control center may determine a position of the auxiliary apparatus **300** or the loading or unloading apparatus **600** according to the first relative position information, and then determine the unloading position to which the transport robot **100** moves.

(257) Specifically, the control center may control the transport robot **100** to approach the auxiliary apparatus **300** or the loading or unloading apparatus **600**, and the control center may obtain a current position of the transport robot **100** and compare the current position with the first relative position information. In a case that a distance deviation between the current position of the transport robot **100** and the first relative position information is within a range of the first threshold, it indicates that the transport robot **100** has moved to the unloading position. In this case, the plurality of storage assemblies **121** are docked with the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620**, and a loading or unloading operation may be performed. In a case that the distance deviation between the current position of the transport robot **100** and the first relative position information exceeds the range of the first threshold, it indicates that the transport robot **100** has not moved to the unloading position. In this case, the plurality of storage assemblies **121** deviate from the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620**, and effective docking cannot be implemented. If a loading or unloading operation is performed in this case, there may be a risk of falling of the goods **200**. Therefore, the control center needs to continue to control the movement of the transport robot **100** until the distance deviation between the current position of the transport robot **100** and the first relative position information is within the range of the first threshold, and the transport robot **100** stops moving. The range of the first threshold herein refers to a maximum deviation range allowed when the plurality of storage assemblies **121** are docked with the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620**. Within this range, the goods **200** can be conveyed normally. If the range is exceeded, the goods **200** are at a risk of falling.

(258) Further optionally, the control center may record position information of the auxiliary apparatus **300** or the loading or unloading apparatus **600** as the second relative position information. The control center may determine, according to the second relative position information, the unloading position to which the transport robot **100** moves. Specifically, the control center may control the transport robot **100** to approach the auxiliary apparatus **300** or the loading or unloading apparatus **600**, and the control center may obtain a current position of the transport robot **100** and compare the current position with the second relative position information. In a case that a distance deviation between the current position of the transport robot **100** and the second relative position information is within a range of the second threshold, it indicates that the transport robot **100** has moved to the unloading position. In this case, the plurality of storage assemblies **121** are docked with the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620**, and a loading or unloading operation may be performed. In a case that the distance deviation between the current position of the transport robot **100** and the

second relative position information exceeds the range of the second threshold, it indicates that the transport robot **100** has not moved to the unloading position. In this case, the plurality of storage assemblies **121** deviate from the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620**, and effective docking cannot be implemented. If a loading or unloading operation is performed in this case, there may be a risk of falling of the goods **200**. Therefore, the control center needs to continue to control the movement of the transport robot **100** until the distance deviation between the current position of the transport robot **100** and the second relative position information is within the range of the second threshold, and the transport robot **100** stops moving.

(259) The first threshold and the second threshold herein refer to maximum deviation ranges allowed when the plurality of storage assemblies **121** are docked with the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620**. Within this range, the goods **200** can be conveyed normally. If the range is exceeded, the goods **200** are at a risk of falling.

(260) It is worth noting that the operation of loading the transport robot **100** by using the auxiliary apparatus **300** or the loading or unloading apparatus **600** is substantially the same as the operation of unloading the transport robot **100** by using the auxiliary apparatus **300** or the loading or unloading apparatus **600**, which is a reverse process of the step of unloading the transport robot **100** by using the auxiliary apparatus **300** or the loading or unloading apparatus **600**, and details are not described herein again.

(261) In an embodiment, the transport system further includes a lifting apparatus **400** and a conveying apparatus **500** that are electrically connected to the control center, and the transport method further includes the following operation:

(262) after the plurality of loading or unloading mechanisms **620** or the plurality of transport mechanisms **320** receive the goods **200**, the control center controls the lifting apparatus **400** to receive and pick goods **200** of at least one of the plurality of loading or unloading mechanisms **620**, or goods **200** of at least one of the plurality of transport mechanisms **320**, and transfer the goods **200** to the conveying apparatus **500**.

(263) A transfer mechanism **430** can carry a plurality of goods **200** at one time without repeated actions, thereby improving working efficiency. Specifically, when unloading goods, the control center may control a moving mechanism **420** to drive the transfer mechanism **430** to receive and pick the goods **200** of the plurality of transport mechanisms **320** layer by layer, and then descend to the conveying apparatus **500** to transfer all the goods **200** on the transfer mechanism **430** to the conveying apparatus **500** at one time, and the goods are conveyed to a specified position by the conveying apparatus **500**. When loading goods, the moving mechanism **420** may drive the transfer mechanism **430** to descend to the conveying apparatus **500**, to sequentially receive and pick a plurality of goods **200** conveyed by the conveying apparatus **500**; and then, the moving mechanism **420** drives the transfer mechanism **430** to ascend, so that the transfer mechanism **430** transfers the goods **200** to the plurality of transport mechanisms **320** layer by layer.

(264) In an embodiment, the plurality of storage assemblies **121** include a loading or unloading end **1215** configured to load or unload the goods **200**, and the transport method further includes the following operation: after the control center receives the second unloading instruction, the control center controls the carrying mechanism **150** to avoid the loading or unloading end **1215**.

(265) That is, after the control center receives the second unloading instruction, the control center controls the carrying mechanism **150** to move to a specified position, so that the carrying mechanism **150** moves away from the loading or unloading end, so as to avoid the loading or unloading of the goods **200** by the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620**. It can be understood that the loading or unloading end **1215** is an opening used for loading or unloading the goods **200**, a specific form thereof has been mentioned above, and details are not described herein again. In a case that the plurality of transport

mechanisms **320** or the plurality of loading or unloading mechanisms **620** are configured to unload goods, the carrying mechanism **150** needs to avoid the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620**, so as to avoid interference. Specifically, the control center may control the carrying mechanism **150** to move to a specified position. The specified position herein may be a topmost position of the transport robot **100** or a position higher than the plurality of transport mechanisms **320** and the plurality of loading or unloading mechanisms **620**, or may be a position different from the loading or unloading end **1215**.

(266) Specifically, in a case that the loading or unloading end **1215** is arranged on a same side as the carrying mechanism **150**, the control center may control the carrying mechanism **150** to ascend to a top end of the transport robot **100**, and may also control the carrying mechanism **150** to ascend to a position higher than the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620** or to move to an other side of the vertical frame **110**, so that the loading or unloading end **1215** is arranged away from the carrying mechanism **150**. In this way, the carrying mechanism **150** can move away from the loading or unloading end **1215**, and the interference between the carrying mechanism **150** and the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620** at the loading or unloading end **1215** can be avoided. In a case that the loading or unloading end **1215** and the carrying mechanism **150** are arranged on opposite sides, the carrying mechanism **150** does not block the loading or unloading end **1215**, and in this case, the carrying mechanism **150** may move to a specified position or may not move, as long as the loading or unloading is not affected.

(267) In an embodiment, the plurality of storage assemblies **121** include a loading or unloading end **1215** configured to load or unload the goods **200**, and the transport method further includes the following operation: after the control center receives the second loading instruction, the control center controls the carrying mechanism **150** to avoid the loading or unloading end **1215**.

(268) It can be understood that, whether loading or unloading from the loading or unloading end **1215**, the control center needs to control the carrying mechanism **150** to avoid the loading or unloading end **1215**, so as to avoid interference between the carrying mechanism **150** and the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620** at the loading or unloading end **1215**. An avoidance principle is the same as that in the foregoing embodiments, and details are not described herein again. Exemplarily, when loading or unloading the goods **200** from one end close to the carrying mechanism **150**, the carrying mechanism **150** (that is, a fork) first ascend to a highest position, thereby leaving a space for the transport robot **100** to be docked with the auxiliary apparatus **300** or the loading or unloading apparatus **600**.

Embodiment 3

(269) Referring to FIG. 9 and FIG. 11, the present disclosure provides a transport robot **100**. The transport robot **100** is applied to a transport system, and can transport goods **200**. It can be understood that the goods **200** may be goods **200** with a bracket **621**, and the transport robot **100** transports the goods **200** through the bracket **621**; and certainly, the goods may alternatively be goods **200** placed in a container, and the transport robot **100** transports the goods **200** through a box. The goods **200** described below are goods **200** placed in a box, and the box may be loaded with the goods **200**, so as to implement the transport of the goods **200**. The transport robot **100** transports the box to an unloading position, and after unloading the goods **200** in the box, the box may be transported back to the transport robot **100**, so as to reuse the box and reduce the cost. Alternatively, the goods are a box with goods **200**, and the transport robot **100** transports the box to the unloading position, and unloads the box with the goods **200** through an unloading apparatus.

(270) The transport robot **100** plays an important role in intelligent warehousing, transports goods **200**, ensures a transport speed of the goods **200**, improves the transport efficiency of the goods **200**, and reduces the consumption of labor resources. The transport robot **100** in the present disclosure can block the goods **200** during a transport process, restrict the goods **200** from sliding out of the transport robot **100**, ensure the safety of the goods **200**, avoid a risk of sliding out, and improve the

transport efficiency. When loading or unloading goods, the transport robot **100** no longer blocks the goods **200**, so that the transport robot **100** can perform a loading or unloading operation, which is convenient for use.

(271) Referring to FIG. **9** and FIG. **10**, in an embodiment, the transport robot **100** includes a vertical frame **110**, a storage mechanism **120**, and a blocking mechanism **170**. The vertical frame **110** is arranged along a vertical direction. The storage mechanism **120** includes a plurality of storage assemblies **121** configured to store to-be-transported goods **200** and arranged on the vertical frame **110** at equal intervals along the vertical direction. The blocking mechanism **170** is capable of switching between a blocking position and an avoidance position, when the blocking mechanism **170** is at the blocking position, the blocking mechanism **170** is configured to block goods **200** in the plurality of storage assemblies **121** from sliding out, and when the blocking mechanism **170** is at the avoidance position, goods **200** are capable of being moved into or moved out of the plurality of storage assemblies **121**.

(272) The vertical frame **110** plays a bearing role, and various components of the transport robot **100** are mounted thereon. When the transport robot **100** transports the goods **200**, the vertical frame **110** may drive synchronous movement of the components on the transport robot **100**, so as to implement the transport of the goods **200**. The storage mechanism **120** is located on the vertical frame **110**, is configured to store the goods **200**, and is capable of moving synchronously with the vertical frame **110**, so as to implement the transport of the goods **200**. The transport robot **100** moves to a loading position, and the to-be-transported goods **200** are transported to the storage mechanism **120** for storage. Then, the transport robot **100** moves from the loading position to an unloading position. Correspondingly, the storage mechanism **120** moves to the unloading position along with the vertical frame **110**. At this time, the goods **200** in the storage mechanism **120** can be unloaded. The storage mechanism **120** can temporarily store the to-be-transported goods **200**, thereby improving the capability of the transport robot **100** to carry the goods **200**.

(273) In addition, the storage mechanism **120** includes a plurality of storage assemblies **121** arranged on the vertical frame **110** at equal intervals. Each of the plurality of storage assemblies **121** can carry goods **200** of a box to ensure a storage capacity of the transport robot **100**. That is, the plurality of storage assemblies **121** are evenly distributed on the vertical frame **110** along the vertical direction. The to-be-transported goods **200** may be transported to the plurality of storage assemblies **121**, and the transport robot **100** drives the goods **200** in the plurality of storage assemblies **121** to be transported to the unloading position. In addition, the plurality of storage assemblies **121** are fixed on the vertical frame **110**, and do not move. The specific loading or unloading of the plurality of storage assemblies **121** is implemented by a loading or unloading apparatus **600** of the transport system and/or a carrying mechanism **150** of the transport robot **100**, which is specifically described in the following specification.

(274) It can be understood that after the plurality of storage assemblies **121** store the to-be-transported goods **200**, during the movement of the transport robot **100** from the loading position to the unloading position, the transport robot **100** travels a specific distance, and the goods **200** stored in the plurality of storage assemblies **121** may be at a risk of falling. Once the goods **200** in the plurality of storage assemblies **121** fall, on the one hand, the goods **200** are damaged, resulting in economic losses; and on the other hand, a manual or intelligent picking apparatus is required to pick the goods **200** and place the goods in the plurality of storage assemblies **121** again for transport, which affects the transport efficiency of the goods **200**.

(275) In view of the foregoing description, the transport robot **100** of the present disclosure further includes a blocking mechanism **170**, and the goods **200** in the plurality of storage assemblies **121** are blocked by the blocking mechanism **170**. In this way, the goods **200** in the plurality of storage assemblies **121** can be prevented from sliding out. Specifically, the blocking mechanism **170** is capable of switching between a blocking position and an avoidance position. When the blocking mechanism **170** is at the avoidance position, the goods **200** may be loaded into the plurality of

storage assemblies **121** or the goods **200** may be taken out from the plurality of storage assemblies **121**. When the blocking mechanism **170** is at the blocking position, the goods **200** in the plurality of storage assemblies **121** are in abutment with the blocking mechanism **170**, and the blocking mechanism **170** may restrict the goods **200** in the plurality of storage assemblies **121** from sliding out and prevent the goods **200** from falling.

(276) Specifically, when the transport robot **100** is at a goods-carrying position, the blocking mechanism **170** is at the avoidance position, and at this time, the goods **200** may be loaded into the plurality of storage assemblies **121**; after the loading is completed, the blocking mechanism **170** moves to the blocking position, and at this time, the blocking mechanism **170** may be in abutment with the goods **200** in the plurality of storage assemblies **121** to restrict the goods **200** from sliding out of the plurality of storage assemblies **121**; subsequently, the transport robot **100** may move from the loading position to the unloading position, and the blocking mechanism **170** is always at the blocking position during this process; and when the blocking mechanism **170** is at the unloading position, the blocking mechanism **170** moves from the blocking position to the avoidance position, and at this time, the goods **200** in the plurality of storage assemblies **121** may be taken out. In addition, the transport robot **100** reciprocates in this way. It can be understood that the blocking mechanism **170** may play a blocking role during the movement of the transport robot **100** regardless of whether there are goods in the plurality of storage assemblies **121**, or may only play a blocking role during goods transport in a case that there are goods in the plurality of storage assemblies **121**.

(277) When the transport robot **100** of the foregoing embodiment transports goods, the blocking mechanism **170** moves to the blocking position and may be in abutment with the goods **200** in the plurality of storage assemblies **121**, so as to restrict the goods **200** from sliding out of the plurality of storage assemblies **121**. Therefore, a current problem that the goods easily slide out of a storage rack of the transport robot during goods transport is effectively resolved, the goods **200** are prevented from sliding out of the plurality of storage assemblies **121** during a transport process of the transport robot **100**, the safety of the goods **200** is ensured, a risk of sliding out is avoided, and the transport efficiency is improved. In addition, when the transport robot **100** loads or unloads goods, the blocking mechanism **170** moves to the avoidance position. At this time, the goods **200** may be loaded into the plurality of storage assemblies **121**, and the goods **200** in the plurality of storage assemblies **121** may also be removed, which does not hinder a loading or unloading operation of the transport robot **100**, and is convenient for use.

(278) In an embodiment, the transport robot **100** further includes a movable chassis **160** arranged at a bottom portion of the vertical frame **110**. The movable chassis **160** can drive the transport robot **100** to move, which greatly improves the adaptability of the transport robot **100** to actual working conditions. Specifically, the chassis **160** includes a chassis frame, a travel drive assembly, and a plurality of rotating wheels, the vertical frame **110** is arranged on an upper portion of the chassis frame, the plurality of rotating wheels are arranged on a bottom portion of the chassis frame, the travel drive assembly is arranged on the chassis frame, and at least one of the plurality of rotating wheels is in driving connection with the travel drive assembly. Further, at least two of the plurality of rotating wheels are separately in driving connection with the travel drive assembly, and the at least two of the plurality of rotating wheels being separately in driving connection with the travel drive assembly are distributed on two sides of the chassis frame along a traveling direction, thereby achieving a steering function of the chassis **160**. The travel drive assembly includes at least two wheel drive motors, and the at least two of the plurality of rotating wheels distributed on the two sides of the chassis frame along the traveling direction are respectively driven by separate wheel drive motors. That the at least two of the plurality of rotating wheels distributed on the two sides of the chassis frame along the traveling direction are respectively driven by separate wheel drive motors can simplify a transmission structure on the chassis **160**.

(279) In an embodiment, each of the plurality of rotating wheels includes a driving wheel and a

driven wheel. The driving wheel and the driven wheel are mounted on a bottom portion of the chassis **160**, may separately rotate relative to the chassis **160**, and jointly support the chassis **160**. The driving wheel is driven by a wheel drive motor to enable the chassis **160** to move. By configuring the movable chassis **160**, the transport robot **100** can transport the goods **200** between the loading position and the unloading position. There are two driving wheels, and the two driving wheels are symmetrically distributed. Correspondingly, there are two wheel drive motors, and the two driving wheels are respectively driven by the two wheel drive motors, so that rotational speeds of the two driving wheels are different, thereby implementing the steering of the chassis **160**. There are four driven wheels, and the four driven wheels are distributed in a rectangular shape. The four driven wheels may be universal wheels or may be of other wheel structures with a steering function. According to actual situations, a quantity of the driven wheel is not limited to four, but may also be six, three, or the like.

(280) In this embodiment, the chassis **160** is also mounted with a guiding apparatus, and the guiding apparatus is a camera configured to identify a graphic code attached to a ground, so that the chassis **160** travels along a preset path. The graphic code may be a two-dimensional code, a barcode, or some customized identification codes. In some other embodiments, the guiding apparatus is a laser guiding apparatus configured to guide the chassis **160** to travel along a laser beam, or the guiding apparatus is a short-wave receiving apparatus configured to receive a preset short-wave signal to guide the chassis **160** to travel along a preset path. It should be noted that, in some other embodiments, the chassis **160** may be omitted, and the vertical frame **110** is directly and fixedly mounted on the ground or another platform, and is only configured to carry the goods **200** between the loading position and the unloading position around the vertical frame.

(281) In an embodiment, the blocking mechanism **170** may simultaneously block the goods **200** in the plurality of storage assemblies **121**. That is, the blocking mechanism **170** may simultaneously move to the blocking position, so as to block the goods **200** in the plurality of storage assemblies **121**, and the blocking mechanism **170** may also simultaneously move to the avoidance position, so that the plurality of storage assemblies **121** can perform a loading or unloading operation.

Certainly, in another implementation of the present disclosure, there are a plurality of blocking mechanisms **170**, and each of the plurality of blocking mechanisms **170** may simultaneously block the goods **200** in at least two of the plurality of storage assemblies **121**. It can be understood that one blocking mechanism **170** may simultaneously act on goods **200** of all storage assemblies **121**, or a plurality of blocking mechanisms **170** may act on a plurality of storage assemblies **121**.

Exemplarily, there are two blocking mechanisms **170**, where one of the two blocking mechanisms **170** is configured to block goods **200** of storage assemblies **121** of first to third layers, and the other one of the two blocking mechanisms **170** is configured to block goods **200** of storage assemblies **121** of fourth to sixth layers. Certainly, in another implementation of the present disclosure, there may be more blocking mechanisms **170**. In the present disclosure, only an example in which one blocking mechanism **170** blocks the goods **200** of all storage assemblies **121** is used for description. A working principle of a plurality of blocking mechanisms **170** is substantially the same as that of the one blocking mechanism **170**, and details are not described herein again.

(282) It is worth noting that an arrangement position of the blocking mechanism **170** is not limited in principle. The blocking mechanism may be movably arranged on the vertical frame **110**, may be movably arranged on the chassis **160**, and may also be movably arranged on the plurality of storage assemblies **121**, as long as it is ensured that the blocking mechanism **170** can move to the avoidance position or the blocking position. In this embodiment, only an example in which the blocking mechanism **170** is movably arranged on the chassis **160** is used for description. A working principle of the blocking mechanism **170** arranged at another position is substantially the same as a working principle of the blocking mechanism **170** movably arranged on the chassis **160**, and details are not described herein again. Specifically, when the blocking mechanism **170** moves relative to the chassis **160**, the blocking mechanism **170** may move to the blocking position or the avoidance

position. After the blocking mechanism **170** can move to the blocking position, the blocking mechanism **170** may block the goods **200** in the plurality of storage assemblies **121**; and after the blocking mechanism **170** can move to the avoidance position, the blocking mechanism **170** no longer blocks the plurality of storage assemblies **121**, and the goods **200** may freely enter or exit the plurality of storage assemblies **121**.

(283) In an embodiment, the plurality of storage assemblies **121** includes a loading or unloading end **1215** that faces away from the vertical frame **110**. The goods **200** are loaded or unloaded from the loading or unloading end **1215** of the plurality of storage assemblies **121** to complete the loading or unloading of the goods **200**. Exemplarily, as shown in FIG. **10**, one ends of the plurality of storage assemblies **121** away from the vertical frame **110** is provided with the loading or unloading end **1215**. During loading, the goods **200** are moved from the loading or unloading end **1215** into the plurality of storage assemblies **121**, and during unloading, the goods **200** are moved from the loading or unloading end **1215** out of the plurality of storage assemblies **121**. Optionally, the loading or unloading end **1215** is an end opening of the plurality of storage assemblies **121**, or another entrance or exit through which the goods **200** can enter or exit. Certainly, in another implementation of the present disclosure, the loading or unloading end **1215** may also be arranged at one ends of the plurality of storage assemblies **121** close to the vertical frame **110**. In this way, the loading or unloading of the goods **200** in the plurality of storage assemblies **121** can also be implemented.

(284) Referring to FIG. **9** and FIG. **10**, in an embodiment, the blocking mechanism **170** may move into or move out of the loading or unloading end **1215**. That is, when the blocking mechanism **170** moves into the loading or unloading end **1215**, the blocking mechanism **170** is at the blocking position. At this time, an end portion of the goods **200** is in abutment with the blocking mechanism **170**, and the blocking mechanism **170** blocks the goods **200** to restrict the goods **200** from sliding out of the loading or unloading end **1215**. When the blocking mechanism **170** moves out of the loading or unloading end **1215**, the blocking mechanism **170** is at the avoidance position. At this time, the loading or unloading end **1215** is unobstructed, the goods **200** may be loaded into the plurality of storage assemblies **121** through the loading or unloading end **1215**, and the goods **200** in the plurality of storage assemblies **121** may also be unloaded through the loading or unloading end **1215**.

(285) In an embodiment, when the blocking mechanism **170** is at the blocking position, the blocking mechanism **170** is in abutment with a side wall or a bottom surface of the goods **200**. That is, the blocking position of the blocking mechanism **170** may be located on a bottom surface or a side surface of the plurality of storage assemblies **121**. When the blocking mechanism **170** moves to the blocking position, the blocking mechanism **170** may be in abutment with the goods **200** in the plurality of storage assemblies **121** at a side surface or a bottom surface. At this time, the movement of the goods **200** in the plurality of storage assemblies **121** is restricted due to an abutting force of the blocking mechanism **170**, so that the goods **200** are prevented from sliding out of the plurality of storage assemblies **121**. After the blocking mechanism **170** moves to the avoidance position, the blocking mechanism **170** is separated from the side surface or the bottom surface of the goods **200** of the plurality of storage assemblies **121**, and the goods **200** may move in the plurality of storage assemblies **121**, so as to perform the loading or unloading operation of the plurality of storage assemblies **121**.

(286) In an embodiment, the blocking mechanism **170** is arranged on at least one side of the plurality of storage assemblies **121**. It can be understood that the blocking mechanism **170** may be arranged on one side of the plurality of storage assemblies **121**, as shown in FIG. **9** and FIG. **10**, and in this case, the blocking mechanism **170** may block the goods **200** in the plurality of storage assemblies **121** at the blocking position. Certainly, in another implementation of the present disclosure, blocking mechanisms **170** may also be located on two sides of the plurality of storage assemblies **121** respectively. In this way, the goods **200** in the plurality of storage assemblies **121**

can be further blocked. Further, two blocking mechanisms **170** may be arranged symmetrically or asymmetrically, as long as the blocking mechanisms can block the goods **200** in the plurality of storage assemblies **121**.

(287) Exemplarily, in this embodiment, only an example in which the blocking mechanism **170** can move into or move out of the loading or unloading end **1215** is used for description. In addition, the blocking mechanism **170** is arranged on one side of the plurality of storage assemblies **121**, working principles of blocking mechanisms **170** with different layouts mentioned in other embodiments are substantially the same as that of the blocking mechanism **170** in this embodiment, and details are not described herein again. In this case, the blocking position of the blocking mechanism **170** is located at the loading or unloading end **1215**. After the blocking mechanism **170** moves to the loading or unloading end **1215**, the blocking mechanism **170** is at the loading or unloading end **1215** and faces the goods **200**, so as to block the goods **200**.

(288) In an embodiment, the blocking mechanism **170** includes a movable blocking connector **171** and a plurality of blocking assemblies **172** separately connected to the blocking connector **171**, and at least one of the plurality of blocking assemblies **172** corresponds to a same storage assembly **121**. The blocking connector **171** is capable of driving the plurality of blocking assemblies **172** to move into the loading or unloading end **1215**, so as to block the goods **200** in the plurality of storage assemblies **121**. The blocking connector **171** functions as a connection, and is configured to connect the plurality of blocking assemblies **172**. When moving, the blocking connector **171** may synchronously drive the plurality of blocking assemblies **172** to move, so that the plurality of blocking assemblies **172** can move to a loading or unloading end **1215** of a corresponding storage assembly **121** or move out of the loading or unloading end **1215** of the plurality of storage assemblies **121**. Optionally, the blocking connector **171** includes, but is not limited to, a connecting rod or a longboard, and the like.

(289) The plurality of blocking assemblies **172** function as a blocking, and is configured to implement blocking of the goods **200**. When the blocking connector **171** drives the plurality of blocking assemblies **172** to move to the blocking position, the plurality of blocking assemblies **172** are located at the loading or unloading end **1215**. At this time, the end portion of the goods **200** faces the plurality of blocking assemblies **172**, and the plurality of blocking assemblies **172** restrict the goods **200** from moving out of the plurality of storage assemblies **121**. When the blocking connector **171** drives the plurality of blocking assemblies **172** to move to the avoidance position, the plurality of blocking assemblies **172** are separated from the loading or unloading end **1215**. At this time, there is no object to block the end portion of the goods **200**, and the plurality of storage assemblies **121** may be loaded or unloaded.

(290) It can be understood that the avoidance position may be located outside the plurality of blocking assemblies **172**, or may be located at a bottom portion of the plurality of storage assemblies **121**, or at a position flush with the plurality of storage assemblies **121**. The avoidance position is located at the bottom portion of the plurality of storage assemblies **121**, as long as the plurality of blocking assemblies **172** are at a position that does not affect the moving in or moving out of goods **200** of a next layer.

(291) Optionally, the blocking connector **171** may ascend or descend, and when ascending or descending, the blocking connector **171** may drive the plurality of blocking assemblies **172** to ascend or descend synchronously, so that the plurality of blocking assemblies **172** are located at the loading or unloading end **1215** or move out of the loading or unloading end **1215**. In this case, the avoidance position may be located at the bottom portion of the plurality of storage assemblies **121** or the position flush with the plurality of storage assemblies **121**. Certainly, the blocking connector **171** may also move horizontally. When moving horizontally, the blocking connector **171** may drive the plurality of blocking assemblies **172** to move horizontally and synchronously, so that the plurality of blocking assemblies **172** are located at the loading or unloading end **1215** or move out of the loading or unloading end **1215**. In this case, the avoidance position may be located outside

the plurality of blocking assemblies **172**. Certainly, the blocking connector **171** may also perform another form of movement, such as one or a combination of rotating motion, swinging motion, moving motion, and the like, as long as the plurality of blocking assemblies **172** can move into or move out of the loading or unloading end **1215**. Exemplarily, in the present disclosure, only an example in which the blocking connector **171** ascends or descends and displaces is used for description. In addition, the avoidance position is located at the bottom portion of the plurality of storage assemblies **121** or the position flush with the plurality of storage assemblies **121**.

(292) In an embodiment, each of the plurality of blocking assemblies **172** includes a stopping member fixedly arranged on the blocking connector **171**, and movement of the blocking connector **171** is capable of driving the stopping member to move into or move out of the loading or unloading end **1215**. In this embodiment, the stopping member is fixedly arranged on the blocking connector **171**, and the movement of the blocking connector **171** may directly drive the stopping member to move, so that the stopping member moves to the blocking position or the avoidance position. For example, when the blocking connector **171** drives the stopping member to ascend, the stopping member may move to the loading or unloading end **1215**, so as to block the goods **200**; and when the blocking connector **171** drives the stopping member to descend, the stopping member may move to the avoidance position, so as to no longer block the goods **200**. Optionally, the stopping member may be a baffle plate, a stopper, a limit post, or another component capable of blocking.

(293) Referring to FIG. **9** and FIG. **10**, in an embodiment, each of the plurality of blocking assemblies **172** includes a swing member **1721** and a blocking member **1722**, one end of the swing member **1721** is rotatably connected to the blocking connector **171**, an other end of the swing member **1721** is mounted with the blocking member **1722**, and a middle portion of the swing member **1721** is rotatably mounted at the loading or unloading end **1215** of the plurality of storage assemblies **121**. When ascending or descending, the blocking connector **171** is capable of driving the swing member **1721** to swing, so that the swing member **1721** drives the blocking member **1722** to move into or move out of the loading or unloading end **1215**.

(294) That is, the blocking connector **171** implements the switching between the blocking position and the avoidance position through the indirect movement of the plurality of blocking assemblies **172**, such as a swinging motion. Specifically, when the blocking connector **171** moves, one end of the swing member **1721** may be driven to move relative to the plurality of storage assemblies **121**, and then an other end of the swing member **1721** may drive the blocking member **1722** to move, so that the blocking member **1722** moves to the avoidance position or the blocking position. A head portion of the swing member **1721** is rotatably connected to the blocking connector **171**, the middle portion of the swing member **1721** is rotatably connected to the plurality of storage assemblies **121**, and a tail portion of the swing member **1721** is connected to the blocking member **1722**. The blocking member **1722** may move to the avoidance position or the blocking position.

(295) Exemplarily, when the blocking connector **171** moves upward along the vertical direction, the blocking connector **171** may drive the blocking member **1722** to move to the blocking position through the swing member **1721**, and when the blocking connector **171** moves downward along the vertical direction, the blocking connector **171** may drive the blocking member **1722** to move to the avoidance position through the swing member **1721**. Optionally, the swing member **1721** is a swing rod, and the blocking member **1722** is a blocking rod.

(296) It should be noted that, the essential spirit of the present disclosure lies in the movement of the blocking connector **171** and the plurality of blocking assemblies **172**, so that the plurality of blocking assemblies **172** respectively move to avoidance positions or blocking positions corresponding to the plurality of storage assemblies **121**. In the foregoing two embodiment, two forms of each of the plurality of blocking assemblies **172** are separately described; and in addition, there are various arrangements of the plurality of blocking assemblies **172**, which cannot all be listed herein, and a linkage manner in the present disclosure is not limited to being implemented by

the foregoing specific structures.

(297) In an embodiment, the blocking mechanism **170** further includes a blocking driving member, and an output end of the blocking driving member is connected to the blocking connector **171**, so as to drive the plurality of blocking assemblies **172** to move into or move out of the loading or unloading end **1215**. The blocking driving member is a power source for the movement of the blocking mechanism **170**, and implements the driving of the movement of a blocking moving member. In addition, the blocking driving member outputs linear motion, so that the blocking connector **171** can ascend or descend, and then the blocking connector **171** may drive the plurality of blocking assemblies **172** to move, so that the plurality of blocking assemblies **172** move to the avoidance position or the blocking position. Optionally, the blocking driving member includes, but is not limited to, an air cylinder, a hydraulic cylinder, a linear motor, or an electric push rod, and may also be another linear driving unit capable of outputting the linear motion. Exemplarily, the blocking driving member is a linear motor. Exemplarily, one end of the blocking driving member is arranged on the chassis **160**. Certainly, in another implementation of the present disclosure, a rotation motor cooperates with a protrusion member to drive.

(298) In an embodiment, a bottom portion of each of the plurality of storage assemblies **121** is provided with a movement space used for a loading or unloading mechanism **620** of a transport system to extend into, so as to load goods into or take the goods out of the plurality of storage assemblies **121**. Because the plurality of storage assemblies **121** cannot move during loading or unloading, other components such as the carrying mechanism **150** or a matching structure of the loading or unloading apparatus **600** are required to move the goods **200** into the plurality of storage assemblies **121** or take the goods out of the plurality of storage assemblies **121** during loading or unloading. Therefore, a bottom portion of each of the plurality of storage assemblies **121** needs to include a space used for the carrying mechanism **150** and the auxiliary apparatus to extend into, so as to facilitate the goods loading or unloading of the plurality of storage assemblies **121**. When loading goods to the plurality of storage assemblies **121**, the carrying mechanism **150** or the loading or unloading apparatus **600** may extend into the movement space to place the goods **200** on the plurality of storage assemblies **121**, and then exit the movement space; and when unloading goods from the plurality of storage assemblies **121**, the carrying mechanism **150** or the loading or unloading apparatus **600** may extend into the movement space to hold the goods **200** in the plurality of storage assemblies **121** and drive the goods **200** to move out of the plurality of storage assemblies **121**.

(299) In an embodiment, each of the plurality of storage assemblies **121** include a first side plate **1213** and a second side plate **1214** that are arranged on the vertical frame **110**, and the first side plate **1213** and the second side plate **1214** are opposite to each other and surround the movement space. The first side plate **1213** and the second side plate **1214** are arranged at a same height of the vertical frame **110**, and are arranged in parallel. In this way, the first side plate **1213** and the second side plate **1214** can be configured to respectively hold bottom portions of two sides of the goods **200**, so that the goods **200** is flat, and deflection is avoided. A portion between the first side plate **1213** and the second side plate **1214** is a gap, that is, the foregoing movement space, which allows the carrying mechanism **150** or the loading or unloading apparatus **600** to extend into, so as to perform a loading or unloading operation.

(300) Certainly, in another implementation of the present disclosure, each of the plurality of storage assemblies **121** includes a carrier body configured to carry the goods **200** and being provided with a movement space along an entrance or exit direction of the goods **200**, and a size of the movement space along the entrance or exit direction of the goods **200** is less than a size of the carrier body along the entrance or exit direction of the goods **200**. That is, the movement space in this case is an opening of the carrier body. The goods **200** are carried by the carrier body, and the movement space of the carrier body may also allow the carrying mechanism **150** or the loading or unloading apparatus **600** to extend into, so as to perform the loading or unloading operation.

(301) In an embodiment, the transport robot **100** further includes a lifting mechanism **140** capable of ascending or descending relative to the vertical frame **110** along the vertical direction and a carrying mechanism **150** configured to carry the goods **200**, where the carrying mechanism **150** is movably arranged on the vertical frame **110** along the vertical direction, is connected to the lifting mechanism **140**, and is capable of ascending or descending along the vertical direction under driving of the lifting mechanism **140**, so as to deliver goods **200** in the carrying mechanism **150** to corresponding storage assemblies **121**.

(302) The carrying mechanism **150** is a terminal configured to perform an action of the transport robot **100**. At the loading position, the carrying mechanism **150** may carry the to-be-transported goods **200**, and transport the goods **200** into the plurality of storage assemblies **121**. Certainly, in some occasions, in a case that the goods **200** in the plurality of storage assemblies **121** need to be unloaded separately, the carrying mechanism **150** may also take out the goods **200** in the plurality of storage assemblies **121**. Optionally, the carrying mechanism **150** includes, but is not limited to, a mechanical arm, an actionable tow bar, or a plane with a conveying function, and the like. The lifting mechanism **140** is configured to implement the ascending or descending movement of the carrying mechanism **150**, and is capable of driving the carrying mechanism **150** to ascend or descend along the vertical direction.

(303) At the loading position, there is a shelving unit with a plurality of layers configured to carry the goods **200**. When the transport robot **100** loads goods at the loading position, the lifting mechanism **140** drives the carrying mechanism **150** to ascend or descend, so that the carrying mechanism **150** can pick goods on the shelving unit. Then, a lifting assembly drives the carrying mechanism **150** to ascend or descend, so as to transfer the goods **200** in the carrying mechanism **150** to the plurality of storage assemblies **121**. This process is repeated until the plurality of storage assemblies **121** store the goods **200**. After the goods loading is completed, the blocking mechanism **170** moves to the blocking position to block the goods **200** in the plurality of storage assemblies **121**, so as to prevent the goods **200** from sliding out of the plurality of storage assemblies **121**. Subsequently, after the transport robot **100** moves from the loading position to the unloading position, the blocking mechanism **170** moves to the avoidance position. At this time, the goods **200** in the plurality of storage assemblies **121** may be unloaded from the loading or unloading end **1215**. After the unloading is completed, the transport robot **100** returns to the loading position, so that continuous transport of the goods **200** can be implemented by repeating the process, thereby improving the transport efficiency.

(304) Optionally, the loading or unloading end **1215** is arranged on a same side as the carrying mechanism **150**. When the loading or unloading end **1215** performs a loading or unloading operation, the carrying mechanism **150** needs to avoid the loading or unloading end **1215**, so as to avoid interference between the carrying mechanism **1215** and a loading or unloading apparatus **600**, and ensure reliable loading or unloading. In this case, the carrying mechanism **150** may ascend to a highest position of the transport robot **100** or a position higher than the loading or unloading apparatus **600**, or move to an other side of the transport robot **100**. Further optionally, the loading or unloading end **1215** is arranged on an opposite side of the carrying mechanism **150**. The goods loading or unloading at the loading or unloading end **1215** is not affected by the carrying mechanism **150**, and when the plurality of storage assemblies **121** are loaded or unloaded, the carrying mechanism **150** does not interfere with the loading or unloading apparatus **600**.

(305) The function of the lifting mechanism **140** is to drive the carrying mechanism **150** to ascend or descend along the vertical direction. In an embodiment, the lifting mechanism **140** includes a lifting power source and a lifting transmission component, and the lifting power source and the lifting transmission component are separately arranged on the vertical frame **110**. The lifting transmission component is in driving connection with the lifting power source and the carrying mechanism **150**. Specifically, an output end of the lifting power source is in driving connection with an input end of the lifting transmission component, and an output end of the lifting

transmission component is in driving connection with the carrying mechanism **150**. That the lifting power source and the lifting transmission component are separately arranged on the vertical frame **110**, and the driving connection between the lifting power source and the lifting transmission component facilitate the disassembly or assembly of the lifting mechanism **140** on the vertical frame **110**. Optionally, a power output from the lifting power source is in a form of rotation and linear motion, or in any other form of motion, and a final output of the lifting transmission component in driving connection with the lifting power source is movement along the vertical direction. Optionally, the lifting power source includes a driving motor in driving connection with the input end of the lifting transmission component. The lifting power source in a form of a motor runs more stably. Further, the driving motor can rotate forwardly or reversely, which facilitates the control of an ascending or descending process of the lifting mechanism **140**.

(306) Optionally, the lifting transmission component may be of a telescopic rod structure, a chain transmission structure, a driving transmission structure, or the like, and may also be of another structure capable of enabling the carrying mechanism **150** to ascend or descend. Exemplarily, the lifting transmission component is of a chain transmission structure, including a sprocket and a chain, the chain is connected to the carrying mechanism **150**, and the chain is arranged on the vertical frame **110** along the vertical direction. When the output end of the lifting power source drives the sprocket to rotate, the chain ascends or descends along the vertical frame **110**, which may further drive the carrying mechanism **150** to ascend or descend.

(307) It should be noted that, the essence of the lifting transmission component is to output the ascending or descending motion to drive the carrying mechanism **150** to ascend or descend, thereby implementing the loading of the goods **200**. In this embodiment, the lifting transmission component is implemented by a chain transmission structure. In addition, there are various structures that can implement ascending or descending, which cannot all be listed herein, and the manner of the ascending or descending motion in the present disclosure is not limited to being implemented by the foregoing specific structures.

(308) In an embodiment, the transport robot **100** further includes a rotary mechanism arranged between the carrying mechanism **150** and the lifting mechanism **140** and configured to drive the carrying mechanism **150** to rotate relative to the lifting mechanism **140**, so that the carrying mechanism **150** is aligned with a corresponding storage assembly **121**.

(309) The rotary mechanism is rotatably connected to the carrying mechanism **150**, and the carrying mechanism **150** is rotatable relative to the rotary mechanism. When the carrying mechanism **150** is rotated by the rotary mechanism, a direction of the carrying mechanism **150** may be adjusted, so that the loading or unloading port of the carrying mechanism **150** can be adjusted. The carrying mechanism **150** implements the loading or unloading of the goods **200** through the loading or unloading port. When the transport robot **100** is at the loading position, the rotary mechanism may drive the carrying mechanism **150** to rotate, so that the loading or unloading port of the carrying mechanism **150** faces a shelving unit, and the goods **200** can be loaded into the carrying mechanism **150**. When the carrying mechanism **150** transfers the goods **200** to the plurality of storage assemblies **121**, the rotary mechanism may drive the carrying mechanism **150** to rotate, so that the loading or unloading port of the carrying mechanism **150** faces the plurality of storage assemblies **121**. At this time, the goods **200** in the carrying mechanism **150** can be transferred to the plurality of storage assemblies **121**.

(310) Optionally, the rotary mechanism includes a carrying bracket, an autorotation gear arranged on the carrying bracket, and an autorotation motor fixedly mounted on the carrying bracket. An output end of the autorotation motor is connected to the autorotation gear, the carrying mechanism **150** is mounted on the autorotation gear, and the carrying bracket is mounted on the lifting mechanism **140**. The autorotation motor may drive the autorotation gear to rotate, which may further drive the carrying mechanism **150** to rotate.

(311) In addition, when the loading or unloading apparatus **600** loads or unloads the goods **200**

with the transport robot **100**, the carrying mechanism **150** ascends to a highest position to avoid the loading or unloading apparatus **600**. It should be noted that, the essence of the rotary mechanism is to output a rotation motion, so as to drive the carrying mechanism **150** to rotate, thereby implementing the loading or unloading of the goods **200**. In this embodiment, the rotary mechanism is implemented by an autorotation motor and an autorotation gear. In addition, there are various structures that can implement rotation, which cannot all be listed herein, and the manner of the rotation motion in the present disclosure is not limited to being implemented by the foregoing specific structures.

(312) In an embodiment, the carrying mechanism **150** includes a transition member **151** and a pick-or-place member **152** that is telescopically arranged on the transition member **151**, and the pick-or-place member **152** is capable of taking out goods **200** and storing the goods in the transition member **151**, and is further capable of pushing out goods **200** in the transition member **151**. The pick-or-place member **152** is telescopically arranged in the transition member **151**. At the loading position, the pick-or-place member **152** extends out of the transition member **151** to take out goods **200** on a shelving unit, and then the pick-or-place member **152** retracts into the transition member **151** to temporarily store the goods **200** in the transition member **151**. Subsequently, the lifting mechanism **140** and the rotary mechanism drive the carrying mechanism **150** to move, so that the carrying mechanism **150** moves to a plurality of storage assemblies **121** in which the goods are to be placed. At this time, the pick-or-place member **152** extends out of the transition member **151**, moves the goods **200** out of the transition member **151**, and transfers the goods to the plurality of storage assemblies **121**. After the transfer, the pick-or-place member **152** retracts into the transition member **151**. Optionally, the transition member **151** includes, but is not limited to, a transition box, and the pick-or-place member **152** includes, but is not limited to, a structure in which a telescopic motor cooperates with a telescopic rod, a mechanical arm mechanism, and the like.

(313) Referring to FIG. 9 and FIG. 11, the present disclosure further provides a transport system including a loading or unloading apparatus **600** and the transport robot **100** in the foregoing embodiments. The loading or unloading apparatus **600** is configured to convey the goods **200** to the transport robot **100** or unload the goods **200** on the transport robot **100**. The loading or unloading apparatus **600** includes an upright frame **610** extending along a vertical direction and a plurality of loading or unloading mechanisms **620** arranged on the upright frame **610** at intervals along the vertical direction, and a manner in which the plurality of loading or unloading mechanisms **620** are arranged at intervals is the same as a manner in which a plurality of storage assemblies **121** are arranged at intervals. After the transport robot **100** is docked with the loading or unloading apparatus **600**, the plurality of loading or unloading mechanisms **620** are capable of respectively conveying, at different heights, the goods **200** to the plurality of storage assemblies **121** or unloading the goods **200** in the plurality of storage assemblies **121**.

(314) The loading or unloading apparatus **600** can implement synchronous unloading or synchronous loading of the goods **200**. The loading or unloading apparatus **600** is mounted at an unloading position or a loading position. In a case that the loading or unloading apparatus **600** is unloaded, the loading or unloading apparatus **600** is at the unloading position; and in a case that the loading or unloading apparatus **600** is loaded, the loading or unloading apparatus **600** is at the loading position. In the present disclosure, only an example in which the loading or unloading apparatus **600** is at the unloading position is used for description. The loading or unloading apparatus **600** is located at the unloading position. After the transport robot **100** completes loading at the loading position, the transport robot **100** moves to the unloading position. At this time, the transport robot **100** is docked with the loading or unloading apparatus **600**, and the loading or unloading apparatus **600** may receive and pick the goods **200** in the plurality of storage assemblies **121** in the transport robot **100**. Certainly, the reverse transport of the goods **200** may also be implemented at this position, that is, after the transport robot **100** is docked with the loading or unloading apparatus **600**, the loading or unloading apparatus **600** may transfer the goods **200** to the

plurality of storage assemblies **121**.

(315) Specifically, the upright frame **610** plays a supporting role, and is configured to support the plurality of loading or unloading mechanisms **620** configured to transport the goods **200**. The loading or unloading apparatus **600** includes a same quantity of loading or unloading mechanisms **620** as the plurality of storage assemblies **121**. The plurality of loading or unloading mechanisms **620** may separately convey, at different heights, the goods **200** to the transport robot **100**, or unload the goods **200** on the transport robot **100**, which greatly shortens the waiting time of the transport robot **100** during a loading or unloading process. In addition, heights at which the plurality of loading or unloading mechanisms **620** are located are consistent with heights at which corresponding storage assemblies **121** are located. After the transport robot **100** is docked with the loading or unloading apparatus **600**, the plurality of storage assemblies **121** and the plurality of loading or unloading mechanisms **620** are at same heights, and the plurality of loading or unloading mechanisms **620** may convey the goods **200** to all storage assemblies **121** on the transport robot **100** at one time, or the plurality of loading or unloading mechanisms **620** may implement one-time removal of goods **200** from all storage assemblies **121** on the transport robot **100**. Certainly, in specific working conditions, one or more loading or unloading mechanisms **620** in the loading or unloading apparatus **600** may simultaneously convey the goods **200** to the transport robot **100** or unload the goods **200** on the transport robot **100**.

(316) Each of the plurality of loading or unloading mechanisms **620** may act independently to convey the goods **200** to the transport robot **100** or unload the goods **200** on the transport robot **100**. Referring to FIG. **10** to FIG. **13**, in an embodiment, each of the plurality of loading or unloading mechanisms **620** includes a bracket **621**, a loading or unloading assembly **622**, and a loading or unloading driving member **623**, a plurality of brackets **621** are arranged on the upright frame **610** at intervals along the vertical direction, the loading or unloading driving member **623** and the loading or unloading assembly **622** are respectively arranged on corresponding brackets **621**, the loading or unloading assembly **622** is connected to the loading or unloading driving member **623**, and the loading or unloading assembly **622** is configured to convey the goods **200** to the plurality of storage assemblies **121** or unload the goods **200** in the plurality of storage assemblies **121**. The loading or unloading driving member **623** may allow a corresponding loading or unloading assembly **622** to individually convey the goods **200** to the transport robot **100** or unload the goods **200** on the transport robot **100**.

(317) Further, as shown in FIG. **10** to FIG. **13**, the loading or unloading assembly **622** includes a chain **6221** and a protrusion **6222**, the chain **6221** is rotatably arranged on the bracket **621** along a loading or unloading direction, and the protrusion **6222** is fixedly arranged on the chain **6221**. The loading or unloading driving member **623** includes a driving motor in driving connection with the chain **6221**; and the chain **6221** may carry the goods **200**. When the driving motor drives the chain **6221** to rotate, the protrusion **6222** pushes a bottom portion of the goods **200**, so as to push the goods **200** to the transport robot **100**, or the protrusion **6222** pulls a bottom portion of the goods **200**, so as to pull the goods **200** from the transport robot **100** to the chain **6221**, or the protrusion **6222** blocks the bottom portion of the goods **200**, and the goods **200** are transferred to the chain **6221** when the transport robot **100** moves away from the loading or unloading apparatus **600**. Specifically, the chain **6221** is arranged on two sprockets arranged at intervals along the loading or unloading direction, and an output shaft of the driving motor is in driving connection with one of the two sprockets. When rotating, the driving motor drives the chain **6221** to operate, and the protrusion **6222** pushes the bottom portion of the goods **200**, so as to push the goods **200** to the transport robot **100**, or the protrusion **6222** pulls the bottom portion of the goods **200**, so as to pull the goods **200** from the transport robot **100** to the chain **6221**. Furthermore, each of the plurality of loading or unloading mechanisms **620** includes two sets of loading or unloading assemblies **622**, the two sets of loading or unloading assemblies **622** are arranged on the bracket **621** in parallel and at intervals, and the driving motor is in driving connection with two chains **6221**. The two sets of

loading or unloading assemblies **622** can increase the stability during the loading or unloading of the goods **200**. In an embodiment of the present disclosure, as shown in FIG. **13**, each of the plurality of loading or unloading mechanisms **620** further includes a synchronization rod **624**, the two chains **6221** are separately in driving connection with the synchronization rod **624**, and the driving motor is in driving connection with one of the two chains **6221**. Specifically, the synchronization rod **624** connects two sprockets arranged at intervals along a horizontal direction perpendicular to the loading or unloading direction, thereby ensuring that the two chains **6221** rotate synchronously.

(318) In another embodiment, as shown in FIG. **10**, FIG. **11**, FIG. **14**, and FIG. **15**, each of the plurality of loading or unloading mechanisms **620** includes a loading or unloading cross arm **625** and a push-pull assembly **626**, one ends of a plurality of loading or unloading cross arms **625** are arranged on the upright frame **610** at intervals along the vertical direction, and the push-pull assembly **626** is rotatably arranged at other ends corresponding to the plurality of loading or unloading cross arms **625**. When rotating, the push-pull assembly **626** includes a push-pull position and an avoidance position, and when rotating to the push-pull position, push-pull assembly **626** conveys the goods **200** to the transport robot **100** or pulls down the goods **200** on the transport robot **100**. When the push-pull assembly **626** rotates to the avoidance position, the push-pull assembly **626** avoids the goods **200**. It can be understood that when pushing or pulling the goods **200**, the push-pull assembly **626** may push or pull a top portion, a middle portion, or a bottom portion of the goods **200**. In an embodiment of the present disclosure, two loading or unloading assemblies **620** are arranged at intervals in a same horizontal direction of the upright frame **610**, and two push-pull assemblies **626** in the same horizontal direction separately rotate to the push-pull position or the avoidance position. The two push-pull assemblies **626** in the same horizontal direction respectively drive two sides of the goods **200** along the loading or unloading direction. The two push-pull assemblies **626** push or pull the two sides of the goods **200** synchronously, which can effectively ensure the stability of a push-pull process of the goods **200**. Further, the two push-pull assemblies **626** in the same horizontal direction push/pull two sides of the middle portion of the goods **200** synchronously along the loading or unloading direction. It can be understood that the two push-pull assemblies **626** in the same horizontal direction rotate to the push-pull position or the avoidance position synchronously, or rotate to the push-pull position or the avoidance position successively.

(319) In an implementation, as shown in FIG. **14** and FIG. **15**, the push-pull assembly **626** includes a push-pull rod **6261** and a push-pull motor **6262**, the push-pull motor **6262** is arranged at one ends of the plurality of loading or unloading cross arms **625** away from the upright frame **610**, the push-pull rod **6261** is arranged on an output shaft of the push-pull motor **6262**, and the push-pull motor **6262** is configured to drive the push-pull rod **6261** to rotate to the push-pull position or the avoidance position. Two push-pull rods **6261** may separately be rotated to the push-pull position under the driving of the push-pull motor **6262**, so as to pull the goods **200** out of the transport robot **100** or push the goods **200** to the transport robot **100**.

(320) In an embodiment, all loading or unloading mechanisms **620** in the loading or unloading apparatus **600** act synchronously to convey, at different heights, the goods **200** to the transport robot **100** or unload the goods **200** on the transport robot **100**, or some of the plurality of loading or unloading mechanisms **620** in the loading or unloading apparatus **600** act independently to convey, at specified heights, the goods **200** to the transport robot **100** or unload the goods **200** on the transport robot **100**. As shown in FIG. **16** and FIG. **17**, in an implementation, the loading or unloading apparatus **600** further includes an adjustment drive mechanism **630** configured to drive the upright frame **610** to approach or move away from the transport robot **100** along the loading or unloading direction, and when the adjustment drive mechanism **630** drives the upright frame **610** to approach the transport robot **100**, the plurality of loading or unloading mechanisms **620** convey the goods **200** to the transport robot **100** or unload the goods **200** on the transport robot **100**. The

loading or unloading apparatus **600** provided in this embodiment can remove all the goods **200** or specified goods **200** on the transport robot **100** at one time, or simultaneously convey a plurality of goods **200** to the transport robot **100**. In an implementation, the adjustment drive mechanism **630** adopts a driving structure in the form of a motor and a belt.

(321) In an embodiment of the present disclosure, the loading or unloading apparatus **600** further includes a temporary storage shelving unit **640**, the upright frame **610** is movably arranged on the temporary storage shelving unit **640** along a horizontal direction, and the adjustment drive mechanism **630** is configured to drive the upright frame **610** to move relative to the temporary storage shelving unit **640** along the horizontal direction. The temporary storage shelving unit **640** includes a shelving unit with a plurality of layers along the vertical direction, and the plurality of loading or unloading mechanisms **620** are configured to pull goods **200** at different heights on the transport robot **100** to corresponding layers of the shelving unit on the temporary storage shelving unit **640**, or the plurality of loading or unloading mechanisms **620** are configured to push goods **200** on the plurality of layers of the shelving unit to the transport robot **100**. The temporary storage shelving unit **640** can temporarily store the goods **200** unloaded from the transport robot **100** by the loading or unloading apparatus **600**, or temporarily store the to-be-transported goods **200** which are transported to the transport robot **100**. In an implementation, the temporary storage shelving unit **640** includes a temporary storage roller **641** with a plurality of layers arranged along the vertical direction, and each layer of the temporary storage roller **641** is capable of individually transporting the goods **200** along the loading or unloading direction. Optionally, each layer of the temporary storage roller **641** can simultaneously carry a plurality of goods **200**.

(322) In an embodiment, the loading or unloading apparatus **600** further includes a movable base arranged at a bottom portion of the upright frame **610**. The loading or unloading apparatus **600** further includes a movable base arranged at the bottom portion of the upright frame **610**. The movable base can drive the loading or unloading apparatus **600** to move, which greatly improves the adaptability of the loading or unloading apparatus **600** to actual working conditions. In this way, the loading or unloading apparatus **600** can easily move to the loading position, the unloading position, or any other position, to work with the transport robot **100**. Optionally, a structure of the base is exactly the same as that of the chassis **160** of the transport robot **100**, and details are not described herein again.

(323) Referring to FIG. **9** and FIG. **11**, in an embodiment, the transport system further includes a conveying apparatus **500** and a lifting apparatus **400** that is arranged between the loading or unloading apparatus **600** and the conveying apparatus **500**, and the lifting apparatus **400** is configured to ascend or descend along the vertical direction, so as to be docked with each of the plurality of loading or unloading mechanisms **620** and the conveying apparatus **500**. The lifting apparatus **400** is capable of receiving and picking the goods **200** of the plurality of loading or unloading mechanisms **620** and transferring the goods to the conveying apparatus **500**; or the lifting apparatus **400** is capable of receiving and picking goods **200** of the conveying apparatus **500** and transferring the goods to the plurality of loading or unloading mechanisms **620**.

(324) The lifting apparatus **400** is configured to receive and pick the goods **200** of the plurality of loading or unloading mechanisms **620** or transport the goods **200** to the plurality of loading or unloading mechanisms **620**. Because the plurality of loading or unloading mechanisms **620** are arranged at intervals along the vertical direction, to facilitate the goods loading or unloading of the loading or unloading apparatus **600**, the lifting apparatus **400** needs to move to a loading or unloading mechanism **620** at a corresponding position, so as to perform a corresponding operation. The conveying apparatus **500** is configured to convey the goods **200**, may transport away goods **200** unloaded by the lifting apparatus **400**, and may also transport to-be-loaded goods **200** to the lifting apparatus **400**. Optionally, the conveying apparatus **500** may be of a structure that can implement the horizontal transport, such as a conveyor belt structure, an assembly line, a conveying roller structure, or a roller structure, or the like. Exemplarily, the conveying apparatus

500 is of an assembly line structure, and specifically, when unloading, the lifting apparatus **400** ascends to one side of a loading or unloading mechanism **620**, after receiving the goods **200** of the loading or unloading mechanism **620**, the lifting apparatus **400** descends, and transfers the goods **200** to the conveying apparatus **500**, and the goods are transported away by the conveying apparatus **500**. Subsequently, the lifting apparatus **400** further ascends to another loading or unloading mechanism **620**, and this process is repeated until all the goods **200** on the plurality of loading or unloading mechanisms **620** are transported away. When loading, after the lifting apparatus **400** descends and receives and picks the goods **200** conveyed by the conveying apparatus **500**, the lifting apparatus **400** ascends to one side of a loading or unloading mechanism **620** and transfers the goods **200** to the loading or unloading mechanism **620**; and subsequently, the lifting apparatus **400** further descends to the conveying apparatus **500**, and this process is repeated until the plurality of loading or unloading mechanisms **620** are loaded with the goods **200**.

(325) In an embodiment, the lifting apparatus **400** includes a lifting frame **410** along the vertical direction, a moving mechanism **420** arranged on the lifting frame **410**, and a transfer mechanism **430** with at least one layer arranged on the moving mechanism **420**, and the moving mechanism **420** may ascend or descend along the lifting frame **410** and drive the transfer mechanism **430** with at least one layer to move, so as to receive and pick or transfer the goods **200** to the plurality of loading or unloading mechanisms **620**. The lifting frame **410** has a bearing function, and is configured to bear the moving mechanism **420** and the transfer mechanism **430** with at least one layer. Optionally, a bottom portion of the lifting frame **410** may also be provided with rotating wheels, so as to adapt to different applications. The transfer mechanism **430** with at least one layer is configured to carry the goods **200** and implement the transfer of the goods **200** between a high position such as a loading or unloading mechanism **620** and a low position such as the conveying apparatus **500**. The moving mechanism **420** is arranged on the lifting frame **410** along the vertical direction, and may output movement in the vertical direction, so as to drive the transfer mechanism **430** with at least one layer to ascend or descend.

(326) It can be understood that the moving mechanism **420** is configured to implement the ascending or descending motion of the transfer mechanism **430** with at least one layer along the vertical direction. A specific structure of the moving mechanism **420** may be a telescopic rod structure, a chain transmission structure, a driving transmission structure, or the like, and may also be another structure capable of enabling the carrying mechanism **150** to ascend or descend. Exemplarily, a specific structure of the moving mechanism **420** is the same as a structure of the lifting mechanism **140** of the transport robot **100**, and details are not described herein again. Certainly, the specific structure of the moving mechanism **420** may also be different from the structure of the lifting mechanism **140** of the transport robot **100**, as long as the moving mechanism **420** can implement the ascending or descending motion.

(327) Exemplarily, there is a transfer mechanism **430** with one layer, and the transfer mechanism **430** with one layer receives and picks goods **200** from one loading or unloading mechanism **620** at one time, or transfers goods **200** to one loading or unloading mechanism **620** at one time. Certainly, in another implementation of the present disclosure, in a case that there is a transfer mechanism **430** with at least two layers, the transfer mechanism **430** with at least two layers may remove goods **200** of at least two loading or unloading mechanisms **620** at one time, or transfer goods **200** to at least two loading or unloading mechanisms **620**, so as to improve the efficiency of turnover of the goods **200**.

(328) In an embodiment, the transfer mechanism **430** with at least one layer includes a transfer base **431** arranged on the moving mechanism **420** and a transfer portion **432** movably arranged on the transfer base **431**, and the transfer portion **432** may drive the goods **200** to move, and may receive and pick or transfer the goods **200** to at least one of the plurality of loading or unloading mechanisms **620**. The transfer base **431** plays a bearing role and is configured to carry the transfer portion **432**, so as to mount the transfer portion **432** on the moving mechanism **420**. When the

moving mechanism **420** ascends or descends, the transfer base **431** may drive the transfer portion **432** to ascend or descend synchronously, so as to implement the loading or unloading of the goods **200**.

(329) Optionally, the transfer portion **432** is of a structure that can implement horizontal transport, such as a conveyor belt structure, an assembly line, a conveyor roller structure, a roller structure, or the like. Exemplarily, the transfer portion **432** is of a rolling shaft structure, and specifically includes a plurality of rolling shafts, and each of the plurality of rolling shafts includes a built-in rolling motor to drive the each of the plurality of rolling shafts to rotate, thereby implementing the transport of the goods **200**. It should be noted that, there are various structures that can implement the horizontal transport of the goods **200**, which cannot all be listed herein, and the transfer portion **432** in the present disclosure is not limited to being implemented by the foregoing specific structures.

(330) The transfer portion **432** may receive and pick the goods **200** of one loading or unloading mechanism **620** at one time, as mentioned above. The transfer portion **432** may also receive and pick the goods **200** of a plurality of loading or unloading mechanisms **620** at one time, and the moving mechanism **420** may receive and pick the goods **200** of the plurality of loading or unloading mechanisms **620** layer by layer, and then convey the goods to the conveying apparatus **500** together for transport after receiving and picking the goods. Exemplarily, the moving mechanism **420** drives the transfer portion **432** to ascend to a top portion. After receiving and picking goods **200** of one loading or unloading mechanism **620**, the transfer portion **432** descends one layer to receive and pick goods **200** of one loading or unloading mechanism **620**. After the transfer portion **432** is full or the goods **200** of the plurality of loading or unloading mechanisms **620** are received, the moving mechanism **420** drives the transfer portion **432** to descend to a position of the conveying apparatus **500**, and the transfer portion **432** transfers all the goods **200** thereon to the conveying apparatus **500**. Certainly, the moving mechanism **420** may move layer by layer from bottom to top, a principle thereof is substantially the same as a principle from top to bottom, and details are not described herein again.

(331) Certainly, the transfer portion **432** may also receive and pick a plurality of goods **200** transferred by the conveying apparatus **500** at one time, and then transfer the goods to the plurality of loading or unloading mechanisms **620** layer by layer, a principle thereof is substantially the same as the foregoing principle of goods unloading, and details are not described herein again.

(332) In the transport robot **100** and the transport system in the present disclosure, when transporting goods, a blocking mechanism **170** moves to a blocking position and may be in abutment with goods **200** in a plurality of storage assemblies **121**, so as to restrict the goods **200** from sliding out of the plurality of storage assemblies **121**. Therefore, the goods **200** are prevented from sliding out of the plurality of storage assemblies **121** during a transport process of the transport robot **100**, the safety of the goods **200** is ensured, a risk of sliding out is avoided, and the transport efficiency is improved. In addition, when the transport robot **100** loads or unloads goods, the blocking mechanism **170** moves to an avoidance position. At this time, the goods **200** may be loaded into the plurality of storage assemblies **121**, and the goods **200** in the plurality of storage assemblies **121** may also be removed, which does not hinder a loading or unloading operation of the transport robot **100**, and is convenient for use.

Embodiment 4

(333) Referring to FIG. 1, FIG. 3, FIG. 6, FIG. 9, and FIG. 11, the present disclosure provides a transport robot **100**. The transport robot **100** is applied to a transport system, and can transport goods **200**. It can be understood that the goods **200** may be goods with a bracket, and the transport robot **100** transports the goods **200** through the bracket; and certainly, the goods may alternatively be goods placed in a container, and the transport robot **100** transports the goods **200** through a box. The goods **200** described below are goods placed in a box, and the box may be loaded with the goods **200**, so as to implement the transport of the goods **200**. The transport robot **100** transports

the box to an unloading position, and after unloading the goods **200** in the box, the box may be transported back to the transport robot **100**, so as to reuse the box and reduce the cost.

Alternatively, the goods **200** is a box with goods, and the transport robot **100** transports the box to the unloading position, and unloads the box with goods through an unloading apparatus.

(334) The transport robot **100** plays an important role in intelligent warehousing, transports goods **200**, ensures a transport speed of the goods **200**, improves the transport efficiency of the goods **200**, and reduces the consumption of labor resources. The transport robot **100** of the present disclosure can unload synchronously, so that goods **200** in the transport robot **100** can be unloaded at one time, thereby improving the unloading efficiency, reducing the unloading time, and improving the overall working efficiency of the transport robot **100**.

(335) Referring to FIG. 1 and FIG. 3, in an embodiment, the transport robot **100** includes a vertical frame **110** and a storage mechanism **120**. The vertical frame **110** is arranged along a vertical direction. The storage mechanism **120** includes a plurality of storage assemblies **121** configured to store to-be-transported goods **200** and arranged on the vertical frame **110** at equal intervals along the vertical direction.

(336) The vertical frame **110** plays a bearing role, and various components of the transport robot **100** are mounted thereon. When the transport robot **100** transports the goods **200**, the vertical frame **110** may drive synchronous movement of the components on the transport robot **100**, so as to implement the transport of the goods **200**. The storage mechanism **120** is located on the vertical frame **110**, is configured to store the goods **200**, and is capable of moving synchronously with the vertical frame **110**, so as to implement the transport of the goods **200**. The transport robot **100** moves to a loading position, and the to-be-transported goods **200** are transported to the storage mechanism **120** for storage. Then, the transport robot **100** moves from the loading position to an unloading position. Correspondingly, the storage mechanism **120** moves to the unloading position along with the vertical frame **110**. At this time, the goods **200** in the storage mechanism **120** can be unloaded. The storage mechanism **120** can temporarily store the to-be-transported goods **200**, thereby improving the capability of the transport robot **100** to carry the goods **200**.

(337) In addition, the storage mechanism **120** includes a plurality of storage assemblies **121** arranged on the vertical frame **110** at intervals. Each of the plurality of storage assemblies **121** can carry goods **200** of a box to ensure a storage capacity of the transport robot **100**. Optionally, a distance between two adjacent storage assemblies **121** may be equal or not equal. Exemplarily, the plurality of storage assemblies **121** are evenly distributed on the vertical frame **110** along the vertical direction. The to-be-transported goods **200** may be transported to the plurality of storage assemblies **121**, and the transport robot **100** drives the goods **200** in the plurality of storage assemblies **121** to be transported to the unloading position.

(338) Referring to FIG. 1 and FIG. 3, in an embodiment, the transport robot **100** further includes a lifting mechanism **140** capable of ascending or descending relative to the vertical frame **110** along the vertical direction and a carrying mechanism **150** configured to carry the goods **200**, where the carrying mechanism **150** is movably arranged on the vertical frame **110** along the vertical direction, is connected to the lifting mechanism **140**, and is capable of ascending or descending along the vertical direction under driving of the lifting mechanism **140**, so as to deliver goods **200** in the carrying mechanism **150** to a corresponding storage mechanism **120**.

(339) The carrying mechanism **150** is a terminal configured to perform an action of the transport robot **100**. At the loading position, the carrying mechanism **150** may carry the to-be-transported goods **200**, and transport the goods **200** into the plurality of storage assemblies **121**. Certainly, in some occasions, in a case that the goods **200** in the plurality of storage assemblies **121** need to be unloaded separately, the carrying mechanism **150** may also take out the goods **200** in the plurality of storage assemblies **121**. Optionally, the carrying mechanism **150** includes, but is not limited to, a mechanical arm, an actionable tow bar, or a plane with a conveying function, and the like. The lifting mechanism **140** is configured to implement the ascending or descending movement of the

carrying mechanism **150**, and is capable of driving the carrying mechanism **150** to ascend or descend along the vertical direction.

(340) At the loading position, there is a shelving unit with a plurality of layers configured to carry goods **200**. When loading goods at the loading position of the transport robot **100**, the lifting mechanism **140** drives the carrying mechanism **150** to ascend or descend, so that the carrying mechanism **150** can pick goods on the shelving unit. Then, the lifting mechanism **140** drives the carrying mechanism **150** to ascend or descend, so as to transfer the goods **200** in the carrying mechanism **150** to the plurality of storage assemblies **121**. This process is repeated until the plurality of storage assemblies **121** store the goods **200**. After the loading is completed, the transport robot **100** moves from the loading position to the unloading position, and the plurality of storage assemblies **121** may perform a synchronous unloading operation. After the unloading is completed, the transport robot **100** returns to the loading position, so that continuous transport of the goods **200** can be implemented by repeating the process, thereby improving the transport efficiency.

(341) The function of the lifting mechanism **140** is to drive the carrying mechanism **150** to ascend or descend along the vertical direction. In an embodiment, the lifting mechanism **140** includes a lifting power source and a lifting transmission component, and the lifting power source and the lifting transmission component are separately arranged on the vertical frame **110**. The lifting transmission component is in driving connection with the lifting power source and the carrying mechanism **150**. Specifically, an output end of the lifting power source is in driving connection with an input end of the lifting transmission component, and an output end of the lifting transmission component is in driving connection with the carrying mechanism **150**. That the lifting power source and the lifting transmission component are separately arranged on the vertical frame **110**, and the driving connection between the lifting power source and the lifting transmission component facilitate the disassembly or assembly of the lifting mechanism **140** on the vertical frame **110**. Optionally, a power output from the lifting power source is in a form of rotation and linear motion, or in any other form of motion, and a final output of the lifting transmission component in driving connection with the lifting power source is movement along the vertical direction. Optionally, the lifting power source includes a driving motor in driving connection with the input end of the lifting transmission component. The lifting power source in a form of a motor runs more stably. Further, the driving motor can rotate forwardly or reversely, which facilitates the control of an ascending or descending process of the lifting mechanism **140**.

(342) Optionally, the lifting transmission component may be of a telescopic rod structure, a chain transmission structure, a driving transmission structure, or the like, and may also be of another structure capable of enabling the carrying mechanism **150** to ascend or descend. Exemplarily, the lifting transmission component is of a chain transmission structure, including a sprocket and a chain, the chain is connected to the carrying mechanism **150**, and the chain is arranged on the vertical frame **110** along the vertical direction. When the output end of the lifting power source drives the sprocket to rotate, the chain ascends or descends along the vertical frame **110**, which may further drive the carrying mechanism **150** to ascend or descend.

(343) It should be noted that, the essence of the lifting transmission component is to output the ascending or descending motion to drive the carrying mechanism **150** to ascend or descend, thereby implementing the loading of the goods **200**. In this embodiment, the lifting transmission component is implemented by a chain transmission structure. In addition, there are various structures that can implement ascending or descending, which cannot all be listed herein, and the manner of the ascending or descending motion in the present disclosure is not limited to being implemented by the foregoing specific structures.

(344) In an embodiment, the transport robot **100** further includes a rotary mechanism arranged between the carrying mechanism **150** and the lifting mechanism **140** and configured to drive the carrying mechanism **150** to rotate relative to the lifting mechanism **140**, so that the carrying

mechanism **150** is aligned with a corresponding storage mechanism **120**. The rotary mechanism is rotatably connected to the carrying mechanism **150**, and the carrying mechanism **150** is rotatable relative to the rotary mechanism. When the carrying mechanism **150** is rotated by the rotary mechanism, a direction of the carrying mechanism **150** may be adjusted, so that the loading or unloading port of the carrying mechanism **150** can be adjusted. The carrying mechanism **150** implements the loading or unloading of the goods **200** through the loading or unloading port. When the transport robot **100** is at the loading position, the rotary mechanism may drive the carrying mechanism **150** to rotate, so that the loading or unloading port of the carrying mechanism **150** faces a shelving unit, and the goods **200** can be loaded into the carrying mechanism **150**. When the carrying mechanism **150** transfers the goods **200** to the plurality of storage assemblies **121**, the rotary mechanism may drive the carrying mechanism **150** to rotate, so that the loading or unloading port of the carrying mechanism **150** faces the plurality of storage assemblies **121**. At this time, the goods **200** in the carrying mechanism **150** can be transferred to the plurality of storage assemblies **121**.

(345) Optionally, the rotary mechanism includes a carrying bracket, an autorotation gear arranged on the carrying bracket, and an autorotation motor fixedly mounted on the carrying bracket. An output end of the autorotation motor is connected to the autorotation gear, the carrying mechanism **150** is mounted on the autorotation gear, and the carrying bracket is mounted on the lifting mechanism **140**. The autorotation motor may drive the autorotation gear to rotate, which may further drive the carrying mechanism **150** to rotate.

(346) It should be noted that, the essence of the rotary mechanism is to output a rotation motion, so as to drive the carrying mechanism **150** to rotate, thereby implementing the loading or unloading of the goods **200**. In this embodiment, the rotary mechanism is implemented by an autorotation motor and an autorotation gear. In addition, there are various structures that can implement rotation, which cannot all be listed herein, and the manner of the rotation motion in the present disclosure is not limited to being implemented by the foregoing specific structures.

(347) When the transport robot **100** in the foregoing embodiment loads goods, the lifting mechanism **140** drives the carrying mechanism **150** to transfer the goods **200** to a plurality of storage assemblies **121** at corresponding heights in the storage mechanism **120**. When unloading, the lifting mechanism **140** drives the carrying mechanism **150** to take out the goods **200** in a plurality of storage assemblies **121** at corresponding heights in the storage mechanism **120**. Through the cooperation between the lifting mechanism **140** and the carrying mechanism **150**, the automation of loading or unloading of the goods **200** is implemented, a problem of high cost and low efficiency in a current transport method is effectively resolved, the cost of the loading or unloading of the goods is reduced, and the efficiency of the loading or unloading of the goods **200** is greatly improved. In addition, the carrying mechanism **150** moves to different heights under the driving of the lifting mechanism **140**, so that the to-be-transported goods **200** can be delivered to a plurality of storage assemblies **121** at different heights in the storage mechanism **120**, which has strong versatility and reduces the floor space.

(348) Referring to FIG. 1 and FIG. 3, in an embodiment, the carrying mechanism **150** includes a transition member **151** and a pick-or-place member **152** that is telescopically arranged on the transition member **151**, and the pick-or-place member **152** is capable of taking out goods **200** and storing the goods in the transition member **151**, and is further capable of pushing out goods **200** in the transition member **151**. The pick-or-place member **152** is telescopically arranged in the transition member **151**. At the loading position, the pick-or-place member **152** extends out of the transition member **151** to take out goods **200** on a shelving unit, and then the pick-or-place member **152** retracts into the transition member **151** to temporarily store the goods **200** in the transition member **151**. Subsequently, the lifting mechanism **140** and the rotary mechanism drive the carrying mechanism **150** to move, so that the carrying mechanism **150** moves to a plurality of storage assemblies **121** in which the goods are to be placed. At this time, the pick-or-place member **152**

extends out of the transition member **151**, moves the goods **200** out of the transition member **151**, and transfers the goods to the plurality of storage assemblies **121**. After the transfer, the pick-or-place member **152** retracts into the transition member **151**. Optionally, the transition member **151** includes, but is not limited to, a transition box, and the pick-or-place member **152** includes, but is not limited to, a structure in which a telescopic motor cooperates with a telescopic rod, a mechanical arm mechanism, and the like.

(349) In an embodiment, the transport robot **100** further includes a movable chassis **160** arranged at a bottom portion of the vertical frame **110**. The movable chassis **160** can drive the transport robot **100** to move, which greatly improves the adaptability of the transport robot **100** to actual working conditions. Specifically, the chassis **160** includes a chassis frame **161**, a travel drive assembly, and a plurality of rotating wheels **162**, the vertical frame **110** is arranged on an upper portion of the chassis frame **161**, the plurality of rotating wheels **162** are arranged on a bottom portion of the chassis frame **161**, the travel drive assembly is arranged on the chassis frame **161**, and at least one of the plurality of rotating wheels **162** is in driving connection with the travel drive assembly. Further, at least two of the plurality of rotating wheels **162** are separately in driving connection with the travel drive assembly, and the at least two of the plurality of rotating wheels **162** being separately in driving connection with the travel drive assembly are distributed on two sides of the chassis frame **161** along a traveling direction, thereby achieving a steering function of the chassis **160**. The travel drive assembly includes at least two wheel drive motors, and the at least two of the plurality of rotating wheels **162** distributed on the two sides of the chassis frame **161** along the traveling direction are respectively driven by separate wheel drive motors. That the at least two of the plurality of rotating wheels **162** distributed on the two sides of the chassis frame **161** along the traveling direction are respectively driven by separate wheel drive motors can simplify a transmission structure on the chassis **160**.

(350) In an embodiment, each of the plurality of rotating wheels **162** includes a driving wheel and a driven wheel. The driving wheel and the driven wheel are mounted on a bottom portion of the chassis **160**, may separately rotate relative to the chassis **160**, and jointly support the chassis **160**. The driving wheel is driven by a wheel drive motor to enable the chassis **160** to move. By configuring the movable chassis **160**, the transport robot **100** can transport the goods **200** between the loading position and the unloading position. There are two driving wheels, and the two driving wheels are symmetrically distributed. Correspondingly, there are two wheel drive motors, and the two driving wheels are respectively driven by the two wheel drive motors, so that rotational speeds of the two driving wheels are different, thereby implementing the steering of the chassis **160**. There are four driven wheels, and the four driven wheels are distributed in a rectangular shape. The four driven wheels may be universal wheels or may be of other wheel structures with a steering function. According to actual situations, a quantity of the driven wheel is not limited to four, but may also be six, three, or the like.

(351) In this embodiment, the chassis **160** is also mounted with a guiding apparatus, and the guiding apparatus is a camera configured to identify a graphic code attached to a ground, so that the chassis **160** travels along a preset path. The graphic code may be a two-dimensional code, a barcode, or some customized identification codes. In some other embodiments, the guiding apparatus is a laser guiding apparatus configured to guide the chassis **160** to travel along a laser beam, or the guiding apparatus is a short-wave receiving apparatus configured to receive a preset short-wave signal to guide the chassis **160** to travel along a preset path. It should be noted that, in some other embodiments, the chassis **160** may be omitted, and the vertical frame **110** is directly and fixedly mounted on the ground or another platform, and is only configured to carry the goods **200** between the loading position and the unloading position around the vertical frame.

First Embodiment

(352) Referring to FIG. 1 to FIG. 8, in the first embodiment, when the transport robot **100** is unloading, a plurality of storage assemblies **121** are capable of moving synchronously to perform a

synchronous unloading action.

(353) To further improve the transport efficiency of the transport robot **100**, the transport robot **100** of the present disclosure can implement synchronous unloading at the unloading position. Specifically, during unloading, a plurality of storage assemblies **121** may move synchronously, so that the goods **200** are moved out of the plurality of storage assemblies **121**, and a synchronous unloading action is performed in real time. In this way, the goods **200** in the plurality of storage assemblies **121** can be unloaded synchronously, which shortens the unloading time and improves the unloading efficiency of the transport robot **100**. After the unloading is completed, the transport robot **100** may return to the loading position to continue loading, which improves the working efficiency of the transport robot **100**.

(354) In this embodiment described above, when the transport robot **100** is unloading, a plurality of storage assemblies **121** of a storage mechanism **120** may move synchronously to perform a synchronous unloading action, so that the synchronous unloading of goods **200** in the plurality of storage assemblies **121** is implemented, the current problem of a low unloading efficiency caused by the layer-by-layer unloading of goods is effectively resolved, goods **200** in the transport robot **100** can be unloaded at one time, the unloading efficiency is improved, the unloading time is reduced, and the overall working efficiency of the transport robot **100** is improved.

(355) Referring to FIG. 1 to FIG. 4, in an embodiment, the transport robot **100** further includes at least one linkage mechanism **130**, and each of the at least one linkage mechanism **130** is connected to at least two storage assemblies **121** and is configured to drive the at least two storage assemblies **121** to move synchronously relative to the vertical frame **110** to perform a synchronous unloading action. When the at least one linkage mechanism **130** moves, a synchronous movement of the at least two storage assemblies **121** may be implemented. It can be understood that one linkage mechanism **130** may be connected to all storage assemblies **121**, and alternatively, among a plurality of linkage mechanisms **130**, each of the plurality of linkage mechanisms **130** may be connected to a plurality of storage assemblies **121**. Exemplarily, there are two linkage mechanisms **130**, where one of the two linkage mechanisms **130** is connected to storage assemblies **121** of first to third layers, and the other one of the two linkage mechanisms **130** is connected to storage assemblies **121** of fourth to sixth layers. Certainly, in another implementation of the present disclosure, there may be more linkage mechanisms **130**. The present disclosure is only described by taking an example in which one linkage mechanism **130** is connected to all storage assemblies **121**. A working principle of a plurality of linkage mechanisms **130** is substantially the same as that of the one linkage mechanism **130**, and details are not described herein again.

(356) The storage mechanism **120** may be rotatably mounted on the vertical frame **110**, and may further be connected to the linkage mechanism **130**. When moving, the linkage mechanism **130** drives the plurality of storage assemblies **121** to rotate relative to the vertical frame **110**, so that the plurality of storage assemblies **121** can undergo a pitching motion. It can be understood that one end of the linkage mechanism **130** may be mounted on the vertical frame **110** or the chassis **160**, as long as the linkage mechanism **130** can drive the plurality of storage assemblies **121** to undergo a pitching motion.

(357) When the linkage mechanism **130** drives the plurality of storage assemblies **121** to move upward, one ends of the plurality of storage assemblies **121** are lifted up, and other ends rotate relative to the vertical frame **110**, so as to stay at initial positions. At this time, the plurality of storage assemblies **121** are lifted up, and goods **200** thereon may slide out of the plurality of storage assemblies **121** under an action of gravity thereof, so as to implement the unloading of the goods **200**. Because the linkage mechanism **130** simultaneously drives the plurality of storage assemblies **121** to move upward, the plurality of storage assemblies **121** can be simultaneously lifted up, thereby simultaneously performing an unloading operation to implement the unloading. After the unloading is completed, the linkage mechanism **130** drives the plurality of storage assemblies **121** to descend, and the plurality of storage assemblies **121** return to horizontal initial

positions.

(358) When the linkage mechanism **130** drives the plurality of storage assemblies **121** to move downward, and after external goods **200** are simultaneously conveyed to the plurality of storage assemblies **121**, the goods **200** can slide into the plurality of storage assemblies **121** under the action of gravity to implement synchronous loading. It should be noted that the synchronous loading of the transport robot **100** needs to be implemented in cooperation with an auxiliary apparatus **300** of the transport system, a specific implementation process is described in detail in the following specification, and only the synchronous unloading of the transport robot **100** is described in detail in this embodiment.

(359) After the transport robot **100** loads the goods **200** into the plurality of storage assemblies **121** at the loading position, the transport robot **100** moves from the loading position to the unloading position. At this time, the linkage mechanism **130** drives the plurality of storage assemblies **121** to move upward, so that the plurality of storage assemblies **121** are lifted up. In this way, the goods **200** in the plurality of storage assemblies **121** can slide out of the plurality of storage assemblies **121** under the action of gravity thereof, and be stored in a specified apparatus such as the auxiliary apparatus **300**, so as to implement the synchronous unloading of the transport robot **100**. After the unloading is completed, the transport robot **100** returns to the loading position to load goods, and in this way, a transport function of the transport robot **100** is achieved.

(360) In an embodiment, the linkage mechanism **130** includes a linkage connector **131** simultaneously connected to at least two storage assemblies **121** and capable of synchronously driving the at least two storage assemblies **121** to synchronously undergo a pitching motion. It can be understood that the pitching motion herein may be a pitching rotational motion, or a curved motion, and certainly, may also be in other forms that can generate the pitching motion. One ends of the at least two storage assemblies **121** are rotatably connected to the vertical frame **110**, and the at least two storage assemblies **121** are also connected to the linkage connector **131**. The linkage connector **131** can ascend or descend. When ascending or descending, the linkage connector **131** may drive the at least two storage assemblies **121** to ascend or descend, so that the at least two storage assemblies **121** rotate relative to the vertical frame **110**, that is, the at least two storage assemblies **121** undergo a pitching motion. It can be understood that, when one of the at least two storage assemblies **121** undergo a pitching motion, the linkage connector **131** is driven to ascend or descend, and the remaining storage assemblies **121** may be driven to move through the linkage connector **131**; or the linkage connector **131** ascends or descends, and then the at least two storage assemblies **121** are driven to move.

(361) As shown in FIG. 1 and FIG. 2, optionally, the linkage connector **131** and the at least two storage assemblies **121** may be rotatably connected or fixedly connected. When the linkage connector **131** and the at least two storage assemblies **121** are rotatably connected, the at least two storage assemblies **121** may have a rotary shaft, and the at least two storage assemblies **121** may be rotatably mounted on the linkage connector **131** through the rotary shaft. Alternatively, the linkage connector **131** may have a rotary shaft, and the linkage connector **131** may be rotatably mounted on the at least two storage assemblies **121** through the rotary shaft. Alternatively, a connection between the linkage connector **131** and the at least two storage assemblies **121** is similar to an olecranon engagement structure. In addition, the rotary shaft may be replaced with a hinge or another component that can implement a rotatable connection.

(362) Optionally, the linkage connector **131** may be a connecting rod connected to the at least two storage assemblies **121**. Further optionally, the linkage member may include a plurality of connecting rods, and two adjacent linkage members are connected by the plurality of connecting rods. In this case, when one of the at least two storage assemblies **121** moves, adjacent connecting rods may drive the remaining storage assemblies **121** to move. It can be understood that a specific structure of the linkage connector **131** is not limited to the connecting rod, but may also be a connecting piece or the like.

(363) It should be noted that, the essential spirit of the present disclosure lies in the linkage between the linkage connector **131** and the at least two storage assemblies **121**, and the linkage connector **131** can implement the synchronous movement of the at least two storage assemblies **121**, thereby performing a synchronous unloading operation. In this embodiment, the connection of connectors is implemented by connecting rods, and there may be one or more connecting rods. In addition, there are various arrangements of the linkage connector **131**, which cannot all be listed herein, and a linkage manner in the present disclosure is not limited to being implemented by the foregoing specific structures.

(364) Referring to FIG. 1 and FIG. 3, in an embodiment, in a same horizontal direction, a distance between the linkage connector **131** and the vertical frame **110** is less than or equal to a length of each of the plurality of storage assemblies **121**. It can be understood that a length at a connection position between the linkage connector **131** and the plurality of storage assemblies **121** may be equal to the length of each of the plurality of storage assemblies **121**. In this case, the linkage connector **131** and the vertical frame **110** are respectively located at two ends of the plurality of storage assemblies **121**. The length at the connection position between the linkage connector **131** and the plurality of storage assemblies **121** may be less than the length of each of the plurality of storage assemblies **121**, and the connection position between the linkage connector **131** and the plurality of storage assemblies **121** is located on side surfaces of the plurality of storage assemblies **121**. That is, the linkage connector **131** may be located at any position on a peripheral side of each of the plurality of storage assemblies **121**. In this way, the linkage connector **131** can drive the plurality of storage assemblies **121** to synchronously ascend or descend when the linkage connector **131** ascends or descends, so as to perform the synchronous unloading operation of the transport robot **100**.

(365) In an embodiment, there may be at least one linkage connector **131**. In a case that there is one linkage connector **131**, the cooperation between the linkage connector with the vertical frame **110** can ensure that the plurality of storage assemblies **121** are fixed and reliable, and simultaneously implement the driving of the movement of the plurality of storage assemblies **121**. In a case that there are a plurality of linkage connectors **131**, the plurality of linkage connectors **131** can further improve the linkage of the plurality of storage assemblies **121** and ensure that the plurality of storage assemblies **121** move in a consistent manner.

(366) In a case that there is one linkage connector **131**, the linkage connector **131** and the vertical frame **110** are respectively arranged at two ends of the plurality of storage assemblies **121**. That is, the connection position between the linkage connector **131** and the plurality of storage assemblies **121** and the vertical frame **110** are respectively located at the two ends of the plurality of storage assemblies **121**, and a distance between the connection position and the vertical frame **110** is equal to a size of each of the plurality of storage assemblies **121** along a horizontal direction. In this way, the plurality of storage assemblies **121** can be reliably supported by the linkage connector **131** and the vertical frame **110**, to prevent the plurality of storage assemblies **121** from falling and dropping, so that the plurality of storage assemblies **121** can reliably store the goods **200**.

(367) In a case that there are a plurality of linkage connectors **131**, the plurality of linkage connectors **131** are arranged at intervals along the peripheral side of the storage assembly **121**. The plurality of linkage connectors **131** are distributed at intervals along the peripheral side of each of the plurality of storage assemblies **121**, and may be distributed uniformly, non-uniformly, or symmetrically. The plurality of storage assemblies **121** can be reliably supported by the plurality of linkage connectors **131** and the vertical frame **110**, to prevent the plurality of storage assemblies **121** from falling and dropping, so that the plurality of storage assemblies **121** can reliably store the goods **200**.

(368) Referring to FIG. 1, FIG. 3, and FIG. 4, in an embodiment, the linkage mechanism **130** further includes a linkage driving member **132** configured to cooperate with the linkage connector **131**, so as to drive the plurality of storage assemblies **121** to implement synchronous unloading.

The linkage driving member **132** is a power source for the movement of the linkage mechanism **130**, and implements the driving of the movement of a linkage moving member. In addition, the linkage driving member **132** outputs linear motion, so that the linkage connector **131** can ascend or descend, and the plurality of storage assemblies **121** can undergo a pitching motion. Optionally, the linkage driving member **132** includes, but is not limited to, an air cylinder, a hydraulic cylinder, a linear motor, or an electric push rod, and may also be another linear driving unit capable of outputting the linear motion. Exemplarily, the linkage driving member **132** is a linear motor. Exemplarily, one end of the linkage driving member **132** is arranged on the chassis **160**. Certainly, one end of the linkage driving member **132** may also be arranged on the vertical frame **110**.

(369) Optionally, the linkage driving member **132** may be connected to the plurality of storage assemblies **121**. In an embodiment, an output end of the linkage driving member **132** is connected to one of the plurality of storage assemblies **121**. One end of the linkage driving member **132** is mounted on the vertical frame **110**, and an other end is connected to the plurality of storage assemblies **121**. After outputting the linear motion, the linkage driving member **132** may drive a plurality of storage assemblies **121** connected thereto to move, and then the plurality of storage assemblies **121** may drive the linkage connector **131** to ascend or descend. At this time, the linkage connector **131** may drive the remaining storage assemblies **121** to move synchronously, so that the plurality of storage assemblies **121** rotate relative to the vertical frame **110**, the plurality of storage assemblies **121** are lifted up, and the synchronous unloading operation of the plurality of storage assemblies **121** is performed.

(370) Further, the output end of the linkage driving member **132** is connected to a bottom portion or a top portion of one of the plurality of storage assemblies **121**. In a case that the linkage driving member **132** is connected to the top portion of the plurality of storage assemblies **121**, the linkage driving member **132** may retract to drive the plurality of storage assemblies **121** to move upward, and the linkage driving member **132** may extend to drive the plurality of storage assemblies **121** to move downward. In a case that the linkage driving member **132** is connected to the bottom portion of the plurality of storage assemblies **121**, the linkage driving member **132** may extend to drive the plurality of storage assemblies **121** to move upward, and the linkage driving member **132** may retract to drive the plurality of storage assemblies **121** to move downward. Exemplarily, the linkage driving member **132** is connected to the bottom portion of the plurality of storage assemblies **121**. Still further, the linkage driving member **132** is located and connected to a bottom portion of a lowermost storage assembly **121**, and the output end of the linkage driving member **132** is in abutment with a middle region of the bottom portion of the storage assembly **121**. In this way, the linkage driving member **132** does not affect the loading or unloading of goods **200** of a carrying component, so as to avoid interference.

(371) Further optionally, the output end of the linkage driving member **132** is connected to the linkage connector **131**. The linkage driving member **132** may directly drive the linkage connector **131** to ascend or descend, and then the linkage connector **131** may drive the plurality of storage assemblies **121** to move synchronously. Further, the linkage driving member **132** may be located at the bottom portion of the lowermost storage assembly **121** and arranged on the chassis **160**, and the output end of the linkage driving member **132** is connected to the linkage connector **131**. Certainly, the linkage driving member **132** may also be located at the top portion of the plurality of storage assemblies **121**.

(372) The linkage mechanism **130** in this embodiment can implement the simultaneous unloading of a plurality of storage assemblies **121**, the plurality of storage assemblies **121** are connected by a same linkage connector **131**, and an output end of a linkage driving member **132** is connected to a lowermost storage assembly **121**. When the linkage driving member **132** extends, the linkage driving member **132** may push the plurality of storage assemblies **121** upward, so that the plurality of storage assemblies **121** rotate relative to the vertical frame **110**. When rotating, the plurality of storage assemblies **121** may drive the linkage connector **131** to move synchronously, and then the

linkage connector **131** drives the remaining storage assemblies **121** to move synchronously, so as to implement the synchronous driving of all storage assemblies **121** to move upward, thereby performing the synchronous unloading operation.

(373) It is worth noting that there are various rotational driving forms in which the plurality of storage assemblies **121** rotate relative to the vertical frame **110** to undergo a pitching motion. In this embodiment, only the linkage driving member **132** capable of outputting the linear motion is configured to drive the movement of the plurality of storage assemblies **121**, and other driving components that can implement the pitching motion of the plurality of storage assemblies **121** should be considered as falling within the protection scope of the present disclosure.

(374) Referring to FIG. 1, FIG. 3, and FIG. 5, in an embodiment, each of the plurality of storage assemblies **121** includes a carrier body **1211** configured to carry the goods **200** and rotatably connected to the linkage connector **131** and the vertical frame **110** separately. The carrier body **1211** is a main body configured to carry the goods **200**, one end of the carrier body **1211** is rotatably connected to the vertical frame **110**, and an other end is rotatably connected to the linkage connector **131**. One end of the carrier body **1211** connected to the vertical frame **110** is a head end, and one end of the carrier body **1211** connected to the linkage connector **131** is a tail end. When the linkage connector **131** drives the carrier body **1211** to ascend or descend, the tail end of the carrier body **1211** rotates around the head end of the carrier body **1211**, so that the carrier body **1211** undergoes a pitching motion. Optionally, an edge of the carrier body **1211** is rotatably connected to the linkage connector **131** and the vertical frame **110** separately, and certainly, a middle region of the carrier body **1211** may also be rotatably connected to the linkage connector **131** and the vertical frame **110** separately.

(375) It can be understood that the rotatable connection between the carrier body **1211** and the vertical frame **110** may be that the carrier body **1211** has a rotary shaft, and the carrier body **1211** is also rotatably mounted on the vertical frame **110** through the rotary shaft, or the vertical frame **110** has a rotary shaft, and the carrier body **1211** may be rotatably mounted on the rotary shaft, or the like. In addition, the foregoing manner of the rotatable connection which is implemented through the rotary shaft may also be replaced by a hinged connection or other forms of rotatable connection.

(376) Optionally, the carrier body **1211** is arranged in a flat plate shape, and a container of the goods **200** may be transferred to the carrier body **1211**. Further, the edge of the carrier body **1211** has three sides of flanges, and the three sides of flanges form a loading or unloading port at the vertical frame **110**, and the goods **200** are mounted in the carrier body **1211** through the loading or unloading port. In addition, the flanges can limit the displacement of the goods **200** on the carrier body **1211**, prevent the goods **200** from falling out of the carrier body **1211**, and ensure that the carrier body **1211** can store the goods **200** accurately.

(377) In an embodiment, each of the plurality of storage assemblies **121** further includes a rolling member **1212** arranged on the carrier body **1211** in a rolling manner and configured to be in a rolling contact with the goods **200** in the carrier body **1211**. The rolling member **1212** can reduce a frictional force between the goods **200** and the carrier body **1211**, so as to facilitate the loading or unloading of the goods **200**. When the goods **200** are loaded, a bottom portion of the goods **200** is in contact with the rolling member **1212** under the action of gravity thereof. During the movement of the goods **200** into the carrier body **1211**, the goods **200** may drive rollers to rotate, so that the frictional force between the goods **200** and the carrier body **1211** is reduced, and the loading of the goods **200** is facilitated. When the goods **200** are unloaded, the linkage connector **131** drives the carrier body **1211** to move upward. At this time, the tail end of the carrier body **1211** is higher than a top end of the carrier body **1211**, and the goods **200** in the carrier body **1211** slide out of the carrier body **1211** under the action of gravity. In addition, during a sliding process of the goods **200** along the carrier body **1211**, the bottom portion of the goods **200** drives the rolling member **1212** to roll, so that the goods **200** slide out of the carrier body **1211** more easily, and the unloading of the

goods **200** is facilitated.

(378) Optionally, the carrier body **1211** is provided with a rolling groove, the rolling member **1212** may be rotatably mounted in the rolling groove, and a top surface of the rolling member **1212** is slightly higher than a top surface of the carrier body **1211**, so as to ensure that the rolling member **1212** can be in contact with the bottom portion of the goods **200**. In addition, the bottom portion of the carrier body **1211** also includes a protection cover covering the rolling member **1212** on the bottom portion of the carrier body **1211**, so as to avoid interference between a bottom portion of the rolling member **1212** and other components.

(379) Optionally, the rolling member **1212** includes, but is not limited to, rollers, rolling shafts, rolling balls, or other components capable of rolling. In addition, there are a plurality of rolling members **1212**, and the plurality of rolling members **1212** may be arranged in one row, or may be arranged in a plurality of rows. Exemplarily, the rolling member **1212** is rollers arranged in three rows.

(380) Referring to FIG. 1, FIG. 3, FIG. 6, and FIG. 7, the first embodiment of the present disclosure further provides a transport system including an auxiliary apparatus **300** and the transport robot **100** in the foregoing embodiment. The auxiliary apparatus **300** includes a support frame **310** and a plurality of transport mechanisms **320** arranged on the support frame **310** at intervals along a vertical direction, and a manner in which the plurality of transport mechanisms **320** are arranged at intervals is the same as a manner in which a plurality of storage assemblies **121** are arranged at intervals. When the transport robot **100** moves to the auxiliary apparatus **300**, goods **200** on the plurality of storage assemblies **121** are capable of being simultaneously transferred to corresponding transport mechanisms **320** to implement synchronous unloading; or goods **200** on the plurality of transport mechanisms **320** are capable of being simultaneously transferred to corresponding storage assemblies **121** to implement synchronous loading.

(381) The auxiliary apparatus **300** can implement the synchronous unloading or synchronous loading of the goods **200**. The auxiliary apparatus **300** is arranged at an unloading position or a loading position. In a case that the auxiliary apparatus **300** is unloaded, the auxiliary apparatus **300** is at the unloading position; and in a case that the auxiliary apparatus **300** is loaded, the auxiliary apparatus **300** is at the loading position. In the present disclosure, only an example in which the auxiliary apparatus **300** is at the unloading position is used for description. The auxiliary apparatus **300** is located at the unloading position. After the transport robot **100** completes loading at the loading position, the transport robot **100** moves to the unloading position. At this time, the transport robot **100** is docked with the auxiliary apparatus **300**, and the auxiliary apparatus **300** may receive and pick the goods **200** in the plurality of storage assemblies **121** in the transport robot **100**.

(382) Specifically, the mounting frame **321** functions as a support, which is configured to support a plurality of transport mechanisms **320** configured to transport the goods **200**. The auxiliary apparatus **300** includes a same quantity of transport mechanisms **320** as the plurality of storage assemblies **121**, and heights at which the plurality of transport mechanisms **320** are located are consistent with heights at which corresponding storage assemblies **121** are located. After the transport robot **100** is docked with the auxiliary apparatus **300**, the plurality of storage assemblies **121** and the plurality of transport mechanisms **320** are at same levels and heights. When unloading, the linkage driving member **132** of the linkage mechanism **130** extends to drive one end of a lowermost storage assembly **121** to be lifted up. During a lifting process of the storage assembly **121**, the linkage connector **131** may be driven to ascend, and the linkage connector **131** may drive the remaining storage assemblies **121** to be lifted up during the lifting process. In this way, the plurality of storage assemblies **121** can be simultaneously lifted up, the goods **200** in the plurality of storage assemblies **121** slide out of the plurality of storage assemblies **121** under the action of gravity and the action of the rolling member **1212**, and move to corresponding transport mechanisms **320**, and the transport mechanisms **320** transport the goods **200** thereon away to implement the unloading of the goods **200**.

(383) The auxiliary apparatus **300** may also implement the loading of the goods **200**. Specifically, transport mechanisms **320** of different layers drive the goods **200** to move toward corresponding storage assemblies **121**, and transfer the goods **200** to the corresponding storage assemblies **121**. It can be understood that when loading the goods **200**, the linkage mechanism **130** may drive ends of the plurality of storage assemblies **121** to descend, and at the same time, the plurality of transport mechanisms **320** simultaneously transfer the goods **200** to the corresponding storage assemblies **121**. After the goods **200** are gradually transferred into the carrier body **1211** and come into contact with the rolling member **1212**, the goods **200** may slide into the plurality of storage assemblies **121** under the action of gravity thereof and through the cooperation with the rolling member **1212**. Certainly, the plurality of storage assemblies **121** may also be stationary, and the goods **200** may also be moved into the plurality of storage assemblies **121** by a pushing force of the plurality of transport mechanisms **320** in cooperation with the rolling member **1212**.

(384) Referring to FIG. 6 and FIG. 7, in an embodiment, each of the plurality of transport mechanisms **320** includes a mounting frame **321** arranged on the support frame **310** and a transport portion **322** movably arranged on the mounting frame **321**, and the transport portion **322** may drive the goods **200** to move. The mounting frame **321** is of a frame structure, which carries the transport portion **322** and is configured to implement the mounting of the transport portion **322**. The transport portion **322** is a main component that implements the transport of the goods **200**. When the goods **200** are in the transport portion **322**, the transport portion **322** may drive the goods **200** to move toward or away from the plurality of storage assemblies **121**.

(385) Optionally, the transport portion **322** is of a structure that can implement horizontal transport, such as a conveyor belt structure, an assembly line, a conveyor roller structure, a roller structure, or the like. Exemplarily, the transport portion **322** is of a roller structure, and specifically includes a plurality of rollers, and each of the plurality of rollers includes a built-in rolling motor to drive the each of the plurality of rollers to rotate, thereby implementing the transport of the goods **200**. It should be noted that, there are various structures that can implement the horizontal transport of the goods **200**, which cannot all be listed herein, and the transport portion **322** in the present disclosure is not limited to being implemented by the foregoing specific structures.

(386) In an embodiment, the auxiliary apparatus **300** further includes a movable base arranged at a bottom portion of the support frame **310**. The movable base can drive the auxiliary apparatus **300** to move, which greatly improves the adaptation of the auxiliary apparatus **300** to actual working conditions. In this way, the auxiliary apparatus **300** can easily move to the loading position, the unloading position, or any other position, to work with the transport robot **100**. Optionally, a structure of the base is exactly the same as that of the chassis **160** of the transport robot **100**, and details are not described herein again.

(387) Referring to FIG. 1, FIG. 6, and FIG. 8, in an embodiment, the transport system further includes a conveying apparatus **500** and a lifting apparatus **400** that is arranged between the auxiliary apparatus **300** and the conveying apparatus **500**, and the lifting apparatus **400** is configured to ascend or descend along the vertical direction, so as to be docked with each of the plurality of transport mechanisms **320** and the conveying apparatus **500**. The lifting apparatus **400** is capable of receiving and picking goods **200** of the plurality of transport mechanisms **320** and transferring the goods to the conveying apparatus **500**; or the lifting apparatus **400** is capable of receiving and picking goods **200** of the conveying apparatus **500** and transferring the goods to the plurality of transport mechanisms **320**.

(388) The lifting apparatus **400** is configured to receive and pick the goods **200** of the plurality of transport mechanisms **320** or transport the goods **200** to the plurality of transport mechanisms **320**. Because the plurality of transport mechanisms **320** are arranged at intervals along the vertical direction, to facilitate the goods loading or unloading of the auxiliary apparatus **300**, the lifting apparatus **400** needs to move to a transport mechanism **320** at a corresponding position, so as to perform a corresponding operation. The conveying apparatus **500** is configured to convey the

goods **200**, may transport away goods **200** unloaded by the lifting apparatus **400**, and may also transport to-be-loaded goods **200** to the lifting apparatus **400**. Optionally, the conveying apparatus **500** may be of a structure that can implement the horizontal transport, such as a conveyor belt structure, an assembly line, a conveying roller structure, or a roller structure, or the like. Exemplarily, the conveying apparatus **500** is of an assembly line structure, and specifically, when unloading, the lifting apparatus **400** ascends to one side of a transport mechanism **320**, after receiving the goods **200** of the transport mechanism **320**, the lifting apparatus **400** descends, and transfers the goods **200** to the conveying apparatus **500**, and the goods are transported away by the conveying apparatus **500**. Subsequently, the lifting apparatus **400** further ascends to another transport mechanism **320**, and this process is repeated until all the goods **200** on the plurality of transport mechanisms **320** are transported away. When loading, after the lifting apparatus **400** descends and receives and picks the goods **200** conveyed by the conveying apparatus **500**, the lifting apparatus **400** ascends to one side of a transport mechanism **320** and transfers the goods **200** to the transport mechanism **320**; and subsequently, the lifting apparatus **400** further descends to the conveying apparatus **500**, and this process is repeated until the plurality of transport mechanisms **320** are loaded with the goods **200**.

(389) In an embodiment, the lifting apparatus **400** includes a lifting frame **410** along the vertical direction, a moving mechanism **420** arranged on the lifting frame **410**, and a transfer mechanism **430** with at least one layer arranged on the moving mechanism **420**. The moving mechanism **420** may ascend or descend along the lifting frame **410** and drive the transfer mechanism **430** with at least one layer to move, so as to receive and pick goods from or transfer goods **200** to the plurality of transport mechanisms **320**. The lifting frame **410** has a bearing function, and is configured to bear the moving mechanism **420** and the transfer mechanism **430** with at least one layer. Optionally, a bottom portion of the lifting frame **410** may also be provided with rotating wheels **162**, so as to adapt to different applications. The transfer mechanism **430** with at least one layer is configured to carry the goods **200** and implement the transfer of the goods **200** between a high position such as a transport mechanism **320** and a low position such as the conveying apparatus **500**. The moving mechanism **420** is arranged on the lifting frame **410** along the vertical direction, and may output movement in the vertical direction, so as to drive the transfer mechanism **430** with at least one layer to ascend or descend.

(390) It can be understood that the moving mechanism **420** is configured to implement the ascending or descending motion of the transfer mechanism **430** with at least one layer along the vertical direction. A specific structure of the moving mechanism **420** may be a telescopic rod structure, a chain transmission structure, a driving transmission structure, or the like, and may also be another structure capable of enabling the carrying mechanism **150** to ascend or descend. Exemplarily, a specific structure of the moving mechanism **420** is the same as a structure of the lifting mechanism **140** of the transport robot **100**, and details are not described herein again. Certainly, the specific structure of the moving mechanism **420** may also be different from the structure of the lifting mechanism **140** of the transport robot **100**, as long as the moving mechanism **420** can implement the ascending or descending motion.

(391) Exemplarily, there is a transfer mechanism **430** with one layer, and the transfer mechanism **430** with one layer receives and picks goods from one transport mechanism **320** at one time, or transfers goods to one transport mechanism **320** at one time. Certainly, in another implementation of the present disclosure, in a case that there is a transfer mechanism **430** with at least two layers, the transfer mechanism **430** with at least two layers may remove goods on at least two transport mechanisms **320** at one time, or transfer goods to at least two transport mechanisms **320**, so as to improve the efficiency of goods turnover.

(392) In an embodiment, the transfer mechanism **430** with at least one layer includes a transfer base **431** arranged on the moving mechanism **420** and a transfer portion **432** movably arranged on the transfer base **431**, and the transfer portion **432** may drive goods **200** to move, and may receive and

pick goods from or transfer goods **200** to at least one of the plurality of transport mechanisms **320**. The transfer base **431** plays a bearing role and is configured to carry the transfer portion **432**, so as to mount the transfer portion **432** on the moving mechanism **420**. When the moving mechanism **420** ascends or descends, the transfer base **431** may drive the transfer portion **432** to ascend or descend synchronously, so as to implement the loading or unloading of the goods **200**.

(393) Optionally, the transfer portion **432** is of a structure that can implement horizontal transport, such as a conveyor belt structure, an assembly line, a conveyor roller structure, a roller structure, or the like. Exemplarily, the transfer portion **432** is of a rolling shaft structure, and specifically includes a plurality of rolling shafts, and each of the plurality of rolling shafts includes a built-in rolling motor to drive the each of the plurality of rolling shafts to rotate, thereby implementing the transport of the goods **200**. It should be noted that, there are various structures that can implement the horizontal transport of the goods **200**, which cannot all be listed herein, and the transfer portion **432** in the present disclosure is not limited to being implemented by the foregoing specific structures.

(394) The transfer portion **432** may receive and pick the goods **200** of one transport mechanism **320** at one time, as mentioned above. The transfer portion **432** may also receive and pick the goods **200** of a plurality of transport mechanisms **320** at one time, and the moving mechanism **420** may receive and pick the goods **200** of the plurality of transport mechanisms **320** layer by layer, and then convey the goods to the conveying apparatus **500** together for transport after receiving and picking the goods. Exemplarily, the moving mechanism **420** drives the transfer portion **432** to ascend to a top portion. After receiving and picking goods **200** of one transport mechanism **320**, the transfer portion **432** descends one layer to receive and pick goods **200** of one transport mechanism **320**. After the transfer portion **432** is full or the goods **200** of the plurality of transport mechanisms **320** are received, the moving mechanism **420** drives the transfer portion **432** to descend to a position of the conveying apparatus **500**, and the transfer portion **432** transfers all the goods **200** thereon to the conveying apparatus **500**. Certainly, the moving mechanism **420** may move layer by layer from bottom to top, a principle thereof is substantially the same as a principle from top to bottom, and details are not described herein again.

(395) Certainly, the transfer portion **432** may also receive and pick a plurality of goods **200** transferred by the conveying apparatus **500** at one time, and then transfer the goods to the plurality of transport mechanisms **320** layer by layer, a principle thereof is substantially the same as a foregoing principle of goods unloading, and details are not described herein again.

(396) In an embodiment, the transport system further includes a control center, components of the transport system perform a coordinated action under the control of the control center, and the control center of the transport system maintains a communication connection with an external server. The control center may identify information of the to-be-transported goods **200**, and the control center may obtain information of a loading position and an unloading position corresponding to each piece of the to-be-transported goods **200**. The control center coordinates and controls the components according to the obtained information, so as to efficiently complete the transport of the goods **200**.

(397) In the transport robot **100** and the transport system in this embodiment, when unloading, a plurality of storage assemblies **121** of a storage mechanism **120** may move synchronously to perform a synchronous unloading action, so that the synchronous unloading of goods **200** in the plurality of storage assemblies **121** is implemented, goods **200** in the transport robot **100** can be unloaded at one time, the unloading efficiency is improved, the unloading time is reduced, and the overall working efficiency of the transport robot **100** is improved. In addition, after the transport robot **100** is used in cooperation with the auxiliary apparatus **300**, the loading or unloading can be simultaneously implemented, thereby improving the working efficiency of the transport system.

Second Embodiment

(398) Referring to FIG. 9 and FIG. 17, in the second embodiment, the transport robot **100** further

includes a blocking mechanism **170** capable of switching between a blocking position and an avoidance position, where when the blocking mechanism **170** is at the blocking position, the blocking mechanism **170** is configured to block goods **200** in the plurality of storage assemblies **121** from sliding out, and when the blocking mechanism **170** is at the avoidance position, goods **200** are capable of being moved into or moved out of the plurality of storage assemblies **121**.

(399) It can be understood that after the plurality of storage assemblies **121** store the to-be-transported goods **200**, during the movement of the transport robot **100** from the loading position to the unloading position, the transport robot **100** travels a specific distance, and the goods **200** stored in the plurality of storage assemblies **121** may be at a risk of falling. Once the goods **200** in the plurality of storage assemblies **121** fall, on the one hand, the goods **200** are damaged, resulting in economic losses; and on the other hand, a manual or intelligent picking apparatus is required to pick the goods **200** and place the goods in the plurality of storage assemblies **121** again for transport, which affects the transport efficiency of the goods **200**.

(400) In view of the foregoing description, the transport robot **100** of the present disclosure further includes a blocking mechanism **170**, and the goods **200** in the plurality of storage assemblies **121** are blocked by the blocking mechanism **170**. In this way, the goods **200** in the plurality of storage assemblies **121** can be prevented from sliding out. Specifically, the blocking mechanism **170** is capable of switching between a blocking position and an avoidance position. When the blocking mechanism **170** is at the avoidance position, the goods **200** may be loaded into the plurality of storage assemblies **121** or the goods **200** may be taken out from the plurality of storage assemblies **121**. When the blocking mechanism **170** is at the blocking position, the goods **200** in the plurality of storage assemblies **121** are in abutment with the blocking mechanism **170**, and the blocking mechanism **170** may restrict the goods **200** in the plurality of storage assemblies **121** from sliding out and prevent the goods **200** from falling.

(401) Specifically, when the transport robot **100** is at the loading position, the blocking mechanism **170** is at the avoidance position, and at this time, the goods **200** may be loaded into the plurality of storage assemblies **121**; after the loading is completed, the blocking mechanism **170** moves to the blocking position, and at this time, the blocking mechanism **170** may be in abutment with the goods **200** in the plurality of storage assemblies **121** to restrict the goods **200** from sliding out of the plurality of storage assemblies **121**; subsequently, the transport robot **100** may move from the loading position to the unloading position, and the blocking mechanism **170** is always at the blocking position during this process; and when the blocking mechanism **170** is at the unloading position, the blocking mechanism **170** moves from the blocking position to the avoidance position, and at this time, the goods **200** in the plurality of storage assemblies **121** may be taken out. In addition, the transport robot **100** reciprocates in this way. It can be understood that the blocking mechanism **170** may play a blocking role during the movement of the transport robot **100** regardless of whether there are goods in the plurality of storage assemblies **121**, or may only play a blocking role during goods transport in a case that there are goods in the plurality of storage assemblies **121**.

(402) When the transport robot **100** of the foregoing embodiment transports goods, the blocking mechanism **170** moves to the blocking position and may be in abutment with the goods **200** in the plurality of storage assemblies **121**, so as to restrict the goods **200** from sliding out of the plurality of storage assemblies **121**. Therefore, a current problem that the goods easily slide out of a storage rack of the transport robot during goods transport is effectively resolved, the goods **200** are prevented from sliding out of the plurality of storage assemblies **121** during a transport process of the transport robot **100**, the safety of the goods **200** is ensured, a risk of sliding out is avoided, and the transport efficiency is improved. In addition, when the transport robot **100** loads or unloads goods, the blocking mechanism **170** moves to the avoidance position. At this time, the goods **200** may be loaded into the plurality of storage assemblies **121**, and the goods **200** in the plurality of storage assemblies **121** may also be removed, which does not hinder a loading or unloading

operation of the transport robot **100**, and is convenient for use.

(403) In an embodiment, the blocking mechanism **170** may simultaneously block the goods **200** in the plurality of storage assemblies **121**. That is, the blocking mechanism **170** may simultaneously move to the blocking position, so as to block the goods **200** in the plurality of storage assemblies **121**, and the blocking mechanism **170** may also simultaneously move to the avoidance position, so that the plurality of storage assemblies **121** can perform a loading or unloading operation.

Certainly, in another implementation of the present disclosure, there are a plurality of blocking mechanisms **170**, and each of the plurality of blocking mechanisms **170** may simultaneously block the goods **200** in at least two of the plurality of storage assemblies **121**. It can be understood that one blocking mechanism **170** may simultaneously act on goods **200** of all storage assemblies **121**, or a plurality of blocking mechanisms **170** may act on a plurality of storage assemblies **121**.

Exemplarily, there are two blocking mechanisms **170**, where one of the two blocking mechanisms **170** is configured to block goods **200** of storage assemblies **121** of first to third layers, and the other one of the two blocking mechanisms **170** is configured to block goods **200** of storage assemblies **121** of fourth to sixth layers. Certainly, in another implementation of the present disclosure, there may be more blocking mechanisms **170**. In the present disclosure, only an example in which one blocking mechanism **170** blocks the goods **200** of all storage assemblies **121** is used for description. A working principle of a plurality of blocking mechanisms **170** is substantially the same as that of the one blocking mechanism **170**, and details are not described herein again.

(404) It is worth noting that an arrangement position of the blocking mechanism **170** is not limited in principle. The blocking mechanism may be movably arranged on the vertical frame **110**, may be movably arranged on the chassis **160**, and may also be movably arranged on the plurality of storage assemblies **121**, as long as it is ensured that the blocking mechanism **170** can move to the avoidance position or the blocking position. In this embodiment, only an example in which the blocking mechanism **170** is movably arranged on the chassis **160** is used for description. A working principle of the blocking mechanism **170** arranged at another position is substantially the same as a working principle of the blocking mechanism **170** movably arranged on the chassis **160**, and details are not described herein again. Specifically, when the blocking mechanism **170** moves relative to the chassis **160**, the blocking mechanism **170** may move to the blocking position or the avoidance position. After the blocking mechanism **170** can move to the blocking position, the blocking mechanism **170** may block the goods **200** in the plurality of storage assemblies **121**; and after the blocking mechanism **170** can move to the avoidance position, the blocking mechanism **170** no longer blocks the plurality of storage assemblies **121**, and the goods **200** may freely enter or exit the plurality of storage assemblies **121**.

(405) In an embodiment, the plurality of storage assemblies **121** includes a loading or unloading end **1215** that faces away from the vertical frame **110**. The goods **200** are loaded or unloaded from the loading or unloading end **1215** of the plurality of storage assemblies **121** to complete the loading or unloading of the goods **200**. Exemplarily, as shown in FIG. **10**, one ends of the plurality of storage assemblies **121** away from the vertical frame **110** is provided with the loading or unloading end **1215**. During loading, the goods **200** are moved from the loading or unloading end **1215** into the plurality of storage assemblies **121**, and during unloading, the goods **200** are moved from the loading or unloading end **1215** out of the plurality of storage assemblies **121**. Optionally, the loading or unloading end **1215** is an end opening of the plurality of storage assemblies **121**, or another entrance or exit through which the goods **200** can enter or exit. Certainly, in another implementation of the present disclosure, the loading or unloading end **1215** may also be arranged at one ends of the plurality of storage assemblies **121** close to the vertical frame **110**. In this way, the loading or unloading of the goods **200** in the plurality of storage assemblies **121** can also be implemented.

(406) Optionally, the loading or unloading end **1215** is arranged on a same side as the carrying mechanism **150**. When the loading or unloading end **1215** performs a loading or unloading

operation, the carrying mechanism **150** needs to avoid the loading or unloading end **1215**, so as to avoid interference between the carrying mechanism **1215** and a loading or unloading apparatus **600**, and ensure reliable loading or unloading. In this case, the carrying mechanism **150** may ascend to a highest position of the transport robot **100** or a position higher than the loading or unloading apparatus **600**, or move to an other side of the transport robot **100**. Further optionally, the loading or unloading end **1215** is arranged on an opposite side of the carrying mechanism **150**. The goods loading or unloading at the loading or unloading end **1215** is not affected by the carrying mechanism **150**, and when the plurality of storage assemblies **121** are loaded or unloaded, the carrying mechanism **150** does not interfere with the loading or unloading apparatus **600**.

(407) Referring to FIG. **9** and FIG. **10**, in an embodiment, the blocking mechanism **170** may move into or move out of the loading or unloading end **1215**. That is, when the blocking mechanism **170** moves into the loading or unloading end **1215**, the blocking mechanism **170** is at the blocking position. At this time, an end portion of the goods **200** is in abutment with the blocking mechanism **170**, and the blocking mechanism **170** blocks the goods **200** to restrict the goods **200** from sliding out of the loading or unloading end **1215**. When the blocking mechanism **170** moves out of the loading or unloading end **1215**, the blocking mechanism **170** is at the avoidance position. At this time, the loading or unloading end **1215** is unobstructed, the goods **200** may be loaded into the plurality of storage assemblies **121** through the loading or unloading end **1215**, and the goods **200** in the plurality of storage assemblies **121** may also be unloaded through the loading or unloading end **1215**.

(408) In an embodiment, when the blocking mechanism **170** is at the blocking position, the blocking mechanism **170** is in abutment with a side wall or a bottom surface of the goods **200**. That is, the blocking position of the blocking mechanism **170** may be located on a bottom surface or a side surface of the plurality of storage assemblies **121**. When the blocking mechanism **170** moves to the blocking position, the blocking mechanism **170** may be in abutment with the goods **200** in the plurality of storage assemblies **121** at a side surface or a bottom surface. At this time, the movement of the goods **200** in the plurality of storage assemblies **121** is restricted due to an abutting force of the blocking mechanism **170**, so that the goods **200** are prevented from sliding out of the plurality of storage assemblies **121**. After the blocking mechanism **170** moves to the avoidance position, the blocking mechanism **170** is separated from the side surface or the bottom surface of the goods **200** of the plurality of storage assemblies **121**, and the goods **200** may move in the plurality of storage assemblies **121**, so as to perform the loading or unloading operation of the plurality of storage assemblies **121**.

(409) In an embodiment, the blocking mechanism **170** is arranged on at least one side of the plurality of storage assemblies **121**. It can be understood that the blocking mechanism **170** may be arranged on one side of the plurality of storage assemblies **121**, as shown in FIG. **9** and FIG. **10**, and in this case, the blocking mechanism **170** may block the goods **200** in the plurality of storage assemblies **121** at the blocking position. Certainly, in another implementation of the present disclosure, blocking mechanisms **170** may also be located on two sides of the plurality of storage assemblies **121** respectively. In this way, the goods **200** in the plurality of storage assemblies **121** can be further blocked. Further, two blocking mechanisms **170** may be arranged symmetrically or asymmetrically, as long as the blocking mechanisms can block the goods **200** in the plurality of storage assemblies **121**.

(410) Exemplarily, in this embodiment, only an example in which the blocking mechanism **170** can move into or move out of the loading or unloading end **1215** is used for description. In addition, the blocking mechanism **170** is arranged on one side of the plurality of storage assemblies **121**, working principles of blocking mechanisms **170** with different layouts mentioned in other embodiments are substantially the same as that of the blocking mechanism **170** in this embodiment, and details are not described herein again. In this case, the blocking position of the blocking mechanism **170** is located at the loading or unloading end **1215**. After the blocking mechanism **170**

moves to the loading or unloading end **1215**, the blocking mechanism **170** is at the loading or unloading end **1215** and faces the goods **200**, so as to block the goods **200**.

(411) In an embodiment, the blocking mechanism **170** includes a movable blocking connector **171** and a plurality of blocking assemblies **172** separately connected to the blocking connector **171**, and at least one of the plurality of blocking assemblies **172** corresponds to a same storage assembly **121**. The blocking connector **171** is capable of driving the plurality of blocking assemblies **172** to move into the loading or unloading end **1215**, so as to block the goods **200** in the plurality of storage assemblies **121**. The blocking connector **171** functions as a connection, and is configured to connect the plurality of blocking assemblies **172**. When moving, the blocking connector **171** may synchronously drive the plurality of blocking assemblies **172** to move, so that the plurality of blocking assemblies **172** can move to a loading or unloading end **1215** of a corresponding storage assembly **121** or move out of the loading or unloading end **1215** of the plurality of storage assemblies **121**. Optionally, the blocking connector **171** includes, but is not limited to, a connecting rod or a longboard, and the like.

(412) The plurality of blocking assemblies **172** function as a blocking, and is configured to implement blocking of the goods **200**. When the blocking connector **171** drives the plurality of blocking assemblies **172** to move to the blocking position, the plurality of blocking assemblies **172** are located at the loading or unloading end **1215**. At this time, the end portion of the goods **200** faces the plurality of blocking assemblies **172**, and the plurality of blocking assemblies **172** restrict the goods **200** from moving out of the plurality of storage assemblies **121**. When the blocking connector **171** drives the plurality of blocking assemblies **172** to move to the avoidance position, the plurality of blocking assemblies **172** are separated from the loading or unloading end **1215**. At this time, there is no object to block the end portion of the goods **200**, and the plurality of storage assemblies **121** may be loaded or unloaded.

(413) It can be understood that the avoidance position may be located outside the plurality of blocking assemblies **172**, or may be located at a bottom portion of the plurality of storage assemblies **121**, or at a position flush with the plurality of storage assemblies **121**. The avoidance position is located at the bottom portion of the plurality of storage assemblies **121**, as long as the plurality of blocking assemblies **172** are at a position that does not affect the moving in or moving out of goods **200** of a next layer.

(414) Optionally, the blocking connector **171** may ascend or descend, and when ascending or descending, the blocking connector **171** may drive the plurality of blocking assemblies **172** to ascend or descend synchronously, so that the plurality of blocking assemblies **172** are located at the loading or unloading end **1215** or move out of the loading or unloading end **1215**. In this case, the avoidance position may be located at the bottom portion of the plurality of storage assemblies **121** or the position flush with the plurality of storage assemblies **121**. Certainly, the blocking connector **171** may also move horizontally. When moving horizontally, the blocking connector **171** may drive the plurality of blocking assemblies **172** to move horizontally and synchronously, so that the plurality of blocking assemblies **172** are located at the loading or unloading end **1215** or move out of the loading or unloading end **1215**. In this case, the avoidance position may be located outside the plurality of blocking assemblies **172**. Certainly, the blocking connector **171** may also perform another form of movement, such as one or a combination of rotating motion, swinging motion, moving motion, and the like, as long as the plurality of blocking assemblies **172** can move into or move out of the loading or unloading end **1215**. Exemplarily, in the present disclosure, only an example in which the blocking connector **171** ascends or descends and displaces is used for description. In addition, the avoidance position is located at the bottom portion of the plurality of storage assemblies **121** or the position flush with the plurality of storage assemblies **121**.

(415) In an embodiment, each of the plurality of blocking assemblies **172** includes a stopping member fixedly arranged on the blocking connector **171**, and movement of the blocking connector **171** is capable of driving the stopping member to move into or move out of the loading or

unloading end **1215**. In this embodiment, the stopping member is fixedly arranged on the blocking connector **171**, and the movement of the blocking connector **171** may directly drive the stopping member to move, so that the stopping member moves to the blocking position or the avoidance position. For example, when the blocking connector **171** drives the stopping member to ascend, the stopping member may move to the loading or unloading end **1215**, so as to block the goods **200**; and when the blocking connector **171** drives the stopping member to descend, the stopping member may move to the avoidance position, so as to no longer block the goods **200**. Optionally, the stopping member may be a baffle plate, a stopper, a limit post, or another component capable of blocking.

(416) Referring to FIG. **9** and FIG. **10**, in an embodiment, each of the plurality of blocking assemblies **172** includes a swing member **1721** and a blocking member **1722**, one end of the swing member **1721** is rotatably connected to the blocking connector **171**, an other end of the swing member **1721** is mounted with the blocking member **1722**, and a middle portion of the swing member **1721** is rotatably mounted at the loading or unloading end **1215** of the plurality of storage assemblies **121**. When ascending or descending, the blocking connector **171** is capable of driving the swing member **1721** to swing, so that the swing member **1721** drives the blocking member **1722** to move into or move out of the loading or unloading end **1215**.

(417) That is, the blocking connector **171** implements the switching between the blocking position and the avoidance position through the indirect movement of the plurality of blocking assemblies **172**, such as a swinging motion. Specifically, when the blocking connector **171** moves, one end of the swing member **1721** may be driven to move relative to the plurality of storage assemblies **121**, and then an other end of the swing member **1721** may drive the blocking member **1722** to move, so that the blocking member **1722** moves to the avoidance position or the blocking position. A head portion of the swing member **1721** is rotatably connected to the blocking connector **171**, the middle portion of the swing member **1721** is rotatably connected to the plurality of storage assemblies **121**, and a tail portion of the swing member **1721** is connected to the blocking member **1722**. The blocking member **1722** may move to the avoidance position or the blocking position.

(418) Exemplarily, when the blocking connector **171** moves upward along the vertical direction, the blocking connector **171** may drive the blocking member **1722** to move to the blocking position through the swing member **1721**, and when the blocking connector **171** moves downward along the vertical direction, the blocking connector **171** may drive the blocking member **1722** to move to the avoidance position through the swing member **1721**. Optionally, the swing member **1721** is a swing rod, and the blocking member **1722** is a blocking rod.

(419) It should be noted that, the essential spirit of the present disclosure lies in the movement of the blocking connector **171** and the plurality of blocking assemblies **172**, so that the plurality of blocking assemblies **172** respectively move to avoidance positions or blocking positions corresponding to the plurality of storage assemblies **121**. In the foregoing two embodiment, two forms of each of the plurality of blocking assemblies **172** are separately described; and in addition, there are various arrangements of the plurality of blocking assemblies **172**, which cannot all be listed herein, and a linkage manner in the present disclosure is not limited to being implemented by the foregoing specific structures.

(420) In an embodiment, the blocking mechanism **170** further includes a blocking driving member, and an output end of the blocking driving member is connected to the blocking connector **171**, so as to drive the plurality of blocking assemblies **172** to move into or move out of the loading or unloading end **1215**. The blocking driving member is a power source for the movement of the blocking mechanism **170**, and implements the driving of the movement of a blocking moving member. In addition, the blocking driving member outputs linear motion, so that the blocking connector **171** can ascend or descend, and then the blocking connector **171** may drive the plurality of blocking assemblies **172** to move, so that the plurality of blocking assemblies **172** move to the avoidance position or the blocking position. Optionally, the blocking driving member includes, but

is not limited to, an air cylinder, a hydraulic cylinder, a linear motor, or an electric push rod, and may also be another linear driving unit capable of outputting the linear motion. Exemplarily, the blocking driving member is a linear motor. Exemplarily, one end of the blocking driving member is arranged on the chassis **160**. Certainly, in another implementation of the present disclosure, a rotation motor cooperates with a protrusion member to drive.

(421) In an embodiment, a bottom portion of each of the plurality of storage assemblies **121** is provided with a movement space used for a loading or unloading mechanism **620** of a transport system to extend into, so as to load goods into or take the goods out of the plurality of storage assemblies **121**. Because the plurality of storage assemblies **121** cannot move during loading or unloading, other components such as the carrying mechanism **150** or a matching structure of the loading or unloading apparatus **600** are required to move the goods **200** into the plurality of storage assemblies **121** or take the goods out of the plurality of storage assemblies **121** during loading or unloading. Therefore, a bottom portion of each of the plurality of storage assemblies **121** needs to include a space used for the carrying mechanism **150** and the auxiliary apparatus **300** to extend into, so as to facilitate the goods loading or unloading of the plurality of storage assemblies **121**. When loading goods to the plurality of storage assemblies **121**, the carrying mechanism **150** or the loading or unloading apparatus **600** may extend into the movement space to place the goods **200** on the plurality of storage assemblies **121**, and then exit the movement space; and when unloading goods from the plurality of storage assemblies **121**, the carrying mechanism **150** or the loading or unloading apparatus **600** may extend into the movement space to hold the goods **200** in the plurality of storage assemblies **121** and drive the goods **200** to move out of the plurality of storage assemblies **121**.

(422) In an embodiment, each of the plurality of storage assemblies **121** include a first side plate **1213** and a second side plate **1214** that are arranged on the vertical frame **110**, and the first side plate **1213** and the second side plate **1214** are opposite to each other and surround the movement space. The first side plate **1213** and the second side plate **1214** are arranged at a same height of the vertical frame **110**, and are arranged in parallel. In this way, the first side plate **1213** and the second side plate **1214** can be configured to respectively hold bottom portions of two sides of the goods **200**, so that the goods **200** is flat, and deflection is avoided. A portion between the first side plate **1213** and the second side plate **1214** is a gap, that is, the foregoing movement space, which allows the carrying mechanism **150** or the loading or unloading apparatus **600** to extend into, so as to perform a loading or unloading operation.

(423) Certainly, in another implementation of the present disclosure, each of the plurality of storage assemblies **121** includes a carrier body configured to carry the goods **200** and being provided with a movement space along an entrance or exit direction of the goods **200**, and a size of the movement space along the entrance or exit direction of the goods **200** is less than a size of the carrier body along the entrance or exit direction of the goods **200**. That is, the movement space in this case is an opening of the carrier body. The goods **200** are carried by the carrier body, and the movement space of the carrier body may also allow the carrying mechanism **150** or the loading or unloading apparatus **600** to extend into, so as to perform the loading or unloading operation.

(424) Referring to FIG. 9 and FIG. 11, the second embodiment of the present disclosure further provides a transport system including a loading or unloading apparatus **600** and the transport robot **100** in the foregoing embodiment. The loading or unloading apparatus **600** is configured to convey the goods **200** to the transport robot **100** or unload the goods **200** on the transport robot **100**. The loading or unloading apparatus **600** includes an upright frame **610** extending along a vertical direction and a plurality of loading or unloading mechanisms **620** arranged on the upright frame **610** at intervals along the vertical direction, and a manner in which the plurality of loading or unloading mechanisms **620** are arranged at intervals is the same as a manner in which a plurality of storage assemblies **121** are arranged at intervals. After the transport robot **100** is docked with the loading or unloading apparatus **600**, the plurality of loading or unloading mechanisms **620** are

capable of respectively conveying, at different heights, the goods **200** to the plurality of storage assemblies **121** or unloading the goods **200** in the plurality of storage assemblies **121**.

(425) The loading or unloading apparatus **600** can implement synchronous unloading or synchronous loading of the goods **200**. The loading or unloading apparatus **600** is mounted at an unloading position or a loading position. In a case that the loading or unloading apparatus **600** is unloaded, the loading or unloading apparatus **600** is at the unloading position; and in a case that the loading or unloading apparatus **600** is loaded, the loading or unloading apparatus **600** is at the loading position. In the present disclosure, only an example in which the loading or unloading apparatus **600** is at the unloading position is used for description. The loading or unloading apparatus **600** is located at the unloading position. After the transport robot **100** completes loading at the loading position, the transport robot **100** moves to the unloading position. At this time, the transport robot **100** is docked with the loading or unloading apparatus **600**, and the loading or unloading apparatus **600** may receive and pick the goods **200** in the plurality of storage assemblies **121** in the transport robot **100**. Certainly, the reverse transport of the goods **200** may also be implemented at this position, that is, after the transport robot **100** is docked with the loading or unloading apparatus **600**, the loading or unloading apparatus **600** may transfer the goods **200** to the plurality of storage assemblies **121**.

(426) Specifically, the upright frame **610** plays a supporting role, and is configured to support the plurality of loading or unloading mechanisms **620** configured to transport the goods **200**. The loading or unloading apparatus **600** includes a same quantity of loading or unloading mechanisms **620** as the plurality of storage assemblies **121**. The plurality of loading or unloading mechanisms **620** may separately convey, at different heights, the goods **200** to the transport robot **100**, or unload the goods **200** on the transport robot **100**, which greatly shortens the waiting time of the transport robot **100** during a loading or unloading process. In addition, heights at which the plurality of loading or unloading mechanisms **620** are located are consistent with heights at which corresponding storage assemblies **121** are located. After the transport robot **100** is docked with the loading or unloading apparatus **600**, the plurality of storage assemblies **121** and the plurality of loading or unloading mechanisms **620** are at same heights, and the plurality of loading or unloading mechanisms **620** may convey the goods **200** to all storage assemblies **121** on the transport robot **100** at one time, or the plurality of loading or unloading mechanisms **620** may implement one-time removal of goods **200** from all storage assemblies **121** on the transport robot **100**. Certainly, in specific working conditions, one or more loading or unloading mechanisms **620** in the loading or unloading apparatus **600** may simultaneously convey the goods **200** to the transport robot **100** or unload the goods **200** on the transport robot **100**.

(427) Each of the plurality of loading or unloading mechanisms **620** may act independently to convey the goods **200** to the transport robot **100** or unload the goods **200** on the transport robot **100**. Referring to FIG. **10** to FIG. **13**, in an embodiment, each of the plurality of loading or unloading mechanisms **620** includes a bracket **621**, a loading or unloading assembly **622**, and a loading or unloading driving member **623**, a plurality of brackets **621** are arranged on the upright frame **610** at intervals along the vertical direction, the loading or unloading driving member **623** and the loading or unloading assembly **622** are respectively arranged on corresponding brackets **621**, the loading or unloading assembly **622** is connected to the loading or unloading driving member **623**, and the loading or unloading assembly **622** is configured to convey the goods **200** to the plurality of storage assemblies **121** or unload the goods **200** in the plurality of storage assemblies **121**. The loading or unloading driving member **623** may allow a corresponding loading or unloading assembly **622** to individually convey the goods **200** to the transport robot **100** or unload the goods **200** on the transport robot **100**. It can be understood that the chain **6221** in the foregoing embodiment only plays a role of driving and carrying goods. In another embodiment of the present disclosure, a belt, a timing belt, or the like, are used to replace the chain.

(428) Further, as shown in FIG. **10** to FIG. **13**, the loading or unloading assembly **622** includes a

chain **6221** and a protrusion **6222**, the chain **6221** is rotatably arranged on the bracket **621** along a loading or unloading direction, and the protrusion **6222** is fixedly arranged on the chain **6221**. The loading or unloading driving member **623** includes a driving motor in driving connection with the chain **6221**; and the chain **6221** may carry the goods **200**. When the driving motor drives the chain **6221** to rotate, the protrusion **6222** pushes a bottom portion of the goods **200**, so as to push the goods **200** to the transport robot **100**, or the protrusion **6222** pulls a bottom portion of the goods **200**, so as to pull the goods **200** from the transport robot **100** to the chain **6221**, or the protrusion **6222** blocks the bottom portion of the goods **200**, and the goods **200** are transferred to the chain **6221** when the transport robot **100** moves away from the loading or unloading apparatus **600**.

Specifically, the chain **6221** is arranged on two sprockets arranged at intervals along the loading or unloading direction, and an output shaft of the driving motor is in driving connection with one of the two sprockets. When rotating, the driving motor drives the chain **6221** to operate, and the protrusion **6222** pushes the bottom portion of the goods **200**, so as to push the goods **200** to the transport robot **100**, or the protrusion **6222** pulls the bottom portion of the goods **200**, so as to pull the goods **200** from the transport robot **100** to the chain **6221**. Furthermore, each of the plurality of loading or unloading mechanisms **620** includes two sets of loading or unloading assemblies **622**, the two sets of loading or unloading assemblies **622** are arranged on the bracket **621** in parallel and at intervals, and the driving motor is in driving connection with two chains **6221**. The two sets of loading or unloading assemblies **622** can increase the stability during the loading or unloading of the goods **200**. In an embodiment of the present disclosure, as shown in FIG. **13**, each of the plurality of loading or unloading mechanisms **620** further includes a synchronization rod **624**, the two chains **6221** are separately in driving connection with the synchronization rod **624**, and the driving motor is in driving connection with one of the two chains **6221**. Specifically, the synchronization rod **624** connects two sprockets arranged at intervals along a horizontal direction perpendicular to the loading or unloading direction, thereby ensuring that the two chains **6221** rotate synchronously.

(429) In another embodiment, as shown in FIG. **10**, FIG. **11**, FIG. **14**, and FIG. **15**, each of the plurality of loading or unloading mechanisms **620** includes a loading or unloading cross arm **625** and a push-pull assembly **626**, one ends of a plurality of loading or unloading cross arms **625** are arranged on the upright frame **610** at intervals along the vertical direction, and the push-pull assembly **626** is rotatably arranged at other ends corresponding to the plurality of loading or unloading cross arms **625**. When rotating, the push-pull assembly **626** includes a push-pull position and an avoidance position, and when rotating to the push-pull position, push-pull assembly **626** conveys the goods **200** to the transport robot **100** or pulls down the goods **200** on the transport robot **100**. When the push-pull assembly **626** rotates to the avoidance position, the push-pull assembly **626** avoids the goods **200**. It can be understood that when pushing or pulling the goods **200**, the push-pull assembly **626** may push or pull a top portion, a middle portion, or a bottom portion of the goods **200**. In an embodiment of the present disclosure, two loading or unloading assemblies **620** are arranged at intervals in a same horizontal direction of the upright frame **610**, and two push-pull assemblies **626** in the same horizontal direction separately rotate to the push-pull position or the avoidance position. The two push-pull assemblies **626** in the same horizontal direction respectively drive two sides of the goods **200** along the loading or unloading direction. The two push-pull assemblies **626** push or pull the two sides of the goods **200** synchronously, which can effectively ensure the stability of a push-pull process of the goods **200**. Further, the two push-pull assemblies **626** in the same horizontal direction push/pull two sides of the middle portion of the goods **200** synchronously along the loading or unloading direction. It can be understood that the two push-pull assemblies **626** in the same horizontal direction rotate to the push-pull position or the avoidance position synchronously, or rotate to the push-pull position or the avoidance position successively. In another embodiment of the present disclosure, only one loading or unloading mechanism **620** is arranged in a same height direction of the upright frame **610**, and the one loading

or unloading mechanism **620** pushes or pulls the top portion or the bottom portion of the goods **200** when pushing or pulling the goods **200**.

(430) In an implementation, as shown in FIG. **14** and FIG. **15**, the push-pull assembly **626** includes a push-pull rod **6261** and a push-pull motor **6262**, the push-pull motor **6262** is arranged at one ends of the plurality of loading or unloading cross arms **625** away from the upright frame **610**, the push-pull rod **6261** is arranged on an output shaft of the push-pull motor **6262**, and the push-pull motor **6262** is configured to drive the push-pull rod **6261** to rotate to the push-pull position or the avoidance position. Two push-pull rods **6261** may separately be rotated to the push-pull position under the driving of the push-pull motor **6262**, so as to pull the goods **200** out of the transport robot **100** or push the goods **200** to the transport robot **100**. It can be understood that the function of the push-pull motor **6262** is to drive the push-pull rod **6261** to rotate, and the push-pull rod **6261** is directly arranged on the output shaft of the push-pull motor **6262**, or the push-pull rod **6261** is connected to the output shaft of the push-pull motor **6262** through a transmission mechanism, as long as the push-pull motor **6262** can drive the push-pull rod **6261** to rotate to the push-pull position or the avoidance position.

(431) In an embodiment, all loading or unloading mechanisms **620** in the loading or unloading apparatus **600** act synchronously to convey, at different heights, the goods **200** to the transport robot **100** or unload the goods **200** on the transport robot **100**, or some of the plurality of loading or unloading mechanisms **620** in the loading or unloading apparatus **600** act independently to convey, at specified heights, the goods **200** to the transport robot **100** or unload the goods **200** on the transport robot **100**. As shown in FIG. **16** and FIG. **17**, in an implementation, the loading or unloading apparatus **600** further includes an adjustment drive mechanism **630** configured to drive the upright frame **610** to approach or move away from the transport robot **100** along the loading or unloading direction, and when the adjustment drive mechanism **630** drives the upright frame **610** to approach or move away from the transport robot **100**, the plurality of loading or unloading mechanisms **620** convey the goods **200** to the transport robot **100** or unload the goods **200** on the transport robot **100**. The loading or unloading apparatus **600** provided in this embodiment can remove all the goods **200** or specified goods **200** on the transport robot **100** at one time, or simultaneously convey a plurality of goods **200** to the transport robot **100**. In an implementation, the adjustment drive mechanism **630** adopts a driving structure in the form of a motor and a belt.

(432) In an embodiment of the present disclosure, the loading or unloading apparatus **600** further includes a temporary storage shelving unit **640**, the upright frame **610** is movably arranged on the temporary storage shelving unit **640** along a horizontal direction, and the adjustment drive mechanism **630** is configured to drive the upright frame **610** to move relative to the temporary storage shelving unit **640** along the horizontal direction. The temporary storage shelving unit **640** includes a shelving unit with a plurality of layers along the vertical direction, and the plurality of loading or unloading mechanisms **620** are configured to pull goods **200** at different heights on the transport robot **100** to corresponding layers of the shelving unit on the temporary storage shelving unit **640**, or the plurality of loading or unloading mechanisms **620** are configured to push goods **200** on the plurality of layers of the shelving unit to the transport robot **100**. The temporary storage shelving unit **640** can temporarily store the goods **200** unloaded from the transport robot **100** by the loading or unloading apparatus **600**, or temporarily store the to-be-transported goods **200** which are transported to the transport robot **100**. In an implementation, the temporary storage shelving unit **640** includes a temporary storage roller **641** with a plurality of layers arranged along the vertical direction, and each layer of the temporary storage roller **641** is capable of individually transporting the goods **200** along the loading or unloading direction. Optionally, each layer of the temporary storage roller **641** can simultaneously carry a plurality of goods **200**.

(433) In an embodiment, the loading or unloading apparatus **600** further includes a movable base arranged at a bottom portion of the upright frame **610**. The loading or unloading apparatus **600** further includes a movable base arranged at the bottom portion of the upright frame **610**. The

movable base can drive the loading or unloading apparatus **600** to move, which greatly improves the adaptability of the loading or unloading apparatus **600** to actual working conditions. In this way, the loading or unloading apparatus **600** can easily move to the loading position, the unloading position, or any other position, to work with the transport robot **100**. Optionally, a structure of the base is exactly the same as that of the chassis **160** of the transport robot **100**, and details are not described herein again.

(434) Referring to FIG. **9** and FIG. **11**, in an embodiment, the transport system further includes a conveying apparatus **500** and a lifting apparatus **400** that is arranged between the loading or unloading apparatus **600** and the conveying apparatus **500**, and the lifting apparatus **400** is configured to ascend or descend along the vertical direction, so as to be docked with each of the plurality of loading or unloading mechanisms **620** and the conveying apparatus **500**. The lifting apparatus **400** is capable of receiving and picking the goods **200** of the plurality of loading or unloading mechanisms **620** and transferring the goods to the conveying apparatus **500**; or the lifting apparatus **400** is capable of receiving and picking goods **200** of the conveying apparatus **500** and transferring the goods to the plurality of loading or unloading mechanisms **620**.

(435) The lifting apparatus **400** is configured to receive and pick the goods **200** of the plurality of loading or unloading mechanisms **620** or transport the goods **200** to the plurality of loading or unloading mechanisms **620**. Because the plurality of loading or unloading mechanisms **620** are arranged at intervals along the vertical direction, to facilitate the goods loading or unloading of the loading or unloading apparatus **600**, the lifting apparatus **400** needs to move to a loading or unloading mechanism **620** at a corresponding position, so as to perform a corresponding operation. The conveying apparatus **500** is configured to convey the goods **200**, may transport away goods **200** unloaded by the lifting apparatus **400**, and may also transport to-be-loaded goods **200** to the lifting apparatus **400**. Optionally, the conveying apparatus **500** may be of a structure that can implement the horizontal transport, such as a conveyor belt structure, an assembly line, a conveying roller structure, or a roller structure, or the like. Exemplarily, the conveying apparatus **500** is of an assembly line structure, and specifically, when unloading, the lifting apparatus **400** ascends to one side of a loading or unloading mechanism **620**, after receiving the goods **200** of the loading or unloading mechanism **620**, the lifting apparatus **400** descends, and transfers the goods **200** to the conveying apparatus **500**, and the goods are transported away by the conveying apparatus **500**. Subsequently, the lifting apparatus **400** further ascends to another loading or unloading mechanism **620**, and this process is repeated until all the goods **200** on the plurality of loading or unloading mechanisms **620** are transported away. When loading, after the lifting apparatus **400** descends and receives and picks the goods **200** conveyed by the conveying apparatus **500**, the lifting apparatus **400** ascends to one side of a loading or unloading mechanism **620** and transfers the goods **200** to the loading or unloading mechanism **620**; and subsequently, the lifting apparatus **400** further descends to the conveying apparatus **500**, and this process is repeated until the plurality of loading or unloading mechanisms **620** are loaded with the goods **200**.

(436) In an embodiment, the lifting apparatus **400** includes a lifting frame **410** along the vertical direction, a moving mechanism **420** arranged on the lifting frame **410**, and a transfer mechanism **430** with at least one layer arranged on the moving mechanism **420**, and the moving mechanism **420** may ascend or descend along the lifting frame **410** and drive the transfer mechanism **430** with at least one layer to move, so as to receive and pick or transfer the goods **200** to the plurality of loading or unloading mechanisms **620**. The lifting frame **410** has a bearing function, and is configured to bear the moving mechanism **420** and the transfer mechanism **430** with at least one layer. Optionally, a bottom portion of the lifting frame **410** may also be provided with rotating wheels, so as to adapt to different applications. The transfer mechanism **430** with at least one layer is configured to carry the goods **200** and implement the transfer of the goods **200** between a high position such as a loading or unloading mechanism **620** and a low position such as the conveying apparatus **500**. The moving mechanism **420** is arranged on the lifting frame **410** along the vertical

direction, and may output movement in the vertical direction, so as to drive the transfer mechanism **430** with at least one layer to ascend or descend.

(437) It can be understood that the moving mechanism **420** is configured to implement the ascending or descending motion of the transfer mechanism **430** with at least one layer along the vertical direction. A specific structure of the moving mechanism **420** may be a telescopic rod structure, a chain transmission structure, a driving transmission structure, or the like, and may also be another structure capable of enabling the carrying mechanism **150** to ascend or descend. Exemplarily, a specific structure of the moving mechanism **420** is the same as a structure of the lifting mechanism **140** of the transport robot **100**, and details are not described herein again. Certainly, the specific structure of the moving mechanism **420** may also be different from the structure of the lifting mechanism **140** of the transport robot **100**, as long as the moving mechanism **420** can implement the ascending or descending motion.

(438) Exemplarily, there is a transfer mechanism **430** with one layer, and the transfer mechanism **430** with one layer receives and picks goods **200** from one loading or unloading mechanism **620** at one time, or transfers goods **200** to one loading or unloading mechanism **620** at one time. Certainly, in another implementation of the present disclosure, in a case that there is a transfer mechanism **430** with at least two layers, the transfer mechanism **430** with at least two layers may remove goods **200** of at least two loading or unloading mechanisms **620** at one time, or transfer goods **200** to at least two loading or unloading mechanisms **620**, so as to improve the efficiency of turnover of the goods **200**.

(439) In an embodiment, the transfer mechanism **430** with at least one layer includes a transfer base **431** arranged on the moving mechanism **420** and a transfer portion **432** movably arranged on the transfer base **431**, and the transfer portion **432** may drive the goods **200** to move, and may receive and pick or transfer the goods **200** to at least one of the plurality of loading or unloading mechanisms **620**. The transfer base **431** plays a bearing role and is configured to carry the transfer portion **432**, so as to mount the transfer portion **432** on the moving mechanism **420**. When the moving mechanism **420** ascends or descends, the transfer base **431** may drive the transfer portion **432** to ascend or descend synchronously, so as to implement the loading or unloading of the goods **200**.

(440) Optionally, the transfer portion **432** is of a structure that can implement horizontal transport, such as a conveyor belt structure, an assembly line, a conveyor roller structure, a roller structure, or the like. Exemplarily, the transfer portion **432** is of a rolling shaft structure, and specifically includes a plurality of rolling shafts, and each of the plurality of rolling shafts includes a built-in rolling motor to drive the each of the plurality of rolling shafts to rotate, thereby implementing the transport of the goods **200**. It should be noted that, there are various structures that can implement the horizontal transport of the goods **200**, which cannot all be listed herein, and the transfer portion **432** in the present disclosure is not limited to being implemented by the foregoing specific structures.

(441) The transfer portion **432** may receive and pick the goods **200** of one loading or unloading mechanism **620** at one time, as mentioned above. The transfer portion **432** may also receive and pick the goods **200** of a plurality of loading or unloading mechanisms **620** at one time, and the moving mechanism **420** may receive and pick the goods **200** of the plurality of loading or unloading mechanisms **620** layer by layer, and then convey the goods to the conveying apparatus **500** together for transport after receiving and picking the goods. Exemplarily, the moving mechanism **420** drives the transfer portion **432** to ascend to a top portion. After receiving and picking goods **200** of one loading or unloading mechanism **620**, the transfer portion **432** descends one layer to receive and pick goods **200** of one loading or unloading mechanism **620**. After the transfer portion **432** is full or the goods **200** of the plurality of loading or unloading mechanisms **620** are received, the moving mechanism **420** drives the transfer portion **432** to descend to a position of the conveying apparatus **500**, and the transfer portion **432** transfers all the goods **200**

thereon to the conveying apparatus **500**. Certainly, the moving mechanism **420** may move layer by layer from bottom to top, a principle thereof is substantially the same as a principle from top to bottom, and details are not described herein again.

(442) Certainly, the transfer portion **432** may also receive and pick a plurality of goods **200** transferred by the conveying apparatus **500** at one time, and then transfer the goods to the plurality of loading or unloading mechanisms **620** layer by layer, a principle thereof is substantially the same as the foregoing principle of goods unloading, and details are not described herein again.

(443) In an embodiment, the transport system further includes a control center, components of the transport system perform a coordinated action under the control of the control center, and the control center of the transport system maintains a communication connection with an external server. The control center may identify information of the to-be-transported goods **200**, and the control center may obtain information of a loading position and an unloading position corresponding to each piece of the to-be-transported goods **200**. The control center coordinates and controls the components according to the obtained information, so as to efficiently complete the transport of the goods **200**.

(444) In the transport robot **100** and the transport system in this embodiment, when transporting goods, a blocking mechanism **170** moves to a blocking position and may be in abutment with goods **200** in a plurality of storage assemblies **121**, so as to restrict the goods **200** from sliding out of the plurality of storage assemblies **121**. Therefore, the goods **200** are prevented from sliding out of the plurality of storage assemblies **121** during a transport process of the transport robot **100**, the safety of the goods **200** is ensured, a risk of sliding out is avoided, and the transport efficiency is improved. In addition, when the transport robot **100** loads or unloads goods, the blocking mechanism **170** moves to an avoidance position. At this time, goods **200** may be loaded into the plurality of storage assemblies **121**, and the goods **200** in the plurality of storage assemblies **121** may also be removed, which does not hinder a loading or unloading operation of the transport robot **100**, and is convenient for use.

Embodiment 5

(445) Referring to FIG. 1, FIG. 3, FIG. 6, FIG. 9, and FIG. 11, the present disclosure provides a transport robot **100**. The transport robot **100** is applied to a transport system, and can transport goods **200**. It can be understood that the goods **200** may be goods with a bracket, and the transport robot **100** transports the goods **200** through the bracket; and certainly, the goods may alternatively be goods placed in a container, and the transport robot **100** transports the goods **200** through a box. The goods **200** described below are goods placed in a box, and the box may be loaded with the goods **200**, so as to implement the transport of the goods **200**. The transport robot **100** transports the box to an unloading position, and after unloading the goods **200** in the box, the box may be transported back to the transport robot **100**, so as to reuse the box and reduce the cost.

Alternatively, the goods **200** is a box with goods, and the transport robot **100** transports the box to the unloading position, and unloads the box with goods through an unloading apparatus.

(446) The transport robot **100** plays an important role in intelligent warehousing, transports goods **200**, ensures a transport speed of the goods **200**, improves the transport efficiency of the goods **200**, and reduces the consumption of labor resources. The transport robot **100** of the present disclosure can unload synchronously, so that goods **200** in the transport robot **100** can be unloaded at one time, thereby improving the unloading efficiency, reducing the unloading time, and improving the overall working efficiency of the transport robot **100**.

(447) Referring to FIG. 1 and FIG. 3, in an embodiment, the transport robot **100** includes a vertical frame **110** and a storage mechanism **120**. The vertical frame **110** is arranged along a vertical direction. The storage mechanism **120** includes a plurality of storage assemblies **121** configured to store to-be-transported goods **200** and arranged on the vertical frame **110** at equal intervals along the vertical direction.

(448) The vertical frame **110** plays a bearing role, and various components of the transport robot

100 are mounted thereon. When the transport robot **100** transports the goods **200**, the vertical frame **110** may drive synchronous movement of the components on the transport robot **100**, so as to implement the transport of the goods **200**. The storage mechanism **120** is located on the vertical frame **110**, is configured to store the goods **200**, and is capable of moving synchronously with the vertical frame **110**, so as to implement the transport of the goods **200**. The transport robot **100** moves to a loading position, and the to-be-transported goods **200** are transported to the storage mechanism **120** for storage. Then, the transport robot **100** moves from the loading position to an unloading position. Correspondingly, the storage mechanism **120** moves to the unloading position along with the vertical frame **110**. At this time, the goods **200** in the storage mechanism **120** can be unloaded. The storage mechanism **120** can temporarily store the to-be-transported goods **200**, thereby improving the capability of the transport robot **100** to carry the goods **200**.

(449) In addition, the storage mechanism **120** includes a plurality of storage assemblies **121** arranged on the vertical frame **110** at intervals. Each of the plurality of storage assemblies **121** can carry goods **200** of a box to ensure a storage capacity of the transport robot **100**. Optionally, a distance between two adjacent storage assemblies **121** may be equal or not equal. Exemplarily, the plurality of storage assemblies **121** are evenly distributed on the vertical frame **110** along the vertical direction. The to-be-transported goods **200** may be transported to the plurality of storage assemblies **121**, and the transport robot **100** drives the goods **200** in the plurality of storage assemblies **121** to be transported to the unloading position.

(450) Referring to FIG. 1 and FIG. 3, in an embodiment, the transport robot **100** further includes a lifting mechanism **140** capable of ascending or descending relative to the vertical frame **110** along the vertical direction and a carrying mechanism **150** configured to carry the goods **200**, where the carrying mechanism **150** is movably arranged on the vertical frame **110** along the vertical direction, is connected to the lifting mechanism **140**, and is capable of ascending or descending along the vertical direction under driving of the lifting mechanism **140**, so as to deliver goods **200** in the carrying mechanism **150** to a corresponding storage mechanism **120**.

(451) The carrying mechanism **150** is a terminal configured to perform an action of the transport robot **100**. At the loading position, the carrying mechanism **150** may carry the to-be-transported goods **200**, and transport the goods **200** into the plurality of storage assemblies **121**. Certainly, in some occasions, in a case that the goods **200** in the plurality of storage assemblies **121** need to be unloaded separately, the carrying mechanism **150** may also take out the goods **200** in the plurality of storage assemblies **121**. Optionally, the carrying mechanism **150** includes, but is not limited to, a mechanical arm, an actionable tow bar, or a plane with a conveying function, and the like. The lifting mechanism **140** is configured to implement the ascending or descending movement of the carrying mechanism **150**, and is capable of driving the carrying mechanism **150** to ascend or descend along the vertical direction.

(452) At the loading position, there is a shelving unit with a plurality of layers configured to carry goods **200**. When loading goods at the loading position of the transport robot **100**, the lifting mechanism **140** drives the carrying mechanism **150** to ascend or descend, so that the carrying mechanism **150** can pick goods on the shelving unit. Then, the lifting mechanism **140** drives the carrying mechanism **150** to ascend or descend, so as to transfer the goods **200** in the carrying mechanism **150** to the plurality of storage assemblies **121**. This process is repeated until the plurality of storage assemblies **121** store the goods **200**. After the loading is completed, the transport robot **100** moves from the loading position to the unloading position, and the plurality of storage assemblies **121** may perform a synchronous unloading operation. After the unloading is completed, the transport robot **100** returns to the loading position, so that continuous transport of the goods **200** can be implemented by repeating the process, thereby improving the transport efficiency.

(453) The function of the lifting mechanism **140** is to drive the carrying mechanism **150** to ascend or descend along the vertical direction. In an embodiment, the lifting mechanism **140** includes a

lifting power source and a lifting transmission component, and the lifting power source and the lifting transmission component are separately arranged on the vertical frame **110**. The lifting transmission component is in driving connection with the lifting power source and the carrying mechanism **150**. Specifically, an output end of the lifting power source is in driving connection with an input end of the lifting transmission component, and an output end of the lifting transmission component is in driving connection with the carrying mechanism **150**. That the lifting power source and the lifting transmission component are separately arranged on the vertical frame **110**, and the driving connection between the lifting power source and the lifting transmission component facilitate the disassembly or assembly of the lifting mechanism **140** on the vertical frame **110**. Optionally, a power output from the lifting power source is in a form of rotation and linear motion, or in any other form of motion, and a final output of the lifting transmission component in driving connection with the lifting power source is movement along the vertical direction. Optionally, the lifting power source includes a driving motor in driving connection with the input end of the lifting transmission component. The lifting power source in a form of a motor runs more stably. Further, the driving motor can rotate forwardly or reversely, which facilitates the control of an ascending or descending process of the lifting mechanism **140**.

(454) Optionally, the lifting transmission component may be of a telescopic rod structure, a chain transmission structure, a driving transmission structure, or the like, and may also be of another structure capable of enabling the carrying mechanism **150** to ascend or descend. Exemplarily, the lifting transmission component is of a chain transmission structure, including a sprocket and a chain, the chain is connected to the carrying mechanism **150**, and the chain is arranged on the vertical frame **110** along the vertical direction. When the output end of the lifting power source drives the sprocket to rotate, the chain ascends or descends along the vertical frame **110**, which may further drive the carrying mechanism **150** to ascend or descend.

(455) It should be noted that, the essence of the lifting transmission component is to output the ascending or descending motion to drive the carrying mechanism **150** to ascend or descend, thereby implementing the loading of the goods **200**. In this embodiment, the lifting transmission component is implemented by a chain transmission structure. In addition, there are various structures that can implement ascending or descending, which cannot all be listed herein, and the manner of the ascending or descending motion in the present disclosure is not limited to being implemented by the foregoing specific structures.

(456) In an embodiment, the transport robot **100** further includes a rotary mechanism arranged between the carrying mechanism **150** and the lifting mechanism **140** and configured to drive the carrying mechanism **150** to rotate relative to the lifting mechanism **140**, so that the carrying mechanism **150** is aligned with a corresponding storage mechanism **120**. The rotary mechanism is rotatably connected to the carrying mechanism **150**, and the carrying mechanism **150** is rotatable relative to the rotary mechanism. When the carrying mechanism **150** is rotated by the rotary mechanism, a direction of the carrying mechanism **150** may be adjusted, so that the loading or unloading port of the carrying mechanism **150** can be adjusted. The carrying mechanism **150** implements the loading or unloading of the goods **200** through the loading or unloading port. When the transport robot **100** is at the loading position, the rotary mechanism may drive the carrying mechanism **150** to rotate, so that the loading or unloading port of the carrying mechanism **150** faces a shelving unit, and the goods **200** can be loaded into the carrying mechanism **150**. When the carrying mechanism **150** transfers the goods **200** to the plurality of storage assemblies **121**, the rotary mechanism may drive the carrying mechanism **150** to rotate, so that the loading or unloading port of the carrying mechanism **150** faces the plurality of storage assemblies **121**. At this time, the goods **200** in the carrying mechanism **150** can be transferred to the plurality of storage assemblies **121**.

(457) Optionally, the rotary mechanism includes a carrying bracket, an autorotation gear arranged on the carrying bracket, and an autorotation motor fixedly mounted on the carrying bracket. An

output end of the autorotation motor is connected to the autorotation gear, the carrying mechanism **150** is mounted on the autorotation gear, and the carrying bracket is mounted on the lifting mechanism **140**. The autorotation motor may drive the autorotation gear to rotate, which may further drive the carrying mechanism **150** to rotate.

(458) It should be noted that, the essence of the rotary mechanism is to output a rotation motion, so as to drive the carrying mechanism **150** to rotate, thereby implementing the loading or unloading of the goods **200**. In this embodiment, the rotary mechanism is implemented by an autorotation motor and an autorotation gear. In addition, there are various structures that can implement rotation, which cannot all be listed herein, and the manner of the rotation motion in the present disclosure is not limited to being implemented by the foregoing specific structures.

(459) When the transport robot **100** in the foregoing embodiment loads goods, the lifting mechanism **140** drives the carrying mechanism **150** to transfer the goods **200** to a plurality of storage assemblies **121** at corresponding heights in the storage mechanism **120**. When unloading, the lifting mechanism **140** drives the carrying mechanism **150** to take out the goods **200** in a plurality of storage assemblies **121** at corresponding heights in the storage mechanism **120**. Through the cooperation between the lifting mechanism **140** and the carrying mechanism **150**, the automation of loading or unloading of the goods **200** is implemented, a problem of high cost and low efficiency in a current transport method is effectively resolved, the cost of the loading or unloading of the goods is reduced, and the efficiency of the loading or unloading of the goods **200** is greatly improved. In addition, the carrying mechanism **150** moves to different heights under the driving of the lifting mechanism **140**, so that the to-be-transported goods **200** can be delivered to a plurality of storage assemblies **121** at different heights in the storage mechanism **120**, which has strong versatility and reduces the floor space.

(460) Referring to FIG. 1 and FIG. 3, in an embodiment, the carrying mechanism **150** includes a transition member **151** and a pick-or-place member **152** that is telescopically arranged on the transition member **151**, and the pick-or-place member **152** is capable of taking out goods **200** and storing the goods in the transition member **151**, and is further capable of pushing out goods **200** in the transition member **151**. The pick-or-place member **152** is telescopically arranged in the transition member **151**. At the loading position, the pick-or-place member **152** extends out of the transition member **151** to take out goods **200** on a shelving unit, and then the pick-or-place member **152** retracts into the transition member **151** to temporarily store the goods **200** in the transition member **151**. Subsequently, the lifting mechanism **140** and the rotary mechanism drive the carrying mechanism **150** to move, so that the carrying mechanism **150** moves to a plurality of storage assemblies **121** in which the goods are to be placed. At this time, the pick-or-place member **152** extends out of the transition member **151**, moves the goods **200** out of the transition member **151**, and transfers the goods to the plurality of storage assemblies **121**. After the transfer, the pick-or-place member **152** retracts into the transition member **151**. Optionally, the transition member **151** includes, but is not limited to, a transition box, and the pick-or-place member **152** includes, but is not limited to, a structure in which a telescopic motor cooperates with a telescopic rod, a mechanical arm mechanism, and the like.

(461) In an embodiment, the transport robot **100** further includes a movable chassis **160** arranged at a bottom portion of the vertical frame **110**. The movable chassis **160** can drive the transport robot **100** to move, which greatly improves the adaptability of the transport robot **100** to actual working conditions. Specifically, the chassis **160** includes a chassis frame **161**, a travel drive assembly, and a plurality of rotating wheels **162**, the vertical frame **110** is arranged on an upper portion of the chassis frame **161**, the plurality of rotating wheels **162** are arranged on a bottom portion of the chassis frame **161**, the travel drive assembly is arranged on the chassis frame **161**, and at least one of the plurality of rotating wheels **162** is in driving connection with the travel drive assembly. Further, at least two of the plurality of rotating wheels **162** are separately in driving connection with the travel drive assembly, and the at least two of the plurality of rotating wheels **162** being

separately in driving connection with the travel drive assembly are distributed on two sides of the chassis frame **161** along a traveling direction, thereby achieving a steering function of the chassis **160**. The travel drive assembly includes at least two wheel drive motors, and the at least two of the plurality of rotating wheels **162** distributed on the two sides of the chassis frame **161** along the traveling direction are respectively driven by separate wheel drive motors. That the at least two of the plurality of rotating wheels **162** distributed on the two sides of the chassis frame **161** along the traveling direction are respectively driven by separate wheel drive motors can simplify a transmission structure on the chassis **160**.

(462) In an embodiment, each of the plurality of rotating wheels **162** includes a driving wheel and a driven wheel. The driving wheel and the driven wheel are mounted on a bottom portion of the chassis **160**, may separately rotate relative to the chassis **160**, and jointly support the chassis **160**. The driving wheel is driven by a wheel drive motor to enable the chassis **160** to move. By configuring the movable chassis **160**, the transport robot **100** can transport the goods **200** between the loading position and the unloading position. There are two driving wheels, and the two driving wheels are symmetrically distributed. Correspondingly, there are two wheel drive motors, and the two driving wheels are respectively driven by the two wheel drive motors, so that rotational speeds of the two driving wheels are different, thereby implementing the steering of the chassis **160**. There are four driven wheels, and the four driven wheels are distributed in a rectangular shape. The four driven wheels may be universal wheels or may be of other wheel structures with a steering function. According to actual situations, a quantity of the driven wheel is not limited to four, but may also be six, three, or the like.

(463) In this embodiment, the chassis **160** is also mounted with a guiding apparatus, and the guiding apparatus is a camera configured to identify a graphic code attached to a ground, so that the chassis **160** travels along a preset path. The graphic code may be a two-dimensional code, a barcode, or some customized identification codes. In some other embodiments, the guiding apparatus is a laser guiding apparatus configured to guide the chassis **160** to travel along a laser beam, or the guiding apparatus is a short-wave receiving apparatus configured to receive a preset short-wave signal to guide the chassis **160** to travel along a preset path. It should be noted that, in some other embodiments, the chassis **160** may be omitted, and the vertical frame **110** is directly and fixedly mounted on the ground or another platform, and is only configured to carry the goods **200** between the loading position and the unloading position around the vertical frame.

(464) In an embodiment, the transport robot **100** further includes a controller electrically connected to the chassis **160**, the carrying mechanism **150**, the lifting mechanism **140**, and the rotary mechanism separately, so as to control the synchronous movement of components or control the movement of at least one component, to achieve a function of automatic goods carrying.

First Embodiment

(465) Referring to FIG. 1 to FIG. 8, in the first embodiment of the present disclosure, when a transport robot **100** is unloading, a plurality of storage assemblies **121** are capable of moving synchronously to perform a synchronous unloading action.

(466) To further improve the transport efficiency of the transport robot **100**, the transport robot **100** of the present disclosure can implement synchronous unloading at the unloading position.

Specifically, during unloading, a plurality of storage assemblies **121** may move synchronously, so that the goods **200** are moved out of the plurality of storage assemblies **121**, and a synchronous unloading action is performed in real time. In this way, the goods **200** in the plurality of storage assemblies **121** can be unloaded synchronously, which shortens the unloading time and improves the unloading efficiency of the transport robot **100**. After the unloading is completed, the transport robot **100** may return to the loading position to continue loading, which improves the working efficiency of the transport robot **100**.

(467) In this embodiment described above, when the transport robot **100** is unloading, a plurality of storage assemblies **121** of a storage mechanism **120** may move synchronously to perform a

synchronous unloading action, so that the synchronous unloading of goods **200** in the plurality of storage assemblies **121** is implemented, the current problem of a low unloading efficiency caused by the layer-by-layer unloading of goods is effectively resolved, goods **200** in the transport robot **100** can be unloaded at one time, the unloading efficiency is improved, the unloading time is reduced, and the overall working efficiency of the transport robot **100** is improved.

(468) Referring to FIG. 1 to FIG. 4, in an embodiment, the transport robot **100** further includes at least one linkage mechanism **130**, and each of the at least one linkage mechanism **130** is connected to at least two storage assemblies **121** and is configured to drive the at least two storage assemblies **121** to move synchronously relative to the vertical frame **110** to perform a synchronous unloading action. When the at least one linkage mechanism **130** moves, a synchronous movement of the at least two storage assemblies **121** may be implemented. It can be understood that one linkage mechanism **130** may be connected to all storage assemblies **121**, and alternatively, among a plurality of linkage mechanisms **130**, each of the plurality of linkage mechanisms **130** may be connected to a plurality of storage assemblies **121**. Exemplarily, there are two linkage mechanisms **130**, where one of the two linkage mechanisms **130** is connected to storage assemblies **121** of first to third layers, and the other one of the two linkage mechanisms **130** is connected to storage assemblies **121** of fourth to sixth layers. Certainly, in another implementation of the present disclosure, there may be more linkage mechanisms **130**. The present disclosure is only described by taking an example in which one linkage mechanism **130** is connected to all storage assemblies **121**. A working principle of a plurality of linkage mechanisms **130** is substantially the same as that of the one linkage mechanism **130**, and details are not described herein again.

(469) The storage mechanism **120** may be rotatably mounted on the vertical frame **110**, and may further be connected to the linkage mechanism **130**. When moving, the linkage mechanism **130** drives the plurality of storage assemblies **121** to rotate relative to the vertical frame **110**, so that the plurality of storage assemblies **121** can undergo a pitching motion. It can be understood that one end of the linkage mechanism **130** may be mounted on the vertical frame **110** or the chassis **160**, as long as the linkage mechanism **130** can drive the plurality of storage assemblies **121** to undergo a pitching motion.

(470) When the linkage mechanism **130** drives the plurality of storage assemblies **121** to move upward, one ends of the plurality of storage assemblies **121** are lifted up, and other ends rotate relative to the vertical frame **110**, so as to stay at initial positions. At this time, the plurality of storage assemblies **121** are lifted up, and goods **200** thereon may slide out of the plurality of storage assemblies **121** under an action of gravity thereof, so as to implement the unloading of the goods **200**. Because the linkage mechanism **130** simultaneously drives the plurality of storage assemblies **121** to move upward, the plurality of storage assemblies **121** can be simultaneously lifted up, thereby simultaneously performing an unloading operation to implement the unloading. After the unloading is completed, the linkage mechanism **130** drives the plurality of storage assemblies **121** to descend, and the plurality of storage assemblies **121** return to horizontal initial positions.

(471) When the linkage mechanism **130** drives the plurality of storage assemblies **121** to move downward, and after external goods **200** are simultaneously conveyed to the plurality of storage assemblies **121**, the goods **200** can slide into the plurality of storage assemblies **121** under the action of gravity to implement synchronous loading. It should be noted that the synchronous loading of the transport robot **100** needs to be implemented in cooperation with an auxiliary apparatus **300** of the transport system, a specific implementation process is described in detail in the following specification, and only the synchronous unloading of the transport robot **100** is described in detail in this embodiment.

(472) After the transport robot **100** loads the goods **200** into the plurality of storage assemblies **121** at the loading position, the transport robot **100** moves from the loading position to the unloading position. At this time, the linkage mechanism **130** drives the plurality of storage assemblies **121** to

move upward, so that the plurality of storage assemblies **121** are lifted up. In this way, the goods **200** in the plurality of storage assemblies **121** can slide out of the plurality of storage assemblies **121** under the action of gravity thereof, and be stored in a specified apparatus such as the auxiliary apparatus **300**, so as to implement the synchronous unloading of the transport robot **100**. After the unloading is completed, the transport robot **100** returns to the loading position to load goods, and in this way, a transport function of the transport robot **100** is achieved.

(473) In an embodiment, the linkage mechanism **130** includes a linkage connector **131** simultaneously connected to at least two storage assemblies **121** and capable of synchronously driving the at least two storage assemblies **121** to synchronously undergo a pitching motion. It can be understood that the pitching motion herein may be a pitching rotational motion, or a curved motion, and certainly, may also be in other forms that can generate the pitching motion. One ends of the at least two storage assemblies **121** are rotatably connected to the vertical frame **110**, and the at least two storage assemblies **121** are also connected to the linkage connector **131**. The linkage connector **131** can ascend or descend. When ascending or descending, the linkage connector **131** may drive the at least two storage assemblies **121** to ascend or descend, so that the at least two storage assemblies **121** rotate relative to the vertical frame **110**, that is, the at least two storage assemblies **121** undergo a pitching motion. It can be understood that, when one of the at least two storage assemblies **121** undergo a pitching motion, the linkage connector **131** is driven to ascend or descend, and the remaining storage assemblies **121** may be driven to move through the linkage connector **131**; or the linkage connector **131** ascends or descends, and then the at least two storage assemblies **121** are driven to move.

(474) As shown in FIG. 1 and FIG. 2, optionally, the linkage connector **131** and the at least two storage assemblies **121** may be rotatably connected or fixedly connected. When the linkage connector **131** and the at least two storage assemblies **121** are rotatably connected, the at least two storage assemblies **121** may have a rotary shaft, and the at least two storage assemblies **121** may be rotatably mounted on the linkage connector **131** through the rotary shaft. Alternatively, the linkage connector **131** may have a rotary shaft, and the linkage connector **131** may be rotatably mounted on the at least two storage assemblies **121** through the rotary shaft. Alternatively, a connection between the linkage connector **131** and the at least two storage assemblies **121** is similar to an olecranon engagement structure. In addition, the rotary shaft may be replaced with a hinge or another component that can implement a rotatable connection.

(475) Optionally, the linkage connector **131** may be a connecting rod connected to the at least two storage assemblies **121**. Further optionally, the linkage member may include a plurality of connecting rods, and two adjacent linkage members are connected by the plurality of connecting rods. In this case, when one of the at least two storage assemblies **121** moves, adjacent connecting rods may drive the remaining storage assemblies **121** to move. It can be understood that a specific structure of the linkage connector **131** is not limited to the connecting rod, but may also be a connecting piece or the like.

(476) It should be noted that, the essential spirit of the present disclosure lies in the linkage between the linkage connector **131** and the at least two storage assemblies **121**, and the linkage connector **131** can implement the synchronous movement of the at least two storage assemblies **121**, thereby performing a synchronous unloading operation. In this embodiment, the connection of connectors is implemented by connecting rods, and there may be one or more connecting rods. In addition, there are various arrangements of the linkage connector **131**, which cannot all be listed herein, and a linkage manner in the present disclosure is not limited to being implemented by the foregoing specific structures.

(477) Referring to FIG. 1 and FIG. 3, in an embodiment, in a same horizontal direction, a distance between the linkage connector **131** and the vertical frame **110** is less than or equal to a length of each of the plurality of storage assemblies **121**. It can be understood that a length at a connection position between the linkage connector **131** and the plurality of storage assemblies **121** may be

equal to the length of each of the plurality of storage assemblies **121**. In this case, the linkage connector **131** and the vertical frame **110** are respectively located at two ends of the plurality of storage assemblies **121**. The length at the connection position between the linkage connector **131** and the plurality of storage assemblies **121** may be less than the length of each of the plurality of storage assemblies **121**, and the connection position between the linkage connector **131** and the plurality of storage assemblies **121** is located on side surfaces of the plurality of storage assemblies **121**. That is, the linkage connector **131** may be located at any position on a peripheral side of each of the plurality of storage assemblies **121**. In this way, the linkage connector **131** can drive the plurality of storage assemblies **121** to synchronously ascend or descend when the linkage connector **131** ascends or descends, so as to perform the synchronous unloading operation of the transport robot **100**.

(478) In an embodiment, there may be at least one linkage connector **131**. In a case that there is one linkage connector **131**, the cooperation between the linkage connector with the vertical frame **110** can ensure that the plurality of storage assemblies **121** are fixed and reliable, and simultaneously implement the driving of the movement of the plurality of storage assemblies **121**. In a case that there are a plurality of linkage connectors **131**, the plurality of linkage connectors **131** can further improve the linkage of the plurality of storage assemblies **121** and ensure that the plurality of storage assemblies **121** move in a consistent manner.

(479) In a case that there is one linkage connector **131**, the linkage connector **131** and the vertical frame **110** are respectively arranged at two ends of the plurality of storage assemblies **121**. That is, the connection position between the linkage connector **131** and the plurality of storage assemblies **121** and the vertical frame **110** are respectively located at the two ends of the plurality of storage assemblies **121**, and a distance between the connection position and the vertical frame **110** is equal to a size of each of the plurality of storage assemblies **121** along a horizontal direction. In this way, the plurality of storage assemblies **121** can be reliably supported by the linkage connector **131** and the vertical frame **110**, to prevent the plurality of storage assemblies **121** from falling and dropping, so that the plurality of storage assemblies **121** can reliably store the goods **200**.

(480) In a case that there are a plurality of linkage connectors **131**, the plurality of linkage connectors **131** are arranged at intervals along the peripheral side of the storage assembly **121**. The plurality of linkage connectors **131** are distributed at intervals along the peripheral side of each of the plurality of storage assemblies **121**, and may be distributed uniformly, non-uniformly, or symmetrically. The plurality of storage assemblies **121** can be reliably supported by the plurality of linkage connectors **131** and the vertical frame **110**, to prevent the plurality of storage assemblies **121** from falling and dropping, so that the plurality of storage assemblies **121** can reliably store the goods **200**.

(481) Referring to FIG. 1, FIG. 3, and FIG. 4, in an embodiment, the linkage mechanism **130** further includes a linkage driving member **132** configured to cooperate with the linkage connector **131**, so as to drive the plurality of storage assemblies **121** to implement synchronous unloading. The linkage driving member **132** is a power source for the movement of the linkage mechanism **130**, and implements the driving of the movement of a linkage moving member. In addition, the linkage driving member **132** outputs linear motion, so that the linkage connector **131** can ascend or descend, and the plurality of storage assemblies **121** can undergo a pitching motion. Optionally, the linkage driving member **132** includes, but is not limited to, an air cylinder, a hydraulic cylinder, a linear motor, or an electric push rod, and may also be another linear driving unit capable of outputting the linear motion. Exemplarily, the linkage driving member **132** is a linear motor. Exemplarily, one end of the linkage driving member **132** is arranged on the chassis **160**. Certainly, one end of the linkage driving member **132** may also be arranged on the vertical frame **110**.

(482) Optionally, the linkage driving member **132** may be connected to the plurality of storage assemblies **121**. In an embodiment, an output end of the linkage driving member **132** is connected to one of the plurality of storage assemblies **121**. One end of the linkage driving member **132** is

mounted on the vertical frame **110**, and an other end is connected to the plurality of storage assemblies **121**. After outputting the linear motion, the linkage driving member **132** may drive a plurality of storage assemblies **121** connected thereto to move, and then the plurality of storage assemblies **121** may drive the linkage connector **131** to ascend or descend. At this time, the linkage connector **131** may drive the remaining storage assemblies **121** to move synchronously, so that the plurality of storage assemblies **121** rotate relative to the vertical frame **110**, the plurality of storage assemblies **121** are lifted up, and the synchronous unloading operation of the plurality of storage assemblies **121** is performed.

(483) Further, the output end of the linkage driving member **132** is connected to a bottom portion or a top portion of one of the plurality of storage assemblies **121**. In a case that the linkage driving member **132** is connected to the top portion of the plurality of storage assemblies **121**, the linkage driving member **132** may retract to drive the plurality of storage assemblies **121** to move upward, and the linkage driving member **132** may extend to drive the plurality of storage assemblies **121** to move downward. In a case that the linkage driving member **132** is connected to the bottom portion of the plurality of storage assemblies **121**, the linkage driving member **132** may extend to drive the plurality of storage assemblies **121** to move upward, and the linkage driving member **132** may retract to drive the plurality of storage assemblies **121** to move downward. Exemplarily, the linkage driving member **132** is connected to the bottom portion of the plurality of storage assemblies **121**. Still further, the linkage driving member **132** is located and connected to a bottom portion of a lowermost storage assembly **121**, and the output end of the linkage driving member **132** is in abutment with a middle region of the bottom portion of the storage assembly **121**. In this way, the linkage driving member **132** does not affect the loading or unloading of goods **200** of a carrying component, so as to avoid interference.

(484) Further optionally, the output end of the linkage driving member **132** is connected to the linkage connector **131**. The linkage driving member **132** may directly drive the linkage connector **131** to ascend or descend, and then the linkage connector **131** may drive the plurality of storage assemblies **121** to move synchronously. Further, the linkage driving member **132** may be located at the bottom portion of the lowermost storage assembly **121** and arranged on the chassis **160**, and the output end of the linkage driving member **132** is connected to the linkage connector **131**. Certainly, the linkage driving member **132** may also be located at the top portion of the plurality of storage assemblies **121**.

(485) The linkage mechanism **130** in this embodiment can implement the simultaneous unloading of a plurality of storage assemblies **121**, the plurality of storage assemblies **121** are connected by a same linkage connector **131**, and an output end of a linkage driving member **132** is connected to a lowermost storage assembly **121**. When the linkage driving member **132** extends, the linkage driving member **132** may push the plurality of storage assemblies **121** upward, so that the plurality of storage assemblies **121** rotate relative to the vertical frame **110**. When rotating, the plurality of storage assemblies **121** may drive the linkage connector **131** to move synchronously, and then the linkage connector **131** drives the remaining storage assemblies **121** to move synchronously, so as to implement the synchronous driving of all storage assemblies **121** to move upward, thereby performing the synchronous unloading operation.

(486) It is worth noting that there are various rotational driving forms in which the plurality of storage assemblies **121** rotate relative to the vertical frame **110** to undergo a pitching motion. In this embodiment, only the linkage driving member **132** capable of outputting the linear motion is configured to drive the movement of the plurality of storage assemblies **121**, and other driving components that can implement the pitching motion of the plurality of storage assemblies **121** should be considered as falling within the protection scope of the present disclosure.

(487) Referring to FIG. 1, FIG. 3, and FIG. 5, in an embodiment, each of the plurality of storage assemblies **121** includes a carrier body **1211** configured to carry the goods **200** and rotatably connected to the linkage connector **131** and the vertical frame **110** separately. The carrier body

1211 is a main body configured to carry the goods **200**, one end of the carrier body **1211** is rotatably connected to the vertical frame **110**, and an other end is rotatably connected to the linkage connector **131**. One end of the carrier body **1211** connected to the vertical frame **110** is a head end, and one end of the carrier body **1211** connected to the linkage connector **131** is a tail end. When the linkage connector **131** drives the carrier body **1211** to ascend or descend, the tail end of the carrier body **1211** rotates around the head end of the carrier body **1211**, so that the carrier body **1211** undergoes a pitching motion. Optionally, an edge of the carrier body **1211** is rotatably connected to the linkage connector **131** and the vertical frame **110** separately, and certainly, a middle region of the carrier body **1211** may also be rotatably connected to the linkage connector **131** and the vertical frame **110** separately.

(488) It can be understood that the rotatable connection between the carrier body **1211** and the vertical frame **110** may be that the carrier body **1211** has a rotary shaft, and the carrier body **1211** is also rotatably mounted on the vertical frame **110** through the rotary shaft, or the vertical frame **110** has a rotary shaft, and the carrier body **1211** may be rotatably mounted on the rotary shaft, or the like. In addition, the foregoing manner of the rotatable connection which is implemented through the rotary shaft may also be replaced by a hinged connection or other forms of rotatable connection.

(489) Optionally, the carrier body **1211** is arranged in a flat plate shape, and a container of the goods **200** may be transferred to the carrier body **1211**. Further, the edge of the carrier body **1211** has three sides of flanges, and the three sides of flanges form a loading or unloading port at the vertical frame **110**, and the goods **200** are mounted in the carrier body **1211** through the loading or unloading port. In addition, the flanges can limit the displacement of the goods **200** on the carrier body **1211**, prevent the goods **200** from falling out of the carrier body **1211**, and ensure that the carrier body **1211** can store the goods **200** accurately. It can be understood that the loading or unloading port herein is the loading or unloading end **1215** in the second embodiment.

(490) In an embodiment, each of the plurality of storage assemblies **121** further includes a rolling member **1212** arranged on the carrier body **1211** in a rolling manner and configured to be in a rolling contact with the goods **200** in the carrier body **1211**. The rolling member **1212** can reduce a frictional force between the goods **200** and the carrier body **1211**, so as to facilitate the loading or unloading of the goods **200**. When the goods **200** are loaded, a bottom portion of the goods **200** is in contact with the rolling member **1212** under the action of gravity thereof. During the movement of the goods **200** into the carrier body **1211**, the goods **200** may drive rollers to rotate, so that the frictional force between the goods **200** and the carrier body **1211** is reduced, and the loading of the goods **200** is facilitated. When the goods **200** are unloaded, the linkage connector **131** drives the carrier body **1211** to move upward. At this time, the tail end of the carrier body **1211** is higher than a top end of the carrier body **1211**, and the goods **200** in the carrier body **1211** slide out of the carrier body **1211** under the action of gravity. In addition, during a sliding process of the goods **200** along the carrier body **1211**, the bottom portion of the goods **200** drives the rolling member **1212** to roll, so that the goods **200** slide out of the carrier body **1211** more easily, and the unloading of the goods **200** is facilitated.

(491) Optionally, the carrier body **1211** is provided with a rolling groove, the rolling member **1212** may be rotatably mounted in the rolling groove, and a top surface of the rolling member **1212** is slightly higher than a top surface of the carrier body **1211**, so as to ensure that the rolling member **1212** can be in contact with the bottom portion of the goods **200**. In addition, the bottom portion of the carrier body **1211** also includes a protection cover covering the rolling member **1212** on the bottom portion of the carrier body **1211**, so as to avoid interference between a bottom portion of the rolling member **1212** and other components.

(492) Optionally, the rolling member **1212** includes, but is not limited to, rollers, rolling shafts, rolling balls, or other components capable of rolling. In addition, there are a plurality of rolling members **1212**, and the plurality of rolling members **1212** may be arranged in one row, or may be

arranged in a plurality of rows. Exemplarily, the rolling member **1212** is rollers arranged in three rows.

(493) Referring to FIG. 1, FIG. 3, FIG. 6, and FIG. 7, the first embodiment of the present disclosure further provides a transport system including an auxiliary apparatus **300** and the transport robot **100** in the foregoing embodiment. The auxiliary apparatus **300** includes a support frame **310** and a plurality of transport mechanisms **320** arranged on the support frame **310** at intervals along a vertical direction, and a manner in which the plurality of transport mechanisms **320** are arranged at intervals is the same as a manner in which a plurality of storage assemblies **121** are arranged at intervals. When the transport robot **100** moves to the auxiliary apparatus **300**, goods **200** on the plurality of storage assemblies **121** are capable of being simultaneously transferred to corresponding transport mechanisms **320** to implement synchronous unloading; or goods **200** on the plurality of transport mechanisms **320** are capable of being simultaneously transferred to corresponding storage assemblies **121** to implement synchronous loading.

(494) The auxiliary apparatus **300** can implement the synchronous unloading or synchronous loading of the goods **200**. The auxiliary apparatus **300** is arranged at an unloading position or a loading position. In a case that the auxiliary apparatus **300** is unloaded, the auxiliary apparatus **300** is at the unloading position; and in a case that the auxiliary apparatus **300** is loaded, the auxiliary apparatus **300** is at the loading position. In the present disclosure, only an example in which the auxiliary apparatus **300** is at the unloading position is used for description. The auxiliary apparatus **300** is located at the unloading position. After the transport robot **100** completes loading at the loading position, the transport robot **100** moves to the unloading position. At this time, the transport robot **100** is docked with the auxiliary apparatus **300**, and the auxiliary apparatus **300** may receive and pick the goods **200** in the plurality of storage assemblies **121** in the transport robot **100**.

(495) Specifically, the mounting frame **321** functions as a support, which is configured to support a plurality of transport mechanisms **320** configured to transport the goods **200**. The auxiliary apparatus **300** includes a same quantity of transport mechanisms **320** as the plurality of storage assemblies **121**, and heights at which the plurality of transport mechanisms **320** are located are consistent with heights at which corresponding storage assemblies **121** are located. After the transport robot **100** is docked with the auxiliary apparatus **300**, the plurality of storage assemblies **121** and the plurality of transport mechanisms **320** are at same levels and heights. When unloading, the linkage driving member **132** of the linkage mechanism **130** extends to drive one end of a lowermost storage assembly **121** to be lifted up. During a lifting process of the storage assembly **121**, the linkage connector **131** may be driven to ascend, and the linkage connector **131** may drive the remaining storage assemblies **121** to be lifted up during the lifting process. In this way, the plurality of storage assemblies **121** can be simultaneously lifted up, the goods **200** in the plurality of storage assemblies **121** slide out of the plurality of storage assemblies **121** under the action of gravity and the action of the rolling member **1212**, and move to corresponding transport mechanisms **320**, and the transport mechanisms **320** transport the goods **200** thereon away to implement the unloading of the goods **200**.

(496) The auxiliary apparatus **300** may also implement the loading of the goods **200**. Specifically, transport mechanisms **320** of different layers drive the goods **200** to move toward corresponding storage assemblies **121**, and transfer the goods **200** to the corresponding storage assemblies **121**. It can be understood that when loading the goods **200**, the linkage mechanism **130** may drive ends of the plurality of storage assemblies **121** to descend, and at the same time, the plurality of transport mechanisms **320** simultaneously transfer the goods **200** to the corresponding storage assemblies **121**. After the goods **200** are gradually transferred into the carrier body **1211** and come into contact with the rolling member **1212**, the goods **200** may slide into the plurality of storage assemblies **121** under the action of gravity thereof and through the cooperation with the rolling member **1212**. Certainly, the plurality of storage assemblies **121** may also be stationary, and the goods **200** may also be moved into the plurality of storage assemblies **121** by a pushing force of the plurality of

transport mechanisms **320** in cooperation with the rolling member **1212**.

(497) Referring to FIG. **6** and FIG. **7**, in an embodiment, each of the plurality of transport mechanisms **320** includes a mounting frame **321** arranged on the support frame **310** and a transport portion **322** movably arranged on the mounting frame **321**, and the transport portion **322** may drive the goods **200** to move. The mounting frame **321** is of a frame structure, which carries the transport portion **322** and is configured to implement the mounting of the transport portion **322**. The transport portion **322** is a main component that implements the transport of the goods **200**. When the goods **200** are in the transport portion **322**, the transport portion **322** may drive the goods **200** to move toward or away from the plurality of storage assemblies **121**.

(498) Optionally, the transport portion **322** is of a structure that can implement horizontal transport, such as a conveyor belt structure, an assembly line, a conveyor roller structure, a roller structure, or the like. Exemplarily, the transport portion **322** is of a roller structure, and specifically includes a plurality of rollers, and each of the plurality of rollers includes a built-in rolling motor to drive the each of the plurality of rollers to rotate, thereby implementing the transport of the goods **200**. It should be noted that, there are various structures that can implement the horizontal transport of the goods **200**, which cannot all be listed herein, and the transport portion **322** in the present disclosure is not limited to being implemented by the foregoing specific structures.

(499) In an embodiment, the auxiliary apparatus **300** further includes a movable base arranged at a bottom portion of the support frame **310**. The movable base can drive the auxiliary apparatus **300** to move, which greatly improves the adaptation of the auxiliary apparatus **300** to actual working conditions. In this way, the auxiliary apparatus **300** can easily move to the loading position, the unloading position, or any other position, to work with the transport robot **100**. Optionally, a structure of the base is exactly the same as that of the chassis **160** of the transport robot **100**, and details are not described herein again.

(500) Referring to FIG. **1**, FIG. **6**, and FIG. **8**, in an embodiment, the transport system further includes a conveying apparatus **500** and a lifting apparatus **400** that is arranged between the auxiliary apparatus **300** and the conveying apparatus **500**, and the lifting apparatus **400** is configured to ascend or descend along the vertical direction, so as to be docked with each of the plurality of transport mechanisms **320** and the conveying apparatus **500**. The lifting apparatus **400** is capable of receiving and picking goods **200** of the plurality of transport mechanisms **320** and transferring the goods to the conveying apparatus **500**; or the lifting apparatus **400** is capable of receiving and picking goods **200** of the conveying apparatus **500** and transferring the goods to the plurality of transport mechanisms **320**.

(501) The lifting apparatus **400** is configured to receive and pick the goods **200** of the plurality of transport mechanisms **320** or transport the goods **200** to the plurality of transport mechanisms **320**. Because the plurality of transport mechanisms **320** are arranged at intervals along the vertical direction, to facilitate the goods loading or unloading of the auxiliary apparatus **300**, the lifting apparatus **400** needs to move to a transport mechanism **320** at a corresponding position, so as to perform a corresponding operation. The conveying apparatus **500** is configured to convey the goods **200**, may transport away goods **200** unloaded by the lifting apparatus **400**, and may also transport to-be-loaded goods **200** to the lifting apparatus **400**. Optionally, the conveying apparatus **500** may be of a structure that can implement the horizontal transport, such as a conveyor belt structure, an assembly line, a conveying roller structure, or a roller structure, or the like.

Exemplarily, the conveying apparatus **500** is of an assembly line structure, and specifically, when unloading, the lifting apparatus **400** ascends to one side of a transport mechanism **320**, after receiving the goods **200** of the transport mechanism **320**, the lifting apparatus **400** descends, and transfers the goods **200** to the conveying apparatus **500**, and the goods are transported away by the conveying apparatus **500**. Subsequently, the lifting apparatus **400** further ascends to another transport mechanism **320**, and this process is repeated until all the goods **200** on the plurality of transport mechanisms **320** are transported away. When loading, after the lifting apparatus **400**

descends and receives and picks the goods **200** conveyed by the conveying apparatus **500**, the lifting apparatus **400** ascends to one side of a transport mechanism **320** and transfers the goods **200** to the transport mechanism **320**; and subsequently, the lifting apparatus **400** further descends to the conveying apparatus **500**, and this process is repeated until the plurality of transport mechanisms **320** are loaded with the goods **200**.

(502) In an embodiment, the lifting apparatus **400** includes a lifting frame **410** along the vertical direction, a moving mechanism **420** arranged on the lifting frame **410**, and a transfer mechanism **430** with at least one layer arranged on the moving mechanism **420**. The moving mechanism **420** may ascend or descend along the lifting frame **410** and drive the transfer mechanism **430** with at least one layer to move, so as to receive and pick goods from or transfer goods **200** to the plurality of transport mechanisms **320**. The lifting frame **410** has a bearing function, and is configured to bear the moving mechanism **420** and the transfer mechanism **430** with at least one layer.

Optionally, a bottom portion of the lifting frame **410** may also be provided with rotating wheels, so as to adapt to different applications. The transfer mechanism **430** with at least one layer is configured to carry the goods **200** and implement the transfer of the goods **200** between a high position such as a transport mechanism **320** and a low position such as the conveying apparatus **500**. The moving mechanism **420** is arranged on the lifting frame **410** along the vertical direction, and may output movement in the vertical direction, so as to drive the transfer mechanism **430** with at least one layer to ascend or descend.

(503) It can be understood that the moving mechanism **420** is configured to implement the ascending or descending motion of the transfer mechanism **430** with at least one layer along the vertical direction. A specific structure of the moving mechanism **420** may be a telescopic rod structure, a chain transmission structure, a driving transmission structure, or the like, and may also be another structure capable of enabling the carrying mechanism **150** to ascend or descend.

Exemplarily, a specific structure of the moving mechanism **420** is the same as a structure of the lifting mechanism **140** of the transport robot **100**, and details are not described herein again. Certainly, the specific structure of the moving mechanism **420** may also be different from the structure of the lifting mechanism **140** of the transport robot **100**, as long as the moving mechanism **420** can implement the ascending or descending motion.

(504) Exemplarily, there is a transfer mechanism **430** with one layer, and the transfer mechanism **430** with one layer receives and picks goods from one transport mechanism **320** at one time, or transfers goods to one transport mechanism **320** at one time. Certainly, in another implementation of the present disclosure, in a case that there is a transfer mechanism **430** with at least two layers, the transfer mechanism **430** with at least two layers may remove goods on at least two transport mechanisms **320** at one time, or transfer goods to at least two transport mechanisms **320**, so as to improve the efficiency of goods turnover.

(505) In an embodiment, the transfer mechanism **430** with at least one layer includes a transfer base **431** arranged on the moving mechanism **420** and a transfer portion **432** movably arranged on the transfer base **431**, and the transfer portion **432** may drive goods **200** to move, and may receive and pick goods from or transfer goods **200** to at least one of the plurality of transport mechanisms **320**. The transfer base **431** plays a bearing role and is configured to carry the transfer portion **432**, so as to mount the transfer portion **432** on the moving mechanism **420**. When the moving mechanism **420** ascends or descends, the transfer base **431** may drive the transfer portion **432** to ascend or descend synchronously, so as to implement the loading or unloading of the goods **200**.

(506) Optionally, the transfer portion **432** is of a structure that can implement horizontal transport, such as a conveyor belt structure, an assembly line, a conveyor roller structure, a roller structure, or the like. Exemplarily, the transfer portion **432** is of a rolling shaft structure, and specifically includes a plurality of rolling shafts, and each of the plurality of rolling shafts includes a built-in rolling motor to drive the each of the plurality of rolling shafts to rotate, thereby implementing the transport of the goods **200**. It should be noted that, there are various structures that can implement

the horizontal transport of the goods **200**, which cannot all be listed herein, and the transfer portion **432** in the present disclosure is not limited to being implemented by the foregoing specific structures.

(507) The transfer portion **432** may receive and pick the goods **200** of one transport mechanism **320** at one time, as mentioned above. The transfer portion **432** may also receive and pick the goods **200** of a plurality of transport mechanisms **320** at one time, and the moving mechanism **420** may receive and pick the goods **200** of the plurality of transport mechanisms **320** layer by layer, and then convey the goods to the conveying apparatus **500** together for transport after receiving and picking the goods. Exemplarily, the moving mechanism **420** drives the transfer portion **432** to ascend to a top portion. After receiving and picking goods **200** of one transport mechanism **320**, the transfer portion **432** descends one layer to receive and pick goods **200** of one transport mechanism **320**. After the transfer portion **432** is full or the goods **200** of the plurality of transport mechanisms **320** are received, the moving mechanism **420** drives the transfer portion **432** to descend to a position of the conveying apparatus **500**, and the transfer portion **432** transfers all the goods **200** thereon to the conveying apparatus **500**. Certainly, the moving mechanism **420** may move layer by layer from bottom to top, a principle thereof is substantially the same as a principle from top to bottom, and details are not described herein again.

(508) Certainly, the transfer portion **432** may also receive and pick a plurality of goods **200** transferred by the conveying apparatus **500** at one time, and then transfer the goods to the plurality of transport mechanisms **320** layer by layer, a principle thereof is substantially the same as a foregoing principle of goods unloading, and details are not described herein again.

(509) In an embodiment, the transport system further includes a control center, components of the transport system perform a coordinated action under the control of the control center, and the control center of the transport system maintains a communication connection with an external server. The control center may identify information of the to-be-transported goods **200**, and the control center may obtain information of a loading position and an unloading position corresponding to each piece of the to-be-transported goods **200**. The control center coordinates and controls the components according to the obtained information, so as to efficiently complete the transport of the goods **200**.

(510) In the transport robot **100** and the transport system in this embodiment, when unloading, a plurality of storage assemblies **121** of a storage mechanism **120** may move synchronously to perform a synchronous unloading action, so that the synchronous unloading of goods **200** in the plurality of storage assemblies **121** is implemented, goods **200** in the transport robot **100** can be unloaded at one time, the unloading efficiency is improved, the unloading time is reduced, and the overall working efficiency of the transport robot **100** is improved. In addition, after the transport robot **100** is used in cooperation with the auxiliary apparatus **300**, the loading or unloading can be simultaneously implemented, thereby improving the working efficiency of the transport system.

Second Embodiment

(511) Referring to FIG. **9** and FIG. **17**, in the second embodiment of the present disclosure, the transport robot **100** further includes a blocking mechanism **170** capable of switching between a blocking position and an avoidance position, where when the blocking mechanism **170** is at the blocking position, the blocking mechanism **170** is configured to block goods **200** in the storage assemblies **121** from sliding out, and when the blocking mechanism **170** is at the avoidance position, goods **200** are capable of being moved into or moved out of the plurality of storage assemblies **121**.

(512) It can be understood that after the plurality of storage assemblies **121** store the to-be-transported goods **200**, during the movement of the transport robot **100** from the loading position to the unloading position, the transport robot **100** travels a specific distance, and the goods **200** stored in the plurality of storage assemblies **121** may be at a risk of falling. Once the goods **200** in the plurality of storage assemblies **121** fall, on the one hand, the goods **200** are damaged, resulting in

economic losses; and on the other hand, a manual or intelligent picking apparatus is required to pick the goods **200** and place the goods in the plurality of storage assemblies **121** again for transport, which affects the transport efficiency of the goods **200**.

(513) In view of the foregoing description, the transport robot **100** of the present disclosure further includes a blocking mechanism **170**, and the goods **200** in the plurality of storage assemblies **121** are blocked by the blocking mechanism **170**. In this way, the goods **200** in the plurality of storage assemblies **121** can be prevented from sliding out. Specifically, the blocking mechanism **170** is capable of switching between a blocking position and an avoidance position. When the blocking mechanism **170** is at the avoidance position, the goods **200** may be loaded into the plurality of storage assemblies **121** or the goods **200** may be taken out from the plurality of storage assemblies **121**. When the blocking mechanism **170** is at the blocking position, the goods **200** in the plurality of storage assemblies **121** are in abutment with the blocking mechanism **170**, and the blocking mechanism **170** may restrict the goods **200** in the plurality of storage assemblies **121** from sliding out and prevent the goods **200** from falling.

(514) Specifically, when the transport robot **100** is at the loading position, the blocking mechanism **170** is at the avoidance position, and at this time, the goods **200** may be loaded into the plurality of storage assemblies **121**; after the loading is completed, the blocking mechanism **170** moves to the blocking position, and at this time, the blocking mechanism **170** may be in abutment with the goods **200** in the plurality of storage assemblies **121** to restrict the goods **200** from sliding out of the plurality of storage assemblies **121**; subsequently, the transport robot **100** may move from the loading position to the unloading position, and the blocking mechanism **170** is always at the blocking position during this process; and when the blocking mechanism **170** is at the unloading position, the blocking mechanism **170** moves from the blocking position to the avoidance position, and at this time, the goods **200** in the plurality of storage assemblies **121** may be taken out. In addition, the transport robot **100** reciprocates in this way. It can be understood that the blocking mechanism **170** may play a blocking role during the movement of the transport robot **100** regardless of whether there are goods in the plurality of storage assemblies **121**, or may only play a blocking role during goods transport in a case that there are goods in the plurality of storage assemblies **121**.

(515) When the transport robot **100** of the foregoing embodiment transports goods, the blocking mechanism **170** moves to the blocking position and may be in abutment with the goods **200** in the plurality of storage assemblies **121**, so as to restrict the goods **200** from sliding out of the plurality of storage assemblies **121**. Therefore, a current problem that the goods easily slide out of a storage rack of the transport robot during goods transport is effectively resolved, the goods **200** are prevented from sliding out of the plurality of storage assemblies **121** during a transport process of the transport robot **100**, the safety of the goods **200** is ensured, a risk of sliding out is avoided, and the transport efficiency is improved. In addition, when the transport robot **100** loads or unloads goods, the blocking mechanism **170** moves to the avoidance position. At this time, the goods **200** may be loaded into the plurality of storage assemblies **121**, and the goods **200** in the plurality of storage assemblies **121** may also be removed, which does not hinder a loading or unloading operation of the transport robot **100**, and is convenient for use.

(516) In an embodiment, the blocking mechanism **170** may simultaneously block the goods **200** in the plurality of storage assemblies **121**. That is, the blocking mechanism **170** may simultaneously move to the blocking position, so as to block the goods **200** in the plurality of storage assemblies **121**, and the blocking mechanism **170** may also simultaneously move to the avoidance position, so that the plurality of storage assemblies **121** can perform a loading or unloading operation.

Certainly, in another implementation of the present disclosure, there are a plurality of blocking mechanisms **170**, and each of the plurality of blocking mechanisms **170** may simultaneously block the goods **200** in at least two of the plurality of storage assemblies **121**. It can be understood that one blocking mechanism **170** may simultaneously act on goods **200** of all storage assemblies **121**,

or a plurality of blocking mechanisms **170** may act on a plurality of storage assemblies **121**. Exemplarily, there are two blocking mechanisms **170**, where one of the two blocking mechanisms **170** is configured to block goods **200** of storage assemblies **121** of first to third layers, and the other one of the two blocking mechanisms **170** is configured to block goods **200** of storage assemblies **121** of fourth to sixth layers. Certainly, in another implementation of the present disclosure, there may be more blocking mechanisms **170**. In the present disclosure, only an example in which one blocking mechanism **170** blocks the goods **200** of all storage assemblies **121** is used for description. A working principle of a plurality of blocking mechanisms **170** is substantially the same as that of the one blocking mechanism **170**, and details are not described herein again.

(517) It is worth noting that an arrangement position of the blocking mechanism **170** is not limited in principle. The blocking mechanism may be movably arranged on the vertical frame **110**, may be movably arranged on the chassis **160**, and may also be movably arranged on the plurality of storage assemblies **121**, as long as it is ensured that the blocking mechanism **170** can move to the avoidance position or the blocking position. In this embodiment, only an example in which the blocking mechanism **170** is movably arranged on the chassis **160** is used for description. A working principle of the blocking mechanism **170** arranged at another position is substantially the same as a working principle of the blocking mechanism **170** movably arranged on the chassis **160**, and details are not described herein again. Specifically, when the blocking mechanism **170** moves relative to the chassis **160**, the blocking mechanism **170** may move to the blocking position or the avoidance position. After the blocking mechanism **170** can move to the blocking position, the blocking mechanism **170** may block the goods **200** in the plurality of storage assemblies **121**; and after the blocking mechanism **170** can move to the avoidance position, the blocking mechanism **170** no longer blocks the plurality of storage assemblies **121**, and the goods **200** may freely enter or exit the plurality of storage assemblies **121**.

(518) In an embodiment, the plurality of storage assemblies **121** includes a loading or unloading end **1215** that faces away from the vertical frame **110**. The goods **200** are loaded or unloaded from the loading or unloading end **1215** of the plurality of storage assemblies **121** to complete the loading or unloading of the goods **200**. Exemplarily, as shown in FIG. **10**, one ends of the plurality of storage assemblies **121** away from the vertical frame **110** is provided with the loading or unloading end **1215**. During loading, the goods **200** are moved from the loading or unloading end **1215** into the plurality of storage assemblies **121**, and during unloading, the goods **200** are moved from the loading or unloading end **1215** out of the plurality of storage assemblies **121**. Optionally, the loading or unloading end **1215** is an end opening of the plurality of storage assemblies **121**, or another entrance or exit through which the goods **200** can enter or exit. Certainly, in another implementation of the present disclosure, the loading or unloading end **1215** may also be arranged at one ends of the plurality of storage assemblies **121** close to the vertical frame **110**. In this way, the loading or unloading of the goods **200** in the plurality of storage assemblies **121** can also be implemented.

(519) Optionally, the loading or unloading end **1215** is arranged on a same side as the carrying mechanism **150**. When the loading or unloading end **1215** performs a loading or unloading operation, the carrying mechanism **150** needs to avoid the loading or unloading end **1215**, so as to avoid interference between the carrying mechanism **150** and a loading or unloading apparatus **600**, and ensure reliable loading or unloading. In this case, the carrying mechanism **150** may ascend to a highest position of the transport robot **100** or a position higher than the loading or unloading apparatus **600**, or move to an other side of the transport robot **100**. Further optionally, the loading or unloading end **1215** is arranged on an opposite side of the carrying mechanism **150**. The goods loading or unloading at the loading or unloading end **1215** is not affected by the carrying mechanism **150**, and when the plurality of storage assemblies **121** are loaded or unloaded, the carrying mechanism **150** does not interfere with the loading or unloading apparatus **600**.

(520) Referring to FIG. **9** and FIG. **10**, in an embodiment, the blocking mechanism **170** may move

into or move out of the loading or unloading end **1215**. That is, when the blocking mechanism **170** moves into the loading or unloading end **1215**, the blocking mechanism **170** is at the blocking position. At this time, an end portion of the goods **200** is in abutment with the blocking mechanism **170**, and the blocking mechanism **170** blocks the goods **200** to restrict the goods **200** from sliding out of the loading or unloading end **1215**. When the blocking mechanism **170** moves out of the loading or unloading end **1215**, the blocking mechanism **170** is at the avoidance position. At this time, the loading or unloading end **1215** is unobstructed, the goods **200** may be loaded into the plurality of storage assemblies **121** through the loading or unloading end **1215**, and the goods **200** in the plurality of storage assemblies **121** may also be unloaded through the loading or unloading end **1215**.

(521) In an embodiment, when the blocking mechanism **170** is at the blocking position, the blocking mechanism **170** is in abutment with a side wall or a bottom surface of the goods **200**. That is, the blocking position of the blocking mechanism **170** may be located on a bottom surface or a side surface of the plurality of storage assemblies **121**. When the blocking mechanism **170** moves to the blocking position, the blocking mechanism **170** may be in abutment with the goods **200** in the plurality of storage assemblies **121** at a side surface or a bottom surface. At this time, the movement of the goods **200** in the plurality of storage assemblies **121** is restricted due to an abutting force of the blocking mechanism **170**, so that the goods **200** are prevented from sliding out of the plurality of storage assemblies **121**. After the blocking mechanism **170** moves to the avoidance position, the blocking mechanism **170** is separated from the side surface or the bottom surface of the goods **200** of the plurality of storage assemblies **121**, and the goods **200** may move in the plurality of storage assemblies **121**, so as to perform the loading or unloading operation of the plurality of storage assemblies **121**.

(522) In an embodiment, the blocking mechanism **170** is arranged on at least one side of the plurality of storage assemblies **121**. It can be understood that the blocking mechanism **170** may be arranged on one side of the plurality of storage assemblies **121**, as shown in FIG. 9 and FIG. 10, and in this case, the blocking mechanism **170** may block the goods **200** in the plurality of storage assemblies **121** at the blocking position. Certainly, in another implementation of the present disclosure, blocking mechanisms **170** may also be located on two sides of the plurality of storage assemblies **121** respectively. In this way, the goods **200** in the plurality of storage assemblies **121** can be further blocked. Further, two blocking mechanisms **170** may be arranged symmetrically or asymmetrically, as long as the blocking mechanisms can block the goods **200** in the plurality of storage assemblies **121**.

(523) Exemplarily, in this embodiment, only an example in which the blocking mechanism **170** can move into or move out of the loading or unloading end **1215** is used for description. In addition, the blocking mechanism **170** is arranged on one side of the plurality of storage assemblies **121**, working principles of blocking mechanisms **170** with different layouts mentioned in other embodiments are substantially the same as that of the blocking mechanism **170** in this embodiment, and details are not described herein again. In this case, the blocking position of the blocking mechanism **170** is located at the loading or unloading end **1215**. After the blocking mechanism **170** moves to the loading or unloading end **1215**, the blocking mechanism **170** is at the loading or unloading end **1215** and faces the goods **200**, so as to block the goods **200**.

(524) In an embodiment, the blocking mechanism **170** includes a movable blocking connector **171** and a plurality of blocking assemblies **172** separately connected to the blocking connector **171**, and at least one of the plurality of blocking assemblies **172** corresponds to a same storage assembly **121**. The blocking connector **171** is capable of driving the plurality of blocking assemblies **172** to move into the loading or unloading end **1215**, so as to block the goods **200** in the plurality of storage assemblies **121**. The blocking connector **171** functions as a connection, and is configured to connect the plurality of blocking assemblies **172**. When moving, the blocking connector **171** may synchronously drive the plurality of blocking assemblies **172** to move, so that the plurality of

blocking assemblies **172** can move to a loading or unloading end **1215** of a corresponding storage assembly **121** or move out of the loading or unloading end **1215** of the plurality of storage assemblies **121**. Optionally, the blocking connector **171** includes, but is not limited to, a connecting rod or a longboard, and the like.

(525) The plurality of blocking assemblies **172** function as a blocking, and is configured to implement blocking of the goods **200**. When the blocking connector **171** drives the plurality of blocking assemblies **172** to move to the blocking position, the plurality of blocking assemblies **172** are located at the loading or unloading end **1215**. At this time, the end portion of the goods **200** faces the plurality of blocking assemblies **172**, and the plurality of blocking assemblies **172** restrict the goods **200** from moving out of the plurality of storage assemblies **121**. When the blocking connector **171** drives the plurality of blocking assemblies **172** to move to the avoidance position, the plurality of blocking assemblies **172** are separated from the loading or unloading end **1215**. At this time, there is no object to block the end portion of the goods **200**, and the plurality of storage assemblies **121** may be loaded or unloaded.

(526) It can be understood that the avoidance position may be located outside the plurality of blocking assemblies **172**, or may be located at a bottom portion of the plurality of storage assemblies **121**, or at a position flush with the plurality of storage assemblies **121**. The avoidance position is located at the bottom portion of the plurality of storage assemblies **121**, as long as the plurality of blocking assemblies **172** are at a position that does not affect the moving in or moving out of goods **200** of a next layer.

(527) Optionally, the blocking connector **171** may ascend or descend, and when ascending or descending, the blocking connector **171** may drive the plurality of blocking assemblies **172** to ascend or descend synchronously, so that the plurality of blocking assemblies **172** are located at the loading or unloading end **1215** or move out of the loading or unloading end **1215**. In this case, the avoidance position may be located at the bottom portion of the plurality of storage assemblies **121** or the position flush with the plurality of storage assemblies **121**. Certainly, the blocking connector **171** may also move horizontally. When moving horizontally, the blocking connector **171** may drive the plurality of blocking assemblies **172** to move horizontally and synchronously, so that the plurality of blocking assemblies **172** are located at the loading or unloading end **1215** or move out of the loading or unloading end **1215**. In this case, the avoidance position may be located outside the plurality of blocking assemblies **172**. Certainly, the blocking connector **171** may also perform another form of movement, such as one or a combination of rotating motion, swinging motion, moving motion, and the like, as long as the plurality of blocking assemblies **172** can move into or move out of the loading or unloading end **1215**. Exemplarily, in the present disclosure, only an example in which the blocking connector **171** ascends or descends and displaces is used for description. In addition, the avoidance position is located at the bottom portion of the plurality of storage assemblies **121** or the position flush with the plurality of storage assemblies **121**.

(528) In an embodiment, each of the plurality of blocking assemblies **172** includes a stopping member fixedly arranged on the blocking connector **171**, and movement of the blocking connector **171** is capable of driving the stopping member to move into or move out of the loading or unloading end **1215**. In this embodiment, the stopping member is fixedly arranged on the blocking connector **171**, and the movement of the blocking connector **171** may directly drive the stopping member to move, so that the stopping member moves to the blocking position or the avoidance position. For example, when the blocking connector **171** drives the stopping member to ascend, the stopping member may move to the loading or unloading end **1215**, so as to block the goods **200**; and when the blocking connector **171** drives the stopping member to descend, the stopping member may move to the avoidance position, so as to no longer block the goods **200**. Optionally, the stopping member may be a baffle plate, a stopper, a limit post, or another component capable of blocking.

(529) Referring to FIG. 9 and FIG. 10, in an embodiment, each of the plurality of blocking

assemblies **172** includes a swing member **1721** and a blocking member **1722**, one end of the swing member **1721** is rotatably connected to the blocking connector **171**, an other end of the swing member **1721** is mounted with the blocking member **1722**, and a middle portion of the swing member **1721** is rotatably mounted at the loading or unloading end **1215** of the plurality of storage assemblies **121**. When ascending or descending, the blocking connector **171** is capable of driving the swing member **1721** to swing, so that the swing member **1721** drives the blocking member **1722** to move into or move out of the loading or unloading end **1215**.

(530) That is, the blocking connector **171** implements the switching between the blocking position and the avoidance position through the indirect movement of the plurality of blocking assemblies **172**, such as a swinging motion. Specifically, when the blocking connector **171** moves, one end of the swing member **1721** may be driven to move relative to the plurality of storage assemblies **121**, and then an other end of the swing member **1721** may drive the blocking member **1722** to move, so that the blocking member **1722** moves to the avoidance position or the blocking position. A head portion of the swing member **1721** is rotatably connected to the blocking connector **171**, the middle portion of the swing member **1721** is rotatably connected to the plurality of storage assemblies **121**, and a tail portion of the swing member **1721** is connected to the blocking member **1722**. The blocking member **1722** may move to the avoidance position or the blocking position.

(531) Exemplarily, when the blocking connector **171** moves upward along the vertical direction, the blocking connector **171** may drive the blocking member **1722** to move to the blocking position through the swing member **1721**, and when the blocking connector **171** moves downward along the vertical direction, the blocking connector **171** may drive the blocking member **1722** to move to the avoidance position through the swing member **1721**. Optionally, the swing member **1721** is a swing rod, and the blocking member **1722** is a blocking rod.

(532) It should be noted that, the essential spirit of the present disclosure lies in the movement of the blocking connector **171** and the plurality of blocking assemblies **172**, so that the plurality of blocking assemblies **172** respectively move to avoidance positions or blocking positions corresponding to the plurality of storage assemblies **121**. In the foregoing two embodiment, two forms of each of the plurality of blocking assemblies **172** are separately described; and in addition, there are various arrangements of the plurality of blocking assemblies **172**, which cannot all be listed herein, and a linkage manner in the present disclosure is not limited to being implemented by the foregoing specific structures.

(533) In an embodiment, the blocking mechanism **170** further includes a blocking driving member, and an output end of the blocking driving member is connected to the blocking connector **171**, so as to drive the plurality of blocking assemblies **172** to move into or move out of the loading or unloading end **1215**. The blocking driving member is a power source for the movement of the blocking mechanism **170**, and implements the driving of the movement of a blocking moving member. In addition, the blocking driving member outputs linear motion, so that the blocking connector **171** can ascend or descend, and then the blocking connector **171** may drive the plurality of blocking assemblies **172** to move, so that the plurality of blocking assemblies **172** move to the avoidance position or the blocking position. Optionally, the blocking driving member includes, but is not limited to, an air cylinder, a hydraulic cylinder, a linear motor, or an electric push rod, and may also be another linear driving unit capable of outputting the linear motion. Exemplarily, the blocking driving member is a linear motor. Exemplarily, one end of the blocking driving member is arranged on the chassis **160**. Certainly, in another implementation of the present disclosure, a rotation motor cooperates with a protrusion member to drive.

(534) In an embodiment, a bottom portion of each of the plurality of storage assemblies **121** is provided with a movement space used for a loading or unloading mechanism **620** of a transport system to move into, so as to load goods into or take goods out of the plurality of storage assemblies **121**. Because the plurality of storage assemblies **121** cannot move during loading or unloading, other components such as the carrying mechanism **150** or a matching structure of the

loading or unloading apparatus **600** are required to move the goods **200** into the plurality of storage assemblies **121** or take the goods out of the plurality of storage assemblies **121** during loading or unloading. Therefore, a bottom portion of each of the plurality of storage assemblies **121** needs to include a space used for the carrying mechanism **150** and the auxiliary apparatus **300** to extend into, so as to facilitate the goods loading or unloading of the plurality of storage assemblies **121**. When loading goods to the plurality of storage assemblies **121**, the carrying mechanism **150** or the loading or unloading apparatus **600** may extend into the movement space to place the goods **200** on the plurality of storage assemblies **121**, and then exit the movement space; and when unloading goods from the plurality of storage assemblies **121**, the carrying mechanism **150** or the loading or unloading apparatus **600** may extend into the movement space to hold the goods **200** in the plurality of storage assemblies **121** and drive the goods **200** to move out of the plurality of storage assemblies **121**.

(535) In an embodiment, each of the plurality of storage assemblies **121** include a first side plate **1213** and a second side plate **1214** that are arranged on the vertical frame **110**, and the first side plate **1213** and the second side plate **1214** are opposite to each other and surround the movement space. The first side plate **1213** and the second side plate **1214** are arranged at a same height of the vertical frame **110**, and are arranged in parallel. In this way, the first side plate **1213** and the second side plate **1214** can be configured to respectively hold bottom portions of two sides of the goods **200**, so that the goods **200** is flat, and deflection is avoided. A portion between the first side plate **1213** and the second side plate **1214** is a gap, that is, the foregoing movement space, which allows the carrying mechanism **150** or the loading or unloading apparatus **600** to extend into, so as to perform a loading or unloading operation.

(536) Certainly, in another implementation of the present disclosure, each of the plurality of storage assemblies **121** includes a carrier body configured to carry the goods **200** and being provided with a movement space along an entrance or exit direction of the goods **200**, and a size of the movement space along the entrance or exit direction of the goods **200** is less than a size of the carrier body along the entrance or exit direction of the goods **200**. That is, the movement space in this case is an opening of the carrier body. The goods **200** are carried by the carrier body, and the movement space of the carrier body may also allow the carrying mechanism **150** or the loading or unloading apparatus **600** to extend into, so as to perform the loading or unloading operation.

(537) Referring to FIG. 9 and FIG. 11, the second embodiment of the present disclosure further provides a transport system including a loading or unloading apparatus **600** and the transport robot **100** in the foregoing embodiment. The loading or unloading apparatus **600** is configured to convey the goods **200** to the transport robot **100** or unload the goods **200** on the transport robot **100**. The loading or unloading apparatus **600** includes an upright frame **610** extending along a vertical direction and a plurality of loading or unloading mechanisms **620** arranged on the upright frame **610** at intervals along the vertical direction, and a manner in which the plurality of loading or unloading mechanisms **620** are arranged at intervals is the same as a manner in which a plurality of storage assemblies **121** are arranged at intervals. After the transport robot **100** is docked with the loading or unloading apparatus **600**, the plurality of loading or unloading mechanisms **620** are capable of respectively conveying, at different heights, the goods **200** to the plurality of storage assemblies **121** or unloading the goods **200** in the plurality of storage assemblies **121**.

(538) The loading or unloading apparatus **600** can implement synchronous unloading or synchronous loading of the goods **200**. The loading or unloading apparatus **600** is mounted at an unloading position or a loading position. In a case that the loading or unloading apparatus **600** is unloaded, the loading or unloading apparatus **600** is at the unloading position; and in a case that the loading or unloading apparatus **600** is loaded, the loading or unloading apparatus **600** is at the loading position. In the present disclosure, only an example in which the loading or unloading apparatus **600** is at the unloading position is used for description. The loading or unloading apparatus **600** is located at the unloading position. After the transport robot **100** completes loading

at the loading position, the transport robot **100** moves to the unloading position. At this time, the transport robot **100** is docked with the loading or unloading apparatus **600**, and the loading or unloading apparatus **600** may receive and pick the goods **200** in the plurality of storage assemblies **121** in the transport robot **100**. Certainly, the reverse transport of the goods **200** may also be implemented at this position, that is, after the transport robot **100** is docked with the loading or unloading apparatus **600**, the loading or unloading apparatus **600** may transfer the goods **200** to the plurality of storage assemblies **121**.

(539) Specifically, the upright frame **610** plays a supporting role, and is configured to support the plurality of loading or unloading mechanisms **620** configured to transport the goods **200**. The loading or unloading apparatus **600** includes a same quantity of loading or unloading mechanisms **620** as the plurality of storage assemblies **121**. The plurality of loading or unloading mechanisms **620** may separately convey, at different heights, the goods **200** to the transport robot **100**, or unload the goods **200** on the transport robot **100**, which greatly shortens the waiting time of the transport robot **100** during a loading or unloading process. In addition, heights at which the plurality of loading or unloading mechanisms **620** are located are consistent with heights at which corresponding storage assemblies **121** are located. After the transport robot **100** is docked with the loading or unloading apparatus **600**, the plurality of storage assemblies **121** and the plurality of loading or unloading mechanisms **620** are at same heights, and the plurality of loading or unloading mechanisms **620** may convey the goods **200** to all storage assemblies **121** on the transport robot **100** at one time, or the plurality of loading or unloading mechanisms **620** may implement one-time removal of goods **200** from all storage assemblies **121** on the transport robot **100**. Certainly, in specific working conditions, one or more loading or unloading mechanisms **620** in the loading or unloading apparatus **600** may simultaneously convey the goods **200** to the transport robot **100** or unload the goods **200** on the transport robot **100**.

(540) Each of the plurality of loading or unloading mechanisms **620** may act independently to convey the goods **200** to the transport robot **100** or unload the goods **200** on the transport robot **100**. Referring to FIG. **10** to FIG. **13**, in an embodiment, each of the plurality of loading or unloading mechanisms **620** includes a bracket **621**, a loading or unloading assembly **622**, and a loading or unloading driving member **623**, a plurality of brackets **621** are arranged on the upright frame **610** at intervals along the vertical direction, the loading or unloading driving member **623** and the loading or unloading assembly **622** are respectively arranged on corresponding brackets **621**, the loading or unloading assembly **622** is connected to the loading or unloading driving member **623**, and the loading or unloading assembly **622** is configured to convey the goods **200** to the plurality of storage assemblies **121** or unload the goods **200** in the plurality of storage assemblies **121**. The loading or unloading driving member **623** may allow a corresponding loading or unloading assembly **622** to individually convey the goods **200** to the transport robot **100** or unload the goods **200** on the transport robot **100**.

(541) Further, as shown in FIG. **10** to FIG. **13**, the loading or unloading assembly **622** includes a chain **6221** and a protrusion **6222**, the chain **6221** is rotatably arranged on the bracket **621** along a loading or unloading direction, and the protrusion **6222** is fixedly arranged on the chain **6221**. The loading or unloading driving member **623** includes a driving motor in driving connection with the chain **6221**; and the chain **6221** may carry the goods **200**. When the driving motor drives the chain **6221** to rotate, the protrusion **6222** pushes a bottom portion of the goods **200**, so as to push the goods **200** to the transport robot **100**, or the protrusion **6222** pulls a bottom portion of the goods **200**, so as to pull the goods **200** from the transport robot **100** to the chain **6221**, or the protrusion **6222** blocks the bottom portion of the goods **200**, and the goods **200** are transferred to the chain **6221** when the transport robot **100** moves away from the loading or unloading apparatus **600**. Specifically, the chain **6221** is arranged on two sprockets arranged at intervals along the loading or unloading direction, and an output shaft of the driving motor is in driving connection with one of the two sprockets. When rotating, the driving motor drives the chain **6221** to operate, and the

protrusion **6222** pushes the bottom portion of the goods **200**, so as to push the goods **200** to the transport robot **100**, or the protrusion **6222** pulls the bottom portion of the goods **200**, so as to pull the goods **200** from the transport robot **100** to the chain **6221**. Furthermore, each of the plurality of loading or unloading mechanisms **620** includes two sets of loading or unloading assemblies **622**, the two sets of loading or unloading assemblies **622** are arranged on the bracket **621** in parallel and at intervals, and the driving motor is in driving connection with two chains **6221**. The two sets of loading or unloading assemblies **622** can increase the stability during the loading or unloading of the goods **200**. In an embodiment of the present disclosure, as shown in FIG. 13, each of the plurality of loading or unloading mechanisms **620** further includes a synchronization rod **624**, the two chains **6221** are separately in driving connection with the synchronization rod **624**, and the driving motor is in driving connection with one of the two chains **6221**. Specifically, the synchronization rod **624** connects two sprockets arranged at intervals along a horizontal direction perpendicular to the loading or unloading direction, thereby ensuring that the two chains **6221** rotate synchronously. It can be understood that the chain **6221** in the foregoing embodiment only plays a role of driving and carrying goods. In another embodiment of the present disclosure, a belt, a timing belt, or the like, are used to replace the chain.

(542) In another embodiment, as shown in FIG. 10, FIG. 11, FIG. 14, and FIG. 15, each of the plurality of loading or unloading mechanisms **620** includes a loading or unloading cross arm **625** and a push-pull assembly **626**, one ends of a plurality of loading or unloading cross arms **625** are arranged on the upright frame **610** at intervals along the vertical direction, and the push-pull assembly **626** is rotatably arranged at other ends corresponding to the plurality of loading or unloading cross arms **625**. When rotating, the push-pull assembly **626** includes a push-pull position and an avoidance position, and when rotating to the push-pull position, push-pull assembly **626** conveys the goods **200** to the transport robot **100** or pulls down the goods **200** on the transport robot **100**. When the push-pull assembly **626** rotates to the avoidance position, the push-pull assembly **626** avoids the goods **200**. It can be understood that when pushing or pulling the goods **200**, the push-pull assembly **626** may push or pull a top portion, a middle portion, or a bottom portion of the goods **200**. In an embodiment of the present disclosure, two loading or unloading assemblies **620** are arranged at intervals in a same horizontal direction of the upright frame **610**, and two push-pull assemblies **626** in the same horizontal direction separately rotate to the push-pull position or the avoidance position. The two push-pull assemblies **626** in the same horizontal direction respectively drive two sides of the goods **200** along the loading or unloading direction. The two push-pull assemblies **626** push or pull the two sides of the goods **200** synchronously, which can effectively ensure the stability of a push-pull process of the goods **200**. Further, the two push-pull assemblies **626** in the same horizontal direction push/pull two sides of the middle portion of the goods **200** synchronously along the loading or unloading direction. It can be understood that the two push-pull assemblies **626** in the same horizontal direction rotate to the push-pull position or the avoidance position synchronously, or rotate to the push-pull position or the avoidance position successively. In another embodiment of the present disclosure, only one loading or unloading mechanism **620** is arranged in a same height direction of the upright frame **610**, and the one loading or unloading mechanism **620** pushes or pulls the top portion or the bottom portion of the goods **200** when pushing or pulling the goods **200**.

(543) In an implementation, as shown in FIG. 14 and FIG. 15, the push-pull assembly **626** includes a push-pull rod **6261** and a push-pull motor **6262**, the push-pull motor **6262** is arranged at one ends of the plurality of loading or unloading cross arms **625** away from the upright frame **610**, the push-pull rod **6261** is arranged on an output shaft of the push-pull motor **6262**, and the push-pull motor **6262** is configured to drive the push-pull rod **6261** to rotate to the push-pull position or the avoidance position. Two push-pull rods **6261** may separately be rotated to the push-pull position under the driving of the push-pull motor **6262**, so as to pull the goods **200** out of the transport robot **100** or push the goods **200** to the transport robot **100**. It can be understood that the function of the

push-pull motor **6262** is to drive the push-pull rod **6261** to rotate, and the push-pull rod **6261** is directly arranged on the output shaft of the push-pull motor **6262**, or the push-pull rod **6261** is connected to the output shaft of the push-pull motor **6262** through a transmission mechanism, as long as the push-pull motor **6262** can drive the push-pull rod **6261** to rotate to the push-pull position or the avoidance position.

(544) In an embodiment, all loading or unloading mechanisms **620** in the loading or unloading apparatus **600** act synchronously to convey, at different heights, the goods **200** to the transport robot **100** or unload the goods **200** on the transport robot **100**, or some of the plurality of loading or unloading mechanisms **620** in the loading or unloading apparatus **600** act independently to convey, at specified heights, the goods **200** to the transport robot **100** or unload the goods **200** on the transport robot **100**. As shown in FIG. **16** and FIG. **17**, in an implementation, the loading or unloading apparatus **600** further includes an adjustment drive mechanism **630** configured to drive the upright frame **610** to approach or move away from the transport robot **100** along the loading or unloading direction, and when the adjustment drive mechanism **630** drives the upright frame **610** to approach or move away from the transport robot **100**, the plurality of loading or unloading mechanisms **620** convey the goods **200** to the transport robot **100** or unload the goods **200** on the transport robot **100**. The loading or unloading apparatus **600** provided in this embodiment can remove all the goods **200** or specified goods **200** on the transport robot **100** at one time, or simultaneously convey a plurality of goods **200** to the transport robot **100**. In an implementation, the adjustment drive mechanism **630** adopts a driving structure in the form of a motor and a belt.

(545) In an embodiment of the present disclosure, the loading or unloading apparatus **600** further includes a temporary storage shelving unit **640**, the upright frame **610** is movably arranged on the temporary storage shelving unit **640** along a horizontal direction, and the adjustment drive mechanism **630** is configured to drive the upright frame **610** to move relative to the temporary storage shelving unit **640** along the horizontal direction. The temporary storage shelving unit **640** includes a shelving unit with a plurality of layers along the vertical direction, and the plurality of loading or unloading mechanisms **620** are configured to pull goods **200** at different heights on the transport robot **100** to corresponding layers of the shelving unit on the temporary storage shelving unit **640**, or the plurality of loading or unloading mechanisms **620** are configured to push goods **200** on the plurality of layers of the shelving unit to the transport robot **100**. The temporary storage shelving unit **640** can temporarily store the goods **200** unloaded from the transport robot **100** by the loading or unloading apparatus **600**, or temporarily store the to-be-transported goods **200** which are transported to the transport robot **100**. In an implementation, the temporary storage shelving unit **640** includes a temporary storage roller **641** with a plurality of layers arranged along the vertical direction, and each layer of the temporary storage roller **641** is capable of individually transporting the goods **200** along the loading or unloading direction. Optionally, each layer of the temporary storage roller **641** can simultaneously carry a plurality of goods **200**.

(546) In an embodiment, the loading or unloading apparatus **600** further includes a movable base arranged at a bottom portion of the upright frame **610**. The loading or unloading apparatus **600** further includes a movable base arranged at the bottom portion of the upright frame **610**. The movable base can drive the loading or unloading apparatus **600** to move, which greatly improves the adaptability of the loading or unloading apparatus **600** to actual working conditions. In this way, the loading or unloading apparatus **600** can easily move to the loading position, the unloading position, or any other position, to work with the transport robot **100**. Optionally, a structure of the base is exactly the same as that of the chassis **160** of the transport robot **100**, and details are not described herein again.

(547) Referring to FIG. **9** and FIG. **11**, in an embodiment, the transport system further includes a conveying apparatus **500** and a lifting apparatus **400** that is arranged between the loading or unloading apparatus **600** and the conveying apparatus **500**, and the lifting apparatus **400** is configured to ascend or descend along the vertical direction, so as to be docked with each of the

plurality of loading or unloading mechanisms **620** and the conveying apparatus **500**. The lifting apparatus **400** is capable of receiving and picking the goods **200** of the plurality of loading or unloading mechanisms **620** and transferring the goods to the conveying apparatus **500**; or the lifting apparatus **400** is capable of receiving and picking goods **200** of the conveying apparatus **500** and transferring the goods to the plurality of loading or unloading mechanisms **620**.

(548) The lifting apparatus **400** is configured to receive and pick the goods **200** of the plurality of loading or unloading mechanisms **620** or transport the goods **200** to the plurality of loading or unloading mechanisms **620**. Because the plurality of loading or unloading mechanisms **620** are arranged at intervals along the vertical direction, to facilitate the goods loading or unloading of the loading or unloading apparatus **600**, the lifting apparatus **400** needs to move to a loading or unloading mechanism **620** at a corresponding position, so as to perform a corresponding operation. The conveying apparatus **500** is configured to convey the goods **200**, may transport away goods **200** unloaded by the lifting apparatus **400**, and may also transport to-be-loaded goods **200** to the lifting apparatus **400**. Optionally, the conveying apparatus **500** may be of a structure that can implement the horizontal transport, such as a conveyor belt structure, an assembly line, a conveying roller structure, or a roller structure, or the like. Exemplarily, the conveying apparatus **500** is of an assembly line structure, and specifically, when unloading, the lifting apparatus **400** ascends to one side of a loading or unloading mechanism **620**, after receiving the goods **200** of the loading or unloading mechanism **620**, the lifting apparatus **400** descends, and transfers the goods **200** to the conveying apparatus **500**, and the goods are transported away by the conveying apparatus **500**. Subsequently, the lifting apparatus **400** further ascends to another loading or unloading mechanism **620**, and this process is repeated until all the goods **200** on the plurality of loading or unloading mechanisms **620** are transported away. When loading, after the lifting apparatus **400** descends and receives and picks the goods **200** conveyed by the conveying apparatus **500**, the lifting apparatus **400** ascends to one side of a loading or unloading mechanism **620** and transfers the goods **200** to the loading or unloading mechanism **620**; and subsequently, the lifting apparatus **400** further descends to the conveying apparatus **500**, and this process is repeated until the plurality of loading or unloading mechanisms **620** are loaded with the goods **200**.

(549) In an embodiment, the lifting apparatus **400** includes a lifting frame **410** along the vertical direction, a moving mechanism **420** arranged on the lifting frame **410**, and a transfer mechanism **430** with at least one layer arranged on the moving mechanism **420**, and the moving mechanism **420** may ascend or descend along the lifting frame **410** and drive the transfer mechanism **430** with at least one layer to move, so as to receive and pick or transfer the goods **200** to the plurality of loading or unloading mechanisms **620**. The lifting frame **410** has a bearing function, and is configured to bear the moving mechanism **420** and the transfer mechanism **430** with at least one layer. Optionally, a bottom portion of the lifting frame **410** may also be provided with rotating wheels, so as to adapt to different applications. The transfer mechanism **430** with at least one layer is configured to carry the goods **200** and implement the transfer of the goods **200** between a high position such as a loading or unloading mechanism **620** and a low position such as the conveying apparatus **500**. The moving mechanism **420** is arranged on the lifting frame **410** along the vertical direction, and may output movement in the vertical direction, so as to drive the transfer mechanism **430** with at least one layer to ascend or descend.

(550) It can be understood that the moving mechanism **420** is configured to implement the ascending or descending motion of the transfer mechanism **430** with at least one layer along the vertical direction. A specific structure of the moving mechanism **420** may be a telescopic rod structure, a chain transmission structure, a driving transmission structure, or the like, and may also be another structure capable of enabling the carrying mechanism **150** to ascend or descend. Exemplarily, a specific structure of the moving mechanism **420** is the same as a structure of the lifting mechanism **140** of the transport robot **100**, and details are not described herein again. Certainly, the specific structure of the moving mechanism **420** may also be different from the

structure of the lifting mechanism **140** of the transport robot **100**, as long as the moving mechanism **420** can implement the ascending or descending motion.

(551) Exemplarily, there is a transfer mechanism **430** with one layer, and the transfer mechanism **430** with one layer receives and picks goods **200** from one loading or unloading mechanism **620** at one time, or transfers goods **200** to one loading or unloading mechanism **620** at one time. Certainly, in another implementation of the present disclosure, in a case that there is a transfer mechanism **430** with at least two layers, the transfer mechanism **430** with at least two layers may remove goods **200** of at least two loading or unloading mechanisms **620** at one time, or transfer goods **200** to at least two loading or unloading mechanisms **620**, so as to improve the efficiency of turnover of the goods **200**.

(552) In an embodiment, the transfer mechanism **430** with at least one layer includes a transfer base **431** arranged on the moving mechanism **420** and a transfer portion **432** movably arranged on the transfer base **431**, and the transfer portion **432** may drive the goods **200** to move, and may receive and pick or transfer the goods **200** to at least one of the plurality of loading or unloading mechanisms **620**. The transfer base **431** plays a bearing role and is configured to carry the transfer portion **432**, so as to mount the transfer portion **432** on the moving mechanism **420**. When the moving mechanism **420** ascends or descends, the transfer base **431** may drive the transfer portion **432** to ascend or descend synchronously, so as to implement the loading or unloading of the goods **200**.

(553) Optionally, the transfer portion **432** is of a structure that can implement horizontal transport, such as a conveyor belt structure, an assembly line, a conveyor roller structure, a roller structure, or the like. Exemplarily, the transfer portion **432** is of a rolling shaft structure, and specifically includes a plurality of rolling shafts, and each of the plurality of rolling shafts includes a built-in rolling motor to drive the each of the plurality of rolling shafts to rotate, thereby implementing the transport of the goods **200**. It should be noted that, there are various structures that can implement the horizontal transport of the goods **200**, which cannot all be listed herein, and the transfer portion **432** in the present disclosure is not limited to being implemented by the foregoing specific structures.

(554) The transfer portion **432** may receive and pick the goods **200** of one loading or unloading mechanism **620** at one time, as mentioned above. The transfer portion **432** may also receive and pick the goods **200** of a plurality of loading or unloading mechanisms **620** at one time, and the moving mechanism **420** may receive and pick the goods **200** of the plurality of loading or unloading mechanisms **620** layer by layer, and then convey the goods to the conveying apparatus **500** together for transport after receiving and picking the goods. Exemplarily, the moving mechanism **420** drives the transfer portion **432** to ascend to a top portion. After receiving and picking goods **200** of one loading or unloading mechanism **620**, the transfer portion **432** descends one layer to receive and pick goods **200** of one loading or unloading mechanism **620**. After the transfer portion **432** is full or the goods **200** of the plurality of loading or unloading mechanisms **620** are received, the moving mechanism **420** drives the transfer portion **432** to descend to a position of the conveying apparatus **500**, and the transfer portion **432** transfers all the goods **200** thereon to the conveying apparatus **500**. Certainly, the moving mechanism **420** may move layer by layer from bottom to top, a principle thereof is substantially the same as a principle from top to bottom, and details are not described herein again.

(555) Certainly, the transfer portion **432** may also receive and pick a plurality of goods **200** transferred by the conveying apparatus **500** at one time, and then transfer the goods to the plurality of loading or unloading mechanisms **620** layer by layer, a principle thereof is substantially the same as the foregoing principle of goods unloading, and details are not described herein again.

(556) In an embodiment, the transport system further includes a control center, components of the transport system perform a coordinated action under the control of the control center, and the control center of the transport system maintains a communication connection with an external

server. The control center may identify information of the to-be-transported goods **200**, and the control center may obtain information of a loading position and an unloading position corresponding to each piece of the to-be-transported goods **200**. The control center coordinates and controls the components according to the obtained information, so as to efficiently complete the transport of the goods **200**.

(557) In the transport robot **100** and the transport system in this embodiment, when transporting goods, a blocking mechanism **170** moves to a blocking position and may be in abutment with goods **200** in a plurality of storage assemblies **121**, so as to restrict the goods **200** from sliding out of the plurality of storage assemblies **121**. Therefore, the goods **200** are prevented from sliding out of the plurality of storage assemblies **121** during a transport process of the transport robot **100**, the safety of the goods **200** is ensured, a risk of sliding out is avoided, and the transport efficiency is improved. In addition, when the transport robot **100** loads or unloads goods, the blocking mechanism **170** moves to an avoidance position. At this time, goods **200** may be loaded into the plurality of storage assemblies **121**, and the goods **200** in the plurality of storage assemblies **121** may also be removed, which does not hinder a loading or unloading operation of the transport robot **100**, and is convenient for use.

(558) Based on the transport robot **100** of the foregoing two embodiments, the present disclosure further provides a transport method of the transport robot **100**, which is applicable to the transport robot **100** in the foregoing two embodiments. The transport method includes the following operations: a controller receives a first loading or unloading instruction; the controller controls the transport robot **100** to move to a first loading or unloading position according to the first loading or unloading instruction; in a case that the controller confirms that the first loading or unloading position is a loading position, the controller controls a carrying mechanism **150** to transfer goods **200** to the plurality of storage assemblies **121** of a storage mechanism **120**; and in a case that the controller confirms that the first loading or unloading position is an unloading position, the controller controls the transport robot **100** to unload goods at the unloading position.

(559) Components of the transport robot **100** perform a coordinated action under the control of the controller, and the controller of the transport robot **100** maintains a communication connection with a control center of the transport system or an external server. The transport robot **100** may identify information of to-be-transported goods **200**, and the transport robot **100** may obtain information of a loading position and an unloading position corresponding to each piece of the to-be-transported goods **200**. The transport robot **100** coordinates and controls the components according to the obtained information, so as to efficiently complete the transport of the goods **200**. Optionally, the controller includes, but is not limited to, a CPU, and may also be another component that can implement control.

(560) When loading or unloading is required, the controller receives the first loading or unloading instruction, and then the controller controls, according to the first loading or unloading instruction, the transport robot **100** to move, so that the transport robot **100** moves at the first loading or unloading position. The first loading or unloading position includes a loading position and an unloading position, the loading position is defined as a position at which a shelving unit is located, and the unloading position is at which a plurality of transport mechanisms **320** or a plurality of loading or unloading mechanisms **620** are located. It can be understood that the loading position and the unloading position may be interchanged, that is, the transport robot **100** may load at the unloading position and unload at the loading position.

(561) Generally, the transport robot **100** may be loaded by the carrying mechanism **150** at the loading position, and unloaded by the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620** at the unloading position. After the controller controls, according to the first loading or unloading instruction, the transport robot **100** to move to the loading position, the controller may control the lifting mechanism **140** to drive the carrying mechanism **150** to ascend or descend, so that the carrying mechanism **150** can pick goods on the

shelving unit. Then, the lifting mechanism **140** drives the carrying mechanism **150** to ascend or descend, so as to transfer the goods **200** in the carrying mechanism **150** to the plurality of storage assemblies **121**, and implement the loading of the goods **200**. This process is repeated until the plurality of storage assemblies **121** store the goods **200**. After the controller moves from the loading position to the unloading position according to the first unloading instruction, the controller controls the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620** to receive and pick the goods **200** in the plurality of storage assemblies **121**, so as to implement the unloading of the goods **200**.

(562) Certainly, the loading or unloading process may also be performed in a reverse direction, that is, the transport robot **100** is loaded at the unloading position by the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620** at the unloading position, and is unloaded by the carrying mechanism **150** at the loading position. After the controller controls, according to the first loading or unloading instruction, the transport robot **100** to move to the unloading position, the controller controls the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620** to transfer the goods **200** thereon to corresponding storage assemblies **121**, so as to implement the loading of the goods **200**. After the transport robot **100** is filled with the goods **200**, the controller moves from the unloading position to the loading position according to the first unloading instruction, the controller may control the lifting mechanism **140** to drive the carrying mechanism **150** to ascend or descend, so that the carrying mechanism **150** can pick goods in the plurality of storage assemblies **121**, and then the lifting mechanism **140** drives the carrying mechanism **150** to ascend or descend, so as to remove the goods **200** in the carrying mechanism **150**. This process is repeated until the goods **200** of the plurality of storage assemblies **121** are taken away, and the unloading of the goods **200** is implemented.

(563) It is worth noting that after controlling the transport robot **100** to move to the first loading or unloading position, the controller needs to determine whether the first loading or unloading position is the loading position or the unloading position. For example, in a case that there are no goods **200** in the transport robot **100**, after the transport robot **100** moves to the first loading or unloading position, in a case that the first loading or unloading position is the loading position, the carrying mechanism **150** loads the goods into the plurality of storage assemblies **121** in this case; and in a case that there are goods **200** in the transport robot **100**, after the transport robot **100** moves to the first loading or unloading position, in a case that the first loading or unloading position is the unloading position, the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620** unload the goods in this case.

(564) In this embodiment described above, the transport method can implement the automatic transport of the goods **200**, so that a problem of high cost and low efficiency in a current transport method is effectively resolved, the cost of the loading or unloading of the goods **200** is reduced, and the efficiency of the loading or unloading of the goods **200** is greatly improved. In addition, the carrying mechanism **150** moves to different heights under the driving of the lifting mechanism **140**, so that the to-be-transported goods **200** can be delivered to a plurality of storage assemblies **121** at different heights in the storage mechanism **120**, which has strong versatility and reduces the floor space.

(565) In an embodiment, when the transport robot **100** is unloading, a plurality of storage assemblies **121** are capable of moving synchronously to perform a synchronous unloading action, and the first loading or unloading instruction includes a first unloading instruction; and that the controller controls the transport robot **100** to unload goods at the unloading position includes the following operation: the controller receives the first unloading instruction, and the controller controls, according to the first unloading instruction, at least two of the plurality of storage assemblies **121** to simultaneously unload goods.

(566) In a case that the transport robot **100** is the transport robot **100** in the first embodiment, the

plurality of storage assemblies **121** in the transport robot **100** can implement synchronous unloading. Specifically, in a case that the first loading or unloading instruction received by the controller is the first unloading instruction, the controller controls, according to the first unloading instruction, the transport robot **100** to move from the loading position to the unloading position. The unloading position in this case corresponds to the auxiliary apparatus **300** of the transport system. In addition, the plurality of storage assemblies **121** are respectively docked with the plurality of transport mechanisms **320**. When the controller controls at least two of the plurality of storage assemblies **121** to unload simultaneously, at least two of the plurality of transport mechanisms **320** corresponding to the at least two of the plurality of storage assemblies **121** may receive and pick the goods **200** removed from the at least two of the plurality of storage assemblies **121**, so as to complete the unloading operation of the transport robot **100**.

(567) In an embodiment, when the transport robot **100** is loading, a plurality of storage assemblies **121** are capable of moving synchronously to perform a synchronous loading action, and the first loading or unloading instruction includes a first loading instruction; and that the controller controls the transport robot **100** to load goods at the loading position includes the following operation: the controller receives the first loading instruction, and the controller controls, according to the first loading instruction, the auxiliary apparatus **300** to simultaneously load goods to at least two of the plurality of storage assemblies **121**.

(568) In a case that the transport robot **100** is the transport robot **100** in the first embodiment, the plurality of storage assemblies **121** in the transport robot **100** can implement synchronous loading. In a case that the transport robot **100** needs to load goods, a loading operation is performed by the auxiliary apparatus **300**. Specifically, in a case that the first loading or unloading instruction received by the controller is the first loading instruction, the controller controls, according to the first loading instruction, the transport robot **100** to move from the unloading position to the loading position. In this case, the loading position is opposite to that in the foregoing embodiments, and the unloading position is opposite to that in the foregoing embodiments. It indicates that the loading position in this case corresponds to the auxiliary apparatus **300** of the transport system. In addition, the plurality of storage assemblies **121** are respectively docked with the plurality of transport mechanisms **320**. The controller controls a plurality of transport mechanisms **320** of the auxiliary apparatus **300** to move goods into a plurality of storage assemblies **121** at corresponding positions, so that the synchronous loading of the plurality of storage assemblies **121** is implemented, and the loading operation of the transport robot **100** is completed.

(569) In an embodiment, the transport robot **100** includes a linkage mechanism **130** electrically connected to the controller, and that the controller controls, according to the first unloading instruction, at least two of the plurality of storage assemblies **121** to simultaneously unload goods includes the following operation: the controller controls, according to the first unloading instruction, the linkage mechanism **130** to drive the at least two of the plurality of storage assemblies **121** to simultaneously move.

(570) The controller is electrically connected to the linkage mechanism **130**, and is further electrically connected to a linkage driving member **132** of the linkage mechanism **130**. The controller may control the movement of the linkage driving member **132**, so that the linkage mechanism **130** can drive the at least two of the plurality of storage assemblies **121** to move synchronously to perform an unloading action. It can be understood that, after the controller receives the first unloading instruction, and after the plurality of storage assemblies **121** of the transport robot **100** are docked with the plurality of transport mechanisms **320** of the auxiliary apparatus **300**, the controller controls, through the linkage driving member **132**, the linkage mechanism **130** to drive the at least two of the plurality of storage assemblies **121** to be lifted up synchronously, so that the goods **200** in the plurality of storage assemblies **121** slide out of the plurality of storage assemblies **121** and move to corresponding transport mechanisms **320**, and an unloading operation of the transport robot **100** is completed.

(571) In an embodiment, the transport robot **100** further includes a blocking mechanism **170** electrically connected to the controller and capable of switching between a blocking position and an avoidance position, and the first loading or unloading instruction includes a first unloading instruction; and that the controller controls the transport robot **100** to unload goods at the unloading position further includes the following operation: the controller receives the first unloading instruction, and the controller controls, according to the first unloading instruction, the blocking mechanism **170** to move to the avoidance position, so that the plurality of storage assemblies **121** are in an unloadable state.

(572) In a case that the transport robot **100** is the transport robot **100** in the second embodiment, the transport robot **100** may block the goods **200** in the plurality of storage assemblies **121**, to prevent the goods **200** from sliding out of the plurality of storage assemblies **121** during a process of transporting the goods **200** by the transport robot **100**, so as to protect the goods **200** in the plurality of storage assemblies **121** and prevent the goods **200** from being damaged. Specifically, the transport robot **100** of the present disclosure blocks the goods **200** in the plurality of storage assemblies **121** by the blocking mechanism **170** at the blocking position during a transport process. When unloading is required, the blocking mechanism **170** moves from the blocking position to the avoidance position, and at this time, the loading or unloading apparatus **600** may perform an unloading operation on the plurality of storage assemblies **121**.

(573) Because a structure and a working principle of the blocking mechanism **170** have been described in detail in the second embodiment, details are not described herein again, and the description herein is only from a perspective of a control method. Specifically, after the controller receives the first unloading instruction, the controller controls, according to the first unloading instruction, the transport robot **100** to move to the unloading position. Subsequently, the controller controls the blocking mechanism **170** to move from the blocking position to the avoidance position, the blocking mechanism **170** no longer blocks the goods **200** in the plurality of storage assemblies **121**, and the goods **200** in the plurality of storage assemblies **121** may be moved out and are in the unloadable state, which is specifically implemented by the plurality of loading or unloading mechanisms **620** of the loading or unloading apparatus **600**. Specifically, the transport robot **100** is at the unloading position. At this time, the transport robot **100** approaches the loading or unloading apparatus **600**, and the plurality of storage assemblies **121** are respectively docked with the plurality of loading or unloading mechanisms **620**. Subsequently, the controller controls the blocking mechanism **170** to move from the blocking position to the avoidance position, the blocking mechanism **170** no longer blocks the goods **200** in the plurality of storage assemblies **121**, and the plurality of loading or unloading mechanisms **620** may extend into the plurality of storage assemblies **121**, and receive and pick and remove the goods **200** in the plurality of storage assemblies **121**, so that the unloading operation of the transport robot **100** is performed.

(574) In an embodiment, the transport robot **100** further includes a blocking mechanism **170** electrically connected to the controller and capable of switching between a blocking position and an avoidance position, and the first loading or unloading instruction includes a first loading instruction; and the transport method further includes the following operation: the controller receives the first loading instruction, and the controller controls, according to the first loading instruction, the blocking mechanism **170** to move to the avoidance position, so that the plurality of storage assemblies **121** are in a loadable state.

(575) In a case that the transport robot **100** is the transport robot **100** in the second embodiment, the transport robot **100** may block the goods **200** in the plurality of storage assemblies **121**, to prevent the goods **200** from sliding out of the plurality of storage assemblies **121** during a process of transporting the goods **200** by the transport robot **100**, so as to protect the goods **200** in the plurality of storage assemblies **121** and prevent the goods **200** from being damaged. Specifically, during a loading process of the transport robot **100** of the present disclosure, the blocking mechanism **170** moves from the blocking position to the avoidance position. At this time, the plurality of loading or

unloading mechanisms **620** may perform a loading operation on the plurality of storage assemblies **121**. Specifically, the to-be-transported goods **200** are placed on the plurality of loading or unloading mechanisms **620**, and then the blocking mechanism **170** moves from the blocking position to the avoidance position, so that the plurality of loading or unloading mechanisms **620** can extend into the plurality of storage assemblies **121**. Subsequently, the goods **200** are placed in the plurality of storage assemblies **121** by the plurality of loading or unloading mechanisms **620** and then removed from the plurality of storage assemblies **121**.

(576) In an embodiment, the blocking mechanism **170** includes a plurality of blocking assemblies **172** respectively corresponding to a plurality of storage assemblies **121**, and that the controller controls, according to the first unloading instruction, the blocking mechanism **170** to move to the avoidance position includes the following operation: the controller controls, according to the first unloading instruction, a blocking assembly **172** at a specified position to move to a corresponding avoidance position, so that a storage assembly **121** at the specified position is in the unloadable state; or the controller controls, according to the first unloading instruction, the plurality of blocking assemblies **172** to respectively move into corresponding avoidance positions, so that at least two of the plurality of storage assemblies **121** are in the unloadable state.

(577) The controller is electrically connected to the blocking mechanism **170**, and is further electrically connected to a blocking driving member of the blocking mechanism **170**. The controller may control the movement of the blocking driving member, thereby causing at least one of the plurality of blocking assemblies **172** in the blocking mechanism **170** to move. It can be understood that in a case that the controller controls the movement of one or more specified blocking assemblies **172** in the blocking mechanism **170**, blocking assemblies **172** at storage assemblies **121** corresponding to the one or more specified blocking assemblies **172** move from the blocking position to the avoidance position, so that the storage assemblies **121** corresponding to the one or more specified blocking assemblies **172** are in the unloadable state. In this case, the plurality of loading or unloading mechanisms **620** may receive and pick the goods **200** in the storage assemblies **121** corresponding to the one or more specified blocking assemblies **172**. Certainly, the controller may also control all blocking assemblies **172** in the blocking mechanism **170** to move from the blocking position to the avoidance position, so that the plurality of storage assemblies **121** are in the unloadable state. In this case, the plurality of loading or unloading mechanisms **620** may receive and pick the goods **200** in corresponding storage assemblies **121**.

(578) In an embodiment, the plurality of storage assemblies **121** include a loading or unloading end **1215** configured to load or unload the goods **200**, and the transport method further includes the following operation: after the controller receives the first unloading instruction, the controller controls the carrying mechanism **150** to avoid the loading or unloading end **1215**.

(579) That is, after the controller receives the first unloading instruction, the controller controls the carrying mechanism **150** to move to a specified position, so that the carrying mechanism **150** moves away from the loading or unloading end, so as to avoid the loading or unloading of the goods **200** by the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620**. It can be understood that the loading or unloading end **1215** is an opening used for loading or unloading the goods **200**, a specific form thereof has been mentioned above, and details are not described herein again. In a case that the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620** are configured to unload goods, the carrying mechanism **150** needs to avoid the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620**, so as to avoid interference. Specifically, the controller may control the carrying mechanism **150** to move to a specified position. The specified position herein may be a topmost position of the transport robot **100** or a position higher than the plurality of transport mechanisms **320** and the plurality of loading or unloading mechanisms **620**, or may be a position different from the loading or unloading end **1215**.

(580) Specifically, in a case that the loading or unloading end **1215** is arranged on a same side as

the carrying mechanism **150**, the controller may control the carrying mechanism **150** to ascend to a top end of the transport robot **100**, and may also control the carrying mechanism **150** to ascend to a position higher than the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620** or to move to an other side of the vertical frame **110**, so that the loading or unloading end **1215** is arranged away from the carrying mechanism **150**. In this way, the carrying mechanism **150** can move away from the loading or unloading end **1215**, and the interference between the carrying mechanism **150** and the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620** at the loading or unloading end **1215** can be avoided. In a case that the loading or unloading end **1215** and the carrying mechanism **150** are arranged on opposite sides, the carrying mechanism **150** does not block the loading or unloading end **1215**, and in this case, the carrying mechanism **150** may move to a specified position or may not move, as long as the loading or unloading is not affected.

(581) In an embodiment, the plurality of storage assemblies **121** include a loading or unloading end **1215** configured to load or unload the goods **200**, and the transport method further includes the following operation: after the controller receives the first loading instruction, the controller controls the carrying mechanism **150** to avoid the loading or unloading end **1215**.

(582) It can be understood that, whether loading or unloading from the loading or unloading end **1215**, the controller needs to control the carrying mechanism **150** to avoid the loading or unloading end **1215**, so as to avoid interference between the carrying mechanism **150** and the plurality of transport mechanisms **320** or the plurality of loading or unloading mechanisms **620** at the loading or unloading end **1215**. An avoidance principle is the same as that in the foregoing embodiments, and details are not described herein again.

Embodiment 6

(583) As shown in FIG. **18** and FIG. **19**, and FIG. **23** and FIG. **24**, an embodiment of the present disclosure provides a loading or unloading apparatus **10a** configured to convey goods **90a** to a transport robot **60a** or unload goods **90a** on the transport robot **60a** and including an upright frame **100a** and a plurality of goods loading or unloading assemblies **200a**. The upright frame **100a** extends along a vertical direction. The plurality of goods loading or unloading assemblies **200a** are arranged on the upright frame **100a** at intervals along the vertical direction and capable of separately conveying, at different heights, the goods **90a** to the transport robot **60a** or unloading the goods **90a** on the transport robot **60a**. In the loading or unloading apparatus **10a**, the plurality of goods loading or unloading assemblies **200a** may separately convey, at different heights, the goods **90a** to the transport robot **60a**, or unload the goods **90a** on the transport robot **60a**, which greatly shortens the waiting time of the transport robot **60a** during a loading or unloading process, thereby significantly improving the loading or unloading efficiency of the transport robot **60a**, and finally improving the overall transport efficiency of a loading or unloading system. It can be understood that the goods **90a** in the present disclosure may also be an empty box or a box carrying the goods **90a**.

(584) It can be understood that heights of the plurality of goods loading or unloading assemblies **200a** respectively correspond to heights of a plurality of storage trays **640a** on the transport robot **60a**, so that the plurality of goods loading or unloading assemblies **200a** can convey the goods **90a** to all storage trays **640a** on the transport robot **60a** at one time, or the plurality of goods loading or unloading assemblies **200a** can remove the goods **90a** on all storage trays **640a** on the transport robot **60a** at one time. Certainly, in specific working conditions, one or more goods loading or unloading assemblies **200a** in the loading or unloading apparatus **10a** may simultaneously convey the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**.

(585) As shown in FIG. **18** and FIG. **19**, in an embodiment of the present disclosure, each of the plurality of goods loading or unloading assemblies **200a** may act independently to convey the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**. In an implementation, each of the plurality of goods loading or unloading assemblies **200a** includes a

bracket **210a**, a loading or unloading structure, and a first driving structure, a plurality of brackets **210a** are arranged on the upright frame **100a** at intervals along the vertical direction, the first driving structure and the loading or unloading structure are respectively arranged on corresponding brackets **210a**, and the loading or unloading structure is in driving connection with the first driving structure and is configured to convey the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**. An independent first driving structure in each of the plurality of goods loading or unloading assemblies **200a** can allow the each of the plurality of goods loading or unloading assemblies **200a** to individually convey the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**.

(586) Further, as shown in FIG. **19**, the loading or unloading structure includes a chain **220a** and a protrusion **230a**, the chain **220a** is rotatably arranged on the bracket **210a** along a loading or unloading direction, and the protrusion **230a** is fixedly arranged on the chain **220a**. The first driving structure includes a driving motor **240a** in driving connection with the chain **220a**; and the chain **220a** is capable of carrying the goods **90a**, and when the driving motor **240a** drives the chain **220a** to rotate, the protrusion **230a** pushes a bottom portion of goods **90a**, so that the goods **90a** are pushed to the transport robot **60a**, or the protrusion **230a** pulls a bottom portion of goods **90a**, so that the goods **90a** are pulled from the transport robot **60a** to the chain **220a**. Specifically, the chain **220a** is arranged on two sprockets arranged at intervals along the loading or unloading direction, and an output shaft of the driving motor **240a** is in driving connection with one of the two sprockets. When rotating, the driving motor **240a** drives the chain **220a** to operate, and the protrusion **230a** pushes the bottom portion of the goods **90a**, so as to push the goods **90a** to the transport robot **60a**, or the protrusion **230a** pulls the bottom portion of the goods **90a**, so as to pull the goods **90a** from the transport robot **60a** to the chain **220a**.

(587) Furthermore, each of the plurality of goods loading or unloading assemblies **200a** includes two sets of loading or unloading structures, the two sets of loading or unloading structures are arranged on the bracket **210a** in parallel and at intervals, and the driving motor **240a** is in driving connection with two chains **220a**. The two sets of loading or unloading structures can increase the stability during the loading or unloading of the goods **90a**. In an embodiment of the present disclosure, as shown in FIG. **19**, each of the plurality of goods loading or unloading assemblies **200a** further includes a synchronization rod **250a**, the two chains **220a** are separately in driving connection with the synchronization rod **250a**, and the driving motor **240a** is in driving connection with one of the two chains **220a**. Specifically, the synchronization rod **250a** connects two sprockets arranged at intervals along a horizontal direction perpendicular to the loading or unloading direction, thereby ensuring that the two chains **220a** rotate synchronously. It can be understood that the chain **220a** in the foregoing embodiment only plays a role of driving and carrying goods. In another embodiment of the present disclosure, a belt, a timing belt, or the like, are used to replace the chain.

(588) In an embodiment of the present disclosure, as shown in FIG. **22a**, the loading or unloading apparatus **10a** further includes a lifting assembly, arranged at one ends of the plurality of goods loading or unloading assemblies **200a** away from the transport robot **60a**, where the lifting assembly is configured to successively receive the goods **90a** unloaded by the plurality of goods loading or unloading assemblies **200a**, or successively convey the goods **90a** to the plurality of goods loading or unloading assemblies **200a**. In an implementation, as shown in FIG. **22**, the lifting assembly includes a lifting roller **500a** extending along the loading or unloading direction and capable of simultaneously carrying a plurality of goods **90a**. The lifting assembly can receive goods **90a** on a temporary storage shelving unit **400a** or the goods **90a** on the plurality of goods loading or unloading assemblies **200a**, and then transfer the goods **90a** to a corresponding transport line, thereby implementing the automation of a transport process of the goods **90a**. Alternatively, the lifting assembly can convey the goods **90a** to a temporary storage shelving unit **400a** or the plurality of goods loading or unloading assemblies **200a**.

(589) In an embodiment of the present disclosure, all goods loading or unloading assemblies **200a** in the loading or unloading apparatus **10a** act synchronously to convey, at different heights, the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**. As shown in FIG. 23 to FIG. 25, in an implementation, the loading or unloading apparatus **10a** further includes a second driving structure **300a** configured to drive the upright frame **100a** to approach or move away from the transport robot **60a** along the loading or unloading direction, and when the second driving structure **300a** drives the upright frame **100a** to approach or move away from the transport robot **60a**, the plurality of goods loading or unloading assemblies **200a** convey the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**. The loading or unloading apparatus **10a** provided in this embodiment can remove all the goods **90a** on the transport robot **60a** at one time, or simultaneously convey a plurality of goods **90a** to the transport robot **60a**. In an implementation, the second driving structure **300a** adopts a driving structure in the form of a motor and a belt.

(590) In an embodiment of the present disclosure, as shown in FIG. 23 and FIG. 24, each of the plurality of goods loading or unloading assemblies **200a** includes a loading or unloading cross arm **260a** and a push-pull structure, one ends of a plurality of loading or unloading cross arms **260a** are arranged on the upright frame **100a** at intervals along the vertical direction, and the push-pull structure is rotatably arranged at other ends corresponding to the plurality of loading or unloading cross arms **260a**. When rotating, the push-pull structure includes a push-pull position and an avoidance position, and when rotating to the push-pull position, the push-pull structure conveys the goods **90a** to the transport robot **60a** or pulls down the goods **90a** on the transport robot **60a**. When the push-pull structure rotates to the avoidance position, the push-pull structure avoids the goods **90a**. It can be understood that when pushing or pulling the goods **90a**, the push-pull structure may push or pull a top portion, a middle portion, or a bottom portion of the goods **90a**. In an embodiment of the present disclosure, two of the plurality of goods loading or unloading assemblies **200a** are arranged at intervals in a same horizontal direction of the upright frame **100a**, and two push-pull structures in the same horizontal direction synchronously rotate to the push-pull position or the avoidance position. The two push-pull structures in the same horizontal direction synchronously drive two sides of the goods **90a** along the loading or unloading direction. The two push-pull structures push or pull the two sides of the goods **90a** synchronously, which can effectively ensure the stability of a push-pull process of the goods **90a**. Further, the two push-pull structures in the same horizontal direction push/pull two sides of the middle portion of the goods **90a** synchronously along the loading or unloading direction. In another embodiment of the present disclosure, only one of the plurality of goods loading or unloading assemblies **200a** is arranged in a same height direction of the upright frame **100a**, and the one of the plurality of goods loading or unloading assemblies **200a** pushes or pulls the top portion or the bottom portion of the goods **90a** when pushing or pulling the goods **90a**.

(591) In an implementation, as shown in FIG. 24 and FIG. 25, the push-pull structure includes a push-pull rod **270a** and a push-pull motor **280a**, the push-pull motor **280a** is arranged at one ends of the plurality of loading or unloading cross arms **260a** away from the upright frame **100a**, the push-pull rod **270a** is arranged on an output shaft of the push-pull motor **280a**, and the push-pull motor **280a** is configured to drive the push-pull rod **270a** to rotate to the push-pull position or the avoidance position. Two push-pull rods **270a** may separately be rotated to the push-pull position under the driving of the push-pull motor **280a**, so as to pull the goods **90a** out of the transport robot **60a** or push the goods **90a** to the transport robot **60a**. It can be understood that the function of the push-pull motor **280a** is to drive the push-pull rod **270a** to rotate, and the push-pull rod **270a** is directly arranged on the output shaft of the push-pull motor **280a**, or the push-pull rod **270a** is connected to the output shaft of the push-pull motor **280a** through a transmission mechanism, as long as the push-pull motor **280a** can drive the push-pull rod **270a** to rotate to the push-pull position or the avoidance position.

(592) In an embodiment of the present disclosure, the loading or unloading apparatus **10a** further includes a temporary storage shelving unit **400a**, the upright frame **100a** is movably arranged on the temporary storage shelving unit **400a** along a horizontal direction, and the second driving structure **300a** is configured to drive the upright frame **100a** to move relative to the temporary storage shelving unit **400a** along the horizontal direction. The temporary storage shelving unit **400a** includes a shelving unit with a plurality of layers along the vertical direction, and the plurality of goods loading or unloading assemblies **200a** are configured to pull goods **90a** at different heights on the transport robot **60a** to corresponding layers of the shelving unit on the temporary storage shelving unit **400a**, or the plurality of goods loading or unloading assemblies **200a** are configured to push goods **90a** on the plurality of layers of the shelving unit to the transport robot **60a**. The temporary storage shelving unit **400a** can temporarily store the goods **90a** unloaded from the transport robot **60a** by the loading or unloading apparatus **10a**, or temporarily store the to-be-transported goods **90a** which are transported to the transport robot **60a**. In an implementation, the temporary storage shelving unit **400a** includes a temporary storage roller **410a** with a plurality of layers arranged along the vertical direction, and each layer of the temporary storage roller **410a** is capable of individually transporting the goods **90a** along the loading or unloading direction. Optionally, each layer of the temporary storage roller **410a** can simultaneously carry a plurality of goods **90a**.

(593) In the present disclosure, corresponding to the loading or unloading apparatus **10a** in the foregoing embodiments, as shown in FIG. 22 and FIG. 26, an embodiment of the present disclosure further provides a loading or unloading system, including a transport robot **60a** and the loading or unloading apparatus **10a** according to any one of the foregoing solutions. The loading or unloading apparatus **10a** is configured to convey the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**. In the loading or unloading apparatus **10a** and the loading or unloading system, a plurality of goods loading or unloading assemblies **200a** may separately convey, at different heights, goods **90a** to a transport robot **60a**, or unload goods **90a** on the transport robot **60a**, which greatly shortens the waiting time of the transport robot **60a** during a loading or unloading process, thereby significantly improving the loading or unloading efficiency of the transport robot **60a**, and finally improving the overall transport efficiency of the loading or unloading system.

(594) In an embodiment of the present disclosure, the transport robot **60a** receives the goods **90a** transported by the loading or unloading apparatus **10a** in the foregoing embodiments, or the transport robot **60a** allows the loading or unloading apparatus **10a** in the foregoing embodiments to remove the goods **90a** carried by the transport robot. In an implementation, as shown in FIG. 20 and FIG. 21 and FIG. 26, the transport robot **60a** includes a carrying component **610a**, a vertical frame **620a**, a movable chassis **630a**, and a storage tray **640a** with a plurality of layers, the vertical frame **620a** is arranged on the movable chassis **630a**, the storage tray **640a** with a plurality of layers are separately arranged on one side of the vertical frame **620a** at intervals along a vertical direction, the carrying component **610a** is arranged on an other side of the vertical frame **620a** along the vertical direction, and the carrying component **610a** is capable of conveying goods **90a** to the storage tray **640a** with a plurality of layers or taking out goods **90a** on the storage tray **640a** with a plurality of layers. It can be understood that the transport robot **60a** provided in this embodiment allows a plurality of goods loading or unloading assemblies **200a** in a loading or unloading apparatus **10a** to synchronously act to load or unload goods **90a**, and also allows the plurality of goods loading or unloading assemblies **200a** in the loading or unloading apparatus **10a** to act separately to load or unload the goods **90a**.

(595) Corresponding to the plurality of goods loading or unloading assemblies **200a** in the form of a push-pull structure, in an embodiment of the present disclosure, as shown in FIG. 26, the plurality of goods loading or unloading assemblies **200a** directly complete the loading or unloading of the goods **90a** through a loading or unloading end **643a** of the storage tray **640a** on a conventional

transport robot **60a**. In this case, the carrying component **610a** needs to avoid the loading or unloading apparatus **10a**. In an implementation, the carrying component **610a** ascends to a highest position, so as to avoid the loading or unloading apparatus **10a**. Optionally, when the transport robot **60a** moves to the loading or unloading apparatus **10a** and a blocking rod **652a** blocks the goods **90a**, the plurality of goods loading or unloading assemblies **200a** move away from the transport robot **60a** or the transport robot **60a** moves away from the plurality of goods loading or unloading assemblies **200a**, thereby completing the loading or unloading of the goods **90a**.

(596) Corresponding to the plurality of goods loading or unloading assemblies **200a** with the structure of a chain **220a** and a protrusion **230a**, in an embodiment of the present disclosure, as shown in FIG. 20 to FIG. 22, the storage tray **640a** includes a first side plate **641a** and a second side plate **642a** that are arranged at a same height of the vertical frame **620a**, arranged on the vertical frame **620a** in parallel and at intervals, and respectively configured to hold bottom portions of two sides of the goods **90a**; and the storage tray **640a** allows the loading or unloading apparatus **10a** to pull the goods **90a** from a bottom portion of the goods **90a** or allows the loading or unloading apparatus **10a** to push the goods **90a** onto the storage tray **640a**. A middle portion of the storage tray **640a** of a split structure is a gap, which allows a chain **220a** of an assembly protrusion **230a** to extend into a bottom portion of the goods **90a** through the middle portion of the storage tray **640a**, and when the chain **220a** rotates, the protrusion **230a** pushes the bottom portion of the goods **90a**, so that the goods **90a** are pushed to the transport robot **60a**, or the protrusion **230a** pulls a bottom portion of the goods **90a**, so that the goods **90a** are pulled from the transport robot **60a** to the chain **220a**. Optionally, when the transport robot **60a** moves to the loading or unloading apparatus **10a** and the protrusion **230a** blocks the goods **90a**, the chain **220a** continues to rotate to complete an action of loading or unloading the goods **90a**, or the transport robot **60a** moves away from the loading or unloading apparatus **10a** to complete an unloading process.

(597) Optionally, the storage tray **640a** includes a loading or unloading end **643a** away from or close to the carrying component **610a**, and the loading or unloading apparatus **10a** completes the loading or unloading of the goods **90a** through the loading or unloading end **643a** of the storage tray **640a**. In an embodiment of the present disclosure, one end of the storage tray **640a** close to the carrying component **610a** includes a loading or unloading end **643a**, and when the loading or unloading apparatus **10a** loads or unloads the goods **90a** with the transport robot **60a**, the carrying component **610a** ascends to a highest position to avoid the loading or unloading apparatus **10a**. In another embodiment of the present disclosure, as shown in FIG. 20 and FIG. 21, one end of the storage tray **640a** away from the carrying component **610a** includes a loading or unloading end **643a**. The transport robot **60a** further includes a blocking assembly **650a** capable of switching between a blocking position and an avoidance position, and when being located at the blocking position, the blocking assembly **650a** protrudes from the loading or unloading end **643a**, so as to prevent the goods **90a** on the storage tray **640a** from sliding out. When being located at the avoidance position, the blocking assembly **650a** avoids the loading or unloading end **643a**. The carrying component **610a** can complete the loading or unloading of the goods **90a** of the storage tray **640a** through one end of the storage tray **640a** which is close thereto. The blocking assembly **650a** can effectively prevent the goods **90a** from sliding out from the loading or unloading end **643a** of the storage tray **640a** when the carrying component **610a** completes the loading or unloading of the storage tray **640a**.

(598) Optionally, blocking assemblies **650a** corresponding to a plurality of storage trays **640a** may act synchronously or may act separately. In an embodiment of the present disclosure, the blocking assemblies **650a** corresponding to the plurality of storage trays **640a** act synchronously. Specifically, as shown in FIG. 20 and FIG. 21, the blocking assembly **650a** includes a driving rod **651a** and a plurality of blocking rods **652a**, middle portions of the plurality of blocking rods **652a** are separately and rotatably arranged at the loading or unloading end **643a** of one storage tray **640a**, tail portions of the plurality of blocking rods **652a** are separately and rotatably arranged on

the driving rod **651a**, and when the driving rod **651a** drives the tail portions of the plurality of blocking rods **652a** to move, head portions of the plurality of blocking rods **652a** separately protrude from the loading or unloading end **643a** or avoid the loading or unloading end **643a**. Only when the blocking assembly **650a** moves to the avoidance position, the loading or unloading apparatus **10a** can load or unload the goods **90a** to the transport robot **60a**. In an implementation, when moving upward along the vertical direction, the driving rod **651a** drives the plurality of blocking rods **652a** to move to the blocking position, when moving downward along the vertical direction, the driving rod **651a** drives the plurality of blocking rods **652a** to move to the avoidance position, and the driving rod **651a** is driven by a linear motor, or is driven by a rotation motor in cooperation with the protrusion **230a**.

(599) In an embodiment of the present disclosure, as shown in FIG. 22, the loading or unloading system further includes a conveyor line **70a**, the loading or unloading apparatus **10a** transports the goods **90a** to the conveyor line **70a** or receives the goods **90a** on the conveyor line **70a**, and the conveyor line **70a** can convey the goods **90a** to a corresponding destination. Further, the loading or unloading system further includes a stationary shelving unit, where the transport robot **60a** carries goods **90a** out of the stationary shelving unit, or carries goods **90a** to the stationary shelving unit. The stationary shelving unit is a starting point or an end point of the transport of the goods **90a**.

(600) In the loading or unloading system of the foregoing embodiments, a transport robot **60a** carrying goods **90a** on a storage tray **640a** moves to a loading or unloading apparatus **10a**, a plurality of goods loading or unloading assemblies **200a** in the loading or unloading apparatus **10a** remove all or some of the goods **90a** on the transport robot **60a**, then the plurality of goods loading or unloading assemblies **200a** sequentially transport the removed goods **90a** to a lifting assembly, and the lifting assembly conveys the goods **90a** to a conveyor line **70a**. The foregoing process may also be implemented in a reverse direction, which still implements the transport of the goods **90a**.

Embodiment 7

(601) As shown in FIG. 18 and FIG. 19, and FIG. 23 and FIG. 24, an embodiment of the present disclosure provides a loading or unloading apparatus **10a** configured to convey goods **90a** to a transport robot **60a** or unload goods **90a** on the transport robot **60a** and including an upright frame **100a** and a plurality of goods loading or unloading assemblies **200a**. The upright frame **100a** extends along a vertical direction. The plurality of goods loading or unloading assemblies **200a** are arranged on the upright frame **100a** at intervals along the vertical direction and capable of separately conveying, at different heights, the goods **90a** to the transport robot **60a** or unloading the goods **90a** on the transport robot **60a**. It can be understood that intervals among the plurality of goods loading or unloading assemblies **200a** correspond to intervals among storage trays **640a** on the transport robot **60a**. In an implementation, the plurality of goods loading or unloading assemblies **200a** are arranged on the upright frame **100a** at equal intervals along the vertical direction. In the loading or unloading apparatus **10a**, a plurality of goods loading or unloading assemblies **200a** may separately convey, at different heights, goods **90a** to a transport robot **60a**, or unload goods **90a** on the transport robot **60a**, which greatly shortens the waiting time of the transport robot **60a** during a loading or unloading process, thereby significantly improving the loading or unloading efficiency of the transport robot **60a**. In addition, the loading or unloading apparatus **10a** may load or unload, at a specified height, the goods **90a**, or load or unload all goods **90a** at all heights at one time, which has high flexibility and ultimately improves the overall transport efficiency of loading or unloading. It can be understood that the goods **90a** in the present disclosure may also be an empty box or a box carrying the goods **90a**. It should be noted that the transport robot **60a** includes various mechanical devices that can transfer goods, such as a device configured to convey goods between two positions, a device with a sorting function, a stacker with a stacking function, and the like.

(602) It can be understood that heights of the plurality of goods loading or unloading assemblies **200a** respectively correspond to heights of a plurality of storage trays **640a** on the transport robot

60a, so that the plurality of goods loading or unloading assemblies **200a** can convey the goods **90a** to all storage trays **640a** on the transport robot **60a** at one time, or the plurality of goods loading or unloading assemblies **200a** can remove the goods **90a** on all storage trays **640a** on the transport robot **60a** at one time. Certainly, in specific working conditions, one or more goods loading or unloading assemblies **200a** in the loading or unloading apparatus **10a** may simultaneously convey the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**.

(603) As shown in FIG. **18** and FIG. **19**, in an embodiment of the present disclosure, each of the plurality of goods loading or unloading assemblies **200a** may act independently to convey the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**. In an implementation, each of the plurality of goods loading or unloading assemblies **200a** includes a bracket **210a**, a loading or unloading structure, and a first driving structure, a plurality of brackets **210a** are arranged on the upright frame **100a** at intervals along the vertical direction, the first driving structure and the loading or unloading structure are respectively arranged on corresponding brackets **210a**, and the loading or unloading structure is in driving connection with the first driving structure and is configured to convey the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**. An independent first driving structure in each of the plurality of goods loading or unloading assemblies **200a** can allow the each of the plurality of goods loading or unloading assemblies **200a** to individually convey the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**.

(604) Further, as shown in FIG. **19**, the loading or unloading structure includes a chain **220a** and a protrusion **230a**, the chain **220a** is rotatably arranged on the bracket **210a** along a loading or unloading direction, and the protrusion **230a** is fixedly arranged on the chain **220a**. The first driving structure includes a driving motor **240a** in driving connection with the chain **220a**; and the chain **220a** can carry the goods **90a**. When the driving motor **240a** drives the chain **220a** to rotate, the protrusion **230a** pushes a bottom portion of goods **90a**, so as to push the goods **90a** to the transport robot **60a**, or the protrusion **230a** pulls a bottom portion of goods **90a**, so as to pull the goods **90a** from the transport robot **60a** to the chain **220a**, or the protrusion **230a** blocks the bottom portion of the goods **90a**, and the goods are transferred to the chain **220a** in the loading or unloading apparatus **10a** when the transport robot **60a** moves away from the loading or unloading apparatus **10a**. Specifically, the chain **220a** is arranged on two sprockets arranged at intervals along the loading or unloading direction, and an output shaft of the driving motor **240a** is in driving connection with one of the two sprockets. When rotating, the driving motor **240a** drives the chain **220a** to operate, and the protrusion **230a** pushes the bottom portion of the goods **90a**, so as to push the goods **90a** to the transport robot **60a**, or the protrusion **230a** pulls the bottom portion of the goods **90a**, so as to pull the goods **90a** from the transport robot **60a** to the chain **220a**.

(605) Furthermore, each of the plurality of goods loading or unloading assemblies **200a** includes two sets of loading or unloading structures, the two sets of loading or unloading structures are arranged on the bracket **210a** in parallel and at intervals, and the driving motor **240a** is in driving connection with two chains **220a**. The two sets of loading or unloading structures can increase the stability during the loading or unloading of the goods **90a**. In an embodiment of the present disclosure, as shown in FIG. **19**, each of the plurality of goods loading or unloading assemblies **200a** further includes a synchronization rod **250a**, the two chains **220a** are separately in driving connection with the synchronization rod **250a**, and the driving motor **240a** is in driving connection with one of the two chains **220a**. Specifically, the synchronization rod **250a** connects two sprockets arranged at intervals along a horizontal direction perpendicular to the loading or unloading direction, thereby ensuring that the two chains **220a** rotate synchronously. It can be understood that the chain **220a** in the foregoing embodiment only plays a role of driving and carrying goods. In another embodiment of the present disclosure, a belt, a timing belt, or the like, are used to replace the chain.

(606) In an embodiment of the present disclosure, all goods loading or unloading assemblies **200a**

in the loading or unloading apparatus **10a** act synchronously to convey, at different heights, the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**, or some of the plurality of goods loading or unloading assemblies **200a** in the loading or unloading apparatus **10a** act independently to convey, at specified heights, the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**. As shown in FIG. 23 to FIG. 25, in an implementation, the loading or unloading apparatus **10a** further includes a second driving structure **300a** configured to drive the upright frame **100a** to approach or move away from the transport robot **60a** along the loading or unloading direction, and when the second driving structure **300a** drives the upright frame **100a** to approach or move away from the transport robot **60a**, the plurality of goods loading or unloading assemblies **200a** convey the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**. The loading or unloading apparatus **10a** provided in this embodiment can remove all the goods **90a** or specified goods **90a** on the transport robot **60a** at one time, or simultaneously convey a plurality of goods **90a** to the transport robot **60a**. In an implementation, the second driving structure **300a** adopts a driving structure in the form of a motor and a belt.

(607) In an embodiment of the present disclosure, as shown in FIG. 23 and FIG. 24, each of the plurality of goods loading or unloading assemblies **200a** includes a loading or unloading cross arm **260a** and a push-pull structure, one ends of a plurality of loading or unloading cross arms **260a** are arranged on the upright frame **100a** at intervals along the vertical direction, and the push-pull structure is rotatably arranged at other ends corresponding to the plurality of loading or unloading cross arms **260a**. When the plurality of loading or unloading cross arms **260a** approach or move away from the transport robot **60a** along a loading or unloading direction, the push-pull structure pushes or pulls the goods **90a**, so as to convey the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**. When rotating, the push-pull structure includes a push-pull position and a second avoidance position, and when rotating to the push-pull position, the push-pull structure conveys the goods **90a** to the transport robot **60a** or pulls down the goods **90a** on the transport robot **60a**. When the push-pull structure rotates to the second avoidance position, the push-pull structure avoids the goods **90a**.

(608) It can be understood that when pushing or pulling the goods **90a**, the push-pull structure may push or pull a top portion, a middle portion, or a bottom portion of the goods **90a**. In an embodiment of the present disclosure, two of the plurality of goods loading or unloading assemblies **200a** are arranged at intervals in a same horizontal direction of the upright frame **100a**, and two push-pull structures in the same horizontal direction separately rotate to the push-pull position or the second avoidance position. The two push-pull structures in the same horizontal direction respectively drive two sides of the goods **90a** along the loading or unloading direction. The two push-pull structures push or pull the two sides of the goods **90a** synchronously, which can effectively ensure the stability of a push-pull process of the goods **90a**. Further, the two push-pull structures in the same horizontal direction push/pull two sides of the middle portion of the goods **90a** synchronously along the loading or unloading direction. It can be understood that the two push-pull structures in the same horizontal direction rotate to the push-pull position or the second avoidance position synchronously, or rotate to the push-pull position or the second avoidance position successively. In another embodiment of the present disclosure, only one of the plurality of goods loading or unloading assemblies **200a** is arranged in a same height direction of the upright frame **100a**, and the one of the plurality of goods loading or unloading assemblies **200a** pushes or pulls the top portion or the bottom portion of the goods **90a** when pushing or pulling the goods **90a**.

(609) In an implementation, as shown in FIG. 24 and FIG. 25, the push-pull structure includes a push-pull rod **270a** and a push-pull motor **280a**, the push-pull motor **280a** is arranged at one ends of the plurality of loading or unloading cross arms **260a** away from the upright frame **100a**, the push-pull rod **270a** is arranged on an output shaft of the push-pull motor **280a**, and the push-pull motor **280a** is configured to drive the push-pull rod **270a** to rotate to the push-pull position or the

second avoidance position. Two push-pull rods **270a** may separately be rotated to the push-pull position under the driving of the push-pull motor **280a**, so as to pull the goods **90a** out of the transport robot **60a** or push the goods **90a** to the transport robot **60a**. It can be understood that the function of the push-pull motor **280a** is to drive the push-pull rod **270a** to rotate, and the push-pull rod **270a** is directly arranged on the output shaft of the push-pull motor **280a**, or the push-pull rod **270a** is connected to the output shaft of the push-pull motor **280a** through a transmission mechanism, as long as the push-pull motor **280a** can drive the push-pull rod **270a** to rotate to the push-pull position or the second avoidance position.

(610) In an embodiment of the present disclosure, the loading or unloading apparatus **10a** further includes at least one temporary storage shelving unit **400a**, the upright frame **100a** is movably arranged on the temporary storage shelving unit **400a** along a horizontal direction, and the second driving structure **300a** is configured to drive the upright frame **100a** to move relative to the temporary storage shelving unit **400a** along the horizontal direction. The temporary storage shelving unit **400a** includes a shelving unit with a plurality of layers along the vertical direction, and the plurality of goods loading or unloading assemblies **200a** are configured to pull goods **90a** at different heights on the transport robot **60a** to corresponding layers of the shelving unit on the temporary storage shelving unit **400a**, or the plurality of goods loading or unloading assemblies **200a** are configured to push goods **90a** on the plurality of layers of the shelving unit to the transport robot **60a**. The temporary storage shelving unit **400a** can temporarily store the goods **90a** unloaded from the transport robot **60a** by the loading or unloading apparatus **10a**, or temporarily store the to-be-transported goods **90a** which are transported to the transport robot **60a**. In an implementation, the temporary storage shelving unit **400a** includes a temporary storage roller **410a** with a plurality of layers arranged along the vertical direction, and each layer of the temporary storage roller **410a** is capable of individually transporting the goods **90a** along the loading or unloading direction. Optionally, each layer of the temporary storage roller **410a** can simultaneously carry a plurality of goods **90a**.

(611) In the present disclosure, corresponding to the loading or unloading apparatus **10a** in the foregoing embodiments, as shown in FIG. 22 and FIG. 26, an embodiment of the present disclosure further provides a loading or unloading system, including a transport robot **60a** and the loading or unloading apparatus **10a** according to any one of the foregoing solutions. The loading or unloading apparatus **10a** is configured to convey the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**. In the loading or unloading apparatus **10a** and the loading or unloading system, a plurality of goods loading or unloading assemblies **200a** may separately convey, at different heights, goods **90a** to a transport robot **60a**, or unload goods **90a** on the transport robot **60a**, which greatly shortens the waiting time of the transport robot **60a** during a loading or unloading process, thereby significantly improving the loading or unloading efficiency of the transport robot **60a**, and finally improving the overall transport efficiency of the loading or unloading system.

(612) In an embodiment of the present disclosure, the transport robot **60a** receives the goods **90a** transported by the loading or unloading apparatus **10a** in the foregoing embodiments, or the transport robot **60a** allows the loading or unloading apparatus **10a** in the foregoing embodiments to remove the goods **90a** carried by the transport robot. In an implementation, as shown in FIG. 20 and FIG. 21 and FIG. 26, the transport robot **60a** includes a carrying component **610a**, a vertical frame **620a**, a movable chassis **630a**, and a storage tray **640a** with a plurality of layers, the vertical frame **620a** is arranged on the movable chassis **630a**, the storage tray **640a** with a plurality of layers are separately arranged on one side of the vertical frame **620a** at intervals along a vertical direction, the carrying component **610a** is arranged on an other side of the vertical frame **620a** along the vertical direction, and the carrying component **610a** is capable of conveying goods **90a** to the storage tray **640a** with a plurality of layers or taking out goods **90a** on the storage tray **640a** with a plurality of layers. It can be understood that the transport robot **60a** provided in this

embodiment allows a plurality of goods loading or unloading assemblies **200a** in a loading or unloading apparatus **10a** to synchronously act to load or unload goods **90a**, and also allows the plurality of goods loading or unloading assemblies **200a** in the loading or unloading apparatus **10a** to act separately to load or unload the goods **90a**.

(613) Corresponding to the plurality of goods loading or unloading assemblies **200a** in the form of a push-pull structure, in an embodiment of the present disclosure, as shown in FIG. 26, the plurality of goods loading or unloading assemblies **200a** directly complete the loading or unloading of the goods **90a** through a loading or unloading end **643a** of the storage tray **640a** on a conventional transport robot **60a**. In this case, the carrying component **610a** needs to avoid the loading or unloading apparatus **10a**. In an implementation, the carrying component **610a** ascends to a highest position, so as to avoid the loading or unloading apparatus **10a**. Optionally, when the transport robot **60a** moves to the loading or unloading apparatus **10a** and a blocking rod **652a** blocks the goods **90a**, the plurality of goods loading or unloading assemblies **200a** move away from the transport robot **60a** or the transport robot **60a** moves away from the plurality of goods loading or unloading assemblies **200a**, thereby completing the loading or unloading of the goods **90a**. It can be understood that when the plurality of goods loading or unloading assemblies **200a** are loaded or unloaded through one end of the storage tray **640a** on the transport robot **60a** away from the carrying component **610a**, the carrying component **610a** does not need to avoid the loading or unloading apparatus **10a**.

(614) Corresponding to the plurality of goods loading or unloading assemblies **200a** with the structure of a chain **220a** and a protrusion **230a**, in an embodiment of the present disclosure, as shown in FIG. 20 to FIG. 22, the storage tray **640a** includes a first side plate **641a** and a second side plate **642a** that are arranged at a same height of the vertical frame **620a**, arranged on the vertical frame **620a** in parallel and at intervals, and respectively configured to hold bottom portions of two sides of the goods **90a**; and the storage tray **640a** allows the loading or unloading apparatus **10a** to pull the goods **90a** from a bottom portion of the goods **90a** or allows the loading or unloading apparatus **10a** to push the goods **90a** onto the storage tray **640a**. A middle portion of the storage tray **640a** of a split structure is a gap, which allows a chain **220a** of an assembly protrusion **230a** to extend into a bottom portion of the goods **90a** through the middle portion of the storage tray **640a**, and when the chain **220a** rotates, the protrusion **230a** pushes the bottom portion of the goods **90a**, so that the goods **90a** are pushed to the transport robot **60a**, or the protrusion **230a** pulls a bottom portion of the goods **90a**, so that the goods **90a** are pulled from the transport robot **60a** to the chain **220a**. Optionally, when the transport robot **60a** moves to the loading or unloading apparatus **10a** and the protrusion **230a** blocks the goods **90a**, the chain **220a** continues to rotate to complete an action of loading or unloading the goods **90a**, or the transport robot **60a** moves away from the loading or unloading apparatus **10a** to complete an unloading process.

(615) Optionally, the storage tray **640a** includes a loading or unloading end **643a**, the loading or unloading end **643a** is one end of the storage tray **640a** away from or close to the carrying component **610a** along the loading or unloading direction, and the loading or unloading apparatus **10a** completes the loading or unloading of the goods **90a** through the loading or unloading end **643a** of the storage tray **640a**. In an embodiment of the present disclosure, one end of the storage tray **640a** close to the carrying component **610a** includes a loading or unloading end **643a**, and when the loading or unloading apparatus **10a** loads or unloads the goods **90a** with the transport robot **60a**, the carrying component **610a** ascends to a highest position to avoid the loading or unloading apparatus **10a**. In another embodiment of the present disclosure, as shown in FIG. 20 and FIG. 21, one end of the storage tray **640a** away from the carrying component **610a** includes a loading or unloading end **643a**. The transport robot **60a** further includes a blocking assembly **650a** capable of switching between a blocking position and a third avoidance position, and when being located at the blocking position, the blocking assembly **650a** protrudes from the loading or unloading end **643a**, so as to prevent the goods **90a** on the storage tray **640a** from sliding out.

When being located at the third avoidance position, the blocking assembly **650a** avoids the loading or unloading end **643a**. The carrying component **610a** can complete the loading or unloading of the goods **90a** of the storage tray **640a** through one end of the storage tray **640a** which is close thereto. The blocking assembly **650a** can effectively prevent the goods **90a** from sliding out from the loading or unloading end **643a** of the storage tray **640a** when the carrying component **610a** completes the loading or unloading of the storage tray **640a**.

(616) Optionally, blocking assemblies **650a** corresponding to a plurality of storage trays **640a** may act synchronously or may act separately. In an embodiment of the present disclosure, the blocking assemblies **650a** corresponding to the plurality of storage trays **640a** act synchronously.

Specifically, as shown in FIG. **20** and FIG. **21**, the blocking assembly **650a** includes a driving rod **651a** and a plurality of blocking rods **652a**, middle portions of the plurality of blocking rods **652a** are separately and rotatably arranged at the loading or unloading end **643a** of one storage tray **640a**, tail portions of the plurality of blocking rods **652a** are separately and rotatably arranged on the driving rod **651a**, and when the driving rod **651a** drives the tail portions of the plurality of blocking rods **652a** to move, head portions of the plurality of blocking rods **652a** separately protrude from the loading or unloading end **643a** or avoid the loading or unloading end **643a**. Only when the blocking assembly **650a** moves to the third avoidance position, the loading or unloading apparatus **10a** can load or unload the goods **90a** to the transport robot **60a**. In an implementation, when moving upward along the vertical direction, the driving rod **651a** drives the plurality of blocking rods **652a** to move to the blocking position, when moving downward along the vertical direction, the driving rod **651a** drives the plurality of blocking rods **652a** to move to the third avoidance position, and the driving rod **651a** is driven by a linear motor, or is driven by a rotation motor in cooperation with the protrusion **230a**.

(617) In an embodiment of the present disclosure, as shown in FIG. **22a**, the loading or unloading system further includes a lifting assembly, arranged at one ends of the plurality of goods loading or unloading assemblies **200a** away from the transport robot **60a**, where the lifting assembly is configured to successively receive the goods **90a** unloaded by the plurality of goods loading or unloading assemblies **200a**, or successively convey the goods **90a** to the plurality of goods loading or unloading assemblies **200a**. In an implementation, as shown in FIG. **22**, the lifting assembly includes a lifting roller **500a** extending along the loading or unloading direction and capable of simultaneously carrying one or more goods **90a**. The lifting assembly can receive goods **90a** on a temporary storage shelving unit **400a** or the goods **90a** on the plurality of goods loading or unloading assemblies **200a**, and then transfer the goods **90a** to a corresponding transport line, thereby implementing the automation of a transport process of the goods **90a**. Alternatively, the lifting assembly can convey the goods **90a** to a temporary storage shelving unit **400a** or the plurality of goods loading or unloading assemblies **200a**.

(618) In an embodiment of the present disclosure, as shown in FIG. **22**, the loading or unloading system further includes a conveyor line **70a**, the lifting assembly transports the goods **90a** to the conveyor line **70a** or receives the goods **90a** on the conveyor line **70a**, and the conveyor line **70a** can convey the goods **90a** to a corresponding destination. Further, the loading or unloading system further includes a stationary shelving unit, where the transport robot **60a** carries goods **90a** out of the stationary shelving unit, or carries goods **90a** to the stationary shelving unit. The stationary shelving unit is a starting point or an end point of the transport of the goods **90a**.

(619) In the loading or unloading system of the foregoing embodiments, a transport robot **60a** carrying goods **90a** on a storage tray **640a** moves to a loading or unloading apparatus **10a**, a plurality of goods loading or unloading assemblies **200a** in the loading or unloading apparatus **10a** remove all or some of the goods **90a** on the transport robot **60a**, then the plurality of goods loading or unloading assemblies **200a** sequentially transport the removed goods **90a** to a lifting assembly, and the lifting assembly conveys the goods **90a** to a conveyor line **70a**. The foregoing process may also be implemented in a reverse direction, which still implements the transport of the goods **90a**.

(620) An embodiment of the present disclosure further provides a loading or unloading method, which is applied to the loading or unloading apparatus **10a** according to any one of the foregoing embodiments. The loading or unloading method includes: **S30**: receiving a second loading/unloading instruction; and **S40**: at least some goods loading or unloading assemblies **200a** separately perform an action according to the second loading/unloading instruction to load/unload goods **90a**, or the at least some goods loading or unloading assemblies **200a** perform a synchronous linkage to load/unload the goods **90a**. The loading or unloading method provided in this embodiment at least has the advantages corresponding to the loading or unloading apparatus **10a**, and details are not described herein again.

(621) Optionally, during a loading or unloading process of the goods **90a**, the loading or unloading apparatus **10a** may complete the loading or unloading of the goods **90a** independently or the loading or unloading apparatus **10a** cooperates with the transport robot **60a** to complete the loading or unloading of the goods **90a**. In an embodiment of the present disclosure, in the operation **S40**: when performing the action, the at least some goods loading or unloading assemblies **200a** pull the goods **90a** from the transport robot **60a** to the loading or unloading apparatus **10a**; or when performing the action, the at least some goods loading or unloading assemblies **200a** block the goods **90a**, and when the transport robot **60a** moves away from the loading or unloading apparatus **10a**, the goods **90a** are left on corresponding goods loading or unloading assemblies **200a**; or when performing the action, the at least some goods loading or unloading assemblies **200a** push the goods **90a** from the loading or unloading apparatus **10a** to the transport robot **60a**. Further, in the operation **S40**, the loading or unloading apparatus **10a** loads or unloads the goods **90a** from one end of the storage tray **640a** on the transport robot **60a** that is close to the carrying component **610a**, or loads or unloads or unloads the goods **90a** from one end of the storage tray **640a** on the transport robot **60a** that is away from the carrying component **610a**. When loading or unloading the goods **90a** from one end close to the carrying component **610a**, the carrying component **610a** first ascend to a highest position, thereby leaving a space for the transport robot **60a** to be docked with the loading or unloading apparatus **10a**. The loading or unloading method provided in this embodiment provides more manners for loading or unloading, and improves the adaptability to actual working conditions.

(622) In an embodiment of the present disclosure, as shown in FIG. **18** and FIG. **19**, each of the plurality of goods loading or unloading assemblies **200a** includes a bracket **210a**, a loading or unloading structure, and a driving motor **240a**, a plurality of brackets **210a** are arranged on an upright frame **100a** at intervals along a vertical direction, the driving motor **240a** and the loading or unloading structure are respectively arranged on corresponding brackets **210a**; the loading or unloading structure includes a chain **220a** and a protrusion **230a**, the chain **220a** is rotatably arranged on the bracket **210a** along a loading or unloading direction, the protrusion **230a** is fixedly arranged on the chain **220a**, and the driving motor **240a** is in driving connection with the chain **220a**; and the chain **220a** can carry the goods **90a**. In the operation **S40**, the protrusion **230a** pushes a bottom portion of goods **90a**, so as to push the goods **90a** to the transport robot **60a**, or the protrusion **230a** pulls a bottom portion of goods **90a**, so as to pull the goods **90a** from the transport robot **60a** to the chain **220a**, or the protrusion **230a** blocks the bottom portion of the goods **90a**, and the goods **90a** are transferred to the chain **220a** when the transport robot **60a** moves away from the loading or unloading apparatus **10a**. The loading or unloading structure in the form of the chain **220a** and the protrusion **230a** can implement the loading or unloading of the goods **90a** through the bottom portion of the goods **90a**.

(623) Specifically, when rotating, the chain **220a** drives the protrusion **230a** to move, so as to form a loading or unloading position and a first avoidance position, and when being located at the loading or unloading position, the protrusion **230a** is capable of being in abutment with the bottom portion of the goods **90a** along the loading or unloading direction; and as shown in FIG. **27** and FIG. **28**, the operation **S40** includes: **S41**: determining, according to the second loading/unloading

instruction, one or more goods loading or unloading assemblies **200a** that need to perform an unloading action; **S42**: controlling a protrusion **230a** in each of the plurality of goods loading or unloading assemblies **200a** that needs to perform the unloading action to move to the first avoidance position; **S43**: controlling, after the transport robot **60a** moves to the loading or unloading position, the protrusion **230a** in the each of the plurality of goods loading or unloading assemblies **200a** that needs to perform the unloading action to move to the loading or unloading position, so that the protrusion **230a** is in abutment with the bottom portion of the goods **90a**; and **S44**: the chain **220a** drives the protrusion **230a** to move, so as to pull the goods **90a** from the transport robot **60a** to the loading or unloading apparatus **10a**, or the transport robot **60a** moves away from the loading or unloading apparatus **10a**, and the goods **90a** are left on corresponding goods loading or unloading assemblies **200a**.

(624) During a loading or unloading process of the goods **90a**, there may be goods **90a** that do not need to be unloaded from the transport robot **60a** at this time. Optionally, in the operation **S42**, whether there are goods **90a** on the transport robot **60a** at a height corresponding to each of the plurality of goods loading or unloading assemblies **200a** is determined, and in a case that there are goods **90a** on the transport robot **60a** at a corresponding height, the protrusion **230a** in the each of the plurality of goods loading or unloading assemblies **200a** at the corresponding height is controlled to move to the first avoidance position; or in the operation **S42**, protrusions **230a** in all goods loading or unloading assemblies **200a** are controlled to rotate to the first avoidance position. The loading or unloading method provided in this embodiment avoids the influence on the loading or unloading process of the goods **90a** on the transport robot **60a** that do not need to be unloaded temporarily.

(625) It can be understood that a loading process of the loading or unloading apparatus **10a** to the transport robot **60a** is a reverse process of the foregoing unloading process. Before the foregoing loading or unloading apparatus **10a** performs loading, at least one of the plurality of goods loading or unloading assemblies **200a** carries the goods **90a**, and the protrusion **230a** is in abutment with one side of the goods **90a** close to the upright frame **100a**. In an embodiment of the present disclosure, the operation **S40** includes: **S411**: determining, according to the second loading/unloading instruction, one or more goods loading or unloading assemblies **200a** that need to perform a loading action; **S422**: controlling a protrusion **230a** in each of the plurality of goods loading or unloading assemblies **200a** that needs to perform the loading action to be in abutment with one side of the goods **90a** close to the upright frame **100a**; and **S43**: controlling, after the transport robot **60a** moves to the loading or unloading position, the protrusion **230a** in the each of the plurality of goods loading or unloading assemblies **200a** that needs to perform the loading action to move to the first avoidance position, where during this process, the protrusion **230a** is driven by the chain **220a** to move toward a direction close to the transport robot **60a**, so as to push the goods **90a** from the loading or unloading apparatus **10a** to the transport robot **60a**.

(626) In another embodiment of the present disclosure, as shown in FIG. 23 to FIG. 25, the loading or unloading apparatus **10a** further includes a second driving structure **300a** configured to drive the upright frame **100a** to approach or move away from the transport robot **60a** along the loading or unloading direction, and when the second driving structure **300a** drives the upright frame **100a** to approach the transport robot **60a**, the plurality of goods loading or unloading assemblies **200a** convey the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**. Each of the plurality of goods loading or unloading assemblies **200a** includes a loading or unloading cross arm **260a** and a push-pull structure, one ends of a plurality of loading or unloading cross arms **260a** are arranged on the upright frame **100a** at intervals along the vertical direction, and the push-pull structure is rotatably arranged at other ends corresponding to the plurality of loading or unloading cross arms **260a**. In the operation **S40**, when the plurality of loading or unloading cross arms **260a** approach or move away from the transport robot **60a** along a loading or unloading direction under driving of the second driving structure **300a**, the push-pull structure

pushes or pulls the goods **90a**, so as to convey the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**, or the push-pull structure blocks the goods **90a**, and when the transport robot **60a** moves away from the loading or unloading apparatus **10a**, the goods **90a** are transferred to the loading or unloading apparatus **10a**. The loading or unloading method provided in this embodiment at least has the advantages corresponding to the loading or unloading apparatus **10a**, and details are not described herein again.

(627) In an embodiment of the present disclosure, as shown in FIG. 23 to FIG. 25, the push-pull structure includes a push-pull rod **270a** and a push-pull motor **280a**, the push-pull motor **280a** is arranged at one ends of the plurality of loading or unloading cross arms **260a** away from the upright frame **100a**, and the push-pull rod **270a** is arranged on an output shaft of the push-pull motor **280a**. When driving the push-pull rod **270a** to rotate, the push-pull motor **280a** includes a push-pull position or a second avoidance position, and when rotating to the push-pull position, the push-pull rod **270a** is in abutment with the goods **90a** in the loading or unloading direction. As shown in FIG. 29, the operation **S40** includes: **S45**: determining, according to the second loading/unloading instruction, one or more goods loading or unloading assemblies **200a** that need to perform an unloading action; **S46**: controlling a push-pull rod **270a** in each of the plurality of goods loading or unloading assemblies **200a** that needs to perform the unloading action to rotate to the second avoidance position; **S47**: the transport robot **60a** moves to the loading or unloading position, the second driving structure **300a** drives all goods loading or unloading assemblies **200a** to extend toward a direction close to the transport robot **60a**, and controls the push-pull rod **270a** in the each of the plurality of goods loading or unloading assemblies **200a** that needs to perform the unloading action to move to the push-pull position, so that the push-pull rod **270a** is in abutment with the goods **90a**; and **S48**: all the goods loading or unloading assemblies **200a** move away from the transport robot **60a** along the loading or unloading direction under the driving of the second driving structure **300a**, the push-pull rod **270a** unloads the goods **90a** on the transport robot **60a**, or the push-pull rod **270a** blocks the goods **90a**, and when the transport robot **60a** moves away from the loading or unloading apparatus **10a**, the goods **90a** are transferred to the loading or unloading apparatus **10a**.

(628) During a loading or unloading process of the goods **90a**, there may be goods **90a** that do not need to be unloaded from the transport robot **60a** at this time. Optionally, in the operation **S46**, whether there are goods **90a** on the transport robot **60a** at a height corresponding to each of the plurality of goods loading or unloading assemblies **200a** is determined, and in a case that there are goods **90a** on the transport robot **60a** at a corresponding height, the push-pull rod **270a** in the each of the plurality of goods loading or unloading assemblies **200a** at the corresponding height is controlled to move to the second avoidance position; or in the operation **S46**, push-pull rods **270a** in all goods loading or unloading assemblies **200a** are controlled to rotate to the second avoidance position. The loading or unloading method provided in this embodiment avoids the influence on the loading or unloading process of the goods **90a** on the transport robot **60a** that do not need to be unloaded temporarily.

(629) In an embodiment of the present disclosure, as shown in FIG. 24 and FIG. 25, the loading or unloading apparatus **10a** further includes at least one temporary storage shelving unit **400a**, the upright frame **100a** is movably arranged on the temporary storage shelving unit **400a** along a horizontal direction, and the second driving structure **300a** is configured to drive the upright frame **100a** to move relative to the temporary storage shelving unit **400a** along the horizontal direction. The temporary storage shelving unit **400a** includes a shelving unit with a plurality of layers along the vertical direction. In the operation **S40**, the plurality of goods loading or unloading assemblies **200a** are configured to pull goods **90a** at different heights on the transport robot **60a** to corresponding layers of the shelving unit on the temporary storage shelving unit **400a**, or the plurality of goods loading or unloading assemblies **200a** are configured to push goods **90a** on the plurality of layers of the shelving unit to the transport robot **60a**. The loading or unloading method

provided in this embodiment at least has the advantages corresponding to the loading or unloading apparatus **10a**, and details are not described herein again.

(630) It can be understood that a loading process of the loading or unloading apparatus **10a** to the transport robot **60a** is a reverse process of the foregoing unloading process. Before the foregoing loading or unloading apparatus **10a** performs loading, at least one of the plurality of goods loading or unloading assemblies **200a** carries the goods **90a**, and the push-pull rod **270a** located at the push-pull position is in abutment with one side of the goods **90a** close to the upright frame **100a**. In an embodiment of the present disclosure, the operation **S40** includes: **S455**: determining, according to the second loading/unloading instruction, one or more goods loading or unloading assemblies **200a** that need to perform a loading action; **S466**: controlling a push-pull rod **270a** in each of the plurality of goods loading or unloading assemblies **200a** that needs to perform the loading action to rotate to the push-pull position or stay at the push-pull position; and **S477**: the transport robot **60a** moves to the loading or unloading position, the second driving structure **300a** drives all loading or unloading assemblies **200a** to push out toward the direction close to the transport robot **60a**, and then the plurality of goods loading or unloading assemblies **200a** push the goods **90a** to storage trays **640a** on the transport robot **60a** along the loading or unloading direction under driving of the second driving structure **300a**.

(631) During a loading or unloading process of the goods **90a**, there may be goods **90a** that do not need to be transported from the loading or unloading apparatus **10a** to the transport robot **60a** at this time. Optionally, in the operation **S466**, it is also necessary to control a push-pull rod **270a** in each of the plurality of goods loading or unloading assemblies **200a** that do not need to perform the loading action to rotate to the second avoidance position or stay at the second avoidance position. The loading or unloading method provided in this embodiment avoids the influence on the loading or unloading process of the goods **90a** on the loading or unloading apparatus **10a** that do not need to be transported to the transport robot **60a** temporarily.

Embodiment 8

(632) As shown in FIG. **18** and FIG. **19**, and FIG. **23** and FIG. **24**, an embodiment of the present disclosure provides a loading or unloading apparatus **10a** configured to convey goods **90a** to a transport robot **60a** or unload goods **90a** on the transport robot **60a** and including an upright frame **100a** and a plurality of goods loading or unloading assemblies **200a**. The upright frame **100a** extends along a vertical direction. The plurality of goods loading or unloading assemblies **200a** are arranged on the upright frame **100a** at intervals along the vertical direction and capable of separately conveying, at different heights, the goods **90a** to the transport robot **60a** or unloading the goods **90a** on the transport robot **60a**. It can be understood that intervals among the plurality of goods loading or unloading assemblies **200a** correspond to intervals among storage trays **640a** on the transport robot **60a**. In an implementation, the plurality of goods loading or unloading assemblies **200a** are arranged on the upright frame **100a** at equal intervals along the vertical direction. In the loading or unloading apparatus **10a**, a plurality of goods loading or unloading assemblies **200a** may separately convey, at different heights, goods **90a** to a transport robot **60a**, or unload goods **90a** on the transport robot **60a**, which greatly shortens the waiting time of the transport robot **60a** during a loading or unloading process, thereby significantly improving the loading or unloading efficiency of the transport robot **60a**. In addition, the loading or unloading apparatus **10a** may load or unload, at a specified height, the goods **90a**, or load or unload all goods **90a** at all heights at one time, which has high flexibility and ultimately improves the overall transport efficiency of a loading or unloading system. It can be understood that the goods **90a** in the present disclosure may also be an empty box or a box carrying the goods **90a**. It should be noted that the transport robot **60a** includes various mechanical devices that can transfer goods, such as a device configured to convey goods between two positions, a device with a sorting function, a stacker with a stacking function, and the like.

(633) It can be understood that heights of the plurality of goods loading or unloading assemblies

200a respectively correspond to heights of a plurality of storage trays **640a** on the transport robot **60a**, so that the plurality of goods loading or unloading assemblies **200a** can convey the goods **90a** to all storage trays **640a** on the transport robot **60a** at one time, or the plurality of goods loading or unloading assemblies **200a** can remove the goods **90a** on all storage trays **640a** on the transport robot **60a** at one time. Certainly, in specific working conditions, one or more goods loading or unloading assemblies **200a** in the loading or unloading apparatus **10a** may simultaneously convey the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**. (634) As shown in FIG. **18** and FIG. **19**, in an embodiment of the present disclosure, each of the plurality of goods loading or unloading assemblies **200a** may act independently to convey the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**. In an implementation, each of the plurality of goods loading or unloading assemblies **200a** includes a bracket **210a**, a loading or unloading structure, and a first driving structure, a plurality of brackets **210a** are arranged on the upright frame **100a** at intervals along the vertical direction, the first driving structure and the loading or unloading structure are respectively arranged on corresponding brackets **210a**, and the loading or unloading structure is in driving connection with the first driving structure and is configured to convey the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**. An independent first driving structure in each of the plurality of goods loading or unloading assemblies **200a** can allow the each of the plurality of goods loading or unloading assemblies **200a** to individually convey the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**. Optionally, projections of the plurality of brackets **210a** in a horizontal plane overlap, or the distribution of the plurality of brackets **210a** in the horizontal plane is adapted to an actual structure of the transport robot **60a**, for example, the projections of the plurality of brackets **210a** in the horizontal plane partially overlap or do not overlap at all.

(635) Further, as shown in FIG. **19**, the loading or unloading structure includes a chain **220a** and a protrusion **230a**, the chain **220a** is rotatably arranged on the bracket **210a** along a loading or unloading direction, and the protrusion **230a** is fixedly arranged on the chain **220a**. The first driving structure includes a driving motor **240a** in driving connection with the chain **220a**; and the chain **220a** can carry the goods **90a**. When the driving motor **240a** drives the chain **220a** to rotate, the protrusion **230a** pushes a bottom portion of goods **90a**, so as to push the goods **90a** to the transport robot **60a**, or the protrusion **230a** pulls a bottom portion of goods **90a**, so as to pull the goods **90a** from the transport robot **60a** to the chain **220a**, or the protrusion **230a** blocks the bottom portion of the goods **90a**, and the goods are transferred to the chain **220a** in the loading or unloading apparatus **10a** when the transport robot **60a** moves away from the loading or unloading apparatus **10a**. Specifically, the chain **220a** is arranged on two sprockets arranged at intervals along the loading or unloading direction, and an output shaft of the driving motor **240a** is in driving connection with one of the two sprockets. When rotating, the driving motor **240a** drives the chain **220a** to operate, and the protrusion **230a** pushes the bottom portion of the goods **90a**, so as to push the goods **90a** to the transport robot **60a**, or the protrusion **230a** pulls the bottom portion of the goods **90a**, so as to pull the goods **90a** from the transport robot **60a** to the chain **220a**. Furthermore, each of the plurality of goods loading or unloading assemblies **200a** includes two sets of loading or unloading structures, the two sets of loading or unloading structures are arranged on the bracket **210a** in parallel and at intervals, and the driving motor **240a** is in driving connection with two chains **220a**. The two sets of loading or unloading structures can increase the stability during the loading or unloading of the goods **90a**. In an embodiment of the present disclosure, as shown in FIG. **19**, each of the plurality of goods loading or unloading assemblies **200a** further includes a synchronization rod **250a**, the two chains **220a** are separately in driving connection with the synchronization rod **250a**, and the driving motor **240a** is in driving connection with one of the two chains **220a**. Specifically, the synchronization rod **250a** connects two sprockets arranged at intervals along a horizontal direction perpendicular to the loading or unloading direction, thereby

ensuring that the two chains **220a** rotate synchronously. It can be understood that the chain **220a** in the foregoing embodiment only plays a role of driving and carrying goods. In another embodiment of the present disclosure, a belt, a timing belt, or the like, are used to replace the chain.

(636) In an embodiment of the present disclosure, all goods loading or unloading assemblies **200a** in the loading or unloading apparatus **10a** act synchronously to convey, at different heights, the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**, or some of the plurality of goods loading or unloading assemblies **200a** in the loading or unloading apparatus **10a** act independently to convey, at specified heights, the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**. As shown in FIG. 23 to FIG. 25, in an implementation, the loading or unloading apparatus **10a** further includes a second driving structure **300a** configured to drive the upright frame **100a** to approach or move away from the transport robot **60a** along the loading or unloading direction, and when the second driving structure **300a** drives the upright frame **100a** to approach or move away from the transport robot **60a**, the plurality of goods loading or unloading assemblies **200a** convey the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**. The loading or unloading apparatus **10a** provided in this embodiment can remove all the goods **90a** or specified goods **90a** on the transport robot **60a** at one time, or simultaneously convey a plurality of goods **90a** to the transport robot **60a**. In an implementation, the second driving structure **300a** adopts a driving structure in the form of a motor and a belt.

(637) In an embodiment of the present disclosure, as shown in FIG. 23 and FIG. 24, each of the plurality of goods loading or unloading assemblies **200a** includes a loading or unloading cross arm **260a** and a push-pull structure, one ends of a plurality of loading or unloading cross arms **260a** are arranged on the upright frame **100a** at intervals along the vertical direction, and the push-pull structure is rotatably arranged at other ends corresponding to the plurality of loading or unloading cross arms **260a**. When the plurality of loading or unloading cross arms **260a** approach or move away from the transport robot **60a** along a loading or unloading direction, the push-pull structure pushes or pulls the goods **90a**, so as to convey the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**. When rotating, the push-pull structure includes a push-pull position and an avoidance position, and when rotating to the push-pull position, the push-pull structure conveys the goods **90a** to the transport robot **60a** or pulls down the goods **90a** on the transport robot **60a**. When the push-pull structure rotates to the avoidance position, the push-pull structure avoids the goods **90a**. It can be understood that when pushing or pulling the goods **90a**, the push-pull structure may push or pull a top portion, a middle portion, or a bottom portion of the goods **90a**. In an embodiment of the present disclosure, two of the plurality of goods loading or unloading assemblies **200a** are arranged at intervals in a same horizontal direction of the upright frame **100a**, and two push-pull structures in the same horizontal direction separately rotate to the push-pull position or the avoidance position. The two push-pull structures in the same horizontal direction respectively drive two sides of the goods **90a** along the loading or unloading direction. The two push-pull structures push or pull the two sides of the goods **90a** synchronously, which can effectively ensure the stability of a push-pull process of the goods **90a**. Further, the two push-pull structures in the same horizontal direction push/pull two sides of the middle portion of the goods **90a** synchronously along the loading or unloading direction. It can be understood that the two push-pull structures in the same horizontal direction rotate to the push-pull position or the avoidance position synchronously, or rotate to the push-pull position or the avoidance position successively.

(638) In an implementation, as shown in FIG. 24 and FIG. 25, the push-pull structure includes a push-pull rod **270a** and a push-pull motor **280a**, the push-pull motor **280a** is arranged at one ends of the plurality of loading or unloading cross arms **260a** away from the upright frame **100a**, the push-pull rod **270a** is arranged on an output shaft of the push-pull motor **280a**, and the push-pull motor **280a** is configured to drive the push-pull rod **270a** to rotate to the push-pull position or the

avoidance position. Two push-pull rods **270a** may separately be rotated to the push-pull position under the driving of the push-pull motor **280a**, so as to pull the goods **90a** out of the transport robot **60a** or push the goods **90a** to the transport robot **60a**. In an embodiment of the present disclosure, the loading or unloading apparatus **10a** further includes at least one temporary storage shelving unit **400a**, the upright frame **100a** is movably arranged on the temporary storage shelving unit **400a** along a horizontal direction, and the second driving structure **300a** is configured to drive the upright frame **100a** to move relative to the temporary storage shelving unit **400a** along the horizontal direction. The temporary storage shelving unit **400a** includes a shelving unit with a plurality of layers along the vertical direction, and the plurality of goods loading or unloading assemblies **200a** are configured to pull goods **90a** at different heights on the transport robot **60a** to corresponding layers of the shelving unit on the temporary storage shelving unit **400a**, or the plurality of goods loading or unloading assemblies **200a** are configured to push goods **90a** on the plurality of layers of the shelving unit to the transport robot **60a**. The temporary storage shelving unit **400a** can temporarily store the goods **90a** unloaded from the transport robot **60a** by the loading or unloading apparatus **10a**, or temporarily store the to-be-transported goods **90a** which are transported to the transport robot **60a**. In an implementation, the temporary storage shelving unit **400a** includes a temporary storage roller **410a** with a plurality of layers arranged along the vertical direction, and each layer of the temporary storage roller **410a** is capable of individually transporting the goods **90a** along the loading or unloading direction. Optionally, each layer of the temporary storage roller **410a** can simultaneously carry a plurality of goods **90a**.

(639) In the present disclosure, corresponding to the loading or unloading apparatus **10a** in the foregoing embodiments, as shown in FIG. 22 and FIG. 26, an embodiment of the present disclosure further provides a loading or unloading system, including a transport robot **60a** and the loading or unloading apparatus **10a** according to any one of the foregoing solutions. The loading or unloading apparatus **10a** is configured to convey the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**. In the loading or unloading apparatus **10a** and the loading or unloading system, a plurality of goods loading or unloading assemblies **200a** may separately convey, at different heights, goods **90a** to a transport robot **60a**, or unload goods **90a** on the transport robot **60a**, which greatly shortens the waiting time of the transport robot **60a** during a loading or unloading process, thereby significantly improving the loading or unloading efficiency of the transport robot **60a**, and finally improving the overall transport efficiency of the loading or unloading system.

(640) In an embodiment of the present disclosure, the transport robot **60a** receives the goods **90a** transported by the loading or unloading apparatus **10a** in the foregoing embodiments, or the transport robot **60a** allows the loading or unloading apparatus **10a** in the foregoing embodiments to remove the goods **90a** carried by the transport robot. In an implementation, as shown in FIG. 20 and FIG. 21 and FIG. 26, the transport robot **60a** includes a carrying component **610a**, a vertical frame **620a**, a movable chassis **630a**, and a storage tray **640a** with a plurality of layers, the vertical frame **620a** is arranged on the movable chassis **630a**, the storage tray **640a** with a plurality of layers are separately arranged on one side of the vertical frame **620a** at intervals along a vertical direction, the carrying component **610a** is arranged on an other side of the vertical frame **620a** along the vertical direction, and the carrying component **610a** is capable of conveying goods **90a** to the storage tray **640a** with a plurality of layers or taking out goods **90a** on the storage tray **640a** with a plurality of layers. It can be understood that the transport robot **60a** provided in this embodiment allows a plurality of goods loading or unloading assemblies **200a** in a loading or unloading apparatus **10a** to synchronously act to load or unload goods **90a**, and also allows the plurality of goods loading or unloading assemblies **200a** in the loading or unloading apparatus **10a** to act separately to load or unload the goods **90a**.

(641) Corresponding to the plurality of goods loading or unloading assemblies **200a** in the form of a push-pull structure, in an embodiment of the present disclosure, as shown in FIG. 26, the plurality

of goods loading or unloading assemblies **200a** directly complete the loading or unloading of the goods **90a** through a loading or unloading end **643a** of the storage tray **640a** on a conventional transport robot **60a**. In this case, the carrying component **610a** needs to avoid the loading or unloading apparatus **10a**. In an implementation, the carrying component **610a** ascends to a highest position, so as to avoid the loading or unloading apparatus **10a**. Optionally, when the transport robot **60a** moves to the loading or unloading apparatus **10a** and a blocking rod **652a** blocks the goods **90a**, the plurality of goods loading or unloading assemblies **200a** move away from the transport robot **60a** or the transport robot **60a** moves away from the plurality of goods loading or unloading assemblies **200a**, thereby completing the loading or unloading of the goods **90a**. It can be understood that when the plurality of goods loading or unloading assemblies **200a** are loaded or unloaded through one end of the storage tray **640a** on the transport robot **60a** away from the carrying component **610a**, the carrying component **610a** does not need to avoid the loading or unloading apparatus **10a**.

(642) Corresponding to the plurality of goods loading or unloading assemblies **200a** with the structure of a chain **220a** and a protrusion **230a**, in an embodiment of the present disclosure, as shown in FIG. 20 to FIG. 22, the storage tray **640a** includes a first side plate **641a** and a second side plate **642a** that are arranged at a same height of the vertical frame **620a**, arranged on the vertical frame **620a** in parallel and at intervals, and respectively configured to hold bottom portions of two sides of the goods **90a**; and the storage tray **640a** allows the loading or unloading apparatus **10a** to pull the goods **90a** from a bottom portion of the goods **90a** or allows the loading or unloading apparatus **10a** to push the goods **90a** onto the storage tray **640a**. A middle portion of the storage tray **640a** of a split structure is a gap, which allows a chain **220a** of an assembly protrusion **230a** to extend into a bottom portion of the goods **90a** through the middle portion of the storage tray **640a**, and when the chain **220a** rotates, the protrusion **230a** pushes the bottom portion of the goods **90a**, so that the goods **90a** are pushed to the transport robot **60a**, or the protrusion **230a** pulls a bottom portion of the goods **90a**, so that the goods **90a** are pulled from the transport robot **60a** to the chain **220a**. Optionally, when the transport robot **60a** moves to the loading or unloading apparatus **10a** and the protrusion **230a** blocks the goods **90a**, the chain **220a** continues to rotate to complete an action of loading or unloading the goods **90a**, or the transport robot **60a** moves away from the loading or unloading apparatus **10a** to complete an unloading process.

(643) Optionally, the storage tray **640a** includes a loading or unloading end **643a**, the loading or unloading end **643a** is one end of the storage tray **640a** away from or close to the carrying component **610a** along the loading or unloading direction, and the loading or unloading apparatus **10a** completes the loading or unloading of the goods **90a** through the loading or unloading end **643a** of the storage tray **640a**. In an embodiment of the present disclosure, one end of the storage tray **640a** close to the carrying component **610a** includes a loading or unloading end **643a**, and when the loading or unloading apparatus **10a** loads or unloads the goods **90a** with the transport robot **60a**, the carrying component **610a** ascends to a highest position to avoid the loading or unloading apparatus **10a**. In another embodiment of the present disclosure, as shown in FIG. 20 and FIG. 21, one end of the storage tray **640a** away from the carrying component **610a** includes a loading or unloading end **643a**. The transport robot **60a** further includes a blocking assembly **650a** capable of switching between a blocking position and an avoidance position, and when being located at the blocking position, the blocking assembly **650a** protrudes from the loading or unloading end **643a**, so as to prevent the goods **90a** on the storage tray **640a** from sliding out. When being located at the avoidance position, the blocking assembly **650a** avoids the loading or unloading end **643a**. The carrying component **610a** can complete the loading or unloading of the goods **90a** of the storage tray **640a** through one end of the storage tray **640a** which is close thereto. The blocking assembly **650a** can effectively prevent the goods **90a** from sliding out from the loading or unloading end **643a** of the storage tray **640a** when the carrying component **610a** completes the loading or unloading of the storage tray **640a**.

(644) Optionally, blocking assemblies **650a** corresponding to a plurality of storage trays **640a** may act synchronously or may act separately. In an embodiment of the present disclosure, the blocking assemblies **650a** corresponding to the plurality of storage trays **640a** act synchronously. Specifically, as shown in FIG. 20 and FIG. 21, the blocking assembly **650a** includes a driving rod **651a** and a plurality of blocking rods **652a**, middle portions of the plurality of blocking rods **652a** are separately and rotatably arranged at the loading or unloading end **643a** of one storage tray **640a**, tail portions of the plurality of blocking rods **652a** are separately and rotatably arranged on the driving rod **651a**, and when the driving rod **651a** drives the tail portions of the plurality of blocking rods **652a** to move, head portions of the plurality of blocking rods **652a** separately protrude from the loading or unloading end **643a** or avoid the loading or unloading end **643a**. Only when the blocking assembly **650a** moves to the avoidance position, the loading or unloading apparatus **10a** can load or unload the goods **90a** to the transport robot **60a**. In an implementation, when moving upward along the vertical direction, the driving rod **651a** drives the plurality of blocking rods **652a** to move to the blocking position, when moving downward along the vertical direction, the driving rod **651a** drives the plurality of blocking rods **652a** to move to the avoidance position, and the driving rod **651a** is driven by a linear motor, or is driven by a rotation motor in cooperation with the protrusion **230a**.

(645) In an embodiment of the present disclosure, as shown in FIG. 22a, the loading or unloading system further includes a lifting assembly, arranged at one ends of the plurality of goods loading or unloading assemblies **200a** away from the transport robot **60a**, where the lifting assembly is configured to successively receive the goods **90a** unloaded by the plurality of goods loading or unloading assemblies **200a**, or successively convey the goods **90a** to the plurality of goods loading or unloading assemblies **200a**. In an implementation, as shown in FIG. 22, the lifting assembly includes a lifting roller **500a** extending along the loading or unloading direction and capable of simultaneously carrying one or more goods **90a**. The lifting assembly can receive goods **90a** on a temporary storage shelving unit **400a** or the goods **90a** on the plurality of goods loading or unloading assemblies **200a**, and then transfer the goods **90a** to a corresponding transport line, thereby implementing the automation of a transport process of the goods **90a**. Alternatively, the lifting assembly can convey the goods **90a** to a temporary storage shelving unit **400a** or the plurality of goods loading or unloading assemblies **200a**.

(646) In an embodiment of the present disclosure, as shown in FIG. 22, the loading or unloading system further includes a conveyor line **70a**, the lifting assembly transports the goods **90a** to the conveyor line **70a** or receives the goods **90a** on the conveyor line **70a**, and the conveyor line **70a** can convey the goods **90a** to a corresponding destination. Further, the loading or unloading system further includes a stationary shelving unit, where the transport robot **60a** carries goods **90a** out of the stationary shelving unit, or carries goods **90a** to the stationary shelving unit. The stationary shelving unit is a starting point or an end point of the transport of the goods **90a**.

(647) In the loading or unloading system of the foregoing embodiments, a transport robot **60a** carrying goods **90a** on a storage tray **640a** moves to a loading or unloading apparatus **10a**, a plurality of goods loading or unloading assemblies **200a** in the loading or unloading apparatus **10a** remove all or some of the goods **90a** on the transport robot **60a**, then the plurality of goods loading or unloading assemblies **200a** sequentially transport the removed goods **90a** to a lifting assembly, and the lifting assembly conveys the goods **90a** to a conveyor line **70a**. The foregoing process may also be implemented in a reverse direction, which still implements the transport of the goods **90a**.

Embodiment 9

(648) As shown in FIG. 18 and FIG. 19, and FIG. 23 and FIG. 24, an embodiment of the present disclosure provides a loading or unloading apparatus **10a** configured to convey goods **90a** to a transport robot **60a** or unload goods **90a** on the transport robot **60a** and including an upright frame **100a** and a plurality of goods loading or unloading assemblies **200a**. The upright frame **100a** extends along a vertical direction. The plurality of goods loading or unloading assemblies **200a** are

arranged on the upright frame **100a** at intervals along the vertical direction according to set intervals and capable of separately conveying, at different heights, the goods **90a** to the transport robot **60a** or unloading the goods **90a** on the transport robot **60a**. It can be understood that set intervals among the plurality of goods loading or unloading assemblies **200a** correspond to intervals among storage trays **640a** on the transport robot **60a**. In an implementation, the plurality of goods loading or unloading assemblies **200a** are arranged on the upright frame **100a** at equal intervals along the vertical direction. In another implementation, the intervals among the plurality of goods loading or unloading assemblies **200a** are different in size, which facilitates loading or unloading of living creatures **90a** at different heights.

(649) In the loading or unloading apparatus **10a**, a plurality of goods loading or unloading assemblies **200a** may separately convey, at different heights, goods **90a** to a transport robot **60a**, or unload goods **90a** on the transport robot **60a**, which greatly shortens the waiting time of the transport robot **60a** during a loading or unloading process, thereby significantly improving the loading or unloading efficiency of the transport robot **60a**. In addition, the loading or unloading apparatus **10a** may load or unload, at a specified height, the goods **90a**, or load or unload all goods **90a** at all heights at one time, which has high flexibility and ultimately improves the overall transport efficiency of a loading or unloading system. It can be understood that the goods **90a** in the present disclosure may also be an empty box or a box carrying the goods **90a**. It should be noted that the transport robot **60a** includes various mechanical devices that can transfer goods, such as a device configured to convey goods between two positions, a device with a sorting function, a stacker with a stacking function, and the like.

(650) It can be understood that heights of the plurality of goods loading or unloading assemblies **200a** respectively correspond to heights of a plurality of storage trays **640a** on the transport robot **60a**, so that the plurality of goods loading or unloading assemblies **200a** can convey the goods **90a** to all storage trays **640a** on the transport robot **60a** at one time, or the plurality of goods loading or unloading assemblies **200a** can remove the goods **90a** on all storage trays **640a** on the transport robot **60a** at one time. Certainly, in specific working conditions, one or more goods loading or unloading assemblies **200a** in the loading or unloading apparatus **10a** may simultaneously convey the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**.

(651) As shown in FIG. **18** and FIG. **19**, in an embodiment of the present disclosure, each of the plurality of goods loading or unloading assemblies **200a** may act independently to convey the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**. In an implementation, each of the plurality of goods loading or unloading assemblies **200a** includes a bracket **210a**, a loading or unloading structure, and a first driving structure, a plurality of brackets **210a** are arranged on the upright frame **100a** at intervals along the vertical direction, the first driving structure and the loading or unloading structure are respectively arranged on corresponding brackets **210a**, and the loading or unloading structure is in driving connection with the first driving structure and is configured to convey the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**. An independent first driving structure in each of the plurality of goods loading or unloading assemblies **200a** can allow the each of the plurality of goods loading or unloading assemblies **200a** to individually convey the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**.

(652) Further, as shown in FIG. **19**, the loading or unloading structure includes a chain **220a** and a protrusion **230a**, the chain **220a** is rotatably arranged on the bracket **210a** along a loading or unloading direction, and the protrusion **230a** is fixedly arranged on the chain **220a**. The first driving structure includes a driving motor **240a** in driving connection with the chain **220a**; and the chain **220a** can carry the goods **90a**. When the driving motor **240a** drives the chain **220a** to rotate, the protrusion **230a** pushes a bottom portion of goods **90a**, so as to push the goods **90a** to the transport robot **60a**, or the protrusion **230a** pulls a bottom portion of goods **90a**, so as to pull the goods **90a** from the transport robot **60a** to the chain **220a**, or the protrusion **230a** blocks the bottom

portion of the goods **90a**, and the goods are transferred to the chain **220a** in the loading or unloading apparatus **10a** when the transport robot **60a** moves away from the loading or unloading apparatus **10a**. Specifically, the chain **220a** is arranged on two sprockets arranged at intervals along the loading or unloading direction, and an output shaft of the driving motor **240a** is in driving connection with one of the two sprockets. When rotating, the driving motor **240a** drives the chain **220a** to operate, and the protrusion **230a** pushes the bottom portion of the goods **90a**, so as to push the goods **90a** to the transport robot **60a**, or the protrusion **230a** pulls the bottom portion of the goods **90a**, so as to pull the goods **90a** from the transport robot **60a** to the chain **220a**. Furthermore, each of the plurality of goods loading or unloading assemblies **200a** includes two sets of loading or unloading structures, the two sets of loading or unloading structures are arranged on the bracket **210a** in parallel and at intervals, and the driving motor **240a** is in driving connection with two chains **220a**. The two sets of loading or unloading structures can increase the stability during the loading or unloading of the goods **90a**. In an embodiment of the present disclosure, as shown in FIG. 19, each of the plurality of goods loading or unloading assemblies **200a** further includes a synchronization rod **250a**, the two chains **220a** are separately in driving connection with the synchronization rod **250a**, and the driving motor **240a** is in driving connection with one of the two chains **220a**. Specifically, the synchronization rod **250a** connects two sprockets arranged at intervals along a horizontal direction perpendicular to the loading or unloading direction, thereby ensuring that the two chains **220a** rotate synchronously.

(653) In an embodiment of the present disclosure, all goods loading or unloading assemblies **200a** in the loading or unloading apparatus **10a** act synchronously to convey, at different heights, the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**, or some of the plurality of goods loading or unloading assemblies **200a** in the loading or unloading apparatus **10a** act independently to convey, at specified heights, the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**. As shown in FIG. 23 to FIG. 25, in an implementation, the loading or unloading apparatus **10a** further includes a second driving structure **300a** configured to drive the upright frame **100a** to approach or move away from the transport robot **60a** along the loading or unloading direction, and when the second driving structure **300a** drives the upright frame **100a** to approach or move away from the transport robot **60a**, the plurality of goods loading or unloading assemblies **200a** convey the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**. The loading or unloading apparatus **10a** provided in this embodiment can remove all the goods **90a** or specified goods **90a** on the transport robot **60a** at one time, or simultaneously convey a plurality of goods **90a** to the transport robot **60a**. In an implementation, the second driving structure **300a** adopts a driving structure in the form of a motor and a belt.

(654) In an embodiment of the present disclosure, as shown in FIG. 23 and FIG. 24, each of the plurality of goods loading or unloading assemblies **200a** includes a loading or unloading cross arm **260a** and a push-pull structure, one ends of a plurality of loading or unloading cross arms **260a** are arranged on the upright frame **100a** at intervals along the vertical direction, and the push-pull structure is rotatably arranged at other ends corresponding to the plurality of loading or unloading cross arms **260a**. When the plurality of loading or unloading cross arms **260a** approach or move away from the transport robot **60a** along a loading or unloading direction, the push-pull structure pushes or pulls the goods **90a**, so as to convey the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**. When rotating, the push-pull structure includes a push-pull position and an avoidance position, and when rotating to the push-pull position, the push-pull structure conveys the goods **90a** to the transport robot **60a** or pulls down the goods **90a** on the transport robot **60a**. When the push-pull structure rotates to the avoidance position, the push-pull structure avoids the goods **90a**.

(655) It can be understood that when pushing or pulling the goods **90a**, the push-pull structure may push or pull a top portion, a middle portion, or a bottom portion of the goods **90a**. In an

embodiment of the present disclosure, two of the plurality of goods loading or unloading assemblies **200a** are arranged at intervals in a same horizontal direction of the upright frame **100a**, and two push-pull structures in the same horizontal direction separately rotate to the push-pull position or the avoidance position. The two push-pull structures in the same horizontal direction respectively drive two sides of the goods **90a** along the loading or unloading direction. The two push-pull structures push or pull the two sides of the goods **90a** synchronously, which can effectively ensure the stability of a push-pull process of the goods **90a**. Further, the two push-pull structures in the same horizontal direction push/pull two sides of the middle portion of the goods **90a** synchronously along the loading or unloading direction. It can be understood that the two push-pull structures in the same horizontal direction rotate to the push-pull position or the avoidance position synchronously, or rotate to the push-pull position or the avoidance position successively. In another embodiment of the present disclosure, only one of the plurality of goods loading or unloading assemblies **200a** is arranged in a same height direction of the upright frame **100a**, and the one of the plurality of goods loading or unloading assemblies **200a** pushes or pulls the top portion or the bottom portion of the goods **90a** when pushing or pulling the goods **90a**. (656) In an implementation, as shown in FIG. 24 and FIG. 25, the push-pull structure includes a push-pull rod **270a** and a push-pull motor **280a**, the push-pull motor **280a** is arranged at one ends of the plurality of loading or unloading cross arms **260a** away from the upright frame **100a**, the push-pull rod **270a** is arranged on an output shaft of the push-pull motor **280a**, and the push-pull motor **280a** is configured to drive the push-pull rod **270a** to rotate to the push-pull position or the avoidance position. Two push-pull rods **270a** may separately be rotated to the push-pull position under the driving of the push-pull motor **280a**, so as to pull the goods **90a** out of the transport robot **60a** or push the goods **90a** to the transport robot **60a**. It can be understood that the function of the push-pull motor **280a** is to drive the push-pull rod **270a** to rotate, and the push-pull rod **270a** is directly arranged on the output shaft of the push-pull motor **280a**, or the push-pull rod **270a** is connected to the output shaft of the push-pull motor **280a** through a transmission mechanism, as long as the push-pull motor **280a** can drive the push-pull rod **270a** to rotate to the push-pull position or the avoidance position.

(657) In an embodiment of the present disclosure, referring to FIG. 25, the loading or unloading apparatus **10a** further includes at least one temporary storage shelving unit **400a**, the upright frame **100a** is movably arranged on the temporary storage shelving unit **400a** along a horizontal direction, and the second driving structure **300a** is configured to drive the upright frame **100a** to move relative to the temporary storage shelving unit **400a** along the horizontal direction. The temporary storage shelving unit **400a** includes a shelving unit with a plurality of layers along the vertical direction, and the plurality of goods loading or unloading assemblies **200a** are configured to pull goods **90a** at different heights on the transport robot **60a** to corresponding layers of the shelving unit on the temporary storage shelving unit **400a**, or the plurality of goods loading or unloading assemblies **200a** are configured to push goods **90a** on the plurality of layers of the shelving unit to the transport robot **60a**. The temporary storage shelving unit **400a** can temporarily store the goods **90a** unloaded from the transport robot **60a** by the loading or unloading apparatus **10a**, or temporarily store the to-be-transported goods **90a** which are transported to the transport robot **60a**. In an implementation, the temporary storage shelving unit **400a** includes a temporary storage roller **410a** with a plurality of layers arranged along the vertical direction, and each layer of the temporary storage roller **410a** is capable of individually transporting the goods **90a** along the loading or unloading direction. Optionally, each layer of the temporary storage roller **410a** can simultaneously carry a plurality of goods **90a**.

(658) Corresponding to the plurality of goods loading or unloading apparatus **10a** in the foregoing embodiments, as shown in FIG. 22 and FIG. 26, an embodiment of the present disclosure further provides a loading or unloading system, including a transport robot **60a** and the loading or unloading apparatus **10a** according to any one of the foregoing solutions. The loading or unloading

apparatus **10a** is configured to convey the goods **90a** to the transport robot **60a** or unload the goods **90a** on the transport robot **60a**. In the loading or unloading apparatus **10a** and the loading or unloading system, a plurality of goods loading or unloading assemblies **200a** may separately convey, at different heights, goods **90a** to a transport robot **60a**, or unload goods **90a** on the transport robot **60a**, which greatly shortens the waiting time of the transport robot **60a** during a loading or unloading process, thereby significantly improving the loading or unloading efficiency of the transport robot **60a**, and finally improving the overall transport efficiency of the loading or unloading system.

(659) In an embodiment of the present disclosure, the transport robot **60a** receives the goods **90a** transported by the loading or unloading apparatus **10a** in the foregoing embodiments, or the transport robot **60a** allows the loading or unloading apparatus **10a** in the foregoing embodiments to remove the goods **90a** carried by the transport robot. In an implementation, as shown in FIG. **20** and FIG. **21** and FIG. **26**, the transport robot **60a** includes a carrying component **610a**, a vertical frame **620a**, a movable chassis **630a**, and a storage tray **640a** with a plurality of layers, the vertical frame **620a** is arranged on the movable chassis **630a**, the storage tray **640a** with a plurality of layers are separately arranged on one side of the vertical frame **620a** at intervals along a vertical direction, the carrying component **610a** is arranged on an other side of the vertical frame **620a** along the vertical direction, and the carrying component **610a** is capable of conveying goods **90a** to the storage tray **640a** with a plurality of layers or taking out goods **90a** on the storage tray **640a** with a plurality of layers. It can be understood that the transport robot **60a** provided in this embodiment allows a plurality of goods loading or unloading assemblies **200a** in a loading or unloading apparatus **10a** to synchronously act to load or unload goods **90a**, and also allows the plurality of goods loading or unloading assemblies **200a** in the loading or unloading apparatus **10a** to act separately to load or unload the goods **90a**.

(660) Corresponding to the plurality of goods loading or unloading assemblies **200a** in the form of a push-pull structure, in an embodiment of the present disclosure, as shown in FIG. **26**, the plurality of goods loading or unloading assemblies **200a** directly complete the loading or unloading of the goods **90a** through a loading or unloading end **643a** of the storage tray **640a** on a conventional transport robot **60a**. In this case, the carrying component **610a** needs to avoid the loading or unloading apparatus **10a**. In an implementation, the carrying component **610a** ascends to a highest position, so as to avoid the loading or unloading apparatus **10a**. Optionally, when the transport robot **60a** moves to the loading or unloading apparatus **10a** and a blocking rod **652a** blocks the goods **90a**, the plurality of goods loading or unloading assemblies **200a** move away from the transport robot **60a** or the transport robot **60a** moves away from the plurality of goods loading or unloading assemblies **200a**, thereby completing the loading or unloading of the goods **90a**. It can be understood that when the plurality of goods loading or unloading assemblies **200a** are loaded or unloaded through one end of the storage tray **640a** on the transport robot **60a** away from the carrying component **610a**, the carrying component **610a** does not need to avoid the loading or unloading apparatus **10a**.

(661) Corresponding to the plurality of goods loading or unloading assemblies **200a** with the structure of a chain **220a** and a protrusion **230a**, in an embodiment of the present disclosure, as shown in FIG. **20** to FIG. **22**, the storage tray **640a** includes a first side plate **641a** and a second side plate **642a** that are arranged at a same height of the vertical frame **620a**, arranged on the vertical frame **620a** in parallel and at intervals, and respectively configured to hold bottom portions of two sides of the goods **90a**; and the storage tray **640a** allows the loading or unloading apparatus **10a** to pull the goods **90a** from a bottom portion of the goods **90a** or allows the loading or unloading apparatus **10a** to push the goods **90a** onto the storage tray **640a**. A middle portion of the storage tray **640a** of a split structure is a gap, which allows a chain **220a** of an assembly protrusion **230a** to extend into a bottom portion of the goods **90a** through the middle portion of the storage tray **640a**, and when the chain **220a** rotates, the protrusion **230a** pushes the bottom portion of the

goods **90a**, so that the goods **90a** are pushed to the transport robot **60a**, or the protrusion **230a** pulls a bottom portion of the goods **90a**, so that the goods **90a** are pulled from the transport robot **60a** to the chain **220a**. Optionally, when the transport robot **60a** moves to the loading or unloading apparatus **10a** and the protrusion **230a** blocks the goods **90a**, the chain **220a** continues to rotate to complete an action of loading or unloading the goods **90a**, or the transport robot **60a** moves away from the loading or unloading apparatus **10a** to complete an unloading process.

(662) Optionally, the storage tray **640a** includes a loading or unloading end **643a**, the loading or unloading end **643a** is one end of the storage tray **640a** away from or close to the carrying component **610a** along the loading or unloading direction, and the loading or unloading apparatus **10a** completes the loading or unloading of the goods **90a** through the loading or unloading end **643a** of the storage tray **640a**. In an embodiment of the present disclosure, one end of the storage tray **640a** close to the carrying component **610a** includes a loading or unloading end **643a**, and when the loading or unloading apparatus **10a** loads or unloads the goods **90a** with the transport robot **60a**, the carrying component **610a** ascends to a highest position to avoid the loading or unloading apparatus **10a**. In another embodiment of the present disclosure, as shown in FIG. 20 and FIG. 21, one end of the storage tray **640a** away from the carrying component **610a** includes a loading or unloading end **643a**. The transport robot **60a** further includes a blocking assembly **650a** capable of switching between a blocking position and an avoidance position, and when being located at the blocking position, the blocking assembly **650a** protrudes from the loading or unloading end **643a**, so as to prevent the goods **90a** on the storage tray **640a** from sliding out. When being located at the avoidance position, the blocking assembly **650a** avoids the loading or unloading end **643a**. The carrying component **610a** can complete the loading or unloading of the goods **90a** of the storage tray **640a** through one end of the storage tray **640a** which is close thereto. The blocking assembly **650a** can effectively prevent the goods **90a** from sliding out from the loading or unloading end **643a** of the storage tray **640a** when the carrying component **610a** completes the loading or unloading of the storage tray **640a**.

(663) Optionally, blocking assemblies **650a** corresponding to a plurality of storage trays **640a** may act synchronously or may act separately. In an embodiment of the present disclosure, the blocking assemblies **650a** corresponding to the plurality of storage trays **640a** act synchronously. Specifically, as shown in FIG. 20 and FIG. 21, the blocking assembly **650a** includes a driving rod **651a** and a plurality of blocking rods **652a**, middle portions of the plurality of blocking rods **652a** are separately and rotatably arranged at the loading or unloading end **643a** of one storage tray **640a**, tail portions of the plurality of blocking rods **652a** are separately and rotatably arranged on the driving rod **651a**, and when the driving rod **651a** drives the tail portions of the plurality of blocking rods **652a** to move, head portions of the plurality of blocking rods **652a** separately protrude from the loading or unloading end **643a** or avoid the loading or unloading end **643a**. Only when the blocking assembly **650a** moves to the avoidance position, the loading or unloading apparatus **10a** can load or unload the goods **90a** to the transport robot **60a**. In an implementation, when moving upward along the vertical direction, the driving rod **651a** drives the plurality of blocking rods **652a** to move to the blocking position, when moving downward along the vertical direction, the driving rod **651a** drives the plurality of blocking rods **652a** to move to the avoidance position, and the driving rod **651a** is driven by a linear motor, or is driven by a rotation motor in cooperation with the protrusion **230a**.

(664) In an embodiment of the present disclosure, as shown in FIG. 22a, the loading or unloading system further includes a lifting assembly, arranged at one ends of the plurality of goods loading or unloading assemblies **200a** away from the transport robot **60a**, where the lifting assembly is configured to successively receive the goods **90a** unloaded by the plurality of goods loading or unloading assemblies **200a**, or successively convey the goods **90a** to the plurality of goods loading or unloading assemblies **200a**. In an implementation, as shown in FIG. 22, the lifting assembly includes a lifting roller **500a** extending along the loading or unloading direction and capable of

simultaneously carrying one or more goods **90a**. The lifting assembly can receive goods **90a** on a temporary storage shelving unit **400a** or the goods **90a** on the plurality of goods loading or unloading assemblies **200a**, and then transfer the goods **90a** to a corresponding transport line, thereby implementing the automation of a transport process of the goods **90a**. Alternatively, the lifting assembly can convey the goods **90a** to a temporary storage shelving unit **400a** or the plurality of goods loading or unloading assemblies **200a**.

(665) In an embodiment of the present disclosure, as shown in FIG. 22, the loading or unloading system further includes a conveyor line **70a**, the lifting assembly transports the goods **90a** to the conveyor line **70a** or receives the goods **90a** on the conveyor line **70a**, and the conveyor line **70a** can convey the goods **90a** to a corresponding destination. Further, the loading or unloading system further includes a stationary shelving unit, where the transport robot **60a** carries goods **90a** out of the stationary shelving unit, or carries goods **90a** to the stationary shelving unit. The stationary shelving unit is a starting point or an end point of the transport of the goods **90a**.

(666) In the loading or unloading system of the foregoing embodiments, a transport robot **60a** carrying goods **90a** on a storage tray **640a** moves to a loading or unloading apparatus **10a**, a plurality of goods loading or unloading assemblies **200a** in the loading or unloading apparatus **10a** remove all or some of the goods **90a** on the transport robot **60a**, then the plurality of goods loading or unloading assemblies **200a** sequentially transport the removed goods **90a** to a lifting assembly, and the lifting assembly conveys the goods **90a** to a conveyor line **70a**. The foregoing process may also be implemented in a reverse direction, which still implements the transport of the goods **90a**.

(667) The foregoing descriptions are merely specific implementations of the present disclosure, but are not intended to limit the protection scope of the present disclosure. Any variation or replacement readily figured out by a person skilled in the art within the technical scope disclosed in the present disclosure shall fall within the protection scope of the present disclosure. Therefore, the protection scope of the present disclosure shall be subject to the protection scope of the appended claims.

Claims

1. A loading or unloading apparatus, configured to convey goods to a transport robot or unload goods on the transport robot, the loading or unloading apparatus comprising: an upright frame, extending along a vertical direction; a plurality of goods loading or unloading assemblies, arranged on the upright frame at intervals along the vertical direction and capable of separately conveying, at different heights, the goods to the transport robot or unloading the goods on the transport robot; and a frame driving structure, configured to drive the upright frame to approach or move away from the transport robot along a loading or unloading direction, wherein when the frame driving structure drives the upright frame to approach or move away from the transport robot, the plurality of goods loading or unloading assemblies convey the goods to the transport robot or unload the goods on the transport robot; wherein each of the plurality of goods loading or unloading assemblies comprises a loading or unloading cross arm and a push-pull structure, one ends of a plurality of loading or unloading cross arms are arranged on the upright frame at intervals along the vertical direction, and the push-pull structure is arranged at other ends corresponding to the plurality of loading or unloading cross arms; and when the plurality of loading or unloading cross arms approach or move away from the transport robot along the loading or unloading direction, the push-pull structure pushes or pulls goods, so as to convey the goods to the transport robot or unload the goods on the transport robot.

2. The loading or unloading apparatus according to claim 1, wherein the loading or unloading apparatus further comprises at least one temporary storage shelving unit, the upright frame is movably arranged on the temporary storage shelving unit along a horizontal direction, and the frame driving structure is configured to drive the upright frame to move relative to the temporary

storage shelving unit along the horizontal direction; and the temporary storage shelving unit comprises a shelving unit with a plurality of layers along the vertical direction, and the plurality of goods loading or unloading assemblies are configured to pull goods at different heights on the transport robot to corresponding layers of the shelving unit on the temporary storage shelving unit, or the plurality of goods loading or unloading assemblies are configured to push goods on the plurality of layers of the shelving unit to the transport robot.

3. The loading or unloading apparatus according to claim 2, wherein the temporary storage shelving unit comprises a temporary storage roller with a plurality of layers arranged along the vertical direction, and each layer of the temporary storage roller is capable of individually transporting goods along the loading or unloading direction.

4. The loading or unloading apparatus according to claim 1, further comprising a lifting assembly, arranged at one ends of the plurality of goods loading or unloading assemblies away from the transport robot, wherein the lifting assembly is configured to successively receive goods unloaded by the plurality of goods loading or unloading assemblies, or successively convey goods to the plurality of goods loading or unloading assemblies.

5. The loading or unloading apparatus according to claim 4, wherein the lifting assembly comprises a lifting roller extending along the loading or unloading direction and capable of simultaneously carrying a plurality of goods.

6. The loading or unloading apparatus according to claim 1, wherein the push-pull structure is rotatably arranged at other ends of the plurality of loading or unloading cross arms away from the upright frame, when rotating, the push-pull structure is capable of switching between a push-pull position and an avoidance position, and when rotating to the push-pull position, the push-pull structure conveys the goods to the transport robot or pulls down the goods on the transport robot; and when the push-pull structure rotates to the avoidance position, the push-pull structure avoids the goods.

7. The loading or unloading apparatus according to claim 6, wherein two of the plurality of goods loading or unloading assemblies are arranged at intervals in a same horizontal direction of the upright frame, and two push-pull structures in the same horizontal direction separately and synchronously rotate to the push-pull position or the avoidance position; and the two push-pull structures in the same horizontal direction respectively and synchronously drive two sides of the goods along the loading or unloading direction.

8. The loading or unloading apparatus according to claim 6, wherein the push-pull structure comprises a push-pull rod rotatably arranged at one end of the loading or unloading cross arm away from the upright frame, and when rotating, the push-pull rod comprises the push-pull position or the avoidance position.

9. The loading or unloading apparatus according to claim 8, wherein the push-pull structure further comprises a push-pull motor arranged at the one end of the loading or unloading cross arm away from the upright frame, the push-pull rod is arranged on an output shaft of the push-pull motor, and the push-pull motor is configured to drive the push-pull rod to rotate to the push-pull position or the avoidance position.

10. A loading or unloading system, comprising: a transport robot, and a loading or unloading apparatus, comprising: an upright frame, extending along a vertical direction; a plurality of goods loading or unloading assemblies, arranged on the upright frame at intervals along the vertical direction and capable of separately conveying, at different heights, the goods to the transport robot or unloading the goods on the transport robot; and a frame driving structure, configured to drive the upright frame to approach or move away from the transport robot along a loading or unloading direction, wherein when the frame driving structure drives the upright frame to approach or move away from the transport robot, the plurality of goods loading or unloading assemblies convey the goods to the transport robot or unload the goods on the transport robot; wherein the loading or unloading apparatus further comprises at least one temporary storage shelving unit, the upright

frame is movably arranged on the temporary storage shelving unit along a horizontal direction, and the frame driving structure is configured to drive the upright frame to move relative to the temporary storage shelving unit along the horizontal direction; and the temporary storage shelving unit comprises a shelving unit with a plurality of layers along the vertical direction, and the plurality of goods loading or unloading assemblies are configured to pull goods at different heights on the transport robot to corresponding layers of the shelving unit on the temporary storage shelving unit, or the plurality of goods loading or unloading assemblies are configured to push goods on the plurality of layers of the shelving unit to the transport robot.

11. The loading or unloading system according to claim 10, wherein the temporary storage shelving unit comprises a temporary storage roller with a plurality of layers arranged along the vertical direction, and each layer of the temporary storage roller is capable of individually transporting goods along the loading or unloading direction.

12. The loading or unloading system according to claim 10, wherein the transport robot comprises a carrying component, a vertical frame, a movable chassis, a plurality of storage assemblies and a blocking mechanism, the vertical frame is arranged on the movable chassis, the plurality of storage assemblies are separately arranged on one side of the vertical frame at intervals along a vertical direction, the carrying component is arranged on an other side of the vertical frame along the vertical direction, and the carrying component is capable of conveying goods to the plurality of storage assemblies or taking out goods on the plurality of storage assemblies; the locking mechanism is capable of switching between a blocking position and an avoidance position, when the blocking mechanism is at the blocking position, the blocking mechanism is configured to block goods in the plurality of storage assemblies from sliding out, and when the blocking mechanism is at the avoidance position, the goods are capable of being moved into or moved out of the plurality of storage assemblies.

13. The loading or unloading system according to claim 12, wherein the blocking mechanism comprises a movable blocking connector and a plurality of blocking assemblies separately connected to the blocking connector, and at least one of the plurality of blocking assemblies corresponds to a same storage assembly; the blocking connector is capable of driving the plurality of blocking assemblies to move into a loading or unloading end of each of the plurality of storage assemblies, so as to block the goods in the plurality of storage assemblies; each of the plurality of blocking assemblies comprises a swing member and a blocking member, one end of the swing member is rotatably connected to the blocking connector, an other end of the swing member is mounted with the blocking member, and a middle portion of the swing member is rotatably mounted at the loading or unloading end of the plurality of storage assemblies; and when ascending or descending, the blocking connector is capable of driving the swing member to swing, so that the swing member drives the blocking member to move into or move out of the loading or unloading end.

14. The loading or unloading system according to claim 10, further comprising a lifting assembly, arranged at one ends of the plurality of goods loading or unloading assemblies away from the transport robot, wherein the lifting assembly is configured to successively receive goods unloaded by the plurality of goods loading or unloading assemblies, or successively convey goods to the plurality of goods loading or unloading assemblies.

15. The loading or unloading system according to claim 14, wherein the lifting assembly comprises a lifting roller extending along the loading or unloading direction and capable of simultaneously carrying a plurality of goods.

16. The loading or unloading system according to claim 15, further comprising a conveyor line, wherein the lifting roller is configured to successively receive goods unloaded by the goods loading or unloading assemblies, or successively convey goods to the goods loading or unloading assemblies; and the lifting roller is configured to transport goods to the conveyor line, or receive goods on the conveyor line.

17. A loading or unloading method, applied to a loading or unloading apparatus the loading or unloading apparatus comprising an upright frame, a plurality of goods loading or unloading assemblies arranged on the upright frame at intervals along the vertical direction, and a frame driving structure; the frame driving structure being configured to drive the upright frame to approach or move away from the transport robot along a loading or unloading direction, wherein when the frame driving structure drives the upright frame to approach or move away from the transport robot, the plurality of goods loading or unloading assemblies convey the goods to the transport robot or unload the goods on the transport robot; the loading or unloading method comprising: receiving a loading or unloading instruction; and controlling, according to the second loading or unloading instruction, the frame driving structure to drive the upright frame to approach or move away from the transport robot along a loading or unloading direction, and controlling the plurality of goods loading or unloading assemblies to convey the goods to the transport robot or unload the goods on the transport robot; wherein the loading or unloading apparatus further comprises at least one temporary storage shelving unit, the upright frame is movably arranged on the temporary storage shelving unit along a horizontal direction, and the frame driving structure is configured to drive the upright frame to move relative to the temporary storage shelving unit along the horizontal direction; the temporary storage shelving unit comprises a shelving unit with a plurality of layers along the vertical direction; and in the controlling, according to the loading or unloading instruction, the frame driving structure to drive the upright frame to approach or move away from the transport robot along a loading or unloading direction, and controlling the plurality of goods loading or unloading assemblies to convey the goods to the transport robot or unload the goods on the transport robot, controlling the at least some goods loading or unloading assemblies to pull goods at different heights on the transport robot to corresponding layers of the shelving unit on the temporary storage shelving unit, or controlling the at least some goods loading or unloading assemblies to push goods on the plurality of layers of the shelving unit to the transport robot.
