

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12398854
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Lim; Eay Jin et al.

Lighting device

Abstract

A lighting device disclosed in an embodiment of the invention comprises a substrate; a light source disposed on the substrate; and a light guide member disposed on the substrate and the light source, wherein the light guide member includes an exit surface and a first reflective surface facing the exit surface, the first reflective surface includes a plurality of reflective portions having different heights with respect to an upper surface of the substrate, and each of the plurality of reflective portions may include a plurality of first surfaces inclined with respect to the upper surface of the substrate.

Inventors:	Lim; Eay Jin (Seoul, KR), Ko; Kwang Hyun (Seoul, KR), Yang; Hyun Duck (Seoul, KR), Lee; Dong Hyun (Seoul, KR)
Applicant:	LG INNOTEK CO., LTD. (Seoul, KR)
Family ID:	1000008781141
Assignee:	LG INNOTEK CO., LTD. (Seoul, KR)
Appl. No.:	18/850257
Filed (or PCT Filed):	April 04, 2023
PCT No.:	PCT/KR2023/004536
PCT Pub. No.:	WO2023/195745
PCT Pub. Date:	October 12, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250207748 A1	Jun. 26, 2025

Foreign Application Priority Data

Publication Classification

Int. Cl.: F21S41/24 (20180101); F21S41/141 (20180101); F21S43/14 (20180101); F21S43/241 (20180101); F21S43/245 (20180101); F21V8/00 (20060101); F21Y115/10 (20160101)

U.S. Cl.:

CPC F21S41/24 (20180101); F21S41/141 (20180101); F21S43/14 (20180101); F21S43/241 (20180101); F21S43/245 (20180101); G02B6/0036 (20130101); F21Y2115/10 (20160801)

Field of Classification Search

CPC: F21S (43/241); F21S (41/24)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5365412	12/1993	Koppolu et al.	N/A	N/A
6036340	12/1999	Fohl	362/558	B60Q 1/26
7639918	12/2008	Sayers	362/621	G02B 6/001
11204150	12/2020	Han	N/A	N/A
2003/0235046	12/2002	Chinniah	362/602	F21S 43/245
2007/0195540	12/2006	Misawa et al.	N/A	N/A
2017/0122519	12/2016	Freiding	N/A	F21S 43/243
2018/0224083	12/2017	Nakayama	N/A	B60Q 1/44

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
07-006610	12/1994	JP	N/A
2007-227356	12/2006	JP	N/A
10-2008-0018329	12/2007	KR	N/A
10-2014-0083807	12/2013	KR	N/A
10-2018-0024588	12/2017	KR	N/A
10-2018-0076708	12/2017	KR	N/A
10-2019-0081790	12/2018	KR	N/A
10-2022-0026919	12/2021	KR	N/A

OTHER PUBLICATIONS

International Search Report dated Jun. 30, 2023 issued in Application No. PCT/KR2023/004536. cited by applicant

Primary Examiner: Eide; Eric T

Background/Summary

CROSS-REFERENCE TO RELATED PATENT APPLICATIONS

(1) This application is a U.S. National Stage Application under 35 U.S.C. § 371 of PCT Application No. PCT/KR2023/004536, filed Apr. 4, 2023, which claims priority to Korean Patent Application Nos. 10-2022-0041879, filed Apr. 4, 2022 and 10-2022-0079951, filed Jun. 29, 2022, whose entire disclosures are hereby incorporated by reference.

TECHNICAL FIELD

(2) An embodiment relates to a lighting device having a light source. The embodiment relates to a lighting device emitting light in a pattern shape or a matrix shape of a reflective surface. The embodiment relates to a vehicle lamp having the lighting device.

BACKGROUND ART

(3) Lighting applications include vehicle lights as well as backlights for displays and signs. Light emitting device, such as light emitting diode (LED), have advantages such as low power consumption, semi-permanent life, fast response speed, safety, and environmental friendliness compared to conventional light sources such as fluorescent lamps and incandescent lamps. These light emitting diodes are applied to various display devices, various lighting devices such as indoor or outdoor lights. Recently, as a vehicle light source, a lamp employing a light emitting diode has been proposed. Compared with incandescent lamps, light emitting diodes are advantageous in that power consumption is small. However, since an emission angle of light emitted from the light emitting diode is small, when the light emitting diode is used as a vehicle lamp, there is a demand for increasing the light emitting area of the lamp using the light emitting diode. Light emitting diodes can increase the design freedom of lamps because of their small size, and they are also economical because of their semi-permanent lifespan.

DISCLOSURE

Technical Problem

(4) An embodiment of the invention provides a lighting device having a dot-shaped pattern image. An embodiment of the invention provides a lighting device having an exit surface of a light guide member and a dot matrix-shaped reflective surface facing the exit surface. An embodiment of the invention provides a lighting device in which a vertical height between the reflective surfaces and the exit surface of the light guide member decreases as it gets farther away from a light source. An embodiment of the invention provides a lighting device having a light guide member having an exit surface and a reflective surface inclined along a stepped step. An embodiment of the invention provides a lighting device having a light source at a lower portion of one side of the light guide member, a primary reflective surface, a secondary reflective surface and an exit surface of the light guide member, and having a light shape of a dot-shaped pattern or a prism pattern through the exit surface. An embodiment of the invention can provide a lamp for a vehicle such as a moving object having the above-described lighting device.

Technical Solution

(5) The lighting device according to an embodiment of an invention comprises a substrate; a light source disposed on the substrate; and a light guide member disposed on the substrate and the light source, wherein the light guide member comprises an exit surface and a first reflective surface facing the exit surface, wherein the first reflective surface comprises a plurality of reflective portions having different heights with respect to an upper surface of the substrate, and each of the plurality of reflective portions may comprise a plurality of first surfaces inclined with respect to the upper surface of the substrate.

(6) According to the embodiment of the invention, the plurality of reflective portions may comprise a first reflective portion having a first height with respect to the upper surface of the substrate and a second reflective portion having a second height greater than the first height, and the first reflective portion may be disposed closer to the light source than the second reflective portion. The first surfaces may be inclined at a first angle of 120 degrees or more with respect to a straight line horizontal to the upper surface of the substrate. The first angle may be in a range of 120 degrees to 150 degrees or in a range of 128 degrees to 140 degrees.

(7) According to an embodiment of the invention, each of the plurality of reflective portions is disposed between the plurality of first surfaces and includes a plurality of inclined second surfaces, and the plurality of second surfaces may be disposed closer to the light source than the first surface. The second surfaces may have an inclination angle equal to an inclination angle of the first surface with respect to the straight line horizontal to the upper surface of the substrate. The heights of the first surface and the second surface may be equal to each other. According to an embodiment of the invention, the plurality of reflective portions may have a higher height as the reflective portion is further from the light source.

(8) According to an embodiment of the invention, a light guide distance of light horizontally incident from the light source to the second reflective portion through another reflective surface may be greater than a light guide distance of light horizontally incident from the light source to the first reflective portion through another reflective surface, and a light guide distance of light traveling vertically from the first reflective portion to the exit surface may be greater than a light guide distance of light traveling vertically from the second reflective portion to the exit surface.

(9) A lighting device according to an embodiment of the invention comprises a substrate; a light source disposed on the substrate; and a light guide member disposed on the substrate and the light source, wherein the light guide member comprises an exit surface and a first reflective surface facing the exit surface, the exit surface comprises a plurality of patterns, and the first reflective surface comprises a plurality of first surfaces having different heights with respect to an upper surface of the substrate, and a number of the plurality of patterns may be different from a number of the plurality of first surfaces.

(10) According to an embodiment of the invention, the number of the plurality of patterns may be greater than the number of the plurality of first surfaces. The plurality of patterns may be connected to each other in first and second directions that are orthogonal to each other.

(11) According to an embodiment of the invention, the light guide member comprises a second reflective surface disposed on an upper end of the light source, an upper end of the second reflective surface may be connected to one end of the exit surface, and one end of the first reflective surface may be connected to the other end of the exit surface. The second reflective surface overlaps the substrate in a vertical direction, and the second reflective surface includes a lower reflective portion and a convex curved reflective portion on the lower reflective portion in a region adjacent to the light source, and a distance between one end of the first reflective surface and the light source may be greater than a minimum distance between the light source and the second reflective surface.

(12) According to an embodiment of the invention, each of the plurality of first surfaces may be inclined, and a thickness of the light guide member may gradually become thinner as the first surface is further from the light source.

(13) According to an embodiment of the invention, the substrate is disposed on a lower surface of the light guide member, the light source is embedded in an inner side of the lower surface of the light guide member, and the patterns of the exit surface of the light guide member may overlap with the lower surface of the light guide member in a vertical direction.

(14) According to an embodiment of the invention, a portion of the first surface may be formed as an uneven pattern. The first surface having the uneven pattern may face a center portion of the upper and lower surfaces of the second reflective surface. A pattern of the exit surface

corresponding to the first reflective surface may include a pattern that overlaps in a vertical direction with the first surface and a pattern that overlaps in a vertical direction with a bottom of the first reflective surface.

(15) A vehicle lamp according to an embodiment of the invention includes the lighting device disclosed above, wherein the lighting device emits a dot matrix-shaped pattern through the exit surface.

Advantageous Effects

(16) According to the lighting device according to the embodiment of the invention, a pattern image in the form of a dot matrix can be provided, various light distribution images can be provided, and the light uniformity of the pattern image can be improved. In addition, the light distribution of the lighting device can be improved and the lighting image can be provided in various forms.

(17) According to an embodiment of the invention, since the light guide member has a reflective surface by which light from different reflective surfaces is corroded to adjust the reflection luminous intensity, uniformity of light on the exit side may be improved.

(18) The optical reliability of the lighting device according to the embodiment of the invention and the vehicle lamp having the same can be improved. The embodiment of the invention can be applied to a light unit having the lighting device, or an external or internal lighting lamp.

Description

DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a perspective view of a lighting device according to an embodiment.

(2) FIG. 2 is a perspective view showing a first reflective surface of a light guide member in the lighting device of FIG. 1.

(3) FIG. 3 is a side cross-sectional view of the lighting device of FIG. 1.

(4) FIG. 4 is a drawing for explaining the first and second reflective surfaces in the lighting device of FIG. 3.

(5) FIG. 5 is a drawing for explaining the inclination angle of the first reflective surface of the lighting device of FIG. 3.

(6) FIG. 6 is a rear view of the light guide member of the lighting device of FIG. 1.

(7) FIG. 7 is a side view showing the second reflective surface of the lighting device of FIG. 1.

(8) FIG. 8 is a drawing for explaining the lower portion of the first reflective surface of the lighting device of FIG. 2.

(9) FIG. 9 is a drawing for explaining the upper portion of the first reflective surface of the lighting device of FIG. 2.

(10) FIG. 10 is a drawing for explaining the path of light in the lighting device of FIG. 3.

(11) FIG. 11 is a perspective view for explaining the first reflective surface in the light guide member of FIG. 2.

(12) FIG. 12 is another example of the lighting device of FIG. 1.

(13) FIG. 13 is a partial side cross-sectional view of the lighting device of FIG. 12.

(14) FIG. 14 is a drawing for explaining the pattern of the exit surface and the reflective surface of the lighting device of FIG. 12.

(15) FIG. 15 is another example of the lighting device of FIG. 1.

(16) FIG. 16 is an example of arranging a reflection member on the second reflective surface of the lighting device according to an embodiment of the invention.

(17) FIG. 17 (a) to (c) are drawings for explaining the distribution of light emitted through the pattern of the exit surface in the lighting device according to an embodiment of the invention.

(18) FIG. 18 is a drawing for explaining the distribution shape of light emitted by the lighting

device of FIG. 1.

(19) FIG. 19 is a drawing for comparing a surface that has been corroded and a surface that has not been corroded in the first reflective surface in an embodiment of the invention.

(20) FIG. 20 is a drawing illustrating a light distribution passing through a light guide member according to an embodiment of the invention.

(21) FIG. 21 is a drawing illustrating a lighting device or a lamp having a lighting device according to an embodiment.

(22) FIG. 22 is an example of a vehicle tail light of FIG. 21.

(23) FIG. 23 is a drawing illustrating a pattern of a lighting device according to an embodiment of the invention applied to a vehicle lamp.

BEST MODE

(24) Hereinafter, preferred embodiments of the invention will be described in detail with reference to the accompanying drawings.

(25) The technical idea of the present invention is not limited to some of the described embodiments, but can be implemented in various different forms, and if it is within the scope of the technical idea of the present invention, one or more of its components may be selectively combined and substituted between embodiments. In addition, terms (including technical and scientific terms) used in the embodiments of the present invention, unless explicitly specifically defined and described, may be interpreted as a meaning that may be generally understood by those skilled in the art to which the present invention belongs, and terms generally used, such as terms defined in the dictionary, may be interpreted in consideration of the context of the related technology. Terms used in the embodiments of the present invention are for describing the embodiments and are not intended to limit the present invention. In the present specification, the singular form may include a plural form unless specifically described in the phrase, and may include at least one of all combinations that may be combined as A, B, and C when described as “A and/or at least one (or more than one) of B and C”. Also, terms such as first, second, A, B, (a), and (b) may be used to describe components of an embodiment of the present invention. These terms are intended only to distinguish the components from other components and are not determined by their nature, sequence, or order. Also, when a component is described as being ‘connected’, ‘coupled’ or ‘connected’ to another component, not only when the component is directly connected, coupled or connected to another component, it may also be ‘connected’, ‘coupled’, or ‘connected’ due to another component between that component and the other component. In addition, when each component is described as being formed or disposed “up (above) or down (bottom)”, the up (down) or down (bottom) includes not only when two components are in direct contact with each other, but also when one or more components are formed or disposed between two components. Also, when expressed as “up (above) or down (bottom)”, it may include the meaning of not only the upward direction but also the downward direction based on one component.

(26) The lighting device according to the embodiment can be applied to various lamp devices requiring lighting, such as vehicle lamps, household lighting devices, and industrial lighting devices. For example, when applied to vehicle lamps, it can be applied to head lamps, side mirror lights, side marker lights, fog lights, tail lamps, brake lights, daytime running lights, vehicle interior lights, door scars, rear combination lamps, backup lamps, and the like. The lighting device of the invention can be applied to indoor and outdoor advertising devices, display devices, and various types of electric vehicles, and can also be applied to all lighting-related fields or advertising-related fields that are currently developed and commercialized or can be implemented in the future with technological advancement.

(27) <Lighting Device>

(28) FIG. 1 is a perspective view of a lighting device according to an embodiment, FIG. 2 is a perspective view showing a first reflective surface of a light guide member in the lighting device of FIG. 1, FIG. 3 is a cross-sectional view taken along the line A-A of the lighting device of FIG. 1,

FIG. 4 is a drawing for explaining the first and second reflective surfaces in the lighting device of FIG. 3, FIG. 5 is a drawing for explaining the first reflective surface of the lighting device of FIG. 3, FIG. 6 is a rear view of the light guide member of the lighting device of FIG. 1, FIG. 7 is a side view showing the second reflective surface of the lighting device of FIG. 1, FIG. 8 is a drawing for explaining the lower portion of the first reflective surface of the lighting device of FIG. 2, FIG. 9 is a drawing for explaining the upper portion of the first reflective surface of the lighting device of FIG. 2, FIG. 10 is a drawing for explaining the path of light in the lighting device of FIG. 3, FIG. 11 is a perspective view for explaining the first reflective surface in the light guide member of FIG. 2, FIG. 12 is another example of the lighting device of FIG. 1, FIG. 13 is a partial side cross-sectional view of the lighting device of FIG. 12, and FIG. 14 is a drawing for explaining the pattern of the exit surface and the reflective surface of the lighting device of FIG. 12.

(29) Referring to FIGS. 1 to 13, a lighting device **200** according to the embodiment of the invention includes a light emitting portion **100** and a light guide member **110**. The light emitting portion **100** includes a substrate **101** disposed under the light guide member **110** and a light source **102** disposed on the substrate **101**.

(30) The light emitting portion **100** is disposed under one side of the light guide member **110** and emits light from the lower side to the upper side of the light guide member **110**. As another example, the light emitting portion **100** may emit light from one side to the other side of the light guide member **110**.

(31) The lighting device **200** can be defined as a light emitting cell for a structure having the light guide member **110**, light source **102**, and substrate **101**. In the lighting device **200**, the light emitting cells may be connected in a plurality as shown in FIG. 15, or arranged in a state where parts or all of the plurality of light emitting cells are separated from each other. In addition, the lighting device **200** may have one light emitting cell or a plurality of light emitting cells arranged on the substrate **101**. The lighting device **200** can emit light in a reflective structure or matrix shape of a reflective surface **131**. The lighting device can provide a lamp having various lighting shapes.

(32) <Substrate **101**>

(33) The substrate **101** may include a printed circuit board (PCB). The substrate **101** may include, for example, at least one of a resin-based PCB, a metal core PCB, a flexible PCB, a ceramic PCB, or an FR-4 substrate. When the substrate **101** is disposed as a metal core PCB having a metal layer disposed on the bottom, the heat dissipation efficiency of the light source **102** may be improved.

(34) The substrate **101** may be electrically connected to the light source **102**. The substrate **101** may include a wiring layer (not shown) on the upper side, and the wiring layer may be electrically connected to the light source **102**. When a plurality of light sources **102** is arranged on the substrate **101**, the plurality of light sources **102** may be connected in series, in parallel, or in series-parallel by the wiring layer. The substrate **101** may function as a base member or a support member disposed under the light source **102** and the light guide member **110**.

(35) The upper surface of the substrate **101** may have an X-Y plane. The upper surface of the substrate **101** may be a flat plane or a curved surface. The thickness of the substrate **101** may be a height in a vertical direction or a Z direction. Here, the X direction may be a first direction, and the Y direction may be a second direction. The Z direction may be a direction orthogonal to the first and second directions. The light source **102** may be disposed singly on the substrate **101**, and when arranged in plurality, they may be arranged in the second direction Y.

(36) The substrate **101** may be made of a flexible material, and the flexible substrate may be closely attached to the housing of a lamp in a vehicle. The substrate **101** may include a light-transmitting material through which light is transmitted through the upper and lower surfaces. The light-transmitting material may include at least one of PET (Polyethylene terephthalate), PS (Polystyrene), and PI (Polyimide). A reflective layer (not shown) may be disposed on the substrate **101**. The reflective layer is disposed between the substrate **101** and the light guide member **110** and may reflect incident light. The reflective layer may include a metallic material or a non-metallic

material. The metallic material may include a metal such as aluminum, silver, or gold. The non-metallic material may include a plastic material or a resin material.

(37) <Light Source **102**>

(38) The light source **102** is disposed on the substrate **101** and emits light in a third direction Z from one side of the light guide member **110**. The light source **102** emits light through a different side surface from the upper surface on one side of the light guide member **110**.

(39) The light source **102** may be disposed on the lower side of one side of the light guide member **110**. The light source **102** may be disposed within one side of the light guide member **110**. That is, the light guide member **110** may be disposed on the surface of the light source **102** or may seal the light source **102**. The upper surface of the light source **102** may be positioned higher than the lower surface SO of the light guide member **110**, and a plurality of side surfaces may be in contact with the light guide member **110**. The light source **102** emits light with the highest intensity in the third direction Z. The light source **102** may be electrically connected to the substrate **101** and may be provided as a package that covers the surface of the LED chip or the LED chip with resin. The light source **102** is a light emitting device having a light emitting diode (LED), and may include a package in which a light emitting chip is packaged. The light emitting chip may emit at least one of blue, red, green, ultraviolet (UV), and infrared, and the light source **102** may emit at least one of white, blue, red, green, and infrared.

(40) <Light Guide Member **110**>

(41) The light guide member **110** may be disposed on the substrate **101**. The lower surface SO of the light guide member **110** may face the substrate **101**. The light guide member **110** may be disposed on a portion of the substrate **101**. An area of the lower surface SO of the light guide member **110** facing the substrate **101** may be equal to or smaller than an area of the upper surface of the substrate **101**. The substrate **110** may be disposed on one side of the lower portion of the light guide member **110**.

(42) The light guide member **110** may be formed of a transparent material. The light guide member **110** may include a resin material such as silicone or epoxy. The light guide member **110** may include a thermosetting resin material, and may optionally include, for example, PC, OPS, PMMA, PVC, etc. The light guide member **110** may be formed of glass, but is not limited thereto. For example, a main material of the light guide member **110** may use a resin material whose main ingredient is urethane acrylate oligomer.

(43) Since the light guide member **110** is provided as a layer that guides light with resin, it may be provided with a thin thickness compared to a glass material and may be provided as a flexible plate. The light guide member **110** can emit light in a circular dot pattern or a polygonal dot pattern from the light source **102**. The light guide member **110** can include a bead (not shown), and the bead can diffuse and reflect incident light, thereby increasing the amount of light. The bead can be composed of any one selected from silicon, silica, glass bubble, PMMA (Polymethyl methacrylate), urethane, Zn, Zr, Al.sub.2O.sub.3, and acryl.

(44) The light source **102** may be embedded in the light guide member **110**. The light source **102** is disposed in the light guide member **110** and emits the generated light toward the light guide member **110**. The light guide member **110** can protect the internal light source **102** and reduce the loss of light emitted from the light source **102**. The light source **102** can be disposed in a region that does not vertically overlap with the exit surface **151** of the light guide member **110**.

(45) The uppermost layer or upper surface of the substrate **101** may be in contact with the lower surface SO of the light guide member **110**. When the reflective layer disclosed above is disposed on the uppermost layer, the reflective layer may be in contact with the lower surface SO of the light guide member **110**. Here, the reflective layer may be fixed between the light guide member **110** and the substrate **101**.

(46) As shown in FIG. 3 and FIG. 6, the maximum length X1 of the light guide member **110** in the first direction X may be greater than the width Y1 in the second direction Y. In this case, the light

guide member **110** is one, two or more, or four or less light emitting cells. The light emitting cell may have a maximum length in the first direction X that is greater than its width in the second direction Y. The maximum height TO of the light guide member **110** in the third direction Z may be smaller than the maximum length X1 in the first direction X and may be equal to or different from the width Y1 in the second direction Y. For example, the maximum height TO of the light guide member **110** in the third direction Z may be greater than the width Y1 (see FIG. 6) in the second direction Y, and the difference between the height TO and the width Y1 may be 5 mm or less, for example, 3 mm or less. By providing the maximum height TO of the third direction Z of the light guide member **110** to be greater than the width Y1, a vertical guide space can be provided for light emitted from the light source **102**, and if it is smaller than the width Y1, light extraction efficiency may be reduced. By providing the width Y1 of the second direction Y of the light guide member **110** to be narrow and the length X1 of the first direction X to be long, a dot pattern light can be provided to a vehicle lamp having a narrow width. The light guide member **110** includes an exit surface **151** and a first reflective surface **131** on the opposite side of the exit surface **151**. The first reflective surface **131** may be disposed on the other side of the light guide member **110**. The light guide member **110** may include a second reflective surface **111** on one side. The second reflective surface **111** is a surface of one side of the light guide member **110** and may reflect light emitted from the light source **102** to the first reflective surface **131**.

(47) The exit surface **151** is a surface from which light emitted from the light source **102** is emitted, and may be the upper surface of the light guide member **110**. The first reflective surface **131** is a surface that reflects the incident light in the direction of the exit surface **151**.

(48) The exit surface **151** may have a pattern P1 having a predetermined shape arranged in a first direction X or/and a second direction Y. The plurality of patterns P1 are arranged in a matrix shape, and each unit pattern may be connected in the first and second directions X and Y that are orthogonal to each other, and may have a convex curved shape, or, as shown in FIG. 12 and FIG. 14, a polygonal pyramid shape, or a prism pattern P2. As another example, the pattern P1 may be arranged in a diagonal direction inclined with respect to the first direction X or/and the second direction Y.

(49) The exit surface **151** may overlap with the first reflective surface **131** in the vertical direction Z. The exit surface **151** may not overlap with the second reflective surface **111** in the vertical direction Z. The first reflective surface **131** may not overlap with the second reflective surface **111** in the vertical direction Z. The first reflective surface **131** may overlap with the second reflective surface **111** in the first direction X. Here, the substrate **101** may overlap with the second reflective surface **111** and the exit surface **151** in the vertical direction. A portion of the substrate **101** may overlap with the first reflective surface **131** in the vertical direction. A one end or starting position of the first reflective surface **131** may be positioned further outward than the upper end or end position of the second reflective surface **111**, or may be positioned closer to the other end of the light guide member **110** than the top or end position of the second reflective surface **111**.

(50) An area of the exit surface **151** may be larger than an area of the first reflective surface **131**. The length of the exit surface **151** in the first direction X may be larger than the length of the first reflective surface **131** in the first direction X. The width Y1 of the exit surface **151** in the second direction Y may be the same as the width of the first reflective surface **131** in the second direction Y. The width Y1 of the second direction Y of the exit surface **151** may be the same as the width of the second direction Y of the second reflective surface **111**.

(51) The first reflective surface **131** may be provided in a multi-step structure. The first position of the first reflective surface **131** adjacent to the light source **102** is the lowest, and a height of the first reflective surface **131** may gradually increase as the position of the region is further from the light source **102**. That is, based on a straight line extending horizontally to the upper surface of the substrate **101**, the height T1, T2, T3, T4, T5 and T6 of the first reflective surface **131** may gradually increase as the region is further from the light source **102**.

(52) The multi-step structure of the first reflective surface **131** includes an inclined surface. The inclined surface may be horizontally opposed to the second reflective surface **111**. The inclined surface may reflect light reflected by the second reflective surface **111** in the direction of the exit surface. A straight line passing through the lower end of each reflective portion **C1-C6** of the second reflective surface **111** may be set at an angle of 70 degrees or less, for example, 30 degrees to 70 degrees or 40 degrees to 52 degrees, based on a straight line horizontal to the upper surface of the substrate **101**. As shown in FIG. 6, the first reflective surface **131** includes a plurality of reflective portions **C1, C2, C3, C4, C5** and **C6**, and the plurality of reflective portions **C1, C2, C3, C4, C5** and **C6** may include n (n is 3 or more) reflective portions. The above-described plurality of reflective portions **C1, C2, C3, C4, C5** and **C6** may be arranged in a step structure having a gradually increasing height from one end to the other end of the first reflective surface **131**. The above-described plurality of reflective portions **C1, C2, C3, C4, C5** and **C6** may include a first reflective portion **C1** adjacent to the light source **102**, a second reflective portion **C2** adjacent to or disposed outside the first reflective portion **C1**, an outermost reflective portion **C6**, and one or more intermediate reflective portions **C3, C4** and **C5** between the outermost reflective portion **C6** and the second reflective portion **C2**. The intermediate reflective portions **C3, C4** and **C5** may include, for example, third to fifth reflective portions **C3, C4** and **C5**, and the outermost reflective portion may be a sixth reflective portion **C6**. For example, the first reflective portion **C1** may have a first height **T1** based on the upper surface of the substrate **101**, and the second reflective portion **C2** may have a second height **T2** greater than the first height **T1**. In this form, the height may gradually increase from the first reflective portion **C1** to the sixth reflective portion **C6**. Each of the plurality of reflective portions **C1, C2, C3, C4, C5** and **C6** may be arranged at equal intervals in the first direction, and the last reflective portion **C6** may be disposed up to the last inclined surface or may include the other end. Here, the other end of the first reflective surface **131** may be connected to the pattern **P1** and may extend horizontally from the inclined surface. The other end of the first reflective surface **131** has an outer first end portion **29A** and an inner second end portion **29B**, and the first and second end portions **29A** and **29B** may be arranged in a zigzag shape. The second end portion **29B** is disposed further inward than the first end portion **29A**, and can be disposed between protrusions **152** having concave or open region **30**. Here, the region **30** between the protrusions **152** is open from the lower surface to the upper surface, and the region **30** between the first to fifth reflective portions **C1-C5** can be a concave region. Each of the plurality of reflective portions **C1, C2, C3, C4, C5** and **C6** includes a plurality of first surfaces **31, 32, 33, 34, 35** and **36** and a plurality of second surfaces **41, 42, 43, 44, 45** and **46**, and the plurality of first surfaces **31, 32, 33, 34, 35** and **36** are spaced apart from each other in the second direction **Y**, and the plurality of second surfaces **41, 42, 43, 44, 45** and **46** can be spaced apart from each other in the second direction **Y**. Each of the first surfaces **31, 32, 33, 34, 35** and **36** and the second surfaces **41, 42, 43, 44, 45** and **46** are arranged in a zigzag shape in the second direction **Y** and may have a constant interval. The plurality of first surfaces **31, 32, 33, 34, 35** and **36** are spaced apart by a width **E1** of the second surfaces **41, 42, 43, 44, 45** and **46**, and the plurality of second surfaces **41, 42, 43, 44, 45** and **46** are spaced apart by a width of the first surfaces **31, 32, 33, 34, 35** and **36**. The widths of the first surfaces **31, 32, 33, 34, 35** and **36** and the widths **E1** of the second surfaces **41, 42, 43, 44, 45** and **46** are lengths in the second direction and may be equal to each other. Each of the plurality of reflective portions **C1-C6** may have the first surface **31, 32, 33, 34, 35** and **36** and the second surface **41, 42, 43, 44, 45** and **46** alternately arranged or may have a matrix form, and may emit light in a dot matrix shape through a matrix-shaped pattern **P1** of the exit surface **151**.

(53) Based on a straight line extended on the upper surface of the substrate **101**, the lower height **T1, T2, T3, T4, T5** and **T6** of the first surface **31, 32, 33, 34, 35** and **36** in each of the reflective portions **C1-C6** may be the same as a lower height of the second surface **41, 42, 43, 44, 45** and **46**. The lower heights **T1, T2, T3, T4, T5** and **T6** of the first surfaces **31, 32, 33, 34, 35** and **36** in different reflective portions may be different from each other. The bottom heights of the second

surfaces **41, 42, 43, 44, 45** and **46** in different reflective portions may be different from each other. The height **T6** of the lower surface of the sixth reflective portion **C6**, which is the last reflective portion, may be disposed at a position equal to or greater than 80% of the maximum thickness **TO** of the light guide member **110** based on a straight line horizontal to the upper surface of the substrate **101**, for example, in a range of 80% to 90%. In the heights **T1-T6** of each reflective portion **C1-C6**, the height difference between two adjacent reflective portions may be equal to the first height **T1**. That is, the height differences between the adjacent reflective portions may be equal to each other. The height **T1** of the first reflective portion **C1** adjacent to the light source **102** may be the lowest, and the height of the last reflective portion **C6** may be the highest. That is, the height of the lower space of the first reflective portion **C1** may be the smallest, and the height **T6** of the lower surface of the sixth reflective portion **C6** may be the largest.

(54) In each of the reflective portions **C1-C6**, the first surface **31, 32, 33, 34, 35** and **36** may be spaced further away from the light source **102** or one end of the first reflective surface **131** than the second surface **41, 42, 43, 44, 45** and **46**. In each of the reflective portions **C1-C6**, the first surface **31, 32, 33, 34, 35** and **36** is disposed further outward along the first direction **X** with respect to one end of the first reflective surface **131** than the second surface **41, 42, 43, 44, 45** and **46**. The first surface **31, 32, 33, 34, 35** and **36** is positioned on the other side of the first direction **X** than the second surface **41, 42, 43, 44, 45** and **46** and may be disposed on one side, the other side, or both sides of the second direction **Y**. The second surface **41, 42, 43, 44, 45** and **46** is positioned on one side of the first direction **X** than the first surface **31, 32, 33, 34, 35** and **36** and may be disposed on one side, the other side, or both sides of the second direction **Y**.

(55) On the first side surface **S1** of the light guide member **131**, the first surface **31, 32, 33, 34, 35** and **36** may be exposed, or the second surface **41, 42, 43, 44, 45** and **46** may be exposed. The second side surface **S2** of the light guide member **131** may expose the second surface **41, 42, 43, 44, 45** and **46** or the first surface **31, 32, 33, 34, 35** and **36**. Different first surfaces **31, 32, 33, 34, 35** and **36** and second surfaces **41, 42, 43, 44, 45** and **46** may be exposed on the first side surface **S1** and the second side surface **S2** of the light guide member **131**. As another example, the same first surface **31, 32, 33, 34, 35** and **36** or second surface **41, 42, 43, 44, 45** and **46** may be exposed on the first side surface **S1** and the second side surface **S2** of the light guide member **131**. The shape of the reflective surface exposed on both sides of the light guide member **131** may vary depending on the pattern shape. Accordingly, the lighting device may provide various light distribution images depending on the pattern shape. The shape of the first and second surfaces **31-36** and **41-46** may be not only a square, but also a polygonal structure larger than a triangle, a long line shape in the first direction, a long line shape in the second direction, a circular shape, or an elliptical shape. The shape of the pattern **P1** may not only be a polygonal shape, but also a polygon such as a triangle or a pentagon, or a circular shape or an elliptical shape. In addition, the pattern **P1** may be a long line shape in the first direction or a long line shape in the second direction.

(56) As shown in FIG. 6, FIG. 10 and FIG. 18, in the matrix-shaped pattern **P1**, each pattern **P1** corresponding to the first surface **31-36** and the second surface **41-46** of the reflective portion **C1-C6** is defined as a light portion **B1**, and each pattern **P1** corresponding to the region between the first surface **31-36** and the second surface **41-46** may be a dark region **B2** having low luminosity or low light quantity. Accordingly, the patterns of the light portion **B1** and the dark portion **B2** in the exit surface **151** may be arranged alternately in the first and second directions. In FIG. 18, the region **A1** is a region corresponding to the middle reflective portion among the reflective portions **C1-C6**.

(57) Referring to FIGS. 4 to 6, the lower surface of the first reflective surface **131** may include a plurality of bottom surfaces **21, 22, 23, 24, 25** and **26**. The plurality of bottom surfaces **21, 22, 23, 24, 25** and **26** may be a bottom surface of each reflective portion **C1-C6**.

(58) The plurality of bottom surfaces **21, 22, 23, 24, 25** and **26** are connected to the lower end of the first surface **31-36** on one side, the other side, or both sides of the second direction **Y** of the

second surface **41-46** of each reflective portion **C1-C6**. Each of the bottom surfaces **21, 22, 23, 24, 25** and **26** has a bottom region **20** between the upper end of the first surface **31-36** and the lower end of the second surface **41-46**, and the bottom region **20** may be connected to the upper end of the first surface **31-36** and the lower end of the second surface **41-46**. In addition, a portion **20A** of the bottom region **20** may extend to the region between each of the bottom surfaces **21-26**.

(59) The plurality of bottom surfaces **21-26** are arranged as horizontal surfaces or non-reflective surfaces in the region between the first surface **31-36** and the second surface **41-46**, and the lower surfaces of two adjacent reflective portions may extend horizontally. The region of the bottom surface **21-26** may correspond to a dark pattern on the exit surface **151**. Here, the sum of the number of the first surfaces **31-36** and the number of the second surfaces **41-46** may be different from the number of the plurality of patterns **P1**, and may be smaller than the number of the patterns **P1**. The number of the patterns **P1** may be at least twice or between twice and three times the sum of the number of the first surfaces **31-36** and the number of the second surfaces **41-46**.

(60) As shown in FIG. 6 and FIG. 11, in the horizontal direction, the length **W1** of the first surface **31-36** and the length **W2** of the second surface **41-46** are the lengths on a straight line passing through both ends of the first surface **31-36** and the second surface **41-46**, and may be equal to each other.

(61) The width **E1** of the first surface **31-36** and the second surface **41-46** in the second direction may be equal to the length **W1** and **W2** of the first surface **31-36** and the second surface **41-46** in the horizontal direction. The length between the lower end and the upper end of each of the first surface **31-36** and the second surface **41-46** in the inclined direction may be greater than the width **E1** of each of the first surface **31-36** and the second surface **41-46**. Accordingly, the first surface **31-36** and the second surface **41-46** may vertically overlap each pattern **P1** of the exit surface **151** and reflect incident light toward each pattern **P1** of the exit surface **151**.

(62) As shown in FIG. 11, a light guiding distance of light that horizontally travels from the light source **102** through the second reflective surface **111** to the center portion of the first surface **32** of the second reflective portion **C2** may be greater than a light guiding distance of light that horizontally travels from the light source **102** through the second reflective surface **111** to the center portion of the first surface **31** of the first reflective portion **C1**. In addition, the light guiding distance of light that vertically travels from the center of the first surface **31** of the first reflective portion **C1** to the exit surface **151** may be greater than the light guiding distance of light that vertically travels from the center of the first surface **32** of the second reflective portion **C2** to the exit surface **151**. In this way, a thickness of the light guide member **110** may be provided thinner in regions farther from the light source **102** so as not to affect the light distribution due to the light guide distance passing through each reflective portion **C1-C6**.

(63) As shown in FIG. 11, the width **W3** between the lower end of the first surface **31-36** and the upper end of the second surface **41-46** may be equal to the horizontal length **W1** and **W2** of the first surface **31-36** and the second surface **41-46**. Accordingly, the exit surface **151** can emit light in a matrix shape having an area of a constant unit dot pattern.

(64) As shown in FIG. 6, a distance **E5** between the first surface **31-36** and the second surface **41-46** of the adjacent reflective portions **C1-C6** may be equal to the length **W1** of the first surface **31, 32, 33, 34, 35** and **36** and/or a length **W2** of the second surface **41, 42, 43, 44, 45** and **46**. As shown in FIG. 11, the interval (e.g., **W2**) between the first surface **31-36** and the second surface **41-46** within each reflective portion **C1-C6** may be equal to the length **W1** of the first surface **31-36** and/or the length **W2** of the second surface **41-46**. In addition, the heights **T11** of each reflective portion **C1-C6** may be equal to each other. Accordingly, light uniformly reflected by the first reflective surface **131** can be extracted through the pattern **P1** of the exit surface **151**.

(65) As shown in FIG. 5, the inclination angle **R12** of the first surface **31-36** is an internal angle and may have an inclination of 120 degrees or more with respect to a straight line horizontal to the upper surface of the substrate **101**. The inclination angle **R12** of the first surface **31, 32, 33, 34, 35**

and **36** may have, for example, a range of 120 degrees to 150 degrees or a range of 128 degrees to 140 degrees.

(66) The inclination angle of the second surface **41, 42, 43, 44, 45** and **46** is an internal angle and may have a range of 120 degrees to 150 degrees or a range of 128 degrees to 140 degrees with respect to a straight line horizontal to the upper surface of the substrate **101**. The inclination angle **R12** of the first surface **31, 32, 33, 34, 35** and **36** may be the same as the inclination angle of the second surface. Accordingly, the light reflected through the first surface **31-36** and the second surface **41-46** may have a uniform light distribution through each pattern **P1** of the exit surface **151**. Here, FIG. **17(a)** is a light distribution in a unit pattern of the exit surface **151** when the inclination angle **R12** of the first surface **31-36** and the second surface **41-46** is 135 degrees, and FIG. **17(b)** is a light distribution in a unit pattern of the exit surface **151** when the inclination angle of the first surface **31-36** and the second surface **41-46** is 133 degrees. The pattern **P1** at this time may be a polygonal plane. FIG. **17(c)** is a light distribution when the inclination angle of the first surface **31-36** and the second surface **41-46** is 133 degrees and the unit pattern **P1** of the exit surface **151** is a convex curved surface, and a three-dimensional pattern can be emitted. In this way, the embodiment of the invention can provide a uniform light distribution in each pattern **P1** by making the inclined first and second surfaces of the first reflective surface **131** and the convex patterns of the exit surface **151** correspond.

(67) FIG. **10** is a result of measuring the light distribution reflected by the second reflective surface **111**. As shown in FIG. **10**, the light source **102** includes an LED chip, and the LED chip has the highest luminosity of light emitted from the center of the upper surface. Accordingly, the distribution angle **R1** of the main light at the center of the upper surface of the light source **102** may have the highest light distribution (i.e., the distribution of the main light) within a range of 70 degrees or less, for example, 30 to 60 degrees. That is, the highest light distribution (i.e., the distribution of the main light) on the light source **102** may have a sum (i.e., **R1**) of the outer angle **R10** and the inner angle **R11** based on the optical axis of 70 degrees or less or within a range of 30 to 60 degrees. Here, the outer angle **R10** may be equal to or greater than the inner angle **R11**, and the difference between the inner angle **R11** and the outer angle **R10** may be 5 degrees or less. In this way, since the distribution of the light emitted from the light source **102** is different depending on the area, the distribution of the light reflected by the first reflective surface **131** may also be transmitted differently.

(68) Referring to FIGS. **4** and **10**, the distance **D1** between the lower end of the second reflective surface **111** and the light source **102** may be 5 mm or less, for example, in the range of 1 to 5 mm or 2 to 4 mm. When the minimum distance **D2** between the light source **102** and the second reflective surface **111** is smaller than the above range, the dark region in the lower center region **G1** disclosed in FIG. **20** may increase, and when it is larger than the above range, the overall brightness may decrease. FIG. **20** is a light distribution diagram on the other side of the light guide member, and it can be seen that the middle regions **G3** and **G4** among the outer regions of the lower center region **G1** appear higher than the other regions. In order to resolve this difference in brightness, the invention can process the surfaces of the first reflective surface **131** corresponding to the middle regions **G3** and **G4** into an inclined surface of an uneven pattern. That is, the center between the top and bottom of the second reflective surface **111** can face a region **A11** of the first and second surfaces having the uneven pattern.

(69) The invention can have an uneven pattern for reducing light reflection in a region where the main light is transmitted among the first reflective surface **131**. The uneven pattern can be provided as a rough surface through surface treatment in a chemical or molding process. As shown in FIG. **19**, it can be provided as an inclined surface **33A** of an inclined uneven pattern and an inclined plane **23A**, and the reflected light intensity or light quantity transmitted to each bright portion pattern can be lowered by the inclined surface **33A** of the inclined uneven pattern. The first surface **31-36** or the second surface **41-46** can include an inclined surface **33A** of an inclined uneven

pattern or an inclined plane **23A**. Accordingly, the corroded inclined surface **33A** may be located in the center region **A11** through which the main light is transmitted, and the center region **A11** of the first reflective surface **131** may be surfaces of the center region among the distributions of the first surfaces **31-36** and the second surfaces **41-46**. Accordingly, the difference in intensity or distribution between the light reflected in the peripheral region of the first reflective surface **131** and the light reflected in the center area **A11** may be reduced, so that the light distribution at the exit surface **151** may be uniform. The center region **A11** of the first reflective surface **131** may be a center region in the second direction and the third direction among the regions of the first reflective surface **131**.

(70) The lower surface **SO** of the light guide member **110** is the lowest surface and may have a region smaller than the region of the first reflective surface **131**. The lower surface **SO** of the light guide member **110** is provided as a horizontal plane and may be bonded to the substrate **101**. The maximum length **X1** of the light guide member **110** in the first direction may be smaller than the maximum length **Y1** of the first reflective surface **131** in the second direction **Y**, and may be less than 60% of the maximum length of the first reflective surface **131** in the second direction **Y**. Accordingly, the region of the first reflective surface **131** of the light guide member **110** may be increased, and the region of the lower surface **SO** facing the substrate **101** may be minimized. The width **Y1** of the second direction **Y** of the lower surface **SO** of the light guide member **110** may be the same as the width of the second direction **Y** of the first reflective surface **131**.

(71) As shown in FIGS. **3**, **4**, and **7**, the second reflective surface **111** is one side of the light guide member **110** and includes a flat reflective portion **112** and a curved reflective portion **113**. The flat reflective portion **112** is disposed on the outside of the light source **102** and may overlap with the light source **102** in a horizontal direction. The height **H1** of the flat reflective portion **112** is the height from the lower end to the upper end, and may be at least twice as high as the thickness of the light source **102**, and may be 30% or less of the maximum height **TO** of the light guide member **110**, for example, in the range of 15% to 30% or in the range of 15% to 25%.

(72) A straight line passing through the upper end of the flat reflective portion **112** and the center of the upper surface of the light source **102** has a third angle **R3** with respect to the center axis of the light source **102**, and the third angle **R3** may be at least 60 degrees, for example, in the range of 60 degrees to 80 degrees or in the range of 65 degrees to 80 degrees. When the upper position of the flat reflective portion **112** is provided within the above-mentioned range, light emitted through the outer surface of the light source **102** may be reflected by the flat reflective portion **112**. The flat reflective portion **112** may have higher reflection efficiency than a convex curved surface, and may be provided as a plane perpendicular to the outside of the light source **102**, thereby reducing the size of a dark portion caused by light emitted to the outside of the light source **102**. In addition, the region of the flat reflective portion **112** may reflect light having a beam angle distribution of the light source **102**, that is, light having a beam angle of 60 degrees or more or 65 degrees or more based on the optical axis.

(73) The curved reflective portion **113** may be disposed around the flat reflective portion **112**, and may be provided as a convex curved surface between the upper end of the flat reflective portion **112** and one end of the exit surface **151**, and between the edge of the flat reflective portion **112** and the two side surfaces **S1** and **S2** of the light guide member **110**. The curved reflective portion **113** has a more convex surface than a straight line passing through an edge of the flat reflective portion **112** and one end of the exit surface **151**, and may have a more convex surface than a straight line passing through an edge of the flat reflective portion **112** and the side surface **S1** and **S2** of the light guide member **110**. Accordingly, the reflection efficiency of the curved reflective portion **113** may be improved.

(74) The curved reflective portion **113** may include a second angle **R2** on the inner side and a third angle **R3** on the outer side with respect to the optical axis, and the sum of the second and third angles **R2** and **R3** may be 70 degrees or more, for example, in a range of 70 degrees to 110 degrees

or in a range of 80 degrees to 100 degrees. The curved reflective portion **113** can reflect light emitted from the light source **102** to the first reflective surface **131**.

(75) The curved reflective portion **113** can overlap with the first reflective surface **131** in the first direction X. The curved reflective portion **113** can overlap with the first surface **31-36** and the second surface **41-46** of each reflective portion **C1-C6** in the first direction X. The second reflective surface **111** may not overlap with the first reflective surface **131** in the vertical direction. A portion of the flat reflective portion **112** may overlap with the first reflective portion **C1** in the first direction X. That is, the height **H1** of the flat reflective portion **112** may be greater than the height (e.g., **T1**) of a step portion **21A** between the first reflective surface **131** and the lower surface **SO**, and may be lower than the lower height **T2** of the second reflective portion **C2**. Accordingly, the decrease in the amount of light incident on the first reflective portion **C1** may be minimized.

(76) The curved reflective portion **113** may be disposed further outside the exit surface **151**. The exit surface **151** may vertically overlap the lower surface **SO** of the light guide member **110** and the first reflective surface **131**.

(77) The distance **D2** from the light source **102** to the step portion **21A** is the distance between the light source **102** and one end of the first reflective portion **C1**, and may be 5 mm or more, for example, in the range of 5 to 20 mm or 10 to 20 mm. By providing the distance **D2** from the light source **102** to the first reflective portion **C1** within the above range, the problem of increased brightness of the light reflected by the first reflective portion **C1** can be reduced.

(78) The exit surface **151** is arranged in a matrix form with unit patterns having convex curves, and the light reflected by the first surfaces **31-36** and the second surfaces **41-46** of the reflective portions **C1-C6** is emitted in the form of a dot matrix. For example, as shown in FIG. **12**, a dark portion **B2** that is lower in brightness or is not emitted than a light portion **B1** where light is emitted is extracted in the form of a dot matrix. Here, the region that does not overlap with the first reflective surface **131**, that is, one side region of the exit surface **151** that vertically overlaps with the lower surface **SO** of the light guide member **110**, can be illuminated as a light region **B1** without the dark portion. This one side region of the exit surface **151** can be blocked by an external lamp structure.

(79) FIGS. **12** to **14** are other examples of the lighting device disclosed above, and will be described focusing on a configuration different from the lighting device disclosed above.

(80) Referring to FIGS. **12** to **14**, the light guide member **110** includes an exit surface **151**, a first reflective surface **131**, and a second reflective surface **111**. The description of the embodiment disclosed above can be applied to the first reflective surface **131**. The second reflective surface **111** of the light guide member **110** includes an upper curved reflective portion **113** and a lower reflective portion **112A**. The lower reflective portion **112A** may have a plurality of sub-reflective surfaces **11-16**, and the first sub-reflective surfaces **11**, **13** and **15** having a curved or inclined surface at the lower end adjacent to the light source **102** and vertical second sub-reflective surfaces **12**, **14** and **16** may be alternately arranged. The lower reflective portion **112A** of the second reflective surface **111** may have the sub-reflective surfaces **11-16** arranged in multiple stages to reduce light loss from the outside of the light source **102**. In addition, the lower reflective portion **112A** closest to the light source **102** may be provided as a third sub-reflective surface **11A** of a vertical plane.

(81) The first sub-reflective surface **11**, **13** and **15** having the curved or inclined surface and the second sub-reflective surface **12**, **14** and **16** have a concentric shape at the center portion of the outer lower end of the second reflective surface **111** and may have a semicircular shape. The upper height of the lower reflective portion **112A** may be less than 50% of the maximum thickness **TO** (see FIG. **3**) of the light guide member **110** based on the upper surface of the substrate **101**. The upper height of the lower reflective portion **112A** may be equal to or lower than the lower height of the third reflective portion **C3**. Here, among the first sub-reflective surfaces **11**, **13** and **15**, a portion of **1-2** and **1-3** sub-reflective surfaces **11**, **13** and **15** and **2-1**, **2-2** and **2-3** sub-reflective

surfaces **12**, **14** and **16** may overlap with the first to second reflective portions **C1** and **C2** in the horizontal direction. In this way, the lower reflective portion **112A** may reflect the light traveling laterally from the light source **102** to the first reflective surface **131** as much as possible, thereby reducing light loss and providing a uniform light distribution over the entire region. Accordingly, the lower reflective portion **112A** can reduce the amount of light loss at the lower portion of the second reflective surface **111** and prevent an increase in the size of the dark portion due to this.

(82) The pattern **P2** of the exit surface **151** is a prism pattern, and for example, unit patterns in the shape of polygonal cones may be arranged in a matrix form. The period or interval of the pattern **P2** of the exit surface **P2** may be equal to or smaller than the length of the first direction of the first surface **31-36** or the second surface **41-46**. Accordingly, the emitted light may be uniformly distributed through the center and the polygonal surface of the pattern **P2** by the triangular pyramid-shaped pattern.

(83) A lighting device such as FIG. **1** and FIG. **12** may be defined as one light emitting cell. In addition, a lighting device **200A** having a plurality of light emitting cells may be provided, as in FIG. **15**.

(84) Referring to FIG. **15**, the lighting device **200A** may include a light emitting portion **100B** having a substrate **101** and a plurality of light sources **102** arranged in a second direction on the substrate **101**, and a light guide member **110A** that guides, reflects, and emits light emitted from the light emitting portion **100B**. The light guide member **110A** may include the exit surface **151B** disclosed above and the first reflective surface (**131**, FIG. **6**) opposite the exit surface **151B**. The light guide member **110A** may include a plurality of second reflective surfaces **111B** that overlap the substrate **101** in a vertical direction on one side.

(85) The lighting device **200A** may be formed by a plurality of light emitting cells as one body. That is, the distance between the two side surfaces **S11** and **S12** of the light guide member **110A** may be obtained by multiplying (e.g., distance*number of cells) the distance between the two side surfaces in FIG. **1** or FIG. **12** by the number of cells (* indicates multiplication). The maximum length of the light guide member **110A** in the first direction may be equal to or less than twice the length **X1** of FIG. **1** or FIG. **12**.

(86) Here, each of the plurality of second reflective surfaces **111B** may be identical to the second reflective surface **111** of FIG. **1** or FIG. **12**. The first reflective surface **131** may be identical to the first reflective surface **131** of FIG. **1** or FIG. **12**. The exit surface may be arranged such that the exit surfaces **151** of FIG. **1** or FIG. **12** are arranged in a second direction. The unit width **Y1** of the second reflective surface **111** in the second direction **Y** may be the width of the second reflective surface **111** of FIG. **1** or FIG. **12**. A concave groove **R0** may be formed in a region between the unit sizes of the second reflective surfaces **111** to provide the curved reflective portion **113** disclosed above. As another example, although the light-emitting cells, which are lighting devices such as FIG. **1** or FIG. **12**, have been described as being integrally formed in the second direction, the light emitting cells may be arranged in a zigzag shape, and adjacent light emitting cells may be partially connected to have an angle of 10 to 90 degrees, so that the light emitting cells may be arranged in a triangle or square shape. As shown in FIG. **23**, the lighting device **200** and **200A** disclosed above may have the pattern **P1** disclosed above exposed or visible to the rear lamp of the vehicle, and may emit light in a dot matrix shape.

(87) As shown in FIG. **16**, a reflective member **115** may be disposed on the outside of the flat reflective portion **112** of the second reflective surface **111** of the light guide member **110**. The reflective portion member **115** may have a reflective material, such as a metal oxide, added to the resin material. The metal oxide may include at least one of TiO_2 , SiO_2 , and Al_2O_3 . The above reflective portion member **115** reflects the light leaked to the outside of the light source **102**, thereby reducing light loss, and also reducing dark portions caused by light leaked through the flat reflective portion **112**.

(88) FIG. **21** is a plan view of a vehicle to which a lighting device according to an embodiment is

applied, and FIG. 22 is a drawing showing an example of a tail light of the vehicle of FIG. 21.

(89) Referring to FIGS. 21 and 22, a front lamp **850** of a moving body or vehicle **900** may include one or more lighting modules, and the driving timing of these lighting modules may be individually controlled to provide not only the function of a conventional headlight, but also additional functions such as a welcome light or a celebration effect when a driver opens a vehicle door. The lamp may be applied to daytime running lights, high beams, low beams, fog lights, or turn signals.

(90) In the vehicle **900**, the tail lamp **800** may be arranged as a plurality of lamp units **810**, **812**, **814** and **816** supported by a housing. For example, the lamp units **810**, **812**, **814** and **816** may include a first lamp unit **810** arranged on the outside, a second lamp unit **814** arranged on the inner periphery of the first lamp unit **810**, and third and fourth lamp units **814** and **816** arranged on the inside of the second lamp unit **814**, respectively. The first to fourth lamp units **810**, **812**, **814** and **816** may selectively apply the lighting device disclosed in the embodiment, and a red lens cover or a white lens cover may be arranged on the outside of the lighting device for the lighting characteristics of the lamp units **810**, **812**, **814** and **816**. The lighting device disclosed in the embodiment applied to the above lamp units **810**, **812**, **814** and **816** can emit surface light with a uniform distribution.

(91) The first and second lamp units **810** and **812** may be provided with at least one of a curved shape, a straight shape, an angular shape, an inclined shape, or a flat shape, or a mixed structure thereof. The first and second lamp units **810** and **812** may be arranged one or more in each tail lamp. The first lamp unit **810** may be provided as a tail lamp, the second lamp unit **812** may be provided as a brake lamp, the third lamp unit **814** may be provided as a reverse lamp, and the fourth lamp unit **816** may be provided as a turn signal lamp. Such lighting lamps can provide higher brightness in the rearward direction than in the lateral direction, thereby complying with lighting regulations for stop lamps or tail lamps, etc. As shown in FIG. 23, the lighting device can emit light in a dot matrix form in the tail lamp.

(92) Features, structures, effects, etc. described in the embodiments are included in at least one embodiment of the invention, and are not necessarily limited to only one embodiment. Furthermore, features, structures, effects, etc. illustrated in each embodiment can be combined or modified for other embodiments by those of ordinary skill in the art to which the embodiments belong. Accordingly, the contents related to such combinations and modifications should be interpreted as being included in the scope of the invention.

(93) In addition, although the embodiments have been mainly described above, this is only an example and does not limit the present invention, and one of ordinary skill in the field to which the present invention belongs will appreciate that various modifications and applications not illustrated above may be possible without departing from the essential characteristics of the present embodiment. For example, each component specifically shown in the embodiment can be implemented by modification. And differences related to such modifications and applications should be construed as being included in the scope of the invention defined in the appended claims.

Claims

1. A lighting device comprising: a substrate; a light source disposed on the substrate; and a light guide member disposed on the substrate and the light source, wherein the light guide member comprises an exit surface, a first reflective surface facing the exit surface and a second reflective surface disposed on one side, wherein the first reflective surface comprises a plurality of reflective portions having different heights with respect to an upper surface of the substrate, wherein each of the plurality of reflective portions comprises a bottom surface, a plurality of first surfaces inclined with respect to the upper surface of the substrate, and a plurality of inclined second surfaces disposed between the plurality of first surfaces, wherein the first reflective surface and the second reflective surface overlap in a first direction, wherein the second reflective surface and the substrate

overlap in a vertical direction, wherein the plurality of first surfaces disposed in each of the plurality of reflective portions is spaced apart from each other in a second direction orthogonal to the first direction, wherein the plurality of second surfaces disposed on each of the plurality of reflective portions is spaced apart in the second direction, wherein the second reflective surface includes a flat reflective portion and a curved reflective portion, wherein the flat reflective portion has a plane perpendicular to an outside of the light source, has a height more than twice a thickness of the light source, and, wherein the curved reflective portion is disposed between an edge of the flat reflective portion and one end of the exit surface.

2. The lighting device of claim 1, wherein the plurality of reflective portions comprises a first reflective portion having a first height with respect to the upper surface of the substrate and a second reflective portion having a second height greater than the first height, wherein the first reflective portion is disposed closer to the light source than the second reflective portion, wherein a distance between the light source and one end of the first reflective portion is in a range of 5 to 20 mm.

3. The lighting device of claim 1, wherein the first surfaces are inclined at a first angle of 120 degrees or more with respect to a straight line horizontal to the upper surface of the substrate.

4. The lighting device of claim 1, wherein the plurality of second surfaces is disposed closer to the light source than the first surface.

5. The lighting device of claim 4, wherein the second surfaces have an inclination angle equal to an inclination angle of the first surface with respect to a straight line horizontal to the upper surface of the substrate.

6. The lighting device of claim 4, wherein the plurality of reflective portions has a higher height that increases as the reflective portion is further from the light source.

7. The lighting device of claim 4, wherein a light guide distance of light horizontally incident from the light source to the second reflective portion through another reflective surface is greater than a light guide distance of light horizontally incident from the light source to the first reflective portion through another reflective surface, and wherein a light guide distance of light vertically traveling from the first reflective portion to the exit surface is greater than a light guide distance of light vertically traveling from the second reflective portion to the exit surface.

8. A lighting device comprising: a substrate; a light source disposed on the substrate; and a light guide member disposed on the substrate and the light source, wherein the light guide member including an exit surface, a first reflective surface facing the exit surface and a second reflective surface disposed on one side, wherein the exit surface including a plurality of patterns, wherein the first reflective surface including a plurality of first surfaces and a plurality of second surfaces having different heights with respect to an upper surface of the substrate, wherein each of the plurality of first surfaces is inclined with respect to the upper surface of the substrate, wherein the plurality of second surface is disposed to be inclined between the plurality of first surfaces, wherein the first reflective surface and the second reflective surface overlap in a first direction, wherein the second reflective surface and the substrate overlap in a vertical direction, wherein the plurality of first surfaces is spaced apart from each other in a second direction orthogonal to the first direction, wherein the plurality of second surfaces is spaced apart in the second direction, wherein the second reflective surface includes a flat reflective portion and a curved reflective portion, wherein the flat reflective portion has a plane perpendicular to an outside of the light source, has a height more than twice a thickness of the light source, wherein the curved reflective portion is disposed between an edge of the flat reflective portion and one end of the exit surface, and wherein a number of the plurality of patterns is different from a sum of a number of the plurality of first surfaces and a number of the plurality of second surfaces.

9. The lighting device of claim 8, wherein the number of the plurality of patterns is greater than the sum of the number of the plurality of first surfaces and the number of the plurality of second surfaces.

10. The lighting device of claim 8, wherein the plurality of patterns is connected to each other in first and second directions that are orthogonal to each other.
 11. The lighting device of claim 8, wherein each of the plurality of first surfaces is inclined, and a thickness of the light guide member gradually becomes thinner as the first surface becomes farther from the light source.
 12. The lighting device of claim 11, wherein the patterns of the exit surface corresponding to the first reflective surface includes a pattern that overlaps in a vertical direction with the first surfaces and the second surfaces and a pattern that overlaps in a vertical direction with a bottom of the first reflective surface.
 13. The lighting device of claim 12, a bottom of the first reflective surface has a bottom region connected to upper ends of the first surfaces and lower ends of the second surfaces, wherein a portion of the bottom region extends to a region between the plurality of first surfaces.
 14. The lighting device of claim 8, wherein the number of the plurality of patterns is in a range of 2 to 3 times the sum of the number of the plurality of first surfaces and the number of the plurality of second surfaces.
 15. The lighting device of claim 8, wherein a height of the flat reflective portion is from a lower end to an upper end, and is 30% or less of a maximum height of the light guide member.
 16. The lighting device of claim 8, wherein a straight line passing through an upper end of the flat reflective portion and a center of the upper surface of the light source has an angle in a range of 60 to 80 degrees with respect to a center axis of the light source.
 17. The lighting device of claim 8, wherein the curved reflective portion has a convex curved surface between both side surfaces of the light guide member at an edge of the flat reflective portion, and wherein the curved reflective portion has a convex curved surface than a straight line passing through the edge of the flat reflective portion and one end of the exit surface.
 18. The lighting device of claim 1, wherein a height of the flat reflective portion is from a lower end to an upper end, and is 30% or less of a maximum height of the light guide member.
 19. The lighting device of claim 1, wherein a straight line passing through an upper end of the flat reflective portion and a center of the upper surface of the light source has an angle in a range of 60 to 80 degrees with respect to a center axis of the light source.
 20. The lighting device of claim 8, wherein the curved reflective portion has a convex curved surface between both side surfaces of the light guide member at an edge of the flat reflective portion, and wherein the curved reflective portion has a convex curved surface than a straight line passing through the edge of the flat reflective portion and one end of the exit surface.
-