

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12399070
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Zhang; Xiaoli

Floating thermometer

Abstract

A floating thermometer includes a light-transmitting suspension chamber, a control main board, a temperature measurement device, a display device and a lighting device; the temperature measurement device. The control main board is used for controlling the lighting device to emit alternately flickering seven-color light. The suspension chamber includes a mounting cover body and a mounting seat. The control main board, the temperature measurement device, the display device and the lighting device are all arranged in the suspension chamber. The mounting cover body is hermetically covered at the first mounting opening, so that the suspension chamber can be suspended on liquid; the temperature measurement device is arranged on a lower side of the mounting seat; a lower side of the mounting seat and the temperature measurement device are put into the liquid; and the display device is used for displaying temperature value of the liquid.

Inventors: Zhang; Xiaoli (Shenzhen, CN)

Applicant: SHENZHEN HAIKE INNOVATION ELECTRONICS CO., LTD. (Shenzhen, CN)

Family ID: 1000008781154

Assignee: SHENZHEN HAIKE INNOVATION ELECTRONICS CO., LTD. (Shenzhen, CN)

Appl. No.: 17/861835

Filed: July 11, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230184598 A1	Jun. 15, 2023

Foreign Application Priority Data

CN	202111500538.5	Dec. 09, 2021
----	----------------	---------------

Publication Classification

Int. Cl.: **G01K13/02** (20210101); **G01K1/02** (20210101); **G01K1/08** (20210101); **G01K1/14** (20210101)

U.S. Cl.:

CPC **G01K13/026** (20210101); **G01K1/028** (20130101); **G01K1/08** (20130101); **G01K1/14** (20130101);

Field of Classification Search

CPC: G01K (13/026); G01K (1/028); G01K (1/08); G01K (1/14)

USPC: 374/155; 374/208

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5169236	12/1991	Iest	374/E1.008	G01K 13/00
2022/0136907	12/2021	Pike	374/100	G01K 1/08

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
210495209	12/2019	CN	N/A
2004281186	12/2003	JP	N/A
WO-2017166339	12/2016	WO	N/A

Primary Examiner: Jagan; Mirellys

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) The application claims priority benefit of Chinese patent application No. 202111500538.5, filed on Dec. 9, 2021, in China National Intellectual Property Administration, and the entire contents of which are incorporated herein by reference.

TECHNICAL FIELD

(2) The present disclosure relates to the field of thermometers, in particular to a floating thermometer.

BACKGROUND

(3) With the development of the society, people have higher requirements for living standards, and more people pursue higher quality of life. For example, people are looking for better thermometers that measure temperatures of liquids. A thermometer is a tool that can accurately determine and measure a temperature. Thermometers are divided into pointer thermometers and digital thermometers. Various thermometers have been developed according to different uses.

Thermometers for measuring water temperatures are widely used in swimming pools, rivers, wells, fish ponds, oceans, etc. The measurement range is generally between minus 40° C. to 125° C. At

present, the existing thermometers on the market, an animal float floats on water, and a thermometer connected to the animal float sinks in the water. It is difficult to read a thermometer when the thermometer is used at night.

SUMMARY

(4) The present disclosure provides a floating thermometer. A user can still read a reading on the thermometer easily, accurately and quickly when the thermometer is used at night; and furthermore, the thermometer can emit brilliant light and also achieve a water surface decorating effect.

(5) A floating thermometer includes a light-transmitting suspension chamber, a control main board, a temperature measurement device, a display device and a lighting device, wherein the temperature measurement device, the display device and the lighting device are all electrically connected to the control main board; the control main board is used for controlling the lighting device to emit alternately flickering seven-color light including red light, orange light, yellow light, green light, cyan light, blue light and purple light; the suspension chamber includes a mounting cover body and a mounting seat; an upper side of the mounting seat has a first mounting opening; the control main board, the temperature measurement device, the display device and the lighting device are all arranged in the suspension chamber through the first mounting opening; the mounting cover body is hermetically covered at the first mounting opening, so that the suspension chamber can be suspended on liquid; the temperature measurement device is arranged on a lower side of the mounting seat; a lower side of the mounting seat and the temperature measurement device are put into the liquid, so that the temperature measurement device can measure a temperature value of the liquid; and the display device is used for displaying the temperature value of the liquid.

(6) In one embodiment, the floating thermometer further includes a power storage module and a solar panel, wherein the power storage module and the solar panel are both electrically connected to the control main board; and the power storage module and the solar panel are both arranged in the suspension chamber through the first mounting opening.

(7) In one embodiment, the lighting device is arranged on a lower side of the control main board; and a light-emitting surface of the lighting device is disposed towards the lower side of the mounting seat.

(8) In one embodiment, an upper side of the control main board is also provided with a liquid crystal display (LCD) screen backlight; and a light-emitting surface of the LCD screen backlight is disposed towards the display device.

(9) In one embodiment, the floating thermometer further includes a counterweight assembly, wherein a cross section of the mounting seat is in a stair shape with a narrow upper part and a wide lower part, so as to form the first mounting opening in the upper side and an accommodating slot in the lower side; and the counterweight assembly and the temperature measurement device are both arranged in the accommodating slot.

(10) In one embodiment, the counterweight assembly has an interpenetrating port; and a probe of the temperature measurement device interpenetrates into the interpenetrating port.

(11) In one embodiment, the control main board is connected to the mounting cover body through a first connector.

(12) In one embodiment, the display device comprises a display screen and a display screen support; the control main board is also provided with a first insertion port and a second insertion port; the display screen support is inserted into the first insertion port; the display screen is connected to the display screen support; and the display screen has a pin which is inserted into the second port to electrically connect the display screen to the control main board.

(13) In one embodiment, a first stop edge is arranged on the display device; one end of the solar panel is connected with the mounting cover body through a second connector; and the first stop edge presses the other end of the solar panel to the mounting cover body.

(14) In one embodiment, a second stop edge and a third stop edge are arranged on the mounting

cover body; the second connector presses one end of the solar panel to the second stop edge; and the first stop edge presses the other end of the solar panel to the third stop edge.

(15) By the above-mentioned structure, since the floating thermometer includes a light-transmitting suspension chamber, a control main board, a temperature measurement device, a display device and a lighting device, the temperature measurement device, the display device and the lighting device are all electrically connected to the control main board. The control main board is used for controlling the lighting device to emit alternately flickering seven-color light including red light, orange light, yellow light, green light, cyan light, blue light and purple light; the suspension chamber includes a mounting cover body and a mounting seat; an upper side of the mounting seat has a first mounting opening; the control main board, the temperature measurement device, the display device and the lighting device are all arranged in the suspension chamber through the first mounting opening; the mounting cover body is hermetically covered at the first mounting opening, so that the suspension chamber can be suspended on liquid; the temperature measurement device is arranged on a lower side of the mounting seat; a lower side of the mounting seat and the temperature measurement device are put into the liquid, so that the temperature measurement device can measure a temperature value of the liquid; and the display device is used for displaying the temperature value of the liquid. Therefore, a user can measure the temperature value of the liquid with the temperature measurement device. Furthermore, the alternately flickering seven-color light including red light, orange light, yellow light, green light, cyan light, blue light and purple light and emitted by the lighting device can be mapped to a water surface to achieve a water surface decorating effect. In addition, the display device can display the temperature value of the liquid tested by the temperature measurement device, so that the user can read the temperature value of the liquid at the current measured position from the display device easily, accurately and quickly. Further, the user can also quickly find the position of the thermometer by means of the light mapped on the water, so that the user associates the read temperature value to a measured position on a one-to-one correspondence basis to achieve accurate, real-time and on-site measurement. Much further, the mounting cover body is hermetically covered at the first mounting opening to suspend the suspension chamber on the liquid, thus preventing the liquid from entering the suspension chamber, avoiding the liquid from corroding the control main board, the temperature measurement device, the display device and the lighting device which are arranged in the suspension chamber, and greatly improving the service life and the safety of the floating thermometer.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a schematic diagram of a structure of the present disclosure;
- (2) FIG. 2 is an exploded diagram of the structure shown in FIG. 1 of the present disclosure;
- (3) FIG. 3 is another exploded diagram of the structure shown in FIG. 1 of the present disclosure;
- (4) FIG. 4 is a sectional view of sectioning along a temperature measurement device;
- (5) FIG. 5 is an enlarged diagram of portions labeled A of FIG. 4;
- (6) FIG. 6 is an enlarged diagram of portions labeled B of FIG. 4;
- (7) FIG. 7 is a sectional view of sectioning along a first connector;
- (8) FIG. 8 is an enlarged diagram of portions labeled C of FIG. 7;
- (9) FIG. 9 is an enlarged diagram of portions labeled D of FIG. 7;
- (10) FIG. 10 is a sectional view of sectioning along a second connector;
- (11) FIG. 11 is an enlarged diagram of portions labeled E of FIG. 10;
- (12) FIG. 12 is an enlarged diagram of portions labeled F of FIG. 10;
- (13) FIG. 13 is a sectional view of sectioning along a display device;

(14) FIG. 14 is an enlarged diagram of portions labeled G of FIG. 13;

(15) FIG. 15 is an enlarged diagram of portions labeled H of FIG. 13.

DETAILED DESCRIPTION OF THE EMBODIMENTS

(16) Referring to FIG. 1 to FIG. 15, a floating thermometer includes a light-transmitting suspension chamber 1, a control main board 2, a temperature measurement device 3, a display device 4 and a lighting device 5; the temperature measurement device 3, the display device 4 and the lighting device 5 are all electrically connected to the control main board 2; the control main board 2 is used for controlling the lighting device 5 to emit alternately flickering seven-color light including red light, orange light, yellow light, green light, cyan light, blue light and purple light; the suspension chamber 1 includes a mounting cover body 11 and a mounting seat 12; an upper side of the mounting seat 12 has a first mounting opening 121; the control main board 2, the temperature measurement device 3, the display device 4 and the lighting device 5 are all arranged in the suspension chamber 1 through the first mounting opening 121; the mounting cover body 11 is hermetically covered at the first mounting opening 121, so that the suspension chamber 1 can be suspended on liquid; the temperature measurement device 3 is arranged on a lower side of the mounting seat 12; a lower side of the mounting seat 12 and the temperature measurement device 3 are put into the liquid, so that the temperature measurement device 3 can measure a temperature value of the liquid; and the display device 4 is used for displaying the temperature value of the liquid.

(17) By the above-mentioned structure, since the floating thermometer includes a light-transmitting suspension chamber, a control main board, a temperature measurement device, a display device and a lighting device, the temperature measurement device, the display device and the lighting device are all electrically connected to the control main board. The control main board is used for controlling the lighting device to emit alternately flickering seven-color light including red light, orange light, yellow light, green light, cyan light, blue light and purple light; the suspension chamber includes a mounting cover body and a mounting seat; an upper side of the mounting seat has a first mounting opening; the control main board, the temperature measurement device, the display device and the lighting device are all arranged in the suspension chamber through the first mounting opening; the mounting cover body is hermetically covered at the first mounting opening, so that the suspension chamber can be suspended on liquid; the temperature measurement device is arranged on a lower side of the mounting seat; a lower side of the mounting seat and the temperature measurement device are put into the liquid, so that the temperature measurement device can measure a temperature value of the liquid; and the display device is used for displaying the temperature value of the liquid. Therefore, a user can measure the temperature value of the liquid with the temperature measurement device. Furthermore, the alternately flickering seven-color light including red light, orange light, yellow light, green light, cyan light, blue light and purple light and emitted by the lighting device can be mapped to a water surface to achieve a water surface decorating effect. In addition, the display device can display the temperature value of the liquid tested by the temperature measurement device, so that the user can read the temperature value of the liquid at the current measured position from the display device easily, accurately and quickly. Further, the user can also quickly find the position of the thermometer by means of the light mapped on the water, so that the user associates the read temperature value to a measured position on a one-to-one correspondence basis to achieve accurate, real-time and on-site measurement. Much further, the mounting cover body is hermetically covered at the first mounting opening to suspend the suspension chamber on the liquid, thus preventing the liquid from entering the suspension chamber, avoiding the liquid from corroding the control main board, the temperature measurement device, the display device and the lighting device which are arranged in the suspension chamber, and greatly improving the service life and the safety of the floating thermometer.

(18) The temperature measurement device is electrically connected to the control main board

through an electric lead **32**.

(19) In this embodiment, the floating thermometer also includes a power storage module **6** and a solar panel **7**. The power storage module **6** and the solar panel **7** are both electrically connected to the control main board **2**; and the power storage module **6** and the solar panel **7** are both arranged in the suspension chamber **1** through the first mounting opening **121**. By the above-mentioned structure, solar energy can be provided through the solar panel. The solar panel converts collected light energy into electric energy and stores the electric energy in a storage battery, so as to supply power to the control main board, the temperature measurement device, the display device and the lighting device, so that this structure is environmentally friendly, and operations of a user for charging the floating thermometer and replacing a battery of the floating thermometer are eliminated; the convenience of temperature measurement is greatly improved; and the service life of the floating thermometer is prolonged.

(20) The lighting device **5** is arranged on a lower side of the control main board **2**; and a light-emitting surface **51** of the lighting device **5** is disposed towards the lower side of the mounting seat **12**. Specifically, the lighting device may be a light-emitting diode (LED) lamp, or may be other lighting devices with a lighting function. By the above-mentioned structure, since the light-emitting surface of the lighting device is disposed towards the lower side of the mounting seat, when the lower side of the mounting seat is put into the liquid, the alternately flickering seven-color light including red light, orange light, yellow light, green light, cyan light, blue light and purple light and emitted by the lighting device can be combined with the liquid to show a surprising and wonderful visual effect. Therefore, the floating thermometer also achieves a water surface decorating effect besides the temperature measurement function, which greatly improves the ornamental value of the floating thermometer. Furthermore, with the continuously flickering light, the user can conveniently quickly find out the position of the thermometer, and conveniently associate the read temperature value to the measured position to achieve accurate, real-time and on-site measurement.

(21) In this embodiment, an upper side of the control main board **2** is also provided with an LCD screen backlight **8**; and a light-emitting surface **81** of the LCD screen backlight **8** is disposed towards the display device **4**. By the above-mentioned structure, light emitted by the LCD screen backlight turns on pixels on the display device, so that the temperature value of the liquid can also be clearly displayed under an environment with strong environmental light, and a user can observe a change in the temperature value of the liquid accurately and in real time.

(22) In this embodiment, the floating thermometer also includes a counterweight assembly **13**. A cross section of the mounting seat **12** is in a stair shape with a narrow upper part and a wide lower part, so as to form the first mounting opening **121** in the upper side and an accommodating slot **122** in the lower side; and the counterweight assembly **13** and the temperature measurement device **3** are both arranged in the accommodating slot **122**. The counterweight assembly **13** has an interpenetrating port **131**; and a probe **31** of the temperature measurement device **3** interpenetrates into the interpenetrating port **131**. By the above-mentioned structure, the design is reasonable; the structure is simple; the connection is stable; mounting of the counterweight assembly and the temperature measurement device is effectively realized, and the mounting space of the accommodating slot is reasonably used; and in addition, due to the counterweight assembly arranged in the accommodating slot in the lower side of the mounting seat, it is convenient to put the lower side of the mounting seat into the liquid, so that the temperature measurement device can accurately measure the temperature of the liquid through the probe.

(23) In this embodiment, the control main board **2** is connected to the mounting cover body **11** through a first connector **14**. The display device **4** includes a display screen **41** and a display screen support **42**; the control main board **2** is also provided with a first insertion port **21** and a second insertion port **22**; the display screen support **42** is inserted into the first insertion port **21**; the display screen **41** is connected to the display screen support **42**; and the display screen **41** has a pin **411** which is inserted into the second port **22** to electrically connect the display screen **41** to the

control main board **2**. Specifically, a first stop edge **43** is arranged on the display device **4**; one end of the solar panel **7** is connected with the mounting cover body **11** through a second connector **15**; and the first stop edge **43** presses the other end of the solar panel **7** to the mounting cover body **11**. Further, a second stop edge **111** and a third stop edge **112** are arranged on the mounting cover body **11**; the second connector **15** presses one end of the solar panel **7** to the second stop edge **111**; and the first stop edge **43** presses the other end of the solar panel **7** to the third stop edge **112**. Much further, a first insertion block **421** is arranged on the display support **42**. The first insertion block **421** is inserted into the first insertion port **21**. By the above-mentioned structure, the design is reasonable; the structure is simple; the connection is stable; mounting among the control main board, the display device and the solar panel is effectively achieved; furthermore, the compact structure can prevent looseness of the control main board, the display device and the solar panel, which further prolongs the service life of the floating thermometer. The first connector and the second connector are screws, or may be bolts, or other connectors with a connection function. Specifically, ethyl vinyl acetate (EVA) foam **422** is arranged between the display screen and the display screen support. Due to its softness, good elasticity and good damping performance, the EVA can effectively prevent offset between the display screen and the display screen support and can also effectively prevent the display screen support from crushing the display screen, which further prolongs the service life of the floating thermometer.

(24) In this embodiment, the mounting seat **12** also includes a sealing ring **123**. When the mounting cover body **11** is hermetically covered at the first mounting opening **121**, an inner side wall of the first mounting opening **121** and an outer side wall of the mounting cover body **11** squeeze the sealing ring **123**, so that the sealing ring **123** squeezes and seals the mounting cover body **11** into the first mounting opening **121**. By the above-mentioned structure, a structure is effectively achieved, where the mounting cover body is hermetically covered at the first mounting opening, so that the sealed suspension chamber is formed, which prevents the liquid from entering the suspension chamber to cause damage and short circuit of electronic elements such as the control main board in the suspension chamber.

(25) The floating thermometer also includes a silica gel press **114**; a button **23** is also arranged on the control main board **2**; a second mounting opening **113** is arranged on the mounting cover body **11**; the silica gel press **114** and the second mounting opening **113** are both located above the button **23**, and the silica gel press **114** is hermetically covered at the second mounting opening **113**. By the above-mentioned structure, the liquid can be effectively prevented from entering the suspension chamber via the second mounting opening, and a user can press the button through the silica gel press, so that a function of controlling and adjusting the floating thermometer by pressing the button is effectively realized. For example, the lighting device can be controlled to be turned on or turned off by pressing the button. For another example, the display device can be controlled to be turned on or turned off by pressing the button.

(26) In this embodiment, a hanging port **115** is also arranged on the mounting cover **11**. The hanging port **115** is used for hanging the floating thermometer. By means of the above structure, a user can fixedly hang the floating thermometer in a water pool and other scenarios through the hanging port **115** for facilitating the operation, and the user experience is enhanced.

(27) In this embodiment, the mounting cover body **11** is hermetically covered at the mounting seat through a third connector **116**.

(28) In this embodiment, the mounting cover body **11** includes a first cover body **117** and a second cover body **118**. The first cover body **117** is covered at the second cover body **118** through a fourth connector **119**. The third connector and the fourth connector are screws, or may be bolts, or other connectors with a connection function.

Claims

1. A floating thermometer, comprising a light-transmitting suspension chamber, a control main board, a temperature measurement device, a display device, and a lighting device, wherein each of the temperature measurement device, the display device, and the lighting device is electrically connected to the control main board; the control main board controls the lighting device to emit alternately flickering seven-color lights including red light, orange light, yellow light, green light, cyan light, blue light, and purple light; the suspension chamber includes a mounting cover body and a mounting seat; an upper side of the mounting seat has a first mounting opening; each of the control main board, the temperature measurement device, the display device, and the lighting device is arranged in the suspension chamber through the first mounting opening; the mounting cover body is hermetically covered at the first mounting opening so that the suspension chamber is suspended on liquid; the temperature measurement device is arranged on a lower side of the mounting seat; a lower side of the mounting seat and the temperature measurement device are immersed into the liquid so that the temperature measurement device can measure a temperature value of the liquid; the display device displays the temperature value of the liquid; the lighting device is arranged on a lower side of the control main board; and a light-emitting surface of the lighting device is disposed towards the lower side of the mounting seat.
2. The floating thermometer according to claim 1, further comprising a power storage module and a solar panel, wherein the power storage module and the solar panel are both electrically connected to the control main board; and the power storage module and the solar panel are both arranged in the suspension chamber through the first mounting opening.
3. The floating thermometer according to claim 1, wherein an upper side of the control main board is provided with a liquid crystal display (LCD) screen backlight; and a light-emitting surface of the LCD screen backlight is disposed towards the display device.
4. The floating thermometer according to claim 1, wherein a counterweight assembly has an interpenetrating port; and a probe of the temperature measurement device interpenetrates into the interpenetrating port.
5. The floating thermometer according to claim 1, wherein the control main board is connected to the mounting cover body through a first connector.
6. The floating thermometer according to claim 1, wherein a first stop edge is arranged on the display device; one end of a solar panel is connected with the mounting cover body through a connector; and the first stop edge presses the other end of the solar panel to the mounting cover body.
7. The floating thermometer according to claim 6, wherein a second stop edge and a third stop edge are arranged on the mounting cover body; the connector presses one end of a solar panel to the third stop edge; and the first stop edge presses the other end of the solar panel to the second stop edge.
8. A floating thermometer, comprising a light-transmitting suspension chamber, a control main board, a temperature measurement device, a display device, a counterweight assembly, and a lighting device, wherein each of the temperature measurement device, the display device, and the lighting device is electrically connected to the control main board; the control main board controls the lighting device to emit alternately flickering seven-color lights including red light, orange light, yellow light, green light, cyan light, blue light, and purple light; the suspension chamber includes a mounting cover body and a mounting seat; an upper side of the mounting seat has a first mounting opening; each of the control main board, the temperature measurement device, the display device, and the lighting device is arranged in the suspension chamber through the first mounting opening; the mounting cover body is hermetically covered at the first mounting opening so that the suspension chamber is suspended on liquid; the temperature measurement device is arranged on a lower side of the mounting seat; a lower side of the mounting seat and the temperature measurement device are immersed into the liquid so that the temperature measurement device can

measure a temperature value of the liquid; the display device displays the temperature value of the liquid; a cross section of the mounting seat is in a stair shape with a narrow upper part and a wide lower part, so as to form the first mounting opening in the upper side and an accommodating slot in the lower side; and the counterweight assembly and the temperature measurement device are both arranged in the accommodating slot.

9. A floating thermometer, comprising a light-transmitting suspension chamber, a control main board, a temperature measurement device, a display device, and a lighting device, wherein each of the temperature measurement device, the display device, and the lighting device is electrically connected to the control main board; the control main board controls the lighting device to emit alternately flickering seven-color lights including red light, orange light, yellow light, green light, cyan light, blue light, and purple light; the suspension chamber includes a mounting cover body and a mounting seat; an upper side of the mounting seat has a first mounting opening; each of the control main board, the temperature measurement device, the display device, and the lighting device is arranged in the suspension chamber through the first mounting opening; the mounting cover body is hermetically covered at the first mounting opening so that the suspension chamber is suspended on liquid; the temperature measurement device is arranged on a lower side of the mounting seat; a lower side of the mounting seat and the temperature measurement device are immersed into the liquid, so that the temperature measurement device can measure a temperature value of the liquid; the display device displays the temperature value of the liquid; the display device comprises a display screen and a display screen support; the control main board is further provided with a first insertion port and a second insertion port; the display screen support is inserted into the first insertion port; the display screen is connected to the display screen support; and the display screen has a pin which is inserted into the second insertion port to electrically connect the display screen to the control main board.
