

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402247
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Na; Se Woong et al.

Circuit board

Abstract

A circuit board according to an embodiment includes: an insulating layer including first to third regions; an outer layer circuit pattern disposed on an upper surface of the first to third regions of the insulating layer; and a solder resist including a first part disposed on the first region of the insulating layer, a second part disposed on the second region, and a third part disposed on the third region, wherein the outer layer circuit pattern includes: a first trace disposed on an upper surface of the first region of the insulating layer; and a second trace disposed on an upper surface of the third region of the insulating layer; wherein a height of the first trace is different from a height of the second trace; and an upper surface of the first part of the solder resist is positioned lower than an upper surface of the first trace.

Inventors:	Na; Se Woong (Seoul, KR), Han; Jung Eun (Seoul, KR), Kim; Moo Seong (Seoul, KR)
Applicant:	LG INNOTEK CO., LTD. (Seoul, KR)
Family ID:	1000008781177
Assignee:	LG INNOTEK CO., LTD. (Seoul, KR)
Appl. No.:	18/009453
Filed (or PCT Filed):	June 11, 2021
PCT No.:	PCT/KR2021/007338
PCT Pub. No.:	WO2021/251795
PCT Pub. Date:	December 16, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230300977 A1	Sep. 21, 2023

Foreign Application Priority Data

KR

10-2020-0071465

Jun. 12, 2020

Publication Classification

Int. Cl.: H05K1/02 (20060101); H05K1/11 (20060101); H05K3/28 (20060101)

U.S. Cl.:

CPC H05K1/0298 (20130101); H05K3/28 (20130101); H05K1/111 (20130101); H05K1/112 (20130101); H05K2201/0191 (20130101); H05K2201/09736 (20130101)

Field of Classification Search

CPC: H05K (1/0298); H05K (3/28); H05K (3/4644); H05K (2201/0191); H05K (2201/09736); H05K (1/111); H05K (3/3452); H05K (3/061); H05K (3/4611)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7186921	12/2006	Igarashi	257/E23.173	H05K 1/0206
7193157	12/2006	Matsuda	174/254	H05K 1/0265
8426739	12/2012	Lee	174/254	H05K 1/0271
9040838	12/2014	Lee et al.	N/A	N/A
9420703	12/2015	Hayashi	N/A	H05K 1/0298
9578743	12/2016	Nagai	N/A	H05K 1/111
9699905	12/2016	Nishida	N/A	H01L 23/498
9999141	12/2017	Baek	N/A	H05K 1/185
2010/0252304	12/2009	Muramatsu	174/251	H01L 23/3121
2014/0037862	12/2013	Lee et al.	N/A	N/A
2014/0054073	12/2013	Lee et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
H04-151895	12/1991	JP	N/A
2014-045195	12/2013	JP	N/A
2015-050307	12/2014	JP	N/A
2015-216332	12/2014	JP	N/A
2016-048786	12/2015	JP	N/A

2017-152477	12/2016	JP	N/A
2017-195372	12/2016	JP	N/A
10-2014-0018016	12/2013	KR	N/A
10-2014-0027731	12/2013	KR	N/A
10-2016-0110159	12/2015	KR	N/A
10-2017-0037331	12/2016	KR	N/A
10-2018-0113996	12/2017	KR	N/A

OTHER PUBLICATIONS

International Search Report dated Sep. 29, 2021 issued in Application No. PCT/KR2021/007338. cited by applicant

Japanese Office Action dated May 20, 2025, issued in Application No. 2022-576532. cited by applicant

Korean Office Action dated Feb. 20, 2025, issued in Application No. 10-2020-0071465. cited by applicant

Primary Examiner: Patel; Ishwarbhai B

Attorney, Agent or Firm: KED & ASSOCIATES, LLP

Background/Summary

CROSS-REFERENCE TO RELATED PATENT APPLICATIONS

(1) This application is a U.S. National Stage Application under 35 U.S.C. § 371 of PCT Application No. PCT/KR2021/007338, filed Jun. 11, 2021, which claims priority to Korean Patent Application No. 10-2020-0071465, filed Jun. 12, 2020, whose entire disclosures are hereby incorporated by reference.

TECHNICAL FIELD

(2) The embodiment relates to a circuit board, and more particularly, to a circuit board capable of supporting an outermost circuit pattern using a solder resist.

BACKGROUND ART

(3) As miniaturization, weight reduction, and integration of an electronic component are accelerated, a line width of a circuit has been made fine. In particular, as a design rule of a semiconductor chip is integrated on a nanometer scale, a circuit line width of a package substrate or a printed circuit board on which the semiconductor chip is mounted has been made fine to several micrometers or less.

(4) Various methods have been proposed in order to increase the degree of circuit integration of the printed circuit board, that is, to reduce the circuit line width. For the purpose of preventing loss of the circuit line width in an etching step for forming a pattern after copper plating, a semi-additive process (SAP) method and a modified semi-additive process (MSAP) have been proposed.

(5) Then, an embedded trace substrate (hereinafter referred to as “ETS”) method for embedding a copper foil in an insulating layer in order to implement a fine circuit pattern has been used in the industry. In the ETS method, instead of forming a copper foil circuit on a surface of the insulating layer, the copper foil circuit is manufactured in an embedded form in the insulating layer, and thus there is no circuit loss due to etching and it is advantageous for making the circuit pitch fine.

(6) Meanwhile, recently, in order to meet a demand for wireless data traffic, efforts have been made to develop an improved 5G (5th generation) communication system or a pre-5G communication system. Here, the 5G communication system uses ultra-high frequency (mmWave) bands (sub 6

GHz, 28 GHz, 38 GHz, or higher frequencies) to achieve high data transfer rates.

(7) In addition, in order to reduce a path loss of radio waves and increase a transmission distance of radio waves in the ultra-high frequency band, in the 5G communication system, integration technologies such as beamforming, massive multi-input multi-output (massive MIMO), and array antennas have been developed. Considering that it may be composed of hundreds of active antennas of wavelengths in the frequency bands, an antenna system becomes large relatively.

(8) Since such an antenna and AP module are patterned or mounted on the printed circuit board, low loss on the printed circuit board is very important. This means that several substrates constituting the active antenna system, that is, an antenna substrate, an antenna power feeding substrate, a transceiver substrate, and a baseband substrate, should be integrated into one compact unit.

(9) In addition, the circuit board applied to the 5G communication system as described above is manufactured in a trend of light, thin and compact, and accordingly, the circuit pattern is becoming gradually finer.

(10) However, a circuit board including a conventional fine circuit pattern has a structure in which a circuit pattern disposed at an outermost portion protrudes above an insulating layer, and thus there is problem that the circuit pattern of the outermost portion easily collapses.

DISCLOSURE

Technical Problem

(11) An embodiment provides a circuit board having a new structure and a method of manufacturing the same.

(12) In addition, the embodiment provides a circuit board capable of providing a structure including a solder resist supporting a circuit pattern disposed on an outermost side and a method of manufacturing the same.

(13) In addition, the embodiment provides a circuit board capable of improving reliability of a circuit pattern by removing resin remaining on a surface of the circuit pattern disposed in a solder resist open region and a method of manufacturing the same.

(14) Technical problems to be solved by the proposed embodiments are not limited to the above-mentioned technical problems, and other technical problems not mentioned may be clearly understood by those skilled in the art to which the embodiments proposed from the following descriptions belong.

Technical Solution

(15) A circuit board according to an embodiment includes: an insulating layer including first to third regions; an outer layer circuit pattern disposed on an upper surface of the first to third regions of the insulating layer; and a solder resist including a first part disposed on the first region of the insulating layer, a second part disposed on the second region, and a third part disposed on the third region, wherein the outer layer circuit pattern includes: a first trace disposed on an upper surface of the first region of the insulating layer; and a second trace disposed on an upper surface of the third region of the insulating layer; wherein a height of the first trace is different from a height of the second trace; and an upper surface of the first part of the solder resist is positioned lower than an upper surface of the first trace.

(16) In addition, the first trace has a first height, wherein the second trace has a second height greater than the first height; and an upper surface of the third part of the solder resist is positioned higher than an upper surface of the second trace.

(17) In addition, the first height of the first trace satisfies a range of 90% to 95% of the second height of the second trace.

(18) In addition, the first part of the solder resist has a third height smaller than the first height, and the third height of the first part of the solder resist satisfies a range of 70% to 85% of the first height of the first trace.

(19) In addition, the outer layer circuit pattern includes a first pad disposed on an upper surface of

the first region of the insulating layer; and the first pad has a height corresponding to the first trace.
(20) In addition, the third height of the first part of the solder resist satisfies a range of 70% to 85% of the height of the first pad.

(21) In addition, the outer layer circuit pattern includes a second pad disposed on an upper surface of the second region of the insulating layer, and the second part of the solder resist has an opening region exposing a part of an upper surface of the second pad.

(22) In addition, an upper surface of the second pad includes a first portion covered by the second part of the solder resist and a second portion exposed through the opening region of the second part of the solder resist, and wherein the first portion of the second pad is positioned higher than the second portion of the second pad.

(23) In addition, a height of the second portion of the second pad satisfies a range of 90% to 95% of a height of the first portion of the second pad.

(24) In addition, a height of the first portion of the second pad corresponds to a height of the second trace, and a height of the second portion of the second pad corresponds to a height of the first trace.

(25) In addition, a surface roughness of the second part and the third part of the solder resist is smaller than a surface roughness of the first part of the solder resist.

(26) In addition, the insulating layer includes a plurality of insulating layers, and the outer layer circuit pattern protrudes from an upper surface of an uppermost insulating layer among the plurality of insulating layers, and wherein a primer layer is disposed between the uppermost insulating layer and the outer layer circuit pattern and between the uppermost insulating layer and the solder resist.

(27) On the other hand, a method of manufacturing of the circuit board according to the embodiment includes: manufacturing an inner layer substrate; forming an uppermost insulating layer having a primer layer disposed thereon on the inner layer substrate; forming an outer layer circuit pattern on the primer layer of the uppermost insulating layer; forming a solder resist layer divided into a first region, a second region, and a third region while covering the outer layer circuit pattern on the primer layer; partially exposing and developing the solder resist layer to form a solder resist including a first part formed in the first region, a second part formed in the second region, and a third part formed in the third region; and etching an outer layer circuit pattern exposed through the first part and the second part of the solder resist, wherein the outer layer circuit pattern includes a first trace disposed in the first region; and a second trace disposed in the third region, the first trace before the etching has a first height equal to a second height of the second trace and smaller than the second height of the first trace after the etching, and wherein a first height of the first trace after the etching satisfies a range of 90% to 95% of a second height of the second trace.

(28) In addition, an upper surface of the first part of the solder resist is positioned lower than the upper surface of the first trace, and an upper surface of the third part of the solder resist is positioned higher than an upper surface of the second trace.

(29) In addition, the first part of the solder resist has a third height smaller than the first height, and the third height of the first part of the solder resist satisfies a range of 70% to 85% of the first height of the first trace.

(30) In addition, the outer layer circuit pattern includes a first pad disposed in the first region, and the first pad is etched along with the first trace during the etching.

(31) In addition, the outer layer circuit pattern includes a second pad disposed in the second region, the second part of the solder resist has an opening region exposing a part of an upper surface of the second pad, and an upper surface of the second pad includes a first portion covered by the second part of the solder resist and a second portion exposed through an opening region of the second part of the solder resist, and the second portion of the second pad is etched during the etching.

(32) In addition, a height of the second portion of the second pad satisfies a range of 90% to 95% of a height of the first portion of the second pad.

(33) In addition, a surface roughness of the second part and the third part of the solder resist is

smaller than a surface roughness of the first part of the solder resist.

Advantageous Effects

(34) A circuit board in the embodiment may have eight or more insulating layers. In addition, the circuit board includes an outer layer circuit pattern disposed on an outer insulating layer positioned at an uppermost portion among the insulating layers and protruding above a surface of the outer insulating layer. In this case, the outer layer circuit pattern includes a first outer layer circuit pattern disposed in a first region and a second region that is an open region where the solder resist is not disposed, and a second outer layer circuit pattern positioned in a third region where the solder resist is disposed. In this case, the second outer layer circuit pattern may be supported and protected by the solder resist, but the first outer layer circuit pattern does not have a support layer capable of supporting the first outer layer circuit pattern, and thus there is a problem that the first outer layer circuit pattern may easily collapse due to various factors.

(35) Accordingly, the embodiment allows remaining without removing all of the solder resist in the first region and the second region, and accordingly, the first outer layer circuit pattern can be supported and protected by the solder resist. According to this, the embodiment can solve problems such as collapsing or rubbing of the first outer layer circuit pattern in the first region and the second region by miniaturizing the outer layer circuit pattern. Accordingly, the embodiment can improve product reliability. Particularly, the embodiment can solve problems such as collapsing or rubbing of a trace of the first outer layer circuit pattern in the first region. Accordingly, the embodiment can improve product reliability.

(36) In addition, the embodiment allows an etching process to be performed on a surface of the second outer layer circuit patterns disposed in the first and second regions. The etching process may be a process for removing resin remaining on the surface of the second outer layer circuit patterns disposed in the first and second regions. Accordingly, in the embodiment, the resin remaining on the surface of the second outer layer circuit pattern may be completely removed through the etching process. Accordingly, the embodiment can improve the product reliability of the circuit board by improving the electrical reliability of the second outer layer circuit pattern.

(37) In addition, an entire surface of the insulating layer or an entire surface of a primer layer in the embodiment has a structure covered by a solder resist. Accordingly, the embodiment can solve a reliability problem caused by exposing a part of a surface of the insulating layer or a part of a surface of the primer layer. In detail, the fact that a part of the surface of the insulating layer or a part of the surface of the primer layer is exposed means that a certain space exists between the outer layer circuit pattern and the solder resist. And, when the certain space exists, residual solution such as an adhesive member remains in the space, and accordingly, a reliability problem in which voids are provided by the residual solution may occur. In contrast, the embodiment may fill the space with a solder resist, thereby solving a reliability problem.

(38) In addition, the embodiment removes the solder resist using an exposure and development method other than a sand blast or plasma method. In this case, when the solder resist is removed using a sandblasting or plasma method, deformation of the outer layer circuit pattern may occur. For example, a cross section of the outer layer circuit pattern may be deformed into a triangular shape or the like. In addition, when the outer layer circuit pattern has a triangular cross section, an adhesive member cannot be stably disposed on the outer layer circuit pattern, and thus a reliability problem may occur. In contrast, in the embodiment, the solder resist can be removed without deformation of the outer layer circuit pattern, and thus reliability can be improved.

(39) In addition, the circuit board in the embodiment can be applied to a 5G communication system, and accordingly, transmission loss of a high frequency can be minimized, thereby further improving the reliability. Specifically, the circuit board in the embodiment can be used at the high frequency and can reduce wave loss.

Description

DESCRIPTION OF DRAWINGS

- (1) FIGS. 1A and 1B are views showing a circuit board manufactured by an SAP method according to a comparative example.
- (2) FIG. 2 is a view showing a circuit board manufactured by a ETS method in a comparative example.
- (3) FIG. 3 is a view showing a circuit board according to an embodiment.
- (4) FIG. 4 is a plan view of a circuit board including a protective layer according to an embodiment.
- (5) FIG. 5 is an enlarged view of a trace in region B of FIG. 3.
- (6) FIG. 6 is a view showing R1 and R2 in region B of FIG. 3.
- (7) FIGS. 7A to 8B are views showing a degree of residual resin according to a degree of etching.
- (8) FIGS. 9A and 9B are views showing a shape according to an etching state of a second outer layer circuit pattern according to an embodiment.
- (9) FIGS. 10 to 17 are views showing a method of manufacturing the circuit board shown in FIG. 3 in order of process.

MODES OF THE INVENTION

- (10) Hereinafter, the embodiment disclosed in the present specification will be described in detail with reference to the accompanying drawings, but the same or similar components are designated by the same reference numerals regardless of drawing numbers, and repeated description thereof will be omitted. The component suffixes “module” and “part” used in the following description are given or mixed together only considering the ease of creating the specification, and have no meanings or roles that are distinguished from each other by themselves. In addition, in describing the embodiments disclosed in the present specification, when it is determined that detailed descriptions of a related well-known art unnecessarily obscure gist of the embodiments disclosed in the present specification, the detailed description thereof will be omitted. Further, the accompanying drawings are merely for facilitating understanding of the embodiments disclosed in the present specification, the technological scope disclosed in the present specification is not limited by the accompanying drawings, and it should be understood as including all modifications, equivalents and alternatives that fall within the spirit and scope of the present invention.
- (11) It will be understood that, although the terms “first,” “second,” etc. may be used herein to describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another.
- (12) It will be understood that when an element is referred to as being “connected” or “coupled” to another element, it can be directly connected or coupled to the other element or intervening elements may be present. In contrast, when an element is referred to as being “directly connected” or “directly coupled” to another element, it will be understood that there are no intervening elements present.
- (13) As used herein, a singular expression includes a plural expression, unless the context clearly indicates otherwise.
- (14) It will be understood that the terms “comprise”, “include”, or “have” specify the presence of stated features, integers, steps, operations, elements, components and/or groups thereof disclosed in the present specification, but do not preclude the possibility of the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.
- (15) Hereinafter, embodiments of the present invention will be described in detail with reference to the accompanying drawings.
- (16) Prior to descriptions of the present embodiment, a comparative example compared with the present embodiment will be described.

(17) FIG. 1 is a view showing a circuit board according to a comparative example.

(18) Referring to FIG. 1 (a), the circuit board according to the comparative example includes a circuit pattern manufactured by a general SAP method.

(19) Specifically, the circuit board includes an insulating layer **10**, a circuit pattern **20**, and a protective layer **30**.

(20) The circuit pattern **20** is respectively disposed on upper and lower surfaces of the insulating layer **10**.

(21) In this case, at least one of the circuit patterns **20** disposed on a surface of the insulating layer **10** includes a fine circuit pattern.

(22) In FIG. 1, the circuit pattern **20** disposed on the upper surface of the insulating layer **10** includes a fine circuit pattern. The fine circuit pattern includes a trace **21** that is a signal transmission wiring line and a pad **22** for mounting a chip and the like.

(23) In this case, in the embodiment, since a supporting layer using a solder resist is formed for protecting the fine circuit pattern, a structure in a region where the fine circuit pattern is formed in the comparative example will be described.

(24) In addition, a protective layer **30** for protecting the circuit pattern **20** is disposed on the surface of the insulating layer **10**.

(25) In this case, an upper region of the insulating layer **10** includes a first region where the protective layer **30** is disposed and a second region that is an open region where the protective layer **30** is not disposed.

(26) Accordingly, a part of the circuit pattern **20** disposed on the upper surface of the insulating layer **10** is covered by the protective layer **30**, and the remaining part is exposed to the outside without being covered by the protective layer **30**.

(27) In this case, the trace **21** and the pad **22** corresponding to the fine circuit pattern as described above are disposed in the second region that is the open region of the protective layer **30**.

(28) For example, at least one of the trace **21** and the pad **22** is formed in a width/interval of 15 μm /15 μm or less.

(29) In this case, when the circuit pattern formed in the open region of the protective layer **30** is a pattern having a width exceeding 15 μm rather than a fine circuit pattern, the circuit pattern may be strong against external impact.

(30) However, as shown in FIG. 1 (b), as the circuit pattern gradually becomes finer, the width and interval of the trace **21** and the pad **22**, which are the fine circuit patterns of the outermost layer, gradually decrease, and accordingly, when the fine circuit pattern protruding above the upper surface of the insulating layer **10** is disposed in the second region that is the open region of the protective layer, there is a problem that the fine circuit pattern easily collapses due to an external impact.

(31) That is, as in B of FIG. 1 (b), the trace **21** corresponding to the fine circuit pattern of the outermost layer has an extremely fine pattern shape, and thus a problem of easily collapsing or rubbing occurs even with a small external impact.

(32) Meanwhile, recently, the fine circuit pattern disposed in the open region of the protective layer while having a structure buried in the insulating layer is formed by using a ETS method.

(33) FIG. 2 is a view showing a circuit board manufactured by an ETS method in a comparative example.

(34) Referring to FIG. 2, specifically, the circuit board includes an insulating layer **10A**, a circuit pattern **20A**, and a protective layer **30A**.

(35) The circuit pattern **20A** is respectively disposed on upper and lower surfaces of the insulating layer **10A**.

(36) In this case, at least one of the circuit patterns **20A** disposed on a surface of the insulating layer **10A** includes a fine circuit pattern.

(37) Here, when the circuit pattern is formed by the ETS method, the circuit pattern formed at first

has a structure buried in the insulating layer **10A**. Accordingly, when the circuit pattern formed at first is formed as a fine circuit pattern, the fine circuit pattern may have a structure in which the fine circuit pattern is buried in the insulating layer **10A** even in Comparative example.

(38) That is, the circuit board manufactured by the ETS method includes a fine circuit pattern having a structure buried in the surface of the insulating layer **10A**. That is, the fine circuit pattern includes a trace **21A** that is a signal transmission wiring line and a pad **22A** for mounting a chip or the like.

(39) In addition, when the circuit board is manufactured by the ETS method as described above, since the fine circuit pattern has the structure buried in the insulating layer, the fine circuit pattern may be protected from an external impact.

(40) In this case, for a substrate having a two-layer structure (based on the number of layers of the circuit pattern) as in FIG. 2, there is no major problem in manufacturing the circuit board by the ETS method. However, in case of manufacturing a circuit board having eight or more layers, in particular, ten or more layers by the ETS method, a lead time for manufacturing the same takes at least 2 months or more, and thus there is a problem that productivity is lowered.

(41) In addition, in order to manufacture the fine circuit pattern of the buried structure by the ETS method, the fine circuit pattern should be formed at first during a manufacturing process of a multilayer circuit board. In addition, recently, in order to be applied to an AP module having high integration/high specification, etc., a circuit board having eight to ten layers are required. In this case, in a process of forming the fine circuit pattern at first during the ETS process and then performing a multilayer stacking process, damage is applied to the fine circuit pattern due to a thermal stress, etc., and thus there is a problem that it is difficult to normally implement the fine circuit pattern.

(42) In addition, when the circuit board is manufactured by the ETS method, an ETS core layer is separately required. In this case, when the circuit board is manufactured by the ETS method, an additional process for finally removing the ETS core layer is required.

(43) In addition, when the circuit board is manufactured by the ETS method, there is a problem that a yield is lowered due to a cumulative tolerance when layers are stacked more than a certain number of times, and accordingly, product costs increase, and there is a problem that pattern damage increases due to stress as the stacking process is respectively performed on both surfaces around the ETS core layer.

(44) In addition, with the development of 5G technology in recent years, interest in circuit boards that may reflect the same is increasing. In this case, in order to apply the 5G technology, the circuit board should have a high multi-layer structure, and accordingly, the circuit pattern should be made fine. However, in Comparative example, it is possible to form the fine pattern, but there is a problem that it is not possible to stably protect the fine pattern.

(45) Accordingly, the embodiment is directed to providing a circuit board of a new structure capable of solving the reliability problem of the fine pattern disposed at the outermost portion and a control method thereof.

(46) FIG. 3 is a view showing a circuit board according to an embodiment, FIG. 4 is a plan view of a circuit board including a protective layer according to an embodiment, FIG. 5 is an enlarged view of a trace in region B of FIG. 3, and FIG. 6 is a view showing R1 and R2 in region B of FIG. 3.

(47) Prior to descriptions of FIGS. 3 to 6, the circuit board according to the embodiment may have a multilayer structure. Preferably, the circuit board according to the embodiment may have a structure of ten or more layers based on a number of layers of the circuit pattern. However, this is merely an example and the embodiment is not limited thereto. That is, the circuit board in the embodiment may have a number of layers smaller than ten layers, or alternatively, the circuit board may have a number of layers greater than ten layers.

(48) However, the circuit board in the embodiment is for solving problems of the ETS method in the comparative example. In this case, the ETS method in Comparative example has many

problems in manufacture a circuit board having eight or more layers, and accordingly, the embodiment will be described as having a ten-layer structure for comparison therewith.

(49) Referring to FIGS. **3** to **6**, a circuit board **100** includes an insulating layer **110**.

(50) Preferably, the circuit board **100** may include first to ninth insulating layers **111**, **112**, **113**, **114**, **115**, **116**, **117**, **118**, and **119** in order to implement a ten-layer structure.

(51) In this case, the first insulating layer **111**, the second insulating layer **112**, the third insulating layer **113**, the fourth insulating layer **114**, the fifth insulating layer **115**, the sixth insulating layer **116**, and the seventh insulating layer **117** of the insulating layer **110** may be an internal insulating layer disposed inside in a stacked insulating layer structure, and the eighth insulating layer **118** may be an uppermost insulating layer (a first outermost insulating layer) disposed on an inner insulating layer, and the ninth insulating layer **119** may be a lowermost insulating layer (a second outermost insulating layer) disposed under the inner insulating layer.

(52) The first insulating layer **111** may be a core insulating layer disposed at a center in the stacked structure of the insulating layer **110**. The second insulating layer **112**, the fourth insulating layer **114**, the sixth insulating layer **116**, and the eighth insulating layer **118** may be upper insulating layers sequentially disposed on the first insulating layer **111**. In addition, the third insulating layer **113**, the fifth insulating layer **115**, the seventh insulating layer **117**, and the ninth insulating layer **119** may be lower insulating layers sequentially disposed under the first insulating layer **111**.

(53) The insulating layer **110** may be a substrate on which an electric circuit capable of changing wiring is formed and may include all of a printed circuit board, a wiring board, and an insulating substrate made of an insulating material capable of forming circuit patterns on a surface thereof.

(54) For example, the insulating layer **110** may be rigid or flexible. For example, the insulating layer **110** may include glass or plastic. Specifically, the insulating layer **110** may include a chemically tempered/semi-tempered glass, such as soda lime glass, aluminosilicate glass, etc., a tempered or flexible plastic such as polyimide (PI), polyethylene terephthalate (PET), propylene glycol (PPG), polycarbonate (PC), etc., or sapphire.

(55) Further, the insulating layer **110** may include an optically isotropic film. As an example, the insulating layer **110** may include cyclic olefin copolymer (COC), cyclic olefin polymer (COP), optically isotropic PC, optically isotropic polymethylmethacrylate (PMMA), or the like.

(56) In addition, at least one of the insulating layer **110** may be partially bent while having a curved surface. That is, at least one of the insulating layer **110** may partially have a plane and may partially be bent while having a curved surface. Specifically, an end portion of at least one of the insulating layer **110** may be bent while having a curved surface, or bent or crooked while having a surface with a random curvature.

(57) In addition, at least one of the insulating layer **110** may be a flexible substrate having flexibility. Further, at least one of the insulating layer **110** may be a curved or bent substrate. In this case, at least one of the insulating layer **110** may form a wiring layout for electrical wirings which connect circuit components based on a circuit design, and electrical conductors may be disposed on an insulating material. Further, electrical components may be mounted on at least one of the insulating layer **110**, and the insulating layer **110** may form wirings configured to connect the electrical components to make a circuit, and may mechanically fix the components besides functioning to electrically connect the components.

(58) A circuit pattern may be disposed on a surface of the insulating layer **110**.

(59) That is, circuit patterns may be disposed on respective surfaces of the first to ninth insulating layers **111**, **112**, **113**, **114**, **115**, **116**, **117**, **118**, and **119** constituting the insulating layer **110**.

(60) Here, the circuit pattern may include an inner layer circuit pattern **120** and outer layer circuit patterns **130** and **140**. The inner layer circuit pattern **120** may be a circuit pattern disposed inside the insulating layer **110** in the stacked structure of the circuit board, and the outer layer circuit patterns **130** and **140** may be a circuit pattern disposed on an outermost side of the insulating layer **110** in the stacked structure of the circuit board.

(61) The inner layer circuit pattern **120** may include a first circuit pattern **121**, a second circuit pattern **122**, a third circuit pattern **123**, a fourth circuit pattern **124**, a fifth circuit pattern **125**, and a sixth circuit pattern **126**, and a seventh circuit pattern **127**.

(62) The first circuit pattern **121** may be disposed on an upper surface of the first insulating layer **111**, and thus the first circuit pattern **121** may be covered by the second insulating layer **112**. The second circuit pattern **122** may be disposed on a lower surface of the first insulating layer **111**, and thus the second circuit pattern **122** may be covered by the third insulating layer **113**. The third circuit pattern **123** may be disposed on an upper surface of the second insulating layer **112**, and thus the third circuit pattern **123** may be covered by the fourth insulating layer **114**. The fourth circuit pattern **124** may be disposed on a lower surface of the third insulating layer **113**, and thus the fourth circuit pattern **124** may be covered by the fifth insulating layer **115**. The fifth circuit pattern **125** may be disposed on an upper surface of the fourth insulating layer **114**, and thus the fifth circuit pattern **125** may be covered by the sixth insulating layer **116**. The sixth circuit pattern **126** may be disposed on a lower surface of the fifth insulating layer **115**, and thus the sixth circuit pattern **126** may be covered by the seventh insulating layer **117**. The seventh circuit pattern **127** may be disposed on an upper surface of the sixth insulating layer **116**, and thus the seventh circuit pattern **127** may be covered by the eighth insulating layer **118**. The eighth circuit pattern **128** may be disposed on a lower surface of the seventh insulating layer **117**, and thus the eighth circuit pattern **128** may be covered by the ninth insulating layer **119**.

(63) The outer layer circuit pattern may be disposed on a surface of the outermost insulating layer disposed on the outermost side of the insulating layer **110**. Preferably, the outer layer circuit pattern may include a first outer layer circuit pattern **130** disposed on a lower surface of the ninth insulating layer **119** disposed at a lowermost portion of the insulating layer **110**.

(64) In addition, the outer layer circuit pattern may include a second outer layer circuit pattern **140** disposed on an upper surface of the eighth insulating layer **118** disposed on an uppermost portion of the insulating layer **110**.

(65) In this case, at least one of the first outer layer circuit pattern **130** and the second outer layer circuit pattern **140** may be formed to protrude above the surface of the insulating layer. Preferably, the first outer layer circuit pattern **130** may be formed to protrude below the lower surface of the ninth insulating layer **119**. In addition, the second outer layer circuit pattern **140** may be formed to protrude above the upper surface of the eighth insulating layer **118**.

(66) That is, an upper surface of the first outer layer circuit pattern **130** may be positioned on the same plane as the lower surface of the ninth insulating layer **119**. In addition, a lower surface of the second outer layer circuit pattern **140** may be positioned on the same plane as an upper surface of the primer layer **150** disposed on an upper surface of the eighth insulating layer **118**.

(67) In other words, the primer layer **150** may be disposed on the upper surface of the eighth insulating layer **118** and below the second outer layer circuit pattern **140**.

(68) That is, the second outer layer circuit pattern **140** may include a fine circuit pattern. Preferably, the second outer layer circuit pattern **140** may be a fine circuit pattern having a line width of 10 μm or less and an interval between patterns of 10 μm or less. Accordingly, when the second outer layer circuit pattern **140** is directly disposed on the eighth insulating layer **118**, a contact area between the eighth insulating layer **118** and the second outer layer circuit pattern **140** is small, and thus a situation in which the second outer layer circuit pattern **150** is separated from the eighth insulating layer **118** may occur.

(69) Therefore, in the embodiment, the primer layer **150** is disposed between the second outer layer circuit pattern **140** and the eighth insulating layer **118**. The primer layer **150** may improve bonding force between the second outer layer circuit pattern **140** and the eighth insulating layer **118**. The primer layer **150** may be disposed to entirely cover the upper surface of the eighth insulating layer **118**. In addition, the second outer layer circuit pattern **140** may be partially disposed on the primer layer **150**. Therefore, the upper surface of the primer layer **150** in an embodiment may include a

first portion in contact with the second outer layer circuit pattern **140** and a second portion in contact with a lower surface of a solder resist **160** to be described later. That is, when the second outer layer circuit pattern **140** by the SAP process is formed, the primer layer **150** may serve to strengthen bonding force between the eighth insulating layer **118** and the second outer layer circuit pattern **140**. Such a primer layer **150** may include a polyurethane-based resin, an acrylic resin, or a silicone-based resin, but the embodiment is not limited thereto.

(70) Meanwhile, it is illustrated in FIG. **3** that the primer layer is not disposed between the ninth insulating layer **119** and the first outer layer circuit pattern **130**, but the primer layer may also be formed between the ninth insulating layer **119** and the first outer layer circuit pattern **130**. However, the first outer layer circuit pattern **130** may not be the fine circuit pattern, and accordingly, the primer layer between the ninth insulating layer **119** and the first outer layer circuit pattern **130** may be selectively omitted.

(71) Consequently, when the fine circuit pattern is disposed on the inner layer, the primer layer may be omitted as the circuit pattern is covered by at least one of the insulating layers **110**. On the other hand, in the embodiment, when the fine circuit pattern is disposed on the outermost layer, since there is no insulating layer covering the fine circuit pattern, the primer layer **150** is disposed in order to improve bonding force between the fine circuit pattern and the insulating layer.

(72) Hereinafter, it will be described that the second outer layer circuit pattern **140** is formed of a fine circuit pattern. However, the embodiment is not limited thereto, and the first outer layer circuit pattern **130** may also be formed of the fine circuit pattern. It will be obvious that a structure for improving reliability, such as strengthening bonding force and preventing collapse of the second outer layer circuit pattern **140** described below, may also be applied to the first outer layer circuit pattern **130**.

(73) The inner layer circuit pattern **120**, the first outer layer circuit pattern **130**, and the second outer layer circuit pattern **140** may be wirings that transmit electrical signals and may be formed of a metal material having high electrical conductivity. To this end, the inner circuit pattern **120**, the first outer layer circuit pattern **130**, and the second outer layer circuit pattern **140** may be formed of at least one metal material selected from among gold (Au), silver (Ag), platinum (Pt), titanium (Ti), tin (Sn), copper (Cu), and zinc (Zn). In addition, the inner circuit pattern **120**, the first outer layer circuit pattern **130**, and the second outer layer circuit pattern **140** may be formed of paste or solder paste including at least one metal material selected from among gold (Au), silver (Ag), platinum (Pt), titanium (Ti), tin (Sn), copper (Cu), and zinc (Zn), which are excellent in bonding force. Preferably, the inner circuit pattern **120**, the first outer layer circuit pattern **130**, and the second outer layer circuit pattern **140** may be formed of copper (Cu) having high electrical conductivity and a relatively low cost.

(74) At least one of the inner layer circuit pattern **120**, the first outer layer circuit pattern **130**, and the second outer layer circuit pattern **140** may be formed by a general process of manufacturing a circuit board, such as an additive process, a subtractive process, a modified semi additive process (MSAP), a semi additive process (SAP), etc., and detailed descriptions thereof will be omitted herein.

(75) Preferably, the first outer layer circuit pattern **130** and the second outer layer circuit pattern **140** are outermost circuit patterns disposed on an outermost side of the circuit board, and thus they may be formed by the SAP (Semi Additive Process) method.

(76) Meanwhile, a via **V** may be disposed in the insulating layer **110**. The vias **V** are disposed in each insulating layer, and thus the via **V** may serve to electrically connect circuit patterns disposed in different layers to each other.

(77) A first via **V1** may be disposed in the first insulating layer **111**. The first via **V1** may electrically connect the first circuit pattern **121** disposed on the upper surface of the first insulating layer **111** and the second circuit pattern **122** disposed on the lower surface of the first insulating layer **111**.

(78) A second via V2 may be disposed in the second insulating layer **112**. The second via V2 may electrically connect the first circuit pattern **121** disposed on the upper surface of the first insulating layer **111** and the third circuit pattern **123** disposed on the upper surface of the second insulating layer **112**.

(79) A third via V3 may be disposed in the third insulating layer **113**. The third via V3 may electrically connect the second circuit pattern **122** disposed on the lower surface of the first insulating layer **111** and the fourth circuit pattern **124** disposed on the lower surface of the third insulating layer **113**.

(80) A fourth via V4 may be disposed in the fourth insulating layer **114**. The fourth via V4 may electrically connect the third circuit pattern **123** disposed on the upper surface of the second insulating layer **111** and the fifth circuit pattern **125** disposed on the upper surface of the fourth insulating layer **114**.

(81) A fifth via V5 may be disposed in the fifth insulating layer **115**. The fifth via V5 may electrically connect the fourth circuit pattern **124** disposed on the lower surface of the third insulating layer **113** and the sixth circuit pattern **126** disposed on the lower surface of the fifth insulating layer **115**.

(82) A sixth via V6 may be disposed in the sixth insulating layer **116**. The sixth via V6 may electrically connect the fifth circuit pattern **125** disposed on the upper surface of the fourth insulating layer **114** and the seventh circuit pattern **127** disposed on the upper surface of the sixth insulating layer **116**.

(83) A seventh via V7 may be disposed in the seventh insulating layer **117**. The seventh via V7 may electrically connect the sixth circuit pattern **126** disposed on the lower surface of the fifth insulating layer **115** and the eighth circuit pattern **128** disposed on the lower surface of the seventh insulating layer **117**.

(84) An eighth via V1 may be disposed in the eighth insulating layer **118**. The eighth via V8 may electrically connect the seventh circuit pattern **127** disposed on the upper surface of the sixth insulating layer **116** and the second outer layer circuit pattern **140** disposed on the upper surface of the primer layer **150**.

(85) A ninth via V9 may be disposed in the ninth insulating layer **119**. The ninth via V9 may electrically connect the eighth circuit pattern **128** disposed on the lower surface of the seventh insulating layer **117** and the first outer layer circuit pattern **130** disposed on the lower surface of the ninth insulating layer **119**.

(86) The via V as described above may be formed by filling the inside of a via hole formed in each insulating layer with a metal material.

(87) The via hole may be formed by any one of mechanical, laser, and chemical processing method. When the via hole is formed by mechanical processing, a method such as milling, drilling and routing may be used, when the via hole is formed by laser processing, a method of UV or CO2 laser may be used, and when the via hole is formed by chemical processing, the insulating layer **110** may be opened using a chemical including aminosilane, ketone, or the like.

(88) Meanwhile, the laser processing is a cutting method in which a part of a material is melted and evaporated by concentrating optical energy at a surface to take a desired shape. Complex formation by a computer program may be easily processed, and composite materials which are difficult to cut by other methods may be processed.

(89) In addition, the processing by the laser may have a cutting diameter of at least 0.005 mm, and has a wide range of thickness that may be processed.

(90) It is preferable to use an yttrium aluminum garnet (YAG) laser or CO2 laser or ultraviolet (UV) laser as the laser processing drill. The YAG laser is a laser capable of processing both a copper foil layer and an insulating layer, and the CO2 laser is a laser capable of processing only an insulating layer.

(91) When the via hole is formed, the first to ninth vias V1, V2, V3, V4, V5, V6, V7, V8, and V9

may be formed by filling the inside of the via hole with a conductive material. The metal material forming the first to ninth vias **V1**, **V2**, **V3**, **V4**, **V5**, **V6**, **V7**, **V8**, and **V9** may be any one material selected from among copper (Cu), silver (Ag), tin (Sn), gold (Au), nickel (Ni), and palladium (Pd), and the conductive material may be filled by any one of electroless plating, electrolytic plating, screen printing, sputtering, evaporation, ink jetting, and dispensing, or a combination thereof.

(92) Meanwhile, a protective layer may be disposed on an outermost side of the circuit board **100**. Preferably, a first protective layer **160** may be disposed on the eighth insulating layer **118** (preferably, on the primer layer **150**). In addition, a second protective layer **175** may be disposed under the ninth insulating layer **119**.

(93) The first protective layer **160** and the second protective layer **175** may be formed of at least one layer using any one or more of solder resist (SR), oxide, and Au. Preferably, the first protective layer **160** and the second protective layer **175** may be a solder resist.

(94) Meanwhile, the first protective layer **160** is disposed on the primer layer **150**. The first protective layer **160** may serve to support the second outer layer circuit pattern **140** disposed on the primer layer **150** and protect a surface of the second outer layer circuit pattern **140**.

(95) That is, the first protective layer **160** may partially overlap the second outer layer circuit pattern **140** disposed on the primer layer **150**. An area of the first protective layer **160** may be smaller than an area of the eighth insulating layer **118**. The area of the first protective layer **160** may be smaller than an area of the primer layer **150**. The first protective layer **160** is partially or entirely disposed on the primer layer **150** and the second outer layer circuit pattern **140**, and thus the first protective layer **170** may include an open region exposing a surface of the second outer layer circuit pattern **140**.

(96) The first protective layer **160** may include an open region having a groove-like shape. Preferably, the first protective layer **160** includes an open region exposing a surface of the second outer layer circuit pattern **140** disposed in the first region **R1** and the second region **R2**. In this case, the first region **R1** and the second region **R2** may be an open region where the surface of the second outer layer circuit pattern **140** is exposed. That is, a device mounting pad on which a chip device is mounted, a core pad or BGA pad serving as a die for connection to an external board, and a signal transfer wire trace, etc. are disposed in the first region **R1** and the second region **R2**. In addition, the first protective layer **160** has an open region exposing surfaces of the device mounting pad, the core pad, and the BGA pad in the first region **R1** and the second region **R2**.

(97) In conclusion, the first region **R1** and the second region **R2** may mean a region in which the surface of the second outer layer circuit pattern **140** is exposed through the first protective layer **160** among an upper region of the primer layer **150** and the second outer layer circuit pattern **140**.

(98) That is, the circuit board includes a first region **R1**, a second region **R2**, and a third region **R3**. The first region **R1** and the second region **R2** are an open region where the surface of the second outer layer circuit pattern **140** should be exposed through the first protective layer **160**, and the third region **R3** may be a buried region where the surface of the second outer layer circuit pattern **140** is covered by the first protective layer **160**.

(99) That is, the first region **R1** is a region in which the first pad **142** and the trace **141a** to be electrically connected to a component such as a chip among the second outer layer circuit pattern **140** are disposed. Accordingly, the first protective layer **160** may have an open region exposing the surface of the first pad **142** included in the first region **R1**. In addition, the second region **R2** is a region in which the second pad **143** corresponding to a core pad or BGA pad serving as a die for bonding to an external board among the second outer layer circuit patterns **140** is disposed.

(100) In addition, the second outer layer circuit pattern **140** disposed in the first region **R1** as described above may have a reliability problem such as collapsing or rubbing due to various factors. Furthermore, the trace **141a** of the second outer layer circuit pattern **140** is a fine circuit pattern, and thus the second outer layer circuit pattern **140** has a line width **W1** of 10 μm or less and an interval of 10 μm or less and is disposed on the primer layer **150**. Accordingly, the trace **141**

disposed on the first region R1 may have a problem that it is easily collapsed or rubbed by various small external impacts.

(101) Accordingly, in the embodiment, in order to improve reliability of the second outer layer circuit pattern **140** disposed on the first region R1, the first protective layer **160** is formed on the primer layer **150** corresponding to the first region R1.

(102) That is, the first protective layer **160** may be disposed in a region of the upper surface of the primer layer **150** where the second outer layer circuit pattern **140** is not disposed. For example, the first protective layer **160** may be disposed on the upper surface of the primer layer **150**, and thus the first protective layer **160** may be disposed between the second outer layer circuit patterns **140** on the first region R1.

(103) In this case, the second outer layer circuit pattern **140** includes a second-first outer layer circuit pattern formed in the first region R1 and the second region R2 and a second-second outer layer circuit pattern formed in the third region R2.

(104) In addition, an upper surface of the primer layer **150** may include a first upper surface corresponding to the first region R1, a second upper surface corresponding to the second region R2, and a third upper surface corresponding to the third region R3.

(105) In this case, the first protective layer **160** may be entirely disposed on the primer layer **150** without dividing the first region R1, the second region R2 and the third region R3. That is, the first protective layer **160** may be respectively disposed in a region between the second-first outer layer circuit patterns and a region between the second-second outer layer circuit patterns.

(106) Accordingly, the first protective layer **160** includes a first part disposed in the first region R1, a second part disposed in the second region R2 and a third part disposed in the third region R3.

(107) In this case, the first protective layer **160** may have a step.

(108) That is, a surface of the second outer layer circuit pattern **140** should be exposed to an outside in the first region R1 and the second region R2, and a surface of the second outer layer circuit pattern **140** should be covered with a protective layer in the third region R3.

(109) Here, the second outer layer circuit pattern **140** disposed in the first region R1 and the second region R2 may have different widths according to functions. For example, the second outer layer circuit pattern **140** disposed in the first region R1 and the second region R2 may include the first pad **142**, the second pad **143**, and the trace **141** as described above.

(110) In this case, the trace **141** may have a width of 10 μm or less. In addition, the first pad may have a width of about 45 μm . In addition, the second pad **143** may have a width W3 of 100 μm to 300 μm .

(111) Accordingly, the embodiment forms the first protective layer **160** having different heights or structures with respect to a region where the trace **141** is disposed, a region where the first pad **142** is disposed, and a region where the second pad **143** is disposed in the open region of the solder resist.

(112) The first protective layer **160** may include a first part disposed in the first region R1, a second part disposed in the second region R2, and a third part disposed in the third region R3. In addition, at least one of the first part, the second part, and the third part may have a height different from that of at least one other of the first part, the second part, and the third part.

(113) For example, an upper surface of the first part disposed in the first region R1 may be positioned lower than an upper surface of the second part disposed in the second region R2 and an upper surface of the third part disposed in the third region R3.

(114) In addition, an upper surface of the second part may be positioned higher than an upper surface of the first part. In addition, an upper surface of the second part may have the same height as an upper surface of the third part. That is, the upper surface of the second part and the upper surface of the third part may be positioned on the same plane.

(115) Hereinafter, the first protective layer **160** will be described in detail.

(116) The first protective layer **160** may be disposed on the primer layer **150**. The first protective

layer **160** is a solder resist.

(117) The first protective layer **160** may be disposed between the second outer layer circuit patterns **140** on the primer layer **150**. That is, the second outer layer circuit patterns **140** are disposed on the primer layer **150** at regular intervals. Also, the first protective layer **160** may be disposed on a region of an upper surface of the primer layer **150** where the second outer layer circuit pattern **140** is not disposed. In addition, the first protective layer **160** may be selectively disposed on the second outer layer circuit pattern **140**.

(118) Hereinafter, the first protective layer **160** will be described as a solder resist **160**.

(119) A solder resist **160** may be disposed on a region of the upper surface of the primer layer **150** on which the second outer layer circuit pattern **140** is not disposed.

(120) Accordingly, a lower surface of the solder resist **160** may directly contact the upper surface of the primer layer **150**. In addition, the solder resist **160** may have a structure in direct contact with the second outer layer circuit pattern **140**.

(121) For example, a first part of the solder resist **160** disposed in the first region R1 may directly contact a side surface of the second outer layer circuit pattern **140**. In addition, the first part of the solder resist **160** disposed in the first region R1 may not contact an upper surface of the second outer layer circuit pattern **140**. That is, the first part of the solder resist **160** disposed in the first region R1 may expose the upper surface of the second outer layer circuit pattern **140**. Accordingly, a height of the first part of the solder resist **160** may be lower than a height of the second outer layer circuit pattern **140**. Accordingly, the first part of the solder resist **160** disposed in the first region R1 may expose an entire upper surface of the second outer layer circuit pattern **140** and a part of the side surface of the second outer layer circuit pattern **140**.

(122) In addition, a second part of the solder resist **160** disposed in the second region R2 may directly contact a side surface of the second outer layer circuit pattern **140**. In addition, the second part of the solder resist **160** disposed in the second region R2 may directly contact a part of the upper surface of the second outer layer circuit pattern **140**. In addition, the second part of the solder resist **160** disposed in the second region R2 may expose an upper surface of the second outer layer circuit pattern **140**.

(123) In addition, a third part of the solder resist **160** disposed in the third region R3 may directly contact a side surface of the second outer layer circuit pattern **140**. In addition, the third part of the solder resist **160** disposed in the third region R3 may directly contact an upper surface of the second outer layer circuit pattern **140**. That is, the third part of the solder resist **160** disposed in the third region R3 may protrude above the upper surface of the second outer layer circuit pattern **140** with a predetermined height and cover the second outer layer circuit pattern **140**. In detail, the third part of the solder resist **160** disposed in the third region R3 may be disposed while surrounding the side surface and upper surface of the second outer layer circuit pattern **140**.

(124) Meanwhile, the second outer layer circuit pattern **140** according to the embodiment may have different heights for each region. Meanwhile, the second outer layer circuit pattern **140** may include a trace **141**, a first pad **142** and a second pad **142** as described above.

(125) In this case, the first pad **142** may be disposed in the first region R1. In addition, the second pad **142** may be disposed in the second region R2. In addition, the trace **141** may include a first trace **141a** disposed in the first region R1 and a second trace **141b** disposed in the third region R3.

(126) In addition, a height of the first trace **141a** may be different from a height of the second trace **141b**.

(127) The first trace **141a** may have a first height H1. The first height H1 of the first trace **141a** may be 14.5 μm to 16.25 μm .

(128) The second trace **141b** may have a second height H2 greater than the first height H1. The second height H2 may be 16 μm to 17 μm . Here, a height difference between the first trace **141a** and the second trace **141b** may be 0.75 μm to 1.5 μm .

(129) For example, the first height H1 of the first trace **141a** may satisfy a range of 90% to 95% of

the second height H2 of the second trace **141b**.

(130) That is, the first height H1 of the first trace **141a** in the embodiment is smaller than the second height H2 of the second trace H2. This is because the first trace **141a** formed in the first region R1 is etched to remove a remaining resin on the upper surface of the first trace **141a**. In other words, the first part of the solder resist **160** is removed through a thinning process while being disposed on the first region R1 while covering the first trace **141a**, and accordingly, the first part of the solder resist **160** has a height lower than that of the first trace **141a**. In this case, a resin remaining on the surface of the first trace **141a** is not completely removed in the thinning process, which may cause a reliability problem. Therefore, in the embodiment, an etching process is performed on the surface of the first trace **141a** to completely remove the remaining resin.

(131) When the first height H1 of the first trace **141a** is less than 90% of the second height H2 of the second trace **141b**, this means that over-etching of the first trace **141a** has progressed, and thus a reliability problem may occur due to deformation of the shape of the first trace **141a**. In addition, when the first height H1 of the first trace **141a** is 95% greater than the second height H2 of the second trace **141b**, this means that the etching of the first trace **141a** is insufficient, and thus a reliability problem may occur due to resin remaining on the surface of the first trace **141a**.

Therefore, in the embodiment, the first height H1 of the first trace **141a** satisfies a range of 90% to 95% of the second height H2 of the second trace **141b**, and thus the reliability problem to solve.

(132) The first part of the solder resist **160** may have a third height H3. The third height H3 may be smaller than the first height H1. For example, the third height H3 of the first part of the solder resist **160** may satisfy 70% to 85% of the first height H1 of the first trace **141a**. For example, when the third height H3 of the first part of the solder resist **160** is less than 70% of the first height H1 of the first trace **141a**, the first part of the solder resist **160** may not stably support the first trace **141a**. For example, when the third height H3 of the first part of the solder resist **160** is less than 70% of the first height H1 of the first trace **141a**, an area of a protruding portion of the first trace **141a** on the surface of the solder resist **160** increases, and accordingly, it may not be easy to control the etching process of the first trace **141a**. That is, when the area of the protruding portion of the first trace **141a** on the surface of the solder resist **160** is increased, it is difficult to precisely etch only a desired height in the etching process. For example, when the area of the protruding portion of the first trace **141a** on the surface of the solder resist **160** is increased, more etching than the desired height is performed in the etching process, and accordingly, a reliability problem in which shape deformation (eg, crushing) of the first trace **141a** becomes severe may occur.

(133) Meanwhile, the third part of the solder resist **160** may have a fourth height H4. A fourth height H4 of the third part of the solder resist **160** is greater than the first height H1, the second height H2, and the third height H3.

(134) In this case, the third part of the solder resist **160** is disposed to cover the second outer layer circuit pattern **140** in order to stably protect the second outer layer circuit pattern **140**. In this case, the fourth height H2 may be 20 μm to 40 μm . When the fourth height H4 is less than 20 μm , the second outer layer circuit pattern **140** buried in the third part of the solder resist **160** cannot be stably protected from various factors. In addition, when the fourth height H4 is greater than 40 μm , an overall thickness of the circuit board may increase. In addition, when the fourth height H4 is greater than 40 μm , a manufacturing cost of the circuit board may increase.

(135) Meanwhile, the second part of the solder resist **160** disposed in the second region R2 may include an opening region. The second part of the solder resist **160** may be disposed in the second region R2 and may have an opening region exposing a portion of an upper surface of the second pad **143**. In addition, the second part of the solder resist **160** may be disposed while covering a part of an upper surface of the second pad **143**. In this case, a height of the second part of the solder resist **160** may correspond to a height of the third part of the solder resist **160**.

(136) That is, the second outer layer circuit pattern **140** included in the second region R2 is the second pad **143**. As described above, the second pad **143** may be a BGA pad or a core pad.

Accordingly, a width of the second pad **143** may be relatively greater than that of other pads. For example, the second pad **143** may have a width W_3 of 100 μm to 300 μm . In addition, since the second pad **143** has a relatively large width, it is not greatly affected by exposure resolution. That is, since the second pad **143** has a relatively large width, there is no problem in reliability even if only a part of the upper surface of the second pad **143** is exposed. In other words, even if only a part of the upper surface of the second pad **143** is exposed, a function of the die for bonding with another external board is not greatly affected. Accordingly, the second part of the solder resist **160** may be disposed while covering a part of the upper surface of the second pad **143** as described above. In detail, the second part of the solder resist **160** has a fourth height H_4 equal to a height of the first part and protrudes from the upper surface of the second pad **143**, and the second part of the solder resist **160** has an opening region exposing a part of the upper surface of the second pad **143**. (137) Meanwhile, an etching process for removing remaining resin may also be performed on the second pad **143** along with the first trace **141a**. Accordingly, an upper surface of the second pad **143** may have a step. That is, the second pad **143** may include a first portion covered by the second part of the solder resist **160** and a second portion exposed by the opening region of the second part of the solder resist **160**. In addition, the first portion and the second portion of the second pad **143** may have different heights.

(138) In addition, the first portion of the second pad **143** may have a fifth height H_5 . In addition, the second portion of the second pad **143** may have a sixth height H_6 smaller than the fifth height H_5 . A sixth height H_6 of the second portion of the second pad **143** may be 14.5 μm to 16.25 μm .

(139) In addition, the first portion of the second pad **143** may have a fifth height H_5 greater than the sixth height H_6 . The fifth height H_5 may be 16 μm to 17 μm . Here, a height difference between the first and second portions of the second pad **143** may be 0.75 μm to 1.5 μm .

(140) For example, the sixth height H_6 of the second portion of the second pad may satisfy a range of 90% to 95% of the fifth height H_5 of the first portion of the second pad **143**.

(141) That is, the sixth height H_6 of the second portion of the second pad **143** in the embodiment is smaller than the fifth height H_5 of the first portion of the second pad **143**. This is because the second part of the second pad **143** exposed through the opening region of the second part of the solder resist **160** is etched to remove the resin remaining on the upper surface of the second pad **143**. In other words, the second part of the solder resist **160** is removed through a thinning process while being disposed on the second region R_2 while covering the second pad **143**, and accordingly, the second part of the solder resist **160** may include the opening region. In this case, the resin remaining on the surface of the second pad **143** is not completely removed in the thinning process, which may cause a reliability problem. Therefore, in the embodiment, an etching process is performed on the surface of the second portion of the second pad **143** to completely remove the remaining resin.

(142) In this case, etching of the second pad **143** may be performed together with the first trace **141a**. Accordingly, an etching condition of the second pad **143** may correspond to an etching condition of the first trace **141a**.

(143) Accordingly, when the sixth height H_6 of the second portion of the second pad **143** is smaller than 90% of the fifth height H_5 of the first portion of the second pad **143**, this means that over-etching of the second portion of the second pad **143** has progressed, and thus a reliability problem may occur due to deformation of the shape of the second portion of the second pad **143**. In addition, when the sixth height H_6 of the second portion of the second pad **143** is 95% greater than the fifth height H_5 of the first portion of the second pad **143**, this means that the etching of the second portion of the second pad **143** is insufficient, and thus a reliability problem may occur due to resin remaining on the surface of the second portion of the second pad **143**. Therefore, in the embodiment, the sixth height H_6 of the second portion of the second pad **143** satisfies a range of 90% to 95% of the fifth height H_5 of the first portion of the second pad **143**, and thus the reliability problem to solve.

(144) Meanwhile, the first pad **142** may have the same height as the second portion of the second pad **143**. That is, the first pad **142** may have a height lower than that of the first portion of the second pad **143**. That is, the first pad **142** is etched together with the second part of the second pad **143**, and accordingly, the first pad **142** may have a seventh height H7 corresponding to the sixth height H6 of the second portion of the second pad **143**.

(145) A photo solder resist film may be used as the solder resist **160**. The solder resist **160** may have a structure in which a resin and a filler are mixed.

(146) For example, the solder resist **160** may include a filler such as BaSO₄, SiO₂, or Talc, and a content of the filler may have a range of 20 wt. % to 35 wt. %.

(147) In this case, when the content of the filler included in the solder resist **160** is less than 20 wt. %, the second outer layer circuit pattern **140** may not be stably protected by the solder resist **160**. In addition, when the content of the filler included in the solder resist **160** is greater than 35 wt. %, a part of the filler may remain on the second outer layer circuit pattern **140** when the solder resist **160** is developed.

(148) That is, a protective layer including the solder resist **160** according to the embodiment will be described. Here, the solder resist **160** may be a protective layer protecting the surface of the second outer layer circuit pattern **140** in the third region R3, and the solder resist **160** may be a support layer supporting the second outer layer circuit pattern **140** in the first region R1.

(149) In this case, a comparative example includes a circuit pattern disposed on the insulating layer with a protruding structure. In addition, the circuit pattern may be independently disposed on the insulating layer without being supported by another support layer. Accordingly, collapse or chafing of the circuit pattern occurs in a region corresponding to the fine pattern in the comparative example.

(150) This may occur in a circuit pattern of an outermost layer of the circuit board including the circuit pattern manufactured by the SAP method.

(151) In contrast, a primer layer **150** is disposed on the eighth insulating layer **118** of the embodiment, and a second outer layer circuit pattern **140** is disposed on the primer layer **150**.

(152) In addition, first to third parts of the solder resist **160** serving as a support layer and a protective layer are disposed on the primer layer **150** while surrounding the second outer layer circuit pattern **140**.

(153) In this case, the solder resist **160** may be disposed on the first region R1, the second region R2, and the third region R3. The solder resist **160** may support the second outer layer circuit pattern **140** disposed on the outermost layer of the circuit board **100**, and in particular, the solder resist **160** supports the trace **141a** and the first pad **142** of the second outer layer circuit pattern **140** disposed in the first region R1. Accordingly, the second outer layer circuit pattern **140** may be protected from external impact.

(154) Meanwhile, as described above, in the embodiment, a residual resin removal process is performed by performing an etching process on the second outer layer circuit pattern **140** exposed through the first region R1 and the second region R2. Accordingly, the second trace **141b** disposed in the third region R3 and the first trace **141a** disposed in the first region R1 have different heights.

(155) At this time, the etching should not cause deformation of the second outer layer circuit pattern **140** while completely removing the residual resin. That is, if a degree of etching is insufficient, residual resin may exist on the surface of the second outer layer circuit pattern **140** despite the progress of the etching. In addition, if the degree of etching is excessive, deformation (eg, surface crushing, etc.) of the second outer layer circuit pattern **140** may occur due to the etching, and thus a reliability problem may occur.

(156) FIGS. 7 and 8 are views showing a degree of residual resin according to a degree of etching.

(157) Referring to FIG. 7, FIG. 7 (a) is a view showing a surface of the second outer layer circuit pattern **140** after etching under a first condition. FIG. 7 (b) is an enlarged view of FIG. 7(a). Specifically, FIGS. 7 (a) and (b) are views showing a surface of the second outer layer circuit

pattern **140** in the case where a height of about 0.5 μm is etched.

(158) At this time, even after etching the surface of the second outer layer circuit pattern **140** by about 0.5 μm , it was confirmed that residual resin remained on the surface of the second outer layer circuit pattern **140**.

(159) That is, surface properties of the second outer layer circuit patterns **140** after etching the second outer layer circuit patterns **140** under the first condition are shown in Table 1 below.

(160) TABLE-US-00001 TABLE 1 elements Wt % C 20.41 N 2.02 Cl 2.23 Cu 74.44

(161) As shown in Table 1, the surface properties of the second outer layer circuit pattern **140** after etching with a height of 0.5 μm were confirmed to include less than 80 wt % of Cu. In addition, as shown in Table 1, it was confirmed that 20 wt % or more of C corresponding to the solder resist was present in the surface properties of the second outer layer circuit pattern **140** after etching with a height of 0.5 μm .

(162) Referring to FIG. 8, FIG. 8 (a) is a view showing a surface of the second outer layer circuit pattern **140** after etching under a second condition. FIG. 8 (b) is an enlarged view of FIG. 8 (a). Specifically, FIGS. 8 (a) and (b) are views showing the surface of the second outer layer circuit pattern **140** in the case where a height of about 0.75 μm to about 0.95 μm is etched.

(163) In this case, after etching the surface of the second outer layer circuit pattern **140** to a height of about 0.75 μm to 0.95 μm , it was confirmed that no residual resin remained on the surface of the second outer layer circuit pattern **140**.

(164) That is, surface properties of the second outer layer circuit pattern **140** after etching the second outer layer circuit pattern **140** under the second condition are as shown in Table 2 below.

(165) TABLE-US-00002 TABLE 2 Elements Wt % C 16.56 N 1.48 Cl 1.88 Cu 80.08

(166) As shown in Table 2, the surface properties of the second outer layer circuit pattern **140** after etching with a height of 0.75 μm to 0.95 μm were confirmed to include 80 wt % or more of Cu. In addition, as shown in Table 2, it was confirmed that the surface properties of the second outer layer circuit pattern **140** after etching with a height of 0.75 μm to 0.95 μm were such that C corresponding to the solder resist was present at 20 wt % or less. When the second outer layer circuit pattern **140** is etched to a height of 0.95 μm to 0.95 μm , it means that the resin remaining on the surface of the second outer layer circuit pattern **140** is completely removed.

(167) Here, in Table 2, it has been described that the second outer layer circuit pattern **140** is etched at a height of 0.75 μm to 0.95 μm , and this may be substantially determined by the height of the second outer layer circuit pattern **140** initially formed. That is, the etching degree may progress to a height of 5% to 10% of the initially formed second outer layer circuit pattern **140**.

(168) FIG. 9 is a view showing a shape according to an etching state of a second outer layer circuit pattern according to an embodiment.

(169) Referring to FIG. 9, FIG. 9 (a) shows a shape change of trace **141** after etching to about 0.5 μm , and FIG. 9 (b) shows a shape change of trace **141** after etching to about 0.75 μm to 0.95 μm .

(170) As shown in FIG. 8, even after the trace **141** is etched to a height of about 0.75 μm to 0.95 μm , although a change in the shape of the surface occurred, it was confirmed that there was no problem in reliability, and it was confirmed that the resin remaining on the surface was also completely removed.

(171) FIGS. 10 to 17 are views showing a method of manufacturing the circuit board shown in FIG. 2 in order of process.

(172) Referring to FIG. 10, in the embodiment, first, a process of manufacturing an inner substrate **100-1** for manufacturing an inner portion of the circuit board **100** may be performed.

(173) The process for manufacturing the inner layer substrate **100-1** will be briefly described.

(174) The inner layer substrate **100-1** may include one insulating layer, or alternatively, a plurality of insulating layers.

(175) It is illustrated in FIG. 10 that the inner-layer substrate **100-1** has an insulating layer structure with seven layers, but the embodiment is not limited thereto. For example, the inner layer substrate

100-1 may include an insulating layer less than seven layers, or alternatively, more than seven layers.

(176) The inner layer substrate **100-1** may include remaining insulating layers excluding an insulating layer disposed on an outermost layer of the circuit board **100**. For example, the inner layer substrate **100-1** may include an insulating layer disposed on an uppermost portion of the circuit board **100** and remaining insulating layers excluding an insulating layer disposed on a lowermost portion of the circuit board **100**.

(177) Briefly describing the process of manufacturing the inner layer substrate **100-1**, first, the first insulating layer **111** is prepared.

(178) Then, when the first insulating layer **111** is prepared, a first via **V1** is formed in the first insulating layer **111**, and a circuit pattern **121** and a second circuit pattern **122** are formed on upper and lower surfaces of the first insulating layer **111**, respectively.

(179) Thereafter, a second insulating layer **112** is formed on the first insulating layer **111**, and a third insulating layer **113** is formed under the first insulating layer **111**.

(180) Next, a second via **V2** is formed in the second insulating layer **112**, and a third circuit pattern **123** is formed on an upper surface of the second insulating layer **112**.

(181) In addition, a third via **V3** is formed in the third insulating layer **113**, and a fourth circuit pattern **124** is formed under a lower surface of the third insulating layer **113**.

(182) Thereafter, a fourth insulating layer **114** is formed on the second insulating layer **112**, and a fifth insulating layer **115** is formed under the third insulating layer **113**.

(183) Next, a fourth via **V4** is formed in the fourth insulating layer **114**, and a fifth circuit pattern **125** is formed on an upper surface of the fourth insulating layer **114**. In addition, a fifth via **V5** is formed in the fifth insulating layer **115**, and a sixth circuit pattern **126** is formed under a lower surface of the fifth insulating layer **115**.

(184) Thereafter, a sixth insulating layer **116** is formed on the fourth insulating layer **114**, and a seventh insulating layer **117** is formed under the fifth insulating layer **115**.

(185) Next, a sixth via **V6** is formed in the sixth insulating layer **116**, and a seventh circuit pattern **127** is formed on an upper surface of the sixth insulating layer **116**. In addition, a seventh via **V7** is formed in the seventh insulating layer **117**, and an eighth circuit pattern **128** is formed under a lower surface of the seventh insulating layer **117**.

(186) Since the process of manufacturing the inner layer substrate **100-1** is a known technique in a technical field to which the present invention pertains, a detailed description thereof will be omitted.

(187) Referring to FIG. **11**, when the inner layer substrate **100-1** is manufactured, an eighth insulating layer **118** corresponding to a first outermost insulating layer is formed on an upper surface of the inner layer substrate **100-1**. In addition, a ninth insulating layer **119** corresponding to a second outermost insulating layer is formed under a lower surface of the inner layer substrate **100-1**.

(188) In this case, when the eighth insulating layer **118** and the ninth insulating layer **119** are stacked, a primer layer **150** may be respectively disposed on the upper surface of the eighth insulating layer **118** and the lower surface of the ninth insulating layer **119**, and a metal layer **155** may be disposed on the primer layer **150**. The metal layer **155** may serve to planarize the eighth insulating layer **118** and the ninth insulating layer **119** to have uniform heights. For example, the metal layer **155** may be disposed in order to improve stacking reliability of the eighth insulating layer **118** and the ninth insulating layer **119**.

(189) The primer layer **150** may serve to increase bonding force between a first outer layer circuit pattern **130** and a second outer layer circuit pattern **140** that are disposed on and under the eighth insulating layer **118** and the ninth insulating layer **119**, respectively. That is, when the first outer layer circuit pattern **130** and the second outer layer circuit pattern **140** are disposed without the primer layer **150**, the bonding force between the eighth insulating layer **118** and the second outer

layer circuit pattern **140** is low, and thus they may be separated from each other.

(190) Meanwhile, it is illustrated in FIG. **11** that the primer layer **150** is respectively disposed on the upper surface of the eighth insulating layer **118** and the lower surface of the ninth insulating layer **119**, but the embodiment is not limited thereto. For example, the primer layer **150** may be selectively disposed on a surface of an insulating layer on which a fine circuit pattern is to be disposed. That is, when only the first outer layer circuit pattern **130** is a fine circuit pattern, the primer layer **150** may be disposed only on the lower surface of the ninth insulating layer **119**. In addition, when only the second outer layer circuit pattern **140** is a fine circuit pattern, the primer layer **150** may be disposed only on the upper surface of the eighth insulating layer **118**. In addition, when the first outer layer circuit pattern **130** and the second outer layer circuit pattern **140** are both fine circuit patterns, the primer layer **150** may be disposed on both the upper surface of the eighth insulating layer **118** and the lower surface of the ninth insulating layer **119**.

(191) Referring to FIG. **12**, when the eighth insulating layer **118** and the ninth insulating layer **119** are disposed, a via hole VH is respectively formed in the eighth insulating layer **118** and the ninth insulating layer **119**. In this case, the via hole VH may be respectively formed not only in the eighth insulating layer **118** and the ninth insulating layer **119** but also in the primer layer **150** and the metal layer **155**.

(192) Next, referring to FIG. **13**, when the via hole VH is formed, an etching process of removing the metal layer **155** disposed on the primer layer **150** may be performed. For example, after the via hole VH is formed, a flash etching process may be performed to remove the metal layer **155**, and thus a process for exposing a surface of the primer layer **150** may be performed.

(193) Next, referring to FIG. **14**, a via V forming process for filling the via hole VH may be performed, and thus the second outer layer circuit pattern **140** may be formed on the upper surface of the eighth insulating layer **118**, and the lower outer layer circuit pattern **130** may be formed on the lower surface of the ninth insulating layer **119**. In this case, in the embodiment, it is illustrated that the first outer layer circuit pattern **130** is a general circuit pattern rather than a fine circuit pattern, but the embodiment is not limited thereto, and the first outer layer circuit pattern **130** together with the second outer layer circuit pattern may be a fine circuit pattern. Accordingly, when the first outer layer circuit pattern **130** is a general circuit pattern, the primer layer **150** between the ninth insulating layer **119** and the first outer layer circuit pattern **130** may be omitted.

(194) An upper outer layer circuit pattern **140** is disposed on the upper surface of the eighth insulating layer **118**. In this case, the upper outer layer circuit pattern **140** disposed on the upper surface of the eighth insulating layer **118** includes a portion disposed in the open region R1 and R2 of the first protective layer **170** and a portion disposed in an arrangement region R3 of the first protective layer **170**. In addition, traces and pads, which are wiring lines for signal transmission, may be disposed in each of the regions R1, R2 and R3.

(195) In detail, the trace **141** and the first pad **142** may be disposed in the first region R1. The first pad **142** may be a mounting pad on which a device is mounted.

(196) In addition, a second pad **143** may be disposed in a second region R2. The second pad **143** may be a BGA pad or a core pad. In particular, the second pad **143** may have a greater width than the first pad **142**. Therefore, the second pad **143** is not greatly affected by a development resolution, and accordingly, a solder resist **170** having a shape different from that of the solder resist **170** disposed in the first region R1 may be disposed.

(197) Meanwhile, the trace **141** may include a first trace **141a** disposed in the first region R1 and a second trace **141b** disposed in the second region R2.

(198) Next, referring to FIG. **15**, a solder resist layer is disposed on the primer layer **150** to cover the upper outer layer circuit pattern **140**. In this case, the solder resist layer may be disposed in both the first region R1, the second region R2 and the third region R3 and may be formed to have a height greater than that of the upper outer layer circuit pattern **140**.

(199) Referring to FIG. **16**, when the solder resist layer is formed, the solder resist layer may be

exposed and developed to form solder resists **160** having different heights for each region. Preferably, the embodiment exposes a part of the second region **R2** and the whole of the third region **R3** of the solder resist layer, and accordingly, a process of developing the entire first region **R1** and a portion of the second region **R2** of the solder resist layer may be performed.

(200) To this end, UV exposure is performed by masking only a desired region on the solder resist layer, and then the solder resist **160** may be formed by performing a process of adjusting the height of the solder resist layer in an unexposed region by dipping in an organic alkaline compound containing tetramethylammonium hydroxide (TMAH) or trimethyl-2-hydroxyethylammonium hydroxide (choline), etc. In this case, a height of the solder resist layer in the second region **R2** may be adjusted based on a height of the second outer layer circuit pattern **140**. For example, a height of the solder resist layer in the second region **R2** may be 70% to 85% of a height of the second outer layer circuit pattern **140**.

(201) Next, referring to FIG. **17**, a process of etching the first trace **141a** and the first pad **142** disposed in the first region **R1** and the second pad **143** disposed in the second region **R2** may be performed. The etching process may be a process of removing resin remaining on surfaces of the first trace **141a**, the first pad **142**, and the second pad **143**.

(202) The characteristics, structures, effects, and the like described in the above-described embodiments are included in at least one embodiment, but are not limited to only one embodiment. Furthermore, the characteristic, structure, and effect illustrated in each embodiment may be combined or modified for other embodiments by a person skilled in the art. Therefore, it should be construed that contents related to such combination and modification are included in the scope of the embodiment.

(203) Embodiments are mostly described above, but the embodiments are merely examples and do not limit the embodiments, and a person skilled in the art may appreciate that several variations and applications not presented above may be made without departing from the essential characteristic of embodiments. For example, each component specifically represented in the embodiments may be varied. In addition, it should be construed that differences related to such a variation and such an application are included in the scope of the embodiment defined in the following claims.

Claims

1. A circuit board comprising: a build-up insulating layer including a plurality of insulating layers laminated along a vertical direction; a circuit layer disposed on the build-up insulating layer; and a protective layer disposed on the circuit layer and including a first region having a first thickness in the vertical direction and a second region having a second thickness greater than the first thickness in the vertical direction, wherein the circuit layer includes a first circuit pattern passing through the first region of the protective layer and a second circuit pattern disposed in the second region of the protective layer, wherein the protective layer includes a through hole passing through the second region, wherein the second circuit pattern includes a pad part overlapping the through hole along the vertical direction, wherein an upper surface of the pad part includes a first portion overlapping the through hole along the vertical direction and a second portion connected to the first portion and not overlapping the through hole along the vertical direction, and wherein a height of the first portion of the pad part is same as a height of the first circuit pattern; wherein the upper surface of the pad part has a step, and the upper surface of the first circuit pattern does not have a step.
2. The circuit board of claim 1, wherein a height of the second portion of the pad part is greater than the height of the upper surface of the first circuit pattern based on the build-up insulating layer.
3. The circuit board of claim 1, wherein the second circuit pattern further includes an embedded pattern embedded in the second region of the protective layer without overlapping the through hole along the vertical direction.
4. The circuit board of claim 3, wherein an upper surface of the embedded pattern does not have a

- step.
5. The circuit board of claim 4, wherein a height of an upper surface of the embedded pattern is same as a height of the second portion of the pad part.
 6. The circuit board of claim 4, wherein a height of an upper surface of the embedded pattern is greater than the height of the upper surface of the first circuit pattern based on the build-up insulating layer.
 7. The circuit board of claim 4, wherein a height of an upper surface of the embedded pattern is greater than the height of the first portion of the pad part based on the build-up insulating layer.
 8. The circuit board of claim 3, wherein a thickness of the first circuit pattern embedded pattern is satisfies a range of 90% to 95% of a thickness of the embedded pattern.
 9. The circuit board of claim 1, wherein a thickness of the first region of the protective layer satisfies a range of 70% to 85% of a thickness of the first pattern.
 10. The circuit board of claim 1, wherein a surface roughness of an upper surface of the first region of the protective layer is greater than a surface roughness of an upper surface of the second region of the protective layer.
-