

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250281190

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Baker; Charles A. et al.

---

## STONE FRAGMENT CAPTURE SYSTEMS FOR LITHOTRIPSY SYSTEMS

---

### Abstract

A lithotripsy device can comprise a handpiece, a lithotripsy probe extending from the handpiece, an energization source configured to deliver an energy to a distal end of the lithotripsy probe, a suction passage extending from the distal end of the probe and through the handpiece, and a capture device comprising a container comprising a storage space, an entry port configured to couple to the handpiece at the suction passage, and an exit port, and a capture element connected to the container and configured to facilitate capture of stone fragments within the storage space. A method can comprise fragmenting stones with a lithotripsy device, drawing a vacuum through the lithotripsy device to pull stone fragments and waste fluid therethrough, pulling the vacuum through a stone capture device connected to the lithotripsy device, depositing stone fragments within the stone capture device using a capture element, and drawing the vacuum through the device.

---

**Inventors:** Baker; Charles A. (Rogers, MN), Bloem; David (Maple Grove, MN), Braga; Richard M. (North Easton, MA), Bertelson; Arthur J. (Buffalo, MN), Schneider; Brian J. (Durham, NH)

**Applicant:** GYRUS ACMI, INC. D/B/A OLYMPUS SURGICAL TECHNOLOGIES AMERICA (Westborough, MA)

**Family ID:** 1000008618279

**Appl. No.:** 19/213256

**Filed:** May 20, 2025

### Related U.S. Application Data

parent US continuation 18417387 20240119 parent-grant-document US 12329398 child US 19213256

parent US continuation 17400499 20210812 parent-grant-document US 11911053 child US

## Publication Classification

**Int. Cl.:** **A61B17/22** (20060101); **A61B17/00** (20060101); **A61M1/00** (20060101); **A61M39/06** (20060101); **A61M39/12** (20060101)

**U.S. Cl.:**

**CPC** **A61B17/22** (20130101); **A61M1/60** (20210501); **A61M1/79** (20210501); **A61M39/06** (20130101); **A61M39/12** (20130101); A61B2017/0034 (20130101); A61B2017/22014 (20130101); A61B2017/22079 (20130101); A61B2217/005 (20130101); A61M2039/0666 (20130101)

---

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a Continuation of U.S. patent application Ser. No. 17/400,499, filed Aug. 12, 2021, which claims the benefit of priority to U.S. Provisional Patent Application Ser. No. 63/065,958, filed Aug. 14, 2020, the contents of which are incorporated herein by reference in their entireties.

### TECHNICAL FIELD

[0002] The present disclosure relates generally to medical devices that can be used to break obstructions, such as physiological calculi or “stones” using lithotripsy.

[0003] More specifically, the present disclosure relates to systems, devices and methods for capturing stone fragments from lithotripsy systems.

### BACKGROUND

[0004] Medical endoscopes were first developed in the early 1800s and have been used to inspect inside the body. A typical endoscope includes a distal end comprising an optical or electronic imaging system and a proximal end with controls for manipulating the tools and devices for viewing the image, with a solid or tubular elongate shaft connecting the ends. Some endoscopes allow a physician to pass tools or treatments down one or more hollow working channels, for example, to resect tissue or retrieve objects.

[0005] Over the past several decades, several advances have been made in the field of endoscopy, and in particular relating to the breaking up of physiologic calculi in the bile ducts, urinary tract, kidneys, and gall bladder. Physiological calculi in these regions may block ducts and cause a patient to experience a substantial amount of pain. Therefore, these calculi are typically broken down for surgical removal or biological passing. Different techniques and procedures have been developed to break up stones, including ultrasonic lithotripsy, pneumatic lithotripsy, electro-hydraulic lithotripsy (EHL), and laser lithotripsy including dissolution of calculi using green light, YAG, or holmium lasers.

### SUMMARY

[0006] The present inventors have recognized, among other things, that problems to be solved in performing lithotripsy procedures is the recovery of stone fragments from the patient during or after the procedure. Typically, stone fragments are removed from inside the patient via suction applied to a distal end of a lithotripsy device. The suction pulls the stone fragments proximally through a suction tube and, typically, deposits the fragments into a waste container, along with other fluids from the patient, such as biological fluid and lavage fluid. As such, stone fragments

typically comprise part of a mixture of materials located in a single container, thereby making retrieval of the stone fragments difficult. Retrieval of stone fragments can be desirable so that analysis can be performed. For example, doctors can view the stone fragments to prescribe diets to prevent future formation of stones or the stone fragments can be sent off to a laboratory for detailed composition analysis.

[0007] The present subject matter can provide solutions to this problem and other problems by providing stone fragment capture systems that collect stone fragments separately from other collected material, such as waste fluids. The stone fragment capture systems of the present disclosure can retrieve stone fragments from the flow of material being removed from the patient via suction. The stone fragments can be retained in a container that can hold the fragments for later retrieval and analysis pre-separated from waste fluids. In examples, the stone fragments can be stored in a sealed container for shipment to a laboratory without needing user intervention or repackaging.

[0008] The present inventors have also recognized, among other things, that problems to be solved in performing lithotripsy procedures is the possibility of a lithotripsy device becoming clogged with stones or stone fragments. If such scenarios arise, it can result in interruption of the procedure so that the device can be disassembled to clear the blockage. For example, the system can be shut down and the device disconnected, disassembled, cleared and reassembled, thereby resulting in increased frustration and length of the procedure, as well as associated costs of extended procedure times.

[0009] The present subject matter can provide solutions to this problem and other problems by providing a vacuum port on an attachment for a lithotripsy device that can permit clearing of a blockage within the lithotripsy device without disassembly of the lithotripsy device or shutting down of the lithotripsy system. The vacuum port can provide a sealable access port into the lithotripsy device to allow insertion of an instrument to clear the blockage without interruption of the lithotripsy system, thereby reducing downtime and frustration associated with disassembly and reassembly. In examples, the vacuum port attachment can be integrated into a stone fragment capture system.

[0010] In an example, a lithotripsy device can comprise a handpiece, a lithotripsy probe extending from the handpiece, an energization source coupled to the handpiece configured to deliver an energy to a distal end of the lithotripsy probe, a suction passage extending from the distal end of the probe and through the handpiece, and a capture device coupled to the handpiece that can comprise a container comprising a storage space within the container, an entry port configured to couple to the handpiece at the suction passage, and an exit port, and a capture element connected to the container and configured to facilitate capture of stone fragments within the storage space.

[0011] In another example, a method of retrieving stone fragments from a lithotripsy procedure can comprise fragmenting stones with a lithotripsy device, drawing a vacuum through the lithotripsy device to pull stone fragments and waste fluid through the lithotripsy device, pulling the vacuum through a stone capture device connected to the lithotripsy device, depositing stone fragments within the stone capture device using a capture element, and continuing to draw the vacuum to deposit the waste fluid in a waste container.

[0012] In an additional example, a capture device for collecting fragments generated during lithotripsy can comprise a container comprising a wall defining a storage space within the container, an entry port coupled to the wall and configured to couple to the handpiece at the suction passage, and an exit port coupled to the wall, a capture element connected to the container and configured to facilitate capture of stone fragments within the storage space, and a coupler for connecting the container to a handpiece of a lithotripsy device.

[0013] This overview is intended to provide an overview of subject matter of the present patent application. It is not intended to provide an exclusive or exhaustive explanation of the invention.

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0014] FIG. 1 is an isometric view of an illustration of an exemplary lithotripsy system with which the various stone fragment capture devices and systems of the present disclosure can be used.

[0015] FIG. 2 is a perspective view of a lithotripsy system comprising a hand-held probe configured to deliver high frequency and ultrasonic energy for the fragmentation of stones.

[0016] FIG. 3 is a schematic cross-sectional illustration of a first example of a stone fragment capture system comprising a valve and filter for use with a stone fragmentation system, such as the lithotripsy systems described herein.

[0017] FIG. 4A is a side view of a valve for use with the stone fragment capture system of FIG. 3 comprising a biased stop.

[0018] FIG. 4B is a cross-sectional view of the valve of FIG. 4A showing support struts for the biased stop with windows to allow for the passage of stones.

[0019] FIG. 5 is a schematic cross-sectional view of a second example of a stone fragment capture system comprising a flapper valve and a flow-restricting valve for use with a stone fragmentation system, such as the lithotripsy systems described herein.

[0020] FIGS. 6A and 6B are schematic perspective views of a flow-restricting valve comprising an adjustable mesh valve suitable for use with the stone fragment capture system of FIG. 5.

[0021] FIGS. 7A-7C comprise schematic top views of the adjustable mesh valve of FIGS. 6A and 6B in large, medium and small opening configurations, respectively.

[0022] FIGS. 8A and 8B are schematic top views of a flow-restricting valve comprising an iris valve in closed and open configurations, respectively, suitable for use with the stone fragment capture system of FIG. 5.

[0023] FIG. 9 is a schematic cross-sectional view of a third example of a stone fragment capture system comprising a cartridge and chassis assembly for use with a stone fragmentation system, such as the lithotripsy systems described herein.

[0024] FIG. 10 is a schematic cross-sectional view of the chassis of FIG. 9 with the cartridge removed.

[0025] FIG. 11 is a schematic cross-sectional view of a valve of the chassis of FIG. 9 configured to interact with an actuator of the cartridge.

[0026] FIGS. 12, 13 and 14 comprise schematic illustrations of a spring valve, a pressure valve and a motorized valve suitable for use as the valve of FIG. 11.

[0027] FIG. 15 is a schematic cross-sectional view of a fourth example of a stone fragment capture system comprising a stone capture with a vacuum port for use with a stone fragmentation system, such as the lithotripsy systems described herein.

[0028] FIG. 16 is a schematic top view of the stone capture of FIG. 15 showing a position of an outlet relative to an inlet and the vacuum port.

[0029] FIG. 17 is a schematic cross-sectional view of a distal tip of the probe of FIG. 2 showing a flow restriction configured to size-limit entry of stones into the probe.

[0030] FIG. 18 is a flow chart illustrating a method for retrieving stone fragments from a lithotripsy procedure using the devices and stone fragment capture systems of the present disclosure.

[0031] In the drawings, which are not necessarily drawn to scale, like numerals may describe similar components in different views. Like numerals having different letter suffixes may represent different instances of similar components. The drawings illustrate generally, by way of example, but not by way of limitation, various embodiments discussed in the present document.

## DETAILED DESCRIPTION

[0032] The present disclosure provides examples of devices, systems and methods that can help address problems associated with fragmenting stones and collecting stone fragments during lithotripsy procedures. In particular, the present disclosure provides examples of devices, systems and methods that can be used to retrieve stone fragments from the collection process for later analysis. Typically, collection of stone fragments for later analysis can be challenging due to the stone fragments being simultaneously collected with other fluids of the procedure, thereby requiring subsequent processing, such as separating and repackaging. Benefits of the approaches described herein include, among other things, capturing stone fragments in a container separately from waste fluid, thereby reducing post-processing procedures and times. The stone fragments can thus be pre-separated from the waste fluid and stored in a container that can be used to store or ship the stone fragments. Furthermore, the stone fragment capture devices described herein can include a vacuum port that allows access for unclogging of a lithotripsy device without the need for disassembly of the lithotripsy device.

[0033] FIG. 1 illustrates an isometric view of an example of lithotripsy system **100** including lithotripter **102** having housing **104**, such as a handle. Lithotripter **102** can include delivery member **106** that is deliverable to a treatment site through working channel WC of endoscope E. Endoscope E can also include light source LS and camera C.

[0034] Delivery member **106** can include flexible or rigid elongate shaft **108** having a tubular structure. Suitable materials for the delivery member include, but are not limited to, polytetrafluoroethylene (“PTFE”), polyethylenes (“PE”) and polyamides. Elongate shaft **108** can include outer surface **110** and at least one lumen **112** extending therethrough, the lumen being suitable for passage of components and materials that communicate with end effectors described herein.

[0035] Delivery member **106** can include an end effector such as probe **114** at a distal end that is deliverable to a treatment site. Probe **114** can be configured to deliver energy to fragment a mobile calculus such as a stone located in a bile duct, urinary tract, kidney or gall bladder. Probe **114** of lithotripter **102** can be introduced into a patient, driven by delivery member **106** through working channel WC of endoscope E or similar instrument. Probe **114** can be flexible or rigid.

[0036] Lithotripter **102** can be connected to signal generator **116**. Signal generator **116** can include power source **118** or can be couplable to an external power source. Signal generator **116** can also include input **120** to receive an instruction from an operator, and may include controller **122** having processing circuitry for determining actions based on operator input and for sending control signals via output **124** for communication to lithotripter **102**. Signal generator **116** can produce signals and send them to probe **114** of lithotripter **102** to cause probe **114** to emit acoustic energy. Acoustic energy can include sound waves, sonic waves, ultrasonic waves or shock waves, or any combination of these. Acoustic energy can be delivered to stone S to deteriorate, crack and thereby fracture stone S. The examples herein are described with reference to combinations of ultrasonic and shock wave applications but any suitable acoustic energy, or combinations thereof, for fracturing stones can be provided. The terms sonic and ultrasonic may be used herein interchangeably, and can include any suitable acoustic energy for fragmenting stones.

[0037] Features of probe **114** can provide improved fragmenting of stone S. For example, probe **114** can include drill **126** (which need not include a rotating drill bit), such as an ultrasonic drill that emits acoustic energy, in longitudinal direction A1, to drill a hole in the stone. Probe **114** can also include one or more lateral emitters **128** such as a lateral ultrasonic transducer to deliver acoustic energy inside the hole to fragment the stone from the inside out.

[0038] Drill **126** can be coupled to elongate shaft **108** and can be located at a distal tip of probe **114**. Drill **126** can include at least a portion that extends distal of elongate shaft **108**. In the example of FIG. 1, drill **126** can be configured to emit ultrasonic energy in longitudinal direction A1. Drill **126** can cause mechanical modification or destruction of stone S by producing pulsatile shock

waves that move generally along longitudinal direction A1. Drill **126** can be configured to drill a hole, such as a recess into, or passage P through, stone S. FIG. **1** shows an example including drill **126** that has drilled passage P through stone S.

[0039] Drill **126** can be an ultrasonic emitter that receives ultrasonic energy from remotely located ultrasonic transducer **136**, which will be referred to as drill transducer **136** for the purposes of clarity over other emitters and transducers in this disclosure. Drill transducer **136** can be located, for example, in housing **104** of lithotripter **102**. Drill transducer **136** can transmit ultrasonic energy in generally longitudinal direction A1, distally out of housing **104**. Ultrasonic energy can be transmitted from drill transducer **136** to drill **126** via ultrasound transmission member **138**.

Ultrasound transmission member **138** can be coupled to drill transducer **136** at a proximal end and to drill **126** at the distal end. Ultrasound transmission member **138** can be formed of any material that is capable of transmitting the ultrasound energy from drill transducer **136** to drill **126**, including but not limited to metal, metal alloys, shape memory alloys, polymers, ceramics, fibers, crystals or composites thereof.

[0040] Drill transducer **136** can be electrically couplable to signal generator **116**, such as by connector **140**, to receive signals for operating drill **126**. Drill transducer **136** can be actuated by, for example, an operator depressing foot pedal **132** that is in electrical communication with signal generator **116**, or can be actuated by drill actuator **134** coupled to housing **104** that is in electrical communication with signal generator **116**. Additionally or alternatively, the drill transducer **136** may be operated based on the input **120** from the operator and/or the actions determined by the controller **122**. Any other suitable actuator for controlling activation of drill **126** can be provided.

[0041] Although drill **126** is described as an ultrasonic drill, in some examples, other types of drills may be provided, including but not limited to, a rotational drill operated by a motor. Like the drill transducer in the example of FIG. **1**, the motor can be located remotely of probe **114**, such as in housing **104**, and the motor can be coupled to drill **126** via a rotational transmission member. In other words, in a variation on the example of FIG. **1**, a rotational motor can be provided in place of drill transducer **136**, and a rotational transmission member can be provided in place of ultrasound transmission member **138**.

[0042] In addition to using an ultrasonic emitter for drilling, probe **114** can include at least one radial or lateral ultrasonic emitter **128** configured to direct ultrasonic energy in radial or lateral direction A2, outward and away from longitudinal direction A1 such as toward an internal surface (passage P) of stone S. In the example of FIG. **1**, the at least one lateral ultrasonic emitter **128** includes a plurality or array of lateral ultrasonic emitters **128**.

[0043] Each of lateral ultrasonic emitters **128** can direct ultrasonic energy in lateral direction A2, with each of lateral ultrasonic emitters **128** located along a different longitudinal position on probe **114**. In some examples lateral ultrasonic emitters **128** can be spaced apart along longitudinal direction A1. Lateral ultrasonic emitters **128** can extend laterally or radially around probe **114**. In some examples, lateral ultrasonic emitters **128** can extend around the entire three-hundred-sixty degree circumference of probe **114**, or around a perimeter of probe **114** when a probe has a non-circular cross-section in direction lateral or perpendicular A1 to longitudinal direction A1. In other examples, lateral ultrasonic emitters **128** can only partially wrap around probe **114**.

[0044] Lateral ultrasonic emitters **128** can be located proximal of drill **126**. A benefit of this arrangement is that lateral ultrasonic emitter **128** can follow drill **126** so that after drill **126** prepares the passage P in stone S, lateral sonic emitter **128** can be advanced through passage P. When activated, such as by lateral emitter actuator **142** that is in electrical communication with lateral ultrasonic emitters **128** via electrical element **144** such as a wire, lateral ultrasonic emitters **128** can be configured to emit ultrasonic energy into to passage P and internal to stone S to fracture stone S from the inside of stone S.

[0045] Similar to drill transducer **136**, lateral ultrasonic emitter **128** can include an ultrasonic or other acoustic transducer. An electrical-to-acoustic transducer is a component that can convert an

electrical signal into variations in a physical quantity such as sound waves or pressure. Ultrasonic transducers can include linear piezoelectric stacks having piezoelectric elements located between two metal plates. In additional examples, magneto-restrictive stacks can be used. Such piezoelectric elements can convert electrical energy (e.g., electric current) into mechanical energy (e.g., sound waves, sonic waves, ultrasonic waves, shock waves). Piezoelectric elements can include crystal, such as quartz, having physical characteristics that results in the crystal undergoing mechanical stress when subjected to an electric field that causes the crystal to change size or shape. The piezoelectric elements or alternatively expand and contract in response to an alternating electric field, such as can be supplied by signal generator **116**. This expansion and contraction can generate sound waves that can be delivered to stone **S** to fracture stone **S**.

[0046] To help locate stone **S** relatively stationary relative to working channel **WC** of endoscope **E** while drilling the hole, and relatively stationary to probe **114** (except for longitudinal **A1** movement of probe **114** through the stone), suction, as denoted by suction arrow **130**, can be applied through working channel **WC**. Suction **130** can cause Stone **S** to be “captured” by pulling stone **S** towards working channel **WC** and thus pulling stone **S** towards drill **126** of probe **114** for drilling. Upon fracturing of stone **S**, stone fragments can be suctioned into working channel **WC**.

[0047] Some lithotripsy systems described herein can include fluid input **166** for receiving fluid from fluid storage **FS** and delivering fluid to a treatment site. For example, irrigation fluid or lavage fluid can be transmitted through endoscope **E** or elongate shaft **108**. Typical stone fragment recovery systems involve simply collecting a mixture of solids and liquids retrieved from the patient while performing the procedure. For example, suction **130** can be applied at distal end of endoscope **E** or elongate shaft **108**, and a vacuum drawn therethrough to deposit, materials, e.g., stone fragments and waste fluid, into a waste container. In examples, tube **150** can be connected to housing **104** to fluidly couple a lumen extending through working channel **WC** of endoscope **E** with collection container **152**. Tube **150** can additionally be connected to suction device **154** or a pump to draw a vacuum through working channel **WC**, indicated with suction arrow **130**.

[0048] FIG. **2** is a perspective view of lithotripsy system **200** comprising hand-held probe **202** configured to deliver high frequency and ultrasonic energy for the fragmentation of stones. In examples, lithotripsy system **200** can comprise an oscillating lithotripter as is described in U.S. Pat. No. 9,974,552 to St. George et al. titled “Oscillating Lithotripter” and which is assigned to Gyrus ACMI, Inc., the contents of which is incorporated herein in its entirety.

[0049] Hand-held probe **202** can comprise handpiece or handle **204** and shaft **206**. Hand-held probe **202** can be connected to generator **208**, such as via cable **210**. Collection tube **212** can be connected to a storage container, such as fluid storage **FS** (FIG. **1**), to collect fluid and other biological material collected via shaft **206**. Shaft **206** can extend from proximal end **214** to distal end **216** and can comprise an internal lumen (e.g., lumen **532** of FIG. **17**). Handle **204** can further comprise buttons **218A** and **218B** to control activation energy and knob **220** to control suction level.

[0050] Handle **204** can comprise any device suitable for facilitating manipulation and operation of shaft **206**. Handle **204** can be located at proximal end **214** of shaft **206** or another suitable location along shaft **206**. In examples, handle **204** can comprise a pistol grip, a knob, a handlebar grip and the like. In addition to or alternatively to buttons **218A** and **218B** and knob **220**, handle **204** can comprise one or more of buttons, triggers, levers, knobs, dials and the like for control of energy activation, suction, irrigation and the like

[0051] In various examples, distal end **216** of shaft **206**, or another suitable location along shaft **16**, can include a surgical device, which can comprise a component or device for interacting with a patient, such as those configured to cut and cauterize tissue and/or produce a desired tissue effect of the patient. In examples, the surgical tool can comprise forceps, a cutting tool, an ablation electrode, a cryogenic needle or applicator, an ultrasonic probe tip and the like, and combinations thereof. As such, hand-held probe **202** can be provided with a linkage, such as a mechanical linkage

to actuate forceps or a cutting tool, an electrical linkage to activate an ablation electrode, an acoustic linkage, a liquid conduit (e.g., for the delivery of cryogenic argon gas) and the like, and combinations thereof. In examples, the surgical device can be included on a device used in conjunction with hand-held probe **202**. In additional examples, hand-held probe **202** can comprise, or can be combined with, a device for viewing the patient, such as optical devices including endoscopes (e.g., endoscope **E**, above) and fiberscopes.

[0052] Generator **208** can comprise a source of energy for hand-held probe **202**. For example, generator **208** can be configured to provide electricity for performing ablation and cauterizing functions and/or ultrasonic energy for providing cutting, coagulating, fragmenting or other types of surgical functions. In examples, generator **208** can provide ultrasonic wave energy, while intermittent ballistic shockwave energy is provided via an oscillating free mass within handle **204**.

[0053] Shaft **206** can comprise an elongate member configured to deliver energy for fragmenting stones into a patient. Shaft **206** can be rigid and formed from a metal or plastic material. In examples, shaft **206** can be sized for performing lithotripsy procedures in conjunction with an endoscope. As such, shaft **206** can be inserted into an incision in the epidermis of a patient, through a body cavity of the patient and into an organ. Thus, it is desirable for the diameter or cross-sectional shape of shaft **206** to be as small as possible to facilitate minimally invasive surgical procedures. However, shaft **206** can also incorporate a lumen (e.g., lumen **532** of FIG. **17**) to allow for removal, e.g., via suction, of fragments of stones produced by the fragmentation energy. As such, the size of shaft **206** and a lumen extending therethrough must be balanced to allow for minimal invasiveness and adequate removal of stone fragments. For example, too small of a lumen can increase the time it takes to fragment the stones into suitably small pieces.

[0054] Lithotripsy **100** of FIG. **1** and lithotripsy system **200** of FIG. **2** are examples of lithotripsy system that can be used with the stone fragment capture devices, systems and methods described herein. For example, a stone fragment capture device can be connected to housing **104** and tube **150** to collect stone fragments retrieved by lithotripter **102** and to facilitate unclogging of blockages that might form in lithotripter **102**. Likewise, a stone fragment capture device of the present disclosure can be connected to handle **204** and tube **212**. Although the present application is described with reference to lithotripsy systems used for retrieval of stones, other types of surgical devices and endoscopy devices can be used with stone fragment capture systems and methods disclosed herein. For example, any surgical device that can be configured for insertion into a patient that involves retrieval of biological matter along with waste fluid via suction can benefit from the present disclosure, such as forceps intended to remove endometrial tissue from a uterus. Examples of surgical devices that can be used with the present disclosure can utilize various energy sources, such as laser energy, ultrasound energy, and the like, for cracking, fragmenting, and/or dusting particles, such as stones and other solid or rigid bodies, and can perform evacuation of such particles after being broken down, such as by using a vacuum that pulls solids, liquids and mixtures into a designated collection receptacle.

[0055] FIG. **3** is a schematic cross-sectional illustration of stone fragment capture system **250** for use with stone fragmentation system **252** of FIG. **2**. Stone fragmentation system **252** can be used with lithotripsy system **100** of FIG. **1** that can deliver fragmentation energy radially along probe **114**, as well as stone lithotripsy system **200** of FIG. **2** that can deliver fragmentation energy longitudinally along shaft **206**. Stone fragment capture system **250** can comprise valve **254** and filter **256**, which can be coupled to container **258**. Container **258** can comprise housing **260**, cap **262**, inlet port **264**, outlet port **266** and baffles **267**.

[0056] Stone fragmentation system **252** can comprise any of the lithotripsy systems described herein, or another surgical system configured to generate suction therethrough. Stone fragmentation system **252** can comprise handle **268** and stem **270**. In examples, handle **268** can include knob **272** similar to knob **220** of FIG. **2** to control a function of stone fragmentation system **252**, such as suction level. Passage **274** can be configured to extend from handle **268**, such as from a shaft or



probe extending distally therefrom, and through knob 272 and stem 270 located at a proximal end. [0057] Container 258 can be coupled to handle 268 and tube 276. Housing 260 can be positioned such that inlet port 264 couples to stem 270. Stem 270 can comprise barb 278 that can be configured to facilitate attachment of container 258 to handle 268. For example, barb 278 can be a resilient rim extending around stem 270 that can have a diameter slightly larger than the inner diameter of stem inlet port 264. Inlet port 264 can comprise a cylindrical tube extending from floor 280 of housing 260. A tube forming inlet port 264 can be tapered to slow movement of fragments 284 entering container 258. Floor 280 can comprise an annular disk connecting inlet port 264 to housing 260. Likewise, outlet port 266 can comprise a cylindrical tube extending from cap 262. Cap 262 can comprise end plate 282, which can comprise an annular disk connecting outlet port 266 to cap 262. Cap 262 can be coupled to housing 260 via any suitable means, such as a threaded connection or a snap fit connection. In examples, tube 276 can be integral with outlet port 266, as illustrated. In other examples, tube 276 can be coupled to outlet port 266 via a barbed connection similar to barb 278. Although the illustrated example shows container 258 being coupled directly to stem 270 of handle 268, container 258 can additionally be coupled to handle 268 via a length of tubing that can couple around stem 270 and be inserted into inlet port 264, for example.

[0058] Container 258 can be positioned between handle 268 and tube 276 to capture stone fragments 284 leaving passage 274. Inlet port 264 can be configured to align with outlet port 266 along axis A3. However, in other examples, outlet port 266 can be offset from axis A3, as discussed below with reference to FIGS. 15 and 16. Stone fragments 284 can flow through passage 274 from handle 268 to stem 270. Stone fragments 284 can be dispersed into the interior of container 258, such as by using a capture element comprising one or more of a tube comprising inlet port 264, baffles 267 and filter 256. For example, stone fragments 284 can fall via gravity to floor 280. In examples, housing 260 can extend beyond tip 286 of inlet port 264 to provide clearance for stone fragments 284 to enter container 258. In examples, end plate 282 can be positioned a distance away from tip 286 to allow momentum of stone fragments 284 to dissipate. Additionally, baffles 267 can be positioned opposite tip 286 to deflect fragments 284 into housing 260. Baffles 267 can comprise various shaped bodies extending radially inward from walls of housing 260 or axially outward from inlet port 264 to obstruct outlet port 266 from direct impingement of fragments 284. Baffles 267 can deaden the momentum of fragments 284 to facilitate movement of fragments 284 out of the suction path, e.g., path of flowing liquid, between inlet port 264 and outlet port 266.

[0059] Filter 256 can be positioned in container 258 to prevent egress of stone fragments 284 from container 258. In the illustrated example, filter 256 is positioned in outlet port 266. However, filter 256 can be positioned anywhere in container 258 to block free entry of material into outlet port 266. In examples, filter 256 can be mounted to cap 262 to facilitate access of stone fragments 284 within container 258 when cap 262 is removed. However, filter 256 can be configured to itself be removable from housing 260 independent of cap 262. Filter 256 can be sized to permit liquid and small pieces of tissue or stone fragments and other debris to pass through container 258, but that prevents large pieces of matter to be retained within container 258. The capture elements described herein, filter 256 and other filter or orifice elements described herein (e.g., flow restricting valve 360 of FIGS. 8A and 8B) can be sized to retain pieces of matter or stone fragments that are suitable for further analysis, such as visual viewing for color and texture analysis.

[0060] Valve 254 can be positioned proximate tip 286 of stem 270 and can be used to intermittently close stem 270 to prevent egress of stone fragments 284 out of container 258. For example, when container 258 is removed from inlet port 264 and tube 276 is removed from cap 262, valve 254 can close to prevent stone fragments 284 from leaving container 258 at inlet port 264. Valve 254 can comprise any suitable device for allowing flow into housing 260 when container 258 is attached to stem 270 and preventing stone fragments from leaving housing 260 when container 258 is detached from handle 268. Valve 254 can be configured to be mechanically opened by engagement with stem 270 or by operation of a vacuum being pulled through container 258. As discussed with

reference to FIGS. 4A and 4B, valve 254 can comprise a biased stop.

[0061] FIG. 4A is a side perspective view of a first example of valve 254 for use with stone fragment capture system 250 of FIG. 3. In the illustrated example, valve 254 can comprise stop 290, resilient element 292, backstop 294, struts 296A-296H and support ring 298. FIG. 4B is a cross-sectional view of valve 254 of FIG. 4A taken at section 4B-4B to show support struts 296A-296H. FIGS. 4A and 4B are discussed concurrently. Struts 296A-296H can be connected to ring 298 at a first end and back stop 294 at a second end. Support ring 298 can be positioned around stem 270 to position backstop 294 to oppose the opening of inlet port 264 connecting to passage 274. Support ring 298 can be coupled to inlet port 264 using any suitable means, such as adhesive, fasteners or threaded fastening. Struts 296A-296H can be used to guide stop 290 into engagement with and away from tip 286. Stop 290 can comprise a circular or rectangular shape, or any suitable shape to close of inlet port 264. Stop 290 can include bores or notches to slide along struts 296A-296H, or can simply be guided between struts 296A-296H. When stone fragmentation system 252 is not operating, resilient element 292 can push against backstop 294 to push stop 290 against inlet port 264. As such, egress and ingress of material into container 258 can be prevented or inhibited. When stone fragmentation system 252 is operating, a vacuum can be drawn from tube 276 to pull stop 290 away from tip 286. As such, stone fragments 284 can flow out of inlet port 264 and between struts 296A-296H to enter container 258.

[0062] FIG. 5 is a schematic cross-sectional illustration of stone fragment capture system 300 for use with stone fragmentation system 252. Stone fragment capture system 300 can comprise valve 304 and filter 306, which can be coupled to container 308. Container 308 can comprise housing 310, cap 312, inlet 314 and outlet 316.

[0063] Stone fragment capture system 300 can be used with stone fragmentations systems described herein, such as stone fragmentation system 252, as well as other lithotripsy systems or another surgical system configured to generate suction therethrough. For example, inlet 314 can be connected to stem 270 such that passage 274 can connect to the interior of housing 310.

[0064] Container 308 can be coupled to handle 268 (FIG. 3) and tube 276 (FIG. 3). Housing 310 can be positioned such that inlet 314 couples to stem 270. Inlet 314 can comprise a cylindrical opening extending through floor 330 of housing 310. Inlet 314 can comprise a resilient material having an opening slightly smaller than the diameter of stem 270 such that a tight, sealed fit can be achieved therebetween. Floor 330 can comprise an annular disk or polygonal plate connecting inlet 314 to housing 310. Likewise, outlet 316 can comprise a cylindrical tube extending from cap 312. Cap 312 can comprise end plate 332, which can comprise an annular disk connecting outlet 316 to cap 312. Cap 312 can be coupled to housing 310 via any suitable means, such as a threaded connection or a snap fit connection. In examples, tube 276 can be integral with outlet 316. In other examples, tube 276 (FIG. 3) can be coupled to outlet 316 via a barbed connection similar to barb 278 (FIG. 3). Although the illustrated example shows container 308 being coupled directly to stem 270 of handle 268, container 308 can be additionally be coupled to handle 268 via a length of tubing that can couple around stem 270 and be inserted into inlet 314, for example.

[0065] Container 308 can be positioned between handle 268 and tube 276 to capture stone fragments 334 leaving passage 274. Inlet 314 can be configured to align with outlet 316 along axis A4. However, in other examples, outlet 316 can be offset from axis A4, as discussed below with reference to FIGS. 15 and 16. Stone fragments 334 can flow through passage 274 from handle 268 to stem 270. Stone fragments 334 can be dispersed into the interior of container 308. For example, stone fragments 334 can fall via gravity to floor 330. In examples, housing 310 can extend beyond tip 336 of stem 270 to provide clearance for stone fragments 334 to enter container 308. In examples, end plate 332 can be positioned a distance away from tip 336 to allow momentum of stone fragments 334 to dissipate. Container 308 can be provided with capture elements as described with reference to FIG. 3, such as an elongate tube extending from inlet 314 and baffles similar to baffles 267.

[0066] Valve **304** can be positioned proximate tip **336** of stem **270** and can be used to intermittently close stem **270** to prevent egress of stone fragments **334** out of container **308**. Valve **304** can comprise any suitable device for allowing flow into housing **310** when container **308** is attached to stem **270** and preventing stone fragments from leaving housing **310** when container **308** is detached from handle **268**. In the illustrated embodiment, valve **304** can comprise a flapper valve having stop **338**, resilient element **340** and sidewall **342**. Sidewall **342** can comprise a cylindrical body or tube having another cross-sectional shape to circumscribe stem **270**. Stop **338** can be pivotably coupled to sidewall **342** at coupling **344**, which can comprise a pinned coupling. As such, stop **338** can rotate about coupling **344** between engaging sidewall **342** and being positioned approximately parallel to the central axis of stem **270**. Resilient element **340** can bias stop **338** to a closed position in engagement with sidewall **342**. Resilient element **340** can comprise a spring, such as a butterfly spring that can push against sidewall **342** and stop **338** simultaneously. Valve **304** can be configured to be opened upon flow of material through container **308**, e.g., when a vacuum is pulled from outlet **316**.

[0067] As discussed in greater detail with reference to FIG. 6A-7C, filter **306** can be positioned in container **308** to prevent egress of stone fragments **334** from container **308**. Filter **306** can comprise a flow-restricting valve that can be adjusted to vary the size of stone fragments **334** that can be permitted to flow through stone fragment capture system **300**. For example, filter **306** can comprise opposing mesh layers **346A** and **346B**, the relative positions of which can be varied to adjust radial gap sizes between the mesh.

[0068] FIGS. 6A and 6B are schematic perspective views of filter **306** comprising a flow-restricting valve suitable for use with stone fragment capture system **500** of FIG. 5, as well as other systems described herein. Filter **306** can comprise opposing mesh layers **346A** and **346B**. Mesh in each of layers **346A** and **346B** can be oriented parallel to each other. For example, layer **346A** can include mesh strands **348A-348D**, and layer **346B** can comprise strands **350A-350D**. Layers **346A** and **346B** are described as having four strands of parallel mesh each, but can include any suitable number of strands to filter or inhibit flow of biological material. Strands **348A-348D** can be mounted to frame **352** and strands **350A-350D** can be mounted to frame **354**. Frames **352** and **354** can be connected by struts **356** such that frames **352** and **354** are rotatable relative to each other. One of frames **352** and **354** can be coupled to handle **358**. As shown in FIG. 6A, strands **348A-348D** and strands **350A-350D** are parallel to each other in horizontal positions (relative to the orientation of FIG. 6A). In FIG. 6B, frame **352** is rotated relative to frame **354** by handle **358** in a counter-clockwise direction such that strands **350A-350D** are in vertical positions (relative to the orientation of FIG. 6B) perpendicular to strands **348A-348D**.

[0069] FIGS. 7A-7C comprise schematic top views of mesh layers **346A** and **346B** of filter **306** in aligned, transverse and perpendicular alignments, respectively. Accordingly, radial spacing between strands (relative to a center axis of frame **354**, for example), such that strands **348A-348D** and strands **350A-350D** are arranged in large, medium and small spacing configurations.

[0070] In FIG. 7A, strands **348A-348D** and strands **350A-350D** are parallel to each other in vertical positions (relative to the orientation of FIG. 7A). As such, spacing **S1**, measured radially from the center of frame **354**, is at its largest. In FIG. 7B, strands **3450A-350D** are rotated approximately forty-five degrees clockwise relative to FIG. 7A. As such, spacing **S2**, measured radially from the center of frame **354**, is smaller than **S1**.

[0071] In FIG. 7C, strands **3450A-350D** are rotated approximately ninety degrees clockwise relative to FIG. 7A. As such, spacing **S3**, measured radially from the center of frame **354**, is smaller than **S2** and at its smallest.

[0072] Mesh layers **346A** and **346B** can be manually adjusted by a user of stone fragment capture system **500** to control the size of stone fragments desired to be captured by container **308**. For example, mesh layers **346A** and **346B** can be adjusted to the position of FIG. 7A to collect large fragments, such as might be useful if only a few fragments are desired for laboratory analysis.

However, mesh layers **346A** and **346B** can be adjusted to the position of **FIG. 7C** to collect only small fragments, such as might be useful if a large volume of fragments are desired for visual inspection.

[0073] **FIGS. 8A** and **8B** are schematic top views of flow-restricting valve **360** suitable for use with stone fragment capture system **300** of **FIG. 5**. Flow-restricting valve **360** can comprise an iris valve having shims **362A-362G**. **FIG. 8A** shows shims **362A-362G** in a closed configuration and **FIG. 8B** shows **362A-362G** in an open configuration. Shims **362A-362G** can be bound by frame **364**. Lever **366** can be connected to frame **364** to move shims **362A-362G** between open and closed positions. As shown in **FIG. 8A**, shims **362A-362G** can be positioned such that orifice **368** is small. Thus, flow-restricting valve **360** can be configured to minimize the amount of biological material that will pass through container **308**, thereby decreasing the size of stone fragments that will be retained in container **308**. As shown in **FIG. 8B**, shims **362A-362G** can be positioned such that orifice **368** is large. Thus, flow-restricting valve **360** can be configured to maximize the amount of biological material that will pass through container **308**, thereby increasing the size of stone fragments that will be retained in container **308**. Thus, an operator of stone fragment capture system **500** of **FIG. 5**, for example, can tune flow-restricting valve **360** to the desired size of stone fragments to be retained by container **308**. Shims **362A-362G** can be configured to operate as would be appreciated by one of skill in the art, such as by being pinned at their outer diameter ends proximate frame **36** and being connected to an outer diameter actuation mechanism that simultaneously rotates each of shims **362A-362G** at the pinned connection. In an example, flow-restricting valve **360** can be constructed similarly to an iris shutter similar to those used in cameras that is scaled-up in size and sturdiness for use in a pressurized environment as a flow control orifice.

[0074] **FIG. 9** is a schematic cross-sectional illustration of stone fragment capture system **400** for use with stone fragmentation system **252**, as well as other systems described herein. Stone fragment capture system **400** can comprise chassis **402** and cartridge **403**. Chassis **402** can comprise stem **404A**, stem **404B**, barb **406A**, barb **406B**, first valve **408A** and second valve **408B**. Cartridge **403** can comprise housing **410** and filter **412**.

[0075] Stone fragment capture system **400** can be coupled to tubes **414A** and **414B**. Stem **404A** can be configured to align with stem **404B** along axis **A5**. However, in other examples, stem **404B** can be offset from axis **A5**, as discussed below with reference to **FIGS. 15** and **16**. Tube **414A** can be connected to a fragmentation tool, such as handle **252**. Tube **414B** can be connected to a waste collection container and a vacuum generator, such as a pump.

[0076] Stone fragment capture system **300** can be used with stone fragmentations systems described herein, such as stone fragmentation system **252**, as well as other lithotripsy systems. For example, inlet **314** can be connected to stem **270** such that passage **274** can connect to the interior of housing **310**.

[0077] Stone fragment capture system **300** can be configured such that chassis **402** can remain connected to tubes **414A** and **414B**, while one or more cartridges **403** can be sequentially coupled to chassis **402**. Additionally, each cartridge **403** can comprise a self-sealing system such that upon removal from chassis **402**, each cartridge **403** is ready to be transported or shipped to a different location for storage and analysis. For example, valves **408A** and **408B** can be configured to open and close upon insertion and removal of cartridges **403** into chassis **402**, as discussed with reference to **FIGS. 11-14**.

[0078] Chassis **402** and cartridge **403** can be configured for use with different system or to collect different sized stone fragments. For example, chassis **402** can include stems **404A** and **404B** with different sizes such that different sized tubes **414A** and **414B** can be connected thereto. Also, cartridge **403** can be configured to have different grade filters **412**. Filter **412** can additionally comprise filter **306** of **FIG. 5** or flow-restricting valve **360** of **FIGS. 8A** and **8B**. As such, stone fragment capture system **300** can be configured to allow different size stone fragments to pass therethrough.

[0079] In examples, valves **408A** and **408B** can be attached to cartridge **403** and can be configured to open upon insertion of cartridge **403** into chassis **402** by engagement of valves **408A** and **408B** with actuators attached to chassis **402**.

[0080] In examples, valves **408A** and **408B** can be attached to chassis **402** and can be configured to open upon insertion of cartridge **403** into chassis **402** by engagement of valves **408A** and **408B** with actuators attached to cartridge **402**, as shown in FIG. **12**.

[0081] FIG. **10** is a schematic cross-sectional view of chassis **402** of FIG. **9** with cartridge **403** removed. Chassis **402** can be configured as a body to easily receive cartridge **403** to permit flow through cartridge **403** when cartridge **403** is seated within chassis **402**, and to allow flow around the space for cartridge **430** when cartridge **403** is removed from chassis **402**. Chassis **402** can comprise shell **432** having socket **432**, internal passage **434**, as well as valves **408A** and **408B**. Cartridge **403** can comprise actuators **436A** and **436B**. In an example, chassis **402** can comprise a half cylinder.

[0082] When cartridge **403** is not located in socket **432**, valves **408A** and **408B** can be configured to direct flow from stem **404A**, through valve **408A**, through internal passage **435**, through valve **408B** and into stem **404B**. When cartridge **403** is positioned in socket **432**, valves **408A** and **408B** can be configured to direct flow from stem **404A**, through valve **408A**, through cartridge **403**, through valve **408B** and into stem **404B**.

[0083] FIG. **11** is a schematic cross-sectional view of a valve **408B** of chassis **402** configured to interact with actuator **436B** of cartridge **403**. Valve **408B** can comprise flap **438** and hinge **440**. As shown in FIGS. **12-14**, flap **438** can be biased toward shell **432**. Cartridge **403** can be fit into socket **432** of chassis **402** such that actuator **436B** pushes against valve **408B**. Actuator **436B** can overcome bias applied to flap **438** by a biasing device. Thus, flow can be permitted through valve **408B** from within cartridge **403**. When flap **438** is closed, fluid can flow freely from internal passage **435** to stem **404B**. When flap **438** is opened, flap **438** can close off internal passage **435** such that fluid can flow freely from cartridge **403** to stem **404B**.

[0084] FIGS. **12**, **13** and **14** comprise schematic illustrations of spring valve **440**, pressure valve **442** and motorized valve **444** suitable for use as valve **408B** of FIG. **11**.

[0085] As shown in FIG. **12**, spring valve **440** can comprise flap **438** connected to shell **432** at hinge **440**, with flap **438** being biased by spring **446**. Spring **446** can be configured to push flap **438** against chassis **402** to close off flow through cartridge **403** and permit flow through internal passage **435**. Actuator **436B** can be configured to engage flap **438** to push flap **438** away from chassis **402**.

[0086] As shown in FIG. **13**, pressure valve **442** can comprise rod **448A**, dashpot **450** and rod **448B**. Rod **448A** can be attached to flap **438** at hinge **452A** and rod **448B** can be attached to shell **432** at hinge **452B**. Dashpot **450** can be configured to push flap **438** against chassis **402** to close off flow through cartridge **403** and permit flow through internal passage **435**. Actuator **436B** can be configured to engage flap **438** to push flap **438** away from chassis **402**.

[0087] As shown in FIG. **14**, motorized valve **444** can comprise motor **454**, which can be connected to flap **438** via linkage **456**. In additional examples, motor **454** can act as hinge **440** and can be directly coupled to flap **438**. Motor **454** can be configured to push flap **438** against chassis **402** to close off flow through cartridge **403** and permit flow through internal passage **435**. Actuator **436B** can be configured to engage flap **438** to push flap **438** away from chassis **402**.

[0088] FIG. **15** is a schematic cross-sectional view of stone fragment capture system **500** for use with stone fragmentation system **252**, as well as other systems described herein. Stone fragmentation system **252** can comprise any of the lithotripsy systems described herein and can comprise handle **204** and shaft **206**. Stone fragment capture system **500** can comprise stone capture device **502** with vacuum port **504**. Stone capture device **502** can comprise housing **506** comprising upper component **508A** and lower component **508B**, and coupler **510**. FIG. **16** is a schematic top view of stone capture device **502** of FIG. **15** showing a position of tube connector **512** relative to

coupler **510**. FIGS. **15** and **16** are discussed concurrently.

[0089] Stone fragment capture system **500** can comprise a system for catching stone fragments that simultaneously allows for access to the interior of handle **204** and shaft **206** via vacuum port **504**. Vacuum port **504** can comprise a sealable port that can be opened to allow for insertion of an instrument into handle **204** through stone capture device **502**. In examples, the sealable port can comprise a threaded port having a cap. In additional examples, the sealable port can comprise a self-sealing access point, such as an iris point entry system comprising a plurality of deflectable tabs that can abut or overlap each other in a non-deflected state to seal off an access point, but that can be bent or deflected away from each other to allow entry into the access point.

[0090] Vacuum port **504** and coupler **510** can be aligned along axis **A6** of hand-held probe **202**, along which shaft **206** and handle **204** extend. As such in the event of a blockage within handle **204** or shaft **206**, such as from a lodged stone fragment, a probe can be inserted into vacuum port **504** all the way toward distal tip **216** (FIG. **17**) of shaft **206** to push or otherwise dislodge the stone fragment or other obstruction.

[0091] Stone capture device **500** can function similarly to container **258** of FIG. **3**, container **308** of FIG. **5** or any of the other stone fragment captures systems described or contemplated herein. However, as shown in FIG. **16**, tube connector **512** can be positioned off of axis **A6** along axis **A7** to allow for vacuum port **504** to be axially aligned with coupler **510**. Vacuum port **504** can be integrated into container **258** of FIG. **3** and container **308** of FIG. **5** by offsetting outlet port **266** and outlet **316** from inlet port **264** and inlet **314**, respectively. For example, with reference to FIG. **3**, outlet port **266** can be offset from axis **A3** on **282** on end plate **282** closer to the sidewall of cap **262** to allow for positioning of an entry port, such as vacuum port **504**, to align with inlet port **264**. In such case, valve **254** can be omitted or can be configured as a two-way valve to allow flow in both direction when activated (e.g., sucked open by a vacuum to allow flow out or pushed open by a probe to allow clearance of a blockage). Similarly, chassis **402** of FIG. **10** can be modified accordingly to include a vacuum port.

[0092] Upper component **508A** and lower component **508B** can be releasably coupled to each other to allow for access to stone fragments captured therein. For example, upper component **508A** and lower component **508B** can be threadedly connected or can be connected by a snap-fit feature. Furthermore, a sealing member, such as an O-ring seal can be provided between upper component **508A** and lower component **508B**.

[0093] FIG. **17** is a schematic cross-sectional view of distal end **216** of shaft **206** of FIG. **2** showing a flow restriction **530** located in lumen **532** configured to size-limit entry of stones into shaft **206**. Flow restriction **530** can comprise a narrowing of lumen **532** by a ring-like or annular feature. Flow restriction **530** can define a maximize stone size that can be permitted through shaft **206**, which can be a stone size that is smaller than the narrowest passage through shaft **206** and handle **204**, thereby reducing the chances of a blockage forming in hand-held probe **202**. In examples, the inner diameter of flow restriction **530** can be larger than the maximum sized stone fragment desired to be collected in the stone fragment capture devices of the present disclosure.

[0094] FIG. **18** is a line diagram illustrating method **600** for retrieving stone fragments from a lithotripsy procedure using the devices and stone fragment capture systems of the present disclosure. Method **600** illustrates various exemplary steps of a stone fragment recovery process. Other steps as described herein can be included and some steps can be omitted. Additionally, the illustrated steps can be performed in a different order.

[0095] At step **602**, stones within a patient can be fragmented using a surgical device, such as one of the lithotripsy devices disclosed herein, e.g., lithotripter **102** and hand-held probe **202**.

[0096] At step **604**, valves, such as an inlet valve (e.g., valve **254**, valve **304**), of a stone fragment capture device can be opened, such as by the drawing of a vacuum through the medical device used in step **602**,

[0097] At step **606**, a stone fragment being pulled by the vacuum being drawn through the stone

fragment capture device can impact a capture element, such as a tapered tube (e.g., inlet port **264**), a filter (e.g., filter **256**, filter **306**), a valve (e.g., valve **254**, valve **304**), an orifice (e.g., flow restricting valve **360**) or a baffle (e.g., baffle **267**), within the stone fragment capture device. [0098] At step **608**, the stone fragment can be diverted out of a main flow of fluid through the stone fragment capture device to be deposited within a container (e.g., container **258**, container **308**) of the stone fragment capture device.

[0099] At step **610**, a blockage, if any, can be cleared from the surgical device, such as by extending a probe into the stone fragment capture device through a vacuum port (e.g., vacuum port **504**), through the stone fragment capture device and into a shaft of the surgical device to clear the blockage.

[0100] At step **612**, biological matter flowing through the stone fragment capture device can impact a filter (e.g., filter **256**, filter **306**) within the stone fragment capture device, thereby only allowing liquid and sufficiently small solids to pass therethrough.

[0101] At step **614**, a size of filtering capacity of the filter can be adjusted (e.g., by rotating handle **358** or handle **366**) to control the size of debris retained in the stone fragment capture device.

[0102] At step **616**, valves, such as an outlet valve (e.g., flow restricting valve **360**, valve **408B**), of the stone fragment capture device can be closed to retain stone fragments deposited therein.

[0103] At step **618**, a cartridge (e.g., cartridge **403**) of the stone fragment capture device holding the stone fragments can be removed from a chassis (e.g., chassis **402**) securing the stone fragment capture device to the surgical device.

[0104] At step **620**, the cartridge or other container holding the stone fragments can be opened (e.g., by removing cap **262** or cap **312** or separating components **508A** and **508B**) such that the stone fragments can be accessed, such as for analysis.

#### Various Notes and Examples

[0105] For the purposes of this disclosure, “proximal” refers to an end of the system that is closer the device operator during use, and “distal” refers to an end of the system that is distal, or further from the device operator during use.

[0106] The above detailed description includes references to the accompanying drawings, which form a part of the detailed description. The drawings show, by way of illustration, specific embodiments in which the invention can be practiced. These embodiments are also referred to herein as “examples.” Such examples can include elements in addition to those shown or described. However, the present inventor also contemplates examples in which only those elements shown or described are provided. Moreover, the present inventor also contemplates examples using any combination or permutation of those elements shown or described (or one or more aspects thereof), either with respect to a particular example (or one or more aspects thereof), or with respect to other examples (or one or more aspects thereof) shown or described herein.

[0107] In this document, the terms “a” or “an” are used, as is common in patent documents, to include one or more than one, independent of any other instances or usages of “at least one” or “one or more.” In this document, the term “or” is used to refer to a nonexclusive or, such that “A or B” includes “A but not B,” “B but not A,” and “A and B,” unless otherwise indicated. In this document, the terms “including” and “in which” are used as the plain-English equivalents of the respective terms “comprising” and “wherein.” Also, in the following claims, the terms “including” and “comprising” are open-ended, that is, a system, device, article, composition, formulation, or process that includes elements in addition to those listed after such a term in a claim are still deemed to fall within the scope of that claim. Moreover, in the following claims, the terms “first,” “second,” and “third,” etc. are used merely as labels, and are not intended to impose numerical requirements on their objects.

[0108] The above description is intended to be illustrative, and not restrictive. For example, the above-described examples (or one or more aspects thereof) may be used in combination with each other. Other embodiments can be used, such as by one of ordinary skill in the art upon reviewing

the above description. The Abstract is provided to comply with 37 C.F.R. § 1.72(b), to allow the reader to quickly ascertain the nature of the technical disclosure. It is submitted with the understanding that it will not be used to interpret or limit the scope or meaning of the claims. Also, in the above Detailed Description, various features may be grouped together to streamline the disclosure. This should not be interpreted as intending that an unclaimed disclosed feature is essential to any claim. Rather, inventive subject matter may lie in less than all features of a particular disclosed embodiment. Thus, the following claims are hereby incorporated into the Detailed Description as examples or embodiments, with each claim standing on its own as a separate embodiment, and it is contemplated that such embodiments can be combined with each other in various combinations or permutations. The scope of the invention should be determined with reference to the appended claims, along with the full scope of equivalents to which such claims are entitled.

[0109] Example 1 is a lithotripsy device comprising: a handpiece; a lithotripsy probe extending from the handpiece; an energization source coupled to the handpiece configured to deliver an energy to a distal end of the lithotripsy probe; a suction passage extending from the distal end of the probe and through the handpiece; and a capture device coupled to the handpiece, the capture device comprising: a container comprising: a wall defining a storage space within the container; an entry port configured to couple to the handpiece at the suction passage; and an exit port; and a capture element connected to the container and configured to facilitate capture of stone fragments within the storage space.

[0110] In Example 2, the subject matter of Example 1 includes, wherein the capture element comprises a filter disposed in the container and extending across the exit port.

[0111] In Example 3, the subject matter of Example 2 includes, wherein the container comprises a first portion having the entry port and a second portion having the exit port, wherein the first and second portions are separable to be able to access the storage space.

[0112] In Example 4, the subject matter of Example 3 includes, wherein the filter is coupled to the second portion.

[0113] In Example 5, the subject matter of Examples 2-4 includes, wherein the filter is adjustable.

[0114] In Example 6, the subject matter of Examples 2-5 includes, wherein the filter comprises an iris valve.

[0115] In Example 7, the subject matter of Examples 2-6 includes, wherein the filter comprises first and second mesh screens, wherein the first mesh screen is rotatably adjustable relative to the second mesh screen.

[0116] In Example 8, the subject matter of Examples 1-7 includes, wherein the capture element comprises a baffle disposed between the inlet port and the exit port.

[0117] In Example 9, the subject matter of Examples 1-8 includes, wherein the capture element comprises an elongate tube extending from the entry port.

[0118] In Example 10, the subject matter of Examples 1-9 includes, a first sealing element disposed at the entry port.

[0119] In Example 11, the subject matter of Example 10 includes, wherein the first sealing element comprises a flapper valve or a sliding valve.

[0120] In Example 12, the subject matter of Example 11 includes, wherein the first sealing element is biased to a closed position.

[0121] In Example 13, the subject matter of Examples 10-12 includes, a second sealing element located at an outlet of the container.

[0122] In Example 14, the subject matter of Example 13 includes, a chassis, wherein the container is removable from the chassis and the second sealing element is located at the exit port.

[0123] In Example 15, the subject matter of Example 14 includes, wherein the chassis comprises: a seat for receiving the container; and a bypass suction passage circumventing the seat.

[0124] In Example 16, the subject matter of Examples 13-15 includes, wherein the second sealing



element comprises a vacuum port.

[0125] In Example 17, the subject matter of Example 16 includes, wherein the vacuum port is axially aligned with the suction passage extending from the distal end of the probe and through the handpiece.

[0126] In Example 18, the subject matter of Examples 16-17 includes, wherein the vacuum port is axially aligned with the entry port of the container and the exit port of the container is offset from the vacuum port and the entry port.

[0127] In Example 19, the subject matter of Examples 17-18 includes, wherein the vacuum port comprises a self-sealing valve.

[0128] In Example 20, the subject matter of Examples 1-19 includes, a tube connecting the inlet port with the handpiece.

[0129] Example 21 is a method of retrieving stone fragments from a lithotripsy procedure, the method comprising: fragmenting stones with a lithotripsy device; drawing a vacuum through the lithotripsy device to pull stone fragments and waste fluid through the lithotripsy device; pulling the vacuum through a stone capture device connected to the lithotripsy device; depositing stone fragments within the stone capture device using a capture element; and continuing to draw the vacuum to deposit the waste fluid in a waste container.

[0130] In Example 22, the subject matter of Example 21 includes, guiding the stones into the capture element of the stone capture device to deposit the stone fragments within the stone capture device.

[0131] In Example 23, the subject matter of Example 22 includes, wherein the capture element comprises a baffle.

[0132] In Example 24, the subject matter of Examples 21-23 includes, filtering the stone fragments from the waste fluid within the stone capture device.

[0133] In Example 25, the subject matter of Example 24 includes, adjusting a filtering capability of the filter.

[0134] In Example 26, the subject matter of Examples 21-25 includes, opening a valve with the stone capture device to permit the stone fragments and waste fluid into the stone capture device.

[0135] In Example 27, the subject matter of Examples 21-26 includes, adjusting an orifice size of the stone capture device to control egress of stone fragments from the stone capture device.

[0136] In Example 28, the subject matter of Examples 21-27 includes, opening the stone capture device to access deposited stone fragments.

[0137] In Example 29, the subject matter of Examples 21-28 includes, removing the stone capture device from a chassis coupling the stone capture device to the lithotripsy device.

[0138] In Example 30, the subject matter of Examples 21-29 includes, inserting a probe through a vacuum port on the stone capture device and into the lithotripsy device to clear a blockage in the lithotripsy device.

[0139] Example 31 is a capture device for collecting fragments generated during lithotripsy, the capture device comprising: a container comprising: a wall defining a storage space within the container; an entry port coupled to the wall and configured to couple to the handpiece at the suction passage; and an exit port coupled to the wall; a capture element connected to the container and configured to facilitate capture of stone fragments within the storage space; and a coupler for connecting the container to a handpiece of a lithotripsy device.

[0140] In Example 32, the subject matter of Example 31 includes, wherein the coupler element comprises a barbed hose coupler.

[0141] In Example 33, the subject matter of Examples 31-32 includes, wherein the

[0142] coupler element comprises a resilient opening extending through the wall.

[0143] In Example 34, the subject matter of Examples 31-33 includes, wherein the exit port comprises a barbed hose coupler.

[0144] In Example 35, the subject matter of Examples 31-34 includes, wherein the capture element

comprises an adjustable filter.

[0145] In Example 36, the subject matter of Examples 31-35 includes, wherein the capture element comprises an adjustable orifice.

[0146] In Example 37, the subject matter of Examples 31-36 includes, wherein the capture element comprises an elongate tube extending from the entry port.

[0147] In Example 38, the subject matter of Examples 31-37 includes, wherein the capture element comprises a baffle.

[0148] In Example 39, the subject matter of Examples 31-38 includes, a first sealing element disposed at the entry port.

[0149] In Example 40, the subject matter of Examples 31-39 includes, a second sealing element located at an outlet of the container.

[0150] In Example 41, the subject matter of Example 40 includes, a chassis, wherein the container is removable from the chassis and the second sealing element is located at the exit port.

[0151] In Example 42, the subject matter of Examples 40-41 includes, wherein the second sealing element comprises a vacuum port axially aligned with the entry port, the vacuum port comprising a self-sealing valve.

[0152] Example 43 is at least one machine-readable medium including instructions that, when executed by processing circuitry, cause the processing circuitry to perform operations to implement of any of Examples 1-42.

[0153] Example 44 is an apparatus comprising means to implement of any of Examples 1-42.

[0154] Example 45 is a system to implement of any of Examples 1-42.

[0155] Example 46 is a method to implement of any of Examples 1-42.

[0156] Each of these non-limiting examples can stand on its own, or can be combined in various permutations or combinations with one or more of the other examples.

## Claims

1. A lithotripsy device comprising: a proximal end portion; a lithotripsy probe extending from the proximal end portion; an energization source coupled to the proximal end portion configured to deliver an energy to a distal end of the lithotripsy probe; a suction passage extending from the distal end of the lithotripsy probe and through at least a portion of the proximal end portion; and a capture device coupled to the proximal end portion, the capture device comprising: a container comprising: a wall defining a storage space within the container; an entry port configured to couple to the proximal end portion at the suction passage; and an exit port; and a capture element connected to the container and comprising an adjustable filter for facilitating capture of stone fragments within the storage space.

2. The lithotripsy device of claim 1, wherein the adjustable filter extends across the exit port and includes an adjustable opening passing through the adjustable filter that is adjustable by an end-user.

3. The lithotripsy device of claim 2, wherein the container comprises a first portion having the entry port and a second portion having the exit port, wherein the first portion and the second portion are separable to be able to access the storage space, wherein the adjustable filter is coupled to the second portion.

4. (canceled)

5. The lithotripsy device of claim 2, wherein the adjustable filter is manually adjustable by the end-user to change a size of the adjustable opening passing through the adjustable filter.

6. The lithotripsy device of claim 2, wherein the adjustable filter comprises an iris valve comprising a variable diameter orifice defining the adjustable opening.

7. The lithotripsy device of claim 2, wherein the adjustable filter comprises a first mesh screen and a second mesh screen, wherein the first mesh screen is rotatably adjustable relative to the second

mesh screen to produce a plurality of adjustable openings including the adjustable opening.

8. (canceled)

9. (canceled)

10. The lithotripsy device of claim 1, further comprising: a first sealing element disposed at the entry port; and a second sealing element located at an outlet of the container.

11. The lithotripsy device of claim 10, wherein the first sealing element comprises a flapper valve or a sliding valve that is biased toward a closed position.

12.-20. (canceled)

21. A method of retrieving stone fragments from a lithotripsy procedure, the method comprising: fragmenting stones with a lithotripsy device; drawing a vacuum through the lithotripsy device to pull stone fragments and waste fluid through the lithotripsy device; pulling the vacuum through a stone capture device connected to the lithotripsy device, the stone capture device comprising an adjustable filter comprising a variable sized opening passing through the adjustable filter configured to prevent stone fragments having a size larger than the variable sized opening from leaving the stone capture device; providing an adjustable filtering capability of the adjustable filter that permits adjusting the variable sized opening to set the size of stone fragments to be captured by the adjustable filter; depositing stone fragments within the stone capture device using a capture element; and continuing to draw the vacuum to deposit the waste fluid in a waste container.

22.-25. (canceled)

26. The method of claim 21, further comprising opening a valve with the stone capture device to permit the stone fragments and waste fluid into the stone capture device.

27. (canceled)

28. The method of claim 21, further comprising opening the stone capture device to access deposited stone fragments.

29. (canceled)

30. (canceled)

31. A capture device for collecting fragments generated during lithotripsy using a lithotripsy device, the capture device comprising: a container comprising: a wall defining a storage space within the container; an entry port coupled to the wall and configured to fluidly couple to a at the suction passage of the lithotripsy device; and an exit port coupled to the wall; a capture element connected to the container and configured to facilitate capture of stone fragments within the storage space, wherein the capture element comprises an adjustable filter having a variable sized opening passing through the adjustable filter to control a size of stone fragments to be captured within the container; an actuator operatively connected to the adjustable filter to allow an end-user to change the variable sized opening during use of the lithotripsy device; and a coupler for connecting the container to a handpiece of the lithotripsy device.

32.-38. (canceled)

39. The capture device of claim 31, further comprising: a first sealing element disposed at the entry port; and a second sealing element located at an outlet of the container.

40.-42. (Canceled)

43. The lithotripsy device of claim 6, wherein the iris valve comprises: a plurality of shims arranged in a circular pattern, each of the plurality of shims being rotatable to form the adjustable opening at a center of the plurality of shims.

44. The lithotripsy device of claim 43, wherein each of the plurality of shims comprises: a first end pinned proximate an outer diameter of the container; and a second end having a variable position relative to a center of the container.

45. The lithotripsy device of claim 7, wherein: the first mesh screen comprises a first plurality of strands extending in a first direction and being spaced at a first interval; and the second mesh screen comprises a second plurality of strands extending in a second direction and being spaced at a second interval; wherein the first direction and the second direction are arranged oblique to each

other such that the plurality of adjustable openings are formed between the first interval and the second interval.

**46.** The lithotripsy device of claim 45, wherein at least one of the first mesh screen and the second mesh screen includes strands of different widths or spacings between strands that are different.

**47.** The lithotripsy device of claim 1, further comprising an actuator positioned on an exterior of the container to actuate the adjustable filter.

**48.** The lithotripsy device of claim 47, wherein the actuator comprises a lever extending from the container to be accessible from an exterior of the container.

**49.** The method of claim 21, wherein the adjustable filter comprises an iris valve comprising: a plurality of shims configured to be positionable to form the variable sized opening; and an actuator accessible from an exterior of the stone capture device to adjust a position of the plurality of shims.

**50.** The method of claim 21, wherein the adjustable filter comprises a screen assembly comprising: a first screen extending across a housing of the stone capture device, the first screen having a first mesh size; a second screen extending across the housing of the stone capture device, the second screen having a second mesh size; wherein the first screen is rotatably adjustable relative to the second screen to produce a plurality of variable sized openings; and wherein at least one of the first mesh size and the second mesh size includes an asymmetry; and an actuator connected to the first screen and extending outside of the housing to allow an end-user to rotate the first screen while the stone capture device is assembled with the lithotripsy device.

---