

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250281732

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

SOLOMON; Clint et al.

METHODS AND DEVICES FOR VASCULAR ACCESS

Abstract

Valve assemblies having improved ability to selectively control flow of fluids through the catheter and prevent leakage of fluids from the proximal end of a catheter that is positioned within a patient. Such improved catheter valve assemblies also prevent leakage of fluids after repeated insertion and removal of medical instruments through the valve.

Inventors: SOLOMON; Clint (Morgan Hill, CA), LESKOWICH; Vincent (Oakhurst, NJ), SUTTON; Thomas (Summit, NJ), HALE; James (Los Osos, CA), HENTZLER; Jacob (Morgan Hill, CA)

Applicant: I-V Access Technology, Inc. (San Francisco, CA)

Family ID: 96948331

Assignee: I-V Access Technology, Inc. (San Francisco, CA)

Appl. No.: 19/041398

Filed: January 30, 2025

Related U.S. Application Data

parent US continuation 18405237 20240105 parent-grant-document US 12239814 child US 19041398

parent US continuation 17656208 20220323 parent-grant-document US 11890447 child US 18405237

parent US continuation 17307766 20210504 parent-grant-document US 11324939 child US 17656208

parent US continuation 16670291 20191031 parent-grant-document US 10850069 child US 17074231

parent US continuation 16520813 20190724 ABANDONED child US 16670291

parent US continuation-in-part 17074231 20201019 parent-grant-document US 11701495 child US 17307766

Publication Classification

Int. Cl.: A61M39/26 (20060101); A61M25/00 (20060101); A61M25/06 (20060101); A61M29/00 (20060101); A61M39/00 (20060101); A61M39/04 (20060101); A61M39/06 (20060101); A61M39/10 (20060101)

U.S. Cl.:

CPC A61M39/26 (20130101); A61M25/0606 (20130101); A61M25/0625 (20130101); A61M39/045 (20130101); A61M39/1011 (20130101); A61M25/0097 (20130101); A61M25/0631 (20130101); A61M2025/0687 (20130101); A61M29/00 (20130101); A61M2039/0036 (20130101); A61M39/06 (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 18/405,237 filed Jan. 5, 2024, which is a continuation of U.S. patent application Ser. No. 17/656,208, filed Mar. 23, 2022 (now U.S. Pat. No. 11,890,447), which is a continuation of U.S. patent application Ser. No. 17/307,766, filed May 4, 2021 (now U.S. Pat. No. 11,324,939), which is a non-provisional of U.S. Provisional Application No. 63/151,562 filed Feb. 19, 2021 and a continuation-in part of U.S. patent application Ser. No. 17/074,231, filed Oct. 19, 2020 (now U.S. Pat. No. 11,701,495), which is a continuation of U.S. patent application Ser. No. 16/670,291, filed Oct. 31, 2019 (now U.S. Pat. No. 10,850,069), which is a continuation of U.S. patent application Ser. No. 16/520,813 filed Jul. 24, 2019 (now Abandoned), which is a continuation of U.S. patent application Ser. No. 16/004,970 filed Jun. 11, 2018 (now U.S. Pat. No. 10,406,326), which claims priority to U.S. Provisional Patent Application No. 62/552,663 filed Aug. 31, 2017. The contents each of the above applications are incorporated herein by reference in their entirety.

FIELD OF THE INVENTION

[0002] The invention is directed to a valve assembly having improved ability to selectively control flow of fluids through the medical device and prevent leakage of fluids from the proximal end of the device that is positioned within a patient. Such improved valve assemblies also prevent leakage of fluids after repeated insertion and removal of medical instruments through the valve, such as catheters introducers, tubes, lines, ports that can be used for vascular or other devices. The valve assembly may also be used as a connection for needles (e.g., fistula needles), hemodialysis circuits, feeding tubes, urinary drain catheters, or any other suitable means.

BACKGROUND

[0003] Catheters allow medical practitioners to administer infusion or removal of fluids from a patient. For example, catheters can function as a conduit that allows infusion of fluids, such as normal saline solution, therapeutic substances, and/or nutritional fluids into a patient. Alternatively, catheters can withdraw fluids such as blood or other bodily fluids as required by the particular medical procedure. In those cases where the medical practitioner intends to position the catheter into a vessel, the medical practitioner will look for a flow of blood back into the catheter (“flashback”) to verify placement of the catheter opening into a vessel. The number of different catheter insertion procedures and techniques is great and may include the use of a needle, dilator, stylet, or other medical device within the catheter when placed.

[0004] Once properly positioned, the catheter's hub (or medical device positioned within the catheter) can be coupled to an adapter (typically a luer fitting) to enable fluid coupling of the

catheter to the source of fluids or reservoir. However, in the case of an accidental disconnection between the catheter and the reservoir, there is a possibility for the patient to bleed out or to entrain air that will lead to an embolism, both of which are potentially life-threatening for the patient. Accidental disconnection can occur if the mating parts are not securely tightened. The mating parts can also become loose from patient movement, unwanted fidgeting, or other patient interference. Further, if the patients have any blood-borne pathogen (e.g., HIV, hepatitis, etc.), blood exposure for the caregiver is potentially lethal. As such, insertion of the catheter requires that the point of access remains sanitary. The period between insertion of the catheter and coupling of an adaptor can cause bodily fluids to escape through the catheter, causing an unsanitary condition for the medical practitioner who must handle the catheter for coupling of the adapter and/or remove the medical device inserted through the catheter. The caregiver often covers an open connection port with their finger to reduce the blood flow until making a mating connection. Since blood can be a medium for bacterial growth, infection chances can rise due to exposure at the time of catheter insertion.

[0005] As such, there remains a need for a valve assembly that permits controlled fluid flow that also reduces risk of infection. There also remains a need for a valve that slows blood loss to give the caretaker time to adequately clean the connection and wipe away any residual blood on the connection. There also remains a need for a valve that minimizes the blood exposure for the caregiver at the time of insertion, removal, or a change in catheters. A valve assembly is described below.

SUMMARY

[0006] The illustrations and variations described herein are meant to provide examples of the methods and devices of the invention. It is contemplated that combinations of aspects of specific embodiments or combinations of the specific embodiments themselves are within the scope of this disclosure. The valve assemblies described herein can be used in any tubing assembly, especially medical tubing not only limited to catheter assemblies.

[0007] A valve assembly configured for use with a male luer having a distal end, a lateral surface, and a connector portion is provided. The assembly can be used as part of a catheter assembly where the valve assembly fits within a catheter hub. However, the valve assembly can be used in any assembly, especially those where valve deformation rather than fluid pressure opens the valve. Such assemblies include but are not limited to medical assemblies. For convenience, the examples below are discussed in relation to catheter assemblies. The catheter can comprise a catheter hub and a valve. The catheter hub can be configured to receive the male luer in a proximal end. The valve can be coupled to a chamber within the catheter hub and can comprise a barrier layer at a far end and a wall portion. The wall portion can extend proximally from the barrier layer towards a near end of the valve. The wall portion can define a valve cavity therein. The barrier layer can have at least one slit extending therethrough. An offset distance can be measured between a surface of the wall portion in the valve cavity and a surface of the chamber adjacent to barrier layer at the far end of the valve at the distal end. The offset distance can be less than a thickness of the barrier layer. The valve can be configured for positioning in the catheter hub such that the wall portion can engage a surface of a chamber within the catheter hub. Insertion of the male luer into the valve cavity can cause the distal end of the male luer to open the at least one slit to permit fluid flow through the barrier layer. The lateral surface of the male luer can engage the wall portion at an interior of the valve cavity, causing the wall portion to engage the surface of the chamber.

[0008] The at least one slit can form a plurality of leaflets in the barrier layer. A perimeter of the at least one slit can be limited to the barrier layer such that the leaflets do not extend into the wall portion. The at least one slit can be branched such that the plurality of leaflets comprises at least three leaflets. A thickness of each of the plurality of leaflets can be the same. An entire outer surface of the wall portion can contact an inner surface of the catheter hub. The entire outer surface of the wall portion can comprise a cylindrical shape having a uniform outer diameter.

[0009] The valve assembly can further comprise a flange portion at a near portion of the valve. The flange can extend out of the chamber of the catheter hub to engage a proximal surface of an exterior of the catheter hub where the connector portion of the male luer can directly engage the flange portion against the proximal surface of the catheter hub. An outer diameter of the flange can be equal or less to an outer diameter of the proximal surface of the exterior of the catheter hub. The flange can be located within a recess in the chamber of the catheter hub. The flange can be located within a recess in a proximal surface of an exterior of the catheter hub. The valve can be axially recessed within the catheter hub. The wall portion can include at least one or more gaps to form at least one or more legs. The valve assembly can further comprise an insert positioned within the valve. The insert can be configured to receive the male luer. The valve assembly can further comprise a raised surface positioned within the valve. Wherein upon insertion of the male luer, the raised surface can be configured to be pushed by the male luer to open the valve.

[0010] The present disclosure is related to the following commonly assigned patents and applications, the entirety of each of which is incorporated by reference: U.S. Pat. Nos.: U.S. Pat. No. 8,105,288 issued on Jan. 31, 2012; U.S. Pat. No. 8,591,469 issued on Nov. 26, 2013; U.S. Pat. No. 9,775,973 issued on Oct. 3, 2017; U.S. Pat. No. 9,604,035 issued on Mar. 28, 2017; and U.S. Pat. No. 10,828,465 issued on Nov. 10, 2020. U.S. publication nos.: US20200016375A1 published on Jan. 16, 2020, and US20210031009A1 published on Feb. 4, 2021. Provisional application No. 62/993,493 filed on Mar. 23, 2020; 63/037,496 filed on Jun. 10, 2020; and 63/037,841 filed on Jun. 11, 2020.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0011] Each of the following figures diagrammatically illustrates aspects and variations to better understand the invention. Variation of the invention from the aspects shown in the figures is contemplated.

[0012] FIGS. 1A to 1K illustrate examples of an improved valve for use with catheters or other medical devices/introducers.

[0013] FIGS. 2A and 2B show another cross-sectional view of another variation of a valve.

[0014] FIGS. 3A and 3B illustrate a cross-sectional view of another variation of a catheter-valve assembly having a valve positioned within a recess within a wall of a chamber of a catheter hub.

[0015] FIGS. 4A and 4B illustrate additional partial cross-sectional views of valves within a chamber of a catheter hub to demonstrate a reduced wall thickness relative to a thickness of a barrier layer.

[0016] FIGS. 5A to 5G show cross-sectional views of a catheter valve assembly with a luer fitting being inserted into a valve located within a chamber to deliver fluids through the catheter tubing.

[0017] FIGS. 6A to 6D illustrate partial cross-sectional views of additional variations of catheter assemblies having valves with various flange configurations.

[0018] FIGS. 7A to 7D illustrate additional examples of improved valves for use with catheter assemblies as described herein.

DETAILED DESCRIPTION

[0019] For a better understanding of the present invention, reference will be made to the following description of the embodiments, which is to be read in association with the accompanying drawings, which are incorporated in and constitute a part of this specification, show certain aspects of the subject matter disclosed herein and, together with the description, help explain some of the principles associated with the disclosed implementations.

[0020] The terms “a” or “an”, as used herein, are defined as one or as more than one. The term “plurality”, as used herein, is defined as two or as more than two. The term “another”, as used

herein, is defined as at least a second or more. The terms “including” and/or “having”, as used herein, are defined as comprising. (i.e., open language). The term “coupled”, as used herein, is defined as connected, although not necessarily directly, and not necessarily mechanically.

[0021] Reference throughout this document to “some embodiments”, “one embodiment”, “certain embodiments”, and “an embodiment” or similar terms means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment of the present invention. Thus, the appearances of such phrases or in various places throughout this specification are not necessarily all referring to the same embodiment. Furthermore, the particular features, structures, or characteristics may be combined in any suitable manner in one or more embodiments without limitation.

[0022] FIGS. 1A to 1C illustrate an improved valve for use with catheters or other medical devices/introducers. Typically, such a catheter **130** is used with a male luer (as described in FIGS. 5A-5G below). The catheter **130** includes a catheter hub **134**, having a chamber **140** with a proximal surface **138** defining an open proximal end. The chamber **140** is in fluid communication with a catheter tubing **132** that is coupled to the catheter. The tubing includes one or more lumens in fluid communication with the chamber **140**. The valve or septum valve **190** includes a barrier layer (or septum) **192** at a distal end. The barrier layer **192** can have one or more slits **194**. The illustrated variation shows a barrier layer **192** with 3 slits **194** that form three leaflet structures **197** or flaps. However, variations of the valve **190** include any number of slits forming any number of leaflets. The barrier layer **192** generally includes a flexible or semi-flexible material that is compatible with exposure to blood, medicaments, and other fluids commonly encountered during catheterization/infusion procedure.

[0023] As shown in FIG. 1B, the valve includes a wall portion **196** extending proximally from the barrier layer **192** and defines a valve cavity **199**. In the variation shown in FIGS. 1A to 1B, the valve **190** includes a flange portion **198** that is formed around the wall **196** at a proximal end of the valve **190**. The flange portion **198** comprises a diameter greater than a diameter of the wall portion **196** for sealing against a proximal surface **138** of the catheter hub **134**. Variations of the valve **190** include a flange portion **198** that encircles the valve **190**. Alternatively, the flange portion **198** can include openings or segments such that it is not circumferentially continuous about the wall.

[0024] FIG. 1C shows the valve **190** coupled to the catheter hub **134** such that the flange portion **198** engages the proximal surface **138** of the catheter hub **134** and is exterior to the chamber **140** of the hub **134**. The wall portion **196** of the valve **190** engages a surface of the chamber. The walls of the chamber **140** can be straight or can comprise any luer taper angle. Likewise, the walls of the valve can comprise a taper angle on the exterior and/or interior (e.g., the surface defining the cavity **199**). The valve **190** can be affixed to the catheter at various points. For example, variations of the assembly include a valve **190** that is only affixed to the catheter hub **134** at the flange portion **198** using an adhesive or joining material where the wall portion **196** is simply positioned against a wall of the chamber **140**. Alternatively, or in combination, the valve **190** can be affixed to the catheter hub **134** at the exterior wall portion **196**. In an alternate variation, the valve **190** can simply be press-fit into the catheter hub **134**. Any number of features known to those in the art can be used to facilitate seating of the valve **190** within the catheter hub **134** (e.g., pockets, ribs, increased frictional resistance of the surface of the valve or chamber, etc.)

[0025] The variations of valve **190** shown in FIGS. 1A to 1C also illustrate a valve **190** having a barrier layer **192** that is thicker than the wall portion **196**. A thicker wall on the slit **194** face was found to increase the sealing surface. For example, the increased thickness of the wall **192** along the slit **194** permits the slit **194** to return to a closed position rather than remaining deformed by insertion of a medical device (see e.g., FIGS. 5B and 5C). The relatively thinner wall portion **196** shown in FIGS. 1A to 1C reduces an offset distance between the internal diameter of the valve cavity **199** and the internal wall **142** of the hub chamber **140**. Reducing this offset allows for insertion of a male luer to a sufficient depth along a longitudinal axis to open the slit **194** at the

barrier layer **192** of the valve without being impeded by the wall **196** of the valve **190**. For example, a thickness of a wall **196** of a valve **190** must be selected such that the internal diameter of a valve cavity **199** is sufficiently large to allow insertion of a male luer into the cavity **199** when the valve is placed within the chamber **140** of the catheter hub. However, if a valve wall **196** is too thin, then the valve may suffer from an increased risk of failure (e.g., cracking or splitting) or a thin wall can present manufacturing difficulties in forming the valve. The variation of the valve **190** having sidewalls **196** that are thinner than the barrier layer **192** allows a slit **194** layer **192**, having increased material thickness such that it is relatively more rigid, allowing the slit **194** to close fully and increases the likelihood that the slit returns to its original state to close the valve. Again, having a barrier layer **192** (i.e., the wall with the slit **194** formed therein) that is thicker than the sidewalls **196** increases the ability of the valve to close while the thinner sidewalls allow for insertion of a male luer into the cavity **199**. In some variations, the thickness differential also allows deformation of the valve to occur at the septum rather than the wall portion.

[0026] FIGS. **1D** and **1E** show perspective and cross-sectional views of another variation of a catheter-valve assembly having an insert **170**. As shown in FIG. **1D**, the insert **170** can be placed within valve **190**. The insert **170** can be made of a relatively harder durometer material as compared to the valve **190**, which can be made from a softer durometer material. The durometer material can be the same material used for the catheter hub **134** and the male luer **52**. The insert **170** has a standard luer taper to receive the male luer **52**. As such, male luer **52** slides within and nests against a hard durometer material when attached to the valve **190**. For example, in some variations, both the insert **170** and valve **190** can comprise the same durometer material but each component can have different properties via a treatment, coating, additive, etc.

[0027] Alternatively, as seen in FIGS. **1F** and **1G**, the insert **170** can include an insert flange **174** that is positioned against the back surface of the valve **190** or against the back surface **138** of the catheter hub **134**. The insert flange **174** can be configured to match or cover the flange portion **198** of valve **190**, providing a secure connection to prevent leakage of fluid. It should be understood that the configurations of the catheter-valve assemblies shown in FIGS. **1A** to **1C**, **2A** to **4B**, and **6A** to **6D** can be provided with the insert **170**. FIG. **1H** illustrates a device similar to that shown in FIG. **1G** but where the valve **190** and insert **170** is recessed with a proximal surface **138** of the catheter hub **134**. In additional variations, the valve **190** and insert **170** can be recessed within the catheter hub **134**.

[0028] FIGS. **1I** to **1K** illustrate another variation where a valve **190** is joined to an insert **170** to form a valve assembly having a durometer region selected to sufficiently hard and a distal relatively more elastic region. As noted above, additional variations include an insert **170** have any number of properties that are different from the valve portion (including, but not limited to differences in durometer). FIG. **1J** shows a partial cross-sectional exploded view of the catheter hub **134**, valve **190** and insert **170** to demonstrate that the insert **170** can include a mating shape **175** that seats with a mating shape **180** in the valve **190**. Alternative variations of a valve assembly can include an insert joined with a valve in an end-to-end configuration and without a step or mating surface. FIG. **1K** illustrates a cross-sectional view of the assembled insert **170**/valve **190** where both components include respective luer tapered surfaces **178** and **181** to provide a continuous luer taper in the joined assembly **170/190**. As discussed herein, the valve **190** can include a configuration where the barrier layer/septum **192** is thicker than the largest width of the sidewall **196** that forms the valve cavity **199**.

[0029] The valve and insert can be joined using adhesives, welding, heat-forming, or any other joining process that allows dissimilar materials to be joined together. Moreover, one or both components can be sealingly joined to a wall of the catheter chamber **140**. As noted herein, the insert can comprise a first material and the valve can comprise a second material, wherein the first material and second material comprise different structural properties. In one variation, the materials are formed from different durometer polymers to provide the valve with a greater elasticity relative

to the insert. Moreover, variations of the assembly include a luer surface that is smooth or continuous (meaning there are no steps or discontinuities in a surface of the luer forming the valve/insert cavity).

[0030] FIGS. 2A and 2B show another cross-sectional view of another variation of a valve **190** for use in a catheter hub **134**. As shown, this variation of a valve **190** does not include a flange member at the proximal end **191** of the valve. In this variation, there are no protrusions on an outer wall **196** of the valve **190**. In addition, the valve **190** can be positioned within a chamber **140** of the catheter hub **134** such that the proximal end **191** of the valve **190** is flush with a rear face **138** of the catheter hub **134**. Alternate variations include the proximal end **191** protruding from the rear face **138** of the hub **134** (not shown). As discussed above, the valve **190** can include a construction where a thickness **195** of the valve wall **196** is less than a thickness **193** of the barrier layer **192** that includes one or more slits **194**. FIG. 2B illustrates a variation of a valve **190** similar to that shown in FIG. 2A, where the valve **190** is axially recessed within a chamber of the catheter hub **134** by distance **180**.

[0031] FIGS. 3A and 3B illustrate a cross-sectional view of another variation of a catheter-valve assembly having a valve **190** positioned within a recess **144** within a wall **142** of a chamber **140** of a catheter hub **134**. As shown, a valve **190** is positioned within a chamber **140** of a catheter hub **134**. While both FIGS. 3A and 3B illustrate a valve **190** where a proximal end **191** of the valve **190** is spaced from a rear end **138** of the hub **134**, variations of the assemblies can include any of the valve configurations described herein where the valve is positioned within a recess **144**.

[0032] FIGS. 3A and 3B illustrate valves **190** where a side wall **196** has a thickness less than a thickness of a barrier wall **192** (as discussed above). However, positioning the valve **190** in a recess **144** located within the wall **142** allows for sizing the internal diameter of the valve cavity **199** closer to an internal diameter of the valve chamber **140** (as discussed below). FIG. 3A illustrates a recess **144** that positions the valve wall **196** to be parallel to the chamber wall **142**. Alternatively, FIG. 3B shows a recess **144** that partially extends beyond the valve wall **196**.

[0033] FIGS. 4A and 4B illustrate additional partial cross-sectional views of valves **190** within a chamber **140** of a catheter hub **134** relative to a thickness of a barrier layer. As shown, the chamber **140** of the catheter hub **134** includes an inner diameter **146** adjacent to a barrier layer **192** of the valve **190**. FIG. 4A illustrates a configuration where a thickness **193** of the barrier wall **192** (i.e., the wall that opens upon insertion of a luer or other device) is greater than a thickness **195** of the sidewall of the valve **190**. This allows for an increased inner diameter **188** of the cavity **199** relative to the inner diameter **146** of the catheter hub **134**, which also allows a male luer (not shown) to be sufficiently inserted to open the valve. The increased inner diameter **188** allows for minimizing an offset distance between a surface of the inner diameter **188** of the interior cavity **199** and a surface of the wall **142** of the chamber **140** of the catheter hub **134**. The offset distance is generally measured in a radial direction (i.e., perpendicular to the wall). FIG. 4B illustrates an additional variation of a valve **190** where a thickness **195** of the sidewall **196** is close or equal to a thickness **193** of the barrier layer **192**. However, the variation shown in FIG. 4B includes a recess **144** within the catheter hub **134**. This recess **144** allow for an increased internal diameter **188** of the valve cavity **199** relative to an internal diameter **146** of a chamber **140** of the catheter hub **134** to permit insertion of a male luer.

[0034] FIGS. 5A to 5D show a cross-sectional view of a catheter valve assembly **130** to provide an example of a luer fitting **50** being inserted into a valve **190** located within a chamber **140** of the valve assembly **130** to deliver fluids through the catheter tubing **132**. The illustrated example shows a valve **190** where a proximal end **191** is flush with a proximal face **138** of the catheter hub **134**. However, any of the variations of valves disclosed herein is contemplated to be within the disclosure. As shown, the luer fitting **50** includes threading that engages threading on the catheter hub **134**. Variations of assemblies can include fittings without threading. Regardless, the male luer **52** of the luer fitting is inserted into the catheter hub **134** and valve **190**.

[0035] FIG. 5B illustrates insertion of the male luer 52 into the cavity of the valve 190. As shown in FIG. 5B, as a lateral surface of the male luer 52 engages the wall portion 196 of the valve, the wall portion 196 is compressed against a surface of the catheter chamber 140. Further axial advancement of the male luer 52 against a barrier layer 192 causes leaflets 197 formed by the slit 194 in the barrier layer 192 to open in a distal direction, permitting fluid flow through the valve 190. In the variation shown in FIG. 5B, the male luer 52 causes leaflets 197 to deflect to an open position. In some variations, as shown in FIG. 5D, insertion of the male luer 52 into the cavity of the valve 190 causes the distal end of the male luer 52 to a fully open position, while the lateral surface of the male luer 52 engages the wall portion 196 of the valve 190. However, in alternate variations, the leaflets 197 merely deflect to allow sufficient fluid flow.

[0036] In the variation shown in FIG. 5C, the valve 190 is fabricated from a compliant and resilient material such that insertion of the male luer 52 causes the valve septum 192 to stretch and deform to open the leaflets 197. In such variations, the wall 196 of the valve 190 can be bonded to the interior of the hub. Alternatively, or in addition, a flange 198 (shown in FIG. 1A) can be used to bond or pinch the walls in position so the valve septum 192 stretches instead of moving forward in its normal shape. In those variations where the male luer deforms the valve, the valve operates by elastic deformation rather than fluid pressure. Therefore, the thickness and elasticity of the septum wall 192 permits the valve to return to a closed position when the luer 52 is removed. Moreover, because the valve opens by physical deformation, the closed valve is not subject to leakage caused by the pressure of fluid flowing against the valve.

[0037] Ultimately, the connector portion 54 of the luer fitting 50 engages the proximal surface 138 of the catheter hub 134. Removal of the luer fitting 50 from the catheter hub 134 causes the leaflets 197 of the valve formed by the slit to return to a closed configuration.

[0038] FIG. 5E illustrates another variation of an assembly where a valve includes a material insert. For example, a variation where the wall and flange split between a hard interior top and soft exterior wall and top can be provided to enable the anchoring needed for the stretching of valve 190.

[0039] FIGS. 5F to 5G show cross-sectional views of another variation of a catheter-valve assembly having a protrusion 182. The protrusion 182 can be a raised surface, such as a ring on the wall of the septum 192, or one or more protrusions arranged to receive the male luer 52, which in turn assists in opening the valve 190. In variations where the protrusion 182 is a ring on the surface of the septum 192, the ring can be configured with a slit (i.e., contiguous sections) to allow separation when the ring passes across different leaflets 197 of the valve 190. As seen in FIG. 5G, the male luer 52 can be inserted into valve 190 and can push the protrusion 182 distally, stretching the valve 190 and causing the valve to pucker open.

[0040] Additionally, the protrusion 182 may be used in combination with the insert 170 described in FIGS. 1D to 1G. In such a configuration, the male luer 52 will stop when wedged into the hard tapered surface of the insert 170. Accordingly, the soft material of the valve can be molded over the harder material of the catheter hub 134 or the insert 170 to help anchor the proximal base of the soft valve. This anchoring can be important when the valve stretches and thins dimensionally due to insertion of the male luer 52. The valve 190 can be stretched about 2 mm or more. The valve leaflets 197 are stretched open and folded to a certain point when the male luer 52 is inserted. After removal of the male luer 52, the valve leaflets 197 return to its original size and sealed position.

[0041] FIGS. 6A to 6D illustrate partial cross-sectional views of additional variations of catheter assemblies 130 having valves 190 with various flange 198 configurations. FIG. 6A illustrates a flange 198 positioned within a recess 148 located in the rear face 138 of the catheter hub 134. As shown, the proximal end 191 of the valve 190 extends beyond the rear face 138 of the catheter hub 134. FIG. 6B illustrates another variation, where the flange 198 is positioned within a recess 148 located in the rear face 138 of the hub 134 but the proximal end 191 of the valve 190 is flush with the rear face 138 of the hub 134. FIGS. 6C and 6D illustrate a flange 198 that comprises a outer

edge on an exterior surface of the valve **190**. In FIG. 6C the flange **198** is positioned within a recess **148** that is located within the catheter hub **134** such that the proximal end **191** of the valve **190** is also recessed from the back face **138** of the hub **134**. FIG. 6D illustrates a similar flange **198** where the proximal end **191** of the valve **190** extends beyond the rear face **138** of the hub **134** but the flange **191** does not entirely cover the rear face **138**.

[0042] FIGS. 7A to 7D illustrate additional examples of improved valves for use with catheter assemblies **130** as described herein. As shown in FIG. 7A, the valve **190** is seated in the hub **134** of the catheter **130** and includes a barrier layer (or septum) **192** at a distal end that contains one or more slits **194** that define leaflets **197**. The valve includes a wall **196** that extends proximally from the barrier layer **192**. In this variation, the wall **196** is divided into a number of legs **186** that extend to a segmented flange **198**. While the illustrated variation shows 4 legs **186**, alternate variations of the valve **190** can include any number of legs (e.g., 1 or more) where the legs do not circumferentially extend over the valve but leave gaps. FIG. 7B illustrates a similar variation of a valve **190** with legs **186** that terminate without a flange. FIG. 7C illustrates an example of a valve **190** where a wall **196** extends circumferentially about the valve but only partially along an axial length where legs **186** extend along a remaining distance of the valve **190**. The flange **198**, legs **186** and/or wall **196** of the valves shown in FIG. 7A to 7C can be positioned within a recess in the chamber of the catheter hub (e.g., see **144** or **148** above) to partially or fully align the interior diameter of the valve with a wall of the catheter chamber. Regarding the variations of the catheter-valve assembly shown in 7D, an insert **170** can have legs **172** as shown in FIG. 7D. To form a barrier between the insert **170** and the catheter hub **134**, the insert **170** can fill in the gaps between legs **186**. When the insert **170** is placed within valve **190**, the legs **186** can be sealed to prevent leakage of any fluid therethrough. In additional variations, an insert **170** can have any number of properties that are different from the valve **190**. The legs **172** of the insert **170** will minimize any gap that may form with the legs of the valve **190** when inserted.

[0043] The previous description of the disclosed embodiments is provided to enable any person skilled in the art to make or use the present invention. Various modifications to these embodiments will be readily apparent to those skilled in the art, and the generic principles defined herein can be applied to other embodiments without departing from the spirit or scope of the invention. For example, a wide variety of materials may be chosen for the various components of the embodiments. It is therefore desired that the present embodiments be considered in all respects as illustrative and not restrictive, reference being made to the appended claims as well as the foregoing descriptions to indicate the scope of the invention.

Claims

1. A valve assembly configured for use with a medical device having a distal end, a lateral surface and a connector portion, the valve assembly comprising: a hub having a proximal end with an opening; a valve in a chamber within the hub and comprising a barrier layer at a far end and a wall portion; the wall portion extending proximally from the barrier layer towards a near end of the valve, the wall portion defining a valve cavity therein, the barrier layer having at least one slit extending therethrough and a raised surface; where the valve is configured for positioning in the hub such that the wall portion engages a surface of a chamber within the hub; and wherein insertion of the medical device into the valve cavity causes the distal end of the medical device to engage the raised surface to open the at least one slit allowing for fluid flow through the barrier layer, while the lateral surface of the medical device engages the wall portion at an interior of the valve cavity causing the wall portion to engage the surface of the chamber.
2. The valve assembly of claim 1, wherein an entire outer surface of the wall portion contacts the surface of the chamber.
3. The valve assembly of claim 1, wherein the wall portion includes at least one or more gaps to

form at least one or more legs.

4. The valve assembly of claim 1, further comprising an insert positioned within the valve, wherein the insert is configured to receive the medical device.
 5. The valve assembly of claim 4, wherein the valve cavity further comprises a mating shape and the insert further comprises a mating shape configured to mate with the mating shape of the valve cavity.
 6. The valve assembly of claim 1, further comprising a raised surface positioned within the valve, wherein upon insertion of the medical device, the raised surface is configured to be pushed by the medical device to open the valve.
 7. The valve assembly of claim 1, wherein an entire outer surface of the wall portion comprises a cylindrical shape having a uniform outer diameter.
 8. The valve assembly of claim 1, wherein the valve is axially recessed within the hub.
 9. The valve assembly of claim 1, wherein the at least one slit forms a plurality of leaflets in the barrier layer.
 10. The valve assembly of claim 9, wherein a thickness of each of the plurality of leaflets is the same.
 11. The valve assembly of claim 9, wherein a perimeter of the at least one slit is limited to the barrier layer such that the plurality of leaflets does not extend into the wall portion.
 12. The valve assembly of claim 1, further comprising a flange portion at the near end of the valve, wherein a proximal end of the flange portion extends beyond the proximal end of the hub.
 13. The valve assembly of claim 12, wherein the flange portion partially covers the proximal end of the hub.
 14. The valve assembly of claim 12, wherein the flange portion comprises a raised surface on an exterior surface of the valve.
 15. The valve assembly of claim 1, wherein the near end of the valve is flush with the proximal end of the hub.
 16. The valve assembly of claim 1, wherein the wall portion further comprises one or more ribs configured to facilitate seating of the valve within the hub.
 17. The valve assembly of claim 1, further comprising an insert coupled to the valve, wherein the insert comprises a first material and the valve comprises a second material, wherein the first material and second material comprise different structural properties.
 18. The valve assembly of claim 17, wherein the first material comprises a first durometer and the second material comprises a second durometer being less than the first durometer such that the second material comprises a greater elasticity relative to the first material.
 19. The valve assembly of claim 1, wherein an offset distance, measured between a surface of the wall portion in the valve cavity and a surface of the chamber adjacent to the barrier layer at the far end of the valve the distal end, is less than a thickness of the barrier layer
-