



US 20250285157A1

(19) **United States**

(12) **Patent Application Publication**
RESZCZYNSKI et al.

(10) **Pub. No.: US 2025/0285157 A1**

(43) **Pub. Date: Sep. 11, 2025**

(54) **TECHNIQUES FOR CONFIGURABLE PART GENERATION**

G06F 16/903 (2019.01)

G06F 16/951 (2019.01)

(71) Applicant: **Partfiniti Inc.**, Haymarket, VA (US)

(52) **U.S. Cl.**

CPC *G06Q 30/0621* (2013.01); *G06F 16/248* (2019.01); *G06F 16/287* (2019.01); *G06F 16/90344* (2019.01); *G06F 16/951* (2019.01); *G06Q 30/0625* (2013.01); *G06Q 30/0641* (2013.01)

(72) Inventors: **Lukasz Marcin RESZCZYNSKI**,
Kórnicza (PL); **Geoffrey Peter LAYCOCK**, Haymarket, VA (US)

(21) Appl. No.: **18/921,553**

(57)

ABSTRACT

(22) Filed: **Oct. 21, 2024**

Related U.S. Application Data

(60) Continuation of application No. 18/218,267, filed on Jul. 5, 2023, now Pat. No. 12,154,155, which is a continuation of application No. 17/382,605, filed on Jul. 22, 2021, now Pat. No. 11,734,741, which is a continuation of application No. 16/153,381, filed on Oct. 5, 2018, now Pat. No. 11,087,375, which is a division of application No. 14/704,636, filed on May 5, 2015, now Pat. No. 10,121,177.

Certain example embodiments relate to techniques generating a database of virtual families for real-time generation of part numbers for configurable products. For instance, certain example embodiments may include receiving a search request for part numbers and determining virtual families including entities matching the search request. The number of matching products matching the search request and the part numbers may be determined based on the virtual families and the independent groups stored in the virtual families that match the search request. The part numbers may be determined based on allowed characters, number and/or symbols for the part number positions defined in the independent groups of the virtual families including the entities matching the one or more configurable properties of the user input search request. Facet counts for the configurable product may also be determined based on the results of the user input search request.


Publication Classification

(51) **Int. Cl.**

G06Q 30/0601 (2023.01)

G06F 16/248 (2019.01)

G06F 16/28 (2019.01)






FIG. 1




FIG. 2

200




FIG. 3




FIG. 4




FIG. 5
500




FIG. 6

600

Virtual Family #1							
Independent Group #1							
# of Fibers	Fiber Name	Brand Name	n_1	n_2	n_3	n_4	n_5
2	OM1	SUPERCABLE	A	B	S	2	C
6	OM1	SUPERCABLE	A	B	S	6	C
Independent Group #2							
Values 100 to 1000							
Virtual Family #2							
Independent Group #1							
# of Fibers	Fiber Name	Brand Name	n_1	n_2	n_3	n_4	n_5
2	OM1	XCABLE	A	B	X	2	C
Independent Group #2							
Values 1 to 1000							
Virtual Family #3							
Independent Group #1							
# of Fibers	Fiber Name	Brand Name	n_1	n_2	n_3	n_4	n_5
4	OM1	SUPERCABLE	A	B	S	4	
Independent Group #2							
Values 100 to 1000							
Virtual Family #4							
Independent Group #1							
# of Fibers	Fiber Name	Brand Name	n_1	n_2	n_3	n_4	n_5
8	OM2	SUPERCABLE			S	8	
Independent Group #2							
Values 1 to 1000							

FIG. 7




FIG. 8




FIG. 9




FIG. 10

1000




FIG. 11



Search

Part Number Configurators

Zero Connect | Fiber Optic Assemblies

select

Assembly Type

select

Fiber Type

select

Fiber Total # Fibers

select

End A Connector

select

End B Connector

select

Leg Diameter

select

Breakout Length

select

Cable

select

Cable Flame Rating

select

Assembly Length Unit of Measure

select

Assembly Length

select

Pulling Grip

Reset & Start Over

Copy

Export results:

1-15 of 49,737,193,488 parts 1 2 3 4 5 11 ... 3315812900 -->

Refine your search

Expand All

Collapse All

{1} Fiber Total # Fibers

☐ 1 (56,583,836)

☐ 2 (180,878,832)

☐ 6 (6,731,418,240)

☐ 12 (6,731,418,240)

☐ 24 (7,617,698,640)

☐ 36 (5,683,839,120)

Part number

Details

BOANEAD0EHF001A

12 F OM2 Multimode, MPO non-pinned Flat - LC PC Simplex, 1 Feet, 900 microns /3.0mm , Straight Through (Method A) , Indoor/Outdoor,Low Smoke Zero Halogen Distribution, Circular, Aluminum Interlocking Armored , Pull Grip-End A, ZConnect, Breakout Fiber Optic Cable Assembly

BOANEAD0RH001B

12 F OM2 Multimode, MPO non-pinned Flat - LC PC Simplex, 1 Feet, 900 microns /3.0mm , Straight Through (Method A) , Indoor/Outdoor,Low Smoke Zero Halogen Distribution, Circular, Aluminum Interlocking Armored , Pull Grip-End B, ZConnect, Breakout Fiber Optic Cable Assembly

BOANEAD0EHF001C

12 F OM2 Multimode, MPO non-pinned Flat - LC PC Simplex, 1 Feet, 900 microns /3.0mm , Straight Through (Method A) , Indoor/Outdoor,Low Smoke Zero Halogen Distribution, Circular, Aluminum Interlocking Armored , Pull Grip-Both Ends, ZConnect, Breakout Fiber Optic Cable Assembly

FIG. 12A

Part Number

Search

Part Number Configurations

Zero Connect | Fiber Optic Assemblies

P

select

Fiber Type

select

Fiber Total # Fibers

select

End A Connector

select

End B Connector

select

Leg Diameter

0

Breakout Length

select

Cable

select

Cable Flame Rating

select

Assembly Length Unit of Measure

select

Assembly Length

select

Pulling Grip

Reset & Start Over

Copy

Refine your search

Expand All

Collapse All

Fiber Total # Fibers

1 (18,861,312)

2 (60,292,944)

Fiber Name

OM1 (10,135,080)

OM2 (10,135,080)

OM3 (10,135,080)

Export results:

1-15 of 79,154,256 parts

1234511... 5276951

Part number

Details

P01EEAUSHE001A

1 F OM2 Multimode, LC PC Simplex - LC PC Simplex, 1 Feet, 900 microns /3.0mm , Indoor,Low Smoke Zero Halogen Interconnect, Circular, non Armored , Pull Grip-End A, ZConnect, Jumper Fiber Optic Cable Assembly

P01EEAUSHE001B

1 F OM2 Multimode, LC PC Simplex - LC PC Simplex, 1 Feet, 900 microns /3.0mm , Indoor,Low Smoke Zero Halogen Interconnect, Circular, non Armored , Pull Grip-End B, ZConnect, Jumper Fiber Optic Cable Assembly

P01EEAUSHE001C

1 F OM2 Multimode, LC PC Simplex - LC PC Simplex, 1 Feet, 900 microns /3.0mm , Indoor,Low Smoke Zero Halogen Interconnect, Circular, non Armored , Pull Grip-Both Ends, ZConnect, Jumper Fiber Optic Cable Assembly

P01EEAUSHE001

1 F OM2 Multimode, LC PC Simplex - LC PC Simplex, 1 Feet, 900 microns /3.0mm , Indoor,Low Smoke Zero Halogen Interconnect, Circular, non Armored , Pull Grip-Romex, ZConnect, Jumper Fiber Optic Cable Assembly

P01EEAUSHE002A

1 F OM2 Multimode, LC PC Simplex - LC PC Simplex, 2 Feet, 900 microns /3.0mm , Indoor,Low Smoke Zero Halogen Interconnect,

FIG. 12B




FIG. 12C

Partfiniti

Inc.

Zero Connect | Fiber Optic Assemblies

Search

Part Number Configurators

P

3

2

0

select

select

select

select

select

select

Assembly Type

Fiber Type

Fiber Total # Fibers

End A Connector

End B Connector

Log Diameter

Breakout Length

Cable

Cable Flame Rating

Assembly Length Unit of Measure

Assembly Length

Pulling Grip

select

select

select

select

Reset & Start Over

Copy

Export results:

1-15 of 7,834,920 parts

2 3 4 5 11 ... 523328

Refine your search

Expand All

Collapse All

(-) End 'A' Connector

PC (718,803)

LC (3,881,520)

SC (2,156,450)

ST (1,078,203)

(+) End 'A' Connector Format

Part number

Details

P32EEADPHF001A

2 F OM3 Multimode, LC PC Simplex - LC PC Simplex, 1 Feet, 900 microns /3.0mm , Indoor,Low Smoke Zero Halogen Interconnect, Circular, non Armored , Pull Grip-End A, ZConnect, Jumper Fiber Optic Cable Assembly

P32EEADPHF001B

2 F OM3 Multimode, LC PC Simplex - LC PC Simplex, 1 Feet, 900 microns /3.0mm , Indoor,Low Smoke Zero Halogen Interconnect, Circular, non Armored , Pull Grip-End B, ZConnect, Jumper Fiber Optic Cable Assembly

P32EEADPHF001C

2 F OM3 Multimode, LC PC Simplex - LC PC Simplex, 1 Feet, 900 microns /3.0mm , Indoor,Low Smoke Zero Halogen Interconnect, Circular, non Armored , Pull Grip-Both Ends, ZConnect, Jumper Fiber Optic Cable Assembly

P32EEADPHF001

2 F OM3 Multimode, LC PC Simplex - LC PC Simplex, 1 Feet, 900 microns /3.0mm , Indoor,Low Smoke Zero Halogen Interconnect, Circular, non Armored , Pull Grip-None, ZConnect, Jumper Fiber Optic Cable Assembly

https://prosandbox.partfiniti.com

FIG. 12D

Partinit

inc.

Zero Connect | Fiber

P

Assembly Type

3

Fiber Type

2

Fiber Size

Refine your search

Expand All

Collapse All

End 'A' Connector

FC (718,800)

LC (3,981,520)

SC (2,158,400)

ST (1,078,200)

End 'M' Connector Format

Duplex Clipped (2,501,424)

End A Connector: refine your search

display disabled rows

make multiple selections

End 'A' Connector

End 'M' Connector Format

Assembly Polarity

Enter...

Filter...

Filter...

LC	Duplex Clipped	A-B	L
LC	Duplex Clipped	A-A	R
LC	Duplex Uniboot	Adjustable	U
LC	Simplex		E
SC	Duplex Clipped	A-B	S
SC	Duplex Clipped	A-A	Y
SC	Simplex		U
ST	Simplex		I
FC	Simplex		E
SCapc	Simplex		C
FCapc	Simplex		A
MPO non-pinned		Straight Through (Method A)	N
MPO non-pinned		Reversed (Method B)	W
MPO non-pinned		Pair Flipped (Method C)	X
MPO pinned		Straight Through (Method A)	P
MPO pinned		Reversed (Method B)	D

Search

Part Number Configurations

select

select

Assembly Length

Pulling Grip

1-15 of 7,834,920 parts

2

3

4

5

11

...

S22328

...

LC (73.0mm) , Indoor, Low Smoke Zero Halogen Interconnect, by Cable Assembly

LC (73.0mm) , Indoor, Low Smoke Zero Halogen Interconnect, by Cable Assembly

LC (73.0mm) , Indoor, Low Smoke Zero Halogen Interconnect, by Cable Assembly

LC (73.0mm) , Indoor, Low Smoke Zero Halogen Interconnect, by Cable Assembly

LC (73.0mm) , Indoor, Low Smoke Zero Halogen Interconnect, by Cable Assembly

LC (73.0mm) , Indoor, Low Smoke Zero Halogen Interconnect, by Cable Assembly

FIG. 12E

Zero Connect | Fiber Optic Assemblies

[Search](#)

[Part Number Configurators](#)

P

3

2

L

select

End B Connector

select

Lag Diameter

0

Breakout Length

select

Cable Rating

select

Assembly Length Unit of Measure

select

Pulling Grip

Reset & Start Over
Copy

Export results:	Details
P32LOAOPHF001A	2 F OM3 Multimode, LC PC Duplex Clipped - Pigtail, 1 Feet, 900 microns / 3.0mm , A-B , Indoor, Low Smoke Zero Halogen Interconnect, Circular, non Armored , Pull Grip-End A, ZConnect, Jumper Fiber Optic Cable Assembly
P32LOAOPHF001B	2 F OM3 Multimode, LC PC Duplex Clipped - Pigtail, 1 Feet, 900 microns / 3.0mm , A-B , Indoor, Low Smoke Zero Halogen Interconnect, Circular, non Armored , Pull Grip-End B, ZConnect, Jumper Fiber Optic Cable Assembly
P32LOAOPHF001C	2 F OM3 Multimode, LC PC Duplex Clipped - Pigtail, 1 Feet, 900 microns / 3.0mm , A-B , Indoor, Low Smoke Zero Halogen Interconnect, Circular, non Armored , Pull Grip-Both Ends, ZConnect, Jumper Fiber Optic Cable Assembly
P32LOAOPHF001	2 F OM3 Multimode, LC PC Duplex Clipped - Pigtail, 1 Feet, 900 microns / 3.0mm , A-B , Indoor, Low Smoke Zero Halogen Interconnect, Circular, non Armored , Pull Grip-None, ZConnect, Jumper Fiber Optic Cable Assembly

Refine your search

- ☒ Expand All
- ☒ Collapse All
- ☐ End 'B' Connector
 - ☐ LC (531,912)
 - ☐ Pigtail (359,400)
- ☐ End 'B' Polish
 - ☐ Not specified (359,400)
 - ☐ PC (531,912)

Export results: 1 2 3 4 5 11 ... 59421 →

1-15 of 891,312 parts

FIG. 12F




FIG. 12G

Part Number

Configuration

Search

>

Zero Connect | Fiber Optic Assemblies

P

3

2

L

U

2

0

P

Assembly Type

Fiber Type

Fiber Total # Fibers

End A Connector

End B Connector

Leg Diameter

Breakout Length

Cable

Cable Flame Rating

Assembly Length Unit of Measure

Assembly Length

Pulling Grip

select

select

select

select

select

Reset & Start Over

Copy

Refine your search

Expand All

Collapse All

[+] Assembly Length

Select values

Available from 1 to 995

[+] Assembly Length Unit of Measure

Feet (7,186)

Meters (7,186)

Export results:

1-15 of 14,376 parts

2 3 4 5 11 ... 959

Part number

Details

P32LU20PHF001A

2 F OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Uniboot, 1 Feet, 2.0mm / 2.0mm, A-B, Indoor, Low Smoke Zero Halogen Interconnect, Circular, non Armored, Pull Grip-End A, ZConnect, Jumper Fiber Optic Cable Assembly

P32LU20PHF001B

2 F OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Uniboot, 1 Feet, 2.0mm / 2.0mm, A-B, Indoor, Low Smoke Zero Halogen Interconnect, Circular, non Armored, Pull Grip-End B, ZConnect, Jumper Fiber Optic Cable Assembly

P32LU20PHF001C

2 F OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Uniboot, 1 Feet, 2.0mm / 2.0mm, A-B, Indoor, Low Smoke Zero Halogen Interconnect, Circular, non Armored, Pull Grip-Both Ends, ZConnect, Jumper Fiber Optic Cable Assembly

P32LU20PHF001

2 F OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Uniboot, 1 Feet, 2.0mm / 2.0mm, A-B, Indoor, Low Smoke Zero Halogen Interconnect, Circular, non Armored, Pull Grip-None, ZConnect, Jumper Fiber Optic Cable Assembly

P32LU20PHF001D

2 F OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Uniboot, 2 Feet, 2.0mm / 2.0mm, A-B, Indoor, Low Smoke Zero Halogen Interconnect, Circular, non Armored, Pull Grip-End A, ZConnect, Jumper Fiber Optic Cable Assembly

https://cobasandbox.partiniti.com

FIG. 12I




FIG. 12J

Part Number Configuration

Search

Zero Connect | Fiber Optic Assemblies

P

3

2

L

U

2

0

P

R

Assembly Type

Fiber Type

Fiber Total # Fibers

End A Connector

End B Connector

Leg Diameter

Breakout Length

Cable

Cable Flame Rating

Assembly Length Unit of Measure

Assembly Length

Assembly Length Unit of Measure

Assembly Length

Assembly Length Unit of Measure

select

select

select

select

Reset & Start Over

Copy

Refine your search

Expand All Collapse All

Assembly Length

Select values

Available from 1 to 995

Assembly Length Unit of Measure

Feet (2,396)

Meters (2,396)

Export results:

Part number

Details

P32LU20PRF001A

2 F OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Uniboot, 1 Feet, 2.0mm /2.0mm , A-B , Indoor Riser Interconnect, Circular, non Armored , Pull Grip-End A, ZConnect, Jumper Fiber Optic Cable Assembly

P32LU20PRF001B

2 F OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Uniboot, 1 Feet, 2.0mm /2.0mm , A-B , Indoor Riser Interconnect, Circular, non Armored , Pull Grip-End B, ZConnect, Jumper Fiber Optic Cable Assembly

P32LU20PRF001C

2 F OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Uniboot, 1 Feet, 2.0mm /2.0mm , A-B , Indoor Riser Interconnect, Circular, non Armored , Pull Grip-Both Ends, ZConnect, Jumper Fiber Optic Cable Assembly

P32LU20PRF001

2 F OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Uniboot, 1 Feet, 2.0mm /2.0mm , A-B , Indoor Riser Interconnect, Circular, non Armored , Pull Grip-None, ZConnect, Jumper Fiber Optic Cable Assembly

P32LU20PRF002A

2 F OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Uniboot, 2 Feet, 2.0mm /2.0mm , A-B , Indoor Riser Interconnect, Circular, non Armored , Pull Grip-End A, ZConnect, Jumper Fiber Optic Cable Assembly

FIG. 12K

Partinitil

INC.

Zero Connect | Fiber Optic Assemblies

Search:

Part Number Configurators

1-15 of 4,792 parts

2345671132B

P

Assembly Type

3

Fiber Type

2

Fiber Total # Fibers

L

End A Connector

make multiple selections

Assembly Length Unit of Measure: refine your...

Feet

Meters

select

select

select

Refine your search

Expand All

Collapse All

Assembly Length

Available from 1 to 995

Assembly Length Unit of Measure

Feet (2,396)

Meters (2,396)

Export results:

Details

Part number

2 P OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Uniboot, 1 Feet, 2.0mm (2.0mm, A-B), Indoor Riser Interconnect, Circular, non Armored, Pull Grip-End A, 2Connect, Jumper Fiber Optic Cable Assembly

2 P OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Uniboot, 1 Feet, 2.0mm (2.0mm, A-B), Indoor Riser Interconnect, Circular, non Armored, Pull Grip-End B, 2Connect, Jumper Fiber Optic Cable Assembly

2 P OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Uniboot, 1 Feet, 2.5mm (2.5mm, A-B), Indoor Riser Interconnect, Circular, non Armored, Pull Grip-Both Ends, 2Connect, Jumper Fiber Optic Cable Assembly

2 P OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Uniboot, 1 Feet, 3.0mm (3.0mm, A-B), Indoor Riser Interconnect, Circular, non Armored, Pull Grip-None, 2Connect, Jumper Fiber Optic Cable Assembly

2 P OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Uniboot, 3 Feet, 2.0mm (2.0mm, A-B), Indoor Riser Interconnect, Circular, non Armored, Pull Grip-End A, 2Connect, Jumper Fiber Optic Cable Assembly

FIG. 12L

Part Number

Part Number Configurators

Search

>

Zero Connect | Fiber Optic Assemblies

P

3

2

L

U

2

0

P

R

M

select

Assembly Type

Fiber Type

Fiber Total # Fibers

End A Connector

End B Connector

Lag Diameter

Breakout Length

Cable

Cable Flame Rating

Assembly Length Unit of Measure

Assembly Length

Pulling Grip

Reset & Start Over

Copy

Refine your search

Expand All

Collapse All

Assembly Length

Select values

Available from 1 to 995

Assembly Pulling Grip

Both Ends (539)

End A (539)

End B (596)

Export results:

1-15 of 2,396 parts

234511160

Details

Part number	2 F OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Uniboot, 1 Meters, 2.0mm / 2.0mm, A-B, Indoor, Riser Interconnect, Circular, non Armored, Pull Grip-End A, ZConnect, Jumper Fiber Optic Cable Assembly
P32LU20PRM001A	
P32LU20PRM001B	2 F OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Uniboot, 1 Meters, 2.0mm / 2.0mm, A-B, Indoor, Riser Interconnect, Circular, non Armored, Pull Grip-End B, ZConnect, Jumper Fiber Optic Cable Assembly
P32LU20PRM001C	2 F OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Uniboot, 1 Meters, 2.0mm / 2.0mm, A-B, Indoor, Riser Interconnect, Circular, non Armored, Pull Grip-Both Ends, ZConnect, Jumper Fiber Optic Cable Assembly
P32LU20PRM001	2 F OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Uniboot, 1 Meters, 2.0mm / 2.0mm, A-B, Indoor, Riser Interconnect, Circular, non Armored, Pull Grip-None, ZConnect, Jumper Fiber Optic Cable Assembly
P32LU20PRM002A	2 F OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Uniboot, 2 Meters, 2.0mm / 2.0mm, A-B, Indoor, Riser Interconnect,

FIG. 12M

Zero Connect | Fiber Optic Assemblies

Search

Part Number Configuration

P

Assembly Type

3

Fiber Type

2

Fiber Total # Fibers

L

End A Connector

M

Assembly Length Unit of Measure

select

Assembly Length

select

Pulling Grip

Assembly Length: refine your ...

Enter Assembly Lengths needed and add to list:

Add

☐ make multiple selections

Select

Cancel

Export results

Expand All

Collapse All

1-1 Assembly Length

Select value

Available from 1 to 995

1-1 Assembly Pulling Grip

Both Ends (\$99)

End A (\$99)

End B (\$99)

Part number

2 F OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Uniboot, 1 Meters, 3.0mm / 2.0mm, A-B, Indoor /Riser Interconnect, Circular, non Armored, Pull Grip-End A, 2Connect, Jumper Fiber Optic Cable Assembly

2 F OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Uniboot, 1 Meters, 2.0mm / 2.0mm, A-B, Indoor /Riser Interconnect, Circular, non Armored, Pull Grip-End B, 2Connect, Jumper Fiber Optic Cable Assembly

2 F OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Uniboot, 1 Meters, 2.0mm / 2.0mm, A-B, Indoor /Riser Interconnect, Circular, non Armored, Pull Grip-Both Ends, 2Connect, Jumper Fiber Optic Cable Assembly

2 F OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Uniboot, 1 Meters, 2.0mm / 2.0mm, A-B, Indoor /Riser Interconnect, Circular, non Armored, Pull Grip-None, 2Connect, Jumper Riser Optic Cable Assembly

2 F OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Uniboot, 2 Meters, 2.0mm / 2.0mm, A-B, Indoor /Riser Interconnect, Circular, non Armored, Pull Grip-End A, 2Connect, Jumper Riser Optic Cable Assembly

FIG. 12N

Part Number

Search

Part Number Configurators

Zero Connect | Fiber Optic Assemblies

P

3

2

L

U

2

0

P

R

M

0

4

5

select

Please choose the connector code in alphabetical order with the lower code first.

Reset & Start Over

Copy

Assembly Type

Fiber Type

Fiber Total # Fibers

Cable

Cable Plume Rating

Assembly Length Unit of Measure

Assembly Length

Pulling Grip

Refine your search

Clear filters

Expand All

Collapse All

Assembly Length clear

Selected values: 45.0

Select values

Available from 1 to 995

Assembly Pulling Grip

Export results:

1-4 of 4 parts

Part number

Details

P32LU20PRM045A

2 F OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Uniboot, 45 Meters, 2.0mm /2.0mm , A-B , Indoor, Riser Interconnect, Circular, non Armored , Pull Grip-End A, ZConnect, Jumper Fiber Optic Cable Assembly

P32LU20PRM045B

2 F OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Uniboot, 45 Meters, 2.0mm /2.0mm , A-B , Indoor, Riser Interconnect, Circular, non Armored , Pull Grip-End B, ZConnect, Jumper Fiber Optic Cable Assembly

P32LU20PRM045C

2 F OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Uniboot, 45 Meters, 2.0mm /2.0mm , A-B , Indoor, Riser Interconnect, Circular, non Armored , Pull Grip-Both Ends, ZConnect, Jumper Fiber Optic Cable Assembly

P32LU20PRM045D

2 F OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Uniboot, 45 Meters, 2.0mm /2.0mm , A-B , Indoor, Riser Interconnect, Circular, non Armored , Pull Grip-None, ZConnect, Jumper Fiber Optic Cable Assembly

FIG. 120

Zero Connect | Fiber Optic Assemblies

Search

Part Number Configuration

P

3

2

L

U

Assembly Type

Fiber Type

Fiber Total # Fibers

Please choose the correct length with the lower case

Assembly Length Unit of Measure

M

Assembly Length

0 4 5

Pulling Grip

Select

make multiple selections

Assembly Pulling Grip

Symbol

End A

A

End B

B

Both Ends

C

None

(no code)

Select

Cancel

Refine your search

Clear Filter

Expand All

Full Screen

Assembly Length: Clear

Selected values:

45.0

Select values

Available from 1 to 995

Assembly Pulling Grip

Search results:

Part number

P32LJ2P2R045A

P32LJ2P2R045B

P32LJ2P2R045C

P32LJ2P2R045D

2 F OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Unitboot, 45 Meters, 2.0mm /2.0mm, A-B, Indoor, Riser Interconnect, Circular, non Armored, Pull Grip-End A, ZConnect, Jumper Fiber Optic Cable Assembly

2 F OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Unitboot, 45 Meters, 2.0mm /2.0mm, A-B, Indoor, Riser Interconnect, Circular, non Armored, Pull Grip-End B, ZConnect, Jumper Fiber Optic Cable Assembly

2 F OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Unitboot, 45 Meters, 2.0mm /2.0mm, A-B, Indoor, Riser Interconnect, Circular, non Armored, Pull Grip-Both Ends, ZConnect, Jumper Fiber Optic Cable Assembly

2 F OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Unitboot, 45 Meters, 2.0mm /2.0mm, A-B, Indoor, Riser Interconnect, Circular, non Armored, Pull Grip-None, ZConnect, Jumper Fiber Optic Cable Assembly

1-4 of 4 parts

FIG. 12P

Part Number

Search

Part Number Configurators

Part Number Complete

P32LU20PRM045B

2 F OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Uniboot, 45 Meters, 2.0mm / 2.0mm, A-B, Indoor, Riser Interconnect, Circular, non Armored, Pull Grip-End B, ZConnect, Jumper Floor Fiber Optic Cable Assembly

Download:

Refine your search

Clear Filter

Expand All

Collapse All

(-) Assembly Length clear

Selected values:

45.0

Select values

Available from 1 to 995

Export results:

Part Number

P32LU20PRM045B

2 F OM3 Multimode, LC PC Duplex Clipped - LC PC Duplex Uniboot, 45 Meters, 2.0mm / 2.0mm, A-B, Indoor, Riser Interconnect, Circular, non Armored, Pull Grip-End B, ZConnect, Jumper Floor Fiber Optic Cable Assembly

1-1 of 1 parts

P

Assembly Type

3

Fiber Type

2

Fiber Total # Fibers

L

End Connect

0

Assembly Length

5

Pulling Grip

FIG. 12Q

Search

>

Part Number Configurators

Zero Connect | Fiber Optic Assemblies

P

3

2

L

U

2

0

P

R

M

0

4

5

B

Assembly Type

Fiber Type

Fiber Total #

End A Connector

End B Connector

Log Diameter

Breakout Length

Cable Rating

Assembly Length Unit

Pulling Grip

Reset & Start Over

Copy

Export results:

1-1 of 1 parts

Part number

932LU20R045B

Details

2 F OM3 Multimode, LC PC Duplex Cleaved - LC PC Duplex Uniboot, 45 Meters, 2.0mm / 2.0mm , A-B , Indoor, Riser Interconnect, Circular, non Armored , Pull Grip-End B, ZConnect, Jumper Fiber Optic Cable Assembly

Refine your search

Clear Filters

Expand All

Collapse All

(-) Assembly Length Clear

Selected values:

45.0

Select values

Available from 1 to 995

FIG. 12R

TECHNIQUES FOR CONFIGURABLE PART GENERATION

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is a continuation of U.S. patent application Ser. No. 18/218,267, filed Jul. 5, 2023, which is a continuation of U.S. patent application Ser. No. 17/382,605, filed Jul. 22, 2021, now U.S. Pat. No. 11,734,741, issued Aug. 22, 2023, which is a continuation of U.S. patent application Ser. No. 16/153,381 filed Oct. 5, 2018, now U.S. Pat. No. 11,087,375, issued Aug. 10, 2021, which is a division of U.S. patent application Ser. No. 14/704,636 filed May 5, 2015 now U.S. Pat. No. 10,121,177. The disclosure of the prior application is incorporated herein in its entirety by reference.

TECHNICAL FIELD

[0002] Certain example embodiments described herein relate to systems and/or methods for generating, storing, and retrieving data that can be used to generate part numbers for a configurable product. More particularly, certain example embodiments described herein relate to systems and/or methods for real-time generation of part numbers and/or specification information for a configurable product based on rules that do not require storing a part number for each possible configuration of the configurable product.

BACKGROUND AND SUMMARY

[0003] Suppliers of products manage product databases that store records of their products. Some of the products are configurable products with product features that can be configured to meet specific requirements. Product databases with configurable product include a list of product part numbers that reflect every possible combination of product features. Based on the list, the customer may select a product having features that match the customer's needs. The customer may also select features that the product needs to have and the records in the product database may be searched to find configured products matching the customer's selections.

[0004] Cables are an example of a configurable product. The supplier may generate a database with records of different cable configurations. A customer may select a cable from the database with the desired features (e.g., cable length, cable color, cable type, type of connectors, number of connectors, or type of shielding). The customer may also be provided with a user interface to select desired features of the cable and, based on the selections, be provided with configured cables from the database that match the selections.

[0005] However, as the number of possible features of a product increases, the size and complexity of the product database exponentially increases. The large number of records reduces the speed with which the results can be returned to a customer and makes it more difficult to present the results efficiently.

[0006] Certain example embodiments of this application address these and/or other concerns. For instance, certain example embodiments relate to a computer implemented method for processing a search request for part numbers of a configurable product. The method may include displaying a user interface for receiving a user input search request for the part numbers of the configurable product and receiving,

via the user interface, the user input search request defining one or more configurable properties of the configurable product. The method may include analyzing the user input search request to determine entities present in a database matching the one or more configurable properties of the user input search request, and determining virtual families stored in the database including the entities. Each virtual family may include one or more independent groups defining configurable properties of the configurable product and part number positions of the part number corresponding to the configurable properties. Each independent group may include part number positions of the part number for characters, number and/or symbols that do not depend on characters, number and/or symbols at part number positions of other independent groups. Based on the determined virtual families including the entities, a calculation may be made to determine a total number of matching products. In addition, the method may include determining the part numbers of the configurable product matching the user input search request, wherein the part numbers are determined based on allowed characters, number and/or symbols for the part number positions defined in the independent groups of the virtual families including the entities matching the one or more configurable properties of the user input search request. A list of part numbers determined to match the user input search request may be displayed to a user on the user interface.

[0007] According to an embodiment of the present disclosure, the independent groups are generated by receiving specification information for the configurable product, generating an independent group for each symbol group, merging independent groups having the same configurable properties to form a new independent group; and merging independent groups that, based on at least one constraint, dependent on each other, wherein the dependent independent groups are merged to form a new independent group. The received specification information may include a plurality of symbol groups for the configurable product. The received specification information may also include at least one constraint involving at least one symbol group. The symbol groups define a format of the part number of the configurable product and each symbol group includes one or more part number positions of the part number for the characters, number and/or symbols corresponding to the configurable properties of the configurable product.

[0008] According to an embodiment of the present disclosure, the possible part number positions formed based on the independent groups of one virtual family have a same length.

[0009] Certain example embodiments of the present disclosure relate to a computer implemented method for building a configurable product data store. The method including receiving specification information for a configurable product and, based on the specification information, generating a plurality of independent groups. The specification information includes at least one symbol group for the configurable product. The specification information may also include at least one constraint involving at least one symbol group, and/or at least one conditional particular for at least one symbol group. The symbol group(s) may define a format of a part number of the configurable product and each symbol group includes one or more part number positions of the part number for characters, number and/or symbols corresponding to configurable properties of the configurable product.

Each independent group includes part number positions for characters, number and/or symbols that do not depend on characters, number and/or symbols at part number positions of other independent groups. The plurality of independent groups are generated by generating an independent group for each symbol group, merging independent groups having the same configurable properties to form a new independent group, and merging independent groups that, based on the at least one constraint, dependent on each other, wherein the dependent independent groups are merged to form a new independent group. When multiple lengths of the part number positions can be generated from the generated independent groups, a plurality of virtual families are generated such that each respective virtual family, based on the independent groups in the virtual family, provides characters, number and/or symbols for part number positions that are of a same length. The generated virtual families are stored a database.

[0010] Non-transitory computer readable storage mediums tangibly storing instructions for performing the above-summarized and/or other approaches also are provided by certain example embodiments, as well as corresponding computer programs.

[0011] These features, aspects, advantages, and example embodiments may be used separately and/or applied in various combinations to achieve yet further embodiments of this invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] These and other features and advantages may be better and more completely understood by reference to the following detailed description of exemplary illustrative embodiments in conjunction with the drawings, of which:

[0013] FIG. 1 is a block diagram illustrating a system in accordance with an embodiment of the present disclosure;

[0014] FIG. 2 illustrates an exemplary system for building a data store and providing part numbers for configurable products based on data stored in the data store according to an embodiment of the present disclosure;

[0015] FIG. 3 illustrates a method 300 for generating rules for part number generation according to an embodiment of the present disclosure;

[0016] FIG. 4 illustrates family specifications for a product according to an embodiment of the present disclosure;

[0017] FIG. 5 illustrates a method for generating meta data from family specifications according to an embodiment of the present disclosure;

[0018] FIG. 6 illustrates a method for creating and storing virtual families from the current independent groups according to an embodiment of the present disclosure;

[0019] FIG. 7 illustrates virtual families with corresponding independent groups generated in response to a constraint according to an embodiment of the present disclosure;

[0020] FIG. 8 illustrates a hierarchical view of the meta data for a first family according to another embodiment of the present disclosure;

[0021] FIG. 9 illustrates a flat view of the meta data for a first family according to an embodiment of the present disclosure;

[0022] FIG. 10 illustrates a method for performing a search query according to an embodiment of the present disclosure;

[0023] FIG. 11 illustrates iterative steps that may be made to determine the part number of parts to be returned according to an embodiment of the present disclosure; and

[0024] FIGS. 12A-12R illustrate the process of making selections of a configurable product according to an embodiment of the present disclosure.

DETAILED DESCRIPTION

[0025] FIG. 1 is a block diagram illustrating a system 100 in accordance with an embodiment of the present disclosure. The system of FIG. 1 may provide part numbers and specifications for configurable products. As shown in FIG. 1, a server 110 may communicate with one or more user devices 120 and one or more supplier devices 130. The components of the system 100 may be coupled to each via a communication link 140. The server 110 may also be coupled directly or via the communication link 140 to a database 112.

[0026] The server 110 may receive information about configurable products from a supplier device 130 and process the data to build a data store to provide information about configurable products. The data store may be stored in the database 112. The data store may be used to generate part numbers and/or specifications of configured products on the fly. As discussed in more detail below, a part number builder may process the received information about the configurable products to generate a set of rules that are used to generate the part numbers and/or specification information for the configured parts. By generating and storing the rules instead of each possible configurable part number and all of the part's data, the size of the required database 112 is not depend on the number of parts. Accordingly, the size of the database does not exponentially increase as the number of configurable product features increases. In addition, the part numbers can be provided quickly and efficiently without significant delay attributed to searching large databases. The database 112 may also store full data for parts added or modified manually. The database 112 may include a plurality of different databases dedicated for specific application. For example, a first database may include data (e.g., rules) for generating part numbers and a second database may include specification data (e.g., specification documentation, images, part descriptions). One or more of the databases may be a relational database.

[0027] The part numbers and the specifications of the configured product may be provided in response to user requests made on the user device 120. The user requests may be made via a user interface provided on the user device 120. The user interface may be provided via an application stored on the user device 120 or may be provided on the user device 120 via a webpage (e.g., maintained by the server 120). As the user makes selections of product configurations, a list of product part numbers matching the selections can be displayed based on the rules stored in the database 112. The available selections for configuring the product may be modified (e.g., removed or limited) based on the rules in response to already selected configurations of the product. The user may select one or more of the product part numbers to receive specification information and/or ordering details (e.g., price and/or availability).

[0028] FIG. 2 illustrates an exemplary system 200 for building a data store and providing part numbers for configurable products based on data stored in the data store according to an embodiment of the present disclosure. The data store 210 may store data for generating part numbers and/or specification information of configurable products. A faceting engine 220 and a search engine 230 may use the

data stored in the data store **210** to generate the part numbers and/or retrieve specification information of configurable products. The generated part number and/or the specification information of the configured products may be presented to a user via the presentation layer **240**. FIGS. **12A-12R** illustrate a user interface that may be presented via the presentation layer **240**.

[0029] The data in the data store **210** may include configurable product meta data and/or static product data. The configurable product meta data may include generation rules for generating part numbers of configurable products. The configurable product meta data may be generated based on configurable product specification data received from a user (e.g., supplier of the product). The static product data may correspond to a specifically configured product and may include full data of the configured product. For example, the static product may be a product that is manually modified after being generated based on the configurable product meta data.

[0030] The faceting engine **220** may perform faceted search of the meta data stored in the data store **210**. The meta data stored in the data store **210** may be organized according to a faceted classification system allowing the assignment of an object to multiple taxonomies (sets of attributes), and enabling the classification to be ordered in multiple ways, rather than in a single, predetermined, taxonomic order. The faceted classification may provide for an analytic-synthetic classification scheme with objects assigned to multiple taxonomies. The faceted search may provide search results that are filtered based upon aspects or facets that are particular to the query being searched. For instance, if a query is received by the search engine **230** containing the term “12 fibers,” facets that are specific to the query may include “12” or “fiber” or “multi fiber.” The meta data being organized according to the faceted classification system allows for fast and flexible way to provide real-time search results and with ad hoc querying abilities through the use of keywords. The faceting engine **220** may return results for a search query and facet counts providing a breakdown or summary of the results based on some simple criteria, which can be used to help implement more advanced searches.

[0031] The configurable product meta data may be generated by a PNB processing engine **250** based on information about the configurable product provided by a part number builder **260** and/or a specification database **270**. The information about the configurable product may include the specifications of the configurable product, which includes constraints and/or particulars.

[0032] The static product data may be input via an application for generation static parts **290** and stored in the data store **210**. The application for generation static parts **290** may provide a user interface to receive a part number and specification information of a specifically configured product. In another embodiment, the application for generation static parts **290** may receive user inputs to configure a part based on the configurable product meta data, receive user defined modification to the configured product specifications and/or part number, and store the information for the modified configured product with an associated part number in the data store **210**. The information for the modified configured product that is stored in the data store **210** may include the full specification of the part. Because the full specification of the modified configured product is stored in

the data store **210** the system requirements may linearly increase with respect to the number of modified configured products.

[0033] The part number builder **260** and the PNB processing engine **250** may receive the configurable product specification information and process the specification information to generate meta data that can be used by search engine. The part number builder **260** and the PNB processing engine **250** may generate meta data organized according to the faceted classification system allows for faceted searched to be performed

[0034] The specification database **270** may store information about the configurable products. The specification database **270** may store information received from suppliers of the products, and may include, for example, configurable features of a product, specifications of the features, constraints, particulars, part number format, images of the product and/or product features, technical information, cost, and/or product availability. The information stored in the specification database **270** may be used by the part number builder **260** and/or the PNB processing engine **250** to generate the configurable product meta data which is stored in the data store **210**. The information stored in the specification database **270** may be retrieved and displayed to a user via the presentation layer **240** after a user configures and selects a configured product.

[0035] The user interface **262** may be used to receive information about the configurable product from a user (e.g., supplier of the configurable product). The information stored in the specification database **270** may be input via the user interface **262**.

[0036] FIG. **3** illustrates a method **300** for generating rules for part number generation according to an embodiment of the present disclosure. The method **300** for generating the part number generation rules may be performed, for example, by one or more components shown in FIG. **2**.

[0037] The method **300** may include defining product families **310** to provide a list of families for one or more configurable products. The product families may be defined based on user specified families via a user interface. A family may correspond to a single configurable product having a plurality of configurable features.

[0038] Next, for each defined family, family specifications may be defined **320**. The family specification for each defined family may include basic information about the family, part number format, constraints, locations (e.g., URLs) of images and datasheets that can be downloaded and attached to each product, particulars, related parts, and/or short values.

[0039] The part number format may define the characters, number, and/or symbols that correspond to specific features of the product and/or the specific arrangement of the characters, number, and/or symbols. For example, the part number format may require that the at a first position of the part number a single character defines an assembly type of a cable, at a second position of the part number a single number defines a type of fiber in the cable, and at a third position of the part number a number defines the number of total fibers in a cable.

[0040] The basic information may include the manufacturer, product category, description, title, subtitle, data source, trademarks, and/or display options. The related parts may provide criteria defining which parts are deemed related to other parts. The related parts may, for example, mark as

related all parts that have identical numbers except symbols at a predefined position (e.g., a third position of the part number), and/or mark as related all parts that have all identical attributes except for value of one attribute (e.g., fiber count). When the user views a part, the related parts of the viewed part may also be displayed to the user.

[0041] Each part may have two descriptions automatically generated. A first description may be a long description and the second description may be a short description. The second description may be derived from the first description. The long description may use full attribute values of the part (e.g., 12 Fiber Cable). The short description may use short values (e.g., 12 F Cbl). A mapping (e.g., via a mapping table) may be used to provide a correspondence between the short description and the long description. For example, the mapping may provide that “Fiber” corresponds to “F” and that “Cable” corresponds to “Cbl.” Thus, the system may generate a long description from a short description, or vice versa, by consulting the mapping.

[0042] When the product families and the specification of the product families are defined, a request may be made to process the defined family specifications to generate the metadata **330**. The request to process the defined family specifications may be made when new information is provided to the family specifications or when modifications are made to the family specifications. The metadata may be created such that the search engine can perform faceted searches and generate the part numbers on the fly.

[0043] The generated meta data may be stored in the sandbox **340** and/or the data store **350**. The meta data stored in the sandbox **340** may provide an isolated version of the meta data. The isolated version of the meta data in the sandbox **340** may allow for the user to review the parts generated based on the meta data and make modifications to the family specifications **360**. Based on the modifications to the family specifications, the generation of the meta data **330** may be repeated to update the meta data.

[0044] The meta data stored in the data store **350** may provide meta data for an application and/or website generating the part numbers on the fly in response to user requests. In one embodiment, the meta data from the sandbox may be merged into the meta data that is already stored in the data store.

[0045] FIG. 4 illustrates family specifications for a product according to an embodiment of the present disclosure. The family specifications may define the part number format **410**, constraints **420**, and particulars **430**. FIG. 4 illustrates family specifications for a cable but, as one of ordinary skill in the art would understand, the part number format **410**, constraints **420**, and particulars **430** may be provided for other products.

[0046] As shown in FIG. 4, the part number format **410** defines a plurality of symbol groups (e.g., symbol group #1, symbol group #2, and symbol group #3). Each symbol group may include one or more symbols. For example, symbol group #1 includes three symbols at part number positions n_1 , n_2 , and n_5 . Symbol group #2 includes one symbol at part number position n_4 . Symbol group #3 includes one symbol at part number position n_3 . Symbol group #4 includes four symbols at part number positions n_6 , n_7 , n_8 , n_9 .

[0047] Each symbol group may be a code table type or a field type. A code table type symbol group (e.g., symbol group #1) may define a code (e.g., combination of character,

numbers and/or symbols) corresponding to specific product features. Each code may define a plurality of product features of the product. For example, symbol group #1 may include code AB that defines cable with fiber name OM1 having 4 fibers.

[0048] A field type symbol group (e.g., symbol group #2, or symbol group #3) may provide a value (e.g., character(s) and/or numeral(s)) for a field corresponding to one or more features of the product. In one embodiment, a field type symbol group may include a single field corresponding to only one feature of the configurable product. For example, symbol group #2 is a field type symbol group with the field defining a number of fibers. One or more of the symbol groups may include restrictions for values that can be provided in the symbol group. For example, for symbol group #2, the fourth symbol of the part number may be restricted to number values between 2 and 8 with increments of 2.

[0049] The constraints **420** may define limitations on certain features of a product when one or more conditions are satisfied. The conditions may include selection of specific values for a feature and/or selection of a feature. Each constraint may include a plurality of conditions (e.g., greater than, less than, equal to) and may include AND conditions, OR conditions or a combination of AND and OR conditions. For example, a first condition may require that when the number of fibers ≤ 4 AND brand name $\neq$ XCABLE THEN length of cable ≥ 100 . A second condition may require that when the number of fibers > 2 THEN brand name = SUPERCABLE. In one embodiment, the family specifications may include no constraints.

[0050] The particulars **430** may define requirements that must be satisfied when one or more conditions are present. The particulars **430** may include conditional particulars that are applied when one or more defined conditions are satisfied and/or static particulars that are applied without having to meet any specified conditions. For example, a conditional particular may require that for all parts with number of fibers ≤ 4 AND brand name $\neq$ XCABLE assign value “multimodal” to fiber type.

[0051] FIG. 5 illustrates a method **500** for generating meta data from family specifications according to an embodiment of the present disclosure. The method **500** for generating the meta data can be performed, for example, by one or more components shown in FIG. 2. In one embodiment, the method **500** may be performed by the PNB processing engine **250**. The method **500** may be performed to generate the meta data each time product specification information is added or modified for configurable products.

[0052] The method **500** may receive family specifications including, for example, part number format, constraints, and/or particulars and generate meta data including virtual families of independent groups. Thus, a single family may be divided into independent groups of one or more symbols, with an exclusive set of particulars assigned to each group. An independent group may include one or more part number symbol positions with character(s) at each position(s) that do not depend on character(s) at position(s) outside of the independent group.

[0053] As shown in FIG. 5, the method **500** may include retrieving symbol groups from the family specifications **510**. Each of the retrieved symbol groups may initially be treated as an independent group (e.g., a first type of independent group that does not have any modifications). For example,

each of the symbol four groups shown in part number format **410** of FIG. 4 may be treated as an independent group providing the four independent groups listed in Table 1.

TABLE 1

Independent group 1: n_1, n_2, n_5
Independent group 2: n_4
Independent group 3: n_3
Independent group 4: n_6, n_7, n_8, n_9

[0054] Next, a determination may be made as to whether any code tables from one group uses fields in another group **520**. If a code table from one group uses fields in another group (YES in step **520**), then the corresponding groups may be merged **530**. For example, code table in symbol group 1 (i.e., independent group 1) uses “a number of fibers” and “a number of fibers” is also used in symbol group 2 (i.e., independent group 2). Accordingly, independent group 1 and independent group 2 may be merged to provide a new independent group 5 that includes symbol positions from both groups.

[0055] Table 2 lists the current independent groups after the merger of independent group 1 and independent group 2.

TABLE 2

Independent group 5: n_1, n_2, n_4 n_5
Independent group 3: n_3
Independent group 4: n_6, n_7, n_8, n_9

[0056] In one embodiment, when two code tables are merged, the rows may be combined only where all fields that the groups have in common (of which there can be more than one) have the same values. Such merging may provide for implicit constraints. For example, consider a symbol group #5 including a table with two rows (first row with Fiber name: OM1; #o f fibers: 4; and second row with Fiber name: OM1; #of fibers: 8) is merged with symbol group #1 shown in FIG. 4. With the merger only the first row of symbol group #5 has a corresponding row (e.g., common fields with same values) in symbol group #1 (i.e., second row). Accordingly, with the merger all other rows would be discarded when symbol group #1 is merged with symbol group #5.

[0057] Next, a determination may be made as to whether the current independent groups are dependent on each other **540**. The determination of which groups are dependent on other groups may be made based on the constraints in the family specifications. If based on the constraints one group depends on another group (YES in step **540**), the dependent groups may be merged to form a new independent group. The merging of groups may be prevented if the merged group would generate a large number of possible values (over a predetermined number of values). The predetermined number of values may be determined based on a function of available working memory (RAM), CPU speed, and/or the nature of the family (e.g., whether there are many virtual families created for different lengths). For example, on a single server with 16 GB RAM, an upper limit for a single family may be a few million (e.g., ≤ 5) possible values split between 30-50 virtual families (avg. 167,000 per family).

[0058] There may be a tradeoff between the number of values and the number of virtual families because when the

groups are not merged, the number of virtual families may be doubled (when there are empty families, which can be discarded, this number may be lower and not be doubled). Handling virtual families thus may be considered costly in some cases. For example, one virtual family with 5,000,000 values may be preferable over the same number of values split between two families or over 4,000,000 values split between two families. It may be preferable, if possible, to split 10,000 values between 32 families. However, such considerations may not always come into play (e.g., when there is a relatively small database or number of combinations, significant processing power is provided, etc.).

[0059] The family specifications shown in FIG. 4 include two constraints. The first constraint requires that when “the number of fibers” and “the brand name” meet predetermined conditions, the length of the cable needs to be less than 100. Accordingly, the first constraint makes the independent group with “the number of fibers” (i.e., independent group 5), the independent group with “the brand name” (i.e., independent group 3), and independent group with “the length of cable” (i.e., independent group 4) be dependent on each other. However, because the length of “the length of cable” can be one of 1,000 possible values, merging these groups to take account of the first constraint would produce a very large group (e.g., a number of combinations that is above a predetermined value). Accordingly, the first constraint is not taken into consideration at this time by merging the groups, but can be considered by other means later.

[0060] The second constraint requires that when “the number of fibers” meets a predetermined condition, the brand name of the cable needs to be a particular brand. Accordingly, the second constraint makes the independent group with “the number of fibers” (i.e., independent group 5) and the independent group with “the brand name” (i.e., independent group 3) be dependent on each other and cab be merged to provide a new independent group 6. Independent group 5 can be merged with independent group 3 because the merger will not provide a very large group (i.e., the merged group will have possible combinations that is below a predetermined value). Table 3 lists the current independent groups after the merger of independent group 5 and independent group 3.

TABLE 3

Independent group 6: n_1, n_2, n_3, n_4 n_5
Independent group 4: n_6, n_7, n_8, n_9

[0061] With consideration of the second constraint, the number of possible values in independent group 6 will be reduced to provide.

TABLE 4

Number of Fibers	Fiber Name	Brand Name	n_1	n_2	n_3	n_4	n_5
2	OM1	SUPERCABLE	A	B	S	2	C
2	OM1	XCABLE	A	B	X	2	C
4	OM1	SUPERCABLE	A	B	S		4
6	OM1	SUPERCABLE	A	B	S	6	C
8	OM2	SUPERCABLE			S		8

[0062] Next, a determination may be made as to whether the conditional particulars have conditions from multiple groups **560**. If the conditional particulars have conditions

from multiple groups (YES in step **560**), then the groups may be merged **570**. For the family specification shown in FIG. 4, the conditional particulars (i.e., the number of fibers and the brand name) are from the same independent group and thus merging of groups is not necessary.

[0063] The new independent group created by merging independent groups and taking account of constraints, and/or particulars may be a second type of independent groups.

[0064] With the constraints and the particulars taken into account, virtual families from the current independent groups may be created **580** and stored as metadata in the storage **590**. The meta data for all of the independent groups may be stored in a single table. The meta data may also include dedicated tables for manually defined products (e.g., a single table including all the information for each manually defined product). The metadata may be stored in a database configured to implement hierarchical faceting. Such a database may support pivot facets. For example, the metadata may be stored in Apache Lucene™ Solr platform. The creating of the virtual families including the independent groups that correspond to the properties of the configurable product allow for facet searches to be performed and to perform pivot faceting to facet within the results of the parent facet.

[0065] FIG. 6 illustrates a method **600** for creating and storing virtual families from the independent groups according to an embodiment of the present disclosure. The method **600** for creating and storing virtual families from the current independent groups can be performed, for example, by one or more components shown in FIG. 2. In one embodiment, the method **600** may be performed by the PNB processing engine **250**.

[0066] The independent groups generated from the family specifications (e.g., by method **500**) may provide part number symbols of varying length. For example, as shown in Table 4, the part number symbols generated from independent group 6 may result in different lengths (e.g., ABS2C, ABX2C, ABS4, ABS6C and S8). To enable wildcard searches (e.g., ABC*DEF or *DEF) by the search engine (e.g., search engine **230** shown in FIG. 2), the method **600** may generate virtual families such that all of the part number symbols provided by a virtual family is of the same length. Accordingly, one virtual family may provide part number symbols of one length and another virtual family may provide part number symbols of another length.

[0067] The method **600** may begin by determining part number length combinations for each independent group **610**. As an example, independent group 4 always has a part length of 4 and independent group 6 has possible part lengths of 5, 4, and 2 (see Table 4 showing the three possible part lengths). Accordingly, the possible part number length combinations for the combination of independent groups 4 and 6 will be lengths of 9, 8, or 6.

[0068] Next, the method **600** may take account of each constraint not handled by merging groups based on the constraint (e.g., constraints that would have produced groups with a number of possible combinations over the predetermined number). As shown in FIG. 6, for each constraint not handled by merging groups, the method **600** may determine inverse constraint **632**, for each length combination, generate two copies of length combinations **634**, associate the constraint with the first copy of length combination **636**, associate the inverse constraint with the second copy of length combination **638**, and replace original

length combination with the first and second copy of length combinations **640** including the constraint and the inverse constraint, respectively.

[0069] With all of the constraints taken into account, for each part number length combination, possible part number symbols of each independent group may be determined **642** and stored in storage **644**. The possible part number symbol combinations for each independent group may be determined while taking into account the constraints attached to the part number length combinations. The maximum number of length combinations may be the original number of length combination times two raised to the number of constraints. Because empty combinations are discarded the actual number of length combination will generally be less than the maximum number of length combinations. The empty combination may be a combination in which at least one independent group is empty (e.g., the independent group has no values allowed by the constraints).

[0070] As discussed above with reference to the family specifications shown in FIG. 4, the independent groups associated with the first constraint were not merged because such a merger would produce a very large group. This constraint can now be considered by determining an inverse constraint of the first constraint. With the first constraint being “if the # of fiber<=4 AND brand name< >XCABLE THEN length>=100” the inverse constraint of the first constraint would be “if the # of fiber>4 OR brand name=XCABLE THEN length can have any value.” The first constraint can be applied to a first copy of each length combinations and the inverse of the first constraint can be applied to a second copy of each length combinations.

[0071] The resulting independent groups with the first constraint and the inverse of the first constraint are shown in FIG. 7. As shown in FIG. 7, four virtual families are generated with one of the first constraint and the inverse of the first constraint being applied to the family. Each virtual family includes the sixth independent group and fourth independent group. The virtual families may be saved in storage as meta data.

[0072] FIG. 8 illustrates a hierarchical view of the meta data for a first family according to another embodiment of the present disclosure. The first virtual family may include a first independent group and a second independent group. The search engine (e.g., search engine **230** shown in FIG. 2) may produce six parts from the first virtual family. A first part number being ABFBGC for a black XCABLE with 12 fibers, a second part number being ABABGG for a yellow XCABLE with 12 fibers, a third part number being ABFBHC for a black PLUS with 36 fibers, a fourth part number being ABABHG for a yellow PLUS with 36 fibers, a fifth part number being ABFBPC for a black NAME with 12 fibers, and a sixth part number being ABABPG for a yellow NAME with 12 fibers. The search engine may produce two parts from the second virtual family. A first part number being ABC for a green XCABLE with 12 fibers and a second part number being ABD for a red ABCDE with 36 fibers. The virtual families may be invisible to a user performing a search. In response to a search, eight part numbers (six from the first virtual family and two from the second virtual family) could be provided from the first family.

[0073] FIG. 9 illustrates a flat view of the meta data for a first family according to an embodiment of the present disclosure. The meta data shown in FIG. 9 corresponds to

the meta data shown with a hierarchical view in FIG. 8. While FIGS. 8 and 9 illustrate meta data for a single family, data for a plurality of heterogeneous families may be stored in a similar manner. With such structure, a single query can return results from different families. In contrast to storing data of the plurality of heterogeneous families in a single table in the manner suggested above, traditionally, different families have been stored in separate database tables. Such structures required multiple queries and/or for products from a family to have a same number field formats. In contrast, the embodiment of the present disclosure allow for multiple virtual families and/or families to be stored in a single table and all searched by a single query.

[0074] FIG. 10 illustrates a method 1000 for performing a search query according to an embodiment of the present disclosure. The method 1000 may be performed by a search engine (e.g., search engine 230 shown in FIG. 2). The method 1000 may begin by receiving a search query 1010. The search query 1010 may include a search string, search criteria, sorting options, and/or pagination selection. The search string may specify the features of a product a user desires. For example, the search string entered by a user may include “12 fiber ABCD*.” The search string may include symbols for wild searches and is not limited to any combination of searchable properties. The search treats all configurable properties as being searchable.

[0075] The search criteria may include selections from predefined search criteria for a product. The predefined search criteria may be preselected based on the kind of product(s) for which the search is performed and/or terms in the search string. For example, the criteria may include providing parts with number of fibers between 12 and 36, and the brand name to be equal to “SUPERCABLE.” The sorting options may define how the results are displayed to the user. For example, the sorting options may provide the field by which to sort the product (e.g., by manufacturer) and/or the direction (e.g., ascending or descending order).

[0076] The received search query may be parsed 1020 and a determination may be made as to which families, virtual families, and/or independent groups contain matching results 1030. The parsing of the search query may include comparing each word, character combination and/or symbol combination present in the query against a database of entities that correspond to all entries present in the metadata. For example, the search query for “12 fiber ABCD*.” May be parsed to provide entries show in Table 5.

TABLE 3

# of fibers # of fibers unit of measure	12 Fiber
n_1	A
n_2	B
n_3	C
n_4	D

[0077] Determining which virtual families contain the matching results of the parsing, may include (1) retrieving pivot facets for family_id->virtual_family_id->independent_group_id and (2) for each virtual family, determine if there are matching records for every independent group that belong to the respective virtual family. Virtual families that have independent groups with no results may be discarded from the results.

[0078] Next, a calculation may be made to determine the total number of matching parts 1040. The following routine may be executed to determine the total number of matching parts.

```

total_count = 0
for each virtual-family
  family_count = 1
  for each independent-group
    group_count = independent-group.getNumFound( )
    family_count = family_count * group_count
  total_count=total_count + family_count
return total_count

```

[0079] Next, a calculation may be made to determine the facet counts 1050. The facet counts may provide a breakdown or summary of the results based on some simple criteria, which can be used to help implement more advanced searches. The facet count may not affect the results section of the matching products and part numbers. The calculated facet counts may provide list of possible values for each attribute and, for each value, the number of parts that will be returned if the value is added as a criterion to the search query. For example, after returning the search results for search query “12 fiber ABCD*,” the facet counts may be calculated for black, yellow, green, and red cables.

[0080] Determination part numbers for parts to be returned 1060 provides a list with part numbers that match the search query. Determining the part number may include performing a plurality of iterations to calculate a number of matching parts in each family, virtual family, and independent groups, and provide allowed symbols at each position that match the search query.

[0081] FIG. 11 illustrates iterative steps that may be made to determine the part number of parts to be returned. The search query may specify an offset of 2,000 and a limit of 3. The offset and limit may specify the pagination for the results. The offset and limit may be set in response to user input specifying a page number and/or page size indicating a number of results on each page. The system may translate the user input into the value for the offset and the value for the limit. The initial results may provide 1,000 part from the first family, 7,500 parts from the third family, and 5,000 parts from the eleventh family.

[0082] In the first iteration, the possible symbols allowed at a first part number position may be determined. FIG. 11 illustrates the three possible symbols (P, Q, or R) that are allowed at the first part number and shows the number of matching parts of each symbol for each virtual family. Because the offset is 2,000 and there are 1,000 parts that start with P in the first family, the parts starting with P can be discarded and the offset can be reduced to be 1,000. There are 10,000 parts that start with Q and because the limit is set to 3, all of the wanted parts will start with Q.

[0083] In the second iteration, the possible symbols allowed at a second part number position may be determined. FIG. 11 illustrates the two possible symbol groups of QA and QB that are allowed and shows the number of matching parts of each symbol group for each remaining family. Because the offset is 1,000 and the limit is set to 3, all of the wanted parts will start with QA.

[0084] In the third iteration, the possible symbols allowed at a third part number position may be determined. FIG. 11 illustrates the two possible symbol groups of QAO, QA1,

QA2, QA3, and QAD are allowed and shows the number of matching parts of each symbol group for the third family and fourth independent group. The parts for QAO can be skipped because the offset is 1,000, and the offset can be updated to be 0. Because there are no symbol combinations after QA1, the limit can be reduced by one to set limit to 2 and QA1 can be returned as one of the results. Because there are no symbol combinations after QA2, the limit can be reduced by one to set limit to 1 and QA2 can be returned as one of the results.

[0085] In the fourth iteration, the possible symbols allowed at a fourth part number position may be determined. FIG. 11 illustrates the one possible symbol QA3H is allowed and shows one match for the third family and fourth independent group. Because there are no symbol combinations after QA3H, the limit can be reduced by one to set limit to zero and QA3H can be returned as one of the results. Accordingly after four iterations, the returned part number may be QA1, QA2 and QA3H.

[0086] A determination of specification for the returned parts **1070** may include retrieving fields stored in the independent groups containing the matching results, retrieving information stored in a relational database for the retrieved fields, and compile short and long descriptions of the parts to be returned. The content for the short and long descriptions may be predefined by the supplier of the product. The information retrieved from the relational database may include part-specific information and information for the family.

[0087] Providing the search results **1080** may include displaying the total count of parts matching the search query, the determined part numbers, and the specification of the parts matching the search query. The search results may be displayed to a user based on the defined constraints, sorting options and/or pagination selections. The search results may also provide a list of possible values of each attribute and for each value, the number of parts that will be found if the value is added as a criterion to the search query.

[0088] FIGS. 12A-12R illustrate the process of making selections of a configurable product according to an embodiment of the present disclosure. While the configuration process in FIGS. 12A-12R is illustrated with reference to a configurable fiber optic cable, the process may be applied to other configurable products.

[0089] FIGS. 12A-12R illustrate a user interface for allowing a user to select desired configurations of a fiber optic assembly. The user interface allows a user to select configurable features of the product (e.g., assembly type, fiber type, fiber total # fibers, end A connector, end B connector, leg diameter, breakout length, cable, cable flame rating, assembly length unit of measure, assembly length, and pulling grip). Products that match the current configuration selections are listed by part number and with a short detailed description. The user may select a particular part number to obtain further specification information for the product and ordering information. The ordering information may include availability of the product, price of the product, where product can be ordered, and/or a request for a price quote.

[0090] As shown in FIG. 12A, before any configuration selections are made, a total of 49,737,193,488 possible parts are available for the fiber optic assemblies. The user interface is able to provide this information on the fly based on the part generation rules provided in the data store. The part

generation rules are implemented in the virtual families including the independent groups. Facet searches can easily be performed based on the information in the independent groups of the virtual families. As the user makes selections of product configurations, the part numbers of products matching the configuration selections are updated in real time. For example, as shown in FIG. 12C, after the user selects the assembly type, fiber type, and the breakout length, the number of parts matching this configuration is updated to include 10,135,080 parts.

[0091] The list of product numbers corresponding to the set of selected options may provide product numbers matching the results without having to complete or almost complete all of the option selections (i.e., define a complete the part number or a base of the part number). The results can be displayed from the start of the user interface before any selections are made and are updated as the user makes additional selections.

[0092] As shown in FIGS. 12A-12R as the user makes selection facet counts may provide a breakdown or summary of the results based on some remaining configurable options. For example, as shown in FIG. 12B, after selecting Assembly type P and breakout length 0, the facet counts may be provided based on “total number of fibers” and “fiber name.” The results may include the number of part number in each of the configuration option. While not shown in FIG. 12B, the results may be provided for each remaining options that has not been defined.

[0093] The user may manually enter a symbol for one or more configurable options. For example, the user may manually enter a number of fibers or a length desired in the fiber optic assembly. The user may also be provided with an interface for selecting the configuration for one or more features of the product. For example, as shown in FIG. 12E, in response to selecting “End A Connector,” the user may be displayed a selection box with “End A Connector” types that can be selected by the user. The selection box may display both selectable type of connectors and connector types that are not selectable in view of the already selected other configurations of the product. The not selectable type of connectors may be displayed as disabled rows.

[0094] The user is not restricted to select the product configuration in any specific order. The user may configure the product in any order and based on the already selected options, the available options for not yet selected configurations of the product may be updated in real time. The available options for not selected configurations may be obtained from virtual families with features matching the current selections. This is possible to do on the fly because the constraints and particulars are already considered in the generated virtual families and independent groups.

[0095] For one or more configurable options, the user may be provided with the ability to make multiple selections. For example, as shown in FIG. 12N, the user may select multiple values for the assembly lengths. The user may select a length of 45 meters and 55 meters. With these two selections, part numbers for both length may be displayed.

[0096] At any time during the selection of the configurable options, the user may select one of the displayed part number to obtain more information on the product. As shown in FIG. 12Q, when the product is selected or when the part number is completed, a user may be displayed a summary of the product details and with options to obtain additional information for the product (e.g., in a PDF file or

an Excel file). While not shown in FIGS. 12A-12R, the user interface may display images of the configured product and/or of the selectable features. The images may be generated based on CAD drawings and/or real images of the configurable product or features. The images may be associated with the virtual families of the configurable product. [0097] FIG. 12R illustrates a part number with all of the configurable options selected. The user can reset and start over the selection of the configurable options at any time during the selection process. In addition, the user may go back and make changes to any one of the selected configurations.

[0098] As shown in FIGS. 12A-12R, the user may perform enter a search string in the search dialog box to return parts matching the search string. The search string may be parsed and return part numbers from virtual families containing the matching results. With the results, one or more of the configurable selections may be automatically selected based on the search results. For example, if the user enters a search string of “number of fibers 2,” the number of fibers in the configuration selection area may be automatically selected.

[0099] It will be appreciated that as used herein, the terms system, subsystem, service, engine, module, programmed logic circuitry, and the like may be implemented as any suitable combination of software, hardware, firmware, and/or the like. It also will be appreciated that the storage locations, stores, and repositories discussed herein may be any suitable combination of disk drive devices, memory locations, solid state drives, CD-ROMs, DVDs, tape backups, storage area network (SAN) systems, and/or any other appropriate tangible non-transitory computer readable storage medium. Cloud and/or distributed storage (e.g., using file sharing means), for instance, also may be used in certain example embodiments. It also will be appreciated that the techniques described herein may be accomplished by having at least one processor execute instructions that may be tangibly stored on a non-transitory computer readable storage medium.

[0100] In the above description, numerous specific details are set forth to provide a thorough understanding of embodiments of the disclosure. One skilled in the relevant art will recognize, however that the various embodiments can be practiced without one or more of the specific details or with other methods, components, techniques, etc. In other instances, well-known operations or structures are not shown or described in detail to avoid obscuring aspects of the disclosure.

[0101] Although the processes illustrated and described herein include series of steps, it will be appreciated that the different embodiments of the present disclosure are not limited by the illustrated ordering of steps, as some steps may occur in different orders, some concurrently with other steps apart from that shown and described herein. In addition, not all illustrated steps may be required to implement a methodology in accordance with the present disclosure. Moreover, it will be appreciated that the processes may be implemented in association with the apparatus and systems illustrated and described herein as well as in association with other systems not illustrated.

[0102] The above descriptions and illustrations of embodiments of the disclosure, including what is described in the Abstract, is not intended to be exhaustive or to limit the embodiments to the precise forms disclosed. While specific embodiments of, and examples for, the embodiments are

described herein for illustrative purposes, various equivalent modifications are possible within the scope of the disclosure, as those skilled in the relevant art will recognize.

[0103] While the invention has been described in connection with what is presently considered to be the most practical and preferred embodiment, it is to be understood that the invention is not to be limited to the disclosed embodiment, but on the contrary, is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the appended claims. These modifications can be made to the embodiments in light of the above detailed description.

1. A computer implemented method for processing a search request for part numbers of a configurable product, the method comprising:

displaying a user interface configured to receive a user input search request for the part numbers of the configurable product;

receiving, via the user interface, the user input search request defining one or more configurable properties of the configurable product;

analyzing the user input search request to determine entities present in a database matching the one or more configurable properties of the user input search request, the database storing a plurality of virtual families, each virtual family of the plurality of virtual families including a plurality of independent groups, each independent group defining (1) at least one configurable property of the configurable product and (2) part number positions of the part number corresponding to the configurable properties in the independent group, each independent group of the plurality of independent groups including part number positions of the part number for one or more characters, one or more numbers and/or one or more symbols that do not depend on one or more characters, one or more numbers and/or one or more symbols at part number positions of other independent groups of the plurality of independent groups, and at least one configurable property of the configurable product is included in independent groups of at least two virtual families;

determining virtual families stored in the database including the entities matching the one or more configurable properties of the user input search request, wherein at least two of the determined virtual families include independent groups with a common configurable property;

determining the part numbers of the configurable product matching the user input search request, wherein the part numbers are determined based on allowed one or more characters, one or more numbers and/or one or more symbols for the part number positions defined in the independent groups of the virtual families determined to include the entities matching the one or more configurable properties of the user input search request; and

displaying information about one or more configurable products corresponding to one or more part numbers determined to match the user input search request.

2. The computer implemented method of claim 1, further comprising generating wherein the independent groups by: receiving specification information for the configurable product, the specification information including a plurality of symbol groups for the configurable product

and at least one constraint involving at least one symbol group, wherein the symbol groups define a format of the part number of the configurable product and each symbol group includes one or more part number positions of the part number for the one or more characters, one or more numbers and/or one or more symbols corresponding to the configurable properties of the configurable product;

generating an independent group for each symbol group; merging independent groups having the same configurable properties to form a new independent group; and merging independent groups that, based on the at least one constraint, dependent on each other, wherein the dependent independent groups are merged to form a new independent group.

3. The computer implemented method of claim 1, wherein the possible part number positions formed based on the independent groups of one virtual family have a same length.

4. The computer implemented method of claim 1, further comprising generating new virtual groups and additional independent groups in the database, wherein generating the additional independent groups includes:

receiving specification information for a new configurable product, the specification information including a plurality of symbol groups for the new configurable product, at least one constraint involving at least one symbol group, and at least one conditional particular for at least one symbol group, wherein the symbol groups define a format of a part number of the new configurable product and each symbol group includes one or more part number positions of the part number for one or more characters, one or more numbers and/or one or more symbols corresponding to configurable properties of the new configurable product;

based on the specification information, generating a plurality of independent groups, each generated independent group including part number positions for one or more characters, one or more numbers and/or one or more symbols that do not depend on one or more characters, one or more numbers and/or one or more symbols at part number positions of other independent groups in the database, wherein generating the plurality of independent groups includes:

generating an independent group for each symbol group; merging independent groups having the same configurable properties to form a new independent group; and merging independent groups that, based on the at least one constraint, dependent on each other, wherein the dependent independent groups are merged to form a new independent group; and

when multiple lengths of the part number positions can be generated from the generated independent groups, generating a plurality of new virtual families such that each respective new virtual family, based on the independent groups in the virtual family, provides one or more characters, one or more numbers and/or one or more symbols for part number positions that are of a same length; and

storing the new virtual families in the database.

5. The computer implemented method of claim 1, further comprising determining specifications for each part number determined to match the user input search request.

6. The computer implemented method of claim 5, wherein the specification for the part number is retrieved from a relational database based on fields stored in the independent groups used to generate the part number.

7. The computer implemented method of claim 1, further comprising:

determining facet counts providing, independent of the part numbers determined to match the user input search request, a breakdown of results based on multiple configurable properties of the configurable product; and

displaying the determined facet counts in the user interface.

8. The computer implemented method of claim 7, wherein the breakdown of the results displays a list of possible values of the configurable properties that have not been determined to match the user input search request, and the list of possible values of the configurable properties is displayed with a number of part numbers that will be returned if the listed configurable property is added to the user input search request.

9. The computer implemented method of claim 7, wherein the breakdown of the results displays a list of all possible values of the configurable properties that have not been determined to match the user input search request.

10. The computer implemented method of claim 1, wherein the user input search request is a search string and analyzing the user input search request includes parsing the search string.

11. The computer implemented method of claim 10, wherein the search string includes one or more characters, one or more numbers and/or one or more symbols defining a portion of the part number.

12. The computer implemented method of claim 1, wherein the user input search request is received by the user selecting displayed values for a plurality of configurable options of the configurable product on the user interface.

13. A part number generation system, comprising:

a user device configured to receive a search request for part numbers of a configurable product;

a non-transitory computer readable storage medium storing a database including a plurality of virtual families corresponding to the configurable product, each virtual family of the plurality of virtual families including a plurality of independent groups, each independent group defining (1) at least one configurable property of the configurable product and (2) part number positions of the part number corresponding to the configurable properties in the independent group, each independent group of the plurality of independent groups including part number positions of the part number for one or more characters, one or more numbers and/or one or more symbols that do not depend on one or more characters, one or more numbers and/or one or more symbols at part number positions of other independent groups of the plurality of independent groups, and at least one configurable property of the configurable product is included in independent groups of at least two virtual families; and

processing resources including at least one processor and a memory, the processing resources being configured to control the system to at least:

receive, via a user interface displayed on a display associated with the user device, the search request defining one or more configurable properties of the configurable product;

determine virtual families stored in the database including entities related to content of the search request, wherein at least two of the determined virtual families include independent groups with a common configurable property;

determine the part numbers of the configurable product matching the search request, wherein the part numbers are determined based on allowed one or more characters, one or more numbers and/or one or more symbols for the part number positions defined in the independent groups of the virtual families determined to include the entities matching the one or more configurable properties of the search request; and

display information about one or more configurable products corresponding to one or more part numbers determined to match the search request.

14. The part number generation system of claim **13** wherein each respective virtual family provides part number positions that are of a same length, and at least one virtual family provides part number positions having a length that is different from lengths provided by other virtual families.

15. The part number generation system of claim **13** further comprising a relational database configured to store specification information for the configurable product, and wherein the processing resources are further configured to control the system to retrieve, from the relational database, specifications for each part number determined to match the search request, wherein the specifications are retrieved from the relational database based on fields stored in the independent groups used to generate the part number.

16. A non-transitory computer readable storage medium having a program for generating part numbers for configured products stored thereon, the program comprising instructions that, when executed, cause a computing system including at least one processor and a memory to at least:

display a user interface configured to receive a user input search request for the part numbers of the configurable product;

receive, via the user interface, the user input search request defining one or more configurable properties of the configurable product;

analyze the user input search request to determine entities present in a database matching the one or more configurable properties of the user input search request,

the database storing a plurality of virtual families, each virtual family of the plurality of virtual families including a plurality of independent groups, each independent group defining (1) at least one configurable property of the configurable product and (2) part number positions of the part number corresponding to the configurable properties in the independent group, each independent group of the plurality of independent groups including part number positions of the part number for one or more characters, one or more numbers and/or one or more symbols that do not depend on one or more characters, one or more numbers and/or one or more symbols at part number positions of other independent groups of the plurality of independent groups, and at

least one configurable property of the configurable product is included in independent groups of at least two virtual families;

determine virtual families stored in the database including the entities matching the one or more configurable properties of the user input search request, wherein at least two of the determined virtual families include independent groups with a common configurable property;

determine the part numbers of the configurable product matching the user input search request, wherein the part numbers are determined based on allowed one or more characters, one or more numbers and/or one or more symbols for the part number positions defined in the independent groups of the virtual families determined to include the entities matching the one or more configurable properties of the user input search request; and

display information about one or more configurable products corresponding to one or more part numbers determined to match the user input search request.

17. The part number generation system of claim **13**, wherein the processing resources are further configured to control the system to generate new virtual groups and additional independent groups in the database, wherein generating the additional independent groups includes:

receiving specification information for a new configurable product, the specification information including a plurality of symbol groups for the new configurable product, at least one constraint involving at least one symbol group, and at least one conditional particular for at least one symbol group, wherein the symbol groups define a format of a part number of the new configurable product and each symbol group includes one or more part number positions of the part number for one or more characters, one or more numbers and/or one or more symbols corresponding to configurable properties of the new configurable product;

based on the specification information, generating a plurality of independent groups, each generated independent group including part number positions for one or more characters, one or more numbers and/or one or more symbols that do not depend on one or more characters, one or more numbers and/or one or more symbols at part number positions of other independent groups in the database, wherein generating the plurality of independent groups includes:

generating an independent group for each symbol group; merging independent groups having the same configurable properties to form a new independent group; and merging independent groups that, based on the at least one constraint, dependent on each other, wherein the dependent independent groups are merged to form a new independent group; and

when multiple lengths of the part number positions can be generated from the generated independent groups, generating a plurality of new virtual families such that each respective new virtual family, based on the independent groups in the virtual family, provides one or more characters, one or more numbers and/or one or more symbols for part number positions that are of a same length; and

storing the new virtual families in the database.

18. The non-transitory computer readable storage medium of claim **16**, wherein the program further comprises instructions that, when executed, further cause the computing system to generate new virtual groups and additional independent groups in the database, wherein generating the additional independent groups includes:

receiving specification information for a new configurable product, the specification information including a plurality of symbol groups for the new configurable product, at least one constraint involving at least one symbol group, and at least one conditional particular for at least one symbol group, wherein the symbol groups define a format of a part number of the new configurable product and each symbol group includes one or more part number positions of the part number for one or more characters, one or more numbers and/or one or more symbols corresponding to configurable properties of the new configurable product;

based on the specification information, generating a plurality of independent groups, each generated independent group including part number positions for one or more characters, one or more numbers and/or one or more symbols that do not depend on one or more characters, one or more numbers and/or one or more symbols at part number positions of other independent groups in the database, wherein generating the plurality of independent groups includes:

generating an independent group for each symbol group;

merging independent groups having the same configurable properties to form a new independent group; and merging independent groups that, based on the at least one constraint, dependent on each other, wherein the dependent independent groups are merged to form a new independent group; and

when multiple lengths of the part number positions can be generated from the generated independent groups, generating a plurality of new virtual families such that each respective new virtual family, based on the independent groups in the virtual family, provides one or more characters, one or more numbers and/or one or more symbols for part number positions that are of a same length; and

storing the new virtual families in the database.

19. The non-transitory computer readable storage medium of claim **16**, wherein each respective virtual family provides part number positions that are of a same length, and at least one virtual family provides part number positions having a length that is different from lengths provided by other virtual families.

20. The non-transitory computer readable storage medium of claim **16**, wherein displaying the information about one or more configurable products corresponding to one or more part numbers determined to match the user input search request includes displaying a total number of matching products.

* * * * *