

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250286840

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Thompson; Isaac Jordan

MESSAGE ROUTING BASED ON UNAVAILABILITY

Abstract

Asynchronous messaging on an instant messaging system is provided. The method comprises receiving an instant message from a send addressed to a recipient on the instant messaging system and determining a current user status of the recipient. Responsive to a determination the recipient is currently available, the instant messaging system sends the instant message to the recipient in real time. Responsive to a determination the recipient is currently unavailable, the instant messaging system, according to sender preferences, sends the instant message to the recipient via an alternative communication system or stores the instant message in a queue until triggered to send the instant message when the current user status of the recipient changes to available.

Inventors: Thompson; Isaac Jordan (Atlanta, GA)

Applicant: ADP, Inc. (Roseland, NJ)

Family ID: 88096670

Assignee: ADP, Inc. (Roseland, NJ)

Appl. No.: 19/088655

Filed: March 24, 2025

Related U.S. Application Data

parent US continuation 18479753 20231002 parent-grant-document US 12261808 child US 19088655

parent US continuation 17656301 20220324 parent-grant-document US 11777878 child US 18479753

Publication Classification

Int. Cl.: H04L51/043 (20220101); H04L51/046 (20220101); H04L51/56 (20220101)

Background/Summary

1. CROSS-REFERENCES TO RELATED APPLICATIONS [0001] This application claims the benefit of priority under 35 U.S.C. § 120 as a continuation of U.S. patent application Ser. No. 18/479,753, filed Oct. 2, 2023, which is a continuation of U.S. patent application Ser. No. 17/656,301, filed Mar. 24, 2022, both of which are hereby incorporated by reference herein in their entirety.

2. FIELD

[0002] The present disclosure relates generally to instant messaging systems, and in particular, to asynchronous messaging in instances of unavailable recipients.

3. BACKGROUND

[0003] Instant messaging services have well instantiated constructs from the early 2000s regarding sending messages and indicating user status. Some instant messaging (IM) services can even communicate if a message has been read or if the other party is typing a response in a high bandwidth connection to ensure that the sender is aware of the recipient's active response activity.

[0004] Therefore, it would be desirable to have a method and apparatus that take into account at least some of the issues discussed above, as well as other possible issues. For example, it would be desirable to have a method and apparatus that automate data management process.

SUMMARY

[0005] An illustrative embodiment provides a computer-implemented method for asynchronous messaging on an instant messaging system. The method comprises receiving an instant message from a send addressed to a recipient on the instant messaging system and determining a current user status of the recipient. Responsive to a determination the recipient is currently available, the instant messaging system sends the instant message to the recipient in real time. Responsive to a determination the recipient is currently unavailable, the instant messaging system, according to sender preferences, sends the instant message to the recipient via an alternative communication system or stores the instant message in a queue until triggered to send the instant message when the current user status of the recipient changes to available.

[0006] Another illustrative embodiment provides a system for asynchronous messaging on an instant messaging system. The system comprises a storage device configured to store program instructions and one or more processors operably connected to the storage device and configured to execute the program instructions to cause the system to: receive, from a sender, an instant message addressed to a recipient on the instant messaging system; determine a current user status of the recipient; responsive to a determination the recipient is currently available, send the instant message to the recipient in real time; and responsive to a determination the recipient is currently unavailable, according to sender preferences: send the instant message to the recipient via an alternative communication system; or store the instant message in a queue until triggered to send the instant message when the current user status of the recipient changes to available.

[0007] Another illustrative embodiment provides a computer program product for asynchronous messaging on an instant messaging system. The computer program product comprises a computer-readable storage medium having program instructions embodied thereon to perform the steps of: receiving, from a sender, an instant message addressed to a recipient on the instant messaging system; determining a current user status of the recipient; responsive to a determination the recipient is currently available, sending the instant message to the recipient in real time; and

responsive to a determination the recipient is currently unavailable, according to sender preferences: sending the instant message to the recipient via an alternative communication system; or storing the instant message in a queue until triggered to send the instant message when the current user status of the recipient changes to available.

[0008] The features and functions can be achieved independently in various embodiments of the present disclosure or may be combined in yet other embodiments in which further details can be seen with reference to the following description and drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] The novel features believed characteristic of the illustrative embodiments are set forth in the appended claims. The illustrative embodiments, however, as well as a preferred mode of use, further objectives and features thereof, will best be understood by reference to the following detailed description of an illustrative embodiment of the present disclosure when read in conjunction with the accompanying drawings, wherein:

[0010] FIG. 1 is a pictorial representation of a network of data processing systems in which illustrative embodiments may be implemented;

[0011] FIG. 2 depicts a block diagram illustrating an instant messaging system in accordance with an illustrative embodiment;

[0012] FIG. 3 depicts a flowchart illustrating a process for asynchronous messaging on an instant messaging system in accordance with illustrative embodiments;

[0013] FIG. 4 depicts a diagram illustrating a user interface with a Do not Disturb notice for an instant messaging system in accordance with an illustrative embodiment;

[0014] FIG. 5 depicts a diagram illustrating a user interface presenting a sender with messaging options in response to a Do not Disturb notice in accordance with an illustrative embodiment;

[0015] FIG. 6 depicts a diagram illustrating a user preferences and priority choice interface for an instant messaging system in accordance with an illustrative embodiment; and

[0016] FIG. 7 is an illustration of a block diagram of a data processing system in accordance with an illustrative embodiment.

DETAILED DESCRIPTION

[0017] The illustrative embodiments recognize and take into account one or more different considerations. For example, the illustrative embodiments recognize and take into account that some instant messaging (IM) services can communicate if a message has been read or if the other party is typing a response in a high bandwidth connection to ensure that the sender is aware of the recipient's active response activity.

[0018] The illustrative embodiments also recognize and take into account that current instant messaging services do not have administrative set up or preferences to support synchronous to asynchronous messaging when a recipient is busy or otherwise unavailable to receive an instant message (e.g., Do not Disturb). Current instant messaging services do not have protected Do not Disturb (DnD) status as messages can still be sent and act as disturbances to the recipient.

[0019] The illustrative embodiments provide an instant messaging system that enables asynchronous messaging when recipients are unavailable. The asynchronous protocol of the illustrative embodiments allows an instant message to be stored in a queue and sent in an alternative manner via the user's preference and priority of message type at a later time triggered by a status change of the recipient or sent immediately via an alternative communication system such as email or SMS text. By providing true asynchronous messaging, the illustrative embodiments enforce the validity of a DnD status. At the same time, the sender does not risk losing the text message or train of thought and does not have to manually park the text in another software or

clipboard solution because the instant messaging system itself can convert the rich text message to email or store the message until the presence servicer indicates the recipient's status as changed back to available/active.

[0020] With reference to FIG. 1, a pictorial representation of a network of data processing systems is depicted in which illustrative embodiments may be implemented. Network data processing system **100** is a network of computers in which the illustrative embodiments may be implemented. Network data processing system **100** contains network **102**, which is the medium used to provide communications links between various devices and computers connected together within network data processing system **100**. Network **102** might include connections, such as wire, wireless communication links, or fiber optic cables.

[0021] In the depicted example, server computer **104** and server computer **106** connect to network **102** along with storage unit **108**. In addition, client devices **110** connect to network **102**. In the depicted example, server computer **104** provides information, such as boot files, operating system images, and applications to client devices **110**. Client devices **110** can be, for example, computers, workstations, or network computers. As depicted, client devices **110** include client computers **112**, **114**, and **116**. Client devices **110** can also include other types of client devices such as mobile phone **118**, tablet computer **120**, and smart glasses **122**.

[0022] In this illustrative example, server computer **104**, server computer **106**, storage unit **108**, and client devices **110** are network devices that connect to network **102** in which network **102** is the communications media for these network devices. Some or all of client devices **110** may form an Internet of things (IoT) in which these physical devices can connect to network **102** and exchange information with each other over network **102**.

[0023] Client devices **110** are clients to server computer **104** in this example. Network data processing system **100** may include additional server computers, client computers, and other devices not shown. Client devices **110** connect to network **102** utilizing at least one of wired, optical fiber, or wireless connections.

[0024] Program code located in network data processing system **100** can be stored on a computer-recordable storage medium and downloaded to a data processing system or other device for use. For example, the program code can be stored on a computer-recordable storage medium on server computer **104** and downloaded to client devices **110** over network **102** for use on client devices **110**.

[0025] The phrase “at least one of,” when used with a list of items, means different combinations of one or more of the listed items can be used, and only one of each item in the list may be needed. In other words, “at least one of” means any combination of items and number of items may be used from the list, but not all of the items in the list are required. The item can be a particular object, a thing, or a category.

[0026] For example, without limitation, “at least one of item A, item B, or item C” may include item A, item A and item B, or item B. This example also may include item A, item B, and item C or item B and item C. Of course, any combinations of these items can be present. In some illustrative examples, “at least one of” can be, for example, without limitation, two of item A; one of item B; and ten of item C; four of item B and seven of item C; or other suitable combinations. In the depicted example, network data processing system **100** is the Internet with network **102** representing a worldwide collection of networks and gateways that use the Transmission Control Protocol/Internet Protocol (TCP/IP) suite of protocols to communicate with one another. At the heart of the Internet is a backbone of high-speed data communication lines between major nodes or host computers consisting of thousands of commercial, governmental, educational, and other computer systems that route data and messages. Of course, network data processing system **100** also may be implemented using a number of different types of networks. For example, network **102** can be comprised of at least one of the Internet, an intranet, a local area network (LAN), a metropolitan area network (MAN), or a wide area network (WAN). FIG. 1 is intended as an

example, and not as an architectural limitation for the different illustrative embodiments.

[0027] In the illustrative example, a “number of” when used with reference to items means one or more items. For example, a number of different types of networks is one or more different types of networks.

[0028] FIG. 2 depicts a block diagram illustrating an instant messaging system in accordance with an illustrative embodiment. Instant messaging system **200** may be implemented in network data processing system **100** shown in FIG. 1.

[0029] Instant messaging system **200** comprises a number of users **202** that communicate with each other via chat software **210**. Each user **204** has an associated user profile **206** stored in instant messaging system **200** and sender preferences **208** that specify alternative methods of sending messages **212** when recipients are not immediately available.

[0030] The current user status **218** of users **202** is maintained by presence server **216**. Synchronous service **214** continually pings presence server **216** to enable instant messaging system **200** to indicate the current user status **218** via user interface (UI) **226**.

[0031] As users **202** attempt to exchange messages **212** through chat software **210**, the current user status **218** indicated via UI **226** informs the sender as to whether the recipient in question is currently available to immediately receive the message in real time. The recipient may be currently unavailable for a number of reasons. For example, the recipient may have a Do not Disturb (DnD) status indicated in the UI **226** and is therefore not receiving messages at the moment. As another example, the current user status **218** of the recipient may indicate that the recipient is sharing a screen with other viewers such as during a video conference, in which case it might be an unwelcome interruption to have an instant message or instant message notification pop up on the recipient's screen. An instant message may also include confidential information that the sender and/or recipient do not want inadvertently disclosed via such a shared screen. Other potential statuses may be used to indicate momentary unavailability of the recipient and tracked by presence server **216** and indicated via UI **226**.

[0032] In instances where the current user status **218** indicates that the recipient is not available, instant messaging system **200** provides several alternatives for sending messages **212** without the need for a sender to manually copy and paste (“park”) the text of the instant message into another software or clipboard solution (e.g., word processor document or notepad application) and send the message later. Which alternative communication method is used depends on the sender preferences **208** and their preferred priority set by the user **204**.

[0033] One alternative method stores the instant message in a message queue **220** while the recipient is unavailable. A change in current user status **218** indicating recipient availability then automatically triggers the instant messaging system **200** to send the message. Another alternative method sends the instant message as an email to the recipient via email application programming interface (API) **222**. If the recipient has a mobile telephone number stored in a user profile **206**, the sender may also have the option of sending the instant message as a short message service (SMS) text message via SMS API **224**.

[0034] Instant messaging system **200** can be implemented in software, hardware, firmware, or a combination thereof. When software is used, the operations performed by instant messaging system **200** can be implemented in program code configured to run on hardware, such as a processor unit. When firmware is used, the operations performed by instant messaging system **200** can be implemented in program code and data and stored in persistent memory to run on a processor unit. When hardware is employed, the hardware may include circuits that operate to perform the operations in instant messaging system **200**.

[0035] In the illustrative examples, the hardware may take a form selected from at least one of a circuit system, an integrated circuit, an application specific integrated circuit (ASIC), a programmable logic device, or some other suitable type of hardware configured to perform a number of operations. With a programmable logic device, the device can be configured to perform

the number of operations. The device can be reconfigured at a later time or can be permanently configured to perform the number of operations. Programmable logic devices include, for example, a programmable logic array, a programmable array logic, a field programmable logic array, a field programmable gate array, and other suitable hardware devices. Additionally, the processes can be implemented in organic components integrated with inorganic components and can be comprised entirely of organic components excluding a human being. For example, the processes can be implemented as circuits in organic semiconductors.

[0036] These components for instant messaging system **200** can be located in computer system **250**, which is a physical hardware system and includes one or more data processing systems. When more than one data processing system is present in computer system **250**, those data processing systems are in communication with each other using a communications medium. The communications medium can be a network. The data processing systems can be selected from at least one of a computer, a server computer, a tablet computer, or some other suitable data processing system.

[0037] For example, instant messaging system **200** can run on one or more processors **252** in computer system **250**. As used herein a processor is a hardware device and is comprised of hardware circuits such as those on an integrated circuit that respond and process instructions and program code that operate a computer. When processors **252** execute instructions for a process, one or more processors can be on the same computer or on different computers in computer system **250**. In other words, the process can be distributed between processors **252** on the same or different computers in computer system **250**. Further, one or more processors **252** can be of the same type or different type of processors **252**. For example, one or more processors **252** can be selected from at least one of a single core processor, a dual-core processor, a multi-processor core, a general-purpose central processing unit (CPU), a graphics processing unit (GPU), a quantum processing unit (QPU), a digital signal processor (DSP), or some other type of processor.

[0038] FIG. **3** depicts a flowchart illustrating a process for asynchronous messaging on an instant messaging system in accordance with illustrative embodiments. Process **300** can be implemented in hardware, software, or both. When implemented in software, the process can take the form of program code that is run by one of more processor units located in one or more hardware devices in one or more computer systems. Process **300** may be implemented in instant messaging system **200** in FIG. **2**.

[0039] Process **300** begins with the instant messaging system receiving, from a sender, an instant message addressed to a recipient on the instant messaging system (step **302**). The instant messaging system determines a current user status of the recipient to ascertain if the recipient is currently available (step **304**). Step **304** may entail a synchronous API call to the “status” server (e.g., presence server **216**) and endpoint to retrieve the status of the recipient. This API call would be real time and resolve instantly in a functioning network.

[0040] The current user status may be provided by a presence server in the instant messaging system. A current user status of unavailable may be indicated by one of a DnD status or a Sharing Screen status.

[0041] Responsive to a determination the recipient is currently available, the instant messaging system sends the instant message to the recipient in real time (step **306**). This message may be a synchronous API call to the instant messaging service as a message body (with rich text or possibly a file attachment such as a .jpg or .doc file) via the standard application handling or via an IM system to IM system endpoint (e.g., Cisco Webex® to iMessage® or MSFT Teams®). This API call would be real time and resolve instantly in a functioning network with a response from the endpoint of a successful receipt.

[0042] Responsive to a determination the recipient is currently unavailable (see FIG. **4**), the instant messaging system may further determine the sender's preference of priority (either SMS/text, email, or send later) and, if SMS is preference **1**, whether a mobile telephone number for the

recipient is stored in a user profile in the instant messaging system (step **308**). This determination may be an application check of the other user's profile settings or alternatively a synchronous API call to another instant messaging service's endpoint to retrieve the profile settings of the recipient. This API call would be real time and resolve instantly in a functioning network. The response in this scenario would be a profile setting of a blank or a populated mobile telephone number field and an authorization to allow SMS messaging.

[0043] Responsive to a determination that a mobile telephone number for the recipient is stored in a user profile in the instant messaging system, the instant messaging system prompts the sender to choose among alternate methods (via a dialog box or via the priority ranking of options) to send the instant message when the recipient is currently unavailable (see FIG. 5) (step **310**). Sending the SMS message may comprise a synchronous API call to the SMS handling server via a SMS message endpoint to send the message to the recipient. This API call would be real time and resolve instantly in a functioning network. The SMS server should handle the message via the SMS Cellular network and respond back with a success message.

[0044] If there is no mobile telephone number for the recipient stored in a user profile, the instant messaging system determines a method choice for messaging the recipient selected by the sender (step **312**). This method choice is specified by sender preferences and priority ranking (see FIG. 6), which may be preset by the sender or selected by the sender in response to a prompt in step **310**. This determination may be an application check of the current user's profile settings to retrieve the profile settings and priority ranking of the sender. The system response in this scenario would be the profile setting of either email or "wait until later."

[0045] If the method choice in the send preferences and priority ranking is to send the message immediately without delay, the instant messaging system sends the message via an alternative communication system (step **314**). This alternative messaging system may comprise email or an SMS text message (in the case where a recipient mobile telephone number is stored in a user profile). Email messaging may comprise an asynchronous API call to the email service as a message (with rich text or possibly a file attachment such as a .jpg or .doc file) via a standard email application handling. This API call to the email software would be real time and resolve instantly in a functioning network with a response from the end point of a successful receipt.

[0046] If the method choice is to wait until the recipient is available, the instant messaging system stores the instant message in a queue until triggered to send the instant message when the current user status of the recipient changes to available (step **316**). This stored message may comprise a message (with rich text or possibly a file attachment such as a .jpg or .doc file) via the message handler as a later message once the instant messaging current user status of the recipient resets to "active" (i.e., available). Process **300** terminates thereafter.

[0047] FIG. 4 depicts a diagram illustrating a user interface with a Do not Disturb notice for an instant messaging system in accordance with an illustrative embodiment. In the present example, the sender has selected a recipient **402** in user interface **400**. Recipient **402** has a DnD current user status, indicated by icon **406** adjacent the user's avatar, as well as by notice **404** at the bottom of the interface.

[0048] FIG. 5 depicts a diagram illustrating a user interface presenting a sender with messaging options in response to a Do not Disturb notice in accordance with an illustrative embodiment. In this example, in response to the sender clicking on the DnD notice set by the recipient, user interface **400** presents the sender with a real time interactive pop-up menu **502** of options for sending the message.

[0049] FIG. 6 depicts a diagram illustrating a user preferences interface for an instant messaging system in accordance with an illustrative embodiment. In this example, preferences interface **600** allows the user to select several options and a priority ranking of each for sending an instant message when a recipient is unavailable. User preferences interface **600** has options and the ability to denote preferred ranking preferences for sending via email **602**, via SMS text **604**, and delay

until recipient is active again **606**. In the present example, the user has selected SMS/text **604** as the priority 1 option, email **602** as the priority 2 option, and delayed **606** as priority 3. User preferences interface **600** also allows the user to provide a mobile telephone number in field **608** for receiving SMS text messages when the user sets a DnD status as a recipient.

[0050] Prioritized send options allow the instant messaging system of the illustrative embodiments to provide fallbacks in cases of API call failures. If an API call fails, and the other endpoint is not responding, the API does not have to continually retry the call but can instead switch to the next highest ranked send option. Using the example in FIG. **6**, the sender has selected SMS **604** as the priority 1 send option, but no mobile telephone number is stored in the profile of the recipient in question. Therefore, the instant messaging system falls back to email **602** as the priority 2 option. If there is a problem with email service, such as an interruption of service with the email server, the instant messaging system would then fall back on placing the message into a queue to send later when the recipient user status changes back to available.

[0051] Turning now to FIG. **7**, an illustration of a block diagram of a data processing system is depicted in accordance with an illustrative embodiment. Data processing system **700** may be used to implement one or more computers and client devices **110** and servers computer **104**, **106** in FIG. **1** and instant messaging system **200** in FIG. **2**. In this illustrative example, data processing system **700** includes communications framework **702**, which provides communications between processor unit **704**, memory **706**, persistent storage **708**, communications unit **710**, input/output unit **712**, and display **714**. In this example, communications framework **702** may take the form of a bus system.

[0052] Processor unit **704** serves to execute instructions for software that may be loaded into memory **706**. Processor unit **704** may be a number of processors, a multi-processor core, or some other type of processor, depending on the particular implementation. In an embodiment, processor unit **704** comprises one or more conventional general-purpose central processing units (CPUs). In an alternate embodiment, processor unit **704** comprises one or more graphical processing units (GPUs).

[0053] Memory **706** and persistent storage **708** are examples of storage devices **716**. A storage device is any piece of hardware that is capable of storing information, such as, for example, without limitation, at least one of data, program code in functional form, or other suitable information either on a temporary basis, a permanent basis, or both on a temporary basis and a permanent basis. Storage devices **716** may also be referred to as computer-readable storage devices in these illustrative examples. Memory **706**, in these examples, may be, for example, a random access memory or any other suitable volatile or non-volatile storage device. Persistent storage **708** may take various forms, depending on the particular implementation.

[0054] For example, persistent storage **708** may contain one or more components or devices. For example, persistent storage **708** may be a hard drive, a flash memory, a rewritable optical disk, a rewritable magnetic tape, or some combination of the above. The media used by persistent storage **708** also may be removable. For example, a removable hard drive may be used for persistent storage **708**. Communications unit **710**, in these illustrative examples, provides for communications with other data processing systems or devices. In these illustrative examples, communications unit **710** is a network interface card.

[0055] Input/output unit **712** allows for input and output of data with other devices that may be connected to data processing system **700**. For example, input/output unit **712** may provide a connection for user input through at least one of a keyboard, a mouse, or some other suitable input device. Further, input/output unit **712** may send output to a printer. Display **714** provides a mechanism to display information to a user.

[0056] Instructions for at least one of the operating system, applications, or programs may be located in storage devices **716**, which are in communication with processor unit **704** through communications framework **702**. The processes of the different embodiments may be performed by processor unit **704** using computer-implemented instructions, which may be located in a memory,

such as memory **706**.

[0057] These instructions are referred to as program code, computer-usable program code, or computer-readable program code that may be read and executed by a processor in processor unit **704**. The program code in the different embodiments may be embodied on different physical or computer-readable storage media, such as memory **706** or persistent storage **708**.

[0058] Program code **718** is located in a functional form on computer-readable media **720** that is selectively removable and may be loaded onto or transferred to data processing system **700** for execution by processor unit **704**. Program code **718** and computer-readable media **720** form computer program product **722** in these illustrative examples. In one example, computer-readable media **720** may be computer-readable storage media **724** or computer-readable signal media **726**.

[0059] In these illustrative examples, computer-readable storage media **724** is a physical or tangible storage device used to store program code **718** rather than a medium that propagates or transmits program code **718**. Alternatively, program code **718** may be transferred to data processing system **700** using computer-readable signal media **726**.

[0060] Computer-readable signal media **726** may be, for example, a propagated data signal containing program code **718**. For example, computer-readable signal media **726** may be at least one of an electromagnetic signal, an optical signal, or any other suitable type of signal. These signals may be transmitted over at least one of communications links, such as wireless communications links, optical fiber cable, coaxial cable, a wire, or any other suitable type of communications link.

[0061] The different components illustrated for data processing system **700** are not meant to provide architectural limitations to the manner in which different embodiments may be implemented. The different illustrative embodiments may be implemented in a data processing system including components in addition to or in place of those illustrated for data processing system **700**. Other components shown in FIG. 7 can be varied from the illustrative examples shown. The different embodiments may be implemented using any hardware device or system capable of running program code **718**.

[0062] The flowcharts and block diagrams in the different depicted embodiments illustrate the architecture, functionality, and operation of some possible implementations of apparatuses and methods in an illustrative embodiment. In this regard, each block in the flowcharts or block diagrams can represent at least one of a module, a segment, a function, or a portion of an operation or step. For example, one or more of the blocks can be implemented as program code, hardware, or a combination of the program code and hardware. When implemented in hardware, the hardware may, for example, take the form of integrated circuits that are manufactured or configured to perform one or more operations in the flowcharts or block diagrams. When implemented as a combination of program code and hardware, the implementation may take the form of firmware. Each block in the flowcharts or the block diagrams may be implemented using special purpose hardware systems that perform the different operations or combinations of special purpose hardware and program code run by the special purpose hardware.

[0063] In some alternative implementations of an illustrative embodiment, the function or functions noted in the blocks may occur out of the order noted in the figures. For example, in some cases, two blocks shown in succession may be performed substantially concurrently, or the blocks may sometimes be performed in the reverse order, depending upon the functionality involved. Also, other blocks may be added in addition to the illustrated blocks in a flowchart or block diagram.

[0064] The different illustrative examples describe components that perform actions or operations. In an illustrative embodiment, a component may be configured to perform the action or operation described. For example, the component may have a configuration or design for a structure that provides the component an ability to perform the action or operation that is described in the illustrative examples as being performed by the component.

[0065] Many modifications and variations will be apparent to those of ordinary skill in the art.

Further, different illustrative embodiments may provide different features as compared to other illustrative embodiments. The embodiment or embodiments selected are chosen and described in order to best explain the principles of the embodiments, the practical application, and to enable others of ordinary skill in the art to understand the disclosure for various embodiments with various modifications as are suited to the particular use contemplated.

Claims

1.-24. (canceled)

25. A system, comprising: one or more processors, coupled with memory, to: provide, for display on a graphical user interface (GUI) of a first device, a set of communication protocols used to transmit messages from the first device to a second device; receive, from the first device, a first selection of a first communication protocol of the set of communication protocols, the first communication protocol configured to delay transmittal of messages to the second device based on a status of the second device being unavailable; configure, responsive to receiving the first selection, the first communication protocol as a first priority communication protocol in a profile of the first device; and execute, responsive to receiving a message from the first device for transmission to the second device, the first priority communication protocol.

26. The system of claim 25, wherein the one or more processors are further configured to: receive, from the first device, a second selection of a second communication protocol of the set of communication protocols; and configure, responsive to receiving the second selection, the second communication protocol as a second priority communication protocol in the profile of the first device.

27. The system of claim 26, wherein the one or more processors are further configured to: receive, responsive to executing the first priority communication protocol, an application programming interface (API) status; and execute, responsive to the API status indicating an endpoint associated with the first priority communication protocol is unresponsive, the second communication protocol.

28. The system of claim 26, wherein the one or more processors are further configured to: execute, based on the status of the second device being available, the second priority communication protocol.

29. The system of claim 26, wherein the one or more processors are further configured to: determine, responsive to configuring the first communication protocol as the first priority communication protocol, that no telephone number is set in a profile of the second device; and execute, responsive to determining that no telephone number is set in the profile of the second device, the second priority communication protocol.

30. The system of claim 26, wherein the second priority communication protocol comprises at least one of: transmitting the messages in an email; delaying transmittal of the messages; or transmitting the messages in a text message.

31. The system of claim 25, wherein executing the first priority communication protocol comprises storing the message in a message queue.

32. The system of claim 25, wherein the one or more processors are further configured to: provide, for display on the GUI of the first device, a prompt indicating the status of the second device; and execute, responsive to receiving a second selection of the prompt from the first device, the first priority communication protocol.

33. A method, comprising: providing, by one or more processors coupled with memory for display on a graphical user interface (GUI) of a first device, a set of communication protocols used to transmit messages from the first device to a second device; receiving, by the one or more processors from the first device, a first selection of a first communication protocol of the set of communication protocols, the first communication protocol configured to delay transmittal of messages to the second device based on a status of the second device being unavailable;

configuring, by the one or more processors, responsive to receiving the first selection, the first communication protocol as a first priority communication protocol in a profile of the first device; and executing, by the one or more processors, responsive to receiving a message from the first device for transmission to the second device, the first priority communication protocol.

34. The method of claim 33, comprising: receiving, by the one or more processors from the first device, a second section of a second communication protocol of the set of communication protocols; and configuring, by the one or more processors, responsive to receiving the second selection, the second communication protocol as a second priority communication protocol in the profile of the first device.

35. The method of claim 34, comprising: receiving, by the one or more processors, responsive to executing the first priority communication protocol, an application programming interface (API) status; and executing, by the one or more processors, responsive to the API status indicating an endpoint associated with the first priority communication protocol is unresponsive, the second communication protocol.

36. The method of claim 34, comprising: executing, by the one or more processors, based on the status of the second device being available, the second priority communication protocol.

37. The method of claim 34, comprising: determining, by the one or more processors, responsive to configuring the first communication protocol as the first priority communication protocol, that no telephone number is set in a profile of the second device; and executing, by the one or more processors, responsive to determining that no telephone number is set in the profile of the second device, the second priority communication protocol.

38. The method of claim 33, comprising: providing, by the one or more processors for display on the GUI of the first device, a prompt indicating the status of the second device; and executing, by the one or more processors, responsive to receiving a second selection of the prompt from the first device, the first priority communication protocol.

39. A non-transitory computer-readable medium comprising instructions embodied thereon, the instructions to cause a processor to: provide, for display on a graphical user interface (GUI) of a first device, a set of communication protocols used to transmit messages from the first device to a second device; receive, from the first device, a first selection of a first communication protocol of the set of communication protocols, the first communication protocol configured to delay transmittal of messages to the second device based on a status of the second device being unavailable; configure, responsive to receiving the first selection, the first communication protocol as a first priority communication protocol in a profile of the first device; and execute, responsive to receiving a message from the first device for transmission to the second device, the first priority communication protocol.

40. The non-transitory computer-readable medium of claim 39, comprising the instructions embodied thereon to cause the processor to: receive, from the first device, a second section of a second communication protocol of the set of communication protocols; and configure, responsive to receiving the second selection, the second communication protocol as a second priority communication protocol in the profile of the first device.

41. The non-transitory computer-readable medium of claim 40, comprising the instructions embodied thereon to cause the processor to: receive, responsive to executing the first priority communication protocol, an application programming interface (API) status; and execute, responsive to the API status indicating an endpoint associated with the first priority communication protocol is unresponsive, the second communication protocol.

42. The non-transitory computer-readable medium of claim 40, comprising the instructions embodied thereon to cause the processor to: execute, based on the status of the second device being available, the second priority communication protocol.

43. The non-transitory computer-readable medium of claim 40, comprising the instructions embodied thereon to cause the processor to: determine, responsive to configuring the first

communication protocol as the first priority communication protocol, that no telephone number is set in a profile of the second device; and execute, responsive to determining that no telephone number is set in the profile of the second device, the second priority communication protocol.

44. The non-transitory computer-readable medium of claim 39, comprising the instructions embodied thereon to cause the processor to: provide, for display on the GUI of the first device, a prompt indicating the status of the second device; and execute, responsive to receiving a second selection of the prompt from the first device, the first priority communication protocol.
