

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250279695

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Lee; Michael MyungSub

Energy converting apparatus, energy converting system including same, and operating method thereof

Abstract

Disclosed is an energy converting apparatus for converting mechanical energy obtained by a fluid flow into electric energy. The energy converting apparatus comprises: a blade; a measuring device for measuring reaction of the blade when the fluid flow exerts an external force on the blade, and generating a measurement value corresponding to a measurement result; a memory for storing control values; a controller for reading a first control value among the control values from the memory in response to the measurement value output from the measuring device, and generating a control signal by using the first control value; and an actuator for changing a three-dimensional shape of the blade in response to the control signal output from the controller.

Inventors: Lee; Michael MyungSub (Cheonan, KR)

Applicant: CYTRONIQ CO. LTD (CHEONAN, KR)

Family ID: 96880608

Appl. No.: 18/594078

Filed: March 04, 2024

Publication Classification

Int. Cl.: H02K7/18 (20060101); F03D1/06 (20060101)

U.S. Cl.:

CPC H02K7/183 (20130101); F03D1/0633 (20130101); F05B2240/31 (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a National Phase of the International Application No. PCT/KR2017/014077 filed on Dec. 4, 2017, which is based on Korean Application No. 10-2016-0167063 filed on Dec. 8, 2016 and Korean Application No. 10-2016-0171948 filed on Dec. 15, 2016. This application is also a continuation of U.S. application Ser. No. 16/610,494 filed on Aug. 6, 2020. The applications are incorporated herein by reference in their entirety.

TECHNOLOGY FIELD

[0002] Embodiments according to the concepts of the present invention relate to an energy conversion device, in particular, when the fluid flow is applied to the turbine by an external force, measuring the response of the turbine, generating a measurement value corresponding to the measurement result, and control related to the measurement value. An energy conversion device capable of modifying the three-dimensional shape of the turbine based on a signal, a method of operating the same, and an energy conversion system including the energy conversion device are provided.

BACKGROUND

[0003] Energy harvesting refers to a technology that harvests energy by converting energy from natural energy sources such as wind, tidal, or wave power into electrical energy.

[0004] For example, wind generators that convert wind energy into mechanical energy using devices such as wind turbines, which use this energy to generate electricity by turning generators, are used as means for producing electricity in many countries.

[0005] Controlling the blades of the wind generator to produce a lot of electricity can increase the load on the wind generator, and increasing the number of wind generators reduces the strength of the wind the wind generator receives.

SUMMARY

[0006] The technical problem to be achieved by the present invention is to generate a control signal corresponding to the turbine's response to the external force when the fluid flow is applied to the external force of the turbine, and to generate the three-dimensional shape of the turbine using the control signal. To provide a deformable energy conversion device and a method of operating the same.

[0007] The technical problem to be achieved by the present invention relates to an energy conversion system, by using the position information of the energy conversion device, the topographic information of the installed area of the energy conversion system including the energy conversion device, and the weather information of the area. It is to provide a technology that can change the three-dimensional shape of each of the blades included in the energy conversion device.

[0008] According to an embodiment of the present invention, an energy conversion device for converting mechanical energy obtained from a fluid flow into electrical energy measures a blade and a response of the blade when the fluid flow is applied to the blade by an external force. A first measurement device for generating a first measurement value corresponding to a result, a memory for storing control values, a first of the control values from the memory in response to the first measurement value output from the first measurement device; And a controller configured to read a control value and generate a control signal using the first control value, and an actuator to deform the three-dimensional shape of the blade in response to the control signal output from the controller.

[0009] According to an embodiment of the present invention, an energy conversion device for converting mechanical energy obtained from a fluid flow into electrical energy measures a blade and a response of the blade when the fluid flow is applied to the blade by an external force. A measuring device for generating a first measured value corresponding to a result of the blade's response when a fluid flow is applied to the blade by an external force. A controller for generating a control signal using the first measured value output from the first measuring device, and a response

to the control signal output from the controller; It includes an actuator for deforming the three-dimensional shape of the blade.

[0010] The energy conversion device further comprises a memory for storing a computational fluid dynamics (CFD) program, the controller executes the CFD program stored in the memory and causes the CFD program to cause the first measured value. To generate the control signal.

[0011] According to an embodiment of the present invention, an energy conversion device for converting mechanical energy obtained from a fluid flow into electrical energy measures a blade and a response of the blade when the fluid flow is applied to the blade by an external force. Storing control values corresponding to a combination of measuring devices for generating measured values corresponding to a result of the first value and first values representing an internal environment of the energy conversion device and second values representing an external environment of the energy conversion device. A controller that reads a control value of any one of the control values from the memory in response to the memory and the measurement values output from the measuring devices and generates a control signal in response to any one of the control values. An actuator is configured to deform the three-dimensional shape of the blade in response to the control signal output from the controller.

[0012] Wind power generation system according to an embodiment of the present invention is a first wind power generator including a first blade and a first actuator, a second wind power generator including a second blade, a measuring unit for measuring wind power and generating wind value And a memory for storing control values, a controller reading a first control value from among the control values from the memory in response to the wind power value output from the measuring instrument, and generating a control signal in response to the read first control value. Includes, the first actuator deforms the three-dimensional shape of the first blade in response to the control signal output from the controller.

[0013] According to an embodiment of the present invention, a wind power generation system includes a first wind power generator including a first blade and a first actuator, a second wind power generator including a second blade, a memory to store control values, and the first wind power generator. A receiver for receiving at least one of weather information around a wind generator, topographic information of a location where the first wind power generator is installed, and position information on a position where the second wind power generator is installed; and at least one output from the receiver. In response to selecting a first control value from the memory and generating a control signal in response to the first control value, wherein the first actuator responds to the control signal output from the controller. To deform the three-dimensional shape of the first blade.

[0014] According to an exemplary embodiment of the present invention, a method of operating an energy conversion device for converting mechanical energy obtained from a fluid flow into electrical energy includes measuring a response of the blade when the fluid flow is applied to the blade by an external force. Generating a measurement value corresponding to the measurement result, and the controller reads a first control value from among control values from a memory in response to the measurement value output from the measurement device and uses the first control value. Generating a control signal, and an actuator deforming the three-dimensional shape of the blade in response to the control signal output from the controller.

[0015] Each of the control values stored in the memory includes at least one of weather information around the energy conversion device, terrain information of a location where the energy conversion device is installed, and location information on a location where the energy conversion device and another energy conversion device are installed. According to different values.

[0016] According to an embodiment of the present invention, a method of operating a wind power generation system including a first wind power generator including a first blade and a first actuator and a second wind power generator including a second blade includes measuring the wind power and measuring the wind power. Generating a value, the controller reading a first control value

among control values stored in a memory in response to the wind power value output from the measuring instrument and generating a control signal using the read first control value; And deforming the three-dimensional shape of the first blade by the first actuator in response to the control signal output from the controller.

[0017] The deforming of the three-dimensional shape of the first blade may be performed by the actuator in response to the control signal. The pitch angle of the blade, opening and closing of a leading edge included in the first blade, or trailing included in the first blade may be determined. The opening and closing of the edges are controlled to deform the three-dimensional shape of the first blade.

[0018] According to an embodiment of the present invention, a method of operating a wind power generation system including a first wind power generator including a first blade and a first actuator and a second wind power generator including a second blade includes a controller configured to store control values in a memory. Storing at least one of weather information around the first wind power generator, terrain information on a location where the first wind power generator is installed, and location information on a location where the second wind power generator is installed; The controller selecting a first control value from the control values stored in the memory in response to the at least one output from the receiver, and generating a control signal in response to the first control value; An actuator deforms the three-dimensional shape of the first blade in response to the control signal output from the controller. It includes the system.

[0019] The operation method of the wind power generation system further includes the step of calculating, by the controller, the accumulated power generation amount of the first wind power generator, and the controller updating each of the control values according to the calculated power generation amount.

[0020] An energy conversion device according to embodiments of the present invention measures the response of the turbine to the external force when a fluid flow acts as an external force on the turbine, generates a measured value according to a measurement result according to the measured value, and has the effect of changing the three-dimensional shape of the turbine based on the measured value.

[0021] Therefore, the energy converter has an effect of improving the energy conversion efficiency of the energy converter without significantly increasing the load on the energy converter.

[0022] The energy conversion device may deform the three-dimensional shape of the turbine included in the energy conversion device by using the position information indicating the position of another energy conversion device, so that the fluid flow used in the energy conversion device is different from the other energy conversion device. Since it can be transmitted to the device a lot, there is an effect that the energy conversion efficiency of the other energy conversion device is improved, there is an effect that can reduce the separation distance between the energy conversion devices.

[0023] An energy conversion apparatus according to embodiments of the present invention is included in the energy conversion apparatus using at least one of terrain information, weather information, and location information of the energy conversion device and another energy conversion device for an area where an energy conversion system is installed. Since the three-dimensional shape of each of the turbines can be modified, there is an effect of improving the energy conversion efficiency of the turbine adaptively to the surrounding environment in which the energy conversion device is installed.

Description

BRIEF EXPLANATION OF THE DRAWINGS

[0024] FIG. 1 is a block diagram of an energy conversion device according to embodiments of the

present invention.

[0025] FIG. 2 is a diagram illustrating an embodiment of the energy conversion device illustrated in FIGS. 1.

[0026] 3 to 8 illustrate an embodiment of control objects and control values stored in the memory illustrated in FIG. 1 or 2.

[0027] FIG. 9 is a diagram illustrating another embodiment of the energy conversion device illustrated in FIG. 1.

[0028] 10 shows a conceptual diagram of an energy conversion system according to embodiments of the present invention.

[0029] FIG. 11 illustrates an embodiment of control objects and control values stored in the memory illustrated in FIG. 10.

[0030] 12 illustrates a conceptual diagram of an energy conversion system according to embodiments of the present invention.

[0031] FIG. 13 shows the structure of the turbine shown in FIG. 1, 2, 9, 10, or 12.

[0032] FIG. 14 illustrates an embodiment in which a three-dimensional shape of the turbine is modified by controlling a leading edge included in the turbine illustrated in FIG. 1, 2, 9, 10, or 12.

[0033] FIG. 15 illustrates an embodiment of modifying a three-dimensional shape of the turbine by controlling a trailing edge included in the turbine illustrated in FIG. 1, 2, 9, 10, or 12.

[0034] FIG. 16 is a flow chart illustrating the operation of the energy conversion device shown in FIG. 1, 2, or 9.

[0035] FIG. 17 is a flow chart illustrating the operation of the energy conversion system shown in FIG. 10 or 12.

DETAILED DESCRIPTION

[0036] FIG. 1 is a block diagram of an energy conversion device according to embodiments of the present invention. Referring to FIG. 1, the energy conversion device **100** includes a turbine **200**, at least one measurement device **300**, a memory **400**, a controller **500**, at least one actuator **600**, and a receiver **700**. It may include.

[0037] For example, the energy conversion device **100** may be a fluid flow, a liquid flow, a fluid flow, or a substance (e.g., gas, particles, liquid, or a device capable of converting energy (e.g., mechanical energy) obtained from the flow of a solid body (solid body) into electric power (e.g., electrical energy). In the present specification, the fluid flow may be broadly interpreted as a concept including a liquid flow, a fluid flow, or a material flow.

[0038] The fluid flow may refer to the movement of a fluid in motion (e.g., including gas, particles, liquids, plasmas, and/or solid materials).

[0039] When the fluid flow is wind, tide, ocean current or sea current, deep water, river water flow, wave, or wind wave, the energy conversion apparatus **100** according to the embodiments of the present invention may be a generator using wind energy or a generator using sea energy but is not limited thereto. For example, the energy conversion device **100** may be a wind generator, tidal generator, or wave generator, but is not limited thereto. In addition, the energy conversion device **100** and its operation method to be described herein may be applied to a generator using geothermal energy. In addition, the technical idea of the present invention to control the three-dimensional shape of the turbine (or blade) can be applied to a generator for generating electrical energy using the turbines (or blades).

[0040] The wind generator may include an onshore type wind generator and an offshore type wind generator. The wind generator may include, but is not limited to, a floating offshore wind generator and a semi-submersible floating wind generator.

[0041] Wind power means converting wind (or wind) into power using a wind turbine, tidal power means generating power using the difference between the high and low tide of the sea, Wave power refers to the transfer of energy by sea wave or the production of power using the energy.

[0042] The turbine **200** may be a rotary mechanical device that extracts energy from a fluid flow.

The turbine **200** may refer to a structure (or device) capable of converting energy obtained from the fluid flow into electric power in response to an external force applied to the turbine **200** by the fluid flow.

[0043] According to embodiments, a turbine may be a blade, a turbine blade, a rotor blade, a wind turbine rotor blade, a tidal turbine blade, or it may mean a wind wave turbine blade. The energy conversion device **100** may include a plurality of turbines (or a plurality of blades). For example, a turbine (or blade) may broadly mean a vertical-axis wind turbine (VAWT) blade or a horizontal axis wind turbine (HAWT) blade.

[0044] The measuring device **300** measures (e.g., directly or indirectly measures) the response of the turbine (or blade) **200** when the fluid flow is exerted on the turbine (or blade; **200**) externally. Measured values (or response values) corresponding to the results can be generated.

[0045] The reaction or the measured value may be determined by the position of the turbine **200** (or the angle of rotation to be described with reference to FIG. 4), the restoring force of the turbine **200**, the elastic force of the turbine **200**, the turbine (Aeroelasticity of **200**, fatigue load of turbine **200**, vibration of turbine **200**, stress of turbine **200**, gravity of turbine **200**, Buoyancy of the turbine **200**, rotational speed of the turbine **200**, revolutions per minute (RPM) of the turbine **200**, pitch angle of the turbine **200**, turbine **200** Strain or strain rate, the acceleration of the turbine **200**, the amount of ultraviolet rays of the turbine **200**, the insolation of the turbine **200**, the speed (or density) of the fluid flow, the turbine **200**), And the humidity of the turbine **200**.

[0046] The measuring device **300** may mean a device (or sensor) capable of measuring the response of the turbine **200** to a fluid flow or external force, or a device (or sensor) capable of generating the measured value. The measuring device **300** may collectively represent a plurality of measuring devices or a plurality of sensors. For example, when the measuring device includes a first measuring device and a second measuring device, the first measuring device can measure the restoring force of the turbine **200**, and the second measuring device can measure the position (or rotational angle) of the turbine.) Can be measured but is not limited thereto.

[0047] The measuring device **300** includes an electricity meter, a voltmeter, an ammeter, a direction sensor, an inertial sensor, a strain sensor, an acceleration sensor, and a gravitational acceleration sensor, Lidar, solarimeter, UV radiometer, barometer, temperature sensor, humidity sensor, pressure sensor, acceleration sensor, image sensor, optical camera, high speed camera, sound wave sensor, ultrasonic sensor (ultrasonic sensor), acoustic detector, Raman-based distributed temperature sensor, water flow sensor, water pressure sensor, wave meter However, it is not limited thereto.

[0048] For example, the measuring device **300** may measure the pitch angle of the turbine **200** using an orientation sensor or an inertial sensor, measure a strain using a strain sensor, and measure acceleration using an acceleration sensor. The time information and the space information of the turbine **200** may be measured by using a Lidar and an acoustic detector.

[0049] For example, each of the strain sensor and the acceleration sensor may be located at the center of a rotor connected to the turbine **200** and may be disposed at regular intervals inside or on the surface of the turbine **200**. For example, the UV photometer, solar meter, temperature sensor, and humidity sensor can be located in the center of the hub of the rotor.

[0050] At least one measuring device **300** may measure the response of the turbine **200** to the external force and generate at least one measured value according to the measurement result. The measured value may be measured in various ways, such as wind direction, wind speed, stress, load, displacement, and accumulated fatigue life as described above, Cumulative amount of ultraviolet light, residual lifetime ratio, and/or power production, but are not limited thereto.

[0051] For example, the displacement means the degree to which the turbine **200** is bent by fluid flow, and the load means a force transmitted perpendicular to the tower **120** shown in FIG. 2, and the cumulative fatigue life is The number of times the load is repeated (or the time under which the load is received) until the energy conversion device **100** that is repeatedly subjected to the load is destroyed, and the power production amount (or power generation amount) may represent the

amount of power generation of the energy conversion device **100**.

[0052] The measuring apparatus **300** may measure the wind speed and wind speed applied to the turbine **200** by measuring the revolutions per minute of the turbine **200** and measure the strain and acceleration of the turbine **200** to displace the turbine **200**. The amount of ultraviolet rays applied to the turbine **200** and the solar radiation system may be measured to measure the cumulative amount of ultraviolet rays of the turbine **200**, and the temperature and humidity of the turbine **200** may be measured to determine the turbine **200**. The stress and the load may be measured, and the cumulative fatigue life of the turbine **200** may be measured using the stress and the load but is not limited thereto. Here, the measurement may mean a calculation.

[0053] Wind direction and wind speed can be measured using a wind vane/anemometer installed in the nacelle (**140** of FIG. **2**), the receiver **700** may receive weather information including information on the wind direction and wind speed from a system that provides satellite or weather information.

[0054] Since the turbine **200** made of a composite material is weak to ultraviolet rays, if the cumulative amount of ultraviolet rays is large, the life of the turbine **200** is quickly decreased, and if the cumulative fatigue of the turbine **200** is increased, the turbine **200** is weakened, and Displacement may increase. Therefore, the controller **500** may calculate the remaining life of the turbine **200** by using the displacement, the cumulative amount of ultraviolet rays, and the cumulative fatigue life. According to embodiments, the measuring apparatus **300** may measure the wind direction and wind speed applied to the turbine **200** by using a wind vane and an anemometer installed in the nacelle (**140** of FIG. **2**).

[0055] The memory **400** may store control values capable of deforming the three-dimensional shape of the turbine **200**. Although FIG. **1** illustrates that the memory **400** is disposed outside the controller **500**, the memory **400** may be replaced with a cache memory or a data cache located inside the controller **500**. The controller **500** accesses the memory **400** disposed externally or internally to obtain at least one control value CTV corresponding to the at least one measured value MSR measured from the at least one measuring device **300**. The acquisition may be performed by a read operation or a pre-fetch operation.

[0056] For example, assume that the measuring device **300** includes a first measuring device and a second measuring device. The first measuring device includes a restoring force of the turbine **200**, an elastic force of the turbine **200**, an aeroelasticity of the turbine **200**, a fatigue load of the turbine **200**, a vibration of the turbine **200**, a deformation force of the turbine **200**, Gravity of turbine **200**, buoyancy of turbine **200**, rotational speed of turbine **200**, pitch angle of turbine **200**, strain of turbine **200**, acceleration of turbine **200**, ultraviolet ray of turbine **200** Amount, the solar radiation of the turbine **200**, the speed (or density) of the fluid flow applied to the turbine **200**, the temperature of the turbine **200**, and the humidity of the turbine **200** is measured and according to the measurement result, Measured values can be generated.

[0057] As shown in FIG. **4**, the second measurement device generates a second measurement value BP1 or BP2 according to a measurement result of measuring the position (or rotation angle) of the rotating turbine **200**. For example, the measured value BP1 measured at the first position has little influence on the power production of the other energy conversion device, and the measured value BP2 measured at the second position has higher influence on the power production of the other energy conversion device.

[0058] The controller **500** reads (or selects) any one control value (e.g., the first control value) among control values stored in the memory **400** in response to the first measurement value output from the first measuring device. The control signal CTRL may be generated using the first control value CTV.

[0059] The actuator **600** responds to the control signal CTRL output from the controller **500** to the pitch angle of the turbine **200**, the leading edge attached to the turbine **200**, and/or or the turbine **200**. Attached trailing edges can be controlled. An embodiment of controlling the leading edge will

be described with reference to FIG. 14, and an embodiment of controlling the trailing edge will be described with reference to FIG. 15. That is, the three-dimensional shape of the turbine 200 may be defined by pitch angle, leading edge, and/or trailing edge, but is not limited thereto.

[0060] The controller 500 may control the other control value among control values stored in the memory 400 in response to the first measurement value output from the first measurement device and the second measurement value output from the second measurement device. For example, the second control value) may be read (or selected) and the control signal CTRL may be generated using the second control value CTV. At this time, the actuator 600 is a pitch angle of the turbine 200, a leading edge attached to the turbine 200, and/or attached to the turbine 200 in response to the control signal CTRL output from the controller 500. The trailing edge can be controlled.

[0061] The receiver 700 may include weather information around the energy conversion device 100, terrain information of a location where the energy conversion device 100 is installed, and/or location information about a location where the energy conversion device 100 and other energy conversion devices are installed. And receive the weather information, the terrain information, and/or the location information to the controller 500. The controller 500 may generate a control value corresponding to the weather information, the terrain information, and/or the location information, and store the control value in the memory 400.

[0062] That is, each of the control values stored in the memory 400 by the controller 500 has a different value according to at least one of the weather information, the terrain information, and the location information. According to embodiments, the controller 500 may mean a processor, a microprocessor, a CPU, or a computing device.

[0063] FIG. 2 is a diagram illustrating an embodiment of the energy conversion device illustrated in FIG. 1. A wind power generator 100A according to an embodiment of the energy conversion device 100 of FIG. 1 includes a foundation 110, a tower 120, a rotor 130, and a nacelle 140. A plurality of blades 200A, at least one measuring device 300A, memory 400A, controller 500A, and at least one actuator 600-1, 600-2, and 600-3. It may include.

[0064] Each blade 200A corresponds to the turbine 200 of FIG. 1, at least one measuring device 300A corresponds to at least one measuring device 300 of FIG. 1, and memory 400A corresponds to the memory of FIG. 1. 400, the controller 500A corresponds to the controller 500 of FIG. 1, and each actuator 600-1, 600-2, and 600-3 corresponds to the actuator 600 of FIG. 1.

[0065] An actuator is used herein to describe a system (e.g., an energy converter, a wind generator, tidal generator, or wave generator, etc.) or a mechanical device used to move or control a component included in the system. It means the component of (component of machine). For example, the actuator may include, but is not limited to, an electric actuator, a hydraulic actuator, and a pneumatic actuator.

[0066] Foundation 110 is installed on the ocean, seabed, or land. The tower 120 supports the rotor 130 and the nacelle 130 and serves to elevate the rotor 130 and the nacelle 130 to obtain a large output at a strong wind speed.

[0067] The rotor 130 converts wind energy into mechanical energy, and a rotor hub attached to the front end of the rotor 130 serves to support the plurality of blades 200A. Each blade (or rotor blade) 200A serves to rotate the rotor 130 by capturing energy possessed by the wind. Nacelle 140 is composed of a device for converting the mechanical energy generated by the rotor 130 into electrical energy.

[0068] Each blade 200A may comprise at least one leading edge 210, at least one trailing edge, and at least one measuring device 300A. In FIG. 2, an embodiment in which the measuring device 300A is disposed on the surface of each blade 200A is illustrated, but according to the exemplary embodiments, the measuring device 300A may be present inside each blade 200A.

[0069] The measuring device 300A, when fluid or fluid flow is exerted on the blade 200A with an external force, reacts the blade 200A with the external force (e.g., a direct or indirect reaction). It can measure and generate measurement value (MSR) according to the measurement result.

[0070] The memory **400A** may store each control value corresponding to each measured value MSR. Each control value may be stored in the form of a lookup table **410**, and various forms of the LUT **410** stored in the memory **400A** will be described in detail with reference to FIGS. **3** to **8**. The LUT **410** may store control values CTV corresponding to the measured values.

[0071] The controller **500A** reads the control value CTV of any one (or at least one) among the control values stored in the memory **400A** in response to the measured value MSR output from the measuring apparatus **300A** and controls the control value (The control signal CTRL may be generated using the CTV).

[0072] The actuator **600-1**, **600-2**, or **600-3** may deform the three-dimensional shape of the blade **200A** in response to the control signal CTRL1, CTRL2, or CTRL3 output from the controller **500A**. The first actuator **600-1** capable of deforming the three-dimensional shape of the blade **200A** adjusts the pitch angle of the blade **200A** in response to the first control signal CTRL1 to adjust the three-dimensional shape of the blade **200A**.

[0073] FIGS. **2** and **14**, the blade **200A** includes at least one leading edge **210**. The second actuator **600-2** may open or close the leading edge **210** in response to the second control signal CTRL2, a gap GAP1 between the leading edge **210** and the blade **200A**, and the leading edge **210**. And at least one of the angles ANG1 between the blades **200A**. According to at least one of the gap GAP1 and the angle ANG1, the speed of the fluid flow applied to the blade **200A**, the density of the fluid, and/or the direction of the fluid may be changed.

[0074] **2** and **15**, blade **200A** includes at least one trailing edge **230**. The third actuator **600-3** may open or close the trailing edge **230** in response to the third control signal CTRL3, a gap GAP2 between the trailing edge **230** and the blade **200A**, and the trailing edge. At least one of the angle ANG2 between the **230** and the blades **200A** may be adjusted. Depending on at least one of the gap GAP2 and the angle ANG2, the speed of the fluid flow through the blade **200A**, the density of the fluid, and/or the direction of the fluid may be changed.

[0075] The control of the leading edge **210** and/or the control of the trailing edge **230** may be determined according to a numerical value (e.g., a measured value) of the blade **200A**'s response to an external force applied to the blade **200A**.

[0076] FIGS. **3** to **8** illustrate an embodiment of control objects and control values stored in the memory illustrated in FIG. **1** or **2**. Referring to FIG. **3**, the measurement object and the measured value measured by the measuring device **300** or **300A** may include wind direction or wind speed, stress or load, displacement, cumulative fatigue life, cumulative ultraviolet light amount, residual life, and/or It may be a power output, but is not limited thereto. The control object and the control value corresponding to the measurement object and the measured value may be stored in the memory **400** or **400A**. According to embodiments, the control object and the control value corresponding to the measurement object and the measurement value may be stored in the memory **400** or **400A** in the form of a first lookup table (LUT1).

[0077] For example, when the deformation force of the turbine **200** or the blade **200A** is the response or measured value MSR, the controller **500** or **500A** may control the plurality of control values PA1, LE1, TE1, A first pitch angle PA1 corresponding to the first measured value MSR=M1, a first leading edge control value LE1, and/or a first trailing edge control value TE1 among PA2, LE2, and TE2)) Can be read or selected as the control value CTV. That is, the controller **500** or **500A** may retrieve the control values PA1, LE1, and/or TE1 corresponding to the first measurement value MSR=M1 from the memory **400** or **400A**.

[0078] In an embodiment, when the cumulative power output PO2 of the wind generator **200A** is the measured value MSR, the controller **500A** may control the plurality of control values PA1, LE1, TE1, PA2, and LE2 stored in the memory **400A**. Control the second pitch angle PA2, the second leading edge control value LE2, and/or the second trailing edge control value TE2 corresponding to the second measured value MSR=PO2. It can be read or selected as the value CTV. That is, the controller **500A** may retrieve the control values PA2, LE2, and/or TE2 corresponding to the second

measurement value MSR=PO2 from the memory **400A**.

[0079] The controller **500** or **500A** determines the type (or measurement object) of the measuring device **300** or **300A** or the sensor, and among the control objects (e.g., pitch angle, leading edge, and trailing edge) according to the result of the determination. It is possible to determine how many control object(s) to control.

[0080] As the wind speed increases, the amount of power generated by the wind generator **100A** increases, but the load applied to the wind generator **100A** increases, so that the first lookup table LUT1 considers the wind speed and the load to generate the maximum amount of power generated by the wind generator **100A**. It may include control values for controlling. For example, the wind direction and the wind speed are the first value (M1), the stress and the load are the second value (L1), the displacement is the third value (D1), the cumulative fatigue life is the fourth value (F1), and the cumulative amount of ultraviolet light When the fifth value (U1), the remaining life is the sixth value (R1), and the power output is the seventh value (PO1), the controller **500A** is the first pitch angle (PA1), the first leading edge control value LE1 and/or the first trailing edge control value TE1 may be output as the control value CTV.

[0081] That is, the controller **500** or **500A** reads, selects or searches one control value or a plurality of control values from the memory **400** or **400A** by using the measured value output from one measuring device or the measured values output from the plurality of measuring devices.

[0082] Referring to FIG. 4, the measured object and the measured value measured by the first measuring device include the restoring force, elastic force, aeroelasticity, fatigue load, vibration, strain force, gravity, buoyancy force, rotational speed, and pitch angle of the blade **200** or **200A**. Strain, acceleration, amount of ultraviolet light, insolation, wind speed, temperature, and/or humidity, and the measurement object and the measured value measured by the second measuring device are assumed to be the positions of the blades **200** or **200A**, but are not limited thereto. As described above, although one measuring device **300** or **300A** is shown in FIGS. 1 and 2, each measuring device **300** or **300A** collectively comprises one or more measuring devices (or sensors). Represented by Thus, each measuring device **300** or **300A** can be understood to include a first measuring device and a second measuring device.

[0083] The control object and the control value corresponding to the measurement object and the measured value may be stored in the memory **400** or **400A**. According to embodiments, the control object and the control value corresponding to the measurement object and the measured value may be stored in the memory **400** or **400A** in the form of a second lookup table LUT2. For example, when the deformation force of the blade **200** or **200A** is measured by the primary measuring device and the position of the blade **200** or **200A** is measured by the secondary measuring device, the controller **500** or **500A** may read, select or search the primary pitch angle PA1-1, the primary leading edge control value LE1-1, and/or the primary trailing edge control value TE1-1 corresponding to measured values M1 and BP1 among the multitude of control values PA1-1, PA1-2, LE1-1, LE1-2, TE1-1, and Te1-20 stored in memory **400** or **400A** in response to measured values (M1 and BP1) as control values (CTV).

[0084] For example, when the strain of the blades **200** or **200A** is measured by the first measuring device and the position of the blades **200** or **200A** is measured by the second measuring device, the controller **500** or **500A** may read, select or search the primary pitch angle PA1-2, the secondary leading edge control value LE1-2, and/or the secondary trailing edge control value TE1-1 corresponding to measured values M1 and BP2 among the multitude of control values PA1-1, PA1-2, LE1-1, LE1-2, TE1-1, and Te1-20 stored in memory **400** or **400A** in response to measured values M1 and BP2 as control values (CTV).

[0085] The controller **500** or **500A** may generate at least one control signal CTRL1, CTRL2, and/or CTRL3 in response to the retrieved control values CTV. Accordingly, at least one actuator **600-1**, **600-2**, and/or **600-3** may select at least one of the pitch angle, the leading edge **210**, and the trailing edge **230** of the blade **200** or **200A**. Can be controlled. As a result, the three-dimensional shape of

the blade **200** or **200A** is changed.

[0086] Referring to FIG. 5, the measured object and the measured value measured by the first measuring device include the restoring force, elastic force, aeroelasticity, fatigue load, vibration, strain force, gravity, buoyancy force, rotational speed, and pitch angle of the blade **200** or **200A**. Strain, acceleration, amount of ultraviolet light, insolation, wind speed, temperature, and/or humidity, the measurement object and the measured value measured by the second measuring device are the positions of the blades **200** or **200A**, and the energy conversion device **100** or the cumulative power output of **100A**) is assumed to be a reference value, but is not limited thereto. It is assumed that the power output is measured by the third measuring device, and the accumulated power output is accumulated in the memory **400** or **400A** by the controller **500** or **500A**.

[0087] As described above, although one measuring device **300** or **300A** is shown in FIGS. 1 and 2, each measuring device **300** or **300A** collectively represents one or more measuring devices. Thus, each measuring device **300** or **300A** may be understood to include a first measuring device, a second measuring device, and a third measuring device.

[0088] The control object and the control value corresponding to the measurement object, the measured value, and the reference value may be stored in the memory **400** or **400A**. According to embodiments, the control object and the control value corresponding to the measurement object, the measurement value, and the reference value may be stored in the memory **400** or **400A** in the form of a third lookup table LUT3.

[0089] For example, the deformation force of the blades **200** or **200A** is measured by the first measuring device and the position of the blades **200** or **200A** is measured by the second measuring device, and the cumulative power production amount is set to the first value PO1-1. The controller **500** or **500A** has a plurality of control values PA1-3 to PA1-6 and LE1 stored in the memory **400** or **400A** using the measured values M2 and BP1 and the reference value PO1-1. The first pitch angle PA1-2, the first leading edge control value LE1-3, and/or the first trailing edge control value (−3 to LE1-6 and TE1-3 to TE1-6). TE1-3) may be read, selected, or retrieved as control values CTV.

[0090] The controller **500** or **500A** may generate at least one control signal CTRL1, CTRL2, and/or CTRL3 in response to the retrieved control values CTV. Accordingly, at least one actuator **600-1**, **600-2**, and/or **600-3** may control at least one of the pitch angle of the blade **200** or **200A**, the leading edge **210**, and the trailing edge **230**.

[0091] Referring to FIG. 6, the measurement target and the measured value measured by the first measuring device include the restoring force, elastic force, aeroelasticity, fatigue load, vibration, strain force, gravity, buoyancy force, rotational speed, and pitch angle of the blade **200** or **200A**. Strain, acceleration, amount of ultraviolet light, insolation, wind speed, temperature, and/or humidity, the measurement object and the measured value measured by the second measuring device are the positions of the blades **200** or **200A**, the topographic information, the weather information, And at least one of location information is assumed to be a reference value, but is not limited thereto. The controller **500** or **500A** receives at least one of the terrain information, the weather information, and the location information through the receiver **700**, and stores the received information in the memory **400** or **400A**.

[0092] The control object and the control value corresponding to the measurement object, the measured value, and the reference value may be stored in the memory **400** or **400A**. According to embodiments, the control object and the control value corresponding to the measurement object, the measurement value, and the reference value may be stored in the memory **400** or **400A** in the form of a fourth lookup table LUT4.

[0093] The terrain information includes information about a terrain (topography or geographical features) in which the energy conversion device **100** or **100A** is installed, and the weather information includes weather information of a place where the energy conversion device **100** or **100A** is installed. The location information includes information on the location where the energy conversion device **100** or **100A** is installed and/or information on the location where the other

energy conversion device is installed.

[0094] For example, the elastic force of the blades **200** or **200A** is measured by the first measuring device, and the position of the blades **200** or **200A** is measured by the second measuring device, and at least one of the terrain information, the weather information, and the position information is determined. When having the second value ECP2, the controller **500** or **500A** uses the measured values M3 and BP2 and the reference value ECP2 to control the plurality of control values PA1-7 stored in the memory **400** or **400A**. A fourth pitch angle (PA1-10), a fourth leading edge control value (LE1-10), and/or a fourth of TA1-10, LE1-7 to LE1-10, and TE1-7 to TE1-10) The trailing edge control value TE1-10 may be read, selected, or retrieved as the control values CTV.

[0095] The controller **500** or **500A** may generate at least one control signal CTRL1, CTRL2, and/or CTRL3 in response to the retrieved control values CTV. Accordingly, at least one actuator **600-1**, **600-2**, and/or **600-3** may select at least one of the pitch angle, the leading edge **210**, and the trailing edge **230** of the blade **200** or **200A**. Can be controlled.

[0096] Referring to FIG. 7, the measured object and the measured value measured by the first measuring device include the restoring force, elastic force, aeroelasticity, fatigue load, vibration, strain force, gravity, buoyancy force, rotational speed, and pitch angle of the blade **200** or **200A**. Strain, acceleration, amount of ultraviolet light, insolation, wind speed, temperature, and/or humidity, the measurement object and the measured value measured by the second measuring device are the state of the part, and at least among the terrain information, weather information, and position information. One assumes a reference value but is not limited thereto. The component may include at least one blade **200** or **200A**, at least one component included in the rotor **130**, at least one component included in the nacelle **140**, and/or at least included in the tower **120**. It may mean one component but is not limited thereto.

[0097] The control object and the control value corresponding to the measurement object, the measured value, the location information, the terrain information, the weather information, and the part state may be stored in the memory **400** or **400A**. According to embodiments, the control object and the control value corresponding to the measurement object, the measured value, the location information, the terrain information, the weather information, and the part state may be stored in the memory **400** or **400A** in the form of a fifth lookup table LUT5.

[0098] For example, when the vibration of the blade **200** or **200A** is measured by the first measuring device and the state of the part is measured by the second measuring device, the controller **500** or **500A** refers to the measured values MV1 and S1. A first pitch angle PA3, a first reading among the plurality of control values PA3, PA4, LE3, LE4, TE3, and TE4 stored in the memory **400** or **400A** using the values P1, T1, and W1. The edge control value LE3 and/or the first trailing edge control value TE3 may be read, selected, or retrieved as the control values CTV.

[0099] The controller **500** or **500A** may generate at least one control signal CTRL1, CTRL2, and/or CTRL3 in response to the retrieved control values CTV. Accordingly, at least one actuator **600-1**, **600-2**, and/or **600-3** may control at least one of following: the pitch angle of the blade **200** or **200A**, the leading edge **210**, and the trailing edge **230**.

[0100] Referring to FIG. 8, the control object and the control value corresponding to the measurement object, the measured value, the location information, the terrain information, and the weather information may be stored in the memory **400** or **400A**. According to embodiments, the control object and the control value corresponding to the measurement object and the measured value, location information, terrain information, and weather information may be stored in the memory **400** or **400A** in the form of a sixth lookup table LUT6.

[0101] For example, when the rotational speed per minute of the blades **200** or **200A** is measured by the first measuring device and the position of the blades **200** or **200A** is measured by the second measuring device, the controller **500** or **500A** determines the measured values. A plurality of control values PA3-1 to PA3-16 and LE3-1 to store in the memory **400** or **400A** using the MV3 and BP2 and the reference values T1-4, W1-7, and P1-2. 14th pitch angle (PA3-14), 14th leading edge

control value (LE3-14), and/or 14th trailing edge control value (TE3-14) among LE3-16 and TE3-1-TE3-16) Can be read, selected, or retrieved as control values CTV.

[0102] The controller **500** or **500A** may generate at least one control signal CTRL1, CTRL2, and/or CTRL3 in response to the retrieved control values CTV. Accordingly, at least one actuator **600-1**, **600-2**, and/or **600-3** may control at least one of following: the pitch angle of the blade **200** or **200A**, the leading edge **210**, and the trailing edge **230**.

[0103] **3** to **8**, the measurement object, the measurement value, the reference value, and the control object and the control value stored in each lookup table (LUT1 to LUT6, LUT collectively) have been described, but the controller **500** or **500A** is described. The values not stored in the lookup tables LUT1 to LUT6 may interpolate adjacent control values to generate control signals CTRL1, CTRL2, and/or CTRL3, collectively CTRL. For example, referring to FIGS. **2** and **3**, when the measured value MSR is present between the measured values M1 and M2, the controller **500** or **500A** causes the pitch angles corresponding to the measured values M1 and M2. The first control signal CTRL1 may be generated by searching for PA1 and PA2 and interpolating the pitch angles PA1 and PA2.

[0104] Referring back to FIG. **2**, the first actuator **600-1** may adjust the pitch angle of the blade **200A** based on the first control signal CTRL1.

[0105] The pitch angle may increase or decrease the lifting force generated in the blade **200A**. For example, as the wind speed increases, the lift force generated in the blade **200A** increases, so that the amount of power generated by the wind generator **100A** increases, but the load applied to the wind generator **100A** also increases, thereby reducing the load and maintaining the amount of power generated constant. To do this, the pitch angle may be adjusted in a direction to reduce the area of the blade **200A** to be winded.

[0106] FIGS. **2** and **14**, the second actuator **600-2** opens and shuts the leading edge **210** in response to the second control signal CTRL2, the leading edge **210** and the blade **200A**. The gap GAP1) or the angle ANG1 between the leading edge **210** and the blade **200A** may be adjusted to deform the three-dimensional shape of the blade **200A**.

[0107] When the wind generator **100A** is located in an area where there is little wind, when the leading edge **210** is opened, the density of fluid flow between the leading edge **210** and the blade **200A** is increased by the venturi effect. And lift force (lift force) increases because the pressure received by the blade (**200A**) increases. Therefore, since the rotational speed of the blade **200A** increases, the leading edge **210** may perform a function of collecting a lot of wind around the wind generator **100A**. In addition, as the leading edge **210** is opened more, the load of the wind generator **100A** or the blade **200A** is reduced. Therefore, unlike when the pitch angle is adjusted, if the lift force is increased, the load of the wind generator **100A** or the blade **200A** decreases.

[0108] FIGS. **2** and **15**, the third actuator **600-3** may open or close the trailing edge **230** based on the third control signal CTRL3 and may open or close the trailing edge **230** between the blade **200A** and the trailing edge **230**. The three-dimensional shape of the blade **200A** may be modified by adjusting the gap GAP2 or the angle ANG2 between the trailing edge **230** and the blade **200A**.

[0109] The higher the speed of the fluid, the more turbulence generated in the blade **200A**. The trailing edge **230** may reduce turbulence and direct the direction of the propeller wash, wake stream, or slip stream to another wind generator. Therefore, the energy conversion efficiency of the other wind generator is effective to increase.

[0110] Although four trailing edges **230** are shown in FIG. **2**, the technical idea of the present invention is not limited to the arrangement and number of trailing edges **230**. In addition, although one leading edge **210** is illustrated in FIG. **2**, the technical idea of the present invention is not limited to the arrangement and number of the leading edges **210**.

[0111] FIG. **13** shows the structure of the turbine shown in FIG. **1**, **2**, **9**, **10**, or **12**. As shown in FIG. **13**, blade **200A** includes a plurality of attachable and detachable parts (A, B, C, and D), each of which (A, B, C, and D) may include closed spaces (a, b, c, and d) for storing gas lighter than air

or a material having a density less than that of the fluid (air or water) acting externally on the blade **200A**.

[0112] Therefore, as each enclosed space (a, b, c, and d) is implemented in the blade (**200A**), the weight of the blade (**200A**) is reduced, so that the load applied to the wind generator (**100A**) is reduced. Each of the enclosed spaces a, b, c, and d may include injection ports **250-1**, **250-3**, **250-5**, and **250-7** for injecting the gas or the substance.

[0113] FIG. **9** is a diagram illustrating another embodiment of the energy conversion device illustrated in FIG. **1**. **9**, a wind generator **100B** according to another embodiment of the energy conversion device **100** of FIG. **1** includes a blade **200A**, a measuring device **300A**, a memory **400B**, a controller **500B**, and an actuator, and the like **600-1**, **600-2**, and **600-3**.

[0114] The structure and function of the blade **200A** of FIG. **9** is the same as or similar to the structure and function of the blade **200A** of FIG. **2**, and the structure and function of the measuring device **300A** of FIG. **9** is the measuring device **300A** of FIG. **2**. The structure and function of each of the actuators **600-1**, **600-2**, and **600-3** of FIG. **9** are similar to those of the actuators **600-1**, **600-2**, and **600-3** of FIG.) Is similar in structure and function. The memory **400B** of FIG. **9** corresponds to the memory **400A** of FIG. **2**, and the controller **500B** of FIG. **9** corresponds to the controller **500A** of FIG. **2**.

[0115] The memory **400B** may store the fluid dynamics simulation program **430**. The controller **500B** may read the hydrodynamic simulation program **430** from the memory **400B** and execute the read hydrodynamic simulation program **430**. The controller **500B** may generate at least one control signal CTRL1, CTRL2, or CTRL3 corresponding to the measured value MSR output from the measuring device **300A** using the fluid dynamics simulation program **430**.

[0116] The energy conversion device **100B** for converting the mechanical energy obtained from the fluid flow into electrical energy measures the blade **200A** and the response of the blade when the fluid flow is applied to the blade **200A** with an external force, at least one control signal CTRL1, CTRL2, and/or CTRL3 using one or more measurement values corresponding to the result using the measurement device **300A** and one or more measurement values output from the measurement device **300A**. The controller **500B** for generating a and at least one actuator for modifying the three-dimensional shape of the blade (**200A**) in response to the at least one control signal (CTRL1, CTRL2, and/or CTRL3) output from the controller (**500B**) **600-1**, **600-2**, and/or **600-3**). Here, the fluid dynamics simulation program may mean firmware, software, a program, or a simulation program.

[0117] The memory **400B** may store a fluid dynamics simulation program, such as a computational fluid dynamics (CFD) program, or finite element method (FEM) software. The controller **500B** executes the CFD program **430** stored in the memory **400B** and causes the CFD program **430** to use at least one control signal (1) by using one or more measurement values output from the measuring device **300A**. CTRL1, CTRL2, and/or CTRL3).

[0118] The memory **400B** may further store any one of the lookup tables LUT1 to LUT6 described with reference to FIGS. **3** to **8** in addition to the fluid dynamics simulation program **430**.

[0119] The controller **500B** includes at least one of weather information around the energy conversion device **100B**, topographic information of a place where the energy conversion device **100B** is installed, and position information on a location where the energy conversion device **100B** and another energy conversion device are installed. One can be received via the receiver **700**. The fluid dynamics simulation program **430** may generate at least one control signal CTRL1, CTRL2, and/or CTRL3 using the at least one and one or more measured values output from the measuring device **300A**. According to embodiments, the fluid dynamics simulation program **430** may use at least one of the lookup tables LUT1 to LUT6 stored in the memory **400B** and one or more measurement values output from the measurement device **300A**. Control signals CTRL1, CTRL2, and/or CTRL3 may be generated.

[0120] Each of the measurement devices included in the measurement device **300A** may measure

the position of one of the measurement objects described above with reference to FIG. 4 and the blade **200A** and generate measurement values corresponding to the measurement result. The controller **500B** or the fluid dynamics simulation program **430** may generate at least one control signal CTRL1, CTRL2, and/or CTRL3 using the measured values output from the measuring devices.

[0121] Each actuator **600-1**, **600-2**, and **600-3** responds to each control signal CTRL1, CTRL2, and CTRL3 to control the pitch angle of the blade **200A**, control of the leading edge **210**, and trailing. By controlling the edge **230**, the three-dimensional shape of the blade **200A** may be modified.

[0122] FIG. 10 shows a conceptual diagram of an energy conversion system according to embodiments of the present invention. The energy conversion system **10** of FIG. 10 may be an energy harvesting system that includes a plurality of energy conversion devices (e.g., wind generators) **100-1** and **100-2**. The energy conversion system **10** may be an embodiment of a wind farm, which may refer to a group of wind turbines (or wonder blades) used to produce electricity.

[0123] Referring to FIG. 10, the energy harvesting system or the energy conversion system **10** may include a first wind power generator **100-1**, a second wind power generator **100-2**, and a measuring device **20**. The measuring device **20** refers to a device capable of measuring wind and wind speed.

[0124] The measurer **20** may measure wind power, generate wind power values WIND, and transmit the generated wind power values WIND to the controller **50**. According to embodiments, weather information (or weather signal) output from the satellite or the lighthouse may be transmitted to the receiver **70**.

[0125] Except that the measuring device **20** is installed instead of the measuring device **300A**, the structure of each wind generator **100-1** and **100-2** is the same as that of the wind generator **100A** or **100B** shown in FIG. 2 or 9. In other words, each wind generator **100-1** and **100-2** includes a tower, a rotor, a nacelle, and a plurality of blades, each of the plurality of blades having at least one leading edge and/or at least one trailing edge.

[0126] Each actuator **600-1**, **600-2**, for controlling the pitch angle, each leading edge **210**, and each trailing edge **230** of each blade of each wind generator **100-1** and **100-2**, and **600-3**, collectively **60**, may be included in each wind generator **100-1** and **100-2**.

[0127] The control center for controlling the operation of each wind generator **100-1** and **100-2** includes a memory **40**, a controller **50**, and a receiver **70**.

[0128] The first wind power generator **100-1** includes the first blades **200-1** and the first actuators, each of the first actuators being the actuators **600-1**, **600-2**, and **600-3**, respectively. Corresponding to the first actuators **600-1**, **600-2**, and **600-3** correspond to and collectively correspond to the control signals CTRL1, CTRL2, and CTRL3 output from the controller **50**. The three-dimensional shape of each of the first blades **200-1** may be modified by controlling the pitch angle, the leading edge, and the trailing edge of each of the first blades **200-1** in response to each of the CTRL.

[0129] The second wind power generator **100-2** includes the second blades **200-2** and the second actuators, each of the second actuators being the actuators **600-1**, **600-2**, and **600-3**, respectively. Corresponding to the second actuators **600-1**, **600-2**, and **600-3** correspond to and collectively correspond to the control signals CTRL1, CTRL2, and CTRL3 output from the controller **50**. In response to each of the CTRLs, the three-dimensional shape of each of the second blades **200-2** may be modified by controlling the pitch angle, the leading edge, and the trailing edge of each of the second blades **200-2**.

[0130] The memory **40** may store a control object and a control value corresponding to the input value to be described with reference to FIG. 11.

[0131] The controller **50** reads a first control value among control values stored in the memory **40** in response to the wind power value WIND output from the measuring device **20** and controls the control signal CTRL in response to the read first control value.) At least one of the first actuators may deform at least one three-dimensional shape of the first blades **200-1** in response to the control signal CTRL output from the controller **50**.

[0132] Each of the control values stored in the memory includes weather information around each wind generator **100-1** and **100-2**, topographic information of a place where each wind generator **100-1** and **100-2** is installed, and each wind generator **100-1** and **100-2** have different values according to at least one of the location information on the installed location.

[0133] The controller **50** may store the weather information, the terrain information, and/or the location information received through the receiver **70** in the memory **40**.

[0134] One of the first actuators may modify the three-dimensional shape of each of the first blades **200-1** by adjusting the pitch angle of each of the first blades **200-1** in response to the control signal CTRL. Can be. The other of the first actuators may open or close a leading edge in response to a control signal CTRL, a gap between the leading edge and each of the first blades **200-1**, and the leading edge and the first blade. The three-dimensional shape of each of the first blades **200-1** may be modified by adjusting at least one of the angles ANG1 between the fields **200-1**.

[0135] Another one of the first actuators may open or close a trailing edge in response to a control signal CTRL, a gap between the trailing edge and each of the first blades **200-1**, and the trailing edge. And three-dimensional shapes of each of the first blades **200-1** may be modified by adjusting at least one of angles between the first blades **200-1** and each of the first blades **200-1**.

[0136] FIG. **11** illustrates an embodiment of control objects and control values stored in the memory illustrated in FIGS. **10**. **10** and **11**, the wind power value, the input value, and the control object and the control value may be stored in the memory **40**. According to embodiments, the control target and the control value corresponding to the wind power value, location information, terrain information, and weather information may be stored in the memory **40** in the form of a seventh look-up table LUT7.

[0137] For example, when the wind power value WIND output from the measuring device **20** is the first wind power value WIND1, the controller **50** determines the measured value WIND1 and the input values T1-2, W1-4, and P1. Pitch angle PA3-8 among the plurality of control values PA3-1 to PA3-16, LE3-1 to LE3-16, and TE3-1 to TE3-16 stored in the memory **40** by using a -2).), The eighth leading edge control value LE3-8, and/or the eighth trailing edge control value TE3-8 may be read, selected, or retrieved as the control values CTV.

[0138] The controller **50** may generate at least one control signal CTRL1, CTRL2, and/or CTRL3, collectively CTRL, in response to the retrieved control values CTV. Therefore, at least one first actuator may control at least one of the pitch angle, the leading edge, and the trailing edge of the first blade **200-1**.

[0139] In addition, when the wind power value WIND output from the measuring device **20** is the first wind power value WIND1, the controller **50** determines the measured value WIND1 and the input values T1-1, W1-1, and P1. The first pitch angle PA3-1 among the plurality of control values PA3-1 to PA3-16, LE3-1 to LE3-16, and TE3-1 to TE3-16 stored in the memory **40** by using a -1).), The first leading edge control value LE3-1, and/or the first trailing edge control value TE3-1 may be read, selected, or retrieved as the control values CTV.

[0140] The controller **50** may generate at least one control signal CTRL1, CTRL2, and/or CTRL3, collectively CTRL, in response to the retrieved control values CTV. Accordingly, at least one first actuator may control at least one of the pitch angle, the leading edge, and the trailing edge of the first blade **200-1**.

[0141] **12** illustrates a conceptual diagram of an energy conversion system according to embodiments of the present invention. Except for the meter **20**, the structure and operation of the energy conversion system **10-1** of FIG. **12** are the same as or similar to the structure and operation of the energy conversion system **10** of FIG. **10**.

[0142] In addition, the control values stored in the memory **40-1** do not include the wind power value WIND measured from the meter **20**.

[0143] The controller **50**, through the receiver **70**, weather information around each of the wind generators **100-1** and **100-2**, terrain information of a place where each wind generator **100-1** and

100-2 is installed, and each wind power. At least one (INV) may be received from the position information on a location where the generators **100-1** and **100-2** are installed, and at least one INV may be stored in the memory **40-1**.

[0144] FIGS. **11** and **12**, the controller **50** uses a plurality of control values PA3-1 to PA3 stored in the memory **40** using input values T1-1, W1-1, and P1-1. A first pitch angle PA3-1, a first leading edge control value LE3-1, and/or a first trailing edge among -16, LE3-1 to LE3-16, and TE3-1 to TE3-16. The control value TE3-1 may be read, selected, or retrieved as the control values CTV.

[0145] FIG. **16** is a flow chart illustrating the operation of the energy conversion device shown in FIGS. **1**, **2**, or **9**. In FIG. **16**, a method of operating the energy conversion device **100** for converting mechanical energy obtained from a fluid flow into electrical energy is measured by the measuring device **300**. When the flow is applied to the blade **200** by an external force, it measures the response of the blade **200**, and generates a measurement value corresponding to the measurement result (S110).

[0146] The controller **500** reads a first control value from among control values stored in the memory **400** in response to the measured value output from the measuring device **300** and uses the first control value to generate a control signal CTRL. It generates (S130). The actuator **600** deforms the three-dimensional shape of the blade **200** in response to the control signal CTRL output from the controller **500** (S150).

[0147] Each of the control values stored in the memory **400** includes weather information around the energy conversion device **100**, terrain information of a location where the energy conversion device **100** is installed, and a location where the energy conversion device **100** and other energy conversion devices are installed. It has different values according to at least one of the location information for.

[0148] FIG. **17** is a flow chart illustrating the operation of the energy conversion system shown in FIG. **10** or **12**. In FIG. **17**, the controller **50** receives at least one of weather information, terrain information, and location information through the receiver **70**, and stores the received at least one memory **40** or **40-1** to store it (S210).

[0149] The controller **50** reads a first control value among control values stored in the memory **40** or **40-1** in response to the at least one, and generates a control signal CTRL using the read first control value (S230). The actuator **60** deforms the three-dimensional shape of the blade in response to the control signal CTRL output from the controller **50** (S250).

[0150] As described with reference to FIGS. **1** through **17**, the energy conversion device **100** for converting mechanical energy obtained from a fluid flow (or flow of fluid) into electrical energy includes a blade **200** or **200A**, measuring devices. **300**, memory **400**, controller **500**, and actuator **600**. The measuring devices **300** measure the response of the blades **200** or **200A** when the fluid flow is exerted on the blades **200** or **200A** and generate measurements corresponding to the results of the measurements.

[0151] As described above with reference to FIGS. **3** through **8** and **11**, the memory **400** includes first values representing an internal environment of the energy conversion device **100** and second values representing an external environment of the energy conversion device **100**. Stores control values corresponding to a combination of the two values.

[0152] The controller **500** reads any one of the control values from the memory **400** in response to the measured values output from the measuring devices **300**, and in response to the one of the read control values. Generate a control signal CTRL.

[0153] The actuator **600** deforms the three-dimensional shape of the blade **200** or **200A** in response to the control signal CTRL output from the controller **500**. The memory **400** may be a cache memory embedded in the controller **500**.

[0154] The internal environment includes the position information of the blade **200** or **200A**, the cumulative amount of generation of the energy conversion device **100**, the cumulative fatigue life of the blade **200** or **200A**, the cumulative amount of ultraviolet light of the blade **200** or **200A**, and

the blade **200**. Or at least one of the remaining lifespan of **200A**) but is not limited thereto. The measurement object described with reference to FIGS. **3** to **8** may also be included in the internal environment.

[0155] The controller **500** or **500A** may update each of the control values stored in each lookup table LUT**1** to LUT**7** by using the internal environment of the energy conversion device **100**. For example, the controller **500** or **500A** may include predictive diagnosis technology, artificial intelligence (AI) technology, context awareness computing technology, cumulative power production of the energy conversion device **100**, or energy. Each of the control values stored in each of the lookup tables LUT**1** to LUT**7** may be updated using the result of monitoring the state of the component of the converter **100**.

[0156] The external environment may include first location information about a first location where the energy conversion device **100** is installed, second location information about a second location where the energy conversion device **100** and another energy conversion device are installed, and the first location. At least one of weather information for at least one of the second locations, and terrain information including the first location information and the second location information.

[0157] The controller **500** or **500A** may update each of the control values stored in each of the lookup tables LUT**1** to LUT**7** by reflecting the external environment. In the present specification, the structure and operation of the wind power generators **100A**, **100B**, **100-1**, and **100-2** are described as embodiments of the energy conversion device **100**. However, the technical idea of the present invention can be applied as it is in the tidal generator and wave generator.

[0158] Although the present invention has been described with reference to the embodiments illustrated in the drawings, this is merely exemplary, and it will be understood by those skilled in the art that various modifications and equivalent other embodiments are possible. Therefore, the true technical protection scope of the present invention will be defined by the technical spirit of the appended claims.

[0159] The present invention can be used in an energy conversion device, a wind power generation system including the energy conversion device, and a method of operating the energy conversion device.

Claims

1. An energy conversion device for converting mechanical energy obtained from flowing fluids into electrical energy, comprising: a blade assembled from a plurality of attachable and detachable parts, wherein the blade includes one or more of closed spaces for storing gases lighter than air or materials with a density less than or equal to that of the fluid acting on the blade.
2. The energy conversion device of claim 1, further comprising an actuator for adjusting a three-dimensional shape of the blade, wherein the actuator is operable via a control signal generated by a controller based on one or more parameters associated with either the energy conversion device or external environment interacting with the energy conversion device.
3. The energy conversion device of claim 2, wherein said one or more parameters associated with either the energy conversion device or external environment interacting with the energy conversion device include parameters representing: restoration force of the blade, elasticity of the blade, aeroelasticity of the blade, current rotational speed of the blade, current pitch angle of the blade, cumulative fatigue load on the blade, vibration of the blade, strain on the blade, weight of the blade, buoyancy of the blade, cumulative amount of ultraviolet light received by the blade, cumulative amount of solar radiation received by the blade, current temperature of the blade, the speed of the fluid flow, or the relative humidity of the blade.
4. The energy conversion device of claim 2, wherein each of said one or more of closed spaces for storing gases includes an injection port, and the controller is configured to generate the control signal based on a parameter representing an internal pressure of the closed space.

5. The energy conversion device of claim 2, wherein the controller is equipped with a memory that stores a numerical analysis model for generating the control signal.
 6. The energy conversion device of claim 2, wherein the blade has at least one of an adjustable leading-edge and an adjustable trailing-edge, and the actuator is configured to adjust the three-dimensional shape of the blade by adjusting at least one of a pitch angle, a leading-edge gap or a trailing-edge gap of the blade in response to the control signal.
 7. The energy conversion device of claim 2, wherein the controller is further configured to adjust the control signals based on weather information, terrain information, and location information where the energy conversion device is installed.
 8. The energy conversion device of claim 2, wherein the controller is provided in a local unit that the blade and the actuator are installed with.
 9. The energy conversion device of claim 2, wherein the controller is provided remotely from a unit that has the blade and the actuator, and configured to send the control signal via a communication network to control the actuator.
 10. An energy conversion system comprising: a plurality of energy conversion devices, each having a blade assembled from a plurality of attachable and detachable parts; and a central control unit capable of coordinating blade adjustments across the plurality of energy conversion devices based on collective data on environmental conditions and performance of each of the plurality of energy conversion devices, wherein the blade includes one or more of closed spaces for storing gases lighter than air or materials with a density less than or equal to that of the fluid acting on the blade.
 11. The system of claim 10, wherein said blade adjustments include adjustment to at least one of a pitch angle, a leading-edge gap or a trailing-edge gap of the blade.
 12. The system of claim 10, wherein the central control unit utilizes a machine learning algorithm to predict optimal blade adjustments based on historical data and current environmental conditions.
 13. The energy conversion system of claim 10, further comprising energy storage units for storing excess electrical energy generated by the plurality of energy conversion devices.
 14. The energy conversion system of claim 10, wherein each of the energy conversion devices includes a feedback system for real-time adjustments based on actual energy conversion efficiency.
 15. A method for operating an energy conversion device to convert mechanical energy from flowing fluids into electrical energy, comprising: measuring one or more parameters associated with either the energy conversion device or external environment interacting with the energy conversion device; generating control signals by a controller using said one or more parameters, with the controller executing a numerical analysis model to determine optimal adjustments for the blade's shape; and adjusting a three-dimensional shape of the blade via an actuator in response to the control signals.
 16. The method of claim 15, wherein adjusting the three-dimensional shape of the blade includes altering at least one of a pitch angle, a leading-edge gap or a trailing-edge gap of the blade based on the control signals.
 17. The method of claim 15, further including dynamically updating the control signals in response to real-time changes in the measured environmental parameters.
 18. The method of claim 15, further comprising updating the control signals based on predictive models of environmental changes.
 19. The method of claim 15, including optimizing the blade's shape on real-time and forecasted environmental data to maximize energy conversion efficiency.
 20. The method of claim 15, including optimizing the control signals based on the blade's condition estimated from historical data on environmental conditions.
-