

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250279997

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Kutthumolu; Durga Prasad et al.

System and method to perform light-based data exchange operations

Abstract

A system comprises a memory communicatively coupled to at least one processor. The at least one processor is configured to receive a code-based data exchange request from a user. The code-based data exchange request comprises first user information associated with a user profile. Further, the at least one processor is configured to trigger a request for a retinal scan of the user in response to receiving the code-based data exchange request and receive a result of the retinal scan of the user. The result comprises second user information. The at least one processor is configured to determine that the code-based data exchange request is authentic in response to determining that the first user information and the second user information are associated with the user profile, convert the code-based data exchange request to a light-based data exchange request, and generate a light-guided contract based on the light-based data exchange request.

Inventors: Kutthumolu; Durga Prasad (Hyderabad, IN), Rajagopalan; Anurajam (Chennai, IN), Krishnan; Subburathinam (Chennai, IN)

Applicant: Bank of America Corporation (Charlotte, NC)

Family ID: 96880688

Appl. No.: 18/594599

Filed: March 04, 2024

Publication Classification

Int. Cl.: H04L9/40 (20220101)

U.S. Cl.:

CPC H04L63/0861 (20130101); H04L63/083 (20130101);

Background/Summary

TECHNICAL FIELD

[0001] The present disclosure relates generally to light-based operations, and more specifically to a system and method to perform light-based data exchange operations.

BACKGROUND

[0002] In communication systems, multiple devices may perform data exchange operations with one another. In certain communication systems, there may be bad actors that attempt to intercept communications between the devices. These bad actors may implement a variety of approaches to gain access to lines of communication between the devices to obtain and/or modify data exchanged between the devices. Further, these bad actors may attempt to obtain and/or modify information associated with the devices or operators (e.g., users) of these devices.

SUMMARY OF THE DISCLOSURE

[0003] In one or more embodiments, systems and methods are configured to perform light-based data exchange operations. In particular, the system is configured to perform data exchange operations in a decentralized network (e.g., a blockchain network) using light-guided contracts and an optical-based ledger on preventing our problem statement. The system may be configured to enable data exchange operations through smart contracts in the decentralized network based on one or more requests received from one or more users. The systems may be configured to trigger any data exchange transactions using light-based triggers instead of code-based triggers. In this regard, signatures of light patterns may be used to confirm and/or verify information in databases instead of structured data associated with code-based communications. In some embodiments, the system is configured to convert code-based data exchange requests from a user to light-based data exchange requests using at least one Artificial Intelligent model. The system may be configured to request a retinal scan from the user to validate users making any requests. In certain embodiments, light communications may be encoded and/or decoded in accordance with one or more rules and policies of an organization. The light communications may be exchanged using networks configured to handle visible light communication technologies (e.g., LI-FI networks).

[0004] In one or more embodiments, the system described herein are integrated into a practical application of performing light-based data exchange operations. For example, the system enables light-based communications in a system configured to perform one or more data exchange operations in a decentralized network. The light-based communications are harder to intercept and more difficult to decode as light is transmitted at near-instant speeds. In some embodiments, the system is integrated in the practical application of encoding and/or decoding light-based communications exchanged between one or more devices. In some embodiments, the light-based communications are secured by performing light-based authentication of a user generating a data exchange request.

[0005] In one or more embodiments, the system is directed to improvements in computer systems. Specifically, the system reduces processor and memory usage in servers and/or user devices by converting code-based data exchange request to light-based data exchange requests. In particular, the system is configured to reduce and/or eliminate data interceptions from bad actors in a communication network. In some embodiments, by converting the code-based requests to light-based requests, the systems may dynamically transform code-based communications into light-based communications. In this regard, memory usage is reduced because subsequent transactions performed by the system rely on near-instant analysis and/or processing allowed by light-based communications. Further, processing speeds are increased by implementing the system because light-based communications enable near-instant verification of data by comparing signatures of a light-based communication.

[0006] In one or more embodiments, the systems may comprise an apparatus, such as the server. Further, the system may be a data exchange system, that comprises the apparatus. In addition, the system may be configured to perform operations as part of a process performed by the apparatus.

As a non-limiting example, the system may comprise a memory and at least one processor communicatively coupled to one another. The memory may be operable to store one or more user profiles. Each user profile may comprise that at least one user is entitled to perform one or more data exchange operations in a decentralized network. The at least one processor is configured to receive a code-based data exchange request from a user. The code-based data exchange request may comprise first user information associated with a user profile and data exchange information associated with a data exchange operation. Further, the at least one processor is configured to trigger a request for a retinal scan of the user in response to receiving the code-based data exchange request and receive a result of the retinal scan of the user. The result may represent second user information. The at least one processor may be configured to determine whether the first user information and the second user information are associated with the user profile in response to receiving the result of the retinal scan of the user, determine that the code-based data exchange request is authentic in response to determining that the first user information and the second user information are associated with the user profile, convert the code-based data exchange request to a light-based data exchange request, and generate a light-guided contract based on the light-based data exchange request. The light-guided contract indicating that the user associated with the user profile is entitled to trigger the data exchange operation. The at least one processor is configured to generate a light-based token to initiate the data exchange operation with the decentralized network and transmit the light-based token to the decentralized network.

[0007] Certain embodiments of this disclosure may include some, all, or none of these advantages. These advantages and other features will be more clearly understood from the following detailed description taken in conjunction with the accompanying drawings and claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] For a more complete understanding of this disclosure, reference is now made to the following brief description, taken in connection with the accompanying drawings and detailed description, wherein like reference numerals represent like parts.

[0009] FIG. 1 illustrates a system in accordance with one or more embodiments; and

[0010] FIG. 2 illustrates an example flowchart of a method to perform light-based data exchange operations in accordance with one or more embodiments.

DETAILED DESCRIPTION

[0011] As described above, this disclosure provides various systems and methods configured to perform light-based data exchange operations. FIG. 1 illustrates a system **100** in which a server **102** performs one or more data exchange operations **104** with one or more decentralized networks **106**. FIG. 2 illustrates a process **200** performed by the system **100** of FIG. 1.

System Overview

[0012] FIG. 1 illustrates an example system **100**, in accordance with one or more embodiments. The system **100** may comprise a server **102** configured to perform one or more light-based data exchange operations **104** in one or more decentralized networks **106**. The system **100** includes a server **102** communicatively coupled to a user device **110a**, a user device **110b**, a user device **110c**, and a user device **110d** (collectively, user devices **110**) and/or a node **112a**, a node **112b**, a node **112c**, a node **112d**, and a node **112e** (collectively, nodes **112**) in the one or more decentralized networks **106** via a network **114**. The user devices **110** may be working nodes configured to receive instructions to perform one or more data exchange operations **104** based on instructions received from the server **102**. In some embodiments, some of the user devices **110** may be clustered together in a user device group **116**. Each of the user devices **110** may be associated with one or more corresponding operators. These operators are shown as a user **118a**, a user **118b**, and a user **118c**.

(collectively, users **118**) in the user device group **116**. In FIG. 1, the user **118a** is shown associated with the user device **110b**, the user **118b** is shown associated with the user device **110c**, and the user **118c** is shown associated with the user device **110d**.

[0013] In one or more embodiments, the server **102** may comprise one or more databases **122**, one or more server input (I)/output (O) interfaces **124**, at least one server processor **126**, and at least one memory **130** communicatively coupled to one another. In some embodiments, the memory **130** may comprise instructions **132**, one or more request converter operations configured to convert one or more code-based requests **136** into one or more light-based requests **138** and/or one or more light-based requests **138** into one or more code-based requests **136**, one or more data exchange requests **140**, the one or more data exchange operations **104**, one or more retinal scans **142**, one or more light signatures **146**, one or more light-based tokens **148** to be used in the one or more decentralized networks **106**, user information **150** configured to associate one or more user profiles **152** with one or more entitlements **154** to access one or more services **156**, one or more artificial intelligence (AI) commands configured to train one or more cognitive AI models **160**, one or more machine learning (ML) algorithms **162**, one or more rules and policies **164**, one or more light-guided contracts **166**, one or more light-based ledgers **168**, and one or more reports **170**.

[0014] Referring to the user device **110a** a non-limiting example, the user device **110a** may comprise one or more device interfaces **172**, one or more server peripherals **174**, at least one server processor **176**, and at least one server memory **178** communicatively coupled to one another. The server memory **178** may comprise server instructions **180**, collected data **182**, and/or one or more local applications **184**.

[0015] Referring to the node **112a** a non-limiting example, the node **112a** may comprise one or more configuration parameter **190a** and/or one or more data exchange controls **192a**. In the example of FIG. 1, the node **112b** includes one or more configuration parameter **190b** and/or one or more data exchange controls **192b**, the node **112c** includes one or more configuration parameter **190c** and/or one or more data exchange controls **192c**, the node **112d** includes one or more configuration parameter **190d** and/or one or more data exchange controls **192d**, and the node **112e** includes one or more configuration parameter **190e** and/or one or more data exchange controls **192e**.

System Components

Server

[0016] The server **102** is generally any device or apparatus that is configured to process data and communicate with computing devices (e.g., the user devices **110** and/or the nodes **112**), additional databases, systems, and the like, via the one or more server I/O interfaces **124** (i.e., a user interface or a network interface). The server **102** may comprise the server processor **126** that is generally configured to oversee operations of the processing engine. The operations of the processing engine are described further below in conjunction with the system **100** described in FIG. 1 and the process **200** described in FIG. 2.

[0017] The server **102** comprises multiple databases **122** configured to provide one or more memory resources to the server **102** and/or the user devices **110**. The server **102** comprises the server processor **126** communicatively coupled with the databases **122**, the server I/O interfaces **124**, and the memory **130**. The server **102** may be configured as shown, or in any other configuration. In one or more embodiments, the databases **122** are configured to store data that enables the server **102** to configure, manage and coordinate one or more middleware systems. In some embodiments, the databases **122** store data used by the server **102** to act as a halfway point in between one or more services **156** and other tools or databases.

[0018] In one or more embodiments, the server I/O interfaces **124** may be configured to enable wired and/or wireless communications. The server I/O interfaces **124** may be configured to communicate data between the server **102** and other user devices (i.e., the user devices **110** and/or the node **112**), network devices (i.e., routers in the network **114**), systems, or domain(s) via the

network **114**. For example, the server I/O interfaces **124** may comprise a WI-FI interface, a LAN interface, a WAN interface, a modem, a switch, or a router. The server processor **126** may be configured to send and receive data using the server I/O interfaces **124**. The server I/O interfaces **124** may be configured to use any suitable type of communication protocol. In some embodiments, the server I/O interfaces **124** may be an admin console comprising a web browser-based or graphical user interface used to manage a middleware server domain via the server **102**. A middleware server domain may be a logically related group of middleware server resources that managed as a unit. A middleware server domain may comprise the server **102** and one or more managed servers. The managed servers may be standalone devices and/or collected devices in the server cluster. The server cluster may be a group of managed servers that work together to provide scalability and higher availability for the services **156**. In this regard, the services **156** are developed and deployed as part of at least one domain. In other embodiments, one instance of the managed servers in the middleware server domain may be configured as the server **102**. The server **102** provides a central point for managing and configure the managed servers and any of the one or more services **156**.

[0019] The server processor **126** comprises one or more processors communicatively coupled to the memory **130**. The server processor **126** may be any electronic circuitry, including, but not limited to, state machines, one or more central processing unit (CPU) chips, logic units, cores (e.g., a multi-core processor), field-programmable gate arrays (FPGAs), application-specific integrated circuits (ASICs), or digital signal processors (DSPs). The server processor **126** may be a programmable logic device, a microcontroller, a microprocessor, or any suitable combination of the preceding. The one or more server processor **126** are configured to process data and may be implemented in hardware or software executed by hardware. For example, the server processor **126** may be 8-bit, 16-bit, 32-bit, 64-bit or of any other suitable architecture. The server processor **126** may include an arithmetic logic unit (ALU) for performing arithmetic and logic operations, processor registers that supply operands to the ALU and store the results of ALU operations, and a control unit that fetches the instructions **132** from the memory **130** and executes them by directing the coordinated operations of the ALU, registers and other components. In this regard, the one or more server processor **126** are configured to execute various instructions. For example, the one or more server processor **126** are configured to execute the instructions **132** to implement the functions disclosed herein, such as some or all of those described with respect to FIGS. **1** and **2**. In some embodiments, the functions described herein are implemented using logic units, FPGAs, ASICs, DSPs, or any other suitable hardware or electronic circuitry.

[0020] In one or more embodiments, the server I/O interfaces **124** may be any suitable hardware and/or software to facilitate any suitable type of wireless and/or wired connection. These connections may include, but not be limited to, all or a portion of network connections coupled to the Internet, an Intranet, a private network, a public network, a peer-to-peer network, the public switched telephone network, a cellular network, a local area network (LAN), a metropolitan area network (MAN), a wide area network (WAN), and a satellite network. The server I/O interfaces **124** may be configured to support any suitable type of communication protocol as would be appreciated by one of ordinary skill in the art. In one or more embodiments, the server I/O interfaces **124** may comprise one or more sensors configured to evaluate physical phenomena surrounding the server **102** and/or one or more of the user devices **110**. The sensors may be proximity sensors, optical sensors, and the like.

[0021] The memory **130** may be volatile or non-volatile and may comprise a read-only memory (ROM), random-access memory (RAM), ternary content-addressable memory (TCAM), dynamic random-access memory (DRAM), and static random-access memory (SRAM). The memory **130** may be implemented using one or more disks, tape drives, solid-state drives, and/or the like. The memory **130** is operable to store the instructions **132**, the one or more request converter operations **134** comprising the one or more code-based requests **136** and/or the one or more light-based

requests **138**, the one or more data exchange requests **140**, the one or more data exchange operations **104**, the one or more retinal scans **142**, the one or more light signatures **146**, the one or more light-based tokens **148**, the user information **150** comprising the one or more user profiles **152** associated with the one or more entitlements **154** to access and/or modify the one or more services **156**, the one or more AI commands **158** comprising one or more models **160**, the one or more algorithms **162**, the one or more rules and policies **164**, the one or more light-guided contracts **166**, the one or more light-based ledgers **168**, and the one or more reports **170**. The instructions **132** may comprise any suitable set of instructions, logic, rules, or code operable to execute the server processor **126**.

[0022] The one or more converter operations **134** may be one or more operations configured to convert one or more of the code-based requests **136** to corresponding one or more of the light-based requests **138**. Further, the one or more converter operations **134** may be one or more operations configured to convert one or more of the light-based requests **138** to corresponding one or more of the code-based requests **136**. The one or more code-based requests **136** may be one or more information strings, alphanumeric data, and/or configuration commands to be exchanged in a data network. The one or more light-based requests **138** may be a collection of light-based information to be exchanged in a light network. The code-based requests **136** and the light-based requests **138** may be data exchange requests **140** configured to trigger one or more of the data exchange operations **104**. The code-based requests **136** and the light-based requests **138** may be exchanged in bulk or individually over the network **114**.

[0023] The one or more data exchange requests **140** may be one or more communications configured to provide triggers in the form of communication or control signals to start operations such as fetching the instructions **132** or running one or more of data exchange operations **104**. The data exchange requests **140** may provide user information **150** to the server **102** to indicate at least one user profile **152** associated with one or more of the entitlements **154** to access and/or modify any of the services **156** available in the server **102**. The data exchange requests **140** may be configured to provide lists, security information, and configuration commands that the server **102** uses to set up a specific service **156** for one of the user devices **110**. The data exchange requests **140** may comprise data that provides starting procedure configuration to the server **102**. In one or more embodiments, the data exchange requests **140** may be optimized instructions that trigger establishing of a specific procedure in the server **102**.

[0024] The one or more retinal scans **142** are light representations of optical scans of one or more user retinas. The one or more retinal scans **142** may be obtained in accordance with one or more photosensitive light accurate detection (LAD) operations performed one or more of the server I/O interfaces **124**. The LAD operations may comprise prompting a user to provide access for an optical scan. In this regard, the user (e.g., one of the users **118**) may look to one of the server I/O interfaces configured to perform the optical scan. The retinal scans **142** may be one or more copies of the collected data **182** collected by one or more of the user devices **110**. The one or more light signatures **146** may be light-based representation of the retinal scans **142**, the one or more light-based tokens **148**, and/or the user information **150**. The light signatures **146** may be light-based representations of light information in a visible spectrum. The light signatures **146** may be data representative of datapoints in a light spectrum.

[0025] In one or more embodiments, the data exchange operations **104** are configured to create, analyze, manage, and update one or more light-based tokens **148**. The data exchange operations **104** may be configured to communicate one or more of the data exchange requests **140** with the one or more decentralized networks **106** via user and/or network interfaces and connections. The data exchange operations **104** may be configured to perform one or more of the operations in the process **200** described in reference to FIG. 2. In some embodiments, the data exchange operations **104** may be configured to update one or more user profiles **152** in the user information **150**. In some embodiments, the server **102** may be configured to generate the light-based tokens **148** to

perform one or more of the data exchange operations **104** with the decentralized network **106** as triggered by one or more of the user devices **110**.

[0026] In yet other embodiments, one or more of the user devices **110** may request the decentralized networks **106** via the server **102** to generate the light-based tokens **148** dynamically or periodically over time in accordance with one or more token attributes. The token attributes may at least partially represent any of the data exchange requests **140** from the user devices **110**. The triggers received from the user devices **110** may be referenced as part of one or more token attributes. In some embodiments, the light-based tokens **148** may be a non-fungible token (NFT) that is generated along encrypted geolocation of the user device and point-of-exchange (PoE) information. The PoE information may comprise location information in which a data exchange request is triggered by one of the user devices. In some embodiments, the PoE information indicate a relation between the light-based tokens **148**, the entitlements **154**, and one or more reports **170** (e.g., receipts) obtained when a data exchange is attempted. The light-based tokens **148** may be a string of numbers, alphanumeric characters, one or more words or phrases, one or more letters, and/or symbols. In some embodiments, the light-based tokens **148** are generated in accordance with one or more token attributes. The server **102** may be configured to present data exchange output receipts in one or more reports **170** to the user devices **110**.

[0027] The user information **150** may comprise the one or more user profiles **152**, one or more entitlements **154**, and one or more services **156**. In one or more embodiments, the user profiles **152** may comprise multiple profiles associated with one or more entitlements **154** to access and/or modify the services **156**. Each of the user profiles **152** may be associated with one or more entitlements **154**. The entitlements **154** may indicate that a given user device **110** is allowed to access one or more network resources in accordance with the one or more rules and policies **164**. The entitlements **154** may indicate that a given user device **110** is allowed to perform one or more operations in the system **100** (e.g., provide a specific application data access to one of the users **118**). To secure or protect operations of the user devices **110** from bad actors, the entitlements **154** may be assigned to a given user profile **152** in accordance with updated security information, which may provide guidance parameters to the use of the entitlements **154** based at least upon corresponding rules and policies **164**. In one or more embodiments, the one or more services **156** are access to one or more application operations performed in accordance with the application data. In some embodiments, the user profiles **152** may comprise multiple profiles for users (e.g., user **118**). Each user profile **152** may comprise one or more entitlements **154**. As described above, the entitlements **154** may indicate that a given user **118** is allowed to access one or more network resources in accordance with one or more rules and policies **164**. The entitlements **154** may indicate that a given user is allowed to perform one or more data exchanges with the light-based tokens **148** via the decentralized networks **106**. In one or more embodiments, each of the user profiles **152** may comprise information about at least one user **118** entitled to trigger one or more data exchange operations **104** in the decentralized network **106**.

[0028] In one or more embodiments, the ML algorithms **162** may be executed by the server processor **126** to evaluate the data exchange requests **140**. Further, the ML algorithms **162** may be configured to interpret and transform the data exchange requests **140** and/or the instructions **132** into structured data sets and subsequently stored as files or tables. The ML algorithms **162** may cleanse, normalize raw data, and derive intermediate data to generate uniform data in terms of encoding, format, and data types. The ML algorithms **162** may be executed to run user queries and advanced analytical tools on the structured data. The ML algorithms **162** may be configured to generate the one or more AI commands **158** based on one or more results of the testing operations. The AI commands **158** may be parameters that proactively trigger one or more of the request converter operations **134** to convert any code-based requests **136** received into one or more light-based requests **138**. The AI commands **158** may be combined with the existing instructions **132** to dynamically trigger and/or perform the data exchange operations **104**. The AI commands **158** may

be configured to trigger one or more cognitive AI operations in accordance with one or more models **160**. The models **160** may be trained by the one or more ML algorithms **162** based on historic information associated with any data exchange operations **104** performed with the server **102**.

[0029] The rules and policies **164** may be security configuration commands or regulatory operations predefined by an organization or one or more users **118**. In one or more embodiments, the rules and policies **164** may be dynamically defined by the one or more users **118**. The rules and policies **164** may be prioritization rules configured to instruct one or more user devices **110** to perform one or more testing operations or perform one or more operations in the system **100** in a specific data exchange request **140**. The one or more rules and policies **164** may be predetermined or dynamically assigned by a corresponding user **118** or an organization associated with the users **118**.

[0030] The one or more light-guided contracts **166** may be configured to maintain one or more light-based tokens **148**. The one or more light-based ledgers **168** may be configured to monitor use of the light-based tokens **148** in the decentralized networks **106**. The one or more reports **170** may be one or more receipts associated with completion of the data exchange requests **140**. In one or more embodiments, the light-guided contracts **166** and the one or more light-based ledgers **168** may be accessed upon validating the identity of the users **118**. The validation of the identity of the users **118** may be performed based on identifying one or more retinal scans **142** of the users **118**.

[0031] In one or more embodiments, the data exchange operations **104** may be one or more operations configured to be performed at multiple locations. The data exchange operations **104** may be operations distributed to exchange one or more data objects associated with one or more user devices **110**. The data exchange operations **104** may be distributed in multiple locations physically separated from one another. The data exchange operations **104** may be testing operations performed to evaluate one or more portions of application data associated with one or more of the services **156**.

[0032] In one or more embodiments, the databases **122** may be one or more light-based repositories configured to store light-based information. In one example, the server **102** may determine the server processor **126** is available (e.g., running) to perform a specific service **156**. In another example, the server **102** may determine that a specific managed server is running to enable a testing application and/or perform the specific service **156** upon receiving a server response indicating that a corresponding managed server is available to perform the service **156**. The databases **122** may be configured to store one or more light representations of data instead of storing coded data. In this regard, the light representations may be encoded in accordance with a light-based encoder configured to identify and/or verify light-based information. For example, the databases **122** may comprise one or more light representations of the retinal scans **142**. As the retinal scans **142** are received from the user devices **110**, the server processor **126** may be configured to compare the retinal scans **142** with a light-based representation of a previous version of a retinal scan **142** for a specific user **118**. The comparison may be performed instantaneously or near-instantaneously (e.g., faster than comparing coded data) as light speed enables faster processing operations.

User Device

[0033] In one or more embodiments, each of the user devices **110** (e.g., the user device **110a** and/or the user devices **110b-110d** in the device group **116**) may be any computing device configured to communicate with other devices, such as the server **102**, other user devices **110** in the user device group **116**, databases, and the like in the system **100**. Each of the user devices **110** may be configured to perform specific functions described herein and interact with the server **102** and/or any other user devices **110**. Examples of the user devices **110** comprise, but are not limited to, a laptop, a computer, a smartphone, a tablet, a smart device, an IoT device, a simulated reality device, an augmented reality device, or any other suitable type of device. The data exchange requests **140** may be provided by the user devices **110** via one or more interfaces comprising input

displays, voice microphones, or sensors capturing gestures performed by a corresponding user **118**. [0034] The user devices **110** may be hardware configured to create, transmit, and/or receive information. The user devices **110** may be configured as a provider node or as worker nodes. The user devices **110** may be configured to receive inputs from a user, process the inputs, and generate data information or command information in response. The data information may include documents or files generated using a graphical user interface (GUI).

[0035] Referring to the user device **110a** as a non-limiting example, the command information may include input selections/commands triggered by a user using a peripheral component or one or more device peripherals **174** (i.e., a keyboard) or an integrated input system (i.e., a touchscreen displaying the GUI). The user devices **110** may be communicatively coupled to the server **102** via a network connection (i.e., the device peripherals **174**). The user devices **110** may transmit and receive data information, command information, or a combination of both to and from the server **102** via the server interfaces **172**. In one or more embodiments, the user devices **110** are configured to exchange data, commands, and signaling with the server **102**. In some embodiments, the user devices **110** are configured to receive at least one firewall configuration from the server **102** to implement a firewall (one of the one or more local applications) at one of the user devices **110**.

[0036] In one or more embodiments, the server interfaces **172** may be any suitable hardware or software (e.g., executed by hardware) to facilitate any suitable type of communication in wireless or wired connections. These connections may comprise, but not be limited to, all or a portion of network connections coupled to additional user devices **110**, the server **102**, the Internet, an Intranet, a private network, a public network, a peer-to-peer network, the public switched telephone network, a cellular network, a LAN, a MAN, a WAN, and a satellite network. The device interfaces **172** may be configured to support any suitable type of communication protocol.

[0037] In one or more embodiments, the one or more device peripherals **174** may comprise audio devices (e.g., speaker, microphones, and the like), input devices (e.g., keyboard, mouse, and the like), or any suitable electronic component that may provide a modifying or triggering input to the user devices **110**. For example, the one or more device peripherals **174** may be speakers configured to release audio signals (e.g., voice signals or commands) during media playback operations. In another example, the one or more device peripherals **174** may be microphones configured to capture audio signals. In one or more embodiments, the one or more device peripherals **174** may be configured to operate continuously, at predetermined time periods or intervals, or on-demand.

[0038] The device processor **176** may comprise one or more processors communicatively coupled to and in signal communication with the device interfaces **172**, the device peripherals **174**, and the device memory **178**. The device processor **176** is any electronic circuitry, including, but not limited to, state machines, one or more CPU chips, logic units, cores (e.g., a multi-core processor), FPGAs, ASICs, or DSPs. The device processor **176** may be a programmable logic device, a microcontroller, a microprocessor, or any suitable combination of the preceding. The one or more processors in the device processor **176** are configured to process data and may be implemented in hardware or software executed by hardware. For example, the device processor **176** may be an 8-bit, a 16-bit, a 32-bit, a 64-bit, or any other suitable architecture. The device processor **176** may comprise an ALU to perform arithmetic and logic operations, processor registers that supply operands to the ALU, and store the results of ALU operations, and a control unit that fetches software instructions such as device instructions **180** from the device memory **178** and executes the device instructions **180** by directing the coordinated operations of the ALU, registers, and other components via a device processing engine (not shown). The device processor **176** may be configured to execute various instructions.

[0039] The device memory **178** may comprise multiple operation data and one or more local applications **184** associated with the server **102**. The operation data may be data configured to enable one or more data processing operations such as those described in relation with the server **102**. The operation data may be partially or completely different from those comprised in the

memory **130**. The local applications **184** may be one or more of the services described in relation with the server **102**. In some embodiments, the local applications **184** may be partially or completely different from those comprised in the memory **130**.

[0040] In one or more embodiments, the collected data **182** may be one or more light-based information and/or code-based information collected by the user device **110a** using the device interfaces **172** and/or the device peripherals **174**. For example, the collected data **182** may be one or more of the retinal scans **142** collected using an optical sensor before being transferred to the server **102**.

Network

[0041] The network **114** facilitates communication between and amongst the various devices of the system **100**. The network **114** may be any suitable network operable to facilitate communication between the server **102** and the user devices **110** of the system **100**. The network **114** may include any interconnecting system capable of transmitting audio, video, signals, data, data packets, messages, or any combination of the preceding. The network **114** may include all or a portion of a public switched telephone network (PSTN), a public or private data network, a LAN, a MAN, a WAN, a local, regional, or global communication or computer network, such as the Internet, a wireline or wireless network, an enterprise intranet, or any other suitable communication link, including combinations thereof, operable to facilitate communication between the devices. The network **114** may be a light-based network configured to provide communications using fiber optical cables and/or other infrastructure configured to transfer light.

Decentralized Network

[0042] In one or more embodiments, the decentralized networks **106** comprises a peer-to-peer networking protocol that enables development of serverless applications. The decentralized networks **106** may include multiple electronic components or devices (i.e., nodes **112**) comprising specific node data. The nodes **112** may not be required to store or validate all data in the decentralized network **106**. Instead, validation of each node's data may be obtained via peer accountability. The decentralized networks **106** may be a blockchain network configured to perform one or more decentralized operations.

[0043] In some embodiments, the nodes **112** may include only their own data and a reference to all other data in a given decentralized network **106** in accordance with rules and policies **164** preestablished by an electronic component or device outside the given decentralized network **106** (e.g., one or more servers, such as the server **102**). Each node may comprise one or more configuration parameters **190** and/or one or more data exchange controls **192**. The configuration parameters **190** may determine how the nodes **112** interact with each other and the server **102**. The configuration parameters **190** may be updated dynamically or periodically with additional data received as updates via one or more planning components (e.g., electronic devices or components configured to provide updates to the configuration parameters **190**). The updates may be triggered by a perceived lack of knowledge level in the nodes **112**. A perceived knowledge level in the nodes **112** may be identified via node scores (not shown) received from the server **102** as feedback.

[0044] In one or more embodiments, each node (i.e., out of nodes **112**) in the given decentralized network **106** includes knowledge-specific information and information associated with peer accountability and a perceived knowledge level. Specifically, referencing the node **112a** as a non-limiting example, includes configuration parameters **190a** and data exchange controls **192a**. The data exchange controls **192a** may include information corresponding to at least one knowledge domain configured to perform interactions of one or more user devices **110**. In one or more embodiments, the node **112a** may be configured to receive one or more of initial tokens. Upon receiving the light-based tokens **148**, the node **112a** may be configured to determine whether any of entitlements **154** of the initial tokens correspond to the knowledge information included in the data exchange controls **192a**.

[0045] In other embodiments, the node **112a** includes a processor (not shown) configured to

provide updates corresponding to specific updated data exchange controls **192a**. The processor in the node **112a** may be configured to provide updated tokens directly to the server processor **126**. Further, the processor of the node **112a** may be configured to route any initial tokens that are not updated to one of the other nodes **112** in accordance with one or more configuration parameters **190** governing the given decentralized network **106**. The data exchange controls **192** at a given node **112** may be configured to generate a light-based token **148** representative of a data exchange request **140** and perform a corresponding interaction in one or more of the decentralized networks **106**. In some embodiments, the data exchange controls **192** may enable the light-based tokens **148** to perform interactions between a first decentralized network **106** and a second decentralized network **106**. Each of the decentralized networks **106** may comprise corresponding configuration information configured to interpret the data exchange requests **140** in the given light-based tokens **148**.

[0046] In the example of FIG. 1, a representation of the decentralized networks **106** includes five nodes **112a-112e**. However, additional nodes or fewer nodes may be included. In some embodiments, each of the nodes **112** includes corresponding configuration parameters **190** and corresponding data exchange controls **192**. In the decentralized networks **106** of FIG. 1, the node **112a** includes the configuration parameters **190a** and the updated data exchange controls **192a**; the node **112b** includes the configuration parameters **190b** and the updated data exchange controls **192b**; the node **112c** includes the configuration parameters **190c** and the updated data exchange controls **192c**; the node **112d** includes the configuration parameters **190d** and the updated data exchange controls **192d**; and the node **112e** includes the configuration parameters **190e** and the updated data exchange controls **192e**.

Operational Flow

[0047] In one or more embodiments, the user devices **110** are endpoints (e.g., ATM, user device) configured to request access to network resources using light-based operations. The user device **110** may comprise an optical sensor configured to collect data **182** comprising a retinal scan **142**. The retinal scan **142** may be configured to authenticate a corresponding user **118** at the user device **110** before the light-based operations are started. Once authenticated, the corresponding user **118** may request blockchain/quantum network operations at the endpoint using one or more code-based requests **136**. The endpoint may translate the code-based requests **136** to light-based requests **138** using cognitive AI. The light-based requests **138** may include information used as a basis to start a light-guided contract **166** at the server **102**. The endpoint then may provide the light-based requests **138** to the server **102**. Once the light-based requests **138** are authenticated at the server **102**, the endpoint receives an approval to establish a light-based communication link with the server **102**. The light-based operations may be performed using Li-Fi technology.

[0048] In one or more embodiments, the server **102** may be configured to create light-guided contracts **166** to access banking resources using light-based operations. The server **102** may be configured to trigger decentralized/quantum network operations using the network resources based on information obtained in one or more light-based requests **138** received from a user device **110** acting as an endpoint. The light-guided contracts **166** may be created and/or updated for each transaction performed by a corresponding user **118**. Once the light-based request **138** is authenticated at the server **102**, the server **102** transmits an approval to establish a light-based communication link directly with the endpoint. The light-based operations may be performed using Li-Fi technology.

[0049] In one or more embodiments, the server **102** is configured to verify information based on a light signature **146** of known information. Each time a user **118** performs a data exchange operation **104** using light-based operations, key light-based datapoints may be saved in one or more data repositories. The key light-based datapoints may be representative of transactional information associated with a user (e.g., user signature, retinal scan, initials). As a user **118** changes over time, the key light-based datapoints may change within predefined thresholds. A cognitive AI may be

used to predict change tolerance for the thresholds. In this regard, the server **102** may be configured to quickly verify the user information **150** when transmitted to the server **102** using light-based operations given that light-based operations are faster to confirm a match between light signatures **146** than two sets of code-based data.

Example Process to Perform Light-Based Data Exchange Operations

[0050] FIG. **2** illustrates an example flowchart of a process **200** configured to perform light-based data exchange operations, in accordance with one or more embodiments. Modifications, additions, or omissions may be made to the process **200**. The process **200** may comprise more, fewer, or other operations than those shown in FIG. **2**. For example, operations may be performed in parallel or in any suitable order. While at times discussed as the server **102**, the user devices **110**, or components of any of thereof performing operations described in operations **202-234** in the process **200**, any suitable system or components of the system **100** may perform one or more operations of the process **200**. For example, one or more operations of the process **200** may be implemented, at least in part, in the form of instructions **132** of FIG. **1**, stored on non-transitory, tangible, machine-readable media (e.g., a non-transitory computer readable medium such as server memory **130** of FIG. **1**) that when run by one or more processors (e.g., the server processor **126** of FIG. **1**) may cause the one or more processors to perform operations described in operations **202-234**.

[0051] The process **200** starts at operation **202**, where the server **102** receive a code-based data exchange request **136** (one of the data exchange requests **140**) associated with first user information **150** from a user **118**. The code-based data exchange request **136** may comprise the first user information **150** associated with a user profile **152** and data exchange information representative of a data exchange operation **104**. At operation **204**, the server **102** is configured to trigger a request for a retinal scan **142** of the user **118**. In response to receiving the code-based data exchange request **136**, the server **102** may be configured to trigger the request for the retinal scan **142** of the user **118**. In some embodiments, the retinal scan **142** is received upon performing an optical scan of the user's retina in accordance with one or more photosensitive light accurate detection operations (e.g., via an optical sensor). At operation **206**, the server **102** is configured to receive a result of the retinal scan **142** of the user **118** comprising second user information **150**.

[0052] At operation **210**, the server **102** is configured to determine the first user information **150** and the second user information **150** are indicative of a same user profile **152**. In response to receiving the result of the retinal scan **142** of the user **118**, the server **102** may be configured to determine whether the first user information and the second user information are associated with the same user profile **152**. If the server **102** determines that the first user information **150** and the second user information **150** are indicative of a same user profile **152** (e.g., YES), the process **200** proceeds to operation **212**. In response to determining that the first user information **150** and the second user information **150** are associated with the same user profile **152**, determine that the code-based data exchange request **136** is authentic. If the server **102** determines that the first user information **150** and the second user information **150** are not indicative of a same user profile **152** (e.g., NO), the process **200** proceeds to operation **232**. In response to determining that the first user information **150** and the second user information **150** are not associated with the same user profile **152**, determine that the code-based data exchange request **136** is not authentic.

[0053] The process **200** may end at operations **212-220**, where the server **102** may be configured to determine that the data exchange request **140** was authentic. At operation **212**, the server **102** is configured to determine that the code-based data exchange request **136** is authentic. At operation **214**, the server **102** is configured to convert the code-based data exchange request **136** to a light-based data exchange request **138**. In conjunction with determining that the code-based data exchange request **136** is authentic, the server **102** may be configured to execute a cognitive AI model **160** configured to convert the code-based data exchange request **136** to the light-based data exchange request **138**. At operation **216**, the server **102** is configured to generate a light-guided contract **166** based on the light-based data exchange request **138**. In some embodiments, the server

102 may be configured to generate the light-guided contract **166** based on the light-based data exchange request **138**. The light-guided contract **166** may indicate that the user **118** associated with the user profile **152** is entitled to trigger the data exchange operation **104**. At operation **218**, the server **102** is configured to generate a light-based token **148** to initiate the data exchange operation **104** with the one or more decentralized networks **106**. In some embodiments, the server **102** may be configured to generate the light-based token **148** to initiate the data exchange operation **104** with the decentralized networks **106**. The process **200** may end at operation **220**, where the server **102** is configured to transmit the light-based token **148** to the decentralized networks **106**.

[0054] In one or more embodiments, the server **102** is configured to transmit the light-based token **148** to the decentralized networks **106**. In conjunction with transmitting the light-based token **148** to the decentralized networks **106**, the server **102** is configured to store a light signature **146** representative of the light-based token **148** in a light data repository (e.g., one of the databases **122**). In conjunction with transmitting additional light-based tokens **148** related to the same user **118** to the decentralized networks **106**, the server **102** may be configured to generate additional light signatures **146** representative of the additional light-based tokens **148**. The server **102** may be configured to compare the additional light signatures **146** to previous light signatures **146** associated with the same user **118** and/or user profile **152**. In response to determining that the light signatures **146** at least partially match to one another (e.g., a previous light signature **146** at least partially matched a new light signature **146**), the server **102** may be configured to determine whether the additional light-based token **148** are already stored in the light data repository. In conjunction with transmitting the light-based tokens **148** to the decentralized networks **106**, the server **102** may be configured to associate the light-based token **148** with the data exchange operation **104** in a light-based ledger **168**.

[0055] The process **200** may end at operation **232** and operation **234**, where the server **102** may be configured to determine that the data exchange request **140** was not authentic. At operation **232**, the server **102** is configured to generate a report **170** indicating that the code-based data exchange request **136** is not authentic. At operation **234**, the server **102** is configured to transmit the report **170** to a trusted device (a corresponding user device **110**) associated with the user profile **152**.

Scope of the Disclosure

[0056] While several embodiments have been provided in the present disclosure, it should be understood that the disclosed systems and methods might be embodied in many other specific forms without departing from the spirit or scope of the present disclosure. The present examples are to be considered as illustrative and not restrictive, and the intention is not to be limited to the details given herein. For example, the various elements or components may be combined or integrated with another system or certain features may be omitted, or not implemented.

[0057] In addition, techniques, systems, subsystems, and methods described and illustrated in the various embodiments as discrete or separate may be combined or integrated with other systems, modules, techniques, or methods without departing from the scope of the present disclosure. Other items shown or discussed as coupled or directly coupled or communicating with each other may be indirectly coupled or communicating through some interface, device, or intermediate component whether electrically, mechanically, or otherwise. Other examples of changes, substitutions, and alterations are ascertainable by one skilled in the art and could be made without departing from the spirit and scope disclosed herein.

[0058] To aid the Patent Office, and any readers of any patent issued on this application in interpreting the claims appended hereto, applicants note that they do not intend any of the appended claims to invoke 35 U.S.C. § 112(f) as it exists on the date of filing hereof unless the words “means for” or “step for” are explicitly used in the particular claim.

Claims

1. A system, comprising: a memory operable to store: one or more user profiles, each user profile comprising information about at least one user entitled to trigger one or more data exchange operations in a decentralized network; and at least one processor communicatively coupled to the memory and configured to: receive a first code-based data exchange request from a first user, the first code-based data exchange request comprising first user information associated with a first user profile and first data exchange information representative of a first data exchange operation; in response to receiving the first code-based data exchange request, trigger a first request for a first retinal scan of the first user; receive a first result of the first retinal scan of the first user, the first result comprising second user information; in response to receiving the first result of the first retinal scan of the first user, determine whether the first user information and the second user information are associated with the first user profile; in response to determining that the first user information and the second user information are associated with the first user profile, determine that the first code-based data exchange request is authentic; convert the first code-based data exchange request to a first light-based data exchange request; generate a first light-guided contract based on the first light-based data exchange request, the first light-guided contract indicating that the first user associated with the first user profile is entitled to trigger the first data exchange operation; generate a first light-based token to initiate the first data exchange operation with the decentralized network; and transmit the first light-based token to the decentralized network.
2. The system of claim 1, wherein the first retinal scan is performed in accordance with one or more photosensitive light accurate detection operations.
3. The system of claim 1, wherein the at least one processor is further configured to: in conjunction with determining that the first code-based data exchange request is authentic, execute a cognitive artificial intelligence (AI) model configured to convert the first code-based data exchange request to the first light-based data exchange request.
4. The system of claim 1, wherein the at least one processor is further configured to: receive a second code-based data exchange request from a second user, the second code-based data exchange request comprising third user information associated with a second user profile and second data exchange information representative of a second data exchange operation; in response to receiving the second code-based data exchange request, trigger a second request for a second retinal scan of the second user; receive a second result of the second retinal scan of the second user, the second result comprising fourth user information; in response to receiving the second result of the second retinal scan of the second user, determine whether the third user information and the fourth user information are associated with the second user profile; in response to determining that the third user information and the fourth user information are associated with the second user profile, determine that the second code-based data exchange request is authentic; convert the second code-based data exchange request to a second light-based data exchange request; generate a second light-guided contract based on the second light-based data exchange request, the second light-guided contract indicating that the second user associated with the second user profile is entitled to trigger the second data exchange operation; generate a second light-based token to initiate the second data exchange operation with the decentralized network; and transmit the second light-based token to the decentralized network.
5. The system of claim 4, wherein the at least one processor is further configured to: in conjunction with transmitting the first light-based token to the decentralized network, store a first signature representative of the first light-based token in a light data repository; and in conjunction with transmitting the second light-based token to the decentralized network, store a second signature representative of the second light-based token in the light data repository.
6. The system of claim 4, wherein the at least one processor is further configured to: in conjunction with transmitting the first light-based token to the decentralized network, generate a first signature representative of the first light-based token; store the first signature of the first light-based token in

a light data repository; in conjunction with transmitting the second light-based token to the decentralized network, generate a second signature representative of the second light-based token; compare the first signature to the second signature; and in response to determining that the first signature at least partially matches the second signature, determine that the second signature representative of the second light-based token is already stored in the light data repository.

7. The system of claim 1, wherein the at least one processor is further configured to: receive a second code-based data exchange request from a second user, the second code-based data exchange request comprising third user information associated with a second user profile and second data exchange information representative of a second data exchange operation; in response to receiving the second code-based data exchange request, trigger a second request for a second retinal scan of the second user; receive a second result of the second retinal scan of the second user, the second result comprising fourth user information; in response to receiving the second result of the second retinal scan of the second user, determine whether the third user information and the fourth user information are associated with the second user profile; in response to determining that the third user information and the fourth user information are not associated with the second user profile, determine that the second code-based data exchange request is not authentic; generate a report comprising that the second code-based data exchange request is not authentic; and transmit the report to a trusted device associated with the second user profile.

8. The system of claim 1, wherein the at least one processor is further configured to: in conjunction with transmitting the first light-based token to the decentralized network, associate the first light-based token with the first data exchange operation in a light-based ledger.

9. A method, comprising: receiving a first code-based data exchange request from a first user, the first code-based data exchange request comprising first user information associated with a first user profile and first data exchange information representative of a first data exchange operation; in response to receiving the first code-based data exchange request, triggering a first request for a first retinal scan of the first user; receiving a first result of the first retinal scan of the first user, the first result comprising second user information; in response to receiving the first result of the first retinal scan of the first user, determining whether the first user information and the second user information are associated with the first user profile; in response to determining that the first user information and the second user information are associated with the first user profile, determining that the first code-based data exchange request is authentic; converting the first code-based data exchange request to a first light-based data exchange request; generating a first light-guided contract based on the first light-based data exchange request, the first light-guided contract indicating that the first user associated with the first user profile is entitled to trigger the first data exchange operation; generating a first light-based token to initiate the first data exchange operation with a decentralized network; and transmitting the first light-based token to the decentralized network.

10. The method of claim 9, wherein the first retinal scan is performed in accordance with one or more photosensitive light accurate detection operations.

11. The method of claim 9, further comprising: in conjunction with determining that the first code-based data exchange request is authentic, executing a cognitive artificial intelligence (AI) model configured to convert the first code-based data exchange request to the first light-based data exchange request.

12. The method of claim 9, further comprising: receiving a second code-based data exchange request from a second user, the second code-based data exchange request comprising third user information associated with a second user profile and second data exchange information representative of a second data exchange operation; in response to receiving the second code-based data exchange request, triggering a second request for a second retinal scan of the second user; receiving a second result of the second retinal scan of the second user, the second result comprising fourth user information; in response to receiving the second result of the second retinal scan of the

second user, determining whether the third user information and the fourth user information are associated with the second user profile; in response to determining that the third user information and the fourth user information are associated with the second user profile, determining that the second code-based data exchange request is authentic; converting the second code-based data exchange request to a second light-based data exchange request; generating a second light-guided contract based on the second light-based data exchange request, the second light-guided contract indicating that the second user associated with the second user profile is entitled to trigger the second data exchange operation; generating a second light-based token to initiate the second data exchange operation with the decentralized network; and transmitting the second light-based token to the decentralized network.

13. The method of claim 12, further comprising: in conjunction with transmitting the first light-based token to the decentralized network, storing a first signature representative of the first light-based token in a light data repository; and in conjunction with transmitting the second light-based token to the decentralized network, storing a second signature representative of the second light-based token in the light data repository.

14. The method of claim 12, further comprising: in conjunction with transmitting the first light-based token to the decentralized network, generating a first signature representative of the first light-based token; storing the first signature of the first light-based token in a light data repository; in conjunction with transmitting the second light-based token to the decentralized network, generating a second signature representative of the second light-based token; comparing the first signature to the second signature; and in response to determining that the first signature at least partially matches the second signature, determining that the second signature representative of the second light-based token is already stored in the light data repository.

15. The method of claim 9, further comprising: receiving a second code-based data exchange request from a second user, the second code-based data exchange request comprising third user information associated with a second user profile and second data exchange information representative of a second data exchange operation; in response to receiving the second code-based data exchange request, triggering a second request for a second retinal scan of the second user; receiving a second result of the second retinal scan of the second user, the second result comprising fourth user information; in response to receiving the second result of the second retinal scan of the second user, determining whether the third user information and the fourth user information are associated with the second user profile; in response to determining that the third user information and the fourth user information are not associated with the second user profile, determining that the second code-based data exchange request is not authentic; generating a report comprising that the second code-based data exchange request is not authentic; and transmitting the report to a trusted device associated with the second user profile.

16. The method of claim 9, further comprising: in conjunction with transmitting the first light-based token to the decentralized network, associating the first light-based token with the first data exchange operation in a light-based ledger.

17. A non-transitory computer readable medium storing instructions that when executed by a processor cause the processor to: receive a first code-based data exchange request from a first user, the first code-based data exchange request comprising first user information associated with a first user profile and first data exchange information representative of a first data exchange operation; in response to receiving the first code-based data exchange request, trigger a first request for a first retinal scan of the first user; receive a first result of the first retinal scan of the first user, the first result comprising second user information; in response to receiving the first result of the first retinal scan of the first user, determine whether the first user information and the second user information are associated with the first user profile; in response to determining that the first user information and the second user information are associated with the first user profile, determine that the first code-based data exchange request is authentic; convert the first code-based data

exchange request to a first light-based data exchange request; generate a first light-guided contract based on the first light-based data exchange request, the first light-guided contract indicating that the first user associated with the first user profile is entitled to trigger the first data exchange operation; generate a first light-based token to initiate the first data exchange operation with a decentralized network; and transmit the first light-based token to the decentralized network.

18. The non-transitory computer readable medium of claim 17, wherein the first retinal scan is performed in accordance with one or more photosensitive light accurate detection operations.

19. The non-transitory computer readable medium of claim 17, wherein the instructions further cause the processor to: in conjunction with determining that the first code-based data exchange request is authentic, execute a cognitive artificial intelligence (AI) model configured to convert the first code-based data exchange request to the first light-based data exchange request.

20. The non-transitory computer readable medium of claim 18, wherein the instructions further cause the processor to: receive a second code-based data exchange request from a second user, the second code-based data exchange request comprising third user information associated with a second user profile and second data exchange information representative of a second data exchange operation; in response to receiving the second code-based data exchange request, trigger a second request for a second retinal scan of the second user; receive a second result of the second retinal scan of the second user, the second result comprising fourth user information; in response to receiving the second result of the second retinal scan of the second user, determine whether the third user information and the fourth user information are associated with the second user profile; in response to determining that the third user information and the fourth user information are associated with the second user profile, determine that the second code-based data exchange request is authentic; convert the second code-based data exchange request to a second light-based data exchange request; generate a second light-guided contract based on the second light-based data exchange request, the second light-guided contract indicating that the second user associated with the second user profile is entitled to trigger the second data exchange operation; generate a second light-based token to initiate the second data exchange operation with the decentralized network; and transmit the second light-based token to the decentralized network.
