

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396592
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Daugherty; Daniel et al.

Food tray chafing stand with hinging legs

Abstract

Various implementations include a food tray stand. The stand includes a body and two or more legs. The body has a first surface and a second surface opposite and spaced apart from the first surface. The first surface defines a tray opening extending to the second surface. The two or more legs are hingedly coupled to the body by a living hinge. Each of the two or more legs is hingedly movable between an extended position and a retracted position. Each of the two or more legs extends away from the second surface in the extended position and is at least partially disposable within the tray opening in the retracted position.

Inventors: Daugherty; Daniel (Knoxville, TN), Roesmann; Jeff (Knoxville, TN), Theusch; Glen (Knoxville, TN), Wiegand; Jason (Knoxville, TN), Wisler; Albion (Knoxville, TN)

Applicant: Brown Bag LLC (Knoxville, TN)

Family ID: 1000008780768

Assignee: UPCYCLE STANDS, LLC (Knoxville, TN)

Appl. No.: 18/588658

Filed: February 27, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240306845 A1	Sep. 19, 2024

Related U.S. Application Data

us-provisional-application US 63490262 20230315

Publication Classification

Int. Cl.: A47J36/24 (20060101); A47J36/34 (20060101); A47J47/16 (20060101)

U.S. Cl.:

CPC A47J36/34 (20130101); A47J47/16 (20130101); A47J36/24 (20130101)

Field of Classification Search

CPC: A47J (36/34); A47J (36/24); A47J (36/2405); A47J (36/20); A47J (36/22); A47J (36/26); A47J (47/16); A47J (37/07); A47J (37/0694); A47J (2037/0777); A47J (39/02); A47J (39/025)

USPC: 248/150; 126/33; 126/50; 99/482; 99/483

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2024259	12/1934	Troeber	126/33	A47J 36/24
2101965	12/1936	Trees	40/611.05	G09F 7/10
2388192	12/1944	Stechbart	248/168	F16M 13/005
2565187	12/1950	Udell	211/195	A63F 1/06
2903311	12/1958	Earhart	211/74	A47G 23/06
3361126	12/1967	Bloomfield	N/A	N/A
D213717	12/1968	Rickmeier	N/A	N/A
D213899	12/1968	Rickmeier	N/A	N/A
3841298	12/1973	Sellors	N/A	N/A
4389946	12/1982	Hwang	108/115	A47C 9/10
4557200	12/1984	Geschwender	248/439	A47B 23/001
4779605	12/1987	Smith	N/A	N/A
4884551	12/1988	Hait	N/A	N/A
D305972	12/1989	Pearce	N/A	N/A
4920873	12/1989	Stevens	N/A	N/A
5119799	12/1991	Cowan	N/A	N/A
5119800	12/1991	Roberts	N/A	N/A
5203257	12/1992	Goad	126/369	H05B 3/82
5287800	12/1993	Orednick	N/A	N/A
5467697	12/1994	Hunziker	99/449	A47J 36/24
5517903	12/1995	Kaufman	N/A	N/A
5819640	12/1997	Cuomo	N/A	N/A
5921513	12/1998	Skvorecz	248/153	B65D 7/20
5992406	12/1998	Lelle	N/A	N/A
6234068	12/2000	Sherman	99/449	A47J 36/2477
6779466	12/2003	Shabram, Jr.	108/115	A47B 3/10
6892721	12/2004	Chen	N/A	N/A
6951213	12/2004	Coleman	126/41R	A47J 37/0704
6955327	12/2004	Skvorecz	248/153	A47J 36/34

7175033	12/2006	Riopel	N/A	N/A
7337728	12/2007	Shabram, Jr.	108/115	A47B 3/10
7765939	12/2009	Chen	108/127	A47B 3/08
D626377	12/2009	Contreras	N/A	N/A
7828160	12/2009	Lin	N/A	N/A
7934494	12/2010	Schneider	N/A	N/A
8172191	12/2011	Zimbalatti	248/688	F16M 11/10
9138098	12/2014	Sun	N/A	N/A
9414712	12/2015	Skvorecz	N/A	N/A
9517858	12/2015	Skvorecz	N/A	N/A
9539677	12/2016	Skvorecz	N/A	N/A
9861228	12/2017	Fariello	N/A	A47J 36/2405
9943186	12/2017	Leonard	N/A	N/A
10307015	12/2018	Shane	N/A	N/A
10478014	12/2018	Revely	N/A	N/A
11181278	12/2020	Cuffaro	N/A	F24C 3/085
D951020	12/2021	Zemel	N/A	N/A
11974695	12/2023	Cuffaro	N/A	A47J 37/0763
11986126	12/2023	Klein	N/A	A47J 36/24
2002/0020304	12/2001	Reynolds	99/450	A47J 36/2405
2003/0070591	12/2002	Shabram, Jr.	108/35	A47B 3/0916
2003/0192525	12/2002	Ruiseco	N/A	N/A
2004/0020373	12/2003	Chen	N/A	N/A
2005/0167381	12/2004	Fariello	211/195	A47J 36/24
2009/0258127	12/2008	Holtz	N/A	N/A
2011/0017079	12/2010	Wall	N/A	N/A
2014/0069284	12/2013	Zhou	99/483	A47J 39/02
2015/0040777	12/2014	Leonard	N/A	N/A
2015/0250357	12/2014	Zhitnitsky	248/176.2	F16M 11/38
2021/0059468	12/2020	Amirault	N/A	A47J 36/2405
2021/0131668	12/2020	Sherrard	N/A	F24C 3/008

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
700406	12/1963	CA	N/A
2172308	12/1996	CA	N/A
2254963	12/1996	CA	N/A
2459700	12/2004	CA	N/A
2706950	12/2010	CA	N/A
101347535	12/2013	KR	N/A
2001027536	12/2000	WO	N/A
2007021341	12/2006	WO	N/A
2020223823	12/2019	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion, related to PCT/US2024/017410, issued May 24, 2024 (10 pages). cited by applicant

Background/Summary

BACKGROUND

(1) Current chafing stands include metal wire stands with wire legs. The stand defines an opening to support a tray therein. While the existing metal wire chafing stands are made from a material which is intended to be reusable, the stands often end up in the trash after one or a few uses. Furthermore, the design of current stands make them difficult to produce for the simplicity of their designs. Current chafing stands are also bulky and have no way storing them in an efficient space.

SUMMARY

(2) Various implementations include a food tray stand. The stand includes a body and two or more legs. The body has a first surface and a second surface opposite and spaced apart from the first surface. The first surface defines a tray opening extending to the second surface. The two or more legs are hingedly coupled to the body by a living hinge. Each of the two or more legs is hingedly movable between an extended position and a retracted position. Each of the two or more legs extends away from the second surface in the extended position and is at least partially disposable within the tray opening in the retracted position.

(3) In some implementations, the two or more legs includes four legs.

(4) In some implementations, each of the two or more legs is fully disposable within the tray opening in the retracted position.

(5) In some implementations, the second surface of the body defines a concavity. In some implementations, the first surface of the body of a first stand is at least partially disposable within the concavity of a second stand.

(6) In some implementations, the stand further includes a base separately formed from the body and the two or more legs. In some implementations, one of the base or the two or more legs defines one or more coupling openings and an other of the two or more legs or the base includes one or more coupling protrusions. Each of the one or more coupling protrusions is engageable with a different one of the one or more coupling openings to couple the base to the two or more legs. In some implementations, the base defines the one or more coupling openings and the two or more legs includes the one or more coupling protrusions. In some implementations, the one or more coupling openings are keyhole openings and the one or more protrusions includes a stem and a distal head. In some implementations, the distal head and the stem each have a largest width as measured perpendicular to a plane that includes a path of movement of the respective leg when the leg moves between the extended position and the retracted position. In some implementations, the largest width of the distal head is greater than the largest width of the stem.

(7) In some implementations, when the two or more legs are in the retracted position, the base is at least partially disposable within the tray opening. In some implementations, the base is fully disposable within the tray opening.

(8) In some implementations, the base defines one or more nesting openings. In some implementations, when the two or more legs are in the retracted position and the base is at least partially disposed within the tray opening, at least one of the two or more legs is at least partially disposable within the one or more nesting openings. In some implementations, the one or more nesting opening includes two or more nesting openings. In some implementations, each of the two or more legs is at least partially disposable within a different one of the two or more nesting openings.

(9) In some implementations, the base defines at least one canned cooking fuel opening sized to receive a canned cooking fuel. In some implementations, the at least one canned cooking fuel

opening has a diameter, wherein the diameter is in the range of 2.0 inches to 6.0 inches.

(10) In some implementations, the body and the two or more legs include a polymer. In some implementations, the polymer includes polypropylene. In some implementations, the polymer includes high impact polystyrene.

(11) In some implementations, the body and the two or more legs are integrally formed.

(12) In some implementations, the body defines one or more utensil holders. In some implementations, the one or more utensil holders are utensil openings defined by the first surface of the body and extending to the second surface of the body.

(13) In some implementations, the tray opening includes a first portion and a second portion. The first portion of the tray opening is wider in at least one dimension than the second portion of the tray opening such that a ledge is formed at the intersection of the first portion and the second portion of the tray opening.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) Example features and implementations of the present disclosure are disclosed in the accompanying drawings. However, the present disclosure is not limited to the precise arrangements and instrumentalities shown. Similar elements in different implementations are designated using the same reference numerals.

(2) FIG. 1 shows a top perspective view of a food tray stand with a serving tray and with the legs in the extended position, according to one implementation.

(3) FIG. 2 shows a bottom perspective view of the food tray stand of FIG. 1 with a serving tray and with the legs in the extended position.

(4) FIG. 3 shows a top perspective view of the food tray stand of FIG. 1 without a serving tray and with the legs in the extended position.

(5) FIG. 4 shows a top perspective view of the food tray stand of FIG. 1 with the legs in the retracted position and the base disposed within the tray opening.

(6) FIG. 5 shows a bottom perspective view of the food tray stand of FIG. 1 with the legs in the retracted position and the base disposed within the tray opening.

(7) FIG. 6 shows a top perspective view of the food tray stand of FIG. 1 with the legs in the retracted position and without the base.

(8) FIG. 7 shows a top perspective view of the base of the stand of FIG. 1.

DETAILED DESCRIPTION

(9) The devices, systems, and methods disclosed herein provide for a food tray stand. The stand can include a body with a tray opening for supporting a tray. The stand can include a plurality of legs that are hingedly coupled to the body by a living hinge. A base can be removably couplable to the distal ends of the legs to hold the legs in an extended position. The base can include one or more canned cooking fuel openings for supporting canned cooking fuel containers below a tray disposed within the tray opening.

(10) When the legs are rotated about the living hinge to a retracted position, the legs are disposed within the tray opening. The base can also be sized to be disposed within the tray opening and can include nesting openings sized such that each of the legs is disposable within a different one of the nesting openings when the base is disposed within the tray opening.

(11) The food tray stands disclosed herein can be made of an easily recyclable material such that the stand can be disposable after use.

(12) Various implementations include a food tray stand. The stand includes a body and two or more legs. The body has a first surface and a second surface opposite and spaced apart from the first surface. The first surface defines a tray opening extending to the second surface. The two or more

legs are hingedly coupled to the body by a living hinge. Each of the two or more legs is hingedly movable between an extended position and a retracted position. Each of the two or more legs extends away from the second surface in the extended position and is at least partially disposable within the tray opening in the retracted position.

(13) FIGS. 1-7 show a food tray stand **100** including many aspects according to various implementations disclosed herein. The stand **100** includes a body **110**, four legs **150**, and a base **170**.

(14) The body **110** has a first surface **112** and a second surface **114** opposite and spaced apart from the first surface **112**. The body **110** shown in FIGS. 1-6 is rectangular when viewed perpendicularly to the first surface **112**. However, in some implementations, the body is circular, ovate, triangular, square, or any other closed shape.

(15) The first surface **112** defines a tray opening **120** extending to the second surface **114**. The tray opening **120** includes a first portion **122** adjacent the first surface **112** of the base **110** and a second portion **132** intersecting the first portion **122** and adjacent the second surface **114** of the body **110**. The first portion **122** of the tray opening **120** has a first width **124** and a first length **126** as measured perpendicular to each other and parallel to a plane defined by the first surface **112** of the body **110**. The second portion **132** of the tray opening **120** has a second width **134** and a second length **136** as measured perpendicular to each other and parallel to a plane defined by the first surface **112** of the body **110**.

(16) The first width **124** is greater than the second width **134** and the first length **126** is greater than the second length **136**. The second portion **132** of the tray opening **120** is centrally located relative to the first portion **122** of the tray opening **120** when viewed perpendicular to the first surface **112** of the body **110**. The difference between the first width **124** and the second width **134**, and the first length **126** and the second length **136**, forms a parametrical ledge **140** along the intersection of the first portion **122** and the second portion **132** of the tray opening **120**. The first portion **122** of the tray opening **120** is sized to receive the lip or flange of a serving tray **190** therein. However, the second width **134** and the second length **136** of the second portion **132** of the tray opening **120** are less than the width and length of the lip or flange of the serving tray **190** such that the lip or flange of the serving tray **190** cannot pass through the second portion **132** of the tray opening **120**. Thus, the lip or flange of the serving tray **190** is able to rest within the first portion **122** of the tray opening **120** on the parametrical ledge **140**.

(17) Although the shape of the tray opening **120** shown in FIGS. 1-6 is rectangular when viewed perpendicularly to the first surface **112**, in some implementations, the tray opening is circular, ovate, triangular, square, or any other closed shape.

(18) Although the first width **124** is larger than the second width **134**, and the first length **126** is larger than the second length **136**, in the body **110** shown in FIGS. 1-6, in some implementations, only the first width is larger than the second width, or only the first length is larger than the second length, such that a ledge is only formed along only one or more portions of the intersection of the first portion and the second portion. In some implementations in which the body is circular, the diameter of the first portion is larger than the second diameter. In some implementations, one or more dimensions of the first portion are larger than the corresponding one or more dimensions of the second portion such that a ledge is formed along at least a portion of the intersection of the first portion and the second portion of the tray opening.

(19) In some implementations, the tray opening is sized to receive two or more serving trays within the single tray opening. In some implementations, the body defines two or more separate tray openings each for receiving one or more serving trays.

(20) The body **110** shown in FIGS. 1-6 further includes four utensil holders **118** in the form of utensil holder openings. Each of the utensil holder openings **118** is defined by the first surface **112** of the body **110** and extend to the second surface **114** of the body **110**. Each of the utensil holder openings **118** overlaps an edge **116** of the body **110** such that the edge **116** of the body **110** partially

defines the utensil holder opening **118**. This forms a utensil holder opening **118** that is open to the edge **116** of the body **110** such that a utensil can be inserted through the open portion of the utensil holder opening **118** along the edge **116** of the body **110**. Although the utensil holders **118** of the body **110** shown in FIGS. **1-6** are utensil holder openings, in some implementations, one or more of the utensil holders are protrusions such as hooks or knobs. In some implementations, one or more utensil holders are slots defined by a surface of the body but not extending fully through the body. In some implementations, the body includes any number of one or more utensil holders.

(21) Each of the four legs **150** shown in FIGS. **1-6** has a proximal end **152** and a distal end **154** that is distal to the proximal end **152**. The proximal end **152** of each of the legs **150** is integrally or monolithically formed with the body **110** of the stand **100** to form a living hinge **156**. Each of the hingedly coupled legs **150** is movable between an extended position and a retracted position. In the extended position, each of the four legs **150** extends away from the second surface **114** of the body **110**. In the retracted position, each of the four legs **150** is fully disposable within the tray opening **120**.

(22) The proximal ends **152** of the four legs **150** shown in FIGS. **1-6** are coupled to portions of the body **110** along the tray opening **120**, but in some implementations, the legs are hingedly coupled to any other portion of the body. Although the legs **150** shown in FIGS. **1-6** are hingedly coupled to the body **110** by living hinges **156**, in some implementations, one or more of the legs is hingedly coupled to the body by a traditional hinge or any other hinging mechanism that allows the leg to rotate relative to the body. In some implementations, one or more of the legs are separately formed from the body.

(23) In some implementations, one or more of the legs is only partially disposable within the tray opening in the retracted position.

(24) In some implementations, the stand includes two legs that are broad enough to be stable in use. In some implementations, the stand includes any number of one or more legs.

(25) The distal end **154** of each of the legs **150** includes a coupling protrusion **160** extending therefrom. The coupling protrusion **160** includes a stem **162** that is coupled to the distal end **154** of the leg **150** and a distal head **164** coupled to the stem **162**. The distal head **164** and the stem **162** each have a largest width as measured perpendicular to a plane that includes the path of movement of the respective leg **150** when the leg **150** moves between the extended position and the retracted position. The largest width of the distal head **164** is greater than the largest width of the stem **162**.

(26) The base **170** shown in FIGS. **1-5** and **7** is separately formed from the body **110** and the legs **150**. The base **170** is engageable with the legs **150** to stabilize the legs **150** and body **110** and to prevent over extension of the legs **150** beyond the extended position. However, in some implementations, the stand does not include a base.

(27) The base **170** defines four coupling openings **180** that are shaped as keyhole openings. Each of the keyhole shaped coupling openings **180** includes a wide portion **182** and a narrow portion **184** that is narrower than the wide portion **182**. The wide portion **182** is sized such that the distal head **164** of the coupling protrusion **160** can be fully inserted through the wide portion **182** of the coupling opening **180**. The narrow portion **184** of the coupling opening **180** is sized such that the stem **162** of the coupling protrusion **160** can be inserted into the narrow portion **184** but the distal head **164** is too wide to be inserted through the narrow portion **184**. The keyhole shaped coupling openings **180** are each located such that a distal head **164** of a coupling protrusion **160** of a separate one of the four legs **150** is insertable into and through the wide portion **182** of the coupling opening **180**. Each of the coupling openings **180** are oriented such that further movement of the respectively engaged leg **150** toward the extended position causes the stem **162** of the coupling protrusion **160** to be inserted into the narrow portion **184** of the coupling opening **180**. Because the distal heads **164** of the coupling protrusions **160** cannot pass through the narrow portions **184** of the coupling openings **180**, each of the four legs **150** is engaged with the base **170** to removably couple the body **110** and legs **150** to the base **170**.

(28) Although the base **170** shown in FIGS. **1-5** and **7** defines the coupling openings **180** and the legs **150** include the coupling protrusions **160**, in some implementations, the legs define the coupling openings, and the base includes the coupling protrusions. In some implementations, each of the base and the legs each define one or more coupling openings, and the base and the legs each include one or more coupling protrusions. In some implementations, the coupling protrusions and the coupling openings are any shape that are engageable with each other to couple the legs to the base. In some implementations, the legs and/or the base include any fastener known in the art, such as nails, tacks, screws, bolts, staples, rivets, adhesive, tape, hook-and-loop, ties, hooks, or any other fastener capable of coupling the base to the legs. Although the distal ends **154** of the legs **150** include the coupling protrusions **160** in FIGS. **1-6**, in some implementations, any portion of the legs include the coupling protrusions and/or the coupling openings.

(29) The base **170** further defines three canned cooking fuel opening **172** sized to each receive a canned cooking fuel container. The canned cooking fuel openings **172** are located on the base **170** such that canned cooking fuel containers disposed within the canned cooking fuel openings **172** evenly distribute enough heat to a serving tray **190** disposed within the tray opening **120** to keep food within the serving tray **190** at a safe temperature for human consumption.

(30) Each of the canned cooking fuel openings **172** shown in FIGS. **1-5** and **7** has a diameter in the range of 3.25 inches to 3.75 inches. However, in some implementations, each of the canned cooking fuel openings has a diameter in the range of 3.0 inches to 4.5 inches. In some implementations, each of the canned cooking fuel openings has a diameter in the range of 2.0 inches to 6.0 inches, such as 2.0 inches, 2.125 inches, 2.25 inches, 2.375 inches, 2.5 inches, 2.625 inches, 2.75 inches, 2.875 inches, 3.0 inches, 3.125 inches, 3.25 inches, 3.375 inches, 3.5 inches, 3.625 inches, 3.75 inches, 3.875 inches, 4.0 inches, 4.125 inches, 4.25 inches, 4.375 inches, 4.5 inches, 4.625 inches, 4.75 inches, 4.875 inches, 5.0 inches, 5.125 inches, 5.25 inches, 5.375 inches, 5.5 inches, 5.625 inches, 5.75 inches, 5.875 inches, or 6.0 inches. Although the base **170** of the stand **100** shown in FIGS. **1-5** and **7** includes three canned cooking fuel openings **172**, in some implementations, the base of the stand includes any number of one or more canned cooking fuel openings.

(31) Similar to the legs **150**, the base **170** shown in FIGS. **1-5** and **7** is also disposable within the tray opening **120** during storage. The base **170** shown in FIGS. **1-5** and **7** defines two nesting openings **174** each sized to receive two legs **150** in the retracted position. The base **170** is sized such that, when the legs **150** are in the retracted position, the base **170** is fully disposable within the tray opening **120**. When the legs **150** are in the retracted position and the base **170** is disposed within the tray opening **120**, the legs **150** are fully disposable within the nesting openings **174** such that the four legs **150** and the base **170** are all fully disposed within the tray opening **120**. Thus, all four legs **150**, the base **170**, and the body **110** can be configured to have the same overall footprint as the body **110** alone.

(32) Although the base **170** shown in FIGS. **1-5** and **7** is fully disposable within the tray opening **120** of the body **110**, in some implementations, the base is only partially disposable within the tray opening. Although the legs **150** shown in FIGS. **1-5** are fully disposable within the nesting openings **174** of the base **170**, in some implementations, the legs are only partially disposable within the nesting openings. Although the base **170** shown in FIGS. **1-5** and **7** include two nesting openings **174** each configured to receive two legs **150**, in some implementations, the base includes any number of one or more nesting openings each configured to receive any number of one or more legs.

(33) The body **110**, the four legs **150**, and the base **170** each comprise polypropylene. However, in some implementations, the body **110**, the four legs **150**, and the base **170** each comprise high impact polystyrene. Polypropylene and high impact polystyrene are easily recyclable materials that allow the user to recycle the stand **100** after using it. A stand **100** made of polypropylene or high impact polystyrene is also cheaper than a stand made of metal, both because of material costs and

from a manufacturing standpoint.

(34) Although the body **110**, the four legs **150**, and the base **170** shown in FIGS. **1-7** each comprise polypropylene or high impact polystyrene, in some implementations, the body, the four legs, and/or the base comprise any polymer.

(35) Two or more of the stands **100** disclosed herein can be stackable with each other for space saving and stability during storage. The second surface **114** of the body **110** defines a concavity **115** extending around and adjacent the tray opening **120** and adjacent the edge **116** of the body **110**. The first surface **112** of the body **110** defines a fillet or chamfer around the outer perimeter along the edges **116** of the body **110** and a fillet or chamfer around the inner perimeter along the tray opening **120**. The edges **116** of the body **110** can also be slightly tapered from widest adjacent the second surface **114** to narrowest adjacent the first surface **112**. These features allow the first surface **112** of the body **110** of a first stand **100** to be at least partially disposable within the concavity **115** of a second stand **100**.

(36) However, it is understood that, in some implementations, the first surface can include the concavity, the second surface can include the fillets and chamfers, and/or the edges of the body can be tapered from widest adjacent the first surface to narrowest adjacent the second surface. In some implementations, the body can include one or more of the concavity, the fillets and chamfers, and/or the tapered edges and still allow a first stand to be at least partially disposable within a second stand. In some implementations, the body does not include any of the concavity, the fillets and chamfers, and/or the tapered edges. In some implementations, the stands are not nestable.

(37) A number of example implementations are provided herein. However, it is understood that various modifications can be made without departing from the spirit and scope of the disclosure herein. As used in the specification, and in the appended claims, the singular forms “a,” “an,” “the” include plural referents unless the context clearly dictates otherwise. The term “comprising” and variations thereof as used herein is used synonymously with the term “including” and variations thereof and are open, non-limiting terms. Although the terms “comprising” and “including” have been used herein to describe various implementations, the terms “consisting essentially of” and “consisting of” can be used in place of “comprising” and “including” to provide for more specific implementations and are also disclosed.

(38) Disclosed are materials, systems, devices, methods, compositions, and components that can be used for, can be used in conjunction with, can be used in preparation for, or are products of the disclosed methods, systems, and devices. These and other components are disclosed herein, and it is understood that when combinations, subsets, interactions, groups, etc. of these components are disclosed that while specific reference of each various individual and collective combinations and permutations of these components may not be explicitly disclosed, each is specifically contemplated and described herein. For example, if a device is disclosed and discussed each and every combination and permutation of the device are disclosed herein, and the modifications that are possible are specifically contemplated unless specifically indicated to the contrary. Likewise, any subset or combination of these is also specifically contemplated and disclosed. This concept applies to all aspects of this disclosure including, but not limited to, steps in methods using the disclosed systems or devices. Thus, if there are a variety of additional steps that can be performed, it is understood that each of these additional steps can be performed with any specific method steps or combination of method steps of the disclosed methods, and that each such combination or subset of combinations is specifically contemplated and should be considered disclosed.

Claims

1. A food tray stand, the stand comprising: a body having a first surface and a second surface opposite and spaced apart from the first surface, wherein the first surface defines a tray opening extending to the second surface; two or more legs hingedly coupled to the body by a living hinge,

wherein each of the two or more legs is hingedly movable between an extended position and a retracted position, wherein each of the two or more legs extends away from the second surface in the extended position and is at least partially disposable within the tray opening in the retracted position; and a base separately formed from the body and the two or more legs, wherein when the two or more legs are in the retracted position, the base is at least partially disposable within the tray opening, and wherein the base defines one or more nesting openings, wherein when the two or more legs are in the retracted position and the base is at least partially disposed within the tray opening, at least one of the two or more legs is at least partially disposable within the one or more nesting openings.

2. The stand of claim 1, wherein the two or more legs comprises four legs.

3. The stand of claim 1, wherein each of the two or more legs is fully disposable within the tray opening in the retracted position.

4. The stand of claim 1, wherein one of the base or the two or more legs defines one or more coupling openings and an other of the two or more legs or the base includes one or more coupling protrusions, wherein each of the one or more coupling protrusions is engageable with a different one of the one or more coupling openings to couple the base to the two or more legs.

5. The stand of claim 4, wherein the base defines the one or more coupling openings and the two or more legs includes the one or more coupling protrusions.

6. The stand of claim 4, wherein the one or more coupling openings are keyhole openings and the one or more protrusions includes a stem and a distal head, wherein the distal head and the stem of each respective one of the two or more legs each have a largest width as measured perpendicular to a plane that includes a path of movement of the respective one of the two or more legs when the respective one of the two or more legs moves between the extended position and the retracted position, wherein the largest width of the distal head is greater than the largest width of the stem.

7. The stand of claim 1, wherein the base is fully disposable within the tray opening.

8. The stand of claim 1, wherein the one or more nesting opening comprises two or more nesting openings, wherein each of the two or more legs is at least partially disposable within a different one of the two or more nesting openings.

9. The stand of claim 1, wherein the base defines at least one canned cooking fuel opening sized to receive a canned cooking fuel.

10. The stand of claim 9, wherein the at least one canned cooking fuel opening has a diameter, wherein the diameter is in the range of 2.0 inches to 6.0 inches.

11. The stand of claim 1, wherein the body and the two or more legs comprise a polymer.

12. The stand of claim 11, wherein the polymer comprises polypropylene or high impact polystyrene.

13. The stand of claim 1, wherein the body and the two or more legs are integrally formed.

14. The stand of claim 1, wherein the body defines one or more utensil holders.

15. The stand of claim 14, wherein the one or more utensil holders are utensil openings defined by the first surface of the body and extending to the second surface of the body.

16. The stand of claim 1, wherein the tray opening includes a first portion and a second portion, wherein the first portion of the tray opening is wider in at least one dimension than the second portion of the tray opening such that a ledge is formed at the intersection of the first portion and the second portion of the tray opening.
