

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397666
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Ishibashi; Masayuki et al.

Electric vehicle

Abstract

An electric vehicle includes a mechanical-electrical integrated unit constituted by a drive apparatus and an electric-power control apparatus that are housed in a same casing. The drive apparatus includes a first electric motor, a second electric motor and a transmission device. The electric-power control apparatus is configured to control an electric power transmitted and received by the first and second electric motors. The electric-power control apparatus and the drive apparatus are housed in upper and lower casing portion of the casing, respectively. The second electric motor includes a stator core that is provided with a plurality of fastened portions, such that one of the plurality of fastened portions is disposed in a position which overlaps the upper casing portion in a vertical direction of the vehicle and which is located on a front side of an axis of the second electric motor in a longitudinal direction of the vehicle.

Inventors: Ishibashi; Masayuki (Numazu, JP), Kunifuda; Hiroki (Chiryu, JP), Kwon; Hyuksoo (Anjo, JP), Suenaga; Shinichiro (Nagoya, JP)

Applicant: TOYOTA JIDOSHA KABUSHIKI KAISHA (Toyota, JP)

Family ID: 1000008780785

Assignee: TOYOTA JIDOSHA KABUSHIKI KAISHA (Toyota, JP)

Appl. No.: 18/441281

Filed: February 14, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240300349 A1	Sep. 12, 2024

Foreign Application Priority Data

JP	2023-036069	Mar. 08, 2023
----	-------------	---------------

Publication Classification

Int. Cl.: **B60L15/00** (20060101); **B60L15/20** (20060101); **B60L50/15** (20190101); **B60L50/61** (20190101); **B60L53/22** (20190101); **B60L53/24** (20190101)

U.S. Cl.:

CPC **B60L53/22** (20190201); **B60L15/2036** (20130101); **B60L50/61** (20190201); **B60L53/24** (20190201); B60L15/007 (20130101); B60L50/15 (20190201); B60L2210/10 (20130101); B60L2220/42 (20130101)

Field of Classification Search

CPC: B60L (53/22); B60L (15/2036); B60L (50/61); B60L (53/24); B60L (15/007); B60L (50/15); B60L (2210/10); B60L (2220/42); Y02T (10/62); Y02T (10/64); Y02T (10/70); B60K (6/445); B60K (6/40); B60K (1/02); B60K (6/405); B60K (6/365); F16H (2037/0873); F16H (3/728)

USPC: 701/22; 180/65.285; 180/65.265; 180/65.1; 180/65.29; 180/65.235; 318/139; 307/10.1; 307/9.1; 320/109

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8905881	12/2013	Sada	475/5	B60K 6/445
2023/0163654	12/2022	Asakura	310/71	B62D 21/152

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2021-046003	12/2020	JP	N/A

Primary Examiner: Ortiz; Elim

Attorney, Agent or Firm: Oliff PLC

Background/Summary

(1) This application claims priority from Japanese Patent Application No. 2023-036069 filed on Mar. 8, 2023, the disclosure of which is herein incorporated by reference in its entirety.

FIELD OF THE INVENTION

(2) The present invention relates to an electric vehicle provided with a mechanical-electrical integrated unit that is constituted by a drive apparatus and an electric-power control apparatus that are housed in a same casing, wherein the drive apparatus includes a first electric motor, a second electric motor and a transmission device, while the electric-power control apparatus is configured to control an electric power transmitted and received by the first and second electric motors.

BACKGROUND OF THE INVENTION

(3) There is known a vehicle in which a drive apparatus and an electric-power control apparatus are

housed in respective casings that are separated from each other, wherein the drive apparatus includes a first electric motor, a second electric motor and a transmission device, while the electric-power control apparatus includes an inverter configured to control an electric power transmitted and received by the first and second electric motors, and wherein the casing housing the electric-power control apparatus is disposed above the casing housing the drive apparatus. A vehicle disclosed in JP 2021-46003 A is an example of such a vehicle.

SUMMARY OF THE INVENTION

(4) By the way, in order to simplify shape of a drive unit, it might be possible to employ an arrangement in which the drive apparatus and the electric-power control apparatus are housed in a same casing, that is, to form a mechanical-electrical integrated unit, for example, such that the electric-power control apparatus is housed in an upper casing portion of the casing while the drive apparatus is housed in a lower casing portion of the casing. In this arrangement, the above-identified Japanese Patent Application Publication does not particularly specify fastened positions in which a stator core of the electric motor of the drive apparatus is fastened to the casing.

Depending on the fastened positions of the stator core of the electric motor, size reduction of the mechanical-electrical integrated unit is suppressed.

(5) The present invention was made in view of the background art described above. It is therefore an object of the present invention to provide an electric vehicle in which size of a mechanical-electrical integrated unit can be reduced.

(6) The object indicated above is achieved according to the following aspects of the present invention.

(7) According to a first aspect of the invention, there is provided an electric vehicle including: a pair of drive wheels; and a mechanical-electrical integrated unit constituted by a drive apparatus and an electric-power control apparatus that are housed in a same casing, wherein the drive apparatus includes a first electric motor, a second electric motor and a transmission device configured to transmit a power outputted by the second electric motor toward the drive wheels, wherein the electric-power control apparatus is configured to control an electric power transmitted and received by the first and second electric motors. In the electric vehicle, (a) the casing has an upper casing portion and a lower casing portion that is disposed on a lower side of the upper casing portion in a vertical direction of the electric vehicle, (b) the electric-power control apparatus is housed in the upper casing portion while the drive apparatus is housed in the lower casing portion, (c) the first electric motor, the second electric motor and the transmission device have respective axes all of which are parallel to a width direction of the electric vehicle, (d) the axis of the second electric motor, the axis of the transmission device and the axis of the first electric motor are arranged in this order from above to below in the vertical direction, (e) the axis of the first electric motor, the axis of the transmission device and the axis of the second electric motor are arranged in this order from front to rear in a longitudinal direction of the electric vehicle, (f) the second electric motor includes a stator core that is provided with a plurality of fastened portions such that a first fastened portion as one of the plurality of fastened portions is disposed in a position which overlaps the upper casing portion in the vertical direction and which is located on a front side of the axis of the second electric motor in the longitudinal direction, and (g) another one of the plurality of fastened portions is disposed in a position which does not overlap the upper casing portion in a circumferential direction of the stator core. The second electric motor is fastened at the plurality of fastened portions to the lower casing portion of the casing, for example.

(8) According to a second aspect of the invention, in the electric vehicle according to the first aspect of the invention, the first fastened portion is disposed in the position which is not higher than an uppermost portion of a yoke of the stator core in the vertical direction and which is not more front than a frontmost portion of the yoke of the stator core in the longitudinal direction.

(9) According to a third aspect of the invention, in the electric vehicle according to the first or second aspect of the invention, the electric vehicle includes: a differential gear device to which the

power is to be transmitted through the transmission device, and a drive shaft connecting between the differential gear device and each of the drive wheels, wherein a second fastened portion as the another one of the plurality of fastened portions is disposed in the position which is lower than the axis of the transmission device in the vertical direction and which is located on an outer peripheral side of the drive shaft.

(10) According to a fourth aspect of the invention, in the electric vehicle according to any one of the first through third aspects of the invention, a third fastened portion as still another one of the plurality of fastened portions is disposed in a position that does not overlap the axis of the second electric motor in the vertical direction.

(11) According to a fifth aspect of the invention, in the electric vehicle according to any one of the first through third aspects of the invention, a third fastened portion as still another one of the plurality of fastened portions is disposed in a position that is higher than a pedal of the electric vehicle in the vertical direction.

(12) According to a sixth aspect of the invention, in the electric vehicle according to any one of the first through third aspects of the invention, a third fastened portion as still another one of the plurality of fastened portions is disposed in a position which does not overlap the axis of the second electric motor in the vertical direction and which is higher than a pedal of the electric vehicle in the vertical direction.

(13) According to a seventh aspect of the invention, in the electric vehicle according to any one of the fourth through sixth aspects of the invention, the plurality of fastened portions consist of the first fastened portion, the second fastened portion and the third fastened portion, wherein the first fastened portion, the second fastened portion and the third fastened portion are arranged at equal angular intervals in the circumferential direction of the stator core.

(14) In the electric vehicle according to the first aspect of the invention, (a) the casing has the upper casing portion and the lower casing portion that is disposed on the lower side of the upper casing portion in the vertical direction of the electric vehicle, (b) the electric-power control apparatus is housed in the upper casing portion while the drive apparatus is housed in the lower casing portion, (c) the first electric motor, the second electric motor and the transmission device have respective axes all of which are parallel to the width direction of the electric vehicle, (d) the axis of the second electric motor, the axis of the transmission device and the axis of the first electric motor are arranged in this order from above to below in the vertical direction, (e) the axis of the first electric motor, the axis of the transmission device and the axis of the second electric motor are arranged in this order from front to rear in the longitudinal direction of the electric vehicle, (f) the second electric motor includes the stator core that is provided with the plurality of fastened portions such that the first fastened portion as one of the plurality of fastened portions is disposed in the position which overlaps the upper casing portion in the vertical direction and which is located on the front side of the axis of the second electric motor in the longitudinal direction, and (g) another one of the plurality of fastened portions is disposed in the position which does not overlap the upper casing portion in the circumferential direction of the stator core. In the electric vehicle in which the first fastened portion is disposed in the position which overlaps the upper casing portion in the vertical direction and which is located on the front side of the axis of the second electric motor in the longitudinal direction, it is possible to suppress a distance by which the first fastened portion protrudes toward the upper casing portion in the vertical direction, as compared with an arrangement in which the first fastened portion is not disposed in such a position. With the first fastened portion being disposed in such a position, it is possible to reduce a size of the mechanical-electrical integrated unit in which the drive apparatus and the electric-power control apparatus are housed in the same casing. If any one of the plurality of fastened portions is not disposed in the position overlapping the upper casing portion in the vertical direction, an angular interval between each adjacent two of the fastened portions in the circumferential direction is increased whereby the stator core of the second electric motor cannot be stably held by the casing. Further, in the electric

vehicle in which the another one of the plurality of fastened portions is disposed in the position which does not overlap the upper casing portion in the circumferential direction of the stator core, the reduction of the size of the mechanical-electrical integrated unit is not impeded.

(15) In the electric vehicle according to the second aspect of the invention, the first fastened portion is disposed in the position which is the same or lower than the uppermost portion of the yoke of the stator core in the vertical direction and which is the same or more rear than the frontmost portion of the yoke of the stator core in the longitudinal direction. Owing to the arrangement, the size of the mechanical-electrical integrated unit can be further reduced.

(16) In the electric vehicle according to the third aspect of the invention, the second fastened portion as the another one of the plurality of fastened portions is disposed in the position which is lower than the axis of the transmission device in the vertical direction and which is located on the outer peripheral side of the drive shaft that connects between each of the drive wheels and the differential gear device to which the power is to be transmitted through the transmission device. Owing to the arrangement, it is possible to reduce the size of the mechanical-electrical integrated unit while ensuring an appropriate distance between the axis of the transmission device and the axis of the drive shaft.

(17) In the electric vehicle according to the fourth aspect of the invention, the third fastened portion as the still another one of the plurality of fastened portions is disposed in the position that does not overlap the axis of the second electric motor in the vertical direction. Owing to the arrangement, it is possible to suppress a distance by which the third fastened portion protrudes rearwardly in the longitudinal direction, as compared with an arrangement in which the third fastened portion is not disposed in the position that does not overlap the axis of the second electric motor in the vertical direction. Thus, a dimension of the mechanical-electrical integrated unit in the longitudinal direction can be reduced.

(18) In the electric vehicle according to the fifth aspect of the invention, the third fastened portion as the still another one of the plurality of fastened portions is disposed in the position that is higher than the pedal of the electric vehicle in the vertical direction. Owing to the arrangement in which the third fastened portion is disposed in the position higher than the pedal, it is possible to suppress the third fastened portion from being moved toward the pedal to press the pedal in event of a collision of the electric vehicle, and accordingly to suppress a foot of a vehicle driver operating the pedal, from being pressed by the third fastened portion through the pedal.

(19) In the electric vehicle according to the sixth aspect of the invention, the third fastened portion as the still another one of the plurality of fastened portions is disposed in the position which does not overlap the axis of the second electric motor in the vertical direction and which is higher than the pedal of the electric vehicle in the vertical direction. Owing to the arrangement, it is possible to reduce the dimension of the mechanical-electrical integrated unit in the longitudinal direction, and also to suppress the foot of the vehicle driver from being pressed by the third fastened portion through the pedal.

(20) In the electric vehicle according to the seventh aspect of the invention, (a) the plurality of fastened portions consist of the first fastened portion, the second fastened portion and the third fastened portion, and (b) the first fastened portion, the second fastened portion and the third fastened portion are arranged at equal angular intervals in the circumferential direction of the stator core. Owing to the arrangement in which the plurality of fastened portions consist of the three fastened portions and the three fastened portion are arranged at equal angular intervals in the circumferential direction, the second electric motor can be stably held by the casing and a required number of steps can be reduced when the second electric motor is to be fastened to the casing.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a view schematically showing, by way of example, a construction of a hybrid electric vehicle to which the present invention is applied;
- (2) FIG. 2 is a view showing an example of an electrical configuration of an electric-power control unit and other components of the hybrid electric vehicle;
- (3) FIG. 3 is a perspective view showing a stator of a second electric motor in a state before it is installed in the hybrid electric vehicle;
- (4) FIG. 4 is a view showing, by way of example, an arrangement of various components of a drive unit installed in the hybrid electric vehicle; and
- (5) FIG. 5 is a view showing, by way of example, a positional relationship between an accelerator pedal and the drive unit installed in the hybrid electric vehicle.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENT

(6) Hereinafter, an embodiment of the present invention will be described in detail with reference to the drawings. In the drawings of the embodiment, the drawings are simplified or modified as appropriate, and the dimensional ratios, shapes, and the like of the respective parts are not necessarily accurately drawn.

EMBODIMENT

- (7) FIG. 1 is a view schematically showing, by way of example, a construction of a hybrid electric vehicle **10** (hereinafter, simply referred to as “vehicle **10**”) to which the present invention is applied. The vehicle **10** corresponds to “electric vehicle” in the present invention.
- (8) The vehicle **10** includes an engine **12** that functions as a power source, and a first electric motor **MG1** and a second electric motor **MG2** that are electric motors that function as power sources. The vehicle **10** includes a pair of drive wheels **14** and a power transmission apparatus **16**.
- (9) The engine **12** is a known internal combustion engine. The first electric motor **MG1** and the second electric motor **MG2** are, for example, rotating electric machines having motor functions and power generator functions, and are so-called motor generators. The first electric motor **MG1** and the second electric motor **MG2** are, for example, inner-rotor-type synchronous motors. The first electric motor **MG1** and the second electric motor **MG2** are housed in a non-rotatable casing **18** which is a non-rotatable member attached to a vehicle body that is a body of the vehicle **10**.
- (10) The power transmission apparatus **16** is provided in a power transmission path between the engine **12** and the pair of drive wheels **14** and in a power transmission path between the second electric motor **MG2** and the pair of drive wheels **14**. The power transmission apparatus **16** includes a damper **20**, an input shaft **22**, a transmission portion **24**, a composite gear **26**, a driven gear **32**, a driven shaft **34**, a final gear **36**, a differential gear device **38** and a reduction gear **40** that are disposed in the casing **18**. The input shaft **22** functions as an input rotary member of the transmission portion **24**, and is connected to a crankshaft **12a** of the engine **12** through the damper **20**, for example. The transmission portion **24** is connected to the input shaft **22**. The composite gear **26** is an output rotary body of the transmission portion **24**. The composite gear **26** has a drive gear **26a** formed on a part of an outer peripheral surface thereof. The drive gear **26a** is an output rotary member of the transmission portion **24**. The driven gear **32** meshes with the drive gear **26a**. The driven gear **32** and the final gear **36** are fixed to the driven shaft **34** so as not to be relatively rotatable. The final gear **36** has a smaller diameter than the driven gear **32** and meshes with a differential ring gear **34a** of the differential gear device **38**. The reduction gear **40** has a smaller diameter than the driven gear **32** and meshes with the driven gear **32**. A rotor shaft of the second electric motor **MG2** is connected to the reduction gear **40**, and the second electric motor **MG2** is connected to the reduction gear **40** in a power transmittable manner. The power transmission apparatus **16** includes a pair of drive shafts **42** connected to the differential gear device **38**. It is noted that the driven gear **32**, the driven shaft **34** and the final gear **36** cooperate to constitute a transmission device **30** that is configured to transmit the power outputted by the second electric

motor MG2 toward the pair of drive wheels **14**, and that the transmission device **30** corresponds to “transmission device” in the present invention.

(11) The power transmission apparatus **16** constructed as described above is suitably used for a vehicle of a front engine front drive (FF) type. In the present embodiment, the vehicle **10** is the vehicle of FF type. The power transmission apparatus **16** transmits a power outputted from the engine **12** to the driven gear **32** via the transmission portion **24**. The power transmission apparatus **16** transmits a power outputted from the second electric motor MG2 to the driven gear **32** via the reduction gear **40**. The power transmission apparatus **16** transmits the power transmitted to the driven gear **32**, to the pair of drive wheels **14** sequentially via the driven shaft **34**, the final gear **36**, the differential gear device **38** and the drive shafts **42**, for example. The differential gear device **38** is a differential gear device that distributes the power transmitted via the final gear **36** to the pair of drive wheels **14**. It is noted that the differential gear device **38** corresponds to “differential gear device” in the present invention.

(12) The power transmission apparatus **16** has a first axis CL1, a second axis CL2, a third axis CL3, and a fourth axis CL4, which are rotational center lines. These four axes CL1, CL2, CL3, CL4 are parallel to each other. The first axis CL1 is an axis of the input shaft **22** and an axis of the rotor shaft of the first electric motor MG1. That is, the first axis CL1 is a rotational center line of the first electric motor MG1. The transmission portion **24** and the first electric motor MG1 are disposed around the first axis CL1. That is, in the transmission portion **24**, the drive gear **26a** is disposed coaxially with the first electric motor MG1. The second axis CL2 is an axis of the rotor shaft of the second electric motor MG2. That is, the second axis CL2 is a rotational center line of the second electric motor MG2. The second electric motor MG2 and the reduction gear **40** are disposed around the second axis CL2. The third axis CL3 is an axis of the driven shaft **34**. The driven gear **32** and the final gear **36** are disposed around the third axis CL3. That is, the third axis CL3 is a rotational center line of the driven gear **32**, the driven shaft **34** and the final gear **36**. The fourth axis CL4 is an axis of each of the drive shafts **42** and an axis of the differential gear device **38**. That is, the fourth axis CL4 is a rotational center line of the differential gear device **38**. The differential gear device **38** is disposed around the fourth axis CL4. It is noted that the first axis CL1 corresponds to “axis of the first electric motor” in the present invention, that the second axis CL2 corresponds to “axis of the second electric motor” in the present invention, and that the third axis CL3 corresponds to “axis of the transmission device”.

(13) The transmission portion **24** includes the first electric motor MG1 and a differential mechanism **44**. The differential mechanism **44** is constituted by a known single-pinion type planetary gear device, and includes a sun gear S, a carrier CA and a ring gear R. The sun gear S is connected to the rotor shaft of the first electric motor MG1, and the first electric motor MG1 is connected to the sun gear S in a power transmittable manner. The carrier CA is connected to the input shaft **22**, and is connected to the engine **12**, through the input shaft **22**, for example, in a power transmittable manner. The ring gear R is formed on a part of an inner circumferential of the composite gear **26**, and is integrally connected to the drive gear **26a**.

(14) The differential mechanism **44** is a differential mechanism which is connected to the engine **12** in a power transmittable manner and which generates a differential effect. The first electric motor MG1 is a differential electric motor that is connected to the differential mechanism **44** in a power transmittable manner. The differential mechanism **44** is a power dividing mechanism for mechanically dividing the power of the engine **12** between the first electric motor MG1 and the drive gear **26a**. The transmission portion **24** is a known electric transmission mechanism in which the operating state of the first electric motor MG1 is controlled to control the operating state of the differential mechanism **44**. The first electric motor MG1 may also function as a power source that outputs the power to the pair of drive wheels **14** via the differential mechanism **44**.

(15) FIG. 2 is a view showing an example of an electrical configuration of an electric-power control unit **54** and the like.

(16) The vehicle **10** further includes a high-voltage battery **46**, an auxiliary battery **48** and the electric-power control unit **54**.

(17) The high-voltage battery **46** is a chargeable and dischargeable secondary battery such as a nickel-hydrogen secondary battery or a lithium ion battery. The high-voltage battery **46** is connected to the electric-power control unit **54**. The high-voltage battery **46** is a battery for driving the first electric motor MG1 and the second electric motor MG2. For example, the stored electric power is supplied from the high-voltage battery **46** to the second electric motor MG2 via the electric-power control unit **54**. Each of the first electric motor MG1 and the second electric motor MG2 generates an electric power by the power of the engine **12** and the driven force inputted from the pair of drive wheels **14**, and the high-voltage battery **46** is charged with the generated electric power supplied via the electric-power control unit **54**.

(18) The auxiliary battery **48** is a chargeable and dischargeable secondary battery such as a lead storage battery. The auxiliary battery **48** has a charging voltage lower than that of the high-voltage battery **46**. The auxiliary battery **48** is charged with the electric power generated by an alternator rotationally driven by the engine **12** or the electric power supplied from the high-voltage battery **46** via a DC-DC converter **56**.

(19) The electric-power control unit **54** includes the DC-DC converter **56**, a boost converter **60**, an inverter **62** and an electric-motor control device **58**. The electric-power control unit **54** is an electric-power control device that controls the electric power transferred between the high-voltage battery **46** and each of the first electric motor MG1 and the second electric motor MG2, that is, the electric power transmitted and received by each of the first electric motor MG1 and the second electric motor MG2. The electric-power control unit **54** corresponds to “electric-power control apparatus” in the present invention.

(20) The DC-DC converter **56** is connected to the high-voltage battery **46**. The DC-DC converter **56** functions as a charging device that reduces the voltage of the high-voltage battery **46** to a voltage equivalent to that of the auxiliary battery **48** and charges the auxiliary battery **48**. The auxiliary battery **48** supplies the electric power for operating auxiliary devices provided in the vehicle **10**. The auxiliary battery **48** supplies the electric power for operating, for example, an engine control device **52** and the electric-motor control device **58**.

(21) The boost converter **60** includes a reactor, a switching element and the like (not shown). The boost converter **60** is a buck-boost circuit having a function of increasing the voltage of the high-voltage battery **46** and supplying the increased voltage to the inverter **62**, and a function of reducing the voltage converted into a direct current by the inverter **62** and supplying the reduced voltage to the high-voltage battery **46**.

(22) The inverter **62** includes an MG1 power module **64** and an MG2 power module **66**. Each of the MG1 power module **64** and the MG2 power module **66** includes a switching element (not shown). The inverter **62** converts the direct current outputted from the boost converter **60** into an alternating current for driving the first electric motor MG1 and the second electric motor MG2. The inverter **62** converts the alternating current generated by the first electric motor MG1 and the alternating current generated by the second electric motor MG2 into the direct current. The inverter **62** uses the electric power generated by the first electric motor MG1 as the electric power for driving the second electric motor MG2 in accordance with a running state of the vehicle **10**.

(23) An electronic control device **50** transmits and receives signals to and from the DC-DC converter **56**, the electric-motor control device **58** and the engine control device **52** via, for example, a known controller area network (CAN) communication line. The electronic control device **50** controls the running state of the vehicle **10** based on, for example, signals from sensors (not shown) or the like. The electronic control device **50** controls, for example, the DC-DC converter **56** to reduce the voltage of the high-voltage battery **46** to a voltage equivalent to that of the auxiliary battery **48**. In the present embodiment, the electronic control device **50** and the engine control device **52** are control devices that are separate from the electric-power control unit **54**, and

particularly from the electric-motor control device **58**.

(24) The electric-motor control device **58** controls the first electric motor **MG1** and the second electric motor **MG2** based on a requested output value supplied from the electronic control device **50**. For example, the electric-motor control device **58** controls the boost converter **60** and the inverter **62** to control an output of each of the first electric motor **MG1** and the second electric motor **MG2**.

(25) Returning to FIG. **1**, a transaxle **98** is a drive apparatus including the first electric motor **MG1**, the second electric motor **MG2**, the transmission portion **24**, the composite gear **26** and the transmission device **30** (the driven gear **32**, the driven shaft **34** and the final gear **36**). A drive unit **96** is a mechanical-electrical integrated unit, i.e., a unit in which the transaxle **98** and the electric-power control unit **54** are integrally housed in the same casing **18**. The meaning of the “same casing” will be described later. The transaxle **98** corresponds to “drive apparatus” in the present invention, and the drive unit **96** corresponds to “mechanical-electrical integrated unit” in the present invention.

(26) FIG. **3** is a perspective view showing a stator **82** of the second electric motor **MG2** in a state before it is installed in the vehicle **10**. To make the invention easier to understand, the axis of the second electric motor **MG2** will be explained as the second axis **CL2**, which is the axis after it is installed in vehicle **10**. Since the stator of the first electric motor **MG1** has substantially the same construction as the stator **82** of the second electric motor **MG2**, the second electric motor **MG2** will be described as a representative, and description of the first electric motor **MG1** is not provided.

(27) The stator **82** of the second electric motor **MG2** includes a stator core **84**, a coil **86** and a power line **88**.

(28) In the following description, a direction parallel to the second axis **CL2** will be simply referred to as “second axis **CL2** direction”, a radial direction of the stator core **84** will be simply referred to as “radial direction”, and a circumferential direction of the stator core **84** will be simply referred to as “circumferential direction”. The radial direction of the stator core **84** is synonymous with a radial direction centered on the second axis **CL2**.

(29) The stator core **84** has a cylindrical body whose center lies on the second axis **CL2**, wherein the cylindrical body is constituted by a plurality of electromagnetic steel plates laminated on each other, for example. On an inner circumferential surface of the cylindrical-shaped stator core **84**, tooth portions **84t** are provided at equal angular intervals, such that each of the tooth portions **84t** protrudes inwardly in the radial direction and extends in the second axis **CL2** direction. Each adjacent pair of the tooth portions **84t** define a slot portion therebetween. It is noted that the stator core **84** does not necessarily have to be constituted by the plurality of electromagnetic steel plates that are laminated on each other, but may be formed by molding electromagnetic powder, solid or the like. The stator core **84** corresponds to “stator core” in the present invention.

(30) The stator core **84** is provided with a plurality of fastened portions **84c** that are disposed in its outer peripheral portion. In the present embodiment, the plurality of fastened portions **84c** consist of three fastened portions **84c**. In the stator core **84**, each of the fastened portions **84c** locally protrudes outwardly in the radial direction, and extends in the second axis **CL2** direction. Each of the fastened portions **84c** protrudes in an arc shape, and has a through-hole **84h** extending through in the second axis **CL2** direction. As viewed in the second axis **CL2** direction, axes (centers) of the respective through-holes **84h** are arranged at equal angular intervals (of $2\pi/3$ [rad] in the present embodiment) in the circumferential direction. The axes of the respective through-holes **84h** are distant from the second axis **CL** by the same distance in the radial direction.

(31) The coil **86** is wound on the tooth portions **84t** of the stator core **84**, and is a three-phase coil for U-phase, V-phase and W-phase, for example. The coil **86** includes a protrusion portion protruding outwardly from the stator core **84** in the second axis **CL2** direction, and the protrusion portion constitutes a coil end. The power line **88** is an elongated-plate-shaped metal body. The power line **88** is electrically connected to the three-phase winding in the coil end, with an end

portion of the power line **88** being fixed to an end portion of the three-phase winding by welding, for example. The power line **88** is electrically connected at another end portion thereof to a crimp terminal by caulking, for example. The stator core **84** has a yoke **84y** that is constituted by a portion of the stator core **84** which is other than the tooth portions **84t** and which is other than the fastened portions **84c**. The yoke **84y** serves as a path of magnetic field lines between the tooth portions **84t** that serve as electromagnets.

(32) FIG. **4** is a view showing, by way of example, an arrangement of various components of the drive unit **96** installed in the vehicle **10**. It is noted that “VERTICAL DIRECTION”, “LONGITUDINAL DIRECTION” and “WIDTH DIRECTION” shown in FIG. **4** and FIG. **5** described later indicate directions in a state in which the drive unit **96** is installed in the vehicle **10**. The “VERTICAL DIRECTION” is a vertical direction of the vehicle **10**. The “LONGITUDINAL DIRECTION” is a longitudinal direction of the vehicle **10**. The “WIDTH DIRECTION” is a width direction of the vehicle **10** and is a horizontal direction perpendicular to the longitudinal direction of the vehicle **10**. The drive unit **96** is disposed in a position adjacent to the engine **12**.

(33) The casing **18** is made of, for example, a casting of an aluminum alloy. The casing **18** includes a first casing portion **70**, a second casing portion **72**, a third casing portion **74** and a fourth casing portion **76**.

(34) The first casing portion **70** is a bottomed cylindrical member. The second casing portion **72** is a bottomed cylindrical member, and is provided with a partition wall **72d** inside thereof. The second casing portion **72** includes a bottom wall and a side wall that extends upwardly from an outer periphery of the bottom wall, such that the bottom wall, the side wall and the above-described partition wall **72d** are formed integrally with one another, for example, by casting. The first casing portion **70** and the second casing portion **72** are integrally connected through fastening members such as bolts **78a** (see FIG. **1**) such that an opening portion of the first casing portion **70** and an engine-side portion of the second casing portion **72** are aligned. With the second casing portion **72** being connected with the first casing portion **70**, the casing **18** has an upper space **U** and a lower space **L** that are vertically separated from each other by the partition wall **72d**.

(35) The casing **18** includes an upper casing portion **18U** that defines or surrounds the above-described upper space **U** and a lower casing portion **18L** that defines or surrounds the above-described lower space **L**. In the casing **18**, the lower casing portion **18L** is disposed on a lower side of the upper casing portion **18U** in the vertical direction.

(36) The partition wall **72d** is a common partition wall that defines a lower end of the upper casing portion **18U** and an upper end of the lower casing portion **18L**. Therefore, where the upper casing portion **18U** and the lower casing portion **18L** are separated from each other, the inside of at least one of the upper casing portion **18U** and the lower casing portion **18L** is necessarily exposed to the outside. The above-described “same casing” means a casing in which the inside of at least one of the upper casing portion **18U** and the lower casing portion **18L** is necessarily exposed to the outside where the upper casing portion **18U** and the lower casing portion **18L** are separated from each other.

(37) The second casing portion **72** has an opening portion in an opposite portion of the side wall that defines the lower space **L**, wherein the opposite portion of the side wall is opposite to the engine **12**. The second casing portion **72** has another opening portion in its upper surface that defines the upper space **U**. That is, the lower casing portion **18L** has an opening portion in an opposite portion of its side wall which is opposite to the engine **12**, while the upper casing portion **18U** has an opening portion in its upper surface. The electric-power control unit **54** and the transaxle **98** are housed in the upper casing portion **18U** and the lower casing portion **18L**, respectively, when being installed in the vehicle **10**.

(38) The third casing portion **74** is a plate-shaped member joined to the second casing portion **72** so as to cover the opening portion of the side wall of the second casing portion **72**. The first and second electric motors **MG1**, **MG2** are attached onto respective seat surfaces provided in the lower

space L, through bolts, before the third casing portion **74** is joined to the second casing portion **72**, namely, before the opening portion of the side wall of the second casing portion **72** is closed. The seat surfaces are provided with first and second mounting holes (not shown). The first mounting holes are located in respective positions corresponding to through-holes of respective fastened portions of a stator core **80** (see FIG. 4) of the first electric motor MG1. The second mounting holes are located in respective positions corresponding to the through-holes **84h** of the respective fastened portions **84c** of the stator core **84** (see FIG. 4) of the second electric motor MG2. The first electric motor MG1 is fixedly disposed in the lower space L of the casing **18**, with the bolts being inserted in the respective through-holes of the respective fastened portions and being screwed in the respective first mounting holes. The second electric motor MG2 is fixedly disposed in the lower space L of the casing **18**, with the bolts being inserted in the respective through-holes **84h** of the respective fastened portions **84c** and being screwed in the respective second mounting holes. The second casing portion **72** and the third casing portion **74** are integrally connected to each other through fastening members such as bolts **78b** (see FIG. 1).

(39) The fourth casing portion **76** is a plate-shaped member joined to the second casing portion **72** so as to cover the opening portion of the upper surface of the second casing portion **72**. The electric-power control unit **54** is disposed in the upper space U, before the fourth casing portion **76** is joined to the second casing portion **72**, namely, before the opening portion of the upper surface of the second casing portion **72** is closed. The second casing portion **72** and the fourth casing portion **76** are integrally connected to each other through fastening members such as bolts **78c** (see FIG. 1).

(40) Thus, the electric-power control unit **54** is housed in the upper casing portion **18U** while the transaxle **98** is housed in the lower casing portion **18L**.

(41) When being installed in the vehicle **10**, the transaxle **98** is disposed such that, for example, each of the first axis CL1, second axis CL2, third axis CL3, and fourth axis CL4 is parallel to the width direction of the vehicle **10**, such that the second axis CL2, third axis CL3, first axis CL1 and fourth axis CL4 are arranged in this order in the vertical direction from top to bottom, and such that the first axis CL1, third axis CL3, fourth axis CL4 and second axis CL2 are arranged in this order in the longitudinal direction from front to rear. Owing to the arrangement, it is possible to reduce a size of the drive unit **96** while ensuring appropriate distances between the first axis CL1, second axis CL2, third axis CL3 and fourth axis CL4. The “size of the drive unit **96**” means an overall size of the drive unit **96** when sizes of respective components such as the first electric motor MG1, the second electric motor MG2 and the transmission device **30**, which are housed in the casing **18**, are not changed. In other words, “reducing the size of the drive unit **96**” means that the casing **18** can accommodate the components such as the first electric motor MG1, the second electric motor MG2 and the transmission device **30** more compact in size.

(42) In the following description, the plurality of fastened portions **84c** of the stator core **84** of the second electric motor MG2 will be referred to as first, second and third fastened portions X, Y, Z.

(43) As indicated by arrow a1 in FIG. 4, the first fastened portion X is located on a front side of the second axis CL2 in the longitudinal direction. Further, as indicated by arrow a2 in FIG. 4, the first fastened portion X is located on an upper side of a lower end of the upper casing portion **18U**. That is, the first fastened portion X is disposed in a position which overlaps the upper casing portion **18U** in the vertical direction and which is located on a front side of the second axis CL2 in the longitudinal direction. Preferably, as indicated by arrow a3 in FIG. 4, the first fastened portion X is disposed in the position that is lower than an uppermost portion of the yoke **84y** of the stator core **84** in the vertical direction. Further, preferably, as indicated by arrow a4 in FIG. 4, the first fastened portion X is disposed in the position that is located on a rear side of a frontmost portion of the yoke **84y** of the stator core **84** in the longitudinal direction.

(44) Each of the second fastened portion Y and the third fastened portion Z is another one of the fastened portions **84c** that is other than the first fastened portion X, and is disposed in a position

that does not overlap the upper casing portion **18U** in the circumferential direction. That is, each of the second fastened portion **Y** and the third fastened portion **Z** is disposed in the position that does not overlap the upper casing portion **18U** as viewed in the radial direction. As indicated by arrow **a5** in FIG. **4**, the second fastened portion **Y** is disposed in the position that is lower than the third axis **CL3** as the axis of the transmission device **30**. Further, as indicated by arrow **a6** in FIG. **4**, the second fastened portion **Y** is disposed in the position that is located on an outer peripheral side of an outermost diameter portion of the drive shaft **42**. As indicated by arrow **a7**, the third fastened portion **Z** is disposed in the position which is higher than the second axis **CL2** in the vertical direction, an which does not overlap the second axis **CL2** in the vertical direction. When the transaxle **98** is installed in the vehicle **10**, the first fastened portion **X**, second fastened portion **Y** and third fastened portion **Z** are located in fastened positions at which the stator core **84** of the second electric motor **MG2** is fastened to the casing **18**. Each of the second fastened portion **Y** and the third fastened portion **Z** corresponds to “another one of the plurality of fastened portions” in the present invention.

(45) As described above, the electric-power control unit **54** is housed in the upper casing portion **18U**. The upper casing portion **18U** is disposed in a position that is included in the lower casing portion **18L** as viewed from above in the vertical direction. The upper casing portion **18U** is disposed in the position that is included in the lower casing portion **18L** in the longitudinal direction. That is, the lower casing portion **18L** extends at least between two positions in the longitudinal direction, wherein one of the two positions corresponds to a frontmost portion of the upper casing portion **18U** while the other of the two positions corresponds to a rearmost portion of the upper casing portion **18U**. For example, the upper casing portion **18U** extends between two positions in the longitudinal direction, wherein one of the two positions is located on a rear side of the second axis **CL2** in the longitudinal direction while the other of the two positions is located on a front side of the first axis **CL1** in the longitudinal direction. The upper casing portion **18U** is disposed in the position that is included in the lower casing portion **18L** also in the width direction. That is, the lower casing portion **18L** extends at least between two positions in the width direction, wherein one of the two positions corresponds to a leftmost portion of the upper casing portion **18U** while the other of the two positions corresponds to a rightmost portion of the upper casing portion **18U**. The upper space **U** defined by the upper casing portion **18U** is a combination of rectangular parallelepiped spaces, for example. In the vertical direction, the upper space **U** is deeper on side of the first electric motor **MG1** side than on side of the second electric motor **MG2** due to the arrangement of the first and second electric motors **MG1**, **MG2**.

(46) Although not being described in detail, when the first electric motor **MG1** is installed in the vehicle **10**, the plurality of fastened portions provided in the stator core **80** of the first electric motor **MG1** are located in respective positions that do not impede reduction of the size of the drive unit **96**.

(47) FIG. **5** is a view showing, by way of example, a positional relationship between an accelerator pedal **90** and the drive unit **96** installed in the vehicle **10**.

(48) The third fastened portion **Z** is disposed in the position that is higher than the accelerator pedal **90** in the vertical direction. Specifically, the third fastened portion **Z** is disposed in the position that is higher than a highest position in which a distal end **90t** of a movable portion of the accelerator pedal **90** is moved to the highest, in the vertical direction. As shown in FIG. **5**, the third fastened portion **Z** is disposed in the position that is higher than the highest position (in which the distal end **90t** of the accelerator pedal **90** is moved to the highest) by a distance **LI** in the vertical direction. As described above, the first fastened portion **X**, second fastened portion **Y** and third fastened portion **Z** are arranged at equal angular intervals in the circumferential direction. It is noted that the accelerator pedal **90** corresponds to “pedal” in the present invention.

(49) In the present embodiment, (a) the casing **18** has the upper casing portion **18U** and the lower casing portion **18L** that is disposed on the lower side of the upper casing portion **18U** in the vertical

direction of the vehicle **10**, (b) the electric-power control unit **54** is housed in the upper casing portion **18U** while the transaxle **98** is housed in the lower casing portion **18L**, (c) the first electric motor **MG1**, the second electric motor **MG2** and the transmission device **30** have respective first, second and third axes **CL1**, **CL2**, **CL3** all of which are parallel to the width direction of the vehicle **10**, (d) the second axis **CL2** of the second electric motor **MG2**, the third axis **CL3** of the transmission device **30** and the first axis **CL1** of the first electric motor **MG1** are arranged in this order from above to below in the vertical direction, (e) the first axis **CL1** of the first electric motor **MG1**, the third axis **CL3** of the transmission device **30** and the second axis **CL2** of the second electric motor **MG2** are arranged in this order from front to rear in the longitudinal direction of the vehicle **10**, (f) the second electric motor **MG2** includes the stator core **84** that is provided with the plurality of fastened portions **84c** such that the first fastened portion **X** as one of the plurality of fastened portions **84c** is disposed in the position which overlaps the upper casing portion **18U** in the vertical direction and which is located on the front side of the second axis **CL2** of the second electric motor **MG2** in the longitudinal direction, and (g) each of the second and third fastened portions **Y**, **Z** as the others of the plurality of fastened portions **84c** is disposed in the position which does not overlap the upper casing portion **18U** in the circumferential direction of the stator core **84**. In the vehicle **10** in which the first fastened portion **X** is disposed in the position which overlaps the upper casing portion **18U** in the vertical direction and which is located on the front side of the second axis **CL2** of the second electric motor **MG2** in the longitudinal direction, it is possible to suppress a distance by which the first fastened portion **X** protrudes toward the upper casing portion **18U** in the vertical direction, as compared with an arrangement in which the first fastened portion **X** is not disposed in such a position. With the first fastened portion **X** being disposed in such a position, it is possible to reduce the size of the drive unit **96**, particularly, the dimension of the drive unit **96** in the vertical direction. If any one of the plurality of fastened portions **84c** is not disposed in the position overlapping the upper casing portion **18U** in the vertical direction, an angular interval between each adjacent two of the fastened portions **84c** in the circumferential direction is increased whereby the stator core **84** of the second electric motor **MG2** cannot be stably held by the casing **18**. Further, in the vehicle **10** in which each of the second and third fastened portions **Y**, **Z** is disposed in the position which does not overlap the upper casing portion **18U** in the circumferential direction of the stator core **84**, the reduction of the size of the drive unit **96** is not impeded.

(50) In the present embodiment, the first fastened portion **X** is disposed in the position which is lower than the uppermost portion of the yoke **84y** of the stator core **84** in the vertical direction and which is more rear than the frontmost portion of the yoke **84y** of the stator core **84** in the longitudinal direction. Owing to the arrangement, the size of the drive unit **96** can be reduced.

(51) In the present embodiment, the second fastened portion **Y** is disposed in the position which is lower than the third axis **CL3** of the transmission device **30** in the vertical direction and which is located on the outer peripheral side of the drive shaft **42** that connects between each of the drive wheels **14** and the differential gear device **38** to which the power is to be transmitted through the transmission device **30**. Owing to the arrangement, it is possible to reduce the size of the drive unit **96** while ensuring an appropriate distance between the third axis **CL3** of the transmission device **30** and the fourth axis **CL4** of the drive shaft **42**.

(52) In the present embodiment, the third fastened portion **Z** is disposed in the position that does not overlap the second axis **CL2** of the second electric motor **MG2** in the vertical direction. Owing to the arrangement, it is possible to suppress a distance by which the third fastened portion **Z** protrudes rearwardly in the longitudinal direction, as compared with an arrangement in which the third fastened portion **Z** is not disposed in the position that does not overlap the second axis **CL2** of the second electric motor **MG2** in the vertical direction. Thus, the dimension of the drive unit **96** in the longitudinal direction can be reduced.

(53) In the present embodiment, the third fastened portion **Z** is disposed in the position that is higher than the accelerator pedal **90**. Owing to the arrangement in which the third fastened portion

Z is disposed in the position higher than the accelerator pedal **90**, it is possible to suppress the third fastened portion Z from being moved toward the accelerator pedal **90** to press the accelerator pedal **90** in event of a collision of the vehicle **10**, and accordingly to suppress a foot of a vehicle driver operating the accelerator pedal **90**, from being pressed by the third fastened portion Z through the accelerator pedal **90** in a direction indicated by white arrow D in FIG. 5.

(54) In the present embodiment, (a) the plurality of fastened portions **84c** consist of the first fastened portion X, the second fastened portion Y and the third fastened portion Z, and (b) the first fastened portion X, the second fastened portion Y and the third fastened portion Z are arranged at equal angular intervals in the circumferential direction of the stator core **84**. Owing to the arrangement in which the plurality of fastened portions **84c** consist of the three fastened portions **84c** and the three fastened portion are arranged at equal angular intervals in the circumferential direction, the second electric motor MG2 can be stably held by the casing **18** and a required number of steps can be reduced when the second electric motor MG2 is to be fastened to the casing **18**.

(55) Although the embodiment of the present invention has been described in detail with reference to the drawings, the present invention is also applicable to other forms.

(56) In the above-described embodiment, the first fastened portion X is disposed in the position which is lower than the uppermost portion of the yoke **84y** of the stator core **84** in the vertical direction and which is located on the rear side of the frontmost portion of the yoke **84y** of the stator core **84** in the longitudinal direction. However, the present invention is not limited to these details. For example, an outer peripheral end of the first fastened portion X may be located on an upper side of the uppermost portion of the yoke **84y** of the stator core **84** in the vertical direction, as long as the first fastened portion X is located on the front side of the second axis CL2 of the second electric motor MG2 in the longitudinal direction. In this arrangement, too, it is possible to suppress a distance by which the first fastened portion X protrudes toward the upper casing portion **18U** in the vertical direction, as compared with an arrangement in which the first fastened portion X is disposed in a position overlapping the second axis CL2 of the second electric motor MG2 in the longitudinal direction. It is preferable that the first fastened portion X is disposed in the position which is not higher than the uppermost portion of the yoke **84y** of the stator core **84** in the vertical direction and which is not more front than the frontmost portion of the yoke **84y** of the stator core **84** in the longitudinal direction. In this preferable arrangement, dimensions of the drive unit **96** in the vertical direction and the longitudinal direction are dependent on the arrangement of the yoke **84y** of the stator core **84** of the second electric motor MG2, and the first fastened portion X does not impede reduction of the size of the drive unit **96**.

(57) In the above-described embodiment, the second fastened portion Y is disposed in the position which is lower than the third axis CL3 of the transmission device **30** and which is located on the outer peripheral side of the outermost diameter portion of the drive shaft **42**. However, the present invention is not limited to these details. For example, the second fastened portion Y may be disposed in a position that is higher than the third axis CL3 of the transmission device **30**.

(58) In the above-described embodiment, the third fastened portion Z is disposed in the position which is higher than the second axis CL2 in the vertical direction and which is higher than the distal end **90t** of the accelerator pedal **90** in the vertical direction. However, the present invention is not limited to these details. For example, the third fastened portion Z may be disposed in a position which does not overlap the second axis CL2 in the vertical direction and which is lower than the second axis CL2 in the vertical direction. Further, the third fastened portion Z may be disposed in a position that is lower than the distal end **90t** of the accelerator pedal **90** in the vertical direction.

(59) In the above-described embodiment, (a) the plurality of fastened portions **84c** consist of three fastened portions, i.e., the first fastened portion X, second fastened portion Y and third fastened portion Z, and (b) the first fastened portion X, second fastened portion Y and third fastened portion Z are arranged at equal angular intervals in the circumferential direction of the stator core **84**.

However, the present invention is not limited to these details. For example, the first fastened portion X, second fastened portion Y and third fastened portion Z do not have to be arranged necessarily at equal angular intervals. Further, for example, the plurality of fastened portions **84c** may consist of four or more fastened portions.

(60) In the above-described embodiment, the accelerator pedal **90** corresponds to the “pedal” in the present invention. However, the present invention is not limited to the detail. For example, the “pedal” in the present invention may be constituted by a brake pedal (not shown) or any other pedal that is to be operatively depressed or released by a driver of the vehicle.

(61) In the above-described embodiment, each of the first and second electric motors **MG1**, **MG2** is the motor generator. However, the present invention is not limited to the detail. For example, the first electric motor **MG1** may be a rotary electric machine that does not have a motor function as long as having a generator function. For example, the second electric motor **MG2** may be a rotary electric machine that does not have a generator function as long as having a motor function.

(62) In the above-described embodiment, the electronic control device **50**, the electric-motor control device **58** (configured to control the first and second electric motors **MG1**, **MG2**) and the engine control device **52** (configured to control the engine **12**) are constituted by respective control devices that are separated from one another. However, the electronic control device **50**, electric-motor control device **58** and engine control device **52** may be constituted by a single control device. In the present embodiment, the electronic control device **50**, electric-motor control device **58** and engine control device **52** may be constituted by respective control devices that are functionally divided from one other, as needed.

(63) It is to be understood that the embodiment described above is given for illustrative purpose only, and that the present invention may be embodied with various modifications and improvements which may occur to those skilled in the art.

NOMENCLATURE OF ELEMENTS

(64) **10**: hybrid electric vehicle (electric vehicle) **14**: pair of drive wheels **18**: casing **18L**: lower casing portion **18U**: upper casing portion **30**: transmission device **38**: differential gear device (differential gear device) **42**: drive shaft **54**: electric-power control unit (electric-power control apparatus) **84**: stator core (stator core) **84c**: plurality of fastened portions **84y**: yoke **90**: accelerator pedal (pedal) **98**: transaxle (drive apparatus) **CL1**: first axis (axis of first electric motor) **CL2**: second axis (axis of second electric motor) **CL3**: third axis (axis of transmission device) **MG1**: first electric motor **MG2**: second electric motor **X**: first fastened portion **Y**: second fastened portion (another one of the plurality of fastened portions) **Z**: third fastened portion (another one of the plurality of fastened portions)

Claims

1. An electric vehicle comprising: a pair of drive wheels; and a mechanical-electrical integrated unit constituted by a drive apparatus and an electric-power control apparatus that are housed in a same casing, wherein the drive apparatus includes a first electric motor, a second electric motor and a transmission device configured to transmit a power outputted by the second electric motor toward the drive wheels, wherein the electric-power control apparatus is configured to control an electric power transmitted and received by the first and second electric motors, wherein the casing has an upper casing portion and a lower casing portion that is disposed on a lower side of the upper casing portion in a vertical direction of the electric vehicle, wherein the electric-power control apparatus is housed in the upper casing portion while the drive apparatus is housed in the lower casing portion, wherein the first electric motor, the second electric motor and the transmission device have respective axes all of which are parallel to a width direction of the electric vehicle, such that the axis of the second electric motor, the axis of the transmission device and the axis of the first electric motor are arranged in this order from above to below in the vertical direction, and such that the axis

of the first electric motor, the axis of the transmission device and the axis of the second electric motor are arranged in this order from front to rear in a longitudinal direction of the electric vehicle, and wherein the second electric motor includes a stator core that is provided with a plurality of fastened portions, such that a first fastened portion as one of the plurality of fastened portions is disposed in a position which overlaps the upper casing portion in the vertical direction and which is located on a front side of the axis of the second electric motor in the longitudinal direction, and such that another one of the plurality of fastened portions is disposed in a position which does not overlap the upper casing portion in a circumferential direction of the stator core.

2. The electric vehicle according to claim 1, wherein the first fastened portion is disposed in the position which is not higher than an uppermost portion of a yoke of the stator core in the vertical direction and which is not more front than a frontmost portion of the yoke of the stator core in the longitudinal direction.

3. The electric vehicle according to claim 1, comprising: a differential gear device to which the power is to be transmitted through the transmission device, and a drive shaft connecting between the differential gear device and each of the drive wheels, wherein a second fastened portion as the another one of the plurality of fastened portions is disposed in the position which is lower than the axis of the transmission device in the vertical direction and which is located on an outer peripheral side of the drive shaft.

4. The electric vehicle according to claim 3, wherein a third fastened portion as still another one of the plurality of fastened portions is disposed in a position that does not overlap the axis of the second electric motor in the vertical direction.

5. The electric vehicle according to claim 3, wherein a third fastened portion as still another one of the plurality of fastened portions is disposed in a position that is higher than a pedal of the electric vehicle in the vertical direction.

6. The electric vehicle according to claim 3, wherein a third fastened portion as still another one of the plurality of fastened portions is disposed in a position which does not overlap the axis of the second electric motor in the vertical direction and which is higher than a pedal of the electric vehicle in the vertical direction.

7. The electric vehicle according to claim 6, wherein the plurality of fastened portions consist of the first fastened portion, the second fastened portion and the third fastened portion, and wherein the first fastened portion, the second fastened portion and the third fastened portion are arranged at equal angular intervals in the circumferential direction of the stator core.

8. The electric vehicle according to claim 1, wherein the second electric motor is fastened at the plurality of fastened portions to the lower casing portion of the casing.
