

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12398503
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Lee; Yunhi et al.

Laundry treating apparatus

Abstract

A laundry treating apparatus according to an aspect of the present disclosure includes a dryer including a first cabinet, and a drum rotatably mounted in the first cabinet; a refresher including a second cabinet disposed on one side of the first cabinet and having an inner space for receiving laundry; a first supply air duct for supplying air into the drum; a second supply air duct for supplying air into the inner space of the second cabinet; and a heating device for heating air flowing into the first supply air duct and the second supply air duct, and disposed in the first cabinet and disposed under the drum, thereby supplying hot air to the dryer and the refresher by using a single heating device.

Inventors: Lee; Yunhi (Seoul, KR), Kim; Jaehyun (Seoul, KR), Yoo; Hyunsun (Seoul, KR)

Applicant: LG ELECTRONICS INC. (Seoul, KR)

Family ID: 1000008780876

Assignee: LG ELECTRONICS INC. (Seoul, KR)

Appl. No.: 17/827082

Filed: May 27, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220380963 A1	Dec. 01, 2022

Foreign Application Priority Data

KR	10-2021-0069528	May. 28, 2021
KR	10-2021-0071149	Jun. 01, 2021
KR	10-2021-0110914	Aug. 23, 2021
KR	10-2021-0110915	Aug. 23, 2021
KR	10-2021-0128828	Sep. 29, 2021
KR	10-2021-0128829	Sep. 29, 2021

Publication Classification

Int. Cl.: **D06F58/10** (20060101); **D06F29/00** (20060101); **D06F33/32** (20200101); **D06F58/04** (20060101); **D06F58/20** (20060101); **D06F58/26** (20060101); **D06F58/38** (20200101); **D06F73/02** (20060101); D06F103/32 (20200101); D06F103/50 (20200101); D06F105/20 (20200101); D06F105/26 (20200101)

U.S. Cl.:

CPC **D06F58/10** (20130101); **D06F29/005** (20130101); **D06F33/32** (20200201); **D06F58/04** (20130101); **D06F58/20** (20130101); **D06F58/206** (20130101); **D06F58/26** (20130101); **D06F58/38** (20200201); **D06F73/02** (20130101); D06F2103/32 (20200201); D06F2103/50 (20200201); D06F2105/20 (20200201); D06F2105/26 (20200201)

Field of Classification Search

CPC: D06F (29/005); D06F (33/32); D06F (39/04); D06F (58/10); D06F (58/206); D06F (58/26); D06F (58/38); D06F (73/02); D06F (2103/32); D06F (2103/50); D06F (2105/20); D06F (2105/26)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7320234	12/2007	Hershey et al.	N/A	N/A
9359714	12/2015	Contarini	N/A	D06F 58/203
9372031	12/2015	Contarini	N/A	F26B 21/086
9435069	12/2015	Contarini	N/A	D06F 58/206
2002/0017117	12/2001	Sunshine et al.	N/A	N/A
2004/0194339	12/2003	Johnson et al.	N/A	N/A
2005/0155393	12/2004	Wright et al.	N/A	N/A
2006/0112585	12/2005	Choi et al.	N/A	N/A
2006/0137210	12/2005	Lee et al.	N/A	N/A
2006/0156765	12/2005	Sunshine	68/19	D06F 39/12
2007/0151300	12/2006	Sunshine	N/A	N/A
2007/0151301	12/2006	Kendall et al.	N/A	N/A
2007/0169519	12/2006	Hershey et al.	N/A	N/A
2007/0256457	12/2006	Kendall	68/3R	D06F 29/00
2008/0229515	12/2007	Hong et al.	N/A	N/A
2009/0126421	12/2008	Kim et al.	N/A	N/A

2010/0299976	12/2009	Roselle et al.	N/A	N/A
2011/0132043	12/2010	Kim	N/A	N/A
2011/0185511	12/2010	Ryoo et al.	N/A	N/A
2012/0260520	12/2011	Hong	34/604	D06F 58/20
2014/0026433	12/2013	Bison	34/73	D06F 39/12
2016/0186374	12/2015	Ryoo et al.	N/A	N/A
2018/0230640	12/2017	Bilionis	N/A	D06F 58/48
2018/0340285	12/2017	Choi	N/A	D06F 31/00
2018/0340288	12/2017	Kim et al.	N/A	N/A
2020/0240065	12/2019	Underly et al.	N/A	N/A
2021/0148029	12/2020	Lv et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103348053	12/2012	CN	N/A
104018328	12/2013	CN	N/A
105316890	12/2015	CN	N/A
106032612	12/2015	CN	N/A
106283485	12/2016	CN	N/A
108301165	12/2017	CN	N/A
109554880	12/2018	CN	D06F 29/005
109582306	12/2018	CN	N/A
209652609	12/2018	CN	N/A
209686107	12/2018	CN	N/A
111996767	12/2019	CN	N/A
10 2006 015 840	12/2006	DE	N/A
10 2008 006 111	12/2008	DE	N/A
10 2008 064 737	12/2015	DE	N/A
1 029 961	12/1999	EP	N/A
3 940 134	12/2021	EP	N/A
2004-159859	12/2003	JP	N/A
2008-307151	12/2007	JP	N/A
10-2005-0066534	12/2004	KR	N/A
10-2006-0042568	12/2005	KR	N/A
10-2006-0046802	12/2005	KR	N/A
10-2006-0060211	12/2005	KR	N/A
10-0587360	12/2005	KR	N/A
10-2006-0111128	12/2005	KR	N/A
10-0658842	12/2005	KR	N/A
10-0674718	12/2006	KR	N/A
10-0839519	12/2007	KR	N/A
10-2008-0100964	12/2007	KR	N/A
10-2010-0025981	12/2009	KR	N/A
10-2019-0131259	12/2018	KR	N/A
10-2120993	12/2019	KR	N/A
10-2020-0109194	12/2019	KR	N/A
10-2200698	12/2020	KR	N/A
10-2254903	12/2020	KR	N/A
WO 2007/148894	12/2006	WO	N/A
WO2008/066539	12/2007	WO	N/A

WO 2011/149320	12/2010	WO	N/A
WO 2014/017004	12/2013	WO	N/A
WO 2017/119673	12/2016	WO	N/A
WO 2019/141063	12/2018	WO	N/A
WO 2019/154266	12/2018	WO	N/A
WO 2021/083006	12/2020	WO	N/A

OTHER PUBLICATIONS

Machine translation of CN 109554880 A to Wang et al. (Year: 2019). cited by examiner

Primary Examiner: Perrin; Joseph L.

Attorney, Agent or Firm: Birch, Stewart, Kolasch & Birch, LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) This application claims the priority benefit of Korean Patent Application No. 10-2021-0069528, filed on May 28, 2021 in the Republic of Korea, Korean Patent Application No. 10-2021-0071149, filed on Jun. 1, 2021 in the Republic of Korea, Korean Patent Application No. 10-2021-0110914, filed on Aug. 23, 2021 in the Republic of Korea, Korean Patent Application No. 10-2021-0110915, filed on Aug. 23, 2021 in the Republic of Korea, Korean Patent Application No. 10-2021-0128828, filed on Sep. 29, 2021 in the Republic of Korea, and Korean Patent Application No. 10-2021-0128829, filed on Sep. 29, 2021 in the Republic of Korea, which are hereby incorporated by reference in their entirety for all purposes as if fully set forth herein.

BACKGROUND OF THE INVENTION

1. Field of the Invention

(2) The present disclosure relates to a laundry treating apparatus, and more particularly to a laundry treating apparatus including a plurality of laundry treating machines.

2. Description of the Background Art

(3) A washing machine, a dryer, and refreshers, which are provided for treating clothes, are installed in different spaces, such as a kitchen, a utility room, and an outdoor space, according to usage in a residential space.

(4) Korean Laid-Open Patent Publication No. 10-2020-0109194 discloses a washing machine. The washing machine washes laundry by supplying water and detergent into a tub and a drum and by rotating the drum in which the laundry is placed. In the washing machine, water from an external water source is supplied into the tub or the drum, and a pump is used to circulate the water in the tub to the drum or to discharge the water in the tub to the outside. The washing machine is generally installed in the kitchen or the utility room for the supply and discharge of water.

(5) The washing machine separately includes a heater for heating air, a blower fan, and a steam generator, to dry or sterilize the laundry.

(6) Korean Patent No. 10-2120993 discloses a dryer. The dryer may dry the laundry, placed in the drum, by heating air using a heating means and a blower fan and by supplying the heated air into the drum. The dryer is generally disposed adjacent to the washing machine, so as to dry the washed laundry and to allow a user to easily load the laundry containing moisture into the dryer.

(7) By using the steam generator for generating steam and spraying the steam into the drum, the dryer may sterilize the laundry or may remove wrinkles of the laundry. Water may be supplied into the dryer for generating the steam, and water not changed into steam may be reused or may be

discharged to the outside. Further, in order to deodorize the dried laundry, the dryer may further have a deodorization function for filtering the circulated air.

(8) Korean Patent No. 10-2254903 discloses a refresher. The refresher may perform functions, such as drying, deodorizing, de-wrinkling, de-static and/or sterilization (hereinafter referred to as “refreshing”).

(9) The refresher is used for treating clothes, such as suits and coats, which are frequently used by a user after washing. Generally, the user hangs the clothes, such as suits and coats, in a wardrobe. Accordingly, the refresher may be installed adjacent to the wardrobe, or may be installed instead of the wardrobe, in a dressing room, a living room, or a bedroom. Further, not only for the clothes or garments, the refresher may be used for all washable items, such as shoes, socks, gloves, hats, scarves, etc., which are frequently worn by users, as well as dolls, towels, blankets, etc., which are frequently used by users.

(10) However, the existing laundry treating machines, which are installed in different spaces, have a problem in that a user needs to move the laundry items, which are sorted by a user, to the respective laundry treating machines performing corresponding laundry treating processes, thereby requiring a longer workflow, and making the clothes treating processes uncomfortable.

(11) In addition, as the refresher is installed in a different place from the washing machine and the dryer, it is cumbersome for the user to move the washed wet clothes or the dried clothes to the place where the refresher is installed.

(12) Furthermore, each of the existing laundry treating machines for treating laundry using hot air and steam separately requires water supply equipment, drainage equipment, an air heater, a steam generator, a pump, a blower fan, an air passage, a steam passage, etc., thereby causing a problem in that a space for receiving clothes is reduced. In addition, as each of the machines includes the heater, the steam generator, etc., there is a problem in that costs and energy consumption of the entire system may increase.

(13) Further, the existing refresher has a problem in that a machine room that generates hot air is disposed at a lower portion of the inner space of the refresher, such that the inner space of the refresher decreases in height. Thus, clothes having a great height, such as a long coat, may not be received in the existing refresher.

SUMMARY OF THE INVENTION

(14) It is an object of the present disclosure to solve the above and other problems.

(15) It is another object of the present disclosure to provide a laundry treating apparatus including a plurality of laundry treating machines.

(16) It is yet another object of the present disclosure to provide a laundry treating apparatus including a washing machine, a dryer, and a refresher.

(17) It is still another object of the present disclosure to provide a laundry treating apparatus capable of performing washing, drying, and refreshing of the laundry in the same space.

(18) It is still another object of the present disclosure to provide a laundry treating apparatus capable of minimizing a user's workflow required for laundry treatment.

(19) It is still another object of the present disclosure to provide a laundry treating apparatus capable of treating laundry which may not be subjected to high temperature drying in a space where washing and drying are performed.

(20) It is still another object of the present disclosure to provide a laundry treating apparatus with improved workability in washing, drying, and refreshing processes of the laundry.

(21) It is still another object of the present disclosure to provide a laundry treating apparatus with reduced vibrations generated in the entire system.

(22) It is still another object of the present disclosure to provide a laundry treating apparatus capable of improving user convenience in manipulation by lowering the height of components, such as a door, a control panel, etc., which require manipulation by a user.

(23) It is still another object of the present disclosure to provide a laundry treating apparatus having

a hot air passage for supplying air to the washing machine, the dryer, and the refresher.

(24) It is still another object of the present disclosure to provide a laundry treating apparatus capable of minimizing a length of a hot air passage for supplying air to the washing machine, the dryer, and the refresher.

(25) It is still another object of the present disclosure to provide a refresher having an extended longitudinal width.

(26) It is still another object of the present disclosure to provide a laundry treating apparatus having a refresher with an extended longitudinal width.

(27) It is still another object of the present disclosure to provide a laundry treating apparatus having an extended vertical height of a laundry receiving space.

(28) It is still another object of the present disclosure to provide a laundry treating apparatus having an extended vertical height of a laundry receiving space.

(29) It is still another object of the present disclosure to provide a laundry treating apparatus having an extended vertical height of a laundry receiving space in the refresher.

(30) It is still another object of the present disclosure to provide a laundry treating apparatus using a difference between a longitudinal width of the refresher and a longitudinal width of the washing machine/dryer.

(31) It is still another object of the present disclosure to provide a laundry treating apparatus having a steam passage for supplying steam to the washing machine, the dryer, and the refresher.

(32) It is still another object of the present disclosure to provide a laundry treating apparatus capable of minimizing a steam passage for supplying steam to the washing machine, the dryer, and the refresher.

(33) It is still another object of the present disclosure to provide a laundry treating apparatus capable of supplying hot air to the plurality of laundry treating machines using a single heating device.

(34) It is still another object of the present disclosure to provide a laundry treating apparatus capable of supplying steam to the plurality of laundry treating machines using a single heating device.

(35) It is still another object of the present disclosure to provide a laundry treating apparatus capable of facilitating discharge of condensate generated by the heating device.

(36) It is still another object of the present disclosure to provide a laundry treating apparatus capable of facilitating the supply of water for steam generation and discharge of the water.

(37) It is still another object of the present disclosure to provide a laundry treating apparatus capable of minimizing a length of a hot air passage for supplying air to the dryer and the refresher.

(38) It is still another object of the present disclosure to provide a laundry treating apparatus capable of optimizing the placement of a fan for supplying hot air to the dryer and the refresher.

(39) It is still another object of the present disclosure to provide a laundry treating apparatus capable of minimizing heat loss of hot air supplied to the refresher.

(40) It is still another object of the present disclosure to provide a laundry treating apparatus capable of minimizing a length of a supply air duct and an exhaust air duct which are connected to the refresher.

(41) It is still another object of the present disclosure to provide a laundry treating apparatus capable of discharging condensate generated by the heating device, without using separate pump equipment.

(42) It is still another object of the present disclosure to provide a laundry treating apparatus capable of managing condensate by using a drain pump of the washing machine.

(43) It is still another object of the present disclosure to provide a laundry treating apparatus in which temperature of hot air supplied to the refresher is lower than that of the dryer.

(44) It is still another object of the present disclosure to provide a laundry treating apparatus capable of using the condensate generated by the heating device.

- (45) It is still another object of the present disclosure to provide a laundry treating apparatus capable of minimizing vibrations generated in the washing machine.
- (46) It is still another object of the present disclosure to provide a laundry treating apparatus capable of reducing rocking of cabinets of the washing machine.
- (47) It is still another object of the present disclosure to provide a laundry treating apparatus in which the plurality of laundry treating machines are coupled to each other.
- (48) It is still another object of the present disclosure to provide a laundry treating apparatus capable of supplying hot air to an upper side of the refresher.
- (49) It is still another object of the present disclosure to provide a laundry treating apparatus capable of recovering hot air from the upper side of the refresher.
- (50) It is still another object of the present disclosure to provide a laundry treating apparatus capable of lowering the height of doors of the washing machine and the dryer.
- (51) It is still another object of the present disclosure to provide a laundry treating apparatus capable of lowering the height of a laundry loading opening, through which the laundry is loaded, and the height of a control panel.
- (52) It is still another object of the present disclosure to provide a laundry treating apparatus capable of allowing users to easily carry the washed laundry.
- (53) It is still another object of the present disclosure to provide a laundry treating apparatus capable of preventing air, heated and dehumidified by the heating device, from being directly discharged to users.
- (54) It is still another object of the present disclosure to provide a laundry treating apparatus having a passage formed at a high position for indoor dehumidification.
- (55) It is still another object of the present disclosure to provide a laundry treating apparatus having an aligned upper end.
- (56) It is still another object of the present disclosure to provide a laundry treating apparatus having an aligned front surface.
- (57) It is still another object of the present disclosure to provide a laundry treating apparatus having a height which is constant in the horizontal direction.
- (58) It is still another object of the present disclosure to provide a laundry treating apparatus having a constant longitudinal width.
- (59) It is still another object of the present disclosure to provide a laundry treating apparatus capable of preventing collision of the laundry treating apparatus with surrounding structures when the laundry treating apparatus is installed.
- (60) The objects of the present disclosure are not limited to the aforementioned objects and other objects not described herein will be clearly understood by those skilled in the art from the following description.
- (61) In accordance with an aspect of the present disclosure, the above and other objects can be accomplished by providing a laundry treating apparatus including a dryer including a first cabinet having a first laundry loading opening.
- (62) The dryer may have a first door for opening and closing the first laundry loading opening.
- (63) The dryer may include a first drum rotatably disposed in the first cabinet.
- (64) The laundry treating apparatus may include a washing machine including a second cabinet vertically disposed with respect to the first cabinet.
- (65) The second cabinet may include a second laundry loading opening.
- (66) The washing machine may include a second door for opening and closing the second laundry loading opening.
- (67) The washing machine may include a tub disposed in the second cabinet.
- (68) The washing machine may include a second drum rotatably disposed in the tub.
- (69) The laundry treating apparatus may include a refresher disposed on one side of the dryer.
- (70) The refresher may be disposed on one side of the washing machine.

- (71) The refresher may include a third cabinet having an opening.
- (72) The refresher may include a third door for opening and closing the opening.
- (73) A space for receiving laundry may be formed in the refresher.
- (74) The laundry treating apparatus may include a duct system connected to the dryer and the refresher.
- (75) The duct system may include a first supply air duct for supplying air into the first drum.
- (76) The duct system may include a second supply air duct for supplying air into an inner space of the refresher.
- (77) The duct system may include a heat exchange channel connected to the first supply air duct and the second supply air duct.
- (78) The laundry treating apparatus may include a heating device for heating air passing through the heat exchange channel.
- (79) The laundry treating apparatus may include a first laundry treating machine including a cabinet having a laundry loading opening, and a door for opening and closing the laundry treating opening.
- (80) The first laundry treating machine may include a drum rotatably disposed in the cabinet.
- (81) The laundry treating apparatus may include a second laundry treating machine including a cabinet having a laundry loading opening, and a door for opening and closing the laundry treating opening.
- (82) A space for receiving laundry may be formed in the second laundry treating machine.
- (83) The duct system may include a first supply air duct for supplying air into the drum of the first laundry treating machine.
- (84) The duct system may include a second supply air duct for supplying air into the inner space of the second laundry treating machine.
- (85) The duct system may include a heat exchange channel connected to the first supply air duct and the second supply air duct.
- (86) The heat exchange channel may include an inlet end through which air is introduced, and a discharge end through which the air is discharged.
- (87) The laundry treating apparatus may include an integrated frame, having a first laundry loading opening and a second laundry loading opening which are vertically spaced apart from each other, and having a horizontal partition wall disposed at a middle portion thereof.
- (88) A drying room may be formed between an upper panel and the horizontal partition wall of the integrated frame.
- (89) The first drum may be disposed in the drying room.
- (90) A washing room may be formed between a lower panel and the horizontal partition wall of the integrated frame.
- (91) The tub and the second drum may be disposed in the washing room.
- (92) The laundry treating apparatus may include a side frame disposed on one side of the integrated frame.
- (93) The second supply air duct may supply air into the side frame.
- (94) The laundry treating apparatus may include a single frame in which a vertical partition wall is disposed.
- (95) The horizontal partition wall may be disposed between the vertical partition wall and the one side panel of the single frame.
- (96) The washing room and the drying room may be vertically separated by the horizontal partition wall between the one side panel and the vertical partition wall.
- (97) A refreshing room for treating clothes may be formed between the vertical partition wall and the other panel of the single frame.
- (98) The dryer may be disposed on one side of the washing machine in a direction horizontal to the washing machine.

- (99) The refresher may be disposed over the dryer and the washing machine.
- (100) The laundry treating apparatus may include a supply air duct connecting the heating device and the refresher.
- (101) The supply air duct may supply the air, heated by the heating device, into the inner space of the refresher.
- (102) The heating device may be disposed under the first drum.
- (103) The washing machine may be disposed over the dryer.
- (104) The heating device may be disposed between the first drum and the tub.
- (105) The heating device may include a heat exchange unit for heating air supplied to the refresher.
- (106) The supply air duct may extend downwardly from the heating device.
- (107) The supply air duct may be connected to a supply air hole formed at a lower portion of the refresher.
- (108) The laundry treating apparatus may include an exhaust air duct extending upwardly from the heating device.
- (109) The exhaust air duct may be connected to an exhaust air hole formed at an upper portion of the refresher.
- (110) The supply air duct may extend upwardly from the heating device.
- (111) The supply air duct may be connected to a supply air hole formed at an upper portion of the refresher.
- (112) The laundry treating apparatus may include an exhaust air duct extending downwardly from the heating device.
- (113) The exhaust air duct may be connected to an exhaust air hole formed at a lower portion of the refresher.
- (114) The dryer may be disposed over the washing machine.
- (115) The washing machine may include a drain pump for discharging water in the tub.
- (116) The heating device may be disposed under the tub.
- (117) The laundry treating apparatus may include a drain pan disposed under the heat exchange unit.
- (118) The washing machine may include an upper panel coupled to a lower portion of the dryer.
- (119) The washing machine may include a suspension connecting the cabinet and the tub of the washing machine.
- (120) The cabinet of the washing machine may include a side panel disposed between the tub and the cabinet of the refresher.
- (121) The side panel may face the cabinet of the refresher.
- (122) The side panel may be coupled to the cabinet of the refresher.
- (123) The second drum may be open toward the second laundry loading opening, so that laundry placed therein may be unloaded through the second laundry loading opening.
- (124) The first drum may be disposed under the second drum.
- (125) The first drum may be open toward the first laundry loading opening, so that the laundry unloaded from the second drum, may be loaded through the first laundry loading opening.
- (126) The laundry treating apparatus may include a dehumidification duct for discharging the air, heated by the heating device, outside of the laundry treating apparatus.
- (127) An upper end of a front surface of the laundry treating apparatus may be aligned horizontally.
- (128) An upper end of a front surface of any one, which is located uppermost, among the dryer, the washing machine, and the heating device, may be aligned with an upper end of a front surface of the refresher.
- (129) Other detailed matters of the exemplary embodiments are included in the detailed description and the drawings.

Effects of the Invention

- (130) According to at least one of the embodiments of the present disclosure, there is provided a

laundry treating apparatus including a plurality of laundry treating machines.

(131) According to at least one of the embodiments of the present disclosure, there is provided a laundry treating apparatus including a washing machine, a dryer, and a refresher.

(132) According to at least one of the embodiments of the present disclosure, there is provided a laundry treating apparatus, in which the washing machine, the dryer, and the refresher are disposed in the same space, thereby performing washing, drying, and refreshing in the same space.

(133) According to at least one of the embodiments of the present disclosure, there is provided a laundry treating apparatus, in which laundry may be treated in the same space regardless of the type of laundry.

(134) According to at least one of the embodiments of the present disclosure, there is provided a laundry treating apparatus, in which when washing, drying, and refreshing are performed, a user's load (e.g., amount of work, workflow, etc.) for moving the laundry may be reduced.

(135) According to at least one of the embodiments of the present disclosure, there is provided a laundry treating apparatus capable of treating laundry, which may not be subjected to high temperature drying, in the same space where washing and drying are performed.

(136) According to at least one of the embodiments of the present disclosure, there is provided a laundry treating apparatus, in which the washing machine and the refresher share one surface, thereby reducing vibrations generated in the washing machine.

(137) According to at least one of the embodiments of the present disclosure, there is provided a laundry treating apparatus, in which the heating device of the refresher is disposed between the washing machine and the dryer, thereby extending the height of a laundry receiving space in the refresher.

(138) According to at least one of the embodiments of the present disclosure, a hot air passage is provided in a rear space of the refresher, such that the entire system may have a uniform longitudinal width.

(139) According to at least one of the embodiments of the present disclosure, the heating device is disposed at a middle height of the refresher, thereby minimizing the length of a hot air supply passage for supplying hot air to each of the washing machine, the dryer, and the refresher.

(140) According to at least one of the embodiments of the present disclosure, a steam generator is disposed at a middle height of the refresher, thereby minimizing the length of a steam supply passage for supplying steam to each of the washing machine, the dryer, and the refresher.

(141) According to at least one of the embodiments of the present disclosure, hot air may be supplied to each of the washing machine, the dryer, and the refresher by using a single heating device.

(142) According to at least one of the embodiments of the present disclosure, steam may be supplied to each of the washing machine, the dryer, and the refresher by using a single steam generator.

(143) According to at least one of the embodiments of the present disclosure, condensate may be managed easily by discharging condensate, generated in an evaporator, through a drain pump of the washing machine.

(144) According to at least one of the embodiments of the present disclosure, steam may be generated easily by supplying water, required for generating steam, through a water supply pipe of the washing machine.

(145) According to at least one of the embodiments of the present disclosure, the heating device for supplying hot air to the refresher may be disposed on a lateral side, thereby increasing the height of an inner space of the refresher.

(146) According to at least one of the embodiments of the present disclosure, hot air may be supplied to the refresher by using the heating device of the dryer, thereby increasing a volume of the inner space of the refresher.

(147) According to at least one of the embodiments of the present disclosure, the heating device is

disposed at a lower side of the laundry treating apparatus, thereby minimizing the length of the hot air passage connected to the dryer and the refresher.

(148) According to at least one of the embodiments of the present disclosure, a supply air duct, connecting the heating device and the refresher, is reduced in length, thereby minimizing heat loss of the hot air supplied to the refresher.

(149) According to at least one of the embodiments of the present disclosure, condensate generated in the evaporator may be discharged through the drain pump of the washing machine, thereby allowing easy management of the condensate.

(150) According to at least one of the embodiments of the present disclosure, water in a tub and the condensate generated in the heating device are discharged through a single drain pump, thereby reducing the number of components required for drainage.

(151) According to at least one of the embodiments of the present disclosure, a cabinet of the washing machine is coupled to a cabinet of the refresher, thereby reducing vibrations generated in the washing machine.

(152) According to at least one of the embodiments of the present disclosure, as the washing machine is disposed over the dryer, heavy laundry after washing may be dropped to a laundry loading opening of the dryer, thereby allowing a user to easily move the laundry.

(153) According to at least one of the embodiments of the present disclosure, an upper end of the laundry treating apparatus is aligned, such that the plurality of laundry treating machines may be easily coupled to each other.

(154) Further scope of applicability of the invention will become apparent from the detailed description given hereinafter. However, it should be understood that the detailed description and specific examples, while indicating embodiments of the invention, are given by way of illustration only, since various changes and modifications within the scope of the invention will become apparent to those skilled in the art from this detailed description.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The present invention will become more fully understood from the detailed description given hereinbelow and the accompanying drawings which are given by way of illustration only, and thus are not limitative of the present invention.

(2) FIG. 1 is a perspective view of a laundry treating apparatus according to at least one embodiment of the present disclosure.

(3) FIG. 2 is a longitudinal cross-sectional view of a laundry treating apparatus according to at least one embodiment of the present disclosure.

(4) FIG. 3 is a longitudinal cross-sectional view of a laundry treating apparatus according to at least one embodiment of the present disclosure.

(5) FIG. 4 is a conceptual diagram illustrating a duct system of a laundry treating apparatus according to at least one embodiment of the present disclosure.

(6) FIG. 5 is a perspective view of a heating device according to at least one embodiment of the present disclosure.

(7) FIG. 6 is another perspective view of a heating device according to at least one embodiment of the present disclosure.

(8) FIG. 7 is yet another perspective view of a heating device according to at least one embodiment of the present disclosure.

(9) FIG. 8 is a diagram explaining an operation of a heating device according to at least one embodiment of the present disclosure.

(10) FIG. 9 is a diagram illustrating a portion of a rear surface of a laundry treating apparatus

according to at least one embodiment of the present disclosure.

(11) FIG. **10** is a diagram illustrating assembly of a laundry treating apparatus according to at least one embodiment of the present disclosure.

(12) FIG. **11** is a rear perspective view of a laundry treating apparatus according to at least one embodiment of the present disclosure.

(13) FIG. **12** is a longitudinal cross-sectional view of a laundry treating apparatus according to at least one embodiment of the present disclosure.

(14) FIG. **13** is a rear perspective view of a laundry treating apparatus according to at least one embodiment of the present disclosure.

(15) FIG. **14** is a perspective view of a laundry treating apparatus according to at least one embodiment of the present disclosure.

(16) FIG. **15** is a longitudinal cross-sectional view of a laundry treating apparatus according to at least one embodiment of the present disclosure.

(17) FIG. **16** is a longitudinal cross-sectional view of a laundry treating apparatus according to at least one embodiment of the present disclosure.

(18) FIG. **17** is conceptual diagram illustrating a duct system of a laundry treating apparatus according to at least one embodiment of the present disclosure.

(19) FIG. **18** is a rear perspective view of a laundry treating apparatus according to at least one embodiment of the present disclosure.

(20) FIG. **19** is a view illustrating a lower structure of a laundry treating apparatus according to at least one embodiment of the present disclosure.

(21) FIG. **20** is a rear perspective view of a laundry treating apparatus according to at least one embodiment of the present disclosure.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

(22) Hereinafter, the present disclosure will be described in detail with reference to the accompanying drawings, in which the same reference numerals are used throughout the drawings to designate the same or similar components, and a redundant description thereof will be omitted.

(23) Terms “module” and “unit” for elements used in the following description are given simply in view of the ease of the description, and do not have a distinguishing meaning or role.

(24) It will be noted that a detailed description of known arts will be omitted if it is determined that the detailed description of the known arts can obscure the embodiments of the invention. Further, the accompanying drawings are used to help easily understand various technical features and it should be understood that the embodiments presented herein are not limited by the accompanying drawings. As such, the present disclosure should be construed to extend to any alterations, equivalents and substitutes in addition to those which are particularly set out in the accompanying drawings.

(25) It will be understood that, although the terms first, second, etc., may be used herein to describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another.

(26) It will be understood that when an element is referred to as being “connected” or “coupled” to another element, it can be directly connected or coupled to the other element or intervening elements may be present. In contrast, when an element is referred to as being “directly connected” or “directly coupled” to another element, there are no intervening elements present.

(27) As used herein, the singular forms are intended to include the plural forms as well, unless the context clearly indicates otherwise.

(28) The laundry treating apparatus according to the embodiments of the present disclosure may include one or more laundry treating machines. The laundry treating machines refer to devices for washing, drying, and/or refreshing objects (e.g., clothes, towels, blankets, etc.).

(29) The laundry treating apparatus may include a plurality of laundry treating machines of the same type. For example, the laundry treating apparatus may include two or more dryers **1**. For

example, the laundry treating apparatus may include two or more washing machines **2**. For example, the laundry treating apparatus may include two or more refreshers **3**.

(30) The laundry treating apparatus may include different types of laundry treating machines. For example, the laundry treating apparatus may include the dryer **1**, the washing machine **2**, and the refresher **3**.

(31) The laundry treating apparatus may include laundry treating machines of the same type and laundry treating machines of types different from the type. For example, the laundry treating apparatus may include two or more washing machines, one dryer, and one refresher. For example, the laundry treating apparatus may include one washing machine, one dryer, and two or more refreshers.

(32) The laundry treating apparatus of the present disclosure is not limited to the type and number of the laundry treating machines, and may include various combinations thereof. Hereinafter, the laundry treating apparatus including one dryer **1**, one washing machine **2**, and one refresher **3** will be described as an example, but the present disclosure is not limited thereto.

(33) The dryer **1**, the washing machine **2**, and the refresher **3** may be referred to as any one of first to third laundry treating machines, respectively. For example, the dryer **1** may be referred to as the “first laundry treating machine,” the washing machine **2** may be referred to as the “second laundry treating machine,” and the refresher **3** may be referred to as the “third laundry treating machine.”

(34) Hereinafter, it will be understood that, although the terms first, second, third, etc., may be used herein to describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another. These elements are not limited to the terms and may include other ordinal numbers. The elements may be used independently without including the ordinal numbers. For example, the elements of the dryer **1** may include the ordinal number “first,” the elements of the washing machine **2** may include the ordinal number “second,” and the elements of the refresher **3** may include the ordinal number “third.” However, the elements of the dryer **1**, the washing machine **2**, and the refresher **3** are not limited to these terms, and may include other ordinal numbers or may be used independently without including the ordinal numbers.

(35) A laundry treating apparatus may include a controller **81** for controlling operation of a dryer **1**, a washing machine **2**, a refresher **3**, and a heating device **50**. The controller **81** may be mounted in a Printed Circuit Board (PCB). The controller **81** may control the dryer **1**, the washing machine **2**, the refresher **3**, and the heating device **50** based on an electric signal received from the control panel **8**. The controller **81** may communicate with the control panel **8**.

(36) The dryer **1** and the washing machine **2** may be vertically disposed. The control panel **8** may be disposed between the dryer **1** and the washing machine **2**. The control panel **8** and the refresher **3** may be vertically disposed.

(37) A user may input a command to the laundry treating apparatus through the control panel **8**. By manipulating the control panel **8**, the user may control the operation of the dryer **1**, the washing machine **2**, and the refresher **3**. By manipulating the control panel **8**, the user may control the operation of the heating device **50**. The control panel **8** may transmit an electrical signal, input by the user's manipulation, to the controller **81**.

(38) A space for providing the PCB may be formed in the control panel **8**. A controller may be mounted in the PCB. The controller may be the controller **81**.

(39) Alternatively, the controller may be disposed on a rear surface of the control panel **8**. The space for providing the PCB may be formed on the rear surface of the control panel **8**. The controller **81** may be mounted in the PCB.

(40) Alternatively, at least some of the dryer **1**, the washing machine **2**, the refresher **3**, and a machine room **S** may include respective controllers for controlling each operation thereof. Even in this case, the respective controllers may be mounted in the PCB. The respective controllers may communicate with each other. In some cases, at least one controller may be an upper level

controller that may control other controllers and devices.

(41) The control panel **8** may display an operating state of the laundry treating apparatus. The user may check information on the operating state of the laundry treating apparatus through the control panel **8**.

(42) The laundry treating apparatus may include a heating device **50**. The heating device **50** may supply hot air to the dryer **1**. The heating device **50** may supply hot air to the refresher **3**. The heating device **50** may supply hot air to the washing machine **2**. The hot air, supplied to the respective laundry treating machines, may be drawn into the heating device **50** again for circulation.

(43) However, without circulating the hot air supplied to each of the dryer **1**, the washing machine **2**, and the refresher **3**, the laundry treating apparatus may discharge the hot air to the outside. That is, the laundry treating apparatus may discharge the hot air supplied to a tub **23** of the washing machine **2** to the outside of the washing machine **2**, may discharge the hot air supplied to a first drum **13** of the dryer **1** to the outside of the dryer **1**, and may discharge the hot air supplied to an inner space **33** of the refresher **3** to the outside of the refresher **3**.

(44) The laundry treating apparatus may include the machine room S (see FIG. 2). The machine room S may provide a space in which the heating device **50** is disposed. The machine room S may be a concept that refers to a space in which the heating device **50** and components other than the heating device **50** are disposed. In addition to the heating device **50**, a pump, a blower fan, an air passage, a steam device, a stream passage, a dehumidification device, a controller, a motor, a fan housing, and the like may be disposed in the machine room S. The machine room S may provide the space in which the aforementioned movable elements (a pump, a blower fan, an air passage, a steam device, a stream passage, a dehumidification device, a controller, a motor, and a fan housing) are disposed.

(45) In the present disclosure, the machine room S may refer to the space in which the heating device **50** is disposed, or may be an upper concept that encompasses the heating device **50**.

(46) The machine room S may include a separate case. When the machine room S includes the separate case, the machine room S may be separated from a first cabinet **10** and a second cabinet **20**. Unlike the example, the machine room S may be disposed in any one of first to third cabinets **10**, **20**, and **30**. In the case where the machine room S is disposed in any one of the first to third cabinets **10**, **20**, and **30**, the machine room S may be a concept that refers to a space in which various components including the heating device **50** are disposed. That is, in the case where the machine room S is disposed in any one of the first to third cabinets **10**, **20**, and **30**, the machine room S may refer to a portion of the inner space of the first to third cabinets **10**, **20**, and **30**.

(47) The machine room S, the dryer **1**, and the washing machine **2** may be vertically disposed. The machine room S may be disposed on an upper side of the dryer **1** and the washing machine **2**. The machine room S may be disposed between the dryer **1** and the washing machine **2**. The machine room S may be disposed on a lower side of the dryer **1** and the washing machine **2**. Unlike the example, the machine room S and the refresher **3** may be vertically disposed. The machine room S may be disposed on the upper side or the lower side of the refresher **3**.

(48) The heating device **50** may supply hot air to the dryer **1**. The heating device **50** may recover the hot air supplied to the dryer **1**.

(49) The heating device **50** may supply hot air to the washing machine **2**. The heating device **50** may recover the hot air supplied to the washing machine **2**.

(50) The heating device **50** may supply hot air to the refresher **3**. The heating device **50** may recover the hot air supplied to the refresher **3**.

(51) The heating device **50** may supply steam to the dryer **1**. The heating device **50** may supply steam to the washing machine **2**. The heating device **50** may supply steam to the refresher **3**.

(52) The heating device **50** may include a heat pump device. The heat pump device may include a compressor **51**, a condenser **52**, an evaporator **53**, and an expansion device **54** (see FIG. 5). The

heating device **50** may include a fan **60** (see FIG. 5). The heat pump device may be referred to as a “heat exchange unit.”

(53) The heating device **50** may include a heat exchange unit for heating air flowing through a heat exchange channel **42** (see FIG. 5). The heat exchange unit may be a heat pump device connected by a refrigerant passage. The heat exchange unit may be a heater using electricity as power. The heat exchange unit may be a heating device. The heat exchange unit may include the heater and a cooler. The cooler may be disposed on an upstream side of the heater. The cooler may be disposed in the heat exchange channel **42**. The cooler may dehumidify and cool air passing through the heat exchange channel **42**.

(54) The heating device **50**, the dryer **1**, and the washing machine **2** may be vertically disposed. The heating device **50** may be disposed on the upper side of the dryer **1** and the washing machine **2**, may be disposed between the dryer **1** and the washing machine **2**, or may be disposed under the dryer **1** and the washing machine **2**.

(55) The heating device **50** and the refresher **3** may be vertically disposed. The heating device **50** may be disposed in a rear space of the refresher **3**.

(56) The heating device **50** may be disposed in the first cabinet **10**. The heating device **50** may also be disposed in the second cabinet **20**. The heating device **50** may also be disposed in the third cabinet **30**.

(57) The dryer **1**, the washing machine **2**, and the heating device **50** (or the machine room **S**) may be vertically arranged, and the refresher **3** may be disposed on a lateral side of the washing machine **2**. The heating device **50** may be disposed on a lateral side of the refresher **3**.

(58) Hereinafter, a laundry treating apparatus **A** according to an aspect of the present disclosure will be described below with reference to FIG. **1**.

(59) The laundry treating apparatus **A** illustrated in FIG. **1** may be an example in which the dryer **1** is disposed over the washing machine **2** and the heating device **50** is disposed between the washing machine **2** and the dryer **1**. However, a vertical arrangement of the dryer **1**, the washing machine **2**, and the heating device **50** is not limited thereto.

(60) The refresher **3** may be disposed on a lateral side of the dryer **1** and the washing machine **2**. For example, the refresher **3** may be disposed on the right side of the dryer **1** and the washing machine **2**. However, an arrangement position of the refresher **3** is not limited to the above example, and the refresher **3** may be disposed on the right side of the dryer **1** and the washing machine **2**.

(61) A longitudinal width of the refresher **3** may be smaller than a front-rear width of the dryer **1** and the washing machine **2**.

(62) A rear case **310**, in which the hot air passage or the steam passage which will be described later is disposed, may be disposed behind the refresher **3**.

(63) The dryer **1** may include the first cabinet **10** having a first laundry loading opening **12** (see FIG. **2**) formed on a front surface thereof, and a first door **11** rotatably coupled to the first cabinet **10**.

(64) By rotating the first door **11**, a user may open the first laundry inlet **12**, and may put the laundry into the first drum **13** through the first laundry inlet **12**.

(65) The washing machine **2** may include a second cabinet **20** having a second laundry loading opening **22** (see FIG. **2**) formed on a front surface, and a second door **21** rotatably coupled to the second cabinet **20**.

(66) By rotating the second door **21**, the user may open the second laundry loading opening **22**, and may load the laundry into the second drum **24** through the second laundry loading opening **22**.

(67) The refresher **3** forms a space in which the laundry is received, and includes a third cabinet **30** having a third laundry loading opening **32** (see FIG. **3**) and a third door **31** rotatably coupled to the cabinet **30**. The third laundry loading opening **32** may be referred to as an “opening.”

(68) By rotating the third door **31**, the user may open the third laundry loading opening **32** and may

load the laundry into the third cabinet **30** through the third laundry loading opening **32**.

(69) Each of the first cabinet **10**, the second cabinet **20**, and the third cabinet **30** may include an upper panel, a lower panel, a front panel, a rear panel, and a side panel. The upper panel may be referred to as an “upper wall.” The lower panel may be referred to as a “lower wall.” The front panel may be referred to as a “front wall.” The rear panel may be referred to as a “rear wall.” The side panel may be referred to as a “side wall.”

(70) Each of the first cabinet **10**, the second cabinet **20**, and the third cabinet **30** may include a pair of side panels. The pair of side panels may be horizontally spaced apart from each other. The side panels may be referred to as “side walls.” The first cabinet **10** may include a first inner wall **106** facing the refresher **3**, and a first outer wall **105** spaced apart from the first inner wall **106**. The second cabinet **20** may include a second inner wall **206** facing the refresher **3**, and a second outer wall **205** spaced apart from the second inner wall **206**. The third cabinet **30** may include a third inner wall **306** facing the dryer **1** and the washing machine **2**, and a third outer wall **305** spaced apart from the third inner wall **306**.

(71) The first cabinet **10** may include a first upper panel **103**, a first lower panel **104**, a first front panel **101**, a first rear panel **102**, and first side panels **105** and **106**.

(72) The second cabinet **20** may include a second upper panel **203**, a second lower panel **204**, a second front panel **201**, a second rear panel **202**, and second side panels **205** and **206**.

(73) The third cabinet **30** may include a third upper panel **303**, a third lower panel **304**, a third front panel **301**, a third rear panel **302**, and third side panels **305** and **306**. The third cabinet **30** may include the third door **31** instead of the third front panel **301**.

(74) The above description of the first to third cabinets **10**, **20**, and **30** may also be applied to the laundry treating apparatus described with reference to FIGS. **1** to **20**.

(75) A plate may be disposed in a space between the dryer **1** and the refresher **3** and in a space between the washing machine **2** and the refresher **3**. The plate may be a damping material. The dryer **1**, the washing machine **2**, and the refresher **3** may be coupled to each other by the plate.

(76) The first upper panel **103** of the dryer **1** and the third upper panel **303** of the refresher **3** may be disposed on the same horizontal plane. The third upper panel **303** of the refresher **3** and the upper wall **313** of the rear case **310** may be disposed on the same horizontal plane.

(77) The first dryer **1** may have a first upper surface **10c**. The first upper surface **10c** may be an upper surface of the first cabinet **10**. The first upper surface **10c** may be an upper surface of the first upper panel **103**.

(78) The refresher **3** may have a third upper surface **30c**. The third upper surface **30c** may be an upper surface of the third cabinet **30**.

(79) The first upper surface **10c** and the third upper surface **30c** may be aligned horizontally. The first upper surface **10c** and the third upper surface **30c** may be disposed on the same horizontal plane.

(80) In the description of the laundry treating apparatus of the present disclosure, the term “aligned” will be defined as follows. The term “aligned” may indicate that components are aligned on a substantially same plane. That is, although components A and B are not disposed on the same plane in a strict sense, it can be said that the components A and B are “aligned” on the same plane even when they are disposed on two planes with a predetermined distance between them. Further, in the description of the laundry treating apparatus of the present disclosure, the phrase “positioned on the same plane” includes a case where components are positioned on a substantially same plane. For example, if a first plane, on which component A is positioned, and a second plane, on which component B is positioned, are spaced apart side by side, it can be said that “components A and B are aligned” and “components A and B are positioned on the same plane.”

(81) The dryer **1** may have a first front surface **10a** or **11a**. The front surface **10a** of the dryer **1** may refer to the front surface of the first cabinet **10**. The first front surface **10a** may be the front surface of the first front panel **101**.

- (82) The first door **11** may have a first front surface **11a**. The front surface **11a** of the dryer **1** may refer to the front surface of the first door **11**.
- (83) The washing machine **2** may have a second front surface **20a** or **21a**. The front surface **20a** of the washing machine **2** may refer to the front surface of the second cabinet **20**. The second front surface **20a** may be the front surface of the second front panel **201**.
- (84) The second door **21** may have the second front surface **21a**. The front surface **21a** of the washing machine **2** may refer to the front surface of the second door **21**.
- (85) The refresher **3** may have a third front surface **31a**. The front surface **31a** of the refresher **3** may refer to the front surface of the third door **31**.
- (86) The front surface **10a** or **11a** of the dryer **1** may be aligned with the front surface **31a** of the refresher **3**. The front surface **20a** or **21a** of the washing machine **2** may be aligned with the front surface **31a** of the refresher **3**. The front surface **10a** or **11a** of the dryer **1** may be aligned with the front surface **20a** or **21a** of the washing machine **2**.
- (87) The front surface **31a** of the refresher **3** may be aligned with the front surfaces **11a** and **21a** of the doors **11** and **21** of the dryer **1** and the washing machine **2**, respectively, and may also be aligned with the front surfaces **10a** and **20a** of the cabinets **10** and **20** of the dryer **1** and the washing machine **2**, respectively. In the case where the respective front surfaces **11a** and **21a** of the doors **11** and **21** of the dryer **1** and the washing machine **2** are disposed on the same plane as the front surfaces **10a** and **20a** of the cabinets **10** and **20**, the front surface **31a** of the refresher **3** may be aligned with the respective doors **11** and **21** of the dryer **1** and the washing machine **2**, and the front surfaces **10a**, **11a**, **20a**, and **21a** of the cabinets **10** and **20**.
- (88) The dryer **1** may have a first upper end **107**. The first upper end **107** may refer to an upper end of the front surface **10a** of the first cabinet **10**. The first upper end **107** may refer to an upper end of the first front panel **101**.
- (89) The refresher **3** may have a second upper end **307**. The second upper end **307** may refer to an upper end of the third door **31**.
- (90) The first upper end **107** and the second upper end **307** may be aligned horizontally. The first upper end **107** and the second upper end **307** may be disposed on the same horizontal plane.
- (91) The laundry treating apparatus **A** may include a connector **92** having a width in a horizontal direction and coupled to each of the first upper end **107** and the second upper end **307**. The connector **92** may be referred to as an “upper connector.”
- (92) The laundry treating apparatus may include the upper connector **92** connecting the first cabinet **10** and the third cabinet **30**, and a lower connector **90** connecting the second cabinet **20** and the third cabinet **30**. The upper connector **92** may connect any one of the first cabinet **10** and the second cabinet **20**, which is disposed on an upper side, to the third cabinet **30**. The lower connector **90** may connect any one of the first cabinet **10** and the second cabinet **20**, which is disposed on a lower side, to the third cabinet **30**.
- (93) The connector **92** may extend rearwardly from the upper ends **107** and **307**. The connector **92** may connect the first upper end **107** and the second upper end **307**. The connector **92** may connect the first upper surface **10c** and the third upper surface **30c**.
- (94) The laundry treating apparatus **A** may include a tower **9** including the dryer **1** and the washing machine **2**. The tower **9** may include the heating device **50**.
- (95) The tower **9** may be an assembly in which the dryer **1** and the washing machine **2** are arranged vertically. In the case where the heating device **50** is disposed on one side of the refresher **3**, the tower **9** may be an assembly in which the dryer **1**, the washing machine **2**, and the heating device **50** are arranged vertically.
- (96) The dryer **1**, the washing machine **2**, and the heating device **50** may be vertically arranged, so as to form the tower **9**. An arrangement order of the dryer **1**, the washing machine **2**, and the heating device **50** in the tower **9** may not be limited to FIG. **1**. For example, the washing machine **2** may be disposed over the dryer **1**, and the heating device **50** may be disposed above the dryer **1** and

the washing machine **2**.

(97) The tower **9** may be disposed on a lateral side of the refresher **3**.

(98) A front surface of the tower **9** may be aligned with the front surface **31a** of the refresher **3**. The front surface of the tower **9** may be disposed on the same plane as the front surface **31a** of the refresher **3**. The front surface of the tower **9** may refer to the front surface **11a** of the first door **11** and the front surface **21a** of the second door **21**. The front surface of the tower **9** may refer to the front surface **10a** of the first cabinet **10**, the front surface **20a** of the second cabinet **20**, and the front surface of the control panel **8**.

(99) An upper end **91** of the front surface of the tower **9** may be aligned with the upper end **307** of the front surface **31a** of the refresher **3**. The upper end **91** of the front surface of the tower **9** may be on the same horizontal plane as the upper end **307** of the front surface **31a** of the refresher **3**.

(100) The upper end **91** of the front surface of the tower **9** may refer to the first upper end **107**.

However, in the case where the washing machine **2** is disposed over the dryer **1**, the upper end **91** of the front surface of the tower **9** may refer to the upper end of the front surface of the washing machine **2**. Further, in the case where the heating device **50** is disposed on the upper side of the dryer **1** and the washing machine **2**, the upper end **91** of the front surface of the tower **9** may refer to the upper end of the front surface of the heating device **50**.

(101) An upper surface **9c** of the tower **9** and the upper surface **30c** of the refresher **3** may be aligned horizontally. The upper surface **9c** of the tower **9** and the upper surface **30c** of the refresher **3** may be disposed on the same horizontal plane.

(102) The connector **92** may connect the upper end **91** of the front surface of the tower **9** and the upper end **307** of the front surface of the refresher **3**. The connector **92** may connect the upper surface **9c** of the tower **9** and the upper surface **30c** of the refresher **3**.

(103) A third side panel **305** of the refresher **3** and a side wall **315** of the rear case **310** may be disposed on the same plane.

(104) The front panel **101** of the dryer **1**, the front panel **201** of the washing machine **2**, and the control panel **8** may be disposed on the same plane. The front surface **10a** of the dryer **1**, the front surface **20a** of the washing machine **2**, and the control panel **8** may be disposed on the same plane.

(105) The third door **31** of the refresher **3** may be disposed on the same plane as the front panel **101** of the dryer **1**, the front panel **201** of the washing machine **2**, and the control panel **8**. Alternatively, the third door **31** of the refresher **3** may also be disposed on the same plane as the first door **11** of the dryer **1** and the second door **21** of the washing machine **2**.

(106) The second lower panel **204** of the washing machine **2** may be disposed on the same horizontal plane as the third lower panel **304** of the refresher **3**.

(107) Hereinafter, an internal structure of the dryer **1**, the washing machine **2**, and the heating device **50** will be described with reference to FIG. **2**. FIG. **2** is a diagram illustrating an internal structure of the dryer **1**, the washing machine **2**, and the heating device **50** which are cut in a longitudinal direction.

(108) The washing machine **2** includes the second cabinet **20**, the second door **21** rotatably coupled to the second cabinet **20**, the tub **23** disposed in the second cabinet **20**, a second drum **24**, which is rotatably disposed in the tub **23** and in which laundry is received, a motor **25** for transmitting power to the second drum **24**, a drain pump **26** for discharging water, generated in the laundry treating apparatus **A** to the outside, a water supply valve **27** connected to an external water source, and a drawer **28** in which detergent is stored. The drawer **28** may be referred to as a “detergent box.”

(109) The drain pump **26** may be connected to the tub **23** by a first pipe **261**. The drain pump **26** may discharge water, introduced through the first pipe **261** and a drain pipe **532**, to the outside of the laundry treating apparatus **A** through a second pipe **262**. However, the drain pipe **532** may be directly connected to the second pipe **262**, in which case condensate generated in the evaporator **53** may be discharged to the outside of the laundry treating apparatus **A** through the drain pipe **532** and

the second pipe **262**.

(110) The water supply valve **27** may open and close water supply pipes **278** and **279** (see FIG. 9) connecting the external water source and the washing machine **2**. The water supply valve **27** may control a flow rate of water flowing into the washing machine **2** from the external water source. The water supply valve **27** may be connected to a first water supply pipe **271**. The first water supply pipe **271** may be connected to the drawer **28** in which the detergent is stored. The water flowing into the drawer **28** through the first water supply pipe **271** may flow into the tub **23** along with the detergent in the drawer **28** through a second water supply pipe **272**.

(111) The dryer **1** includes the first cabinet **10**, the first door **11** rotatably coupled to the first cabinet **10**, and the first drum **13** which is rotatably disposed in the first cabinet **10** and in which the laundry is received.

(112) The dryer **1** may include a motor **133** (see FIG. 5) for rotating the first drum **13**. A pulley may be fixed to a rotating shaft of the motor **133**. A belt may connect the pulley with a circumferential surface of the drum, such that torque of the motor **133** may be transferred to the drum **13** via the pulley and the belt.

(113) The motor **133** may be disposed under the first drum **13**. The motor **133** may be disposed in the heating device **50**. The motor **133** may be disposed on a lateral side of the heat exchange channel **42**. A case **570** (see FIG. 5) of the heating device **50** may be provided with a motor mounting portion **133s** (see FIG. 6).

(114) Unlike the example, the motor **133** may be directly coupled to the first drum **13** to rotate the first drum **13**.

(115) The heating device **50** may be disposed over the second upper panel **203**. The heating device **50** may be disposed in the first cabinet **10**.

(116) The heating device **50** includes: a condenser **52** for performing heat exchange between high-temperature refrigerant and air to heat the air; a fan **60** for blowing air heated by passing through the condenser **52**; and an evaporator **53** for performing heat exchange between the air flowing into the heating device **50** and low-temperature refrigerant to cool and dehumidify the air. The condenser **52** and the evaporator **53** may be referred to as a “heat exchange unit.”

(117) The air heated by passing through the condenser **52** (hereinafter referred to as “hot air”) may be blown by the fan **60**, and may be supplied to at least one of the dryer **1**, the washing machine **2**, or the refresher **3**.

(118) The heating device **40** may be connected to the first drum **13** by a first supply air duct **43**. The hot air generated by the heating device **50** may be blown by the fan **60** to be supplied into the first drum **13** through the first supply air duct **43**. The first supply air duct **43** may extend upwardly from the heating device **50**.

(119) The heating device **50** may be connected to the tub **23** through a third supply air duct **48**. The hot air generated by the heating device **50** may be blown by the fan **60** to be supplied into the tub **23** through the third supply air duct **48**. The third supply air duct **48** may extend downwardly from the heating device **50**.

(120) The hot air generated by the heating device **50** may be blown by the fan **60** to be supplied to the outside of the laundry treating apparatus A through a dehumidification duct **46**. The dehumidification duct **46** may be disposed between a base plate **575** to be described below and the second upper panel **203**. The air blown by the fan **60** may be supplied into an indoor space through the dehumidification duct **46**. An opening member **463** may be disposed in front of the dehumidification duct **46**. The opening member **463** may open and close the front side of the dehumidification duct **46**. The opening member **463** may be rotatably coupled to the first cabinet **10** or the second cabinet **20**.

(121) The supply air ducts **43**, **45**, and **48** may be referred to as any one of first to third supply air ducts. For example, the supply air duct connected to the dryer **1** may be referred to as a first supply air duct **43**; the supply air duct connected to the refresher **3** may be referred to as a second supply

air duct **45**, and the supply air duct connected to the washing machine **2** may be referred to as a third supply air duct **48**. The supply air ducts **43**, **45**, and **48** may be referred to as “supply pipes.” The respective first, second, and third supply air ducts **43**, **45**, and **48** may be referred to as any one of the “first to third supply pipes.” For example, the first supply air duct **43** may be referred to as a first supply pipe; the second supply air duct **45** may be referred to as a second supply pipe; and the third supply air duct **48** may be referred to as a third supply pipe.

(122) The air supplied to the dryer **1**, the washing machine **2**, or the refresher **3** may be recovered to the heating device **50**.

(123) The heating device **50** may be connected to the first drum **13** by a first exhaust air duct **41**. The hot air flowing into the first drum **13** through the first supply air duct **43** may dry the laundry placed in the first drum **13**, and then may return to the heating device **50** through the first exhaust air duct **41**. The first exhaust air duct **41** may extend downwardly from the first drum **13**.

(124) The heating device **50** may be connected to the tub **23** by a third exhaust air duct **47**. The hot air flowing into the tub **23** through the third supply air duct **48** may dry the laundry placed in the second drum **24**, and then may return to the heating device **50** through the third exhaust air duct **41**. The third exhaust air duct **47** may extend upwardly from the tub **23**.

(125) The exhaust air ducts **41**, **44**, and **47** may be referred to as any one of first to third exhaust air ducts. For example, the exhaust air duct connected to the dryer **1** may be referred to as a first exhaust air duct **41**; the exhaust air duct connected to the refresher **3** may be referred to as a second exhaust air duct **44**; and the exhaust air duct connected to the washing machine **2** may be referred to as a third exhaust air duct **47**. The respective first, second, and third exhaust air ducts **41**, **44**, and **47** may be referred to as any one of “first to third return lines.” For example, the first exhaust air duct **41** may be referred to as a first return line, the second exhaust air duct **44** may be referred to as a second return line, and a third exhaust air duct **47** may be referred to as a third return line.

(126) The hot air generated by the heating device **50** may be supplied to the dryer **1**, the washing machine **2**, and the refresher **3**, to dry the laundry placed in the respective laundry treating machines **1**, **2**, and **3**, and then may return to the heating device **50**. That is, the hot air generated by the heating device **50** may circulate within the laundry treating apparatus A. The hot air, recovered to the heating device **50** after drying the laundry received in each of the plurality of laundry treating machines **1**, **2**, and **3**, may contain a greater amount of moisture than the air drying the laundry placed in one laundry treating machine.

(127) By performing heat exchange between the air returning to the heating device **50** and a refrigerant, the evaporator **53** may reduce the temperature of the returning air and removes moisture contained in the air. The air returning to the heating device **50** may be heat exchanged with the evaporator **53** to generate condensate.

(128) The heating device **50** may include a drain pan **531** disposed on a lower side of the evaporator **53**. The drain pan **531** may receive the condensate generated in the evaporator **53**.

(129) The drain pan **531** may be connected to the drain pump **26** by the drain pipe **532**. The drain pipe **532** may extend downwardly from the drain pan **531** to be connected to the drain pump **26**.

(130) The water collected in the drain pan **531** may flow to the drain pump **26** through the drain pipe **532**, and may be discharged to the outside of the laundry treating apparatus A by the drain pump **26**.

(131) The dryer **1** may have a first rear surface **10b**. The first rear surface **10b** may refer to a rear surface of the first cabinet **10**.

(132) The washing machine **2** may have a second rear surface **20b**. The second rear surface **20b** may refer to a rear surface of the second cabinet **20**.

(133) The tower **9** may have widths **W1** and **W2** in a front-rear direction. A width from the front surfaces **11a** and **21a** of the doors **11** and **21** to the rear surfaces **10b** and **20b** may be defined as a first width **W1**. A width from the front surfaces **10a** and **20a** of the cabinets **10** and **20** to the rear surfaces **10b** and **20b** may be defined as a second width **W2**.

(134) Each of the dryer **1** and the washing machine **2** may have the first width **W1** and the second width **W2**. The dryer **1** and the washing machine **2** may have the same width in the front-rear direction.

(135) The tower **9** may have a height **9H** in an up-down direction. The height **9H** of the tower **9** may be defined as a sum of the height of the dryer **1** and the height of the washing machine **2**. However, in the case where the heating device **50** is disposed outside of the dryer **1** and the washing machine **2**, the height **9H** of the tower **9** may be defined as a sum of the height of the dryer **1**, the height of the washing machine **2**, and the height of the heating device **50**.

(136) Hereinafter, an internal structure of the refresher **3** will be described with reference to FIG. **3**. FIG. **3** is a diagram illustrating an internal structure of the refresher **3** of the laundry treating apparatus **A** which is cut in a longitudinal direction.

(137) The refresher **3** may include the third cabinet **30** having an inner space **33** for receiving laundry.

(138) The refresher **3** may include a hanger **36**, on which clothes are hung, and an inner panel **34** defining a lower portion of a space **33** in which clothes are received. The inner panel **34** may be referred to as an “inner plate.”

(139) The inner plate **34** may be disposed below the tub **23**. The inner plate **34** may be disposed below the second drum **24**. However, in the case where the dryer **1** is disposed under the washing machine **2**, the inner plate **34** may be disposed below the first drum **13**. Accordingly, as the height of the position of the inner plate **34** is reduced, a volume of the inner space of the refresher **3** may increase.

(140) The hanger **36** may be disposed between the third upper panel **303** and the third lower panel **304**, and may be disposed closer to the third upper panel **303** than the third lower panel **304**.

(141) The hanger **36** may be disposed above the first drum **13**. The hanger **36** may be disposed at a height corresponding to an upper portion of the first drum **13**. However, in the case where the dryer **1** is disposed under the washing machine **2**, the hanger **36** may be disposed above the tub **23** or may be disposed on an upper side of the second drum **24**, and may be disposed at a height corresponding to the tub **23** or the upper portion of the second drum **24**. Accordingly, as the height of the position of the hanger **36** increases, a volume of the inner space of the refresher **3** may increase.

(142) The inner panel **34** may be disposed between the third upper panel **303** and the third lower panel **304**, and may be disposed closer to the third lower panel **304** than the third upper panel **303**.

(143) Garments **G** received in the inner space **33** of the third cabinet **30** may be located between the hanger **36** and the inner panel **34**.

(144) The height **H** of the inner space **33** may refer to a height between the hanger **36** and the inner panel **34**. The height **H** of the inner space **33** may refer to a vertical gap between the upper panel **303** and the inner panel **34**. The height **H** of the inner space **33** may be extended compared to a case where the heating device **50** is disposed between the inner panel **34** and the third lower panel **304**. Accordingly, unlike an existing refresher, the refresher **3** according to the present disclosure may receive garments **G**, such as a long coat or a suit, which occupy a great height in the vertical direction.

(145) In addition, compared to the existing refresher, the refresher **3** according to the present disclosure may have a longitudinal width which may be extended according to the longitudinal width of the dryer **1** and the washing machine **2**. Accordingly, the refresher **3** according to the present disclosure may receive a larger number of garments in the front-rear direction than the existing refresher. The longitudinal width **W3** of the inner space **33** of the refresher **3** may refer to a width between the third door **31** and the third panel **302**.

(146) The refresher **3** may have a third rear surface **30b**. The third rear surface **30b** may refer to a rear surface of the third cabinet **30**.

(147) The refresher **3** may have longitudinal widths **W3**, **W4**, and **W5**. A width from an inner

surface of the third door **31** to an inner surface of the third rear panel **302** may be defined as a third width **W3**. The third width **W3** may be the longitudinal width of the inner space **33** of the refresher **3**. A width from the front surface **31a** of the third door **31** to the rear surface **30b** of the third cabinet **30** may be defined as a fourth width **W4**. A width from the front surface **31a** of the third door **31** to a rear surface **44b** of the second exhaust air duct **44** may be defined as a fifth width **W5**. However, the first to fifth widths **W1**, **W2**, **W3**, **W4**, and **W5** are randomly defined for convenience of explanation, and the respective widths **W1**, **W2**, **W3**, **W4**, and **W5** defined above may be referred to as any one of the first to fifth widths.

(148) The longitudinal width **W3** of the inner space **33** of the refresher **3** may be smaller than the longitudinal widths **W1** and **W2** of the dryer **1** and the washing machine **2**. The longitudinal width **W4** of the third cabinet **30** may be smaller than the longitudinal widths **W1** and **W2** of the dryer **1** and the washing machine **2**.

(149) In the laundry treating apparatus **A** according to an aspect of the present disclosure, the supply air duct **45** and the exhaust air duct **44** are disposed behind the space **33** in which the laundry is placed, such that the front surface **31a** of the refresher **3** and the front surface of the dryer **1** and the washing machine **2** may be aligned.

(150) The refresher **3** may have a vertical height **3H**. The height **H3** of the refresher **3** may be defined as a length from the upper surface **30c** of the refresher **3** to the lower surface thereof.

(151) The vertical height **3H** of the refresher **3** may be equal to the vertical height **H9** of the tower **9**. However, it is also possible that the vertical height **3H** of the refresher **3** may be equal to or lower than the vertical height **H9** of the tower **9**.

(152) A storage space **35** may be formed between the inner panel **34** and the third lower panel **304**. Garments, such as socks, underwear, hats, scarves, gloves, etc., which take up a relatively small volume, may be placed in the storage space **35**. However, the storage space **35** may refer to a space in which the supply air duct **45** and the exhaust air duct **44** are disposed.

(153) The inner panel **34** may be connected to the second supply air duct **45**. The third cabinet **30** may be connected to the second exhaust air duct **44**.

(154) The inner panel **34** may include a first inner panel **341** spaced apart from an upper side of the third lower panel **304**, and a second inner panel **342** extending diagonally upward from the first inner panel **341**. The second inner panel **342** may extend at an incline upwardly from the first inner panel **341** toward the third rear panel **302**.

(155) The second supply air duct **45** may be connected to the second inner panel **342**. The second inner panel **342** may have a supply air hole **308** that is open toward the inner space **33**. The second supply air duct **45** may be connected to the supply air hole **308**. The hot air supplied from the heating device **50** may be discharged to the inner space **33** through the supply air hole **308**.

(156) The second supply air duct **45** may include a first hot air duct **451** disposed at a rear side of the third rear panel **302**, and a second hot air duct **452** disposed in front of the third rear panel **302**.

(157) The first hot air duct **451** may be disposed in the rear case **310**. A second hot air duct **452** may be disposed in the storage space **35**. The first hot air duct **451** and the second hot air duct **452** may be coupled to the third rear panel **302**. The first hot air duct **451** may extend upwardly in the rear case **310** to be connected to the heating device **50**. The second hot air duct **452** may extend upwardly to be connected to the second inner panel **342**.

(158) The second exhaust air duct **44** may be connected to the third rear panel **302**. The third rear panel **302** may have an exhaust air hole **309** that is open toward the inner space **33**. The second exhaust air duct **44** may be coupled to the third rear panel **302** so as to correspond to the exhaust air hole **309**. The hot air discharged to the inner space **33** of the refresher **3** may dry the garments **G**, and then may flow into the second exhaust air duct **44** through the exhaust air hole **309**.

(159) The exhaust air hole **309** which is open may be formed in the rear panel **302**. The exhaust air hole **309** may be open from an inner surface **302a** of the rear panel to an outer surface **302b** of the rear panel **302**. The exhaust air hole **309** may refer to an open portion of the upper side of the rear

panel **302**.

(160) The exhaust air duct **44** may be connected to the exhaust air hole **309**. The exhaust air duct **44** may be coupled to the rear panel **302**. The exhaust air duct **44** may be connected to the outer surface **302b** of the rear panel **302**. The exhaust air duct **44** may pass through the rear panel **302**.

(161) The exhaust air duct **44** may include a first exhaust air portion **441** connected to the rear panel **302**, and a second exhaust air portion **442** extending downwardly from the first exhaust air portion **441**.

(162) The first exhaust air portion **441** may extend rearwardly from the rear panel **302**. The second exhaust air portion **442** may be integrally formed with the first exhaust air portion **441**. The second exhaust air portion **442** may extend downwardly from the first exhaust air portion **441**.

(163) The exhaust air duct **44** may be disposed behind the rear panel **302**. The second exhaust air portion **442** may extend downwardly from the rear side of the rear panel **302**.

(164) A filter **37** may be disposed in the exhaust air hole **309**. The filter **37** may be disposed on the rear panel **302**. The filter **37** may be disposed between the inner surface **302a** of the rear panel **302** and the outer panel **302b** of the rear panel **302**. The filter **37** may be disposed at the upper portion of the cabinet **30**.

(165) The filter **37** may have a filter insertion hole **371** which is open toward the inner space **33** of the cabinet **30**, and a filter net **372** disposed at a rear portion of the filter insertion hole **371**.

(166) The filter insertion hole **371** may be disposed behind the inner surface **302a** of the rear panel **302**. The filter net **372** may be disposed in front of the outer surface **302b** of the rear panel **302**.

(167) The outer surface **302b** of the rear panel **302** may be defined as the rear surface **30b** of the refresher **3**.

(168) The exhaust air hole **309** may be disposed below the hanger **36**.

(169) The supply air hole **308** may be disposed at a lower portion of the refresher **3**, and the exhaust air hole **309** may be disposed at an upper portion of the refresher **3**. However, the positions of the supply air hole **308** and the exhaust air hole **309** are not limited to the above example. For example, the supply air hole **308** may be disposed at the upper portion of the refresher **3**, and the exhaust air hole **309** may be disposed at the lower portion of the refresher **3**. In this case, the supply air hole **308** may be disposed above the hanger **36**. As the supply air hole **308** is disposed above the hanger **36**, dust deposited on the garments **G** may be removed. Further, any one of the supply air hole **308** or the exhaust air hole **309** is disposed at the upper side, and the other one is disposed at the lower side, air supplied through the supply air hole **308** may be distributed evenly throughout the inner space **33**, and then may return to the heating device **50** through the exhaust air hole **309**.

(170) The refresher **3** may include rollers **39** and legs **39a** protruding downwardly from the third lower panel **304**. A plurality of rollers **39** may be disposed which are spaced apart from each other in the front-rear direction. A roller structure of the refresher **3** may also be applied to the second lower panel **204** of the washing machine **2**. The rollers of the washing machine **2** and the refresher **3** may serve to support the weight of the laundry treating apparatus **A** when the laundry treating apparatus **A** is moved.

(171) Hereinafter, a duct system of the laundry treating apparatus **A** according to the present disclosure will be described with reference to FIG. **4**. In FIG. **4**, a left side of a reference line **Y** shows a duct system of the dryer **1** and the washing machine **2**, and a right side of the reference line **Y** shows a duct system of the refresher **3**. The left side of the reference line **Y** in FIG. **4** is view conceptually illustrating a duct system of the dryer **1** and the washing machine **2** which are cut by a plane perpendicular to a left and right direction; and the right side of the reference line **Y** in FIG. **4** is a view conceptually illustrating a rear surface of the refresher **3** to show a duct system. The directions used in the description of FIG. **4** may be the same as those illustrated in FIG. **1**.

(172) The left side of the reference line **Y** in FIG. **4** may be referred to as a first conceptual diagram **S1**. The right side of the reference line **Y** in FIG. **4** may be referred to as a second conceptual diagram **S2**.

(173) The “duct system DS” may be a concept that collectively refers to passages of hot air circulating in the laundry treating apparatus A. The “duct system DS” may be a concept that collectively refers to passages connecting the heating device **50**, the dryer **1**, the washing machine **2**, and the refresher **3**. The “duct system DS” may be a concept that collectively refers to passages of hot air heated by the heating device **50**.

(174) The heating device **50** heats air and supplies the heated air to each of the dryer **1**, the washing machine **2**, and the refresher **3**.

(175) The duct system DS may include the heat exchange channel **42** in which the air is heated. The duct system may include the first supply air duct **43** connecting the heating device **50** and the dryer **1**. The duct system DS may include the second supply air duct **45** connecting the heating device **50** and the refresher **3**. The duct system DS may include the third supply air duct **48** connecting the heating device **50** and the washing machine **2**. The duct system DS may include the dehumidification duct **46** connected to the heating device **50**. The air heated by passing through the heat exchange channel **42** is blown by the fan **60** to be supplied to at least any one of the first supply air duct **43**, the second supply air duct **45**, the third supply air duct **48**, and the dehumidification duct **46**.

(176) The duct system DS may include the first exhaust air duct **41** connecting the heating device **50** and the dryer **1**. The duct system DS may include the second exhaust air duct **44** connecting the heating device **50** and the refresher **3**. The duct system DS may include the third exhaust air duct **47** connecting the heating device **50** and the washing machine **2**. The heated air supplied to the dryer **1** may flow into the heat exchange channel **42** through the first exhaust air duct **41**. The heated air supplied to the refresher **3** may flow into the heat exchange channel **42** through the second exhaust air duct **44**. The heated air supplied to the washing machine **2** may flow into the heat exchange channel **42** through the third exhaust air duct **47**.

(177) The heat exchange channel **42**, through the air flows, may be provided in the heating device **50**. The heating device **50** may include a heat exchange unit disposed in the heat exchange channel **42**. The heat exchange unit may heat the air flowing in the heat exchange channel **42**. The heat exchange unit may include the condenser **52** and the evaporator **53**.

(178) The laundry treating apparatus A may include the fan **60**. The fan **60** may blow the air in the heat exchange channel **42**. The fan **60** may be disposed on a downstream side of the condenser **52**. The air heated by heat exchange with the evaporator **53** and the condenser **52** may be blown by the fan **60**. The fan **60** may be disposed in the heat exchange channel **42**.

(179) The air blown by the fan **60** may be supplied to at least any one of the dryer **1**, the washing machine **2**, the refresher **3**, and the dehumidification duct **46**.

(180) The laundry treating apparatus A may include a blowing duct **420** surrounding the fan **60**. The duct system DS may include the blowing duct **420**. The fan **60** may be disposed in the blowing duct **420**.

(181) An inner space of the blowing duct **420** may be a portion of the heat exchange channel **42**.

(182) The fan **60** and the blowing duct **420** may be disposed at a discharge end **42B** of the heat exchange channel **42**. The discharge end **42B** may be disposed at a downstream side of the condenser **52** and the evaporator **53**.

(183) The blowing duct **420** may include a first discharge port **425** connected to the first supply air duct **43**. The blowing duct **420** may include a second discharge port **427** connected to the second supply air duct **45**. The blowing duct **420** may include a third discharge port **426** connected to the third supply air duct **48**. The blowing duct **420** may include a fourth discharge port **428** connected to the dehumidification duct **46**.

(184) The first discharge port **425** may protrude upwardly from the blowing duct **420**. The first supply air duct **43** may connect the first drum **13** and the first discharge port **425**.

(185) The second discharge port **427** may protrude from the blowing duct **420** to a lateral side. The second supply air duct **45** may connect the third cabinet **30** and the second discharge port **427**.

(186) The third discharge port **426** may protrude downwardly from the blowing duct **420**. The third supply air duct **48** may connect the tub **23** and the third discharge port **426**.

(187) The fourth discharge port **428** may protrude from the blowing duct **420** to the lateral side. The fourth discharge port **428** may protrude in a direction opposite to the second discharge port **427**. The dehumidification duct **46** may be connected to the fourth discharge port **428**.

(188) A rotating body **71** of a switching device **70** (see FIG. 6) which will be described later may be disposed in the blowing duct **420**. The rotating body **71** may be connected to a driving motor **711** to be rotated in the blowing duct **420**. The air blown by the fan **60** may flow into at least any one of the first supply air duct **43**, the second supply air duct **45**, the third supply air duct **48**, and the dehumidification duct **46** by the operation of the switching device **70**.

(189) The laundry treating apparatus A according to the present disclosure may also include a separate distribution device in addition to the switching device **70** which will be described later. The distribution device may distribute the air blown by the fan **60** to each of the dryer **1**, the washing machine **2**, the refresher **3**, and the dehumidification duct **46**. That is, the air blown by the fan **60** may be supplied at the same time to each of the dryer **1**, the washing machine **2**, the refresher **3**, and the dehumidification duct **46**. The distribution device may be disposed in the blowing duct **420** or may be disposed on a distribution passage connected to the blowing duct **420**. The distribution device may be a valve. The distribution device may include an actuator and a switching damper. The laundry treating apparatus A may include both the switching device **70** and the distribution device at the same time, may include only the switching device **70**, or may include only the distribution device.

(190) The hot air flowing into the first drum **13** through the first supply air duct **43** may dry the laundry placed in the first drum **13**, and then may flow into the heat exchange channel **42** through the first exhaust air duct **41**. The first drum **13** may include a front cover **131** disposed on a front side, and a rear cover **132** disposed on a rear side. The first supply air duct **43** may be connected to the rear cover **132**, and the first exhaust air duct **41** may be connected to the front cover **131**.

(191) The first exhaust air duct **41** may connect the first drum **13** and the heat exchange channel **42**. The first exhaust air duct **41** may extend downwardly from the first drum **13** to be connected to the heat exchange channel **42**.

(192) An inlet end **42A** of the heat exchange channel **42** may have a first inlet port **421** connected to the first exhaust air duct **41**. The first inlet port **421** may extend upwardly from the heat exchange channel **42**. The first inlet port **421** may extend upwardly from the case **570** of the heating device **50**.

(193) The laundry treating apparatus A may include a first opening and closing valve **41a** disposed in the first exhaust air duct **41**. The first opening and closing valve **41a** may control a flow rate of air in the first exhaust air duct **41**. The first opening and closing valve **41a** may block an air flow in the first exhaust air duct **41**. The first opening and closing valve **41a** may block the air flow in the first exhaust air duct **41** when the hot air is not supplied into the first drum **13** through the first exhaust air duct **43**.

(194) The hot air flowing into third cabinet **30** through the second supply air duct **45** may dry the laundry placed in the third cabinet **30**, and then may flow into the heat exchange channel **42** through the second exhaust air duct **44**. The second supply air duct **45** and the second exhaust air duct **44** may be connected to the third rear panel **302** of the third cabinet **30**.

(195) The second exhaust air duct **44** may connect the third cabinet **30** and the heat exchange channel **42**. The second exhaust air duct **44** may extend downwardly from an upper portion of the third cabinet **30** to be connected to the heat exchange channel **42**.

(196) The second exhaust air duct **44** may include a first exhaust air portion **441** disposed between the heating device **50** and the second cabinet **20**. A first exhaust air portion **441** may be disposed between a base plate **575** (see FIG. 6) to be described later and the second upper panel **203** of the second cabinet **20**. The first exhaust air portion **441** may extend forwardly and rearwardly in a

separation space **55** (see FIG. **6**) which will be described later.

(197) The inlet end **42A** of the heat exchange channel **42** may have a second inlet port **422** connected to the second exhaust air duct **44**. The second inlet port **422** may extend downwardly from the heat exchange channel **42**. The second inlet port **422** may extend downwardly from the case **570** of the heating device **50**.

(198) The laundry treating apparatus A may include a second opening and closing valve **44a** disposed in the second exhaust air duct **44**. The second opening and closing valve **44a** may control a flow rate of air in the second exhaust air duct **44**. The second opening and closing valve **44a** may block an air flow in the second exhaust air duct **44**. The second opening and closing valve **44a** may block the air flow in the second exhaust air duct **44** when the hot air is not supplied into the third drum **30** through the second exhaust air duct **45**. The second opening and closing valve **44a** may be disposed in the first exhaust air portion **441**.

(199) The hot air flowing into the tub **23** through the third supply air duct **48** may dry the laundry placed in the tub **23**, and then may flow into the heat exchange channel **42** through the third exhaust air duct **47**.

(200) The third exhaust air duct **47** may connect the tub **23** and the heat exchange channel **42**. The third exhaust air duct **47** may extend upwardly from an upper portion of the tub **23** to be connected to the heat exchange channel **42**.

(201) A third inlet port **424** connected to the third exhaust air duct **47** may be formed at the inlet end **42A** of the heat exchange channel **42**. The third inlet port **424** may extend downwardly from the heat exchange channel **42**. The third inlet port **424** may extend downwardly from the second exhaust air duct **44**. The third inlet port **424** may extend downwardly from the first exhaust air portion **441**.

(202) The third inlet port **424** may protrude downwardly from a lower surface of the second exhaust air duct **44**. The third exhaust air duct **47** may connect the tub **23** and the third inlet port **424**. The air in the third exhaust air duct **47** may join the air in the second exhaust air duct **44** to flow into the heat exchange channel **42**.

(203) The laundry treating apparatus A may include a third opening and closing valve **47a** disposed in the third exhaust air duct **47**. The third opening and closing valve **47a** may control a flow rate of air in the third exhaust air duct **47**. The third opening and closing valve **47a** may block an air flow in the third exhaust air duct **47**. The third opening and closing valve **47a** may block the air flow in the third exhaust air duct **47** when the hot air is not supplied into the tub **23** through the third supply air duct **48**.

(204) The hot air flowing through the dehumidification duct **46** may be supplied to the outside of the laundry treating apparatus A through an outlet **462** that is opened forward. The hot air flowing through the dehumidification duct **46** may be supplied to an indoor space through the outlet **462**.

(205) The dehumidification duct may include a second duct section **461** disposed between the heating device **50** and the second cabinet **20**. The second duct section **461** may be disposed between the base plate **575** (see FIG. **6**) to be described later and the second upper panel **203** of the second cabinet **20**. The second duct section **461** may extend forwardly and rearwardly in the separation space **55** (see FIG. **6**) which will be described later.

(206) An outside air inlet port **423** connected to the heat exchange channel **42** may be formed at the inlet end **42A** of the heat exchange channel **42**. The outside air inlet port **423** may extend forwardly from the heat exchange channel **42**. The outside air inlet port **423** may extend forwardly from the second exhaust air duct **44**.

(207) The outside air inlet port **423** may protrude forwardly from one side of the second exhaust air duct **44**. The outside air inlet port **423** may allow the indoor space and the second exhaust air duct **44** to communicate with each other. The air in the outside air inlet port **423** may join the air in the second exhaust air duct **44** to flow into the heat exchange channel **42**. The outside air inlet port **423** may have an outside air inlet **49** that is opened forward. The air drawn in through the outside air

inlet **49** may join the air in the second exhaust air duct **44** to flow into the heat exchange channel **42**.

(208) The laundry treating apparatus **A** may include a fourth opening and closing valve **49a** disposed at the outside air inlet port **423**. The fourth opening and closing valve **49a** may control a flow rate of air in the outside air inlet port **423**. The fourth opening and closing valve **49a** may block an air flow in the outside air inlet port **423**. The fourth opening and closing valve **49a** may block the air flow in the outside air inlet port **423** when the hot air is not supplied to the dehumidification duct **46**.

(209) Hereinafter, the heating device **50** will be described with reference to FIGS. 5 to 7. The description of the heating device **50**, which will be described below with reference to FIGS. 5 to 7, may be applied commonly to all embodiments of the laundry treating apparatus described with reference to FIGS. 1 to 20. Even in this case, however, depending on relative arrangement positions of the laundry treating machines included in the laundry treating apparatus, a shape of the case **570**, a shape of the blowing duct **420**, an opening direction of the discharge ports **425**, **426**, **427**, and **428**, an opening direction of the inlet ports **421**, **422**, **423**, and **424**, and the like may vary.

(210) Referring to FIG. 5, the heating device **50** may include the case **570**, the compressor **51**, the condenser **52**, the evaporator **53**, and the expansion device **54**.

(211) The compressor **51**, the condenser **52**, the evaporator **53**, and the expansion device **54** may be connected by a refrigerant passage. The heat pump device may include the compressor **51**, the condenser **52**, the evaporator **53**, and the expansion device **54**.

(212) The drain pan **531** may be disposed under the evaporator **53**.

(213) The case **570** may provide a space in which the compressor **51**, the condenser **52**, the fan **60**, and the evaporator **53** are disposed. The compressor **51**, the condenser **52**, the fan **60**, the evaporator **53**, and the switching device **70** may be disposed in the case **570**.

(214) The case **570** may include a cover **573**, a base plate **575** spaced apart from a lower side of the cover **573**, a front wall **574** disposed in front of the condenser **53**, a first side wall **571** disposed on one side of the condenser **53**, and a second side wall **572** disposed on the other side of the condenser **53**.

(215) The drum motor **133** rotating the first drum **13** of the dryer **1** may be disposed in the case **570** of the heating device **50**. The drum motor **133** may be disposed on an upper side of the case **570**. A motor mounting portion **133s**, on which the drum motor **133** is mounted, is provided in the case **570**.

(216) The condenser **52**, the fan **60**, and the evaporator **53** may be disposed on an upper side of the base plate **575**.

(217) The heat exchange channel **42** may be a space surrounded by the base plate **575**, the front wall **574**, the first side wall **571**, and the second side wall **572**. The cover **573** may not be provided, in which case an upper portion of the heat exchange channel **42** may be open. The heat exchange channel **42** may communicate with the fan **60** disposed at a rear side of the heating device **50**. Air in the heat exchange channel **42** may be blown by the fan **60**. The heat exchange channel **42** may be referred to as a "heating passage." The condenser **52** and the evaporator **53** may be disposed in the heat exchange channel **42**. The heat exchange channel **42** may refer to a partially open space.

(218) The heat exchange channel **42** may be a space surrounded by the cover **573**, the base plate **575**, the front wall **574**, the first side wall **571**, and the second side wall **572**. The cover **573** may cover the upper portion of the heat exchange channel **42**. The heat exchange channel **42** may refer to a space between the cover **573** and the base plate **575**. The cover **573**, the base plate **575**, the front wall **574**, the first side wall **571**, and the second side wall **572** may form a "heating duct" surrounding the heat exchange channel **42**. The heating duct may communicate with the fan **60**, and air in the heating duct may be blown by the fan **60**. The condenser **52** and the evaporator **53** may be disposed in the heating duct. The heat exchange channel **42** may refer to a duct shielded in all directions.

(219) The heat exchange channel **42** may be formed in the heating device **50**. The heat exchange channel **42** may be a portion of the inner space of the heating device **50**.

(220) The first inlet port **421** may be disposed in front of the heat exchange channel **42**. The first inlet port **421** may cover the front side of the heat exchange channel **42**. The first inlet port **421** may be connected to the front wall **574**. The first inlet port **421** may be formed in the case **570**. The first exhaust air duct **41** may be inserted into the first inlet port **421** and may be fixed thereto.

(221) The heating device **50** may be disposed in the machine room **S**. The controller **81** may control the operation of components disposed in the machine room **S**. The machine room **S** may have a space in which the PCB is disposed, and the controller **81** may be mounted in the PCB.

(222) The heating device **50** may include a steam generator **502** for generating steam and a dehumidifier **504** for removing moisture from air flowing through the heat exchange channel **42**.

(223) The steam generator **502** may generate steam by heating water. The steam generator **502** may be disposed between the condenser **52** and the fan **60**. The steam generated by the steam generator **502** may be pressurized by the fan **60** to be supplied to each of the dryer **1**, the washing machine **2**, and the refresher **3**. The steam generated by the steam generator **502** may be supplied to each of the first drum **13**, the second drum **24**, and the inner space **33** of the refresher **3**.

(224) The dehumidifier **504** may dehumidify air under room temperature conditions (about 25 degrees Celsius). The dehumidifier **504** may dehumidify air by using desiccant cooling. The dehumidifier **504** may be filled with zeolite. The zeolite filled in the dehumidifier **504** may be replaced periodically.

(225) The dehumidifier **504** may be disposed between the condenser **52** and the fan **60**. The dehumidifier **504** may dehumidify the air flowing through the heat exchange channel **42** even when the compressor **51** is not in operation.

(226) The switching device **70** may control the direction of air blown by the fan **60**. The switching device **70** may be disposed in the machine room **S**.

(227) Referring to FIG. **6**, the switching device **70** may control the supply of hot air to the dryer **1**, the washing machine **21**, the refresher **3**, or the dehumidification duct **46**.

(228) The switching device **70** may include the rotating body **71** rotatably mounted in the blowing duct **420**. The switching device **70** may include the driving motor **711** that rotates the rotating body **71**. The rotating body **71** may be rotated by the driving motor **711** in the blowing duct **420**. The fan **60** may be disposed in the rotating body **71**.

(229) The driving motor **711** may rotate the rotating body **71**. A driving gear **712** may be fixed to the rotating shaft of the driving motor **711**. The driving gear **712** may be a pinion gear or a spur gear.

(230) A driven gear **713** may be rotated in engagement with the driving gear **712**. The driven gear **713** may be fixed to the rotating body **71** or may be integrally formed with the rotating body **71**. The driven gear **713** may be a ring gear. The driven gear **713** may be a ring-shaped rack.

(231) The driving gear **712** and the driven gear **713** may be geared with each other. By the rotation of the driving gear **712**, the driven gear **713** may be moved in a circumferential direction with respect to the rotational axis of the fan **60**. When the driven gear **713** is moved in a circumferential direction, the rotating body **71** having the driven gear **713** fixed thereto may also be moved in the circumferential direction with respect to the rotational axis of the fan **60**.

(232) The driving motor **711** may be disposed outside of the blowing duct **420**. One surface (e.g., rear surface) of the blowing duct **420** that faces the rotating body **71** may have a cut-out portion **714**. The cut-out portion **714** may be formed at a position corresponding to the driven gear **713**. A portion of the driving gear **712** may be inserted into the cut-out portion **714**. The driving gear **712** and the driven gear **713** may be geared with each other in the cut-out portion **714**.

(233) A rotating shaft of the driving motor **711** may be disposed side by side with the rear surface of the blowing duct **420**. Accordingly, a volume occupied by the driving motor **711** and the driving gear **712** in the front-rear direction may be reduced.

(234) The driving motor **711** may be a motor capable of controlling the position, angle, and direction of rotation. For example, the driving motor may be a Brushless Direct Current (BLDC) motor. Alternatively, the driving motor **711** may be a step motor. The driving motor **711** may be electrically connected to the control panel **8** and/or the controller **81**. Rotation of the driving motor **711** may be controlled by an electrical signal transmitted from the control panel **8** and/or the controller **81** to the driving motor **711**. The control panel **8** and/or the controller **81** may control a hot air supplying direction by controlling the rotation angle of the driving motor **711**.

(235) Meanwhile, the driving motor **711** may rotate the rotating body **71** by various known methods used by the motor for rotating the rotating body. For example, the driving motor **711** may rotate the rotating body **71** by using a belt-pulley method, or by using a plurality of gears that are geared with each other, or the rotating shaft of the motor may be rotated together with the rotating body.

(236) The blowing duct **420** may be connected to the first supply air duct **43**, the second supply air duct **45**, the third supply air duct **48**, and the dehumidification duct **46**.

(237) The blowing duct **420** may be connected to a motor mount **564**, to which a fan motor rotating the fan **60** is fixed. The motor mount **64** may be disposed on a rear surface of the blowing duct **420**. The driving motor **711**, the driving gear **712**, and the driven gear **713** may be disposed radially outwardly from the motor mount **64**.

(238) The blowing duct **420** may include the first discharge port **425**, the second discharge port **427**, the third discharge port **426**, and the fourth discharge port **428**.

(239) The first supply air duct **43** may be connected to the first discharge port **425**. The first supply air duct **43** may be inserted into the first discharge port **425**. The first discharge port **425** may be disposed facing upward in the blowing duct **420**. The first discharge port **425** may provide a supply air hole that is vertically open.

(240) The second supply air duct **45** may be connected to the second discharge port **427**. The second supply air duct **45** may be inserted into the second discharge port **427**. The second discharge port **427** may be disposed facing toward the lateral side in the blowing duct **420**. The second discharge port **427** may provide a supply air hole that is horizontally open.

(241) The third supply air duct **48** may be connected to the third discharge port **426**. The third supply air duct **48** may be inserted into the third discharge port **426**. The third discharge port **426** may be disposed facing downwardly in the blowing duct **420**. The third discharge port **426** may provide a supply air hole that is vertically open.

(242) The dehumidification duct **46** may be connected to the fourth discharge port **428**. The dehumidification duct **46** may be inserted into the fourth discharge port **428**. The fourth discharge port **428** may be disposed facing a direction opposite to the second discharge port **427**. The fourth discharge port **428** may be disposed facing toward the lateral side in the blowing duct **420**. The fourth discharge port **428** may provide a supply air hole that is horizontally open.

(243) The heating device **50** may be connected to each of the first exhaust air duct **41**, the second exhaust air duct **44**, the third exhaust air duct **47**, and the outside air inlet port **423**. The third exhaust air duct **47** and the outside air inlet port **423** may be connected to the heating device **50** via the second exhaust air duct **44**.

(244) The heating device **50** may include the first inlet port **421** connected to the first exhaust air duct **41**, and the second inlet port **422** connected to the second exhaust air duct **44**. The first inlet port **421** may extend upwardly, and the second inlet port **422** may extend downwardly. The first inlet port **421** and the second inlet port **422** may protrude from the case **570** of the heating device **50**.

(245) Air drawn into the heating device **50** through the first exhaust air duct **41**, the second exhaust air duct **44**, the third exhaust air duct **47**, and the outside air inlet port **423** may pass through the heat exchange channel **42** and flow into the fan **60** by the suction force of the fan **60**.

(246) Referring to FIG. 7, the air flowing through the first exhaust air duct **41**, the second exhaust

air duct **44**, the third exhaust air duct **47**, and the outside air inlet port **423** may meet in the heat exchange channel **42** to flow into the fan **60**.

(247) The third inlet port **424** connected to the third exhaust air duct **47** may protrude downwardly from the second exhaust air duct **44**. The air in the third exhaust air duct **47** may join the air in the second exhaust air duct **44** to flow into the heat exchange channel **42**.

(248) The outside air inlet port **423** communicating with the indoor space may protrude forward from the second exhaust air duct **44**. The air flowing into the outside air inlet port **423** through the outside air inlet **49** may join the air in the second exhaust air duct **44** to flow into the heat exchange channel **42**.

(249) The air flowing into the heat exchange channel **42** through the second exhaust air duct **44** may join the air flowing into the heat exchange channel **42** through the first exhaust air duct **41** to flow to the fan **60**.

(250) The heating device **50** may include a first support plate **576** extending downwardly from the base plate **575**, and a second support plate **577** extending downwardly from the base plate **575** and spaced apart from the first support plate **576**.

(251) A separation space **55** may be formed between the first support plate **576** and the second support plate **577**.

(252) The second exhaust air duct **44**, the third exhaust air duct **47**, and the dehumidification duct **46** may be disposed in the separation space **55**. The second exhaust air duct **44**, the third exhaust air duct **47** and the dehumidification duct **46** may be formed between the first support plate **576** and the second support plate **577**. The second exhaust air duct **44**, the third exhaust air duct **47**, and the dehumidification duct **46** may be disposed under the base plate **575**.

(253) The dehumidification duct **42** may be disposed under the base plate **575** and may extend forwardly to discharge the air forwardly through a hot air outlet **462**. When an opening member **463** (see FIG. **10**) which will be described later opens a front portion of the separation space **55**, the air discharged through the hot air outlet **462** may be discharged forwardly from the laundry treating apparatus **A**.

(254) A portion of the second exhaust air duct **44** disposed under the base plate **575** may be defined as the first exhaust air portion **441**.

(255) A portion of the dehumidification duct **46** disposed under the base plate **575** may be defined as the second duct section **461**.

(256) Hereinafter, a method of controlling a blowing direction of air by the switching device **70** will be described with reference to FIG. **8**. In FIG. **8**, (a) is a diagram illustrating an example of operation when air is supplied to the first supply air duct **43** by the operation of the switching device **70**, and (b) is a diagram illustrating an example of operation when air is supplied to the first supply air duct **43** and the second supply air duct **45** at the same time by the operation of the switching device **70**. The description of the switching device **70**, which will be described with reference to FIG. **8**, may be applied commonly to all embodiments of the laundry treating apparatus described with reference to FIGS. **1** to **20**. Even in this case, however, an opening direction of the discharge ports **425**, **426**, **427**, and **428**, an arrangement and connection structure of the exhaust air ducts **41**, **44**, and **47**, and the like may vary depending on the relative arrangement of the laundry treating machines included in the laundry treating apparatus.

(257) The fan **60** may be a Sirocco fan. The fan **60** may rotate to blow air in a direction perpendicular to the rotating shaft **61**. The fan **60** may blow air in a direction coming into contact with the rotation direction. The air blown by the fan **60** may be concentrated in a predetermined range of angles relative to the rotating shaft **61**.

(258) The fan **60** may include the rotating shaft **61** coupled to the fan motor and rotated thereby, a plurality of blades **62** spaced apart in a radially outward direction of the rotating shaft **61**, and an outer body **63** coupled to the blades **62** and extending in a rotation direction of the fan **60**. The outer body **63** may have an annular shape. The rotating shaft **61** and the blades **62** may be

connected by the outer body **63**. When the rotating shaft **61** rotates, the outer body **63** and the blades **62** may also be rotated together with the rotating shaft **61**.

(259) The rotating body **71** may include a rotating plate **71a** having the driven gear **713**, a scroll **71b** coupled to the rotating plate **71a**, and a shaft through hole **71c** formed in the rotating plate **71a**.

(260) The rotating plate **71a** may have a disk shape and may be disposed behind the fan **60**. The driven gear **713** may be formed in an annular shape on one side surface of the rotating plate **71a**. The driven gear **713** may be formed integrally with the rotating plate **71a**. When the driven gear **713** is rotated in engagement with the driving gear **712**, the rotating plate **71a** may be rotated in the same direction as the rotation direction of the fan **60**. The rotating plate **71a** may have the shaft through hole **71c**, through which the rotating shaft **61** passes. The rotating shaft **61** may pass through the shaft through hole **71c** to be coupled to the fan motor.

(261) The fan **60** may be disposed between the heat exchange channel **42** and the rotating plate **71a**. That is, the rotating plate **71a** may be disposed behind the heat exchange channel **42** and the fan **60**. The rotating plate **71a** may be disposed behind the fan **60** in the blowing duct **420**.

(262) The scroll **71b** may be integrally formed with the rotating plate **71a**. When the rotating plate **71a** is rotated, the scroll **71b** may also be rotated together. The scroll **71b** may extend in the rotation direction of the fan **60**. The scroll **71b** may be disposed to surround the fan **60**. The fan **60** may be disposed in the scroll **71b**.

(263) The scroll **71b** may include a blowing channel **72**. The blowing channel **72** may be a cut-out portion of an outer circumferential surface of the scroll **71b**. The scroll **71b** may cover the outside of the fan **60**, and the blowing channel **72** may be an outer region of the fan **60** which is not covered by the scroll **71b**. The air blown by the fan **60** may be discharged to the outside of the blowing duct **420** through the blowing channel **72**.

(264) When the scroll **71b** is rotated by the rotation of the rotating plate **71a**, the blowing channel **72** may be changed in position. That is, by the rotation of the scroll **71b**, the position of the blowing channel **72** may be changed relative to the rotating shaft **61**. By rotating the scroll **71b** to change the position of the blowing channel **72**, the driving motor **711** may control the direction of air discharged from the blowing duct **420**.

(265) A longitudinal section of the blowing duct **420** may have a square shape. Accordingly, by the rotation of the scroll **71b**, interference between the scroll **71b** and the blowing duct may be avoided.

(266) The blowing duct **420** may include a first wall **420a** disposed on an upper side of the fan **60**, a second wall **420b** disposed on a lower side of the fan **60**, a third wall **420c** disposed on one side of the fan **60**, and a fourth wall **420d** disposed on the other side of the fan **60**.

(267) The first discharge port **425** may protrude upwardly from the first wall **420a**. The second discharge port **427** may protrude toward the lateral side from the third wall **420c**. The third discharge port **426** may protrude downwardly from the second wall **420b**. The fourth discharge port **428** may protrude toward the lateral side from the fourth wall **420d**.

(268) Referring to (a) of FIG. **8**, the driving motor **711** may rotate the rotating body **71** by a first angle, and when the rotating body **71** is rotated by the first angle, the air blown by the fan **60** may be supplied to the first supply air duct **43**. In this case, the blowing channel **72** may communicate with only an inner space of the first discharge port **425**. Accordingly, the air blown by the fan **60** may be supplied to only the dryer **1**.

(269) Referring to (b) of FIG. **8**, the driving motor **711** may rotate the rotating body **71** by a second angle, and when the rotating body **71** is rotated by the second angle, the air blown by the fan **60** may be supplied to the first supply air duct **43** and the second supply air duct **45** at the same time. In this case, the blowing channel **72** may communicate with an inner space of the first discharge port **425** and an inner space of the second discharge port **427**. Accordingly, the air blown by the fan **60** may be supplied to the dryer **1** and the refresher **3** at the same time. The blowing channel **72** may include a first blowing channel **72a** communicating with the inner space of the first discharge port **425**, and a second blowing channel **72b** communicating with the inner space of the second

discharge port **427**. The air blown by the fan **60** may be supplied to the dryer **1** through the first blowing channel **72a**. The air blown by the fan **60** may be supplied to the refresher **3** through the second blowing channel **72b**.

(270) A user may control the switching device **70** by inputting a signal to the control panel **8**. Once the signal is input to the control panel **8**, the signal may be transmitted to the driving motor **711**, to control a rotation angle of the driving motor **711**. For example, when the user inputs, to the control panel **8**, a signal for supplying hot air to the dryer **1**, the driving motor **711** may rotate the rotating body **71** so that the blowing channel **72** may be moved to a position as illustrated in (a) of FIG. **8**. For example, when the user inputs, to the control panel **8**, a signal for supplying hot air to the dryer **1** and the refresher **3** at the same time, the driving motor **711** may rotate the rotating body **71** so that the blowing channel **72** may be moved to a position as illustrated in (b) of FIG. **8**.

(271) Hereinafter, a structure for supplying hot air and steam by the heating device **50** to each of laundry treating machines **1**, **2**, and **3** will be described with reference to FIG. **9**.

(272) The heating device **50** may be disposed on an upper side of the second upper panel **203**. The heating device **50** may be disposed in the cabinet **10** of the dryer **1**.

(273) The switching device **70** may be disposed on the upper side of the second panel **203**. The switching device **70** may be disposed in the cabinet **10** of the dryer **1**.

(274) The blowing duct **420** may be connected to the first supply air duct **43**, the second supply air duct **45**, and the third supply air duct **48**.

(275) The first supply air duct **43** may extend upwardly from the blowing duct **420**. The first supply air duct **43** may be connected to the first drum **13**.

(276) The second supply air duct **45** may extend from the blowing duct **420** to a lateral side. The second supply air duct **45** may be connected to the refresher **3**.

(277) The third supply air duct **48** may extend downwardly from the blowing duct **420**. The third supply air duct **48** may pass through the separation space **55** to extend into the second cabinet **20**.

(278) The laundry treating apparatus A may include a first steam supply pipe **502a** connecting the steam generator **502** and the first drum **13**, a second steam supply pipe **502b** connecting the steam generator **502** and the refresher **3**, and a third steam supply pipe **502c** connecting the steam generator **502** and the tub **23**.

(279) The steam generator **502** may be disposed in the heating device **50**. The steam generated by the steam generator **502** may be sprayed into the first drum **13** through the first steam supply pipe **502a**. The steam generated by the steam generator **502** may be sprayed into the inner space **33** of the refresher **3** through the second steam supply pipe **502b**. The steam generated by the steam generator **502** may be sprayed into the second drum **24** through the third steam supply pipe **502c**.

(280) The first steam supply pipe **502a** may extend upwardly from the steam generator **502** to be connected to the first drum **13**.

(281) The second steam supply pipe **502b** may extend from the steam generator **502** to the lateral side, to be connected to the refresher **3**.

(282) The third steam supply pipe **502c** may extend downwardly from the steam generator **502** to be connected to the tub **23**.

(283) The steam generated by the steam generator **502** may flow to each of the first drum **13**, the second drum **24**, and the inner space **33** of the refresher **3** by the blowing force of the fan **60**. That is, by pressurizing the steam generated by the steam generator **502**, the fan **60** may cause the steam to flow to the first drum **13**, the second drum **24**, and the inner space **33** of the refresher **3**.

(284) A valve for controlling an amount of steam flow may be provided for each of the first steam supply pipe **502a**, the second steam supply pipe **502b**, and the third steam supply pipe **502c**. By adjusting an opening degree of the valve, the controller **81** may adjust the amount of steam supplied to each of the first drum **13**, the second drum **24**, and the inner space **33** of the refresher **3**.

(285) The washing machine **2** may be connected to a cold water supply pipe **278** for supplying cold water to the tub **23**, and a hot water supply pipe **279** for supplying hot water to the tub **23**.

(286) The steam generator **502** may be connected to a third water supply pipe **277** branching off from the cold water supply pipe **278** or the hot water supply pipe **279**. The steam generator **502** may be connected to the third water supply pipe **277** branching off from the hot water supply pipe **279**.

(287) The steam generator **502** may be supplied with hot water through the third water supply pipe **277**. The steam generator **502** may generate steam by heating the water supplied through the third water supply pipe **277**.

(288) Water supply ports **273** and **274** may be disposed closer to the second upper panel **203** than to the second lower panel **204**. The steam generator **502** may be disposed between the second upper panel **203** and the first drum **13**. Accordingly, as a distance between the steam generator **502** and the water supply pipes **278** and **279** becomes shorter, the third water supply pipe **277** may be reduced in length.

(289) Hereinafter, a connection structure of the first cabinet **10** and the second cabinet **20** will be described with reference to FIG. **10**.

(290) The base plate **575** of the heating device **50** may be spaced from the upper side of the second upper panel **203** of the washing machine **2**. The separation space **55** may be formed between the base plate **575** and the second upper panel **203**.

(291) The first side panels **105** and **106** of the dryer **1** may protrude downwardly below the base plate **575**. The first side panels **105** and **106** may be referred to as the “first side walls.”

(292) The first side walls **105** and **106** may include a first outer wall **105** forming one side surface of the laundry treating apparatus **A**, and a first inner wall **106** facing the third cabinet **30**.

(293) The heating device **50** may include the first support plate **576** extending downwardly from the base plate **575**. The first support plate **576** may be disposed inside the first outer wall **105**.

(294) The heating device **50** may include the second support plate **577** extending downwardly from the base plate **575**. The second support plate **577** may be disposed inside the first inner wall **106**.

(295) The base plate **575** and the support plates **576** and **577** may be integrally formed with each other. The first outer wall **105** and the first support plate **576** may be integrally formed with each other. The first inner wall **106** and the second support plate **577** may be integrally formed with each other.

(296) The first side walls **105** and **106** may include first protrusions **105a** and **106a** protruding downwardly. The first outer wall **105** may include a first outer protrusion **105a** protruding downwardly. The first inner wall **106** may include a first inner protrusion **106a** protruding downwardly. The first protrusions **105a** and **106a** may protrude downwardly from a lower end of the first side walls **105** and **106**.

(297) The second cabinet **20** may include first recesses **203a** into which the first protrusions **105a** and **106a** are inserted. The first recesses **203a** may be formed in the second upper panel **203**. The first recesses **203a** may be formed at positions vertically corresponding to the first protrusions **105a** and **106a**.

(298) The support plates **576** and **577** may include second protrusions **576a** and **577a** protruding downwardly. The first support plate **576** may include a second outer protrusion **576a** protruding downwardly. The second support plate **577** may include a second inner protrusion **577a** protruding downwardly. The second protrusions **576a** and **577a** may protrude downwardly from a lower end of the support plates **576** and **577**.

(299) The second cabinet **20** may include second recesses **203b** into which the second protrusions **576a** and **577a** are inserted. The second recesses **203b** may be formed in the second upper panel **203**. The second recesses **203b** may be formed at positions vertically corresponding to the second protrusions **576a** and **577a**.

(300) The first protrusions **105a** and **106b** and the second protrusions **576a** and **577a** may be referred to as “protrusions.” The first recesses **203a** and the second recesses **203b** may be referred to as “recesses.”

- (301) The first cabinet **10** and the second cabinet **20** may be coupled to each other as the protrusions **105a**, **106b**, **576a**, and **577a** are inserted into the recesses **203a** and **203b**.
- (302) The machine room **S** may be formed on the upper side of the base plate **575**. Accordingly, the machine room **S** may be spaced from the upper side of the second upper panel **203**.
- (303) The separation space **55** may be formed between the first support plate **576** and the second support plate **577**.
- (304) The second exhaust air duct **44**, the dehumidification duct **46**, and the third exhaust air duct **47** may be disposed in the separation space **55**. The second exhaust air duct **44**, the dehumidification duct **46**, and the third exhaust air duct **47** may be disposed between the second upper panel **203** and the base plate **575**.
- (305) The third exhaust air duct **47** may protrude downwardly toward the second upper panel **203**. The third exhaust air duct **47** may include a first connection duct **48a** extending downwardly from the blowing duct **230**, and a second connection duct **48b** connected to the tub **23**.
- (306) The first connection duct **48a** may be disposed in the separation space **55**.
- (307) The second connection duct **48b** may extend downwardly from the second upper panel **203** to be connected to the tub **23**. The second connection duct **48b** may have a first insertion hole **48s**, which is formed on the inside thereof, and into which the first connection duct **48a** is inserted.
- (308) The first connection duct **48a** is inserted into the first insertion hole **48s** to be fixed to the second connection duct **48b**.
- (309) The third inlet port **424** may be connected to the second exhaust air duct **44**, and may be disposed in the separation space **55**.
- (310) The third inlet port **424** may be inserted into a second insertion hole **47s**, formed on the inside of the third exhaust air duct **47**, to be fixed to the third exhaust air duct **47**.
- (311) When the first cabinet **10** and the second cabinet **20** are assembled, the first connection duct **48a** and the third inlet port **424** are inserted into the first insertion hole **48s** and the second insertion hole **47s**, respectively, to be fixed thereto, thereby facilitating the assembly and alignment of the first cabinet **10** and the second cabinet **20**.
- (312) The laundry treating apparatus **A** may include an auxiliary panel **58** disposed behind the separation space **55**.
- (313) The auxiliary panel **58** may shield a rear side of the separation space **55**. The auxiliary panel **58** may be connected to the first rear panel **102** and the second rear panel **202**. The first rear panel **102** and the second rear panel **202** may be connected to each other by the auxiliary panel **58**.
- (314) The auxiliary panel **58** may include a duct through hole **59**, through which the second exhaust air duct **44** passes. The second exhaust duct **44** may extend into the separation space **55** by passing through the auxiliary panel **58**.
- (315) The auxiliary panel **58** may be coupled to the first side panels **105** and **106** and the support plates **576** and **577**.
- (316) The opening member **463** may shield the front side of the separation space **55**. The opening member **463** may be disposed in front of the dehumidification duct **46** and the outside air inlet port **423**.
- (317) The laundry treating apparatus **A** may include a hinge **463a** connected to the opening member **463**, and a motor **463b** rotating the hinge **463a**.
- (318) The hinge **463a** may be rotatably connected to the first front panel **101**. The hinge **46a** may extend in a left-right direction. The opening member **46** may be rotated in a front-rear direction with the hinge **463a** serving as a rotational axis. The opening member **463** may be integrally formed with the hinge **463a**. When the motor **463b** rotates the hinge **463a**, the opening member **463** may be rotated together with the hinge **463a**. The opening member **463** may rotate forward to open the front side of the separation space **55**. Once the opening member **463** opens the front side of the separation space **55**, outside air of the laundry treating apparatus **A** may flow into the heat exchange channel **44** through the outside air inlet port **423**, and the air passing through the dehumidification

duct **46** may be discharged to the outside of the laundry treating apparatus A.

(319) The controller **81** may be electrically connected to the motor **463b**. The controller **81** may control the operation of the motor **463b**. The user may open the separation space **55** by manipulating the control panel **8**.

(320) Hereinafter, a longitudinal width of the laundry treating apparatus A will be described with reference to FIG. **11**. The description of the widths of the laundry **1**, the washing machine **2**, and the refresher **3**, which will be described with reference to FIG. **11**, may be applied commonly to all embodiments of the laundry treating apparatus described with reference to FIGS. **1** to **20**.

(321) The longitudinal width **W4** of the refresher **3** may be smaller than the longitudinal width **W1** of the tower **9**. When the front surface **31a** of the refresher **3** is aligned with the front surface of the tower **9**, a gap **X** may be formed between the rear surface **30b** of the refresher **3** and the rear surfaces **10b** and **20b** of the tower **9**. The rear surface **30b** of the refresher **3** may be disposed in front of the rear surfaces **10b** and **20b** of the tower **9**, and may be disposed in front of the rear surfaces **10b** and **20b** of the tower **9** by the gap **X**.

(322) A portion of the first inner wall **106** of the dryer **1** and a portion of the second inner wall **206** of the washing machine **2** may be disposed behind the rear surface **30b** of the refresher **3**. The portion of the first inner wall **106** and the portion of the second inner wall **296** may be exposed at the rear side of the third cabinet **30**.

(323) The laundry treating apparatus A may include the rear case **310** disposed at the rear side of the inner space **33** of the refresher **3**. The rear case **310** may be disposed at the rear side of the third cabinet **30**.

(324) The rear case **310** may be connected to each of the dryer **1**, the washing machine **2**, and the refresher **3**.

(325) The rear case **310** may provide a space for accommodating the second supply air duct **45** and the second exhaust air duct **44**. The second supply air duct **45** and the second exhaust air duct **44** may be accommodated in the rear case **310**.

(326) The second supply air duct **45** and the second exhaust air duct **44** for circulating hot air to the refresher **3** may be disposed at the rear side of the third cabinet **30**.

(327) The second supply air duct **45** and the second exhaust air duct **44** may be disposed behind the third rear panel **302**.

(328) The second supply air duct **45** may extend downwardly from the heating device **50** to be connected to the inner panel **34**.

(329) The second supply air duct **45** may face the second inner wall **206** of the washing machine **2**. The second supply air duct **45** may be disposed side by side with the second inner wall **206**.

(330) The second supply air duct **45** may include the first hot air duct **451** and the second hot air duct **452**. The first hot air duct **451** may include a first connection part **451a** connected to the heating device **50**, a first extension part **451b** extending downwardly from the first connection part **451a**, and a second connection part **451c** connected to the second hot air duct **452**.

(331) The first connection part **451a** may pass through the first inner wall **106** of the first cabinet **10**. The first connection part **451a** may be connected to the blowing duct **420**, and the air blown by the fan **60** may be introduced through the first connection part **451a**. The first connection part **451a** may extend horizontally from the heating device **50**.

(332) The first extension part **451b** may be bent downwardly from the first connection part **451a**. The first extension part **451b** may extend downwardly from one end of the first connection part **451a**. The first extension part **451b** may face the second inner wall **206** of the washing machine **2**, and may be disposed side by side with the second inner wall **206**.

(333) The second connection part **451c** may be connected to the third rear panel **302** of the third cabinet **30**. The second connection part **451c** may be connected to the second hot air duct **452**. That is, the third rear panel **302** may be disposed between the second hot air duct **452** and the second connection part **451c**. The second connection part **451c** may extend from the first extension part

451b in the front-rear direction.

(334) Water supply ports **273** and **274** may be connected to the water supply pipes **278** and **279** which are connected to the external water source. The tub **23** may be supplied with water from the external water source through the water supply pipes **278** and **279**.

(335) The tub **23** may be supplied with cold water through the cold water supply pipe **278**, and may be supplied with hot water through the hot water supply pipe **279**.

(336) The laundry treating apparatus **A** may include a cooling pipe **275** branching off from the cold water supply pipe **289** or the hot water supply pipe **279**. The cooling pipe **275** may branch off from the cold water supply pipe **278**.

(337) The cooling pipe **275** may branch off from the cold water supply pipe **278** to be heat exchanged with the second supply air duct **45**. The cooling pipe **275** may extend side by side with the second supply air duct **45** or may come into contact with the second supply air duct **45**. Hot air flowing in the second supply air duct **45** may be heat exchanged with water flowing in the cooling pipe **275**, such that temperature of the hot air may be reduced. The cooling pipe **275** may be disposed to be heat exchanged with the first extension part **451b** or may come into contact with the first extension part **451b**.

(338) The cooling pipe **275** may be connected to the drain pump **26**. Water branched off from the cold water supply pipe **278** and flowing into the cooling pipe **275** may be heat exchanged with the hot air flowing in the second supply air duct **45**, and then may flow into the drain pump **26**. The drain pump **26** may discharge the water, introduced through the cooling pipe **275**, to the outside of the laundry treating apparatus **A**.

(339) Clothes treated by the refresher **3** may be susceptible to damage when dried at a high temperature. It may be required to supply hot air at a relatively lower temperature to the clothes dried by the refresher **3** than the clothes treated by the dryer **1** and the washing machine **2**. The hot air at a high temperature generated by the heating device **50** may be supplied immediately to the dryer **1** or the washing machine **2**. By contrast, the high temperature hot air generated by the heating device **50** is required to be cooled before being supplied to the refresher **3**. Accordingly, in the laundry treating apparatus **A** according to the present disclosure, hot air at a lower temperature than the hot air supplied to the dryer **1** and the washing machine **2** may be supplied to the refresher **3** by using the water supply pipes **275**, **278**, and **279**, thereby preventing damage to the clothes placed in the refresher **3**. In addition, by discharging water, used for reducing the temperature of the hot air supplied to the refresher **3**, to the outside through the drain pump **26**, it is possible to effectively manage the water used for cooling the hot air.

(340) The second exhaust air duct **44** may include a first exhaust air portion **441** connected to the refresher **3**, a second exhaust air portion **442** extending downwardly from the first exhaust air portion **441**, and a third exhaust air portion **443** connected to the heating device **50**.

(341) The first exhaust air portion **441** may be connected to the third rear panel **302** of the third cabinet **30**. The first exhaust air portion **441** may communicate with the inner space **33** of the refresher **3**, and air circulating in the refresher **3** may flow to the first exhaust air portion **441**. The first exhaust air portion **441** may be connected to the exhaust air hole **309**. The first exhaust air portion **441** may extend rearwardly from the third cabinet **30**. A position where the first exhaust air portion **441** and the third cabinet **30** are connected may be between the third upper panel **303** and the hanger **36**. The exhaust air hole **309** may be formed between the third upper panel **303** and the hanger **36**.

(342) The second exhaust air portion **442** may be bent downwardly from the first exhaust air portion **441**. The second exhaust air portion **442** may extend downwardly from the first exhaust air portion **441**. The second exhaust air portion **442** may extend downwardly from one end of the first exhaust air portion **441**. The second connection part **442** may face the first inner wall **106** of the dryer **1**, and may be disposed side by side with the first inner wall **106**.

(343) The third exhaust air portion **443** may extend into the separation space **55**. The third exhaust

air portion **443** may extend in the front-rear direction from the second exhaust air portion **442**. The third exhaust air portion **443** may be connected to the heating device **50** in the separation device **55**. (344) The rear case **310** may have a longitudinal width **W6**. The longitudinal width **W6** of the rear case **310** may be smaller than the longitudinal width **W1** of the tower **9**. The longitudinal width **W6** of the rear case **310** may be equal to the gap **X**.

(345) The rear surface **310b** of the rear case **310** may be aligned with the rear surfaces **10b** and **20b** of the tower **9**. The rear surface **310b** of the rear case **310** may be disposed on the same plane as the rear surfaces **10b** and **20b** of the tower **9**.

(346) A sum (**W4+W6**) of the longitudinal width **W6** of the rear case **310** and the longitudinal width **W4** of the refresher **3** may be equal to the longitudinal width **W1** of the tower **9**. However, it is also possible that the sum (**W4+W6**) of the longitudinal width **W6** of the rear case **310** and the longitudinal width **W4** of the refresher **3** may be similar to or greater than the longitudinal width **W1** of the tower **9**.

(347) In the laundry treating apparatus **A** according to an aspect of the present disclosure, the rear case **310** is disposed at a rear side of the refresher **3**, such that a constant longitudinal width may be formed. That is, by providing the rear case **310** on the rear side of the refresher **3**, not only the front surface **31a** of the refresher **3** may be aligned with the front surface of the tower **9**, but also the rear surface **310b** of the rear case **310** may be aligned with the rear surfaces **10b** and **20b** of the tower **9**.

(348) The rear case **310** may have a vertical height **310H**. The vertical height **310H** may be equal to the height **3H** of the refresher **3** and the height **9H** of the tower **9**. However, it is also possible that the height **310H** of the rear case **310** may be similar to or greater than the height **3** of the refresher **3** and the height **9H** of the tower **9**.

(349) The rear case **310** may be fixed to the refresher **3** by a fastening member **316** passing through a fastening plate **317** extending in the front-rear direction. There may be a plurality of fastening plates **317** which are vertically spaced apart from each other. The fastening plates **317** may extend in the front-rear direction to be connected to respective side walls of the rear case **310** and the third cabinet **30**. The fastening member **316** may pass through the respective side walls of the rear case **310** and the third cabinet **30** and the fastening plate **317**.

(350) Hereinafter, a laundry treating apparatus **A'** according to another embodiment of the present disclosure will be described with reference to FIGS. **12** and **13**. The above description with reference to FIGS. **1** to **11** may also be applied to the description of the dryer **1**, the washing machine **2**, the refresher **3**, and the heating device **50** in the following description of the laundry treating apparatus **A'** which will be described with reference to FIGS. **12** and **13**.

(351) Referring to FIG. **12**, the second supply air duct **450** may be connected to the upper portion of the refresher **3**, and the second exhaust air duct **440** may be connected to the lower portion of the refresher **3**.

(352) The supply air hole **308** connected to the second supply air duct **450** may be formed at the upper portion of the cabinet **30**. The supply air hole **308** may be formed above the hanger **36**. The supply air hole **308** may be formed below an inner surface **303a** of the third upper panel **303**. The supply air hole **308** may be formed between the third upper panel **303** and the hanger **36**.

(353) The third upper panel **303** may include the inner surface **303a** directed toward the inner space **33** of the cabinet **30**, an outer surface **303b** directed toward the outside of the cabinet **30**, and an inclined surface **303c** extending at an incline downwardly from the inner surface **303a**. The inner surface **303a** may be referred to as a "first surface." The inclined surface **303c** may be referred to as a "second surface." The third upper panel **303** may be referred to as an "upper wall."

(354) The first surface **303a** may be separated from an upper side of the hanger **36**. A space may be formed between the first surface **303a** and the hanger **36**.

(355) The second surface **303c** may extend at an incline downwardly from a rear end of the first surface **303a**. The second surface **303c** may extend rearwardly from the first surface **303a**. The second surface **303c** may be disposed above the hanger **36**. The second surface **303c** may have an

inclination angle θ with respect to a horizontal direction.

(356) The supply air hole **308** may be formed on the second surface **303c**. The supply air hole **308** may be open obliquely downwardly on the second surface **303c**.

(357) The supply air hole **308** may be formed above the hanger **36**. A first virtual line diagram **H1** extending in a horizontal direction from the supply air hole **308** and a second virtual line diagram **H2** extending in the horizontal direction from the hanger **36** are defined as follows. The first line diagram **H1** may be disposed above the second line diagram **H2**. The first line diagram **H1** and the second line diagram **H2** may have a height difference **D**. The supply air hole **308** may be spaced apart from the hanger **36** by the height difference **D**.

(358) The supply air duct **450** may be connected to the supply air hole **308**. The supply air duct **450** may be coupled to the upper wall **303**. The supply air duct **450** may be connected to the second surface **303c**. The supply air duct **450** may pass through the third rear panel **302**. The third rear panel **302** may be referred to as a “rear panel.”

(359) The rear panel **302** may have the inner surface **302a** directed toward the inner space **33** of the cabinet **30** and the outer surface **302b** directed toward the outside of the cabinet **30**. The supply air hole **308** may be disposed in front of the inner surface **302a** of the rear panel **302**.

(360) The supply air duct **450** may include a first hot air duct **453** connected to the heating device **50**, and a second hot air duct **454** connecting the first hot air duct **453** and the supply air hole **308**.

(361) The first hot air duct **453** may extend upwardly. The second hot air duct **454** may be integrally formed with the first hot air duct **453**. The second hot air duct **454** may extend upwardly and convexly. The second hot air duct **454** may extend upwardly and convexly from the first hot air duct **453**, to be connected to the supply air hole **308**.

(362) The first hot air duct **453** may be disposed behind the rear panel **302**. The first hot air duct **453** may extend upwardly from the rear side of the rear panel **302**. The second hot air duct **454** may pass through the rear panel **302** to be connected to the supply air hole **308**.

(363) The exhaust air hole **309** connected to the exhaust air duct **440** may be disposed at the lower portion of the cabinet **30**. The exhaust air hole **309** may be disposed below the supply air hole **308**.

(364) The exhaust air hole **309** which is open may be formed in the rear panel **302**. The exhaust air hole **309** may be open from the inner surface **302a** of the rear panel to the outer surface **302b** of the rear panel **302**. The exhaust air hole **309** may refer to an open portion of the lower side of the rear panel **302**.

(365) The exhaust air duct **440** may be connected to the exhaust air hole **309**. The exhaust air duct **440** may be coupled to the rear panel **302**. The exhaust air duct **440** may be connected to the outer surface **302b** of the rear panel **302**. The exhaust air duct **440** may pass through the rear panel **302**.

(366) The exhaust air duct **440** may include a first exhaust air portion **444** connected to the rear panel **302**, and a second exhaust air portion **445** extending upwardly from the first exhaust air portion **444**.

(367) The first exhaust air portion **444** may extend rearwardly from the rear panel **302**. The second exhaust air portion **445** may be integrally formed with the first exhaust air portion **444**. The second exhaust air portion **445** may extend upwardly from the first exhaust air portion **444**.

(368) The exhaust air duct **440** may be disposed behind the rear panel **302**. The second exhaust air portion **445** may extend upwardly from the rear side of the rear panel **302**.

(369) The filter **37** may be disposed in the exhaust air hole **309**. The filter **37** may be disposed on the rear panel **302**. The filter **37** may be disposed between the inner surface **302a** of the rear panel **302** and the outer panel **302b** of the rear panel **302**. The filter **37** may be disposed at the lower portion of the cabinet **30**. As the filter **37** is disposed at the lower portion of the cabinet **30**, a user may easily remove and clean the filter **37**.

(370) The filter **37** may have the filter insertion hole **371** which is open toward the inner space **33** of the cabinet **30**, and the filter net **372** disposed at a rear portion of the filter insertion hole **371**.

(371) The filter insertion hole **371** may be disposed behind the inner surface **302a** of the rear panel

302. The filter net **372** may be disposed in front of the outer surface **302b** of the rear panel **302**.

(372) A plate **34'** may be disposed at the lower portion of the cabinet **30**. The plate **34'** may include a first plate **344** having a dust hole **346** formed therein which is vertically open, and a second plate **345** disposed under the first plate **344**.

(373) The first plate **344** may be disposed at the lower portion of the inner space **33**. The first plate **344** may extend at a downward incline in a forward direction. The dust hole **346** may be vertically open in the first plate **344**. Dust in the inner space **33** may pass through the dust hole **346** to be accumulated on the top of the second plate **345**.

(374) The second plate **345** may extend horizontally from the lower side of the first plate **344**. The second plate **345** may be withdrawn to the outside of the cabinet **30**. By opening the door **31**, a user may take the second plate **345** out of the cabinet **30**.

(375) The exhaust air hole **309** may be disposed above the first plate **344**. The exhaust air hole **309** may be disposed above a lower end of the first plate **344**.

(376) As the supply air hole **308** is disposed at the upper portion of the refresher **3**, and the exhaust air hole **309** is disposed at the lower portion of the refresher **3**, the hot air supplied into the inner space **33** through the supply air hole **308** may sufficiently circulate in the inner space **33**. The hot air supplied to the upper portion of the inner space **33** through the supply air hole **308** may flow downwardly to return to the heating device **50** through the exhaust air hole **309** formed at the lower portion. The positions of the supply air hole **308** and the exhaust air hole **309** may promote the diffusion of hot air, supplied through the supply air hole **308**, into the inner space **33**.

(377) Referring to FIG. **13**, the supply air duct **450** may connect the upper portion of the refresher **3** and the heating device **50**, and the exhaust air duct **440** may connect the lower portion of the refresher **3** and the heating device **50**.

(378) The heating device **50** may be disposed at a position corresponding to a middle height of the refresher **3**. The heating device **50** may be positioned at a height between the supply air hole **308** and the exhaust air hole **309**. The supply air hole **308** may be disposed above the heating device **50**, and the exhaust air hole **309** may be disposed below the heating device **50**.

(379) The supply air duct **450** may connect the heating device **50** and the supply air duct **308**. The supply air hole **308** may be disposed above the hanger **36**, and the supply air duct **450** may be connected to the supply air hole **308** at a position above the hanger **36**. The supply air duct **450** may be coupled to the rear panel **302** and may pass through the rear panel **302**.

(380) The supply air duct **450** may face the first inner wall **106** of the dryer **1**.

(381) The supply air duct **450** may include the first hot air duct **453** connected to the heating device **50**, and the second hot air duct **454** connecting the first hot air duct **453** and the supply air hole **308**.

(382) The first hot air duct **453** may extend from the heating device **50** to a lateral side. After extending from the heating device **50** to the lateral side, the first hot air duct **453** may be bent upwardly from the rear side of the rear panel **302**.

(383) The second hot air duct **454** may extend upwardly and convexly from an upper end of the first hot air duct **453**. The second hot air duct **454** may be disposed above the hanger **36**.

(384) The exhaust air duct **440** may connect the heating device **50** and the exhaust air hole **309**. The exhaust air duct **440** may be coupled to the rear panel **302** and may pass through the rear panel **302**.

(385) The exhaust air duct **440** may face the second inner wall **206** of the washing machine **2**.

(386) The exhaust air duct **440** may include the first exhaust air portion **444** connected to the exhaust air hole **309** and the second exhaust air portion **445** extending upwardly from the first exhaust air portion **444**.

(387) The first exhaust air portion **444** may extend rearwardly from the exhaust air hole **309**.

(388) The second exhaust air portion **445** may extend upwardly from a rear end of the first exhaust air portion **444**. The second exhaust air portion **445** may extend upwardly from the rear side of the rear panel **302**. After extending upwardly from the rear side of the rear panel **302**, the second exhaust air portion **445** may be bent to the lateral side to be connected to the heating device **50**.

(389) Hereinafter, laundry treating apparatuses B and B' according to other embodiments of the present disclosure will be described with reference to FIGS. **14** to **20**.

(390) The description of the dryer **1**, the washing machine **2**, the refresher **3**, and the heating device **50**, which are described above with reference to FIGS. **1** to **13**, may also be applied to laundry treating apparatuses according to the embodiments of the present disclosure described with reference to FIGS. **14** to **20**.

(391) Further, the description of components illustrated in FIGS. **1** to **13** may also be applied to FIGS. **14** to **20**, even when the corresponding components are not illustrated in the description of the laundry treating apparatuses with reference to FIGS. **14** to **20**. For example, even when the rear case **310** is not illustrated in FIGS. **14** to **20**, the description of the rear case **310** described with reference to FIGS. **1** to **13** may also be applied to the description of the rear case **310** given with reference to FIGS. **14** to **20**.

(392) Referring to FIG. **14**, in the laundry treating apparatus B, the dryer **1** may be disposed under the washing machine **2**, and the heating device **50** may be disposed at a lower portion of the dryer **1**.

(393) The second upper panel **203** of the washing machine **2** and the third upper panel **303** of the refresher **3** may be disposed on the same horizontal plane.

(394) The first lower panel **104** of the dryer **1** and the third lower panel **304** of the refresher **3** may be disposed on the same horizontal plane.

(395) The heating device **50** may be disposed in the dryer **1**. The heating device **50** may be disposed in the first cabinet **10**. The heating device **50** may be disposed at a lower portion of the first cabinet **10**.

(396) Referring to FIG. **15**, the heating device **50** may be disposed under the first drum **13**.

(397) The heating device **50** may be disposed at the lower portion of the first cabinet **10**, and the machine room S, in which the heating device **50** is disposed, may be formed at the lower portion of the first cabinet **10**.

(398) The first supply air duct **43** may extend upwardly from the heating device **50** to be connected to the first drum **13**.

(399) The first exhaust air duct **41** may extend downwardly from the first drum **13** to be connected to the heating device **50**.

(400) Referring to FIG. **16**, the supply air hole **308** and the exhaust air hole **309** of the refresher **3** may be disposed at the lower portion of the refresher **3**.

(401) The second supply air duct **45** may be connected to the lower portion of the third cabinet **30**.

(402) The supply air hole **308** connected to the second supply air duct **45** may be disposed at the lower portion of the cabinet **3**. The supply air hole **308**, which is open toward the inner space **33**, may be formed in the inner panel **34**. The supply air hole **308** may be formed in the second inner panel **342**.

(403) The supply air duct **45** may be connected to the supply air portion **308**. The supply air duct **45** may be coupled to the third rear panel **302**. The supply air duct **45** may pass through the third rear panel **302**.

(404) The rear panel **302** may include the inner surface **302a** directed toward the inner space **33** of the cabinet **30** and the outer surface **302b** directed toward the outside of the cabinet **30**. The supply air hole **308** may be disposed in front of the inner surface **302a** of the rear panel **302**.

(405) The supply air duct **45** may include a first hot air duct **451** connected to the heating device **50**, and a second hot air duct **452** connecting the first hot air duct **451** and the supply air hole **308**.

(406) The first hot air duct **451** may extend to the lateral side. The second hot air duct **452** may be integrally formed with the first hot air duct **451**. The second hot air duct **452** may extend upwardly. The second hot air duct **452** may extend upwardly from the first hot air duct **451**, to be connected to the supply air hole **308**.

(407) The first hot air duct **451** may be disposed behind the rear panel **302**. The first hot air duct

451 may extend to the lateral side from the rear side of the rear panel **302**. The second hot air duct **452** may pass through the rear panel **302** to be connected to the supply air hole **308**.

(408) The supply air duct **45** may extend horizontally from the rear side of the rear panel **302**. The supply air duct **45** may extend horizontally from the rear side of the rear panel **302** to be connected to the heating device **50**. The first hot air duct **451** may extend horizontally from the rear side of the rear panel **302**.

(409) The second exhaust air duct **44** may be disposed at the lower portion of the third cabinet **30**.

(410) The exhaust air hole **309** connected to the exhaust air duct **44** may be disposed at the lower portion of the cabinet **30**. The exhaust air hole **309** may be disposed below the supply air hole **308**.

(411) The exhaust air hole **309** may be open in the inner panel **34**. The exhaust air hole **309** may be open in the first inner panel **341**. The exhaust air hole **309** may be disposed at a front portion of the first inner panel **341**. The exhaust air hole **309** may be separated from the front side of the supply air hole **308**.

(412) The exhaust air duct **44** may be connected to the exhaust air hole **309**. The exhaust air duct **44** may be coupled to the inner panel **34**. The exhaust air duct **44** may be connected to the lower side of the inner panel **34**.

(413) The exhaust air duct **44** may extend horizontally from the lower side of the inner panel **34**. The exhaust air duct **44** may extend horizontally from the lower side of the inner panel **34** to be connected to the heating device **50**.

(414) The filter **37** may be disposed in the exhaust air hole **309**. The filter **37** may be disposed on the inner panel **34**.

(415) Referring to FIG. **17**, the laundry treating apparatus **B** may include a duct system connecting the dryer **1**, the washing machine **2**, the refresher **3**, and the heating device **50**.

(416) The blowing duct **420** may include a first discharge port **425** connected to the first supply air duct **43**. The blowing duct **420** may include a second discharge port **427** connected to the second supply air duct **45**. The blowing duct **420** may include a fourth discharge port **428** connected to the dehumidification duct **46**. The third supply air duct **48** may branch off from the second supply air duct **45**, and a third discharge port **426** may be formed at a portion where the third supply air duct **48** branches off from the second supply air duct **45**.

(417) The first discharge port **425** may protrude upwardly from the blowing duct **420**. The first supply air duct **43** may connect the first drum **13** and the first discharge port **425**.

(418) The second discharge port **427** may protrude from the flowing duct **420** to the lateral side. The second supply air duct **45** may connect the refresher **3** and the second discharge port **427**. The second supply air duct **45** may connect the supply air hole **308** and the second discharge port **427**.

(419) The third discharge port **426** may protrude upwardly from the second supply air duct **45**. The third supply air duct **48** may connect the tub **23** and the third discharge port **426**. The third supply air duct **48** may connect the tub **23** and the second supply air duct **45**.

(420) The fourth discharge port **428** may protrude from the blowing duct **420** to the lateral side. The fourth discharge port **428** may protrude in a direction opposite to the second discharge port **427**. The dehumidification duct **45** may be connected to the fourth discharge port **428**.

(421) The hot air flowing into the first drum **13** through the first supply air duct **43** may dry the laundry placed in the first drum **13**, and then may flow into the heat exchange channel **42** through the first exhaust air duct **41**. The first drum **13** may include the front cover **131** disposed on a front side, and the rear cover **132** disposed on a rear side. The first supply air duct **43** may be connected to the rear cover **132**, and the first exhaust air duct **41** may be connected to the front cover **131**.

(422) The first exhaust air duct **41** may connect the first drum **13** and the heat exchange channel **42**. The first exhaust air duct **41** may extend downwardly from the first drum **13** to be connected to the heat exchange channel **42**.

(423) The first inlet port **421** connected to the first exhaust air duct **41** may be formed at the inlet end **42A** of the heat exchange channel **42**. The first inlet port **421** may extend upwardly from the

heat exchange channel **42**. The first inlet port **421** may extend upwardly from the case **570** of the heating device **50**.

(424) The laundry treating apparatus B may include the first opening and closing valve **41a** disposed in the first exhaust air duct **41**. The first opening and closing valve **41a** may control a flow rate of air in the first exhaust air duct **41**. The first opening and closing valve **41a** may block an air flow in the first exhaust air duct **41**. The first opening and closing valve **41a** may block the air flow in the first exhaust air duct **41** when the hot air is not supplied into the first drum **13** through the first exhaust air duct **43**.

(425) The hot air flowing into third cabinet **30** through the second supply air duct **45** may dry the laundry placed in the third cabinet **30**, and then may flow into the heat exchange channel **42** through the second exhaust air duct **44**. The second supply air duct **45** may be connected to the third rear panel **302** of the third cabinet **30**. The second exhaust air duct **44** may be connected to the heat exchange channel **42** by passing through the third inner wall **306**.

(426) The second exhaust air duct **44** may connect the exhaust air hole **309** and the heat exchange channel **42**. The second exhaust air duct **44** may extend from the lower side of the third cabinet **30** to the lateral side, to be connected to the heat exchange channel **42**.

(427) The second inlet port **422** connected to the second exhaust air duct **44** may be formed at the inlet end **42A** of the heat exchange channel **42**. The second inlet port **422** may extend from the heat exchange channel **42** to the lateral side. The second inlet port **422** may extend from the third exhaust air duct **47** to the lateral side. The second inlet port **422** may extend from a first duct section **471** to the lateral side. Based on FIG. **17**, it is illustrated that the second inlet port **422** extends downwardly from the first duct section **471**, but this is merely for convenience of explanation. That is, rather than extending downwardly from the first duct section **471**, the second inlet port **422** may extend to the lateral side from the first duct section **471**.

(428) The second inlet port **422** may protrude from one side surface of the third exhaust air duct **47** to the lateral side. The second exhaust air duct **44** may connect the inner space **33** of the refresher **3** and the second inlet port **422**. The second exhaust air duct **44** may connect the inner space **33** of the refresher **3** and the third exhaust air duct **47**. The air in the second exhaust air duct **44** may join the air in the third exhaust air duct **47**, to flow into the heat exchange channel **42**.

(429) The laundry treating apparatus B may include the second opening and closing valve **44a** disposed in the second exhaust air duct **44**. The second opening and closing valve **44a** may control a flow rate of air in the second exhaust air duct **44**. The second opening and closing valve **44a** may block an air flow in the second exhaust air duct **44**. The second opening and closing valve **44a** may block the air flow in the second exhaust air duct **44** when the hot air is not supplied into the third cabinet **30** through the second supply air duct **45**.

(430) The hot air flowing into the tub **23** through the third supply air duct **48** may dry the laundry placed in the tub **23**, and then may flow into the heat exchange channel **42** through the third exhaust air duct **47**.

(431) The third exhaust air duct **47** may connect the tub **23** and the heat exchange channel **42**. The third exhaust air duct **47** may extend from an upper side of the tub **23**, to be connected to the heat exchange channel **42**.

(432) The third exhaust air duct **47** may include the first duct section **471** located between the base plate **575** of the heating device **50** and the first lower panel **104**. The first duct section **471** may be disposed in the separation space **55** of the heating device **50**. The first duct section **471** may extend forward or backward in the separation space **55**.

(433) The third inlet port **424** connected to the third exhaust air duct **47** may be formed at the inlet end **42A** of the heat exchange channel **42**. The third inlet port **424** may extend downwardly from the heat exchange channel **42**. The third inlet port **424** may extend downwardly from the case **570** of the heating device **50**.

(434) The laundry treating apparatus B may include the third opening and closing valve **47a**

disposed in the third exhaust air duct **47**. The third opening and closing valve **47a** may control a flow rate of air in the third exhaust air duct **47**. The third opening and closing valve **47a** may block an air flow in the third exhaust air duct **47**. The third opening and closing valve **47a** may block the air flow in the third exhaust air duct **47** when the hot air is not supplied into the tub **23** through the third supply air duct **48**.

(435) The outside air inlet port **423** may protrude forwardly from one side of the third exhaust air duct **47**. The outside air inlet port **423** may allow the indoor space and the third exhaust air duct **47** to communicate with each other. The air in the outside air inlet port **423** may join the air in the third exhaust air duct **47** to flow into the heat exchange channel **42**. The outside air inlet port **423** may have the outside air inlet **49** that is opened forward. The air drawn in through the outside air inlet **49** may join the air in the third exhaust air duct **47** to flow into the heat exchange channel **42**.

(436) Referring to FIG. **18**, the heating device **50** may be disposed at the lower portion of the dryer **1**, and may supply hot air to each of the dryer **1**, the washing machine **2**, and the refresher **3**.

(437) The second supply air duct **45** for supplying hot air to the refresher **3** may be disposed at the rear side of the third cabinet **30**. The second exhaust air duct **44** may be disposed under the inner panel **34**.

(438) The second supply air duct **45** may be disposed behind the third rear panel **302**.

(439) The second supply air duct **45** may extend from the heating device **50** in a lateral direction, to be connected to the inner panel **34**.

(440) The second supply air duct **45** may pass through the first inner wall **106** of the dryer **1**. The second supply air duct **45** may extend into the rear case **310** by passing through the first inner wall **106**.

(441) The first hot air duct **451** may be connected to the first inner wall **106**. The first hot air duct **451** may be connected to the blowing duct **420**, and air blown by the fan **60** may flow into the first hot air duct **451**. The first hot air duct **451** may extend horizontally from the heating device **50**.

(442) The second hot air duct **452** may be bent upwardly from the first hot air duct **451**. The second hot air duct **452** may extend upwardly from one end of the first hot air duct **451**.

(443) The supply air hole **308** of the refresher **3** may be disposed at the lower portion of the refresher **3**. As the heating device **50** and the supply air hole **308** are disposed at the lower portion of the laundry treating apparatus B, the second supply air duct **45** connecting the heating device **50** and the supply air hole **308** may be reduced in length, thereby minimizing heat loss occurring when the air heated by the heating device **50** flows toward the supply air hole **308**. In addition, the hot air supplied by the heating device **50** may be discharged to the inner space **33** through the supply air hole **308** disposed at the lower portion of the refresher **3**, such that the hot air may be distributed uniformly over the upper side of the refresher **3**.

(444) The second exhaust air duct **44** may be disposed under the inner panel **34**. The second exhaust air duct **44** may be connected to the exhaust air hole **309** formed in the inner panel **34**.

(445) The second exhaust air duct **44** may extend in the left-right direction, to be connected to the heating device **50**. The second exhaust air duct **44** may be connected to the third exhaust air duct **47**. The second exhaust air duct **44** may be connected to the third exhaust air duct **47** by passing through the support plate **577**.

(446) The third supply air duct **48** may branch off from the second supply air duct **45**. The third supply air duct **48** may branch off from the first hot air duct **451**. The third supply air duct **48** may branch off from the first hot air duct **451** at the rear side of the third cabinet **30**.

(447) The laundry treating apparatus B may include a control valve disposed at a position where the third supply air duct **48** branches off from the second supply air duct **45**.

(448) The control valve may control a flow direction of air flowing in the second supply air duct **45**. The control valve may control a flow direction of air flowing in the first hot air duct **451**. The control valve may open and close the second hot air duct **452** and the third supply air duct **48**. The control valve may open only either the second hot air duct **452** or the third supply air duct **48**. The

control valve may open both the second hot air duct **452** and the third supply air duct **48**. The control valve may control a flow amount of air supplied to the second hot air duct **452** or the third supply air duct **48**. The control valve may distribute the air, blown by the fan **60** to the second supply air duct **45**, to the second hot air duct **452** and the third supply air duct **48**.

(449) The controller **81** may control the control valve. By controlling the control valve, the controller **81** may supply the hot air, supplied from the fan **60** to the second supply air duct **450**, into the inner space **33** of the refresher **3**. By controlling the control valve, the controller **81** may supply the hot air, supplied from the fan **60** to the second supply air duct **45**, into the tub **23**.

(450) The third supply air duct **48** may extend upwardly from the second supply air duct **45**. The third supply air duct **48** may face the first inner wall **106**. By extending upwardly from the second supply air duct **45**, the third supply air duct **48** may pass through the second inner wall **206**, to be connected to the tub **23**. The second drum **24** may be supplied with hot air, heated by the heating device **50**, through the third supply air duct **48**.

(451) The third exhaust air duct **47** may extend from the tub **23** to pass through the second inner wall **206**.

(452) The third exhaust air duct **47** may include a first connection part **47b** passing through the second inner wall **206** to be connected to the tub **23**, an extension part **47c** extending downwardly from the first connection part **47b**, and a second connection part **47d** bent from the extension part **47c** to be connected to the heating device **50**.

(453) The second exhaust air duct **44** may pass through the support plate **577**. The second supply air duct **45** may pass through the first inner wall **106**.

(454) The fan **60** may be disposed closer to the first inner wall **106** than to the first outer wall **105**. The fan **60** may be disposed adjacent to the refresher **3**. The fan **60** may be disposed closer to the first rear panel **102** than to the first front panel **101**. The fan **60** may be disposed behind the third rear panel **302** of the refresher **3**. The fan **60** may be disposed between the first drum **13** and the first lower panel **104**. The fan **60** may be disposed between the base plate **575** and the first drum **13**.

(455) The switching device **70** for controlling the supply of air to the first supply air duct **43** and the second supply air duct **45** may be disposed at a height corresponding to the lower portion of the refresher **3**. The switching device **70** may be disposed under the first drum **13**. The switching device **70** may be disposed between the first drum **13** and the first lower panel **104**. The switching device **70** may be disposed between the first drum **13** and the base plate **575**.

(456) In the above arrangement structure, the length of the first supply air duct **43** and the second supply air duct **45** may be minimized. That is, the fan **60** and the switching device **70** are all disposed adjacent to the first drum **13** and the refresher **3**, such that the length of the first supply air duct **43** and the second supply air duct **45** may be minimized, thereby reducing heat loss occurring when the air heated by the heating device **50** flows through the first supply air duct **43** and the second supply air duct **45**.

(457) The laundry treating apparatus B may include the steam generator **502**. The steam generator **502** may generate steam by heating water. The steam generator **502** may be disposed in the heating device **50**.

(458) The steam generator **502** may be connected to the first drum **13** by the first steam supply pipe **502a**. The steam generator **502** may be connected to the refresher **3** by the second steam supply pipe **502a**. The steam generated by the steam generator **502** may be supplied into the first drum **13** through the first steam supply pipe **502a**. The steam generated by the steam generator **502** may be supplied into the inner space **33** of the refresher **3** through the second steam supply pipe **502b**.

(459) Referring to FIG. **19**, the heating device **50** may be disposed at the lower portion of the laundry treating apparatus B, and the duct system may be connected to the lower portion of the laundry treating apparatus B.

(460) The base plate **575** of the heating device **50** may be disposed above the first lower panel **104**.

The separation space **55** may be formed under the base plate **575**.

(461) The separation space **55** may be disposed between the first support plate **576** and the second support plate **577**.

(462) The laundry treating apparatus **B** may include the auxiliary panel **58** and the first lower panel **104**.

(463) The auxiliary panel **58** may shield a rear side of the separation space **55**. The auxiliary panel **58** may be connected to the first rear panel **102** and the first side panels **105** and **106**.

(464) The first lower panel **104** may shield a lower side of the separation space **55**. The first lower panel **104** may be coupled to the support plates **576** and **577** and the auxiliary panel **58**.

(465) The first support plate **576** may include a first protrusion **576a** protruding downwardly. The second support plate **577** may include a second protrusion **577a** protruding downwardly. The first protrusion **576a** and the second protrusion **577a** may be referred to as "protrusions."

(466) The first lower panel **104** may include recesses **104a**, into which the protrusions **576a** and **577a** are inserted. The recesses **104a** may be recessed downwardly from the upper surface of the first lower panel **104**.

(467) As the protrusions **576a** and **577a** are inserted into the recesses **104a**, the first lower panel **104** may be coupled to the heating device **50**.

(468) The dehumidification duct **46** and the third exhaust air duct **47** may be disposed in the separation space **55**. The third exhaust air duct **47** disposed in the separation space **55** may be defined as the first duct section **471**, and the dehumidification duct **46** disposed in the separation space **55** may be defined as the second duct section **461**.

(469) The dehumidification duct **46** may extend forwardly and rearwardly. The hot air outlet **462** may be formed on a front side of the dehumidification duct **46**. The air heated by the heating device **50** may be blown by the fan **60** to be supplied to the indoor space through the dehumidification duct **46**.

(470) The second exhaust air duct **44** may extend horizontally and may extend into the separation space **55**. The second exhaust air duct **44** may pass through the third inner wall **306** and the second support plate **577**. The second exhaust air duct **44** may be connected to the third exhaust air duct **47** in the separation space **55**. The air in the second exhaust air duct **44** may join the air in the third exhaust air duct **47** to flow into the heat exchange channel **42**.

(471) Referring to FIG. **20**, without branching off from the second supply air duct **450**, the third supply air duct **480** may directly connect the heating device **50** and the washing machine **2**.

(472) The third supply air duct **480** and the third exhaust air duct **470** may be directly connected to the heating device **50**. Without branching off from the second supply air duct **450**, the third supply air duct **480** may be directly connected to the heating device **50**. The third supply air duct **480** may be connected to the blowing duct **420**.

(473) The third discharge port **426** may protrude downwardly from the blowing duct **420**. The third discharge port **426** may protrude downwardly from the second wall **420b** of the blowing duct **420**.

(474) The third discharge port **426** may be connected to the third supply air duct **480**. The air blown by the fan **60** may be supplied into the third supply air duct **480** connected to the third discharge port **426**.

(475) The third supply air duct **480** may include a first supply air portion **480a** connected to the third discharge port **426**, a second supply air portion **480b** extending rearwardly from the first supply air portion **480a**, and a third supply air portion **480c** extending upwardly from the second supply air portion **480b**.

(476) The first supply air portion **480a** may extend downwardly from the third discharge port **426**. The first supply air portion **480a** may extend vertically in the separation space **55**.

(477) The second supply air portion **480b** may extend rearwardly in the separation space **55**. A part of the second supply air portion **480b** may be disposed in the separation space **55**, and the other part of the second supply air portion **480b** may be disposed outside of the separation space **55**. A

lower end of the second supply air portion **480b** may be disposed behind the first rear panel **102**.
(478) The third supply air portion **480c** may extend upwardly from the second supply air portion **480b**, to be connected to the washing machine **2**. An end of the third supply air portion **480c** may be connected to the tub **23**. The third supply air portion **480c** may be disposed behind the first rear panel **102** and the second rear panel **202**. The third supply air portion **480c** may face the first rear panel **102** and the second rear panel **202**.

(479) The third exhaust air duct **470** may pass through the rear side of the washing machine **2** and the dryer **1**, to be connected to the heating device **50**. That is, without extending in the rear case **310**, the third exhaust air duct **470** may extend vertically behind the first and second rear panels **102** and **202**.

(480) The third exhaust air duct **470** may include the first duct section **471** disposed in the separation space **55**, and a duct extension part **472** connected to the first duct section **471**.

(481) The first duct section **471** may extend forwardly in the separation space **55**. The first duct section **471** may be connected to the inlet end **42A** of the heat exchange channel **42**. The second exhaust air duct **440** may extend in the left-right direction under the inner panel **34**, and may be connected to the first duct section **471** in the separation space **55**. The air in the second exhaust air duct **440** may join the air in the first duct section **471** to flow into the heat exchange channel **42**.

(482) The first duct section **471** may include a communication hole **471a** communicating with the duct extension part **472**. The communication hole **471a** may open rearwardly. The duct extension part **472** may be inserted into the communication hole **471a** to be fixed to the first duct section **471**.

(483) The duct extension part **472** may include a first duct extension part **472a** connected to the first duct section **471**, and a second duct extension part **472b** extending upwardly from the first duct extension part **472a**.

(484) The first duct extension part **472a** may extend rearwardly from the first duct section **471**, and may be disposed outside of the separation space **55**. The first duct extension part **472a** may be disposed behind the first rear panel **102**.

(485) The second duct extension part **472b** may be bent upwardly from the first duct extension part **472a**. The second duct extension part **472b** may be connected to the tub **23**. An end of the second duct extension part **472b** may be connected to the tub **23**. The second duct extension part **472a** may be disposed behind the first rear panel **120** and the second rear panel **202**. The second duct extension part **472a** may face the first rear panel **102** and the second rear panel **202**.

(486) However, a structure of the supply air duct and the exhaust air duct which are connected to the washing machine **2** and the refresher **3** of the laundry treating apparatus B is not limited thereto. For example, it is also possible that the supply air duct is installed in the structure as illustrated in FIG. **18**, and the exhaust air duct may be installed in the structure as illustrated in FIG. **20**. In addition, it is also possible that the supply air duct is installed in the structure as illustrated in FIG. **20**, and the exhaust air duct is installed in the structure as illustrated in FIG. **18**.

(487) While the present disclosure has been particularly shown and described with reference to preferred embodiments thereof, it will be understood by those skilled in the art that the present disclosure is not limited to those exemplary embodiments and various changes in form and details may be made therein without departing from the scope and spirit of the invention as defined by the appended claims and should not be individually understood from the technical spirit or prospect of the present disclosure.

(488) It will be apparent to those skilled in the art that various modifications and variations can be made in the present invention without departing from the spirit or scope of the invention. Thus, it is intended that the present invention cover the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

(489) Certain embodiments or other embodiments of the disclosure described above are not mutually exclusive or distinct from each other. Any or all elements of the embodiments of the disclosure described above may be combined with another or combined with each other in

configuration or function.

(490) For example, a configuration “A” described in one embodiment of the disclosure and the drawings and a configuration “B” described in another embodiment of the disclosure and the drawings may be combined with each other. Namely, although the combination between the configurations is not directly described, the combination is possible except in the case where it is described that the combination is impossible.

(491) Although embodiments have been described with reference to a number of illustrative embodiments thereof, it should be understood that numerous other modifications and embodiments can be devised by those skilled in the art that will fall within the scope of the principles of this disclosure. More particularly, various variations and modifications are possible in the component parts and/or arrangements of the subject combination arrangement within the scope of the disclosure, the drawings and the appended claims. In addition to variations and modifications in the component parts and/or arrangements, alternative uses will also be apparent to those skilled in the art.

(492) A laundry treating apparatus may include a dryer including a first cabinet, and a drum rotatably mounted in the first cabinet; a refresher including a second cabinet disposed on one side of the first cabinet and having an inner space for receiving laundry; a first supply air duct for supplying air into the drum; a second supply air duct for supplying air into the inner space of the second cabinet; and a heating device heating air flowing into the first supply air duct and the second supply air duct, and disposed in the first cabinet and disposed under the drum.

(493) The laundry treating apparatus may be configured as above, wherein the heating device comprises a heat exchange unit for heating air; and a heat exchange channel in which the heat exchange unit is disposed, wherein the first supply air duct and the second supply air duct are connected to the heat exchange channel.

(494) The laundry treating apparatus may be configured as above, further comprising a washing machine including a third cabinet disposed under the first cabinet, a tub disposed in the third cabinet, and a second drum rotatably mounted in the tub, wherein the heating device is disposed between the drum and the third cabinet.

(495) The laundry treating apparatus may be configured as above, further comprising a third supply air duct for supplying air into the second drum, wherein the first supply air duct extends upwardly from the heating device to be connected to the drum, the second supply air duct extends to a lateral side from the heating device to be connected to the refresher, and the third supply air duct extends downwardly from the heating device to be connected to the tub.

(496) The laundry treating apparatus may be configured as above, further comprising a first exhaust air duct supplying air in the drum to the heating device and extending downwardly from the drum to be connected to the heating device; a second exhaust air duct supplying air in the inner space of the second cabinet to the heating device and extending to the lateral side from the refresher to be connected to the heating device; and a third exhaust air duct supplying air in the second drum to the heating device and extending upwardly from the tub to be connected to the heating device.

(497) The laundry treating apparatus may be configured as above, further comprising a second exhaust air duct connecting the refresher and the heating device, wherein the second supply air duct extends to the lateral side from the heating device and is connected to a supply air hole formed at a lower portion of the refresher; and the second exhaust air duct extends to the lateral side from the heating device and is connected to an exhaust air hole formed at an upper portion of the refresher.

(498) The laundry treating apparatus may be configured as above, further comprising a second exhaust air duct connecting the refresher and the heating device, wherein the second supply air duct extends to the lateral side from the heating device and is connected to a supply air hole formed at an upper portion of the refresher; and the second exhaust air duct extends to the lateral side from the heating device and is connected to an exhaust air hole formed at a lower portion of the

refresher.

(499) The laundry treating apparatus may be configured as above, wherein the supply air hole is open obliquely downwardly toward the inner space of the second cabinet.

(500) The laundry treating apparatus may be configured as above, wherein the refresher further comprises a hanger on which the laundry received in the inner space of the second cabinet is hung, and which is disposed below the supply air hole.

(501) The laundry treating apparatus may be configured as above, wherein the refresher further comprises a first plate disposed below the second exhaust air duct and having a dust hole formed therein which is vertically open; and a second plate disposed under the first plate.

(502) The laundry treating apparatus may be configured as above, wherein the dryer further comprises a motor rotating the drum and disposed in the first cabinet, wherein the motor is disposed in the heating device.

(503) The laundry treating apparatus may be configured as above, further comprising a dehumidification duct disposed between the drum and the third cabinet and discharging air, heated by the heating device, outside of the laundry treating apparatus.

(504) The laundry treating apparatus may be configured as above, further comprising a steam generator disposed in the heating device; a first steam supply pipe connecting the steam generator and the drum; a second steam supply pipe connecting the steam generator and the refresher; and a third steam supply pipe connecting the steam generator and the tub.

(505) The laundry treating apparatus may be configured as above, wherein the dryer comprises protrusions protruding downwardly from the first cabinet, wherein the washing machine has recesses which are vertically open on an upper surface of the third cabinet, and into which the protrusions are inserted.

(506) The laundry treating apparatus may be configured as above, further comprising a washing machine including a third cabinet disposed over the first cabinet, a tub disposed in the third cabinet, and a second drum rotatably mounted in the tub.

(507) The laundry treating apparatus may be configured as above, wherein the first supply air duct extends upwardly from the heating device to be connected to the drum; and the second supply air duct extends to the lateral side from the heating device to be connected to the supply air hole disposed at the lower portion of the refresher.

(508) The laundry treating apparatus may be configured as above, further comprising a second exhaust air duct connecting the heating device and the refresher, wherein the refresher further comprises a supply air hole connected to the second supply air duct and being open obliquely upwardly toward the inner space of the second cabinet; and an exhaust air hole connected to the second exhaust air duct and being open toward the inner space of the second cabinet at a position spaced apart from the supply air hole.

(509) The laundry treating apparatus may be configured as above, further comprising a third supply air duct connecting the tub and the heating device.

(510) A laundry treating apparatus may include a dryer including a first cabinet and a first drum rotatably mounted in the first cabinet; a washing machine including a second cabinet disposed under the first cabinet, a tub disposed in the second cabinet, and a second drum rotatably mounted in the tub; a refresher including a third cabinet disposed on one side of the first cabinet and the second cabinet and having an inner space for receiving laundry; a duct system including a first supply air duct connected to the first drum, a second supply air duct connected to the refresher, and a third supply air duct connected to the tub; and a heating device disposed between the first drum and the second drum and including a heat exchange channel connected to the first supply air duct, the second supply air duct, and the third supply air duct.

(511) A laundry treating apparatus may include a dryer including a first cabinet and a first drum rotatably mounted in the first cabinet; a washing machine including a second cabinet disposed over the first cabinet, a tub disposed in the second cabinet, and a second drum rotatably mounted in the

tub; a refresher including a third cabinet disposed on one side of the first cabinet and the second cabinet and having an inner space for receiving laundry; a heating device disposed under the first drum, and heating air supplied into the first drum; and a supply air duct supplying the air, heated by the heating device, into the inner space of the third cabinet and connecting a supply air hole, disposed at a lower portion of the refresher, and the heating device.

(512) A laundry treating apparatus may include an integrated frame having a first laundry loading opening and a second laundry loading opening which are vertically spaced apart from each other, and having a horizontal partition wall formed at a middle portion; a first door for opening and closing the first laundry loading opening; a second door for opening and closing the second laundry loading opening; a refresher having a drying room in which a first drum is rotatably disposed between an upper panel and the horizontal partition wall of the integrated frame, a washing room having a tub, which is disposed between a lower panel and the horizontal partition wall of the integrated frame, and having a second drum which is rotatably mounted in the tub, a side frame disposed on one side of the integrated frame and having an opening and an inner space for receiving laundry, and a third door for opening and closing the opening; a duct system including a first supply air duct for supplying air into the first drum, a second supply air duct for supplying air into the side frame, and a heat exchange channel connected to the first supply air duct and the second supply air duct; and a heating device for heating air passing through the heat exchange channel.

(513) The laundry treating apparatus may be configured as above, wherein the heating device is disposed in the drying room or in the side frame.

(514) The laundry treating apparatus may be configured as above, wherein the heating device is disposed between the horizontal partition wall and the first drum.

(515) A laundry treating apparatus may include a single frame which has a vertical partition wall formed therein, and a horizontal partition wall disposed between the vertical partition wall and one side panel, and in which a washing room and a drying room are vertically separated by the horizontal partition wall between the one side panel and the vertical partition wall, and a refreshing room is disposed between the vertical partition wall and an opposite side panel; a first drum for receiving laundry is rotatably mounted in the drying room, a tub is disposed in the washing machine, a second drum for receiving the laundry is rotatably mounted in the tub, and the single frame has a first laundry loading opening through which the laundry is loaded into the first drum, a second laundry loading opening through which the laundry is loaded into the second drum, an opening through which the laundry is introduced into the refreshing room, and first, second, and third doors coupled to the single frame, and opening and closing the first and second laundry loading openings and the opening, respectively; a duct system including a first supply air duct for supplying air to the first drum, a second supply air duct for supplying air to the refreshing room, and a heat exchange channel connected to the first supply duct and the second supply air duct; and a heating device for heating air passing through the heat exchange channel.

(516) The laundry treating apparatus of may be configured as above, wherein the heating device is disposed in the drying room or the refreshing room.

(517) The laundry treating apparatus of may be configured as above, wherein the drying room is disposed over the washing room, and the heating device is disposed between the horizontal partition wall and the first drum.

(518) A laundry treating apparatus may include a first laundry treating machine including a cabinet having a laundry loading opening, a door for opening and closing the laundry loading opening, and a drum rotatably mounted in the cabinet and receiving laundry; a second laundry treating machine including a cabinet having a laundry loading opening, a door for opening and closing the laundry loading opening, and having an inner space for receiving laundry; a duct system including a first supply air duct for supplying air into the drum of the first laundry treating machine, a second supply air duct for supplying air into the inner space of the second laundry treating machine, and a

heat exchange channel having an inlet end where air is introduced, and a discharge end where the air is discharged, with the first and second supply air ducts being connected to the discharge end; and a heating device for heating air passing through the heat exchange channel.

(519) The laundry treating apparatus may be configured as above, wherein the heating device is disposed in the cabinet of the first laundry treating machine.

(520) The laundry treating apparatus may be configured as above, wherein the heating device is disposed under the drum.

(521) The laundry treating apparatus may be configured as above, wherein the duct system comprises a first inlet port which is formed at the inlet end of the heat exchange channel, and through which the air flows into the heat exchange channel; and a second inlet port which is formed at the inlet end of the heat exchange channel, through which the air flows into the heat exchange channel, and which is spaced apart from the first inlet port.

(522) The laundry treating apparatus may be configured as above, wherein the duct system comprises a first exhaust air duct connected to the first inlet port and discharging the air in the drum; a second exhaust air duct connected to the second inlet port and discharging the air in the inner space of the second laundry treating machine.

(523) The laundry treating apparatus may be configured as above, comprising a first opening and closing valve disposed in the first exhaust air duct and opening and closing the first exhaust air duct; and a second opening and closing valve disposed in the second exhaust air duct and opening and closing the second exhaust air duct.

(524) The laundry treating apparatus may be configured as above, further comprising a switching device for selectively opening the first supply air duct and the second supply air duct.

(525) The laundry treating apparatus may be configured as above, wherein the heating device is a heat pump device including a compressor, an evaporator, and a condenser which are connected by a refrigerant passage.

(526) The laundry treating apparatus may be configured as above, wherein the evaporator and the condenser are disposed in the heat exchange channel.

(527) The laundry treating apparatus may be configured as above, wherein the heating device comprises a heater for heating the air passing through the heat exchange channel, wherein the heater is disposed in the heat exchange channel.

(528) The laundry treating apparatus may be configured as above, further comprising a cooler disposed in the heat exchange channel, wherein the cooler is disposed on an upstream side of the heater.

(529) The laundry treating apparatus may be configured as above, further comprising a fan disposed in the heat exchange channel.

(530) A laundry treating apparatus may include a dryer including a first cabinet having a first laundry loading opening, a first door for opening and closing the first laundry loading opening, and a first drum rotatably mounted in the first cabinet and receiving laundry; a washing machine including a second cabinet disposed vertically with respect to the first cabinet and having a second laundry loading opening, a second door opening and closing the second laundry loading opening, a tub disposed in the second cabinet, and a second drum rotatably mounted in the tub and receiving laundry; a refresher including a third cabinet disposed on one side of the washing machine and the dryer and having an opening, a third door for opening and closing the opening, and having an inner space for receiving laundry; a duct system including a first supply air duct for supplying air into the first drum, a second supply air duct for supplying air into the inner space of the refresher, and a heat exchange channel connected to the first supply air duct and the second supply air duct; and a heating device for heating air passing through the heat exchange channel.

(531) The laundry treating apparatus may be configured as above, wherein the heating device is disposed in any one of the dryer and the refresher.

(532) The laundry treating apparatus may be configured as above, wherein the heating device is

disposed in the first cabinet.

(533) The laundry treating apparatus may be configured as above, wherein the first cabinet is disposed over the second cabinet, and the heating device is disposed between the first drum and the second cabinet.

(534) The laundry treating apparatus may be configured as above, wherein the heating device is disposed over an upper panel of the second cabinet.

(535) The laundry treating apparatus may be configured as above, wherein the first cabinet comprises a machine room, which is a space formed under the first drum, and the heating device is disposed in the machine room.

(536) The laundry treating apparatus may be configured as above, further comprising a driving motor for rotating the first drum, wherein the driving motor is disposed in the machine room.

(537) The laundry treating apparatus may be configured as above, wherein the heating device is a heat pump device comprising a compressor, a condenser, and an evaporator which are connected by a refrigerant passage.

(538) The laundry treating apparatus may be configured as above, wherein the evaporator and the condenser are disposed in the heat exchange channel and are configured to heat exchange the air, passing through the heat exchange channel, with a refrigerant.

(539) The laundry treating apparatus may be configured as above, wherein the heating device comprises a base plate, on which the condenser and the evaporator are disposed; both side walls connected to the base plate and standing on both sides of the condenser and the evaporator; and a cover disposed on an upper side of the condenser and the evaporator, wherein the heat exchange channel are surrounded by the base plate and the both side walls.

(540) The laundry treating apparatus may be configured as above, wherein the heating device comprises a base plate, on which the condenser and the evaporator are disposed; a first support plate protruding downwardly from the base plate; and a second support plate protruding downwardly from the base plate and facing the first support plate, wherein a space, in which a portion of the duct system is disposed, is formed between the first support plate and the second support plate.

(541) The laundry treating apparatus may be configured as above, wherein the first support plate and the second support plate are disposed over the second cabinet.

(542) The laundry treating apparatus may be configured as above, wherein the first support plate and the second support plate have protrusions protruding downwardly toward the second cabinet, wherein the second cabinet comprises a second upper panel disposed under the first support plate and the second support plate; and recesses which are formed in the second upper panel, and into which the protrusions are inserted.

(543) The laundry treating apparatus may be configured as above, wherein the heat exchange channel comprises an inlet end through which the air in the first drum and the air in the inner space of the refresher are introduced; and a discharge end through which the air, having passed through the heat exchange channel, is supplied to the first supply air duct or the second supply air duct, wherein the duct system comprises a first inlet port which is formed at the inlet end and through which the air in the first drum is introduced; a second inlet port which is formed at the inlet end and through which the air in the inner space of the refresher is introduced; a first discharge port formed at the discharge end and connected to the first supply air duct; and a second discharge port formed at the discharge end and connected to the second supply air duct.

(544) The laundry treating apparatus may be configured as above, wherein the duct system comprises a first exhaust air duct connecting the first drum and the first inlet port; and a second exhaust air duct connecting the inner space of the refresher and the second inlet port.

(545) The laundry treating apparatus may be configured as above, wherein the refresher comprises a supply air hole connected to the second supply air duct; and an exhaust air hole connected to the second exhaust air duct, wherein the supply air hole is formed at a lower portion of the refresher,

and the exhaust air hole is formed at an upper portion of the refresher.

(546) The laundry treating apparatus may be configured as above, wherein the supply air hole is disposed below a height of the heating device, and the exhaust air hole is disposed above the height of the heating device.

(547) The laundry treating apparatus may be configured as above, further comprising a fan disposed in the duct system.

(548) The laundry treating apparatus may be configured as above, wherein the fan is disposed in the heat exchange channel.

(549) The laundry treating apparatus may be configured as above, wherein the duct system further comprises a blowing duct disposed on the discharge side of the heat exchange channel, and having a fan disposed therein, wherein the blowing duct comprises a first discharge port connected to the first supply air duct; and a second discharge port connected to the second supply air duct.

(550) The laundry treating apparatus may be configured as above, wherein the blowing duct has a square-shaped cross-section with upper, lower, left, and right walls, wherein the first discharge port and the second discharge port are formed in different walls among the upper, lower, left, and right walls.

(551) The laundry treating apparatus may be configured as above, further comprising a switching device disposed in the blowing duct, and controlling a flow direction of air blown by the fan.

(552) The laundry treating apparatus may be configured as above, wherein the switching device comprises a rotating body rotatably disposed in the blowing duct, and selectively communicating with the first discharge port or the second discharge port; and a driving motor for rotating the rotating body.

(553) The laundry treating apparatus may be configured as above, wherein the rotating body comprises a rotating plate coupled to the driving motor; and a scroll coupled to the rotating plate and having the blowing channel formed therein.

(554) The laundry treating apparatus may be configured as above, wherein the duct system comprises a third supply air duct connected to the heat exchange channel and supplying air into the tub; a third exhaust air duct through which the air in the tub is introduced into the heat exchange channel; a third discharge port connecting the heat exchange channel and the third supply air duct; and a third inlet port connecting the heat exchange channel and the third exhaust air duct.

(555) The laundry treating apparatus may be configured as above, wherein the duct system further comprises a second exhaust air duct connecting the inner space of the refresher and the heat exchange channel, wherein the third inlet port is formed in the second exhaust air duct.

(556) The laundry treating apparatus may be configured as above, wherein the duct system further comprises an outside air inlet port through which outside air is introduced, and which is connected to the heat exchange channel; and a dehumidification duct discharging air, heat exchanged in the heat exchange channel, to the outside of the laundry treating apparatus.

(557) The laundry treating apparatus may be configured as above, wherein the duct system further comprises a second exhaust air duct connecting the inner space of the refresher and the heat exchange channel, wherein the outside air inlet port is formed in the second exhaust air duct.

(558) The laundry treating apparatus may be configured as above, wherein the duct system further comprises a fourth discharge port connecting the heat exchange channel and the dehumidification duct, wherein the dehumidification duct is disposed under the heating device and extends forwardly from the fourth discharge port, and has an outlet through which the heat-exchanged air is discharged to the outside.

(559) The laundry treating apparatus may be configured as above, wherein the duct system further comprises a second exhaust air duct connecting the inner space of the refresher and the heat exchange channel, wherein the second exhaust air duct has a duct section disposed in a space formed under the heat exchange channel, and extending forwardly and backwardly in the space.

(560) The laundry treating apparatus may be configured as above, wherein the heat exchange

channel comprises a discharge end through which the air, having passed through the heat exchange channel, is supplied to the first supply air duct and the second supply air duct, wherein the duct system comprises a first discharge port connected to the first supply air duct and formed on an upper side the discharge end; and a second discharge port connected to the second supply air duct and formed on a lateral side of the discharge end.

(561) The laundry treating apparatus may be configured as above, wherein the heat exchange channel comprises a inlet end through which the air in the first drum or the air in the inner space of the refresher is introduced, wherein the duct system comprises a first inlet port formed on an upper side of the inlet end; and a second inlet end formed on a lower side of the inlet end.

(562) A laundry treating apparatus may include a dryer having a drum for receiving laundry; a washing machine disposed on one side of the dryer in a direction horizontal to the dryer; a refresher disposed over the dryer and the washing machine, and having an inner space for receiving laundry; a duct system including a first supply air duct supplying air into the drum, a second supply air duct supplying air into the inner space of the refresher, an inlet end through which air is introduced, a discharge end through which the air is discharged, the first supply air duct and the second supply air duct being connected to the discharge end; and a heating device for heating air passing through the heat exchange channel.

(563) A laundry treating apparatus may include a dryer having a cabinet and a drum rotatably mounted in the cabinet; a refresher disposed on one side of the dryer and having an inner space for receiving laundry; a heating device disposed under the drum and heating air supplied into the drum; and a supply air duct connecting the heating device and the refresher, and supplying the air, heated by the heating device, into the inner space of the refresher.

(564) The laundry treating apparatus may be configured as above, wherein the heating device is disposed in the cabinet, and the supply air duct extends from the heating device to a lateral side to be connected to the refresher.

(565) The laundry treating apparatus may be configured as above, wherein the refresher has a supply air hole formed at a lower portion of the inner space thereof, where the supply air duct communicates with the supply air hole and is connected to the lower portion of the refresher.

(566) The laundry treating apparatus may be configured as above, wherein the refresher comprises an inner panel disposed on a lower side of the inner space and having the supply air hole formed therein, wherein the inner panel comprises a first inner panel disposed horizontal to the lower side of the inner space; and the second inner panel bent upwardly from the first inner panel, wherein the supply air hole is formed in the second inner panel.

(567) The laundry treating apparatus may be configured as above, wherein the refresher comprises a third cabinet having the inner space, wherein the supply air duct comprises a first hot air duct connected to the heating device and disposed at a rear side of the third cabinet; and a second hot air duct connecting the first hot air duct and the inner panel and disposed in the third cabinet.

(568) The laundry treating apparatus may be configured as above, further comprising a fan pressurizing air heated by the heating device, wherein the fan is disposed on one side of the refresher and is disposed under the drum.

(569) The laundry treating apparatus may be configured as above, wherein the cabinet comprises a first side panel disposed adjacent to the refresher; and a second side panel disposed farther from the refresher than the first side panel, wherein the fan is disposed in the cabinet and is disposed closer to the first side panel than to the second side panel.

(570) The laundry treating apparatus may be configured as above, wherein the supply air duct comprises a first supply air duct connecting the heating device and the drum and extending upwardly from the heating device; and a second supply air duct connecting the heating device and the refresher and extending from the heating device to a lateral side.

(571) The laundry treating apparatus may be configured as above, further comprising a blowing duct which is connected to the first supply air duct and the second supply air duct, and in which the

fan is received; and a switching device disposed in the blowing duct and controlling a flow direction of air blown by the fan, wherein the blowing duct is disposed under the drum and disposed at a height corresponding to a lower portion of the refresher.

(572) The laundry treating apparatus may be configured as above, further comprising a first exhaust air duct connecting the drum and the heating device; and a second exhaust air duct connecting the inner space of the refresher and the heating device, wherein the second exhaust air duct is disposed at the lower portion of the refresher.

(573) The laundry treating apparatus may be configured as above, further comprising an inner panel disposed on a lower side of the inner space; and an exhaust air hole formed in the inner panel and connected to the second exhaust air duct, wherein the second exhaust air duct extends from the lower side of the inner panel to the lateral side toward the heating device.

(574) A laundry treating apparatus may include a dryer including a first cabinet and a first drum rotatably mounted in the first cabinet; a washing machine disposed over the dryer and including a second cabinet, a tub disposed in the second cabinet, and a second drum rotatably mounted in the tub; a refresher disposed on one side of the washing machine and the dryer and including a third cabinet having an inner space for receiving laundry; and a heating device heating air supplied into the inner space of the refresher, wherein the heating device is disposed under the first drum.

(575) The laundry treating apparatus may be configured as above, wherein the refresher has a supply air hole disposed at a lower portion of the inner space, wherein the supply air duct communicates with the supply air hole and is connected to a lower portion of the refresher.

(576) The laundry treating apparatus may be configured as above, wherein the refresher comprises an inner panel disposed on a lower side of the inner space, extending to be bent upwards, and having the supply air hole.

(577) The laundry treating apparatus may be configured as above, further comprising a first supply air duct connecting the heating device and the first drum, and extending upwardly from the heating device; a second supply air duct connecting the heating device and the refresher, and extending from the heating device to the lateral side; and a third supply air duct branching off from the second supply air duct and connected to the tub.

(578) The laundry treating apparatus may be configured as above, wherein the third supply air duct branches off from the second supply air duct outside of the first cabinet.

(579) The laundry treating apparatus may be configured as above, further comprising a first exhaust air duct connecting the first drum and the heating device; a second exhaust air duct connecting the inner space of the refresher and the heating device; and a third exhaust air duct connecting the tub and the heating device, wherein the second exhaust air duct is connected to the third exhaust air duct.

(580) The laundry treating apparatus may be configured as above, wherein the heating device comprises a heat exchange unit heating air introduced through the first, second, and third exhaust air ducts; and a base plate on which the heat exchange unit is mounted, wherein a separation space is formed between the base plate and the first cabinet, and a portion of the third exhaust air duct is disposed in the separation space.

(581) The laundry treating apparatus may be configured as above, further comprising an outside air inlet port communicating with the outside of the laundry treating apparatus and disposed in the separation space; and a dehumidification duct, to which air heated by the heat exchange unit is supplied, and which extends forwardly in the separation space.

(582) A laundry treating apparatus may include a dryer having a first cabinet and a first drum rotatably mounted in the first cabinet; a washing machine disposed over the dryer and including a second cabinet, a tub disposed in the second cabinet, and a second drum rotatably mounted in the tub; a refresher disposed on one side of the washing machine and the dryer, and including a third cabinet having an inner space for receiving laundry; a heating device disposed under the first drum and heating air supplied into the first drum; and a supply air duct connecting the heating device and

the third cabinet, and supplying air heated by the heating device into the inner space of the third cabinet.

(583) A laundry treating apparatus may include a cabinet having an opening formed on a front side thereof and an inner space for receiving laundry; a hanger on which the laundry received in the inner space of the cabinet is hung, and which is disposed at an upper portion of the inner space of the cabinet; a door coupled to a front side of the cabinet and opening and closing the opening; a heating device heating air supplied into the inner space of the cabinet; and a supply air duct connecting the heating device and the cabinet, wherein the supply air duct is connected to a supply air hole that opens toward the inner space of the cabinet, and is disposed above the hanger.

(584) The laundry treating apparatus may be configured as above, wherein the cabinet comprises an upper wall having a first surface separated from an upper side of the hanger, wherein the supply air hole is positioned at a height between the first surface and the hanger.

(585) The laundry treating apparatus may be configured as above, wherein the upper wall has a second surface extending at an incline downwardly toward a lower side from the first surface, wherein the supply air hole is open in the second surface.

(586) The laundry treating apparatus may be configured as above, wherein the supply air duct extends upwardly and convexly from the supply air hole.

(587) The laundry treating apparatus may be configured as above, further comprising an exhaust air duct connecting the heating device and the cabinet, wherein the exhaust air duct is connected to an exhaust air hole that opens toward the inner space of the cabinet and is disposed at a lower portion of the cabinet.

(588) The laundry treating apparatus may be configured as above, further comprising a filter disposed in the exhaust air hole.

(589) The laundry treating apparatus may be configured as above, further comprising a first plate disposed under the inner space of the cabinet, and having a dust hole formed therein which is vertically open; and a second plate disposed under the first plate.

(590) The laundry treating apparatus may be configured as above, wherein the first plate is disposed below the exhaust air hole.

(591) The laundry treating apparatus may be configured as above, further comprising an exhaust air duct connecting the heating device and the cabinet, wherein the exhaust air duct is connected to the exhaust air hole that opens toward the inner space of the cabinet and is disposed at an upper portion of the cabinet.

(592) The laundry treating apparatus may be configured as above, wherein the exhaust air hole is disposed below the hanger.

(593) The laundry treating apparatus may be configured as above, wherein the exhaust air hole is disposed below the supply air hole.

(594) The laundry treating apparatus may be configured as above, wherein the exhaust air hole is disposed further away from the heating device than the supply air hole.

(595) A laundry treating apparatus may include a cabinet having an opening formed on a front side thereof and an inner space for receiving laundry; a door coupled to the front side of the cabinet and opening and closing the opening; a heating device heating air supplied into the inner space of the cabinet; and a supply air duct connecting the heating device and the cabinet, wherein the heating device is disposed on one side of the cabinet, and the supply air duct extends from the heating device to be connected to an upper portion of the cabinet.

(596) The laundry treating apparatus may be configured as above, wherein the heating device is disposed at a position corresponding to a middle height of the cabinet, wherein the supply air duct comprises a first supply air portion extending from the heating device to a lateral side and bent upwardly; and a second supply air portion extending upwardly and convexly from the first supply air portion and connected to the upper portion of the cabinet.

(597) The laundry treating apparatus may be configured as above, further comprising an exhaust air

duct extending from the heating device to be connected to the lower portion of the cabinet, wherein the heating device is disposed at a position corresponding to the middle height of the cabinet, wherein the exhaust air duct comprises a first exhaust air portion extending rearwardly from the lower portion of the cabinet; and a second exhaust air portion extending upwardly from the first exhaust air portion and bent toward the lateral side to be connected to the heating device.

(598) The laundry treating apparatus may be configured as above, wherein the heating device is disposed at a position corresponding to the upper portion of the cabinet, wherein the supply air duct extends from the heating device to the lateral side to be connected to the upper portion of the cabinet.

(599) The laundry treating apparatus may be configured as above, further comprising an exhaust air duct extending from the heating device to be connected to the upper portion of the cabinet, wherein the heating device is disposed at a position corresponding to the upper portion of the cabinet, and the exhaust air duct extends from the heating device to the lateral side to be connected to the upper portion of the cabinet.

(600) The laundry treating apparatus may be configured as above, further comprising a dryer disposed on one side of the cabinet, and having a first drum rotatably mounted therein; and a washing machine disposed on one side of the cabinet, and having a second drum rotatably mounted therein, wherein the dryer, the washing machine, and the heating device are vertically arranged on one side of the cabinet.

(601) The laundry treating apparatus may be configured as above, wherein the supply air duct extends from the heating device to the lateral side and is connected to the cabinet at a rear side of the cabinet.

(602) A laundry treating apparatus may include a cabinet having an opening formed on a front side thereof and an inner space for receiving laundry; a door coupled to the front side of the cabinet and opening and closing the opening; a heating device heating air supplied into the inner space of the cabinet; and a supply air duct connecting the heating device and the cabinet, wherein the supply air duct is connected to the upper side of the cabinet.

(603) A laundry treating apparatus may include a cabinet having an opening formed on a front side thereof and an inner space for receiving laundry; a door coupled to the front side of the cabinet and opening and closing the opening; a heating device heating air supplied into the inner space of the cabinet and disposed on one side of the cabinet; and a supply air duct extending from the heating device to a lateral side and connected to a supply air hole disposed at a lower portion of the cabinet.

(604) The laundry treating apparatus may be configured as above, wherein the heating device is disposed at a position corresponding to a middle height of the cabinet, and the supply air duct extends by being bent downwardly from the heating device.

(605) The laundry treating apparatus may be configured as above, wherein the cabinet comprises a rear panel separated from a rear side of the door and forming the inner space of the cabinet with the door, wherein the supply air duct comprises a first hot air duct having a first supply air portion extending from the heating device to a lateral side; a second supply air portion extending downwardly from the first supply air portion, and a third supply air portion extending from the second supply air portion toward the rear panel; and a second hot air duct disposed in front of the rear panel, and connecting the first hot air duct and the supply air hole.

(606) The laundry treating apparatus may be configured as above, further comprising an exhaust air duct extending by being bent upwardly from the heating device, and connected to an exhaust air hole formed at an upper portion of the cabinet.

(607) The laundry treating apparatus may be configured as above, wherein the exhaust air duct comprises a first exhaust air portion extending from the exhaust air hole toward a rear side of the cabinet; a second exhaust air portion extending downwardly from the first exhaust air portion; and a third exhaust air portion extending from the second exhaust air portion to the lateral side to be connected to the heating device.

(608) The laundry treating apparatus may be configured as above, further comprising a dryer disposed on one side of the cabinet, and having a first drum rotatably mounted therein; and a washing machine disposed under the dryer, and having a second drum rotatably mounted therein, wherein the heating device is disposed between the first drum and the second drum.

(609) The laundry treating apparatus may be configured as above, wherein the heating device is disposed at a position corresponding to the lower portion of the cabinet, and the supply air duct extends from the heating device to the lateral side.

(610) The laundry treating apparatus may be configured as above, further comprising an exhaust air duct connected to the exhaust air hole formed at the lower portion of the cabinet, and extending to the lateral side toward the heating device.

(611) The laundry treating apparatus may be configured as above, further comprising a dryer disposed on one side of the cabinet, and having a first drum rotatably mounted therein; and a washing machine disposed over the dryer, and having a second drum rotatably mounted therein, wherein the heating device is disposed under the first drum and the second drum.

(612) The laundry treating apparatus may be configured as above, wherein the heating device comprises a heat exchange channel for heating air supplied into the first drum and the cabinet, wherein the supply air duct comprises a first supply air duct connecting the heat exchange channel and the first drum; and a second supply air duct connecting the heat exchange channel and the cabinet.

(613) A laundry treating apparatus may include a cabinet having an opening formed on a front side thereof and an inner space for receiving laundry; a door coupled to the front side of the cabinet and opening and closing the opening; a heating device heating air supplied into the inner space of the cabinet; and a supply air duct connecting the heating device and the cabinet, wherein the supply air duct is connected to a supply air hole that opens toward the inner space of the cabinet and is disposed at a lower portion of the cabinet.

(614) The laundry treating apparatus may be configured as above, wherein the cabinet comprises a rear panel separated from a rear side of the door and forming the inner space of the cabinet with the door, wherein the supply air duct comprises a first hot air duct disposed behind the rear panel and connected to the heating device; and a second hot air duct connecting the first hot air duct and the supply air hole.

(615) The laundry treating apparatus may be configured as above, further comprising an inner panel disposed on a lower side of the inner space of the cabinet, wherein the supply air hole is open upwardly in the inner panel.

(616) The laundry treating apparatus may be configured as above, wherein the cabinet comprises a rear panel separated from a rear side of the door and forming the inner space of the cabinet with the door, wherein the inner panel comprises a first inner panel horizontally extending from the lower side of the inner space of the cabinet toward the rear panel; and a second inner panel extending at an incline upwardly from the first inner panel toward the rear panel, wherein the supply air hole is formed in the second inner panel.

(617) The laundry treating apparatus may be configured as above, further comprising an exhaust air duct that opens toward the inner space of the cabinet and is connected to the exhaust air hole formed at the upper portion of the cabinet.

(618) The laundry treating apparatus may be configured as above, further comprising a hanger on which the laundry received in the inner space of the cabinet is hung, and which is disposed at an upper portion of the inner space of the cabinet, wherein the exhaust air hole is disposed below the hanger.

(619) The laundry treating apparatus may be configured as above, wherein the cabinet comprises a rear panel separated from a rear side of the door and forming the inner space of the cabinet with the door, wherein the exhaust air hole is open in the rear panel, and the exhaust air duct is bent downwardly from a rear side of the rear panel.

(620) The laundry treating apparatus may be configured as above, further comprising an exhaust air duct connected to an exhaust air hole that is open toward the inner space of the cabinet and is disposed at a lower portion of the cabinet.

(621) The laundry treating apparatus may be configured as above, further comprising an inner panel disposed on a lower side of the inner space of the cabinet, wherein the exhaust air hole is open upwardly in the inner panel.

(622) The laundry treating apparatus may be configured as above, wherein the cabinet comprises a rear panel separated from a rear side of the door and forming the inner space of the cabinet with the door, wherein the inner panel comprises a first inner panel horizontally extending from the lower side of the inner space of the cabinet toward the rear panel; and a second inner panel extending at an incline upwardly from the first inner panel toward the rear panel, wherein the exhaust air hole is open upwardly in the first inner panel, and the supply air hole is open obliquely upwardly in the second inner panel.

(623) Various embodiments described herein may be implemented in a computer-readable medium using, for example, software, hardware, or some combination thereof. For example, the embodiments described herein may be implemented within one or more of Application Specific Integrated Circuits (ASICs), Digital Signal Processors (DSPs), Digital Signal Processing Devices (DSPDs), Programmable Logic Devices (PLDs), Field Programmable Gate Arrays (FPGAs), processors, controllers, micro-controllers, microprocessors, other electronic units designed to perform the functions described herein, or a selective combination thereof. In some cases, such embodiments are implemented by the controller. That is, the controller is a hardware-embedded processor executing the appropriate algorithms (e.g., flowcharts) for performing the described functions and thus has sufficient structure. Also, the embodiments such as procedures and functions may be implemented together with separate software modules each of which performs at least one of functions and operations. The software codes can be implemented with a software application written in any suitable programming language. Also, the software codes can be stored in the memory and executed by the controller, thus making the controller a type of special purpose controller specifically configured to carry out the described functions and algorithms. Thus, the components shown in the drawings have sufficient structure to implement the appropriate algorithms for performing the described functions.

(624) The present invention being thus described, it will be obvious that the same may be varied in many ways. Such variations are not to be regarded as a departure from the spirit and scope of the present invention, and all such modifications as would be obvious to one skilled in the art are intended to be included within the scope of the following claims.

Claims

1. A laundry treating apparatus comprising: a dryer including: a first cabinet; and a first drum rotatably disposed in the first cabinet; a washing machine including: a second cabinet disposed under the first cabinet; a tub disposed in the second cabinet; and a second drum rotatably disposed in the tub, a refresher including a third cabinet disposed at a lateral side of the first cabinet, the third cabinet having an inner space for receiving laundry; a first supply air duct for supplying air into the first drum; a second supply air duct for supplying air into an inner space of the second cabinet; a heating device for heating air flowing into the first supply air duct and the second supply air duct, the heating device being disposed in the first cabinet and under the first drum; and a third supply air duct for supplying air into the second drum, wherein the dryer, the refresher and the washing machine are adjacently disposed, wherein the washing machine and the dryer are vertically adjacently disposed, wherein the refresher is adjacently disposed on one side of the washing machine and the dryer, wherein the heating device is disposed between the first drum and the second cabinet, wherein the first supply air duct extends upwardly from the heating device and

is connected to the first drum, wherein the second supply air duct extends laterally from the heating device and is connected to the refresher, and wherein the third supply air duct extends downwardly from the heating device and is connected to the tub.

2. The laundry treating apparatus of claim 1, wherein the heating device includes: a heat exchange unit for heating air; and a heat exchange channel in which the heat exchange unit is disposed, and wherein the first supply air duct and the second supply air duct are connected to the heat exchange channel.

3. The laundry treating apparatus of claim 1, further comprising: a first exhaust air duct supplying air in the first drum to the heating device, the first exhaust air duct extending downwardly from the first drum and connected to the heating device; a second exhaust air duct supplying air in the inner space of the third cabinet to the heating device, the second exhaust air duct being connected to the heating device; and a third exhaust air duct supplying air in the second drum to the heating device, the third exhaust air duct extending upwardly from the tub and connected to the heating device.

4. The laundry treating apparatus of claim 1, further comprising a second exhaust air duct connecting the refresher and the heating device, wherein the second supply air duct is connected to a supply air hole formed at an upper portion of the refresher, and wherein the second exhaust air duct is connected to an exhaust air hole formed at a lower portion of the refresher.

5. The laundry treating apparatus of claim 4, wherein the supply air hole is open obliquely downwardly toward the inner space of the second cabinet.

6. The laundry treating apparatus of claim 4, wherein the refresher further includes a hanger for hanging the laundry received in the inner space of the second cabinet, the hanger being positioned below the supply air hole.

7. The laundry treating apparatus of claim 4, wherein the refresher further includes: a first plate disposed below the second exhaust air duct, the first plate having a dust hole formed therein; and a second plate disposed under the first plate, and wherein the first plate is inclined relative to the second plate.

8. The laundry treating apparatus of claim 1, further comprising a dehumidification duct disposed between the first drum and the second cabinet, the dehumidification duct for discharging air heated by the heating device to outside of the laundry treating apparatus.

9. The laundry treating apparatus of claim 1 further comprising: a steam generator disposed in the heating device; a first steam supply pipe connecting the steam generator and the first drum; a second steam supply pipe connecting the steam generator and the refresher; and a third steam supply pipe connecting the steam generator and the tub.

10. The laundry treating apparatus of claim 1, wherein the dryer has a protrusion protruding downwardly from the first cabinet, and wherein the washing machine has a recess on an upper surface of the second cabinet, the protrusion being inserted into the recess.

11. The laundry treating apparatus of claim 1, wherein the dryer further includes a motor for rotating the first drum, the motor being disposed in the heating device.

12. The laundry treating apparatus of claim 1, wherein the heating device includes: a heat exchange channel for dehumidifying the air supplied into the inner space of the second cabinet; an evaporator disposed in the heat exchange channel; and a drain pan disposed under the evaporator.

13. The laundry treating apparatus of claim 1, wherein the second supply air duct extends laterally from the heating device, the second supply air duct being connected to a supply air hole formed at an upper portion of the refresher, wherein the supply air hole is open obliquely downwardly toward the inner space of the second cabinet, and wherein a second exhaust air duct is connected to an exhaust air hole formed at a lower portion of the refresher.
