

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12399670
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Song; Jim Joojin et al.

Enabling bidirectional visual communication between two devices associated with a wireless telecommunication network

Abstract

A device receives from the UE a representation of a first screen associated with the UE and presents the representation of the first screen on a second screen associated with the device. The device creates a first overlay associated with the first screen and a second overlay associated with the second screen. The second overlay is configured to receive an input from a user. The device receives from the second user the input and presents the input in the second overlay. The device sends the input to the UE, which is configured to present the input in the first overlay associated with the first screen.

Inventors:	Song; Jim Joojin (Atlanta, GA), Foster; Eric (Bellevue, WA)
Applicant:	T-Mobile USA, Inc. (Bellevue, WA)
Family ID:	1000008780885
Assignee:	T-Mobile USA, Inc. (Bellevue, WA)
Appl. No.:	17/833578
Filed:	June 06, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230393799 A1	Dec. 07, 2023

Publication Classification

Int. Cl.: G06F3/14 (20060101); G06F3/0481 (20220101); H04L65/403 (20220101)

U.S. Cl.:

Field of Classification Search**CPC:** G06F (3/1454)**References Cited****U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8269719	12/2011	Kim	345/169	G08C 17/02
8286084	12/2011	Castleman	N/A	N/A
8405627	12/2012	Karlsson	N/A	N/A
8493353	12/2012	Blanchflower et al.	N/A	N/A
8560004	12/2012	Sipe et al.	N/A	N/A
8674957	12/2013	Raveendran et al.	N/A	N/A
8692763	12/2013	Kim	N/A	N/A
8843963	12/2013	Boylan et al.	N/A	N/A
8924957	12/2013	Newstadt et al.	N/A	N/A
8977293	12/2014	Rodriguez et al.	N/A	N/A
9027117	12/2014	Wilairat	N/A	N/A
9083610	12/2014	Griff et al.	N/A	N/A
9104302	12/2014	Chai et al.	N/A	N/A
9161186	12/2014	Bolton et al.	N/A	N/A
9164658	12/2014	Sadhvani et al.	N/A	N/A
9219992	12/2014	Wu	N/A	N/A
9237377	12/2015	Bhatia et al.	N/A	N/A
9268517	12/2015	Privat	N/A	N/A
9280310	12/2015	Oike	N/A	N/A
9294914	12/2015	Wilfred et al.	N/A	N/A
9407861	12/2015	Huenerfauth et al.	N/A	N/A
9424536	12/2015	Bear et al.	N/A	N/A
9483584	12/2015	Batra	N/A	N/A
9491418	12/2015	Iversen et al.	N/A	N/A
9523977	12/2015	Fuller et al.	N/A	N/A
9529899	12/2015	Hao et al.	N/A	N/A
9549059	12/2016	Ross et al.	N/A	N/A
9582482	12/2016	Sharifi et al.	N/A	N/A
9606695	12/2016	Matas	N/A	N/A
9628600	12/2016	Pratt et al.	N/A	N/A
9685072	12/2016	Patel et al.	N/A	N/A
9690445	12/2016	Rice et al.	N/A	N/A
9866999	12/2017	Noeth et al.	N/A	N/A
9942105	12/2017	Gardner et al.	N/A	N/A
9953454	12/2017	Rivard et al.	N/A	N/A
9985786	12/2017	Bhabbur et al.	N/A	N/A
10182141	12/2018	Paretti et al.	N/A	N/A
10262382	12/2018	Moore et al.	N/A	N/A
11340857	12/2021	Smith	N/A	G06F 3/1454

2003/0043179	12/2002	Gusler	715/708	G06F 9/453
2005/0233733	12/2004	Roundtree et al.	N/A	N/A
2007/0116241	12/2006	Flocken	379/265.05	G06Q 30/00
2010/0156913	12/2009	Ortega	345/520	G06F 3/1438
2010/0306022	12/2009	Plut	N/A	N/A
2011/0115816	12/2010	Brackney	N/A	N/A
2012/0089923	12/2011	Pettit	715/746	H04N 21/858
2013/0050230	12/2012	Jeong	345/522	G06F 3/1454
2013/0067035	12/2012	Amanat et al.	N/A	N/A
2013/0179827	12/2012	Eriksson et al.	N/A	N/A
2013/0179837	12/2012	Eriksson et al.	N/A	N/A
2014/0033050	12/2013	Shin	715/733	H04N 21/4788
2014/0267074	12/2013	Balci	345/173	G06F 9/451
2014/0279584	12/2013	Lee et al.	N/A	N/A
2014/0372886	12/2013	Ramasubramanian	N/A	N/A
2015/0049681	12/2014	Huang et al.	N/A	N/A
2015/0067894	12/2014	Aghara	726/30	G06F 16/44
2016/0034133	12/2015	Wilson et al.	N/A	N/A
2016/0094560	12/2015	Stuntebeck	726/1	G06F 3/0481
2016/0196584	12/2015	Franklin et al.	N/A	N/A
2016/0246466	12/2015	Waddell et al.	N/A	N/A
2018/0159979	12/2017	Amir	N/A	H04M 3/5183
2018/0176272	12/2017	Zur et al.	N/A	N/A
2018/0333612	12/2017	Davis	N/A	N/A
2018/0373885	12/2017	Arad	N/A	G06F 21/6254
2019/0034441	12/2018	Capon	N/A	N/A
2019/0053706	12/2018	Martie et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103069849	12/2012	CN	N/A
104704442	12/2014	CN	N/A
104956299	12/2014	CN	N/A
106716324	12/2016	CN	N/A
104584513	12/2016	CN	N/A
107735828	12/2017	CN	N/A
108292190	12/2017	CN	N/A
112512406	12/2020	CN	N/A
113612680	12/2020	CN	N/A
112010005067	12/2011	DE	N/A
202015006141	12/2014	DE	N/A
2313847	12/2010	EP	N/A
2499556	12/2011	EP	N/A
2559030	12/2012	EP	N/A
2635997	12/2012	EP	N/A
2718890	12/2013	EP	N/A
2765502	12/2013	EP	N/A
2801065	12/2013	EP	N/A
2839429	12/2014	EP	N/A
2945341	12/2014	EP	N/A

3143598	12/2016	EP	N/A
3179355	12/2016	EP	N/A
3210137	12/2016	EP	N/A
2785026	12/2017	EP	N/A
3337583	12/2017	EP	N/A
3414924	12/2017	EP	N/A
3449398	12/2018	EP	N/A
3453169	12/2018	EP	N/A
3510542	12/2018	EP	N/A
3857481	12/2020	EP	N/A
2013509644	12/2012	JP	N/A
2015043199	12/2014	JP	N/A
2015210631	12/2014	JP	N/A
6102016	12/2016	JP	N/A
6445464	12/2017	JP	N/A
6461562	12/2018	JP	N/A
2019501465	12/2018	JP	N/A
6497002	12/2018	JP	N/A
20110086622	12/2010	KR	N/A
101065644	12/2010	KR	N/A
101431397	12/2013	KR	N/A
20160042289	12/2015	KR	N/A
20170000196	12/2016	KR	N/A
20180028855	12/2017	KR	N/A
101886608	12/2017	KR	N/A
20180109631	12/2017	KR	N/A
20180116731	12/2017	KR	N/A
101939806	12/2018	KR	N/A
20190021141	12/2018	KR	N/A
2009120925	12/2008	WO	N/A
2014088472	12/2013	WO	N/A
2014149643	12/2013	WO	N/A
2014183458	12/2013	WO	N/A
2015112108	12/2014	WO	N/A
2015162550	12/2014	WO	N/A
2015173653	12/2014	WO	N/A
2015187861	12/2014	WO	N/A
2016144255	12/2015	WO	N/A
2017095800	12/2016	WO	N/A
2017213937	12/2016	WO	N/A
2017218192	12/2016	WO	N/A
2017221659	12/2016	WO	N/A
2018144051	12/2017	WO	N/A
2018209152	12/2017	WO	N/A
2018213506	12/2017	WO	N/A
2018222756	12/2017	WO	N/A

Primary Examiner: Boddie; William

Background/Summary

BACKGROUND

(1) When mobile device users experience issues and call customer service, the effectiveness of the customer service is limited because the customer service cannot see the mobile device screen and does not have physical possession of the mobile device. Consequently, the help provided by the customer service can be inefficient, and the resolution of the problem can take a while.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Detailed descriptions of implementations of the present invention will be described and explained through the use of the accompanying drawings.
- (2) FIG. 1 is a block diagram that illustrates a wireless communications system that can implement aspects of the present technology.
- (3) FIG. 2 shows bidirectional visual communication between two devices.
- (4) FIG. 3 shows presenting additional instruction using picture-in-picture technology.
- (5) FIG. 4 shows sharing of operating system settings between two devices.
- (6) FIG. 5 is a flowchart of a method to enable bidirectional visual communication between a first UE associated with a wireless telecommunication network and a second device associated with the wireless telecommunication network.
- (7) FIG. 6 is a flowchart of a method to present additional instruction using picture-in-picture technology.
- (8) FIG. 7 is a block diagram that illustrates an example of a computer system in which at least some operations described herein can be implemented.
- (9) The technologies described herein will become more apparent to those skilled in the art from studying the Detailed Description in conjunction with the drawings. Embodiments or implementations describing aspects of the invention are illustrated by way of example, and the same references can indicate similar elements. While the drawings depict various implementations for the purpose of illustration, those skilled in the art will recognize that alternative implementations can be employed without departing from the principles of the present technologies. Accordingly, while specific implementations are shown in the drawings, the technology is amenable to various modifications.

DETAILED DESCRIPTION

- (10) Disclosed here is a system and method to enable bidirectional visual communication between a mobile devices A and a device B, both associated with the same wireless telecommunication network. Device B can be a mobile device, a desktop computer, a laptop computer, a tablet, etc., associated with the wireless telecommunication network that enables an operator to access the wireless telecommunication network and to communicate with the mobile device A.
- (11) The system can receive an indication that a user associated with the mobile device A is experiencing an issue. The device B receives from the mobile device A a representation of a screen A associated with the mobile device A. The representation can show operating system settings and/or device settings associated with the mobile device A. The system can present the representation of the screen A associated with the mobile device A on a screen B associated with

the device B.

(12) The system can create an overlay A associated with the screen A and an overlay B associated with the screen B. The overlay A can include a transparent image A fitted over the screen A, while the overlay B can include a transparent image B fitted over the screen B. The overlay B can be configured to receive an input from a user. The input can be textual or visual, such as enclosing a user interface element shown on the screen A.

(13) The system can receive from the user the input. The system can present the input in the overlay B associated with the screen B, where the input is visible on top of the screen B. The system can send the input to the mobile device A, which is configured to present the input in the overlay A associated with the screen A. The mobile device A can present the input and so guide the user of the mobile device A in resolving the issue.

(14) The description and associated drawings are illustrative examples and are not to be construed as limiting. This disclosure provides certain details for a thorough understanding and enabling description of these examples. One skilled in the relevant technology will understand, however, that the invention can be practiced without many of these details. Likewise, one skilled in the relevant technology will understand that the invention can include well-known structures or features that are not shown or described in detail, to avoid unnecessarily obscuring the descriptions of examples.

(15) Wireless Communications System

(16) FIG. 1 is a block diagram that illustrates a wireless telecommunication network **100** (“network **100**”) in which aspects of the disclosed technology are incorporated. The network **100** includes base stations **102-1** through **102-4** (also referred to individually as “base station **102**” or collectively as “base stations **102**”). A base station is a type of network access node (NAN) that can also be referred to as a cell site, a base transceiver station, or a radio base station. The network **100** can include any combination of NANs, including an access point, radio transceiver, gNodeB (gNB), NodeB, eNodeB (eNB), Home NodeB or Home eNodeB, or the like. In addition to being a wireless wide area network (WWAN) base station, a NAN can be a wireless local area network (WLAN) access point, such as an Institute of Electrical and Electronics Engineers (IEEE) 802.11 access point.

(17) The NANs of a network **100** formed by the network **100** also include wireless devices **104-1** through **104-7** (referred to individually as “wireless device **104**” or collectively as “wireless devices **104**”) and a core network **106**. The wireless devices **104-1** through **104-7** can correspond to or include network **100** entities capable of communication using various connectivity standards. For example, a 5G communication channel can use millimeter wave (mmW) access frequencies of 28 GHz or more. In some implementations, the wireless device **104** can operatively couple to a base station **102** over a long-term evolution/long-term evolution-advanced (LTE/LTE-A) communication channel, which is referred to as a 4G communication channel.

(18) The core network **106** provides, manages, and controls security services, user authentication, access authorization, tracking, Internet Protocol (IP) connectivity, and other access, routing, or mobility functions. The base stations **102** interface with the core network **106** through a first set of backhaul links (e.g., S1 interfaces) and can perform radio configuration and scheduling for communication with the wireless devices **104** or can operate under the control of a base station controller (not shown). In some examples, the base stations **102** can communicate with each other, either directly or indirectly (e.g., through the core network **106**), over a second set of backhaul links **110-1** through **110-3** (e.g., X1 interfaces), which can be wired or wireless communication links.

(19) The base stations **102** can wirelessly communicate with the wireless devices **104** via one or more base station antennas. The cell sites can provide communication coverage for geographic coverage areas **112-1** through **112-4** (also referred to individually as “geographic coverage area **112**” or collectively as “geographic coverage areas **112**”). The geographic coverage area **112** for a base station **102** can be divided into sectors making up only a portion of the coverage area (not

shown). The network **100** can include base stations of different types (e.g., macro and/or small cell base stations). In some implementations, there can be overlapping geographic coverage areas **112** for different service environments (e.g., Internet-of-Things (IoT), mobile broadband (MBB), vehicle-to-everything (V2X), machine-to-machine (M2M), machine-to-everything (M2X), ultra-reliable low-latency communication (URLLC), machine-type communication (MTC), etc.).

(20) The network **100** can include a 5G network **100** and/or an LTE/LTE-A or other network. In an LTE/LTE-A network, the term eNBs is used to describe the base stations **102**, and in 5G new radio (NR) networks, the term gNBs is used to describe the base stations **102** that can include mmW communications. The network **100** can thus form a heterogeneous network **100** in which different types of base stations provide coverage for various geographic regions. For example, each base station **102** can provide communication coverage for a macro cell, a small cell, and/or other types of cells. As used herein, the term “cell” can relate to a base station, a carrier or component carrier associated with the base station, or a coverage area (e.g., sector) of a carrier or base station, depending on context.

(21) A macro cell generally covers a relatively large geographic area (e.g., several kilometers in radius) and can allow access by wireless devices that have service subscriptions with a wireless network **100** service provider. A small cell is a lower-powered base station, as compared to a macro cell, and can operate in the same or different (e.g., licensed, unlicensed) frequency bands as macro cells. Examples of small cells include pico cells, femto cells, and micro cells. In general, a pico cell can cover a relatively small geographic area and can allow unrestricted access by wireless devices that have service subscriptions with the network **100** provider. A femto cell covers a relatively small geographic area (e.g., a home) and can provide restricted access by wireless devices having an association with the femto unit (e.g., wireless devices in a closed subscriber group (CSG), wireless devices for users in the home). A base station can support one or multiple (e.g., two, three, four, and the like) cells (e.g., component carriers). All fixed transceivers noted herein that can provide access to the network **100** are NANs, including small cells.

(22) The communication networks that accommodate various disclosed examples can be packet-based networks that operate according to a layered protocol stack. In the user plane, communications at the bearer or Packet Data Convergence Protocol (PDCP) layer can be IP-based. A Radio Link Control (RLC) layer then performs packet segmentation and reassembly to communicate over logical channels. A Medium Access Control (MAC) layer can perform priority handling and multiplexing of logical channels into transport channels. The MAC layer can also use Hybrid ARQ (HARQ) to provide retransmission at the MAC layer, to improve link efficiency. In the control plane, the Radio Resource Control (RRC) protocol layer provides establishment, configuration, and maintenance of an RRC connection between a wireless device **104** and the base stations **102** or core network **106** supporting radio bearers for the user plane data. At the Physical (PHY) layer, the transport channels are mapped to physical channels.

(23) Wireless devices can be integrated with or embedded in other devices. As illustrated, the wireless devices **104** are distributed throughout the system **100**, where each wireless device **104** can be stationary or mobile. For example, wireless devices can include handheld mobile devices **104-1** and **104-2** (e.g., smartphones, portable hotspots, tablets, etc.); laptops **104-3**; wearables **104-4**; drones **104-5**; vehicles with wireless connectivity **104-6**; head-mounted displays with wireless augmented reality/virtual reality (ARNR) connectivity **104-7**; portable gaming consoles; wireless routers, gateways, modems, and other fixed-wireless access devices; wirelessly connected sensors that provides data to a remote server over a network; IoT devices such as wirelessly connected smart home appliances, etc.

(24) A wireless device (e.g., wireless devices **104-1**, **104-2**, **104-3**, **104-4**, **104-5**, **104-6**, and **104-7**) can be referred to as a user equipment (UE), a customer premise equipment (CPE), a mobile station, a subscriber station, a mobile unit, a subscriber unit, a wireless unit, a remote unit, a handheld mobile device, a remote device, a mobile subscriber station, terminal equipment, an

access terminal, a mobile terminal, a wireless terminal, a remote terminal, a handset, a mobile client, a client, or the like.

(25) A wireless device can communicate with various types of base stations and network **100** equipment at the edge of a network **100** including macro eNBs/gNBs, small cell eNBs/gNBs, relay base stations, and the like. A wireless device can also communicate with other wireless devices either within or outside the same coverage area of a base station via device-to-device (D2D) communications.

(26) The communication links **114-1** through **114-9** (also referred to individually as “communication link **114**” or collectively as “communication links **114**”) shown in network **100** include uplink (UL) transmissions from a wireless device **104** to a base station **102**, and/or downlink (DL) transmissions from a base station **102** to a wireless device **104**. The downlink transmissions can also be called forward link transmissions, while the uplink transmissions can also be called reverse link transmissions. Each communication link **114** includes one or more carriers, where each carrier can be a signal composed of multiple sub-carriers (e.g., waveform signals of different frequencies) modulated according to the various radio technologies. Each modulated signal can be sent on a different sub-carrier and carry control information (e.g., reference signals, control channels), overhead information, user data, etc. The communication links **114** can transmit bidirectional communications using frequency division duplex (FDD) (e.g., using paired spectrum resources) or time division duplex (TDD) operation (e.g., using unpaired spectrum resources). In some implementations, the communication links **114** include LTE and/or mmW communication links.

(27) In some implementations of the network **100**, the base stations **102** and/or the wireless devices **104** include multiple antennas for employing antenna diversity schemes to improve communication quality and reliability between base stations **102** and wireless devices **104**. Additionally or alternatively, the base stations **102** and/or the wireless devices **104** can employ multiple-input, multiple-output (MIMO) techniques that can take advantage of multi-path environments to transmit multiple spatial layers carrying the same or different coded data.

(28) Enabling Bidirectional Visual Communication Between Two Devices Associated with a Wireless Telecommunication Network

(29) FIG. 2 shows bidirectional visual communication between two devices. The first device **200** can be a user equipment (UE), such as a mobile phone, associated with a wireless telecommunication network **100** in FIG. 1 such as a 3G, 4G, 5G, or 6G network. The user of the first device **200** can be experiencing technical issues such as a problem configuring an embedded SIM (eSIM) card on the first device. The user may need to contact a customer assistance operator, such as a person or an artificial intelligence (AI), for help. The customer assistance operator can operate the second device **210**.

(30) To help resolve the issues associated with the first device **200**, the first device **200** can share the screen **220** of the first device, so that the operator can identify the problem and visually guide the user of the first device. The first device **200** can share only a selected element such as the full screen, only a certain application associated with the first device, and/or the operating system settings associated with the first device. In addition, the user can specify a time in which to share the screen, so that the first device **200** does not continuously stream the selected elements to the second device **210**. Once the first device **200** sends the representation of the screen **230** to the second device **210**, the second device **210** displays the representation of the screen **230** on the second device, and the first device and the second device can see the same view.

(31) The operator of the second device **210** can then visually guide the user of the first device **200** by, for example, creating a visual indicator **240** pointing out which user interface element **250** to select. To create the visual indicator **240**, **245**, the first device **200** and the second device **210** can create a first overlay **260** and a second overlay **270**, which are fitted over the screens of the devices **200**, **210**. The first overlay **260** can be the size of the screen of the first device **200**, while the

second overlay **270** can be the size of the screen of the second device **210**. The devices **200**, **210** can have different sizes. The overlays **260**, **270** can be transparent, and only the visual indicator **240** can be visible.

(32) To initiate the screen sharing and the creation of the overlays **260**, **270**, the operator can select the user element **280**. Upon creating the visual indicator **240**, the operator can select the user element **290** to communicate the visual indicator **240** to the second overlay **270**. Consequently, the first device **200** can display the corresponding visual indicator **245**. The operator can create one or more visual indicators **240**. To remove the visual indicators **240**, **245** from the first and second overlays **260**, **270**, the operator can select the user interface element **205**.

(33) FIG. **3** shows presenting additional instruction using picture-in-picture technology. In addition to providing the visual indicator **240**, **245**, the second device **210** sometimes needs to provide additional instruction to the first device **200**. For example, the user of the first device **200** could be hard of hearing and might better understand textual instruction as opposed to audio instruction. In addition to or instead of providing the visual indicator **240**, **245**, the second device **210** can provide additional instruction **300** to the first device **200**, further instructing the user how to resolve the issue. The additional instruction **300** can be textual instruction, as seen in FIG. **3**, or it can be another image or an explanatory video. To create the additional instruction **300**, the second device **210** can utilize picture-in-picture software development kit (SDK), which is available on Android, iPhones, or other mobile devices.

(34) FIG. **4** shows sharing of operating system settings between two devices. The disclosed technology can enable the first device **200** to share with the second device **210** the device configuration settings and/or the operating system settings **400** associated with the first device **200**. While sharing the screen generated by an application can be easily done, most systems do not support sharing the device configuration settings and/or the operating system settings **400** as shown in FIG. **4** because operating system settings are normally protected and require additional permissions.

(35) For security reasons, the user can specify a time **410** at which to share the settings **400**. The time **410** can be instantaneous, as shown in FIG. **4**, or can include a time period. Once the current time is outside the specified time **410**, the first device **200** can stop sharing the screen.

(36) FIG. **5** is a flowchart of a method to enable bidirectional visual communication between a first UE associated with a wireless telecommunication network and a second device associated with the wireless telecommunication network. In step **500**, a hardware or software processor executing instructions described in this application can cause the second device to receive, from the first UE a representation of a first screen associated with the first UE. The representation can show operating system settings associated with the first UE or an application associated with the first UE.

(37) In step **510**, the processor can present the representation of the first screen associated with the first UE on a second screen associated with the second device. The second device can be an electronic device such as a laptop computer, a desktop computer, or a UE associated with an operator of the network **100** in FIG. **1**.

(38) In step **520**, the processor can create a first overlay associated with the first screen and a second overlay associated with the second screen, where the first overlay includes a first transparent image fitted over the first screen and the second overlay includes a second transparent image fitted over the second screen. The second overlay is configured to receive an input from a second user. The input can be textual or visual, such as a circle. Also, the processor can receive the first screen, and create a composite of the received first screen from the first UE and the currently displayed second screen at the second device, with a delta between the two highlighted or otherwise emphasized. For example, the processor can gray out the visual elements between the first and second screens that are the same. The processor can share the composite with the first UE and the second device.

(39) In step **530**, the processor can receive from the second user an input. In step **540**, the processor

can present the input in the second overlay associated with the second screen, where the input is visible on top of the second screen associated with the second device.

(40) In step 550, the processor can send the input to the first UE, which is configured to present the input in the first overlay associated with the first screen. When presented to the first user, the input can guide the first user to resolve a technical issue with the UE.

(41) The processor can share a specific application or a whole screen of the first UE indefinitely, or for a specified period of time, without streaming. The processor can receive an indication of time during which to share the representation associated with the first screen. The indication of time can be instantaneous or can be a period of time. The processor can obtain a current time. The processor can determine whether the current time is outside the indication of time during which to share the representation. Upon determining that the current time is within the indication of time during which to share the representation, the processor can cause the first UE to send the representation of the first screen associated with the first UE to the second device. Upon determining that the current time is outside the indication of time during which to share the representation, the processor can cause the first UE to refrain from sending the representation of the first screen associated with the first UE.

(42) The processor can create a picture-in-picture textual instruction and/or graphical instruction, which can be useful if the user is hard of hearing or has trouble following audio instructions. The processor can receive an indication that a first user associated with the first device is experiencing an issue, such as an issue with configuring an eSIM. Upon receiving the representation of the first screen associated with the first UE, the processor can generate a visual representation including instructions indicating how to resolve the issue. The visual representation can include text for hard-of-hearing clients. The processor can send the visual representation to the first UE. The processor can cause the first UE to present the visual representation on a first portion of the first screen, where the first portion of the first screen does not obscure a second portion of the first screen needed to follow the instructions.

(43) The processor can automatically position the visual representation to not obscure the second portion of the first screen. In addition, the processor can cause the first UE to receive a second input from the first user indicating to relocate the visual representation. For example, the user may want to relocate the visual presentation because the picture-in-picture is obscuring an important part of the screen. The processor can cause the first UE to relocate the visual representation based on the second input from the first user.

(44) The processor can utilize AI to provide automated guidance to the user seeking assistance. The processor can analyze the representation of the first screen associated with the first UE. To analyze the representation of the first screen, the processor can retrieve from a database multiple screens and multiple solutions, where a screen among the multiple screens is associated with a solution among multiple solutions. The solution can be a solution to the issue that the user is experiencing when sharing the particular screen. To further analyze the representation of the first screen, the processor can select among the multiple screens a third screen that is most similar to the first screen. The processor can measure a similarity between screens based on similarity of texts displayed on the screens or similarity of icons displayed on the screens. The processor can identify a third solution associated with the third screen. The processor can provide the third solution to the first UE.

(45) The processor can store the solutions in a database for future reference. The processor can receive an indication that a first user associated with the first device is experiencing an issue. The processor can receive an indication that the issue has been resolved and an indication of a solution of the issue. The processor can store the indication of the solution of the issue and at least one of the first overlay or the second overlay. In addition, the processor can store a description of the issue associated with the screen.

(46) The processor can remove overlays after the connection between the first UE and the second

device is closed. The processor can store the overlays in a database for future reference. The processor can receive an indication to end a communication between the first UE and the second device. The processor can remove the first overlay associated with the first screen and the second overlay associated with the second screen. The processor can store at least one of the first overlay or the second overlay. In addition, the processor can store a description of the issue associated with the overlay.

(47) FIG. 6 is a flowchart of a method to present additional instruction using picture-in-picture technology. A processor can use a picture-in-picture software development kit to provide additional instruction to a user seeking assistance, such as a user that has difficulty following verbal instructions.

(48) In step 600, a processor can receive an indication that a first user associated with the first UE is experiencing an issue, such as an issue configuring the first device to use an eSIM.

(49) In step 610, the processor can cause the second device to receive, from the first UE a representation of a first screen associated with the first UE. In step 620, the processor can present the representation of the first screen associated with the first UE on a second screen associated with the second device.

(50) In step 630, the processor can generate a visual representation including instructions indicating how to resolve the issue. The instructions can be textual or visual, such as a video, and can help users having difficulty following verbal instructions, such as hearing-impaired users.

(51) In step 640, the processor can send the visual representation to the first UE. In step 650, the processor can use a picture-in-picture software development kit to cause the first UE to present the visual representation on a first portion of the first screen. The visual presentation can obscure the first portion of the first screen. In other words, the visual representation can be opaque and can be overlaid over the first portion of the screen. The processor can position the visual representation on the screen so that the first portion of the first screen does not obscure a second portion of the first screen needed to follow the instructions.

(52) The processor can present the representation of the first screen associated with the first UE on a second screen associated with the second device. The processor can create a first overlay associated with the first screen and a second overlay associated with the second screen. The first overlay can include a first transparent image fitted over the first screen, while the second overlay can include a second transparent image fitted over the second screen. In other words, the first overlay can be the same size as the first screen, while the second overlay can be the same size as the second screen. The first overlay and the second overlay can be different sizes. The second overlay can be configured to receive an input from a second user. The input can be textual or visual, such as enclosing or highlighting a portion of the screen. The processor can receive from the second user the input, such as a visual or an alphanumeric input. The processor can present the input in the second overlay associated with the second screen, where the input is visible on top of the second screen associated with the second device. The processor can send the input to the first UE, which is configured to present the input in the first overlay associated with the first screen. The first UE can present the input on the first screen and the user of the first UE.

(53) The processor can enable the user to select the whole screen, a portion of the screen, or a particular application associated with the first UE to share. In addition, the processor can enable the user to select a time, such as a time instant or a period of time during which to share the UE. Consequently, the processor can share the first screen without streaming the first screen, instead sharing the first screen only at the specified time.

(54) To share the screen without streaming, the processor can receive an indication of time during which to share the representation associated with the first screen. The processor can obtain a current time. The processor can determine whether the current time is outside the indication of time during which to share the representation. Upon determining that the current time is within the indication of time during which to share the representation, the processor can cause the first UE to

send the representation of the first screen associated with the first UE to the second device. Upon determining that the current time is outside the indication of time during which to share the representation, the processor can cause the first UE to refrain from sending the representation of the first screen associated with the first UE.

(55) The processor can create a picture-in-picture textual and/or graphical instruction, which can be helpful when the user is hard of hearing or has trouble following instructions. The processor can cause the first UE to present the visual representation on a first portion of the first screen. The processor can cause the first UE to receive a second input from the first user indicating to relocate the visual representation because, for example, the picture-in-picture is obscuring an important part of the first screen. The processor can cause the first UE to relocate the visual representation based on the second input from the first user.

(56) The processor can send screen captures to machine learning models that can provide automated guidance to the user. The processor can analyze the representation of the first screen associated with the first UE. To analyze the first screen, the processor can retrieve from a database multiple screens and multiple solutions, where a screen among the multiple screens is associated with a solution among multiple solutions. To further analyze the screen, the processor can identify among the multiple screens a third screen that is most similar to the first screen. The processor can measure the similarity between screens by measuring similarity of texts or similarity of icons displayed on the screens. The processor can identify a third solution associated with the third screen. The processor can provide the third solution to the first UE.

(57) The processor can store solutions in a database for future reference. The processor can receive an indication that the issue has been resolved and an indication of a solution of the issue. The processor can store the indication of the solution of the issue and at least one of the first overlay or the second overlay. The processor can also store the issue that the user was experiencing when sharing the screen.

(58) Computer System

(59) FIG. 7 is a block diagram that illustrates an example of a computer system **700** in which at least some operations described herein can be implemented. As shown, the computer system **700** can include one or more processors **702**, main memory **706**, non-volatile memory **710**, a network interface device **712**, a video display device **718**, an input/output device **720**, a control device **722** (e.g., keyboard and pointing device), a drive unit **724** that includes a machine-readable (storage) medium **726**, and a signal generation device **730** that are communicatively connected to a bus **716**. The bus **716** represents one or more physical buses and/or point-to-point connections that are connected by appropriate bridges, adapters, or controllers. Various common components (e.g., cache memory) are omitted from FIG. 7 for brevity. Instead, the computer system **700** is intended to illustrate a hardware device on which components illustrated or described relative to the examples of the Figures and any other components described in this specification can be implemented.

(60) The computer system **700** can take any suitable physical form. For example, the computing system **700** can share a similar architecture as that of a server computer, personal computer (PC), tablet computer, mobile telephone, game console, music player, wearable electronic device, network-connected (“smart”) device (e.g., a television or home assistant device), AR/VR systems (e.g., head-mounted display), or any electronic device capable of executing a set of instructions that specify action(s) to be taken by the computing system **700**. In some implementations, the computer system **700** can be an embedded computer system, a system-on-chip (SOC), a single-board computer system (SBC), or a distributed system, such as a mesh of computer systems, or include one or more cloud components in one or more networks. Where appropriate, one or more computer systems **700** can perform operations in real time, near real time, or in batch mode.

(61) The network interface device **712** enables the computing system **700** to mediate data in a network **714** with an entity that is external to the computing system **700** through any

communication protocol supported by the computing system **700** and the external entity. Examples of the network interface device **712** include a network adaptor card, a wireless network interface card, a router, an access point, a wireless router, a switch, a multilayer switch, a protocol converter, a gateway, a bridge, a bridge router, a hub, a digital media receiver, and/or a repeater, as well as all wireless elements noted herein.

(62) The memory (e.g., main memory **706**, non-volatile memory **710**, machine-readable (storage) medium **726**) can be local, remote, or distributed. Although shown as a single medium, the machine-readable (storage) medium **726** can include multiple media (e.g., a centralized/distributed database and/or associated caches and servers) that store one or more sets of instructions **728**. The machine-readable (storage) medium **726** can include any medium that is capable of storing, encoding, or carrying a set of instructions for execution by the computing system **700**. The machine-readable medium **726** can be non-transitory or comprise a non-transitory device. In this context, a non-transitory storage medium can include a device that is tangible, meaning that the device has a concrete physical form, although the device can change its physical state. Thus, for example, non-transitory refers to a device remaining tangible despite this change in state.

(63) Although implementations have been described in the context of fully functioning computing devices, the various examples are capable of being distributed as a program product in a variety of forms. Examples of machine-readable storage media, machine-readable media, or computer-readable media include recordable-type media such as volatile and non-volatile memory devices **710**, removable flash memory, hard disk drives, optical disks, and transmission-type media such as digital and analog communication links.

(64) In general, the routines executed to implement examples herein can be implemented as part of an operating system or a specific application, component, program, object, module, or sequence of instructions (collectively referred to as “computer programs”). The computer programs typically comprise one or more instructions (e.g., instructions **704**, **708**, **728**) set at various times in various memory and storage devices in computing device(s). When read and executed by the processor **702**, the instruction(s) cause the computing system **700** to perform operations to execute elements involving the various aspects of the disclosure.

REMARKS

(65) The terms “example,” “embodiment,” and “implementation” are used interchangeably. For example, references to “one example” and “an example” in the disclosure can be, but not necessarily are, references to the same implementation, and such references mean at least one of the implementations. The appearances of the phrase “in one example” are not necessarily all referring to the same example, nor are separate or alternative examples mutually exclusive of other examples. A feature, structure, or characteristic described in connection with an example can be included in another example of the disclosure. Moreover, various features are described that can be exhibited by some examples and not by others. Similarly, various requirements are described that can be requirements for some examples but not other examples.

(66) The terminology used herein should be interpreted in its broadest reasonable manner, even though it is being used in conjunction with certain specific examples of the invention. The terms used in the disclosure generally have their ordinary meanings in the relevant technical art, within the context of the disclosure, and in the specific context where each term is used. A recital of alternative language or synonyms does not exclude the use of other synonyms. Special significance should not be placed upon whether or not a term is elaborated or discussed herein. The use of highlighting has no influence on the scope and meaning of a term. Further, it will be appreciated that the same thing can be said in more than one way.

(67) Unless the context clearly requires otherwise, throughout the description and the claims, the words “comprise,” “comprising,” and the like are to be construed in an inclusive sense, as opposed to an exclusive or exhaustive sense; that is to say, in the sense of “including, but not limited to.” As used herein, the terms “connected,” “coupled,” or any variant thereof means any connection or

coupling, either direct or indirect, between two or more elements; the coupling or connection between the elements can be physical, logical, or a combination thereof. Additionally, the words “herein,” “above,” “below,” and words of similar import can refer to this application as a whole and not to any particular portions of this application. Where context permits, words in the above Detailed Description using the singular or plural number may also include the plural or singular number, respectively. The word “or” in reference to a list of two or more items covers all of the following interpretations of the word: any of the items in the list, all of the items in the list, and any combination of the items in the list. The term “module” refers broadly to software components, firmware components, and/or hardware components.

(68) While specific examples of technology are described above for illustrative purposes, various equivalent modifications are possible within the scope of the invention, as those skilled in the relevant art will recognize. For example, while processes or blocks are presented in a given order, alternative implementations can perform routines having steps, or employ systems having blocks, in a different order, and some processes or blocks may be deleted, moved, added, subdivided, combined, and/or modified to provide alternative or sub-combinations. Each of these processes or blocks can be implemented in a variety of different ways. Also, while processes or blocks are at times shown as being performed in series, these processes or blocks can instead be performed or implemented in parallel, or can be performed at different times. Further, any specific numbers noted herein are only examples such that alternative implementations can employ differing values or ranges.

(69) Details of the disclosed implementations can vary considerably in specific implementations while still being encompassed by the disclosed teachings. As noted above, particular terminology used when describing features or aspects of the invention should not be taken to imply that the terminology is being redefined herein to be restricted to any specific characteristics, features, or aspects of the invention with which that terminology is associated. In general, the terms used in the following claims should not be construed to limit the invention to the specific examples disclosed herein, unless the above Detailed Description explicitly defines such terms. Accordingly, the actual scope of the invention encompasses not only the disclosed examples, but also all equivalent ways of practicing or implementing the invention under the claims. Some alternative implementations can include additional elements to those implementations described above or include fewer elements.

(70) Any patents and applications and other references noted above, and any that may be listed in accompanying filing papers, are incorporated herein by reference in their entireties, except for any subject matter disclaimers or disavowals, and except to the extent that the incorporated material is inconsistent with the express disclosure herein, in which case the language in this disclosure controls. Aspects of the invention can be modified to employ the systems, functions, and concepts of the various references described above to provide yet further implementations of the invention.

(71) To reduce the number of claims, certain implementations are presented below in certain claim forms, but the applicant contemplates various aspects of an invention in other forms. For example, aspects of a claim can be recited in a means-plus-function form or in other forms, such as being embodied in a computer-readable medium. A claim intended to be interpreted as a means-plus-function claim will use the words “means for.” However, the use of the term “for” in any other context is not intended to invoke a similar interpretation. The applicant reserves the right to pursue such additional claim forms in either this application or in a continuing application.

Claims

1. At least one computer-readable storage medium, excluding transitory signals and carrying instructions to enable bidirectional visual communication between a first mobile device associated with a wireless telecommunication network and a second device associated with the wireless

telecommunication network, which, when executed by at least one data processor of a system, cause the system to: receive, by the second device, from the first mobile device a representation of a first screen associated with the first mobile device, wherein the first screen indicates a technical issue experienced by the first mobile device, wherein the representation shows operating system settings of the first mobile device, the operating system settings controlling operations of one or more systems of the first mobile device and related to a cause of the technical issue; present the representation of the first screen associated with the first mobile device on a second screen associated with the second device; create a first overlay associated with the first screen and a second overlay associated with the second screen, wherein the first overlay includes a first transparent image fitted over the first screen, wherein the second overlay includes a second transparent image fitted over the second screen, and wherein the second overlay is configured to receive an input from a second user; obtain a solution associated with the technical issue experienced by the first mobile device by: retrieving, from a database, multiple screens associated with multiple solutions of multiple technical issues previously experienced by multiple mobile devices operating on the wireless telecommunication network, wherein the multiple screens show operating system settings of the multiple mobile devices during the multiple technical issues, the operating system settings controlling operations of one or more systems of the multiple mobile devices and related to causes of the multiple technical issues; among the multiple screens, determining a third screen most similar to the first screen by measuring similarity of an icon displayed on the first screen and an icon displayed on the third screen; obtaining a solution among the multiple solutions associated with the third screen, wherein the solution among the multiple solutions associated with the third screen includes the solution associated with the technical issue experienced by the first mobile device, wherein the solution associated with the technical issue experienced by the first mobile device comprises an adjustment to the operating system settings of the first mobile device; receive from the second user the input, wherein the input is based on the obtained solution associated with the technical issue experienced by the first mobile device and includes a visual or an alphanumeric input configured to assist a first user of the first mobile device with the technical issue experienced by the first mobile device; present the input in the second overlay associated with the second screen, wherein the input is visible on top of the second screen associated with the second device; and send the input to the first mobile device configured to present the input in the first overlay associated with the first screen.

2. The at least one computer-readable storage medium of claim 1, comprising instructions to: receive an indication of time during which to share the representation of the first screen associated with the first mobile device; obtain a current time; determine whether the current time is outside the indication of time during which to share the representation; upon determining that the current time is within the indication of time during which to share the representation, cause the first mobile device to send the representation of the first screen associated with the first mobile device to the second device; and upon determining that the current time is outside the indication of time during which to share the representation, cause the first mobile device to refrain from sending the representation of the first screen associated with the first mobile device.

3. The at least one computer-readable storage medium of claim 1, comprising instructions to: receive an indication that the first user associated with the first mobile device is experiencing the technical issue; upon receiving the representation of the first screen associated with the first mobile device, generate a visual representation including instructions indicating how to resolve the technical issue; send the visual representation to the first mobile device; and cause the first mobile device to present the visual representation on a first portion of the first screen, wherein the first portion of the first screen does not obscure a second portion of the first screen needed to follow the instructions indicating how to resolve the technical issue.

4. The at least one computer-readable storage medium of claim 1, comprising instructions to: receive an indication that the first user associated with the first mobile device is experiencing the

technical issue; upon receiving the representation of the first screen associated with the first mobile device, generate a visual representation including instructions indicating how to resolve the technical issue; send the visual representation to the first mobile device; cause the first mobile device to present the visual representation on a first portion of the first screen; cause the first mobile device to receive a second input from the first user indicating to relocate the visual representation; and cause the first mobile device to relocate the visual representation based on the second input from the first user.

5. The at least one computer-readable storage medium of claim 1, comprising instructions to: receive an indication that the first user associated with the first mobile device is experiencing the technical issue, an indication that the technical issue has been resolved, and an indication of a solution of the technical issue; and store the indication of the solution of the technical issue and at least one of the first overlay or the second overlay.

6. The at least one computer-readable storage medium of claim 1, comprising instructions to: receive an indication to end a communication between the first mobile device and the second device; remove the first overlay associated with the first screen and the second overlay associated with the second screen; and store at least one of the first overlay or the second overlay.

7. A system comprising: at least one hardware processor; and at least one non-transitory memory storing instructions, which, when executed by the at least one hardware processor, cause the system to: receive, by a second device, from a first user equipment (UE) a representation of a first screen associated with the first UE, wherein the first screen indicates a technical issue experienced by the first UE, wherein the representation shows operating system settings of the first UE, the operating system settings controlling operations of one or more systems of the first UE and related to a cause of the technical issue; present the representation of the first screen associated with the first UE on a second screen associated with the second device; create a first overlay associated with the first screen and a second overlay associated with the second screen, wherein the first overlay includes a first transparent image fitted over the first screen, wherein the second overlay includes a second transparent image fitted over the second screen, and wherein the second overlay is configured to receive an input from a second user; obtain a solution associated with the technical issue experienced by the first UE by: retrieving, from a database, multiple screens associated with multiple solutions of multiple technical issues previously experienced by multiple UEs, wherein the multiple screens show operating system settings of the multiple UEs during the multiple technical issues, the operating system settings controlling operations of one or more systems of the multiple UEs and related to causes of the multiple technical issues; among the multiple screens, determining a third screen most similar to the first screen by measuring similarity of an icon displayed on the first screen and an icon displayed on the third screen; obtaining a solution among the multiple solutions associated with the third screen, wherein the solution among the multiple solutions associated with the third screen includes the solution associated with the technical issue experienced by the first UE, wherein the solution associated with the technical issue experienced by the first UE comprises an adjustment to the operating system settings of the first UE; receive from the second user the input, wherein the input is based on the obtained solution associated with the technical issue experienced by the first UE and includes a visual or an alphanumeric input configured to assist a first user of the first UE with the technical issue experienced by the first UE; present the input in the second overlay associated with the second screen, wherein the input is visible on top of the second screen; and send the input to the first UE configured to present the input in the first overlay associated with the first screen.

8. The system of claim 7, comprising instructions to: receive an indication of time during which to share the representation of the first screen associated with the first UE; obtain a current time; determine whether the current time is outside the indication of time during which to share the representation; upon determining that the current time is within the indication of time during which to share the representation, cause the first UE to send the representation of the first screen

associated with the first UE to the second device; and upon determining that the current time is outside the indication of time during which to share the representation, cause the first UE to refrain from sending the representation of the first screen associated with the first UE.

9. The system of claim 7, comprising instructions to: receive an indication that the first user associated with the first UE is experiencing the technical issue; upon receiving the representation of the first screen associated with the first UE, generate a visual representation including instructions indicating how to resolve the technical issue; send the visual representation to the first UE; and cause the first UE to present the visual representation on a first portion of the first screen, wherein the first portion of the first screen does not obscure a second portion of the first screen needed to follow the instructions indicating how to resolve the technical issue.

10. The system of claim 7, comprising instructions to: receive an indication that the first user associated with the first UE is experiencing the technical issue; upon receiving the representation of the first screen associated with the first UE, generate a visual representation including instructions indicating how to resolve the technical issue; send the visual representation to the first UE; cause the first UE to present the visual representation on a first portion of the first screen; cause the first UE to receive a second input from the first user indicating to relocate the visual representation; and cause the first UE to relocate the visual representation based on the second input from the first user.

11. The system of claim 7, comprising instructions to: analyze the representation of the first screen associated with the first UE by: retrieving from a database multiple screens and multiple solutions, wherein a screen among the multiple screens is associated with a solution among the multiple solutions; and identifying among the multiple screens a third screen that is most similar to the first screen; identify a third solution associated with the third screen; and provide the third solution to the first UE.

12. The system of claim 7, comprising instructions to: receive an indication that the first user associated with the first UE is experiencing the technical issue, an indication that the issue has been resolved, and an indication of a solution of the technical issue; and store the indication of the solution of the technical issue and at least one of the first overlay or the second overlay.

13. The system of claim 7, comprising instructions to: receive an indication to end a communication between the first UE and the second device; remove the first overlay associated with the first screen and the second overlay associated with the second screen; and store at least one of the first overlay or the second overlay.

14. A system comprising: at least one hardware processor; and at least one non-transitory memory storing instructions, which, when executed by the at least one hardware processor, cause the system to: receive an indication that a first user associated with a first user equipment (UE) is experiencing a technical issue; receive, by a second device, from the first UE a representation of a first screen associated with the first UE, wherein the first screen indicates the technical issue experienced by the first UE, wherein the representation shows operating system settings of the first UE, the operating system settings controlling operations of one or more systems of the first UE and related to a cause of the technical issue; present the representation of the first screen associated with the first UE on a second screen associated with the second device; obtain a solution associated with the technical issue experienced by the first UE by: retrieving, from a database, multiple screens associated with multiple solutions of multiple technical issues previously experienced by multiple UEs, wherein the multiple screens show operating system settings of the multiple UEs during the multiple technical issues, the operating system settings controlling operations of one or more systems of the multiple UEs and related to causes of the multiple technical issues; among the multiple screens, determining a third screen most similar to the first screen by measuring similarity of an icon displayed on the first screen and an icon displayed on the third screen; obtaining a solution among the multiple solutions associated with the third screen, wherein the solution among the multiple solutions associated with the third screen includes the solution associated with the technical issue experienced by the first UE, wherein the solution associated with the technical issue

experienced by the first UE comprises an adjustment to the operating system settings of the first UE; generate a visual representation including instructions indicating how to resolve the technical issue, wherein the visual representation is based on the obtained solution associated with the technical issue experienced by the first UE and; send the visual representation to the first UE; and use a picture-in-picture software development kit to cause the first UE to present the visual representation on a first portion of the first screen, wherein the visual presentation obscures the first portion of the first screen, and wherein the first portion of the first screen does not obscure a second portion of the first screen needed to follow the instructions.

15. The system of claim 14, comprising instructions to: present the representation of the first screen associated with the first UE on a second screen associated with the second device; create a first overlay associated with the first screen and a second overlay associated with the second screen, wherein the first overlay includes a first transparent image fitted over the first screen, wherein the second overlay includes a second transparent image fitted over the second screen, and wherein the second overlay is configured to receive an input from a second user; receive from the second user the input, wherein the input includes a visual or an alphanumeric input; present the input in the second overlay associated with the second screen, wherein the input is visible on top of the second screen; and send the input to the first UE configured to present the input in the first overlay associated with the first screen.

16. The system of claim 14, comprising instructions to: receive an indication of time during which to share the representation of the first screen associated with the first UE; obtain a current time; determine whether the current time is outside the indication of time during which to share the representation; upon determining that the current time is within the indication of time during which to share the representation, cause the first UE to send the representation of the first screen associated with the first UE to the second device; and upon determining that the current time is outside the indication of time during which to share the representation, cause the first UE to refrain from sending the representation of the first screen associated with the first UE.

17. The system of claim 14, comprising instructions to: cause the first UE to present the visual representation on a first portion of the first screen; cause the first UE to receive a second input from the first user indicating to relocate the visual representation; and cause the first UE to relocate the visual representation based on the second input from the first user.

18. The system of claim 14, comprising instructions to: analyze the representation of the first screen associated with the first UE by: retrieving from a database multiple screens and multiple solutions, wherein a screen among the multiple screens is associated with a solution among the multiple solutions; and identifying among the multiple screens a third screen that is most similar to the first screen; identify a third solution associated with the third screen; and provide the third solution to the first UE.

19. The system of claim 14, comprising instructions to: receive an indication that the technical issue has been resolved and an indication of a solution of the technical issue; and store the indication of the solution of the technical issue and at least one of the first screen or the second screen.
