

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408585
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Chung; Koon For et al.

Force amplified fastener for power tool implements

Abstract

Systems and methods which provide force amplified fastener assemblies configured for use with respect to detachable implements for power tools are described. Force amplified fastener assemblies may implement various gear train configurations for giving a mechanical advantage with respect to manual manipulation of the fastener assembly. A force amplified fastener assembly may include a lock mechanism operative to lock and/or unlock the force amplified fastener assembly and thus a fastening element thereof. Force amplified fastener assemblies of embodiments of the inventions may be utilized in place of conventional lock nut for affixing detachable implements to power tools.

Inventors:	Chung; Koon For (Kwai Chung, CN), Wong; Tsz Kin (Kwai Chung, CN)
Applicant:	TECHTRONIC CORDLESS GP (Anderson, SC)
Family ID:	76059614
Assignee:	TECHTRONIC CORDLESS GP (Anderson, SC)
Appl. No.:	18/287777
Filed (or PCT Filed):	April 23, 2021
PCT No.:	PCT/CN2021/089276
PCT Pub. No.:	WO2022/222135
PCT Pub. Date:	October 27, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240191777 A1	Jun. 13, 2024

Publication Classification

Int. Cl.: F16H13/06 (20060101); A01D34/416 (20060101); A01D34/73 (20060101); F16H1/32 (20060101); F16H35/00 (20060101)

U.S. Cl.:

CPC A01D34/733 (20130101); A01D34/4165 (20130101); F16H1/32 (20130101); A01D34/416 (20130101); F16H1/321 (20130101); F16H2001/323 (20130101); F16H13/06 (20130101); F16H2035/005 (20130101)

Field of Classification Search

CPC: A01D (34/733); A01D (34/4165); A01D (34/416); F16H (1/32); F16H (1/321); F16H (13/06); F16H (2001/323); F16H (2035/005)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4585025	12/1985	Hendrick	N/A	N/A
5934853	12/1998	Junkers	N/A	N/A
6682284	12/2003	Chen	N/A	N/A
6913429	12/2004	Phillips	N/A	N/A
7124566	12/2005	Treger	N/A	N/A
7179035	12/2006	Axelsson	N/A	N/A
8016532	12/2010	Park	N/A	N/A
8220365	12/2011	Yang	N/A	N/A
8225698	12/2011	Yang	N/A	N/A
8225699	12/2011	Yang	N/A	N/A
8702363	12/2013	Lee	N/A	N/A
8746100	12/2013	Cook	N/A	N/A
8899894	12/2013	Limpert	N/A	N/A
9267587	12/2015	Abevi	N/A	N/A
9568076	12/2016	McGrath	N/A	N/A
9631663	12/2016	Carnevali	N/A	N/A
9936635	12/2017	Gottinger	N/A	N/A
10041573	12/2017	Abevi	N/A	N/A
D828153	12/2017	Sato	N/A	N/A
10265837	12/2018	Lin	N/A	B25B 17/02
2015/0354667	12/2014	Tesar	475/180	H02K 7/116
2019/0003517	12/2018	Hess	N/A	N/A
2019/0285141	12/2018	Ohr	N/A	B60K 17/145
2019/0299373	12/2018	Usui	N/A	N/A
2019/0353198	12/2018	Moarefi	N/A	N/A
2020/0124081	12/2019	Bengtsson et al.	N/A	N/A
2020/0291984	12/2019	Wang	N/A	N/A
2020/0393030	12/2019	Guan	N/A	N/A
2024/0188490	12/2023	Chung	N/A	A01D 34/4165

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2733067	12/2004	CN	N/A
201456225	12/2009	CN	N/A
202742328	12/2012	CN	N/A
104265749	12/2015	CN	N/A
105805100	12/2015	CN	N/A
205715196	12/2015	CN	N/A
303985034	12/2015	CN	N/A
106763603	12/2016	CN	N/A
106979212	12/2016	CN	N/A
107642536	12/2017	CN	N/A
206883155	12/2017	CN	N/A
107926325	12/2017	CN	N/A
207315836	12/2017	CN	N/A
108331829	12/2017	CN	N/A
207754151	12/2017	CN	N/A
108679076	12/2017	CN	N/A
207927298	12/2017	CN	N/A
108825636	12/2017	CN	N/A
108953354	12/2017	CN	N/A
109168571	12/2018	CN	N/A
109372877	12/2018	CN	N/A
106640913	12/2018	CN	N/A
109773470	12/2018	CN	N/A
209115511	12/2018	CN	N/A
110185691	12/2018	CN	N/A
209268092	12/2018	CN	N/A
110206809	12/2018	CN	N/A
110355712	12/2018	CN	N/A
209539931	12/2018	CN	N/A
110397657	12/2018	CN	N/A
209628155	12/2018	CN	N/A
110578743	12/2018	CN	N/A
209774484	12/2018	CN	N/A
209954711	12/2019	CN	N/A
110788790	12/2019	CN	N/A
110792678	12/2019	CN	N/A
111034455	12/2019	CN	N/A
210290450	12/2019	CN	N/A
210318115	12/2019	CN	N/A
210328614	12/2019	CN	N/A
210371535	12/2019	CN	N/A
111271364	12/2019	CN	N/A
108757695	12/2019	CN	N/A
111396436	12/2019	CN	N/A
111457070	12/2019	CN	N/A
210920040	12/2019	CN	N/A
211163727	12/2019	CN	N/A

211185047	12/2019	CN	N/A
111649055	12/2019	CN	N/A
211693411	12/2019	CN	N/A
211761131	12/2019	CN	N/A
112013001	12/2019	CN	N/A
112141368	12/2019	CN	N/A
212278872	12/2020	CN	N/A
112497156	12/2020	CN	N/A
110657152	12/2020	CN	N/A
112425346	12/2020	CN	N/A
111878512	12/2021	CN	N/A
20208806	12/2001	DE	N/A
20302843	12/2002	DE	N/A
102016117487	12/2017	DE	N/A
102019202035	12/2019	DE	N/A
0764789	12/1996	EP	N/A
2014933	12/2009	EP	N/A
2404495	12/2011	EP	N/A
2784350	12/2013	EP	N/A
2798937	12/2013	EP	N/A
2798937	12/2015	EP	N/A
3636097	12/2019	EP	N/A
2854213	12/2003	FR	N/A
3098268	12/2020	FR	N/A
2498829	12/2012	GB	N/A
WO-8805386	12/1979	WO	N/A
WO 81/00337	12/1980	WO	N/A
WO9910662	12/1998	WO	N/A
WO2018097592	12/2017	WO	N/A
WO2019190116	12/2018	WO	N/A
WO2020121865	12/2019	WO	N/A
WO2020131972	12/2019	WO	N/A
WO2020158700	12/2019	WO	N/A
WO2020213774	12/2019	WO	N/A
WO2020213828	12/2019	WO	N/A

OTHER PUBLICATIONS

International Search Report Corresponding with Chinese Application No. PCT/CN2021/089276 dated Oct. 15, 2021. cited by applicant

Primary Examiner: Holmes; Justin

Attorney, Agent or Firm: Dority & Manning, P.A.

Background/Summary

(1) This application is a National Stage Patent Application of PCT/CN2021/089276, filed on Apr. 23, 2021, the disclosure of which is incorporated by reference herein in its entirety.

TECHNICAL FIELD

(2) The present invention relates generally to garden machines having detachable implements and, more particularly, to fasteners useful with respect to detachable implements for power tools.

BACKGROUND OF THE INVENTION

(3) Various configurations of power tools are commonly used in performing routine tasks in daily life. For example, power tools in the form of garden machines, such as lawn mowers, brush cutters, string trimmers, grass edgers, etc., are used every day by persons performing work and leisure related tasks. These power tools often comprise a motor of some form (e.g., electric motor or internal combustion motor) outputting power via a shaft which drives an implement configured for the related task. As examples, a lawn mower may drive an implement in the form of a grass cutting blade, a brush cutter may drive an implement in the form of a multipurpose cutting blade, a string trimmer may drive an implement in the form of string spool head, and a grass edger may drive an implement in the form of an edging blade.

(4) An implement may be configured to be detachable from a host power tool. For example, detachable implements may be utilized to accommodate selection of an implement configuration for a particular task (e.g., selectively installing a grass cutting blade configured for mulching or clipping collection, etc.) and/or to facilitate replacing or repairing a damaged implement (e.g., removal and reinstalling a grass cutting blade after sharpening its previously dulled edges or replacing a dull grass cutting blade with a sharp grass cutting blade, etc.).

(5) Typically, one or more tools are required for changing (e.g., removing and/or installing) a detachable implement. For example, a hand tool in the form of a wrench (e.g., open-end wrench, socket wrench, or adjustable wrench) in the appropriate size for engaging a fastener (e.g., locking nut assembly, such as a reusable nut and lock washer, single use nyloc nut, etc.) affixing the implement to a shaft assembly (e.g., spindle) of the power tool is needed for changing a detachable implement. Additionally, a hand tool in the form of a brace or second wrench is often needed to prevent movement of the shaft and implement when tightening or loosening the fastener affixing the implement to a shaft assembly of the power tool for changing the detachable implement. As an alternative to a second hand tool, some implementations have used a pin which may be manually pushed inside an aligned hole in order to lock the spindle of the power tool. As another alternative to a second hand tool, such as may be implemented with respect to a power tool that does not provide for reverse rotation operation, a shaft bearing of the power tool may be replaced by a one-way bearing that serves as spindle lock.

(6) In many situations, the fastener affixing the implement to the power tool is seated with appreciable torque (e.g., intentionally, such as to prevent unwanted relative displacement of the implement due to driving forces and/or impacts during use, or unintentionally, such as resulting from inertial tightening in association with application of driving forces). Accordingly, a wrench used for changing a detachable implement must be of sufficient length and durability to accommodate facilitate application of significant forces on a nut fastening the implement on the garden machine, such as when unfastening the implement.

(7) It is often difficult or impractical to store hand tools appropriate for changing a detachable implement on or with the power tool. For example, even where the size and bulk of such hand tools may be provided some form of storage space on a power tool, the often rugged use, presence of appreciable vibrations, etc. can cause the hand tools to migrate from their storage space and be lost. Further, power tools having detachable implements are often operated in areas away from repair facilities or places in which it is convenient or customary to store tools appropriate to changing detachable implements. For example, a lawn mower, string trimmer, or grass edger may be operated in a home environment in which the owner has a very limited selection of tools, and thus appropriately sized hand tools for changing a detachable implement may not be available to the operator. In another example, a lawn mower or brush cutter may be operated in a field or other large parcel of land relatively far from a supply of tools and, although a replacement cutting blade

may be carried by the operator, sufficient tools for changing the cutting blade may not be available. (8) Manipulation of a fastener by hand (e.g., without aid of separate tools) to remove and replace a detachable implement is often not possible due to the forces required. For example, as described above, the fastener may have been seated with appreciable torque whereby a typical user may not be able to apply sufficient counter torque (e.g., on the order of 12 Nm) to facilitate loosening the fastener. Similarly, a typical user may be unable to apply sufficient torque to a fastener by hand to seat the fastener sufficiently to prevent unwanted relative displacement of the implement during use due to driving forces.

(9) Various special configurations of detachable implements have been proposed to prevent unwanted relative displacement of the implement during use even in situations where a fastener is applied by hand without significant torque. For example, the blade carrier of EP 2 798 937 B1 (the disclosure of which is incorporated herein by reference) includes two pins which protrude into corresponding openings in the blade for providing a rotationally fixed connection with the blade. Such specially configured detachable implements generally do not provide a backward compatible solution. Moreover, the lack of sufficient torque when the fastening device is applied by hand to attach the specially configured blade to the lawn mower may not result in a frictional interface between the fastening device and the blade to prevent the fastening device from rotating in a releasing direction and disengaging from the lawn mower. Accordingly, a latch for the fastening device is proposed by EP 2 798 937 B1. The proposed latch provides for manually operated latching elements, wherein two levers are pivotably mounted on the blade carrier and are used to release the fastening device. The configuration of the latching elements and levers on the blade carrier is such that these components are exposed to objects encountered by the lawn mower and/or objects propelled by impacting the rotating blade. For example, the design of the fastening device exposes the components to dirt build up on surfaces and clearances of moving parts creating large friction between relative movement of the parts, such as may lead to larger actuating force needed and even loss of intended function. The design of the fastening device likewise exposes the components to various objects (e.g., rocks, gravel, sticks from trees, etc.) which may strike components of the fastening device with considerable force. Accordingly, the latch may be subject to damage and even functional failure, such as may result in the latch no longer being capable of manipulation by hand and/or the latch being unintentionally released allowing the fastening device to become detached from the lawn mower.

(10) Special configurations of quick-connect detachable implements have also been attempted. However, such detachable implements and/or their quick-connect apparatus suffer from a number of drawbacks. For example, quick-connect detachable implements often utilize a special arbor or shape design for torque transmission instead of frictional flange and nut design commonly used, and thus do not provide a backward compatible solution. Moreover, many power tools, such as lawn mowers and brush trimmers, have high demands with respect to a detachable implement (e.g., blades) withstanding shock forces from striking other objects, which often cannot be met by quick-connect detachable implement solutions.

(11) It can be appreciated from the foregoing that existing solutions often are inadequate to facilitate convenient changing of detachable implements utilized with respect to various power tools. For example, it is often inconvenient and sometimes even impossible to change a detachable implement despite the implement having been configured for detachment and reattachment. Even where it is possible to change a detachable implement, it is often inconvenient to do so (e.g., separate tools must be kept up with, force sufficient to cause pain or discomfort to a user's hand must be applied, etc.).

BRIEF SUMMARY OF THE INVENTION

(12) The present invention is directed to systems and methods which provide force amplified fastener assemblies configured for use with respect to detachable implements for power tools. Force amplified fastener assemblies of embodiments of the invention may implement a gear train

configured for giving a mechanical advantage with respect to manual manipulation (e.g., grasping by hand to manually apply tightening or loosening torque) of the fastener assembly. Various force amplifying gear train configurations may, for example, be utilized with respect to a force amplified fastener assembly according to concepts of the present invention to provide a requisite mechanical advantage.

(13) In accordance with embodiments of the invention, a force amplified fastener assembly may comprise planetary gearing disposed within a hand graspable housing to give mechanical advantage with respect to manual fastener tightening and/or loosening forces. Additionally or alternatively, a force amplified fastener assembly of embodiments may comprise cycloidal gearing disposed within a hand graspable housing to give mechanical advantage with respect to manual fastener tightening and/or loosening forces.

(14) Force amplified fastener assemblies of embodiments of the invention may be utilized in place of a conventional lock nut for affixing detachable implements to power tools. For example, force amplified fastener assemblies of embodiments may be used for fixing a blade assembly to a host garden machine (e.g., a lawn mower, a brush cutter, a grass edger, etc.). It should be appreciated, however, that force amplified fastener assemblies provided according to concepts herein may be utilized in a variety of applications and with various host power tool configurations, such as with garden machines which do not have blade implements (e.g., string trimmers) and/or other forms of power tools (e.g., carpentry saws). Irrespective of the particular power tool configuration with which a force amplified fastener assembly is used, the force amplified fastener assembly of embodiments facilitates a user manually, by bare hand, applying force for loosening (e.g., releasing direction) and/or tightening (e.g., fastening direction) the fastener (e.g., for changing a detachable implement). For example, when used in a lawnmower, a force amplified fastener assembly may be operated directly by hand (e.g., tool-free) to achieve cutting blade installation, removal, replacement, and/or the like. Accordingly, a force amplified fastener assembly of embodiments of the invention may provide a tool-free implement change mechanism, whereby changing (e.g., installation, removal, replacement, etc.) of detachable implements with respect to a host power tool is facilitated without aid of separate tools.

(15) Force amplified fastener assemblies of embodiments of the invention may include a lock mechanism operative to lock and/or unlock the force amplified fastener assembly and thus a fastening element thereof. In operation according to embodiments, the fastening element (e.g., a nut or other threaded fastening device) can be rotated in a fastening direction by the force amplified fastener assembly so as to fix, mount, tighten, etc. a blade or other detachable implement onto a motor shaft, wherein this rotation is reversible. That is, the fastening element can be rotated in a releasing direction opposite to the fastening direction so as to loosen, release, etc. the blade or other detachable implement from the motor shaft. A lock mechanism of embodiments may lock the force amplified fastener assembly so that the fastening assembly is not released unwantedly or unintentionally.

(16) A lock mechanism of embodiments of a force amplified fastener assembly may rely upon user action to unlock and/or lock the lock mechanism. For example, a user may squeeze one or more members of a lock mechanism to unlock operation of the locking mechanism for rotation of a force amplified fastener in a releasing direction, otherwise the force amplified fastener assembly may be rotated only in the fastening direction. Additionally or alternatively, a lock mechanism of embodiments may be locked and/or unlocked in response to one or more forces other than from user unlocking/locking action. For example, a lock mechanism of some embodiments may be locked and/or unlocked by centrifugal force (e.g., locked to prevent rotation in the releasing direction while the detachable implement is spinning) or by the force of gravity when the power tool is disposed in a particular orientation (e.g., unlocked when a head of the power tool upon which a detachable implement is fastened is turned upside down for user service). In accordance with some examples, rotation of the detachable implement and corresponding force amplified

fastener assembly at a certain speed provides sufficient centrifugal force to encourage pawls of a lock mechanism in the force amplified fastener assembly to engage and lock the fastening element (e.g., nut) to discourage rotation of the force amplified fastener assembly and the fastening element therein in the releasing direction. In accordance with this example, when the power tool is stopped, a bias spring may pull the locking pawl into a disengaged position so user can rotate the force amplified fastener assembly and the fastening element therein in the fastening and/or releasing direction. In accordance with another example, when the force amplified fastener assembly faces to the ground (e.g., the host power tool is in a use orientation), a lock pawl of a lock mechanism thereof is engaged by gravity, whereas when the force amplified fastener assembly faces upward (e.g., the host power tool is in a service orientation) the locking pawl of the lock mechanism is released.

(17) The foregoing has outlined rather broadly the features and technical advantages of the present invention in order that the detailed description of the invention that follows may be better understood. Additional features and advantages of the invention will be described hereinafter which form the subject of the claims of the invention. It should be appreciated by those skilled in the art that the conception and specific embodiment disclosed may be readily utilized as a basis for modifying or designing other structures for carrying out the same purposes of the present invention. It should also be realized by those skilled in the art that such equivalent constructions do not depart from the spirit and scope of the invention as set forth in the appended claims. The novel features which are believed to be characteristic of the invention, both as to its organization and method of operation, together with further objects and advantages will be better understood from the following description when considered in connection with the accompanying figures. It is to be expressly understood, however, that each of the figures is provided for the purpose of illustration and description only and is not intended as a definition of the limits of the present invention.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) For a more complete understanding of the present invention, reference is now made to the following descriptions taken in conjunction with the accompanying drawing, in which:
- (2) FIG. 1 shows a portion of a power tool for which a force amplified fastener assembly is provided according to embodiments of the present invention;
- (3) FIGS. 2A-2E show various views of a force amplified fastener assembly implementing an exemplary planetary gear train according to embodiments of the present invention;
- (4) FIGS. 3A-3E show various views of a force amplified fastener assembly implementing an exemplary cycloid gear train according to embodiments of the present invention;
- (5) FIGS. 4A-7B show details of exemplary lock mechanisms for force amplified fastener assemblies according to embodiments of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

(6) FIG. 1 shows a portion of a power tool configured to utilized detachable implements, wherein a force amplified fastener assembly of embodiments of the present invention is provided to facilitate changing (e.g., installation, removal, replacement, and/or the like) of the detachable implements. Power tool **100** may comprise various configurations of motorized tools configured for performing one or more tasks using corresponding configurations of detachable implement **120**. By way of example, power tool **100** of some embodiments may comprise a garden machine in the form of a lawn mower or brush cutter and detachable implement **120** may comprise a cutting blade (e.g., low lift/side-discharge blade, mulching blade, dethatching blade, brush blade, etc.). In accordance with other embodiments, power tool **100** and detachable implement **120** may comprise configurations of a string trimmer and string spool head, leaf blower, cultivator, hedge trimmer blade, and/or brush

cutter attachments, a grass edger and edging blade, a carpentry saw and crosscut blade, rip saw blade, and/or dado blade, etc.

(7) In the example of FIG. 1, power tool **100** comprises motor assembly **110** driving detachable implement **120**. Motor assembly **110** of embodiments may comprise various motor configurations. For example, motor assembly **110** of some embodiments may comprise an electric motor, such as a direct current (DC) motor (e.g., brushed motor, brushless motor, etc.) or alternating current (AC) motor (e.g., induction motor, synchronous motor, etc.), powered by batteries, main lines, solar collector, generator, etc. In accordance with some embodiments, motor assembly **110** may comprise an internal combustion motor, such as a gasoline engine or diesel engine, powered by a combustible fuel source.

(8) As shown in the example of FIG. 1, a shaft assembly of motor assembly **110** is utilized to drive detachable implement **120** in operation of power tool **100**. Accordingly, in the example of FIG. 1, detachable implement **120** is coupled to a first end of shaft **111** shown passing through the main body of motor assembly **110**. It should be appreciated that, although not shown in FIG. 1, the shaft assembly may comprise structure in addition to shaft **111**. For example, a shaft assembly of motor assembly **110** may include a mounting or backer plate affixed to shaft **111** for interfacing with detachable implement **120**. For example, a mounting or backer plate may be provided to serve as a means by which relative axial motion between the detachable implement and shaft assembly may be prevented or discouraged (e.g., a mounting or backer plate may be configured to provide a clamp-fit interface providing a friction interface using clamping force and/or a form-fit interface providing an interference interface using structures that receive or project into the implement to prevent the relative axial motion). As another example, shaft assembly of motor assembly **110** may include drive gearing and/or a transmission (e.g., providing speed and/or direction control, increased/decreased rotational speed and/or torque, etc.). Accordingly, although the example shown in FIG. 1 shows motor assembly **110** directly driving detachable implement **120**, a gear train may be utilized between an output shaft of motor assembly **110** and detachable implement **120** according to embodiments. Irrespective of the particular structure of the shaft assembly of motor assembly **110**, detachable implement **120** is removably coupled (e.g., directly or indirectly) to shaft **111** for receiving power from motor assembly **110** in operation of power tool **100**.

(9) Force amplified fastener assembly **130** of embodiments of the invention is shown in the example of power tool **100** fastening detachable implement **120** to shaft **111** of motor assembly **110**. Force amplified fastener assembly **130** may, for example, be utilized in place of a conventional lock nut (e.g., retrofitting a conventional lock nut in some cases or as an original fastener means in other cases) for affixing detachable implement **120** to power tool **100**. In accordance with embodiments of the invention, force amplified fastener assembly **130** facilitates a user manually (e.g., by bare hand) applying force for loosening (e.g., releasing direction) and/or tightening (e.g., fastening direction) force amplified fastener assembly **130** for changing detachable implement **120**.

(10) By way of a concrete example for aiding in understanding concepts of the present invention, force amplified fastener assembly **130** of FIG. 1 may be used to replace a blade for a brush cutter or mower (e.g., brush cutter or mower configuration of power tool **100** implementing a blade configuration of detachable implement **120**). Manual actuation of force amplified fastener assembly **130** can loosen the fastener assembly and allow for its removal from shaft **111**, thereby loosening the blade and facilitating its removal from the brush cutter or mower. When a new blade is to be affixed onto the motor shaft, actuation of force amplified fastener assembly **130** may tighten the fastener assembly on shaft **111** to thereby affixing the blade on the brush cutter or mower.

(11) Force amplified fastener assembly **130** of embodiments of the invention implements a force amplifying gear train configured for giving a mechanical advantage with respect to manual manipulation of the fastener assembly. In operation of a force amplifying gear train of force amplified fastener assembly **130**, a force applied by a user (e.g., torque applied in a fastening direction and/or torque applied in a releasing direction) to force amplified fastener assembly **130**

(e.g., by grasping a housing of the fastener assembly by hand to manually apply tightening or loosening torque) is increased with respect to its transmission to a fastening element of the fastener assembly. As such, a user may be enabled to apply appreciably more force with respect to rotation of fastening element than would otherwise be possible by the user directly engaging the fastening element.

(12) Various force amplifying gear train configurations may be utilized with respect to force amplified fastener assembly **130** of embodiments to provide a requisite mechanical advantage. According to some embodiments of the invention, force amplified fastener assembly **130** may comprise planetary gearing disposed within a hand graspable housing to give mechanical advantage with respect to manual fastener tightening and/or loosening forces. Additionally or alternatively, force amplified fastener assembly **130** of embodiments may comprise cycloidal gearing disposed within a hand graspable housing to give mechanical advantage with respect to manual fastener tightening and/or loosening forces. The mechanical advantage provided by such force amplifying gear train configurations of embodiments may, for example, provide force amplification on the order of 3-15 times between a manual force applied to a housing of the fastener assembly and a corresponding force applied with respect to a fastening element of the fastener assembly. The force applied to the fastening element as increased by force amplified fastener assembly **130** of embodiments is thus sufficient to overcome static forces of a fastener element seated with appreciable torque (e.g., intentionally, such as to prevent unwanted relative displacement of the detachable implement due to driving forces and/or impacts during use, or unintentionally, such as resulting from inertial tightening in association with application of driving forces). Moreover, force amplifying gear train configurations of embodiments of the invention facilitate implementations of reliable lock mechanisms.

(13) In accordance with embodiments of the invention, force amplified fastener assembly **130** may be manually engaged by a user to fasten and/or unfasten detachable implement **120** from power tool **100** without aid of separate tools. Accordingly, force amplified fastener assembly **130** of embodiments may provide a tool-free implement change configuration.

(14) Embodiments of power tool **100** may be configured for facilitating changing of detachable implement **120** using force amplified fastener assembly **130** without aid of separate tools. For example, power tool **100** may include motor shaft locking apparatus **140** operative cooperatively with force amplified fastener assembly **130** to facilitate changing of detachable implement **120** with respect to power tool **100**. In accordance with some examples, motor shaft locking apparatus **140** may be engaged without aid of separate tools to prevent movement of shaft **111** when affixing detachable implement **120** to shaft **111** and/or removing detachable implement **120** from shaft **111**. For example, motor shaft locking apparatus **140** may comprise a pin which may be pushed inside an aligned hole in order to lock shaft **111** of power tool **100**. According to another example, motor shaft locking apparatus **140** may comprise a one-way bearing that serves as reverse rotational lock with respect to shaft **111**. In accordance with yet another example, motor shaft locking apparatus **140** may comprise a locker collar configuration in which a locking collar includes a wide slot section and a narrow slot section configured for selectively allowing and discouraging rotation of shaft **111**. For example, in operation of a locker collar of some examples, when shaft **111** is within the wide slot section, shaft **111** and the locking collar do not interface and shaft **111** is free to rotate. However, when the locker collar is slid laterally with respect to shaft **111**, shaft **111** is disposed within the narrow slot section such that shaft **111** and the locking collar interface to discourage shaft **111** from rotating (e.g., a portion of shaft **111** disposed in juxtaposition with the locking collar may be provided with a square cross-section configured to cooperate with the narrow slot section of locking collar to interface and discourage rotation of shaft **111** when motor shaft locking apparatus **140** is engaged).

(15) Irrespective of the particular configuration of motor shaft locking apparatus **140**, motor shaft locking apparatus **140** may be operable in cooperation with force amplified fastener **130** to

facilitate affixing detachable implement **120** to or removing detachable implement **120** from the motor shaft assembly of power tool **100** without the use of additional tools according to some embodiments of the invention. For example, an operator of power tool **100** may install and/or remove detachable implement **120** by engaging motor shaft locking apparatus **140** (e.g., through manual manipulation or automatic engagement) and loosening or tightening force amplified fastener assembly **130** through manual manipulation.

(16) It should be appreciated that embodiments of force amplified fastener assembly **130** herein may be utilized with or without further configuration of power tool **100** for facilitating changing of detachable implement **120**. For example, some embodiments of force amplified fastener assembly **130** may be utilized without cooperation of a motor shaft locking apparatus (e.g., an implementation of power tool **100** not having motor shaft locking apparatus **140**). In one example, a user may manually prevent detachable implement **120** from rotating (e.g., grasping a unsharpened portion, such as a handle portion, of a blade configuration of detachable implement **120** with one hand) while manually manipulating force amplified fastener assembly **130** in a fastening direction or releasing direction with another hand.

(17) FIGS. 2A-2E and 3A-3E show details with respect to various embodiments of force amplified fastener assembly **130**. In particular, FIGS. 2A-2E show details with respect to an embodiment of force amplified fastener assembly **130** implementing a planetary gear configuration for giving a mechanical advantage with respect to manual manipulation of the fastener assembly. Similarly, FIGS. 3A-3E show details with respect to an embodiment of force amplified fastener assembly **130** implementing a cycloid gear configuration for giving a mechanical advantage with respect to manual manipulation of the fastener assembly. Although planetary gear and cycloid gear configurations are shown in the illustrated examples, it should be appreciated that other forms of gear trains (e.g., double reduction gear configurations, reverted gear configurations, etc.) may be utilized in addition to or in the alternative to a planetary gear configuration and/or a cycloid gear configuration. Moreover, multiple types of gearing (e.g., a gear train configuration including a combination of planetary gearing and cycloid gearing) may be utilized in a gear train of some embodiments of force amplified fastener assembly **130**.

(18) Reference is first made to the exemplary embodiment of FIGS. 2A-2E in which a planetary gear configuration is implemented. FIGS. 2A and 2B show a planetary gear configuration of an embodiment of force amplified fastener assembly **130** in its assembled state. As shown in the top isometric view of FIG. 2A, the illustrated planetary gear configuration comprises top housing **210**. Correspondingly, as shown in the bottom isometric view of FIG. 2B, the illustrated planetary gear configuration comprises bottom structure **220**. It should be appreciated that, although the views, housings, and structures are referred to as top and bottom, the designations are relative and there is no limitation that the example force amplified fastener assembly be disposed or utilized in any particular orientation with respect to top and bottom. For example, when utilized with respect to a lawn mower implementation of power tool **100**, top housing **210** may be oriented as facing down when installed on shaft **111** and affixing detachable implement **120** in the form of a grass cutting blade to power tool **100**.

(19) Top housing **210** and bottom structure **220** are configured for cooperatively incarcerating a planetary gear train and fastening element of the example force amplified fastener assembly. For example, as may be seen in the partially exploded views of FIGS. 2C and 2D, bottom structure **220** may form a cupped structure sized and shaped to nest within a cupped casing formed by top housing **210**. In accordance with some examples, the top edge circumference of bottom structure **220** may, when fully nested with top housing **210**, terminate at or very near the bottom facing surface of top housing **210**, such as for incarcerating components of the planetary gear train and for providing a substantially enclosed area in which infiltration of debris and/or other matter is discouraged. The nested relationship of top housing **210** and bottom structure **220** of embodiments, however, allows for relative rotational movement between the top housing and bottom structure

(e.g., top housing **210** may be rotated while bottom structure **220** nested therein is held stationary). (20) In accordance with the exemplary embodiment, locking tabs **211a-211d** of top housing **210** may facilitate bottom structure **220** being slid into a cavity of the cupped casing formed by top housing **210**, whereby once bottom structure **220** is fully nested with top housing **210** the locking tabs retain the top housing and bottom structure in the nested relationship. For example, bottom structure **220** of the illustrated embodiment substantially encloses the gap between the bottom edge circumference of top housing **210** and the bottom edge circumference of bottom structure **220**, such as to facilitate locking tabs **211a-211d** of top housing **210** engaging bottom structure **220** for facilitate retaining the top housing and bottom structure in the nested relationship. Additionally or alternatively such a relationship with respect to the bottom edge circumference of top housing **210** and the bottom edge circumference of bottom structure **220** may be configured to prevent infiltration of debris and/or other matter into the area enclosed by the top housing and bottom structure.

(21) Top housing **210** of embodiments may be configured to facilitate manual manipulation by a user. For example, top housing **210** may be sized and shaped to facilitate grasping by hand so that a user may manually apply torque forces (e.g., torque in fastening and/or releasing directions) to force amplified fastener assembly **130**. Additionally or alternatively, top housing **210** may comprise surface features (e.g., rib structure, surface perturbations, rubberized over-molding, etc.) for facilitating gripping and application of force. The illustrated embodiment of top housing **210**, for example, includes rib structures **213a-213d** disposed about the circumference of the top housing, such as may be utilized to enable and/or enhance a user's grip upon force amplified fastener assembly **130**.

(22) Bottom structure **220** of the illustrated embodiment is configured to accept insertion of drive member of a power tool, such as shaft **111** of power tool **100**, for facilitating interfacing the drive member with a fastening element of force amplified fastener assembly **130**. For example, shaft orifice **221** of the illustrated embodiment of bottom structure **220** may be sized and shaped to accommodate insertion of an end of shaft **111** there through. According to some examples, shaft orifice **221** may be shaped or otherwise be configured (e.g., comprising the undulated circumference of the illustrated embodiment, a square circumference, a hexagonal circumference, etc.) for interfacing with one or more components external to force amplifying fastener assembly **130** (e.g., stay **121** of FIG. 1, as may be disposed upon shaft **111**), such as for discouraging or preventing relative rotary movement (e.g., for avoiding unintended unfastening the fastening element as a result of inertial force when the power tool stops or is braked).

(23) Force amplified fastener assembly **130** of the embodiment of FIGS. 2A-2E implements a planetary gear train configured for giving a mechanical advantage with respect to applying tightening or loosening torque to fastening element **230** in response to manual manipulation (e.g., grasping by hand to manually apply torque in a fastening direction or releasing direction) of the fastener assembly. Accordingly, as shown in FIG. 2C, top housing **210** of the example embodiment includes sun gear **212** of the planetary gear train in the illustrated planetary gear configuration of force amplified fastener assembly **130**. As shown in FIG. 2D, bottom structure **220** includes ring gear **222** of the exemplary planetary gear train. Planet gear assembly **240**, visible in the further exploded view of FIG. 2E (having some components of the exemplary embodiment of force amplified fastener assembly **130** omitted), comprises planet gears **242a-242c** which interface between sun gear **212** and ring gear **222** to provide a planetary gearing implementation. In particular, planet gear assembly **240** of the illustrated embodiment is received within a cavity of the cupped structure formed by bottom structure **220**, whereby once bottom structure **220** is fully nested with top housing **210** planet gears **242a-242c** are incarcerated within an interior area of the top housing and bottom structure and provide a geared interface between sun gear **212** and ring gear **222**.

(24) In accordance with embodiments, sun gear **212** is affixed to or formed as part of top housing

210 and ring gear **222** is affixed to or formed as part of bottom structure **220**. Accordingly, when top housing **210** is rotated (e.g., in response to a user manually applying a torque force thereto), sun gear **212** of embodiments will correspondingly be rotated. Similarly, ring gear **222** rotates or does not rotate in correspondence with bottom structure **220**. The incarcerated relationship of planet gear assembly **240** within the interior area of bottom structure **220** nested within top housing **210** allows for relative rotational movement of gear plate **241** with respect to the top housing and bottom structure. For example, top housing **210** may be rotated with bottom structure **220** nested therein held stationary and gear plate **241** may rotate at a different speed than top housing **210**. That is, rotation of top housing **210** and thus sun gear **212** meshed with planet gears **242a-242c** causes the planet gears to rotate oppositely, whereby planet gears **242a-242c** meshed with ring gear **222** held stationary by bottom structure **220** results in gear plate **241** rotating in the direction of top housing **210**/sun gear **212**, albeit at a reduced rotational rate and having a higher torque force.

(25) Planet gear assembly **240** includes fastening element housing **243** configured for accepting fastening element **230** in coaxial correspondence with shaft orifice **221**. Accordingly, fastening element housing **243** of the illustrated embodiment includes shaft orifice **244** sized and shaped to accommodate insertion of an end of shaft **111** there through, whereby a fastening element disposed within receiver cavity **245** of fastening element housing **243** may interface with shaft **111**. The illustrated embodiment of fastening element housing **243** is sized and shaped to extend into and nest within an inner circumference of sun gear **212** when planet gear assembly **240** is incarcerated within the nested top housing and bottom structure. Accordingly, fastening element **230** disposed in receiver cavity **245** may be captured in a space between fastening element housing **243** and top housing **210** of embodiments of the invention.

(26) Fastening element housing **243** may be affixed to or formed as part of gear plate **241** of the illustrated embodiment. Accordingly, when gear plate **241** rotates, fastening element housing **243** of embodiments will correspondingly be rotated. Receiver cavity **245** of embodiments is configured to encourage fastening element **230** to rotate in correspondence with gear plate **241**. Fastening element **230** of embodiments may comprise a nut or other threaded fastening device configured to be rotated in a fastening direction and a releasing direction upon a power member. For example, the illustrated embodiment of fastening element **230** comprises a nut appropriately threaded to engage an end of shaft **111** of power tool **100**, such as may be utilized to fix, mount, tighten, etc. detachable implement **120** onto shaft **111**. Accordingly, receiver cavity **245** of fastening element housing **243** of the illustrated embodiment is shaped to receive fastening element **230** and to provide control of movement thereof relative to shaft **111**. For example, the illustrated embodiment of receiver cavity **245** comprises a hexagon circumference corresponding to the shape of the example nut implementation of fastening element **230**.

(27) Although fastening element **230** of the example illustrated in FIGS. 2A-2E is described as disposed in receiver cavity **245** of fastening element housing **243** on gear plate **241**, it should be appreciated that other configurations of fastening elements may be utilized according to embodiments of the invention. For example, rather than a separate component (e.g., nut) providing fastening element **230**, some embodiments of fastening element **230** may be formed integral to another component of force amplified fastener assembly **130**. As a specific example, fastening element **230** may be formed as suitably threaded portion of shaft orifice **244** sized and shaped to correspond to the size and shape of the end of shaft **111**.

(28) In operation of force amplified fastener assembly **130** of the embodiment of FIGS. 2A-2E, when shaft **111** is inserted through orifices **221** and **244** and interfaces with fastener element **230**, top housing **210** may be grasped by the hand of a user and rotated in a fastening direction or a releasing direction to correspondingly rotate fastener element **230** relative to shaft **111**. Sun gear **212**, planet gears **242a-242c**, and ring gear **222** of the planetary gear train provide a mechanical advantage with respect to applying tightening or loosening torque to fastening element **230**. That is, a mechanical advantage corresponding to the size relationship between sun gear **212** and planet

gears **242a-242c** (e.g., on the order of 3-5 times) may be implemented between the torque manually applied to top housing **210** and the resultant torque applied to fastener element **230**.

(29) Having described an embodiment of force amplified fastener assembly **130** implementing a planetary gear train, reference is now made to the exemplary embodiment of FIGS. **3A-3E** in which a cycloid gear configuration is implemented. FIGS. **3A** and **3B** show a cycloid gear configuration of an embodiment of force amplified fastener assembly **130** in its assembled state. As shown in the top isometric view of FIG. **3A**, the illustrated cycloid gear configuration comprises top housing **310**. Correspondingly, as shown in the bottom isometric view of FIG. **3B**, the illustrated cycloid gear configuration comprises bottom structure **320**. It should be appreciated that, although the views, housings, and structures are referred to as top and bottom, the designations are relative and there is no limitation that the example force amplified fastener assembly be disposed or utilized in any particular orientation with respect to top and bottom. For example, when utilized with respect to a lawn mower implementation of power tool **100**, top housing **310** may be oriented as facing down when installed on shaft **111** and affixing detachable implement **120** in the form of a grass cutting blade to power tool **100**.

(30) Top housing **310** and bottom structure **320** are configured for cooperatively incarcerating a cycloid gear train and fastening element of the example force amplified fastener assembly. For example, as may be seen in the partially exploded views of FIGS. **3C-3E**, bottom structure **320** may form a cupped structure sized and shaped to nest within a cupped casing formed by top housing **310**. In accordance with some examples, the top edge circumference of bottom structure **320** may, when fully nested with top housing **310**, terminate at or very near the bottom facing surface of top housing **310**, such as for incarcerating components of the cycloid gear train and for providing a substantially enclosed area in which infiltration of debris and/or other matter is discouraged. The nested relationship of top housing **310** and bottom structure **320** of embodiments allows for relative rotational movement between the top and bottom structures (e.g., top housing **310** may be rotated while bottom structure **320** nested therein is held stationary).

(31) As can be seen in FIGS. **3A-3E**, the example cycloid gear configuration of force amplified fastener assembly **130** comprises bottom housing **301** configured to enclose components of the gear train and/or a lock mechanism used therewith within the cupped structure of top housing **310**. Bottom housing **301** of the illustrated example comprises a substantially planar bottom housing that may be affixed by various fastening means (e.g., screws, adhesive, welding, locking tabs, etc.) to top housing **310** to enclose some or all of the area within the concavity of the top housing cupped structure. Bottom structure **320** may, for example, be incarcerated by bottom housing **301** whereby at least a portion of bottom structure **320** is disposed within the concavity of the top housing cupped structure. In accordance with embodiments of the invention, bottom structure **320** is free to rotate axially with respect to top housing **310** and bottom housing **301** affixed to top housing **310**.

(32) In the illustrated example, bottom structure **320** is sized so as to provide clearance with respect to components of an embodiment of a lock mechanism (described in detail below). The configuration of bottom housing **301** may provide a skirting flange and/or other structure to substantially enclose the gap between the bottom edge circumference of top housing **310** and the bottom edge circumference of bottom structure **320**, such as to prevent infiltration of debris and/or other matter into the area of the lock mechanism and/or to facilitate retaining the top housing and bottom structure in the nested relationship.

(33) Top housing **310** of embodiments may be configured to facilitate manual manipulation by a user. For example, top housing **310** may be sized and shaped to facilitate grasping by hand so that a user may manually apply torque forces (e.g., torque in fastening and/or releasing directions) to force amplified fastener assembly **130**. Additionally or alternatively, top housing **310** may comprise surface features (e.g., rib structure, surface perturbations, rubberized over-molding, etc.) for facilitating gripping and application of force. The illustrated embodiment of top housing **310**, for example, includes rib structures **313a-313h** disposed about the circumference of the top housing,

such as may be utilized to enable and/or enhance a user's grip upon force amplified fastener assembly **130**.

(34) Bottom structure **320** of the illustrated embodiment is configured to accept insertion of drive member of a power tool, such as shaft **111** of power tool **100**, for facilitating interfacing the drive member with a fastening element of force amplified fastener assembly **130**. For example, shaft orifice **321** of the illustrated embodiment of bottom structure **320** may be sized and shaped to accommodate insertion of an end of shaft **111** there through. According to some examples, shaft orifice **321** may be shaped or otherwise be configured (e.g., comprising the undulated circumference of the illustrated embodiment, a square circumference, a hexagonal circumference, etc.) for interfacing with one or more components external to force amplifying fastener assembly **130** (e.g., stay **121** of FIG. 1, as may be disposed upon shaft **111**), such as for discouraging or preventing relative rotary movement (e.g., for avoiding unintended unfastening the fastening element as a result of inertial force when the power tool stops or is braked).

(35) Force amplified fastener assembly **130** of the embodiment of FIGS. 3A-3E implements a cycloid gear train configured for giving a mechanical advantage with respect to applying tightening or loosening torque to fastening element **330** in response to manual manipulation (e.g., grasping by hand to manually apply torque in a fastening direction or releasing direction) of the fastener assembly. Accordingly, as shown in FIG. 3C, top housing **310** of the example embodiment includes eccentric receiver **312** configured for providing eccentric rotation of shaft **346** of the cycloid gear train in the illustrated cycloid gear configuration of force amplified fastener assembly **130**.

Eccentric receiver **312** of embodiments is disposed slightly off-center within the bottom facing surface of top housing **310**, whereby as top housing **310** is rotated eccentric receiver **312** rotates about or orbits a central point of the bottom facing surface. As shown in FIG. 3D, bottom structure **320** includes ring gear **322** of the exemplary cycloid gear train. Cycloid gear assembly **340**, visible in the further exploded view of FIG. 3E (having some components of the exemplary embodiment of force amplified fastener assembly **130** omitted), interfaces between eccentric receiver **312** and ring gear **322** to provide a cycloid gearing implementation. Cycloid gear assembly **340** of the illustrated embodiments comprises cycloidal disk **341** and roller pins **342a-342f** disposed on pin plate **343**, wherein roller pins **342a-342f** are inserted in corresponding ones of orifices **344a-344f** of cycloidal disk **341** when cycloid gear assembly **340** is assembled. Shaft **346** of cycloidal disk **341** interfaces with eccentric receiver **312** via bearing **345** of the illustrated embodiment. Cycloid gear assembly **340** of the illustrated embodiment is received within a cavity of the cupped structure formed by bottom structure **320**, whereby once bottom structure **320** is fully nested with top housing **310** cycloid gear assembly **340** is incarcerated within an interior area of the top and bottom structures and provide an interface between eccentric receiver **312** and ring gear **322**.

(36) In accordance with embodiments, eccentric receiver **312** is formed as part of or otherwise affixed to top housing **310** and ring gear **322** is affixed to or formed as part of bottom structure **320**. Accordingly, when top housing **310** is rotated (e.g., in response to a user manually applying a torque force thereto), eccentric receiver **312** of embodiments will correspondingly be rotated eccentrically (e.g., rotating about a center point of the bottom surface of top housing **310**), correspondingly eccentrically rotating cycloid gear assembly **340** via shaft **346**. Similarly, ring gear **322** rotates or does not rotate in correspondence with bottom structure **320**. The incarcerated relationship of cycloid gear assembly **340** within the interior area of bottom structure **320** nested within top housing **310** allows for relative rotational movement of pin plate **343** with respect to the top housing and bottom structure. For example, top housing **310** may be rotated with bottom structure **320** nested therein held stationary and pin plate **343** may rotate at a different speed than top housing **310**. That is, rotation of top housing **310** and thus eccentric receiver **312** interfaced with cycloidal disk **341** causes the cycloidal disk to rotate correspondingly in an eccentric motion, whereby cycloidal disk **341** meshed with the lobes of ring gear **322** held stationary by bottom structure **320** engages roller pins **342a-342f** via orifices **344a-344f** to transfer rotational force to pin

plate **343**, albeit at a reduced rotational rate and having a higher torque force.

(37) Cycloid gear assembly **340** includes fastening element **330** disposed in coaxial correspondence with shaft orifice **321**. For example, the illustrated embodiment of fastening element **330** comprises a portion of an orifice in pin plate **343** that is sized and shaped to correspond to the size and shape of an end of shaft **111** of power tool **100** and is appropriately threaded to engage the end of shaft **111**, such as may be utilized to fix, mount, tighten, etc. detachable implement **120** onto shaft **111**. Accordingly, fastening element **330** of the illustrated embodiment comprises a threaded fastening device formed integral to another component of force amplified fastener assembly **130** and is configured to be rotated in a fastening direction and a releasing direction upon a power member.

(38) Although fastening element **330** of the example illustrated in FIGS. **3A-3E** is described as being formed integral to pin plate **343**, it should be appreciated that other configurations of fastening elements may be utilized according to embodiments of the invention. For example, rather than a portion of another component being configured to provide fastening element **330**, some embodiments of fastening element **330** may comprise a separate component (e.g., nut). For example, a fastening element housing may be affixed to or formed as part of pin plate **343** and may have a shaft orifice sized and shaped to accommodate insertion of an end of shaft **111** there through, whereby a fastening element may be disposed within a receiver cavity of the fastening element housing.

(39) In operation of force amplified fastener assembly **130** of the embodiment of FIGS. **3A-3E**, when shaft **111** is inserted through orifice **321** and interfaces with fastener element **330**, top housing **310** may be grasped by the hand of a user and rotated in a fastening direction or a releasing direction to correspondingly rotate fastener element **330** relative to shaft **111**. Eccentric receiver **312**, cycloidal disk **341**, ring gear **322**, and roller pins **342a-342f** of the cycloid gear train provide a mechanical advantage with respect to applying tightening or loosening torque to fastening element **330**. That is, a mechanical advantage corresponding to the relationship between the number of lobes on the cycloidal disk and the ring gear (e.g., on the order of 3-15 times) may be implemented between the torque manually applied to top housing **310** and the resultant torque applied to fastener element **330**.

(40) As can be appreciated from the foregoing, force amplified fastener assembly **130** is configured according to embodiments of the invention to provide appreciable mechanical advantage with respect to rotating a fastening element through implementation of a force amplifying gear train configuration. In accordance with aspects of the invention, a user may be enabled to manually apply tightening or loosening torque by hand sufficient to impart a friction interface between force amplified fastener assembly **130** and a corresponding detachable implement so as to prevent unwanted relative displacement of the detachable implement during use of the power tool, to overcome increased frictional interfacing resulting from inertial tightening of the amplified fastener assembly during use of the power tool, and/or to prevent unwanted loosening or separation of the force amplified fastener assembly during use of the power tool. For example, force amplified fastener assembly **130** of embodiments may facilitate tightening a fastening element thereof sufficiently by hand to retain a detachable implement upon a reversible power tool such that relative motion of the detachable implement is held to below 150 in either direction upon application of torque applied to the detachable implement by operation of the power tool.

(41) Force amplified fastener assembly **130** of some embodiments of the invention may include a lock mechanism operative to lock and/or unlock the force amplified fastener assembly and thus a fastening element thereof. For example, a lock mechanism of embodiments may be used in addition to or in the alternative to the above mentioned friction interface between force amplified fastener assembly **130** and detachable implement **120** to prevent unwanted relative displacement of the detachable implement. Accordingly, in operation according to some examples, a lock mechanism may be utilized to lock force amplified fastener assembly **130** so that the fastening assembly is not released unwantedly or unintentionally. For example, a locking mechanism of embodiments of the

invention may provide locking with respect to movement of a top housing relative to a bottom structure of a force amplified fastener assembly, whereby undesired rotation of a fastening element in a fastening direction and/or a releasing direction may be prevented. Such embodiments of a locking mechanism may thus act indirectly upon the fastening element for preventing unwanted rotation in one or more directions. Additionally or alternatively, a lock mechanism of embodiments of the invention may act directly upon a fastening element, such as by directly interfacing with one or more surfaces thereof to prevent unwanted rotation in one or more directions.

(42) FIGS. 4A and 4B show details with respect to an exemplary lock mechanism implemented with respect to the planetary gear train configuration of the embodiment of FIGS. 2A-2E. Lock mechanism **400** of the example illustrated in FIGS. 4A and 4B includes lock elements **410a** and **410b** disposed in the underside of top housing **210**. Lock elements **410a** and **410b** are configured for engaging bottom structure **220** (FIG. 2D) and provide locking with respect to movement of top housing **210** relative to bottom structure **220** of force amplified fastener assembly **130**. For example, lock elements **410a** and **410b** of the illustrated embodiment include teeth **411a** and **411b**, respectively, configured for interfacing with the teeth of ring gear **222** (FIG. 2D) of bottom structure **220**. Lock elements **410a** and **410b** may, for example, be slidably coupled to the underside surface of top housing **210**, whereby when the lock elements are slid radially outward teeth **411a** and **411b** engage the teeth of ring gear **222** and prevent movement of top housing **210** relative to bottom structure **220**. Further, lock elements **410a** and **410b** may be slid radially inward to a point that teeth **411a** and **411b** clear the teeth of ring gear **222** and movement of top housing **210** relative to bottom structure **220** is permitted.

(43) Lock elements **410a** and **410b** of embodiments of lock mechanism **400** may utilize user action to unlock and/or lock the lock mechanism. Springs **401a** and **401b** may, for example, provide a bias force to hold lock elements **410a** and **410b**, respectively, in a radially outward position (e.g., lock mechanism **400** in a locked state). A user may apply a force (e.g., squeezing force) to a portion of lock elements **410a** and **410b** accessible via corresponding openings in top housing **210** to cause the lock elements to slide radially inward (e.g., lock mechanism **400** in an unlocked state) to disengage the lock mechanism. Alternatively, lock elements of lock mechanism **400** may be configured to move between locked and unlocked positions in response to one or more forces other than from user unlocking/locking action. For example, weighted pivot members may be provided with respect to lock elements **410a** and **410b**, whereby weights disposed at ends of the weighted pivot members may be acted on by centrifugal force to encourage lock elements **410a** and **410b** to move radially outward (e.g., placing lock mechanism **400** in a locked state) when power tool **100** is operating. Bias springs and/or gravity may be utilized to encourage the weighted pivot members to encourage lock elements **410a** and **410b** to move radially inward (e.g., placing lock mechanism **400** in an unlocked state) when power tool **100** is not operating or is disposed in a service orientation.

(44) In operation according to the illustrated embodiment of lock mechanism **400**, movement of top housing **210** relative to bottom structure **220** when lock mechanism **400** is in a locked state is prevented in both the fastening direction and the releasing direction. For example, teeth **411a** and **411b** are sized and shaped to correspond to the size and shape of the teeth of ring gear **222** to thereby provide a locking engagement (e.g., when lock elements **410a** and **410b** are in a radially outward position) which discourages rotation in either direction. Alternative embodiments may, however, provide different configurations of teeth **411a** and **411b**, such as to facilitate preventing movement of top housing **210** relative to bottom structure **220** in a first direction (e.g., releasing direction) when lock elements **410a** and **410b** are in a radially outward position while allowing movement of top housing **210** relative to bottom structure **220** in a second direction (e.g., fastening direction) when lock elements **410a** and **410b** are in a radially outward position. For example, teeth **411a** and **411b** may be provided in a saw-tooth type configuration, wherein a ramped side of the saw-teeth permits relative movement and a bulkhead side prevents relative movement such that movement of top housing **210** relative to bottom structure **220** is prevented in one direction (e.g.,

the releasing direction) but not the other (e.g., the fastening direction).

(45) FIGS. 5A and 5B show details with respect to another exemplary lock mechanism as may be implemented with respect to the planetary gear train configuration of the embodiment of FIGS. 2A-2E. Lock mechanism **500** of the example illustrated in FIGS. 5A and 5B includes lock elements **510a** and **510b** disposed in the underside of top housing **210**. Lock elements **510a** and **510b** are configured for engaging bottom structure **220** (FIG. 2D) and provide locking with respect to movement of top housing **210** relative to bottom structure **220** of force amplified fastener assembly **130**. For example, lock elements **510a** and **510b** of the illustrated embodiment include teeth **511a** and **511b**, respectively, configured for interfacing with the teeth of ring gear **222** (FIG. 2D) of bottom structure **220**. Lock elements **510a** and **510b** may, for example, be slidably coupled to the underside surface of top housing **210**, whereby when the lock elements are slid radially outward teeth **511a** and **511b** engage the teeth of ring gear **222** and prevent movement of top housing **210** relative to bottom structure **220**. Further, lock elements **510a** and **510b** may be slid radially inward to a point that teeth **511a** and **511b** clear the teeth of ring gear **222** and movement of top housing **210** relative to bottom structure **220** is permitted.

(46) Lock elements **510a** and **510b** of embodiments of lock mechanism **500** may move between locked and unlocked positions in response to various forces, such as centrifugal force and/or the force of gravity. For example, lock mechanism **500** may be placed in a locked state to prevent rotation in the releasing direction while the detachable implement is spinning sufficiently rapidly to cause lock elements **510a** and **510b** to slide outward and cause teeth **511a** and **511b** to engage the teeth of ring gear **222**. In accordance with the illustrated example, lock elements **510a** and **510b** are weighted sufficiently to cause the lock elements to overcome the tension bias of springs **501a** and **501b** slide such that teeth **511a** and **511b** move outward and engage the teeth of ring gear **222** in response to centrifugal force resulting from rotation of the detachable implement and corresponding force amplified fastener assembly at a sufficient speed. In accordance with this example, when power tool **100** is stopped, a springs **501a** and **501b** may provide bias forces to pull lock elements **510a** and **510b** such that they are slid sufficiently inward for teeth **511a** and **511b** to disengage the teeth of ring gear **222**. Additionally or alternatively, lock mechanism **500** may be placed in an unlocked state by the force of gravity to allow rotation in the releasing direction when power tool **100** is disposed in a particular orientation (e.g., unlocked when a head of the power tool upon which a detachable implement is fastened is turned upside down for user service). According to some embodiments, lock mechanism **500** may additionally or alternatively utilize user action to unlock and/or lock the lock mechanism. Springs **501a** and **501b** may, for example, be disposed to provide a bias force to hold lock elements **510a** and **510b**, respectively, such that teeth **511a** and **511b** are disposed in a radially outward position (e.g., lock mechanism **500** in a locked state). A user may apply a force (e.g., squeezing force) to a portion of lock elements **510a** and **510b** (e.g., pressing the lock elements) made accessible via corresponding openings in top housing **310** to cause the lock elements to slide such that teeth **511a** and **511b** move radially inward (e.g., lock mechanism **500** in an unlocked state) to disengage the lock mechanism.

(47) In operation according to the illustrated embodiment of lock mechanism **500**, movement of top housing **210** relative to bottom structure **220** when lock mechanism **500** is in a locked state is prevented in both the fastening direction and the releasing direction. For example, teeth **511a** and **511b** are sized and shaped to correspond to the size and shape of the teeth of ring gear **222** to thereby provide a locking engagement (e.g., when lock elements **510a** and **510b** are in a radially outward position) which discourages rotation in either direction. Alternative embodiments may, however, provide different configurations of teeth **511a** and **511b**, such as to facilitate preventing movement of top housing **210** relative to bottom structure **220** in a first direction (e.g., releasing direction) when lock elements **510a** and **510b** are in a radially outward position while allowing movement of top housing **210** relative to bottom structure **220** in a second direction (e.g., fastening direction) when lock elements **510a** and **510b** are in a radially outward position. For example, teeth

511a and **511b** may be provided in a saw-tooth type configuration, wherein a ramped side of the saw-teeth permits relative movement and a bulkhead side prevents relative movement such that movement of top housing **210** relative to bottom structure **220** is prevented in one direction (e.g., the releasing direction) but not the other (e.g., the fastening direction).

(48) FIGS. **6A** and **6B** show details with respect to an exemplary lock mechanism implemented with respect to the cycloid gear train configuration of the embodiment of FIGS. **3A-3E**. Lock mechanism **600** of the example illustrated in FIGS. **6A** and **6B** includes lock elements **610a** and **610b** disposed in the underside of top housing **310**. Lock elements **610a** and **610b** are configured for engaging bottom structure **320** (FIG. **3D**) and provide locking with respect to movement of top housing **310** relative to bottom structure **320** of force amplified fastener assembly **130**. For example, lock elements **610a** and **610b** of the illustrated embodiment include teeth **611a** and **611b**, respectively, configured for interfacing with teeth **323** (FIG. **3D**) disposed upon an outer circumference of ring gear **322** of bottom structure **220**. Lock elements **610a** and **610b** may, for example, comprise pawls pivotally coupled to the underside surface of top housing **310**, whereby when the lock elements are pivoted such that teeth **611a** and **611b** move radially inward such that the teeth engage teeth **323** of ring gear **322** and prevent movement of top housing **310** relative to bottom structure **320**. Further, lock elements **610a** and **610b** may be pivoted radially outward to a point that teeth **611a** and **611b** clear teeth **323** of ring gear **322** and movement of top housing **310** relative to bottom structure **320** is permitted.

(49) Lock elements **610a** and **610b** of embodiments of lock mechanism **600** may utilize user action to unlock and/or lock the lock mechanism. Springs **601a** and **601b** may, for example, provide a bias force to hold lock elements **610a** and **610b**, respectively, in a radially inward position (e.g., lock mechanism **600** in a locked state). A user may apply force (e.g., squeezing force) to arms **612a** and **612b** of lock elements **610a** and **610b**, respectively, accessible via corresponding openings in top housing **310** to cause the lock elements to pivot between locked and unlocked positions (e.g., lock mechanism in an unlocked state) to disengage the lock mechanism. Additionally or alternatively, lock elements of lock mechanism **600** may be configured to move between locked and/or unlocked positions in response to one or more forces other than from user unlocking/locking action. For example, arms **612a** and **612b** may be weighted, whereby the weighted pivot members may be acted on by centrifugal force to encourage lock elements **610a** and **610b** to pivot (e.g., placing lock mechanism **600** in a locked state) when power tool **100** is operating. Lock mechanism **600** of some embodiments may be placed in an unlocked state by the force of gravity to allow rotation in the releasing direction when power tool **100** is disposed in a particular orientation (e.g., unlocked when a head of the power tool upon which a detachable implement is fastened is turned upside down for user service).

(50) In operation according to the illustrated embodiment of lock mechanism **600**, movement of top housing **310** relative to bottom structure **320** when lock mechanism **600** is in a locked state is prevented in the releasing direction while movement in the fastening direction is permitted. For example, teeth **611a** and **611b** and teeth **323** of the illustrated embodiment are provided in saw-tooth type configurations, wherein a ramped side of the saw-teeth permits relative movement and a bulkhead side prevents relative movement such that movement of top housing **310** relative to bottom structure **320** is prevented in one direction (e.g., the releasing direction) but not the other (e.g., the fastening direction). Alternative embodiments of lock mechanism **600** may be configured to prevent movement of top housing **310** relative to bottom structure **320** in both the fastening direction and releasing direction when lock mechanism **600** is in a locked state. For example, teeth **611a** and **611b** and teeth **323** may be correspondingly sized and shaped to provide a locking engagement (e.g., when lock elements **610a** and **610b** are pivoted such that teeth **611a** and **611b** engage teeth **323**) which discourages rotation in either direction.

(51) FIGS. **7A** and **7B** show details with respect to another exemplary lock mechanism as may be implemented with respect to the cycloid gear train configuration of the embodiment of FIGS. **3A-**

3E. Lock mechanism **700** of the example illustrated in FIGS. 7A and 7B includes lock elements **710a** and **710b** disposed in the underside of top housing **310**. Lock elements **710a** and **710b** are configured for engaging bottom structure **320** (FIG. 3D) and provide locking with respect to movement of top housing **310** relative to bottom structure **320** of force amplified fastener assembly **130**. For example, lock elements **710a** and **710b** of the illustrated embodiment include teeth **711a** and **711b**, respectively, configured for interfacing with teeth **323** (FIG. 3D) disposed upon an outer circumference of ring gear **322** of bottom structure **220**. Lock elements **710a** and **710b** may, for example, comprise pawls pivotally coupled to the underside surface of top housing **310**, whereby when the lock elements are pivoted such that teeth **711a** and **711b** move radially inward such that the teeth engage teeth **323** of ring gear **322** and prevent movement of top housing **310** relative to bottom structure **320**. Further, lock elements **710a** and **710b** may be pivoted radially outward to a point that teeth **711a** and **711b** clear teeth **323** of ring gear **322** and movement of top housing **310** relative to bottom structure **320** is permitted.

(52) Lock elements **710a** and **710b** of embodiments of lock mechanism **700** may pivoted between locked and unlocked positions in response to various forces, such as centrifugal force and/or the force of gravity. For example, lock mechanism **700** may be placed in a locked state to prevent rotation in the releasing direction while the detachable implement is spinning sufficiently rapidly to cause lock elements **710a** and **710b** to pivot and cause teeth **711a** and **711b** to engage teeth **323**. In accordance with the illustrated example, weighted arms **712a** and **712b** of lock elements **710a** and **710b**, respectively, may cause the lock elements to pivot such that teeth **711a** and **711b** move inward and engage teeth **323** in response to centrifugal force resulting from rotation of the detachable implement and corresponding force amplified fastener assembly at a sufficient speed. In accordance with this example, when power tool **100** is stopped, springs **701a** and **701b** may provide bias forces to pull lock elements **710a** and **710b** such that they are pivoted sufficiently for teeth **711a** and **711b** to disengage teeth **323**. Additionally or alternatively, lock mechanism **700** may be placed in an unlocked state by the force of gravity to allow rotation in the releasing direction when power tool **100** is disposed in a particular orientation (e.g., unlocked when a head of the power tool upon which a detachable implement is fastened is turned upside down for user service). According to some embodiments, lock mechanism **700** may additionally or alternatively utilize user action to unlock and/or lock the lock mechanism. Springs **701a** and **701b** may, for example, be disposed to provide a bias force to hold lock elements **710a** and **710b**, respectively, such that teeth **711a** and **711b** are disposed in a radially inward position (e.g., lock mechanism **700** in a locked state). A user may apply a force (e.g., squeezing force) to a portion of lock elements **710a** and **710b** (e.g., pressing weighted arms **712a** and **712b**) made accessible via corresponding openings in top housing **310** to cause the lock elements to pivot such that teeth **711a** and **711b** move radially outward (e.g., lock mechanism **700** in an unlocked state) to disengage the lock mechanism.

(53) In operation according to the illustrated embodiment of lock mechanism **700**, movement of top housing **310** relative to bottom structure **320** when lock mechanism **700** is in a locked state is prevented in the releasing direction while movement in the fastening direction is permitted. For example, teeth **711a** and **711b** and teeth **323** of the illustrated embodiment are provided in saw-tooth type configurations, wherein a ramped side of the saw-teeth permits relative movement and a bulkhead side prevents relative movement such that movement of top housing **310** relative to bottom structure **320** is prevented in one direction (e.g., the releasing direction) but not the other (e.g., the fastening direction). Alternative embodiments of lock mechanism **700** may be configured to prevent movement of top housing **310** relative to bottom structure **320** in both the fastening direction and releasing direction when lock mechanism **700** is in a locked state. For example, teeth **711a** and **711b** and teeth **323** may be correspondingly sized and shaped to provide a locking engagement (e.g., when lock elements **710a** and **710b** are pivoted such that teeth **711a** and **711b** engage teeth **323**) which discourages rotation in either direction.

(54) It should be appreciated that the foregoing lock mechanisms are substantially protected by

structure of force amplified fastener assembly **130**. For example, lock mechanisms **400**, **500**, **600**, and **700** of the illustrated embodiments are disposed within an area of the cupped casing formed by the top housing. Moreover, embodiments of the lock mechanisms may be fully encased by the top housing and bottom structure (e.g., as provided by top housing **210** and bottom structure **220** with respect to the example of lock mechanisms **500** and as provided by top housing **310**, bottom structure **320**, and bottom housing **301** with respect to the example of lock mechanism **700**), thereby providing added protection of the lock mechanisms. Accordingly, the latch mechanisms of embodiments of the invention may be protected from damage and unintentional release, such as may otherwise result in damage causing unintentional release of the latch mechanism and allowing the fastening device to become detached from the lawn mower.

(55) Force amplified fastener assemblies of embodiments of the invention are configured to provide mechanical advantage with respect to rotating a fastening element, whereby a user may be enabled to manually apply tightening or loosening torque by hand for tool-free changing of a detachable implement. Configurations of force amplified fastener assemblies herein may be utilized in place of a conventional lock nut for affixing detachable implements to power tools, even retrofitting a conventional lock nut in some cases. Accordingly, backwardly compatible detachable implement configurations may be accommodated with a force amplified fastener assembly of embodiments of the invention.

(56) Although the present invention and its advantages have been described in detail, it should be understood that various changes, substitutions and alterations can be made herein without departing from the spirit and scope of the invention as defined by the appended claims. Moreover, the scope of the present application is not intended to be limited to the particular embodiments of the process, machine, manufacture, composition of matter, means, methods and steps described in the specification. As one of ordinary skill in the art will readily appreciate from the disclosure of the present invention, processes, machines, manufacture, compositions of matter, means, methods, or steps, presently existing or later to be developed that perform substantially the same function or achieve substantially the same result as the corresponding embodiments described herein may be utilized according to the present invention. Accordingly, the appended claims are intended to include within their scope such processes, machines, manufacture, compositions of matter, means, methods, or steps.

(57) Moreover, the scope of the present application is not intended to be limited to the particular embodiments of the process, machine, manufacture, composition of matter, means, methods and steps described in the specification.

Claims

1. A force amplified fastener assembly for removably coupling a detachable implement to a power tool, the force amplified fastener assembly comprising: a top housing forming a cupped casing; a bottom structure nested within an area of the cupped casing; a fastening element disposed between the top housing and the bottom structure and within the area of the cupped casing, wherein the fastening element is configured for engagement with a shaft of the power tool; a force amplifying gear train disposed in the area of the cupped casing and in mechanical communication with the top housing, the bottom structure, and the fastening element, wherein the force amplifying gear train provides a mechanical advantage with respect to application of torque to the fastening element in response to torque applied to the top housing; and a lock mechanism disposed within the area of the cupped casing of the top housing and operative to prevent rotation of the fastening element relative to the shaft in at least one rotational direction.

2. The force amplified fastener assembly of claim 1, wherein the top housing, bottom structure, force amplifying gear train, and the fastening element cooperate to facilitate installation and removal of the detachable implement on the shaft of the power tool in response to manual

manipulation of the top housing without aid of additional tools.

3. The force amplified fastener assembly of claim 1, wherein force amplified torque applied to the fastening element by the force amplifying gear train is in a same direction as the torque applied to the top housing.

4. The force amplified fastener assembly of claim 1, wherein the bottom structure forms a cupped structure, and wherein the fastening element and the force amplifying gear train are disposed within an area incarcerated by the cupped casing of the top housing and the cupped structure of the bottom structure.

5. The force amplified fastener assembly of claim 4, wherein the force amplifying gear train comprises: a planetary gear configuration, wherein the cupped structure of the bottom structure provides a ring gear of the planetary gear configuration and a sun gear of the planetary gear configuration is attached to the top housing within the cupped casing.

6. The force amplified fastener assembly of claim 5, wherein the planetary gear configuration comprises: a gear plate attached to a plurality of planet gears that are meshed with the sun gear and the ring gear, wherein the fastening element rotates in direct correspondence to rotation of the gear plate.

7. The force amplified fastener assembly of claim 4, wherein the force amplifying gear train comprises: a cycloid gear configuration, wherein the cupped structure of the bottom structure provides a ring gear of the cycloid gear configuration and an eccentric shaft of the cycloid gear configuration is attached to the top housing within the cupped casing.

8. The force amplified fastener assembly of claim 7, wherein the cycloid gear configuration comprises: a cycloidal gear in mechanical communication with the eccentric shaft and the ring gear; and a pin plate in mechanical communication with the cycloidal gear via a plurality of roller pins of the pin plate, wherein the fastening element rotates in direct correspondence to rotation of the pin plate.

9. The force amplified fastener assembly of claim 1, wherein the lock mechanism is operative to prevent rotation of the fastening element relative to the shaft in two rotational directions.

10. The force amplified fastener assembly of claim 1, wherein the lock mechanism is engaged to prevent the rotation of the fastening element relative to the shaft by centrifugal force.

11. The force amplified fastener assembly of claim 1, wherein the lock mechanism is disengaged from preventing the rotation of the fastening element relative to the shaft without a user directly interacting with the lock mechanism.

12. A method for removably coupling a detachable implement to a power tool, the method comprising: interfacing a force amplified fastener assembly with a shaft of the power tool, wherein the force amplified fastener assembly includes a top housing forming a cupped casing, a bottom structure nested within an area of the cupped casing, a fastening element disposed between the top housing and the bottom structure and within the area of the cupped casing, and a force amplifying gear train disposed in the area of the cupped casing and in mechanical communication with the top housing, the bottom structure, and the fastening element, wherein the interfacing the force amplified fastener assembly with the shaft of the power tool engages the fastening element with the shaft; and applying torque to the top housing and inducing torque at the fastening element in a same direction as the torque applied to the top housing, wherein the force amplifying gear train provides a mechanical advantage with respect to the torque induced at the fastening element; and preventing rotation of the fastening element relative to the shaft in at least one rotational direction through operation of a lock mechanism disposed within the area of the cupped casing of the top housing.

13. The method of claim 12, wherein the applying torque to the top housing is a result of manual manipulation of the top housing and the mechanical advantage results in the torque induced at the fastening element sufficient to affix the detachable implement to the power tool for use of the power tool without aid of additional tools.

14. The method of claim 12, wherein the bottom structure forms a cupped structure, and wherein the fastening element and the force amplifying gear train are disposed within an area incarcerated by the cupped casing of the top housing and the cupped structure of the bottom structure.
15. The method of claim 14, wherein the force amplifying gear train is provided in a planetary gear configuration, wherein the cupped structure of the bottom structure provides a ring gear of the planetary gear configuration, and wherein a sun gear of the planetary gear configuration is attached to the top housing within the cupped casing.
16. The method of claim 15, wherein the planetary gear configuration includes a gear plate attached to a plurality of planet gears that are meshed with the sun gear and the ring gear, wherein the fastening element rotates in direct correspondence to rotation of the gear plate.
17. The method of claim 14, wherein the force amplifying gear train is provided in a cycloid gear configuration, wherein the cupped structure of the bottom structure provides a ring gear of the cycloid gear configuration, and wherein an eccentric shaft of the cycloid gear configuration is attached to the top housing within the cupped casing.
18. The method of claim 17, wherein the cycloid gear configuration includes a cycloidal gear in mechanical communication with the eccentric shaft and the ring gear, wherein the cycloid gear configuration also includes a pin plate in mechanical communication with the cycloidal gear via a plurality of roller pins of the pin plate, and wherein the fastening element rotates in direct correspondence to rotation of the pin plate.
19. The method of claim 12, wherein the lock mechanism is operative to prevent rotation of the fastening element relative to the shaft in two rotational directions.
20. The method of claim 12, wherein the lock mechanism is engaged to prevent the rotation of the fastening element relative to the shaft by centrifugal force.
21. The method of claim 12, wherein the lock mechanism is disengaged from preventing the rotation of the fastening element relative to the shaft without a user directly interacting with the lock mechanism.
22. A system for removably coupling a detachable implement to a power tool, the system comprising: force amplified fastener assembly including a top housing, a bottom structure, and a force amplifying gear train in mechanical communication with the top housing and bottom structure, wherein the force amplifying gear train is configured to provide a mechanical advantage with respect to torque induced at a fastening element responsive to torque applied to the top housing; and a stay disposed on a shaft or the detachable implement and configured to interface with the bottom structure preventing rotation of the bottom structure relative to the top housing when the torque is applied to the top housing.
23. The system of claim 22, wherein the top housing forms a cupped casing and the bottom structure is nested within an area of the cupped casing, wherein the fastening element is disposed between the top housing and the bottom structure and within the area of the cupped casing, and wherein the force amplifying gear train is disposed in the area of the cupped casing.
24. The system of claim 23, further comprising: a lock mechanism disposed within the area of the cupped casing of the top housing and operative to prevent rotation of the fastening element relative to the shaft in at least one rotational direction.
-