

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412246
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Hirokawa; Mariko et al.

Image processing method, image processing device, and image processing program

Abstract

An image processing method including acquiring a fundus image, extracting a first area including a first feature from the fundus image, extracting a second area including a second feature different from the first feature from the fundus image, and generating a combined image in which the extracted first area and the extracted second area are combined.

Inventors:	Hirokawa; Mariko (Yokohama, JP), Tanabe; Yasushi (Fujisawa, JP)
Applicant:	NIKON CORPORATION (Tokyo, JP)
Family ID:	75537756
Assignee:	NIKON CORPORATION (Tokyo, JP)
Appl. No.:	17/769313
Filed (or PCT Filed):	October 17, 2019
PCT No.:	PCT/JP2019/040889
PCT Pub. No.:	WO2021/075026
PCT Pub. Date:	April 22, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230139849 A1	May. 04, 2023

Publication Classification

Int. Cl.: G06T5/50 (20060101); A61B3/10 (20060101); A61B3/12 (20060101); G06T7/11 (20170101); G06T7/136 (20170101)

U.S. Cl.:

CPC **G06T5/50** (20130101); **A61B3/102** (20130101); **A61B3/1233** (20130101); **A61B3/1241** (20130101); **G06T7/11** (20170101); **G06T7/136** (20170101); G06T2207/10101 (20130101); G06T2207/20212 (20130101); G06T2207/30041 (20130101); G06T2207/30101 (20130101)

Field of Classification Search

CPC: G06T (5/50); G06T (7/136); G06T (7/11); G06T (2207/10101); G06T (2207/20212); G06T (2207/30041); G06T (2207/30101); A61B (3/102); A61B (3/1233); A61B (3/1241)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5881124	12/1998	Giger	250/363.04	G06T 7/0012
2002/0009215	12/2001	Armato, III	382/131	G06T 7/187
2010/0104148	12/2009	Bovik	382/128	G06T 5/20
2011/0164219	12/2010	Ono	351/206	A61B 3/12
2019/0139223	12/2018	Nie	N/A	G06V 10/25
2021/0004939	12/2020	Hirokawa	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
112004457	12/2019	CN	A61B 3/0025
114828732	12/2021	CN	A61B 3/10
118078205	12/2023	CN	A61B 3/0025
118982519	12/2023	CN	G06T 7/0012
WO-2019/181981	12/2018	WO	N/A

OTHER PUBLICATIONS

Office Action issued in corresponding Japanese Patent Application No. 2021-552060 dated May 23, 2023 (7 pages). cited by applicant

Sonoda, Shozo, “Introducing Timelines to Imaging Analysis : Quantitative Analysis of Retinochoroidal Disease Using Imaging Technology”, Journal of Japanese Ophthalmological Society) Mar. 10, 2019, vol. 123, No. 3, pp. 260-283, with partial translation (26 pages). cited by applicant

JP Notice of Reasons for Refusal issued in corresponding Japanese Application No. 2024-084261 Dated Dec. 10, 2024 (6 pages). cited by applicant

Shota Uruma et al., “Computerized extraction of vessel regions in retinal fundus images”, vol. 111 No. 389, IEICE Technical Report, JAPAN, The Institute of Electronics, Information and Communication Engineers, 2012 (5 pages). cited by applicant

CN First Office Action issued in corresponding CN Application No. 201980102988.3 Dated Dec. 31, 2024 (20 pages). cited by applicant

Primary Examiner: Patel; Pinalben

Attorney, Agent or Firm: Foley & Lardner LLP

Background/Summary

TECHNICAL FIELD

(1) The technology disclosed herein relates to an image processing method, an image processing device, and an image processing program.

BACKGROUND ART

(2) An optical coherence tomography instrument that makes a choroidal vascular network selectively visible is disclosed in the specification of U.S. Pat. No. 10,136,812. There is a desire for an image processing method for analyzing the choroidal vasculature.

SUMMARY OF INVENTION

(3) An image processing method of a first aspect of technology disclosed herein includes acquiring a fundus image, extracting a first area including a first feature from the fundus image, extracting a second area including a second feature different from the first feature from the fundus image, and generating a combined image in which the extracted first area and the extracted second area are combined.

(4) An image processing device of a second aspect of technology disclosed herein includes an image acquisition section configured to acquire a fundus image, a first extraction section configured to extract a line-shaped portion of vasculature from the fundus image, a second extraction section configured to extract a lump-shaped portion of vasculature from the fundus image, and a blood vessel visualizing section configured to integrate an image of the extracted line-shaped portion together with an image of the extracted lump-shaped portion to generate a vascular image in which blood vessels have been made visible.

(5) A non-transitory storage medium storing an image processing program of a third aspect of technology disclosed herein causes a computer to function as an image acquisition section configured to acquire a fundus image, a first extraction section configured to extract a line-shaped portion of vasculature from the fundus image, a second extraction section configured to extract a lump-shaped portion of vasculature from the fundus image; and a blood vessel visualizing section configured to integrate an image of the extracted line-shaped portion together with an image of the extracted lump-shaped portion to generate a vascular image in which blood vessels have been made visible.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a block diagram of an ophthalmic system **100**.

(2) FIG. 2 is a schematic configuration diagram illustrating an overall configuration of an ophthalmic device **110**.

(3) FIG. 3 is a block diagram of configuration of an electrical system of a management server **140**.

- (4) FIG. 4 is a block diagram illustrating functionality of a CPU **262** of a management server **140**.
- (5) FIG. 5 is a block diagram illustrating functionality of an image processing control section **206** of a CPU **262** of a management server **140**.
- (6) FIG. 6 is a flowchart of an image processing program.
- (7) FIG. 7 is a flowchart of choroidal vasculature analysis processing of step **304** of FIG. 6.
- (8) FIG. 8A is a schematic diagram illustrating an example of extracted line shaped portions **12V1**, **12V2**, **12V3**, **12V4** of choroidal vasculature.
- (9) FIG. 8B is a schematic diagram illustrating an example of extracted bulge portions **12E1**, **12E2**, **12E3**, **12E4** of choroidal vasculature.
- (10) FIG. 8C is a schematic diagram illustrating a case in which line shaped portions **12V1**, **12V2**, **12V3**, **12V4** of choroidal vasculature have been joined to bulge portions **12E1**, **12E2**, **12E3**, **12E4** of choroidal vasculature.
- (11) FIG. 9 is a schematic diagram illustrating a display screen **500**.
- (12) FIG. 10 is a schematic diagram illustrating a case in which choroidal vasculature extraction images of a specific region **12V3B** have been combined with RGB color fundus images of the specific region **12V3A** having the same respective imaging date, displayed in a time series in a follow-up observation region **570**.
- (13) FIG. 11 is a schematic diagram illustrating a case in which outline emphasis images extracted from RGB color fundus images of a specific region **12V3A** have been combined with choroidal vasculature extraction images of a specific region **12V3B** having the same respective imaging date displayed in a time series in a follow-up observation region **570**.
- (14) FIG. 12 is a diagram illustrating a choroidal vascular image CLA.

DESCRIPTION OF EMBODIMENTS

- (15) Detailed explanation follows regarding exemplary embodiments, with reference to the drawings.
- (16) Explanation follows regarding a configuration of an ophthalmic system **100**, with reference to FIG. 1. As illustrated in FIG. 1, the ophthalmic system **100** includes an ophthalmic device **110**, a management server device (referred to hereafter as “management server”) **140**, and a display device (referred to hereafter as “viewer”) **150**. The ophthalmic device **110** acquires an image of the fundus. The management server **140** stores plural fundus images and eye axial lengths obtained by imaging the fundi of plural patients using the ophthalmic device **110** in association with patient IDs. The viewer **150** displays fundus images and analysis results acquired by the management server **140**.
- (17) The viewer **150** includes a display **156** that displays the fundus images and analysis results acquired by the management server **140**, and a mouse **155M** and a keyboard **155K** that are used for operation.
- (18) The ophthalmic device **110**, the management server **140**, and the viewer **150** are connected together through a network **130**. The viewer **150** is a client in a client-server system, and plural such devices are connected together through a network. There may also be plural devices for the management server **140** connected through the network in order to provide system redundancy. Alternatively, if the ophthalmic device **110** is provided with image processing functionality and with the image viewing functionality of the viewer **150**, then the fundus images may be acquired and image processing and image viewing performed with the ophthalmic device **110** in a standalone state. Moreover, if the management server **140** is provided with the image viewing functionality of the viewer **150**, then the fundus images may be acquired and image processing and image viewing performed by a configuration of the ophthalmic device **110** and the management server **140**.
- (19) Note that other ophthalmic equipment (examination equipment for measuring a field of view, measuring intraocular pressure, or the like) and/or a diagnostic support device that analyzes images using artificial intelligence (AI) may be connected to the ophthalmic device **110**, the management

server **140**, and the viewer **150** over the network **130**.

(20) Next, explanation follows regarding configuration of the ophthalmic device **110**, with reference to FIG. **2**. For ease of explanation, scanning laser ophthalmoscope is abbreviated to SLO. Optical coherence tomography is also abbreviated to OCT.

(21) With the ophthalmic device **110** installed on a horizontal plane and a horizontal direction taken as an X direction, a direction perpendicular to the horizontal plane is denoted a Y direction, and a direction connecting the center of the pupil at the anterior eye portion of the examined eye **12** and the center of the eyeball is denoted a Z direction. The X direction, the Y direction, and the Z direction are thus mutually perpendicular directions.

(22) The ophthalmic device **110** includes an imaging device **14** and a control device **16**. The imaging device **14** is provided with an SLO unit **18**, and an OCT unit **20**, and acquires a fundus image of the fundus of the examined eye **12**. Two-dimensional fundus images that have been acquired by the SLO unit **18** are referred to hereafter as SLO images. Tomographic images, face-on images (en-face images) and the like of the retina created based on OCT data acquired by the OCT unit **20** are referred to hereafter as OCT images.

(23) The control device **16** includes a computer provided with a Central Processing Unit (CPU) **16A**, Random Access Memory (RAM) **16B**, Read-Only Memory (ROM) **16C**, and an input/output (I/O) port **16D**.

(24) The control device **16** is provided with an input/display device **16E** connected to the CPU **16A** through the I/O port **16D**. The input/display device **16E** includes a graphical user interface to display images of the examined eye **12** and to receive various instructions from a user. An example of the graphical user interface is a touch panel display.

(25) The control device **16** is also provided with an image processing device **17** connected to the I/O port **16D**. The image processing device **17** generates images of the examined eye **12** based on data acquired by the imaging device **14**. Note that the control device **16** is connected to the network **130** through a non-illustrated communication interface.

(26) Although the control device **16** of the ophthalmic device **110** is provided with the input/display device **16E** as illustrated in FIG. **2**, the technology disclosed herein is not limited thereto. For example, a configuration may adopted in which the control device **16** of the ophthalmic device **110** is not provided with the input/display device **16E**, and instead a separate input/display device is provided that is physically independent of the ophthalmic device **110**. In such cases, the display device is provided with an image processing processor unit that operates under the control of the CPU **16A** in the control device **16**. Such an image processing processor unit may display SLO images and the like based on an image signal output as an instruction by the CPU **16A**.

(27) The imaging device **14** operates under the control of the CPU **16A** of the control device **16**. The imaging device **14** includes the SLO unit **18**, an imaging optical system **19**, and the OCT unit **20**. The imaging optical system **19** includes a first optical scanner **22**, a second optical scanner **24**, and a wide-angle optical system **30**.

(28) The first optical scanner **22** scans light emitted from the SLO unit **18** two dimensionally in the X direction and the Y direction. The second optical scanner **24** scans light emitted from the OCT unit **20** two dimensionally in the X direction and the Y direction. As long as the first optical scanner **22** and the second optical scanner **24** are optical elements capable of deflecting light beams, they may be configured by any out of, for example, polygon mirrors, minor galvanometers, or the like. A combination thereof may also be employed.

(29) The wide-angle optical system **30** includes an objective optical system (not illustrated in FIG. **2**) provided with a common optical system **28**, and a combining section **26** that combines light from the SLO unit **18** with light from the OCT unit **20**.

(30) The objective optical system of the common optical system **28** may be a reflection optical system employing a concave mirror such as an elliptical mirror, a refraction optical system employing a wide-angle lens, or may be a reflection-refraction optical system employing a

combination of a concave mirror and a lens. Employing a wide-angle optical system that utilizes an elliptical mirror, wide-angle lens, or the like enables imaging to be performed not only of a central portion of the fundus, but also of the retina at the periphery of the fundus.

(31) For a system including an elliptical mirror, a configuration may be adopted that utilizes an elliptical mirror system as disclosed in International Publication (WO) Nos. 2016/103484 or 2016/103489. The disclosures of WO Nos. 2016/103484 and 2016/103489 are incorporated in their entirety by reference herein.

(32) Observation of the fundus over a wide field of view (FOV) **12A** is implemented by employing the wide-angle optical system **30**. The FOV **12A** refers to a range capable of being imaged by the imaging device **14**. The FOV **12A** may be expressed as a viewing angle. In the present exemplary embodiment the viewing angle may be defined in terms of an internal illumination angle and an external illumination angle. The external illumination angle is the angle of illumination by a light beam shone from the ophthalmic device **110** toward the examined eye **12**, and is an angle of illumination defined with respect to a pupil **27**. The internal illumination angle is the angle of illumination of a light beam shone onto the fundus **F**, and is an angle of illumination defined with respect to an eyeball center **O**. A correspondence relationship exists between the external illumination angle and the internal illumination angle. For example, an external illumination angle of 120° is equivalent to an internal illumination angle of approximately 160° . The internal illumination angle in the present exemplary embodiment is 200° .

(33) SLO fundus images obtained by imaging at an imaging angle having an internal illumination angle of 160° or greater are referred to as UWF-SLO fundus images. UWF is an abbreviation of ultra-wide field (ultra-wide angled).

(34) An SLO system is realized by the control device **16**, the SLO unit **18**, and the imaging optical system **19** as illustrated in FIG. 2. The SLO system is provided with the wide-angle optical system **30**, enabling fundus imaging over the wide FOV **12A**.

(35) The SLO unit **18** is provided with a blue (B) light source **40**, a green (G) light source **42**, a red (R) light source **44**, an infrared (for example near infrared) (IR) light source **46**, and optical systems **48**, **50**, **52**, **54**, **56** to guide the light from the light sources **40**, **42**, **44**, **46** onto a single optical path using reflection or transmission. The optical systems **48**, **50**, **56** are configured by mirrors, and the optical systems **52**, **54** are configured by beam splitters. B light is reflected by the optical system **48**, is transmitted through the optical system **50**, and is reflected by the optical system **54**. G light is reflected by the optical systems **50**, **54**, R light is transmitted through the optical systems **52**, **54**, and IR light is reflected by the optical systems **52**, **56**. The respective lights are thereby guided onto a single optical path.

(36) The SLO unit **18** is configured so as to be capable of switching between the light source or the combination of light sources employed for emitting laser light of different wavelengths, such as a mode in which G light, R light and B light are emitted, a mode in which infrared light is emitted, etc. Although the example in FIG. 2 includes four light sources, i.e. the B light source **40**, the G light source **42**, the R light source **44**, and the IR light source **46**, the technology disclosed herein is not limited thereto. For example, the SLO unit **18** may, furthermore, also include a white light source, in a configuration in which light is emitted in various modes, such as a mode in which white light is emitted alone.

(37) Light introduced to the imaging optical system **19** from the SLO unit **18** is scanned in the X direction and the Y direction by the first optical scanner **22**. The scanning light passes through the wide-angle optical system **30** and the pupil **27** and is shone onto the posterior eye portion (fundus) of the examined eye **12**. Reflected light that has been reflected by the fundus passes through the wide-angle optical system **30** and the first optical scanner **22** and is introduced into the SLO unit **18**.

(38) The SLO unit **18** is provided with a beam splitter **64** that, from out of the light coming from the posterior eye portion (fundus) of the examined eye **12**, reflects the B light therein and transmits

light other than B light therein, and a beam splitter **58** that, from out of the light transmitted by the beam splitter **64**, reflects the G light therein and transmits light other than G light therein. The SLO unit **18** is further provided with a beam splitter **60** that, from out of the light transmitted through the beam splitter **58**, reflects R light therein and transmits light other than R light therein. The SLO unit **18** is further provided with a beam splitter **62** that reflects IR light from out of the light transmitted through the beam splitter **60**. The SLO unit **18** includes a B light detector **70** for detecting B light reflected by the beam splitter **64**, and a G light detector **72** for detecting G light reflected by the beam splitter **58**. The SLO unit **18** includes an R light detector **74** for detecting R light reflected by the beam splitter **60** and an IR light detector **76** for detecting IR light reflected by the beam splitter **62**.

(39) Light that has passed through the wide-angle optical system **30** and the scanner **22** and been introduced into the SLO unit **18** (i.e. reflected light that has been reflected by the fundus) is reflected by the beam splitter **64** and photo-detected by the B light detector **70** when B light, and is transmitted through the beam splitter **64** and reflected by the beam splitter **58** and photo-detected by the G light detector **72** when G light. When R light, the incident light is transmitted through the beam splitters **64**, **58**, reflected by the beam splitter **60**, and photo-detected by the R light detector **74**. When IR light, the incident light is transmitted through the beam splitters **64**, **58**, **60**, reflected by the beam splitter **62**, and photo-detected by the IR light detector **76**. The image processing device **17** that operates under the control of the CPU **16A** employs signals detected by the B light detector **70**, the G light detector **72**, the R light detector **74**, and the IR light detector **76** to generate UWF-SLO images. Examples of the B light detector **70**, the G light detector **72**, the R light detector **74**, and the IR light detector **76** include, for example, photodiodes (PDs) and avalanche photodiodes (APDs). The B light detector **70**, the G light detector **72**, the R light detector **74**, and the IR light detector **76** correspond to the “image acquisition section” of technology disclosed herein. In the SLO unit **18**, light returning after being reflected (scattered) by the fundus subject arrives at the light detectors through the first optical scanner **22**, and always returns to the same position, namely the positions where the B light detector **70**, the G light detector **72**, the R light detector **74**, and the IR light detector **76** are present. The light detectors accordingly do not need to be of a flat planar shape (two dimensional) configuration such as an area sensor, and detectors of a point shape (zero dimensional) configuration such as a PD or APD are optimal as the light detectors in the present exemplary embodiment. However, there is no limit to being a PD, APD, or the like, and a line sensor (one dimension) or an area sensor (two dimensions) may be employed.

(40) The UWF-SLO image encompasses a UWF-SLO image (green fundus image) obtained by imaging the fundus in green, and a UWF-SLO image (red fundus image) obtained by imaging the fundus in red. The UWF-SLO image further encompasses a UWF-SLO image (blue fundus image) obtained by imaging the fundus in blue, and a UWF-SLO image (IR fundus image) obtained by imaging the fundus in IR.

(41) The control device **16** also controls the light sources **40**, **42**, **44** so as to emit light at the same time. A green fundus image and a red fundus image, and a blue fundus image are obtained with mutually corresponding positions by imaging the fundus of the examined eye **12** at the same time with the B light, G light, and R light. An RGB color fundus image is obtained from the green fundus image, the red fundus image, and the blue fundus image. The control device **16** obtains a green fundus image and a red fundus image with mutually corresponding positions by controlling the light sources **42**, **44** so as to emit light at the same time and by imaging the fundus of the examined eye **12** at the same time with the G light and R light. An RG color fundus image is obtained by mixing the green fundus image and the red fundus image together at a specific mixing ratio.

(42) The UWF-SLO images further include an UWF-SLO image (video) imaged using ICG fluoroscopy. When indocyanine green (ICG) is injected into a blood vessel so as to reach the fundus, the indocyanine green (ICG) first reaches the retina, then reaches the choroid, before

passing through the choroid. The UWF-SLO image (video) is a video image from the time the indocyanine green (ICG) injected into a blood vessel reached the retina until after passing through the choroid.

(43) Image data of the blue fundus image, the green fundus image, the red fundus image, the IR fundus image, the RGB color fundus image, the RG color fundus image, and the UWF-SLO image is transmitted from the ophthalmic device **110** to the management server **140** through a non-illustrated communication IF.

(44) An OCT system is realized by the control device **16**, the OCT unit **20**, and the imaging optical system **19** illustrated in FIG. 2. The OCT system is provided with the wide-angle optical system **30**. This enables fundus imaging to be performed over the wide FOV **12A** similarly to when imaging the SLO fundus images as described above. The OCT unit **20** includes a light source **20A**, a sensor (detector) **20B**, a first light coupler **20C**, a reference optical system **20D**, a collimator lens **20E**, and a second light coupler **20F**.

(45) Light emitted from the light source **20A** is split by the first light coupler **20C**. After one part of the split light has been collimated by the collimator lens **20E** into parallel light, to serve as measurement light, the parallel light is introduced into the imaging optical system **19**. The measurement light is scanned in the X direction and the Y direction by the second optical scanner **24**. The scanning light is shone onto the fundus through the wide-angle optical system **30** and the pupil **27**. Measurement light that has been reflected by the fundus passes through the wide-angle optical system **30** and the second optical scanner **24** so as to be introduced into the OCT unit **20**. The measurement light then passes through the collimator lens **20E** and the first light coupler **20C** before being incident to the second light coupler **20F**.

(46) The other part of the light emitted from the light source **20A** and split by the first light coupler **20C** is introduced into the reference optical system **20D** as reference light, and is made incident to the second light coupler **20F** through the reference optical system **20D**.

(47) The respective lights that are incident to the second light coupler **20F**, namely the measurement light reflected by the fundus and the reference light, interfere with each other in the second light coupler **20F** so as to generate interference light. The interference light is photo-detected by the sensor **20B**. The image processing device **17** operating under the control of an image processing control section **206** generates OCT images, such as tomographic images and en-face images, based on OCT data detected by the sensor **20B**.

(48) OCT fundus images obtained by imaging at an imaging angle having an internal illumination angle of 160° or greater are referred to as UWF-OCT images.

(49) The image data of the UWF-OCT images is sent from the ophthalmic device **110** to the management server **140** through the non-illustrated communication IF and is stored in a storage device **254**.

(50) Note that although in the present exemplary embodiment an example is given in which the light source **20A** is a swept-source OCT (SS-OCT), the light source **20A** may be configured from various types of OCT system, such as a spectral-domain OCT (SD-OCT) or a time-domain OCT (TD-OCT) system.

(51) Explanation follows regarding a configuration of an electrical system of the management server **140**, with reference to FIG. 3. As illustrated in FIG. 3, the management server **140** is provided with a computer body **252**. The computer body **252** includes a CPU **262**, RAM **266**, ROM **264**, and an input/output (I/O) port **268**. The storage device **254**, a display **256**, a mouse **255M**, a keyboard **255K**, and a communication interface (I/F) **258** are connected to the input/output (I/O) port **268**. The storage device **254** is, for example, configured by non-volatile memory. The input/output (I/O) port **268** is connected to the network **130** through the communication interface (I/F) **258**. The management server **140** is thus capable of communicating with the ophthalmic device **110** and the viewer **150**. The storage device **254** is stored with an image processing program, described later. Note that the image processing program may be stored in the ROM **264**.

(52) The management server **140** stores respective data received from the ophthalmic device **110** in the storage device **254**.

(53) Next, description follows regarding various functions implemented by the CPU **262** of the management server **140** executing the image processing program, with reference to FIG. **4**. The image processing program includes a display control function, an image processing control function and a processing function. By the CPU **262** executing the image processing program including each of these functions, the CPU **262** functions as a display control section **204**, the image processing control section **206**, and a processing section **208**, as illustrated in FIG. **4**.

(54) The image processing control section **206** corresponds to a “first extraction section”, “second extraction section”, “blood vessel visualizing section”, and “choroidal vascular image generation section” of technology disclosed herein.

(55) Next, description follows regarding various functions of the image processing control section **206**, with reference to FIG. **5**. The image processing control section **206** includes the functionality of a fundus image processing section **2060** that performs image processing such as generating sharpened images of the choroidal vasculature and the like from the fundus image, and a choroidal vasculature analysis section **2062** that performs image processing such as extracting line shaped portions and bulge portions (lump shaped portions) of the choroid. The line shaped portions correspond to a “first feature” of technology disclosed herein, and the bulge portions correspond to a “second feature” of technology disclosed herein.

(56) Detailed explanation now follows regarding image processing by the management server **140**, with reference to FIG. **6**. Image processing (an image processing method) illustrated by the flowchart in FIG. **6** is implemented by the CPU **262** of the management server **140** executing an image processing program.

(57) At step **300** the image processing control section **206** acquires the UWF-SLO images from the storage device **254**. At step **302** the image processing control section **206** creates a choroidal vascular image in which the choroidal vasculature has been extracted from the acquired UWF-SLO images (red fundus image and green fundus image). Since red light is of longer wavelength, red light passes through the retina and reaches the choroid. The red fundus image therefore includes information relating to blood vessels present within the retina (retinal blood vessels) and information relating to blood vessels present within the choroid (choroidal vasculature). In contrast thereto, due to green light being of shorter wavelength than red light, green light only reaches as far as the retina. The green fundus image accordingly only includes information relating to the blood vessels present within the retina (retinal blood vessels). This thereby enables a choroidal vascular image CLA to be obtained by extracting the retinal blood vessels from the green fundus image and removing the retinal blood vessels from the red fundus image. The red fundus image corresponds to a “red-light capture image” of technology disclosed herein.

(58) An explanation now follows regarding specific processing executed by the image processing control section **206** at step **302**.

(59) First, the image processing control section **206** performs de-noise processing to remove noise from each of the green fundus image and the red fundus image. A median filter or the like may be applied to remove noise.

(60) The image processing control section **206** performs black hat filter processing to the green fundus image after noise removal to extract the retinal blood vessels from the green fundus image.

(61) Next the image processing control section **206** removes the retinal blood vessels from the red fundus image by performing in-painting processing thereon using the retinal blood vessel position information extracted from the green fundus image to infill the retinal vasculature structure of the red fundus image with the same values as those of surrounding pixels. This processing generates an image in which the retinal blood vessels have been removed from the red fundus image and only the choroidal vasculature is made visible.

(62) Next the image processing control section **206** removes low frequency components from the

red fundus image after in-painting processing. Any well-known type of image processing for removing the low frequency components may be applied therefor, such as frequency filtering and spatial filtering.

(63) Then finally, the image processing control section **206** emphasizes the choroidal vasculature in the red fundus image by performing contrast limited adaptive histogram equalization processing on the image data of the red fundus image including the choroidal blood vessels that remain after the retinal blood vessels have been removed. The choroidal vascular image CLA illustrated in FIG. **12** is created by performing one cycle of the processing of step **302**. The created choroidal vascular image CLA is stored in the storage device **254**.

(64) In the example described above the choroidal vascular image CLA is generated from the red fundus image and the green fundus image. However, there is no limitation thereto, and the image processing control section **206** may generate the choroidal vascular image CLA from a green fundus image and an IR fundus image. Moreover, the image processing control section **206** may generate the choroidal vascular image CLA from a blue fundus image and either a red fundus image or an IR fundus image.

(65) Furthermore, the choroidal vascular image CLA may be generated from a UWF-SLO image (video) **510**. The UWF-SLO image (video) **510** is, as described above, a video image from when indocyanine green (ICG) injected into a blood vessel reached the retina until after passing through the choroid. The choroidal vascular image CLA may be generated from a video image over the period of time from when the indocyanine green (ICG) passed through the retina until passing through the choroid.

(66) Choroidal vasculature analysis processing is executed at step **304** to analyze the choroidal vasculature by independently performing extraction processing of the line shaped portions of the choroidal vasculature and extraction processing of the bulge portions thereof. Positions of vortex veins that are part of the choroidal vasculature are extracted from the extracted line shaped portions and bulge portions. The vortex veins are, anatomically, blood vessel sites where there is a concentration of choroidal blood vessels, and are the discharge paths for blood fluid that has flowed into the eyeball. The vortex veins are part of the choroidal vasculature, and there are from three to seven vortex veins present in the eyeball, present at fundus peripheral portion (in the vicinity of an equatorial portion of the eyeball). The vortex vein positions are recognized by performing image recognition on a fundus image, and have a lump shaped center portion with plural line shaped portions connected to the lump shaped center portion.

(67) The choroidal vasculature analysis of step **304** is described in detail later.

(68) At step **306**, analysis data obtained by the choroidal vasculature analysis processing of step **304** is output to the storage device **254** of the management server **140**. At step **308**, the display control section **204** generates a display screen **500**, described later and including an image of the extracted choroidal vasculature and also reflecting patient attribute information (patient name, age, information as to whether each fundus image is from the right eye or left eye, eye axial length, visual acuity, imaging date/time, etc.) corresponding to the patient ID. The display control section **204** then displays the display screen **500** on the display **256** of the management server **140**, and ends processing.

(69) The display screen **500** is stored in the storage device **254** of the management server **140**. The display screen **500** stored in the storage device **254** of the management server **140** is transmitted to the viewer **150** according to operation from the viewer **150**, and is output in a state enabling viewing on the display **156** of the viewer **150**.

(70) The processing illustrated in FIG. **6** may be executed by the CPU **16A** provided to the control device **16** of the ophthalmic device **110**. In cases in which this processing is executed by the CPU **16A** of the ophthalmic device **110**, along with display of the display screen **500** on the display of an ophthalmic device, the display screen **500** is also stored on a storage device of the management server **140**.

(71) The processing illustrated in FIG. 6 may be executed by a CPU provided to the viewer **150**. In cases in which this processing is executed by a CPU of the viewer **150**, along with display of the display screen **500** on the display **156** of the viewer **150**, the display screen **500** is also stored on a storage device of the viewer **150** and on a storage device of the management server **140**.

(72) FIG. 7 is a flowchart illustrating details regarding the choroidal vasculature analysis processing (step **304**) illustrated in FIG. 6. At step **400**, first blood vessel extraction processing is performed to extract line shaped portions from the choroidal vascular image CLA. At step **400**, first, line emphasis processing is performed on the analysis image that is the choroidal vascular image CLA illustrated in FIG. 12. Choroidal blood vessels of line shape is emphasized by this line emphasis processing. The line emphasized image is then subjected to binarization processing. Next, image processing is performed to extract the line shaped portions from the line emphasized choroidal vascular image CLA.

(73) The line emphasis processing is, for example, processing to emphasize line shaped structures by Hessian analysis using a Hessian matrix. The Hessian analysis discriminates as to whether a local structure in an image is a point, a line, or a plane by analyzing the eigenvalues of the Hessian matrix having elements of second order partial derivative coefficients computed using a second order derivative kernel for a specific filter such as a Gaussian kernel.

(74) In the emphasis of the line shaped portions of the choroidal vasculature, in addition to the line emphasis processing described above, a Gabor filter may be employed to extract the orientation of an outline contained in the image, or a graph cut filter may be employed to extract by cutting the line shaped portions from the other portions. Moreover, edge emphasis processing may be employed such as a Laplacian filter or an unsharp mask.

(75) The line shaped portions of the choroidal vasculature are extracted as illustrated in FIG. 8A by the first blood vessel extraction processing of step **400**. In FIG. 8A, the line shaped portions **12V1**, **12V2**, **12V3**, **12V4** are displayed clearly distinct from other areas of the fundus.

(76) At step **402**, second blood vessel extraction processing is performed to extract bulge portions of the choroidal vasculature from the choroidal vascular image CLA. The second blood vessel extraction processing is performed by first binarizing the analysis image. Then areas of a specific number of contiguous white pixels are extracted from the binarized choroidal vascular image CLA as choroidal vasculature bulge portions. The specific number or area size is a number preset from a size of vortex veins (from standard data or the like for the choroid). This extraction processing may be performed by Hessian analysis using a Hessian matrix to detect concave and convex parts of an image, with the convex portions extracted as bulge portions. Hessian analysis corresponds to an "image processing filter that extracts the lump shaped portion alone" of technology disclosed herein.

(77) Sometimes line shaped portions of the choroidal vasculature are also extracted together with pixels corresponding to the bulge portions. However, the line shaped portions and the bulge portions are integrated together by data integration processing described later, and so this does not affect the extraction of vortex vein positions.

(78) The bulge portions of the choroidal vasculature are extracted as illustrated in FIG. 8B by the second blood vessel extraction processing at step **402**. FIG. 8B illustrates an example of a case in which there are four vortex veins present in the eyeball (there are normally from four to six present), and the bulge portions **12E1**, **12E2**, **12E3**, **12E4** are displayed so as to be clearly distinct from the other regions of the fundus. The bulge portions **12E1**, **12E2**, **12E3**, **12E4** may be called inflow locations to the sclera side of the vortex veins present in the fundus peripheral portion (inlets of the choroid side of the vortex veins that run toward the outside of the eyeball). The choroidal bulge portions that were not able to be extracted by the line shaped portion extraction processing using the first blood vessel extraction processing of step **400** are able to be extracted by the binarization processing performed on the entire choroidal vascular image CLA at step **402**.

(79) Note that the second blood vessel extraction processing may be performed at step **400** and the

first blood vessel extraction processing may be performed at step **402** by switching the sequence in the flowchart of FIG. 7 of the first blood vessel extraction processing and the second blood vessel extraction processing. This is because the first blood vessel extraction processing and the second blood vessel extraction processing are each independent processing unrelated to each other.

(80) As illustrated in FIG. 8C, at step **404** data integration is performed to integrate the line shaped portions resulting from the first blood vessel extraction processing and the bulge portions resulting from the second blood vessel extraction processing. In other words, a line shaped portion image of the extracted line shaped portions obtained at step **400** is combined with a bulge portion image of the extracted bulge portions obtained at step **402**, so as to generate a single choroidal vascular image. Processing then proceeds to step **306** of FIG. 7, and processing to analyze the combined image is started. The choroidal vascular image illustrated in FIG. 8C corresponds to the “combined image” of technology disclosed herein.

(81) FIG. 8C is a display of a joined state of the line shaped portions **12V1**, **12V2**, **12V3**, **12V4** with the respective bulge portions **12E1**, **12E2**, **12E3**, **12E4**. Note that in each of FIGS. 8A, FIG. 8B, FIG. 8C, a background image where the fundus is not displayed is depicted in white, and an image of extracted choroidal vasculature, which is a binarized image, is clearly displayed, however, the outline between the binarized image and the background image may alone be depicted in white as long as it is possible to clearly see the binarized image. In the display screen **500** described later, a case is illustrated in which the background image, which is a region where the fundus is not being displayed, is depicted in white.

(82) FIG. 9 is a schematic diagram illustrating the display screen **500** displayed on the display **256** of the management server **140** or the like. In addition to being displayed on the display **256** of the management server **140**, the display screen **500** may also be displayed on the display **156** of the viewer **150**, and may be displayed on the input/display device **16E** of the ophthalmic device **110**.

(83) The display screen **500** includes an information display area **502** and an image display area **504**, as illustrated in FIG. 9. The information display area **502** includes a patient ID display field **512**, a patient name display field **514**, an age display field **516**, a visual acuity display field **518**, a right eye/left eye display field **520**, and an eye axial length display field **522**.

(84) The image display area **504** includes a latest image display field **550** to display the latest image (the fundus image imaged on Jul. 16, 2019 in FIG. 9), a previous image display field **560** to display an image imaged before the latest image (the fundus image imaged on Apr. 16, 2019 in FIG. 9), a follow-up observation field **570** to display changes by a time series of the fundus, and a remarks field **580** to display a treatment and a diagnostic memo or the like input by a user. There is an imaging date display field **552** at the top of the latest image display field **550** where a RG color fundus image **554** and a choroidal vasculature extraction image **556**, which is a binarized image in which the line shaped portions **12V1**, **12V2**, **12V3**, **12V4** of the choroidal vasculature are joined to the bulge portions **12E1**, **12E2**, **12E3**, **12E4** of the choroidal vasculature, are displayed.

(85) The previous image display field **560** includes an imaging date display field **562** at the top with an RG color fundus image **564** and a choroidal vasculature extraction image **566**, which is a binarized image in which the line shaped portions **12V1**, **12V2**, **12V3**, **12V4** are joined to the bulge portions **12E1**, **12E2**, **12E3**, **12E4** of the choroidal vasculature, displayed therein.

(86) The latest image display field **550** and the previous image display field **560** may each display a choroidal vasculature contrast image (ICG) and an optical coherence tomography angiogram (OCTA) instead of the RG color fundus images **554**, **564** and the choroidal vasculature extraction images **556**, **566**. The RG color fundus images **554**, **564**, ICG, and OCTA are each also not limited to 2D representations, and may be displayed in 3D representations. Images displayed in the latest image display field **550** and the previous image display field **560** may be selected from a displayed menu by switching switch display icons **558**, **568** ON.

(87) The follow-up observation field **570** displays changes to a specific region **12V3A** of the RG color fundus images **554**, **564** and to a specific region **12V3B** of the choroidal vasculature

extraction images **556**, **566** in time series. The follow-up observation field **570** includes a latest image display field **576** for displaying the latest image of each of the specific regions **12V3A**, **12V3B**, a previous image display field **574** for displaying a previous image that is an image imaged prior to the latest image of each of the specific regions **12V3A**, **12V3B**, and a two-previous image display field **572** for displaying an image imaged prior to the previous image of each of the specific regions **12V3A**, **12V3B** (the fundus image imaged on Jan. 16, 2019 in FIG. **9**). Below this is a time series blood vessel diameter display section **578** in which changes to the blood vessel diameters of the bulge portion **12E3** and the peripheral portion (line shaped portion **12V3**) are displayed for the imaging times of each of the latest image, previous image, and two-previous image. In FIG. **9** three images that were imaged at three timings, latest, previous, and two-previous, are displayed in the follow-up observation field **570**, however, there is no limitation to three images, and four or more fundus images imaged at different dates and times may be displayed in a time series.

(88) FIG. **10** is a schematic diagram illustrating cases in which the respective RG color fundus images of the specific region **12V3A** displayed in time series in the follow-up observation field **570** are combined with the respective choroidal vasculature extraction images of the specific region **12V3B** having the same imaging dates. A combined image such as that of FIG. **10** may be displayed in the follow-up observation field **570**.

(89) FIG. **11** is a schematic diagram illustrating a case in which outline emphasis images extracted from the RG color fundus images of the specific region **12V3A** are combined with the choroidal vasculature extraction images of the specific region **12V3B** of the same imaging date displayed in time series in the follow-up observation field **570**. A combined image such as that of FIG. **11** may be displayed in the follow-up observation field **570**. The image displayed in the follow-up observation field **570** can be selected from a displayed menu by switching a switch display icon **582** ON. The outline emphasis image can be generated by applying a well-known method such as a Sobel filter to an RG color fundus image or a choroidal vasculature extraction image. Combining the outline emphasis image with a choroidal vasculature extraction image, which is a binarized image, enables the line shaped portion **12V3** and the bulge portion **12E3** of the choroidal vasculature to be ascertained even more clearly than with a binarized image. Moreover, by changing the color of the outline sections in the outline emphasis image at the line shaped portion **12V3** and the bulge portion **12E3**, the line shaped portion **12V3** and the bulge portion **12E3** can be clearly discriminated.

(90) As explained above, in the present exemplary embodiment the line shaped portions of the choroidal vasculature are emphasized in the analysis image by the line emphasis processing, and the line shaped portions of the choroidal vasculature can be selectively extracted by binarization of the image.

(91) Moreover, in the present exemplary embodiment the bulge portions of the choroidal vasculature can be selectively extracted by performing binarization processing on the analysis image or by detecting convex portions in the analysis image using a Hessian matrix.

(92) The choroidal vasculature and vortex veins can be reliably extracted from a fundus image by the extraction of line shaped portions and bulge portions of the choroidal vasculature according to the present exemplary embodiment. This enables the choroidal vascular network including the vortex veins to be digitalized, and various analyses to be performed thereon. For example, prompt detection of signs of arterial sclerosis is facilitated, and an ophthalmologist is able to predict disorders related to vascular disease.

(93) It must be understood that the image processing of the respective exemplary embodiments described above is merely an example thereof. Obviously redundant steps may be omitted, new steps may be added, and the processing sequence may be swapped around within a range not departing from the spirit of technology disclosed herein.

(94) Although explanation has been given in the respective exemplary embodiments described above envisaging an example in which a computer is employed to implement image processing

using a software configuration, the technology disclosed herein is not limited thereto. For example, instead of a software configuration employing a computer, the image processing may be executed solely by a hardware configuration such as a field programmable gate array (FPGA) or an application specific integrated circuit (ASIC). Alternatively, a configuration may be adopted in which some processing out of the image processing is executed by a software configuration, and the remaining processing is executed by a hardware configuration.

Claims

1. An image processing method comprising: acquiring a fundus image; extracting a line-shaped portion from a first processing image generated by line emphasis processing on the fundus image and followed by binarization processing; extracting a lump-shaped portion from a second processing image generated by binarization processing on the fundus image; and generating a combined image in which the extracted the line-shaped portion from the first processing image and the extracted the lump-shaped portion from the second processing image are combined.
2. The image processing method of claim 1, wherein: the line-shaped portion is a line-shaped portion of blood vessel; and the lump-shaped portion is a lump-shaped portion of blood vessel.
3. The image processing method of claim 1, wherein the fundus image is a red-light capture image imaged with red light.
4. The image processing method of claim 3, wherein the fundus image is a binarized fundus image resulting from performing binarization processing on the red-light capture image.
5. The image processing method of claim 1, wherein the combined image is an image indicating vasculature structure of a fundus.
6. The image processing method of claim 1, wherein the combined image is an image indicating vasculature structure of a choroid of a fundus.
7. The image processing method of claim 1, wherein the line-shaped portion is a line-shaped area-portion of choroidal vasculature, and the lump-shaped portion is a lump-shaped portion of choroidal vasculature.
8. The image processing method of claim 7, wherein the line-shaped portion is a line-shaped portion of a vortex vein, and the lump-shaped portion is a vortex vein bulge portion.
9. The image processing method of any one of claim 1, wherein the line emphasis processing including discriminating that a local structure in the fundus image is a line.
10. The image processing method of any one of claim 1, wherein extracting the lump-shaped portion including extracting an area of a specific number of contiguous pixels having a specific luminance value as the lump-shaped portion.
11. An image processing method comprising: acquiring a fundus image; extracting a line-shaped portion of vasculature from a first processing image generated by line emphasis processing on the fundus image and followed by binarization processing; extracting a lump-shaped portion of vasculature from a second processing image generated by binarization processing on the fundus image; and integrating an image of the extracted line-shaped portion from the first processing image together with an image of the extracted lump-shaped portion from the second processing image to generate a vascular image in which blood vessels have been made visible.
12. The image processing method of claim 11, wherein the fundus image is a grayscale image, and the vascular image is a binarized image.
13. The image processing method of claim 11, wherein the vascular image is a choroidal vascular image in which a choroidal vasculature has been made visible.
14. The image processing method of claim 13, wherein the line-shaped portion is a line-shaped portion of the choroidal vasculature.
15. The image processing method of claim 13, wherein the lump-shaped portion is a bulge portion of the choroidal vasculature.

16. An image processing method comprising: acquiring a fundus image including a choroidal vasculature; extracting a line-shaped portion of choroidal vasculature from a first processing image generated by line emphasis processing on the fundus image; extracting a lump-shaped portion of choroidal vasculature from a second processing image generated by binarization processing on the fundus image; and integrating an image of the extracted line-shaped portion from the first processing image together with an image of the extracted lump-shaped portion from the second processing image to generate a choroidal vascular image configured by the line-shaped portion and the lump-shaped portion.

17. The image processing method of claim 16, wherein the fundus image is an image acquired by a scanning laser ophthalmoscope.

18. The image processing method of claim 16, wherein the fundus image is a face-on image by an angiographic method using optical coherence tomography.
