

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12413699
B2
September 09, 2025
Liu; Lilin et al.

Near-eye display module, I-type composite display module, II-type composite display module, and III-type composite display module based on pixel-block-aperture structures

Abstract

The invention discloses a near-eye display module based on pixel-block-aperture structures, which includes more than one pixel-block-aperture structures. The divergence angle and propagation direction of the light beam from a pixel is specially modulated, and the light beams from pixels of adjacent pixel-block-aperture structures are endowed with different orthogonal characteristics, to guarantee the light beam from a pixel transmitting to the viewer's pupil only through corresponding aperture(s) for Maxwellian View or one-pupil-multi-view display. The arrangement of multiple pixel-block-aperture structures makes a large field of view (FOV) realizable, and the orthogonal-characteristics design can suppress the crosstalk between adjacent pixel-block-aperture structures effectively.

Inventors: Liu; Lilin (Guangdong, CN), Teng; Dongdong (Guangdong, CN)
Applicant: SUN YAT-SEN UNIVERSITY (Guangdong, CN)
Family ID: 76161672
Assignee: SUN YAT-SEN UNIVERSITY (Guangdong, CN)
Appl. No.: 17/832717
Filed: June 06, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220311993 A1	Sep. 29, 2022

Foreign Application Priority Data

CN	201911243039.5	Dec. 06, 2019
----	----------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/CN2019/126813 20191220 PENDING child-doc US 17832717

Publication Classification

Int. Cl.: G02B30/52 (20200101); H04N13/339 (20180101); H04N13/344 (20180101);
H04N13/363 (20180101); H04N13/398 (20180101)

U.S. Cl.:

CPC H04N13/344 (20180501); G02B30/52 (20200101); H04N13/339 (20180501);
H04N13/363 (20180501); H04N13/398 (20180501);

Field of Classification Search

CPC: H04N (13/344); H04N (13/339); H04N (13/363); H04N (13/398); G02B (30/52)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2019/0204600	12/2018	Ha et al.	N/A	N/A
2022/0174263	12/2021	Teng et al.	N/A	N/A
2024/0272431	12/2023	Futterer	N/A	G02B 6/0016

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103376551	12/2012	CN	N/A
104104934	12/2013	CN	N/A
205450447	12/2015	CN	N/A
106873170	12/2016	CN	N/A
207318860	12/2017	CN	N/A
20190010095	12/2018	KR	N/A
2017186020	12/2016	WO	N/A

OTHER PUBLICATIONS

CN 205450447 U machine translation (Year: 2016). cited by examiner
“International Search Report (Form PCT/ISA/210) of PCT/CN2019/126813”, mailed on Sep. 2,
2020, with English translation thereof, pp. 1-4. cited by applicant

Primary Examiner: Dudek; James A

Attorney, Agent or Firm: JCIPRNET

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a continuation of international application of PCT application serial no. PCT/CN2019/126813, filed on Dec. 20, 2019, which claims the priority benefit of China application no. 201911243039.5 filed on Dec. 6, 2019. The entirety of each of the above-mentioned patent applications is hereby incorporated by reference herein and made a part of this specification.

TECHNICAL FIELD

(1) The invention relates to the technical field of three-dimensional display, and more particularly, to a near-eye display module based on pixel-block-aperture structures.

BACKGROUND

(2) As a potential next-generation mobile terminal platform, the three-dimensional display system including VR/AR is a hot spot in the display field at present, and has extremely broad application prospects. However, most of existing three-dimensional displays are based on the conventional stereoscopic technology. Employing two eyepieces for two eyes of a viewer, two different perspective views are projected to two pupils of the viewer, respectively. Then through the intersection of two eyes' visual directions, 3D depth is perceived by the viewer's brain. During this process, an eye's focus should keep being fixed at the pixels or their images for clear perspective views, which results in the inconsistency between the focusing distance and the converging distance, often called as Vergence-Accommodation Conflict (VAC conflict) problem. The VAC conflict induces visual discomforts to the viewer, especially in the case of near-eye displays. It is the bottleneck problem that hinders the popularization and application of 3D display.

(3) Researchers are working hard to settle the VAC problem along multiple technical approaches. Maxwellian view (US2019/0204600, AUGMENTED REALITY OPTICS SYSTEM WITH PINPOINT MIRROR) and one-pupil-multi-view (PCTCN2017080874, THREE-DIMENSIONAL DISPLAY SYSTEM BASED ON DIVISION MULTIPLEXING OF VIEWER'S ENTRANCE-PUPIL AND DISPLAY METHOD) are two of them capable of being applied to near-eye display. The former takes an aperture smaller than the viewer's pupil as a window for each eye, confining the light intensity gradient of the perceived light beams by the small size of the aperture. Thus focusing of the eye gets free from the pixels or their images, and the intercoupling between binocular convergence and monocular accommodation drags the eye's focus to the converging depth, resulting in VAC-free display. However, small aperture induces a small field of view (FOV) when only one aperture is employed. For a larger FOV, multiple apertures are often employed, with different apertures corresponding to different display zones of the display screen, respectively. However, in this case, light from a display zone often reaches to the pupil through non-corresponding apertures as crosstalk noise. The later, one-pupil-multi-view display, projects two or more perspective views with different viewpoints to a pupil of the viewer. For a displayed point, two or more passing-through light beams from the perceived perspective views superimpose into a spatial light spot. When the superimposed light spots are more attractive to the viewer's focusing than the pixels or their images, the viewer's eye will be dragged to focus at the displayed superimposed light spots naturally. Thus, for a displayed point, two or more passing-through light beams should be perceived by an eye through different segments of its pupil. That is to say, a light beam from a displayed point covers an area smaller than the pupil's size at least along one direction. When this kind of small footprint of a light beam on the pupil gets implemented by physical aperture near to the eye, a problem of small FOV gets confronted by the display too. As described in PCT/CN2017/080874, the introduction of multiple apertures of timing characteristics can enlarge the FOV. But the degree of timing multiplexing is severely limited by the frame rate of the on-shelf display devices, which is not enough for a large enough FOV.

SUMMARY

(4) The present invention is designed for a near-eye display module based on pixel-block-aperture structures, which is simply called as display module. Two such display modules can function as

two eyepieces for two eyes of a viewer, to build a head-mounted VR or AR system. In the proposed display module, multiple pixel-block-aperture structures are aligned for a large FOV, different orthogonal characteristics are endowed to adjacent pixel-block-aperture structures for crosstalk suppression. Then following the display technology route of Maxwell view or one-pupil-multi-view, a VAC-free display with large FOV can get implemented.

(5) The invention provides a near-eye display module based on pixel-block-aperture structures, comprising:

(6) M pixel-block-aperture structures, each of which being constructed by mutually corresponded a pixel block, an aperture, a modulation component, an orthogonality generating component and an orthogonality detecting component, wherein a positive integer $M \geq 2$; wherein, a pixel block is composed of pixels for optical information loading, and a pixel array is composed of the pixels of all pixel blocks of the M pixel-block-aperture structures; an aperture array is composed of all apertures of M pixel-block-aperture structures on an aperture surface; a modulation component is composed of modulation elements, which correspond to pixels of a corresponding pixel block in a one-to-one manner, to guide the light beam from a pixel to a corresponding aperture with a confined diverging angle; an orthogonality detecting component is attached to a corresponding aperture, for only allowing light of corresponding orthogonal characteristic passable, but blocking light of other non-corresponding orthogonal characteristic; the orthogonality generating component of each block-aperture structures is attached to a corresponding pixel block, endowing pass-through light with orthogonal characteristic same to that of a corresponding orthogonality detecting component; a control device, which loads optical information onto a pixel at a time-point, with the optical information being the projecting information of a 3D scene to be displayed at the time-point along a line connecting the pixel and its corresponding aperture; said near-eye display module based on pixel-block-aperture structures is configured that the N orthogonality detecting components of adjacent N pixel-block-aperture structures are with N kinds of orthogonal characteristics respectively, with the apertures attached by orthogonality generating components of a same orthogonal characteristic taken as apertures of a same kind, wherein an integer $M \geq N \geq 2$, and the light beam from a pixel is modulated by a corresponding modulation element, to guarantee its light distribution covers the corresponding aperture, but misses the non-corresponding apertures of the same kind.

(7) Further, the near-eye display module further comprises a projection device, which projects an enlarged virtual image of the pixel array to a projection surface, with the virtual image called as a pixel-array image; wherein, optical information loaded onto a pixel at a time-point is the projecting information of a 3D scene to be displayed at the time-point along a line connecting the virtual image of the pixel and its corresponding aperture, with the virtual image of a pixel called as a pixel image, and light beam from a pixel can be equivalently seen as being from its virtual image on the projection surface;

(8) Further, the pixel-block-aperture structure further comprises a baffle, which blocks the light in the non-aperture zone.

(9) Further, the near-eye display module further comprises a relay device for guiding light from the pixel array to a corresponding pupil of a viewer; wherein, the modulation element makes light from a corresponding pixel miss non-corresponding apertures of the same kind.

(10) Further, a pixel-block-aperture structure further comprises a light splitting device, which is attached to the corresponding pixel block and guides light from G groups of pixels of the pixel block to G zones, respectively, wherein $G \geq 2$, and, G apertures covered by a corresponding orthogonality detecting component are placed in the G zones, respectively, with a pixel taking the aperture to which the light from the pixel is guided as the corresponding aperture, and the other (G-1) apertures as the non-corresponding apertures of a same kind.

(11) Further, a size of the aperture is smaller than that of a viewer's pupil.

(12) Further, a viewer's pupil perceives light beams through at least 2M apertures, and a size of the

aperture is smaller than that of a viewer's pupil along their arrangement direction.

(13) Further, light beam from a pixel missing a non-corresponding aperture refers to that the transmission light intensity of the light beam through the non-corresponding aperture is less than 10% of that through the corresponding aperture.

(14) Further, an aperture can be transmission-type or reflection-type.

(15) Further, the aperture has a phase modulation function for projecting an image of the corresponding pixel block which is named as an equivalent pixel block, and coverage angles of all the equivalent pixel blocks with respect to a point around the sub-apertures splice together seamlessly.

(16) Further, all equivalent pixel blocks are divided into two or more groups, and for each group of equivalent pixel blocks, the coverage angles of the group of equivalent pixel blocks with respect to a point around the sub-apertures splice together seamlessly.

(17) Further, the orthogonal characteristics are two linear polarizations with mutually perpendicular polarization directions, or two circular polarizations of left circular polarization and right left circular polarization, or timing characteristics being activated at different time-points, or combination of linear polarizations and timing characteristics, or combination of circular polarizations and timing characteristics; wherein, timing characteristics get implemented by a light-valve array, whose light valves are attached to the apertures in a one-to-one manner, for activating the aperture by turning on a corresponding light valve, and the function of an orthogonality generating device gets implemented by the control device, activating corresponding pixels by loading corresponding optical information when the aperture gets turned on.

(18) Further, the projection device is an optical device with adjustable focal length; wherein, the projection device is driven by the control device to generate multiple projection surfaces to different depths sequentially, with a pixel getting refreshed by projection optical information of the 3D scene to be displayed along the line connecting its virtual image and corresponding aperture synchronously; or, the convergence depth of the viewer is real-time tracked by an external auxiliary device, and the projection device projects a projection surface to the convergence depth driven under the control device synchronously, with a pixel getting refreshed by projection optical information of the 3D scene to be displayed along the line connecting its virtual image and corresponding aperture.

(19) Further, the projection device is a liquid crystal lens with adjustable focal length, or an assembly of multiple liquid crystal sheets; wherein, the assembly produces different focal lengths by activating different liquid crystal sheets or different combinations of the liquid crystal sheets.

(20) Further, the relay device is a light-deflection device, to deflect the propagation direction of incident light beams.

(21) Further, the relay device is a beam-path-folding structure for a thin structure.

(22) Further, the relay device is an optical wave-guide device.

(23) Further, the near-eye display module further comprises a compensation device inserted between the relay device and the external environment, for neutralizing the impact of the relay device on the light from the external environment.

(24) Further, each aperture is replaced by J sub-apertures respectively, wherein an integer $J \geq 2$; said near-eye display module based on the pixel-block-aperture structures is configured that, at one time-point of J time-points in a time-period δt , only one sub-aperture corresponding to each replaced aperture is turned on, with a pixel taking the turned-on sub-aperture of its replaced corresponding aperture as the corresponding sub-aperture at the time-point, and at J time-points in a time-period, J sub-apertures of a replaced aperture are turned on sequentially; wherein, at each time-point, a corresponding pixel gets refreshed by the projection information of the 3D scene to be displayed along the line connecting the virtual image of the pixel and its corresponding sub-aperture.

(25) Further, a size of the sub-aperture is smaller than that of the viewer's pupil.

- (26) Further, a viewer's pupil perceives light beams through at least $2M$ sub-apertures, and a size of the sub-aperture is smaller than a diameter of the viewer's pupil along their arrangement direction.
- (27) Further, wherein the sub-aperture has phase modulation function for projecting a virtual image of the corresponding pixel block, wherein the virtual image of the corresponding pixel block is named as equivalent pixel block, and at a time-point the coverage angles of equivalent pixel blocks with respect to a point around the sub-apertures splice together seamlessly.
- (28) Further, each sub-aperture of each pixel-block-aperture structure has phase modulation function to image corresponding pixel block to different depth positions.
- (29) The present application also provides another solution as below.
- (30) An I-type composite display module based on pixel-block-aperture structures, comprising K near-eye display modules based on the pixel-block-aperture structures as mentioned above, with the K pixel-array images overlapped into a projection area on the projection surface, wherein an integer $K \geq 2$; wherein, K near-eye display modules based on pixel-block-aperture structures function as K element modules.
- (31) Further, a size of the aperture is smaller than that of the viewer's pupil.
- (32) Further, a viewer's pupil perceives light beams through at least $2M$ apertures, and a size of the aperture is smaller than the diameter of the viewer's pupil along the arrangement direction of the apertures.
- (33) Further, each aperture is replaced by J sub-apertures respectively, wherein an integer $J \geq 2$; said I-type composite display module based on pixel-block-aperture structures is configured that, at one time-point of J time-points in a time-period δt , only one sub-aperture corresponding to each replaced aperture is turned on, with a pixel taking the turned-on sub-aperture of its replaced corresponding aperture as the corresponding sub-aperture at the time-point, and at J time-points of a time-period, J sub-apertures of a replaced aperture are turned on sequentially; wherein, at each time-point, a corresponding pixel gets refreshed by the projection information of the 3D scene to be displayed along the line connecting the virtual image of the pixel and the corresponding sub-aperture.
- (34) Further, each sub-aperture of each pixel-block-aperture structure has a phase modulation function for imaging a corresponding pixel block to a corresponding depth position.
- (35) The present application also provides another solution as below.
- (36) An II-type composite display module based on pixel-block-aperture structures, comprising K near-eye display modules based on the pixel-block-aperture structures as mentioned above, with the K pixel-array images splicing together, wherein an integer $K \geq 2$; wherein, K near-eye display modules based on the pixel-block-aperture structures function as K element modules.
- (37) Further, an aperture is replaced by J sub-apertures, wherein an integer $J \geq 2$; said II-type composite display module based on the pixel-block-aperture structures is configured that, at one time-point of J time-points in a time-period δt , only one sub-aperture corresponding to each replaced aperture is turned on, with the pixel taking the turned-on sub-aperture of the replaced corresponding aperture as corresponding sub-aperture at the time-point, and at J time-points in a time-period, J sub-aperture of a replaced aperture are turned on sequentially; wherein, at each time-point, a corresponding pixel gets refreshed by the projection information of the 3D scene to be displayed along the line connecting the virtual image of the pixel and the corresponding sub-aperture.
- (38) The present application also provides another solution as below.
- (39) An III-type composite display module based on pixel-block-aperture structures, which comprises K near-eye display modules based on the pixel-block-aperture structures as mentioned above, with the K pixel-array images positioning at different depths, respectively, where in an integer $K \geq 2$; wherein, K near-eye display modules based on the pixel-block-aperture structures function as K element modules.
- (40) Further, an aperture is replaced by J sub-apertures, wherein an integer $J \geq 2$; said III-type

composite display module based on pixel-block-aperture structures is configured that, at one time-point of J time-points in a time-period δt , only one sub-aperture of each replaced aperture is turned on, with a pixel taking the turned-on sub-aperture of its replaced corresponding aperture as the corresponding sub-aperture at the time-point, and at J time-points of a time-period, J sub-apertures of a replaced aperture are turned on sequentially; wherein, at each time-point, a corresponding pixel gets refreshed by the projection information of the 3D scene to be displayed along the line connecting the virtual image of the pixel and the corresponding sub-aperture.

(41) Further, an aperture is replaced by a backlight structure correspondingly; wherein, a backlight structure projects light of orthogonal characteristic which can be modulated by the corresponding pixel block, but be blocked by the pixel blocks of orthogonal characteristics different to that of the corresponding pixel block, and on a plane near the pupil, the light from a backlight structure covers a region same to the region covered by the light from the corresponding pixel block through the replaced aperture.

(42) Further, a sub-aperture is replaced by a backlight structure correspondingly; wherein, a backlight structure projects light of orthogonal characteristic which can be modulated by the corresponding pixel block, but be blocked by the pixel blocks of orthogonal characteristics different to that of the corresponding pixel block, and on a plane near the pupil, the light from a backlight structure covers a region same to the region covered by the light from the corresponding pixel block through the replaced sub-aperture.

(43) Compared with existing near-eye 3D display, the merits of the present invention are listed as follow.

(44) This invention designs pixel-block-aperture structures, which project light beams to the viewer's eye only through corresponding small size apertures. Multiple such pixel-block-aperture structures constitute a display module for Maxwellian view display or one-pupil-multi-view display, which is free from VAC-conflict. In the proposed display module, multiple pixel-block-aperture structures are aligned for a large FOV, different orthogonal characteristics are endowed to adjacent pixel-block-aperture structures for crosstalk suppression.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 shows an optical structure of a pixel-block-aperture structure with transmission-type apertures.

(2) FIG. 2 shows the schematic diagram of a display module in which a pixel block projects light only through the corresponding aperture.

(3) FIG. 3 shows the orthogonal characteristics designing of a two-dimensional arranged aperture array.

(4) FIG. 4 shows apertures of timing characteristics.

(5) FIG. 5 shows an arrangement of pixel-block-aperture structures with light splitting devices.

(6) FIG. 6 shows a pixel-block-aperture structure with reflection-type apertures.

(7) FIG. 7 shows an example of a display module with transmission-type apertures.

(8) FIG. 8 shows a display module implementing Maxwellian view display.

(9) FIG. 9 illustrates the display principle of one-pupil-multi-view display.

(10) FIG. 10 illustrates the display principle of Maxwellian view display.

(11) FIG. 11 shows the pixel sub-groups of a pixel block.

(12) FIG. 12 shows an example of a display module with reflection-type apertures.

(13) FIG. 13 is a display module with equivalent pixel blocks.

(14) FIG. 14 shows a projection surface **100** projected by a projection device with an adjustable focus.

- (15) FIG. 15 shows another projection surface **100'** projected by a projection device with an adjustable focus.
- (16) FIG. 16 shows a display module with a mirror or a semi-transparent mirror working as the relay device.
- (17) FIG. 17 is a free-form surface device working as the relay device.
- (18) FIG. 18 shows another spatial relationship between the projection device and relay device.
- (19) FIG. 19 shows a display module with a beam-path-folding structure functioning as the relay device.
- (20) FIG. 20 shows a beam-path-folding structure allowing light from external ambient passing through.
- (21) FIG. 21 shows another beam-path-folding structure.
- (22) FIG. 22 shows a display module with an optical wave-guide device functioning as the relay device.
- (23) FIG. 23 shows the different exiting positions of light beams with different incident positions in an optical wave-guide device.
- (24) FIG. 24 shows an optical wave-guide device with the coupling-out element being constructed by multiple reflection-type coupling-out areas and the display module thereof.
- (25) FIG. 25 shows another spatial position for the orthogonality detecting component in a display module, which adopts a wave-guide-type relay device with discrete distributed reflection-type coupling-out areas.
- (26) FIG. 26 shows an optical configuration of a composite display module.
- (27) FIG. 27 shows a projection device which is integrated into the apertures.
- (28) FIG. 28 shows a pixel-block-aperture structure with sub-apertures.
- (29) FIG. 29 shows the viewing zone for Maxwellian view display through a group of sub-aperture.
- (30) FIG. 30 shows another viewing zone for Maxwellian view display through another group of sub-apertures.
- (31) FIG. 31 shows a displayed point overlapped by light beams from pixels that are imaged to different depths.
- (32) FIG. 32 shows a case of projecting a perspective view through a group of sub-apertures at a time-point for one-eye-multi-view display.
- (33) FIG. 33 shows another case of projecting another perspective view through another group of sub-apertures at another time-point for one-eye-multi-view display.
- (34) FIG. 34 shows a case of projecting a perspective view to a depth through a group of sub-apertures at a time-point.
- (35) FIG. 35 shows another case of projecting another perspective view to another depth through another group of sub-apertures at another time-point.
- (36) FIG. 36 shows the pixel blocks of pixel-block-aperture structures aligned along a curve.
- (37) FIG. 37 shows the schematic diagram of a display module without a projection device.
- (38) FIG. 38 shows the display principle of a display module without the projection device.
- (39) FIG. 39 shows the replaced aperture and an example of a backlight structure.
- (40) FIG. 40 shows another example of a backlight structure.
- (41) FIG. 41 shows a third example of a backlight structure.

DETAILED DESCRIPTION

(42) The drawings are only for illustrative purposes, and should not be construed as limitations on the present application. In order to better illustrate this embodiment, some components of the drawings may be omitted, enlarged or reduced, and do not represent the size of the actual product. As far as people are concerned, it is understandable that some well-known structures, repetitive structures in the drawings and related descriptions may be omitted. The invention designs a kind of pixel-block-aperture structures with characteristics that light beams from a pixel block are designed to only transmit through corresponding aperture(s) of small size. Multiple such pixel-block-

aperture structures constitute a near-eye display module for FOV-enlarged Maxwellian view or one-pupil-multi-view display, with adjacent pixel-block-aperture structures being endowed with different orthogonal characteristics for effective crosstalk suppression. Such near-eye display module based on pixel-block-aperture structures is abbreviated as a display module in the present application. Two display modules work as two eye-pieces of 3D display systems such as head-mounted VR/AR. The technical solution of the present invention will be further described below with reference to the accompanying drawings and embodiments.

Embodiment 1

(43) The optical structure of a pixel-block-aperture structure **10** is shown in FIG. 1, which includes a pixel block **11**, an aperture **12**, a modulation component **13**, an orthogonality generating component **14**, an orthogonality detecting component **16**, and a baffle **15**. Different components of a same pixel-block-aperture structure **10** correspond to each other. The pixel block **11** is composed of pixels, such as pixels p.sub.i1, P.sub.i2, p.sub.i3, p.sub.i4, p.sub.i5, . . . in FIG. 1. Each pixel gets refreshed with optical information by a control device **40**. The aperture **12** allows incident light to pass through under the turned-on state. The orthogonality detecting component **16** is attached to the corresponding aperture **12**, to allow only light with corresponding orthogonal characteristic passing through, but block light with anyone of other $N-1$ orthogonal characteristics. In the present application, taking the function of the orthogonality detecting component **16** into consideration, it is equivalently described that an aperture only permits light of corresponding characteristic passing through. Here, an integer $N \geq 2$. For example, linear polarizations with mutually perpendicular polarization directions can be taken as $N=2$ orthogonal characteristics, circular polarizations of left circular polarization and right circular polarization can be taken as $N=2$ orthogonal characteristics, sequential activating of $N \geq 2$ apertures at $N \geq 2$ time-points can be taken as $N \geq 2$ orthogonal characteristics. The orthogonality generating component **14** is attached to the corresponding pixel block **11**, to make its pixels project light of orthogonal characteristic capable passing through the corresponding aperture **12**. The baffle **15** is placed on the aperture surface **200** containing the aperture **12** for blocking light in the non-aperture area. A modulation component **13** consists of modulation elements. These modulation elements correspond to pixels of the corresponding pixel block **11** in a one-to-one manner, to guide the light beam from a pixel to a corresponding aperture **12** with a confined diverging angle and along a specific direction. As shown in FIG. 1, the modulation elements g.sub.i1, g.sub.i2, g.sub.i3, g.sub.i4, g.sub.i5, . . . correspond to the pixels p.sub.i1, p.sub.i2, p.sub.i3, p.sub.i4, p.sub.i5, . . . , respectively. A modulation element modulates the diverging angle and propagation direction of the light beam from a corresponding pixel. Optimally, an aperture **12** is placed parallel to the corresponding pixel block **11**. In FIG. 1, the aperture **12** being parallel to the x-y plane should be drawn as a line. For denoting its shape more directly, the aperture **12** is drawn as an ellipse in FIG. 1.

(44) M pixel-block-aperture structures are aligned side by side in FIG. 2, here $M=5$ is taken as an example. The complete structures of three pixel-block-aperture structures **10**, **10'**, **10''** are shown in the FIG. 2. For clarity, the other two pixel-block-aperture structures **10'''**, **10''''** are only partially drawn. Their apertures **12**, **12'**, **12''**, **12'''**, **12''''** constitute an aperture array **120** at the aperture surface **200**, and the corresponding pixel blocks **11**, **11'**, **11''**, **11'''**, **11''''** constitute a pixel array **110**. Among all the $M=5$ pixel-block-aperture structures, the orthogonality detecting components of adjacent N pixel-block-aperture structures are designed with N different orthogonal characteristics, respectively, wherein the orthogonality detecting components of adjacent N pixel-block-aperture structures corresponding to the N different orthogonal characteristics in a one-to-one manner. An orthogonality detecting component only allows light of corresponding orthogonal characteristic passing through, but blocks light of anyone of other $(N-1)$ orthogonal characteristics. FIG. 2 takes $N=2$ as example, concretely linear polarization along the horizontal x-direction and the linear polarization along the vertical y-direction, respectively. They are denoted as “ custom character” light and “•” light in the present application, respectively. In FIG. 2, the generating and detecting of

the “ custom character” light and “•” light can get implemented by physical polarizers. Of course, the light emitted from each pixel can have the corresponding polarization state. Concretely, light from the pixel blocks **11'** and **11''** propagates forward as “•” light after passing through their orthogonality generating components **14'** and **14''** respectively, and their corresponding orthogonality detecting components **16'** and **16''** permit “•” light passing through, but block “ custom character” light. Light from the pixel blocks **11**, **11'''** and **11''''** propagates forward as “ custom character” light after passing through their orthogonality generating components **14**, **14'''** and **14''''** respectively, and their corresponding orthogonality detecting components **16**, **16'''** and **16''''** permit “ custom character” light passing through, but block “•” light. Thus, an aperture attached by corresponding orthogonality detecting component permits light from corresponding pixel block passing through, but blocks light from adjacent $N-1=1$ pixel block from both sides. More concretely, the light from pixels of pixel block **10**, such as that from the pixel p.sub.i1, can pass through the corresponding aperture **12** which is denoted as light beam **1** in FIG. 2. But the light from the pixel p.sub.i1 is blocked by apertures **12'** and **12''**, which is denoted as light beam **2** and light beam **3**. Obviously, an aperture itself is transparent at the turned-on state. But taking the function of corresponding orthogonality detecting component into consideration, it is equivalently described that an aperture only permits light of corresponding characteristic passing through. Sentences such as “light of an orthogonal characteristic can pass through an aperture”, “light of an orthogonal characteristic cannot pass through an aperture”, “an aperture allows light of an orthogonal characteristic passing through”, “an aperture does not allow light of an orthogonal characteristic passing through” are often used in the following segment of the present application.

(45) In FIG. 2, $M=5$ pixel-block-aperture structures are arranged along one-dimensional x-direction. This arrangement can be extended to two-dimensional directions. However, the difference lies in that when pixel-block-aperture structures are arranged along two-dimensional directions, the number of apertures adjacent to an aperture changes from 2 (in the case of one-dimensional arrangement) to more, such as 8 apertures adjacent to the center aperture shown in FIG. 3. With only linear polarization along the horizontal x-direction and linear polarization along the vertical y-direction as the orthogonal characteristics, for an aperture, light from those pixel blocks adjacent to its corresponding pixel blocks cannot be designed to be all blocked by this aperture. Such as FIG. 3, when the apertures denoted by “?” correspond to orthogonal characteristic “ custom character” adjacent two apertures along x-direction or along the y-direction may allow light of a same orthogonal characteristic passing through. When the apertures marked by “?” correspond to orthogonal characteristic “•”, adjacent two apertures along a diagonal direction may allow light of a same orthogonal characteristic passing through. Thus, only $N=2$ available orthogonal characteristics cannot guarantee the requirement that an aperture blocks light from pixel blocks whose corresponding apertures being adjacent to this aperture. To solve this problem, the apertures marked by “?” need to be endowed with a third orthogonal characteristic, such as a timing orthogonal characteristic. FIG. 4 is drawn for explaining the timing orthogonal characteristics. A light-valve array **17** is attached to the aperture array **120**, with its light valves corresponding to the apertures in a one-to-one manner. A light valve functions as the orthogonality detecting component to the corresponding aperture. At time-point t , the light valves corresponding to the apertures **12'** and **12''** get turned on, with the light valve corresponding to the aperture **12** being turned off. At time-point $t+\Delta t/N=t+\Delta t/2$, the apertures **12'** and **12''** get turned off, while the aperture **12** is turned on. At time-point t , the pixel blocks **11'** and **11''** corresponding to the turned-on apertures **12'** and **12''** get refreshed by corresponding optical information, with the pixel blocks **11** corresponding to the turned-off aperture **12** inactivated. Then, at this time-point, light from the pixel blocks **11'** and **11''** cannot pass through the non-corresponding aperture **12**, and no light from the inactivated pixel block **11** reaches to the non-corresponding apertures **12'** and **12''**. Similarly, at the time-point $t+\Delta t/N=t+\Delta t/2$, light from the pixel blocks **11** cannot pass through the non-corresponding aperture **12'** and **12''**, and no light from the inactivated pixel block **11'** and **11''**

reaches to the aperture **12**. Thus, $N=2$ timing characteristics get implemented. The turning-on and turning-off of a light valve keep a period of time, called a time frame. The orthogonality generating component corresponding to an orthogonality detecting component can be implemented by a light valve, or by activating or inactivating the corresponding pixel block.

(46) The design of different orthogonal characteristics to adjacent N orthogonality detecting components can make an aperture blocking light from $N-1$ non-corresponding pixel blocks of $N-1$ adjacent pixel-block-aperture structures. However, when the number M of pixel-block-aperture structures is greater than the number N of adopted orthogonal characteristics, there exist apertures of a same orthogonal characteristic in the display module, which allow light from non-corresponding pixel block(s) passing through. As shown in FIG. 2, the apertures **12'** and **12''** both allow “•” light passing through, the apertures **12**, **12'''** and **12''''** all allow “custom character” light passing through. The apertures, attached by corresponding orthogonality detecting components and permitting light of a same characteristic passing through, are taken as apertures of a same kind. In FIG. 2, the apertures **12'** and **12''** are of a same kind, the apertures **12**, **12'''**, and **12''''** are of another same kind. When the divergence angle of a beam light from a pixel is large, it can reach to a non-corresponding aperture belong to a same kind and pass through it as noise. As shown in FIG. 2, the light from the pixel block **11** can pass through the apertures **12'''** and **12''''** of the same kind with “custom character” as the corresponding orthogonal characteristic. For the timing characteristic, the apertures turned-on at a same time-point are of a same kind. For example, the apertures **12'** and **12''** in FIG. 4 are of a same kind, and the aperture **12** is of another kind. If the orthogonal characteristics are hybrid, for example, the hybrid orthogonal characteristics of the linear polarizations and the timing characteristics, the apertures of the same linear polarization and the same timing characteristic are of a same kind. Concretely, two apertures being turned on at a same time-point are not of a same kind if they are with different linear polarizations. It is unnecessary to consider the crosstalk of light beams passing through non-corresponding aperture(s) of a same kind, when the crosstalk does not reach to the observing zone for the pupil **50**. Actually, due to different orthogonal characteristics between adjacent apertures, there exists an observing zone free from this kind of noise. The noise discussed above can not reach to this zone. When this zone is not large enough for a comfortable viewing experience, a modulation component **13** can be introduced into a pixel-block-aperture structure **10** for suppressing the noise discussed above. The modulation component **13** is composed of modulation elements, which correspond to pixels of a corresponding pixel block **11** in a one-to-one manner. A modulation element modulates the diverging angle or/and propagation direction of the light beam from the corresponding pixel. As exemplified by FIG. 2, after being modulated by the corresponding modulation element $g_{sub.i1}$, the projected light beam from pixel $p_{sub.i1}$ points to the corresponding aperture **12** along the line 1, with no light intensity covering non-corresponding apertures **12''** and **12''''** of the same kind, which defines a maximum transmission angle with an included angle β between dotted lines 4 and 5. The dotted lines 4 and 5 are the lines connecting pixel $p_{sub.i1}$ and nearer marginal points of non-corresponding apertures **12''** and **12'''** of the same kind. Optimally, the line 1 is consistent with the principal ray of the projected light beam. It is noteworthy that “with no light intensity covering non-corresponding apertures of the same kind” does not mean a light intensity of 0. For the light beam from a pixel, after being modulated by the corresponding modulation element, when the transmitted light intensity through a non-corresponding aperture of the same kind is less than 10% of that through the corresponding aperture, the crosstalk will not bring severe effect on the display quality, and we take it as “with no light intensity covering non-corresponding apertures of the same kind” in the present application. Under this condition, the actual maximum transmission angle of the light beam from pixel $p_{sub.i1}$ is larger than β , as shown in FIG. 2. Micro-gratings, micro-lenses, micro-prisms, and micro-apertures, et al., all can be taken as the physical device of a modulation element. Generally speaking, a pixel is rather small, the corresponding modulation element is also small. So, here “micro-” does not refer to a specific scale, but an abstract pronoun used to name the physical

device of a modulation element. Taking a micro-aperture as an example, the change of its position relative to the corresponding pixel along arrangement direction of the pixels will change the propagation direction of the light from this corresponding pixel when it passes through this micro-aperture. And, different sizes of this micro-aperture will result in different transmission angles. The modulated light beam from a pixel may point to the corresponding aperture along a non-principal ray. The modulation component **13** can make the light beams from corresponding pixel block **11** propagate forward only through corresponding aperture. If only the propagation direction, or only the transmission angle needs to be modulated for guiding light from a pixel only passing through corresponding aperture, of course it belongs to the protection scope of the present application.

Furthermore, the modulation components are not necessary when a noise-free observing zone for the pupil, which is resulted from the design of orthogonal-characteristics, is large enough for the pupil. Furthermore, the modulation element also can be integrated into corresponding pixel.

(47) The baffles can be placed around corresponding apertures, such as the baffles **15**, **15'** and **15''** in FIG. **4**, to block the light in the non-aperture area.

(48) Thus, a significant characteristic of the said M pixel-block-aperture structures lies in that, light from the pixel block **11** of a pixel-block-aperture structure **10** can propagate forward through the corresponding aperture **12**, but be blocked by or pass at low transmittance through apertures of other pixel-block-aperture structures. The low transmittance here means that, the light from a pixel is with an actual transmittance to the non-corresponding aperture of a same kind in other pixel-block-aperture structures, but this transmittance is less than 10% of that to the aperture corresponding to this pixel. Said low transmittance is expressed as being blocked by non-corresponding apertures of the same kind in the present application.

(49) A pixel-block-aperture structure can further include a light splitting device **18**. As shown in FIG. **5**, in a pixel-block-aperture structure **10**, a light splitting device **18** consisting of grating periodic structures along one direction or two directions is attached to the pixel block **11**. The light splitting device **18** guides light beams from G groups of pixels to G zones, respectively. One aperture is placed into each such zone. That is to say, a pixel-block-aperture structure **10** will be equipped with G apertures when a light splitting device **18** is introduced. Here, the integer $G \geq 2$. FIG. **5** takes a lenticular grating functioning as a light splitting device and $G=2$ as an example. Concretely, in the pixel-block-aperture structure **10**, its light splitting device **18** guides the light beams from pixels p.sub.i1, p.sub.i3, p.sub.i5, . . . to the zone containing an aperture **12a**, guides light beams from pixels p.sub.i2, p.sub.i4, . . . to the zone containing an aperture **12b**. The pixels p.sub.i1, p.sub.i3, p.sub.i5, . . . corresponding to the aperture **12a** constitute a pixel group, and the pixels p.sub.i2, p.sub.i4, . . . corresponding to the aperture **12b** constitute another pixel group. The orthogonality detecting component **16** covers both apertures **12a** and **12b**. The apertures **12a** and **12b** are apertures of a same kind, and they are also the apertures corresponding to the pixel block **11**. That is to say, the introduction of a light splitting device brings G corresponding apertures to a pixel block. But, there is one corresponding aperture for each pixel only, to which the light beam from this pixel is guided. The other (G-1) apertures of the pixel-block-aperture structure which includes this pixel, are also non-corresponding apertures of this pixel. The light splitting device **18** makes light from p.sub.i1, p.sub.i3, p.sub.i5, . . . having no light intensity distribution around the non-corresponding aperture **12b**, which belongs to the same kind as the corresponding aperture **12a**. Similarly, the light splitting device **18** makes light from p.sub.i2, p.sub.i4, . . . having no light intensity distribution around the aperture **12a**. The apertures **12a** and **12b** are placed adjacent to each other in FIG. **5**. In fact, when a light splitting device **18** is employed, apertures of adjacent pixel-block-aperture structures can also be interlaced with each other. A light splitting device **18** can also be other optical element, such as a micro-structure array consisting of micro-structure elements. The micro-structure elements correspond to the pixel or sub-pixel of the pixel array **110** in a one-to-one manner, to guiding light beam from a pixel or sub-pixel to corresponding aperture.

(50) In a pixel-block-aperture structure **10**, the modulation component **13** and the orthogonality

generating component **14** are both placed corresponding to the pixel block **11**. Their spatial positions are interchangeable. The aperture **12** and the orthogonality detecting component **16** can be on a common plane, or with one in the front and the other one at the back. In the above FIG. 1, FIG. 2, FIG. 4, and FIG. 5, the pixel array **110** and the aperture array **120** are both shown on a planar plane. They can also locate on a non-planar plane, even a pixel blocks can be non-planar. (51) In above FIG. 1, FIG. 2, FIG. 4, and FIG. 5, the transmission-type apertures are taken as the examples. They also can be reflection-type apertures, such as the aperture **12** shown in FIG. 6. (52) Along the projection direction of the light from the pixel array **110**, a projection device **20** is placed between the pixel array **110** and the aperture array **120**, or in front of the aperture array **120**, so to set up a near-eye display module based on pixel-block-aperture structures. In FIG. 7, a projection device **20** is placed between the pixel array **110** and the aperture array **120**. $M=4$ pixel blocks are designed in this display module. For example, a pixel block **11'**, an aperture **12'**, a modulation component **13'**, an orthogonality generating component **14'**, a baffle **15'**, and an orthogonality detecting component **16'** constitute a pixel-block-aperture structure **10'**. The projection device **20** images the virtual image of a pixel onto the projection surface **100**, to form a virtual image of this pixel block. The I.sub.11, I.sub.11', I.sub.11'', and I.sub.11''' shown in FIG. 8 are the virtual images of the pixel blocks **11**, **11'**, **11''**, **11'''** in FIG. 7. The virtual images of the pixel blocks constitute a virtual image of the pixel array **110**. Here, the projection device **20** is an imaging device, such as a lens, a group of lenses, a phase gratings or a phase plate. According to the object-image relationship, light from a pixel can equivalently be taken as from its virtual image, and light from a pixel block can equivalently be taken as from its virtual image.

(53) Optimally, the virtual images of all the pixel blocks are arranged with an equal interval D , the apertures are aligned by an equal interval d along the arrangement direction, and the lines with each connecting the center of a pixel block and the center of the corresponding aperture intersect at a point P.sub.r (which is not shown in FIG. 8). When the viewer's pupil **50** can receive all light beams with each coming from a pixel and passing through the corresponding aperture, that is to say, the geometric relationship shown in FIG. 8 satisfies

$$w_{sub.1} + 2w_{sub.2} \leq D_{sub.p} \quad (1),$$

the pupil **50** can receive all the information from the pixel array **110**. Here, $w_{sub.1}$ is the coverage size on the pupil **50** of two lines with each connecting the center point of the virtual image of a marginal pixel block and the center point of the corresponding aperture. $w_{sub.2}$ is the coverage size on the pupil **50** of two lines connecting two marginal points of a pixel block's virtual image with the center point of corresponding aperture. Here,

$$w_{sub.1} = \text{abs}(Ld + Rd - RD)(M - 1)/L \quad (2),$$

$$w_{sub.2} = RD/(2L) \quad (3).$$

(54) where, $\text{abs}()$ is an absolute value function, R denotes the distance of the viewer's pupil **50** to the aperture surface **200**, and L is the distance between the projection surface **100** and the aperture surface **200**. The above formulas are deduced with the size of an aperture being ignored. In the above process, the lines with each connecting the center of a pixel block and the center of the corresponding aperture also can not intersect at a point.

(55) In a Maxwellian view display, the light beam from a pixel has a small diverging angle within a certain depth range around this pixel or its image, which means a weak light intensity gradient along its propagation direction. Designing the size of an aperture smaller than that of the pupil **50**, light beams from the virtual image of a pixel array **110**, which is called as a pixel-array image, shown in FIG. 8, have small diverging angles when they reach to the pupil **50**. Thus, with a pixel-block-aperture structure of FIG. 7 as an eyepiece, two such eyepieces for two eyes of a viewer build up a VAC-free VR or AR display system based on Maxwellian view technology. In this process, the binocular convergence drives the focus of an eye following the convergence distance, under the premise that a light beam of small diverging angle has weak traction to the focus. The control device **40** refreshes the pixel array **110** synchronously, with the optical information loaded

on a pixel being the projecting information of the 3D scene to be displayed along the line connecting the virtual image of this pixel and its corresponding aperture **12**.

(56) In an above-mentioned display module, the modulation of the diverging angle and the propagation direction of the light beam from a pixel should take the projection device **20** into consideration. That is to say, a modulated light beam from a pixel should miss the non-corresponding apertures of the same kind in other pixel-block-aperture structures when the projection device exists. In the following part of the present application, when further components are inserted between the pixel array **110** and the aperture array **120**, their effects on the diverging angle and the propagation direction of a light beam should be taken into consideration, too.

(57) In FIG. 7 and FIG. 8, a light splitting device **18** can be introduced into a pixel-block-aperture structure **10**. In such a pixel-block-aperture structure **10**, the light splitting device **18** is attached to the corresponding pixel block **11**, and guides light from G groups of pixels of this pixel block **11** to G zones, respectively. Here, the integer $G \geq 2$. The light beam from a pixel is guided to the aperture placed in the corresponding zone. That is to say, in a pixel-block-aperture structure **10**, G apertures are placed in the G zone in a one-to-one manner, and pixels of different groups correspond to different apertures.

(58) In a pixel-block-aperture structure **10** without a light splitting device **18**, only one aperture exists. Under this condition, two display modules for two eyes of a viewer can implement Maxwellian view display, when the images on all the pixel blocks of a display module are perceived by the corresponding pupil through corresponding apertures. The introduction of the light splitting devices can bring more apertures to each light block-aperture structure, making one-pupil-more-view display implementable. As exemplified by the pixel-block-aperture structure **10** with $G=2$ shown in FIG. 9, the pixel images (. . . , I.sub.pi1, I.sub.pi2, I.sub.pi3, I.sub.pi4, I.sub.pi5, I.sub.pi6, . . .) on the projection surface **100** constitute the virtual image I.sub.11 of the pixel block **11**. A light splitting device **18** guides the equivalent light beams from the pixel images . . . , I.sub.pi1, I.sub.pi3, I.sub.pi5, I.sub.pi7, I.sub.pi9, . . . to an aperture **12a**, and guides the equivalent light beams from the pixel images . . . , I.sub.pi2, I.sub.pi4, I.sub.pi6, I.sub.pi8, I.sub.pi10, . . . to an aperture **12b**. Among them, the corresponding pixels of the pixel images . . . , I.sub.pi1, I.sub.pi3, I.sub.pi5, I.sub.pi7, I.sub.pi9, . . . come into a pixel sub-group, the corresponding pixels of the pixel images . . . , I.sub.pi2, I.sub.pi4, I.sub.pi6, I.sub.pi8, I.sub.pi10, . . . come into another pixel sub-group.

(59) When the interval between the apertures **12a** and **12b** is sufficiently small, the light beams form the $G=2$ pixel sub-groups enter the pupil **50** for one-pupil-multi-view display. Taking a displayed point P as example in FIG. 9, passing through this displayed point, light beams I.sub.pi6P and I.sub.pi7P from the pixels p.sub.i6 and p.sub.i7 of different pixel sub-groups enter the pupil **50** along different propagation directions, and overlap into a focusable displayed point. Here, the interval between adjacent apertures of a light block-aperture structure must be smaller than the diameter of the pupil **50**. A larger value of G can make more passing-through light beams for a displayed point reach to a pupil **50**, for simulating a cone-shaped beam from a corresponding real object point more naturally. In this case, along the arrangement direction of the apertures, the size of each aperture should be smaller than the diameter D.sub.p of the pupil **50**. The apertures arranged along one-dimensional direction can take strip-type, with the scale along the direction perpendicular to the arrangement direction not necessary being smaller than D.sub.p anymore. Optimally, the center points VP.sub.12a of the aperture **12a** in FIG. 9 is taken as the viewpoint for an image displayed by the corresponding pixel sub-group image, the center points VP.sub.12b of the aperture **12b** is taken as the viewpoint for an image displayed by the corresponding pixel sub-group image.

(60) Differently, if the interval between the apertures **12a** and **12b** is not small enough, such as the case shown in FIG. 10, the pupil **50** at position Po1 only can perceive the light beams which pass through the aperture **12a**. Through a displayed point P, only light beam I.sub.pi7P reaches to the

pupil **50**. Under this condition, a Maxwellian view display gets implemented. With the pupil **50** moving to the position Po2 shown in FIG. **11**, partial pixels (corresponding to the pixel image . . . , I.sub.pi1, I.sub.pi3, I.sub.pi5, I.sub.pi7, I.sub.pi9 in the zone Z.sub.11a) of a pixel sub-group corresponding to the aperture **12a** and partial pixels (corresponding to the pixel image I.sub.pi10, I.sub.pi12, I.sub.pi14, I.sub.pi16, . . . in the zone Z.sub.11b) of a pixel sub-group corresponding to the aperture **12b** are visible. These two zones cover the whole image of the pixel block exactly, and these pixels splice together into a composite pixel sub-group. In FIG. **11**, a sideline of the zone Z.sub.11a is a line connecting an edge point of the pupil **50** and the center point of the aperture **12a**. For the pupil **50** at a position, if light beams from a whole composite pixel sub-group or a whole pixel sub-group can be perceived, at least a Maxwellian view display can get implemented. When more apertures are introduced into each pixel-block-aperture structure accompanying light splitting devices, a composite pixel sub-group can be constructed by pixels from more pixel sub-groups. Furthermore, when light beams from at least two composite pixel sub-groups without a common pixel, or at least a composite pixel sub-group and a pixel sub-group without a common pixel, or at least two pixel sub-groups without a common pixel, are perceived by each pupil of the viewer, one-pupil-multi-view display will get implemented.

(61) FIGS. **9** to **11** illustrate how to achieve one-pupil-multi-view or Maxwellian view display by a pixel-block-aperture structure **10**. In a near eye display module based on pixel-block-aperture structures, M pixel-block-aperture structures are arranged for display of a larger FOV. In any one of the M pixel-block-aperture structures, when more than one apertures are designed, light beams from at least two composite pixel sub-groups without a common pixel, or at least a composite pixel sub-group and a pixel sub-group without a common pixel, or at least two pixel sub-groups without a common pixel are perceived by the corresponding pupils, one-pupil-more-view display gets implemented. Under this condition, the size of an aperture can be smaller than the size of the pupil **50** along all directions, or only along a direction. The premise for one-pupil-multi-view display is described as follows: along an arrangement direction of the grating periodic structure, pixel images corresponding to the light beams perceived by a pupil **50** through at least 2M apertures can constitute at least two pixel-image sets. The characteristic of a pixel-image set lies in that, it has a field angle with respect to a point around the apertures covering the 3D scene to be displayed. Often, a pixel-image set includes P/G pixel images along an arrangement direction of the grating periodic structure, with P being the number of the pixels in the pixel array along this arrangement direction. Different pixel-image sets do not share a common pixel. For example, in FIG. **11**, the pixel images . . . , I.sub.pi1, I.sub.pi3, I.sub.pi5, I.sub.pi7, I.sub.pi9, and I.sub.pi10, I.sub.pi12, I.sub.pi14, I.sub.pi16, . . . constitute a pixel-image set. When the apertures are arranged along two-dimensional directions, the formation of a pixel-image set is based on the similar rule. If pixel images corresponding to the light beams perceived by a pupil can constitute just one complete pixel-image set, the display gets implemented by Maxwellian view. Under this condition, the size of an aperture is required to be smaller than the size of the pupil **50**. There exists a situation that for some displayed points more than one passing-through light beams enter into the pupil **50**, but for the other displayed points only one passing-through light beam enters into the pupil **50**. In this case, the display principles of the one-pupil-multi-view and the Maxwellian view coexist. That is to say, partial spots are displayed based on Maxwellian view, and the other spots based on one-pupil-multi-view. Furthermore, P/G may not be an integer. In this case, the used value of P/G may be an integer near to the actual value of P/G.

(62) According to above discussions about FIG. **9**, no matter whether a light splitting device is introduced or not, a same method keeps valid for information loading of a pixel: a pixel is refreshed by the projection information of the 3D scene to be displayed along the line connecting the virtual image of this pixel and its corresponding aperture.

(63) FIG. **12** shows an optical structure of a display module with transmission-type apertures. The external ambient light may pass through the non-aperture region of the aperture surface **200**, when

the baffle **15** is discarded. In the optical structure shown in FIG. 7 and FIG. 12, the light from the pixel array **110** can transmit to the aperture array **120** in the air or in other medium, such as optical glass.

(64) An aperture **12** shown above further can have a phase modulation function, imaging the corresponding pixel block **11**. The image of a pixel block imaged by an aperture is called an equivalent pixel block. The coverage angles of M equivalent pixel blocks, which are from the M pixel-block-aperture structures respectively, with respect to a point around the apertures splice together seamlessly. As shown in FIG. 13, $I_{\text{sub.eq11'}}$, $I_{\text{sub.eq11}}$, $I_{\text{sub.eq11''}}$, and $I_{\text{sub.eq11'''}}$ are the equivalent pixel blocks corresponding to the pixel blocks **11'**, **11**, **11''**, and **11'''**, respectively. The apertures **12'**, **12**, **12''**, **12'''** are with corresponding modulation functions, respectively. In FIG. 13, $I_{\text{sub.eq11'}}$, $I_{\text{sub.eq11}}$, $I_{\text{sub.eq11''}}$, and $I_{\text{sub.eq11'''}}$ splice together by end to end into an equivalent display surface $I_{\text{sub.eq}}$. They may also splice together with some overlap into an equivalent display surface $I_{\text{sub.eq}}$. The said "splice together seamlessly" refers to a splicing with an angular interval not larger than the coverage angle of an interval between pixel images of a pixel group or a pixel sub-group. Then, the projection device **20** images the equivalent display surface $I_{\text{sub.eq}}$ again, to generate a pixel-array image $I_{\text{sub.110}}$ on the projection surface **100**. The loading information of a pixel is also the projection information of the 3D scene to be displayed along the line connecting its pixel image on the projection surface **100** and the corresponding aperture. Different apertures can be designed to project corresponding equivalent pixel blocks to different depths, respectively. This condition keeps requiring that the coverage angles of all the equivalent pixel blocks with respect to a point around the apertures splice seamlessly. The advantage of designing equivalent pixel blocks lies in that, a spatial interval between pixel blocks of adjacent pixel-block-aperture structures is allowed. In the embodiments without using equivalent pixel blocks, the pixel blocks have to be arranged adjacent to each other seamlessly, which often are different parts of a display screen. The spatial interval between adjacent pixel blocks, which results from the usage of the equivalent pixel blocks, also can help to decrease the crosstalk between apertures of adjacent pixel-block-aperture structures, even completely avoid this kind of crosstalk to make the modulation component **13**, or the modulation component **13**, the orthogonality generating component **14** and the orthogonality detecting component **16** non-necessary any more. Furthermore, the spatial interval between adjacent pixel blocks allows the baffle **15** to extend toward the pixel array **110** along the mid-planes between adjacent pixel-block-aperture structures. The extended baffle **15** can block the crosstalk between adjacent pixel-block-aperture structures, making the modulation component **13**, or the modulation component **13**, the orthogonality generating component **14** and the orthogonality detecting component **16** non-necessary any more. Another advantage of using equivalent pixel blocks lies in that, when the number of the pixel-block-aperture structures of a display module is high enough, all the pixel-block-aperture structures can be divided into two or more groups. Anyone of these groups has a seamless coverage angle with respect to a point around the apertures, and said seamless coverage angle covers the 3D scene to be displayed. Thus, these groups can carry out one-pupil-multi-view display or Maxwellian view display, even with different groups for displaying around different depths.

(65) When a light splitting device **18** is introduced into a pixel-block-aperture structure **10**, its multiple apertures can have corresponding phase modulation functions, respectively. Under this condition, different pixel sub-groups of the pixel block **11** are imaged by a corresponding aperture as different equivalent pixel blocks, respectively.

(66) A small light intensity gradient along the propagation direction of a light beam gets implemented by a corresponding small sized aperture or sub-aperture in above VAC-free Maxwellian view display. But the depth range of a small light intensity gradient is always limited. The projection device **20** also can be designed with an adjustable focus, such as a liquid lens whose focus can be changed by the control device **40**. Then, at different time-points of a time-period, the projection device **20** projects the image of the pixel array **110** to different depths sequentially for a

larger depth of field. As exemplified in FIG. 14 and FIG. 15, at two time-points of a time-period $T-T+\Delta t'$, the pixel array is imaged to the projection surfaces **100** and **100'**, respectively. With Maxwellian view display getting implemented around the projection surfaces **100** and **100'** at these two time-points, respectively, a Maxwellian view display with a larger depth of field will get implemented based on the persistence of vision, when this process is repeated in each time-period. In addition, when the viewer's convergence distance is real-time tracked by an auxiliary device, the control device **40** can drive the projection device **20** to image the pixel array to the tracked convergence distance synchronously, thus the viewer's focus keeps following the convergence distance without timing multiplexing in a 3D display. These processes are compatible with and can be introduced into one-pupil-multi-view display.

(67) A projection device **20** of an adjustable focus also can be a composite liquid crystal lens formed by stacking multiple liquid crystal sheets, which produces different focal lengths by activating different liquid crystal sheets or different combinations of the liquid crystal sheets.

(68) In the optical structure of a near-eye display module based on pixel-block-aperture structures discussed above, as shown in FIG. 7, a relay device **30** can be inserted between the pixel array **110** and the pupil **50**. The relay device **30** is designed not only for guiding light from the pixel array **110** to the pupil **50**, but also thinning the display module, or allowing external ambient light be perceived by the pupil **50**. A relay device **30** can take the deflection devices commonly used by conventional VR/AR system, such as a mirror or a semi-transparent mirror shown in FIG. 16, or a free-form surface device shown in FIG. 17. In FIG. 17, the curved surface **F1** is a transmissive surface, the curved surface **F3** is a reflective surface, the curved surface **F2** is a semi-transparent surface, and the curved surface **F4** is a transmissive surface. Among them, the curved surfaces **F1**, **F3**, **F2**, and **F4** jointly play the function of imaging the corresponding pixel array **110**, and replacing the projection device **20**. Actually, different components of a display module can be integrated into a physical device. For example, the aperture array **120** and the baffle **15** of FIG. 2 can be implemented by a liquid crystal sheet with light transmission zones as the apertures and the opaque region as the baffle. Another example, the function of a modulation component **13** can also be implemented by a corresponding pixel block **11** with the light beam from a pixel of this pixel block having pre-designed diverging angle and propagation direction. The curved surface **F5** is a compensation surface, eliminating the influence of the curved surfaces **F2** and **F4** on the incident light from the external environment. Along the projection direction of the light, the position of the relay device **30** is flexible. In FIG. 18, it locates between the projection device **20** and the aperture array **120**.

(69) The relay device **30** also can be a beam-path-folding structure for thinning the display module. FIG. 19 shows a beam-path-folding structure, which comprises an optional-reflecting-transmitting device **301**, two modulation sheet **302,302'**, and two reflectors **305,305'**. The optional-reflecting-transmitting device **301** reflects light of a kind of characteristic and transmits light of another kind of characteristic, which are named as reflection characteristic and transmission characteristic, respectively. The light of transmission characteristic from the pixel array **110**, for example the “custom character” light in FIG. 19, passes through the optional-reflecting-transmitting device **301**; then goes through the modulation sheet **302** and gets reflected by the reflector **305**; the reflected light passes through the modulation sheet **302** again, the “custom character” light of transmission characteristic changes into light of reflection characteristic by twice modulations of the modulation sheet **302**, and ultimately propagates to the observing zone for the pupil **50** by deflecting of the optional-reflecting-transmitting device **301**. The light of reflection characteristic from the pixel array **110** is reflected by the optional-reflecting-transmitting device **301**, then passes through the modulation sheet **302'** twice by the help of the reflection sheet **305'**, converting into light of transmission characteristic; and ultimately propagates to the observing zone for the pupil through the optional-reflecting-transmitting device **301**. A polarization beam splitter is taken as the optional-reflecting-transmitting device **301**, and the modulation sheet **302** is a quarter wave plate in

FIG. 19. The beam-path-folding-type relay device **30** shown in FIG. 19 also works for pixel-block-aperture structures of other orthogonal characteristics, such as timing characteristics, as shown in FIG. 20. Under the condition shown in FIG. 20, “ custom character” light from external ambient light reaches to the pupil **50** for AR display.

(70) FIG. 21 shows another beam-path-folding-type relay device **30**. The beam-path-folding structure includes an optional-reflecting-transmitting device **301**, a modulation sheet **302**, a semi-transparent-semi-reflective plate **303**, and a polarization pre-modulator **304**. The polarization pre-modulator **304** modulates the optical characteristics of the incident light, so to make it be deflected by the optional-reflecting-transmitting device **301** after passing through the semi-transparent-semi-reflective plate **303** and the modulation sheet **302**; then the reflected light is reflected by the semi-transparent-semi-reflective plate **303** after passing through the modulation sheet **302** and passes through the modulation sheet **302** once again. Then the light of transmission characteristic ultimately propagates to the observing zone for the pupil **50** through the optional-reflecting-transmitting device **301**.

(71) An optical wave-guide device commonly used in the traditional AR field can work as a wave-guide-type relay device **30** for obtaining a thin structure. FIG. 22 shows a display module with a wave-guide-type relay device **30**. The wave-guide-type relay device **30** includes a wave-guide body **306**, a modulating group **307**, a coupling-in element **308**, and a coupling-out element **309**. The wave-guide body **306** consists of a wave-guide plate **3061**, total-reflection surfaces **3062**, an entrance pupil **3063**, and an exit pupil **3064**. The total-reflection surfaces **3062** guide light from the entrance pupil **3063** to the exit pupil **3064** through the wave-guide plate **3061** by total reflections; the modulating group **307** modulates the light beams from the pixel array **110** and guides them into the wave-guide plate **3061** through the entrance pupil **3063**; the coupling-in element **308** guides incident light from the entrance pupil **3063** to propagate along the wave-guide plate **3061** under total-reflection condition; the coupling-out element **309** guides light propagating along the wave-guide plate **3061** to go out the wave-guide plate **3061** through the exit-pupil **3064**. A compensation device **60** can be inserted between the wave-guide-type relay device **30** and the external environment, for neutralizing the impact of the wave-guide-type relay device **30** on the light from the external environment. The optical wave-guide body **306** can be a planar optical wave-guide or a curved optical wave-guide, and the coupling-in element **308** can be a microstructure grating etched into the optical wave-guide body **306** by a micromachining process, a holographic grating exposed in the optical wave-guide body **306**, or mirrors coated onto the optical wave-guide body **306**. After passing through the wave-guide-type relay device **30** and the projection device **20**, the pixel array **110** is imaged to the projection surface **100**, which locates at an infinite or a finite distance. And the light from the exit-pupil **3064**, which is taken as light equivalently emitted by the pixel-array image, is guided to the observing zone for the pupil **50**. Along the light transmission direction, the aperture array **120** is placed in front of the exit pupil **3064**. When the virtual image of the pixel array **110** is projected to infinity, the function of the projection device **20** can be replaced by the modulating group **307** which transforms light beam from a pixel into a corresponding parallel light beam, the total-reflection surfaces **3062**, and the viewer's eye jointly.

(72) The display module shown by FIG. 22 requires the wave-guide-type relay device **30** to keep the orthogonal characteristic of the incident light being unaffected. For example, the wave-guide-type relay device **30** should have polarization preserving ability when linear polarizations are used as the orthogonal characteristics. The optical information refreshed by a pixel still is the projecting information of the 3D scene to be displayed along the line connecting the virtual image of this pixel and its corresponding aperture. In this process, light beam from a pixel also should miss a non-corresponding aperture of the same kind and of non-corresponding pixel-block-aperture structures. To guarantee this, the position and propagation direction of a light beam should be well designed. For example, influence of a modulation element and the modulation group **307** on the incident position and the spot size at the entrance pupil **3063** should be considered by ray tracing. FIG. 23

shows a concrete example. The light beams **1** and **2** from two pixels have their corresponding positions and propagation directions on the entrance pupil **3063**, respectively, which determine their different positions and propagation directions at the exit pupil **3064**. For a same pixel, the corresponding position and propagation direction at the exit pupil **3064** get changed when the corresponding position and incident direction at the entrance pupil **3063** changes. In FIG. **23**, for the light beam from the pixel **2**, when its incident position at the entrance pupil **3063** is translated from the point P.sub.o2 to the point P'.sub.o2, its projection position on the exit pupil **3064** changes accordingly.

(73) In above processes, the light beam from a pixel can enter the wave-guide body **306** as a parallel light, or as a non-parallel light. The function of the projection device **20** can be integrated into the apertures, or replaced by the modulating group **307**, the total reflection surface **3062**, and a viewer's eyes jointly.

(74) FIG. **24** shows a display module with a reflection-type aperture and a wave-guide-type relay device **30**. The discrete distributed apertures **12**, **12'**, **12''** and **12'''** jointly function as the coupling-out element **309**. Corresponding orthogonality detecting components **16**, **16'**, **16''** and **16'''** are attached to the apertures **12**, **12'**, **12''** and **12'''** directly, or attached to the exit pupil **3064**, as shown in FIG. **25**.

(75) In a display module with a wave-guide-type relay device **30**, the apertures can also have corresponding modulation function, respectively.

Embodiment 2

(76) Above discussed display module with a wave-guide-type relay device **30** can function as an element module. K such element modules stack up into a composite near-eye display module based on pixel-block-aperture structures, which is abbreviated as a composite display module. FIG. **26** takes K=2 element modules a and b as an example. The component is marked by subscripts a and b to denote their corresponding element module. For example, **308a** is the coupling-in element of the element module a, **308b** is the coupling-in element of the element module b.

(77) When images of the pixel-arrays from different element modules splice together, we called the composite display module as an II-type composite display module. In the II-type composite display module, different element modules are aligned for a larger FOV. With a light splitting device **18** being introduced to each pixel-block-aperture structure and each aperture being smaller than the diameter $D_{sub.p}$ of the pupil at least along an arrangement direction of the apertures, the one-pupil-multi-view display is expected. But the implementation of one-pupil-multi-view display further requires the aperture interval of a pixel-block-aperture structure be small enough, so to ensure a premise as follows: pixel images corresponding to the light beams perceived by the pupil **50** through at least 2M apertures can constitute at least two pixel-image sets. A pixel-image set has a field angle with respect to a point around the apertures covering the 3D scene to be displayed. Here, a pixel-image set often includes P/G pixel images along an arrangement direction of the grating periodic structure, with P being the number of pixels in all pixel arrays from different element modules along this arrangement direction. Different pixel-image sets do not share a pixel. When P/G is not an integer, the value of P/G can take an integer near to the actual value of P/G. If pixel images corresponding to the perceived light beams only can constitute one complete pixel-image set at most, Maxwellian view display gets implemented, or partial spots are displayed based on Maxwellian view and the other spots are displayed based on one-pupil-multi-view. Under this condition, the size of an aperture is required to be smaller than that of the pupil **50**.

(78) When the pixel-array images from different element modules overlap on the projection surface **100**, we name the composite display module as an I-type composite display module. The apertures corresponding to different display modules are designed in staggered arrangement, for getting denser apertures or larger observing zone for the pupil **50**. To implement one-pupil-multi-view display, an aperture should be smaller than the diameter $D_{sub.p}$ of the pupil **50** at least along an arrangement direction of the apertures. At the same time, pixel images corresponding to the light

beams perceived by the pupil **50** through at least 2M apertures can constitute at least two pixel-image sets. A pixel-image set has a field angle with respect to a point around the apertures covering the 3D scene to be displayed. Here, a pixel-image set often includes P/G' pixel images along an arrangement direction of the grating periodic structure, with the integer P being the pixel number of the pixel array in an element module along this arrangement direction. Integer $G'=G$ when light splitting devices are adopted, else $G'=1$. Different pixel-image sets do not share a pixel. When P/G is not an integer, the value of P/G can take an integer near to the actual value of P/G . If pixel images corresponding to the perceived light beams only can constitute one complete pixel-image set at most, the display gets implemented based on the Maxwellian view, or partial spots based on Maxwellian view and the other spots based on one-pupil-multi-view. Under this condition, the size of an aperture is required to be smaller than the size of the pupil **50**.

(79) When images of the pixel-arrays from different element modules are projected to different depths for a larger depth of field, we name the composite display module as an III-type composite display module. Under this condition, overlapping of light beams equivalently from pixel-array images at different depths also can activate the one-pupil-multi-view display.

(80) In a composite display module, an aperture with modulation function can project a corresponding pixel block to the corresponding depth, respectively. Different apertures image the corresponding pixel blocks to a same depth or different depths.

(81) The projection device **20** in above structures also can be composed of several discretely distributed substructures. For example, each substructure is cut from a common mother lens and has a same focal length, as shown in FIG. **27**. These substructures are located at corresponding apertures respectively, for imaging corresponding pixel blocks. These discretely distributed substructures also can correspond to different focal lengths, so that the virtual images of different pixel blocks appear at corresponding depths, respectively. The modulation function of the discretely distributed substructure of the projection device **20** also can be compounded with the modulation function of the apertures themselves.

Embodiment 3

(82) In above-mentioned display modules or composite display modules, an aperture can be replaced by J sub-apertures. Take a pixel-block-aperture structure **10** without a light splitting device **18** as an example, an aperture **12** is replaced by sub-apertures **12-1**, $\dots$, **12-j**, $\dots$, **12-J**, as shown in FIG. **28**. They are called J sub-apertures of the replaced aperture. Here, an integer $J \geq 2$, and an integer $2 \leq j \leq J$. FIG. **28** takes $J=3$ as example. At adjacent $J=3$ time-points with an interval $\delta t/J = \delta t/3$ of a time period, the $J=3$ sub-apertures **12-1**, **12-2**, and **12-3** get turned on sequentially, with only one sub-aperture being turned on at a time-point. At a time-point, the pixel block **12** and its pixels take the turned-on sub-aperture of the corresponding replaced aperture as the corresponding sub-aperture. This rule applies to all the pixel-block-aperture structures, with only one sub-aperture of each replaced aperture being turned on at a time-point. Such as the time-point T shown in FIG. **29**, the pixels corresponding to the image I.sub.11' take the turned-on sub-aperture **12-1'** as the corresponding sub-aperture, the pixels corresponding to the image I.sub.11 take the turned-on sub-aperture **12-1** as the corresponding sub-aperture, and so on. At the time-point $T + \delta t/3$ shown in FIG. **30**, the corresponding sub-aperture of the pixels corresponding to the image I.sub.11' changes to sub-aperture **12-2'**, the corresponding sub-aperture of the pixels corresponding to the image I.sub.11 changes to sub-aperture **12-2**, and so on.

(83) M sub-apertures are turned on at a time-point, the control device **40** refreshing all pixels synchronously. The loaded optical information of a pixel is the projection information of the 3D scene to be displayed along the line connecting the virtual image of this pixel and the corresponding sub-aperture at this time-point. Thus, by the sub-apertures, the number of projected images offered by a display module or a composite display module gets increased based on persistence of vision. The turned-on or turned-off of a sub-aperture can get implemented by a corresponding light valve attached to this sub-aperture, under the control of the control device **40**.

The light valves for different sub-aperture constitute a light-valve array **17**. When a light splitting device **18** is employed in each pixel-block-aperture structure, a pixel takes the turned-on sub-aperture to which the light from this pixel is guided by the light splitting device as the corresponding sub-aperture at a time-point.

(84) For sub-apertures designed for one-pupil-multi-view display, the size of a sub-aperture is smaller than the diameter $D_{sub.p}$ of the pupil **50** along at least an arrangement direction of the sub-apertures. At the same time, the sub-aperture interval of a pixel-block-aperture structure is small enough, so to ensure a premise as follows: pixel images corresponding to the light beams perceived by the pupil **50** can constitute at least two pixel-image sets. A pixel-image has a field angle with respect to a point around the sub-apertures covering the 3D scene to be displayed. Different pixel-image sets do not share a pixel at a same time-point. If pixel images corresponding to the perceived light beams only can construct at most one complete pixel-image set, Maxwellian view display get implemented, or partial spots based on Maxwellian view and the other spots based on one-pupil-multi-view. Under this condition, the size of a sub-aperture is required to be smaller than that of the pupil **50**.

(85) Each sub-aperture can further be designed with a modulation function. When a sub-aperture with modulation function is turned on, the corresponding pixel block or pixel sub-group is imaged to a corresponding depth. The images of a pixel block or a pixel sub-group can be at different depths, images of different pixel blocks or pixel sub-groups can be at different depths. Under these conditions, the equivalent light beams from pixel images at different depths can overlap into displayed light spots. As shown in FIG. **31**, a light beam equivalently coming from the pixel image at the depth $D_{sub.a}$ and a light beam equivalently coming from the pixel image at the depth $D_{sub.b}$ overlap into a displayed point P. They enter the pupil **50** through apertures or sub-apertures **12c** and **12d**, respectively. The $I_{sub.a}$ and $I_{sub.b}$ are virtual images of the corresponding pixel block(s) or corresponding pixel sub-group(s).

(86) The introduction of sub-apertures can be designed to enlarge the observing zone for the pupil **50**. For example, FIG. **29** shows turned-on sub-apertures **12-1**, **12-1'**, **12-1''**, and **12-1'''** at time-point t , and FIG. **30** shows turned-on sub-apertures **12-2**, **12-2'**, **12-2''**, and **12-2'''** at time-point $t+\delta t$. Obviously, the pupil **50** shown in FIG. **29** can perceive light beams from the pixel array consisting of four pixel blocks at time-point t , and miss the light beams at time-point $t+\delta t$. But if the pupil moves a little along the $-x$ direction, the pupil **50** will perceive the light beams from the pixel-array image at time-point $t+\delta t$, but miss the light beams from the pixel-array image at time-point t . Thus the observing zone for the pupil **50** gets enlarged.

(87) FIGS. **32** and **33** show a one-pupil-multi-view display by the sequentially turning-on and turning-off of the sub-apertures. Here $M=4$ is taken as an example. At time-point T , light beams from $M=4$ pixel blocks pass through corresponding $M=4$ sub-apertures **12-1'**, **12-1**, **12-1''**, **12-1'''**, respectively, and are perceived by the pupil **50**. At the time-point $T+t/3$, light beams from $M=4$ pixel blocks pass through corresponding $M=4$ sub-apertures **12-2'**, **12-2**, **12-2''**, **12-2'''**, respectively, and are perceived by the pupil **50**. That is to say, at least at these two time-points, the pixel-array image works as two pixel-image sets, projecting two images to the pupil **50** for a one-pupil-multi-view display. With increasing of the sub-aperture interval in a pixel-block-aperture structure, a complete image can be perceived at two or more time-points. For each displayed point, at least two passing-through light beams being perceived by the pupil **50** in a time-period is the premise for one-pupil-multi-view display. When only partial displayed points have more than one passing-through light beams being perceived by the pupil **50**, and the other displayed points have only one passing-through light beams being perceived by the pupil **50**, the one-pupil-multi-view display and Maxwellian view display coexist. When all the displayed points have only one passing-through light beams being perceived by the pupil **50**, Maxwellian view display gets implemented. In a display module with sub-apertures, the function of the projection device **20** also can be integrated to the sub-apertures. Such as a case shown by FIG. **34** and FIG. **35**, a sub-aperture projects a

corresponding pixel block to a corresponding depth. In these two figures, the virtual images of all pixel blocks are projected to a same depth at a time-point, but they can be projected to different depths. Of course, a sub-aperture can be designed with modulation function, for projecting an equivalent pixel block.

(88) In above-mentioned figures, the pixel-block-aperture structures are arranged along one dimension (except FIG. 3) for illustration. Obviously, the pixel-block-aperture structures can be arranged along two dimensions. The concrete shape of an aperture or a sub-aperture is also not mandatory. For example, an aperture with a size small than $D_{sub.p}$ along one direction can take a bar-shape. The apertures or sub-apertures can be arranged with gaps, or adjacent to each other without gaps, even partially overlapped.

(89) In above-mentioned display modules or composite display modules, pixel-block-aperture structures are arranged on a plane surface. They can be aligned on a non-planar surface. Under this condition, the projection device **20** consists of multiple sub-projection elements, with a sub-projection element projecting the virtual image of its corresponding pixel block, such as FIG. 36. Only pixel blocks **11**, **11'** and **11''** and sub-projection elements **201**, **201'** and **201''** are shown in FIG. 36, with other components of the near-eye display module not drawn for simplicity. The sub-projection elements **201**, **201'** and **201''** correspond to the pixel blocks **10**, **10'** and **10''**, respectively. Under this condition, a gap may exist between adjacent two pixel blocks. In a pixel-block-aperture structure **10**, the sub-projection elements **201** can be placed between the corresponding pixel block **11** and aperture **12**, or not.

Embodiment 4

(90) In above-mentioned display modules or composite display modules, a projection device **20** is used. Actually, a display module or composite display module can don't have a projection device **20**. Under this condition, the structure shown in FIG. 2 functions as a near-eye display module for display, where only an aperture is assigned to a pixel block correspondingly. In FIG. 37, all light beams from a pixel block through corresponding aperture enter into the pupil **50**. Under this condition, for a displayed point with a certain distance to the pixel blocks, such as the point $DP_{sub.j}$ or the point $DP_{sub.i}$ shown in FIG. 38, two or more passing-through light beams will be perceived by the pupil **50** for display. Concretely, taking the displayed point $DP_{sub.j}$ as an example, the passing-through light beam $DP_{sub.jp.sub.j1}$ from the pixel $p_{sub.j1}$ of the pixel block **11'** and the passing-through light beam $DP_{sub.jp.sub.j2}$ from the pixel $p_{sub.j2}$ of the pixel block **11** are perceived by the pupil **50**.

(91) Furthermore, in a display module or composite display module without a projection device **20**, multiple apertures accompanied with a light splitting device **18** or multiple sub-apertures can also be designed in a pixel-block-aperture structure. The design goal of the display module or composite display module is guiding two or more light beams passing through a displayed point toward the corresponding pupil **50**. On the premise of this goal achieved, when multiple apertures or sub-apertures are employed in a pixel-block-aperture structure, the pupil **50** may miss partial even all light beams passing through some of the apertures or sub-apertures.

Embodiment 5

(92) In above-mentioned display modules or composite display modules, an aperture or a sub-aperture can be replaced by a backlight structure **12R**. The backlight structure **12R** has two characteristics. Firstly, it projects light of orthogonal characteristic which can be modulated by the corresponding pixel block, but be blocked by the pixel blocks of orthogonal characteristics different to that of the corresponding pixel block. Secondly, on a plane near the pupil **50**, the light from a backlight structure **12R** covers a region same to the region covered by the light from the corresponding pixel block through the replaced aperture or sub-aperture. For example, FIG. 39 takes a point backlight as a backlight structure **12R** to replace an aperture **12**. In FIG. 39, the pixel block **11** is set with orthogonal characteristic “

as the corresponding pixel block, which also is the corresponding pixel block for the replaced aperture **12**. The backlight structure **12R** emits “custom character” light, which is modulated by the corresponding pixel block **11** of orthogonal characteristic “custom character”, but blocked by the adjacent pixel block **11'** of orthogonal characteristic “•”. After passing through the corresponding pixel block **11**, the modulated light covers a region Z.sub.cov on a plane P.sub.e near to or on the pupil **50**. Correspondingly, if the replaced aperture **12** is in-service, light beams from the pixel block **11** will cover the same region Z.sub.cov after passing through the aperture **12**. This replacement between a backlight structure and an aperture or a sub-aperture can be applied to all the apertures or sub-apertures.

(93) FIG. **40** shows another kind backlight structure **12R**, which consists of a point backlight **12R1** and a lens **12R2**. In FIG. **41**, the exemplified backlight structure **12R** includes a point backlight **12R1** and an optical wave-guide **12R2**.

(94) Obviously, the foregoing embodiments are merely examples for clearly explaining the present invention, and are not intended to limit the embodiments of the present invention. For those of ordinary skills in the art, other different forms with changes or modifications can be made on the basis of the above description. This is achievable. It is not possible to exhaust all implementations. For example, various optical wave-guide devices designed with different specific optical components can be used as the relay device **30** instead of the optical wave-guides mentioned in the present application. The projection device may be different kinds of phase modulation devices, including holographic devices, micro-structures, nano-structures. The optical structure of this patent can also be combined with methods described in other patents. For example, combination with U.S. patent Ser. No. 17/107,964 will result in a display module or a composite display module without modulation components. In fact, for any modification, equivalent replacement, and improvement made within the spirit and principle of the present invention should be included in the protection scope of the claims of the present invention, when the display is with the characteristic of “the divergence angle or/and propagation direction of the light beam from a pixel is specially modulated to miss non-corresponding apertures of the same kind, and the light beams from pixels of adjacent pixel block-aperture structures are endowed with different orthogonal characteristics for suppressing crosstalk between adjacent pixel block-aperture structures”.

(95) Some components may be omitted when the display can get implemented without them. For example, the modulation components may be omitted when orthogonal-characteristic designs can guarantee an acceptable observing zone for the pupil, or the orthogonal generating component and orthogonal detecting component may be omitted when the modulation component can make a light beam miss non-corresponding aperture or sub-aperture precisely.

Claims

1. A near-eye display module based on pixel-block-aperture structures, comprising: M pixel-block-aperture structures, each of which being constructed by mutually corresponded a pixel block, an aperture, a modulation component, an orthogonality generating component and an orthogonality detecting component, wherein a positive integer $M \geq 2$; wherein, the pixel block is composed of pixels for optical information loading, and a pixel array is composed of the pixels of all pixel blocks of the M pixel-block-aperture structures; an aperture array is composed of all apertures of M pixel-block-aperture structures on an aperture surface; the modulation component is composed of modulation elements, which correspond to pixels of a corresponding pixel block in a one-to-one manner, to guide the light beam from a pixel to a corresponding aperture with a confined diverging angle; the orthogonality detecting component is attached to a corresponding aperture, for only allowing light of corresponding orthogonal characteristic passable, but blocking light of other non-corresponding orthogonal characteristic; the orthogonality generating component of each block-aperture structures is attached to a corresponding pixel block, endowing pass-through light with

orthogonal characteristic same to that of a corresponding orthogonality detecting component; a control device, which loads optical information onto a pixel at a time-point, with the optical information being the projecting information of a 3D scene to be displayed at the time-point along a line connecting the pixel and its corresponding aperture; said near-eye display module based on pixel-block-aperture structures is configured that the N orthogonality detecting components of adjacent N pixel-block-aperture structures are with N kinds of orthogonal characteristics respectively, with the apertures attached by the orthogonality generating components of a same orthogonal characteristic taken as apertures of a same kind, wherein an integer $M \geq N \geq 2$, and the light beam from a pixel is modulated by a corresponding modulation element, to guarantee its light distribution covers the corresponding aperture, but misses the non-corresponding apertures of the same kind.

2. The near-eye display module based on the pixel-block-aperture structures according to claim 1, wherein the near-eye display module further comprises a projection device, which projects an enlarged virtual image of the pixel array to a projection surface, with the virtual image called as a pixel-array image; wherein, optical information loaded onto a pixel at a time-point is the projecting information of a 3D scene to be displayed at the time-point along a line connecting the virtual image of the pixel and its corresponding aperture, with the virtual image of a pixel called as a pixel image, and light beam from a pixel can be equivalently seen as being from its virtual image on the projection surface.

3. The near-eye display module based on the pixel-block-aperture structures according to claim 1, wherein the pixel-block-aperture structure further comprises a baffle, which blocks the light in the non-aperture zone.

4. The near-eye display module based on the pixel-block-aperture structures according to claim 2, wherein the near-eye display module further comprises a relay device for guiding light from the pixel array to a corresponding pupil of a viewer; wherein, the modulation element makes light from a corresponding pixel miss non-corresponding apertures of the same kind.

5. The near-eye display module based on the pixel-block-aperture structures according to claim 2, wherein the pixel-block-aperture structure further comprises a light splitting device, which is attached to the corresponding pixel block and guides light from G groups of pixels of the pixel block to G zones, respectively, wherein $G \geq 2$, and, G apertures covered by a corresponding orthogonality detecting component are placed in the G zones, respectively, with a pixel taking the aperture to which the light from the pixel is guided as the corresponding aperture, and the other (G-1) apertures as the non-corresponding apertures of a same kind.

6. The near-eye display module based on the pixel-block-aperture structures according to claim 1, wherein a size of the aperture is smaller than that of a viewer's pupil.

7. The near-eye display module based on the pixel-block-aperture structures according to claim 5, wherein a viewer's pupil perceives light beams through at least 2M apertures, and a size of the aperture is smaller than that of the viewer's pupil along their arrangement direction.

8. The near-eye display module based on the pixel-block-aperture structures according to claim 1, wherein light beam from a pixel missing a non-corresponding aperture refers to that the transmission light intensity of the light beam through the non-corresponding aperture is less than 10% of that through the corresponding aperture.

9. The near-eye display module based on the pixel-block-aperture structures according to claim 1, wherein the aperture is transmission-type or reflection-type.

10. The near-eye display module based on the pixel-block-aperture structures according to claim 1, wherein the aperture has a phase modulation function for projecting an image of the corresponding pixel block which is named as an equivalent pixel block, and coverage angles of all the equivalent pixel blocks with respect to a point around the sub-apertures splice together seamlessly.

11. The near-eye display module based on the pixel-block-aperture structures according to claim 10, wherein all equivalent pixel blocks are divided into two or more groups, and for each group of

equivalent pixel blocks, the coverage angles of the group of equivalent pixel blocks with respect to a point around the sub-apertures splice together seamlessly.

12. The near-eye display module based on the pixel-block-aperture structures according to claim 1, wherein the orthogonal characteristics are two linear polarizations with mutually perpendicular polarization directions, or two circular polarizations of left circular polarization and right left circular polarization, or timing characteristics being activated at different time-points, or combination of linear polarizations and timing characteristics, or combination of circular polarizations and timing characteristics; wherein, timing characteristics get implemented by a light-valve array, whose light valves are attached to the apertures in a one-to-one manner, for activating the aperture by turning on a corresponding light valve, and the function of the orthogonality generating device gets implemented by the control device, activating corresponding pixels by loading corresponding optical information when the aperture gets turned on.

13. The near-eye display module based on pixel-block-aperture structures according to claim 2, wherein the projection device is an optical device with adjustable focal length; wherein, the projection device is driven by the control device to generate multiple projection surfaces to different depths sequentially, with a pixel getting refreshed by projection optical information of the 3D scene to be displayed along the line connecting its virtual image and corresponding aperture synchronously; or, the convergence depth of the viewer is real-time tracked by an external auxiliary device, and the projection device projects the projection surface to the convergence depth driven under the control device synchronously, with a pixel getting refreshed by projection optical information of the 3D scene to be displayed along the line connecting its virtual image and corresponding aperture.

14. The near-eye display module based on the pixel-block-aperture structures according to claim 13, wherein the projection device is a liquid crystal lens with adjustable focal length, or an assembly of multiple liquid crystal sheets; wherein, the assembly produces different focal lengths by activating different liquid crystal sheets or different combinations of the liquid crystal sheets.

15. The near-eye display module based on the pixel-block-aperture structures according to any claim 4, wherein the relay device is a light-deflection device, to deflect the propagation direction of incident light beams.

16. The near-eye display module based on the pixel-block-aperture structures according to claim 4, wherein the relay device is a beam-path-folding structure for a thin structure.

17. The near-eye display module based on the pixel-block-aperture structures according to claim 4, wherein the relay device is an optical wave-guide device.

18. The near-eye display module based on the pixel-block-aperture structures according to claim 17, further comprising a compensation device inserted between the relay device and the external environment, for neutralizing the impact of the relay device on the light from the external environment.

19. The near-eye display module based on the pixel-block-aperture structures according to claim 1, wherein each aperture is replaced by J sub-apertures respectively, wherein an integer $J \geq 2$; said near-eye display module based on the pixel-block-aperture structures is configured that, at one time-point of J time-points in a time-period δt , only one sub-aperture corresponding to each replaced aperture is turned on, with a pixel taking the turned-on sub-aperture of its replaced corresponding aperture as the corresponding sub-aperture at the time-point, and at J time-points in a time-period, J sub-apertures of a replaced aperture are turned on sequentially; wherein, at each time-point, a corresponding pixel gets refreshed by the projection information of the 3D scene to be displayed along the line connecting the virtual image of the pixel and its corresponding sub-aperture.

20. The near-eye display module based on the pixel-block-aperture structures according to claim 19, wherein a size of the sub-aperture is smaller than that of the viewer's pupil.

21. The near-eye display module based on the pixel-block-aperture structures according to claim

19, wherein the viewer's pupil perceives light beams through at least $2M$ sub-apertures, and a size of the sub-aperture is smaller than a diameter of the viewer's pupil along their arrangement direction.

22. The near-eye display module based on the pixel-block-aperture structures according to claim 19, wherein the sub-aperture has phase modulation function for projecting a virtual image of the corresponding pixel block, wherein the virtual image of the corresponding pixel block is named as equivalent pixel block, and at a time-point the coverage angles of equivalent pixel blocks with respect to a point around the sub-apertures splice together seamlessly.

23. The near-eye display module based on the pixel-block-aperture structures according to claim 19, wherein each sub-aperture of each pixel-block-aperture structure has phase modulation function to image corresponding pixel block to different depth positions.

24. An I-type composite display module based on pixel-block-aperture structures, comprising K near-eye display modules based on the pixel-block-aperture structures according to claim 17, with the K pixel-array images overlapped into a projection area on the projection surface, wherein an integer $K \geq 2$; wherein, K near-eye display modules based on pixel-block-aperture structures function as K element modules.

25. The I-type composite display module based on the pixel-block-aperture structures according to claim 24, wherein a size of the aperture is smaller than that of the viewer's pupil.

26. The I-type composite display module based on the pixel-block-aperture structures according to claim 24, wherein a viewer's pupil perceives light beams through at least $2M$ apertures, and a size of the aperture is smaller than the diameter of the viewer's pupil along the arrangement direction of the apertures.

27. The I-type composite display module based on the pixel-block-aperture structures according to claim 24, wherein each aperture is replaced by J sub-apertures respectively, wherein an integer $J \geq 2$; said I-type composite display module based on pixel-block-aperture structures is configured that, at one time-point of J time-points in a time-period δt , only one sub-aperture corresponding to each replaced aperture is turned on, with a pixel taking the turned-on sub-aperture of its replaced corresponding aperture as the corresponding sub-aperture at the time-point, and at J time-points of a time-period, J sub-apertures of a replaced aperture are turned on sequentially; wherein, at each time-point, a corresponding pixel gets refreshed by the projection information of the 3D scene to be displayed along the line connecting the virtual image of the pixel and the corresponding sub-aperture.

28. The I-type composite display module based on the pixel-block-aperture structures according to claim 27, wherein each sub-aperture of each pixel-block-aperture structure has a phase modulation function for imaging a corresponding pixel block to a corresponding depth position.

29. An II-type composite display module based on pixel-block-aperture structures, comprising K near-eye display modules based on the pixel-block-aperture structures according to claim 17, with the K pixel-array images splicing together, wherein an integer $K \geq 2$; wherein, K near-eye display modules based on the pixel-block-aperture structures function as K element modules.

30. The II-type composite display module based on the pixel-block-aperture structures according to claim 29, wherein an aperture is replaced by J sub-apertures, wherein an integer $J \geq 2$; said II-type composite display module based on the pixel-block-aperture structures is configured that, at one time-point of J time-points in a time-period δt , only one sub-aperture corresponding to each replaced aperture is turned on, with the pixel taking the turned-on sub-aperture of the replaced corresponding aperture as corresponding sub-aperture at the time-point, and at J time-points in a time-period, J sub-aperture of a replaced aperture are turned on sequentially; wherein, at each time-point, a corresponding pixel gets refreshed by the projection information of the 3D scene to be displayed along the line connecting the virtual image of the pixel and the corresponding sub-aperture.

31. An III-type composite display module based on pixel-block-aperture structures, which

comprises K near-eye display modules based on the pixel-block-aperture structures according to claim 17, with the K pixel-array images positioning at different depths, respectively, where in an integer $K \geq 2$; wherein, K near-eye display modules based on the pixel-block-aperture structures function as K element modules.

32. The III-type composite display module based on the pixel-block-aperture structures according to claim 31, wherein an aperture is replaced by J sub-apertures, wherein an integer $J \geq 2$; said III-type composite display module based on pixel-block-aperture structures is configured that, at one time-point of J time-points in a time-period δt , only one sub-aperture of each replaced aperture is turned on, with a pixel taking the turned-on sub-aperture of its replaced corresponding aperture as the corresponding sub-aperture at the time-point, and at J time-points of a time-period, J sub-apertures of a replaced aperture are turned on sequentially; wherein, at each time-point, a corresponding pixel gets refreshed by the projection information of the 3D scene to be displayed along the line connecting the virtual image of the pixel and the corresponding sub-aperture.

33. The near-eye display module based on the pixel-block-aperture structures according to claim 1, wherein an aperture is replaced by a backlight structure correspondingly; wherein, the backlight structure projects light of orthogonal characteristic which can be modulated by the corresponding pixel block, but be blocked by the pixel blocks of orthogonal characteristics different to that of the corresponding pixel block, and on a plane near the pupil, the light from the backlight structure covers a region same to the region covered by the light from the corresponding pixel block through the replaced aperture.

34. The near-eye display module based on the pixel-block-aperture structures according to claim 19, wherein a sub-aperture is replaced by a backlight structure correspondingly; wherein, the backlight structure projects light of orthogonal characteristic which can be modulated by the corresponding pixel block, but be blocked by the pixel blocks of orthogonal characteristics different to that of the corresponding pixel block, and on a plane near the pupil, the light from the backlight structure covers a region same to the region covered by the light from the corresponding pixel block through the replaced sub-aperture.
