

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396754
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Tomalinas; William

Tick removal and encapsulation device

Abstract

A tick removal and capturing device of embodiments of the disclosed technology includes a first end and a second end removably attachable to the first end, with a pivot point attached therebetween. A removably attached combination of the first and second ends form a tick removal head and a tick encapsulation chamber, the chamber disposed between the tick removal head and the pivot point. The tick encapsulation chamber is adapted to substantially fully encapsulate a tick therein in the removably attached combination.

Inventors:	Tomalinas; William (Mountain Top, PA)
Applicant:	Tomalinas; William (Mountain Top, PA)
Family ID:	1000008781318
Appl. No.:	18/321519
Filed:	May 22, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240390035 A1	Nov. 28, 2024

Publication Classification

Int. Cl.: **A61B17/50 (20060101)**

U.S. Cl.:

CPC **A61B17/50 (20130101); A61B2017/505 (20130101)**

Field of Classification Search

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2431922	12/1946	Curtiss	30/1.5	B25C 11/02
5116347	12/1991	Butler	N/A	N/A
5246449	12/1992	Webster	606/1	A61B 17/50
5380339	12/1994	Webster	N/A	N/A
5554161	12/1995	Thibeault	N/A	N/A
5607434	12/1996	Alvino	N/A	N/A
D388859	12/1997	Carroll, Jr.	D22/122	N/A
D889646	12/2019	Bauer	N/A	N/A
10980572	12/2020	Poremba	N/A	N/A
11154328	12/2020	Gelardi, Sr.	N/A	N/A
2006/0271069	12/2005	Glaesel	N/A	N/A
2018/0177527	12/2017	Cohen et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
202014006075	12/2013	DE	N/A
102016113582	12/2017	DE	N/A
2347712	12/2009	ES	N/A
2657196	12/2017	ES	N/A

Primary Examiner: Dang; Anh T

Attorney, Agent or Firm: Feigin and Fridman LLC

Background/Summary

FIELD OF THE DISCLOSED TECHNOLOGY

(1) The disclosed technology relates generally to tick removal devices, and more specifically to a device for simultaneously removing a tick from a surface and securing the tick for further analysis.

BACKGROUND OF THE DISCLOSED TECHNOLOGY

(2) Lyme disease is a disease which infects many people yearly. This disease is often contracted by way of bites from infected ticks incurred while spending time outdoors. When ticks are found after time outdoors, it is necessary to find a way to remove them properly, and occasionally test them, to prevent or diagnose potential tick borne diseases such as Lyme disease. However, properly removing and sending ticks for testing can be difficult, as portions of the tick can occasionally be removed from the tick's body and left in the human host's body during removal. There is therefore a need for a device to allow for safe removal of ticks and encapsulation of removed ticks in order to prevent disease and/or send ticks for disease testing after removal.

SUMMARY OF THE DISCLOSED TECHNOLOGY

(3) A tick removal and capturing device of embodiments of the disclosed technology includes a first linear portion in a shape of a rectangular prism and a second linear portion, removably

attachable along a longest linear extent thereof to a longest linear extent of the first linear portion, in a shape of a rectangular prism. The first and second linear portions each have a first end and a second end. A U-shaped pivot point is attached to the second ends of both the first and the second linear portions, with a thinnest portion at a center thereof.

(4) The first ends of the first and second linear portions of embodiments of the disclosed technology are a tick remover head. The first end of the first linear portion is a concave semi-circle. The first end of the second linear portion is a majority of a concave circle. “Concave circle” and “concave semi-circle” are defined, respectively, as a circle or a semi-circle which is curved such that a distance of a central point of a circle thereof from the pivot point is greater than a distance from the pivot point to edges of the circle.

(5) In embodiments, in an arrangement where the first and second linear portions are removably attached along longest linear extents thereof, a hollow within the first linear portion and a corresponding hollow within the second linear portion reversibly form a tick encapsulation chamber.

(6) When joined, the first and second linear portions may form a rectangular prism.

(7) In the removably attached configuration, in various embodiments, the tick remover head forms a side of the tick encapsulation chamber. Furthermore, in the removably attached configuration, the tick remover head is covered by a head cover, which substantially forms a seal over a seam between the first end of the first linear portion and the first end of the second linear portion.

(8) The sides of the pivot, in embodiments, are rotatable by way of a pivot point up to an angle of substantially 180 degrees.

(9) In the arrangement where the first and second linear portions are removably attached along longest linear extents thereof, the second linear portion may further have at least one deformable protrusion adapted to prevent detachment of the first and second linear portions along longest linear extents thereof unless acted upon by an external force substantially greater than a normal force thereof and/or a force due to gravity.

(10) The at least one deformable protrusion may further be adapted, when the first and second linear portions are detached along a longest linear extent of each of the first and the second linear portions, to prevent attachment of the first and second linear portions along longest linear extents thereof unless acted upon by an external force substantially greater than a normal force thereof and/or a force due to gravity.

(11) In some embodiments, at least one of the first and second linear portions further comprise a second pivot point between extreme ends thereof, being a pivot point between the first end of the at least one linear portion away from the other linear portion.

(12) The tick encapsulation chamber may encapsulate a tick therein in the arrangement where the first and second linear portions are removably attached along longest linear extents thereof.

“Encapsulate” is defined as enclosing an object therein in a structure such that the object cannot be removed from the structure without substantially deforming the object or the structure.

(13) Described differently, a tick removal and capturing device has a first end, a second end removably attachable to the first end, and pivot point there-between. A removably attached combination of the first end and the second end forms a tick removal head and a tick encapsulation chamber, the chamber disposed between the head and the pivot point and adapted to substantially fully encapsulate a tick therein in the removably attached combination.

(14) In the removably attached combination, the tick removal head may form a wall of the tick encapsulation chamber.

(15) The tick removal head may include at least one element disposed on the first end and at least one element disposed on the second end. In the removably attached combination, the tick removal head may be covered by a head cover, which may substantially form a seal over a seam between edges of the at least one element of the tick removal head disposed on the first end and the at least one element of the tick removal head disposed on the second end.

(16) The first end may be rotatable by way of the pivot point substantially up to 180 degrees relative to the second end.

(17) At least one of the ends may include at least one deformable protrusion adapted, in an arrangement where the first and second ends are reversibly combined, to substantially prevent reversion of the combination unless acted upon by an external force substantially greater than a normal force thereof and/or a force due to gravity. Furthermore, the at least one deformable protrusion may be adapted, in an arrangement where the first and second ends are reversibly disconnectable, to substantially prevent combination of the first and second ends unless acted upon by an external force substantially greater than a normal force thereof and/or a force due to gravity.

(18) In some embodiments, at least one end of the first and second ends further includes a second pivot point between extreme ends thereof, being a pivot point between an extreme end of the at least one end away from an other of the first and second ends.

(19) A method of used the aforementioned tick removal and capturing device includes steps of removably combining the first and second ends such that a tick is encapsulated in the tick encapsulation chamber, and removably separating the first and second ends such that the tick is removable from the tick encapsulation chamber.

(20) In some embodiments, the step of removably combining the first and second ends such that a tick is encapsulated in the tick encapsulation chamber is preceded by a step of using the tick remover head to remove a tick from a surface external to the device such that the tick is placed within a portion of the tick encapsulation chamber.

(21) In other embodiments of the disclosed technology, the step of removably combining the first and second ends such that a tick is encapsulated in the tick encapsulation chamber is simultaneously a step of using the tick remover head to remove a tick from a surface external to the device such that the tick is placed within a portion of the tick encapsulation chamber.

(22) In further embodiments, the step of using the tick remover head to remove a tick from a surface external to the device such that the tick is placed within a portion of the tick encapsulation chamber is preceded by a step of changing an angle between the first and second ends of the device by way of the pivot point such that the a location of the tick on the surface external to the device is accessible to the tick remover head.

(23) Any device or step to a method described in this disclosure can comprise or consist of that which it is a part of, or the parts which make up the device or step. The term “and/or” is inclusive of the items which it joins linguistically and each item by itself.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 shows a top and right perspective view of a tick removal device in an open configuration of embodiments of the disclosed technology.

(2) FIG. 2 shows a bottom and left perspective view of the tick removal device in the open configuration of FIG. 1.

(3) FIG. 3 shows a bottom and left perspective view of a tick removal device in a closed configuration of embodiments of the disclosed technology.

(4) FIG. 4 shows a top and right perspective view of the tick removal device in the open configuration of FIG. 1.

DETAILED DESCRIPTION OF EMBODIMENTS OF THE DISCLOSED TECHNOLOGY

(5) A tick removal and capturing device of embodiments of the disclosed technology includes a first end and a second end removably attachable to the first end, with a pivot point attached therebetween. A removably attached combination of the first and second ends form a tick removal head and a tick encapsulation chamber, the chamber disposed between the tick removal head and the

pivot point. The tick encapsulation chamber is adapted to substantially fully encapsulate a tick therein in the removably attached combination.

(6) Embodiments of the disclosed technology will become more clear in view of the following discussion of the figures.

(7) FIG. 1 shows a top and right perspective view of a tick removal device in an open configuration of embodiments of the disclosed technology. FIG. 2 shows a bottom and left perspective view of the tick removal device in the open configuration of FIG. 1. The device **10** has a first side **20** and a second side **30**, which are substantially same lengths, widths, and shapes. The first side **20** ends in a first end **50**, and the second side **30** ends in a second end **60**.

(8) The two sides **20**, **30** are connected by a pivot **40**. In the embodiment shown, the pivot **40** has two arms **45**, each of which is connected to an end of the sides **20**, **30** which is opposite the first and second ends **50**, **60**. In some embodiments, the pivot **40** further includes additional pivot points between the pivot **40** and the first and second sides **20**, **30**. In other embodiments, the pivot **40** may be any other form of pivot joint between the two sides **20**, **30** that restricts rotation of the two sides **20**, **30** there-about to being in a single plane.

(9) In the embodiment shown, the first side **20** includes a pair of rigid deformable structures **90**. A “rigid deformable structure” is defined as a structure whose exterior shape can be temporarily changed by way of pressure applied by two fingers of an average human” such as 50 Newtons. The second side **30** includes a portal **100** corresponding to the locations of the rigid deformable structures **90**. In various embodiments, the rigidly deformable structures **90** may be only a single structure **90** or may be any number of structures **90**. The portal **100** may be any number of portals, such that each rigid deformable structure **90** corresponds to at least one portal **100**. In various embodiments, the portal **100** may be on the first side **20** and the rigid deformable structures **90** may be on the second side **30**.

(10) The two sides **20**, **30**, in the embodiment shown, include a plurality of grips **110** at ends thereof near the first and second ends **50**, **60**. The grips, in the embodiment shown, are convex in shape, where “convex” is defined as being curved such that a width of a surface in which a convex shape is disposed is wider at edges thereof than at a most convex point thereof, such that the surface is deeper at the most convex point thereof. In other embodiments, the grips may be any other shape, or made of any other material, or placed in any location such that a finger may be inserted therein and exert sufficient force to operate the device **10** while remaining substantially stationary due to at least a normal force and a force of friction and not interfering with operation of the device **10**.

(11) The first side **20** includes a first hollow **70**, having a single portal, and the second side **30** includes a second hollow **80**, having a single portal. The hollows **70**, **80** and the portals thereof are aligned, such that when the two sides **20**, **30** are brought into contact by way of rotation about the pivot **40**, the hollows **70**, **80** form a single enclosure substantially lacking any external portals. In various other embodiments, the single enclosure may be of any shape and may comprise holes of a size such that an average-size adult or non-larvae tick is unable to pass there-through while remaining structurally intact, such as half a millimeter. In some embodiments, one of the sides **20**, **30** may include a hollow **70**, **80** while the other side **20**, **30** includes a corresponding cover, such that the hollow **70** or **80**, when covered by the corresponding cover, forms a single enclosure substantially lacking any external portals.

(12) In the embodiment shown, the first hollow **70** has a wall **25** between the hollow **70** and the rigid deformable structures **90** and the second hollow **80** has a wall **35** between the hollow **80** and the portal **100**.

(13) In embodiments, one or more of the grips **110** are located on a portion of the sides **20**, **30** corresponding to the internal hollows **70**, **80** thereof. In some embodiments where one or more of the grips **110** are in forms of convex circles, a most convex point of one or more of the grips **110** bulges into the internal hollows **70**, **80**. In other embodiments, a surface between the hollows **70**,

80 and the grip or grips **110** is substantially flat on a side which is internal to the hollows **70, 80** and is thinnest at a point thereof corresponding to the most convex point of one or more of the grips **110**.

(14) In the embodiment shown, the first end **50** is a tick remover and the second end **60** is a tick remover cover. In other embodiments, the two ends **50, 60** may form a single tick remover, or each may be a tick remover, and the tick remover cover may be a separate removably attachable component. In the embodiment shown, the first end **50** is in a shape of a concave circle lacking a minority segment including a hollow point. The second end **60** is in a shape of a concave semicircle. The concave circle lacking a minority segment is disposed on the first end **50** such that an intact half thereof is attached to the first end **50**, and the concave semicircle is disposed substantially entirely on the second end **60** with a linear portion thereof facing the lacking minority segment of the concave circle on the first end **50**. In the embodiment shown, each of the circle attached to the first end **50** and the semicircle attached to the second end **60** simultaneously forms a wall of the hollow **70, 80** of their corresponding sides **20, 30**.

(15) FIG. 3 shows a bottom and left perspective view of a tick removal device in a closed configuration of embodiments of the disclosed technology. In the closed configuration shown, the sides **20, 30** are brought flush against each other by way of rotation about the pivot **40** and the rigid deformable structures **90** are or have been deformed such that portions thereof pass through the portal **100**.

(16) The pivot **40** may tend to a single position, such as a single angle between the sides **20, 30**, such that while deformed into a different position, such as a different angle between the sides **20, 30**, the pivot **40** pushes the sides **20, 30** back into the preferred position unless the sides **20, 30** are held in place by an external force. Thus, in some embodiments, while in the closed configuration as shown, the sides **20, 30** may be pressed outward, toward a larger angle there-between, such that portions of the rigid deformable structures **90** are pressed against portions of an edge of the portal **100**. In such embodiments, the device **10** may be returned to the preferred position by way of deforming the rigid deformable structures **90** such that they may fully pass through the portal **100** simultaneously.

(17) In the closed configuration shown, a seam between the two sides **20, 30** may be substantially flush, such that substantially no portal exists there-between, at least at portions thereof surrounding the internal combined hollows **70, 80**. Furthermore, the tick cover, such that the concave semicircle attached to the second end **60**, may be substantially fully flush with solid portions of the tick remover at the first end **50**, such that substantially no portals exist in the combination of the first and second ends **50, 60** while in the closed configuration. Additionally, the walls **25, 35** of the hollows **70, 80** may be substantially flush, such that no portals exist in the combination thereof.

(18) FIG. 4 shows a top and right perspective view of the tick removal device in the open configuration of FIG. 1. The tick remover at the first end **50**, in the embodiment shown, is sized to remove a tick **5** from a surface, such as skin, while keeping the tick **5** intact. The sides **20, 30** may be rotated together such that the tick is removed while the rigid deformable structures **90** are deformed, such as by pressing against angled portions within the device **10**. Thus, the tick **5** may be simultaneously removed by way of the tick remover at the first end **50** and placed into the first hollow **70** while the first and second ends **20, 30** are rotated into the closed configuration such that the internal hollow is formed by way of combination of the first hollow **70**, second hollow **80**, first and second ends **50, 60** and walls **25, 35**, substantially enclosing the tick **5** therein.

(19) In embodiments, the sides **20, 30** may be rotated about the pivot **40** such that an angle there-between is increased relative to the preferred angle. The pivot **40** may furthermore be constructed such that the angle there-between is limited to a maximal angle, such as 180 degrees, while being rotated by use of normal human force while using the device **10**.

(20) In further embodiments, one or more of the sides **20, 30** may further include one or more internal pivots therein, such that a corresponding end **50, 60** may be rotated farther from the

opposite end **20, 30**. In such embodiments, one or more of the sides **20, 30** may include further locking mechanisms, such as further rigid deformable structures, such that the sides **20, 30** are lockable in an unbent shape.

(21) For purposes of this disclosure, the term “substantially” is defined as “between 95% and 100%, inclusive, of” the term which it modifies.

(22) Any device or aspect of the technology can “comprise” or “consist of” the item it modifies, whether explicitly written as such or otherwise.

(23) When the term “or” is used, it creates a group which has within either term being connected by the conjunction as well as both terms being connected by the conjunction.

(24) While the disclosed technology has been disclosed with specific reference to the above embodiments, a person having ordinary skill in the art will recognize that changes can be made in form and detail without departing from the spirit and the scope of the disclosed technology. The described embodiments are to be considered in all respects only as illustrative and not restrictive. All changes that come within the meaning and range of equivalency of the claims are to be embraced within their scope. Combinations of any of the methods and apparatuses described hereinabove are also contemplated and within the scope of the invention.

Claims

1. A tick removal and capturing device, comprising: a first linear portion in a shape of a rectangular prism comprising a first end and a second end; a second linear portion, removably attachable along a longest linear extent thereof to a longest linear extent of said first linear portion, in a shape of a rectangular prism comprising a first end and a second end; and a U-shaped pivot point attached to said second ends of said first and said second linear portions comprising a thinnest portion at a center thereof; wherein said first ends of said first and second linear portions comprise a tick remover head; wherein said first end of said first linear portion comprises a concave semi-circle; wherein said first end of said second linear portion comprises a majority of a concave circle; wherein in an arrangement where said first and second linear portions are removably attached along longest linear extents thereof, a hollow within said first linear portion and a corresponding hollow within said second linear portion reversibly form a tick encapsulation chamber; wherein, in said removably attached configuration, said tick remover head is covered by a head cover, said head cover substantially forming a seal over a seam between said first end of said first linear portion and said first end of said second linear portion.

2. The tick removal and capturing device of claim 1, wherein said first and said second linear portions, when joined, form a rectangular prism.

3. The tick removal and capturing device of claim 1, wherein, in said removably attached configuration, said tick remover head forms a side of said tick encapsulation chamber.

4. The tick removal and capturing device of claim 1, wherein sides of said pivot point are rotatable by way of a pivot point up to an angle of substantially 180 degrees.

5. The tick removal and capturing device of claim 1, wherein said second linear portion further comprises at least one deformable protrusion adapted, in said arrangement where said first and said second linear portions are removably attached along longest linear extents thereof, preventing detachment of said first and said second linear portions along longest linear extents thereof unless acted upon by an external force substantially greater than a normal force thereof and/or a force due to gravity.

6. The tick removal and capturing device of claim 1, wherein said second linear portion further comprises at least one deformable protrusion, wherein said first and said second linear portions are detached along a longest linear extent of each said first and said second linear portions, preventing attachment of said first and said second linear portions along longest linear extents thereof unless acted upon by an external force substantially greater than a normal force thereof and/or a force due

to gravity.

7. The tick removal and capturing device of claim 1, wherein at least one of said first and second linear portions further comprises a second pivot point between extreme ends thereof, being a pivot point between said first end of said at least one linear portion away from said other linear portion.

8. The tick removal and capturing device of claim 1, wherein said tick encapsulation chamber encapsulates a tick therein in said arrangement where said first and second linear portions are removably attached along longest linear extents thereof.

9. A tick removal and capturing device, comprising: a first linear portion in a shape of a rectangular prism comprising a first end and a second end; a second linear portion, removably attachable along a longest linear extent thereof to a longest linear extent of said first linear portion, in a shape of a rectangular prism comprising a first end and a second end; and a U-shaped pivot point attached to said second ends of said first and said second linear portions comprising a thinnest portion at a center thereof; wherein said first ends of said first and second linear portions comprise a tick remover head; wherein said first end of said first linear portion comprises a concave semi-circle; wherein said first end of said second linear portion comprises a majority of a concave circle; wherein in an arrangement where said first and second linear portions are removably attached along longest linear extents thereof, a hollow within said first linear portion and a corresponding hollow within said second linear portion reversibly form a tick encapsulation chamber; wherein at least one of said first and second linear portions further comprises a second pivot point between extreme ends thereof, being a pivot point between said first end of said at least one linear portion away from said other linear portion.

10. A tick removal and capturing device, comprising: a first linear portion in a shape of a rectangular prism comprising a first end; a second linear portion in a shape of a rectangular prism comprising a second end removably attachable to said first end; and a pivot point between said first and said second ends; wherein a removably attached combination of said first end and said second end forms a tick removal head and a tick encapsulation chamber, said chamber disposed between said tick removal head and said pivot point and adapted to substantially fully encapsulate a tick therein in said removably attached combination; wherein said tick removal head comprises at least one element disposed on said first end and at least one element disposed on said second end; wherein in said removably attached combination said tick removal head is covered by a head cover, said head cover substantially forming a seal over a seam between edges of said at least one element of said tick removal head disposed on said first end and said at least one element of said tick removal head disposed on said second end.

11. The tick removal and capturing device of claim 10, wherein in said removably attached combination said tick removal head forms a wall of said tick encapsulation chamber.

12. The tick removal and capturing device of claim 10, wherein said first end is rotatable by way of said pivot point substantially up to 180 degrees relative to said second end.

13. The tick removal and capturing device of claim 10, wherein at least one of said ends comprises at least one deformable protrusion adapted, in an arrangement where said first and second ends are reversibly combined, to substantially prevent disconnection of said combination unless acted upon by an external force substantially greater than a normal force thereof and/or a force due to gravity.

14. The tick removal and capturing device of claim 13, wherein said at least one deformable protrusion is further adapted, in an arrangement where said first and second ends are reversibly disconnectable, to substantially prevent combination of said first and second ends unless acted upon by an external force substantially greater than a normal force thereof and/or a force due to gravity.

15. The tick removal and capturing device of claim 10, wherein at least one end of said first and second ends further comprises a second pivot point between extreme ends thereof, being a pivot point between an extreme end of said at least one end away from an other of said first and second ends.

16. A method of using the tick removal and capturing device of claim 10, comprising steps of: removably combining said first and second ends such that a tick is encapsulated in said tick encapsulation chamber; and removably disconnecting said first and second ends such that said tick is removable from said tick encapsulation chamber.
17. The method of using the tick removal and capturing device of claim 16, wherein said step of removably combining said first and second ends such that a tick is encapsulated in said tick encapsulation chamber is preceded by a step of using said tick remover head to remove a tick from a surface external to said device such that said tick is placed within a portion of said tick encapsulation chamber.
18. The method of using the tick removal and capturing device of claim 16, wherein said step of removably combining said first and second ends such that a tick is encapsulated in said tick encapsulation chamber simultaneously comprises a step of using said tick remover head to remove a tick from a surface external to said device such that said tick is placed within a portion of said tick encapsulation chamber.
19. The method of using the tick removal and capturing device of claim 17, wherein said step of using said tick remover head to remove a tick from a surface external to said device such that said tick is placed within a portion of said tick encapsulation chamber is preceded by a step of changing an angle between said first and second ends of said device by way of said pivot point such that said a location of said tick on said surface external to said device is accessible to said tick remover head.
-