

# US Patent & Trademark Office

## Patent Public Search | Text View

---

|                      |                       |
|----------------------|-----------------------|
| United States Patent | 12397099              |
| Kind Code            | B2                    |
| Date of Patent       | August 26, 2025       |
| Inventor(s)          | Germain; Aaron et al. |

---

### Medical systems and methods

---

#### Abstract

A fluid management system for use in a tissue resection procedure includes a controller. An inflow pump is operated by the controller and configured to provide fluid inflow through a flow path to a site in patient's body. An outflow pump is operated by the controller and configured to provide fluid outflow through a flow path from the site in patient's body. A motor driven resecting device may be provided for resecting tissue at the site. The controller is configured to actuate an inflow pump and an outflow pump in response to various signals and various algorithms are provided to provide malfunction warnings and assure safe operation.

---

**Inventors:** Germain; Aaron (Campbell, CA), Klein; Kyle (San Jose, CA), Walker; Michael D. (San Francisco, CA), Bek; Robin (Campbell, CA)

**Applicant:** BOSTON SCIENTIFIC SCIMED, INC. (Maple Grove, MN)

**Family ID:** 1000008781363

**Assignee:** BOSTON SCIENTIFIC SCIMED, INC. (Maple Grove, MN)

**Appl. No.:** 18/150374

**Filed:** January 05, 2023

#### Prior Publication Data

| Document Identifier | Publication Date |
|---------------------|------------------|
| US 20230143878 A1   | May. 11, 2023    |

#### Related U.S. Application Data

continuation parent-doc US 16858231 20200424 US 11571228 child-doc US 18150374  
continuation parent-doc US 15887390 20180202 US 10716584 20200721 child-doc US 16858231  
continuation parent-doc US 14247649 20140408 US 9907563 20180306 child-doc US 15887390  
us-provisional-application US 61809681 20130408

---

## Publication Classification

**Int. Cl.:** **A61M1/00** (20060101); **A61B17/22** (20060101); **A61B17/32** (20060101); **A61B17/42** (20060101); **A61B18/14** (20060101); **A61M3/02** (20060101); A61B18/00 (20060101); A61B18/16 (20060101)

**U.S. Cl.:**

**CPC** **A61M1/77** (20210501); **A61B17/22** (20130101); **A61B17/32002** (20130101); **A61B17/42** (20130101); **A61B18/1485** (20130101); **A61M1/777** (20210501); **A61M3/0208** (20140204); **A61M3/0212** (20140204); **A61M3/0216** (20140204); **A61M3/022** (20140204); A61B2017/22079 (20130101); A61B2017/4216 (20130101); A61B2018/00196 (20130101); A61B2018/00559 (20130101); A61B2018/162 (20130101); A61B2217/005 (20130101); A61B2217/007 (20130101); A61B2562/0247 (20130101); A61M2210/1433 (20130101)

## Field of Classification Search

**CPC:** A61M (3/0208); A61M (3/0212); A61M (3/0216); A61M (3/022); A61M (1/777); A61B (17/22); A61B (17/32002); A61B (17/42); A61B (18/1485); A61B (2017/22079); A61B (2018/00196); A61B (2018/00559); A61B (2217/005); A61B (2217/007)

---

## References Cited

### U.S. PATENT DOCUMENTS

| Patent No. | Issued Date | Patentee Name     | U.S. Cl.  | CPC        |
|------------|-------------|-------------------|-----------|------------|
| 4068475    | 12/1977     | Binstock          | 122/406.5 | F22B 35/14 |
| 4261360    | 12/1980     | Perez             | N/A       | N/A        |
| 4475901    | 12/1983     | Kraegen et al.    | N/A       | N/A        |
| 4650462    | 12/1986     | DeSatnick et al.  | N/A       | N/A        |
| 4735603    | 12/1987     | Goodson et al.    | N/A       | N/A        |
| 5053002    | 12/1990     | Barlow            | N/A       | N/A        |
| 5098375    | 12/1991     | Baier             | N/A       | N/A        |
| 5106364    | 12/1991     | Hayafuji et al.   | N/A       | N/A        |
| 5213571    | 12/1992     | Fujio et al.      | N/A       | N/A        |
| 5277696    | 12/1993     | Hagen             | N/A       | N/A        |
| 5382229    | 12/1994     | Grabenkort et al. | N/A       | N/A        |
| 5437629    | 12/1994     | Goldrath          | N/A       | N/A        |
| 5599301    | 12/1996     | Jacobs et al.     | N/A       | N/A        |
| 5643203    | 12/1996     | Beiser et al.     | N/A       | N/A        |
| 5643302    | 12/1996     | Beiser et al.     | N/A       | N/A        |
| 5669921    | 12/1996     | Berman et al.     | N/A       | N/A        |
| 5730752    | 12/1997     | Alden et al.      | N/A       | N/A        |
| 5810858    | 12/1997     | Berman et al.     | N/A       | N/A        |
| 5823990    | 12/1997     | Henley            | N/A       | N/A        |
| 5830180    | 12/1997     | Chandler et al.   | N/A       | N/A        |
| 5853392    | 12/1997     | Dennis            | N/A       | N/A        |
| 5906615    | 12/1998     | Thompson          | N/A       | N/A        |
| 5925050    | 12/1998     | Howard, III       | N/A       | N/A        |

|              |         |                     |     |     |
|--------------|---------|---------------------|-----|-----|
| 6032673      | 12/1999 | Savage et al.       | N/A | N/A |
| 6052060      | 12/1999 | Butler et al.       | N/A | N/A |
| 6109268      | 12/1999 | Thapliyal et al.    | N/A | N/A |
| RE36914      | 12/1999 | Carlsen et al.      | N/A | N/A |
| 6159160      | 12/1999 | Hsei et al.         | N/A | N/A |
| 6206014      | 12/2000 | Cameron, III et al. | N/A | N/A |
| 6245084      | 12/2000 | Mark et al.         | N/A | N/A |
| 6259074      | 12/2000 | Brunner et al.      | N/A | N/A |
| 6358263      | 12/2001 | Mark et al.         | N/A | N/A |
| 6629986      | 12/2002 | Ross et al.         | N/A | N/A |
| 7029451      | 12/2005 | Anderson et al.     | N/A | N/A |
| 7070604      | 12/2005 | Garito et al.       | N/A | N/A |
| 7204821      | 12/2006 | Clare et al.        | N/A | N/A |
| 7226459      | 12/2006 | Cesarini et al.     | N/A | N/A |
| 7384417      | 12/2007 | Cucin               | N/A | N/A |
| 7549987      | 12/2008 | Shadduck            | N/A | N/A |
| 7674259      | 12/2009 | Shadduck            | N/A | N/A |
| 7892229      | 12/2010 | Shadduck et al.     | N/A | N/A |
| 8313485      | 12/2011 | Shadduck            | N/A | N/A |
| 8512326      | 12/2012 | Shadduck et al.     | N/A | N/A |
| 8568424      | 12/2012 | Shugrue et al.      | N/A | N/A |
| 8728066      | 12/2013 | Shadduck et al.     | N/A | N/A |
| 8840625      | 12/2013 | Adams et al.        | N/A | N/A |
| 8840626      | 12/2013 | Adams et al.        | N/A | N/A |
| 8951274      | 12/2014 | Adams et al.        | N/A | N/A |
| 2002/0010463 | 12/2001 | Mulier et al.       | N/A | N/A |
| 2002/0072745 | 12/2001 | Truckai et al.      | N/A | N/A |
| 2002/0085952 | 12/2001 | Ellingboe           | N/A | N/A |
| 2003/0060862 | 12/2002 | Goble et al.        | N/A | N/A |
| 2004/0049217 | 12/2003 | Ross et al.         | N/A | N/A |
| 2004/0092980 | 12/2003 | Cesarini et al.     | N/A | N/A |
| 2004/0102770 | 12/2003 | Goble               | N/A | N/A |
| 2004/0167427 | 12/2003 | Quick et al.        | N/A | N/A |
| 2004/0167428 | 12/2003 | Quick et al.        | N/A | N/A |
| 2004/0267255 | 12/2003 | Auge, II et al.     | N/A | N/A |
| 2005/0096649 | 12/2004 | Adams               | N/A | N/A |
| 2005/0236329 | 12/2004 | Brotherton et al.   | N/A | N/A |
| 2006/0047185 | 12/2005 | Shener et al.       | N/A | N/A |
| 2006/0129091 | 12/2005 | Bonnette et al.     | N/A | N/A |
| 2006/0135955 | 12/2005 | Shadduck            | N/A | N/A |
| 2006/0200064 | 12/2005 | Gross et al.        | N/A | N/A |
| 2006/0224154 | 12/2005 | Shadduck et al.     | N/A | N/A |
| 2007/0016182 | 12/2006 | Lipson et al.       | N/A | N/A |
| 2007/0021713 | 12/2006 | Kumar et al.        | N/A | N/A |
| 2007/0036768 | 12/2006 | Fraser et al.       | N/A | N/A |
| 2007/0088275 | 12/2006 | Stearns et al.      | N/A | N/A |
| 2007/0244353 | 12/2006 | Larsen              | N/A | N/A |
| 2008/0027368 | 12/2007 | Kollar              | N/A | N/A |
| 2008/0039832 | 12/2007 | Palanker et al.     | N/A | N/A |
| 2008/0065060 | 12/2007 | Ein-Gal             | N/A | N/A |

|              |         |                 |     |     |
|--------------|---------|-----------------|-----|-----|
| 2008/0091061 | 12/2007 | Kumar et al.    | N/A | N/A |
| 2008/0091071 | 12/2007 | Kumar et al.    | N/A | N/A |
| 2008/0097468 | 12/2007 | Adams et al.    | N/A | N/A |
| 2008/0097471 | 12/2007 | Adams et al.    | N/A | N/A |
| 2008/0097563 | 12/2007 | Petrie et al.   | N/A | N/A |
| 2008/0216827 | 12/2007 | Seydel et al.   | N/A | N/A |
| 2008/0232977 | 12/2007 | Pan et al.      | N/A | N/A |
| 2008/0249366 | 12/2007 | Gruber et al.   | N/A | N/A |
| 2008/0249553 | 12/2007 | Gruber et al.   | N/A | N/A |
| 2008/0287893 | 12/2007 | Ineson          | N/A | N/A |
| 2009/0030402 | 12/2008 | Adahan          | N/A | N/A |
| 2009/0043238 | 12/2008 | Lane et al.     | N/A | N/A |
| 2009/0082715 | 12/2008 | Charles         | N/A | N/A |
| 2009/0137943 | 12/2008 | Stearns et al.  | N/A | N/A |
| 2009/0157016 | 12/2008 | Adahan          | N/A | N/A |
| 2009/0270897 | 12/2008 | Adams et al.    | N/A | N/A |
| 2009/0270898 | 12/2008 | Chin et al.     | N/A | N/A |
| 2009/0312753 | 12/2008 | Shadduck        | N/A | N/A |
| 2010/0100091 | 12/2009 | Truckai         | N/A | N/A |
| 2010/0152533 | 12/2009 | Mark            | N/A | N/A |
| 2010/0228222 | 12/2009 | Williams et al. | N/A | N/A |
| 2010/0312054 | 12/2009 | Beyar et al.    | N/A | N/A |
| 2011/0177415 | 12/2010 | Harrington      | N/A | N/A |
| 2011/0224486 | 12/2010 | Nguyen et al.   | N/A | N/A |
| 2011/0264090 | 12/2010 | Shadduck et al. | N/A | N/A |
| 2011/0306968 | 12/2010 | Beckman et al.  | N/A | N/A |
| 2012/0053583 | 12/2011 | Palanker et al. | N/A | N/A |
| 2012/0172888 | 12/2011 | Shugrue et al.  | N/A | N/A |
| 2012/0271256 | 12/2011 | Locke et al.    | N/A | N/A |
| 2012/0271300 | 12/2011 | Shadduck et al. | N/A | N/A |
| 2012/0330292 | 12/2011 | Shadduck et al. | N/A | N/A |
| 2013/0046304 | 12/2012 | Germain et al.  | N/A | N/A |
| 2013/0079702 | 12/2012 | Klein et al.    | N/A | N/A |
| 2013/0103021 | 12/2012 | Germain et al.  | N/A | N/A |
| 2013/0172805 | 12/2012 | Truckai et al.  | N/A | N/A |
| 2013/0172870 | 12/2012 | Germain et al.  | N/A | N/A |
| 2013/0211321 | 12/2012 | DuBois et al.   | N/A | N/A |
| 2013/0231652 | 12/2012 | Germain et al.  | N/A | N/A |
| 2013/0245637 | 12/2012 | Norred          | N/A | N/A |
| 2013/0267779 | 12/2012 | Woolford        | N/A | N/A |
| 2013/0296847 | 12/2012 | Germain et al.  | N/A | N/A |
| 2014/0012097 | 12/2013 | McCrea et al.   | N/A | N/A |
| 2014/0114238 | 12/2013 | Lee et al.      | N/A | N/A |
| 2019/0282073 | 12/2018 | Truckai         | N/A | N/A |
| 2021/0038297 | 12/2020 | Germain et al.  | N/A | N/A |

#### FOREIGN PATENT DOCUMENTS

| Patent No. | Application Date | Country | CPC |
|------------|------------------|---------|-----|
| 1911391    | 12/2007          | EP      | N/A |
| 2100567    | 12/2008          | EP      | N/A |

|            |         |    |     |
|------------|---------|----|-----|
| 2327351    | 12/1998 | GB | N/A |
| 2337000    | 12/1998 | GB | N/A |
| 2002513614 | 12/2001 | JP | N/A |
| 2004073833 | 12/2003 | JP | N/A |
| 2009502301 | 12/2008 | JP | N/A |
| 2010509984 | 12/2009 | JP | N/A |
| 2007013064 | 12/2006 | WO | N/A |
| 2010096139 | 12/2009 | WO | N/A |
| 2010096139 | 12/2010 | WO | N/A |
| 2012017959 | 12/2011 | WO | N/A |

## OTHER PUBLICATIONS

AAGL Practice Report: Practice Guidelines for the Management of Hysteroscopic Distending Media: (Replaces Hysteroscopic Fluid Monitoring Guidelines. J Am Assoc Gynecol Laparosc. 2000;7: 167-168) J Minim Invasive Gynecol. Mar.-Apr. 2013;20:137-48. doi:

10.1016/j.jmig.2012.12.002. cited by applicant

Liu et al. Clinical application of hysteroscopic electroresection in 775 cases. Di YH Jun Yi Da Xue Xue Bao. Apr. 2004;24(4):467-9. (in Chinese with English abstract). cited by applicant

Phillips et al. The Effect of Dilute Vasopressin Solution on Blood Loss During Operative Hysteroscopy. J Am Assoc Gynecol Laparosc. Aug. 1996;3(4, Supplement):S38. cited by applicant

*Primary Examiner:* Dang; Phong H

*Attorney, Agent or Firm:* Seager, Tufte & Wickhem, LLP

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. application Ser. No. 16/858,231, filed Apr. 24, 2020, which is a continuation of U.S. application Ser. No. 15/887,390, filed Feb. 2, 2018, now U.S. Pat. No. 10,716,584; which is a continuation of U.S. application Ser. No. 14/247,649, filed Apr. 8, 2014, now U.S. Pat. No. 9,907,563, which claims priority to U.S. Provisional Application 61/809,681, filed on Apr. 8, 2013, the full disclosures of which are incorporated herein by reference.

## FIELD OF THE INVENTION

(1) The present invention relates to surgical fluid management systems and methods, for example for use in distending the uterine cavity to allow resection and extraction of abnormal uterine tissue such as fibroids and polyps.

## BACKGROUND OF THE INVENTION

(2) Uterine fibroids are non-cancerous tumors that develop in the wall of uterus. Such fibroids occur in a large percentage of the female population, with some studies indicating up to 40 percent of all women have fibroids. Uterine fibroids can grow over time to be several centimeters in diameter and symptoms can include menorrhagia, reproductive dysfunction, pelvic pressure and pain.

(3) One current treatment of fibroids is hysteroscopic resection or myomectomy which involves transcervical access to the uterus with a hysteroscope together with insertion of a resecting instrument through a working channel in the hysteroscope. The resecting instrument may be a mechanical tissue cutter or an electrosurgical resection device such as a cutting loop. Mechanical cutting devices are disclosed in U.S. Pat. Nos. 7,226,459; 6,032,673 and 5,730,752 and U.S.

Published Patent Application 2009/0270898. An electrosurgical resecting device is disclosed in U.S. Pat. No. 5,906,615.

(4) In a myomectomy or hysteroscopic resection, the initial step of the procedure includes distention of the uterine cavity to create a working space for assisting viewing through the hysteroscope. In a relaxed state, the uterine cavity collapses with the uterine walls in contact with one another. A fluid management system is used to distend the uterus to provide a working space wherein a fluid is administered through a passageway in the hysteroscope under sufficient pressure to expand or distend the uterine cavity. The fluids used to distend the uterus are typically liquid aqueous solutions such as a saline solution or a sugar-based aqueous solution.

(5) In some RF electrosurgical resection procedures, the distending fluid is a non-conductive aqueous solution to limit RF current conduction.

(6) One particular concern is the fact that fluid management systems typically administer the fluid under a pressure of up to 100 mm Hg or more which results in a significant risk that the distending fluid may be taken up by a cut blood vessel exposed in the uterine cavity. Such unwanted fluid uptake is known as intravasation, which can lead to serious complications and even death. For this reason, fluid management systems have been developed to monitor the patient's fluid uptake on a continuous basis during a procedure, typically using complicated systems that capture, collect and weigh distending fluids that flow through the uterine cavity.

(7) While hysteroscopic resection can be effective in removing uterine fibroids, many commercially available instrument are too large in diameter and thus require anesthesia in an operating room environment. Conventional resectoscopes require cervical dilation to about 9 mm. What is needed is a system that can effectively resect and remove fibroid tissue through a small diameter hysteroscope.

#### SUMMARY OF THE INVENTION

(8) In a first aspect of the present invention, a fibroid treatment system comprises a controller, an inflow pump operated by the controller and configured to provide fluid inflow through a flow path to a patient's uterine cavity, an outflow pump operated by the controller and configured to provide fluid outflow through a flow path to the uterine cavity and a motor driven resecting device operated by the controller. The resecting device comprises an elongate introducer member having a tissue extraction channel therein with a diameter of no less than 2.4 mm and an outer sleeve having a diameter of no more than 3.8 mm. Further, the resecting device is adapted to remove fibroid tissue at a rate of at least 2 gm/min. In one variation, the controller can be configured to actuate the inflow and outflow pumps in response to signals of fluid pressure in the uterine cavity and to maintain the target pressure as described above. Additionally, the signal of fluid pressure can be provided by a pressure sensor coupled to a static fluid column communicating with the uterine cavity. In another variation, the controller can be configured to operate the resecting device in response to at least one parameter selected from a group consisting of an inflow pump speed, an outflow pump speed and signals of fluid pressure in the uterine cavity as will be described further below.

(9) In a second aspect of the invention, a fluid management system comprises a controller. A first pump is operated by the controller and configured to provide a fluid inflow to a site in patient's body. A second pump is also operated by the controller and configured to provide a fluid outflow from the site in patient's body. The controller is configured to maintain at least one operating parameter selected from a group consisting of a first pump speed, a fluid inflow rate, a second pump speed, and a fluid outflow rate, and the controller is configured to provide a fluid loss warning if the first pump speed exceeds a predetermined level for a pre-selected time interval.

(10) In exemplary embodiments of the second aspect, the pre-selected time interval may be at least 1 second, at least 5 seconds, or at least 10 seconds. The controller may be further configured to de-activate at least one pump if the first pump speed exceeds the predetermined level for the pre-selected time interval, and the controller may be still further configured to de-activate a powered

resecting device positioned in the site if the first pump speed exceeds the predetermined level for the pre-selected time interval.

(11) In a third aspect of the present invention, a fluid management system comprises a controller. An inflow pump is operated by the controller and adapted to provide a fluid inflow through a flow path to a site in a patient's body. An outflow pump is also operated by the controller and adapted to provide a fluid outflow through a flow path from the site in the patient's body. The controller is configured to maintain at least one operating parameter selected from a group consisting of a first pump speed, a fluid inflow rate, a second pump speed, and a fluid outflow rate, and the controller is configured to provide a blocked flow warning if a calculated power for driving the inflow pump exceeds a predetermined level for a pre-selected time interval.

(12) In exemplary embodiments of the third aspect of the present invention, the controller may be further configured to de-activate at least one pump if the calculated power for driving the inflow pump exceeds the predetermined level for the pre-selected time interval. The controller may be still further configured to de-activate a powered resecting device positioned in the site if the calculated power for driving the inflow pump exceeds the predetermined level for the pre-selected time interval.

(13) In a fourth aspect of the present invention, a fluid management system comprises a controller. A first pump is operated by the controller and configured to provide fluid inflow to a site in patient's body. A second pump is also operated by the controller and configured to provide fluid outflow from the site in patient's body. The controller is configured to maintain at least one operating parameter selected from a group consisting of a first pump speed, a fluid inflow rate, a second pump speed, and a fluid outflow rate, and the controller is further configured to provide a blocked flow warning if an input voltage to the inflow pump motor is below a predetermined threshold voltage for a pre-selected time interval.

(14) In exemplary embodiments of the fourth aspect of the present invention, the pre-selected time interval may range from 5 seconds to 120 seconds. The controller may be further configured to de-activate at least one pump if the input voltage to the inflow pump falls below the predetermined level for the pre-selected time interval, and the controller may be still further configured to de-activate the powered resecting device positioned in the site if the voltage to the inflow pump motor exceeds the predetermined level for the pre-selected time interval.

(15) In a fifth aspect of the present invention, a fluid management system comprises a controller. An inflow pump is operated by the controller and configured to provide fluid inflow through a flow path to a site in patient's body. An outflow pump is also operated by the controller and configured to provide fluid outflow through a flow path from the site in patient's body. The controller is configured to maintain at least one operating parameter selected from a group consisting of a first pump speed, a fluid inflow rate, a second pump speed, and a fluid outflow rate, and the controller is further configured to provide a blocked flow warning if a measured current to the outflow pump exceeds a predetermined threshold voltage for a pre-selected time interval.

(16) In a sixth aspect of the present invention, a fluid management system for use in a tissue resection procedure comprises a controller. An inflow pump is operated by the controller and configured to provide a fluid inflow through a flow path to a site in patient's body. An outflow pump is also operated by the controller and configured to provide a fluid outflow through a flow path from the site in patient's body. A motor driven resecting device for resecting tissue at the site is also provided. The controller is configured to actuate an inflow pump and an outflow pump in response to signals of actual pressure at the site in the patient's body to provide respective fluid inflow and fluid outflow to maintain a target pressure at the site, and the controller is further configured to de-activate the motor driven resecting device upon sensing that the actual pressure in the site falls below a predetermined threshold pressure level.

(17) In exemplary embodiments of the sixth aspect of the present invention, the controller may be further configured to de-activate a motor in the motor driven resecting device if actual pressure in

the site falls below a predetermined threshold pressure level. The controller may be alternatively configured to de-activate at least one tissue resecting electrode in the motor driven tissue resection device if actual pressure in the site falls below a predetermined threshold pressure level. The threshold pressure level is 100 mmHg or less, 50 mmHg or less, or 25 mmHg or less.

(18) In a seventh aspect of the present invention, a fluid management system for use in tissue resection comprises a controller. The controller is configured to (a) actuate an inflow pump and an outflow pump in response to signals of actual pressure in a site in patient's body to thereby provide respective fluid inflows and fluid outflows to maintain a target pressure at said site, (b) send a tissue-engagement signal to the controller after sensing a predetermined increase in the actual pressure within a pre-selected interval resulting from a resecting tool engaging targeted tissue in the site, (c) send a tissue-disengagement signal to the controller after sensing a predetermined decrease in the actual pressure within a pre-selected interval resulting from a resecting tool subsequently disengaging from the tissue, and (d) modulate an operating parameter of the fluid management system in response to a tissue-engagement signal or a tissue-disengagement signal.

(19) In exemplary embodiments of the seventh aspect of the present invention, the controller may be further configured to place the inflow pump in a ready state to provide a selected high inflow rate in response to a tissue-engagement signal. The controller may also be configured to actuate the inflow pump to provide a selected high inflow rate in response to a tissue dis-engagement signal.

---

## Description

### BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a plan view of an assembly including a hysteroscope and a tissue-resecting device corresponding to the invention that is inserted through the working channel of the hysteroscope.

(2) FIG. 2 is a schematic perspective view of a fluid management system used for distending the uterus and for assisting in electrosurgical tissue resection and extraction.

(3) FIG. 3 is a cross-sectional view of the shaft of the hysteroscope of FIG. 1 showing various channels therein.

(4) FIG. 4 is a schematic side view of the working end of the electrosurgical tissue-resecting device of FIG. 1 showing an outer sleeve and a reciprocating inner sleeve and an electrode arrangement.

(5) FIG. 5 is a schematic perspective view of the working end of the inner sleeve of FIG. 4 showing its electrode edge.

(6) FIG. 6A is a schematic cut-away view of a portion of outer sleeve, inner RF resecting sleeve and a tissue-receiving window of the outer sleeve.

(7) FIG. 6B is a schematic view of a distal end portion another embodiment of inner RF resecting sleeve.

(8) FIG. 7A is a cross sectional view of the inner RF resecting sleeve of FIG. 6B taken along line 7A-7A of FIG. 6B.

(9) FIG. 7B is another cross sectional view of the inner RF resecting sleeve of FIG. 6B taken along line 7B-7B of FIG. 6B.

(10) FIG. 8 is a schematic view of a distal end portion of another embodiment of inner RF resecting sleeve.

(11) FIG. 9A is a cross sectional view of the RF resecting sleeve of FIG. 8 taken along line 9A-9A of FIG. 8.

(12) FIG. 9B is a cross sectional view of the RF resecting sleeve of FIG. 8 taken along line 9B-9B of FIG. 8.

(13) FIG. 10A is a perspective view of the working end of the tissue-resecting device of FIG. 1 with the reciprocating RF resecting sleeve in a non-extended position.

(14) FIG. 10B is a perspective view of the tissue-resecting device of FIG. 1 with the reciprocating



RF resecting sleeve in a partially extended position

(15) FIG. **10C** is a perspective view of the tissue-resecting device of FIG. **1** with the reciprocating RF resecting sleeve in a fully extended position across the tissue-receiving window.

(16) FIG. **11A** is a sectional view of the working end of the tissue-resecting device of FIG. **10A** with the reciprocating RF resecting sleeve in a non-extended position.

(17) FIG. **11B** is a sectional view of the working end of FIG. **10B** with the reciprocating RF resecting sleeve in a partially extended position.

(18) FIG. **11C** is a sectional view of the working end of FIG. **10C** with the reciprocating RF resecting sleeve in a fully extended position.

(19) FIG. **12A** is an enlarged sectional view of the working end of tissue-resecting device of FIG. **11B** with the reciprocating RF resecting sleeve in a partially extended position showing the RF field in a first RF mode and plasma resecting of tissue.

(20) FIG. **12B** is an enlarged sectional view of the working end of FIG. **11C** with the reciprocating RF resecting sleeve almost fully extended and showing the RF fields switching to a second RF mode from a first RF mode shown in FIG. **12**.

(21) FIG. **12C** is an enlarged sectional view of the working end of FIG. **11C** with the reciprocating RF resecting sleeve again almost fully extended and showing the explosive vaporization of a captured liquid volume to expel resected tissue in the proximal direction.

(22) FIG. **13** is an enlarged perspective view of a portion of the working end of FIG. **12C** showing an interior chamber and a fluted projecting element.

(23) FIG. **14** is a sectional view of the working end of FIG. **12C** showing an interior chamber and a variation of a projecting element.

(24) FIG. **15** is a sectional view of the working end of FIG. **12C** showing an interior chamber and a variation of a projecting element configured to explosively vaporize the captured liquid volume.

(25) FIG. **16** is a schematic view of a system for fibroid removal including a fluid management system.

(26) FIG. **17** is a schematic view of the fluid management system of FIG. **16** with an enlarged view of the working end of a tissue-resecting probe as generally described in FIGS. **1-12C** in a position to resect and extract fibroid tissue.

(27) FIG. **18** is a schematic view of a pressure sensor component of the fluid management system of FIGS. **16-17**.

(28) FIG. **19** is a cut-away schematic view of a filter module of the fluid management system of FIGS. **16-17**.

(29) FIG. **20** is a schematic view of an endoscope and fluid management system being used in a diagnostic mode.

(30) FIG. **21** is a schematic view of the endoscope and fluid management system of FIG. **20** together with a resecting probe with the assembly as used is a non-diagnostic or therapeutic mode.

#### DETAILED DESCRIPTION

(31) FIG. **1** illustrates an assembly that comprises an endoscope **50** used for hysteroscopy together with a tissue resecting device **100** extending through a working channel **102** of the endoscope. The endoscope or hysteroscope **50** has a handle **104** coupled to an elongated shaft **105** having a diameter of 5 mm to 7 mm. The working channel **102** therein may be round, D-shaped or any other suitable shape. The endoscope shaft **105** is further configured with an optics channel **106** and one or more fluid inflow/outflow channels **108a**, **108b** (FIG. **3**) that communicate with valve-connectors **110a**, **110b** configured for coupling to a fluid inflow source **120** thereto, or optionally a negative pressure source **125** (FIGS. **1-2**). The fluid inflow source **120** is a component of a fluid management system **126** as is known in the art (FIG. **2**) which comprises a fluid container **128** and pump mechanism **130** which pumps fluid through the hysteroscope **50** into the uterine cavity. As can be seen in FIG. **2**, the fluid management system **126** further includes the negative pressure source **125** (which can comprise an operating room wall suction source) coupled to the tissue-

resecting device **100**. The handle **104** of the endoscope includes the angled extension portion **132** with optics to which a videoscopic camera **135** can be operatively coupled. A light source **136** also is coupled to light coupling **138** on the handle of the hysteroscope **50**. The working channel **102** of the hysteroscope is configured for insertion and manipulation of the tissue-resecting and extracting device **100**, for example to treat and remove fibroid tissue. In one embodiment, the hysteroscope shaft **105** has an axial length of 21 cm, and can comprise a 0° scope, or 15° to 30° scope.

(32) Still referring to FIG. **1**, the tissue-resecting device **100** has a highly elongated shaft assembly **140** configured to extend through the working channel **102** in the hysteroscope. A handle **142** of the tissue-resecting device **100** is adapted for manipulating the electrosurgical working end **145** of the device. In use, the handle **142** can be manipulated both rotationally and axially, for example, to orient the working end **145** to resect targeted fibroid tissue. The tissue-resecting device **100** has subsystems coupled to its handle **142** to enable electrosurgical resecting of targeted tissue. A radiofrequency generator or RF source **150** and controller **155** are coupled to at least one RF electrode carried by the working end **145** as will be described in detail below. In one embodiment shown in FIG. **1**, an electrical cable **156** and negative pressure source **125** are operatively coupled to a connector **158** in handle **142**. The electrical cable couples the RF source **150** to the electrosurgical working end **145**. The negative pressure source **125** communicates with a tissue extraction channel **160** in the shaft assembly **140** of the tissue extraction device **100** (FIG. **4**).

(33) FIG. **1** further illustrates a seal housing **162** that carries a flexible seal **164** carried by the hysteroscope handle **104** for sealing the shaft **140** of the tissue-resecting device **100** in the working channel **102** to prevent distending fluid from escaping from a uterine cavity.

(34) In one embodiment as shown in FIG. **1**, the handle **142** of tissue-resecting device **100** includes a motor drive **165** for reciprocating or otherwise moving a resecting component of the electrosurgical working end **145** as will be described below. The handle **142** optionally includes one or more actuator buttons **166** for actuating the device. In another embodiment, a footswitch can be used to operate the device. In one embodiment, the system includes a switch or control mechanism to provide a plurality of reciprocation speeds, for example 1 Hz, 2 Hz, 3 Hz, 4 Hz and up to 8 Hz. Further, the system can include a mechanism for moving and locking the reciprocating resecting sleeve in a non-extended position and in an extended position. Further, the system can include a mechanism for actuating a single reciprocating stroke.

(35) Referring to FIGS. **1** and **4**, an electrosurgical tissue resecting device has an elongate shaft assembly **140** extending about longitudinal axis **168** comprising an exterior or first outer sleeve **170** with passageway or lumen **172** therein that accommodates a second or inner sleeve **175** that can reciprocate (and optionally rotate or oscillate) in lumen **172** to resect tissue as is known in that art of such tubular cutters. In one embodiment, the tissue-receiving window **176** in the outer sleeve **170** has an axial length ranging between 10 mm and 30 mm and extends in a radial angle about outer sleeve **170** from about 45° to 210° relative to axis **168** of the sleeve. The outer and inner sleeves **170** and **175** can comprise a thin-wall stainless steel material and function as opposing polarity electrodes as will be described in detail below. FIGS. **6A-8** illustrate insulative layers carried by the outer and inner sleeves **170** and **175** to limits, control and/or prevent unwanted electrical current flows between certain portions of the sleeve. In one embodiment, a stainless steel outer sleeve **170** has an O.D. of 3.6 mm to 3.8 mm with an I.D. of 3.38 mm to 3.5 mm and with an inner insulative layer (described below) the sleeve has a nominal I.D. of about 3.175 mm". In this embodiment, the stainless steel inner sleeve **175** has an O.D. of about 3.05 mm with an I.D. of about 2.84 mm". The inner sleeve **175** with an outer insulative layer has a nominal O.D. of about 3.12 mm" to reciprocate in lumen **172**. The inner diameters of the inner sleeve portions are described below. As can be seen in FIG. **4**, the distal end **177** of inner sleeve **175** comprises a first polarity electrode with distal resecting electrode edge **180** about which plasma can be generated. The electrode edge **180** also can be described as an active electrode during tissue resecting since the electrode edge **180** then has a substantially smaller surface area than the opposing polarity or

return electrode. In one embodiment in FIG. 4, the exposed surfaces of outer sleeve 170 comprises the second polarity electrode 185, which thus can be described as the return electrode since during use such an electrode surface has a substantially larger surface area compared to the functionally exposed surface area of the active electrode edge 180.

(36) In one aspect of the invention, the inner sleeve or resecting sleeve 175 has an interior tissue extraction lumen 160 with first and second interior diameters that are adapted to electrosurgically resect tissue volumes rapidly—and thereafter consistently extract the resected tissue strips through the highly elongated lumen 160 without clogging. Now referring to FIGS. 5 and 6A, it can be seen that the inner sleeve 175 has a first diameter portion 190A that extends from the handle 142 (FIG. 1) to a distal region 192 of the sleeve 175 wherein the tissue extraction lumen transitions to a smaller second diameter lumen 190B with a reduced diameter indicated at B which is defined by the electrode sleeve element 195 that provides resecting electrode edge 180. The axial length C of the reduced cross-section lumen 190B can range from about 2 mm to 20 mm. In one embodiment, the first diameter A is between 2.8 mm and 2.9 mm and the second reduced diameter B is between 2.4 mm and 2.5 mm. As shown in FIG. 5, the inner sleeve 175 can be an electrically conductive stainless steel and the reduced diameter electrode portion also can comprise a stainless steel electrode sleeve element 195 that is welded in place by weld 196 (FIG. 6A). In another alternative embodiment, the electrode and reduced diameter electrode sleeve element 195 comprises a tungsten tube that can be press fit into the distal end 198 of inner sleeve 175. FIGS. 5 and 6A further illustrates the interfacing insulation layers 202 and 204 carried by the first and second sleeves 170, 175, respectively. In FIG. 6A, the outer sleeve 170 is lined with a thin-wall insulative material 200, such as PFA, or another material described below. Similarly, the inner sleeve 175 has an exterior insulative layer 202. These coating materials can be lubricious as well as electrically insulative to reduce friction during reciprocation of the inner sleeve 175.

(37) The insulative layers 200 and 202 described above can comprise a lubricious, hydrophobic or hydrophilic polymeric material. For example, the material can comprise a bio-compatible material such as PFA, TEFLON™, polytetrafluoroethylene (PTFE), FEP (Fluorinated ethylenepropylene), polyethylene, polyamide, ECTFE (Ethylenechlorotrifluoro-ethylene), ETFE, PVDF, polyvinyl chloride or silicone.

(38) Now turning to FIG. 6B, another variation of inner sleeve 175 is illustrated in a schematic view together with a tissue volume being resected with the plasma electrode edge 180. In this embodiment, as in other embodiments in this disclosure, the RF source operates at selected operational parameters to create a plasma around the electrode edge 180 of electrode sleeve 195 as is known in the art. Thus, the plasma generated at electrode edge 180 can resect and ablate a path P in the tissue 220, and is suited for resecting fibroid tissue and other abnormal uterine tissue. In FIG. 6B, the distal portion of the resecting sleeve 175 includes a ceramic collar 222 which is adjacent the distal edge 180 of the electrode sleeve 195. The ceramic 222 collar functions to confine plasma formation about the distal electrode edge 180 and functions further to prevent plasma from contacting and damaging the polymer insulative layer 202 on the resecting sleeve 175 during operation. In one aspect of the invention, the path P cut in the tissue 220 with the plasma at electrode edge 180 provides a path P having an ablated width indicated at W, wherein such path width W is substantially wide due to tissue vaporization. This removal and vaporization of tissue in path P is substantially different than the effect of cutting similar tissue with a sharp blade edge, as in various prior art devices. A sharp blade edge can divide tissue (without cauterization) but applies mechanical force to the tissue and may prevent a large cross section slug of tissue from being cut. In contrast, the plasma at the electrode edge 180 can vaporize a path P in tissue without applying any substantial force on the tissue to thus resect larger cross sections or slugs strips of tissue. Further, the plasma resecting effect reduces the cross section of tissue strip 225 received in the tissue-extraction lumen 190B. FIG. 6B depicts a tissue strip to 225 entering lumen 190B which has such a smaller cross-section than the lumen due to the vaporization of tissue. Further, the cross

section of tissue **225** as it enters the larger cross-section lumen **190A** results in even greater free space **196** around the tissue strip **225**. Thus, the resection of tissue with the plasma electrode edge **180**, together with the lumen transition from the smaller cross-section (**190B**) to the larger cross-section (**190A**) of the tissue-extraction lumen **160** can significantly reduce or eliminate the potential for successive resected tissue strips **225** to clog the lumen. Prior art resection devices with such small diameter tissue extraction lumen typically have problems with tissue clogging.

(39) In another aspect of the invention, the negative pressure source **225** coupled to the proximal end of tissue extraction lumen **160** (see FIGS. **1** and **4**) also assists in aspirating and moving tissue strips **225** in the proximal direction to a collection reservoir (not shown) outside the handle **142** of the device.

(40) FIGS. **7A-7B** illustrate the change in lumen diameter of resecting sleeve **175** of FIG. **6B**. FIG. **8** illustrates the distal end of a variation of resecting sleeve **175'** which is configured with an electrode resecting element **195'** that is partially tubular in contrast to the previously described tubular electrode element **195** (FIGS. **5** and **6A**). FIGS. **9A-9B** again illustrate the change in cross-section of the tissue extraction lumen between reduced cross-section region **190B'** and the increased cross-section region **190A'** of the resecting sleeve **175'** of FIG. **8**. Thus, the functionality remains the same whether the resecting electrode element **195'** is tubular or partly tubular. In FIG. **8A**, the ceramic collar **222'** is shown, in one variation, as extending only partially around sleeve **175** to cooperate with the radial angle of resecting electrode element **195'**. Further, the variation of FIG. **8** illustrates that the ceramic collar **222'** has a larger outside diameter than insulative layer **202**. Thus, friction may be reduced since the short axial length of the ceramic collar **222'** interfaces and slides against the interfacing insulative layer **200** about the inner surface of lumen **172** of outer sleeve **170**.

(41) In general, one aspect of the invention comprises a tissue resecting and extracting device (FIGS. **10A-11C**) that includes first and second concentric sleeves having an axis and wherein the second (inner) sleeve **175** has an axially-extending tissue extraction lumen therein, and wherein the second sleeve **175** is moveable between axially non-extended and extended positions relative to a tissue receiving window **176** in first sleeve **170** to resect tissue, and wherein the tissue extraction lumen **160** has first and second cross-sections. The second sleeve **175** has a distal end configured as a plasma electrode edge **180** to resect tissue disposed in tissue receiving window **176** of the first sleeve **170**. Further, the distal end of the second sleeve, and more particularly, the electrode edge **180** is configured for plasma ablation of a substantially wide path in the tissue. In general, the tissue extraction device is configured with a tissue extraction lumen **160** having a distal end portion with a reduced cross-section that is smaller than a cross-section of medial and proximal portions of the lumen **160**.

(42) In one aspect of the invention, referring to FIGS. **7A-7B** and **9A-9B**, the tissue extraction lumen **160** has a reduced cross-sectional area in lumen region **190A** proximate the plasma resecting tip or electrode edge **180** wherein said reduced cross section is less than 95%, 90%, 85% or 80% than the cross sectional area of medial and proximal portions **190B** of the tissue extraction lumen, and wherein the axial length of the tissue extraction lumen is at least 10 cm, 20 cm, 30 cm or 40 cm. In one embodiment of tissue resecting device **100** for hysteroscopic fibroid resecting and extraction (FIG. **1**), the shaft assembly **140** of the tissue resecting device is 35 cm in length.

(43) FIGS. **10A-10C** illustrate the working end **145** of the tissue resecting device **100** with the reciprocating resecting sleeve or inner sleeve **175** in three different axial positions relative to the tissue receiving window **176** in outer sleeve **170**. In FIG. **10A**, the resecting sleeve **175** is shown in a retracted or non-extended position in which the sleeve **175** is at its proximal limit of motion and is prepared to advance distally to an extended position to thereby electrosurgically resect tissue positioned in and/or suctioned into window **176**. FIG. **10B** shows the resecting sleeve **175** moved and advanced distally to a partially advanced or medial position relative to tissue resecting window **176**. FIG. **10C** illustrates the resecting sleeve **175** fully advanced and extended to the distal

limit of its motion wherein the plasma resecting electrode **180** has extended past the distal end **226** of tissue receiving window **176** at which moment the resected tissue strip **225** is excised from tissue volume **220** and captured in reduced cross-sectional lumen region **190A**.

(44) Now referring to FIGS. **10A-10C** and FIGS. **11A-11C**, another aspect of the invention comprises “tissue displacement” mechanisms provided by multiple elements and processes to “displace” and move tissue strips **225** in the proximal direction in lumen **160** of resecting sleeve **175** to thus ensure that tissue does not clog the lumen of the inner sleeve **175**. As can be seen in FIG. **10A** and the enlarged views of FIGS. **11A-11C**, one tissue displacement mechanism comprises a projecting element **230** that extends proximally from distal tip **232** which is fixedly attached to outer sleeve **170**. The projecting element **230** extends proximally along central axis **168** in a distal chamber **240** defined by outer sleeve **170** and distal tip **232**. In one embodiment depicted in FIG. **11A**, the shaft-like projecting element **230**, in a first functional aspect, comprises a mechanical pusher that functions to push a captured tissue strip **225** proximally from the small cross-section lumen **190B** of resecting sleeve **175** as the resecting sleeve **175** moves to its fully advanced or extended position. In a second functional aspect, the chamber **240** in the distal end of sleeve **170** is configured to capture a volume of saline distending fluid **244** from the working space, and wherein the existing RF electrodes of the working end **145** are further configured to explosively vaporize the captured fluid **244** to generate proximally-directed forces on tissue strips **225** resected and disposed in lumen **160** of the resecting sleeve **175**. Both of these two functional elements and processes (tissue displacement mechanisms) can apply a substantial mechanical force on the captured tissue strips **225** by means of the explosive vaporization of liquid in chamber **240** and can function to move tissue strips **225** in the proximal direction in the tissue extraction lumen **160**. It has been found that using the combination of multiple functional elements and processes can virtually eliminate the potential for tissue clogging the tissue extraction lumen **160**.

(45) More in particular, FIGS. **12A-12C** illustrate sequentially the functional aspects of the tissue displacement mechanisms and the explosive vaporization of fluid captured in chamber **240**. In FIG. **12A**, the reciprocating resecting sleeve **175** is shown in a medial position advancing distally wherein plasma at the resecting electrode edge **180** is resecting a tissue strip **225** that is disposed within lumen **160** of the resecting sleeve **175**. In FIG. **12A-12C**, it can be seen that the system operates in first and second electrosurgical modes corresponding to the reciprocation and axial range of motion of resecting sleeve **175** relative to the tissue receiving window **176**. As used herein, the term “electrosurgical mode” refers to which electrode of the two opposing polarity electrodes functions as an “active electrode” and which electrode functions as a “return electrode”. The terms “active electrode” and “return electrode” are used in accordance with convention in the art—wherein an active electrode has a smaller surface area than the return electrode which thus focuses RF energy density about such an active electrode. In the working end **145** of FIGS. **10A-11C**, the resecting electrode element **195** and its resecting electrode edge **180** must comprise the active electrode to focus energy about the electrode to generate the plasma for tissue resecting. Such a high-intensity, energetic plasma at the electrode edge **180** is needed throughout stroke X indicated in FIG. **12A-12B** to resect tissue. The first mode occurs over an axial length of travel of inner resecting sleeve **175** as it crosses the tissue receiving window **176**, at which time the entire exterior surface of outer sleeve **170** comprises the return electrode indicated at **185**. The electrical fields EF of the first RF mode are indicated generally in FIG. **12A**.

(46) FIG. **12 B** illustrates the moment in time at which the distal advancement or extension of inner resecting sleeve **175** entirely crossed the tissue receiving window **176**. At this time, the electrode sleeve **195** and its electrode edge **180** are confined within the mostly insulated-wall chamber **240** defined by the outer sleeve **170** and distal tip **232**. At this moment, the system is configured to switch to the second RF mode in which the electric fields EF switch from those described previously in the first RF mode. As can be seen in FIG. **12B**, in this second mode, the limited interior surface area **250** of distal tip **232** that interfaces chamber **240** functions as an active

electrode and the distal end portion of resecting sleeve **175** exposed to chamber **240** acts as a return electrode. In this mode, very high energy densities occur about surface **250** and such a contained electric field EF can explosively and instantly vaporize the fluid **244** captured in chamber **240**. The expansion of water vapor can be dramatic and can thus apply tremendous mechanical forces and fluid pressure on the tissue strip **225** to move the tissue strip in the proximal direction in the tissue extraction lumen **160**. FIG. **12C** illustrates such explosive or expansive vaporization of the distention fluid **244** captured in chamber **240** and further shows the tissue strip **225** being expelled in the proximal direction the lumen **160** of inner resecting sleeve **175**. FIG. **14** further shows the relative surface areas of the active and return electrodes at the extended range of motion of the resecting sleeve **175**, again illustrating that the surface area of the non-insulated distal end surface **250** is small compared to surface **255** of electrode sleeve which comprises the return electrode.

(47) Still referring to FIGS. **12A-12C**, it has been found that a single power setting on the RF source **150** and controller **155** can be configured both (i) to create plasma at the electrode resecting edge **180** of electrode sleeve **195** to resect tissue in the first mode, and (ii) to explosively vaporize the captured distention fluid **244** in the second mode. Further, it has been found that the system can function with RF mode-switching automatically at suitable reciprocation rates ranging from 0.5 cycles per second to 8 or 10 cycles per second. In trial, it has been found that the tissue resecting device described above can resect and extract tissue at the rate of from 2 grams/min to 8 grams/min without any potential for tissue strips **225** clogging the tissue extraction lumen **160**. In one embodiment, a negative pressure source **125** can be coupled to the tissue extraction lumen **160** to apply tissue-extracting forces to tissue strips in the lumen.

(48) Of particular interest, the fluid-capture chamber **240** defined by sleeve **170** and distal tip **232** can be designed to have a selected volume, exposed electrode surface area, length and geometry to optimize the application of expelling forces to resected tissue strips **225**. In one embodiment, the diameter of the chamber is 3.175 mm and the length is 5.0 mm which taking into account the projecting element **230**, provided a captured fluid volume of approximately 0.040 mL. In other variations, the captured fluid volume can range from 0.004 to 0.080 mL.

(49) In one example, a chamber **240** with a captured liquid volume of 0.040 mL together with 100% conversion efficiency in an instantaneous vaporization would require 103 Joules to heat the liquid from room temperature to water vapor. In operation, since a Joule is a W\*s, and the system reciprocate at 3 Hz, the power required would be on the order of 311 W for full, instantaneous conversion to water vapor. A corresponding theoretical expansion of 1700× would occur in the phase transition, which would results in up to 25,000 psi instantaneously (14.7 psi×1700), although due to losses in efficiency and non-instantaneous expansion, the actual pressures would be less. In any event, the pressures are substantial and can apply expelling forces sufficient to the expel the captured tissue strips **225** the length of the extraction channel in the probe.

(50) Referring to FIG. **12A**, the interior chamber **240** can have an axial length from about 0.5 mm to 10 mm to capture a liquid volume ranging from about 0.004 mL to 0.010 mL. It can be understood in FIG. **12A**, that the interior wall of chamber **240** has an insulator layer **200** which thus limits the electrode surface area **250** exposed to chamber **240**. In one embodiment, the distal tip **232** is stainless steel and is welded to outer sleeve **170**. The post element **248** is welded to tip **232** or machined as a feature thereof. The projecting element **230** in this embodiment is a non-conductive ceramic. FIG. **13** shows the cross-section of the ceramic projecting element **230** which is fluted, which in one embodiment has three flute elements **260** in three corresponding axial grooves **262** in its surface. Any number of flutes, channels or the like is possible, for example from 2 to about 20. The purpose of this design is to provide a significant cross-sectional area at the proximal end of the projecting element **230** to push the tissue strip **225**, while at the same time the three grooves **262** permit the proximally-directed jetting of water vapor to impact the tissue exposed to the grooves **262**. In one embodiment, the axial length D of the projecting element **230** is configured to push tissue entirely out of the reduced cross-sectional region **190B** of the electrode

sleeve element **195**. In another embodiment, the volume of the chamber **240** is configured to capture liquid that when explosively vaporized provided a gas (water vapor) volume sufficient to expand into and occupy at least the volume defined by a 10% of the total length of extraction channel **160** in the device, at least 20% of the extraction channel **160**, at least 40% of the extraction channel **160**, at least 60% of the extraction channel **160**, at least 80% of the extraction channel **160** or at least 100% of the extraction channel **160**.

(51) As can be understood from FIGS. **12A** to **12C**, the distention fluid **244** in the working space replenishes the captured fluid in chamber **240** as the resecting sleeve **175** moves in the proximal direction or towards its non-extended position. Thus, when the resecting sleeve **175** again moves in the distal direction to resect tissue, the interior chamber **240** is filled with fluid **244** which is then again contained and is then available for explosive vaporization as described above when the resecting sleeve **175** closes the tissue receiving window **176**. In another embodiment, a one-way valve can be provided in the distal tip **232** to draw fluid directly into interior chamber **240** without the need for fluid to migrate through window **176**.

(52) FIG. **15** illustrates another variation in which the active electrode surface area **250'** in the second mode comprises a projecting element **230** with conductive regions and non-conductive regions **260** which can have the effect of distributing the focused RF energy delivery over a plurality of discrete regions each in contact with the captured fluid **244**. This configuration can more efficiently vaporize the captured fluid volume in chamber **240**. In one embodiment, the conductive regions **250'** can comprise metal discs or washers on post **248**. In other variation (not shown) the conductive regions **250'** can comprise holes, ports or pores in a ceramic material **260** fixed over an electrically conductive post **248**.

(53) In another embodiment, the RF source **150** and controller **155** can be programmed to modulate energy delivery parameters during stroke X and stroke Y in FIGS. **12A-12C** to provide the optimal energy (i) for plasma resecting with electrode edge **180**, and (ii) for explosively vaporizing the captured fluid in chamber **240**. In one variation, the controller **155** can include an algorithm that activates the RF source **150** to delivery RF energy to working end as the resecting sleeve **175** moves in the distal direction towards its extended position to resect tissue but terminates RF energy delivery to the working end as the resecting sleeve **175** moves in the proximal direction towards its non-extended position. The termination of RF energy delivery during the proximal stroke of the resecting sleeve **175** eliminates energy delivery to electrode edge **180** when it is not resecting tissue which thus prevents unnecessary heating of distention fluid which would occur when RF energy is delivered during both the forward and backward strokes of the resecting sleeve.

(54) FIGS. **16-18** illustrate a fluid management system **500** that can be used when treating tissue in a body cavity, space or potential space **502** (FIG. **17**). The fluid management system **500** is depicted schematically in a hysteroscopic tissue resecting system **510** that is adapted for resecting and extraction of fibroids or other abnormal intra-uterine tissue using an endoscope or hysteroscope **512** and tissue resecting probe **515** that can be similar to those described above. FIG. **16** depicts the tissue resecting probe **515** with handle **516** and extending member including outer sleeve **518** with working end **520** (FIG. **17**) that can be introduced through working channel **522** extending through the body **523** and shaft **524** of the hysteroscope **512**. FIG. **16** further shows a motor **525** in handle **516** of the tissue resecting probe that is coupled to a controller and power supply by power cable **526**. FIG. **17** illustrates the working end **520** of the resecting probe **515** in a uterine cavity proximate a targeted fibroid **530**.

(55) Referring to FIGS. **16-17**, in general, the fluid management system **500** comprises a fluid source or reservoir **535** of a distention fluid **244**, a controller and pump system to provide fluid inflows and outflows adapted to maintain distension of a body space and a filter system **540** for filtering distention fluid **244** that is removed from the body cavity and thereafter returned to the fluid source **535**. The use of a recovered and filtered fluid **244** and the replenishment of the fluid source **535** is advantageous because (i) the closed-loop fluid management system can effectively

measure fluid deficit to thereby monitor intravasation and insure patient safety, (ii) the system can be set up and operated in a very time-efficient manner, and (ii) the system can be compact and less expensive to thereby assist in enabling office-based procedures.

(56) The fluid management system **500** (FIG. **16**) includes a computer control system that is integrated with the RF control system in an integrated controller **545**. The controller **545** is adapted to control first and second peristaltic pumps **546A** and **546B** for providing inflows and outflows of a distention fluid **244**, such as saline solution, from source **535** for the purpose of distending the body cavity. The first peristaltic pump may also be called an inflow pump or infusion pump herein. The second peristaltic pump may also be called an outflow pump or aspiration pump herein. The controller **545** and control algorithms are adapted to control the intra-cavity pressure during a tissue resecting and extracting procedure as depicted in FIG. **17**. In one embodiment shown in FIGS. **16-18**, the controller **545** controls the inflow pump **546A** to provide positive pressure at the outflow side **548** of the pump (FIG. **17**) to provide inflows of distention fluid **244** through inflow line **550** which is in communication with fitting **561** and fluid flow channel **108a** in hysteroscope **515**. The flow channel **108a** is described above in a previous embodiment and is illustrated in FIG. **3** above. The controller **545** further controls the outflow pump **546B** to provide negative pressure to the outflow line **555** at the inflow side **552** of the pump (FIG. **17**) to provide outflows of distention fluid **244** from the body cavity **502**. As described above, the explosive vaporization of fluid in the working end **525** of resecting probe **515** functions to expel tissue strips **225** proximally in the extraction channel **160** of resecting sleeve **175**, which can operate in conjunction with negative pressure in line **555** provided by pump **546B**. In operation, the outflow pump **546B** also operates to provide positive pressure on the outflow side **556** of pump **546B** in the second outflow line portion **555'** to pump outflows of distention fluid **244** through the filter system **540** and back to the fluid source **535**.

(57) In one system embodiment, the controller **545** operates to control pressure in cavity **502** by pressure signals from a pressure sensor **560** that is coupled to a fitting **562** in hysteroscope **512** which communicates with a flow channel **108b** (see FIG. **16**) that extends through the hysteroscope. In one embodiment, the flow channel **108b** has a diameter of at least 1.0 mm to allow highly accurate sensing of actual intra-cavity pressure. In prior art commercially-available fluid management systems, the intra-cavity pressure is typically estimated by various calculations using known flow rates through a pump or remote pressure sensors in the fluid inflow line that can measure back pressures. Such prior art fluid management systems are stand-alone systems and are adapted for use with a wide variety of hysteroscopes and endoscopes, most of which do not have a dedicated flow channel for communicating with a pressure sensor. For this reason, prior art fluid management systems rely on algorithms and calculations to only estimate intra-cavity pressure.

(58) In one embodiment, as depicted in FIG. **16**, the pressure sensor **560** is disposable and is detachably coupled to the endoscope **512** and is in fluid communication with the body cavity through a flow channel **108b** in the endoscope. The pressure sensor **560** is operatively coupled to controller **545** by cable **564**. The pressure sensor can be a biocompatible, piezoresistive silicon sensor of the type used in invasive blood pressure monitoring. For example, the sensor can be a piezoresistive silicon pressure sensor, Model No. 1620, available from Measurement Specialties, Ltd., 45738 Northport Loop West, Fremont, Calif. 94538. The sensor is designed with a pressure sensing element mounted on a ceramic substrate. A dielectric gel can be placed over the sensor element to provide electrical and fluid isolation. The sensor housing can have a Luer connection to couple to the endoscope **512**. Further, the sensor body can have a pressure relief valve for redundant overpressure protection (not shown).

(59) As can be understood from FIGS. **16** and **17**, the pressure sensor **560** is attached to the endoscope **512** to communicate with a fluid channel extending through the endoscope shaft to the body cavity. The fluid channel or sensor channel **108b** used by the pressure sensor **560** is independent of flow channel **108a** used for distention fluid inflows into the body cavity. In the



absence of fluid flows in the sensor channel **108b**, the fluid in the channel **108b** then forms a static column of incompressible fluid that changes in pressure as the pressure in the body cavity changes. With a sensor channel cross-section of 1 mm or more, the pressure within the pressure channel column and the pressure in the body cavity are equivalent. Thus, the pressure sensor **560** is capable of a direct measurement of pressure within the body cavity. In another variation shown schematically in FIG. **18**, the pressure sensor **560** as indicated in FIG. **16** can consist of two independent sensing elements **560'** and **560''** that both interface with fluid extending into the sensor **560** from the single fluid channel **108b**. The sensing elements **560'** and **560''** send pressure signals to controller **545** through cables **564'** and **564''** (FIG. **18**). At the initiation of a procedure, or during a procedure, the controller then can be configured to monitor or compare pressure signals from the independent sensing elements **560'** and **560''**. If the two sensors' pressure signals are not within a preselected range from one another, the controller **545** can provide a warning of sensor malfunction and/or terminate or modulate any ongoing operation of the fluid management system or resection device.

(60) FIG. **17** schematically illustrates the fluid management system **500** in operation. The uterine cavity **502** is a potential space and needs to be distended to allow for hysteroscopic viewing. A selected pressure can be set in the controller **545**, for example via a touch screen **565**, which the physician knows from experience is suited for distending the cavity **502** and/or for performing a procedure. In one embodiment, the selected pressure can be any pressure between 0 and 150 mm Hg. In one system embodiment, the inflow pump **546A** can operate as a variable speed pump that is actuated to provide a flow rate of up to 850 ml/min through first line or inflow line **550**. In this embodiment, the outflow pump **546B** can operate at a fixed speed to move fluid in the second line or outflow line **555**. In use, the controller **545** can operate the pumps **546A** and **546B** at selected matching or non-matching speeds to increase, decrease or maintain the volume of distention fluid **244** in the uterine cavity **502**. Thus, by independent control of the pumping rates of the inflow and outflow pumps **546A** and **546B**, a selected set pressure in the body cavity can be achieved and maintained in response to signals of actual intra-cavity pressure provided by sensor **560**.

(61) In one system embodiment, as shown in FIGS. **17** and **19**, the fluid management system **500** includes a filter module or system **540** that can include a first filter or tissue capturing filter **570** that is adapted to catch tissue strips **225** that have been resected and extracted from the body cavity **502**. A second filter or molecular filter **575**, typically a hollow fiber filter, is provided beyond the first filter **570**, wherein the molecular filter **575** is adapted to remove blood and other body materials from the distention fluid **244**. In particular, the molecular filter **575** is capable of removing red blood cells, hemoglobin, particulate matter, proteins, bacteria, viruses and the like from the distention fluid **244** so that endoscopic viewing of the body cavity is not obscured or clouded by any such blood components or other contaminants. As can be understood from FIGS. **16-19**, the outflow pump **546B** at its outflow side **556** provides a positive pressure relative to fluid flows into the filter module **540** to move the distention fluid **244** and body media through the first and second filters, **570** and **575**, and in a circulatory flow back to the fluid source **535**.

(62) Referring to FIG. **19**, in an embodiment, the first filter **570** comprises a container portion or vial **576** with a removable cap **577**. The inflow of distention fluid **244** and body media flows through line portion **555** and through fitting **578** into a mesh sac or perforate structure **580** disposed in the interior chamber **582** of the vial **576**. The pore size of the perforate structure **580** can range from about 200 microns to 10 microns. The lumen diameter of hollow fibers **585** in the second filter **575** can be from about 400 microns to 20 microns. In general, the pore size of perforate structure **580** in the first filter **570** is less than the diameter of the lumens of hollow fibers **585** in the second filter **575**. In one embodiment, the pore size of the perforate structure **580** is 100 microns, and the lumen size of the hollow fibers **585** in the molecular filter **575** is 200 microns. In one embodiment, the molecular filter **575** is a Nephros DSU filter available from Nephros, Inc., 41 Grand Ave., River Edge, N.J. 07661. In one variation, the filter **575** is configured with hollow

fibers having a nominal molecular weight limit (NMWL) of less than 50 kDa, 30 kDa or 20 kDa. (63) In another aspect of the invention, the molecular filter **575** is configured to filter large volumes of distention fluid, since the fluid flows are circulating. Additionally, the molecular filter **575** is configured to filter significant potential volumes of distention fluid that may be contaminated with blood, blood products and the like that will be mixed with the fluid. In one embodiment, the molecular filter **575** has a membrane surface area of at least 0.6 m.<sup>2</sup>, 0.8 m.<sup>2</sup>, 1.0 m.<sup>2</sup>, 1.2 m.<sup>2</sup> and 1.4 m.<sup>2</sup>, wherein the membrane surface area is defined as the total surface area of the lumens of the hollow fibers **585** in the molecular filter **575**. In another aspect of the invention, a method of fluid management can include distending a body space and maintaining a flow rate of up to 850 ml/min of a distention fluid flow into and out of a body space and thereafter through a filter system **540** capable of removing at least 20 ml, 40 ml or 60 ml of blood from the distention fluid **244**.

(64) Referring to FIG. **19**, it can be seen that the filter module **540** includes detachable connections between the various fluid flow lines to allow for rapid coupling and de-coupling of the filters and flow lines. More in particular, flow line **555** extending from the tissue resecting probe **515** has a connector portion **592** that connects to inlet fitting **578** in the first filter **546A**. Flow line portion **555'** that is intermediate the filters **546A** and **546B** has connector portion **596a** that connects to outlet fitting **596b** in first filter **542A**. The outflow end of flow line **555'** has connector **598a** that connects to inlet fitting **598b** of the second filter **546B**. The return flow line **600** that is intermediate the second **546B** and fluid source **535** has connector portion **602a** that connects to outlet fitting **602b** in second first filter **546B**. In one embodiment, at least one check valve **605** is provided in the flow path intermediate the filters **546A**, **546B** which for example can be in line **555'**, connectors **596a**, **598a** or fittings **596b**, **598b**. In FIG. **19**, a check valve **605** is integrated with the inlet end **608** of the second filter **546B**. In use, the operation of the system will result in substantial fluid pressures in the interior of the second filter, and the check valve **605** allows for de-coupling the first filter without escape of pressure and release of fluid media into the environment, for example, when the tissue resecting procedure is completed and the physician or nurse wishes to transport the vial **576** and tissue strips **225** therein to a different site for biopsy purposes. In general, a one-way valve such as check valve **605** can be provided at one or more locations in flow lines **555** and **555'** to prevent back flows of pressure through line **555** to the resecting device **515**. For example, a one-way valve **605'**, such as a float valve, can be provided at one or more locations in line **555** or fitting **578** as indicated by the dashed line in FIG. **19** (see also FIGS. **20-21**). A float valve **605''** can also be provided in line **550** proximate the saline source **535**.

(65) In one aspect, a fluid management system comprising a first fluid line **550** configured to carry distention fluid **224** from a fluid source **535** to a body space, a second fluid line **555**, **555'** and **560** configured to carry fluid from the body space to a first filter **570** and then to a second filter **575** and then back to the fluid source **535**, an outflow pump operatively coupled to the second fluid line and at least one check valve **605** in the second fluid line intermediate the first and second filters **570** and **575**.

(66) In one embodiment, the controller **545** of the fluid management system **500** is configured for calculation of a fluid deficit that is measured as a difference between a fluid volume delivered to the body space **502** and a fluid volume recovered from the body space during a medical procedure such as fibroid removal (see FIGS. **16-19**). A method of fluid management in a hysteroscopic procedure comprises providing a distention fluid source **535** (FIG. **17**) having a predetermined volume, introducing fluid (e.g., saline) from the source **535** through a first flow line or inflow line **550** into the uterine cavity and through a second flow line or outflow line **555** out of the cavity into a filter module **540** and through a further portion **600** of the second flow line back to the fluid source **535** wherein the interior volume of the first and second flow lines and the filter module when subtracted from the predetermined volume of the source **535** equals 2.5 liters or less. The instructions for use then can include the requirement that only a single 3 liter saline bag can be used

in any fibroid or polyp removal procedure, which in turn will insure that saline intravasation can never exceed 2.5 liters. In this variation, the predetermined volume of the source **535** can be 3.0 liters, as in a standard 3 liter saline bag, and the interior system volume can be at least 0.5 liters. (67) FIGS. **20** and **21** are schematic diagrams relating to the integrated operation of an RF tissue resecting probe **515** of the type described above and a fluid management system **500** of the type described above. In general, the controller **545**, RF generator **670** and fluid management system **500** are adapted to provide controlled flows of distention fluid into and out of a body cavity **502** while maintaining a targeted pressure within the body cavity while at the same providing RF energy delivery to the resecting probe contemporaneous with fluid flows. In one system embodiment, the system can operate in three different modes, all controlled by the controller **545**: (i) a diagnostic mode for hysteroscopy, (ii) a resecting treatment mode for tissue resection and extraction; and (iii) and a coagulation treatment mode for tissue coagulation.

(68) Referring to FIG. **20**, in diagnostic mode, the inflow or infusion pump **546A**, the outflow or aspiration pump **546B** and the pressure sensor **560** and monitoring system are all activated. In one embodiment, the touchscreen **565** on controller **545** has a graphical user interface (GUI) with fluid control settings that can be adjusted by the physician (FIG. **16**). The inflow pump **546A** can be toggled ON/OFF by touching the inflow pump button on the GUI. The targeted intra-cavity pressure can be set on the touchscreen **565**, for example from 0 to 150 mmHg or more (FIG. **16**).

(69) In a method of operation as shown in FIG. **20**, the physician sets a target intra-cavity pressure on the GUI and then activates the inflow pump **546A** which causes a flow of distention fluid **244** through the inflow or infusion line **550** and endoscope **512** into the body cavity **502**. In one embodiment, the inflow pump **546A** in diagnostic mode can be actuated on the touchscreen **565**. In the diagnostic mode, the controller **545** is configured to not actuate the outflow pump **546B** until the set pressure is attained or there is an overpressure condition. Thereafter, in one variation, the outflow pump **546A** will then operate at a fixed rate and the inflow pump speed can be modulated in response to signals from the pressure sensor to stabilize the pressure around the targeted cavity pressure. The actual intra-cavity pressure measured by the pressure sensor **560** can be displayed on the controller GUI (FIG. **16**).

(70) In order to stabilize fluid pressure in a body cavity, the controller **545** includes a pressure control algorithm that is configured as a feedback control loop. The controller microprocessor reads both the intra-cavity pressure set point and the actual cavity pressure based on signals from the pressure sensor **560**. In response to these two parameters, the algorithm calculates a delta value signal based on a generic proportional integral (PI) control algorithm. The delta value is sent to a digital to analog converter and fed into a motor amplifier that drives the inflow pump **546A**. The controller algorithm then minimizes the difference between the set pressure and the actual pressure by adjusting the speed of the inflow (infusion) pump **546A**.

(71) In one embodiment, the system further includes an actuator and algorithm for providing a rapid fluid inflow and fluid outflow for flushing the body cavity **502**, which for example can be an actuator button **672** on a footswitch assembly **675**. In this flushing method, the outflow (aspiration) pump **546B** is actuated to provide an increased level of outflow and then the pressure algorithm modulates the speed of the inflow (infusion) pump **564A** to maintain the targeted pressure in the cavity. Thus, in the diagnostic mode, the system can be actuated to rapidly flush the body cavity with fluid inflows and outflows while the controller algorithm maintains intra-cavity pressure as described above. The flow rate through the system and body cavity can be pre-set at 100 ml/min or greater, for example at 200 ml/min or 300 ml/min. In another embodiment, the physician may select a rapid flow rate on the touchscreen from 200 ml/min to 800 ml/min.

(72) In a non-diagnostic or therapeutic resecting mode for resecting tissue, referring to FIG. **21**, the controller **545** delivers radiofrequency energy to the bi-polar electrode arrangement of the probe **515** (see FIGS. **12A-12C**) to resect tissue and also actuates the two pumps to provide fluid inflows and outflows as described above. To operate in the resection mode, the physician can use the

touchscreen **565** (FIG. **16**) to enter a non-diagnostic (therapeutic) mode of operation. Thereafter, a first pedal **677a** on the footswitch **675** can be used to actuate the system in resection mode to resect tissue. Actuation of the first pedal **677a** results in the controller contemporaneously: (i) activating the outflow pump **546B** at a fixed speed to provide outflows at a rate of 400 ml/min to 850 ml/min; (ii) activating the inflow pump **564A** which has a rotation speed controlled and modulated by the controller **545** as described above to maintain a targeted pressure in the body cavity; (iii) delivering DC voltage to the motor **525** of the resecting probe **515** to reciprocate the resecting sleeve **175**; and (iv) delivering RF energy to the bi-polar electrode arrangement of the resecting probe **515**. In one embodiment, the RF generator **670** and controller **545** provide a variable DC voltage from 5-20 volts to the motor **525** of the resecting probe, a peak RF power of 200 watts, and a peak RF voltage of 240 volts at a 148 kHz frequency.

(73) In the resection mode, the controller's pressure algorithm operates in a dynamic flow condition wherein the outflow of distention fluid **244** from the body cavity **502** varies as it will be dependent on the rate of tissue resection and the speed at which resected tissue strips **225** and fluid **244** can move through the extraction channel **160**. The intra-cavity pressure is maintained at the set pressure by the feedback loop which operates in a similar manner as described above when the system operates in the diagnostic mode. Resected tissue strips **225** are moved through the system as described above and extracted from the body cavity and probe through the outflow line **555**. The outflows of fluid carries resected tissue, blood and other body fluids into the first filter **570** and then the second filter **575** as can be seen in FIG. **21**. When the physician releases pressure on the first pedal **677a**, the resecting probe **515** is then de-activated and only the inflow **546A** will remain active in controlling the intra-cavity pressure as described previously.

(74) In the coagulation mode, the controller **545** and controller algorithm activates the bi-polar electrode arrangement of probe **515** to coagulate tissue and also to intermittently actuate the fluid flow functions as described above. The motor **525** in the probe handle is not activated, and the resecting sleeve **175** is positioned in an intermediate position in the window **517** in the outer sleeve **518** (cf. FIG. **12A**). The intermediate position of the resecting sleeve **175** in the window **517** is a default position that occurs each time that DC current to probe motor **525** is terminated.

(75) To initiate operation under the coagulation mode, it is assumed that the physician has previously selected the non-diagnostic (therapeutic) mode of operation using the touchscreen **565**. The physician then can actuate a second pedal **677b** on the footswitch **675** to coagulate tissue. Actuation of the second pedal **677b** results in the controller contemporaneously: (i) delivering RF energy to the bi-polar electrode arrangement of the resecting probe **515**; and (ii) intermittently actuating the inflow and outflow pumps **546A** and **546B** to cause a circulating fluid flow while maintaining intra-cavity pressure as described above. In one embodiment, the dual pumps operate for 1 to 8 seconds after a continuous interval of RF energy delivery for greater than 10 seconds. The fluid flow rate can be from 100 to 600 ml/min. Further, each time the physician terminates RF energy delivery, the inflow and outflow pumps **546A** and **546B** can be activated for 1 to 10 seconds. The intermittent circulating flows in the coagulation mode are adapted to aid in visualization and further to prevent heating of distention fluid **244** in the body cavity **502** as a result of the RF energy application. In one embodiment, the RF generator **670** and controller **545** provide bi-polar radiofrequency outputs for coagulation at a peak RF power of 110 watts and a peak voltage of 200 volts at a 148 kHz frequency.

(76) In operating the system in any diagnostic or therapeutic mode, the controller **545** has an over-pressure protection algorithm in the event that pressure exceeds the targeted intra-cavity set pressure. In one embodiment, if the intra-cavity pressure exceeds the set pressure by a predetermined amount for a pre-selected time interval, then the controller **545** can activate the outflow pump **546B** at a higher pumping rate than the inflow pump **546A** until the measured fluid pressure in the cavity drops below the set pressure. Optionally, the controller **545** can slow or stop the inflow pump **546A** until intra-cavity pressure drops to the targeted level. In one variation, the

pump or pumps can be activated to reduce intra-cavity pressure if the measured pressure exceeds the set pressure by 5 mmHg for greater than 1 second, 2 seconds or 5 seconds.

(77) Another mechanism for over-pressure protection is provided in the form a pressure relief valve **680** as depicted in FIG. **18**. In one variation, the pressure relief valve **680** is coupled the housing **682** of sensor **560** and communicates with flow channel **108b'** in the sensor **560** to allow fluid venting and pressure relief through the sensor body. The pressure relief valve **680** can relieve pressure at a suitable pressure greater than 100 mm Hg, for example 100 mm Hg, 125 mmHg, 150 mmHg or another predetermined pressure. Thus, if intra-cavity pressure exceeds the targeted maximum level, the controller **545** provides an algorithm-based pressure relief mechanism by modulating the pumps while the check-valve **680** provides a back-up form of pressure relief (FIG. **18**). Further, the system can include a manual pressure relief valve **688** in a disposable fitting **712** coupled to the endoscope for additional safety redundancy (FIG. **20**).

(78) In another aspect of the invention, the controller **545** includes an algorithm that is adapted to de-activate a powered resection device in the event that the actual pressure in the treatment site drops below a predetermined threshold level. The controller **545** is provided with continuous signals of actual pressure in the site from the pressure sensor assembly **560** (FIG. **18**). In one variation, if the actual pressure in the site drops below an allowable threshold pressure level, then the controller algorithm can automatically de-activate the motor that drives a reciprocating or rotating resecting member. In another variation, the controller algorithm can de-activate RF energy delivery to the working end of a resecting device **515** as shown in FIGS. **16-17**. In this variation wherein RF energy delivery is de-activated, the algorithm may permit continued movement of the resecting sleeve **175** for a selected interval and then RF may be re-activated after the intra-cavity pressure level increases above the predetermined threshold either instantaneously or when such pressure exceeds the threshold level for a selected interval, for example of 1 to 10 seconds. In another variation, the controller algorithm can de-activate both the motor drive and RF delivery upon a fall in pressure below the threshold pressure level. The threshold pressure level in this algorithm can be any predetermined pressure, for example, 100 mmHg or less, 50 mmHg or less, or 25 mmHg or less. In one variation, the threshold pressure level is set at 15 mmHg.

(79) In one aspect of the invention relating to treating tissue and directly sensing pressure in a body space, a method comprises (i) accessing a body space or potential body space with at least one system component configured to provide an inflow of distention fluid **244** to the space and an outflow of fluid from the space, the at least one component including an electrosurgical tissue resecting probe, (ii) providing a pressure sensor coupled to the at least one component configured to measure actual pressure in the space, (iii) sensing pressure within the space and modulating inflow and outflow rates in response to the sensed pressure to achieve or maintain a pressure set point in the space, and (iv) operating the electrosurgical probe at first RF parameters to resect tissue. The probe can be operated at second RF parameters to coagulate tissue. The step of modulating the inflow rates can provide inflows between 0 ml/min and 800 ml/min. The pressure set point can be between 30 mmHg and 200 mmHg. As described above, the step of sensing pressure is accomplished with a sensor coupled to an independent fluid channel that is separate from the flow channels carrying the distention fluid inflows and outflows.

(80) In general, a fibroid treatment system corresponding to the invention comprises a controller, an inflow pump operated by the controller and configured to provide fluid inflow through a flow path to a patient's uterine cavity, an outflow pump operated by the controller and configured to provide fluid outflow through a flow path to the uterine cavity; and a motor driven resecting device operated by the controller. The resecting device comprise an elongate introducer having a tissue extraction channel (**190A**, **190B** in FIG. **6A**) therein with a diameter of no less than 2.4 mm and an outer sleeve **170** having a diameter of no more than 3.8 mm. The resecting device is adapted to remove fibroid tissue at a rate of at least 2 gm/min. In this variation, the controller can be configured to actuate the inflow and outflow pumps in response to signals of fluid pressure in the

uterine cavity and to maintain the target pressure as described above. More in particular, the signal of fluid pressure can be provided by a pressure sensor coupled to a static fluid column communicating with the uterine cavity. In another variation, the controller can be configured to operate the resecting device in response to at least one parameter selected from a group consisting of an inflow pump speed, an outflow pump speed and signals of fluid pressure in the uterine cavity as will be described further below. In another aspect of the invention, a fluid management system **500** and cooperating electrosurgical probe are provided that include an inflow pump **546A** configured for providing an inflow of a distention fluid into a site in a patient's body, a control system configured for operator selection of at least first and second flow control modes wherein the first flow control mode is configured for tissue resection and operates the inflow pump to provide a first peak inflow rate and wherein the second flow control mode is configured for tissue coagulation and operates the inflow pump to provide a second peak inflow rate. Typically, the first peak inflow rate is greater than the second peak inflow rate. In one variation, the first peak inflow is 1,000 ml/min, 800 ml/min, 600 ml/min or 500 ml/min. The fluid management and procedure system include a control system configured for operator-selection of a pressure set point at the site. As described above, the fluid management system and controller are configured to operate the inflow pump and an outflow pump to provide an outflow of distention fluid from the site to achieve or maintain the pressure set point in both the first and second flow control modes.

(81) Referring to FIGS. **16-21**, a fluid management system **500** of the invention comprises an inflow pump **546A** configured for providing an inflow of a distention fluid **244** into a site in a patient's body and an outflow pump **546B** configured for providing an outflow of fluid from the site, and a controller **545** configured for operator-selection of at least first, second and third flow control modes wherein the first flow control mode is configured for a diagnostic procedure and provides an inflow rate up to 800 ml/min, wherein the second flow control mode is configured for a tissue resection procedure and provides an inflow rate up to 1,000 ml/min, and wherein the third flow control mode is configured for a tissue coagulation and provides an inflow rate up to 800 ml/min with intermittent outflows at pre-selected time intervals.

(82) Still referring to FIGS. **16-21**, a fluid management and resection system corresponding to the invention comprises an elongated assembly configured for accessing and performing a procedure in a site in a patient's body, the system components including an endoscope, a tissue resecting probe, a fluid source and tubing set, inflow and outflow pumps and a controller wherein the inflow pump is configured for providing an inflow of fluid from the fluid source through a first channel in the assembly to the site, wherein the outflow pump is configured for providing an outflow of fluid through a second channel in the assembly from the site and wherein the controller is configured for contemporaneous control of the probe in at least one mode of operation and the inflow and outflow pumps to provide and maintain an operator-selected pressure set point at the site.

(83) The system further includes a disposable pressure sensor detachably coupled to a system component, and in one variation, the pressure sensor is operatively coupled to a third channel in the system which typically is in the endoscope. In another variation, a pressure sensor is operatively coupled to the tubing set. Typically, the first channel described above is in the endoscope shaft **524** and the second channel is in the tissue resecting probe **515**.

(84) In another aspect of the invention, referring to FIGS. **20-21**, the fluid management system includes a fluid source **535**, typically a saline bag, with a sealed outflow port **702** and a inflow line tubing **550** that has a connector end **705** including at least one barb feature configured to permit said connector end **705** to advance into and spike the outflow port **702** but prevents withdrawal of said connector end **705** from the outflow port **702**.

(85) In another aspect of the invention, the fluid management system **500** (FIGS. **16-17**) includes controller algorithms that are adapted to detect a significant fluid leak or loss within the system when deployed and in use in a diagnostic or therapeutic procedure. Such a leak can consist of fluid loss anywhere in the fluid path, such as at a connector in the inflow or outflow lines (**550**, **555**) or

through the cervical canal around the elongated shaft **524** of the endoscope **512** (see FIG. 17). (86) In order to determine a leak or fluid loss, a controller algorithm continuously monitors the input voltage to the motor of the inflow or infusion pump **546A** wherein such input voltage corresponds directly to pump speed and thus corresponds to the fluid inflow rate. The algorithm further continuously monitors the input voltage to the motor of the outflow or aspiration pump **546B** which corresponds directly the fluid outflow rate. During such continuous monitoring, if the algorithm determines that the inflow pump motor is operating at an input voltage (inflow rate) that exceeds a predetermined threshold voltage level, then a timer is started. The threshold voltage level is a function of the set pressure, the actual intra-cavity pressure and which of the operational modes in operation at the time (diagnostic mode, resection mode, etc.). In each of the operational modes, the input voltage of the outflow pump (outflow rate) is different to meet the objectives of each mode. Thus, for each different mode and corresponding outflow rate, a different threshold voltage, inflow rate and time interval is used to determine if there exists an unwanted fluid loss. In another variation, a controller algorithm can detect a leak or fluid loss in the system using a linear fit curve that relates infusion motor voltage to an elapsed time interval to signal the leak or fluid loss. This type of algorithm may allow for faster detection of a fluid loss in operating modes in which the inflow pump motor operates at higher speeds, such as in a resection mode. In other words, the fluid loss could be detected earlier in cases in which there is a higher rate of loss. Test data can be collected to measure fluid loss at different motor speeds over a time interval to develop such a linear fit curve.

(87) If the timer exceeds a pre-selected time interval during which input voltage of the inflow pump motor exceeds the predetermined voltage threshold, the controller then will display a notification warning and/or audible or visual alarm to indicate a leak or fluid loss. The length of the pre-selected interval also can vary depending on the severity of the fluid inflow rate, that is, the input voltage to the inflow pump motor, in any of the system's operating modes. As the inflow rate increases above the nominal inflow rate in any mode, the time interval preceding the fluid loss warning or alarm will be decreased. In one variation, the predetermined voltage threshold level can correspond to inflow rates of at least 25 ml/min, at least 50 ml/min or at least 100 ml/min and the pre-selected time interval can be at least 1 second, at least 5 seconds or at least 10 seconds.

(88) In another aspect of the invention, the controller **545** includes algorithms that are adapted to detect kinks or clogs in the infusion tubing of inflow line **550** or the aspiration tubing of outflow line **555**. It is possible for the flexible tubing of either the inflow line **550** or outflow line **555** to be kinked which may remain temporarily unnoticed by the physician and the nursing staff. If the inflow line **550** is kinked, the decrease in fluid inflows into the treatment site will result in a loss of pressure in the site and the working space may collapse. A kink in the outflow line **555** can lead to an unwanted fluid pressure increase in the treatment site.

(89) In order to rapidly detect a kink in the infusion line **550** on the positive pressure side of the inflow pump **564A**, a controller algorithm is adapted to provide a kinked tubing warning if the calculated power driving the inflow pump motor exceeds a predetermined value over a pre-selected time interval. Such a predetermined value depends on the motor, gear box, pump head, and a predetermined pressure limit. As can be understood from the above description of the dual pump system, the motor power directly corresponds to the pressure on the positive pressure side of the inflow pump **564A**. As the pressure in the inflow tubing increases as a result of a kink or clog in the tubing, the hydraulic load on the pump rollers from the tubing will increase, which transfers load to the inflow pump motor. This increase in load on the motor then results in an increase in the current which is required to drive the pump motor at the targeted speed. The controller **545** includes an algorithm for maintaining the pump speed (and corresponding flow rate) at a predetermined level, no matter the load, during use of the fluid management system in its various modes. The power value is measured by a controller algorithm, and at the predetermined limit, the algorithm can (i) display a warning of a blocked fluid flow which can relate to kinked tubing or a clog in the flow

paths or filter 575; (ii) display a message or warning that the molecular filter 575 may be clogged; or (iii) display a message to exchange the filter 575. The algorithm can further interrupt the procedure by de-activating the pumps 546A, 546B, and/or by de-activating the power to any tissue-resecting device 515 in use.

(90) The fluid management system 500 further includes a controller algorithm for detecting a kink or clog in the outflow line 555 on the negative pressure side of the outflow pump 546B. This kink detection is accomplished by monitoring the motor voltage of both pump motors. If the system is being operated in either the resection mode or diagnostic mode, the algorithm first checks to determine if the outflow pump 546B is in an ON state, and then checks that voltage applied to the inflow pump 546A. If the motor of inflow pump 546A is operating at a voltage below a predetermined threshold level, then a timer is started. The predetermined voltage threshold of the inflow pump motor is selected based on the expected input motor voltage during the resection and diagnostic modes. The typical fluid outflow rate from the uterine cavity during the resection and diagnostic modes is 250 to 500 ml/minute, a flow rate which requires a minimum motor voltage input on the inflow pump motor to maintain pressure. If the outflow from the uterine cavity decreases or stops as a result of a kink in the outflow line 555, then the actual intra-cavity pressure would remain at a relatively static level. In this static condition, the input voltage of the inflow pump motor would be below the predetermined threshold input voltage, and as such, the kink detection timer would be initiated. When the timer exceeds a pre-selected time interval ranging from 5 seconds to 120 seconds, the algorithm is adapted to provide a kinked tubing warning. Additionally, the algorithm can interrupt the procedure by de-activating the pumps (546A, 546B) and/or by de-activating the power to any resection device 515 in use.

(91) The fluid management system 500 further includes a controller algorithm for detecting a kink in the tubing of outflow line 555 on the positive pressure side of the outflow pump 546B. The controller algorithm detects such a kink in the outflow line 555 if the measured motor current on the motor driving the outflow pump 546B exceeds a predetermined level. The predetermined level again depends on the motor, gear box, pump head, and a predetermined pressure limit. The motor current directly corresponds to the pressure on the positive pressure side of the pump 546B. As the pressure in the tubing increases (as a result of a tubing kink or a clogged filter) the hydraulic load onto the pump rollers from the tubing increases, which transfers load to the motor. This increase in load to the motor increases the current required to drive the motor at the targeted speed and flow rate. As described previously, the controller 545 includes an algorithm that maintains the pump speed at a predetermined level during use of the fluid management system in various modes. Thus, the kink detection algorithm measures the current that drives the outflow pump motor, and at the predetermined current limit over a pre-selected time interval, the algorithm can (i) display a warning of kinked tubing; (ii) display a message or warning that the molecular filter 575 is clogged; or (iii) display a message to exchange the filter 575. Additionally, the algorithm can automatically interrupt the procedure by de-activating the pumps (546A, 546B) and/or by de-activating the power to any resection device 515 in use in response to detection of the kinked tubing or clog in a flow path.

(92) In another aspect of the invention, the controller 545 includes algorithms that are adapted to further control and optimize fluid pressure in a site during a tissue resection interval that uses a feedback control loop to maintain the targeted set pressure. The feedback control loop consists of utilizing the pressure sensor 560 to monitor actual pressure in the site, and then utilizing controller algorithms to modulate speeds of both the inflow pump 546A and the outflow pump 546B (FIG. 21). More in particular, when the physician initiates tissue resection with a tissue resecting device 515 as shown in FIGS. 16-17 and 21, the tissue volume interfacing the window 517 (FIG. 21) will at least partially block the window and thus begin to slow the fluid outflow through the extraction channel 160 in the inner sleeve 175. As a result of the reduction in outflow, signals from the pressure sensor 560 to the controller 545 will indicate an increase in actual pressure in the site,



which then under previously described algorithms will cause a reduction in the input voltage in the inflow pump motor to thus slow down the fluid inflow rate. If the condition of reduced outflow continues for a first pre-selected time interval, the controller algorithm then will recognize that the resecting device is resecting tissue and sends a tissue-engagement signal to the controller. After a subsequent or second pre-selected time interval, the algorithm will cause the controller **545** to reduce the input voltage of the outflow pump motor (and fluid outflow rate) from a higher voltage level (e.g., 15 to 30 volt range) to a lower voltage (e.g., 5 to 12 volt range) and contemporaneously will put the inflow pump into a “ready” state. In this ready state, if a sudden decrease in actual pressure in the site were signaled by the pressure sensor **560**, then the algorithm would cause delivery of a maximum voltage (e.g., 30 volts, instead of nominal voltage) to the inflow pump motor to thus cause the maximum fluid inflow into the site. Upon such a sudden decrease in pressure, the algorithm then sends a tissue-disengagement signal to the controller, which actuates the inflow pump at a maximum voltage as described above. In normal operating conditions, the nominal inflow pump voltage may be in the 10 to 20 volt range. The objective of this pressure maintenance algorithm is to anticipate a sudden decrease in pressure in the site when the window **517** in the resecting device is cleared of tissue while the resecting device is operating, or when tissue chips are cleared through the extraction channel **160** which then results in a rapid increase in outflow. The then ongoing decreased outflow pump voltage also reduces the outflow rate, and the “ready” state of the inflow pump insures that when the sudden tissue-clearing condition (tissue-disengagement signal) occurs, the inflow pump **546A** is activated at its maximum voltage and inflow rate to match or exceed the outflow rate which then will prevent any drop in actual pressure in the site. The maximum inflow rate and the reduced outflow rate will continue until the targeted set pressure is maintained for a pre-selected interval that can range from 0.1 second to 10 seconds.

(93) Another method of operating a fluid management system and RF resecting probe as depicted in FIGS. **16-21** comprises (i) accessing a site in a patient's body with a distal end of an endoscope and working end of an electrosurgical probe, (ii) delivering RF energy to the working end to apply energy to tissue at the site, (iii) contemporaneously operating a fluid management system to provide a selected rate of a fluid inflow to, and fluid outflow from, the site, (iv) detecting a change of a signal of an electrical parameter of the probe during operation and in response to detecting said change, switching at least one operational parameter of said fluid management system. Typically, the electrical parameter can include at least one of an impedance level, a power level, a voltage level and a current level. The operational parameter of the fluid management system that can be modulated includes at least one of a rate of fluid inflow to the site, a rate of fluid outflow through a system outflow channel from the site, a positive pressure level in communication with the fluid inflow channel, a negative pressure level in communication with the fluid outflow channel, a targeted pressure set point at the site and a rate of change of any of the preceding. In another variation, the at least one operational parameter can include an algorithm for operating a pressure sensing system configured to determine fluid pressure at the site. In the method described above, the applied energy can be adapted to ablate and resect tissue or to coagulate tissue.

(94) While certain embodiments of the present invention have been described above in detail, it will be understood that this description is merely for purposes of illustration and the above description of the invention is not exhaustive. Specific features of the invention are shown in some drawings and not in others, and this is for convenience only and any feature may be combined with another in accordance with the invention. A number of variations and alternatives will be apparent to one having ordinary skills in the art. Such alternatives and variations are intended to be included within the scope of the claims. Particular features that are presented in dependent claims can be combined and fall within the scope of the invention. The invention also encompasses embodiments as if dependent claims were alternatively written in a multiple dependent claim format with reference to other independent claims.

## Claims

1. A fluid management system, comprising: an inflow pump configured to pump fluid from a fluid supply source to a treatment site within a patient at a flow rate; and a controller configured to operate at a target flow rate in a flow control mode; wherein in the flow control mode, the controller is configured to maintain the target flow rate while monitoring a measured pressure communicated to the controller from a pressure sensor; wherein when the measured pressure reaches a preset pressure threshold, the controller is configured to automatically switch from the flow control mode to a pressure override mode in which the controller automatically reduces the flow rate below the target flow rate to return the measured pressure at or below the preset pressure threshold.
2. The fluid management system of claim 1, further comprising an outflow pump configured to provide a fluid outflow from the treatment site.
3. The fluid management system of claim 2, wherein the pressure override mode includes activating the outflow pump at a speed greater than the inflow pump to reduce the flow rate below the target flow rate until the measured pressure drops below the preset pressure threshold.
4. The fluid management system of claim 3, wherein the pressure override mode includes activating the outflow pump at a speed greater than the inflow pump to reduce the flow rate below the target flow rate if the measured pressure exceeds the preset pressure threshold by for a preselected time interval.
5. The fluid management system of claim 2, wherein the pressure override mode includes slowing the inflow pump to reduce the flow rate below the target flow rate until the measured pressure drops below the preset pressure threshold.
6. The fluid management system of claim 5, wherein the pressure override mode includes slowing the inflow pump to reduce the flow rate below the target flow rate if the measured pressure exceeds the preset pressure threshold for a preselected time interval.
7. The fluid management system of claim 2, wherein the pressure override mode includes stopping the inflow pump to reduce the flow rate below the target flow rate until the measured pressure drops below the preset pressure threshold.
8. The fluid management system of claim 7, wherein the pressure override mode includes stopping the inflow pump to reduce the flow rate below the target flow rate if the measured pressure exceeds the preset pressure threshold for a preselected time interval.
9. The fluid management system of claim 1, wherein the measured pressure is an intracavity pressure.
10. The fluid management system of claim 9, wherein the preset pressure threshold is an intracavity pressure limit.
11. The fluid management system of claim 1, wherein the controller is configured to switch from the pressure override mode back to the flow control mode when the measured pressure falls below the preset pressure threshold.
12. The fluid management system of claim 1, wherein the controller is configured to switch from the pressure override mode to an adjusted flow control mode when the measured pressure falls below the preset pressure threshold.
13. The fluid management system of claim 12, wherein the controller is configured to operate at the reduced flow rate of the pressure override mode when in the adjusted flow control mode.
14. The fluid management system of claim 1, wherein the controller is configured to operate at a second target flow rate in a second flow control mode, the second target flow rate being less than the target flow rate.
15. The fluid management system of claim 14, wherein the flow control mode is configured for tissue resection and the second flow control mode is configured for tissue coagulation.

16. The fluid management system of claim 1, wherein the controller is configured to operate at a second target flow rate in a second flow control mode and a third target flow rate in a third flow control mode.

17. The fluid management system of claim 16, wherein the second target flow rate is different from the first target flow rate and the third target flow rate.

18. The fluid management system of claim 17, wherein the third target flow rate is less than the second target flow rate.

19. The fluid management system of claim 18, wherein the flow control mode is configured for a diagnostic procedure, the second flow control mode is configured for a tissue resection procedure, and the third flow control mode is configured for a tissue coagulation procedure.

20. A method of controlling fluid flow in a fluid management system, wherein the fluid management system comprises an inflow pump configured to pump fluid from a fluid supply source to a treatment site within a patient at a flow rate and a controller configured to operate at a target flow rate in a flow control mode, the method comprising: setting parameters within the controller, wherein the parameters include the target flow rate and a preset pressure threshold; operating the controller in the flow control mode, wherein the controller maintains the target flow rate while monitoring a measured pressure communicated to the controller from a pressure sensor; when the measured pressure reaches the preset pressure threshold, automatically switching the controller from the flow control mode to a pressure override mode in which the controller automatically reduces the flow rate below the target flow rate to return the measured pressure at or below the preset pressure threshold; and returning to the flow control mode when the measured pressure falls below the preset pressure threshold.

---