

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12398784
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Dobroth; Thomas J.

Rotary speed reducer

Abstract

A mechanism including a first pair of races having a first pair of raceways and a first rolling element operable to roll between the first pair of raceways, wherein at least one of the first pair of raceways has a substantially variable curvature along at least a portion of a path of the first rolling element. A program product that determines a solution by adjusting the curvature of a first pair of raceways on opposite sides of a rolling element, at least one of the first pair of raceways having a substantially variable curvature along the contact points in the direction of the corresponding range of motion for the rolling element.

Inventors:	Dobroth; Thomas J. (Sunnyvale, CA)
Applicant:	21GEO Corp. (Sunnyvale, CA)
Family ID:	1000008781291
Assignee:	21GEO Corp. (Sunnyvale, CA)
Appl. No.:	18/092197
Filed:	December 30, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230375074 A1	Nov. 23, 2023

Related U.S. Application Data

continuation parent-doc US 16535048 20190807 US 11692613 child-doc US 18092197
us-provisional-application US 62715274 20180807
us-provisional-application US 62742431 20181007

Publication Classification

Int. Cl.: **F16H1/32** (20060101); **F16C19/26** (20060101); **F16C33/58** (20060101); B67B7/04 (20060101)

U.S. Cl.:

CPC **F16H1/32** (20130101); **F16C19/26** (20130101); **F16C33/585** (20130101); B67B7/0417 (20130101)

Field of Classification Search

CPC: F16H (1/32)

USPC: 475/168

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1706180	12/1928	George	475/168	F16H 25/06
1773568	12/1929	Lorenz	475/179	F16H 1/32
3439562	12/1968	Bickley	475/168	F16H 25/06
3472097	12/1968	Paul	475/168	F16H 3/70
4552037	12/1984	Distin, Jr.	475/159	F16H 1/32
4604916	12/1985	Distin, Jr.	475/168	F16H 25/06
6314826	12/2000	Cunningham	475/168	F16H 25/06
8162790	12/2011	Imase	475/168	F16H 1/32
11692613	12/2022	Dobroth	74/640	F16H 1/32

Primary Examiner: Estremsky; Sherry L

Attorney, Agent or Firm: Witkowski Law

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This is a Continuation Application of U.S. Non-Provisional application Ser. No. 16/535,048, filed on Aug. 7, 2019, entitled “Rolling-Contact Bearings”, now U.S. Pat. No. 11,692,613, issued Jul. 4, 2023, which claims the benefit of U.S. Provisional Application No. 62/715,274, filed on Aug. 7, 2018, and claims the benefit of U.S. Provisional Application No. 62/742,431, filed on Oct. 7, 2018, all of which are expressly incorporated by reference herein in their entirety.

BACKGROUND

Technical Field

(1) This disclosure relates generally to the field of machines and mechanisms. More particularly, the disclosure relates to machines and mechanisms that employ rolling-contact bearings.

Background Art

- (2) Bearings are among the most useful mechanical devices. They are commonly employed in machines and mechanisms in a wide range of applications. For example, bearings can be found in drawer slides, refrigerators, air conditioners, washing machines and dryers. Automobiles may have dozens of bearings.
- (3) Bearings are typically designed to receive a load having certain characteristics, within a space specified, and have a satisfactory life for a particular application, considering issues such as fatigue loading, friction, heat, corrosion resistance, kinematic issues, material properties, lubrication, machine tolerances, assembly, use and cost.
- (4) A typical structure of a bearing includes an inner ring and an outer ring enclosing multiple ball bearings. The ball bearings roll between an inner bearing ring and an outer bearing ring. The bearing rings are sometimes referred to as races. The ball bearing rolls between surfaces of the inner and outer races. The surfaces in contact with the bearings as it slides or rolls between the races are sometimes referred to as raceways. Some bearings employ separators that keep the ball bearings spaced apart on the races.
- (5) Other bearing elements are roller bearings, sometimes referred to as pins.
- (6) A class of bearing in which the main load is transferred from one component to the other through the bearing elements in rolling contact rather than sliding contact is generally referred to as a rolling-contact bearing, an antifriction bearing, or a rolling bearing. Rolling typically has less friction than sliding and therefore rolling bearings tend to be more energy efficient than bearings that slide.

SUMMARY

- (7) Embodiments include a mechanism that has at least one rolling element operable to roll on a corresponding path between the pair of raceways, wherein at least one of the pair of raceways has a substantially variable curvature along a plurality of contact points with at least one of the rolling elements along at least a portion of the corresponding path.
- (8) Mechanisms as used herein is meant to include basic bearings including those claimed herein, such as the bearing element described in the preceding paragraph, to complex machines including numerous bearing elements working in conjunction with gears, cams, and multi-bar linkages.
- (9) Embodiments include a mechanism having a the pair of raceways operable to substantially oppose each other at the plurality of contact points with the rolling element along at least a portion of the path.
- (10) Embodiments include a mechanism wherein the rolling element does not substantially slide on either of the pair of raceways.
- (11) Embodiments include a mechanism wherein the first rolling element is constrained to roll between two endpoints between the pair of raceways.
- (12) Embodiments include a mechanism wherein the first pair of raceways form a closed loop, the rolling element operable to roll along the path around the closed loop.
- (13) Embodiments include a mechanism wherein the first pair of raceways have a repeating pattern along the first path of the first rolling element.
- (14) Embodiments include a mechanism wherein the repeating pattern comprises a plurality of regularly spaced lobes.
- (15) Embodiments include a mechanism wherein at least one of the first pair of raceways has an irregular shape.
- (16) Embodiments include a mechanism wherein at least some of the rolling element are ball bearings.
- (17) Embodiments include a mechanism wherein at least some of the rolling element are roller bearings.
- (18) Embodiments include a mechanism wherein the one of the first pair of races is coupled to one end of a linkage bar.
- (19) Embodiments include a mechanism wherein the first rolling element is a split pin with at least

two shape profiles.

(20) Embodiments include a second mechanism that has at least one rolling element operable to roll on a corresponding path between the pair of raceways, wherein at least one of the pair of raceways has a substantially variable curvature along a plurality of contact points with at least one of the rolling elements along at least a portion of the corresponding path.

(21) Embodiments include a mechanism wherein the raceways comprise a first plurality of guide structures and the first rolling element comprise a second plurality of guide structures, the first plurality of guide structures being positioned to interface with the second plurality of guide structures as each of the first rolling element rolls through the path.

(22) Embodiments include a mechanism that has a first rolling element operable to roll on a corresponding path between a first pair of raceways, a first rolling element operable to roll on a corresponding path between a first pair of raceways, wherein at least one of the two pairs of raceways has a substantially variable curvature along a plurality of contact points with at least one of the rolling elements along at least a portion of the corresponding path.

(23) Embodiments include a mechanism wherein one of the first pair of races is coupled to one of the second pair of races so that they move in concert.

(24) Embodiments include a mechanism wherein the first rolling element operable to roll between a first rotor and a first stator and the second rolling element operable to roll between a second rotor and a second stator, the first rotor being coupled to the second rotor.

(25) Embodiments include a program product wherein a designer specifies design parameters that are stored in a computer-aided-design (CAD) system. The design process determines physical parameters of a mechanism **100** consistent with the design parameters. These design parameters may be determined based on an overall machine level design process. The overall machine level design process employs well-known techniques to consider the goals and constraints of the application for the mechanism.

(26) Reference in this specification to “one embodiment,” “an embodiment,” and “embodiments” means that a feature, structure, characteristic, advantage or benefit described in connection with the embodiment or embodiments are included in at least one embodiment of the disclosure, but may not be exhibited by other embodiments. The appearances of the phrase “in one embodiment” or the like in various places in the specification are not necessarily all referring to the same embodiment or embodiments, nor are separate or alternative embodiments mutually exclusive of other embodiments. Similarly, various requirements are described which may be requirements for some embodiments but not for other embodiments. The specification and drawings are to be regarded in an illustrative sense rather than a restrictive sense. Various modifications may be made thereto without departing from the spirit and scope as set forth in the claims.

Description

DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 illustrates one embodiment of a mechanism including rolling bearings between a pair of races.

(2) FIG. 2 illustrates an embodiment of guide structures on a segment of a raceway.

(3) FIG. 3 illustrates a second embodiment of guide structures on a segment of a raceway.

(4) FIG. 4 illustrates a third embodiment of guide structures on a segment of a raceway.

(5) FIG. 5 illustrates an embodiment of a rolling bearing between two linear races.

(6) FIG. 6 illustrates an embodiment of two interlocking gears.

(7) FIG. 7 illustrates a close-up view of the mechanism of FIG. 1.

(8) FIG. 8 illustrates a first embodiment of a split pin.

(9) FIG. 9 illustrates a second embodiment of a split pin.

- (10) FIG. **10** illustrates a top view of one embodiment of a split pin.
- (11) FIG. **11** illustrates one embodiment of an error calculation for a test point for co-opposing shape profiles for a split pin.
- (12) FIG. **12** illustrates a close-up view of the error diagram of FIG. **11**.
- (13) FIG. **13** is a top view of one embodiment of a mechanism prior to optimization.
- (14) FIG. **14** illustrates a mechanism prior to optimization, the rolling element at the midpoint of an interval.
- (15) FIG. **15** illustrates a close-up of the mechanism of FIG. **14**.
- (16) FIG. **16** illustrates a mechanism after optimization, the rolling element at the midpoint of an interval.
- (17) FIG. **17** illustrates a close-up of the mechanism of FIG. **16**.
- (18) FIG. **18** is a close-up view of a portion of the mechanism after optimization, the rolling element at an endpoint of an interval.
- (19) FIG. **19** is a first embodiment of a corkscrew device.
- (20) FIG. **20** is a second embodiment of a corkscrew device.
- (21) FIG. **21** is a graph of a lever height specification for a corkscrew.
- (22) FIG. **22** is a graph of a lever rotation specification for a corkscrew.
- (23) FIG. **23** is an embodiment of a corkscrew shown with the lever at a first end of the range of motion with the worm raised into the frame.
- (24) FIG. **24** is an embodiment of a corkscrew shown with the lever at a second end of the range of motion with the worm fully extended out of the frame.
- (25) FIG. **25** is a close-up view of an embodiment of a corkscrew shown with the lever at a first end of the range of motion with the worm raised into the frame.
- (26) FIG. **26** is a close-up view of an embodiment of a corkscrew shown with the lever in the middle of the range of motion with the worm partially extended out of the frame.
- (27) FIG. **27** is a close-up view of an embodiment of a corkscrew shown with the lever at a second end of the range of motion with the worm fully extended out of the frame.
- (28) FIG. **28** is a close-up view of an embodiment of corkscrew showing a portion of the bearing element between the worm drive component and the frame.
- (29) FIG. **29** is a graph of piston height as a function of shaft rotation for a 120-degree engine relative to the same for a prior art engine.
- (30) FIG. **30** is one embodiment of a 120-degree engine according to one embodiment of an optimization process.
- (31) FIG. **31** is a graph of piston height as a function of shaft rotation for a 180-degree engine relative to the same for a prior art engine.
- (32) FIG. **32** is one embodiment of a 180-degree engine according to one embodiment of an optimization process.
- (33) FIG. **33** is one embodiment of a close up view of a split pin interfacing with three raceways.
- (34) FIG. **34** is a graph of piston height as a function of shaft rotation for a crankcase for a compressor relative to the same for a prior art crankcase.
- (35) FIG. **35** is a first perspective view of one embodiment of a crankcase for a compressor according to one embodiment of an optimization process.
- (36) FIG. **36** is a second perspective view of one embodiment of a crankcase for a compressor according to one embodiment of an optimization process.
- (37) FIG. **37** is a bottom view of one embodiment of a crankcase for a compressor according to one embodiment of an optimization process.
- (38) FIG. **38** is a perspective view of one embodiment of a rotary mechanism.
- (39) FIG. **39** is a perspective view of one embodiment of a rotary mechanism.
- (40) FIG. **40** is a bottom view of one embodiment of a rotary mechanism.
- (41) FIG. **41** is a perspective view of one embodiment of a rotary mechanism of FIG. **38** at a first

position in the cycle of rotation.

(42) FIG. **42** is a perspective view of one embodiment of a rotary mechanism of FIG. **38** at a second position in the cycle of rotation.

(43) FIG. **43** is a perspective view of one embodiment of a rotary mechanism of FIG. **38** at a third position in the cycle of rotation.

(44) FIG. **44** is a perspective view of one embodiment of a rotary mechanism of FIG. **38** at a fourth position in the cycle of rotation.

(45) FIG. **45** is a perspective view of one embodiment of a rotary mechanism of FIG. **38** at a fifth position in the cycle of rotation.

(46) FIG. **46** is a perspective view of one embodiment of a rotary mechanism according to one embodiment of an optimization process at a first position in the cycle of rotation.

(47) FIG. **47** is a perspective view of one embodiment of a rotary mechanism according to one embodiment of an optimization process at a second position in the cycle of rotation.

(48) FIG. **48** is a close-up view of one embodiment of a rotary mechanism according to one embodiment of an optimization process.

(49) FIG. **49** is a perspective view of one embodiment of a linear-to-linear mechanism according to one embodiment of an optimization process at a first position in the cycle of rotation.

(50) FIG. **50** is a perspective view of one embodiment of a linear-to-linear mechanism according to one embodiment of an optimization process at a second position in the cycle of rotation.

(51) FIG. **51** is a perspective view of one embodiment of a linear-to-linear mechanism according to one embodiment of an optimization process at a third position in the cycle of rotation.

(52) FIG. **52** illustrates one embodiment of the first step of a method for inserting a two-piece rolling element between two raceways.

(53) FIG. **53** illustrates one embodiment of the second step of a method for inserting a two-piece rolling element between two raceways.

(54) FIG. **54** illustrates one embodiment of the third step of a method for inserting a two-piece rolling element between two raceways.

(55) FIG. **55** illustrates a top perspective view of one embodiment of a speed reducer.

(56) FIG. **56** illustrates an close-up view of the speed reducer of FIG. **55**.

(57) FIG. **57** illustrates a bottom perspective view of the speed reducer of FIG. **55**.

(58) FIG. **58** illustrates a exploded view of the speed reducer of FIG. **55**.

(59) FIG. **59** illustrates a top perspective view of the speed reducer of FIG. **59**.

(60) FIG. **60** illustrates a top perspective view of the bottom mechanism of the speed reducer of FIG. **59**.

(61) FIG. **61** is a diagrammatic representation of an embodiment of a machine **950**

DETAILED DESCRIPTION

(62) FIG. **1** illustrates one embodiment of a mechanism **100** including a pair of races **104**. The races **104** have raceways **101** that make contact with twelve rolling elements **102** as they roll through a range of motion. Most of the embodiments are described with reference to rolling elements **102**, also referred to as pins. In other embodiments, the rolling elements **102** are ball bearings. In other embodiments, the rolling elements **102** may be tapered roller elements, spherical roller elements, or needle roller elements, for example.

(63) In the illustrated embodiment, the raceways **101** form concentric circles each having a constant curvature. For perfectly circular raceways, the curvature is constant at the reciprocal of the radius of the respective implied circles. Substantially circular raceways may have some variations in the constant curvature. Such variations would have a magnitude associated with imperfections attributable to manufacturing tolerances and ordinary wear and tear, for example.

(64) In preferred embodiments, one or both raceways **101** have substantially variable curvature over at least a portion of the path of one or more rolling elements **102**. In a preferred embodiment, each raceway **101** makes contact with each rolling element **102** so that the raceways **101** on either

side of a rolling element **102** substantially oppose each other at the corresponding contact points on either side of the rolling element **102** as the rolling element **102** rolls through each position around the closed loop.

(65) The raceways **101** substantially oppose each other when the normal vectors at a corresponding pair of contact points are aligned to directly oppose each other within an accepted level of tolerance throughout the range of motion. The substantial opposition of the raceways **101** at the corresponding pair of contact points with each rolling element as it rolls through the range of motion tends to keep that rolling element **102** stable between the raceways **101**.

(66) In some embodiments, the raceways **101** have repeating guide structures **103b** on the surface positioned to interface with a guide structure **103a** on each rolling element **102** as it rolls throughout its range of motion. The guide structures **103a** and the guide structures **103b** interface with each other to maintain the rolling element **102** even when exposed to disturbances such as vibrations, debris, warping, and thermal strains, for example. The guide structures **103a** and the guide structures **103b** are structured so that they constrain the motion of each rolling element **102** to keep it on the path along the raceways **101**. In some embodiments, the guide structures **103a** and the guide structures **103b** do not transmit torque between each raceway **101** and each rolling element **102**.

(67) The guide structures **103a** on the rolling elements **102** interface with a corresponding repeating pattern of the guide structures **103b** on the raceways **101** as the rolling elements **102** roll through the range of motion. The guide structures **103a** on the rolling elements **102** may be protrusions positioned to be received by corresponding guide structures **103b** that are formed as receptacles on the raceways **101**.

(68) In a preferred embodiment, the protrusions of the guide structures on one surface are fully received by the receptacles of the guide structures on the other surface throughout the range of motion of each of the rolling elements **102**. The surface of each rolling element **102** adjacent to the guide structures makes contact with a portion of the surface of each raceway **101** adjacent to the guide structures throughout the range of motion of each of the rolling elements **102**. Thus, in a preferred embodiment, at least some portion of the surfaces of each rolling element **102** makes contact with both raceways **101** continuously throughout the range of motion.

(69) In some embodiments, some or all of the guide structures **103a** on the rolling elements **102** may be protrusions positioned to be received by corresponding receptacles of the guide structures **103b** on the raceways **101**. In some embodiments, some or all of the guide structures **103a** on the rolling elements **102** may be receptacles positioned to receive corresponding protrusions of the guide structures **103b** on the raceways **101**.

(70) In preferred embodiments, the pattern of the guide structures **103a** on the rolling elements **102** are repeated an integer number of times as the guide structures **103** on the raceways **101** so that the rolling elements **102** can roll through multiple cycles around the closed loop without a discontinuity in the pattern on the raceways **101**. The pattern will repeat more times on the outer raceway **101** than the inner raceway **101** because the outer raceway **101** has a longer path length along the surface in contact with the rolling elements **102** through each rolling elements **102** range of motion—in this case a cycle of the closed loop.

(71) FIGS. 2, 3 and 4 illustrate exemplary guide structures **103b** on a portion of a raceway **101**.

(72) In some embodiments, the guide structures **103a** on the rolling element **102** fit into a tongue and groove arrangement with the guide structures **103b** on the raceway **101**. This tends to keep the rolling element **102** from sliding along the axis of the rolling direction of the rolling element **102** and it tends to keep the rolling element **102** from sliding laterally with respect to the rolling direction.

(73) FIG. 2 shows one embodiment of guide structures **103b** along a portion of a raceway **101**. Each instance of this pattern shown is known as a chevron. The chevrons are spaced so that there is no portion of the rotation of a rolling element **102** on that raceway **101** that does not have at least a

portion of the guide structures **103b** interfacing with at least a portion of the guide structures **103a** on the rolling element **102** as it rolls throughout its range of motion.

(74) FIG. **3** shows another embodiment guide structures **103b** along a segment of a raceway **101**. This pattern repeats more frequently than the fully formed chevron of FIG. **1**. No portion of the rotation does not have at least a portion of the guide structures **103b**. In this way, the guide structures **103b** are constantly engaged with the guide structures **103a** of the rolling element **102** so that the rolling element **102** is constrained from sliding at each point in the rotation of the rolling element **102** on the raceway **101**.

(75) The guide structures **103b** in FIG. **4** have two types of repeating patterns. The guide structures **103b** include two linear tracks along the rolling direction of the rolling element **102**. The guide structures **103b** also includes short linear segments on lateral sides of the raceway **101** oriented perpendicular to the rolling direction.

(76) These guide structures tend to keep the rolling elements **102** from sliding backward or forward along rolling direction and it tends to keep the rolling element from sliding laterally with respect the rolling direction.

(77) FIG. **5** includes a double headed arrow to show the direction of the forces on substantially co-opposing raceways **101** on a rolling element **102** at one position along the range of motion. In the illustrated embodiment, the raceways **101** are linear.

(78) FIG. **6** includes a double headed arrow to show the primary direction of the forces on two interlocking gears **110**. The gear teeth transmit torque between the gears.

(79) FIG. **7** shows a close-up view of a portion of the mechanism **100** of FIG. **1**.

(80) The races **104** have raceways **101** on either side of the rolling elements **102**.

(81) The guide structures **103a** are protrusions on the rolling elements **102** and the guide structures **103b** are receptacles on the raceways **101** configured to receive the protrusions.

(82) The raceways **101** shown in FIGS. **1** and **7** are circular. The curvature at a particular contact point on each raceway **101** may be numerically represented as the reciprocal of the implied radius of a circle having that curvature. The inner raceway **101** has a higher curvature than the outer raceway **101**.

(83) For perfectly circular raceways, the curvature would be constant at the reciprocal of the radius of the implied circle. Substantially circular raceways may have some variations in the constant curvature. Such variations would typically have a magnitude associated with imperfections attributable to manufacturing tolerances and ordinary wear and tear, for example.

(84) A mechanism has two or more components coupled to the races **104** at least two of which are designed to move with respect to each other, and one or more rolling elements each comprising at least two raceways and at least one rolling element **102**, that form an interface between components.

(85) Embodiments include a mechanism that has at least one rolling element operable to roll on a corresponding path between the pair of raceways, wherein at least one of the pair of raceways has a substantially variable curvature along a plurality of contact points with at least one of the rolling elements along at least a portion of the corresponding path.

(86) Embodiments include raceways that form closed loops which allow the rolling elements to have a range of motion around the closed loop. In other embodiments, these raceways form open segments to allow for a back and forth range of motion.

(87) Mechanisms as used herein is meant to include basic bearings including those claimed herein to complex machines including numerous bearing elements working in conjunction with gears, cams, and multi-bar linkages, for example.

(88) The shape of the raceways are determined by a process described herein whereby a designer or someone skilled in the art, for example, can specify the desired motion of the components according to the application of the mechanism. In a preferred embodiment, the process determines the raceway **101** shapes based at least in part on the specified motion of the races **104** with

constraints such as that the pin-raceway contact points substantially oppose each other throughout the range of motion of the rolling elements **102**.

(89) For perfectly straight raceways **101**, the curvature is zero. Substantially straight raceways **101** may have some variations from perfectly straight. Such variations would result in a curvature with a magnitude associated with imperfections attributed to manufacturing tolerances and ordinary wear and tear, for example.

(90) In preferred embodiments, the mechanism includes raceways **101** with substantially variable curvature along at least a portion of the path of one or more rolling elements **102** rolling along the raceways **101**. A substantially variable curvature varies by design, to a greater degree than that due to manufacturing imperfections or ordinary wear and tear, from that of a nominally zero curvature (straight) or that of a nominally constant curvature (circular). In some embodiments, portions of the raceways **101** have a substantially variable curvature along at least a portion of the path of one or more rolling elements **102**, as well as a nominally zero or constant curvature along at least a portion of the path of the rolling elements **102**.

(91) In the embodiment shown in FIGS. **1** and **7**, the raceways **101** are closed loops. A closed loop has no end point so that the rolling elements **102** can roll in one direction or the other through multiple passes around the closed-loop raceways **101**.

(92) In some embodiments, the raceways **101** are one or more open loops. An open loop has endpoints on either side of the raceway along the path of one or more rolling elements **102** so that each rolling element **102** can roll back and forth between the endpoints.

(93) In some embodiments, the mechanism **100** includes raceways **101** with periodic pattern of variable curvature along at least a portion of the path of the rolling elements **102**. For example, the pattern may include regularly-spaced lobes such as shown with respect to the forward and backward rotary mechanism described below. In some embodiments, the mechanism **100** includes raceways **101** with periodic pattern of substantially variable curvature along at least a portion of the path of the rolling elements **102**.

(94) In some embodiments, the mechanism **100** includes raceways **101** with an irregular shape having substantially variable curvature along at least a portion of the path of the rolling elements **102**. An irregular shape is one that is not even or balanced.

(95) In a preferred embodiment, the substantially variable curvature of the raceways **101** are designed to accommodate the motion of the components as specified by a designer, while minimizing sliding of the rolling elements **102** as they move along the raceways **101** and maintain opposing contact points at the raceways **101** on either side of the rolling elements **102** throughout the range of motion.

(96) The direct opposition of the raceways **101** at the contact points with each rolling element **102** tends to keep that rolling element **102** stable between the raceways. A raceway **101** on one side of a rolling element **102** is positioned to substantially oppose a raceway **101** on the other side of the rolling element **102** when the raceways are aligned to directly oppose each other throughout the range of motion within an accepted level of error tolerance.

(97) In some embodiments, the rolling elements **102** are cylindrical. A cylindrical rolling element has a diameter and length.

(98) In other embodiments, the rolling elements **102** are split pins. In a preferred embodiment, split pins **102** have multiple segments defined by slices perpendicular to the axis of rotation. Each slice has a shape profile defined by the shape of the cross section of the segment. The different shape profiles can provide more flexibility to facilitate finding a solution or finding a better solution in the design process described herein.

(99) FIG. **8** illustrates one embodiment of a split pin.

(100) The first split pin **105** has a first segment **111**, a second segment **112**, and a third segment **113**. The first segment **111** has a first shape profile. The second segment **112** and the third segment **113** have a second shape profile. The first and second shapes are cylindrical so that the shape

profiles—a cross section of each segment perpendicular to the axis of rotation **117**—are circular. The first shape profile is a circle having a larger diameter than the circle of the second shape profile.

(101) The first segment **111** is configured to interface with a first raceway, the second segment **112** is configured to interface with a second raceway and the third segment **113** is configured to interface with a third raceway. In a preferred embodiment, the first and third raceways are shaped identically. In the illustrated embodiment, the guide structures **103b** are identical for each segment. In other embodiments, the patterns of the guide structures **103b** may differ for each segment. The raceways are not shown.

(102) FIG. **9** illustrates another embodiment of a split pin.

(103) The second split pin **106** has a first segment **114**, a second segment **115**, and a third segment **116**. The first segment **114** has a first shape profile. The second segment **115** and the third segment **116** has a second shape profile. The first and second shapes are cylindrical so that the shape profiles are circular. The first shape profile is a circle having a smaller diameter than the circle of the second shape profile.

(104) The first segment **114** is configured to interface with a first raceway, the second segment **112** is configured to interface with a second raceway and the third segment **113** is configured to interface with a third raceway. The first and third raceways are shaped identically. The raceways are not shown.

(105) FIG. **10** illustrates a top view of one embodiment of a split pin **130** having first shape profile and a second shape profile. In the illustrated embodiment, the first shape profile is elongated in a first direction and the second shape profile is elongated in a second direction that is at a right angle to the first direction.

(106) A first segment **131** has a first shape profile that is at the middle of a split pin **130**. A second segment **132** has a second shape profile that is at the top of the split pin **130** as shown. A third segment is not shown but is at the bottom of the split pin **130** directly beneath the first segment **131** with the same shape profile as the second segment **132**. The first shape profile interfaces with a first raceway (not shown) and each of the two second shape profiles interface with a corresponding one of a second raceway (not shown) and a third raceway (not shown).

(107) In the illustrated embodiment, the first shape profile and the second shape profile are co-opposing in that the first raceway can be positioned to substantially oppose the second and third raceways at contact points with each co-opposing shape profile as the co-opposing split pin rolls throughout the range of motion. The direct opposition of the raceways at the contact points with each split pin **130** tends to keep that split **130** stable between the raceways.

(108) The co-opposing nature of the first and second shape profiles is illustrated using the dotted lines. Each dotted line runs from the perimeter of the first segment **131**, perpendicular to the edge of the first segment **131** at that point, to the perimeter of the second segment **132**, perpendicular to the edge of the second segment **132** at that point.

(109) A first raceway (not shown) contacts a point **134** and a point **137**, for example, as the segment **131** of the split pin **130** rolls through the range of motion. A second raceway (not shown) contacts a point **133** and a point **136**, for example, as the segment **132** of the split pin **130** rolls through the range of motion.

(110) The endpoints of each dotted line are exemplary points where the raceways can simultaneously make contact to substantially oppose each other as the split pin **130** rolls through its range of motion. When the points are co-opposing, the normal vector extending from the contact point at one endpoint of the dotted line is parallel to the normal vector extending from the contact point at the other endpoint of the dotted line. When the shapes are substantially co-opposing, the normal vector extending from one endpoint is parallel to the normal vector extending from the other endpoint within an accepted tolerance for error, for all points throughout the range of motion.

(111) The dotted line between point **136** and point **137** is a normal to the surface at point **136** and

normal to the surface at point **137**. The dotted line between point **133** and point **134** is a normal to the surface at point **133** and normal to the surface at point **134**. Each dotted line represents the relationship between co-opposing points on the split pin as the rolling elements rotates along the raceways (not shown) through its range of motion.

(112) In some embodiments, both the first and second shapes are cylindrical and the first and second shape profiles are circular but have different diameters. Examples of cylindrical segments are shown in the split pins of FIGS. **8** and **9**. In other embodiments, the shapes are elongated as shown in FIGS. **10** and **11**. Alternatively, shapes can be more generally described with a set of frequencies each with associated constants:

$$(113) \text{ShapeX}(\theta) = \sum_{n=1}^{NX} (a_n \cos(n\theta)) \quad \text{ShapeY}(\theta) = \sum_{n=1}^{NY} (b_n \sin(n\theta))$$

$\text{ShapeA}(\theta) = (\text{ShapeX}(\theta), \text{ShapeY}(\theta))$ for $\vec{a}$ and $\vec{b}$ specific to ShapeA

$\text{ShapeB}(\theta) = (\text{ShapeX}(\theta), \text{ShapeY}(\theta))$ for $\vec{a}$ and $\vec{b}$ specific to ShapeB where θ is the parametric edge value that varies from 0 to 2π . NX is the number of frequencies in the X direction and NY is the number of frequencies in the Y direction, and a_n and $b_{\text{sub}.n}$ are constants for the specific shape. $\vec{a} = a_{\text{sub}.0} \dots a_{\text{sub}.n}$ are constants. $\vec{b} = b_{\text{sub}.0} \dots b_{\text{sub}.n}$ are constants.

(114) In a preferred embodiment, the co-opposing shapes are determined by specifying one of the shapes and running an optimization process to find the other. Not all shapes have a co-opposing pair. In a preferred embodiment, the shapes are smooth and regular.

(115) The initial condition for the constants are set as a 1 followed by all zeroes:

$$a_{\text{sub}.0} \dots a_{\text{sub}.n} = 1, 0 \dots 0$$

$$b_{\text{sub}.0} \dots b_{\text{sub}.n} = 1, 0 \dots 0$$

(116) An error function is evaluated using a number of test points dispersed around the edge of the shapes. An array of error values for each test point can be collected to form an error vector for an optimization algorithm. The number of test points is generally at least as many as the number of constants in $\vec{a}$ and $\vec{b}$. Given ShapeA , the optimization algorithm adjusts $\vec{a}$ and $\vec{b}$ of ShapeB so as to minimize the error vector.

(117) FIG. **11** illustrates a diagram showing the basis for one embodiment of an error calculation for a test point in an iteration of an optimization process for co-opposing shape profiles for a split pin **130**. FIG. **12** shows a close-up view of the region where the exemplary error measurements are made to show the relationship between the points in that region.

(118) The first segment **131** has a first shape profile. The second segment **132** has a second shape profile. The first shape profile is referred to as ShapeA and the second shape profile is referred to as ShapeB in formulas described herein.

(119) A normal vector **139** extends out from a tangent **143** at a test point **143** on the second segment **132**. The normal vector **147** crosses the surface of the first segment **131** at a point **146**.

(120) A tangent **148** at a tangent point **144** on the first segment **131** is a tangent line that is parallel to the tangent **147** and closest to the point **146**. In a preferred embodiment, the point **144** is found using a search algorithm.

(121) A point **145** is where the normal vector **147** intersects with the tangent **148**.

(122) In a preferred embodiment, the error distance is the distance from the tangent point **144** and the point **145**. The sign of the error distance is different depending on which side of the tangent point **148** that the point **145** is located. The error distance is zero when the point **145** and the tangent point **144** are at the same location. When the error distance is zero, the point **146** is also at the tangent point **144**.

(123) In a preferred embodiment, the error function returns a zero when the surfaces are co-opposing at the test point **146**, is positive when the error distance is on one side of the tangent point

144 and is negative when the error distance is on the other side of the tangent point **144**.

(124) As the optimization algorithm iterates, the shape is adjusted to converge on a solution. In a preferred embodiment, the solution determined by the optimization process has an error vector containing all zeros, but results having non-zero errors is contemplated. Substantially co-opposing shapes includes co-opposing shapes with some errors within an accepted level of tolerance at various points through the range of motion. Some shapes do not have co-opposing shapes. When those shapes are encountered, they must be flagged for review by the overall design process.

(125) Mechanism Design

(126) In some embodiments, a designer specifies design parameters that are stored in a computer-aided-design (CAD) system. The design process determines physical parameters of a mechanism **100** consistent with the design parameters. These design parameters may be determined based on an overall machine level design process. The overall machine level design process employs well-known techniques to consider the goals and constraints of the application for the mechanism.

(127) Some of the components in the mechanism may be prior art mechanisms such as gears, cams, and multi-bar linkages. In some embodiments, the prior art mechanisms are optimized together with the raceway-based components as part of an overall machine level design. In other embodiments, the design parameters for the raceway-based components are determined at least in part by the prior art mechanisms.

(128) One typical goal of a design is to maintain forces and stresses within accepted tolerance levels and ensure that the components do not interfere with each other. In some embodiments, this may require trial and error, changing input and output motions and rolling element start positions if the previously identified solution does not meet these or other requirements.

(129) In some embodiments the physical parameters are stored in a standard CAD design format that specifies the physical design of a mechanism so that it can be used directly or indirectly by manufacturing systems and devices to manufacture the mechanism.

(130) In a preferred embodiment, a designer specifies the motion of two or more components of a mechanism. In some embodiments, one component is configured to receive an external force that is an input to the mechanism and another component is configured to drive an output motion. In some embodiments, multiple components can receive input motions and multiple components can drive output motions. In some embodiments, one or more components can either accept an input motion or drive an output motion depending on how the mechanism is used. In some embodiments, the mechanism includes one or more ground components that do not move relative to the reference coordinate system, but which interact with the moving components. Such components are typically referred to as a “ground”, “chassis” or “frame”.

(131) At least two of the components have at least one raceway. The raceway comprises just one edge of the component. The rest of the component is specified by the designer to meet other requirements for the application of the device.

(132) The motion of each component is specified in terms of x-position, y-position, and rotation angle, for a range of motion having a specified number of intervals (n points). The position information for the components are stored as floating-point numbers in X, Y, and rotation arrays each having n points where the ith element of the array represents the position of the component at the with interval. The number of intervals is selected to sufficiently represent features of the specified movement. In a preferred embodiment, the movement is sufficiently represented when the movement is smooth.

(133) The initial rolling element path includes the starting position of the rolling element and the second and subsequent positions of the rolling element throughout the range of motion. The initial rolling element path and the direction of rotation, clockwise or counterclockwise, must be specified. The rotations of the rolling element are computed.

(134) If the motion of the components are reciprocating or back-and-forth motion, only the forward motion may be optimized in some embodiments under the assumption that the optimization in the

reverse direction is redundant.

(135) Given the design parameters such as the input motion of a first component, the output motion of a second component, the initial paths for the pins, and the direction of rotation of the pins, a search algorithm may be used to find an optimal or satisfactory solution. In a preferred embodiment, the goal of the search algorithm is to find second and subsequent positions of the rolling element path which minimizes the rolling element sliding on the raceway and maintains substantially opposing pin-raceways contact points throughout the range of motion.

(136) FIG. **13** depicts a flow chart for one embodiment of a search algorithm for each bearing element. The bearing elements comprise a pair of raceways on either side of one or more rolling elements. Each bearing element forms an interface between two components of a mechanism. Multiple bearing elements may define multiple interfaces between the same pair of components. Multiple bearing elements may each define interfaces between different pairs of components.

(137) An input motion store **601**, an output motion store **602**, a pin-rotation-direction store **603** and initial rolling element path store **604** are computer-readable medium that stores respective data structures for each design parameter.

(138) In a preferred embodiment, the path of the rolling element is iteratively determined, along with the shape of the raceways, to converge on a solution using a multivariable search algorithm (MVSA). Alternatively, other optimization or solution search algorithms may be used to find a satisfactory solution. The process may use alternative directed algorithms designed to efficiently search for a solution.

(139) The process may be an algorithm that evaluates randomly selected scenarios, tests each against the best-known solution, and updates the best-known solution if the currently evaluated scenario is better.

(140) In other embodiments, the scenarios are determined based upon results from prior scenarios. An example of such search is described below.

(141) In some embodiments, the process is directed at finding the best solution according to evaluation criteria. In other embodiments, the process is directed at finding a satisfactory solution according to evaluation criteria.

(142) In step **610**, the initial rolling element path store **604** is accessed from a computer readable medium to retrieve the initial rolling element path for the rolling element **102** and store the rolling element path in a trial rolling element path store **605**. The initial rolling element path **610** may be specified by the designer or determined based on an automated initial rolling element path estimator algorithm, or from an overall machine level design, for example.

(143) The trial rolling element path store **605** stores the rolling element paths representing the scenario currently being evaluated by the search algorithm. The first trial rolling element path is the initial rolling element path from the initial rolling element path store **604**.

(144) In a preferred embodiment, the MVSA process will iteratively generate candidate scenarios having various parameters including shapes of the two raceway surfaces separated by the rolling elements. The combination of the design parameters controlled and modified during the MVSA, as well as other relevant characteristics of the design, is referred to as a candidate scenario or candidate solution. In some embodiments, the candidate scenarios include rolling element configuration(s), including whether each rolling element is a split pin or a single-shape pin, the initial rolling element position(s) and the shape(s) of the pin(s), including the diameter of the rolling elements **102**.

(145) The MVSA process is constrained based on requirements that a solution must satisfy. The specified motion of the components, such as the input motion and the output motion, are constraints on the MVSA process.

(146) For a closed-loop raceway, another constraint on the MVSA process is the requirement that the shape of the raceway surfaces results in a closed loop.

(147) In a preferred embodiment, the shape of the closed-loop raceways are continuous and smooth

over the whole loop. At the point where the ends of the raceways are joined, the ends are aligned and the slope is continuous. In some embodiments, a spline function is used to smooth the motion of the components and to insure a continuous and smooth motions across the beginning and the end.

(148) Another constraint on the MVSA process is that the guide structure pattern defined by the pattern of one rotation of the guide rolling element is repeated an integer number of times on the surface of each closed loop raceway so that the rolling element can rotate through multiple loops of the closed loop raceway without a discontinuity in the rolling-element/raceway interface. In some embodiments, the use of split pins may be required to satisfy these constraints, or to achieve a better solution according to evaluation criteria.

(149) In a preferred embodiment, the candidate solution is evaluated based on a predetermined evaluation criterion sometimes referred to as an objective function. The objective function may be a sum of various characteristics of a candidate design that are calculated or estimated based on the candidate scenario.

(150) In step **620**, a virtual make and measure process is performed. Since the mechanism **100** is virtually made based on a computer-based model rather than physically manufactured, it is referred to as a virtual make and measure process. Generally, this process includes three steps. First, find the raceways edges using a 2D sweep surface algorithm. Each sweep will generate two surfaces for each component, one on either side of the pin. One corresponds to a clockwise rolling element rotation and the other a counterclockwise rolling element rotation. The specification from the designer determines the surface to use. The next step is to measure the opposition of the pin-raceway contact positions. Third, the rotation of the rolling element against each raceway is calculated and the rotation difference at any interval is the sliding of the pin.

(151) In a preferred embodiment, a particular shape for each of the raceway surfaces is determined based on the candidate scenario. After the key physical characteristics such as raceway surfaces are determined for the candidate design, various characteristics of the candidate design are computed or estimated for evaluation of that candidate design. The path and rotation of the rolling element between the raceway surfaces can be calculated at multiple test points through a plurality of intervals within the range of motion.

(152) The amount of sliding during any interval can be calculated by first calculating the rotation of the rolling element against each candidate raceway. The difference in rotation along any interval is the degree of sliding. Sliding is undesirable and used a part of the error vector for the search algorithm. The sliding tends to increase friction and energy loss during operation of the mechanism **100**.

(153) The sliding error is the sum of the absolute value of difference in rolling element rotation computed for each raceway, for each point on the rolling element path.

(154) When the sliding error for a rolling element is zero, sliding is avoided for that pin. When the sliding error is non-zero, the rolling element slides to some extent, but the rolling element is substantially rolling if the rotation error is within a predetermined tolerance level.

(155) A contact normal vector can be determined for each contact point between the rolling element and the raceway surfaces at each interval. An opposing-angles error measures the cross product of the contact normal vectors at the contact points between the raceways coupled to the pin. When the cross product is zero the contact normal vectors directly oppose each other. When the dot product is non-zero, the contact normal vectors are not perfectly aligned. The contact points are substantially opposing if the cross product of the normal vectors are within an predetermined tolerance level.

(156) The sliding error is the sum of the absolute value of difference in rolling element rotation computed between each raceway, for each interval, summed across all intervals. The opposing angle error is the absolute value of each opposing angle summed across all points of the rolling element path.

(157) When the opposing-angles error for a rolling element is zero, the raceways directly oppose

each other over all intervals throughout the range of motion. When the opposing-angles error is non-zero, the raceways do not perfectly oppose each other at the respective contact points for at least some intervals, but the raceways are substantially opposing if the opposing-angles error is within a predetermined tolerance level.

(158) Mechanical stress can also be determined for each contact point between the rolling element and the raceway surfaces at each interval, according to various methods including finite element analysis.

(159) In a preferred embodiment, the goal of the MVSA is to find a candidate scenario that minimizes sliding error and contact normal alignment error. When specifying an objective function for the MVSA algorithm, the sliding error and contact normal alignment error may be weighted to compensate for the different numerical scales and the relative importance of the errors in evaluating a candidate scenario.

(160) Once the error vectors are defined, different scenarios can be objectively compared to determine which scenario is better according to the error vector. A solution is found when the error vector is minimized or determined to be satisfactory (within a specified tolerance level).

(161) In some embodiments, the diameter of the rolling elements are evaluated and modified during the MVSA process.

(162) In some embodiments, split pins are used, and the shape of the co-opposing split pins are evaluated and modified during the MVSA process. In such cases, the co-opposing angle error may be incorporated into the objective function for evaluation of the candidate scenarios. In some embodiments where a closed-loop solution is desired, the difference in the first and last rolling element path X values and Y values are included in the error vector. To enable the closure of the path, the two radiuses of the split pin are included in the candidate scenario. To get the loop to close with an integer number of guides, a target guide number is set for either the input or output raceways. The target guide error is the difference between the target guide number and the perimeter of the raceway divided by the perimeter between two guides on the corresponding pin. To enable the process to reduce target guide error, the radial distance of the rolling element start position is added to the candidate scenario.

(163) In step **625**, it is determined whether the candidate scenario stored in the trial candidate store **606** is better than that stored in the best candidate store **607**. In some embodiments, this determination is made by comparing the error vector for the candidate scenario and the best candidate scenario.

(164) Various objective functions can be used to compare scenarios. In some embodiments, the better error vector is one that has a lower maximum of the absolute value of the errors in the error vector. In other embodiments, the better error vector is one that has a lower sum of the absolute values of the errors in the error vector. Other methods of comparing error vectors may be used.

(165) For the initial rolling element path, the best candidate store **607** is initialized to the first candidate scenario for comparison with future candidate scenarios.

(166) If the candidate scenario is not better than the best scenario in the best candidate store **607** as determined by comparing the error vectors, step **630** is executed to vary the rolling element path and other variables included in the optimization. Otherwise the trial scenario is copied to the best scenario in step **640**.

(167) If the candidate scenario is better than the best scenario in the best candidate store **607** according to the objective function, step **640** is performed to copy the information for the candidate scenario into the best candidate store **607**. In some embodiments, the information includes the raceway shapes, the rolling element path, the error vectors for the objective function and the value of the objective function.

(168) In step **645**, it is determined whether the candidate scenario is good enough. In some embodiments, the candidate scenario may be good enough if the associated objective function is maximized or minimized. In some embodiments, the candidate scenario may be good enough if the

associated objective function is zero (e.g., no rolling element sliding, no opposing-angles error or other error characteristics) or within a predetermined error tolerance from the optimal objective function. In other embodiments, the best candidate scenario found at some point might be considered good enough after a predetermined number of scenarios have been evaluated in the optimization process.

(169) If the candidate scenario is not good enough according to the objective function, step **630** is executed to vary the rolling element path according to the MVSA and copy the new rolling element path into the trial rolling element path store **605**. Step **620** is then performed to make and measure as described herein according to the new trial rolling element path.

(170) When the candidate scenario is good enough, a solution is determined.

(171) In step **650**, the raceway edges are exported. The pair of two-dimensional (2D) lines (representing the edges of a raceway) are extruded to a 3D surface to represent the raceway for each raceway in the solution. The patterns associated with guides are then imposed onto the three-dimensional (3D) surface.

(172) In a preferred embodiment, the result of the design process is saved in a computer aided design (CAD) file according to any number of standard formats. The CAD file can be converted to a format accepted by a Computer Numeric Control (CNC) machine, 3D printer, or other manufacturing device or system to generate physical embodiments of the mechanism. The CAD format can also be used to generate a mold for the component, whereby the component can be made of plastic. The mechanism may be made in various materials such as steel, alloys, and plastics. Alloys with various proportions of molybdenum, tungsten, chromium, vanadium, aluminum, and silicon are often used for bearing elements to maintain hardness at high temperatures.

(173) In step **660**, the mechanism **100** is manufactured directly or indirectly from the CAD file.

(174) FIGS. **14** and **15** illustrate one embodiment of the optimization process applied to a mechanism **150**. It includes a shaft **151** on a circular mechanism **152** coupled to a rotor **153**. The preferred embodiment, the motion of the rotor **153** is part of the input specification to the optimization process.

(175) In some embodiments the number of rotating elements **102** are determined by the application. For example, the number of rotating elements **102** may be dictated by design considerations for a speed reducer as explained below. In other embodiments, the number of rotating elements **102** may be suggested by physical stability considerations as the mechanism **150** moves through its range of motion.

(176) In some embodiments the number of rotating elements **102** is one of the parameters in the candidate scenarios in order to find the best solution. In some cases, there may not be a solution for a particular number of rotating elements **102**. In other cases, a particular result may be rejected for physical stability reasons.

(177) In the illustrated example, the raceway **101** for the rotor **153** has 4 repeating intervals. There are 5 rolling elements **102**. The raceway **101** on the other side of the rolling elements **102** has 6 repeating intervals. The rolling element **102** is shown in the mid-point of the interval.

(178) The overview of the mechanism **150** on FIG. **14** shows 6 discontinuities **154** in the outer raceway **101** and 4 discontinuities **155** in the inner raceway **101**. These discontinuities are a result of the intervals interface with each other. Similarly, a path **157** illustrates the path of the center of the rolling elements **102** as they roll around the mechanism **150**. The path **157** seems to move into the rotor **153** and various positions, but one must remember that the position of the rotor **153** is moving as the rotating elements **102** move. There are discontinuities in the path **157** between each of the six intervals. There is a misalignment of the guide structures **103a** with the guide structure **103b**, at point **159**, for example. In some embodiments, the misalignment of the guide structures **103a** to guide structures **103b** is a result of sliding instead of rolling of the rolling elements **102** as it rolls through the range of motion.

(179) When the optimization is completed, there should not be any discontinuity in the raceways **101**, the path **157**, or alignment of the guide structures **103a** and **103b**, as the rolling elements **102** should smoothly roll over these sections of the raceways **101**.

(180) FIG. **15** shows a close-up of one of the intervals prior to optimization. The rolling element **102** is shown in the mid-point of the interval. It shows the discontinuities **154**, discontinuities **155**, and misalignment **159**.

(181) The discontinuities occur because the path of the rolling elements do not precisely end the point needed for the repeating pattern. The raceway shapes

(182) FIG. **16** shows the mechanism **150** of FIG. **14** after the optimization is completed.

(183) The rolling element **102** is shown in the mid-point of the interval. The discontinuities **154**, discontinuities **155**, and misalignment **159** have been resolved so that the raceways **101** are continuous and smooth.

(184) FIG. **17** shows a close-up view of the mechanism **150** of FIG. **14** after the optimization is completed.

(185) The raceways **101a** is the initial raceway path and the raceway **101** is the solution to the optimization. The discontinuities **154**, discontinuities **155**, and misalignment **159** have been resolved so that the raceways **101** are continuous and smooth. The path **157** is continuous and smooth.

(186) FIG. **18** shows a close-up view of the mechanism **150** of FIG. **14** after the optimization is completed. The rolling element **102** is shown at an end of an interval rather than at the mid-point.

(187) The raceways **101a** is the initial raceway path and the raceway **101** is the solution to the optimization. The discontinuities **154**, discontinuities **155**, and misalignment **159** have been resolved so that the raceways **101** are continuous and smooth. The path **157** is continuous and smooth.

(188) FIGS. **19** and **20** shows an image of two embodiments of corkscrew devices for removing corks from a wine bottle (not shown).

(189) A corkscrew **170** has a worm **173** that is screwed into a cork, and a handle **171** for pulling the cork with the inserted worm **173** out of the wine bottle using a fulcrum **172** resting on the neck of the wine bottle. The mechanical advantage of the corkscrew is the ratio of movement of the handle **171** to the movement of the worm **173**. The mechanical advantage of the fulcrum **172** increases during the removal process. This causes two problems, first the low initial mechanical advantage makes it difficult to start removing the cork, since this is where the required force is highest. Second, the rapidly increasing mechanical advantage prevents complete removal of the cork without having to pull the cork out of the wine bottle as the last step of the process.

(190) A corkscrew **160** has a handle **161** for securing the corkscrew **160** around the neck of the wine bottle, a worm **163** that is screwed into the cork as the lever **162** is lowered and pulls the cork out as the lever **162** is raised. A worm cap **164**, upper ratchet mechanism **165** and lower ratchet mechanism **166** is positioned above the worm **163**. Control of the rotation of the worm **163** during the cork removal process is controlled by the upper ratchet mechanism **165** and the lower ratchet mechanism **166** according to well-known processes. However, the mechanical advantage of the lever **162** has a constant mechanical advantage throughout the removal process. This typically makes cork removal easier than with the corkscrew **150**. This device uses a rack-and-pinion mechanism that has significant friction and does not work well if without lubrication.

(191) FIGS. **21** and **22** shows a motion specification for a corkscrew.

(192) FIG. **21** shows the worm drive height as a function of the lever arm height. The chart showing the relationship between the lever arm height and the screw pull height. One can see the worm drive height rises at about three times as quickly at the end of the removal process than at the beginning, thus increasing the mechanical advantage at the beginning. The forces for removing the cork are highest at the beginning where there is more cork in contact with the bottle. With this device, the mechanical advantage follows the force and hence the force on the lever is more

constant.

(193) FIG. 22 shows the rotation of the lever as it relates to the lever height and worm cap height shown in FIG. 21.

(194) FIGS. 23 and 24 illustrates one embodiment of a corkscrew 200, derived from the motion specifications of FIGS. 21 and 22, at both ends of its range of motion. FIG. 23 shows the lever 202 at the top of a range of motion and FIG. 20 shows the lever 202 at the bottom of the range of motion.

(195) The corkscrew 200 includes a handle 201 coupled to a clamp 207 that is configured to receive the neck of a bottle of wine. The clamp 207 is also coupled to a frame component 210 that positions the worm drive component 209 to drive a worm cap 204 of a worm 203 into and out of the neck of the wine bottle in response to the motion of the lever 202 that drives a lever component 208. The lever component 208 includes a plate referenced in the following figures.

(196) The corkscrew includes three components that interact with each other through bearing elements each comprising a pair of raceways and a rolling element as described herein. The components include the lever component 208, the worm drive component 209 and the frame component 210.

(197) The worm cap 204 is connected to the worm 203 through an upper ratcheting mechanism 205 and a lower ratcheting mechanism 206. The details of the ratcheting mechanism are not shown. The ratcheting mechanisms controls the rotation of the worm 203 during operation of the corkscrew 200. The ratcheting mechanisms rotate the worm 203 into the cork, stop rotation of the worm while the worm is pulled up to remove the cork from the bottle and while the removed cork is brought down through the clamp 207, and rotates the worm 203 as the user holds the cork to remove the cork from the worm 203.

(198) FIGS. 25, 26 and 27 illustrate a close-up view of the lever mechanism for one embodiment of a corkscrew 200. The lever mechanism includes the lever component 208 and the attached rolling elements 211, 212, 213 (not shown), 214, 215 and 216, used to interface with the frame component 210 and the worm drive component 209. FIG. 16 shows the corkscrew 200 with the lever 202 in the top position. FIG. 17 shows the corkscrew 200 with the lever 202 in an intermediate position. FIG. 18 shows the corkscrew 200 with the lever 202 in the bottom position.

(199) FIG. 25 illustrates a perspective view of the mechanism for a corkscrew 200 where the lever 202 is at the top of the range of motion. The top plate of the lever component 208 is not shown so as to avoid obscuring the underlying portion of the lever component 208 and the attached bearing elements. The raceway 211a and the raceway 211a are coupled to edges of the top plate (not shown) of the lever component 208. The raceway 211a and the raceway 212a seem to float in the drawing without the top plate, but the top plate is not shown to illustrate how the those and other raceways interface with the rest of the mechanism as the lever 202 moves through the range of motion. The raceways 211a and 212a of the top plate are coupled together through the omitted top plate of the lever component 208.

(200) The range of motion of the lever 202 is restricted by the slot in the frame component 210. This restricted range of motion in the lever 202 is important for also limiting the range of motion of the lever component 208. The slot in the frame component 210 also restricts the lateral motion of the lever 202 to prevent the bearing element 211, bearing element 212, bearing element 213, bearing element 214, bearing element 215 and bearing element 216 from going out of alignment with the planar range of motion.

(201) The bearing element 211 includes the raceway 211a coupled to the lever component 208, the raceway 211c coupled to the frame component 210, and the rolling element 211b rolling between the raceway 211a and the raceway 211c throughout the range of motion.

(202) The bearing element 212 includes the raceway 212a coupled to the lever component 208, the raceway 212c coupled to the frame component 210, and the rolling element 212b rolling between the raceway 212a and the raceway 212c throughout the range of motion.

(203) The bearing element **213** includes the raceway **213a** coupled to the lever component **208**, the raceway **213c** coupled to the frame component **210**, and the rolling element **213b** rolling between the raceway **213a** and the raceway **213c** throughout the range of motion. Bearing element **213** is most clearly seen in FIG. **27**.

(204) The bearing element **214** includes the raceway **214a** coupled to the lever component **208**, the raceway **214c** coupled to the frame component **210**, and the rolling element **214b** rolling between the raceway **214a** and the raceway **214c** throughout the range of motion.

(205) Together, bearing elements **211**, **212**, **213** and **214**, interface between the lever component **208** and the frame component **210**.

(206) The bearing element **215** includes the raceway **215a** coupled to the lever component **208**, the raceway **215c** coupled to the worm drive component **209**, and the rolling element **215b** rolling between the raceway **215a** and the raceway **215c** throughout the range of motion.

(207) The bearing element **216** includes the raceway **216a** coupled to the lever component **208**, the raceway **216c** coupled to the worm drive component **209**, and the rolling element **216b** rolling between the raceway **216a** and the raceway **216c** throughout the range of motion.

(208) Together, bearing elements **215** and **216**, interface between the lever component **208** and the worm drive component **209**.

(209) The rolling element paths and the shapes of the raceways for each bearing element are determined according to an optimization process described herein based on specified design parameters such as the motion of the lever component and the worm drive component relative to the frame component. In a preferred embodiment, the optimization results in bearing elements with substantially rolling rolling elements and raceways with substantially opposing contact points on the rolling rolling elements throughout the range of motion.

(210) The bearing element **217** in the foreground is shown in more detail in a subsequent figure. However, one can see that in when the lever **202** is in the top position, the rolling elements **217b** are at an end of their range of motion.

(211) FIG. **26** illustrates a perspective view of the mechanism for a corkscrew **200** where the lever **202** is in the middle of the range of motion.

(212) The rolling elements are positioned along the raceways at an intermediate position within their range of motion. The worm cap **204** is at an intermediate position within the range of motion.

(213) When the lever **202** is in this intermediate position, the rolling elements **217b** are at an intermediate position in their range of motion.

(214) FIG. **27** illustrates a perspective view of the mechanism for a corkscrew **200** where the lever **202** is at the bottom of the range of motion.

(215) The rolling elements are positioned along the raceways at an endpoint of the range of motion. The worm cap **204** is lowered to the lowest position within the range of motion.

(216) When the lever **202** is in the bottom position, the rolling elements **217b** are at an end of their range of motion. One can see the movement of the rolling elements **217b** from their location in FIG. **25** to their location in FIG. **26**, is greater than the movement of the rolling elements **217b** from their location in FIG. **26** to their location in FIG. **27**. This is one of the manifestations of the changing mechanical advantage throughout the range of motion.

(217) FIG. **28** is a close-up view of a portion of the bearing element **217** interfacing between the frame component **210** and the worm drive component **209**.

(218) The raceways of bearing element **217** and **218** (partially shown) are angled with respect to the plane defined by the motion of the lever **202**. The bearing elements **217** and **218** on either side of the plane of the lever **202** are symmetrically angled toward the plane of the lever **202**. This arrangement provides rigidity to the worm drive mechanism by stabilizing it to the plane of the lever motion.

(219) A crankcase is the housing for the crankshaft in a reciprocating internal combustion engine. The crankshaft controls the combustion engine through a cycle of four stages: intake, compression,

power and exhaust.

(220) FIG. **29** shows a chart of the height of the piston of an engine as a function of shaft rotation through one cycle for one embodiment of a crankcase for a 120-degree engine.

(221) A cycle **275** shows piston height through one cycle for a typical combustion engine. In a first rotation of the shaft, the rising edge is the exhaust cycle and the falling edge is the intake cycle. In a second rotation of the shaft, the rising edge is the compression cycle and the falling edge is the power cycle. Thus, four strokes can complete in two rotations of the shaft.

(222) A typical engine uses four, six or eight cylinders. In a four-cylinder engine, each cylinder is out of phase by 90 degrees. In a six-cylinder engine, each cylinder is out of phase by 60 degrees. In an eight-cylinder engine, each cylinder is out of phase by 45 degrees. The even distribution of cylinders across the cycle distributes power delivery over the whole cycle. The extra cylinders generally provide smoother operation and more consistent power.

(223) A cycle **276** shows cylinder head height with an additional harmonic to shape the combustion cycle. The first rising edge is the exhaust cycle and the first falling edge is the intake cycle. The second rising edge is the compression cycle and the second falling edge is the power cycle. Thus, four strokes can complete in one rotation of the shaft.

(224) Furthermore, the power stroke can be extended to 120-degrees of shaft rotation. The extended power stroke effectively allows for three cylinders to be used to distribute power over a cycle. This is referred to herein as a 120-degree engine.

(225) FIG. **30** shows one embodiment of a mechanism for a 120-degree engine using the cycle **276** as shown in FIG. **28**.

(226) A frame component **303** is generally coupled to the frame of the vehicle or the frame of another device employing the engine. A piston component **302** is driven by a piston (not shown). Bearing elements **305**, **306**, **307** and **308** are disposed between the frame component **303** and the piston component **302** so that the piston component **302** slides linearly back and forth along the range of motion as driven by the piston.

(227) The bearing element **305** includes a raceway **305a** coupled to the piston component **302**, a raceway **305c** coupled to the frame component **303**, and the rolling element **305b** rolling between the raceway **305a** and the raceway **305c** throughout the range of motion.

(228) The bearing element **306** includes a raceway **306a** coupled to the piston component **302**, a raceway **306c** coupled to the frame component **303**, and the rolling element **306b** rolling between the raceway **306a** and the raceway **306c** throughout the range of motion.

(229) The bearing element **307** includes a raceway **307a** coupled to the piston component **302**, a raceway **307c** coupled to the frame component **303**, and the rolling element **307b** rolling between the raceway **307a** and the raceway **307c** throughout the range of motion.

(230) The bearing element **308** includes a raceway **308a** coupled to the piston component **302**, a raceway **308c** coupled to the frame component **303**, and the rolling element **308b** rolling between the raceway **308a** and the raceway **308c** throughout the range of motion.

(231) Together, bearing elements **305**, **306**, **307** and **308**, interface between the frame component **303** and the piston component **302**.

(232) A raceway **304a** runs along the perimeter of the component **301**. The raceway **304a** forms a closed loop that has a substantially variable curvature.

(233) Two closed-loop raceways **304c** and **304d** are disposed around the component **301** and coupled to the interior of the piston component **302**. Each of the raceways **304c** and **304d** are identically shaped with a substantially variable curvature. The component **301** drives a shaft **309** forming an axel.

(234) A pair of split pins **304b** are positioned between the raceway **304a** of the component **301** and the raceways **304c** and **304d** of the piston component **302**. The raceway **304a** interfaces with the middle segment of the split pins **304b**. The raceways **304c** and **304d** interface with the segments of the split pins **304b** on either side of the middle segment of the split pins **304b**.

(235) The shape of the raceways **304a**, **304c** and **304d** are irregular in that they are not even or balanced in shape or arrangement. The paths of the rolling elements **304b** are irregular in that they are not even or balanced in shape or arrangement.

(236) The bearing element **304** interfaces between the component **301** and the piston component **302**.

(237) The rolling element paths and raceway shapes of the bearing elements **304**, **305**, **306**, **307**, and **308** are determined by a design process described herein to produce the motion of the components to drive the head cylinder motion as shown in cycle **701** of FIG. **15**.

(238) FIG. **31** shows a chart of the height of the cylinder head of an engine as a function of shaft rotation through one cycle for one embodiment of a crankcase for a 180-degree engine.

(239) The cycle **278** shows piston motion through one cycle for a typical combustion engine. In a first rotation of the shaft, the rising edge is the exhaust cycle and the falling edge is the intake cycle. In a second rotation of the shaft, the rising edge is the compression cycle and the falling edge is the power cycle. Thus, four strokes can complete in two rotations of the shaft.

(240) A cycle **277** shows cylinder head motion with an additional harmonic to shape the combustion cycle. The first rising edge is the exhaust cycle and the first falling edge is the intake cycle. The second rising edge is the compression cycle and the second falling edge is the power cycle. Thus, four strokes can complete in one rotation of the shaft.

(241) However, the cycle **277** is distinguished from the cycle **276** shown in FIG. **15**, in that the first three edges of the cycle **277** are compressed in the first 180 degrees of the shaft rotation and the fourth edge—the power stroke—is expanded into the second 180 degrees of the shaft rotation. Also, the head cylinders rise higher through a greater range of motion, producing a more energy efficient cycle.

(242) Furthermore, the power stroke can be extended to 180-degrees of shaft rotation. The extended power stroke effectively allows for two cylinders to be used to distribute power over a cycle. This is referred to herein as a 180-degree engine.

(243) Since the power stroke is extended to 180-degrees of shaft rotation two cylinders can be used to distribute power over a cycle. This is referred to herein as a 180-degree engine.

(244) In another embodiment, the shape of the power stroke is modified so that the power ratio will follow the force on the cylinder head. This will provide more consistent torque.

(245) FIG. **32** shows one embodiment of a mechanism for a 180-degree engine using the cycle **277** as shown in FIG. **31**.

(246) A frame component **403** is generally coupled to the frame of the vehicle or the frame of another device employing the engine. A component **402** is driven by a piston (not shown). Bearing elements **405**, **406**, **407** and **408** are disposed between the frame component **403** and the component **402** so that the component **402** slides linearly back and forth along the range of motion as driven by the piston.

(247) The bearing element **405** includes a raceway **405a** coupled to the component **402**, a raceway **405c** coupled to the frame component **403**, and the rolling element **405b** rolling between the raceway **405a** and the raceway **405c** throughout the range of motion.

(248) The bearing element **406** includes a raceway **406a** coupled to the component **402**, a raceway **406c** coupled to the frame component **403**, and the rolling element **406b** rolling between the raceway **406a** and the raceway **406c** throughout the range of motion.

(249) The bearing element **407** includes a raceway **407a** coupled to the component **402**, a raceway **407c** coupled to the frame component **403**, and the rolling element **407b** rolling between the raceway **407a** and the raceway **407c** throughout the range of motion.

(250) The bearing element **408** includes a raceway **408a** coupled to the component **402**, a raceway **408c** coupled to the frame component **403**, and the rolling element **408b** rolling between the raceway **408a** and the raceway **408c** throughout the range of motion.

(251) Together, bearing elements **405**, **406**, **407** and **408**, interface between the frame component

403 and the frame component **403**.

(252) A raceway **404a** runs along the perimeter of the component **401**. The raceway **404a** forms a closed loop that has a substantially variable curvature.

(253) Two closed-loop raceways **404c** and **404d** are disposed around the component **401** and coupled to the interior of the component **402**. Each of the raceways **404c** and **404d** are identically shaped with a substantially variable curvature. The component **401** drives a shaft **409** forming an axel.

(254) A pair of split pins **404b** are positioned between the raceway **404a** of the component **401** and the raceways **404c** and **404d** of the component **402**. The raceway **404a** interfaces with the middle segment of the split pins **404b**. The raceways **404c** and **404d** interface with the segments of the split pins **404b** on either side of the middle segment of the split pins **404b**.

(255) The shape of the raceways **404a**, **404c** and **404d** are irregular in that they are not even or balanced in shape or arrangement. The paths of the rolling elements **405b** are irregular in that they are not even or balanced in shape or arrangement. The rolling element paths and raceway shapes of the bearing elements **404**, **405**, **406**, **407**, and **408** are determined by a design process described herein to produce the motion of the components to drive the piston motion as shown in cycle **701** of FIG. **15**.

(256) FIG. **33** shows one embodiment of a close up of a split pin assembly of the mechanism shown in FIG. **32**.

(257) FIG. **34** shows a chart of the height of the piston of a compressor as a function of shaft rotation through one cycle for one embodiment of a crankcase for a compressor.

(258) The cycle **280** shows piston motion through one cycle for a typical legacy crankcase.

(259) A cycle **281** has a modified cycle starting with a rapid compression, followed by 180 degrees of steady injection, and the balance of the cycle for intake. The steady injection reduces pressure spikes and lost energy.

(260) FIG. **35** shows a perspective view of one embodiment of a crankcase mechanism for a compressor producing the cycle **281** as shown in FIG. **34**. FIG. **36** shows a more vertical perspective view of the top of the crankcase mechanism for the compressor. FIG. **37** shows a more vertical perspective view of the bottom of the crankcase mechanism for the compressor. Certain features of the compressor described below may be visible in some of the FIGS. **35**, **36** and **37**.

(261) A component **503** is a frame. The frame component **303** is generally coupled to the frame of the frame of a device employing the compressor. A component **502** is driven by a piston (not shown). Bearing elements **505**, **506**, **505**, **508**, **515**, **516**, **517** and **518** are disposed between the component **503** and the component **502** so that the component **502** slides linearly back and forth along the range of motion as driven by the piston.

(262) The bearing element **505** includes a raceway **505a** coupled to the component **502**, a raceway **505c** coupled to the frame component **503**, and the rolling element **505b** rolling between the raceway **505a** and the raceway **505c** throughout the range of motion.

(263) The bearing element **506** includes a raceway **506a** coupled to the component **502**, a raceway **506c** coupled to the frame component **503**, and the rolling element **506b** rolling between the raceway **506a** and the raceway **506c** throughout the range of motion.

(264) The bearing element **507** includes a raceway **507a** coupled to the component **502**, a raceway **507c** coupled to the frame component **503**, and the rolling element **507b** rolling between the raceway **507a** and the raceway **507c** throughout the range of motion.

(265) The bearing element **508** includes a raceway **508a** coupled to the component **502**, a raceway **508c** coupled to the frame component **503**, and the rolling element **508b** rolling between the raceway **508a** and the raceway **508c** throughout the range of motion.

(266) The bearing element **515** includes a raceway **515a** coupled to the component **502**, a raceway **515c** coupled to the frame component **503**, and the rolling element **515b** rolling between the raceway **515a** and the raceway **515c** throughout the range of motion.

(267) The bearing element **516** includes a raceway **516a** coupled to the component **502**, a raceway **516c** coupled to the frame component **503**, and the rolling element **516b** rolling between the raceway **516a** and the raceway **516c** throughout the range of motion.

(268) The bearing element **517** includes a raceway **517a** coupled to the component **502**, a raceway **517c** coupled to the frame component **503**, and the rolling element **517b** rolling between the raceway **517a** and the raceway **517c** throughout the range of motion.

(269) The bearing element **518** includes a raceway **518a** coupled to the component **502**, a raceway **518c** coupled to the frame component **503**, and the rolling element **518b** rolling between the raceway **518a** and the raceway **518c** throughout the range of motion.

(270) Together, bearing elements **505**, **506**, **507**, **508**, **515**, **516**, **517** and **518** interface between the component **503** and the frame component **502**.

(271) A raceway **504a** runs along the perimeter of the component **501**. The raceway **504a** forms a closed loop that has a substantially variable curvature.

(272) Two closed-loop raceways **504c** and **504d** are disposed around the component **501** and coupled to the interior of the component **502**. Each of the raceways **504c** and **504d** are identically shaped with a substantially variable curvature.

(273) A pair of split pins **504b** are positioned between the raceway **504a** of the component **501** and the raceways **504c** and **504d** of the component **502**. The raceway **504a** interfaces with the middle segment of the split pins **504b**. The raceways **504c** and **504d** interface with the segments of the split pins **504b** on either side of the middle segment of the split pins **504b**. The split pins **504b** are shaped similar to the split pin **105** where the cylindrical middle segment has a with smaller diameter than the cylindrical segments on either side of the middle segment.

(274) From the bottom view of the compressor shown in FIG. **37**, raceway **514a** runs along the perimeter of the component **510**. The raceway **514a** forms a closed loop that has a substantially variable curvature. The component **510** is coupled to component **501** so that they move together, but the raceway **514a** has a different shape than the raceway **504a**.

(275) Two closed-loop raceways **514c** and **514d** are disposed around the component **510** and coupled to the interior of the component **502**. Each of the raceways **514c** and **514d** are identically shaped with a substantially variable curvature.

(276) A pair of split pins **514b** are positioned between the raceway **514a** of the component **510** and the raceways **514c** and **514d** of the component **502**. The raceway **514a** interfaces with the middle segment of the split pins **514b**. The raceways **514c** and **514d** interface with the segments of the split pins **514b** on either side of the middle segment of the split pins **514b**. The split pins **504b** are shaped similar to the split pin **105** where the cylindrical middle segment has a with smaller diameter than the cylindrical segments on either side of the middle segment.

(277) The component **501** and the component **510** drives a shaft **509** forming part of an axel that drives the compressor.

(278) The shape of the raceways **504a**, **504c**, **504d**, **514a**, **514b**, and **514c** are irregular in that they are not even or balanced in shape or arrangement. They are neither circular nor linear. The paths of the rolling elements **504b** and **514b** are irregular in that they are not even or balanced in shape or arrangement. The rolling element paths and raceway shapes of the bearing elements **504**, **505**, **506**, **507**, **508**, **515**, **516**, **517**, and **518** are determined by a design process described herein to produce a specified motion of the components to drive the head cylinder motion as shown in cycle **704** of FIG. **34**.

(279) The compressor has the height function developed using spline functions. To get the splines to be continuous over the 0 and 360 degrees, the control points were reflected before and after 0 and 360. For instance, if the second control point were at 15 degrees and a height of 0.5 then a control point at 375 and height of 0.5 is included. If the second to last point were 340 degrees and a height of 0.4 then a point at -20 degrees and 0.4 would be added. While only 0 to 360 degrees are used, reflecting the control point forward and back insures the derivative will be continuous over

the loop-closure.

(280) FIGS. **38** and **39** shows perspective view of one embodiment of a rotary mechanism at different points in the rotation process. FIG. **40** shows a close-up view of a portion of the rotary mechanism. This mechanism may be used in a pump, for example, where rotor rotates in the opposite direction as the input shaft **709**. Two such devices with a differing number of rolling elements can be combined to create a speed reducer by attaching the two rotors and allowing the stator on the second device to spin. The relationship between the number of rolling elements define the speed reduction factor.

(281) The mechanism includes an eccentric **701**, a rotor **703** and a stator **705**. The rotor **703** turns in a reverse direction as the input shaft **709**.

(282) An input shaft **709** is positioned off-center on the eccentric **701**. Power received on the input shaft **709** causes the eccentric **701** to rotate. The rotation causes the rolling elements **702b** to rotate which in turn causes the rotor **703** to rotate in the reverse direction as the shaft. The rotor **703** is the output of the mechanism that is coupled to drive the pump.

(283) There are twelve rolling elements **702b** (one not shown behind input shaft **709**) positioned between a closed-loop raceway **702a** of the eccentric **701** and the closed-loop raceway **702c** of the rotor **703**. The raceway **702a**, the rolling elements **702b**, and the raceway **702c** form a bearing element **702**.

(284) Six rolling elements **704b** are positioned between a closed-loop raceway **704a** of the rotor **703** and a raceway **704c** of the stator **705**. The closed-loop raceway **704a** has a substantially variable curvature including five lobes. The closed-loop raceway **704c** has a substantially variable curvature including seven lobes. The raceway **704a**, the rolling elements **704b**, and the raceway **704c** form a bearing element **704**.

(285) For this type of device, the number of rolling elements **704b** can vary with 2 as a minimum. Lobes are the periodic protrusions or trenches in the shape of the raceways. The number of stator lobes, sLobes, will be one greater than the number of rolling elements (in the stator **705** that is seven) and the number of rotor lobes, rLobes, will be one less than the number of rolling elements (in the rotor **703** that is five). The center of the rotor moves with the eccentric **701**. The center position is given by: $x=e*\cos(\theta+\theta_0)$ and $y=e*\sin(\theta+\theta_0)$, where θ is the input shaft rotation, and θ_0 is the initial shaft rotation. The rotation of the rotor, r , will be given by $r=r_0-2*(\theta+\theta_0)/rlobes$, where r_0 is the initial rotation of the rotor.

(286) To generate the closed-loop raceways, only half of one set of lobes need to be calculated. The second half is an angular reflection of the first half. The rest of the lobes are angular copies. The angle that needs to be simulated is $2*PI/sLobes$. The shaft rotation for that section is $PI*(1.0/(sLobes)+1.0/rLobes)$. For the closed-loop raceways, the rolling element needs to finish at the angular position described above. To enable that to happen, the MVSA need to adjust the radius of the rolling element and the distance of the start position of the rolling element from the system center as well as the second and subsequent positions of the pin.

(287) FIGS. **41**, **42**, **43**, **44**, and **45**, shows one embodiment of a sequence of movement for a mechanism of FIG. **38**.

(288) The mechanism includes an eccentric **701**, a rotor **703**, and a stator **705**.

(289) FIGS. **46** and **47** shows perspective view of one embodiment of a rotary mechanism **720** at different points in the rotation process. FIG. **48** shows a close-up view of a portion of the rotary mechanism. This mechanism may be used in a pump, for example, where rotor turns in the same direction as an input shaft **809**.

(290) The mechanism includes an eccentric **801**, a rotor **803**, and a stator **805**.

(291) An input shaft **809** is positioned off-center on the eccentric **801**. Power received on the input shaft **809** causes the eccentric **801** to rotate. The rotation causes the rolling elements **802b** to rotate which in turn causes the rotor **803** to rotate in the direction of the input shaft **809**. The rotor **803** is the output of the mechanism that is coupled to drive the pump.

(292) There are six rolling elements **804b** positioned between a closed-loop raceway **804a** of the stator **805** and a closed-loop raceway **804c** of the rotor **803**. The closed-loop raceways **804c** and **804d** have a substantially variable curvature including five lobes. The closed-loop raceway **804a** has a substantially variable curvature including seven lobes.

(293) There are twelve rolling elements **802b** (one not shown) positioned between a closed-loop raceway **802c** of the rotor **803** and the closed-loop raceway **802a** of the eccentric **801**.

(294) An input shaft **809** is positioned off-center on the eccentric **801**. Powers received on the input shaft causing the eccentric **801** to rotate. The rotation causes the rolling elements **802b** to rotate which in turn causes the rotor **803** to rotate. The rotor **803** is the output of the mechanism.

(295) For this type of device, the number of rolling elements **804b** can vary, with 2 as a minimum. Lobes are the periodic protrusions or trenches in the shape of the raceways. The number of stator lobes, sLobes, will be one less than the number of rolling elements (in the stator **805** that is five) and the number of rotor lobes, rLobes, will be one greater than the number of rolling elements (in the rotor **803** that is seven). The center of the rotor moves with the eccentric **701**. The center position is given by: $x=e*\cos(\theta+\theta_0)$ and $y=e*\sin(\theta+\theta_0)$, where θ is the input shaft rotation, and θ_0 is the initial shaft rotation. The rotation of the rotor, r , will be given by $r=r_0+2*(\theta+\theta_0)/rlobes$, where r_0 is the initial rotation of the rotor.

(296) To generate the closed-loop raceways, only half of one set of lobes need to be calculated. The second half is an angular reflection of the first half. The rest of the lobes are angular copies. The angle that needs to be simulated is $2*PI/sLobes$. The shaft rotation for that section is $PI*(1.0/(sLobes)+1.0/rLobes)$. For the closed-loop raceways, the rolling element needs to finish at the angular position described above. To enable that to happen, the MVSA need to adjust the radius of the rolling element and the distance of the start position of the rolling element from the system center as well as the second and subsequent positions of the pin.

(297) FIGS. **49**, **50** and **51** shows perspective view of one embodiment of a linear to linear mechanism at different points in the range of motion. This mechanism may be used in to linearly in a direction as defined by the relative shape of the bearing element **745** and bearing element **746**. In one embodiment, the inputs may be the races associated with raceway **745a** and raceway **746a** as driven by drive components (not shown) and the output may be on a component (not shown) attached to the races associated with raceway **745c** and raceway **746c**.

(298) In this embodiment, the power ratio is programmed to vary from 0.25 to 4. The power ratio depends on the ratio of movement of bearing elements along either axis in the two-dimensional movement space parallel to the plane of the frame **750**.

(299) FIG. **52** a first half of a rolling element **760b** and a second half of a rolling element **761b** being screwed into opposite sides of a raceway **762c** and a raceway **763c**.

(300) FIG. **53** shows the first half of a rolling element **760b** and a second half of a rolling element **761b** partially screwed into opposite sides of a raceway **762c** and a raceway **763c**.

(301) FIG. **54** shows the first half of a rolling element **760b** and a second half of a rolling element **761b** fully screwed into opposite sides of a raceway **762c** and a raceway **763c** to meet in the middle and form a bearing element **860**.

(302) FIGS. **55**, **56**, **57**, and **58** illustrate two rotary devices coupled together to form a speed reducer **780**.

(303) FIG. **55** shows the front view of a speed reducer with 15 rolling elements along the stator **785**. The shaft shown is the input shaft **789** for the speed reducer **780**. The top rotary device **791** use split pins **787b** that roll on raceway **787a**, raceway **787c**, and raceway **787d**.

(304) FIG. **58** shows an exploded view of the speed reducer. These bottom rotary device **792** use split pins **807b** that roll on raceway **807a**, raceway **807c**, and raceway **807d**.

(305) The rotor **783** is coupled to the rotor **803** through the dowels **784** inserted into the dowel openings **804b**. This causes the rotor **783** and the rotor **803** to remain fixed to each other.

(306) The input stator **785** has a certain number of rolling elements **807b**. The output stator **805** has

15 rolling elements.

(307) Since the rotation of the rotor **803** is dependent upon the number of rolling elements, the rotor **783** would rotate at different speeds if each of the stator **785** and stator **805** were stationary. Instead the rotors are connected through dowels **784**, and the back stator **805** rotates.

(308) FIG. **56** shows a close up view of a portion of the top of the speed reducer. The shaft shown is the input shaft **809** for the speed reducer. Although the bottom rotary mechanism is not shown, it has 14 rolling mechanisms in this embodiment.

(309) FIG. **57** shows the back view of the speed reducer. The shaft **809** is the output shaft for the speed reducer.

(310) The speed ratio of the input shaft to the output shaft is given by:

$$(311) \text{ speedRatio} = \frac{(\text{backRate} - \text{frontRate})}{(1 - \text{frontRate})}$$

(312) Where the backRate is the rotor rate for the back rotary system, and the frontRate is the rotor rate for front system.

(313) For the speed reducer shown the output shaft would rotate at 0.0095 times the speed of the input shaft. The speed reduction is the inverse of the speed ratio is 105.

(314) By adding a spring between the eccentric and the bearing, the speed reducer can be made to be zero-backlash. In FIG. **28**, the spring would be creating force to the left, forcing the play out of both the bearing and the pin-raceway system.

(315) The speed reducer can be have multiple speed ratios by stacking multiple front rotor of differing number of pins. All but one of the stator elements would be free to rotate. To change speeds, the new stator would be braked, while the old speed would be freed. This type of shifting would be desirable because the braking and release could take place at the same time and power could continue to be transmitted. Normal shifting requires the following: depower, disengage, engage, and repower.

(316) The speed reducer shown could also be made in a single column. The outer layer would be the output. Next is a row of pin, mating to a common rotor. Then another set of rolling elements connecting to the eccentric.

(317) FIG. **59** illustrates a top perspective view of a speed reducer **820** including a top rotary device **851** and a bottom rotary device **852**.

(318) The operation of this speed reducer is similar to that of FIGS. **55-58**. However, this speed reducer does not use split pins. Although one embodiment of the optimization method suggested the use of split pins, the difference in the diameters for the segments of the split pins was approximately 0.2 percent. For many applications, this is close enough to use a standard pin rather than a split pin.

(319) FIG. **60** illustrates a top perspective view of the bottom rotary device **852** of the speed reducer of FIG. **59**.

(320) FIG. **61** is a diagrammatic representation of an embodiment of a machine **950**, within which a set of instructions for causing the machine to perform one or more of the methods discussed herein. The machine **950** may be connected (e.g., networked) to other machines. In a networked deployment, the machine may operate in the capacity of a server or a client machine in a client-server network environment, or as a peer machine in a peer-to-peer (or distributed) network environment. In one embodiment, the machine communicates with a server to facilitate operations of the server and/or to access the operation of the server. In some embodiments, the machine **950** may act as a server for some functions and a client for other functions.

(321) In some embodiments, the machine **950** is a CAD system for performing any one or more of the methods of the functions of the inventive subject matter or a component of such systems, such as one or more processors that make up the machine **950**. In other embodiments, the machine **950** is a general purpose computer adapted to perform the inventive subject matter.

(322) In some embodiments, the system is connected directly or via a network to a 3D Printer, CNC machine or other prototype or manufacturing based tools for prototyping and manufacturing

devices according to the inventive subject matter.

(323) The machine **950** includes a processor **960** (e.g., a central processing unit (CPU), a graphics processing unit (GPU) or both), a main memory **970** and a nonvolatile memory **980**, which communicate with each other via a bus **969**. In some embodiments, the machine **950** may be a cluster of computers or comprise multiple processors or multiple processor cores. In one embodiment, the machine **950** also includes a video display **981**, an alphanumeric input device **962** (e.g., a keyboard), a cursor control device **963** (e.g., a mouse), a drive unit **964** (e.g., solid state drive (SSD), hard disk drive, Digital Versatile Disk (DVD) drive, or flash drive), a signal generation device **968** (e.g., speaker) and a network interface device **990**.

(324) In some embodiments, the video display **961** includes a touch-sensitive screen for user input. In some embodiments, the touch-sensitive screen is used instead of a keyboard and mouse. The drive unit **964** includes a machine-readable medium **965** on which is stored one or more sets of instructions **966** (e.g. software) embodying any one or more of the methods or functions of the inventive subject matter.

(325) The instructions **966** may also reside, completely or partially, on machine-readable media within the main memory **970** and within machine-readable media within the processor **960** during execution thereof by the machine **950**. The instructions **966** may also be transmitted or received over a network **995** via the network interface device **990**. In some embodiments, the main memory **970** and the machine-readable medium **965** also includes data **967**. In some embodiments, the data **967** includes CAD design information defining components that have machines and mechanisms as described herein. The data **967** also includes data structures that define position and movement information, error vectors and other information used in the design, testing and optimization process described herein.

(326) While the machine-readable medium **965** is shown in an exemplary embodiment to be a single medium, the term “machine-readable medium” should be taken to include a single medium or multiple media (e.g., a centralized or distributed database, and/or associated caches and servers) that store the one or more sets of instructions and/or data. The term “machine readable medium” shall also be taken to include any non-transitory medium that is capable of storing, encoding or carrying a set of instructions for execution by the machine. The instructions may include instructions that cause the machine to perform any one or more of the methods or functions of the inventive subject matter. The term “machine-readable medium” shall accordingly be taken to include, but not be limited to, solid-state memories, optical and magnetic media, and other non-transitory tangible media.

(327) In general, the methods executed to implement the embodiments of the disclosure, may be implemented as part of an operating system or a specific application, component, program, object, module or sequence of instructions referred to as “programs.” For example, one or more programs may be used to execute specific processes according to the inventive subject matter. The programs typically comprise one or more instructions set at various times in various memory and storage devices in the machine **950**, and that, when read and executed by one or more processors, cause the machine to perform operations to execute methods, functions and other elements of the inventive subject matter.

(328) In some embodiments, the software for performing the inventive subject matter is a stand-alone program delivered on a computer-readable medium, downloaded from a server, or operated by a server that delivers the services as software-as-a-service. In other embodiments, an add-on program, or plug-in, to to third-party software, such as CAD software, allow the third-party CAD program to incorporate some or all of the inventive subject matter.

(329) Moreover, while embodiments have been described in the context of machines, those skilled in the art will appreciate that the various embodiments are capable of being distributed as a program product in a variety of forms, and that the disclosure applies equally regardless of the particular type of machine or computer-readable media used to actually effect the distribution.

Examples of machine-readable media include, but are not limited to, recordable type media such as volatile and non-volatile memory devices, solid state drives (SSDs), flash memory devices, floppy and other removable disks, hard disk drives, and optical disks such as Compact Disk Read-Only Memory (CD-ROMS) and DVDs, among others.

(330) The foregoing discussion is described with reference to rolling elements and pins. However, in other embodiments, ball bearings are used. Instead of guides, separators or other structures may be used to keep the ball bearings spaced apart.

(331) Initial Rolling Element Path Estimation

(332) Having an automated initial rolling element path estimate is a great convenience to the design process. It saves the designers of the burden and enables rapid design iterations. The method described herein is accurate and nearly resembles the actual optimized rolling element paths.

(333) The premise is that when a rolling element rotates between two straight surface, the rolling element moves at half the difference of the velocities. If it's a split pin then the velocity is given by the following:

(334)
$$v_{\text{pin}} = \frac{v_o}{(1 - \frac{\text{radius}_o}{\text{radius}_i})} + \frac{\text{radius}_o}{\text{radius}_i} \times \frac{v_i}{(1 - \frac{\text{radius}_o}{\text{radius}_i})}$$
 Where: $v_{\text{sub.pin}}$ is the velocity of the pin. $v_{\text{sub.i}}$ is the

velocity of the input component at the point of contact with the pin. $v_{\text{sub.o}}$ is the velocity of the output component at the point of contact with the pin. radius.sub.o is the radius of the split pin that makes contact with the output component. radius.sub.i is the radius of the split pin that makes contact with the input component.

(335) The difficulty in solving this equation is that the contact point on each of the components depends upon the velocity of the pin. There are four variables that cannot be solved directly, so it needs to be solved using a MVSA. The error calculation has two rolling element velocities, one that is an input to the error calculation (the x and y values are state variables) and the other is a result that will be used for the error calculation. The state vector will be the angles from the rolling element centers, and the estimated velocity of the pin, $V_{\text{sub.pin-est}}$. With $v_{\text{sub.pin-est}}$ set, the velocity of the contact points can be found. The contact point velocities are fed into the equation above to yield the second rolling element velocity. The velocity error is the difference between the two velocities and is computed by subtracting $v_{\text{sub.pin}} - V_{\text{sub.pin-est}}$. The error in contact angle is computed using the dot product of the normal vector and the velocity at the contact point. That gives four state variables, velocity x and y, and two rolling element angles and four error variables, the two dot products and the velocity difference x and y value.

(336) Once the rolling element velocity is found, the rolling element path can be numerically integrated to the next interval.

(337) CAD Interface

(338) In some embodiments, the bearing elements are created using a CAD program. In some embodiments, the capability is added to a CAD program using a software plug-in that includes software configured to perform some of the processes described herein. The plug-in enable a designer to design, test, and visualize the motion of raceway-based mechanisms described herein.

(339) The first step would be to establish the number of points and the plane for which the bearing elements will operate. The plane of for which the raceways and rolling elements will operate will also need to be defined. Then the interface would need to enable the creation of motion specifications. There are several easy specifications that could be incorporated into the user interface, like the rotation of a shaft, straight-line motion or still motion (also called ground, or reference) like that of the chassis or frame. More complicated motion descriptions could come from analysis packages like a spreadsheet. Once there are two or more motion specifications, then the User Interface (UI) would enable creating bearing elements. The UI would allow the creation of a rolling element and the raceways would follow. The rolling elements could be icons that could be drag-and-drop offering or through a drop down. For each combination of motions definitions, the UI will need to be an offer of a rolling element to include in the user interface.

(340) The designer would be able to drag a rolling element into the 3D view. The raceways and the rolling element would be shown, either approximated using the initial rolling element path approximation or the complete optimization. The rolling element could be dragged from location to location. As it is dragged, the raceways would move with the pin. A background process could reshape the raceways according to the new location and update the image with the new shapes. The CAD program could perform other functions like checking if the raceways and the components to which they are attached make contact with other components. The designer should also be able to move the rolling element perpendicular to the plane of motion. The designer should also be able to change the interval in the motion description of the components to view how they move. Either by a slider, by typing, through the mouse wheel, or by pushing a play button. By enabling the three-dimensional views of raceways and their motions the designer can review interference problems and force problems.

(341) The other variables that would be an option for the UI are:

(342) The angular orientation of the plane of motion of the Bearing elements.

(343) The rotation designation of the pin, either clockwise or counterclockwise.

(344) The distance of the bearing elements from the plane of motion.

(345) The width of the raceways and the pin.

(346) The number of guides on the pin.

(347) The diameter of the rolling element for a non-split pin and the diameters for a split pin.

(348) The pattern of the rolling element guides.

(349) The height, width and the bevel of the guides.

(350) Whether the raceways are closed-loop or open-loop

(351) For a closed-raceway, the target number of guides.

(352) The raceways are only one surface of the component. The designer would use the CAD program to specify the rest of the component, including all the other surfaces. The additional surfaces also need to be simulated though the range of motion to preview interference problems as well as stresses.

(353) It can be desirable to make a mechanism comprised of one or more bearing elements and a legacy mechanism like linkages, bearing, gears and cams. Many CAD programs have simulation systems for such legacy mechanisms. It would be best if the simulation systems for the raceways were integrated into the simulation systems of the legacy mechanisms.

(354) Many CAD systems also include capabilities to perform force and stress analysis. They can include the ability to compute the forces through a contact load or through a linkage. They can also be used to calculate the stresses within a component as well using techniques like Finite Element Analysis. A well-integrated solution would enable a force and stress analysis throughout the range of motion.

(355) Other Considerations in Using Bearing Elements in Design

(356) First, the desired motions cannot have extreme accelerations. This includes sharp corners. The motion should have continuous first derivatives. Make sure the functions used are smooth and continuous. A spline function can be used to generate the function.

(357) For closed-loop raceways, the function needs to be continuous and smooth over the loop-closure. At 0 and 360 degrees of shaft rotation the component path must be the same point and the slopes must be smooth. The compressor shown had the height function developed using the spline functions. To get the splines to be continuous over the 0 and 360 degrees, the control points were reflected before and after 0 and 360. For instance, if the second control point were at 15 degrees and a height of 0.5 then a control point at 375 and height of 0.5 is included. If the second to last point were 340 degrees and a height of 0.4 then a point at -20 degrees and 0.4 would be added. While only 0 to 360 degrees are used, reflecting the control point forward and back insures the derivative will be continuous over the loop-closure.

(358) Another potential pitfall is invalid geometry due to contact positions reversing. When a

rolling element is moving slowly, it is possible for the contact position of a raceway to backup. This is not valid and has to be rejected by either the designer the software can detect the problem. Either the pin-start-position must be modified, or the motion description.

(359) Interference is another problem. The components may make undesired contact that would prevent the device to work properly. The designer should review the motion of the device through the entire range to insure there is sufficient clearance. The most common fix is to modify the rolling element start position.

(360) For closed-loop systems, there can be many valid rolling element start positions. This enables using multiple component raceways that include a pin. The compressors example uses two such raceways and rolling elements. This can be helpful to insure proper support of the system and also relieve stresses.

(361) Detailed Mathematical Description

(362) Once a designer has determined how the components are to move and the rolling element start positions determined along with their rotation designation the Bearing Elements can be found. The objective is to adjust the path of the rolling element so to simultaneously reduce the friction and maximize the opposing angles. The path adjustments are made by adjusting a state vector to minimize an error vector.

(363) The MVSA requires an error function either compiled with or some other means where the function can be computed. The error function takes the state vector, an array of floating point numbers, as an argument, and copies the values to the correct elements to create the raceways. For instance, if the state vector was encoded to have the radius of the rolling element in the first position of the array, then the error function must copy that value to the correct structure that holds the rolling element radius. Then the raceways are created using the state variables supplied by the MVSA. The error values are computed and returned to the MVSA in terms of an array of values.

(364) In this case, state vector is an array of floating point numbers containing the X and Y values of the second and subsequent elements of the rolling element path. The error vector is a combination of the computed friction and a measure for the opposing angles. The state vector is used to calculate the error vector. There are three steps to creating an error vector from a state vector. First, the raceway surface is derived. With the raceway surface, friction can be calculated and then the measure of the opposing angle error is calculated.

(365) Before computing the friction or opposing angles, the surface of the raceway is found. The surface is the two-dimensional sweep surface created by the rolling element as it moves relative to either of the components associated with the raceway. The creation of a 2D sweep surface is a well-documented mathematical process and is included in many computer aided design (CAD) packages. The 2D sweep derives two surfaces, one on either side. Rolling a rolling element along one of the surfaces will result in either a clockwise or counter-clockwise rotation. The surface to use is the one that rotates the same as designated by the input. This becomes the raceway. The raceway is an edge of the component, and is described by arrays of X and Y values. Each of the X and Y values also designates a contact position between the rolling element and the edge. The i'th X and Y will be in contact with the rolling element when the rolling element and the component are in their i'th location.

(366) The location on the pin's surface where the contact point will take place satisfies the following condition:

$$(\{\text{right arrow over } (vPin)\} - \{\text{right arrow over } (vComponent)\}) \cdot \{\text{right arrow over } (surfaceNormal)\} = 0$$

(367) Where the $\{\text{right arrow over } (vPin)\}$ and $\{\text{right arrow over } (vComponent)\}$ are numerically differentiated velocity vectors of the rolling element and component at the contact point and $\{\text{right arrow over } (surfaceNormal)\}$ is a surface normal vector at the point of contact. The “ $\cdot$ ” operation is the vector dot product. If the condition is not satisfied, then the angle of the contact point must be adjusted. The left side of the equation becomes an error measure for a search algorithm. The search

algorithm utilizes an initial estimate for the angle. A good initial estimate for the contact angle can be found by computing the direction of the velocity difference at the rolling element center, $\{\text{right arrow over (vDiffCenter)}\}$.

$\{\text{right arrow over (vDiffCenter)}\} = (\{\text{right arrow over (vPin)}\} - \{\text{right arrow over (vComponent)}\})$
 (368) Then find the angle, angleCenter, of the $\{\text{right arrow over (vDiffCenter)}\}$ using an atan 2 function used in most computer languages. Where the input X and Y are the X and Y velocities of $\{\text{right arrow over (vDiffCenter)}\}$.

angleCenter = atan 2(Y,X)

(369) A good initial estimate, initAngle, is the following:

(370) initAngle = $\begin{cases} \text{angleCenter} + 90\text{degrees,} & \text{forclockwiserotation} \\ \text{angleCenter} - 90\text{degrees,} & \text{forcounter - clockwise} \end{cases}$

(371) The mathematical creation of the sweep surface utilizes a Single Variable Search Algorithm (SVSA). Examples of SVSAs include _____. The SVSA searches for a contact point where the error value becomes zero, cpi.

(372) Once the contact point has been found, it must be included in the component edge. To do so, the contact point must be transformed and rotated back to the original component location.

(373) The edge will be represented by two arrays of floating point numbers, one for the X values, edgex and one for the Y values, edgey. The following equation generates the location for the ith position. Whereby cx and cy are the X and Y locations for the component at the ith position. And cpx and cpy are the X and Y locations for the ith value of the contact point, cpi. And theta is the ith value for the components rotation.

$$(374) \begin{bmatrix} \text{edgex} \\ \text{edgey} \end{bmatrix} = \begin{bmatrix} \cos(\theta) & -\sin(\theta) \\ \sin(\theta) & \cos(\theta) \end{bmatrix} \begin{bmatrix} \text{cx} \\ \text{cy} \end{bmatrix} + \begin{bmatrix} \text{cpx} \\ \text{cpy} \end{bmatrix}$$

Error Vectors

(375) With the sweep surface intact, the error vectors can be created. Two arrays need to be estimated, the friction and the error in opposing angles. For computing friction, the rolling element can rotate along a raceway such that there is no sliding. But there are two raceways. The rotation may not be equal. If a device were made with this discrepancy, then the rolling element would need to partially slide along one of the raceways. A device with no sliding has a rolling element that rotates the same for each raceway.

(376) The difference in rotation is part of the error vector used by the MVSA. To compute the rolling elements rotation as it moves from one position to the next, start by computing the length of each edge segment, li. There are nPoints-1 elements in array.

$$l_{\text{sub},i} = \sqrt{\{(x_{\text{sub},i} - x_{\text{sub},i+1})^2 + (y_{\text{sub},i} - y_{\text{sub},i+1})^2\}}$$

(377) The perimeter, P, of the edge from the starting point to the i'th element. Is computed as:

$$P_{\text{sub},1} = 0$$

$$P_{\text{sub},i} = P_{\text{sub},i-1} + l_{\text{sub},i-1}, \text{ for } i=2 \text{ to } n\text{Points}$$

(378) Next, the location is found for the i'th edge position as the component is rotated and translated. First rotate the point.

$$(379) \begin{bmatrix} x_{r_i} \\ y_{r_i} \end{bmatrix} = \begin{bmatrix} \cos(\text{Rotation}_i) & -\sin(\text{Rotation}_i) \\ \sin(\text{Rotation}_i) & \cos(\text{Rotation}_i) \end{bmatrix} \begin{bmatrix} x_i \\ y_i \end{bmatrix}$$

(380) Next, the motion of the component is added. This is the location of the contact point between the rolling element and the edge xci, yci.

$$x_{\text{csub},i} = x_{r_{\text{sub},i}} + x_{\text{sub},i}$$

$$y_{\text{csub},i} = y_{r_{\text{sub},i}} + y_{\text{sub},i}$$

(381) The rolling element center at the i'th location is pin's location xi, yi. The distance from the rolling element center to the contact point center is also the rolling element angle in vector form, designated as pixi, piyi:

$pix.sub.i = xc.sub.i - x.sub.i$

$Piy.sub.i = yc.sub.i - y.sub.i$

(382) The contact angle, c_i , between the rolling element and the can be computed using a standard arctan 2 function available in many computer languages:

$c.sub.i = \text{atan2}(piy.sub.i, pix.sub.i)$

(383) Where x_i and y_i are the from the rolling element x_i and y_i . The atan 2 function yields discontinuities from one quadrant to the next. The array will have to be processed to insure the contact angles stay continuous. To do this, subtract the subsequent value from the current value to create a the angle difference, $angleDiff_i$.

$angleDiff.sub.i = c.sub.i+1 - c.sub.i$

(384) If the absolute value of angle $angleDiff$ is greater than π then and the following to c_{i+1} .

(385) $C_{i+1} = C_{i+1} + \text{floor}(\frac{\text{floor}(\frac{angleDiff_i}{2}) + 1}{2}) \times 2 \times$

(386) Where “floor” is the standard floor value function available in most computer languages.

(387) If the difference between two array elements is greater or less than 270 degrees, then 360 degrees will have to be subtracted or added respectively to each subsequent element in the array.

(388) The rolling element rotation, pr_i , from the beginning to the i 'th element is:

$pr.sub.i = P.sub.i - c.sub.i$

(389) A segment is a section of the raceway between one point in the raceway to the next point on the raceway. The incremental rotation, iir_i for the input component, and oir_i for the output component.

$iir_i = pr_i - pr.sub.i+1$, for $i=0$ to $nPoints-1$ and computed using the input component pr

$oir_i = pr.sub.i - pr.sub.i+1$, for $i=0$ to $nPoints-1$ and computed using the output component pr

(390) The friction, f_i , difference in incremental rotation:

$f.sub.i = iir.sub.i - oir.sub.i$

Opposing Angle Error

(391) The error is successively estimated from a measure of the error. The measure needs to be zero when the angles appose each other, and be greater with greater error. The simplest measure of error is to use cross product the angle vectors. The variables pix_i , piy_i are specific to the input and output. $ipix_i$, $ipiy_i$ are the pix_i , piy_i computed for the input component. Correspondingly, $opix_i$, $opiy_i$ are the pix_i , piy_i computed at the output component. The opposing angle error at the i 'th position, oae_i , are the cross product of the two vectors:

$oae.sub.i = opix.sub.i * ipiy.sub.i - ipix.sub.i * opiy.sub.i$

(392) With the friction and the measure for opposing error, the errors can be reduced using an initial estimate of the path and a function that takes a state vector as an argument and returns an error vector as a result. The function is responsible for unpacking the vector into meaningful data for the measurement and packing the error vector.

(393) In this case, the state vector, $stateV$, ARE filled with second and subsequent X values of the rolling element path followed by the second and subsequent Y values. The initial path supplied by the designer estimate is packed in that order to create the initial state vector, $initState$.

(394) The error function takes the front half of the array and replaces the X values of the rolling element path, then the Y values from the second half. The error function then calculates the 2D sweep surface, the friction and then opposing error. Next it encodes the error vector, $errorV$.

(395) Both $errorV$ and $stateV$ have the same number of elements. There are $2*nPoints - 2$ elements in $stateV$. Friction, f , has $npoints-1$ elements and opposing aoe has $nPoints$ giving a total of $2*nPoints-1$. To resolve the discrepancy, the last value of the opposing angle error is not used, which is why an additional point was needed from the designer. The number of array elements for the state and error vectors, n , are $2*nPoints - 2$.

(396) The error function is called with the designer supplied initial path estimate, to establish the initial error, $initError$;

initError=errorFun(initState)

(397) Successive calls are made to the error function to approximate the Transposed Jacobian Matrix, J.sup.T.

$$(398) J^T = \begin{bmatrix} \frac{\partial e_1}{\partial s_1} & \frac{\partial e_2}{\partial s_1} & \text{.Math.} & \frac{\partial e_n}{\partial s_1} \\ \frac{\partial e_1}{\partial s_2} & \frac{\partial e_2}{\partial s_2} & \text{.Math.} & \frac{\partial e_n}{\partial s_2} \\ \text{.Math.} & \text{.Math.} & \text{.Math.} & \text{.Math.} \\ \frac{\partial e_1}{\partial s_n} & \frac{\partial e_2}{\partial s_n} & \text{.Math.} & \frac{\partial e_n}{\partial s_n} \end{bmatrix}$$

(399) Each row of the matrix, rowi, is approximated with three steps. First by coping initState to a new array stateVi, then adding a small value, delta, to the state variable with the same row index.

stateV.sub.i.sub.i=stateV.sub.i.sub.i+delta

(400) Second, the error function is then run for the perturbed state vector resulting in errori.

error.sub.i=errFun(stateV.sub.i)

(401) The row is calculated subtracting each individual element of initError from the corresponding element of errori, then dividing by delta.

$$(402) irow_{ij} = \frac{(error_{ij} - initError_{ij})}{delta}$$

(403) It's best to create and manipulate a matrix using a specialized matrix package such as Boost for C++. Each of the rows are then inserted into the matrix. The matrix J, is create by calling a matrix transform on the matrix J.sup.T. The object now is to manipulate the following expression to solve for the step in state values, stepV.

(404) J*stepV=errorV

(405) The step V is found by calling a LU factorization routine on J then call a LU substitution routine on J and errorV to result in stepV. A new state vector, newState, is the result of adding the step value.

newState=initState+stepV

(406) By calling the error function with newState, the raceways are created, and the new error is calculated.

newError=errorFun(newState)

(407) The newError vector should be inspected for the application. If the the application requires lower errors, the process can be run again with newState as the initState.

Claims

1. A rotary speed reducer comprising: a first pair of races comprising a first pair of raceways forming a first closed loop about an axis; a second pair of races comprising a second pair of raceways forming a second closed loop about the axis and around the first closed loop; and a first plurality of rolling elements operable to roll between each of the first pair of raceways, wherein each of the first plurality of rolling elements substantially rolls as it travels around the first closed loop; and a second plurality of rolling elements operable to roll between each of the second pair of raceways, wherein each of the second pair of raceways has a substantially variable curvature, wherein each of the second plurality of rolling elements substantially rolls as it travels around the second closed loop.
2. The rotary speed reducer of claim 1 wherein each of the second pair of raceways has a repeating pattern around the second closed loop.
3. The rotary speed reducer of claim 2 wherein the repeating pattern comprises a plurality of regularly spaced lobes.
4. The rotary speed reducer of claim 1 wherein each of the second plurality of rolling elements is a ball bearing.

5. The rotary speed reducer of claim 1 wherein each of the second plurality of rolling elements is a roller bearing.
6. A rotary speed reducer of claim 1 wherein each of the plurality of rolling elements has a first rolling portion having a cross-section perpendicular to an axis of rotation defining a first shape, and a second rolling portion and third rolling portion laterally on either side of the first rolling portion, each having a cross-section perpendicular to the axis of rotation defining a second shape, the first shape being different from the second shape, the mechanism further comprising a third race having a third raceway, the first one of the first pair of raceways and the third raceway being operable to interface with the second and third portion of each of the plurality rolling elements, the second one of the first pair of raceways being operable to interface with the first portion of each of the plurality of rolling elements.
7. The rotary speed reducer of claim 6 wherein the first shape and the second shape differ in at least a distance of the surface of a portion of the rolling element at the corresponding raceway to the axis of rotation for at least a portion of the rotation of each of the plurality of rolling elements.
8. The rotary speed reducer of claim 1 wherein the second pair of raceways comprise a first plurality of guide structures and the second plurality of rolling elements comprise a second plurality of guide structures, the first plurality of guide structures being positioned to interface with the second plurality of guide structures as each of the plurality of rolling elements roll through the second closed loop.
9. The rotary speed reducer of claim 1 wherein one of the first pair of races is coupled to one of the second pair of races so that they move in concert.
10. The rotary speed reducer of claim 1 wherein the first rolling element operable to roll between a first rotor and a first stator and the second rolling element operable to roll between a second rotor and a second stator, the first rotor being coupled to the second rotor.
11. A rotary speed reducer comprising: a first pair of races comprising a first pair of raceways forming a first closed loop about an axis; a second pair of races comprising a second pair of raceways forming a second closed loop about the axis and around the first closed loop; and a first plurality of rolling elements operable to roll over a first plurality of contact points on each of the first pair of raceways, and a second plurality of rolling elements operable to roll over a second plurality of contact points on each of the second pair of raceways, wherein each of the second pair of raceways has a substantially variable curvature, wherein the path length for any corresponding interval along the second plurality of contact points for each of the second pair of raceways are substantially the same.
12. A rotary speed reducer comprising: a first pair of races comprising a first pair of raceways forming a first closed loop about an axis; a second pair of races comprising a second pair of raceways forming a second closed loop radially about the axis and around the first closed loop; and a first plurality of rolling elements operable to roll over a first plurality of contact points on each of the first pair of raceways; and a second plurality of rolling elements operable to roll over a second plurality of contact points on each of the second pair of raceways, wherein each of the second pair of raceways has a substantially variable curvature, wherein the second plurality of rolling elements do not slide as they roll around the second closed loop.
13. A rotary speed reducer comprising: a first race comprising a first raceway around a first closed loop about an axis; a second pair of races comprising a second pair of raceways around a second pair of closed loops; and a plurality of rolling elements having a first rolling portion with a radius $R1$ and a second pair of rolling portions with a radius $R2$, the first rolling portion being operable to roll over a first plurality of contact points on the first raceway, the second pair of rolling portion each being operable to roll over a corresponding plurality of contact points on each of the second pair of raceways, wherein at least one of the first raceway or the second pair of raceways has a substantially variable curvature, the path length along the first raceway being substantially $R1/R2$.

times the path length along the second raceway, wherein $R1$ does not equal $R2$, wherein the plurality of rolling elements substantially rolls as it travels around the corresponding closed loop.
