

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409259
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Wyeth; Mark T. et al.

Fluid preparation and treatment devices methods and systems

Abstract

Methods, device, and systems for preparing peritoneal dialysis fluid and/or administering a peritoneal dialysis treatment are disclosed. In embodiments, peritoneal dialysis fluid is prepared at a point of use automatically using a daily sterile disposable fluid circuit and one or more long-term concentrate containers that are changed only after multiple days (e.g. weekly). The daily disposable may have concentrate containers that are initially empty and are filled from the long-term concentrate containers once per day at the beginning of a treatment.

Inventors: Wyeth; Mark T. (Andover, MA), Yantz; Gregory (Boxford, MA), de la Vega; Ciro A. (Amesbury, MA)

Applicant: NxStage Medical, Inc. (Lawrence, MA)

Family ID: 67683818

Assignee: NxStage Medical, Inc. (Lawrence, MA)

Appl. No.: 18/536637

Filed: December 12, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240115787 A1	Apr. 11, 2024

Related U.S. Application Data

continuation parent-doc US 16288725 20190228 US 11872337 child-doc US 18536637
us-provisional-application US 62676098 20180524
us-provisional-application US 62636404 20180228

Publication Classification

Int. Cl.: **A61M1/28** (20060101); **A61M1/14** (20060101); **A61M1/16** (20060101); **A61M1/26** (20060101); **C02F1/44** (20230101); **C02F103/02** (20060101)

U.S. Cl.:

CPC **A61M1/287** (20130101); **A61M1/1524** (20220501); **A61M1/154** (20220501); **A61M1/155** (20220501); **A61M1/156** (20220501); **A61M1/1562** (20220501); **A61M1/1565** (20220501); **A61M1/159** (20220501); **A61M1/1664** (20140204); **A61M1/1666** (20140204); **A61M1/1672** (20140204); **A61M1/1674** (20140204); **A61M1/1696** (20130101); **A61M1/267** (20140204); **A61M1/28** (20130101); **A61M1/288** (20140204); A61M2205/05 (20130101); A61M2205/12 (20130101); A61M2205/126 (20130101); A61M2205/127 (20130101); A61M2205/128 (20130101); A61M2205/15 (20130101); A61M2205/215 (20130101); A61M2205/3334 (20130101); A61M2205/3344 (20130101); A61M2205/3569 (20130101); A61M2205/702 (20130101); A61M2205/8212 (20130101); C02F1/444 (20130101); C02F2103/026 (20130101); C02F2201/005 (20130101); C02F2209/03 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2369070	12/1944	Nielsen	N/A	N/A
2575447	12/1950	Gossick	N/A	N/A
2874351	12/1958	John	N/A	N/A
3490591	12/1969	Jones et al.	N/A	N/A
3526834	12/1969	Brown	N/A	N/A
3753493	12/1972	Mellor	N/A	N/A
3786810	12/1973	Pannier et al.	N/A	N/A
3847809	12/1973	Kopf	N/A	N/A
3861388	12/1974	Vaughn	N/A	N/A
3871913	12/1974	Shaldon	N/A	N/A
3992301	12/1975	Shippey et al.	N/A	N/A
3994293	12/1975	Ferro	N/A	N/A
4138639	12/1978	Hutchins	N/A	N/A
4158034	12/1978	Riede et al.	N/A	N/A
4161264	12/1978	Malmgren et al.	N/A	N/A
4197848	12/1979	Garrett et al.	N/A	N/A
4209391	12/1979	Lipps et al.	N/A	N/A
4338190	12/1981	Kraus et al.	N/A	N/A
4361485	12/1981	Boonstra	N/A	N/A
4396382	12/1982	Goldhaber	N/A	N/A
4399030	12/1982	Hlavinka et al.	N/A	N/A
4412834	12/1982	Kulin et al.	N/A	N/A

4420752	12/1982	Davis et al.	N/A	N/A
4432759	12/1983	Gross et al.	N/A	N/A
4432765	12/1983	Oscarsson	N/A	N/A
4435171	12/1983	Goldberg et al.	N/A	N/A
4439179	12/1983	Lueders et al.	N/A	N/A
4439188	12/1983	Dennehey et al.	N/A	N/A
4440207	12/1983	Genatempo et al.	N/A	N/A
4447230	12/1983	Gula et al.	N/A	N/A
4479760	12/1983	Bilstad et al.	N/A	N/A
4489535	12/1983	Veltman	N/A	N/A
4493705	12/1984	Gordon et al.	N/A	N/A
4526572	12/1984	Donnan et al.	N/A	N/A
4553552	12/1984	Valdespino et al.	N/A	N/A
4559043	12/1984	Whitehouse et al.	N/A	N/A
4585436	12/1985	Davis et al.	N/A	N/A
4605895	12/1985	Park	N/A	N/A
4612170	12/1985	Luther et al.	N/A	N/A
4617115	12/1985	Vantard	N/A	N/A
4618343	12/1985	Polaschegg	N/A	N/A
4636204	12/1986	Christopherson et al.	N/A	N/A
4654026	12/1986	Underwood	N/A	N/A
4655742	12/1986	Vantard	N/A	N/A
4657529	12/1986	Prince et al.	N/A	N/A
4663006	12/1986	Yao et al.	N/A	N/A
4670007	12/1986	Wheeldon et al.	N/A	N/A
4673506	12/1986	Henne et al.	N/A	N/A
4695385	12/1986	Boag	N/A	N/A
4702829	12/1986	Polaschegg et al.	N/A	N/A
4747822	12/1987	Peabody	N/A	N/A
4747950	12/1987	Guinn	N/A	N/A
4752292	12/1987	Lopez et al.	N/A	N/A
4797191	12/1988	Metzner et al.	N/A	N/A
4823833	12/1988	Hogan et al.	N/A	N/A
4825168	12/1988	Ogawa et al.	N/A	N/A
4846950	12/1988	Yao et al.	N/A	N/A
4857199	12/1988	Cortial	N/A	N/A
4867739	12/1988	Kawano	N/A	N/A
4871353	12/1988	Thomsen	N/A	N/A
4876515	12/1988	Ball	N/A	N/A
4954782	12/1989	Ball	N/A	N/A
4966585	12/1989	Gangemi	N/A	N/A
4976685	12/1989	Block, Jr.	N/A	N/A
4981469	12/1990	Whitehouse et al.	N/A	N/A
4997570	12/1990	Polaschegg	N/A	N/A
5004535	12/1990	Bosko et al.	N/A	N/A
5061365	12/1990	Utterberg	N/A	N/A
5062774	12/1990	Kramer et al.	N/A	N/A
5071413	12/1990	Utterberg	N/A	N/A
5078699	12/1991	Haber et al.	N/A	N/A
5087245	12/1991	Doan	N/A	N/A

5139483	12/1991	Ryan	N/A	N/A
5139675	12/1991	Arnold et al.	N/A	N/A
5141493	12/1991	Jacobsen et al.	N/A	N/A
5203771	12/1992	Melker et al.	N/A	N/A
5209800	12/1992	Spencer et al.	N/A	N/A
5224932	12/1992	Lappas	N/A	N/A
5225783	12/1992	Suzuki et al.	N/A	N/A
5242392	12/1992	Vaughn	N/A	N/A
5256371	12/1992	Pippert	N/A	N/A
5268144	12/1992	Heilmann et al.	N/A	N/A
5326476	12/1993	Grogan et al.	N/A	N/A
5330425	12/1993	Utterberg	N/A	N/A
5336173	12/1993	Folden	N/A	N/A
5344392	12/1993	Senninger et al.	N/A	N/A
5344568	12/1993	Kitaevich et al.	N/A	N/A
5346472	12/1993	Keshaviah et al.	N/A	N/A
5360395	12/1993	Utterberg	N/A	N/A
5442969	12/1994	Troutner et al.	N/A	N/A
5484397	12/1995	Twardowski	N/A	N/A
5485083	12/1995	Pulice	N/A	N/A
5486286	12/1995	Peterson et al.	N/A	N/A
5490925	12/1995	Eigendorf	N/A	N/A
5522998	12/1995	Polaschegg	N/A	N/A
5567320	12/1995	Goux et al.	N/A	N/A
5570026	12/1995	Buffaloe, IV et al.	N/A	N/A
5589070	12/1995	Maltais et al.	N/A	N/A
5603902	12/1996	Maltais et al.	N/A	N/A
5628908	12/1996	Kamen et al.	N/A	N/A
5631552	12/1996	Ogawa et al.	N/A	N/A
5650071	12/1996	Brugger et al.	N/A	N/A
5651893	12/1996	Kenley et al.	N/A	N/A
5674390	12/1996	Matthews et al.	N/A	N/A
5725773	12/1997	Polaschegg	N/A	N/A
5800383	12/1997	Chandler et al.	N/A	N/A
5836933	12/1997	Buttitta et al.	N/A	N/A
5865764	12/1998	Moorhead	N/A	N/A
5895578	12/1998	Simard et al.	N/A	N/A
5900136	12/1998	Gotsu et al.	N/A	N/A
5925011	12/1998	Faict et al.	N/A	N/A
5932110	12/1998	Shah et al.	N/A	N/A
5938634	12/1998	Packard	N/A	N/A
5945449	12/1998	Purcell et al.	N/A	N/A
6036680	12/1999	Horne et al.	N/A	N/A
6110384	12/1999	Goux et al.	N/A	N/A
6129699	12/1999	Haight et al.	N/A	N/A
6136201	12/1999	Shah et al.	N/A	N/A
6139754	12/1999	Hartranft et al.	N/A	N/A
6156797	12/1999	Kubo et al.	N/A	N/A
6168578	12/2000	Diamond	N/A	N/A
6196991	12/2000	Keilman	N/A	N/A

6228047	12/2000	Dadson	N/A	N/A
6241943	12/2000	Wieslander et al.	N/A	N/A
6254567	12/2000	Treu et al.	N/A	N/A
6270673	12/2000	Belt et al.	N/A	N/A
6280634	12/2000	Shah et al.	N/A	N/A
6327895	12/2000	Jeppsson et al.	N/A	N/A
6391404	12/2001	Rosenbaum et al.	N/A	N/A
6409699	12/2001	Ash	N/A	N/A
6423029	12/2001	Elsberry	N/A	N/A
6460592	12/2001	Sano et al.	N/A	N/A
6463979	12/2001	Sano et al.	N/A	N/A
6471855	12/2001	Odak et al.	N/A	N/A
6488647	12/2001	Miura et al.	N/A	N/A
6489785	12/2001	McAllister	N/A	N/A
6491658	12/2001	Miura et al.	N/A	N/A
6492336	12/2001	Mahiout	N/A	N/A
6503062	12/2002	Gray et al.	N/A	N/A
6537976	12/2002	Gupta	N/A	N/A
6585682	12/2002	Haraldsson et al.	N/A	N/A
6591126	12/2002	Roeper et al.	N/A	N/A
6595948	12/2002	Suzuki et al.	N/A	N/A
6605214	12/2002	Taylor	N/A	N/A
6610206	12/2002	Callan et al.	N/A	N/A
6626862	12/2002	Duchon et al.	N/A	N/A
6645191	12/2002	Knerr et al.	N/A	N/A
6648906	12/2002	Lasheras et al.	N/A	N/A
6666842	12/2002	Sakai	N/A	N/A
6689275	12/2003	Gupta	N/A	N/A
6705372	12/2003	Sano et al.	N/A	N/A
6738052	12/2003	Manke et al.	N/A	N/A
6749580	12/2003	Work et al.	N/A	N/A
6758975	12/2003	Peabody et al.	N/A	N/A
6769231	12/2003	Danby	N/A	N/A
6803363	12/2003	Polaschegg	N/A	N/A
6808369	12/2003	Gray et al.	N/A	N/A
6814869	12/2003	Brandl et al.	N/A	N/A
6861033	12/2004	Mullins et al.	N/A	N/A
6877713	12/2004	Gray et al.	N/A	N/A
6887214	12/2004	Levin	N/A	N/A
6889713	12/2004	Navis	N/A	N/A
6911014	12/2004	Wentling et al.	N/A	N/A
6912917	12/2004	Brugger et al.	N/A	N/A
6929751	12/2004	Bowman et al.	N/A	N/A
6981977	12/2005	Herweck et al.	N/A	N/A
6986752	12/2005	McGuckin et al.	N/A	N/A
6995563	12/2005	Talutis	N/A	N/A
7013928	12/2005	Navis	N/A	N/A
7033539	12/2005	Krensky et al.	N/A	N/A
7053059	12/2005	Zieske et al.	N/A	N/A
7057400	12/2005	Gaignet	N/A	N/A

7067061	12/2005	Bosetto et al.	N/A	N/A
7083719	12/2005	Bowman et al.	N/A	N/A
7119305	12/2005	Sano et al.	N/A	N/A
7138088	12/2005	Wariar et al.	N/A	N/A
7175606	12/2006	Bowman, Jr. et al.	N/A	N/A
7214228	12/2006	Crabtree	N/A	N/A
7235589	12/2006	Hausheer	N/A	N/A
7243893	12/2006	Sobue et al.	N/A	N/A
7250619	12/2006	Taylor et al.	N/A	N/A
7320676	12/2007	Miesel	N/A	N/A
7354190	12/2007	Demers et al.	N/A	N/A
7410475	12/2007	Krensky et al.	N/A	N/A
7421316	12/2007	Gray et al.	N/A	N/A
7441108	12/2007	Fisher et al.	N/A	N/A
7459054	12/2007	Landherr et al.	N/A	N/A
7544301	12/2008	Shah et al.	N/A	N/A
7559483	12/2008	Hickle et al.	N/A	N/A
7559524	12/2008	Gray et al.	N/A	N/A
7559913	12/2008	Jeppsson et al.	N/A	N/A
7641753	12/2009	Gao et al.	N/A	N/A
7670491	12/2009	Callan et al.	N/A	N/A
7686279	12/2009	Nerbonne et al.	N/A	N/A
7758552	12/2009	Zoltan et al.	N/A	N/A
7763013	12/2009	Baldwin et al.	N/A	N/A
7803628	12/2009	Glocker	N/A	N/A
7837666	12/2009	Jensen et al.	N/A	N/A
7842002	12/2009	Mantle	N/A	N/A
7847564	12/2009	Rossi	N/A	N/A
7857805	12/2009	Raines	N/A	N/A
7862530	12/2010	Callan et al.	N/A	N/A
7867214	12/2010	Childers et al.	N/A	N/A
7883725	12/2010	Shah et al.	N/A	N/A
7892423	12/2010	Rohde et al.	N/A	N/A
7901376	12/2010	Steck et al.	N/A	N/A
7905853	12/2010	Chapman et al.	N/A	N/A
7905855	12/2010	Childers	N/A	N/A
7935074	12/2010	Plahey et al.	N/A	N/A
7955295	12/2010	Lee et al.	N/A	N/A
7988849	12/2010	Biewer et al.	N/A	N/A
7993050	12/2010	Demers et al.	N/A	N/A
8034017	12/2010	Petersen	N/A	N/A
8083709	12/2010	Childers et al.	N/A	N/A
8088094	12/2011	Hamada et al.	N/A	N/A
8096969	12/2011	Roberts et al.	N/A	N/A
8105487	12/2011	Fulkerson et al.	N/A	N/A
8147696	12/2011	Pandya	N/A	N/A
8178040	12/2011	Brauer	N/A	N/A
8202547	12/2011	Shah et al.	N/A	N/A
8222229	12/2011	Kiribayashi et al.	N/A	N/A
8246826	12/2011	Wilt et al.	N/A	N/A

8287724	12/2011	Slepicka et al.	N/A	N/A
8297954	12/2011	Moubayed	N/A	N/A
8298167	12/2011	Peters et al.	N/A	N/A
8298170	12/2011	Lundtveit et al.	N/A	N/A
8308128	12/2011	Mackal	N/A	N/A
8348904	12/2012	Petersen	N/A	N/A
8361009	12/2012	Lee et al.	N/A	N/A
8367731	12/2012	Wieslander et al.	N/A	N/A
8375797	12/2012	Beden et al.	N/A	N/A
8382447	12/2012	Wang et al.	N/A	N/A
8393690	12/2012	Grant et al.	N/A	N/A
8398590	12/2012	Sternberg et al.	N/A	N/A
8414686	12/2012	Gura et al.	N/A	N/A
8414768	12/2012	Shah et al.	N/A	N/A
8431086	12/2012	Lurvey et al.	N/A	N/A
8444593	12/2012	Hamada et al.	N/A	N/A
8449496	12/2012	Hamada et al.	N/A	N/A
8460544	12/2012	Völker	N/A	N/A
8474784	12/2012	Kashmirian et al.	N/A	N/A
8491184	12/2012	Kamen et al.	N/A	N/A
8500676	12/2012	Jansson et al.	N/A	N/A
8501009	12/2012	Peterson et al.	N/A	N/A
8506885	12/2012	Kotsos et al.	N/A	N/A
8516902	12/2012	Beavis et al.	N/A	N/A
8529496	12/2012	Britton et al.	N/A	N/A
8540886	12/2012	Hedmann et al.	N/A	N/A
8556225	12/2012	Gray	N/A	N/A
8560510	12/2012	Brueggerhoff et al.	N/A	N/A
8587516	12/2012	Kopychev et al.	N/A	N/A
8597229	12/2012	Pan	N/A	N/A
8600772	12/2012	Bacon	N/A	N/A
8613739	12/2012	Sobue	N/A	N/A
8641685	12/2013	Mansour et al.	N/A	N/A
8671996	12/2013	Weilhoefer et al.	N/A	N/A
8678224	12/2013	D'Ayot et al.	N/A	N/A
8685251	12/2013	Smejtek et al.	N/A	N/A
8698741	12/2013	Wang et al.	N/A	N/A
8708992	12/2013	Kobayashi et al.	N/A	N/A
8728056	12/2013	Colantonio et al.	N/A	N/A
8731726	12/2013	Gray et al.	N/A	N/A
8740864	12/2013	Hoang et al.	N/A	N/A
8741131	12/2013	Bedingfield et al.	N/A	N/A
8747370	12/2013	Feith et al.	N/A	N/A
8758626	12/2013	Wong	N/A	N/A
8764702	12/2013	Childers et al.	N/A	N/A
8774885	12/2013	Abreu	N/A	N/A
8777892	12/2013	Sandford et al.	N/A	N/A
8789558	12/2013	Volker	N/A	N/A
8801652	12/2013	Landherr et al.	N/A	N/A
8801677	12/2013	Wallin	N/A	N/A

8808595	12/2013	Babrowicz et al.	N/A	N/A
8813769	12/2013	Gastauer et al.	N/A	N/A
8815095	12/2013	Micheli	N/A	N/A
8828232	12/2013	Shah et al.	N/A	N/A
8834718	12/2013	Randall et al.	N/A	N/A
8834719	12/2013	Childers et al.	N/A	N/A
8838395	12/2013	Matsiev et al.	N/A	N/A
8840581	12/2013	McGill et al.	N/A	N/A
8858792	12/2013	Ding et al.	N/A	N/A
8869612	12/2013	Chen et al.	N/A	N/A
8870812	12/2013	Alberti et al.	N/A	N/A
8875748	12/2013	Beden et al.	N/A	N/A
8876753	12/2013	Roberts et al.	N/A	N/A
8882700	12/2013	Chapman et al.	N/A	N/A
8924458	12/2013	Levin et al.	N/A	N/A
8926550	12/2014	Plahey et al.	N/A	N/A
8926551	12/2014	Lo et al.	N/A	N/A
8930213	12/2014	Gotlib et al.	N/A	N/A
8945042	12/2014	Lee et al.	N/A	N/A
8961444	12/2014	Chapman et al.	N/A	N/A
8961466	12/2014	Steinbach	N/A	N/A
8980070	12/2014	Nishio et al.	N/A	N/A
8989906	12/2014	Gray et al.	N/A	N/A
8992454	12/2014	Anand	N/A	N/A
8992777	12/2014	Doyle	N/A	N/A
9004886	12/2014	Beck et al.	N/A	N/A
9014775	12/2014	Bennett et al.	N/A	N/A
9022969	12/2014	Helmore et al.	N/A	N/A
9044544	12/2014	Lo et al.	N/A	N/A
9060727	12/2014	Saikley et al.	N/A	N/A
9066968	12/2014	Ohta et al.	N/A	N/A
9067017	12/2014	Tan et al.	N/A	N/A
9069886	12/2014	Shimizu et al.	N/A	N/A
9108031	12/2014	Brandenburger et al.	N/A	N/A
9112245	12/2014	Yen	N/A	N/A
9132220	12/2014	Kugelman et al.	N/A	N/A
9138523	12/2014	Burnett et al.	N/A	N/A
9152918	12/2014	McNair	N/A	N/A
9153002	12/2014	Jones et al.	N/A	N/A
9162044	12/2014	Traversaz	N/A	N/A
9165112	12/2014	Doyle et al.	N/A	N/A
9180238	12/2014	Bedingfield et al.	N/A	N/A
9198830	12/2014	Kugelman et al.	N/A	N/A
9199070	12/2014	Wegener et al.	N/A	N/A
9216247	12/2014	Callan et al.	N/A	N/A
9217702	12/2014	Sullivan	N/A	N/A
9242035	12/2015	Karoor	N/A	N/A
9254356	12/2015	Shah et al.	N/A	N/A
9254358	12/2015	Volker	N/A	N/A
9274073	12/2015	Nier et al.	N/A	N/A

9284960	12/2015	Chappel et al.	N/A	N/A
9308309	12/2015	Hedmann et al.	N/A	N/A
9310232	12/2015	Heide et al.	N/A	N/A
9319110	12/2015	Kopychev et al.	N/A	N/A
9320680	12/2015	Schröder	N/A	N/A
9345871	12/2015	Guala	N/A	N/A
9358332	12/2015	McGill et al.	N/A	N/A
9381290	12/2015	Yu et al.	N/A	N/A
9393356	12/2015	Karoor et al.	N/A	N/A
9408958	12/2015	Wang et al.	N/A	N/A
9427518	12/2015	Brueckner	N/A	N/A
9433768	12/2015	Tekeste et al.	N/A	N/A
9440016	12/2015	Lin et al.	N/A	N/A
9440019	12/2015	Falkenhagen et al.	N/A	N/A
9470220	12/2015	Becker	N/A	N/A
9471754	12/2015	Mastalli et al.	N/A	N/A
9474841	12/2015	Volker	N/A	N/A
9495511	12/2015	Harrington et al.	N/A	N/A
9500188	12/2015	Ly et al.	N/A	N/A
9514131	12/2015	Bochenko et al.	N/A	N/A
9519969	12/2015	Kusens	N/A	N/A
9539387	12/2016	Fini et al.	N/A	N/A
9555232	12/2016	Davis et al.	N/A	N/A
9593679	12/2016	Gray et al.	N/A	N/A
9610518	12/2016	Kamen et al.	N/A	N/A
9616163	12/2016	Wong et al.	N/A	N/A
9629993	12/2016	Klewinghaus	N/A	N/A
9651511	12/2016	Howell et al.	N/A	N/A
9669145	12/2016	Günther et al.	N/A	N/A
9677555	12/2016	Kamen et al.	N/A	N/A
9687646	12/2016	Sobue et al.	N/A	N/A
9694125	12/2016	Plahey et al.	N/A	N/A
9694126	12/2016	Hedmann et al.	N/A	N/A
9700711	12/2016	Grant et al.	N/A	N/A
9724270	12/2016	Bonnal et al.	N/A	N/A
9724298	12/2016	Nilsson et al.	N/A	N/A
9724505	12/2016	Williams et al.	N/A	N/A
9757693	12/2016	Gillespie	N/A	N/A
10183106	12/2018	Okabe et al.	N/A	N/A
10973968	12/2020	Rohde	N/A	N/A
2001/0005487	12/2000	Kamibayashi et al.	N/A	N/A
2002/0045851	12/2001	Suzuki et al.	N/A	N/A
2002/0072718	12/2001	Brugger et al.	N/A	N/A
2002/0087126	12/2001	Quah	N/A	N/A
2002/0120227	12/2001	Childers et al.	N/A	N/A
2002/0123715	12/2001	Sorenson et al.	N/A	N/A
2002/0162778	12/2001	Peabody et al.	N/A	N/A
2003/0065284	12/2002	Briggs	N/A	N/A
2003/0086794	12/2002	Gray et al.	N/A	N/A
2003/0143352	12/2002	Yang et al.	N/A	N/A

2003/0153865	12/2002	Connell et al.	N/A	N/A
2003/0217976	12/2002	Bowman et al.	N/A	N/A
2003/0218623	12/2002	Krensky et al.	N/A	N/A
2004/0019312	12/2003	Childers et al.	N/A	N/A
2004/0031756	12/2003	Suzuki et al.	N/A	N/A
2004/0040620	12/2003	Brauer et al.	N/A	N/A
2004/0078024	12/2003	Peluso et al.	N/A	N/A
2004/0087890	12/2003	Sakai	N/A	N/A
2004/0099521	12/2003	Demers et al.	N/A	N/A
2004/0108223	12/2003	Jansson	N/A	N/A
2004/0111294	12/2003	McNally et al.	N/A	N/A
2004/0215129	12/2003	Edgson et al.	N/A	N/A
2004/0215336	12/2003	Udipi et al.	N/A	N/A
2004/0221643	12/2003	Ehwald et al.	N/A	N/A
2004/0254513	12/2003	Shang et al.	N/A	N/A
2005/0006296	12/2004	Sullivan et al.	N/A	N/A
2005/0020507	12/2004	Zieske et al.	N/A	N/A
2005/0082226	12/2004	Bene et al.	N/A	N/A
2005/0089994	12/2004	Neftel	N/A	N/A
2005/0094483	12/2004	Demers et al.	N/A	N/A
2005/0094485	12/2004	Demers et al.	N/A	N/A
2005/0095154	12/2004	Tracey et al.	N/A	N/A
2005/0126998	12/2004	Childers	N/A	N/A
2005/0131141	12/2004	Poss et al.	N/A	N/A
2005/0167363	12/2004	Taylor	N/A	N/A
2005/0173344	12/2004	Bowman et al.	N/A	N/A
2005/0202395	12/2004	Edrich et al.	N/A	N/A
2005/0209563	12/2004	Hopping et al.	N/A	N/A
2005/0211373	12/2004	Tomasetti et al.	N/A	N/A
2005/0224372	12/2004	Sasso et al.	N/A	N/A
2005/0244909	12/2004	Hamada et al.	N/A	N/A
2005/0283132	12/2004	Stanus et al.	N/A	N/A
2006/0005886	12/2005	Parrino et al.	N/A	N/A
2006/0015015	12/2005	Kawamoto et al.	N/A	N/A
2006/0161107	12/2005	Mantle	N/A	N/A
2006/0172954	12/2005	Jensen et al.	N/A	N/A
2006/0189923	12/2005	Neftel et al.	N/A	N/A
2006/0195064	12/2005	Plahey et al.	N/A	N/A
2007/0007208	12/2006	Brugger et al.	N/A	N/A
2007/0043317	12/2006	Sugawara	N/A	N/A
2007/0048161	12/2006	Moubayed	N/A	N/A
2007/0088314	12/2006	Gollier et al.	N/A	N/A
2007/0106197	12/2006	Lauman et al.	N/A	N/A
2007/0106247	12/2006	Burnett et al.	N/A	N/A
2007/0112297	12/2006	Plahey et al.	N/A	N/A
2007/0149913	12/2006	Busby et al.	N/A	N/A
2007/0179422	12/2006	Schnell et al.	N/A	N/A
2007/0194792	12/2006	Quackenbush et al.	N/A	N/A
2007/0213651	12/2006	Busby et al.	N/A	N/A
2007/0213654	12/2006	Lundtveit et al.	N/A	N/A

2007/0213665	12/2006	Curtin et al.	N/A	N/A
2007/0253463	12/2006	Perry et al.	N/A	N/A
2007/0276328	12/2006	Childers et al.	N/A	N/A
2007/0287966	12/2006	Keeley	N/A	N/A
2008/0015492	12/2007	Biesel	N/A	N/A
2008/0023135	12/2007	Ivansons et al.	N/A	N/A
2008/0027374	12/2007	Jensen et al.	N/A	N/A
2008/0031746	12/2007	Gray et al.	N/A	N/A
2008/0058712	12/2007	Plahey	N/A	N/A
2008/0065006	12/2007	Roger et al.	N/A	N/A
2008/0097283	12/2007	Plahey	N/A	N/A
2008/0101969	12/2007	Moubayed	N/A	N/A
2008/0112258	12/2007	Demers et al.	N/A	N/A
2008/0125693	12/2007	Gavin et al.	N/A	N/A
2008/0138223	12/2007	Lanigan et al.	N/A	N/A
2008/0161751	12/2007	Plahey et al.	N/A	N/A
2008/0183126	12/2007	Landherr et al.	N/A	N/A
2008/0183127	12/2007	Landherr et al.	N/A	N/A
2008/0200865	12/2007	Bedingfield	N/A	N/A
2008/0200866	12/2007	Prisco et al.	N/A	N/A
2008/0200867	12/2007	Bedingfield	N/A	N/A
2008/0200868	12/2007	Alberti et al.	N/A	N/A
2008/0200869	12/2007	Bedingfield	N/A	N/A
2008/0208195	12/2007	Shores et al.	N/A	N/A
2008/0216898	12/2007	Grant et al.	N/A	N/A
2008/0230450	12/2007	Burbank et al.	N/A	N/A
2008/0240929	12/2007	Kamen et al.	N/A	N/A
2008/0243211	12/2007	Cartwright et al.	N/A	N/A
2008/0253427	12/2007	Kamen et al.	N/A	N/A
2008/0253911	12/2007	Demers et al.	N/A	N/A
2008/0273996	12/2007	Gray et al.	N/A	N/A
2008/0275382	12/2007	Biesel et al.	N/A	N/A
2009/0007642	12/2008	Busby et al.	N/A	N/A
2009/0008306	12/2008	Cicchello et al.	N/A	N/A
2009/0009290	12/2008	Kneip et al.	N/A	N/A
2009/0012447	12/2008	Huitt et al.	N/A	N/A
2009/0012451	12/2008	Sobue et al.	N/A	N/A
2009/0012452	12/2008	Slepicka et al.	N/A	N/A
2009/0012453	12/2008	Childers et al.	N/A	N/A
2009/0012455	12/2008	Childers et al.	N/A	N/A
2009/0012458	12/2008	Childers et al.	N/A	N/A
2009/0012460	12/2008	Steck et al.	N/A	N/A
2009/0012464	12/2008	Martin et al.	N/A	N/A
2009/0024096	12/2008	Hai et al.	N/A	N/A
2009/0054873	12/2008	Landherr et al.	N/A	N/A
2009/0078592	12/2008	Jensen et al.	N/A	N/A
2009/0082758	12/2008	Gill et al.	N/A	N/A
2009/0095679	12/2008	Demers et al.	N/A	N/A
2009/0098215	12/2008	Riser et al.	N/A	N/A
2009/0101549	12/2008	Kamen et al.	N/A	N/A

2009/0112151	12/2008	Chapman et al.	N/A	N/A
2009/0143723	12/2008	Szpara et al.	N/A	N/A
2009/0149810	12/2008	Ring et al.	N/A	N/A
2009/0169872	12/2008	Krongauz et al.	N/A	N/A
2009/0173682	12/2008	Robinson et al.	N/A	N/A
2009/0177149	12/2008	Childers et al.	N/A	N/A
2009/0182263	12/2008	Burbank et al.	N/A	N/A
2009/0185920	12/2008	Lanigan et al.	N/A	N/A
2009/0196776	12/2008	Moubayed	N/A	N/A
2009/0198170	12/2008	Childers et al.	N/A	N/A
2009/0206023	12/2008	Rohde et al.	N/A	N/A
2009/0212178	12/2008	Westberg	N/A	N/A
2009/0213521	12/2008	Bedingfield	N/A	N/A
2009/0218290	12/2008	Poss et al.	N/A	N/A
2009/0222119	12/2008	Plahey et al.	N/A	N/A
2009/0223899	12/2008	Poss et al.	N/A	N/A
2009/0232908	12/2008	Zhou	N/A	N/A
2009/0264854	12/2008	Jensen et al.	N/A	N/A
2009/0275881	12/2008	Lo et al.	N/A	N/A
2009/0275883	12/2008	Chapman et al.	N/A	N/A
2009/0277276	12/2008	Evering et al.	N/A	N/A
2009/0294339	12/2008	Biewer et al.	N/A	N/A
2009/0295591	12/2008	Bedingfield	N/A	N/A
2009/0299272	12/2008	Hopping et al.	N/A	N/A
2009/0299273	12/2008	Lee et al.	N/A	N/A
2010/0004588	12/2009	Yeh et al.	N/A	N/A
2010/0004589	12/2009	Hedmann et al.	N/A	N/A
2010/0004590	12/2009	Hedmann et al.	N/A	N/A
2010/0005416	12/2009	Hedmann et al.	N/A	N/A
2010/0010423	12/2009	Yu et al.	N/A	N/A
2010/0010424	12/2009	Yu et al.	N/A	N/A
2010/0010425	12/2009	Yu et al.	N/A	N/A
2010/0010426	12/2009	Childers et al.	N/A	N/A
2010/0010427	12/2009	Yu et al.	N/A	N/A
2010/0010428	12/2009	Yu et al.	N/A	N/A
2010/0016802	12/2009	Tambourgi et al.	N/A	N/A
2010/0019686	12/2009	Gutierrez	N/A	N/A
2010/0028170	12/2009	Schneeberger et al.	N/A	N/A
2010/0028208	12/2009	Shekalim et al.	N/A	N/A
2010/0038322	12/2009	Hedmann et al.	N/A	N/A
2010/0049158	12/2009	Roger	N/A	N/A
2010/0051552	12/2009	Rohde et al.	N/A	N/A
2010/0063445	12/2009	Sternberg et al.	N/A	N/A
2010/0069817	12/2009	Falkvall et al.	N/A	N/A
2010/0078387	12/2009	Wong	N/A	N/A
2010/0084326	12/2009	Takesawa	N/A	N/A
2010/0087777	12/2009	Hopping et al.	N/A	N/A
2010/0096329	12/2009	Kotanko et al.	N/A	N/A
2010/0100027	12/2009	Schilthuizen et al.	N/A	N/A
2010/0100034	12/2009	Wich-Heiter	N/A	N/A

2010/0114012	12/2009	Sandford et al.	N/A	N/A
2010/0129247	12/2009	Lauer	N/A	N/A
2010/0130918	12/2009	Elahi	N/A	N/A
2010/0130919	12/2009	Elahi	N/A	N/A
2010/0133153	12/2009	Beden et al.	N/A	N/A
2010/0137782	12/2009	Jansson et al.	N/A	N/A
2010/0168652	12/2009	Landherr et al.	N/A	N/A
2010/0169513	12/2009	Levin	N/A	N/A
2010/0185132	12/2009	Han et al.	N/A	N/A
2010/0187476	12/2009	Yugari et al.	N/A	N/A
2010/0191180	12/2009	Childers et al.	N/A	N/A
2010/0191181	12/2009	Childers et al.	N/A	N/A
2010/0192686	12/2009	Kamen et al.	N/A	N/A
2010/0197817	12/2009	Bui et al.	N/A	N/A
2010/0204765	12/2009	Hall et al.	N/A	N/A
2010/0217178	12/2009	Lo et al.	N/A	N/A
2010/0217179	12/2009	Lo et al.	N/A	N/A
2010/0217180	12/2009	Akonur et al.	N/A	N/A
2010/0222735	12/2009	Plahey et al.	N/A	N/A
2010/0224492	12/2009	Ding et al.	N/A	N/A
2010/0229978	12/2009	Zhou	N/A	N/A
2010/0241062	12/2009	Morris et al.	N/A	N/A
2010/0252490	12/2009	Fulkerson et al.	N/A	N/A
2010/0252702	12/2009	Spang et al.	N/A	N/A
2010/0258690	12/2009	Kleitsch et al.	N/A	N/A
2010/0296953	12/2009	Gray	N/A	N/A
2010/0308243	12/2009	Bedingfield	N/A	N/A
2010/0312174	12/2009	Hoffman	N/A	N/A
2010/0314314	12/2009	Ding et al.	N/A	N/A
2010/0326916	12/2009	Wrazel et al.	N/A	N/A
2010/0331768	12/2009	Hedmann et al.	N/A	N/A
2011/0000902	12/2010	Hedmann et al.	N/A	N/A
2011/0004152	12/2010	Brady et al.	N/A	N/A
2011/0010101	12/2010	Lo et al.	N/A	N/A
2011/0015610	12/2010	Plahey et al.	N/A	N/A
2011/0017665	12/2010	Updyke et al.	N/A	N/A
2011/0034866	12/2010	Zhang et al.	N/A	N/A
2011/0038755	12/2010	Pesci et al.	N/A	N/A
2011/0040242	12/2010	Fallon et al.	N/A	N/A
2011/0040243	12/2010	Busby et al.	N/A	N/A
2011/0040244	12/2010	Busby et al.	N/A	N/A
2011/0046533	12/2010	Stefani et al.	N/A	N/A
2011/0054397	12/2010	Schneeberger	N/A	N/A
2011/0064608	12/2010	Lee et al.	N/A	N/A
2011/0085923	12/2010	Gray et al.	N/A	N/A
2011/0092893	12/2010	Demers et al.	N/A	N/A
2011/0092895	12/2010	Yardimci et al.	N/A	N/A
2011/0093294	12/2010	Elahi et al.	N/A	N/A
2011/0098635	12/2010	Helmore et al.	N/A	N/A
2011/0105979	12/2010	Schlaeper et al.	N/A	N/A

2011/0105981	12/2010	Wagner et al.	N/A	N/A
2011/0114559	12/2010	Fislage et al.	N/A	N/A
2011/0131058	12/2010	McNally et al.	N/A	N/A
2011/0132838	12/2010	Curtis et al.	N/A	N/A
2011/0137236	12/2010	Prisco et al.	N/A	N/A
2011/0137237	12/2010	Prisco et al.	N/A	N/A
2011/0138936	12/2010	Collins et al.	N/A	N/A
2011/0141116	12/2010	Dalesch et al.	N/A	N/A
2011/0144557	12/2010	Childers et al.	N/A	N/A
2011/0144569	12/2010	Britton et al.	N/A	N/A
2011/0158823	12/2010	Wang et al.	N/A	N/A
2011/0160649	12/2010	Pan	N/A	N/A
2011/0163033	12/2010	Chapman et al.	N/A	N/A
2011/0166507	12/2010	Childers et al.	N/A	N/A
2011/0171713	12/2010	Bluchel et al.	N/A	N/A
2011/0184339	12/2010	Tan	N/A	N/A
2011/0184340	12/2010	Tan et al.	N/A	N/A
2011/0186517	12/2010	Hedmann et al.	N/A	N/A
2011/0189048	12/2010	Curtis et al.	N/A	N/A
2011/0190691	12/2010	Cazzini	N/A	N/A
2011/0192796	12/2010	Smejtek et al.	N/A	N/A
2011/0196289	12/2010	Plahey et al.	N/A	N/A
2011/0198350	12/2010	Meisberger et al.	N/A	N/A
2011/0218486	12/2010	Huitt et al.	N/A	N/A
2011/0224603	12/2010	Richter	N/A	N/A
2011/0230822	12/2010	Lee et al.	N/A	N/A
2011/0249916	12/2010	Herrenbauer et al.	N/A	N/A
2011/0257124	12/2010	Fenn et al.	N/A	N/A
2011/0262555	12/2010	Riser et al.	N/A	N/A
2011/0264042	12/2010	Shang et al.	N/A	N/A
2011/0266221	12/2010	Ware et al.	N/A	N/A
2011/0275984	12/2010	Biewer et al.	N/A	N/A
2011/0284377	12/2010	Rohde	N/A	N/A
2011/0286167	12/2010	Winkler	N/A	N/A
2011/0288480	12/2010	Bedingfield et al.	N/A	N/A
2011/0300231	12/2010	Peterson et al.	N/A	N/A
2011/0309019	12/2010	Ahrens	N/A	N/A
2012/0001762	12/2011	Turner et al.	N/A	N/A
2012/0022440	12/2011	Childers et al.	N/A	N/A
2012/0029325	12/2011	Neftel	N/A	N/A
2012/0029937	12/2011	Neftel et al.	N/A	N/A
2012/0030933	12/2011	Lanigan et al.	N/A	N/A
2012/0031826	12/2011	Childers et al.	N/A	N/A
2012/0035533	12/2011	Britton et al.	N/A	N/A
2012/0058328	12/2011	Tourvieille et al.	N/A	N/A
2012/0065581	12/2011	Childers et al.	N/A	N/A
2012/0067805	12/2011	Childers et al.	N/A	N/A
2012/0071815	12/2011	Childers et al.	N/A	N/A
2012/0071816	12/2011	Busby et al.	N/A	N/A
2012/0074060	12/2011	Lass	N/A	N/A

2012/0078168	12/2011	Veneroni et al.	N/A	N/A
2012/0082576	12/2011	Beck et al.	N/A	N/A
2012/0089085	12/2011	Childers et al.	N/A	N/A
2012/0095392	12/2011	Jensen et al.	N/A	N/A
2012/0105850	12/2011	Slepicka	N/A	N/A
2012/0116294	12/2011	Boenig et al.	N/A	N/A
2012/0132574	12/2011	Ware et al.	N/A	N/A
2012/0145615	12/2011	Rohde et al.	N/A	N/A
2012/0150102	12/2011	Childers et al.	N/A	N/A
2012/0179133	12/2011	Bedingfield et al.	N/A	N/A
2012/0185267	12/2011	Kamen et al.	N/A	N/A
2012/0185619	12/2011	Levin	N/A	N/A
2012/0199205	12/2011	Eyrard et al.	N/A	N/A
2012/0205306	12/2011	Reich et al.	N/A	N/A
2012/0209169	12/2011	Morris et al.	N/A	N/A
2012/0211422	12/2011	Thys	N/A	N/A
2012/0212434	12/2011	Bluemler et al.	N/A	N/A
2012/0212455	12/2011	Kloeffel	N/A	N/A
2012/0215151	12/2011	Han et al.	N/A	N/A
2012/0215159	12/2011	Childers et al.	N/A	N/A
2012/0226237	12/2011	Russo	N/A	N/A
2012/0230844	12/2011	Farrell et al.	N/A	N/A
2012/0232469	12/2011	Medina	N/A	N/A
2012/0238525	12/2011	Leypoldt et al.	N/A	N/A
2012/0241367	12/2011	Childers et al.	N/A	N/A
2012/0248017	12/2011	Beiriger et al.	N/A	N/A
2012/0259275	12/2011	Jensen et al.	N/A	N/A
2012/0265145	12/2011	Mefti et al.	N/A	N/A
2012/0271226	12/2011	Farrell et al.	N/A	N/A
2012/0271273	12/2011	Childers et al.	N/A	N/A
2012/0273354	12/2011	Orhan et al.	N/A	N/A
2012/0283629	12/2011	Childers et al.	N/A	N/A
2012/0310150	12/2011	Brandl et al.	N/A	N/A
2012/0318740	12/2011	Ekdahl et al.	N/A	N/A
2013/0006171	12/2012	Griessmann et al.	N/A	N/A
2013/0020237	12/2012	Wilt et al.	N/A	N/A
2013/0030356	12/2012	Ding et al.	N/A	N/A
2013/0030404	12/2012	Gerlach et al.	N/A	N/A
2013/0037142	12/2012	Farrell	N/A	N/A
2013/0037461	12/2012	Biewer et al.	N/A	N/A
2013/0037465	12/2012	Heyes et al.	N/A	N/A
2013/0056419	12/2012	Curtis	N/A	N/A
2013/0072895	12/2012	Kreischer et al.	N/A	N/A
2013/0075309	12/2012	West et al.	N/A	N/A
2013/0079705	12/2012	Cazzini	N/A	N/A
2013/0079706	12/2012	Childers et al.	N/A	N/A
2013/0085437	12/2012	Deshpande	N/A	N/A
2013/0085451	12/2012	Sheu	N/A	N/A
2013/0106609	12/2012	Singh et al.	N/A	N/A
2013/0126430	12/2012	Kenley et al.	N/A	N/A

2013/0131581	12/2012	Lundtveit et al.	N/A	N/A
2013/0131583	12/2012	Chapman et al.	N/A	N/A
2013/0138037	12/2012	Lee et al.	N/A	N/A
2013/0150781	12/2012	Busby et al.	N/A	N/A
2013/0153048	12/2012	Schwalm	N/A	N/A
2013/0158469	12/2012	Hopping et al.	N/A	N/A
2013/0165848	12/2012	Sebesta et al.	N/A	N/A
2013/0167052	12/2012	Niesslein et al.	N/A	N/A
2013/0172806	12/2012	Griessmann et al.	N/A	N/A
2013/0177455	12/2012	Kamen et al.	N/A	N/A
2013/0180905	12/2012	Wong	N/A	N/A
2013/0186759	12/2012	Lin et al.	N/A	N/A
2013/0190681	12/2012	Jansson et al.	N/A	N/A
2013/0193041	12/2012	Rohde	N/A	N/A
2013/0195792	12/2012	Chan et al.	N/A	N/A
2013/0204173	12/2012	Kelly et al.	N/A	N/A
2013/0205873	12/2012	Wagner et al.	N/A	N/A
2013/0211322	12/2012	Degen et al.	N/A	N/A
2013/0245530	12/2012	Brandl et al.	N/A	N/A
2013/0245531	12/2012	Brandl et al.	N/A	N/A
2013/0248448	12/2012	Shah et al.	N/A	N/A
2013/0248449	12/2012	Kelly et al.	N/A	N/A
2013/0263650	12/2012	Nier et al.	N/A	N/A
2013/0272902	12/2012	Chappel	N/A	N/A
2013/0277306	12/2012	Chapman et al.	N/A	N/A
2013/0310726	12/2012	Miller et al.	N/A	N/A
2013/0310735	12/2012	Yu et al.	N/A	N/A
2013/0310736	12/2012	Hedmann et al.	N/A	N/A
2013/0313191	12/2012	Wolf et al.	N/A	N/A
2013/0317795	12/2012	Akonur et al.	N/A	N/A
2013/0324915	12/2012	Britton et al.	N/A	N/A
2013/0330208	12/2012	Ly et al.	N/A	N/A
2013/0331774	12/2012	Farrell et al.	N/A	N/A
2013/0331775	12/2012	Britton et al.	N/A	N/A
2013/0334138	12/2012	Cicchello et al.	N/A	N/A
2013/0338102	12/2012	Martis et al.	N/A	N/A
2013/0345621	12/2012	Cicchello et al.	N/A	N/A
2013/0346099	12/2012	Yu et al.	N/A	N/A
2013/0346102	12/2012	Yu et al.	N/A	N/A
2014/0010691	12/2013	Lanigan et al.	N/A	N/A
2014/0018272	12/2013	Thoea et al.	N/A	N/A
2014/0018727	12/2013	Burbank et al.	N/A	N/A
2014/0021115	12/2013	Ellegaard	N/A	N/A
2014/0027380	12/2013	Childers et al.	N/A	N/A
2014/0031631	12/2013	Hall et al.	N/A	N/A
2014/0046150	12/2013	Gagel et al.	N/A	N/A
2014/0046248	12/2013	Fini et al.	N/A	N/A
2014/0052044	12/2013	Crnkovich et al.	N/A	N/A
2014/0074018	12/2013	Childers et al.	N/A	N/A
2014/0098359	12/2013	Gross et al.	N/A	N/A

2014/0129250	12/2013	Daniel et al.	N/A	N/A
2014/0135878	12/2013	Burnett et al.	N/A	N/A
2014/0148409	12/2013	Ohta et al.	N/A	N/A
2014/0188040	12/2013	Busby et al.	N/A	N/A
2014/0207055	12/2013	Junod et al.	N/A	N/A
2014/0216994	12/2013	Ki	N/A	N/A
2014/0217029	12/2013	Meyer et al.	N/A	N/A
2014/0217030	12/2013	Meyer et al.	N/A	N/A
2014/0249683	12/2013	Gray et al.	N/A	N/A
2014/0263063	12/2013	Jones et al.	N/A	N/A
2014/0288947	12/2013	Simpson et al.	N/A	N/A
2014/0291218	12/2013	Bluchel et al.	N/A	N/A
2014/0299545	12/2013	Wrazel et al.	N/A	N/A
2014/0316332	12/2013	Lo et al.	N/A	N/A
2014/0360594	12/2013	Lee et al.	N/A	N/A
2015/0005699	12/2014	Burbank et al.	N/A	N/A
2015/0014249	12/2014	Alberti et al.	N/A	N/A
2015/0051536	12/2014	Mendels et al.	N/A	N/A
2015/0088053	12/2014	Lundtveit et al.	N/A	N/A
2015/0093450	12/2014	Riser et al.	N/A	N/A
2015/0129055	12/2014	Byler	N/A	N/A
2015/0133854	12/2014	Zhu et al.	N/A	N/A
2015/0159643	12/2014	Koob	N/A	N/A
2015/0196698	12/2014	Grant et al.	N/A	N/A
2015/0197431	12/2014	Shiki	N/A	N/A
2015/0204807	12/2014	Kamen et al.	N/A	N/A
2015/0209500	12/2014	Lin et al.	N/A	N/A
2015/0231571	12/2014	Volker	N/A	N/A
2015/0233367	12/2014	Shimogata et al.	N/A	N/A
2015/0273471	12/2014	Manzella et al.	N/A	N/A
2015/0276742	12/2014	Henrie	N/A	N/A
2015/0335808	12/2014	White et al.	N/A	N/A
2015/0359956	12/2014	Gray et al.	N/A	N/A
2016/0030654	12/2015	Singh et al.	N/A	N/A
2016/0051949	12/2015	Jansson et al.	N/A	N/A
2016/0097382	12/2015	Kamen et al.	N/A	N/A
2016/0106904	12/2015	Cicchello et al.	N/A	N/A
2016/0153444	12/2015	Chappel et al.	N/A	N/A
2016/0193399	12/2015	Wallace et al.	N/A	N/A
2016/0206804	12/2015	Holmer et al.	N/A	N/A
2016/0239637	12/2015	Miller et al.	N/A	N/A
2016/0245277	12/2015	Lanigan et al.	N/A	N/A
2016/0271312	12/2015	Lance et al.	N/A	N/A
2016/0310653	12/2015	Wang et al.	N/A	N/A
2016/0319954	12/2015	Smith	N/A	N/A
2016/0346451	12/2015	Stonger et al.	N/A	N/A
2016/0362234	12/2015	Peret et al.	N/A	N/A
2016/0367794	12/2015	Bedingfield	N/A	N/A
2017/0043079	12/2016	Jensen et al.	N/A	N/A
2017/0112992	12/2016	Plahey et al.	N/A	N/A

2017/0157310	12/2016	Scarpaci et al.	N/A	N/A
2017/0157311	12/2016	Egley	N/A	N/A
2017/0232175	12/2016	Burbank et al.	N/A	N/A
2017/0281846	12/2016	Manda et al.	N/A	N/A
2017/0319768	12/2016	Szpara et al.	N/A	N/A
2017/0319769	12/2016	Wieslander et al.	N/A	N/A
2017/0319770	12/2016	Fitzgerald et al.	N/A	N/A
2017/0333609	12/2016	O'Brien et al.	N/A	N/A
2018/0021501	12/2017	Gerber et al.	N/A	N/A
2018/0043079	12/2017	Gerber et al.	N/A	N/A
2018/0066648	12/2017	Kamen et al.	N/A	N/A
2018/0078692	12/2017	Cicchello et al.	N/A	N/A
2018/0093031	12/2017	Crawford et al.	N/A	N/A
2018/0106246	12/2017	Kamen et al.	N/A	N/A
2018/0128259	12/2017	Kamen et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2544144	12/2011	CA	N/A
2791816	12/2012	CA	N/A
2950325	12/2014	CA	N/A
2832661	12/2015	CA	N/A
201150709	12/2007	CN	N/A
201710718	12/2010	CN	N/A
201806987	12/2010	CN	N/A
101901000	12/2010	CN	N/A
102258942	12/2010	CN	N/A
202116617	12/2011	CN	N/A
102363054	12/2011	CN	N/A
202355628	12/2011	CN	N/A
202379834	12/2011	CN	N/A
202478260	12/2011	CN	N/A
202505852	12/2011	CN	N/A
202542986	12/2011	CN	N/A
102989047	12/2012	CN	N/A
202822485	12/2012	CN	N/A
204723486	12/2014	CN	N/A
105013031	12/2014	CN	N/A
204824277	12/2014	CN	N/A
2838414	12/1979	DE	N/A
4308586	12/1993	DE	N/A
19546027	12/1996	DE	N/A
29918801	12/1999	DE	N/A
69725104	12/2003	DE	N/A
102007020573	12/2007	DE	N/A
102007053752	12/2008	DE	N/A
102008045422	12/2009	DE	N/A
102009037917	12/2010	DE	N/A
102010009816	12/2010	DE	N/A
102010033241	12/2011	DE	N/A

102010053903	12/2011	DE	N/A
102011103325	12/2011	DE	N/A
102012004673	12/2012	DE	N/A
102012007412	12/2012	DE	N/A
102013103223	12/2013	DE	N/A
102013013414	12/2014	DE	N/A
102013013415	12/2014	DE	N/A
102013016204	12/2014	DE	N/A
102013018444	12/2014	DE	N/A
102014201714	12/2014	DE	N/A
102014004476	12/2014	DE	N/A
102014013152	12/2015	DE	N/A
102015010418	12/2016	DE	N/A
100682	12/1983	EP	N/A
0104460	12/1983	EP	N/A
0112104	12/1983	EP	N/A
049673	12/1984	EP	N/A
0256640	12/1987	EP	N/A
0265352	12/1987	EP	N/A
0090093	12/1987	EP	N/A
0367252	12/1989	EP	N/A
0442310	12/1990	EP	N/A
0611227	12/1993	EP	N/A
0711569	12/1995	EP	N/A
0763367	12/1996	EP	N/A
0778033	12/1996	EP	N/A
0813880	12/1996	EP	N/A
1187642	12/2001	EP	N/A
1314442	12/2002	EP	N/A
0846470	12/2002	EP	N/A
1346749	12/2002	EP	N/A
1048316	12/2002	EP	N/A
0971674	12/2002	EP	N/A
0914093	12/2003	EP	N/A
1438981	12/2003	EP	N/A
1438982	12/2003	EP	N/A
0970699	12/2004	EP	N/A
0994739	12/2004	EP	N/A
0958832	12/2005	EP	N/A
1648536	12/2005	EP	N/A
1066068	12/2005	EP	N/A
1677900	12/2005	EP	N/A
1351726	12/2006	EP	N/A
1382359	12/2006	EP	N/A
1110564	12/2006	EP	N/A
1236685	12/2006	EP	N/A
1867359	12/2006	EP	N/A
1938849	12/2007	EP	N/A
1191960	12/2007	EP	N/A
1582227	12/2007	EP	N/A

1218039	12/2008	EP	N/A
1641473	12/2009	EP	N/A
1357958	12/2009	EP	N/A
2289577	12/2010	EP	N/A
1432462	12/2010	EP	N/A
2350897	12/2010	EP	N/A
2402047	12/2011	EP	N/A
1509231	12/2011	EP	N/A
1465687	12/2011	EP	N/A
2446910	12/2011	EP	N/A
1195171	12/2011	EP	N/A
2503150	12/2011	EP	N/A
2510958	12/2011	EP	N/A
2517742	12/2011	EP	N/A
1735028	12/2012	EP	N/A
2656785	12/2012	EP	N/A
2689790	12/2013	EP	N/A
2712648	12/2014	EP	N/A
1878430	12/2015	EP	N/A
2114487	12/2015	EP	N/A
2131891	12/2015	EP	N/A
2173433	12/2015	EP	N/A
2594340	12/1986	FR	N/A
2021418	12/1978	GB	N/A
2312055	12/1999	GB	N/A
S59166156	12/1983	JP	N/A
60155952	12/1984	JP	N/A
S61008057	12/1985	JP	N/A
H05502614	12/1992	JP	N/A
2001511400	12/2000	JP	N/A
2002539896	12/2001	JP	N/A
2002355305	12/2001	JP	N/A
2003024435	12/2002	JP	N/A
2003509126	12/2002	JP	N/A
2003205031	12/2002	JP	N/A
2004518462	12/2003	JP	N/A
2006181386	12/2005	JP	N/A
2005533574	12/2005	JP	N/A
2006218037	12/2005	JP	N/A
2008119509	12/2007	JP	N/A
03150035	12/2008	JP	N/A
2009131573	12/2008	JP	N/A
2009139091	12/2008	JP	N/A
2009142436	12/2008	JP	N/A
2009533092	12/2008	JP	N/A
2009539522	12/2008	JP	N/A
2009279110	12/2008	JP	N/A
2009279532	12/2008	JP	N/A
2010502405	12/2009	JP	N/A
2010042312	12/2009	JP	N/A

2010088759	12/2009	JP	N/A
2010099631	12/2009	JP	N/A
2010131495	12/2009	JP	N/A
2010175285	12/2009	JP	N/A
2010214132	12/2009	JP	N/A
2010238013	12/2009	JP	N/A
2010532217	12/2009	JP	N/A
2010279423	12/2009	JP	N/A
2011056395	12/2010	JP	N/A
2011067535	12/2010	JP	N/A
2011120713	12/2010	JP	N/A
2011131209	12/2010	JP	N/A
2011188996	12/2010	JP	N/A
2011189190	12/2010	JP	N/A
2011207867	12/2010	JP	N/A
2011217965	12/2010	JP	N/A
2011241174	12/2010	JP	N/A
2012011260	12/2011	JP	N/A
2012071287	12/2011	JP	N/A
2012075572	12/2011	JP	N/A
2012075573	12/2011	JP	N/A
2012075574	12/2011	JP	N/A
2012075575	12/2011	JP	N/A
2012210382	12/2011	JP	N/A
2012223248	12/2011	JP	N/A
2012228285	12/2011	JP	N/A
2013006128	12/2012	JP	N/A
2013048894	12/2012	JP	N/A
2013048895	12/2012	JP	N/A
2013202231	12/2012	JP	N/A
2014014645	12/2013	JP	N/A
2014519345	12/2013	JP	N/A
2014184380	12/2013	JP	N/A
2014184384	12/2013	JP	N/A
2014184410	12/2013	JP	N/A
2014184411	12/2013	JP	N/A
2015517834	12/2014	JP	N/A
2017000802	12/2016	JP	N/A
2017006538	12/2016	JP	N/A
6080937	12/2016	JP	N/A
2018027256	12/2017	JP	N/A
2018050751	12/2017	JP	N/A
20120118906	12/2011	KR	N/A
M411244	12/2010	TW	N/A
1983002060	12/1982	WO	N/A
1984000137	12/1983	WO	N/A
1984000340	12/1983	WO	N/A
1992003202	12/1991	WO	N/A
1994020154	12/1993	WO	N/A
1996025214	12/1995	WO	N/A

1997007837	12/1996	WO	N/A
1998032480	12/1997	WO	N/A
1999006082	12/1998	WO	N/A
2000057833	12/1999	WO	N/A
2000057935	12/1999	WO	N/A
0119413	12/2000	WO	N/A
2001032237	12/2000	WO	N/A
2001058509	12/2000	WO	N/A
0232476	12/2001	WO	N/A
2002066099	12/2001	WO	N/A
2004006992	12/2003	WO	N/A
2004009156	12/2003	WO	N/A
2004043566	12/2003	WO	N/A
2005009511	12/2004	WO	N/A
2005042139	12/2004	WO	N/A
2005089832	12/2004	WO	N/A
2007061368	12/2006	WO	N/A
2007091217	12/2006	WO	N/A
2007103411	12/2006	WO	N/A
2007118235	12/2006	WO	N/A
2007144427	12/2006	WO	N/A
2007148443	12/2006	WO	N/A
2008086619	12/2007	WO	N/A
2008106440	12/2007	WO	N/A
2008154435	12/2007	WO	N/A
2009005900	12/2008	WO	N/A
2009094182	12/2008	WO	N/A
2009094183	12/2008	WO	N/A
2009094186	12/2008	WO	N/A
2009127683	12/2008	WO	N/A
2009134881	12/2008	WO	N/A
2010002830	12/2009	WO	N/A
2010009867	12/2009	WO	N/A
2010020380	12/2009	WO	N/A
2010024963	12/2009	WO	N/A
2010031424	12/2009	WO	N/A
2010059959	12/2009	WO	N/A
2010121751	12/2009	WO	N/A
2010143693	12/2009	WO	N/A
2011017215	12/2010	WO	N/A
2011052348	12/2010	WO	N/A
2011065222	12/2010	WO	N/A
2011091998	12/2010	WO	N/A
2011113615	12/2010	WO	N/A
2011132165	12/2010	WO	N/A
2012049261	12/2011	WO	N/A
2012087798	12/2011	WO	N/A
2012095829	12/2011	WO	N/A
2012129501	12/2011	WO	N/A
2012148781	12/2011	WO	N/A

2012163537	12/2011	WO	N/A
2012172818	12/2011	WO	N/A
2012176135	12/2011	WO	N/A
2013000569	12/2012	WO	N/A
2013012744	12/2012	WO	N/A
2013019179	12/2012	WO	N/A
2013019994	12/2012	WO	N/A
2013040420	12/2012	WO	N/A
2013051927	12/2012	WO	N/A
2013057109	12/2012	WO	N/A
2013110919	12/2012	WO	N/A
2013114063	12/2012	WO	N/A
2013121162	12/2012	WO	N/A
2013135386	12/2012	WO	N/A
2013135388	12/2012	WO	N/A
2013159935	12/2012	WO	N/A
2013163949	12/2012	WO	N/A
2013185080	12/2012	WO	N/A
2013191344	12/2012	WO	N/A
2014009111	12/2013	WO	N/A
2014053858	12/2013	WO	N/A
2014081367	12/2013	WO	N/A
2014106010	12/2013	WO	N/A
2014124186	12/2013	WO	N/A
2014155120	12/2013	WO	N/A
2014162489	12/2013	WO	N/A
2015050752	12/2014	WO	N/A
2015177606	12/2014	WO	N/A
2015188154	12/2014	WO	N/A
2016049542	12/2015	WO	N/A
2016059634	12/2015	WO	N/A
2016049542	12/2015	WO	N/A
2016080883	12/2015	WO	N/A
2016088072	12/2015	WO	N/A
2016091366	12/2015	WO	N/A
2016095026	12/2015	WO	N/A
2016193930	12/2015	WO	N/A
2016206949	12/2015	WO	N/A
2017193065	12/2016	WO	N/A
2018041760	12/2017	WO	N/A
2018115028	12/2017	WO	N/A

OTHER PUBLICATIONS

Agar, "An Obituary for Baxter's Viviva Home HD Machine," Home Dialysis Central, 2016, pp. 1-11, Home Dialysis Central, Madison, Wisconsin. cited by applicant

Agar, "Technology: What's Coming," Nocturnal Haemodialysis Program, Barwon Health, 2012, pp. 1-8, www.nocturnaldialysis.org/technology_whats_coming.html. cited by applicant

Communication under Rule 71(3) EPC dated Apr. 23, 2020, issued in EP 19 166 992.8. cited by applicant

English language abstract for Swedish application publication No. SE 198300739 A, published

Aug. 13, 1983. cited by applicant
Examination Report for United Kingdom Patent Application No. 1316544.4 dated Nov. 1, 2017. cited by applicant
Extended European Search Report dated Apr. 2, 2019 for European Patent Application No. 18215332.0. cited by applicant
Extended European Search Report dated Feb. 17, 2021 for European Patent Application No. 18821268.2. cited by applicant
Extended European Search Report dated Oct. 18, 2021, issued in European Application No. 19760761.7. cited by applicant
Extended European Search Report dated Oct. 22, 2019 for European Patent Application No. 19167042.1. cited by applicant
Extended European Search Report for European Application No. 17170146 dated Jul. 25, 2017. cited by applicant
Extended European Search Report for European Application No. 17170151.9 dated Aug. 22, 2017. cited by applicant
Extended European Search Report for European Patent Application No. 12760085.6 issued Sep. 25, 2015. cited by applicant
Extended European Search Report for European Patent Application No. 12871735.2 issued Oct. 15, 2015. cited by applicant
Extended European Search Report for European Patent Application No. 19166992.8 dated Aug. 2, 2019. cited by applicant
Extended European Search Report issued in EP Application 19173274.2 and mailed Jul. 29, 2019. cited by applicant
Fassbinder, "Experience with the Genius hemodialysis system," *Kidney Blood Press Res.*, 2003, vol. 26(2), pp. 96-99 (Abstract only), Karger, Basel, Switzerland. cited by applicant
Heroux, "Aksys—Dialysis Technologists," *Dialysis Technologists*, 2005, pp. 1-5, <https://www.tapataalk.com/groups/dialysistechnologists39151/aksys-t607.html>. cited by applicant
International Search Report and Written Opinion dated Oct. 24, 2018 issued in International Patent Application No. PCT/US2018/039188. cited by applicant
International Search Report and Written Opinion dated Sep. 6, 2019 and issued in International Application No. PCT/US2019/019967. cited by applicant
International Search Report and Written Opinion for International Application No. PCT/US2012/30350 dated Sep. 13, 2012. cited by applicant
International Search Report and Written Opinion for International Application No. PCT/US2012/56781 dated Apr. 4, 2013. cited by applicant
Kjellstrand et al., "The Aksys personal hemodialysis system," *Seminars in Dialysis*, 2004, vol. 17(2), Abstract only, Wiley, Hoboken, New Jersey. cited by applicant
Notice of Reasons for Refusal dated Nov. 15, 2018 for Japanese Patent Application No. 2018-071806. cited by applicant
Office Action (Communication Pursuant to Article 94(3) EPC) dated Aug. 11, 2022 for European Patent Application No. 19167042.1. cited by applicant
Office Action (Communication Pursuant to Article 94(3) EPC) dated Jun. 24, 2020 for European Patent Application No. 19173274.2. cited by applicant
Office Action (Communication Pursuant to Article 94(3) EPC) dated May 10, 2021, issued in European Application No. 18215332.0. cited by applicant
Office Action (Examination Report No. 1) dated Jun. 1, 2021 for Australian Patent Application No. 2019228526. cited by applicant
Office Action (Examination Report No. 1) dated Jun. 1, 2021 for Australian Patent Application No. 2020244565. cited by applicant
Office Action (Examination Report No. 1) dated Jun. 1, 2021 for Australian Patent Application No.

2020244566. cited by applicant
Office Action (Examination Report No. 1) dated Jun. 1, 2021 for Australian Patent Application No. 2020244567. cited by applicant
Office Action (Notice of Reasons for Refusal) dated Mar. 1, 2022 for Japanese Patent Application No. 2020-200127. cited by applicant
Office Action (Notice of Reasons for Refusal) mailed Aug. 9, 2022 for Japanese Patent Application No. 2020-545472. cited by applicant
Office Action (Notice of Reasons for Refusal) mailed Mar. 22, 2022 for Japanese Patent Application No. 2020-545472. cited by applicant
Office Action (Notice of Reasons for Refusal) mailed Oct. 11, 2022 for Japanese Patent Application No. 2020-200127. cited by applicant
Office Action (Notification of Examination) issued in German Application No. 112012001381.6 dated Mar. 30, 2022. cited by applicant
Office Action (Pre-Appeal Examination Report) mailed Feb. 9, 2021 for Japanese Patent Application No. 2019-063926. cited by applicant
Office Action dated Aug. 4, 2020, issued in JP App No. 2019-063926. cited by applicant
Office Action dated Mar. 24, 2020 issued in JP Patent App. No. 2019-063926. cited by applicant
Office Action for Chinese Patent Application No. 201280015466.8 issued Apr. 20, 2015 (with translation). cited by applicant
Office Action for Japanese Patent Application No. 2014-501276 issued Mar. 1, 2016 (with translation). cited by applicant
Office Action for Japanese Patent Application No. 2014-501276 issued on Aug. 9, 2022 (includes English translation). cited by applicant
Office Action for Japanese Patent Application No. 2015-503186 issued on Jun. 6, 2017 (with translation). cited by applicant
Office Action for Japanese Patent Application No. 2020-200127, issued on Apr. 11, 2023. cited by applicant
Office Action in Japanese Patent Application No. 2015-503186 on Aug. 2, 2016 (with translation). cited by applicant
Office Action issued on Aug. 9, 2022 in Japanese Patent Application No. 2020-545472. cited by applicant
Partial European Search Report issued in application 19167042.1 and dated Jul. 15, 2019. cited by applicant
Partial Supplementary European Search Report for European Patent Application No. 12760085.6 issued Jun. 1, 2015. cited by applicant
Schlaeper et al., “The Fresenius Medical Care Home Hemodialysis System,” Seminars in Dialysis, 2004, vol. 17 (2), pp. 159-161, Wiley, Hoboken, New Jersey. cited by applicant
Unknown, “4008 H—Hemodialysis Machine Operating Instructions,” Fresenius Medical Care AG, Software Version 4.3, May 1, 2005, pp. 1-365. cited by applicant
Unknown, “4008 S—Hemodialysis Machine Operating Instructions,” Fresenius Medical Care, Software Version 4.5, Oct. 1, 2011, pp. 1-368. cited by applicant
Office Action for Japanese Patent Application No. 2023-063941 issued on Feb. 27, 2024 (includes English language translation). cited by applicant
Office Action for U.S. Appl. No. 15/400,978 issued Sep. 21, 2017. cited by applicant
Office Action (Second) dated Aug. 7, 2024 for Canadian Patent Application No. 3,092,575. cited by applicant
Unknown, “4400HX Hot Water Disinfection Water Treatment Solutions for Hemodialysis,” Mar Car Purification—A Cantel Medical Company, 2006, 4 pages. cited by applicant
Unknown, “Aquaboss EcoRO Dia 70—Portable water treatment for hemodialysis,” Lauer Membran Wassertechnik, 2008, Rev. 4.53, Software version 4.00_12, pp. 1-144. cited by applicant

Unknown, "AquaUNO Single Station Reverse Osmosis Unit—Operation Instructions," Fresenius Medical Care, Jul. 1, 2006, Software Version: V2.05, pp. 1-116. cited by applicant

Unknown, "Baxter nixes Vivia home hemodialysis machine," Nephrology News & Issues, 2016, p. 1, Healio, <https://www.healio.com/news/nephrology/20180227/baxter-nixes-vivia-home-hemodialysis-machine>. cited by applicant

Unknown, "Conversion/Retrofit Kit—No. M37525—Connection of an AguaUNO or AquaC UNO H to a 4008" Fresenius Medical Care, 2012, pp. 1-8. cited by applicant

Unknown, "User and service manual—Single place reverse osmosis system—RO 4008," DWA GmbH & Co. KG, Oct. 1, 2008, pp. 1-39. cited by applicant

Unknown, "User Interface Design—PHD Personal Hemodialysis System for Aksys," Brochure, Stream Product Development, Inc., 2020, North Chelmsford, Massachusetts. cited by applicant

Unknown, "Xcorporeal, Inc Announces The XCR-6 Dialysis Platform for Self-Directed Kidney Hemodialysis," Med Device Online, 2008, pp. 1-2, Business Wire, San Francisco, California, <https://www.meddeviceonline.com/doc/xcorporeal-inc-announces-the-xcr-6-dialysis-0001>. cited by applicant

Primary Examiner: Menon; Krishnan S

Attorney, Agent or Firm: Potomac Law Group, PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. application Ser. No. 16/288,725 filed Feb. 28, 2019, which claims the benefit of U.S. Provisional Application 62/636,404, filed Feb. 28, 2018 and U.S. Provisional Application 62/676,098, filed on May 24, 2018, all of which are hereby incorporated by reference in their entireties.

BACKGROUND

- (1) The disclosed subject matter relates generally to the treatment of end stage renal failure and more specifically to devices, methods, systems, improvements, and components for performing peritoneal dialysis.
- (2) Peritoneal dialysis is a mature technology that has been in use for many years. It is one of two common forms of dialysis, the other being hemodialysis, which uses an artificial membrane to directly cleanse the blood of a renal patient. Peritoneal dialysis employs the natural membrane of the peritoneum to permit the removal of excess water and toxins from the blood.
- (3) In peritoneal dialysis, sterile peritoneal dialysis fluid is infused into a patient's peritoneal cavity using a catheter that has been inserted through the abdominal wall. The fluid remains in the peritoneal cavity for a dwell period. Osmotic exchange with the patient's blood occurs across the peritoneal membrane, removing urea and other toxins and excess water from the blood. Ions that need to be regulated are also exchanged across the membrane. The removal of excess water results in a higher volume of fluid being removed from the patient than is infused. The net excess is called ultrafiltrate, and the process of removal is called ultrafiltration. After the dwell time, the dialysis fluid is removed from the body cavity through the catheter.
- (4) Peritoneal dialysis requires the maintenance of strict sterility because of the high risk of peritoneal infection.
- (5) In one form of peritoneal dialysis, which is sometimes referred to as cycler-assisted peritoneal dialysis, an automated cycler is used to infuse and drain dialysis fluid. This form of treatment can be done automatically at night while the patient sleeps. One of the safety mechanisms for such a

treatment is the monitoring by the cyclor of the quantity of ultrafiltrate. The cyclor performs this monitoring function by measuring the amount of fluid infused and the amount removed to compute the net fluid removal.

(6) The treatment sequence usually begins with an initial drain cycle to empty the peritoneal cavity of spent dialysis fluid, except on so-called "dry days" when the patient begins automated treatment without the peritoneal cavity filled with dialysis fluid. The cyclor then performs a series of fill, dwell, and drain cycles, typically finishing with a fill cycle.

(7) The fill cycle presents a risk of over-filling or over-pressurizing the peritoneal cavity, which has a low tolerance for excess pressure. In traditional peritoneal dialysis, a dialysis fluid container is elevated to certain level above the patient's abdomen so that the fill pressure is determined by the height difference. Automated systems sometimes employ pumps that cannot generate a pressure beyond a certain level, but this system is not foolproof since a fluid column height can arise due to a patient-cyclor level difference and cause an overpressure. A reverse height difference can also introduce an error in the fluid balance calculation as a result of incomplete draining.

(8) Modern cyclors may fill by regulating fill volume during each cycle. The volume may be entered into a controller based on a prescription. The prescription, which also determines the composition of the dialysis fluid, may be based upon the patient's size, weight, and other criteria. Due to errors, prescriptions may be incorrect or imperfectly implemented resulting in a detriment to patient well-being and health.

SUMMARY

(9) Embodiments of peritoneal dialysis systems, devices, and methods are described herein. The features, in some cases, relate to automated peritoneal dialysis and in particular to systems, methods, and devices that prepare peritoneal dialysis fluid in a safe and automated way at a point of care. Other features relate to the precision, safety, and ease of use of such systems.

(10) Objects and advantages of embodiments of the disclosed subject matter will become apparent from the following description when considered in conjunction with the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIGS. 1A-1D show peritoneal dialysis fluid proportioner/cyclors according to respective embodiments of the disclosed subject matter.

(2) FIG. 1E shows a series testable filter arrangement that may be substituted for the filters employed in the embodiments of FIGS. 1A-1D.

(3) FIGS. 1F-1H show embodiments similar to those of FIGS. 1A-1D and elaborating further details thereof.

(4) FIG. 2A shows a disposable fluid circuit for use with peritoneal dialysis fluid proportioner/cyclors of certain embodiments disclosed herein.

(5) FIG. 2B shows an actuator portion of a peritoneal dialysis fluid proportioner/cyclor, according to embodiments of the disclosed subject matter.

(6) FIG. 2C shows a connection platform between a purified water source and the peritoneal dialysis fluid proportioner/cyclor, according to embodiments of the disclosed subject matter.

(7) FIG. 2D shows a peristaltic pumping actuator that permits the use of a straight pumping tube segment in a generally planar cartridge, employed as a feature of embodiments disclosed herein.

(8) FIG. 2E shows a disposable fluid circuit for a peritoneal dialysis fluid proportioner/cyclor according to embodiment of the disclosed subject matter in which concentrates are extracted from a disposable component that is separate from the cyclor/preparation fluid circuit.

(9) FIGS. 2F and 2G show concentrate disposable components for use with embodiments of the disclosed subject matter.

(10) FIG. 2H shows a disposable fluid circuit for a peritoneal dialysis fluid proportioner/cycler according to embodiments of the disclosed subject matter in which concentrates are extracted from a disposable component that is separate from the cycler/preparation fluid circuit through respective filtered lines.

(11) FIGS. 2I, 2J, and 2K show respective embodiments of connection platforms between a purified water source and a separate concentrate source and the peritoneal dialysis fluid proportioner/cycler embodiments disclosed herein, according to embodiments of the disclosed subject matter.

(12) FIGS. 2L and 2M show details of variations of the embodiments described with reference to FIG. 2K.

(13) FIG. 3 shows a method of manufacturing a disposable circuit such as is disclosed in FIG. 2A.

(14) FIG. 4A shows a peritoneal dialysis fluid proportioner/cycler according to embodiments of the disclosed subject matter.

(15) FIG. 4B shows the peritoneal dialysis fluid proportioner/cycler of FIG. 4A in a first phase of fluid preparation in which osmotic agent concentrate is added to a mixing container, according to embodiments of the disclosed subject matter.

(16) FIG. 4C shows the peritoneal dialysis fluid proportioner/cycler of FIG. 4A in a second phase of fluid preparation in which a dialysis fluid precursor is obtained by diluting and mixing the contents of the mixing container, according to embodiments of the disclosed subject matter.

(17) FIG. 4D shows the peritoneal dialysis fluid proportioner/cycler of FIG. 4A in a third phase of fluid preparation in which the peritoneal dialysis fluid precursor properties are verified, according to embodiments of the disclosed subject matter.

(18) FIG. 4E shows the peritoneal dialysis fluid proportioner/cycler of FIG. 4A in a fourth phase of fluid preparation in which dialysis fluid precursor is further prepared by addition of electrolyte concentrate to the mixing container, according to embodiments of the disclosed subject matter.

(19) FIG. 4F shows the peritoneal dialysis fluid proportioner/cycler of FIG. 4A in a fifth phase of fluid preparation in which end-use dialysis fluid is prepared by adjustment of the dilution of the mixing container contents, according to embodiments of the disclosed subject matter.

(20) FIG. 4G shows the peritoneal dialysis fluid proportioner/cycler of FIG. 4A in a sixth phase of fluid preparation in which dialysis fluid in the mixing container is verified, according to embodiments of the disclosed subject matter.

(21) FIG. 4H and FIG. 4K show the peritoneal dialysis fluid proportioner/cycler of FIG. 4A in various peritoneal dialysis treatment modes, according to embodiments of the disclosed subject matter.

(22) FIG. 4L shows a peritoneal dialysis fluid proportioner/cycler similar to that of FIG. 4A in which a single mixing container line connects a valve network to the mixing container.

(23) FIGS. 5A-5D illustrate the structure and use of a multifunction connector according to embodiments of the disclosed subject matter.

(24) FIG. 5E shows features for a variation of a double connector **500** that protects against contamination.

(25) FIG. 6A shows mechanical aspects and a control and sensor system for the cut-and-seal devices with actuation, temperature, and force control features, according to embodiments of the disclosed subject matter.

(26) FIGS. 6B through 6G show various embodiments of cut-and-seal devices.

(27) FIGS. 7A through 7D show various jaw arrangements for cut-and-seal devices according to different embodiments of the disclosed subject matter.

(28) FIGS. 8A and 8B show details of chamber portions of fluid circuits according to embodiments of the disclosed subject matter.

(29) FIGS. 8C through 8G show various features to promote mixing of fluids in a mixing container according to embodiments of the disclosed subject matter.

(30) FIG. 9A shows a manifold according to embodiments of the disclosed subject matter.

(31) FIG. 9B shows a peritoneal dialysis fill/drain line according to embodiments of the disclosed subject matter.

(32) FIGS. 10A and 10B show the structure of a valve network portion of a fluid circuit according to embodiments of the disclosed subject matter.

(33) FIG. 11 shows a fluid circuit for peritoneal dialysis according to embodiments of the disclosed subject matter.

(34) FIG. 12 shows a method of priming a fluid circuit according to embodiments of the disclosed subject matter.

(35) FIGS. 13A and 13B show embodiments of a fluid circuit with sources of concentrate where different compositions are provided for priming.

(36) FIG. 14 shows a block diagram of an example computer system according to embodiments of the disclosed subject matter.

(37) FIGS. 15A and 15B illustrate a mixing method according to embodiments of the disclosed subject matter.

(38) FIG. 15C illustrates an optimization point for a mixing method according to embodiments of the disclosed subject matter.

(39) FIG. 15D illustrates a mixing method different from that of FIG. 15A according to further embodiments of the disclosed subject matter.

(40) FIG. 15E is a flow chart in outline form for conductivity error recovery for various mixing methods described herein.

(41) FIGS. 16A through 16C are flow diagrams describing a method for mixing a medicament in which electrolyte concentrate is added first to a mixing container according to embodiments of the disclosed subject matter.

(42) FIGS. 17A through 17D show embodiments of proportioning/treatment systems in which long-term, multi-treatment containers of concentrate are used to form a ready-to-use peritoneal dialysis fluid according to embodiments of the disclosed subject matter.

(43) FIG. 18A shows an embodiment of a proportioning/treatment system in which long-term, multi-treatment containers of concentrate are used to fill a disposable used during a treatment to form a ready-to-use peritoneal dialysis fluid according to embodiments of the disclosed subject matter.

(44) FIG. 18B-18D show a single flow chart when linked together to define a process for making a batch of dialysis fluid based on the embodiment of FIG. 18A.

(45) FIGS. 18E through 18H show variations of details of the embodiment of FIG. 18A for supplying concentrate or water to the fluid circuit according to embodiments of the disclosed subject matter.

(46) FIG. 19A through 19C describe a first device and corresponding method of controlling the supply of water to a peritoneal dialysis fluid treatment device, according to embodiments of the disclosed subject matter.

(47) FIG. 19D through 19F describe a second device and corresponding method of controlling the supply of water to a peritoneal dialysis fluid treatment device, according to embodiments of the disclosed subject matter.

(48) FIGS. 19G through 19H and 19J describe a third device and corresponding method of controlling the supply of water to a peritoneal dialysis fluid treatment device, according to embodiments of the disclosed subject matter.

(49) FIGS. 19K through 19M describe a fourth device and corresponding method of controlling the supply of water to a peritoneal dialysis fluid treatment device, according to embodiments of the disclosed subject matter.

(50) FIGS. 20A through 20E show mechanisms for providing sterile filtration in the various peritoneal proportioning/treatment systems of the various disclosed embodiments.

(51) FIG. 20F shows a device for measuring conductivity with minimal loss of fluid by locating a conductivity cell in the disposable at a point where fluid exits the mixing container, according to embodiments of the disclosed subject matter.

(52) FIG. 20G shows a system and method that may be applied to any of the embodiments in which a pressure sensor used for flow control provides an additional function of pressure testing of a filter membrane by opening a particular set of valves that define a path from the fluid side of the filter to the pressure sensor.

(53) FIGS. 21A through 21C show a flow chart for making and correcting errors in water and concentrate mixtures according to embodiments of the disclosed subject matter.

(54) FIGS. 22A and 22B show a water filtration system with flushing and priming modes controlled by a controller which is commanded by a cyclor controller according to embodiments of the disclosed subject matter with FIGS. 22A and 22B showing production with flushable filters.

(55) FIG. 22C shows multiple additional features that may be added to form variations of the various embodiments disclosed herein, including those of FIGS. 22A and 22B.

(56) FIG. 23 shows an embodiment of a proportioning and treatment system in which sampling of spent dialysate is supplemented by a mechanism to allow for the sampling and testing of spent dialysate aliquots rather than a full treatment volume of spent dialysate.

(57) FIG. 24 shows a peritoneal dialysis system connected to a remote device for purposes of describing various features that may be used with the disclosed embodiments to form additional disclosed embodiments.

(58) FIG. 25 shows a flow chart for describing an embodiment based on the premise that discrepancies between a measured conductivity and the expected conductivity result from a reduction in moisture content of one or both of the pre-packaged concentrates, such as may result from moisture loss due to evaporation, according to embodiments of the disclosed subject matter.

(59) FIGS. 26A through 26C illustrate a system and method for using a proportioning system to infuse a medicament with a drug or other substance.

(60) Embodiments will hereinafter be described in detail below with reference to the accompanying drawings, wherein like reference numerals represent like elements. The accompanying drawings have not necessarily been drawn to scale. Where applicable, some features may not be illustrated to assist in the description of underlying features.

DETAILED DESCRIPTION

(61) FIGS. 1A-1D show peritoneal dialysis fluid proportioner/cyclers according to respective embodiments of the disclosed subject matter. Referring now to FIG. 1A, medical fluid preparation and peritoneal dialysis fluid proportioner/cycler system 90A includes a purified water source 104 that provides water suitable for peritoneal dialysis to a peritoneal dialysis fluid proportioner/cycler 103 which is connected to a disposable component 100A. The purified water source 104 also provides a connection to a drain (shown in FIG. 1A only, but similar in FIGS. 1B-1D). The peritoneal dialysis fluid proportioner/cycler 103 meters concentrate from one or more concentrate containers 101 (one container is shown but multiple containers may be present) and adds them to, and dilutes them with purified water in a mixing container 102. The concentrate containers 101 and mixing container 102 form parts of a single disposable which may also contain a switchable fluid circuit (not shown) that forms part of the disposable component 100A. Mixed dialysis fluid (or other medicament) is pumped by the peritoneal dialysis fluid proportioner/cycler 103 through a connected line to a patient 101A, for example for peritoneal dialysis. The configuration of FIG. 1A allows the sterile concentrate and the fluid circuit and containers used for preparation, as well as short term storage, to be provided as a single sealed sterile disposable with a small predefined number of connections to external devices. These may include connections to the purified water source 104 and connections to the external medicament consumer. The small number of connections minimizes the risk of contamination. By diluting and mixing concentrate at the point of use, the volume of fluid that has to be stored at a peritoneal dialysis treatment location is also

minimized. In a peritoneal dialysis embodiment, the disposable component **100A** may be configured with sufficient concentrate to perform multiple fill/drain cycles of a single peritoneal dialysis treatment. For example, the disposable component **100A** may have sufficient concentrate for multiple fill cycles of a daily automated peritoneal dialysis treatment (APD).

(62) Referring now to FIG. **1B**, a medical preparation and peritoneal dialysis fluid proportioner/cycler system **90B** is similar to the medical fluid preparation and peritoneal dialysis fluid proportioner/cycler system **90A** except that the disposable component **100B** that has a fluid circuit for proportioning and diluting as well as delivering the product medicament does not contain the concentrate. This allows the size of the disposable component **100B**, which is handled frequently, for example, daily, to be reduced in mass and easier for a patient and/or user to handle and store. It also can make the disposable component **100B** more economical by reducing waste and providing packaging and manufacturing economies. To provide the concentrate, a separate disposable component **100E** is provided which contains one or more concentrate containers **101**. The disposable component **100E** may have a large capacity and may be changed on a schedule that is much less frequent than the frequency of the replacement of the disposable component **100B**. For example, the disposable component **100B** may be replaced each time a daily peritoneal dialysis treatment is performed. It may be called a “daily disposable component.” For example, the disposable component **100E** may be replaced once every month so it may be called a “monthly disposable” or it may be replaced every week and called a “weekly disposable”. The precise capacity and the time the disposable generally lasts is not a limiting feature of the disclosed subject matter. What is relevant is that the disposable component **100E** (and others disclosed below) have sufficient capacity for multiple treatments where each treatment includes multiple fill/drain cycles of a peritoneal dialysis treatment.

(63) The disposable component **100B** may also have, as part of the fluid circuit included therein, a sterilizing filter **115** of a type that has an air-line **118** to permit the pressure testing of a membrane thereof. The latter type of filter test may be performed automatically by a controller of the peritoneal dialysis fluid proportioner/cycler **103** on a schedule that is more frequent than the replacement schedule for the disposable component **100E**. In embodiments, the sterilizing filter **115** may be integrated, and therefore, replaced with, the disposable component **100B**. This allows the sterilizing filter **115** to be sealed and sterilized with the disposable component **100B** and mixing container **102** as a single unit along with the switchable fluid circuit (not shown). Note details of a suitable configuration for a switchable fluid circuit may be found in International Patent Application Publication WO2013141896 to Burbank, et al.

(64) A function provided by the sterilizing filter **115** is to provide safety given that a new sterile disposable component **100B** is attached to the concentrate **101** for each peritoneal dialysis treatment. A similar filter may be employed in all the embodiments for the line indicated at **107** conveying the purified water to the peritoneal dialysis fluid proportioner/cycler **103**. Since a new connection is required each time the disposable component **100B** is replaced, there is a risk of contamination from the new connection. The sterilizing filter **115** (and others) can be provided as a sterile barrier to protect the sterile interior of the disposable component **100B**, thereby ensuring that any contamination resulting from the newly-made connection does not enter the disposable component **100B** interior. In addition, the automatic testing of the filter provides assurance that the sterilizing filter **115** integrity has provided the expected sterile fluid. Thus, the testability functions as a guarantee of the filter's sterilizing function. Testing of sterilizing filters using pressurized air testing can be done in various ways, for example, a bubble point test can be performed.

Alternatively, a pressure decay test can be done where fluid is pumped across the membrane and the pressure drop measured and compared with a pressure drop representative of an intact filter or pressure is increased on one side, pumping stopped, and the rate of decay of pressure compared to a predefined curve representative of an intact filter. In other embodiments, the filter is housed in an air-tight container and the container is pressurized to a level that is below the expected bubble

point, but high enough to guarantee that the membrane is sterilizing grade. The filter has air vents so this pressurizes the membrane. The rate of (air) pressure decay is then measured and if the decay rate is greater than a predefined threshold rate, the filter is indicated to have failed. Other means of testing filter integrity may be used, for example, concentrates can include a large-molecule excipient whose presence can be detected using automatic chip-based analyte detection (e.g., attachment of fluid samples to selective fluorophore after flowing through the filter and optical detection after concentration). A feature of the embodiments that use a filter to provide the guarantee, as mentioned, is that the filter forms part of a sterilized unit that is otherwise hermetically sealed or protected by one or more additional sterilizing filters. Thus, in embodiments, the entire sealed and sterilized circuit may have sterilizing filters (1) at all openings to its interior or at least (2) at all openings to which fluid is admitted from the external environment.

(65) Referring now to FIG. 1C, a medical preparation and peritoneal dialysis fluid proportioner/cycler system **90C** is similar to the medical fluid preparation and peritoneal dialysis fluid proportioner/cycler system **90B** in that the disposable component **100C** that has a fluid circuit for proportioning and diluting as well as delivering the product medicament does not contain the concentrate. As in peritoneal dialysis fluid proportioner/cycler system **90B**, a separate disposable component **100F** is provided which contains one or more concentrate containers **101**, in this example, a first concentrate container **105A** and a second concentrate container **105B** are shown. These may be in the form of canisters held by a single packaging wrapper **105C** or they may be replaced separately when they expire or are exhausted. As in the peritoneal dialysis fluid proportioner/cycler system **90B**, the disposable component **100C** may have a large capacity and may be changed on a schedule that is much less frequent than the frequency of the replacement of the disposable component **100B**. For example, the first concentrate container **105A** and/or second concentrate container **105B** may be sized to be replaced on a monthly basis. In the medical fluid preparation and peritoneal dialysis fluid proportioner/cycler system **90C**, the disposable component **100C** may also have, as part of the fluid circuit included therein, two sterilizing filters (collectively indicated as the sterilizing filter **115**), each of the type that has an air-line **118** to permit the pressure-testing of a membrane thereof. Each of the concentrates from first concentrate container **105A** and second concentrate container **105B** may thereby be sterile-filtered and the filter tested for each separately. As in the peritoneal dialysis fluid proportioner/cycler system **90B**, this configuration allows the sterilizing filters **115** to be sealed and sterilized with the disposable component **100C** and mixing container **102** as a single unit along with the switchable fluid circuit (not shown). As in any of the embodiments a sterilizing filter may be used in the water line as indicated at **107**.

(66) Referring now to FIG. 1D, a medical preparation and peritoneal dialysis fluid proportioner/cycler system **90D** is similar to the medical fluid preparation and peritoneal dialysis fluid proportioner/cycler system **90C** in that the disposable component **100C** that has a fluid circuit for proportioning and diluting as well as delivering the product medicament does not contain the concentrate. As in peritoneal dialysis fluid proportioner/cycler system **90C**, a separate disposable component **100G** is provided which contains a first concentrate container **105A** and a second concentrate container **105B**. As in any of the embodiments, the number of concentrates may be greater or fewer. The concentrates may be held in the canisters which may have a single packaging wrapper **105C** or they may be replaced separately when they expire. As in the peritoneal dialysis fluid proportioner/cycler system **90C**, the disposable component **100G** may have a large capacity such that it can be replaced on a schedule that is much less frequent than the frequency of the replacement of the disposable component **100D**. For example, the first concentrate container **105A** and/or second concentrate container **105B** may be sized to be replaced on a monthly basis. In the medical fluid preparation and peritoneal dialysis fluid proportioner/cycler system **90D**, the disposable component **100D** may also have, as part of the fluid circuit included therein, the sterilizing filter **115**, also of the type that has an air-line **118** to permit the pressure testing of a

membrane thereof. To sterile-filter each of the concentrates from first concentrate container **105A** and second concentrate container **105B**, a connection platform allows the peritoneal dialysis fluid proportioner/cycler **103** to draw purified water, first concentrate container **105A** or second concentrate container **105B** selectively by closing a valve on all but one of these at a time by the connection platform **106** under control of the peritoneal dialysis fluid proportioner/cycler **103**. As in the peritoneal dialysis fluid proportioner/cycler system **90B**, this configuration allows the sterilizing filter **115** to be sealed and sterilized with the disposable component **100D** and mixing container **102** as a single unit along with the switchable fluid circuit (not shown). The switching fluid circuit of the connection platform **106** may be part of a disposable that is replaced with the first concentrate container **105A** and second concentrate container **105B**.

(67) In the present and any of the embodiments, the long-term concentrate containers (e.g., monthly disposable) may be replaced on separate schedules so they need not be packaged as a single disposable. This may provide further economy when one concentrate is used at a lower rate by some patients than others, thus allowing the concentrate to be consumed fully before replacing.

(68) It should be evident that there is the potential for the reduction of waste of concentrate by structuring the batch preparation components to permit the changing of concentrates independently of each other and at intervals that cover multiple peritoneal dialysis treatment sessions. Each concentrate container can be used until exhaustion. For embodiments, exhaustion may be defined to be a condition where insufficient concentrate remains in a single container to permit the preparation of a full batch of peritoneal dialysis fluid, a full batch, in embodiments, being a quantity of concentrate component sufficient for a single fill cycle. In other embodiments, a concentrate container may be exhausted when there is insufficient concentrate to make a predefined number of batches or enough to make sufficient dialysate for a full treatment. If two concentrates are mixed to form a batch, each component concentrate may be changed out when the prescription's required contribution of that concentrate to make a single batch exceeds the remaining volume in the particular container. The residual volume threshold associated with this insufficiency is a fixed volume, so that its percentage of the total volume available from a full container is smaller for a large container than for a smaller container. Thus, in embodiments where the concentrate container is replaced only when the threshold is reached, which container holds large total volume, for example, enough for multiple fill cycles, or better, enough for multiple peritoneal dialysis treatments each including multiple fill cycles, the total waste is much smaller than a disposable component containing concentrate for a single peritoneal dialysis treatment. An example of the latter is discussed below with reference to FIGS. **8A** and **8B**. In addition, since each concentrate container can be replaced separately, the fixed residual thresholds of the multiple concentrate containers are independent of each other because each container can be replaced independently of the other. In contrast, in the embodiments of FIGS. **8A** and **8B**, if one container reaches the minimum volume before the other, the contents of neither concentrate container can be used further.

(69) In embodiments, the concentrate containers are sized to permit a single peritoneal dialysis treatment. For convenience and convention, a single peritoneal dialysis treatment would be considered a single day's worth of peritoneal dialysis treatment, for example, a series of nocturnal PD cycles ending with a fill. So, a single day's peritoneal dialysis treatment is equal to a sufficient quantity of fluid to perform multiple fill and drain cycles. Embodiments in which the concentrate containers are sized for a single day's peritoneal dialysis treatment differ from those described with reference to the embodiments of FIGS. **8A** and **8B** in that the concentrates can be changed independently thereby achieving a potential savings of a first concentrate that is used at a rate such that a residual volume of the first concentrate can be used more fully as described above. More specifically, if the concentrate containers are sized such that batches of at least predefined prescriptions require more of a first concentrate component than of a second concentrate component and such that at least one batch, or at least one day's worth of batches can be completed

while leaving sufficient residual concentrate of the second component to make at least one additional batch, or one additional day's worth of batches, after replacing the first concentrate component, then a savings of the second concentrate may be enjoyed. In embodiments, the total concentrate of the most heavily used container of a multiple-component concentrate system is at least sufficient for: Multiple batches, a batch being sufficient for a single peritoneal cycle (fill volume of a peritoneum of a predefined class of patient (e.g., child, adult, adult of a certain size, etc.); Same as 1, but where the multiple batches are sufficient for a single peritoneal dialysis treatment of multiple fill-drain cycles; Same as 2, but the most heavily used concentrate container is sufficient for making enough dialysis fluid for multiple peritoneal dialysis treatments; Same as 2, but the most heavily used concentrate container is sufficient for making enough dialysis fluid for multiple days' worth of peritoneal dialysis treatments if a single day's worth is not identical to a single peritoneal dialysis treatment's worth; A full week's worth of peritoneal dialysis treatments; or A full month's worth of peritoneal dialysis treatments or some other interval on the order of a month or multiple months.

(70) FIGS. **1F-1H** show embodiments similar to those of FIGS. **1A-1D** and elaborating further details thereof. Referring now to FIG. **1F**, a fluid circuit is indicated at **112**. The fluid circuit **112** engages with the peritoneal dialysis fluid proportioner/cycler **114** by means of valve actuators **123** and one or more pumping actuators **125** which engage the fluid circuit elements of the fluid circuit **112** without wetting the actuator components. For example, a type of valve actuator such as a linear-motor driven pinch clamp may close and open tubing for flow therethrough and peristaltic pump rollers may engage pumping tube segments. The configuration is not limited to such examples, and many are known in the art, any of which may be used in the present embodiment. The fluid circuit **112** has water suitable for peritoneal dialysis and drain lines **126**, **127**. The water suitable for peritoneal dialysis flows through a line with a sterilizing filter **115** according to any of the disclosed embodiments including a testable filter and two sterilizing filters in series. The only connections that need to be made for supplying fluid or draining fluid are connections indicated at **129**. The water suitable for peritoneal dialysis and drain lines **126**, **127** may be formed as part of the fluid circuit **112**. In embodiments, the fluid circuit **112**, concentrate container(s) **101**, and mixing container **102** may be pre-connected to form a complete disposable fluid circuit **100A** including concentrate.

(71) Referring now to FIG. **1G**, further details of the peritoneal dialysis fluid proportioner/cycler system **90C** are shown. The separate disposable component **100F** contains concentrate containers **105A** and **105B** and connects to the peritoneal dialysis fluid proportioner/cycler **114** by connectors **121**, which may include a double connector as described in embodiments described herein or other types. The peritoneal dialysis fluid proportioner/cycler **114** has pumping actuators **125** and valve actuators **123** that engage the fluid circuit **112**. Here the peritoneal dialysis fluid proportioner/cycler **114** provides a pass-through connection for the concentrate while the sterilizing filters **115** on the concentrate lines **130** form part of the disposable component **100C**, which includes the fluid circuit **112** and mixing container **102**. That is, the peritoneal dialysis fluid proportioner/cycler **114** connects the concentrate lines **131** respectively to the concentrate lines **155A** and **155B** of the fluid circuit **112**. Here also, connectors for air-lines **130A** and **130B** are provided to the peritoneal dialysis fluid proportioner/cycler **114** where an air pump (not shown) can generate a positive pressure and a pressure sensor can measure the positive pressure. A filter integrity test may be done after flowing fluid into the fluid circuit. During set-up, the disposable component **100C** may be connected by connecting water suitable for peritoneal dialysis and drain lines **116**, **117**, concentrate lines **155A** and **155B** and air-lines **130A** and **130B**, while the connectors **121** can remain in place through the entire long-term disposable cycle, that is, until the separate disposable component **100F** is expired. Since the latter is replaced much less frequently, the connectors **121** can remain in place for a relatively long period, and frequent changes can be limited to changing connectors **122**, **120**, and connectors for water suitable for peritoneal dialysis and drain lines **116**, **117** as well as the air-

lines **130A** and **130B**. In embodiments, for convenience, all of these connections can be provided in the form of ganged connectors to make and unmake multiple connections at once. The concentrate containers **105A** and **105B** may connect to a connection platform (not shown as a unit but may include the connectors and a support for the concentrate containers **105A** and **105B**) and a holder for the by the peritoneal dialysis fluid proportioner/cycler **114**. See further connection platform embodiments for details.

(72) Referring to FIG. **1H**, a simplified arrangement becomes possible if the disposable component **100G** is connected to the peritoneal dialysis fluid proportioner/cycler **114** by connectors **121**, but all concentrates and water flow into the fluid circuit **112** via the fluid line **135** and all of these fluids are filtered by sterilizing filter **115**. To provide this, a connection platform with its own controller (not shown separately) may be provided and connected to a peritoneal dialysis fluid proportioner/cycler, the combination being illustrated at **119**. The connection platform portion of the combined peritoneal dialysis fluid proportioner/cycler and connection platform **119** may be as described with reference to FIGS. **2K** through **2M**, for example. The connection platform portion of the combined peritoneal dialysis fluid proportioner/cycler and connection platform **119** selects one of the fluids at a given time by closing off the others and opening a fluid path to the selected one of water, concentrate A, and concentrate B. As indicated, here and in any embodiments, further or fewer concentrates may be used. A drain line **135** is present. A communications interface may be provided to allow commands to be sent from the fluid circuit **112** to the peritoneal dialysis fluid proportioner/cycler and connection platform **119**.

(73) FIG. **2A** shows a disposable fluid circuit **200** with fluid lines and components **200A** and a cartridge portion **205** containing a fluid flow director portion **200B** and a manifold portion **200E**. The disposable fluid circuit **200** is used as a replaceable disposable component with a peritoneal dialysis fluid proportioner/cycler according to embodiments disclosed herein. The present disposable fluid circuit **200** may be used with the peritoneal dialysis fluid proportioner/cycler system **90A**, for example. Two concentrate containers **111A** and **111B** and a mixing container **102** are connected as a pre-connected unit with other parts of the fluid circuit. The two concentrate containers **111A** and **111B** and mixing container **102** may be provided as a welded double panel sheet with welded seams that define the respective chambers. The mixing container **102** has two lines, an inflow line **165** and an outflow line **166**. A first concentrate container **111A** container has **167**, which may be pre-connected and a second concentrate container **111B** line **164**, which may be pre-connected. The present embodiment is for a peritoneal dialysis fluid proportioner/cycler and has a pre-connected fill-drain line **160** with a dialysis fluid line **172** attached to an air-line **129**. The latter may be formed as a single unit by co-extrusion. The air-line **129** attaches to a pressure-sensing pod **162** located at a distal end of the pre-connected fill-drain line **160**. A connector **185** at the distal end of the pre-connected fill-drain line **160** is sealed. Another double line **161** has an air-line **129** and a fluid line **171**. The fluid line **171** receives fluid from peritoneal dialysis fluid proportioner/cycler **114** and the air-line is used for testing the membrane of the filter. The two air-lines **129** connect to respective ports **191** that automatically connect in the actuator portion **140** of any of the suitable peritoneal dialysis fluid proportioner/cycler embodiments. The actuator portion **140** may be is described with reference to FIG. **2B**. Sample ports are provided at **168** at the ends of sample fluid lines **132** and **133** for extracting fluid from respective chambers **175** and **176** of a manifold **174**. The two chambers **175** and **176** are separated by a barrier **134** and connected by a pumping tube segment **137**. Pressure pods **178** are installed in each of the two chambers **175** and **176** to measure pressure on the suction and pressure sides of the pumping tube segment **137**. The dialysis fluid line **172** has two branches **136** and **139**. A waste line **128** and the fluid line **171** connect via a double connector **181**. Lines **132**, **128**, **165**, and branch **136** connect to chamber **175**. Lines **133**, **164**, **166**, **167**, **171** and branch **139** connect to chamber **176**.

(74) The double connector **181** supports lines **171** and **128** and provides a pair of connectors **186** and **187** to permit connection of lines **171** and **128** to water inlet and fluid drain line ports on the

peritoneal dialysis fluid proportioner/cycler **114**. The connectors **186** and **187** are sealed by a cap **180**. A recess **5251** (See FIGS. 5A, 5B) to engage a détente pin (not shown, but may be a spring-biased pin in the opening that receives the double connector **181**) provides tactile confirmation of full engagement of the double connector **181**. The double connector **181** has a window **183** that provides access to a cut and seal actuator (not shown in this drawing but indicated at **210** in FIGS. 2I through 2K). When the segments **182** and **184** of lines **171** and **128** are cut, the double connector can remain in place sealing the water inlet and fluid drain line ports until it is removed immediately prior to connecting a fresh double connector **181**. This provides a barrier to prevent contaminants from entering the water inlet and fluid drain line ports, which in turn protects the sterile fluid path used by the peritoneal dialysis fluid proportioner/cycler or connection platform.

(75) The first concentrate container **111A** and concentrate container **111B** are both sealed by a frangible seal **154** in each of the lines **164** and **167**. The seal is fractured automatically by an actuator after the manifold cartridge **205** is loaded into a receiver that engages it with the interface shown in FIG. 1B. Holes **170** are provided in a cartridge support **169** that holds the lines in predefined positions. Holes **170** provide access to pinch actuators that selectively close and open the lines **177**. Certain lines such as lines **177** engage with valve actuators so that they function as valve segments. Holes **179** provide access to actuators that fracture the frangible seals **154**. Note that the cartridge support **169** is bridged to the manifold **174** by a battery of tubes indicated collectively at **200C**. Even though the polymer of the tubes is flexible, their lengths, number, are such that the overall structure including the cartridge support **169** and the manifold **174** is sufficiently stiff may be readily inserted in a receiving slot.

(76) FIG. 2B shows an actuator portion **140** of a peritoneal dialysis fluid proportioner/cycler, according to embodiments of the disclosed subject matter. Referring to FIG. 2B, a receiving slot **158** receives the cartridge portion **205** and aligns it with the various actuators and sensors now identified. The various actuators and sensors include pinch clamp actuators **141** that selectively press against selected tubes to provide a valve function. The actuators and sensors further include frangible seal actuators **142** that fracture frangible seals **154** in the concentrate lines that contain them. The frangible seal actuators **142** may be activated simultaneously to open the lines between the pump and the concentrate containers once the pump (e.g., eight-roller peristaltic pump **143**—note that the number of rollers can be any number) is engaged with the pumping tube segment **137**. The actuators and sensors further include an air sensor **150**, for example an optical air sensor, that wraps partly around the tube segment of branch **136** in the upper portion of the hole indicated at **124**. Ports **146** and **147** connect a vacuum or pressure pump to the respective ports **191**.

(77) FIG. 2C shows connection platform **219** that serves as an interface between a purified water source and the peritoneal dialysis fluid proportioner/cycler, according to embodiments of the disclosed subject matter. Connection platform **219** is an embodiment that may provide for connection to water and drain lines **116** and **117** of embodiments of FIGS. 1G and 1H as well as connectors for the concentrate containers **105A** and **105B** for interfacing with the peritoneal dialysis fluid proportioner/cycler **114**. The connection platform **219** permits the purified water source **104** to be connected to different devices, such as different peritoneal dialysis treatment devices. Shown here is a configuration adapted for peritoneal dialysis medicament preparation, and optionally peritoneal dialysis treatment also.

(78) Water from the purified water source **104** is received in water line **245** via connection **244** and flows through ultrafilters **237**. Pressure of the water suitable for peritoneal dialysis supply is monitored by a pressure sensor **218**. A valve **234** selectively controls the flow of water suitable for peritoneal dialysis to a double connector **215**. The purified water source terminates at a purified water connector **224** of the double connector **215**. The double connector **215** also has a drain terminal connector **225** which splits at a junction **220** into a path that flows to a pair of conductivity sensors **230** and then merges at junction **238** to proceed to a drain **236** and a path that flows directly to the drain **236**. The selected path is controlled by valves **232**, **240**, and **242** which are controlled

by a controller **210**. The double connector **181** previously described is received in a slot **214** where connections are made to the purified water connector **224** and drain terminal connector **225**. A détente mechanism **216** provides tactile and audible feedback to the operator when a home (fully connected) position of the double connector **181** is realized by inserting into the receiving slot **214**. The receiving slot **214A** has a cutting and sealing actuator **212** driven by a controller **210** that cuts the tubes through the window of double connector **181**. A connector **239** serves as an adapter to permit connection to various types of drains. The connection platform **219** is also provided with sensors including a moisture sensor **249** located to detect leaking fluid in the connection platform **219**, a tilt sensor **226** to indicate the proper orientation of the connection platform **219**, and a user interface to interact with the controller **210**. The connection platform **219** may be received in a receiving slot **231** and may be formed as a unitary replaceable component. If sterility or leakage problems arise, the connection platform **219** can be replaced easily.

(79) FIG. 2D shows a peristaltic pumping actuator **143** that permits the use of a straight pumping tube segment in a generally planar cartridge, employed as a feature of embodiments disclosed herein. The rollers **145** are attached to a rotor that has recesses to permit clearance for the bulge of an adjacent pumping tube segment positioned between a race **148** and the rollers **145**. The rollers **145** are unsprung, unlike other peristaltic pump rollers, and rotate on fixed bearings **1472**. Instead, the race **148** is sprung by springs **144** which urge the race against a pumping tube segment pinched by the rollers **145**. This is a particular embodiment of a pump and at least some of the embodiments are not limited based on whether the rollers or race are sprung. Either the rotor **149** can be moved toward the race **148** to engage a pumping tube segment, or the race **148** can be moved toward the rotor **149**. A sufficient gap at **1492** during loading allows a cartridge, such as cartridge portion **200B** with a pumping tube segment to be slid in with no interference. The race **148** is constrained to tilt (in the plane of the drawing) and translate up and down in the plane of the drawing by pins **152** received in guides **153**.

(80) FIG. 2E shows a disposable fluid circuit for a peritoneal dialysis fluid proportioner/cycler according to an embodiment of the disclosed subject matter in which concentrates are extracted from a disposable component that is separate from the cycler/preparation fluid circuit. A disposable fluid circuit **300** has fluid lines and components **300A** and a cartridge portion **305** containing a fluid flow director portion **300B** and a manifold portion **300E**. The disposable fluid circuit **300** is for use with peritoneal dialysis fluid proportioner/cyclers of certain embodiments disclosed herein. The present disposable is an embodiment that may be used with the peritoneal dialysis fluid proportioner/cycler system **90B** or **90D**, for example, where two concentrate containers **105A** and **105B** (not shown in this drawing but shown in FIGS. 1B and 1H—again, only as examples so other features of the peritoneal dialysis fluid proportioner/cycler are not limiting of the disposable fluid circuit **300**) are provided as a separate unit from disposable fluid circuit **300**, which has a mixing container **102** and no concentrate containers. The mixing container **102** may be provided as a welded double panel sheet with welded seams that define the chambers. The mixing container **102** may have two lines, an inflow line **165** and an outflow line **166**. In alternative embodiments, the mixing container **102** may have only a single line for both inflow and outflow.

(81) The present embodiment is for a peritoneal dialysis fluid proportioner/cycler and has a pre-connected fill-drain line **160** with a dialysis fluid line **172** attached to an air-line **129**. The latter may be formed as a single unit by co-extrusion. In alternative embodiments, the fill-drain line may be separate and connectable with a separate connector. In the present embodiment, the air-line **129** attaches to a pressure-sensing pod **162** located at a distal end of the pre-connected fill-drain line **160**. A connector **185** at the distal end of the pre-connected fill-drain line **160** is sealed. Another double line **161** has an air-line **129** and a fluid line **171**. The fluid line **171** receives fluid from peritoneal dialysis fluid proportioner/cycler **114** and the air-line is used for testing the membrane of the filter. The two air-lines **129** connect to respective ports **191** that automatically connect in an actuator portion **140** as described with reference to FIG. 2B. Sample ports are provided at **168** at

the ends of sample fluid lines **132** and **133** for extracting fluid from respective chambers **175** and **176** of a manifold **174**. The two chambers **175** and **176** are separated by a barrier **134** and connected by a pumping tube segment **137**. Pressure pods **178** are installed in each of the two chambers **175** and **176** to measure pressure on the suction and pressure sides of the pumping tube segment **137**. The dialysis fluid line **172** has two branches **136** and **137**. A waste line **128** and the fluid line **171** connect via a double connector **181**. Lines **132**, **128**, **165**, and branch **136** connect to chamber **175**. Lines **133**, **164**, **166**, **167**, **171** and branch **139** connect to chamber **176**.

(82) The double connector **181** supports lines **171** and **128** and provides a pair of connectors **186** and **187** to permit connection of lines **171** and **128** to water inlet and fluid drain line ports on the peritoneal dialysis fluid proportioner/cycler **114**. The connectors **186** and **187** are sealed by a cap **180**. A recess to engage a détente pin provides tactile confirmation of full engagement of the double connector **181**. The double connector **181** has a window **183** that provides access to a cut and seal actuator (not shown in this drawing). When the segments **182** and **184** of lines **171** and **128** are cut, the double connector can remain in place sealing the water inlet and fluid drain line ports on the peritoneal dialysis fluid proportioner/cycler **114** until it is removed immediately prior to connecting a fresh double connector **181**. This provides a barrier to prevent contaminants from entering the connection platform **219** fluid path, which in turn protects the sterile fluid path used by the peritoneal dialysis fluid proportioner/cycler **114**. The connection platform **219** selects the fluid to be delivered to the fluid line **171**. Holes **170** are provided in the cartridge support **169** that holds the lines in predefined positions. Holes **170** provide access to pinch actuators that selectively close and open the lines **177**. Note that the cartridge support **169** is bridged to the manifold **174** by a battery of tubes indicated collectively at **300C**. Even though the polymer of the tubes is flexible, the cartridge support **169** and the manifold **174** may be readily inserted in a receiving slot.

(83) FIGS. 2F and 2G show concentrate disposable components for use with embodiments of the disclosed subject matter. Referring to FIG. 2F, a concentrate package **206**, for example a cardboard box, contains a pair of concentrate containers **262** and **264**. Each of the concentrate containers **262** and **264** may be connected to a respective port **265**, **266** of a double connector **181B**, the double connector **181B** may be as the one described above (FIGS. 2A, 2E) or below (e.g., 5A-5E) or another type of connector or pair of connectors. For example, a simple two-port connector **273** may be used. Separate connectors may also be used to permit the containers to be replaced independently of each other. In embodiments, the double port may be connected to a receiving device **287** as shown in FIG. 2G so that each concentrate **262** or **264** can be installed in the receiving device **287** independently of the other while the double connector **181B** remains connected to the receiving device **287**. The receiving device **287** has fluid connectors **285** for connecting to corresponding connectors on the concentrate containers **262** and **264** such that once a respective one of the containers **262** or **264** is installed, fluid can be drawn through the ports **288A** and **288B** of the two-port connector **273**. The latter may be connected to the connection platform **219**, for example as shown in FIG. 2I.

(84) FIG. 2H shows a disposable fluid circuit **310** for a peritoneal dialysis fluid proportioner/cycler according to embodiments of the disclosed subject matter in which concentrates are extracted from a disposable component that is separate from the cycler/preparation fluid circuit through respective filtered lines. The disposable fluid circuit **310** has fluid lines and components **310A** and a cartridge portion **315** containing a fluid flow director portion **310B** and a manifold portion **310E**. The disposable fluid circuit **310** is for use with peritoneal dialysis fluid proportioner/cyclers of certain embodiments disclosed herein. The present disposable is an embodiment that may be used with the peritoneal dialysis fluid proportioner/cycler system **90C** where two concentrate containers **105A** and **105B** are provided as a separate disposable from one shown in **100C** with a mixing container **102**, only. The mixing container **102** may be provided as a welded double panel sheet with welded seams that define a chamber. The mixing container **102** has two lines, an inflow line **165** and an outflow line **166**. The present embodiment is for a peritoneal dialysis fluid proportioner/cycler and

has a pre-connected fill-drain line **160** with a dialysis fluid line **172** attached to an air-line **129**. The fill-drain line **160** with a dialysis fluid line **172** attached to an air-line **129** may be formed as a single unit by co-extrusion of both lines. The air-line **129** attaches to a pressure-sensing pod **162** located at a distal end of the pre-connected fill-drain line **160**. A connector **185** at the distal end of the pre-connected fill-drain line **160** is sealed. Another double line **161** has an air-line **129** and a fluid line **171**. The fluid line **171** receives fluid from peritoneal dialysis fluid proportioner/cycler **114** and the air-line is used for testing the membrane of the filter. The two air-lines **129** connect to respective ports **191** that automatically connect in an actuator portion such as **140** as described with reference to FIG. 2B (see **146** and **147** of FIG. 2B). Sample ports are provided at **168** at the ends of sample fluid lines **132** and **133** for extracting fluid from respective chambers **175** and **176** of a manifold **174**. The two chambers **175** and **176** are separated by a barrier **134** and connected by a pumping tube segment **137**. Pressure pods **178** are installed in each of the two chambers **175** and **176** to measure pressure on the suction and pressure sides of the pumping tube segment **137**. The dialysis fluid line **172** has two branches **136** and **139**. A waste line **128** and the fluid line **171** connect via a double connector **181**. Lines **132**, **128**, **165**, and branch **136** connect to chamber **175**. Lines **133**, **164**, **166**, **167**, **171** and branch **139** connect to chamber **176**. The fluid line **171** connects to a water source.

(85) The double connector **181** supports lines **171** and **128** and provides a pair of connectors **186** and **187** to permit connection of lines **171** and **128** to water inlet and fluid drain line ports on the peritoneal dialysis fluid proportioner/cycler **114**. The connectors **186** and **187** are sealed by a cap **180**. A recess to engage a détente pin provides tactile confirmation of full engagement of the double connector **181**. The double connector **181** has a window **183** that provides access to a cut and seal actuator (not shown in this drawing). When the segments **182** and **184** of lines **171** and **128** are cut, the double connector can remain in place sealing the water inlet and fluid drain line ports on the peritoneal dialysis fluid proportioner/cycler **114** until it is removed immediately prior to connecting a fresh double connector **181**. This provides a barrier to prevent contaminants from entering the connection platform fluid path, which in turn protects the sterile fluid path used by the peritoneal dialysis fluid proportioner/cycler **114**. The connection platform **219** selects the fluid to be delivered to the fluid line **171**. Holes **170** are provided in a cartridge support **169** (which may be vacuum-formed) that holds the lines in predefined positions. Holes **170** provide access to pinch actuators that selectively close and open the lines **177**. Note that the cartridge support **169** is bridged to the manifold **174** by a battery of tubes indicated collectively at **310C**. Even though the polymer of the tubes is flexible, the cartridge support **169** and the manifold **174** may be readily inserted in a receiving slot. Two concentrates are received through lines **164** and **167**, respectively. Each of the lines is filtered by a filter **115** as described with reference to FIG. 1G. Respective holes **170** are provided to control the flow of concentrate through each of the lines **164** and **167**. FIGS. 21 and 2J show examples of connection platforms **219** for connecting to a double connector **181A** to permit concentrate to be drawn through the lines **164** and **167**.

(86) Note that the actuators and sensors of the embodiments of FIGS. 2I, 2J, 2K, 2L, and 2M may be controlled by a single controller, for example.

(87) FIGS. 2I, 2J, and 2K show respective embodiments of connection platforms that interface between a purified water source and a separate concentrate source and the peritoneal dialysis fluid proportioner/cycler embodiments disclosed herein, according to embodiments of the disclosed subject matter. Referring now to FIG. 2I and connection platform **219** is an embodiment of the interface providing the water supply and drain connections (**116**, **117**, See FIGS. 1G and 1H) between the purified water source **104** and the peritoneal dialysis fluid proportioner/cycler **114**. The connection platform **219** permits the purified water source **104** (FIGS. 1F-1G) to be connected to different devices, such as different peritoneal dialysis treatment devices. Shown here is a configuration adapted for peritoneal dialysis medicament preparation, and optionally peritoneal dialysis treatment also. The present configuration differs from that of FIG. 2C in that the present

arrangement includes a mechanism for connecting a circuit such as disposable fluid circuit **310** of FIG. **2H** which draws concentrate from a double connector **181A** which fits in slot **214A** to receive concentrate through ports **283**. The double connector **181A** also has a détente mechanism **216** to provide feedback to the operator when a home (fully connected) position of the double connector **181A** is realized by inserting into the receiving slot **214A**. The receiving slot **214A** has a cutting and sealing actuator **212**, driven by controller **210**, that cuts the tubes through the window of double connector **181**, **181A**. The ports **283** may be supported on a replaceable double connector **273** as described in FIG. **2F** so that these ports are provided by a replaceable connector as part of a concentrate package **260** as shown in FIG. **2F** that includes concentrate containers **262** and **264** or is fitted to the receiving device **287** described above with reference to FIG. **2G**. In alternative embodiments, the ports **283** may be part of the connection platform **219**. In that case, the tubes **290** and **292** may be part of the connection platform **219** and provided with separate connectors for connecting the tubes **293** and **294** of the concentrate containers **262** and **264** (FIG. **2F**) or similarly to connect the receiving device **287**.

(88) As in the FIG. **2C** embodiment, water from the purified water source **104** is received in water line **245** via connection **244** and flows through ultrafilters **237**. Pressure of the water suitable for peritoneal dialysis supply is monitored by a pressure sensor **218**. A valve **234** selectively controls the flow of water suitable for peritoneal dialysis to a double connector **215**. The purified water source terminates at a purified water connector **224** of the double connector **215**. The double connector **215** also has a drain terminal connector **225**, which splits at a junction **220** into a path that flows to a pair of conductivity sensors **230**, and then merges at junction **238** to proceed to a drain **236** and a path that flows directly to the drain **236**. The selected path **247** is controlled by valves **232**, **240**, and **242** which are controlled by a controller **210**. The double connector **181** previously described is received in a slot **214** where connections are made to the purified water connector **224** and drain terminal connector **225**. A détente mechanism **216** provides tactile and audible feedback to the operator when a home (fully connected) position of the double connector **181** is realized by inserting into the receiving slot **214**. A connector **239** serves as an adapter to permit connection to various types of drains. The connection platform **219** is also provided with sensors including a moisture sensor **249** located to detect leaking fluid in the connection platform **219**, a tilt sensor **226** to indicate the proper orientation of the connection platform **219**, and a user interface to interact with the controller **210**. The connection platform **219** may be received in a receiving slot **231** and may be formed as a unitary replaceable component. If sterility or leakage problems arise, the connection platform **219** can be replaced easily.

(89) Note that the configuration of FIG. **2I** provides a simple and clean connection between the large concentrate containers and the disposable. However, there is no reason a direct connection could not be provided. That is, the long-term concentrate disposable may be provided with its own connector to connect to a double connector **181A** or similar connector or pair of connectors. In another variation, shown in FIG. **2J**, the connection platform **219** provides a receiving connector for the concentrate connector **181B**, which may be attached to the receiving device **287** of the concentrate containers as shown in FIGS. **2F** and **2G**. In the connection platform **219** of FIG. **2J**, a pair of lines **280** and **281** connect the double connectors **181A** and **181B** so that concentrate can be drawn by the peritoneal dialysis fluid proportioner/cycler **114** according to any of the various embodiments. Effectively, the connection platform **219** in this case functions as a pass-through. The connection with double **181B** can be made on a low frequency basis according to the size of the concentrate containers, and the connection with double connector **181A** can be made on a per-peritoneal dialysis treatment basis (or other schedule) each time the mixing container **102** and associated fluid circuit (e.g. **310**) is replaced. FIG. **2K** shows another mechanism for connecting and controlling flow of concentrate to the peritoneal dialysis fluid proportioner/cycler **114**. Here connectors **289** connect to a manifold **297** with controllable valves **279** which open and close under the control of a controller **213** to permit only a selected one of the water suitable for peritoneal

dialysis from a water line **296**, the first concentrate from a first concentrate line **295A**, and the second concentrate from a second concentrate line **295B**. Each of these may be drawn through common fluid line **298** through connector **224**. Thus, the pumping actuator **125** of the peritoneal dialysis fluid proportioner/cycler **114** (FIGS. **1F** and **1G**) is able to draw each of the fluids. The controller of the peritoneal dialysis fluid proportioner/cycler **114** can be made to control the valves **279** by communicating with the controller **213** through a user interface **312**. The function of the controller **213** and user interface **312** (optional) may be the same except as otherwise indicated across FIGS. **2I**, **2J**, and **2K**. Note that a single controller of the peritoneal dialysis fluid proportioner/cycler **103** (**410**, **109**) or an independent controller common to both (e.g. as indicated by **109** in FIGS. **1A** to **1H**) may be employed for controlling the described functions of the peritoneal dialysis fluid proportioner/cycler systems **90A** through **90D**.

(90) FIGS. **2L** and **2M** show modifications of the connection platform of FIG. **2K** to provide for water and concentrate to be supplied through the common fluid line **298**. Referring to FIG. **2L**, instead of a single manifold as in manifold **297**, a pair of junctions **222** is used, one to join the first concentrate line **295A** and the second concentrate line **295B**. The concentrates are pumped respectively, according to the selection of valves **250A** and **250B** which are controlled automatically by a controller of the peritoneal dialysis fluid proportioner/cycler **103** or through a separate controller **109** or through an interface by a dedicated controller **213** of the connection platform **219** (or variations as illustrated in FIGS. **2L** and **2M**). If the fluid circuit **100B**, **110D** is used which has a testable type of filter such as the filter **115** (e.g., FIGS. **1B**, **1C**) having an air side and a fluid side separated by a membrane, then the fluid may advantageously be pumped by a pump **221** in a push configuration with respect to the filter (arranged downstream of the pump **221** as is filter **115**) rather than relying solely on a suction force provided by the pumping actuator through pumping tube segment **137**. A particular concentrate is selected by valves **250A** and **250B**. A control valve **250C** is also operated by the controller to control flow in the water line **296**. In any of the embodiments, water may be advantageously pumped by a push pump **246** if water is supplied through a filtration plant **223**. For example, water may be filtered through reverse osmosis, deionization, activated carbon, and other types of filters in filter plant **223** to generate water suitable for peritoneal dialysis from potable water. The pumps **221**, and **246** may be controlled as indicated above with respect to the valves **250A** and **250B** to operate in tandem with the pumping actuators of the peritoneal dialysis fluid proportioner/cycler (e.g., **103**). Thus, the present variant of the connection platform of FIG. **2K**, functions to select one of multiple fluids among water and one or more concentrates thereby allowing all fluids to pass into the fluid circuit through a single inlet line (as in the fluid circuit of FIG. **2E**, for example). This allows a single filter to be used for sterilization. The embodiment of FIG. **2M**, another variant of the connection platform **219** of FIG. **2K**, may be employed advantageously where a push pump such as push pump **246** (as in FIG. **2L**) is not required to draw water, for example, if instead of using the cycler to prepare dialysis fluid, a premixed dialysis fluid is connected to one of the inlets instead with suitable programming of the controller to permit flow only from one of the premixed containers at a time. Here, control valves **279** select the fluid to be drawn each time and the pump **221** draws the selected fluid, pushing it through the filter. Note that in the embodiment of FIG. **2L**, the pressure sensor **218** may be used for feedback control of the push pump **246**.

(91) FIG. **3** shows a method of manufacturing a disposable circuit such as is disclosed in FIG. **2A**. First, the concentrate containers are filled at **S10**. The concentrate containers are then sealed with frangible elements that form a hermetic seal at **S12**. This isolates the contents of the concentrate containers from the outside environment and causes them to be protected from intrusion of contaminants. Then at **S14**, the concentrate containers are connected to a remainder of the fluid circuit, for example the disposable fluid circuit **200**. The remaining portions of the fluid circuit are sealed by ensuring that end caps are placed on any line terminations that are not interconnected within the circuit. For example, caps are present on connector **185**, sample ports **168**, and

connectors **186** and **187**. Finally, optionally at **S16**, the entire circuit assembly with the concentrates, may be radiation sterilized or sterilized by other means.

(92) FIG. **4A** shows a peritoneal dialysis fluid proportioner/cycler according to embodiments of the disclosed subject matter. The present FIGS. **4A** through **4K** are generalizations of the various embodiments disclosed above for purposes of explaining the operational use thereof for preparing peritoneal dialysis fluid and for treating a patient using the structures described above. Referring now to FIG. **4A**, a peritoneal dialysis fluid proportioner/cycler **400** may correspond to any of the foregoing embodiments described for generating dialysis fluid by mixing concentrates and water. For example, note embodiments **90A-90D**. Here, the peritoneal dialysis fluid proportioner/cycler **400** generates custom peritoneal dialysis fluid according to a prescription stored in a controller **410** (corresponding to controllers described above). The prescription may be entered in the controller via a user interface **401**, via a remote terminal and/or server **403**, or by other means such as a smart card or bar code reader (not shown). The controller applies control signals to a fluid conveyer and valve network **416** and a water purifier **420** and receives signals from distal and proximal pressure sensors **413** and **414**, respectively, on a fill/drain line **450** which may be in accord with foregoing embodiments.

(93) The fluid circuit with pump and valve network **416** is a fluid circuit element with one or more sensors, actuators, and/or pumps which is effective to convey fluid between selected lines **442**, **444**, **446**, **448**, **450** and **418** responsively to control signals from the controller **410**. Example embodiments are described herein, but many details are known from the prior art for making such a device so they are not elaborated here.

(94) A multiple-container unit **441** includes a pre-filled, pre-sterilized osmotic agent concentrate container for osmotic agent concentrate **402** and another electrolyte concentrate container **404** for electrolyte concentrate. The multiple-container unit **441** also contains the mixing container **406** (which is empty) which is large enough to hold a sufficient volume of dialysis fluid for the completion of at least one fill cycle of an automated peritoneal dialysis treatment. The containers **402**, **404**, and **406** may be flexible bag-type containers that collapse when fluid is drawn from them and therefore, do not require any means to vent air into them when drained.

(95) Osmotic agent concentrate container **402**, electrolyte concentrate container **404**, and mixing container **406** are all connected by respective lines **442**, **448**, **444**, and **446** to the fluid circuit with pump and valve network **416**. The fill/drain line (or multiple lines) **450** and a drain line **418** for spent fluid (and other fluids) with a conductivity sensor **428** may also be connected to the fluid circuit with pump and valve network **416**. The fluid circuit with pump and valve network **416** also has a purified water line **431** for receiving water. The water purifier **420** may be a purifier or any source of sterile and purified water including a pre-sterilized container of water or multiple containers. In a preferred configuration, water purifier **420** may be configured as described in WO2007/118235 (PCT/US2007/066251) and US20150005699, which are hereby incorporated by reference in their entireties. For example, the water purifier **420** may include the flow circuit components of FIG. **22A** of WO2007/118235 including the water purification stages and conform generally to the mechanical packaging design shown in FIG. **24** of WO2007/118235.

(96) It should be evident that **416** is a generalization of the peritoneal dialysis fluid proportioner/cycler **114** as well as elements of a fluid circuit such as fluid circuit **112** and connection platform **219**. It should also be evident that **402** and **404** represent concentrate containers according to any of the disclosed embodiments including the concentrate containers **101** and **102**, **262** and **264**, **105A** and **105B**. The mixing container **406** corresponds to any of the mixing container embodiments (**102**) described above. Other elements will be evident from their description with the understanding that the figures represent generalizations thereof for purposes of describing the function. It should also be understood that the number and type of concentrates may differ from the present figure which is disclosed as an example, only. It should also be evident that the examples of concentrates discussed herein are glucose and electrolyte concentrates but they

could be one or other multiples or other concentrates in other embodiments. Also, the osmotic agent concentrate or glucose concentrate is presumed here to include an electrolyte concentrate marker to permit the concentration of osmotic agent to be inferred from a measurement of conductivity of diluted agent with a priori knowledge (stored in a memory used by the controller) of the ratio of osmotic agent concentrate to electrolyte concentrate in the osmotic agent concentrate. See US20150005699. In alternative embodiments, the osmotic agent is not provided with an electrolyte marker and the peritoneal dialysis fluid proportioner/cycler **400** may rely on volumetric proportioning for the transfer of osmotic agent. Note also that the order of concentrate addition may be reversed, with electrolyte being added first.

(97) FIG. **4B** shows a preliminary stage of fluid preparation prior to peritoneal dialysis treatment according to an embodiment of the disclosed subject matter. The controller **410** reads a prescription and generates a command, responsive to a peritoneal dialysis treatment preparation initiation command, to flow osmotic agent concentrate from osmotic agent concentrate container **402** to the mixing container **406**. The command is applied to the fluid circuit with pump and valve network **416** to connect the osmotic agent concentrate line **442** to the batch fill line **444** and also to convey the osmotic agent concentrate into the mixing container **406**. This may be done by one or more valve actuators and one or more pumps that form the fluid circuit with pump and valve network **416**. The fluid circuit with pump and valve network **416** may be configured to meter the quantity of osmotic agent concentrate precisely according to a predicted amount of dilution by electrolyte concentrate and water to produce the desired prescription fluid. The metering may be performed by a positive displacement pump internal to the fluid circuit with pump and valve network **416** or other means such as a measurement of the weight of the osmotic agent concentrate container **402** or the mixing container or a volumetric flow measurement device.

(98) In an alternative embodiment, part of the water (less than the total used for dilution as discussed below with reference to FIG. **4C**) is added to the mixing container first, before the osmotic agent concentrate and electrolyte concentrates (if needed) are pumped into the mixing container.

(99) Referring now to FIG. **4C**, a dilution stage is performed using the peritoneal dialysis fluid proportioner/cycler **400**. The controller **410**, in response to the prescription, generates a command to flow purified water from the water purifier **420** to the mixing container **406**. The command is applied to the fluid circuit with pump and valve network **416** to connect the purified water line **431** to the mixing container **406** to add a measured quantity of water to dilute the osmotic agent concentrate in the mixing container **406**. The controller **410** may control the fluid circuit with pump and valve network **416** to ensure the correct amount of water is conveyed. Alternatively, the water purifier may incorporate a flow measurement device or metering pump or other suitable mechanism to convey the correct amount of water. The controller **410** may be connected to the water purifier **420** to effectuate the dilution result. The fluid circuit with pump and valve network **416** may also be configured to circulate diluted osmotic agent concentrate solution through lines **444** and **446** either simultaneously with the dilution or after the diluting water has been transferred to the mixing container **406** according to alternative embodiments. The circulation mixes the contents of the mixing container **406**.

(100) The relative amounts of water, osmotic agent concentrate, and electrolyte concentrate may be realized based on the ratiometric proportioning properties of the pump. Since a single pump tube is used to convey all the liquids into the mixing container, most sources of offset from predicted pumping rate (based on shaft rotations, for example) to actual pumping rate affect all the fluids roughly equally.

(101) Referring now to FIG. **4D**, the diluted osmotic agent concentrate solution in the mixing container **406** is tested to ensure that the correct concentration of osmotic agent is achieved. In an embodiment, the osmotic agent concentrate **402** has an amount of electrolyte concentrate to generate a conductivity signal using the conductivity sensor **428** when fluid from the mixing

container **406** is conveyed by the fluid circuit with pump and valve network **416** to the drain line **418** past the conductivity sensor. The amount of electrolyte concentrate pre-mixed with the osmotic agent concentrate may be the lowest ratio of electrolyte concentrate to osmotic agent concentrate that a predetermined prescription may require. The fluid circuit with pump and valve network **416** may perform the function using one or more valve actuators and one or more pumps that form the fluid circuit with pump and valve network **416**. The fluid circuit with pump and valve network **416** may be configured to meter the quantity of water precisely or the function may be provided by the water purifier **420**. The controller **410** may add additional water or osmotic agent concentrate and test the conductivity again if the measured concentration of osmotic agent and/or electrolytes, if applicable, is incorrect. In addition to using a combined osmotic agent and electrolyte concentrate in osmotic agent concentrate container **402**, in an alternative embodiment, the osmotic agent concentrate container **402** holds osmotic agent concentrate with no electrolytes and osmotic agent concentration is optionally measured directly by other means such as specific gravity (hydrometer), refractive index (refractometer), polarization, infrared absorption or other spectrographic technique.

(102) FIG. **4E** shows an electrolyte concentrate addition stage of fluid preparation prior to peritoneal dialysis treatment according to an embodiment of the disclosed subject matter. The controller **410** reads a prescription and generates a command to flow electrolyte concentrate from container **404** to the mixing container **406**. The command is applied to the fluid circuit with pump and valve network **416** to connect the electrolyte concentrate line **448** to the mixing container **406** fill line **444** and also to convey the electrolyte concentrate into the mixing container **406**. This may be done by one or more valve actuators and one or more pumps that form the fluid circuit with pump and valve network **416**. The fluid circuit with pump and valve network **416** may be configured to meter the quantity of electrolyte concentrate precisely according to a predicted amount of dilution by osmotic agent concentrate and water that has been previously determined to be in the mixing container **406**, to achieve the prescription. The metering may be performed by a positive displacement pump internal to the fluid circuit with pump and valve network **416** or other means such as a measurement of the weight of the electrolyte concentrate container **404** or the mixing container **406** or a volumetric flow measurement device.

(103) Referring now to FIG. **4F**, the electrolyte concentrate may be mixed using the batch fill and drain lines **446** and **444** in a closed loop. If necessary, depending on how much dilution was performed during the osmotic agent concentrate dilution process, further dilution may be performed as described above. The final formulation may be achieved by the process illustrated in FIG. **4F**. Then, as illustrated in FIG. **4G**, the final electrolyte concentration of the mixture in mixing container **406** may be determined with a conductivity sensor **428** by flowing a sample therethrough.

(104) Although gravimetric and tracer/conductance sensing were described as devices for ensuring proper proportioning and dilution rates for achieving target prescriptions, it should be clear that any embodiments of a peritoneal dialysis fluid proportioner/cycler disclosed herein may employ ratiometric proportioning as well, particularly where positive displacement pumping is employed. Ratiometric proportioning takes advantage of the volumetric repeatability and predictability of certain pumps. For example, a particular pump can deliver a highly repeatable volume of fluid for a given number of pumping cycles (pump rotations for a peristaltic pump or cycles for a diaphragm pump, for example). If all dialysis fluid components (water, osmotic agent concentrate, and electrolyte concentrate, for example) are delivered to the mixing container using the same pump, including, for example, the pumping tube segment of a peristaltic pump, then the volume ratios of the components will, after adjustment for potential flow path and/or viscosity differences as described below, be fully determined by the number of pump cycles used to convey each component.

(105) Ratiometric proportioning may supplement or substitute for measurement of the fluid conductance or density or other measurements. To convert the number of pump cycles to actual displaced mass or volume, a calibration may be performed and/or flow path (including fluid

properties) compensation parameters may be employed. The flow path compensation parameters may be respective to each particular fluid flow path and/or fluid type, or may be identical for all fluid paths and fluid types. To provide enhanced accuracy, one or more pump calibration and/or flow path compensation parameters may be generated through a calibration procedure. Typically, flow path compensation factors will be established and stored in non-volatile memory. Typically, one or more flow path calibration procedures will be performed when the peritoneal dialysis fluid proportioner/cycler is used by a patient. The calibration procedure may be performed after each new fluid set is installed, or before each batch preparation cycle, or even multiple times during the preparation of a single batch. A disposable fluid set may be installed every day. The calibration procedure may be done using water. The calibration may sequentially pump fluid through one or more of the stages provided in Table 1.

(106) TABLE-US-00001 TABLE 1 Example stages for sequentially pumping fluid during calibration

From Water source	Drain Mixing container	Drain Osmotic agent concentrate container	Drain Electrolyte concentrate container	Drain Patient access	Drain Osmotic agent concentrate container	Mixing container	Electrolyte concentrate container	Mixing container	Water source	Mixing container
-------------------	------------------------	---	---	----------------------	---	------------------	-----------------------------------	------------------	--------------	------------------

(107) In the calibration procedure, fluid is pumped between any or all of the paths identified above. A separate calibration coefficient may be generated for each of the paths. The calibration coefficient may be stored in a memory or non-volatile data store, for example, as a parameter representing the number of ml/per pump rotation (or diaphragm pump cycle), or as a proportionality ratio relative to a particular reference flow path. The actual fluid quantity transported during the calibration step may be measured by any suitable device (flow sensor) including volume or mass measurement devices or direct flow rate measurement with integration, for example, using laser Doppler velocimetry, thermal transit time, magnetohydrodynamics, propeller hydrometer, positive displacement flow measurement, differential pressure through a resistance such as a venturi, nozzle, orifice plate, or other flow obstruction, variable area or rotameter, pitot or impact tube, vortex shedding frequency counting, ultrasonic, or other device. A particularly advantageous device for flow calibration is to measure the transit time of a fluid property perturbation between spaced fluid property sensors as described below. Any of the disclosed embodiments may employ a flow sensor in which at least the portion of which that carries fluid is disposable so that the flow rate (or total displaced fluid quantity) can be input to a controller while allowing the use of a disposable fluid circuit. Examples include an ultrasonic soft tube flowmeter made by Strain Measurement Devices SMD that non-invasively measure flow in soft tubing by means of slotted transducers in which a length of tubing can be inserted during fluid circuit installation. For cartridge embodiments, the PD cycler can employ a moving transducer stage that engages an exposed tube length of the cartridge after passive insertion of the cartridge.

(108) The pumping system may also be sufficiently repeatable in a way that allows precise ratios to be established without calibration, depending on the predefined tolerances. If the manufacturing tolerances, including materials, are sufficiently controlled, a desired level of control over ratios may be achieved without in situ (point of care) calibration. A particularly sensitive component in terms of guaranteeing repeatability is the pumping tube segment of a peristaltic pump. In a first embodiment, the peristaltic pump tube segment is made from a material whose mechanical and material tolerances are controlled within predefined limits. The lengths of the tubing circuit elements and mechanical parameters are also controlled within respective predefined limits. A calibration may then be done outside the peritoneal dialysis treatment context, e.g., in the laboratory, to calculate precise values to convert pump cycles to fluid quantity transferred for a single lot of replaceable fluid circuits. The calibration may be done for multiple lots. The calibration may also be done for each fluid circuit. The calibration may also be done by the peritoneal dialysis fluid proportioner/cycler for each fluid circuit. The calibration may also be done for each batch of peritoneal dialysis fluid prepared by the fluid circuit.

(109) Referring to FIG. 4H, subsequent to the preparation of the contents of the mixing container **406** as described above, the fluid circuit with pump and valve network **416** may be configured to drain the patient **411** depending on the patient's prior status. Spent dialysis fluid may be withdrawn by the fluid circuit with pump and valve network **416** and conveyed through the drain line **418**. Then, the contents of the mixing container **406** may be conveyed as illustrated in FIG. 4K to the patient. Here the controller **410** has configured the fluid circuit with pump and valve network **416** to flow fluid to a patient **412**.

(110) Referring now to FIG. 5A, the double connector of **181**, **181A**, **181B** is shown in detail as the connector embodiment **500**. A single monolithic member has a shape with at least one window, where two windows are shown one of which is indicated as window **512**. The body **506** has a ridge **507** that overhangs the frame **506** to permit the frame **506** overall to be grasped easily by a user, for pushing or pulling, to connect ports **515**, **516** to ports of a device (e.g., **219**) to which lines **508** and **510** of a fluid circuit **530** are to be connected. A releasable port cover **502** (see also cap **180**) seals ports **525** and **526** to prevent contamination thereof. The window **512** provides access to cut and seal elements that seal and cut the lines **508**, **510** when the double connector **500** is to be replaced. Lines **508** and **510** pass through holes **514** in the frame **506**. FIG. 5B shows the double connector **500** after cutting and sealing, the sealed ends of one end of cut tubes forming stubs indicated at **520** and **521** and the opposing ends at **522**, **523**. The ends **522**, **523** remain attached to a fluid circuit **530** which is to be replaced. The stubs **520**, **521** remain attached to a resulting stub connector **519** which can remain attached to a connected device, after use, so as to act as a cover and seal against environmental contamination of a connected device, such as connection platform **219** connectors **224** and **225**. Here, the protected ports of the connected device are indicated at **525** and **526**. Although two channels are shown, it should be evident that the configuration may be modified to provide connections for any number of channels including one or more than two.

(111) Referring to FIGS. 5C and 5D, the use of a connector **500** (which may be a double connector) including a cut and seal operation in which a portion **540** of a connector (e.g., double connector **181**) is left in place to act as a sterile barrier begins with the removal of a sterile barrier-type cap from the end of the connector **S32**. For example, the sterile barrier may take the form of the double releasable port cover **502**. Next, as **S33**, the sterile barrier formed by a previous connector which was cut and sealed (see FIGS. 6A-7D and elsewhere in the present disclosure) is removed, and a new replacement connector of the same form as the connector **500** is attached **S34**. Then the circuit connected by means of the new connector is used until it is expired **S35**. A cut and seal operation is initiated at **S36**, resulting in the separation of the fluid circuit (cut and sealed forming the stubs **520**, **521** and ends **522**, **523**) and a new portion **640** of the new connector to be left in place to act as a sterile barrier. The cut and seal operation may include cooling the cut ends of the tube to speed the operation so that a delay for sufficient passive cooling is not required. The latter may also permit the cutting heads to act as a mechanism for gripping the stubs **520** and **521** to prevent them being removed before cooling. See, for example, the embodiment of FIGS. 6E and 6F which have a broad flat interface for gripping the ends of the cut tube **666**.

(112) FIG. 5E shows features for a variation of a double connector **501** that protects against contamination. A male connector portion **541** mates with a female connector portion **543**. Ports **526** (male) pass through openings **547** of female ports **548**. A pin **545** is provided on the male connector portion **541** that is received within a recess **546**. The female ports **548** open in a wall **524** as does an access **549** of the recess **546**. Lines **544** connect to the male connector portion **541**. The remainder of the double connector **501** is as described with reference to connector **500** shown in FIGS. 5C and 5D. The pin **545** may be sized to prevent the ports **526** from contacting a flat surface inadvertently and thereby prevent contact contamination. The pin **545** may also be shaped asymmetrically to prevent incorrect orientation of the connectors. In variations, the double connector **501** may be modified such that it has a greater or lesser number of tubes **508**, **510**, and connectors **547**. Also, the number of pins **545** and recesses **546** may differ from what is shown. For

example, two pins and recesses may be provided at the edges 527 with or without the illustrated pin and recess. Note that in variations of the embodiments, the male and female connectors may be swapped or mixed on a given side of the male connector portion 541 and the female connector portion 543. One or more pins 545 may be provided on either side or mixed, as may openings 547.

(113) FIG. 6A shows mechanical aspects and a control and sensor system for the cut-and-seal devices with actuation, temperature, and force control features, according to embodiments of the disclosed subject matter. FIGS. 6B through 6D show a sealing and cutting operation provided by the embodiment of FIG. 6A. A pair of jaws 11 and 18 close on opposite sides of a tube 50 to cut and seal the tube 50 such that the tube 50 is divided into two parts with ends 54A and 54B sealed. The jaw 11 receives heating or cooling through a conveyance 20A or multiple conveyances 20B which may be electrical conductors for resistive heating element 14 or a combination of heating and cooling heat transfer fluids such as molten salt and refrigerant. The source of heat/cool or current supply is provided by a source 6. Either jaw 11 or 18 may be heated to achieve the described effect in alternative embodiments. A drive 2 under control of a controller 4 moves at least one of the jaws 11 and 18 toward the other or together. Temperature sensors 16 and 12 may be provided to regulate the temperature and provide feedback control for a cutting and sealing operation. The controller 4 may receive the temperature signals and control the drive 2. A force sensor 40 may indicate to the controller the magnitude of force applied through the tube 50 for feedback control of a cutting operation or for error detection (out of bounds force, for example). The cutting heads can have various shapes as shown in FIGS. 7A-7D. FIG. 7A illustrates opposing jaw shapes with jaw 604 having a flattened tip 606 and jaw 602 having a flat surface. FIG. 7B illustrates opposing jaw shapes with jaw 614 having a sharp tip 616 and jaw 602 having a flat surface. FIG. 7C illustrates opposing jaw shapes with jaw 624 having a rounded tip 626 and jaw 622 having a flat surface. In FIG. 7D, a sharp ridge 636 is provided on jaw 634 and a recess 637 on jaw 635. An alternative jaw 632 that may be used with the jaw 634 has a flat surface 638.

(114) FIGS. 6E and 6F show a cut and seal arrangement in which the cutting and sealing portions move partially independently. A cutting knife 662 cuts a tube 666 when a jaw 658 pushes up against it. The jaw 658 or the jaw 654 (or both) may be heated to melt the tube 666 such that tube is cut and sealed in a single operation. A spring 664 ensures that a predefined amount of force is maintained for heating the tube 666 during the closing of the jaws. FIG. 6G shows a configuration in which the jaws are rounded elements 670 and 672 which may cut and seal the tube 666 where either or both jaws may be heated. Cooling in the above embodiments may be provided to cool the jaws and the tubing cut ends for safety or speed of completion. The arrangements of FIGS. 6A through 6F are details that may apply to the cutting and sealing actuator 212.

(115) Referring to FIGS. 8A and 8B, a multiple chamber portion 200D (e.g., FIG. 2A) of disposable fluid circuit 200 is shown in greater detail. Features of the present embodiment may be applied to other fluid circuit portions as well, including the single mixing container 300C (FIG. 2E). Concentrate containers 953 and 954 and mixing container 952 are formed from a single pair of sheets by welding seals 962, shown as a pair of lines all around the depicted structure. Concentrate fill tubes 964, concentrate outlet tubes 956 and 957, mixing container inlet 948 and outlet line 9541, as well as a mixing container sample tube 958 are all welded as the seals 962 are closed by solvent bonding, thermal welding, polymer fill-bonding, ultrasonic welding, or other means. The entire structure may then be folded as shown in FIG. 8B to form a compact structure before or after a predefined quantity of concentrate is conveyed through the concentrate fill tubes 964 and the latter sealed.

(116) A nozzle 950 may terminate the mixing container inlet 948 tube which extends into the chamber. This causes the extended part of the tube to whip around to inject incoming fluid around the mixing container 952 to agitate the contents and promote effective mixing of the contents. The mixing container sample tube 958 may be terminated by a septum to permit the insertion of a hypodermic needle. The length of the extended part may be at least 3 diameters into the container.

The length may be five, 7.5, 10, or 15 diameters. The length may be between 3 diameters and 25 diameters. The length may be at least 5 diameters. Here, the term diameter refers to the tube outer diameter. Note that another alternative is for the inlet line to have a nozzle but no extended part, that is, the nozzle may be located at the wall of the mixing container and be aimed toward the center of the mixing container.

(117) FIGS. 8C through 8F show various features to promote mixing of fluids in a mixing container according to embodiments of the disclosed subject matter. A mixing container 952 uses a single mixing container inlet and outlet line 949 that functions as a mixing container 952 inlet and outlet line 949. FIG. 8C shows a fluid outgoing from the mixing container 952 and FIG. 8D shows fluid incoming into the mixing container 952. A two-way header 924 has a check valve 918 that allows outgoing fluid to be drawn through an opening 920 into the mixing container 952 inlet and outlet line 949 but blocks flow out of the opening 920. When fluid is pumped into the mixing container 952, the check valve 918 closes and all of the flow is forced through a nozzle 924 so that it emerges at high velocity from a nozzle opening 922 as illustrated in FIG. 8D. As result, mixing is promoted and a substantial convective flow or jet is generated to transport the incoming flow to locations remote from the opening 920, thereby promoting mixing. A similar effect is obtained in the embodiment of FIG. 8E in which incoming flow is released from a tube 937 inside the mixing container 952 from an opening 930 remote from the opening 920. In this embodiment, also, a check valve 918 causes the incoming and outgoing flows to take different paths. Note that a check valve, although not shown, may be incorporated in the flow path of the tube 937 or the nozzle 924 to block flow through opening 922 or 930 when fluid is pumped out of the mixing container 952 to enhance the separation effect between the ingoing and outgoing flows. FIG. 8F shows an embodiment in which the container inlet and outlet line 949 attaches to a header tube 934 that is similar in structure to a peritoneal catheter in that it has openings distributed along a portion of its length such that ingoing flows are distributed. Such a header tube 934 may be used as a single container inlet and outlet line as for 949 or, in combination with a dedicated outlet line 9542, as an inlet line. In the foregoing embodiments, instead of a check valve, a flexible member such as a reed or flap valve as indicated in FIG. 8G, which creates greater resistance for flow in one direction than another, may be employed. So flow does not necessarily need to be halted altogether in a selected direction to achieve substantially the above effect. In FIG. 8G, a single part that may be formed, for example, by 3D printing, assembled from parts, or molded directly has a flap 921 that bends in response to both suction and pressure resulting from pumping fluid from and to the mixing container 952, causing flow out of the mixing container to be drawn through the inlet covered by the flap 921 and to be projected by the nozzle 924 when fluid is pumped into the mixing container as described with reference to FIGS. 8C and 8D. Here the flap 921 need not fully close or open but may, in embodiments, merely create a differential resistance to ingoing and outgoing flows such that fluid pumped into the mixing container is projected away from the location where it is drawn in, thereby facilitating the mixing process.

(118) FIG. 4L illustrates schematically a variation of the peritoneal dialysis fluid proportioner/cycler 400 of FIG. 4A with the addition of an accumulator 447 connected by an accumulator line 449 to allow a pump such as a peristaltic pump according to any of the disclosed embodiments, to provide mixing with a single mixing container line 445 connecting the mixing container 406. The controller 410 pumps fluid from the mixing container 406 to the accumulator 447 back and forth multiple times to mix the contents of the mixing container 406. This is in contrast to the disclosed embodiments in which two lines connect the mixing container 406 to the fluid circuit with pump and valve network 416. As indicated, use of a pump that has the ability to accumulate fluid, such as a diaphragm pump, may allow fluid to be pumped into and out of the mixing container 406 without a separate accumulator 447, by pumping fluid into the mixing container 406 from the diaphragm pump internal volume. Reference numeral 451 points to the arrows indicating spaced ingoing and outgoing flows to/from the mixing container that may be

provided by the foregoing embodiments of devices for separating (at least partially) the ingoing and outgoing flows.

(119) Referring to FIG. 9A, a manifold **900**, which functions as manifold **174** (e.g., FIG. 2A), has two chambers **982** and **981** defined by the shape of a rigid housing **989** that is sealed by a welded or bonded film **986**. Rigid housing **989** may be formed by casting and an internal volume sealed by the bonded film. The film has regions **987** overlying the housing for pressure detection. Pressure transducers (not shown) contact the regions **987** and detect a force applied by pressure within the chambers **982** and **981** at either end of a pumping tube segment **985** which connects the two chambers **982** and **981**. Respective ones of ports **983**, for the various fluids described herein according to the different embodiments, convey fluid to respective ones of the chambers **982** and **981**. Tubes may be friction fitted or bonded to the ports **983**. The ports **988** have air-lines attached to them and these are respectively fluidly coupled to air ports **990** which sealingly engage pressure transducers (See **146** and **147** of FIG. 2B). In other embodiments, the rigid housing **989** is replaced with a fully enclosed housing (not shown) with pod type pressure sensors embedded in them and there is no film required for sealing the structure closed.

(120) Referring to FIG. 9B, a dialysis fluid line **172** has a pre-connected fill-drain line **160** and an air-line **129** as well as a pressure-sensing pod **162** which has an internal diaphragm which is displaced responsively to pressure changes in the pre-connected fill-drain line **160** near the patient connector **995**. Movement of the internal diaphragm compresses or expands an air volume in the air-line **129** which is conveyed to a connector **181**. The patient connector **995** connects to a peritoneal catheter. The proximal end **997** of the pre-connected fill-drain line **160** is attached or bonded to a respective one of the ports **983**.

(121) Referring now to FIGS. 10A and 10B, a cartridge portion **910** of the fluid circuits according to the various embodiments provides the manifold and the pumping and pressure sensing portions previously described. The cartridge support **169** may be made from a single panel **912** that is folded at a pair of creases indicated at **914**. The panel **912** portions contain recesses for all the tubes held between them precisely controlling their positions. A compartment is defined by the shapes of the panels to hold the rigid housing **989**. FIG. 2A shows an alternative embodiment in which the manifold **174** is connected by a battery of tubes indicated collectively at **200C** so the double panel structure is not directly attached to the manifold **174**. FIG. 11 shows the single vacuum formed panel **912** before it is closed about the pair of creases **914**. FIG. 11 otherwise shows a complete fluid circuit **909** including how the features of 8A through 10B are assembled in a completed fluid circuit **909**.

(122) In any and all of the foregoing disposable fluid circuits, the components may be integrally-attached, meaning the components may be permanently bonded or otherwise locked together as delivered for use except for removable caps on inlets and outlets. In embodiments, only a single cap may be required to connect one or more concentrate inlets and a single cap may be required to connect a peritoneal dialysis catheter to the integrally-attached fill/drain line. This helps to ensure that a fluid circuit as-delivered will have less of a chance of being contaminated as a result of having only a small number of connections.

(123) Generally, in systems that process or treat fluids and return processed or treated fluids to a patient, it is necessary to eliminate air from the fluid circuit prior to and/or during use to avoid introduction of air into the individual undergoing treatment. This may be accomplished by “priming” the fluid circuit which refers to circulating a fluid in the fluid circuit so that the fluid circuit is filled prior to treating a patient.

(124) In the disclosed embodiments, preparing a complete batch for a PD treatment cycle, which is hereinafter referred to as the “main” batch, may take a certain minimum amount of time depending on the number of components that need to be mixed, the amount of fluid required for treatment of a patient, the need for proportioning error recovery, etc. For example, preparing a full batch of peritoneal dialysis fluid may take a significant fraction of an hour. Generally, the full batch will

also be used for priming the fluid circuit when the new fluid circuit is loaded. Since the fluid circuit generally should be primed before being connected to the patient, the patient would have to start preparation of a full batch and then wait until the full batch is prepared before connecting and then either getting in bed or attending to some other activity such as relaxing. Thus, a patient desiring to connect to the cyclor may be required to perform initial activities including attachment of a new fluid circuit to the cyclor and then wait for a full treatment batch to be fully prepared before connecting to the fluid circuit. In a situation where the patient is tired and wishes to connect quickly in order to go to sleep or perform some other activity, this delay may be inconvenient. In particular, this delay may cause lost sleep and impact patient health.

(125) In embodiments, a priming batch which is considerably smaller in volume than the treatment batch is first prepared and used for priming the fluid circuit so that the patient does not have to wait for the full batch to be prepared before the patient connects to the fluid circuit. The smaller volume of the priming batch may be just sufficient to prime the fluid circuit. In alternative embodiments, the smaller batch has a different composition which may be faster to generate than the composition of the batch used for treatment. For example, in embodiments in which multiple concentrate components are diluted by combining with water to form a treatment batch, a subset of the multiple concentrates and water is used to form the priming batch. In embodiments, the subset may include only water. In further embodiments, the priming fluid may be a blood-normal fluid, or formed from a concentrate that is different from the composition of the treatment fluid. For example, the single component may be a saline fluid or concentrate. Since the priming fluid is used solely for priming, there is minimal advantage to including an osmotic agent concentrate as does regular PD fluid.

(126) The disposable fluid circuit that includes a small priming batch or concentrate container may be pre-attached and sealed to the disposable. After priming, the priming fluid may be flushed from the fluid circuit to the drain along with the spent dialysis fluid during initial treatment stage so that the composition of the dialysis fluid supplied to the patient is not altered by the differing composition of the priming fluid. Thus, the method of priming may include, following priming the fluid circuit, including the fill-drain line, pumping spent dialysis fluid from the patient immediately to the drain and flushing any portions of the fluid circuit containing residual priming fluid with the first treatment batch of fluid prior to filling the patient with a fresh batch. In this way, the quantities and proportions of fluid for the treatment do not have to account for any impact of the composition of the priming fluid. This can be the case irrespective of the type of fluid used, be it saline, pure electrolyte concentrate, purified water, or some other fluid.

(127) In further embodiments, the disposable fluid circuit is provided with a container of priming fluid. The latter may be filled with a single or multi-component concentrate which is further diluted in preparation for priming or it may be provided fully diluted and ready for use. The priming fluid container may be pre-attached as described with reference to the concentrates described in the disclosed embodiments. Note that a single component concentrate container may be provided for priming-only because the weight and volume-saving benefits of the embodiment may be less important for the small volume of priming fluid than for treatment.

(128) Accordingly, embodiments allow for quick priming and patient connection. In some embodiments, the quick priming may be provided as a user-selectable option, and if the user does not select the option, the system simply starts by preparing the treatment batch and using it for priming the fluid circuit.

(129) In embodiments, the priming batch is mixed in the same disposable unit as used for the treatment batch. For example, with reference to FIG. 1A, the dialysis fluid preparation/cyclor unit **103** may generate the priming batch by metering concentrate from concentrate containers **101** and adding them to, and diluting them with purified water in, the mixing container **102**. However, in alternative embodiments, the priming batch may be stored separately from the treatment batch. In embodiments, the priming batch is formed from a subcombination of multiple components used for preparing a treatment batch. For example, the priming fluid may be formed from only the

electrolyte concentrate component and water without mixing the osmotic agent concentrate. In this way time may be saved by only diluting and mixing a single component. In such embodiments, the composition of the single component used to make the priming batch may be selected such that when mixed with the second component it forms a dialysis fluid that is suitable for treatment and when mixed with water alone, it forms a desired blood-normal fluid.

(130) FIG. **12** shows a method of priming a fluid circuit according to embodiments of the disclosed subject matter. At optional step **1202**, a controller determines that the patient has selected an option for quick priming, for example, by activating a soft or hard key on a user interface in communication with the controller. Alternatively, quick priming may be performed by default and without receiving any explicit indication from the patient. If the patient chooses not to do quick priming, the method of FIG. **12** is not executed. In embodiments, the controller may request an indication of whether the patient is full or dry, meaning whether the patient's peritoneum is already full and therefore to be drained initially, or empty (dry) in which case the peritoneum is not to be emptied. If empty, the quick prime operation is skipped and a full batch of treatment fluid is made. The purpose of quick prime is to allow the drain cycle to be initiated quickly, so the patient doesn't have to wait for the cyclor to prepare a full batch of treatment fluid. For example, this may be done at a time the patient is going to bed.

(131) At **1204**, the controller determines a composition for the priming fluid. For example, the composition may be based on a prescription or other data stored on a memory device connected with the controller. In embodiments, the composition may be configured by a physician or other healthcare professional via the user interface or over a network communication with a server or a central control system at a medical facility. In embodiments, the composition may be the same as used for the treatment of the patient, another composition as discussed elsewhere, or it may be water or saline solution.

(132) At **1206**, the controller determines a required volume of priming fluid. The determination may be a predefined volume stored in a non-volatile data store connected with the controller. In embodiments, the required volume may be configured by a physician or other healthcare professional via the user interface or over a network communication with a server or a central control system at a medical facility. In embodiments, the required volume may be based on physical properties of the fluid circuit such as the length and diameter of fluid lines.

(133) At **1208**, the controller operates a dialysis fluid preparation/cyclor unit and corresponding connections/valves/pumps to prepare the required volume of the priming fluid according to the composition. For example, with reference to FIG. **1A**, the dialysis fluid preparation/cyclor unit **103** may generate the priming batch by metering concentrate from concentrate containers **101** and adding these to, and diluting them with purified water, in the mixing container **102** according to methods described elsewhere in the present disclosure or other methods such as described in US 2015-0005699A1, a copy of which is attached hereto as an appendix.

(134) At **1210**, the controller primes the fluid circuit with the priming fluid. The priming may be performed by pumping fluid as in the preparation phases described above to generate a batch of smaller size, and then pumping the resulting mixed batch through the fill/drain line (e.g., **450**, FIG. **4A**) until some reaches a point near the end of the fill/drain line. In embodiments in which water is used alone, water may be pumped into the mixing container and then into the fill/drain line, thereby filling the flow switching mechanism. The described flow diverters may also permit the water to flow from the mixing container to the drain thereafter, in preparation for making the first batch of a sequence for treatment.

(135) At **1212**, the controller indicates to the patient that the fluid circuit is primed and ready to be connected. The indication may be performed by generating a visual and/or audible alarm and corresponding text on the user interface. At this time, the patient may connect to the fluid circuit. Alternatively, the patient may indicate when fluid has reached the end of the fill/drain line by inputting a command through the user interface, the result of which would be to ready the system to

begin treatment after the patient indicates s/he has made a connection to the peritoneal access.

(136) At **1214**, the controller may confirm that the patient has connected the patient access to the fluid circuit, for example by receiving an indication/confirmation via the user interface and/or by receiving sensor inputs (proximity sensors, switches, etc.) that indicate a physical connection of the fluid circuit to a catheter. The distal pressure sensor may be used by the system to confirm connection by having the controller detect and respond to pressure signals from patient respiration or pulse. At this time, the patient may place the system in a treatment mode at **1216** and allow automated treatment to proceed without attending to the system any longer. For example, the patient may go to sleep to receive a nocturnal treatment.

(137) Referring to FIG. **13A**, a fluid circuit has an attached priming fluid container **706**. The fluid circuit includes a flow switching circuit **708** with a manifold and a pre-attached fill/drain line **710**. Concentrate containers **703** and **704** are diluted as described to form a treatment batch which fills a mixing container **702**. A priming concentrate may be provided in container **706** or, alternatively, a container of fully diluted priming fluid **707** is attached. The latter may be used as described above. FIG. **13B** shows a fluid circuit that may be used to provide a priming batch by mixing a special composition from larger containers **724** of concentrate or fully diluted container **725** alternatively. The configuration may employ a multiple connector **726** as described elsewhere for connection to the long-term concentrate containers **720** and **722** for treatment batch preparation. In yet other embodiments, the fluid circuit may have a pre-attached priming fluid container (concentrate or diluted) and the multi-use container **724** or **725** may be omitted.

(138) In alternative embodiments, quick priming may be done with priming fluid that remains in the mixing container after a normal priming process is used to prime the fluid circuit. The normal fluid circuit priming process begins with pumping water into and through the fluid circuit including circulating fluid into and out of the mixing container, at least partly in order to break-in the pumping tube segment, ultimately leaving a volume of, for example, four hundred ml. in the mixing container. The sterilizing filter protecting the water inlet according to any of the foregoing embodiments may then be tested to confirm its integrity after the priming operation. If the filter integrity is confirmed by the testing, this indicates the fluid in the mixing container which has passed through the sterilizing filter, the mixing container and fluid circuit being sterile as initially provided, must also be sterile, at least with a high certainty. That is, the only means by which contaminants can enter the mixing container, which is pre-sterilized, is through at least one filter (see foregoing embodiments), which essentially guarantees the contents are sterile. The quick prime operation may be performed using a portion of the contents of the mixing container. Other limitations of the quick priming as discussed above may be as indicated except for the use of concentrate.

(139) Note that the quick prime procedure is contraindicated if the patient begins a treatment without a full peritoneal cavity. The term “full” in this context does not specify a particular volume, except that it should be sufficient for the treatment following the quick prime to begin with an initial drain cycle.

(140) In any of the claimed embodiments identifying an element, it is understood that the identification of an element does not preclude the claims covering embodiments having multiple ones of the elements. For example, in any of the claimed embodiments identifying a concentrate line or concentrate container, it is understood that the identification of a single concentrate line or container does not preclude the claim covering multiple concentrate lines or concentrate containers. Further embodiments are contemplated in which multiple ones of the claimed elements may be provided to form additional embodiments, for example, the concentrate lines or containers. The same applies to method claims where additional steps may be provided to form new embodiments, where the additional steps repeat an operation performed by a recited step and act upon another material or article in equivalent fashion, for example, an additional concentrate.

(141) Referring now to FIGS. **15A-15C**, method and system embodiments for proportioning

concentrates and water are described. FIG. 15A shows a flow chart of the proportioning procedure next to a schematic diagram of the mixing container contents **320**. The diagram at each stage of processing has rows **321** through **336**, each of which shows a figurative representation of components of electrolyte, osmotic agent, and the water contained by the container after addition of a fluid. In this example, the osmotic agent concentrate contains both osmotic agent with water so its addition to the mixing container adds osmotic agent, electrolyte, and the water contained in the osmotic agent concentrate. See row **322** column **338**. Row **321** shows the mixing container contains water alone after addition of water. Row **322** shows the components of electrolyte and osmotic agent plus the water contained by the osmotic agent concentrate all of which are combined to form the osmotic agent concentrate plus electrolyte marker added at **S108**.

(142) The rows **322** through **336** are aligned with the process stages **S106** through **S122** and each row shows a composition that exists, or is achieved by, the corresponding process stage. Columns **338**, **339**, and **340** show the concentrates and water components. The concentrates are further broken down in the columns to indicate the constituents thereof. Again, the osmotic agent concentrate **338** has constituents water, osmotic agent, and electrolyte used as a marker. These constituents are indicated by “E,” “O,” and “H₂O.” The electrolyte concentrate **339** has constituents electrolyte and water indicated by “E” and “H₂O.”

(143) In an initial operation **S100** the fluid circuit, including the manifold, if one is present (the method is not exclusive to the mechanical features of the foregoing embodiments as will be evident from the presentation), is primed with water and the water is circulated through the mixing container to break-in the pump tube segment. The sterilizing filter, through which water is drawn, may be tested at this point to ensure its integrity. At **S102**, if a quick prime is to be performed, the batch contents may be used for this purpose. Either way, the remaining batch contents are emptied to the drain **S104**. The controller stores final target quantities of water, osmotic agent concentrate, and electrolyte concentrate ultimately to be transferred to the mixing container, mixed, and tested. Initially the mixing container is empty. At **S106**, an initial quantity of water is transferred to the mixing container. Prior to **S106**, the mixing container is essentially empty, although there may be a small residual trace from the priming operation. The resulting batch contents are indicated in alignment with the **S106** process in row **321**. The quantity of water may be optimized to minimize mixing time. In embodiments, the water quantity may be 50% of the target water requirement. At **S108** osmotic agent concentrate is transferred to the mixing container as required by the target composition. The transferred osmotic agent concentrate illustrated at **322** indicates the that entire target quantity of concentrate is transferred. Also illustrated at **322** is that a quantity of water and a quantity of electrolyte concentrate are also transferred as part of the osmotic agent concentrate **338**.

(144) Note that the target quantities of the electrolyte, the osmotic agent, and water can be stored as the quantities of electrolyte concentrate and osmotic agent concentrate or the quantities of the undissolved species. The quantities can be converted between each and can be stored as volume or mass or other suitable measure.

(145) In the present embodiment, the volume of osmotic agent concentrate includes electrolyte as a marker, which contributes to the amount of electrolyte of the target stored by the controller. If a final dialysis fluid requires no more than the quantity of electrolyte appearing in the osmotic agent concentrate to function as a marker, then the quantity of electrolyte concentrate transferred in this initial step is sufficient to form the final dialysis fluid. Next, the mixing container contents are mixed by pumping at **S110**. At **S112**, the batch content conductivity is tested to determine if the concentration is as expected. The controller may store a number indicating a number N of conductivity retests that can be performed in the event the conductivity test result is outside of an expected range. To retest, the controller mixes the contents of the mixing container again. In embodiments, this latter mixing may be for a shorter predefined interval than a predefined interval of operation **S110**. The testing and mixing may be iterated the N number (N being a predefined number) of times and if the final test fails, the preparation is halted and a recovery operation

invoked, for example, halting pumping and outputting a display to restart preparation with a new disposable fluid circuit. Through **S108** to **S112**, the contents of the mixing container remain the same as indicated at **324** and **326**.

(146) If the final dialysate calls for a higher ratio of electrolyte concentrate to osmotic agent concentrate than is in the osmotic agent concentrate, then at **S114**, a corresponding quantity of electrolyte concentrate is added to the mixing container. Otherwise operations **S114**, **S116**, and **S118** are skipped. Proceeding with **S114**, the mixing container contents are mixed at **S116** and a conductivity check is performed at **S118** with M iterations where M may be any number including equal to N. The balance of the required water for achieving the target is added at **S120**. At that point the final composition indicated at **334** and **336** is obtained. Then, as above, the mixing container contents are mixed at **S122** and a conductivity check is performed at **S124** with L iterations where L may be any number including equal to N or M. In a final operation **S126** the one or more filters used to protect against touch contamination (depending on the configuration of the fluid circuit) is tested to confirm its integrity during the fluid proportioning.

(147) The reason only a fraction of the water is added initially at **S106**, even if the ratio of electrolyte to osmotic agent in the osmotic agent concentrate is correct for the target dialysis fluid, is that mixing initially with part of the water and then again with the remainder of the water may reduce the total mixing time compared to adding all of the water at once at **S106**.

(148) In the foregoing methods, there were described three steps of mixing and testing. Within any of these operations, a titration process may be used to adjust the quantity of water or concentrate added to the mixing container or for adjusting the accounting of the total volume of water to be added in a final dilution operation. At **S112**, for example, in embodiments, the amount of osmotic agent concentrate may be increased if the conductivity measurement indicates the quantity falls below a minimum mass of osmotic agent (the solute) for the target dialysis fluid. Since ratiometric proportioning is relied upon, such a correction would assume that the amount of water transferred is validly quantified and the osmotic agent concentrate quantity is inaccurate. If testing indicates that the quantity of osmotic agent concentrate is consistently less accurately or precisely metered by the pumping than the water, then this correction would be valid for such systems. In further embodiments, the controller may be programmed so as to make an adjustment in the concentrate only after a predefined number of mixing/testing reattempts. This will ensure against any concentration bias resulting from incomplete mixing. When a dialysis fluid is being made, whose ratio of electrolyte to osmotic agent is identical to that in the osmotic agent concentrate containing electrolyte concentrate as a marker, the testing of the batch contents at **S112** is sufficient to indicate the concentrations of both the osmotic agent concentrate and electrolyte concentrate because the ratio of electrolyte concentrate to osmotic agent concentrate is fixed in the osmotic agent concentrate. Many dialysis fluids are characterized by standard ratios of osmotic agent concentrate to electrolyte concentrate. If the highest osmotic agent/electrolyte ratio of such a fixed set is equal to the proportion of electrolyte concentrate used as a marker in the osmotic agent concentrate, then this ability to confirm the final dialysis fluid quality by a conductivity test will be available. A controller may be programmed to control the proportioning process such that a final batch is cleared only after confirmation of the final conductivity. For standard dialysis fluids having lower ratios of osmotic agent to electrolyte, the system may rely on ratiometric proportioning.

(149) FIG. 15D shows a flow chart of another proportioning procedure next to a corresponding schematic diagram of the mixing container contents **320**. As in FIG. 15A, the diagram at each stage of processing has rows **351** through **366**, each showing a figurative representation of components of electrolyte concentrate, osmotic agent concentrate with no electrolyte marker, and water. As discussed with reference to FIG. 15A, the concentrates contribute some water in addition to the respective electrolyte and osmotic agent components they contribute. Also, the rows **351** through **366** are aligned with the process stages **S206** through **S222**, with each row showing a composition that exists at the corresponding stage. Columns **368**, **369**, and **370** show the concentrates and water

components. The concentrates are further broken down in the columns to indicate the constituents thereof. The osmotic agent concentrate **368** has as constituents osmotic agent and water only. No marker is used. The electrolyte concentrate **339** has as constituents electrolyte and water. The constituents are indicated by “E,” “O,” and “H₂O” as in FIG. **15A**.

(150) In an initial operation **S200**, the fluid circuit including the manifold, if present, is primed with water and the water is circulated through the mixing container to break-in the pump tube segment. The sterilizing filter through which water is drawn may be tested at this point to ensure sterility. At **S202**, if a quick prime is to be performed, the batch contents may be used for this purpose. Either way, remaining batch contents are emptied to the drain **S204**. The controller stores final target quantities of water, osmotic agent concentrate and electrolyte concentrate ultimately to be transferred to the mixing container, mixed, and tested. Initially the mixing container is empty. At **S206**, an initial quantity of water is transferred to the mixing container. Prior to **S206**, the mixing container is essentially empty although there may be a small residual trace from the priming operation. The resulting batch contents are indicated in alignment with the **S206** process in row **351**. The quantity of water may be optimized to minimize mixing time. In embodiments, the water quantity may be 50% of the target water requirement. At **S208** electrolyte concentrate is transferred to the mixing container as required by the target composition. This may be the full quantity of electrolyte concentrate required in the target composition. The transferred electrolyte concentrate illustrated at **352** indicates the quantity of electrolyte solute that is transferred. Also illustrated at **352** is that a quantity of water is also transferred as part of the electrolyte concentrate **369**.

(151) Next, the mixing container contents are mixed by pumping at **S210**. At **S212**, the batch content conductivity is tested to determine if the concentration is as expected. The controller may store a number indicating a number N of conductivity retests that can be performed in the event the conductivity test result is outside of an expected range. To retest, the controller mixes the contents of the mixing container again. In embodiments, this latter mixing may be for a shorter predefined interval than a predefined interval of operation **S210**. The testing and mixing may be iterated the N number of times and if the final test fails, the preparation is halted and a recovery operation invoked, for example, halting pumping and outputting a display to restart preparation with a new disposable fluid circuit. Through **S208** to **S212**, the contents of the mixing container remain the same as indicated at **354** and **356**.

(152) Proceeding with **S214**, the osmotic agent is added to the mixing container and the mixing container contents are mixed at **S216**. Then a conductivity check is performed at **S218** with M iterations where M may be any number including equal to N. The quantity of osmotic agent concentrate added can be verified at **S218** because the combined effect of dilution by the water constituent and the osmotic agent constituent is to lower the conductivity a measurable amount which depends on how much water and osmotic agent concentrate is added. This decrement in conductivity may be stored as a predefined quantity by the controller and compared to measured levels just as the other conductivity measurements are.

(153) The balance of the required water for achieving the target mixture is added at **S220**. At that point the final composition indicated at **364** and **366** is obtained. Then, as above, the mixing container contents are mixed at **S222** and a conductivity check is performed at **S224** with L iterations where L may be any number including equal to N or M. In a final operation **S226** the one or more filters used to protect against touch contamination (depending on the configuration of the fluid circuit) is tested to confirm its integrity during the fluid proportioning.

(154) The reason only a fraction of the water is added initially at **S206** is that mixing initially with part of the water and then again with the remainder of the water may reduce the total mixing time compared to adding all of the water at once at **S206**. In embodiments, however, mixing all the water at once is a possible alternative embodiment.

(155) In all of the foregoing conductivity measurement operations, the conductivity and the temperature of the fluid may be converted directly to concentration of the electrolytes in water, or

for a fluid that contains both electrolytes and an osmotic agent, to concentration of either the electrolytes or the osmotic agent, or both. A similar result may be achieved by correcting a measured conductivity to account for a difference between a reference temperature and the temperature of the fluid to obtain the conductivity at the reference temperature. A table of concentrations of the various admixtures vs conductivity at the reference temperature can then be stored in the controller to determine the concentration for purposes of making corrections in the dialysis fluid composition. In embodiments of disclosed proportioning systems, the reference temperature may be a human body temperature and the proportioning process may include controlling the temperature of the dialysis fluid to be at the body temperature (e.g., 37 C) such that the actual temperature at the time of conductivity measurement is close to the reference temperature. This makes any errors in the corrected conductivity measurement very small because the actual and reference temperatures will be close due to the control of the dialysis fluid temperatures.

(156) In a method embodiment, the constituents are warmed to the delivery temperature in advance of combining them. In alternative embodiments, the constituents are warmed after combining but prior to testing. In embodiments, the conductivity is used without compensation for comparison to reference values. In embodiments, the estimated temperature at which concentration or target conductivity is taken is an estimated room temperature. This would be relevant where the combining is done before warming the product to a temperature for administration to the patient. Warming to body temperature may be done at a later time. In embodiments, the conductivity levels and associated temperature compensation coefficients for each of the expected concentration targets are taken at 37 C.

(157) FIG. 15B shows, approximately, the relationship between conductivity and concentration of dextrose during the proportioning procedure described above with reference to FIG. 15A. Curves **1506A**, **1506B**, and **1506C** represent dilution curves for each of three kinds of dialysis fluid having final concentrations of osmotic agent in the finally diluted dialysis fluid. The fully diluted concentrate of each curve may represent, for example, 4.25% dextrose in curve **1506A**, 2.5% dextrose in curve **1506B**, and 1.5% dextrose in curve **1506C**, respectively. The other constituents may be the same in all three, i.e., the clinically accepted components of what is carried in the electrolyte concentrate including sodium, magnesium, calcium chloride, etc. In other words, at all points to the right of the final diluted dialysis fluid (diluted to usable concentration) are over-concentrated solutions for 4.25%, 2.5%, and 1.5% dialysis fluid. By selecting the ratio of dextrose (osmotic agent concentrate, more generally) to electrolyte concentrates to be in the proportions of a final dialysis fluid characterized as a 4.25% osmotic agent (dextrose) dialysis fluid, a usable dialysis fluid can be formed without the addition of electrolyte concentrate and other dialysis fluids can be formed by adding respective amounts of electrolyte.

(158) Presenting the dilution curves as shown in FIG. 15B highlights what has been pointed out above, namely, that the steps of mixing constituents in stages has implications for mixing efficiency and also, as discussed now, for proper measurement of conductivity. The ability to make unambiguous conductivity measurements varies for different points in the dilution vs. conductivity space. For example, curve **1506A** illustrates the dilution curve for a concentrate with lowest percentage of electrolyte to osmotic agent and it can be seen that certain conductivity values indicate two different dilution levels. Also indicated at **1508** is a range for efficient mixing. The indications are all figurative and the precise ranges would be determined by experiment.

(159) In the proportioning procedure of FIG. 15A outlined above, the measurement zones are restricted to a range where conductivity is single-valued and optimized mixing efficiency regions **1508**. Referring also to FIG. 15A, water **S106** is combined with electrolyte concentrate and osmotic agent concentrate **S108** and mixed in the mixing container and the conductivity measured at **S112**. This corresponds to point **1500** where the composition corresponds to 4.25% dextrose that is partially diluted. Next, assume that the target dialysis fluid is 2.5% dextrose dialysis fluid. The

addition of electrolyte concentrate **S114** brings the composition of the mixing container to point **1502** which is on curve **1506B** which corresponds to an overconcentrated 2.5% dextrose dialysis fluid. The final dilution at **S120** brings the composition to the point **1504** which is that for ready to use 2.5% dextrose dialysis fluid. The measurement points **1500**, **1502**, and **1504** are all in desirable regions of the dilution/conductivity space. In the graph the osmotic agent concentrate is identified as dextrose but could be other kinds of osmotic agent concentrate.

(160) In all of the foregoing embodiments, the final product can be obtained by ratiometrically balanced proportioning, relying purely on the repeatability of volumes delivered by the pumping. In such embodiments, the concentration need not be detected and proportioning can be done independently of any concentration measurements. In further embodiments, the final composition can be verified through a single concentration sampling and measurement.

(161) Referring now to FIG. **15C**, a graph shows mixing time versus dextrose concentration (note that other osmotic agent concentrates may be similarly represented) with a curve indicating total pumping time required to transfer the required full water and concentrate quantities and to mix the contents to a point that ensures complete mixing. The latter may be determined experimentally by periodically sampling the contents of a mixing container at times during mixing and identifying the time required for full transfer and complete mixing ("pumping time") as the point where the concentration reads a constant value. The ratio of water and the osmotic agent (e.g., dextrose) concentrate in the initial combination at **1500** in FIG. **15B** may affect the total time required to create the admixture including time to pump water and concentrate and time to mix the container contents. Requiring the point **1500** to lie in the range of ratios of water and osmotic agent concentrate where the concentration measurement is monotonic and requiring the point to be remote from the solubility limit of the osmotic agent, a minimum pumping time may be identified. Accordingly, an optimum initial ratio of ratio of masses of osmotic agent concentrate and water may be found and used to define the combination identified with the point **1500** in FIG. **15B**. In embodiments of the disclosed subject matter, for example the method of FIG. **15D**, the point **1500** may be determined responsively to these conditions.

(162) Note that in any of the embodiments, the use of peristaltic pumps can be replaced by metering pumps that employ any of a variety of pumping mechanisms that may provide sufficient absolute accuracy to satisfy a prescribed treatment (i.e., a ratio of the commanded quantity transferred to the actual is bounded by a predefined range that further falls within the permitted proportions of the admixture or final product dialysate constituents). This is compared to a pumping mechanism that relies on ratiometric accuracy in that the ratio of components is accurate even if the ratio of commanded-to-actual rates (or volumes) is not as accurate as the prescribed requirement.

(163) Referring to FIG. **16A**, in another method embodiment for creating a batch of dialysis fluid, electrolyte concentrate is pumped into the mixing container before osmotic agent concentrate is added. This allows the testing and adjustment of the electrolyte concentrate concentration to be performed on the mixed batch prior to the addition of osmotic agent concentrate. Because the tolerance of the dialysis fluid prescription to variation in the electrolyte concentrate concentration is much tighter, for example $\pm 2.5\%$, than the concentration of osmotic agent concentrate ($\pm 5\%$), the addition, confirmation, and adjustment of electrolyte concentrate alone allows the proportioning to be more tightly controlled. In embodiments, additional water or concentrate may be added to ensure the concentration is within the electrolyte concentrate limits. In embodiments, the dose of osmotic agent concentrate is controlled solely by volumetric control. In embodiments, the quantity of osmotic agent concentrate added during proportioning is checked with a conductivity measurement but the quantity is not titrated to adjust it based on conductivity measurements.

(164) The method begins with the pumping of all, or a fraction of the required water for the batch into the mixing container **458**. In a variation, a quantity of water equal to a predefined fraction

required for the final batch is pumped into the mixing container. For example, 50% of the target quantity of water may be added. As noted elsewhere, the quantity may be selected to minimize overall pumping time or at least responsively to overall mixing time. Next, 100% of the required dose of electrolyte concentrate is pumped into the mixing container **459**. The mixing container contents are then mixed at **460** and a sample of the mixing container is withdrawn and tested at **461** by pumping a sample through one or more conductivity sensors, for example as described in the above embodiments. At **463**, the osmotic agent concentrate dose is pumped into the mixing container and the batch contents are mixed **464**. Mixing here, and in all method embodiments, may be done by any of the mechanisms identified above or by any suitable method.

Magnetohydrodynamic mixing (excitation circuits may be provided, for mixing and/or for warming, in a support for the mixing container) may be employed here to reduce the count of roller strikes on the fluid circuit that would otherwise occur if pump mixing were used. A sample may be pumped from the mixing container and tested at **465** by pumping a sample through one or more conductivity sensors, for example as described in the above embodiments. If additional water is required, depending on the amount originally added at **458**, then the final balance of water is pumped into the mixing container at **467** and the final diluted concentration check as at **465** is done at **468**.

(165) At **469** a pressure test of one or more sterilizing filters depending on the embodiment (e.g., **115** of any FIG. **1A-1D**, **2A**, **2E** or **2H**) may be performed and a result of the test may be made a condition for the release of the batch for a treatment. That is, in the method, all fluids added to the batch that are not otherwise preconnected to the mixing container (as done in some but not all disclosed embodiments) may have an inline sterilizing filter preconnected between the outside source and the mixing container. That is, the sterilizing filter is preconnected such that its sterilizing filter membrane defines a barrier to the interior of the mixing container such that any touch contamination resulting from the making of a connection to the mixing container is blocked by the filter membrane when a fluid transfer occurs through the made connection. When the sterilizing filter or filters is/are pressure tested—that is, one or more sterilizing filters relied upon to define the sterile barrier are pressure tested—the controller makes a determination as to whether they have passed the pressure test and then either prevents or permits the batch to be used. In a method, the controller generates a message indicating the outcome of the pressure test or tests. The controller may generate the message to be output on a display along with an indication that the batch is not permitted to be used. The controller may further prevent the transition to a treatment mode in which the batch is used. The controller may, in an alternative embodiment, transition to a mode for preparation of a new batch. The controller, in the latter case, may output an instruction to replace a failed disposable with a new one and to initiate preparation of a new batch.

(166) At **461**, **465**, and **468**, the conductivity of the mixing container is detected and compared to an expected value in order to ensure the proportioning process is proceeding correctly. If a comparison to an expected value stored in a controller fails to pass, a recovery procedure may be performed as described with reference to FIGS. **15A** and **15D**, that is, the batch may be mixed (for any time, or for an interval shorter or equal to a mixing time of **460**) and the batch contents sampled and tested again. Thus, one form of recovery is to recover from an invalid test rather than a bad mixture. If, after some predefined number of remix/test attempts, the conductivity differs from the stored expected value by more than a predefined amount or percentage, the proportioning process may stop, and the controller may output a message to restart the proportioning process. In addition to stopping the proportioning process, the controller may prevent access to the batch by clamping a line or take some other safety precaution to prevent misuse of the failed batch contents.

(167) An additional recovery process may be implemented by the controller to adjust the conductivity of the batch in a way that corrects for a mixing error. When a conductivity test fails, i.e., the measured conductivity is outside a predefined range with respect to a stored expected value, the controller may adjust the proportions of the batch by adding water or one or both

concentrates in an amount that is in response to the magnitude of the error. As an initial operation, the controller may compare the magnitude of the error in combination with the stage of proportioning in order to determine if an adjustment is permitted. In embodiments, the controller stores a respective error magnitude range of conductivity for each test (**461**, **465**, and **468**). The stored error magnitude, which may be different for negative and positive errors, may be compared with a detected error at **461**, **465**, or **468** and the controller may proceed with an adjustment process if the error magnitude is below the stored error magnitude or terminate proportioning if not. The error magnitude may be advantageously based on the last remix/test cycle for the particular operation **461**, **465**, or **468**.

(168) The recovery procedure may also employ a scale that measures the weight of the disposable unit. The disposable unit includes a mixing container and one or more concentrate containers depending on the embodiment. Only water is added and it is added to the mixing container. After obtaining a baseline weight after the disposable unit is rested on a scale, thereafter the quantity of water added to the mixing container can be detected by weight. No change in the total weight of the disposable unit occurs when concentrate is transferred to the mixing container. Using the conductivity plus the weight of the disposable unit, at each operation **461**, **465**, or **468**, the controller can determine precisely the amount of added water or concentrate needed to achieve the target ratios.

(169) In embodiments without a scale, or in which a scale is not used for proportioning control, the controller may perform operations as follows to recover by changing the mixing container contents to correct for an erroneous reading. Referring to FIG. **15E**, a flow chart is shown in outline form. It repeats elements of other mixing methods presented here but is not a separate embodiment in that it can be added (with substitution, as necessary) as a conductivity error recovery method to any of the methods presented herein.

(170) Referring to FIG. **15E**, at 1.0 an initial water dose is added to the mixing container. At 2.0 a first concentrate is added, which can be, for example, osmotic agent concentrate or electrolyte concentrate according to any of the embodiments. At 3.0 the batch contents are mixed and at 4.0, the conductivity is measured. At 4.1 the controller determines if the conductivity measurement matches, within a predefined tolerance, the expected value and if so, operation proceeds to 5.0. Otherwise, at 4.2, an error recovery method 4.2.1 calculates an actual first concentrate in the batch by assuming that the correct quantity of water was pumped into the container. This may be obtained because the relationship between concentration and conductivity is stored. This relationship can be stored as a lookup table, a power function fitted formula, or some other way to allow a new quantity of concentrate to be calculated from the given water quantity and the calculated concentration of the first concentrate. The new quantity of concentrate (e.g., volume, but the units of the computation are not essential) is used to calculate a new target quantity of the second concentrate at 4.2.2.

(171) At 5.0 the second concentrate is added, mixed 6.0, and the batch contents conductivity measured 7.0. If the conductivity value matches the expected conductivity based on the reset volume transfer of concentrate from 4.2.2 if this operation was performed previously, then control proceeds to 8.0. If the conductivity is erroneous and was previously erroneous for the first concentrate, then at 7.2 then the proportioning process is terminated and a recovery process initiated. The batch is a failed batch at this point. Control reaches 7.3 if the conductivity measurement at 4.0 was in range and the conductivity measurement at 7.0 was not in range. At 7.3.1 if the conductivity indicates deficiency of the second concentrate was added to the batch container at 5.0, then an additional amount to be added is calculated based on the magnitude of the conductivity measurement and thereafter added to the mixing container. Control proceeds to 7.3.2.1. At 7.3.1 if the conductivity indicates a surfeit of the second concentrate was added to the mixing container at 5.0, then an additional amount the first concentrate and water to be added are calculated based on the magnitude of the conductivity measurement and thereafter added to the

mixing container. At 7.3.2.1 the batch contents are mixed and conductivity measured again at 7.3.2.2. If the measurement is within expected range, then at 7.3.2.2.1 control proceeds to 8.0; otherwise the proportioning is terminated at 7.3.2.2.2.

(172) If no hard termination of the proportioning has occurred, then at 8.0 the balance of the water is added, at 9.0 the mixing container contents are mixed, and at 10.0 the conductivity of the batch fluid is measured. If the measurement is good, at 10.1, then control proceeds to 11.0. If the conductivity measurement is within the expected range, then control proceeds to 11.0, otherwise control proceeds to 10.1.1 or 10.1.2 based on whether the conductivity measurement indicated under-dilution or over-dilution at 8.0. If over-dilution is indicated by the conductivity measurement (i.e., measured conductivity is lower than the expected threshold) then at 10.1.1 both concentrates are added in the prescribed ratio as described in the present disclosure. If under-dilution is indicated at 10.1.2, water is added as described in the present disclosure. In both cases, the water deficit or surfeit can be estimated from the conductivity measurement based on the prescribed quantities of the concentrate constituents with any adjustments stored due to preceding recovery operations. In this final adjustment stage it is possible to add water or concentrates in increments and test repeatedly to titrate the batch contents to a final target level of conductivity. At 10.1.2.1 the batch contents are mixed and conductivity measured again at 10.1.2.2. If the measurement is within the expected range, then at 10.1.2.2.1 control proceeds to 11.0; otherwise, the proportioning is terminated at 10.1.2.2.2.

(173) At 11.0, the filter or filters that ensure sterility of all fluids is/are tested and if the test fails, the batch is terminated as discussed above. Otherwise the batch is released at 12.0.

(174) Note that in all the relevant operations in FIG. 15E, a magnitude of the error between the expected value of conductivity and the measured value is compared to a permitted range and if outside that range, control may proceed to a hard termination of the proportioning, as in 7.2, for example and as described elsewhere.

(175) FIG. 17A shows a proportioning and treatment system for peritoneal dialysis 700A. Two multi-treatment containers 736 and 738 contain electrolyte concentrates and osmotic agent concentrates, respectively. They are connected by aseptic connectors 730 to a fluid circuit 701A by respective osmotic agent concentrate 744 and electrolyte concentrate 742 lines. Non-aseptic connectors may also be used. In embodiments, where the connectors are non-aseptic, the osmotic agent concentrate 744 and electrolyte concentrate 742 lines may contain sterilizing filters. Due to the cost and number of filters required this is not a preferred way to ensure sterility. A last fill container 734 may also be connected to the fluid circuit 701A via last fill line 740. The last fill container 734 may contain a specific medicament for the last fill cycle of a multi-cycle treatment. The fluid circuit 701A contains first 758 and second 760 manifolds connected by a pumping tube 763. The manifolds 758 and 760 define selectable fluid paths connecting various sources of fluids to fluid consumers using clamps 751 under control of a controller 739. The details of the flow switching may be as discussed above with respect to similar embodiments. A purified water source 766 supplies purified water to the manifold 758 through redundant sterilizing filters 731. The filters 731 may be replaced by a single testable filter that is automatically tested to confirm that a batch is sterile as described in method embodiments in the present disclosure. Manifold 760 is connected by a drain line 756 to a drain line circuit 765 through a non-aseptic connector 729. The drain line circuit has a conductivity sensor 764 in its path to permit the measurement of conductivity of samples of fluid conveyed through the manifold 760 under control of the controller 739. The mixing container 732 is connected by inlet and outlet lines 746 and 750 to the manifolds 758 and 760, respectively, to allow fluid to be pumped into the mixing container 732, to be drawn from the mixing container 732, and to permit mixing via recirculation of the contents of the mixing container 732. A pump 762 pumps fluid between the manifolds 758 and 760. Pressure sensors 769 are positioned on either side of the pump 762 to detect pump inlet and outlet pressures in pump tube 763. Signals corresponding to the pressures are applied to the controller 739 and used for

pump pressure compensation and/or pump calibration as discussed elsewhere and in US Patent Publication 2015-0005699, hereby incorporated by reference in its entirety herein. A waste container **768** may be attachable to the drain line circuit **765** by a non-aseptic connector **729**. A heater **770** contacts the mixing container **732**. In embodiments, the heater **770** forms a bed on which the mixing container **732** rests. A patient line **754** is connected by a Y-connector to separate lines **748** and **752** to permit the filling and draining of a patient **718** through the patient line **754**, which is connected to a catheter (not shown) by means of another aseptic connector **730**.

(176) The fluid circuit **701A** connects to proportioning/cycler machine **772** by a mechanism that aligns clamps **751** with respective clamping portions of lines **741**, **740**, **742**, **744**, **750**, **746**, **752**, and **756**. Various such mechanisms are known in the art such as supports that hold tubing portions at predefined positions in cassettes and cartridges and compact fluid circuits that can be easily laid over a set of actuators and sensors. The manifolds and clamps can be replaced by a variety of different types of flow selector devices known in the art, so the current system is not limited to using flow selectors based on clamping of tubing. If the pump **762** is a peristaltic pump, a pumping tube segment of line **763** may be aligned by the connection of the fluid circuit **701A**. The purified water source **766** may be housed in an enclosure **767** together with the drain line circuit **765** or portions of either. The waste container **768** may be housed in the same enclosure, or not, as illustrated. The concentrate containers **736** and **738** may contain sufficient concentrate for multiple fill/drain cycles, multiple days' worth of treatments, each consisting of multiple fill/drain cycles, a week's worth of treatments, a month's worth of treatments, or some other schedule. The concentrate containers **736** and **738** may be independently replaceable by use of the aseptic connectors. The benefits of independent replacement are discussed elsewhere in the present disclosure. The contents of the last fill medicament container **734** may be fully diluted or may consist of, or include, a concentrate that requires further dilution. The manifolds **758** and **760** may have a minimum volume to reduce waste when changing over fluids. In embodiments, the maximum hydraulic diameters of the manifolds **758** and **760** are each no more than 5 times the diameter of the largest line connecting to them. In further embodiments, they are no more than 3 times the diameter of the largest line and in still further embodiments, no more than twice.

(177) Referring to FIGS. **16B** and **17A**, in a method for creating a batch of dialysis fluid, a set of priming operations is first performed. The operations **485**, **486**, **487**, **488** and **489** collectively form an overall operation sequence that fills osmotic agent concentrate, electrolyte concentrate and last fill lines **740**, **742**, and **744** with the respective fluids and fills the mixing container **732** inlet **746** and outlet **750** lines as well as the manifold **758**, pumping tube **763**, manifold **760**, and water line **741** with purified water. The operations can be in any order but in particular embodiments, the water is primed through the manifold last.

(178) At **485**, a first concentrate **736** or **738** is conveyed to the waste container **768** (which can be a sewage drain rather than a container) by closing the valves **751** for all of the lines except for the valves **751** that permit flow through the respective concentrate line **742** or **744** and the valve **751** that permits flow through the drain line **756**. The pump **762** is operated to establish a flow until a predefined condition is met. The predefined condition may be detected by the controller **739**. The predefined condition may be a detected volume of concentrate determined by the controller **739**, a number of cycles (e.g., rotations) of a pump actuator, or a detected conductivity or rate of change thereof, indicated by the conductivity sensor **764**. The condition may be selected to ensure that the respective concentrate line **742** or **744** is filled. The condition may be further selected to ensure that the respective concentrate line **742** or **744** is purged of any air. The absence of any air in the respective concentrate line **742** or **744** may be established by an air detector, for example one that is located at the conductivity sensor **764** or located elsewhere along the path. The condition may include a combination of a threshold level of (or no) detected air combined with a predefined threshold of conductivity.

(179) At **486**, a second concentrate **736** or **738** (other than the first concentrate) is conveyed to the

waste container **768** (which can be a sewage drain rather than a container) by closing the valves **751** for all of the lines except for the valves **751** that permit flow through the respective concentrate line **742** or **744** and the valve **751** that permits flow through the drain line **756**. The pump **762** is operated to establish a flow until a predefined condition is met. The predefined condition may be detected by the controller **739**. The predefined condition may be a detected volume of concentrate determined by the controller **739**, a number of cycles (e.g., rotations) of a pump actuator, or a detected conductivity or rate of change thereof indicated by the conductivity sensor **764**. The condition may be selected to ensure that the respective concentrate line **742** or **744** is filled. The condition may be further selected to ensure that the respective concentrate line **742** or **744** is purged of any air. The absence of any air in the respective concentrate line **742** or **744** may be established by an air detector, for example one that is located at the conductivity sensor **764** or located elsewhere along the path. The condition may include a combination of a threshold level of (or no) detected air combined with a predefined threshold of conductivity.

(180) At **487**, a last fill (either a concentrate or a ready for use medicament) is conveyed to the waste container **768** (which can be a sewage drain rather than a container) by closing the valves **751** for all of the lines except for the valves **751** that permit flow through the last fill line **740**, and the valve **751** permits flow through the drain line **756**. The pump **762** is operated to establish a flow until a predefined condition is met. The predefined condition may be detected by the controller **739**. The predefined condition may be a detected volume of fluid determined by the controller **739**, a number of cycles (e.g., rotations) of a pump actuator, or a detected conductivity or rate of change thereof indicated by the conductivity sensor **764**. The condition may be selected to ensure that the last fill line **740** is filled. The condition may be further selected to ensure that the last fill line **740** is purged of any air. The absence of any air in the last fill line **740** may be established by an air detector, for example one that is located at the conductivity sensor **764** or located elsewhere along the path. The condition may include a combination of a threshold level of (or no) detected air combined with a predefined threshold of conductivity.

(181) At **488**, purified water is conveyed to the waste container **768** (or sewage drain) by closing the valves **751** for all of the lines except for the valves **751** that permit flow through the water line **741** and the valve **751** that permits flow through the drain line **756**. The pump **762** is operated to establish a flow until a predefined condition is met. The predefined condition may be detected by the controller **739**. The predefined condition may be a detected volume of water determined by the controller **739**, a number of cycles (e.g., rotations) of a pump actuator, or a detected conductivity or rate of change thereof indicated by the conductivity sensor **764**. The condition may be selected to ensure that the water line **741** is filled. The condition may be further selected to ensure that the water line **741** is purged of any air. The absence of any air in the water line **741** may be established by an air detector, for example one that is located at the conductivity sensor **764** or located elsewhere along the path. The condition may include a combination of a threshold level of (or no) detected air combined with a predefined threshold of conductivity.

(182) At **489**, an optional step is performed of recirculating the water through the mixing container **732**. In embodiments, this may be done before or in the middle of the operation at **488** as well as after. The valves **751** opening inlet line **746** and the valve opening water line **741** are opened while all other valves **751** are closed so that when the pump **762** is operated, water is pumped into the mixing container **732**. Then the water line **741** valve **751** is closed and the outlet line **750** valve **751** is opened so that when the pump **762** runs, water can be continuously recirculated in the mixing container **732**. The controller implements this flow configuration for a predetermined number of pump cycles or a predefined time (which may depend on the flow rate). This operation breaks in the pump tube **763** for a peristaltic pump, thereby making the relationship between pump cycle rate (e.g., RPM) and flow rate more consistent. This operation is beneficial when a new fluid circuit **701A** is installed. After the pump tube **763** break-in is completed, the inlet line **746** may be closed by the respective valve **751** and the drain line **756** opened by the respective valve, after which the

pump **762** operates to drain the mixing container. Whether the pump break-in is completed after, before, or during priming of the manifold and drain line with water, the operation serves to prime the inlet **746** and outlet **750** lines and further prime the drain line **756** and manifolds **758** and **760**. (183) Note that instead of a conductivity detector at **764**, other types of sensors may be used to detect the filling of the respective concentrate line. For example, a flow sensor may be responsive to the density or viscosity of fluid flowing in the drain line **756**. Another alternative is a temperature sensor for cases where the temperature of the fluid reaching the sensor is different from the fluid being displaced.

(184) In the embodiment of FIG. **16A**, electrolyte concentrate is pumped into the mixing container before osmotic agent concentrate is added. However, in alternative embodiments, osmotic agent concentrate (which may contain electrolytes that function as a marker) is added to the mixing container before the remaining electrolyte concentrate. The method begins with the pumping of 100% or less of the required water for the treatment batch into the mixing container **732**. By closing all valves **751** except those closing water line **741** and inlet line **750**, a predefined volume of water is pumped by the pump **762** from the purified water source **766** through sterilizing filters **731** (or a single testable filter if present), through the optionally aseptic connector **730**, through water line **741**, manifold **758**, through pumping tube **763**, into manifold **760**, through mixing container inlet line **746**, and into the mixing container **732**. The volume displaced may be controlled by the controller by controlling the number of cycles of the pump **762** to a predefined number of cycles (e.g., rotations of a peristaltic pump). The embodiment of FIG. **16B** can be modified in a similar manner, however, the osmotic agent concentrate pumped into the mixing container first, may contain electrolyte concentrate in sufficient quantity to serve as a marker in order to test the admixture at **473**.

(185) For purposes of accounting for the precise quantities of fluids that are pumped into the mixing container **732**, the controller's operations to the pump **762** are such that displacement of residual volumes of fluids remaining in respective parts of the fluid circuit are accounted for. In operation **470**, the total quantity entering the mixing container is equal to the quantity displaced by the pump **762** in this operation because the manifolds **758** and **760** and the inlet line **746** were previously primed. So, no additional accounting is reflected in the control of the pump in that case. The pump is operated to displace a target volume of water and the controller can be programmed to do calculations based on the batch volume being equal to the displaced volume during operation **470**. For convenience in discussing the further operations where displacement of a fluid also displaces another remaining in the fluid circuit **701A**, the following identifiers will be used: MIMO, for the combined volume of the manifold **758**, pump tube **763**, and manifold **760**; MOTI, for the volume of the inlet line **746** between the mixing container **732** and the manifold **760**; SOMI, for the volume of the outlet line **750** between the mixing container **732** and the manifold **758**.

(186) At **471**, electrolyte concentrate from electrolyte concentrate container **736** is pumped to the mixing container **732** by opening respective valves **751** for the electrolyte concentrate line **742** and the inlet line **746** and closing other valves **751** to form a direct path that includes MOTI and MIMO. The electrolyte concentrate is pumped by the pump **762** from the electrolyte concentrate container **736**, through the manifold **758** by opening only the clamp **751** that closes the electrolyte concentrate line **742**. The pump draws the electrolyte concentrate from manifold **758** through the pump tube **763** and into manifold **760** through the inlet line **746** into the mixing container **732**. A volume equal to 100% of the required dose of electrolyte concentrate is pumped toward the mixing container **471** but a predetermined fraction equal to MOTI and MIMO remains behind. In addition, through the pumping of electrolyte concentrate, a volume of water equal to MOTI and MIMO is added to the mixing container **732**. The controller uses a predetermined conductivity threshold for a mixed diluted electrolyte concentrate based on the added volume MOTI plus MIMO of water. This conductivity threshold allows the testing at **473** and adjustment at **474** of the electrolyte concentrate concentration to be performed on the mixed batch prior to the addition of osmotic agent

concentrate with the concomitant tolerance benefits discussed above.

(187) The mixing container contents are then mixed at **472** by closing all valves **751** except those closing the inlet **746** and outlet **750** lines to the mixing container **732** such that fluid is circulated into and out of the mixing container **732**. As a result, the fraction of electrolyte concentrate equal to MOTI and MIMO is integrated into the batch contents and the water left in SOMI is integrated in as well. For concentration measurement purposes the total pumped volume of concentrate conveyed at **471** is mixed with the total pumped volume of water conveyed at **470** with the additional dilution of a SOMI volume to determine the expected concentration. A sample of the mixing container is withdrawn and tested at **473** by pumping a sample through one or more conductivity sensors, for example as described in the above embodiments. This is done by closing all the valves **751** except for those controlling the outlet line **750** and the drain line **756** and operating the pump **762** to convey a predetermined volume of fluid from the mixing container **732** to the conductivity sensor **764**. The controller **739** may account for the drained volume in making adjustments to its internal model of the batch contents at **474** including total volume and proportions of constituents. The concentration of electrolyte concentrate can be determined by the controller **739** by the conductivity measurement permitting the controller to add more water or electrolyte concentrate to change the concentration to fit a target. Alternatively, the internal model of composition of the mixing container stored by the controller **739** may be adjusted responsively to the measurement and accounted for later to change the amount of osmotic agent concentrate and/or water added to the mixing container **732** in later operations to generate the target prescription fluid. At **474**, if the batch contents are adjusted immediately and responsively to the results of the concentration test, then water or additional electrolyte concentrate may be pumped into the mixing container **732** using the valve **751** settings identified above, depending on whether the concentration measurement indicated over-dilution or under-dilution. If less than 100% of the water dose is used in **470** (as in the embodiment variation identified above), then additional water may be added up to the requirement per prescription. Again, such a water balance may be added after **475** and **454** at **455**.

(188) At **475**, osmotic agent concentrate from osmotic agent concentrate container **738** is pumped to the mixing container **732** by opening respective valves **751** for opening the osmotic agent concentrate line **744** and the inlet line **746** and closing other valves **751** to form a direct path that includes MOTI and MIMO. The osmotic agent concentrate is pumped by the pump **762** from the osmotic agent concentrate container **738**, through the manifold **758** by opening only the clamp **751** that control the osmotic agent concentrate line **744** and the inlet line **746**. The pump draws the osmotic agent concentrate from manifold **758** through the pump tube **763** and into manifold **760** through the inlet line **746** into the mixing container **732**. A volume equal to 100% of the required dose of osmotic agent concentrate is pumped toward the mixing container **471** but a predetermined fraction equal to MOTI and MIMO remains behind. The required dose may be determined, in part, by the results of the conductivity test at **473** as indicated above. The volume transferred may also account for the volume of diluted electrolyte concentrate of the prior batch contents which remains in MOTI and MIMO before the osmotic agent concentrate is pumped. Finally, the residual volume is transferred to the mixing container **732** in the final dilution at **455**, if present, such that the volume of osmotic agent concentrate transferred to the mixing container **732** is in part compensated to account for that additional volume. The batch contents are mixed using the valve settings identified in the discussion of operation **472**. This mixes-in the residual MOTI and MIMO volumes of osmotic agent concentrate remaining behind after pumping the osmotic agent concentrate, as well as the SOMI volume of the mixture, before addition of osmotic agent concentrate.

(189) At **454**, the batch contents may be sampled as discussed in relation to the operation **473** by setting appropriate valves **751** and operating the pump **762**. The conductivity determined from the sample indicates to the controller whether the batch is good and can be used for a treatment cycle or whether it is bad and should be drained and remade or some other recovery cycle implemented.

The addition of osmotic agent concentrate and associated water has a measurable effect on the conductivity. The addition of osmotic agent concentrate, depending on the specific type (dextrose, for example), tends to lower the conductivity. However the concentrate impacts the conductivity, it can be predetermined and stored by the controller so that the conductivity measurement at **454** can be used to determine if the conductivity corresponds to the internal model or is outside a predefined range thereabout. As stated, the controller will enable the batch to be used for a treatment or regenerated or it will prevent usage by preventing the advance of the control system to treatment mode, generate an error signal, drain and generate a new batch, or any combination thereof, based on the conductivity result.

(190) At **455**, if less than 100% of the required water for a complete batch was added to the mixing container **732** at **470**, then the remaining complement of water is added at **455** using the settings described above with regard to operation **470**. The total amount of water displaced is ultimately added to the batch, even though a fraction remains behind initially in MOTI and MIMO. This is because of the additional mixing operation at **476**, where the MOTI and MIMO portions are mixed into the batch. The SOMI volume of the previous mixture attained at the end of **475** is also mixed in.

(191) At **475**, an osmotic agent concentrate volume is transferred to the mixing container **732**. A dose is pumped into the mixing container **732** and the batch contents are mixed. At **454** the conductivity of the batch contents is measured and if it is within limits, control moves on to **455**, and if not, the proportioning is terminated. At **455**, if less than 100% of the water was added at **470**, then the final volume of water is added to the mixing container **732**. At **476**, the batch contents are mixed and the MOTI and MIMO volumes of water are mixed in as well as the prior mixture from SOMI to form the final mixed batch. At **456**, the conductivity is tested using the procedure described above in reference to **473**. At **457**, any sterilizing filters responsible for ensuring sterility of fluids may be tested or redundant filters may be used. If the filter(s) integrity is/are confirmed, then the batch will be released; otherwise, the batch is not released. The possible responses to an out-of-range reading of conductivity may be as described with reference to operation **454**.

(192) Referring to FIG. **16C**, in a further embodiment, suitable for a pumping system and/or method that provides a high degree of volumetric accuracy, water and osmotic agent concentrate and electrolyte concentrates are transferred to the mixing container and mixed **477-481** in a single set of operations relying on volumetric control. At **477** 100% or a fraction of a target water volume is pumped into the mixing container. At **478**, 100% of a target volume of electrolyte is transferred to the mixing container. At **479**, a volume of osmotic agent is pumped into the mixing container. At **480**, if less than 100% of the water was transferred at **477**, then a complementary quantity of water is added to bring the total to 100%. At **480** the conductivity of the mixing container contents can be measured and if necessary additional water added. Conductivity is measured after mixing. At **481** the mixing container contents are mixed. The operations may be followed by a pressure test of a sterilizing filter as discussed with reference with the other embodiments.

(193) FIG. **17B** shows a proportioning and treatment system for peritoneal dialysis **700B**. Two multi-treatment containers **736** and **738** contain electrolyte concentrates and osmotic agent concentrates, respectively. They are connected by aseptic connectors **730** to a fluid circuit **701B** by respective osmotic agent concentrate **744** and electrolyte concentrate **742** lines. Non-aseptic connectors may also be used. In embodiments where the connectors are non-aseptic, the osmotic agent concentrate **744** and electrolyte concentrate **742** lines contain sterilizing filters. Due to the cost and number of filters required this is not a preferred way to ensure sterility. A last fill container **734** may also be connected to the fluid circuit **701B** via last fill line **740**. The last fill container **734** may contain a specific medicament for the last fill cycle of a multi-cycle treatment. The fluid circuit **701B** contains first **758** and second **760** manifolds connected by a pumping tube **763**. The manifolds **758** and **760** define selectable fluid paths connecting various sources of fluids to fluid consumers using clamps **751** under control of a controller **739**. The details of the flow switching

may be as discussed above with respect to similar embodiments. A purified water source **766** supplies purified water to the manifold **758** through redundant sterilizing filters **731**. The filter **733** is a single testable filter that is automatically tested by pumping air by means of an air pump through an air line **737** and measuring pressure, detecting whether the filter's bubble point has been exceeded, and if not, confirming the integrity of a filter membrane of the filter **733**. Alternative filter integrity tests may also be provided such as a pressure decay test. The test of the filter **733** is used by the controller **739** to confirm that a batch is sterile as described in method embodiments in the present disclosure. Manifold **760** is connected by a drain line **756** to a conductivity sensor module **714** through a non-aseptic connector **729**. The conductivity sensor module **714** is a replaceable component interconnectable between outlet manifold **760** and a waste container **768** (or a waste outlet such as a drain). The conductivity sensor module **714** has a pair of conductivity sensors **764** in a drain channel **715**. The conductivity sensors **764** provide independent indications of conductivity that can be compared to indicate a bad sensor and/or to provide a mechanism for flow sensing based on a time of flight of a conductivity perturbation in the flow through the drain channel **715**. The conductivity module **714** engages with the proportioning/cycler machine **772** which houses a valve actuator **721**. The latter is not replaced when the conductivity module **714** is replaced. The conductivity module **714** can be a low cost component by employing plastic conductivity cells, a tube with connectors and a pinching portion defining a valve **751** by separating the valve actuator **721** (the one shown that controls flow through the drain channel **715**) from the tube pinching portion and selecting a low cost arrangement for the conductivity cells **764**, the tubing forming the drain channel **715**, the connectors **729** and a housing or support indicated at **714**.

(194) A mixing container **732** is connected by inlet and outlet lines **746** and **750** to the manifolds **758** and **760**, respectively to allow fluid to be pumped into the mixing container **732**, to be drawn from the mixing container **732**, and to permit mixing via recirculation of the contents of the mixing container **732**. A pump **762** pumps fluid between the manifolds **758** and **760**. A waste container **768** may be attachable to the drain line circuit **765** by a non-aseptic connector **729**. A heater **770** contacts the mixing container **732**. In embodiments, the heater **770** forms a bed on which the mixing container **732** rests. A patient line **754** is connected by a Y-connector to separate lines **748** and **752** to permit the filling and draining of a patient **718** through the patient line **754**, which is connected to a catheter (not shown) by means of another aseptic connector **730**.

(195) In all embodiments, **17A** through **17D** and others, a sampling arrangement, now described, may be provided. Although not shown in FIG. **17A**, a sample line may be provided stemming from header **760**. Referring to the embodiment of FIG. **17D** presently, the sample line **774** is connected to a sample container **773** through a non-aseptic connector **729**. A valve **751** controlling flow through the sample line **757** is controlled to sample fluid from the header **760** automatically by the controller **739**. In embodiments, a temperature of draining dialysis fluid is monitored for a condition indicating an infection or some other condition for which a sample may be automatically drawn and stored during draining according to the condition. See US Patent Publication US20150005699, incorporated by reference elsewhere herein and International Patent Publication WO2018045102, for details of how parameter monitoring of the spent dialysis fluid may be used to detect a condition.

(196) In traditional peritoneal dialysis systems, all of the patient effluent is collected in a large sample bag which may contain, for example, 10 or more liters of fluid. In the present embodiments, small samples (less than the total amount of effluent, are routed to a small volume sample collection container. Thus, an aliquot from each patient drain cycle may be generated automatically in a small container (e.g., ~200 ml, for example, but it could be less or more). The collection container may be a bag. At the end of a treatment, the system controller may output instructions for removing, sealing, and delivering the collected sample. For example, the container may be delivered to the patient's dialysis center which would analyze it to assess the adequacy of therapy.

(197) According to a method, the following control scheme may be implemented by the proportioner/cycler controller **739**. The controller **739** first initiates a drain cycle of a predefined number of drain cycles of an entire treatment. A command indicating the aliquot volume or mass may be generated and used to control the pump **762** of the proportioner/cycler. A command may also be generated to indicate an initial volume or mass to pass to waste container or drain **768** before beginning a diversion of the drain flow while metering the size of the cumulating sample and then switching valves **751** to a configuration where the spent peritoneal dialysis fluid is sent to waste container or drain **768**. The sequence may be implemented using valves **751** and pump **762**. The process of switching between patient line **754** to waste container or drain **768** and patient line to sample container **773** may include halting the pump while the relevant valves **751** are activated and deactivated to define the correct flow path. The volume that is drained before the aliquot is transferred to the sample container **773** may be determined by how long it takes to clear any residual fluid (fresh peritoneal dialysis fluid, for example) in MIMO. In embodiments, the sample container **773** may be changed at each drain cycle in order to collect samples representative of multiple cycles of a single treatment. The controller may also permit sampling to be done in a manner that acquires multiple fractions throughout the drain cycle to be stored in the sample container **773** by repeatedly, over multiple instances, diverting to drain and diverting to the sample container **773**. This may allow for the sample to better represent the composition of the entire drain volume which may change through the drain cycle. These fractional samples can also be stored in separate sample containers **773**. Parameters of collection, which may be set by the patient, nurse, or physician accessing the controller **739** locally or remotely, include: The volume of the sample; Spacing of samples (for example 1 spacing would be a sample for each drain cycle and 2 spacing would refer to every other drain cycle); For spaced samples, the first drain cycle to start sampling; The volume to be discarded before beginning the diversion to the sample container **773**; The days on which to take one or more samples and according to a predefined cluster of the listed parameters; A permitted number of reschedulings of samplings; A schedule of samplings by date, day of week, day of month, or number of times per time interval; The number of samples per drain cycle; The number of samples per treatment; and The flow rate of draining.

(198) The controller **739** may store a specific schedule for the taking of samples, for example a particular day of the week. The controller **739** may output a reminder for the benefit of an operator or patient to let that person know of an imminent scheduled sample so that the user can prepare. For example, the system may let the patient know that today is a day to take a sample. The notification can be attended, or followed, by an input control that accepts input indicating whether the patient desires to override, comply, or reschedule. The controller **739** may reschedule automatically in the event the patient or other user fails to acquire samples or overrides. The controller **739** may store a guided instruction script for helping the user to set up and store samples after acquisition. The guided instruction may be stored on a web server and displayed on the proportioner/cycler through a browser so that the script can be updated centrally. The guided instruction may be prompted upon entry of a user command indicating that the user will perform a scheduled or unscheduled sampling procedure.

(199) Referring now to FIG. **26A**, an proportioning and treatment system for peritoneal dialysis **700G** has a fluid circuit **705** that is identical to **701B** except for the connection of a medication container **759** at port **730** or port **729**. Connections at both are shown but it should be understood that it may be that only one may be connected at a given time and the ports **730** and **729** may otherwise be used for the purpose described above. Medication container **759** may contain a medication (e.g., antibiotics), an anticoagulant, or other substance to be mixed with peritoneal dialysis fluid. The substance may be mixed with the contents of the mixing container **732** in an automated way.

(200) Referring to FIG. **26B**, at **S900** the substance container **759** is connected to the first manifold **758**. Then at **S902** the mixing container **732** is filled by preparing a dialysis fluid. Then at **S904** the

valve **751** is opened and the pump operated to draw the substance from substance container **759** into the mixing container **732**. Then at **S906**, the pump recirculates the contents of the mixing container **732** in a recirculating mixing mode to mix the substance with the dialysis fluid.

(201) Referring to FIG. **26C**, at **S908** the substance container **759** is connected to the second manifold **760**. Then at **S914** the mixing container **732** is filled by preparing a dialysis fluid. Then at **S916** the valve **751** is opened and the pump operated in reverse to draw the substance from substance container **759** into the mixing container **732**. Then at **S918**, the pump recirculates the contents of the mixing container **732** in a recirculating mixing mode to mix the substance with the dialysis fluid.

(202) Referring to FIG. **23**, in embodiments, the drain is replaced by a container connected to a scale **771** that generates a weight indication that is stored by the controller **739**. This total weight can be combined with a detected measure of the volume captured in the same container **773** to provide a cumulative total mass of collected peritoneal dialysis fluid. For example, the total mass can be taken as an average of the mass calculated from weight and the mass calculated from volumetric measurement. These data may be associated by a code with a code read from the sample container **773** such as by means of a bar code, smart chip, RFID tag, or other means. The data indicative of cumulative total mass estimate may be uploaded to a web site for a laboratory with data representing the sample container **773** code. Alternatively, a chip attached to the sample container **773** may hold the cumulative mass data so that when shipped to a laboratory, the data can be read by the workers analyzing the samples. In embodiments, the sample container **773** and the waste container **768** can be attached to the scale **771** or may be formed as a single disposable unit with the sample bag portion being detachable from the waste container **768**.

(203) The fluid circuit **701F** connects to proportioning/cycler machine **772** by a mechanism that aligns clamps **751** with respective clamping portions of lines **741**, **740**, **742**, **744**, **750**, **746**, **752**, and **756**. Various such mechanisms are known in the art such as supports that hold tubing portions at predefined positions in cassettes and cartridges and compact fluid circuits that can be easily laid over a set of actuators and sensors. The manifolds and clamps can be replaced by a variety of different types of flow selector devices known in the art, so the current proportioning and treatment system is not limited to using flow selectors based on clamping of tubing. If the pump **762** is a peristaltic pump, a pumping tube segment of line **763** may be aligned by the connection of the fluid circuit **701F**. The purified water source **766** may be housed in an enclosure **767** together with the drain line circuit **765** or portions of either. The waste container **768** may be housed in the same enclosure, or not, as illustrated. The concentrate containers **736** and **738** may contain sufficient concentrate for multiple fill/drain cycles, multiple days' worth of treatments, each consisting of multiple fill/drain cycles, a week's worth of treatments, a month's worth of treatments, or some other schedule. The concentrate containers **736** and **738** may be independently replaceable by use of the aseptic connectors. The benefits of independent replacement are discussed elsewhere in the present disclosure. The contents of the last fill medicament container **734** may be fully diluted or may consist of, or include, a concentrate that requires further dilution. The manifolds **758** and **760** may have a minimum volume to reduce waste when changing over fluids. In embodiments, the maximum hydraulic diameters of the manifolds **758** and **760** are each no more than 5 times the diameter of the largest line connecting to them. In further embodiments, they are no more than 3 times the diameter of the largest line and in still further embodiments, no more than twice. In other respects, the embodiment of FIG. **23** is identical to that of FIG. **18A**.

(204) FIG. **17C** shows an proportioning and treatment system for peritoneal dialysis **700C**. Two multi-treatment containers **736** and **738** contain electrolyte concentrates and osmotic agent concentrates, respectively. They are connected by aseptic connectors **730** to a fluid circuit **701C** by respective osmotic agent concentrate **744** and electrolyte concentrate **742** lines. Non-aseptic connectors may also be used. In embodiments, where the connectors are non-aseptic, the osmotic agent concentrate **744** and electrolyte concentrate **742** lines contain sterilizing filters. Due to the

cost and number of filters required this is not a preferred way to ensure sterility. A last fill container **734** may also be connected to the fluid circuit **701C** via last fill line **740**. The last fill container **734** may contain a specific medicament for the last fill cycle of a multi-cycle treatment. The fluid circuit **701E** contains first **758** and second **760** manifolds connected by a pumping tube **763**. The manifolds **758** and **760** define selectable fluid paths connecting various sources of fluids to fluid consumers using clamps **751** under control of a controller **739**. The details of the flow switching may be as discussed above with respect to similar embodiments. A purified water source **766** supplies purified water to the manifold **758** through redundant sterilizing filters as shown FIG. **17A** at **731**, or a testable filter may be used as shown in FIG. **17C**. The filter **733** is a single testable filter that is automatically tested by pumping air by means of an air pump through an air line **737** and measuring pressure, detecting whether the filter's bubble point has been exceeded, and if not, confirming the integrity of a filter membrane of the filter **733**. Alternative filter integrity tests may also be provided such as a pressure decay test. The test of the filter **733** is used by the controller **739** to confirm that a batch is sterile as described in method embodiments in the present disclosure. Manifold **760** is connected by a drain line **756** to a conductivity sensor module **714** through a non-aseptic connector **729**. The conductivity sensor module **714** is a replaceable component interconnectable between outlet manifold **760** and a waste container **768** (or a waste outlet such as a drain). The conductivity sensor module **714** has a pair of conductivity sensors **764** in a drain channel **715**. The conductivity sensors **764** provide independent indications of conductivity that can be compared to indicate a bad sensor and/or to provide a mechanism for flow sensing based on a time of flight of a conductivity perturbation in the flow through the drain channel **715**. The conductivity module **714** engages with the proportioning/cycler machine **772** which houses a valve actuator **721**. The latter is not replaced when the conductivity module **714** is replaced. The conductivity module **714** can be a low-cost component by employing plastic conductivity cells, a tube with connectors and a pinching portion defining a valve **751** by separating the valve actuator **721** (the one shown that controls flow through the drain channel **715**) from the tube pinching portion and employing injection-molded rigid plastic for the conductivity cells **764**, tubing to define the drain channel **715**, aseptic connectors **729** such as locking luer-type, and a housing or support indicated at **714**.

(205) A mixing container **732** is connected by inlet and outlet lines **746** and **750** to the manifolds **758** and **760**, respectively, to allow fluid to be pumped into the mixing container **732**, to be drawn from the mixing container **732**, and to permit mixing via recirculation of the contents of the mixing container **732**. A pump **762** pumps fluid between the manifolds **758** and **760**. A waste container **768** may be attachable to the drain line circuit **756** by a non-aseptic connector **729**. A heater **770** contacts the mixing container **732**. In embodiments, the heater **770** forms a bed on which the mixing container **732** rests.

(206) A patient line **754** is connected to the fluid circuit in such a manner as to ensure that fluid sent to the patient through fill line **755** is sterile filtered by sterilizing filter **719**, thereby providing a sole, or additional, assurance against exposure of the patient to unsterile fluid including fluids or fluids containing pyrogens, which, as is known, may be removed by filter membranes with a suitably small pore diameter, for example, 0.2 micron.

(207) A patient fill/drain line **754** has an air detector **753**. Fluid is received through a junction from a fill line **755** and drained through drain line **748**, flow being controlled in each of the fill line **755** and the drain line **748** by respective valves **751**. Fluid is supplied to a batch inlet line **746** and the fill line **755** from header **760** through a common batch/fill line **716** from a respective junction **717**. The selection of the two branches of the junction, namely the batch inlet line **746** and the fill line **752** is carried out by respective valves **751** that control flow through these branches. A sterile/pyrogen filter **733** filters all fluid flowing to the patient by filtering all fluid flowing through the fill line **752**. This may obviate the need for any other filters on fluid entering the system such as water inlet **741** using filter **733** on the patient fill line. A common fill/inlet line **716** feeds the inlet

746 and fill **755** lines. The line **755** which conveys fluid to the patient **718** has a testable sterile filter **719**. Flow through lines **746** and **755** is controlled by respective valves **751**.

(208) The controller **739** may invoke a failsafe operation if air is detected above a predefined threshold in the fill drain/line **754**. Flow in inlet line **746** is controlled with the additional function that the valve **751** controlling flow in the fill line **755** is closed when fluid is directed to the mixing container **732**.

(209) The fluid circuit **701C** connects to proportioning/cycler machine **772** by a mechanism that align clamps **751** with respective clamping portions of lines **741**, **740**, **742**, **744**, **750**, **746**, **752**, **755**, and **756**. Various such mechanisms are known in the art such as supports that hold tubing portions at predefined positions in cassettes and cartridges and compact fluid circuits that can be easily laid over a set of actuators and sensors. The manifolds and clamps can be replaced by a variety of different types of flow selector device known in the art, so the current proportioning and treatment system is not limited to using flow selectors based on clamping of tubing. If the pump **762** is a peristaltic pump, a pumping tube segment of line **763** may be aligned by the connection of the fluid circuit **701C**. The purified water source **766** may be housed in an enclosure **767** together with the drain line circuit **765** or portions of either. The waste container **768** may be housed in the same enclosure, or not, as illustrated. The concentrate containers **736** and **738** may contain sufficient concentrate for multiple fill/drain cycles, multiple days' worth of treatments, each consisting of multiple fill/drain cycles, a week's worth of treatments, a month's worth of treatments, or some other schedule. The concentrate containers **736** and **738** may be independently replaceable by use of the aseptic connectors. The benefits of independent replacement are discussed elsewhere in the present disclosure. The contents of the last fill medicament container **734** may be fully diluted or may consist of, or include, a concentrate that requires further dilution. The manifolds **758** and **760** may have a minimum volume to reduce waste when changing over fluids. In embodiments, the maximum hydraulic diameters of the manifolds **758** and **760** are each no more than 5 times the diameter of the largest line connecting to them. In further embodiments, they are no more than 3 times the diameter of the largest line and in still further embodiments, no more than twice. Pressure sensors **769** are positioned on either side of the pump **762** to detect pump inlet and outlet pressures in pump tube **763**. Signals corresponding to the pressures are applied to the controller **739** and used for pump pressure compensation and/or pump calibration as discussed elsewhere and in US Patent Publication 2015-0005699, hereby incorporated by reference in its entirety herein.

(210) FIG. **17D** shows an proportioning and treatment system for peritoneal dialysis **700D** with a fluid circuit **701D**. The system **700D** differs from **700C** in that a testable sterilizing filter **719** is used for the fill line **755** to ensure against infusion of pyrogens and/or pathogens.

(211) Note that instead of separate inlet **746** and outlet **750** lines leading into and out of the mixing container **732**, the mixing container **732** may be attached by a single line. In such a case, mixing of the contents may be accomplished by flowing fluid between the mixing container **732** and an accumulator connected to one of the manifolds. A flow switch could be used to interconnect the single line of the mixing container to a selectable one of the manifolds. Also, the pump **762** may be run in either direction so that the inlet and outlet lines **746** and **750** can switch roles under control of the controller. Thus, the modifiers "inlet" and "outlet" serve to differentiate the two lines **746** and **750** but are not strictly limiting in terms of structure or function and it should be evident that the functionality of batch preparation, mixing, and treatment can be carried out with the roles of inlet and outlet switched during certain operations. For other operations, the manifolds may be modified to permit a different fluid source and destination to be selected that is not possible with the depicted configuration. Such variations are contemplated within the scope of the disclosure unless otherwise expressly limited.

(212) FIG. **18A** shows a fluid circuit **701E** having a disposable unit that is initially provided with empty, low-capacity concentrate containers **780** and **781** which are filled from multi-treatment concentrate containers **736** and **738** during a dialysis fluid preparation cycle. A proportioning and

treatment system for peritoneal dialysis **700E** has two multi-treatment concentrate containers **736** and **738** that contain electrolyte concentrates and osmotic agent concentrates, respectively. The multi-treatment concentrate containers **736** and **738** are connected through a fluid module **723** by means of a single fluid intake line **728** which has a testable filter **733** that forms part of a disposable with a fluid circuit **701E**. The disposable unit is connected through the fluid intake line **728** by an aseptic connector **743** (same type as **729**) to the fluid module **723**. The fluid module **723** may be a permanent structure that receives multi-treatment concentrate containers **736** and **738** as a replaceable unit or as separate containers according to various embodiments. The fluid module **723** may also have a pump **788** and a purified water source **766** as well as a fluid switch circuit **747** that provides for the selective flow of water and the different concentrates into the fluid intake line **728**. (213) The testable filter **733** may be preconnected to the fluid circuit **701E** and sterilized with the remainder of the fluid circuit **701E** as a unit which may be sealed in a sterile package and delivered for use. An air pump **735** and pressure sensor **727** may be provided as a permanent fixture of the proportioning/cycler machine **772**.

(214) The initially empty low-capacity concentrate containers **780** and **781** are preconnected along with the initially empty mixing container **732** to the remainder of the fluid circuit **701E**. The low-capacity concentrate containers **780** and **781** may be filled, as discussed later, with osmotic agent concentrate and electrolyte concentrate from multi-treatment concentrate containers **736** and **738**, respectively. A last fill container **734** may also be connected by an aseptic connector **730** to the fluid circuit **701E** via last fill line **740**. The last fill container **734** may contain a specific medicament for the last fill cycle of a multi-cycle treatment. The contents of the last fill medicament container **734** may be fully diluted or may consist of, or include, a concentrate that requires further dilution.

(215) The fluid circuit **701E** contains first **758** and second **760** manifolds connected by a pumping tube **763**. The manifolds **758** and **760** define selectable fluid paths connecting various sources of fluids to fluid consumers using clamps **751** under control of a controller **739**. The details of the flow switching may be as discussed above with respect to similar embodiments. The manifolds **758** and **760** may have a minimum volume to reduce waste when changing over fluids. In embodiments, the maximum hydraulic diameters of the manifolds **758** and **760** are each no more than 5 times the diameter of the largest line connecting to them. In further embodiments, they are no more than 3 times the diameter of the largest line and in still further embodiments, no more than twice. Pressure sensors **769** are positioned on either side of the pump **762** to detect pump inlet and outlet pressures in pump tube **763**. Signals corresponding to the pressures are applied to the controller **739** and used for pump pressure compensation and/or pump calibration as discussed elsewhere and in US Patent Publication 2015-0005699, hereby incorporated by reference in its entirety herein. A waste container **768** may be attachable to the drain line circuit **765** by a non-aseptic connector **729**.

(216) The filter **733** is a single testable filter that is automatically tested by pumping air by means of an air pump **735** through an air line **737** and measuring pressure by means of pressure sensor **727**, detecting whether the filter's bubble point has been exceeded, and if not, confirming the integrity of a filter membrane of the filter **733**. Alternative filter integrity tests may also be provided such as a pressure decay test. The test of the filter **733** is used by the controller **739** to confirm that a batch is sterile as described in method embodiments in the present disclosure.

(217) Manifold **760** is connected by a drain line **756** to a conductivity sensor module **714** through a non-aseptic connector **729**. The conductivity sensor module **714** is a replaceable component interconnectable between the outlet manifold **760** and a waste container **768** (or a waste outlet such as a drain). The conductivity sensor module **714** has a pair of conductivity sensors **764** in a drain channel **715**. The conductivity sensors **764** provide independent indications of conductivity that can be compared to indicate a bad sensor and/or to provide a mechanism for flow sensing based on a time of flight of a conductivity perturbation in the flow through the drain channel **715**. The

conductivity module **714** engages with the proportioning/cycler machine **772** which houses a valve actuator **721**. The latter is not replaced when the conductivity module **714** is replaced. The conductivity module **714** can be a low-cost component by employing plastic conductivity cells, a tube with connectors and a pinching portion defining a valve **751** by separating the valve actuator **721** (the one shown that controls flow through the drain channel **715**) from the tube pinching portion and selecting a low cost arrangement for the conductivity cells **764**, the tubing forming the drain channel **715**, the connectors **729**, and a housing or support indicated at **714**.

(218) A mixing container **732** is connected by inlet and outlet lines **746** and **750** to the manifolds **758** and **760**, respectively, to allow fluid to be pumped into the mixing container **732**, to be drawn from the mixing container **732**, and to permit mixing via recirculation of the contents of the mixing container **732**. A pump **762** pumps fluid between the manifolds **758** and **760**. A waste container **768** may be attachable to the drain line circuit **765** by a non-aseptic connector **729**. A heater **770** contacts the mixing container **732**. In embodiments, the heater **770** has a bed on which the mixing container **732**, in the form of a plastic bag, rests. A patient line **754** is connected by a Y-connector to separate lines **748** and **752** to permit the filling and draining of a patient **718** through the patient line **754**, which is connected to a catheter (not shown) by means of another aseptic connector **730**. A sample line **757** is connected to a sample container **773** through a non-aseptic connector **729**, or may be pre-attached. A valve **751** controlling flow through the sample line **757** is controlled to sample fluid from the header **760** automatically by the controller **739**. In embodiments, a temperature of draining dialysis fluid is monitored for a condition indicating an infection or some other condition for which a sample may be automatically drawn and stored during draining according to the condition. See US 2015-0005699, incorporated by reference elsewhere herein and International patent publication WO2018045102, hereby incorporated by reference in its entirety for details of how parameter monitoring of the spent dialysis fluid may be used to detect a condition.

(219) The fluid circuit **701E** connects to proportioning/cycler machine **772** by a mechanism that align clamps **751** with respective clamping portions of lines **741**, **740**, **742**, **744**, **750**, **746**, **752**, and **756**. Various such mechanisms are known in the art such as supports that hold tubing portions at predefined positions in cassettes and cartridges and compact fluid circuits that can be easily laid over a set of actuators and sensors. The manifolds and clamps can be replaced by a variety of different types of flow selector devices known in the art, so the current proportioning and treatment system is not limited to using flow selectors based on clamping of tubing. If the pump **762** is a peristaltic pump, a pumping tube segment of line **763** may be aligned by the connection of the fluid circuit **701B**.

(220) The concentrate containers **736** and **738** may contain sufficient concentrate for multiple fill/drain cycles, multiple days' worth of treatments, each treatment consisting of multiple fill/drain cycles. For example, concentrate containers **736** and **738** may contain sufficient concentrate a week's worth of treatments, a month's worth of treatments, or some other schedule. The concentrate containers **736** and **738** may be independently replaceable by use of the aseptic connectors. The benefits of independent replacement are discussed elsewhere in the present disclosure. The pump **788** draws and pumps a concentrate selected by valves that control flow through electrolyte concentrate line **790** and osmotic agent concentrate line **789**, respectively. The output of the pump **788** is pumped through a common concentrate line **791** through the connector **743** into the fluid intake line **728**. When water is conveyed through the fluid intake line, it is pumped by the pump **762** with corresponding valves opened as in prior embodiments by closing the valves **751** that control flow through electrolyte concentrate line **790** and osmotic agent concentrate line **789**, respectively, and by opening the valve **751** that controls the flow through a water source line **792**. A pressure sensor **727** may be provided in the water source line **792** to control the flow of water as described with reference to FIGS. **19A** through **19M**.

(221) Note that in all the embodiments having a water source such as **766**, the latter may be

provided with a pump **794** that pumps water independently of the pump of a downstream proportioning device and/or cyclor such as pump **762**.

(222) FIGS. **18B** through **18D** are a single flow chart illustrating a method embodiment for controlling the embodiment of FIG. **18A**. The chart portion of FIG. **18B** is linked at the end to the beginning of the flow chart of FIG. **18C** as indicated by the letter A in a circle. The chart portion of FIG. **18C** is linked at the end to the beginning of the flow chart of FIG. **18D** as indicated by the letter B in a circle. At **S502**, the pump **762** is used to pump water from the fluid source module **723** to the drain to prime the fluid circuit manifolds **758** and **760** as well as the lines leading from the fluid source module **723** to the waste container or drain **768**. The controller **739** stores a predefined value to indicate how much water to pump at this stage. For example, the controller **739** may store a predefined number of cycles of the pump **762** or a predefined volume. The controller **739** may be programmed to translate the predefined volume to a predefined number of cycles to implement a control procedure to regulate the volume transferred responsively to the predefined volume.

Alternatively, the controller **739** may store a predetermined speed and interval of operation that corresponds to the predefined volume. Other alternatives are possible. In the operation **S502**, only the valves **751** required to open the specified path are opened and the others are closed to restrict flow to the predefined path. This is the case for all the operations described by the flow chart.

(223) At **S503**, an optional operation is performed in which a sample of each concentrate is pumped to the drain to generate a pressure drop across the filter **733** and to use the pressure drop to identify the type of concentrate solution by its viscosity. For example, the osmotic agent concentrate is more viscous than the electrolyte concentrate, and therefore the pressure drop for a given flow rate will be higher. The pressure drop may be indicated by a single downstream pressure by the pressure sensor **769** since the upstream pressure may be assumed to be sufficiently identical between the two test conditions to indicate a difference. Thus, a lower pressure at sensor **769** would indicate the more viscous fluid. The controller **739** may store the identity of the type of concentrate associated with lines **789** and **790** and control the corresponding valves **751** accordingly. Alternatively, if one type of concentrate is required to be connected to a respective connector, then the controller **739** may identify a misconnection and generate an output from the controller indicating the misconnection so that corrective action can be taken.

(224) At **S504**, the valves **751** are opened to define a path from the water source **766** to the waste container or drain **768**. Water is pumped by the pump **794** in tandem with the pump **762** to flush the path with water. Optionally, the conductivity of the fluid passing by conductivity sensors **764** may be detected to serve as an indication that sufficient water has been flushed to prime and clear the flow path. Alternatively, another criterion may be used to stop the flow of water, such as a predetermined volume of water being flushed.

(225) At **S505**, a quantity of electrolyte concentrate sufficient to prime the lines from the electrolyte concentrate container **736** through the manifold **758** and at least partly into the outflow line **750** is pumped by pump **788**. This process may prime the sterilizing filter **733**. The total quantity may be selected to be sufficient to ensure that the sterilizing filter **733** is primed and flushed of any air. This priming step may be performed at a preselected flow rate determined to be optimal for priming of the filter **733**, for example a flow rate of about 30 ml/min.

(226) At **S506**, a sufficient quantity of electrolyte concentrate for a single cycle or for a full treatment (e.g., daily treatment) including multiple fill cycles is pumped through the path **790**, **791**, **728**, **745**, **758**, **742** with all valves **751** closed except those defining this path. This has the effect of priming the electrolyte concentrate line **742** as well as providing a sufficient amount of electrolyte concentrate in the osmotic agent container **781** to generate multiple batches each for respective fill cycles in sufficient number for a full treatment, for example a single day's treatment.

(227) At **S510**, the pump **788** pumps sufficient osmotic agent concentrate into mixing container **732** to prime the lines and the header **760**. The lines include batch outlet line **750**, fluid line **745**, and osmotic agent concentrate line **789**, which are opened by means of respective valves **751**. The

volume transferred may be determined to be sufficient to prime the lines and header **760** leading to osmotic agent concentrate line **744**.

(228) At **S514**, a sufficient quantity of osmotic agent concentrate for a single cycle or for a full treatment (e.g., daily treatment) that includes multiple fill cycles, is pumped through the path **790**, **791**, **728**, **745**, **758**, **744** with all valves **751** closed except those defining this path. This has the effect of priming the osmotic agent concentrate line **742** as well as providing a sufficient amount of osmotic agent concentrate in the osmotic agent container **781** to generate multiple batches each for a respective fill cycle and in sufficient number for a full treatment, for example a single day's treatment.

(229) At **S520**, a flow channel is established by closing all valves **751** except ones required to flow from the water source **766** to outlet line **750**. Water is pumped from the water source **766** using the pump **794** to prime the manifold **758** and the outlet line **750** thereby transferring a small amount of water into the mixing container **732**.

(230) At **S522**, a recirculating channel between in the inflow **746** and outflow **750** lines through the pump **762** is established and the mixing container **732** contents are pumped for a period of time or a number of pump rotations sufficient to break in the pumping tube segment of pump tube **763**. The contents of the mixing container **732** may be mixed by this process.

(231) At **S528**, if a special last fill, different from the prescriptions generated from the concentrates, is to be used, a special last fill medicament container **734** will be provided. At **S528**, the last fill line **740** may be primed by flowing a portion of the last fill container **734** contents to a waste container or drain **768** to prime the last fill line **740**.

(232) At **530**, the pump **794** pumps a pre-determined volume of water into the mixing container **732**. The pump recirculates fluid from the mixing container **732** through inflow and outflow lines **746** and **750** for a time sufficient to break in pump tube segment and mix contents. This is a closed loop path that includes the manifolds **758** and **760**, the inflow and outflow lines **746** and **750** and the mixing container **732**.

(233) At **S532**, the controller **739** performs an integrity test of the filter **733** on fluid intake line **728**. This is to confirm that all fluids that have flowed into the fluid circuit are sterile/pyrogen-free. If the integrity of the filter membrane is not confirmed, the controller **739** may perform an error recovery operation by instructing the operator to replace fluid circuit **701E**. The controller **739** is programmed at least to generate a signal indicating a failed test. The controller **739** may prevent fluid in the mixing container **732** from being used by pumping the contents to the drain automatically and generating an output on the user interface indicating a failed filter, along with instructions for replacing the fluid circuit.

(234) At **S534**, the controller **739** opens a circuit through manifolds **758** and **760** from the water source to drain and flows water through the open circuit to rinse the conductivity sensors **764**. The conductivity may be monitored by the controller **739** to confirm that a sufficient amount of water has been transferred to rinse the conductivity cells to a predetermined threshold.

(235) At **S536**, the controller **739** opens a circuit including line **742** through manifolds **758** and **760** through to drain and passes a small bolus (e.g., 6-8 ml) from electrolyte concentrate container **780** into manifold **758**. This stores a marker in the line that ultimately gets pumped to the conductivity sensors **764** and is used for calibration of the pump **762**.

(236) At **S538**, a circuit is opened by operating valves **751** that includes water line **728** manifolds **758** and **760** and runs through to the drain from the purified water source **766** to flow a small purified water spacer (e.g. 10 ml.) from the fluid module **723** into the open circuit such that it flows into it but does not reach the conductivity sensors nor does it push the bolus formed at **S536** to the conductivity sensors. Rather, the bolus and the spacer are queued in the fluid path waiting for **S540** to perform a calibration operation by measuring time of flight of the bolus. That is, with a fixed volume of the channel between the conductivity sensors, the system can be calibrated to determine the flow rate from the time delay between the indications of the perturbation crossing the two

conductivity sensors.

(237) At S540, the controller 739 opens a circuit including outflow line 750 through manifolds 758 and 760 through to drain and pumps sufficient fluid from mixing container 732 (about 50 ml) to push the electrolyte concentrate bolus and the water spacer past the conductivity sensors 764 to calibrate the pump. This system is described in the US 2015-0005699 incorporated by reference. The technique is for the controller to calculate the volume flow rate of fluid by detecting the cross of a conductivity perturbation across two spaced apart conductivity sensors. With a fixed volume of the channel between the conductivity sensors, the system can be calibrated to determine the flow rate from the time delay between the indications of the perturbation crossing the two conductivity sensors.

(238) At S542, the controller 739 flows sufficient water toward mixing container 732 (about 22.6 ml. for example) to fill inflow line 746 with water. To ensure the inflow line 746 is completely filled, an amount sufficient to transfer some water to the mixing container 732 is pumped.

(239) At S544 the controller 739 runs the pump 762 so as to drain the mixing container 732 until a vacuum is detected on pressure sensor 769. The controller then calculates a discounted value for fluid accounting purposes accounting for the total volume of water MOTI in 746 to account for effect of vacuum drawn on the inflow line 746

(240) At S546 the controller 739 pumps water to the drain to prime the manifolds 758 and 760 with water. All valves 751 are closed except those that define a path from the water source 766 to the drain.

(241) At S548 the controller 739 pumps 100% or less (e.g. 50%) of a target volume of water into the mixing container 732. This is the amount of water the controller 739 determines is required for a ready-to-use PD dialysis fluid according to a current prescription stored by the controller 739.

(242) At S550 the controller 739 pumps a predetermined amount of water from mixing container 732 to waste container or drain 768 to fill the mixing container 732 outflow line 750 with water to fill the volumes defined as MIMO, MOTI, and SOMI, that is, the inflow and outflow lines 746 and 750, the manifolds 758 and 760 and the pump tube 763.

(243) At S552 the controller 739 pumps 100% of the electrolyte concentrate required for the target prescription into the mixing container 732 (noting that the reverse order of electrolyte and osmotic agent is also possible, so osmotic agent with electrolyte sufficient to act as a marker may be added first instead).

(244) At S554 the controller 739 mixes the mixing container 732 contents by recirculating through the lines 746 and 750 and the manifolds 758 and 760 using the pump 762.

(245) At S556 the controller 739 opens a path from the mixing container 732 to the drain and pumps a quantity of its contents sufficient to test conductivity to confirm the level of dilution of electrolyte. Any difference between the actual and expected conductivity measurements is compared to a threshold and if the threshold is exceeded, at S558, additional water or electrolyte concentrate may be added to provide the target ratio.

(246) At S558 the controller 739 conditionally pumps further water or electrolyte concentrate responsively to the previous conductivity test done at S556. This process may be iterative to provide, effectively, a titration until the required ratio of electrolyte to water is achieved. In embodiments, the total measured water volume is used as ground truth by the controller 739 for purposes of adjusting the second concentrate (osmotic agent concentrate in this example) to be added.

(247) At S560 the controller 739 pumps osmotic agent concentrate into the mixing container 732 using ratiometric control of transferred concentrate (noting the reverse order of concentrates is also possible).

(248) At S562, the controller 739 mixes the mixing container 732 contents by recirculating through the lines 746 and 750 and the manifolds 758 and 760 using the pump 762.

(249) At S564 the controller 739 tests conductivity of mixing container contents and passes or fails

the batch based on the result by passing a sample from the mixing container **732** to the conductivity sensors **764**.

(250) At **S566**, the controller **739** determines and adds the complement of water depending on the initial amount provided at **S548**. In the example of 50% water, the 50% balance of water is added. If the quantity of water was adjusted in **S558**, then the balance is adjusted based on any additional quantity added to the contents of the mixing container **732**.

(251) At **S568**, the mixing container contents are mixed by the controller **739** by recirculating through the lines **746** and **750** and the manifolds **758** and **760** using the pump **762**.

(252) At **S570**, the controller **739** tests conductivity of mixing container **732** contents and passes or fails the batch based on the result. At this point, the failure of the batch may not be compensated by adjusting its constituents. If the contents do not meet the predefined expected conductivity, the contents of the mixing container **732** may be blocked from further use and a signal may be generated to indicate the failure. In embodiments, the contents of the mixing container **732** may be automatically flushed to drain in the event of a failure.

(253) At **S572**, the controller **739** tests the sterilizing filter(s) and passes or fails the completed batch based on the result of the filter test. At this point, the contents of the mixing container **732** may be blocked from further use and a signal may be generated to indicate the failure. In embodiments, the contents of the mixing container **732** may be automatically flushed to drain in the event of a failure.

(254) FIGS. **18E** through **18H** show various fluid circuit configurations for the fluid module **723** of the foregoing embodiments such as that of FIG. **18A**. In the embodiment of FIG. **18E**, a fluid module **723A** has concentrate containers **736** and **738** which are preconnected to the respective concentrate lines **790** and **789** which are interconnected to a connector **798** for connection to the water inlet of a fluid circuit such as that of FIG. **18A**. In this embodiment, the concentrate containers **736** and **738** may be mechanically attached to each other or enclosed in a common housing indicated at **795A** to form a single unit that may be replaced, as a unit, when one of the concentrate containers, **736** or **738**, is exhausted. FIG. **18F** shows an embodiment in which the concentrate containers **736** and **738** each has its own connector **799** which allows each of the concentrate containers **736** and **738** to be replaced independently of the other. The concentrate containers **736** and **738** may be housed, or held, in a permanent fixture **795B**. FIG. **18G** shows a fluid module **723C** where one of the concentrate containers **738** is not disconnectable from a fluid line (here, osmotic agent concentrate line **789**) while the other concentrate container **736** is connected by a removable connector **799**. In embodiments, which of the two concentrates is not disconnectable can be reversed so that the electrolyte concentrate container **736** is not disconnectable and the osmotic agent concentrate container **738** is disconnectable. In this embodiment, only one of the types of concentrate is ever preconnected to a line, such as line **789**. The configuration of the embodiment of FIG. **18G** prevents connection of a respective one of the lines **789** and **790** to the wrong type of concentrate container. FIG. **18H** shows an embodiment **723D** in which separate testable filters are provided for each of the concentrates **736** and **738**. In this case, the fluid module may have its own air pumps **735** and pressure sensors **727**.

(255) Note that in any of the embodiments, the air pump's **735** functions may be provided by a single pump with multiple lines stemming from a common output. Each may be controlled by a respective valve under control of the controller.

(256) Note that in any of the embodiments in which a fluid source module is provided to actively pump fluid to a consuming appliance such as proportioning and treatment systems for peritoneal dialysis **700A-700E**, the fluid module may be controlled by direct electronic communication such as wired or wireless. Such direct communication may be used for closed loop control of the fluid module pump by the proportioning and treatment system for peritoneal dialysis controller, for example.

(257) In any of the fluid module embodiments (**723**, **723A**, **723B**, **723C**, **723D**), the pump **794** that

pumps water may be of a type that pushes water through a filtration system and may be of a high precision non-pulsatile type such as a gear pump or a screw pump. This pump, indicated in embodiments at **794**, may be closed-loop controlled based on pressure by the pressure sensor **727A**. In any of the fluid module embodiments, the valve of the type **751** indicated at **749** in FIG. **18A** and corresponding locations in other embodiments is controlled by the controller **739**.

(258) In embodiments in which the water pump **794** is activated and deactivated in response to pressure (see for example FIG. **9A-19C** and associated discussion) and is also closed-loop controlled to maintain a predefined pressure range, the control of the water pump **794** may be regulated by a control algorithm such that a pressure rise above a predefined level or above a predefined rate due to the halting of the cyclor pump may be detected quickly. For example, if the pressure rises above a predefined level or rises faster than a predefined rate, the water pump controller may detect that condition and halt the water pump rather than slewing to a low flow rate in response to the close-loop control algorithm. The controller may also terminate closed-loop control of the flow rate if such a condition is detected.

(259) The direct control of water and/or other fluid sources by wired or wireless digital signals may be preferred. FIGS. **19A-19H** and **19J-19M** show embodiments for control of a fluid source, here exemplified by a water source **810**, without direct data communications applying control inputs from a medical treatment device, here exemplified by a peritoneal dialysis fluid preparation device **800**, which may optionally have a cyclor as well. Referring to FIG. **19A**, a peritoneal dialysis fluid preparation device **800** has a pump **808** and a fluid circuit **802** for mixing fluids and for performing a peritoneal dialysis treatment. The water source **810** has a pump **806** that conveys water to the peritoneal dialysis fluid preparation device **800** through a water line **803**. A pressure sensor **804** detects pressure in the water line and applies a corresponding signal to a controller **807** of the water source **810**. The controller **807** controls the pump **806**. FIG. **19B** shows a control loop executed by a controller **809** of the peritoneal dialysis fluid preparation device **800**. At **S400**, the controller **809** receives or generates a command for water. This may be as described in the foregoing embodiments as incident to a concentrate dilution operation in the preparation of a dialysis fluid by the peritoneal dialysis fluid preparation device **800**. At **S402A** the peritoneal dialysis fluid preparation device **800** begins operating the pump **806** to draw water through the water line **803**. At **S412**, the peritoneal dialysis fluid preparation device **800** pump **806** draws a quantity of water until a command is received or generated at **S414** to halt the pumping of water whereupon at **S416A**, the pump **806** is deactivated. FIG. **19C** shows a control loop executed by the controller **807**. At **S404A**, the water source **810** controller detects a pressure below a predetermined threshold indicated by the pressure sensor **804**. A drop in pressure is caused by the **S402A** operation which causes a negative pressure in the water line **803**. Note that instead of an absolute (gauge or absolute pressure in absolute terms) pressure, the controller **807** at **S404A** may respond to a predefined rate of change of pressure or a predefined total pressure change over a predefined interval of time. The predefined ranges may be stored in a memory of the controller **807**. **S404A** loops continuously until the condition is met. At **S405A**, the controller **807** activates the water pump **806** causing water to flow into the water line and alleviating the negative pressure such that water flows freely under control of the pump **808**. At **S406A**, control loops until the pressure indicated by the pressure sensor **804** rises above a threshold or increases a predefined total amount or at a predefined rate whereupon the water source pump **806** is halted at **S409**. The rise in pressure is caused by the operation **S414**. Thus, the water source **810** is automatically demand-controlled by the peritoneal dialysis fluid preparation device **800** controller **809** without a signal connection between the controllers **809** and the water source **810** controller **807**.

(260) Although the embodiments described with reference to FIGS. **19A** through **19M** described the peritoneal dialysis fluid preparation device **800** as controlling the halting of the water source **810** pump **806**, it is possible in variations of these embodiments to instead cause the halting of the water source **810** pump to be controlled by providing the controller **807** with a predefined volume

of water or a predefined pumping time. Water pump **806** will halt automatically after being started so that the peritoneal dialysis fluid preparation device **800** can halt operation of pump **808** independently.

(261) Thus, in operation, the peritoneal dialysis fluid preparation device **800** controller **809** start the water source **810** pump **806** as described in the embodiments **19A** through **19M**, but the halting of the pump occurs automatically as a result of the expiration of the predefined volume or running time.

(262) Note also, that in the embodiment of FIGS. **19G**, **19H**, and **19J** the controller **809** may transmit, by means of pressure pulse signals, the duration of pumping by the water pump **806** or the amount to be pumped, by the peritoneal dialysis fluid preparation device **800** controller **809** to the water source **810** controller. This may allow the peritoneal dialysis fluid preparation device **800** controller **809** to establish the volume of fluid or the duration of pumping.

(263) In any of the embodiments, the pressure modulator may generate pulses by modulating the peritoneal dialysis fluid preparation device **800** pump **808**. For example, such pumps may be driven by motors that allow forward and reverse movement such as by means of a stepper motor drive. Other means for creating pulses are also possible such as an independent actuator such as a solenoid-driven diaphragm pump. Further variations are described elsewhere in the present application.

(264) Note also in the embodiment of FIGS. **19A-19C**, in alternative embodiments, the water source **810** may halt the flow of water after a certain quantity of water has been pumped by pump **806**, instead of receiving a command at **S414**. In other embodiments, the pump **808** may generate a pressure spike when it is halted by the controller **809**. This spike may be detected by the pressure sensor **804** and cause the controller **807** to halt the pump **806**.

(265) Referring now to FIG. **19D**, as in the embodiment of FIG. **19A**, the peritoneal dialysis fluid preparation device **800** has a pump **808** and a fluid circuit **802** for mixing fluids and for performing a peritoneal dialysis treatment. The water source **810** has a pump **806** that conveys water to the peritoneal dialysis fluid preparation device **800** through a water line **803**. The controller **807** controls the pump **806**. A power supply **815** provides power to the pump **808**. In the water source, a voltage detector **816** is connected to the power supply **815** or power leads leading to the pump **808**, to detect power sent to the pump **808**. Thus, the voltage detector **816** applies a signal to the controller **807** indicating when the pump **808** is activated. The pressure sensor **804** may be used for flow control of the pump **806** to ensure the tandem operation of the pumps **808** and **806** are synchronized by flow such that the pump **806** does not unduly resist the pumping of pump **808**. A closed loop control of pump **806**, executed by controller **807**, on a pressure set point may accomplish this. This closed loop control may be provided in embodiments. FIG. **19E** shows a control loop executed by a controller **809** of the peritoneal dialysis fluid preparation device **800**. At **S400**, the controller **809** receives or generates a command for water. This may be as described in the foregoing embodiments as incident to a concentrate dilution operation in the preparation of a dialysis fluid by the peritoneal dialysis fluid preparation device **800**. At **S402A** the peritoneal dialysis fluid preparation device **800** begins operating the pump **806** to draw water through the water line **803**. At **S412**, the peritoneal dialysis fluid preparation device **800** pump **806** draws a quantity of water until a command is received or generated at **S414** to halt the pumping of water whereupon at **S416A**, the pump **806** is deactivated. FIG. **19F** shows a control loop executed by the controller **807**. At **S404B**, the water source **810** controller detects a voltage above a predetermined threshold indicated by the voltage detector **816**. The predefined threshold may be stored in a memory of the controller **807**. **S404B** loops continuously until the condition is met. At **S405B**, the controller **807** activates the water pump **806** causing water to flow into the water line and alleviating the negative pressure such that water flows freely under control of the pump **808**. At **S406B**, control loops until the voltage indicated by the voltage detector **816** falls below a predefined threshold which may be different from the one at **S404B**, whereupon the water source

pump **806** is halted at **S409**. The fall in voltage is caused by the operation **S414**. Thus, the water source **810** is automatically demand-controlled by the peritoneal dialysis fluid preparation device **800** controller **809** without a signal connection between the controllers **809** and the water source **810** controller **807**.

(266) Referring now to FIG. **19G**, as in the embodiment of FIG. **19A**, the peritoneal dialysis fluid preparation device **800** has a pump **808** and a fluid circuit **802** for mixing fluids and for performing a peritoneal dialysis treatment. The water source **810** has a pump **806** that conveys water to the peritoneal dialysis fluid preparation device **800** through a water line **803**. The controller **807** controls the pump **806**. A pressure modulator **818** generates pressure pulses in the water line **803** that are detected by the pressure sensor **804** of the water source **810** to apply resulting pressure pulse indications to a decoder **819** which decodes them to generate command signals that are applied to the controller **807**. The controller **809** may store pressure pulse patterns that are thus decoded by the decoder **819**. Using pressure pulses, various commands can be encoded and decoded to provide commands to the water source **810** from the peritoneal dialysis fluid preparation device. Such commands may include to start and stop the pump **806**, or to command a speed of the pump **806**, for example. The pressure sensor **804** may be used for flow control of the pump **806** to ensure the tandem operation of the pumps **808** and **806** are synchronized by flow such that the pump **806** does not unduly resist the pumping of pump **808**. A closed loop control of pump **806**, executed by controller **807**, on a pressure set point may accomplish this. The pressure pulse signal generated by the pressure modulator may prescribe a pressure setpoint for such closed loop control. The closed loop control may be provided in embodiments. FIG. **19H** shows a control loop executed by a controller **809** of the peritoneal dialysis fluid preparation device **800**. At **S400**, the controller **809** receives or generates a command for water. This may be as described in the foregoing embodiments as incident to a concentrate dilution operation in the preparation of a dialysis fluid by the peritoneal dialysis fluid preparation device **800**. At **5402B** the peritoneal dialysis fluid preparation device **800** begins operating the pump **806** to draw water through the water line **803** and simultaneously, shortly or immediately before or shortly or immediately afterwards, generates a pulse command to turn on the water pump **806**. At this time, further commands such as a pressure setpoint or a speed of the pump **806** may be generated using pressure pulses through the pressure modulator **818**. At **S412**, the peritoneal dialysis fluid preparation device **800** pump **806** draws a quantity of water until a command is received or generated at **S414** to halt the pumping of water whereupon at **S416B**, the pump **806** is deactivated and simultaneously, shortly or immediately before or shortly or immediately afterwards, generates a pulse command to turn off the water pump **806**. FIG. **19J** shows a control loop executed by the controller **807**. At **5404C**, the water source **810** controller **807** detects a command from the decoder **819** to start the pump and establish operating conditions if operating conditions are included in the pulse train received by the decoder **819**. **S404C** loops continuously until the condition is met. At **S405C**, the controller **807** activates the water pump **806** causing water to flow into the water line and alleviating the negative pressure such that water flows freely under control of the pump **808**. The controller **807** may also set operating conditions as indicated by the received command. At **S406C**, control loops until a further pressure pulse signal command is received by the decoder **819** to halt the pump **806**. Thereupon, the water source pump **806** is halted at **S409**. Thus, the water source **810** is automatically demand-controlled by the peritoneal dialysis fluid preparation device **800** controller **809** without a wired or radio-based signal connection between the controllers **809** and the water source **810** controller **807**.

(267) Referring now to FIG. **19K**, as in the embodiment of FIG. **19A**, the peritoneal dialysis fluid preparation device **800** has a pump **808** and a fluid circuit **802** for mixing fluids and for performing a peritoneal dialysis treatment. The water source **810** has a pump **806** that conveys water to the peritoneal dialysis fluid preparation device **800** through a water line **803**. The controller **807** controls the pump **806**. A valve actuator **822** opens and closes a valve **821** that provides for flow

into the fluid circuit **802** from the water line **803**. Details of such operation and embodiments are disclosed elsewhere herein. A voltage sensor **816** detects the activation of the valve actuator **822** and applies a corresponding signal to the controller **807**. Both opening and closing indications may be applied and interpreted by the controller **807** using known principles and according to various valve types so details are not discussed. The pressure sensor **804** may be used for flow control of the pump **806** to ensure the tandem operation of the pumps **808** and **806** are synchronized by flow such that the pump **806** does not unduly resist the pumping of pump **808**. A closed loop control of pump **806**, executed by controller **807**, on a pressure set point may accomplish this. This closed loop control may be provided in embodiments. FIG. **19L** shows a control loop executed by a controller **809** of the peritoneal dialysis fluid preparation device **800**. At **S400**, the controller **809** receives or generates a command for water. This may be as described in the foregoing embodiments as incident to a concentrate dilution operation in the preparation of a dialysis fluid by the peritoneal dialysis fluid preparation device **800**. At **S402C** the peritoneal dialysis fluid preparation device **800** activates the valve actuator **822** to open the valve controlling the fluid circuit **802** access to the water line **803** and then begins operating the pump **806** to draw water through the water line **803**. At **S412**, the peritoneal dialysis fluid preparation device **800** pump **806** draws a quantity of water until a command is received or generated at **S414** to halt the pumping of water whereupon at **S416C**, the pump **806** is deactivated and the valve actuator **822** is activated to close (or deactivated, depending on the type of valve, for example a solenoid would be powered-down) the water inlet valve **821**. FIG. **19M** shows a control loop executed by the controller **807**. At **S404D**, the water source **810** controller detects a voltage above a predetermined threshold indicated by the voltage detector **816**. This is one example of the direct detection of the opening of a valve. In a linear motor actuated pinch valve, a forward applied voltage may be detected that runs the linear motor in a forward direction to close the valve **821** and a reverse applied voltage may be detected that runs the linear motor in the reverse direction to open the valve **821**. For a solenoid valve, a predefined threshold voltage may be stored in a memory of the controller **807** to indicate the valve open position of the actuator **822**. For other types of actuator, a suitable mechanism for direct detection of the valve status (e.g., an encoder or other mechanism) may be employed. **S404D** loops continuously until the condition is met. At **S405D**, the controller **807** activates the water pump **806** causing water to flow into the water line such that water flows freely under control of the pump **808**. At **S406D**, control loops until the valve actuator **822** close condition is detected. Thereupon, the water source pump **806** is halted at **S409**. The close condition is caused by the operation in **S416C**. Thus, the water source **810** is automatically demand-controlled by the peritoneal dialysis fluid preparation device **800** controller **809** without a signal connection between the controllers **809** and the water source **810** controller **807**.

(268) In any of the foregoing embodiments in which pressure, voltage, or other indications are used to control the flow of a fluid, such as water, the upstream source such as fluid source may be placed in a demand mode to enable control by pressure, voltage, or other indications. This may be done by a unique user command through a connected user interface. Alternatively, the controller (e.g. **807**, **739**) may generate a command using a unique pattern of pressure or final control to a valve or pump power supply to indicate the demand mode. When not in the demand mode, the fluid source ability to respond to the commands for fluids is disabled.

(269) Referring now to FIGS. **20A** through **20E**, any of the foregoing embodiments may be modified to employ any one of a variety of locations for a filter that removes pyrogens and infectious agents such as bacteria. Any of the filters **824** may be, or include, a single filter, for example with a membrane having pores of 0.2 micron or smaller diameter. Any of the filters **824** may be, or include, a single filter of the same type with additional apparatus and/or controls suitable for testing. For example, a pressurized line may permit the application of pressurized air below the bubble point of the membrane to one side of the filter to measure the membrane's ability to withstand the pressure and thereby indicate its integrity. This type of filter integrity test is known

in the art and details are known to those skilled in the art. In other embodiments, the filters **824** may be redundant to reduce the probability of a failure to the joint probability of a failure in both filters. In each of the FIGS. **20A** through **20E**, a patient **842** is filled and drained through a patient fill/drain line **841** via a fluid circuit **856** which may be configured in accord with any of the embodiments disclosed herein or in the embodiments disclosed in the references referenced in the incorporation-by-reference statements. A mixing chamber **855** is connected to the fluid circuit **856** where the fluid circuit **856** prepares a batch using inflow **857** and outflow **858** lines with flow direction designated by arrows. As in the foregoing and later embodiments, a water source **850**, a first long-term concentrate container **852**, and a second long-term concentrate container **863** are connected to the fluid circuit **856**.

(270) In the embodiment of FIG. **20A**, each of the inlet lines for water **826**, the first concentrate **852**, and the second concentrate **853** have a filter **824** to prevent contaminants from entering the fluid circuit **856** and thereby prevent contaminants from entering the patient **842**. The guarantee against contamination provided by the filters **824** is optimized if all other components are permanently (or previously, as-delivered and sterilized) connected within and to the fluid circuit **856** such that only connections to the water **850**, the first concentrate **852**, and the second concentrate **853** need to be made upstream of the filters **824**. Thus, the filters themselves are attached to the lines **826**, **827**, and **828**. Note that connectors are not separately shown, but may be provided for connecting between each of the respective water **850**, the first concentrate **852**, and the second concentrate **853** and the lines **826**, **827**, and **828** on the fluid-source side of the respective filter **824**.

(271) In the embodiment of FIG. **20B**, a drain line **861** drains fluid from the fill/drain line **841** and a fill line **862** fills the fill/drain line. The fill line **862** has a filter **824**. In this embodiment, no other filters are used. The fill/drain line **841** is permanently or previously attached to the fill line **862** prior to sterilization such that when the fill/drain line **862** is connected to the fluid circuit **856** (note that it could be previously attached and sterilized as a unit with all or parts of the fluid circuit **856**), any contamination, including touch contamination, is blocked from reaching the patient **842** by the filter **824**. Other elements are as described above.

(272) In the embodiment of FIG. **20C**, a filter **824** is placed on the mixing container **855** inflow line **857**. The mixing container **855** is presumed to be attached to the fluid circuit before sterilization so that a sealed unit is formed and any touch contamination is prevented from entering the mixing container **855**. A filter may also be provided on the fill line **862** as in the embodiment of FIG. **20B**. Alternatively, instead of a filter on the fill line **862**, the fluid circuit **856** may be designed such that a dedicated channel is defined between the mixing container **855** and the fill line **862** so that unsterile fluids, or fluids not protected by sterile filtration, do not contact any part of the circuit connecting the mixing container outflow line **858** and the fill line **862**. As in other embodiments, the filter **824** is connected to the downstream portion and preattached to ensure sterility of the contents of the mixing container **855**.

(273) In the embodiment of FIG. **20D**, the water line **826** and a common concentrate line **845** are protected by respective filters **824**. The downstream side of the water line **826** and the filter **824** may be preattached to the fluid circuit **856**, mixing container **855**, and the patient lines including fill, drain, and fill/drain **861**, **862**, and **841**. The downstream side of the common concentrate line **845** and the filter **824** may be preattached to the fluid circuit **856**, mixing container **855**, and the patient lines including fill, drain, and fill/drain **861**, **862**, and **841**. The preattachment specifies that all these elements are sealed with each other before sterilization (or during) to ensure the delivered disposable set is sterile and protected from contamination ingress by the presence of the filters **824**. In this case components upstream of the filters **824** can be replaced without risk of contamination.

(274) In the embodiment of FIG. **20E**, which corresponds to the embodiment of FIG. **18A**, the filter **824** is placed in the common fluid line **827** and preattached to the remainder of the fluid handling components which are also interattached. That is the filter **824**, the portion of the common fluid

line **827** downstream of the filter **824**, the fluid circuit **856**, mixing container, and the patient lines including fill, drain, and fill/drain **861**, **862**, and **841** are all interconnected to form a sealed unit prior to sterilization. This ensures the delivered disposable set is sterile and protected from contamination ingress by the presence of the filter **824**. In this case components upstream of the filter **824** can be replaced without risk of contamination of the downstream circuit.

(275) FIG. **20F** shows a generalized embodiment similar to that of FIG. **18A** in which a conductivity sensor **859** is provided on the mixing container **855** outflow line **858**. The configuration allows the method embodiments herein to be modified to minimize the total amount of fluid that must be drawn from the mixing container **855** toward the drain to measure conductivity of the mixing container **855** contents. The present embodiment may be modified to provide two conductivity sensors connected in series to be used for volume flow rate measurement as described herein. Note that in any of the embodiments, identified conductivity cells may be of the direct contact or capacitive type of conductivity cell.

(276) FIG. **20G** shows an embodiment similar to that of FIGS. **20E** and **20F** in terms of the filter placement at a common fluid inlet **827**. The filter **825**, in the present embodiment, permits a membrane integrity test which may be performed by pressurizing with air from an air pump **835**. The pump **832** has inlet and outlet pressure sensors **831** and **830** that are used by the controller **847** for pressure compensation of a commanded rate of pump **832** as described with reference to various embodiments including the incorporated reference US Patent Publication 2015-0005699 also attached to the provisional application. The pump **832** flows fluid between manifolds **833** which may as described in the various embodiments described herein. In the present embodiment, the controller **847** is configured to open any valves necessary to open a fluid channel from the filter **825** to the pressure sensor **831** and to apply air pressure from pump **835** while monitoring the pressure signal from pressure sensor **831** for any change. A filter membrane with no compromise to its integrity will hold the pressure from the air pump **835**, which may be controlled to be maintained below the bubble point of the membrane. The controller **847** may generate a signal based on whether a pressure change is indicated by the pressure sensor **831** or not. By opening a channel to a pressure sensor that provides another function, the need for an additional pressure sensor may be avoided.

(277) FIGS. **21A** through **21C** show, respectively, correction procedures for recovering from incorrect conductivity measurements in the preparation of a batch of dialysate by proportioning two concentrates and water. FIG. **21A** shows the flow from, after initially adding up to 100% of the required amount of water to the mixing container (Refer to FIG. **18A**, for example, noting that the method of FIGS. **21A** through **21C** can be used with other embodiments). Initially, before **S602**, a fraction (less than 100% of target quantity) of water is added to the mixing container, then at **S602**, a first concentrate is added, mixed, and a conductivity detected and determined to be within the expected range (**C1** ok). Note that **S648** (FIG. **21B**) corresponds to the condition where conductivity after mixing the initial amount of water and the first concentrate is out of the expected range such that the added quantity of the first concentrate indicated to be too high and **S688** (FIG. **21C**) where the conductivity is out of range indicating the added quantity of the first concentrate was too low. In all three cases, water was added to the mixing chamber, the contents mixed, and the conductivity tested.

(278) At **S606**, 100% of the second concentrate **C2** is added to the mixing container. At **S608** the mixing chamber contents, with the added second concentrate **C2**, is tested and conductivity found to be within the expected range. **S628** corresponds to the condition where conductivity is out of the expected range and the added quantity of the second concentrate indicated to be too high and **S634** corresponds to where the conductivity is out of range indicating that the added quantity of the second concentrate was too low. At **S610**, both the first and second concentrates were added in the correct amounts and the balance, if any, of the water is added to the mixing container and the mixing container conductivity tested to confirm its usability. At **S612**, the conductivity is in the

expected range indicating proper dilution. If 100% of the water was previously added prior to **S602**, then the test can be omitted. **S616** and **S622** correspond to over-diluted and under-diluted conditions, respectively. If the batch is the correct dilution, then at **S614** it is made available for use. At **S616**, if the batch is over diluted, there are two possible responses. The first response is that the batch can be indicated as failed and an output corresponding to recover operation can be output. Alternatively, additional concentrates in the same proportion as the target, can be added sequentially to the mixing container as indicated at **S618**, after which, at **S620**, the batch is tested again for conductivity and if it fails, the batch is failed or if the conductivity is in range, the batch is made available for use.

(279) Returning to **S628**, the condition where conductivity is out of the expected range and the added quantity of the second concentrate indicated to be too high, at **S630** an additional quantity (bolus) of each of the first concentrate and water are calculated in the target proportions to bring the proportions of these and bring the mixing container contents to the expected range of conductivity. Then, at **S632**, the balance, if any, of the water is added to the mixing container plus the water bolus plus the first concentrate bolus (calculated at **S630**) and the batch's conductivity tested **S634** to confirm its usability. If the conductivity is in range, the batch is made available for use otherwise the batch is failed.

(280) Returning to **S634**, the condition where conductivity is out of the expected range with the added quantity of the second concentrate indicated to be too low, at **S636** an additional quantity (bolus) of the second concentrate is calculated to achieve the target proportion to bring the mixing container contents to the expected range of conductivity. The conductivity is tested again. If the conductivity is not in the expected range, then at **S638**, the batch is failed, otherwise **S642**, the balance, if any, of the water is added to the mixing container at **S644** and the contents conductivity tested **S646** to confirm its usability. If the conductivity is in range, the batch is made available for use otherwise the batch is failed.

(281) Returning to **S648** and FIG. 21B, which corresponds to the condition where conductivity after mixing the initial amount of water and the first concentrate is out of the expected range such that the added quantity of the first concentrate is indicated to be too high, correction begins at **S650**. At **S650**, boluses of the second concentrate and water are calculated to bring the proportions to the target and at **S652**, the total quantity of the first concentrate plus this bolus are added to the mixing container. The mixing container contents are then tested at **S654** and if in range, meaning the second concentrate is in the correct proportion to the first, **S656**, the balance of the water plus the water bolus are added and the batch tested at **S658**. Note that the expected conductivity at **S656** corresponds to a higher concentration of the second concentrate than if the first concentrate had been added in the correct amount because the water bolus is not yet added at this point. The reason for delaying the water addition is that optimally additions to the mixing container contents are scheduled to coincide with the point at which the fluid circuit is primed with the fluid corresponding to the one to be added to minimize the time spent priming between switchovers. If the batch conductivity is in the expected range **S660**, then the batch is released for use. If the batch is over-diluted **S664**, boluses of the first and second concentrate in the required proportion may be added and the batch further tested at **S666** where, if it the conductivity is again out of range, the batch will be failed. In an alternative embodiment, at **S664**, the batch is simply failed without taking any step to correct. If the batch is under diluted **S668**, a bolus of water may be added and the batch further tested at **S670** where, if it the conductivity is again out of range, the batch will be failed. In an alternative embodiment, at **S668**, the batch is simply failed without taking any step to correct.

(282) If the quantity of second concentrate added was indicated by the conductivity measurement **S654** to be too great at **S672**, then at **S674**, the batch is failed. In alternative embodiments, a correction may be performed by adding proportionate boluses of water and the first concentrate. In the present embodiment, errors in the first and second concentrate additions both occurred

indicating the potential for a system problem, so the system may fail the batch and provide instructions for testing the system or replacing the fluid circuit, which may be the source of the problem. The controller may perform this as part of a batch fail recovery process. If the quantity of second concentrate added was indicated by the conductivity measurement **S654** to be too low at **S676**, then at **S678**, the batch proportions may be recovered by adding a bolus of the second concentrate at **S678** and testing again. If the conductivity of the mixing container is again out of range, the batch is failed at **S682**; otherwise, at **686**, the balance, if any, of the water is added to the mixing container and the contents conductivity tested to confirm its usability and made available for use, unless the batch failed based on the outcome of the conductivity test.

(283) Returning to **S688** and FIG. 21C, where the first concentrate added was found to be too low, at **S690**, since the system is already primed with the first concentrate, an additional amount can be calculated from the conductivity and added. No additional bolus of water is required. The mixing container contents are sampled at **S690** and if the conductivity is out of range at **S692**, then the batch is failed. If the conductivity is in the range **S696**, the second concentrate target amount is added **S698** and tested **S700**. If the mixing container contents conductivity shows that the correct amount of the second concentrate was added **S702**, then the balance, if any, of the water **S704** is added to the mixing container and the batch contents' conductivity is tested to confirm its usability, and is made available for use if within range **S706**. If the mixing container contents conductivity is not in range, and the batch is found to be too dilute **S710**, then boluses of the first and second concentrates are calculated and added **S712** and the batch is tested and used or failed based on the result. If the batch is found at **S704** to be overly concentrated, then the conductivity measurement is used to calculate a water bolus **S724**, which is added, and the contents are tested and used or failed depending on the result.

(284) If at **S700**, the second concentrate amount added to the mixing container was found to be too high **S726**, then the batch is failed at **S728**. Again, this would be caused by two concentrate measurement failures. If at **S700**, the second concentrate amount added to the mixing container was found to be too low **S730**, then additional second concentrate is added at **S734**, the batch is tested, and if the conductivity is out of range, the batch is failed **S736**. If at **S732**, the conductivity is in range, then the balance, if any, of the water **S740** is added to the mixing container and the contents conductivity is tested to confirm its usability and is made available for use if within range.

(285) In alternative embodiments, instead of the procedure being based on the premise that the volume of concentrate is incorrect, the error may be presumed to be the concentration (or "strength") of the concentrate. The embodiment of FIG. 25 describes an example of a procedure based on this presumption.

(286) FIGS. 22A and 22B show a water filtration system **551** with cleaning and priming modes controlled by a water system controller **550** which is commanded by a proportioner/cycler controller **576** according to embodiments of the disclosed subject matter. A source of raw water **556**, such as a source of potable water, is pumped by a pump **552** through a primary filter **554** which is not cleaned or regenerated, and then through a selected one of a pair of filters **558** and **560** which can be cleaned or regenerated. At any given time, the water system controller **550** controls the pump, a four-way reversing valve **570**, and flow restrictors **571**, **572**, and **573** to direct a forward flow of the output of primary filter **554** through one of the filters **558** and **560**, and directs a reverse output flow through the other of the filters **558** and **560** to the drain **562**, depending on its setting. Output of one of the filters **558** and **560** is divided at a respective one of the junctions at flow restrictors **571** and **572** depending on settings of variable flow restrictors **571**, **572**, and **573** such that a fraction (from 0 to 100%) is directed through the branch **574** and a remainder toward the outlet **578** so that one filter can produce product water to clean the other and for release through outlet **578** while the other is being cleaned with product water. The settings of the flow restrictors **571**, **572**, and **573** make it possible to clean one filter with all the product water or for both filters to produce product water until a cleaning is required. In FIG. 22A, the arrows show the flow for

forward flow through filter **558** and reverse flow of filtered product water from valve **566** and **568** flowing through the filter **560**. In FIG. 22B, the arrows show the flow for forward flow through filter **560** and reverse flow of filtered product water from valve **566** and **568** flowing through the filter **558**. The flow restrictors **571**, **572**, and **573** may be controlled by the water system controller **550** which in turn may be commanded by the proportioner/cycler controller **576** of the proportioner/cycler **576** which may be configured according to any of the embodiments disclosed or referenced herein or others.

(287) In addition to the cleaning mode, the water filtration system **551** may also have a flushing mode in which water that has remained for too long in the system is diverted by a diverting valve **555** to the drain **562**. This operation may be performed on a periodic basis or in response to a condition (such as a time since last use) under control of the water system controller **550** of the cycler controller **576**. In addition to cleaning and flushing modes, the water filtration system **551** may also have priming mode wherein raw water is pumped through both filters **558** and **560** in a forward direction with flow restrictor **573** set to fully open and flow restrictors **571** and **572** alternating between fully open and partially restricting so that the branch line **574** is primed. In this mode, all flow may be directed through the drain line **557** by a diverting valve **555**. An air or other type of detector may be provided in the drain line **557** to indicate when the water passing through has been sufficiently cleared by priming. The filters **558** and **560** may also be reverse flushed to drain during the priming sequence.

(288) The filtration system **551** may also have a primary filter stage **554** with, for example, an ultraviolet lamp **559** that is controlled by the water system controller **550**. The water system controller **550** may optimize lamp life by regulating the lamp's **559** output so that it is cycled on when required (e.g., when water is flowing) and turned off when water is not flowing. The controller **550** or **576** may be configured to turn the ultraviolet lamp **559** on just prior to the water pump activation to ensure that its output is applied to all water flowing through the stage.

(289) The filtration system **551** may have an off mode, a sleep mode, and an operating mode. In the off mode, the water system controller **550** and controlled flow restrictors **571**, **572**, and **573**, the pump **552**, the valves **555** and **570** may all be powered down. From the sleep mode, these may be powered up with the water system controller **550** in a mode in which it can immediately accept commands and act accordingly. The sleep mode may also include regulating the pressure and primed state of the water lines such that there is minimal delay from the receipt of the command to pump and deliver product water and the actual output. The water source controller **550** may transmit to the proportioner/cycler controller **576** a signal indicating a ready status. The water source controller **550** may transmit a signal, either unprompted or in response to a request from the proportioner/cycler controller **576** indicating its operating state. For unprompted signaling, the water source controller **550** may transmit a heartbeat signal that contains the state of the water filtration system **551**. This heartbeat signal may be periodically cast to the proportioner/cycler controller **576** where communication is unidirectional from the water source controller **550** to the proportioner/cycler controller **576**. Such cases may be relevant for configurations in which the water source controller responds to direct measurements such as pressure signals as described in connection with FIGS. 19A through 19M embodiments. A state signal can indicate various state information such when the water filtration system **551** is performing a flushing or priming operation or in another non-ready state, the water source controller **550** may transmit a state signal indicating so. Additional state information may include time left on the filters, expiration of filters, diagnostic information such as time taken for priming and flushing operations, smoothness of pressure regulation, power consumption, duty cycle of the system over a predefined period, and other information.

(290) The water source controller **550** may regulate the pump and flow restrictors **571**, **572**, and **573** to maintain a target pressure at the product water outlet **578**. This may be based on a closed loop control method with a target pressure which may include and range (deadband). At **569** a

pressure sensor is indicated in the product water outlet line **578**.

(291) The water source controller **550** and proportioner/cycler controller **576** may communicate by any suitable device or system. That communication may be unidirectional or bidirectional as indicated above. Either or both of the water source controller **550** and proportioner/cycler controller **576** may be of the various forms described with reference to FIG. **14**.

(292) The water source controller **550** may activate an alarm **575** in response to any conditions indicating a need for intervention or change of configuration. For example, the water source controller **550** may activate an alarm output **575** such as a general purpose user interface (See for example, display **1018** and speaker **1024**) or special purpose output such as a lamp or annunciator. The water source controller **550** may also, concurrently, output any alarms to its communications link to the proportioner/cycler controller **576**. The latter may command the water source controller **550** to suppress alarm outputs, delay alarm outputs by a predefined interval, or to perform other actions associated with alarms such as the suppression of the local output from the alarm output **575**. In addition to outputting alarms to the proportioner/cycler controller **576**, the water source controller **550** may also transmit instructions for use or instructions for alarm condition recovery to the proportioner/cycler controller **576** for output and use by a user interface of the proportioner/cycler controller **576**. The user interface of the proportioner/cycler controller **576** may transmit commands back to water source controller **550** as well by generating an alarm handler input/output session on the proportioner/cycler controller **576**. One mechanism for doing this is for the water source controller **550** to generate a remote session on the user interface of the proportioner/cycler controller **576** whereby the water source controller **550** has an ability to control the output and respond to inputs such as mouse and keyboard input, directly, by replicating an adapted model of the user interface it generates internally on the user interface of the proportioner/cycler controller **576** functioning as a thin client, effectively. The user interfaces of the water source controller **550** and proportioner/cycler controller **576** are not shown but may be understood to have one or more of the aspects described with reference to FIG. **14**. The water source controller **550** may also generate a troubleshooting session on the proportioner/cycler controller **576** in the same manner or by simply outputting informational data and instructions in the form of a decision tree for output and control by the water source controller **550**.

(293) In alternative embodiments, the water source controller **550** outputs a uniform resource locator (URL) with metadata indicating the condition to which it pertains, for example, a set of conditions may indicate an urgency or priority of the information contained in the URL. The metadata may be sent in preceding message or may be combined with the URL. The proportioner/cycler controller **576** may have a priority table stored within that indicates how the proportioner/cycler controller **576** handles the URL (or other alarm data) to allow the proportioner/cycler controller **576** to determine whether the URL should be accessed and displayed immediately, right after a current input/output session, or output only after a certain condition is detected by the proportioner/cycler controller **576**. In embodiments, the instructions for troubleshooting the water filtration system **551** are stored in the proportioner/cycler controller **576** and their output is initiated by the receipt of alarm data from the water source controller **550**.

(294) In addition to the above functions, the proportioner/cycler controller **576** may indirectly control the water source controller **550** to control a product water heater **553** according to certain commands from the proportioner/cycler controller **576**. For example, the proportioner/cycler **577** may be provided with a fluid heater **579**. Such a fluid heater, as known in various prior art embodiments of peritoneal dialysis cyclers, may be provided to raise the peritoneal dialysis fluid to body temperature. Such heaters as **579** may be instantaneous or batch heaters. The heater **579** may heat incoming water, mixtures of concentrate and water such as ready-to-use medicament, or precursor fluids such as partially diluted concentrate, or combinations of these. The power requirement of a cycler-based heater must be sufficient to raise the temperature from room temperature to body temperature because typically ready-to-use bagged dialysis fluid is used for

treatment. However, in the system of FIG. 22A/22B, the water temperature may be lower than that, for example it may be at ground temperature or even near freezing as may come from a domestic tap. In order to reduce the peak power requirement of the proportioner/cycler 577 heater, at least part of the heating burden may be shared by the product water heater 553. Note that product water heater 553 may be located at other positions in the flow of water such as the raw water inlet or elsewhere. The product water heater 553 may be commanded indirectly by the proportioner/cycler controller 576 to provide a predefined power output or delivery temperature. In the case of the latter, the product water heater 553 may be closed-loop controlled by the water source controller 550 or another controller on a detected output temperature by a temperature sensor 580.

(295) The proportioner/cycler controller 576 may also receive status information from water source controller 550. Such information may include indications that the water filtration system 551 is in flushing, priming, or cleaning mode. Other information may include water temperature, estimate of time till ready, estimated time left till filter replacement (estimated time to exhaustion), time on the UV lamp 559, time till next flush or cleaning cycle, and whether the water filtration system 551 is in sleep mode and how long the before it is available to produce water. This information, because it may indicate reasons for delay, may be useful to provide in real time to a connected patient through the user interface of the proportioner/cycler controller 576. Additional information output to the proportioner/cycler controller 576 user interface may also include forecasting of maintenance tasks such as filter replacement and ultraviolet bulb 559 replacement. One or more resistivity sensors may be provided in the product water outlet line 578, which may be connected to the water source controller 550 with the resistivity transmitted as status information to the proportioner/cycler controller 576 and relevant synthesis of this information output on a user interface. For example, such a synthesis may be the display of an alert when the resistivity is out of bounds. The raw water resistivity may be similarly monitored. Since the lifespan of the filters may be affected by the raw water quality, this information may be provided to the proportioner/cycler controller 576 and relevant outputs generated in response to it. For example, the proportioner/cycler controller 576 may alert the user to a low water quality level in the supply which may be mitigated by changes in infrastructure and at least warn the user that filter replacement may need to be frequent.

(296) Some of the functions of the water filtration system 551 can be scheduled with some flexibility without seriously impairing its ability provide purified water or causing premature exhaustion or failure of components such as filters. For example, functions whose timing may interfere with a patient's lifestyle may be moved up or delayed in order to permit the patient to be treated on a schedule that better fits the patient's life schedule. The user interface of the water source controller 550 or the proportioner/cycler controller 576 may provide a control to allow the user to enter scheduled events such as treatment time, treatment duration (e.g., wakeup time), and time ready for treatment (which requires the line to be primed and connected to the patient). In embodiments, relevant data such as the patient's treatment schedule may be entered in the controller, e.g., the proportioner/cycler controller 576. In further embodiments, the patient's treatment schedule may be stored over time and used to estimate future treatment schedules including connect time, bedtime, treatment start time, wake time, treatment end time and any other events associated with treatment and maintenance normally indicated by the respective controllers (550, 576). The respective controllers 550 (or indirectly as commanded through proportioner/cycler controller 576) may be controlled to run flushing and cleaning modes at times that lie between certain interfering events such as treatment or to prime the water system a certain interval ahead of a predicted connection of the patient to the proportioner/cycler 577. Note that in embodiments, the water filtration system 551 may have a reservoir to receive product water for use on-demand by the proportioner/cycler 577. The heater 553 may, in such embodiments, be a batch heater that applies heat to the reservoir. In such embodiments, the water source controller 550 or proportioner/cycler controller 576 may schedule production and storage of purified water in the reservoir and heating thereof according to an estimated time of use for treatment. Such a reservoir may be a disposable

component, for example a plastic bag. The reservoir may be sized to receive water for a single cycle, part of a cycle, or multiple cycles of a full treatment. A reservoir may be provided with a sterilizing filter on its inlet (for touch contamination), its outlet (to block back-growth contamination), or both. Check valves may be provided on inlets or outlets or both to prevent backflow. A predefined pressure at the outlet of the reservoir may be maintained at a constant level by means of a recirculation loop with a check valve having the predefined cracking pressure.

(297) The water filtration system **551** illustrated shows a very basic example. Many purifiers that create water suitable for peritoneal dialysis involve many stages, each with filters having different lifetimes which may be affected by the quality of the raw water. In embodiments, the controllers **550**, **576** indicate estimated exhaustion events for filters such as reverse osmosis membranes, carbon filters, ultrafilters, deionization resin beds, sediment filters, or other consumable types of filters. The indications may be based on time, raw water quality, number of cleaning cycles, etc. Either controller **550** or **576** may be programmed to order replacements for such consumable components and/or consumable supplies used for treatment automatically. For example, commands for ordering supplies may be sent to a server by means of the network **1012** (which may include the Internet). Failed components that are not consumables may also be reported and replacement parts ordered automatically along with repair orders in the same way.

(298) FIG. **22C** shows the water source and associated systems similar to the embodiment of water filtration system **551** described with reference to FIGS. **21A** and **21B**. A reservoir **581** is fluidly connected to receive product water filtered through a sterilizing filter **582** and a check valve **583**. The water is supplied to the proportioner/cycler **577** through an outlet **578** under a predefined pressure maintained by a loop **S851** containing a pump **585** and a check valve **584** with cracking pressure set at the predefined pressure. Pressure **569** and temperature **580** sensors may be located at various positions, including one located to monitor the predefined pressure. An error in the detected versus expected predefined pressure may be output as an alarm condition. Other filters **582** and check valves **583** may be provided to prevent grow-back contamination and to prevent back flow, respectively.

(299) Note that where both controllers are referenced together as controllers **550**, **576** it is intended to refer to either water source controller **550** or the proportioner/cycler controller **576** acting as a command controller and the other acting as a slave depending on whether the function is performed directly or indirectly by the controller and on whether the function is performed by the proportioner/cycler **577** or the water filtration system **551**.

(300) Note that in all the embodiments herein where a cycler is described, a proportioner/cycler may be substituted, i.e., a device that performs as a peritoneal cycler as well as a fluid proportioning device (aka a proportioning device). Note that in all the embodiments herein where a proportioner/cycler is described or identified, a cycler or proportioning device (also called proportioner) may be substituted. Note that in all the embodiments herein where a proportioner or proportioning device or system is described or identified, a cycler or a proportioner/cycler may be substituted.

(301) Note that the present application has generally avoided the terms such as “admixing” to make the present application clearer. The term “admixing” is suggestive of an intermediate mixture of fluids rather than a final mixture such as ready-to-use peritoneal dialysis fluid.

(302) For example, in the present application, applicants have used the term proportioning instead admixing because admixing implies the making of an intermediate product. The term proportioning implies a more general process such as the making of an intermediate product (an admixture) or a final product such as a ready-to-use peritoneal dialysis fluid. Thus, the term proportioning suggests something more general and is adopted in the present application where in the priority application, the term admixing was also used in this broader sense. Thus usages of terms such as “admix,” “admixing,” and “admixer” in the priority applications refer to corresponding terms such as “proportion,” “proportioning,” and “proportioner” in the present application. The differences in the

terms does not modify the subject matter relative to the priority applications. The priority applications simply used “admix,” “admixing,” and “admixer” and related terms in a broader sense. (303) According to the above embodiments, especially those discussed with reference to FIGS. 19A-19M and 22A-22C, there are provided the following features and embodiments of a system that includes a water source system with a controller in combination with a proportioner/cycler or cycler, also with its own controller.

(304) The water system pumps water in response to a demand signal communicated via a fluid connection between the water system and the proportioner/cycler. The demand signal may be a detection by the water system controller of a change in pressure generated by the proportioner/cycler. The pressure change may be generated by the cycler pump operation, where the cycler pump is one that is used for fill and drain of a patient peritoneal cavity, or a pump (if different) used for proportioning, or some other pump controlled by a proportioner/cycler controller. The pressure may be a draw-down of pressure caused by forward operation of the proportioner/cycler pump. The water source may have a pump which may start when a pressure sensor in a connection to the proportioner/cycler water system passes a particular (negative) threshold. The water source may have a pressure sensor that detects and conveys signals by way of pressure pulses to the water source controller which decodes them into specific predefined commands. One command may be for the water source to start pumping product water into the connection to the proportioner/cycler. Another command may communicate a value and command to which a closed-loop control pressure target of the water source outlet should be reset. Other aspects of the water source may be commanded, such as a time for the water system to flush, clean, or prime, a future time of treatment, and other parameters identified above. As for closed-loop control of a water source pump, the speed of a water pump that pushes water through one or more filters may be adjusted automatically in response to an outlet (outlet being the interface to the proportioner/cycler) or other intermediate pressure of the water system. The pressure pulses may be generated by a selected one (or more if present) cycler/admixer pump(s) that is/are positioned to influence the pressure at the outlet of the water source. For example, pulses may be generated by modulating driving power of a pump actuator in a stepwise fashion.

(305) In other embodiments, the water source receives commands from the proportioner/cycler. In embodiments, such commands are transmitted and/or exchanged between the water source and the proportioner/cycler by any suitable means for exchanging digital data including wired and wireless. In embodiments, the proportioner/cycler may control the timing, duration, and type of all water source functions including priming and flushing operations. In embodiments, the water source controller indicates to the proportioner/cycler controller its status including an indication that it is ready to output product water. In embodiments, the proportioner/cycler controller starts and stops water production. In embodiments, the proportioner/cycler transmits commands to start and stop an ultraviolet (germicidal) lamp in the water source. In embodiments, the commands may be adapted for extending the life of such an ultraviolet lamp by ensuring it is operated and ready only when required for treatment of water. The proportioner/cycler may use two-way communication with the water source to place it in a sleep mode at end of a treatment such that some or all power functions are switched off to save power and reduce wear. The proportioner/cycler may send commands to wake up the water source so that it is ready at a time of a predefined treatment stored in the proportioner/cycler. Commands from the proportioner/cycler may also be used to regulate the pressure and flow rate at which product water is delivered. As indicated above, closed loop control based on a pressure signal may be provided by the water source controller. The two-way communication may support the transmission of alarms generated by the water source and the proportioner/cycler may respond by ceasing dialysate preparation in response to predefined alarms. Alarm or status outputs of the water source may be used to generate specific outputs through the proportioner/cycler user interface which may have audio and visual output capability. The proportioner/cycler user interface may output guided troubleshooting steps in response to and

related to the water source outputs and alarms, and these may be output to a patient or operator. The output may be attended by the presentation of input controls to receive relevant feedback to create a guided session. Feedback may include answers to questions about the system such as the observations about the status of the parameters being checked, such as closure of fluid connections, proper electrical connections, proper mating of tubing with actuators, and instructions to skip to certain steps.

(306) The proportioner/cycler may control the water source heater and receive indications of power output, temperature, and ready status. The total heat required by the product dialysate may be shared by the water source and the proportioner/cycler so that the power required of either is split between the water source and the proportioner/cycler. This may be relevant where the proportioner/cycler heater power is sized to raise the temperature of premixed dialysate from room temperature to body temperature so that the additional power required to raise the temperature of water from a tap temperature (which may be very low in some cases, such as in northern climates where water mains can have temperatures near freezing) to room temperature may be borne by the water source heater. The water source consumable component status (predicted or indicated by sensors) including carbon filters, deionization resins, ultrafilters and others may be indicated by the water source to the proportioner/cycler and output by the latter's user interface to inform a user or patient of the need for maintenance and resupply. The controller of the water source or proportioner/cycler may be programmed to auto-order replacements through the Internet. The timing of such auto-order replacements may be done to effect the required change-out before exhaustion. The estimated time for a needed replacement may be responsive to the disposable consumption rate, therapy frequency, raw water quality, and order processing/delivery lead times.

(307) The priming of the proportioner/cycler may include priming and flushing with water from the water source. The proportioner/cycler controller may transmit commands to the water source controller to output water at pressures and flow rates required for the proportioner/cycler to perform these functions. The priming may be preceded by a flushing operation with purified water to reduce the potential presence of endotoxins in the disposable fluid circuit.

(308) The water source may include a reservoir sized to provide water sufficient for a fill/drain cycle or for a full treatment (multiple fill/drain cycles). The reservoir may have one or more sterilizing-grade filters on its inlet (and/or outlet) lines to prevent touch contamination or back-growth contamination. The reservoir may include one or more check valves on its outlet lines to prevent backflow. The disposable reservoir outlet may include a recirculation loop with a pump that maintains a target head pressure useful to maintain consistent dosing.

(309) Referring now to FIG. 24, the proportioner/cycler **800** with the pump **808** and fluid circuit **802** is provided for mixing fluids and for performing a peritoneal dialysis treatment. The proportioner/cycler **800** has a controller **809** for controlling operations involving the fluid circuit directed at generating dialysate and performing an automated treatment. The fluid source **810** pump **806** conveys fluid to the peritoneal dialysis fluid preparation device **800** through a fluid line **803**. A pressure sensor **804** detects pressure in the fluid line and applies a corresponding signal to a controller **807** of the fluid source **810**. The controller **807** controls a fluid multiplexer **814** that direct a selected one of water, a first concentrate **811** and a second concentrate **812**. The multiplexer **814** may have a pump **813**. The controller **807** also controls the pump **806** or pumps **806**, **813**. It will be observed that this is a generalization of embodiments described elsewhere herein. Each of the controllers **807** and **809** has a respective communications modem **668** to permit each to communicate wirelessly with a mobile terminal **669** using a wireless protocol such as near field communication (NFC). In other embodiments, the mobile terminal is substituted with another type of data-bearing device such as a bar code, a QR code, a radio frequency identification device (RFID), or a battery powered transponder. Note that in embodiments, only one modem is used to transfer information to one of the controllers **807**, **809** which transfers information to the other of the controllers **807**, **809** by other means. The mobile terminal **669** may be a general or special

purpose device such as an embedded system device, a tablet or a smart phone. The mobile terminal **669** may have an internal modem to permit it to communicate with the controllers **807** and **809**. (310) In embodiments, the mobile terminal **669** stores prescriptions for a treatment that can be uploaded wirelessly to the controller **807** and **809**. The prescriptions may contain parameters including proportions and dilutions of concentrate, tolerance of the proportions, and other information. The prescription may be encoded with information specifying the identity of a particular patient. A user of the mobile terminal **669** may be a patient, a caregiver, or a doctor. The mobile terminal may have a biometric authentication component such as an iris scanner, a fingerprint scanner, a face recognition algorithm, or other. A user may authenticate himself to enable the capability for a prescription transfer to a modem **668**.

(311) A token **659** may incorporate a NFC, Bluetooth, or other type of communications device to identify and track a person. For example, such a device may be worn by a patient. The controller(s) **807**, **809** may confirm the identity of the patient before implementing an uploaded prescription. Such tokens may take the form of tags or labels. The token **659** may identify consumable materials used for treatment such as concentrates and fluid circuits.

(312) As mentioned above, methods above may be based on the premise that the volume of concentrate is incorrect if a conductivity measurement indicates the target is not matched. This may instead be changed to a presumption that the error arises in the concentration (or strength) of the concentrates. Here the presumption is based on the observation that a long storage interval may cause evaporative loss from a typical bag-type container. This causes the concentration of the concentrate to be excessive. If the storage interval is much too high, the concentration may be non-uniform or the conductivity measurement may indicate excessive time in storage in which case the batch may be failed. The embodiment of FIG. 25 describes an example of a procedure based on this presumption.

(313) Referring now to FIG. 25, at **S802**, after a command is received or generated by a controller, a fraction (alternatively, all) of a target quantity of purified water is added to a mixing container. The apparatus may be as described according to any of the embodiments disclosed or claimed herein. At **S803**, a quantity of osmotic agent and partial electrolyte concentrate may be added. In alternative embodiments, the electrolyte concentrate may be added first and later the osmotic agent with or without electrolyte may be added. As discussed above, since osmotic agent can have a conductivity signal-suppressing effect, the osmotic agent conductivity change can be used as an indicator of concentration. At **S806**, the conductivity of the mixing container contents is tested.

(314) It is determined at **S808** whether the concentration of the mixing container contents is lower than an expected target (X) or higher than X by a predefined amount, in which case the mixing container contents may be failed and not used at **S810**. Although not presently shown, it should be understood that an error output to a user interface may be generated by the controller which may include instructions for checking for certain faults in the system and instructions for recovery. A measured conductivity that is too high may also be identified and failed. If the concentration of the mixing container surpasses such a threshold it may indicate that the contents of the mixing container are insufficiently mixed. Thus, in alternative embodiments a modification may be included to retry mixing a predefined number of times. The batch may also be subjected to remix trials if the mixing container contents have a conductivity that is too low. This is not illustrated but may be added readily as a short additional flow. If the mixing retry attempts fail, the additional flow may terminate (after the predefined number of retries) and proceed to **S810**. If the mixing container contents conductivity is above X (in embodiments, within a predefined conductivity range), then at **S812** the water deficiency may be calculated from the magnitude of the overage and used as a basis for estimating the water loss for the first concentrate (in this example, osmotic agent, but as indicated above, it could be electrolyte concentrate instead), as well as the second concentrate. The amount of the second concentrate (C2 in the figure) is also adjusted by this measure since to maintain the correct ratio of the two solutes, the amount of the second concentrate

needs to be adjusted as well. This is discussed above. This overage estimate may thus be used to calculate the amount of additional water required to add in a final completion step in order to bring the conductivity to the desired level for a final treatment fluid. That is, the same estimate for water deficiency may be used to calculate a water deficiency for both concentrates (or the total number of separate concentrates according to the embodiment).

(315) At **S814**, the proper quantity of the second concentrate, in the present example, the electrolyte concentrate, is added to the mixing container. As indicated, the quantity of the second concentrate is adjusted to account for the first concentrate overage as calculated in **S812**. At **S816**, water sufficient to make up for any deficiency calculated in **S812** is added to the mixing container. Then at **S818**, the conductivity of the mixing container contents is tested, and at **S820** the flow branches responsively to the result. The batch is failed if the target conductivity (Y) is too low or, optionally higher than a predefined level beyond the target Y. If the target Y is found, the batch is ready to use. If the conductivity is too high, at **S824**, additional water may be calculated and added. Then the conductivity may be tested again and if it fails ($\neq Y$) **S828**, the batch may be failed. **S824-S828** may be omitted in embodiments.

(316) Any of the methods for treatment fluid preparation described herein may be modified based in part on an analysis of the tolerance stacking. Such a stacking may take into account different kinds of variability, some of which are not straightforward to derive from the process itself. For example, the process analyzed may be defined between the manufacture of the input constituents, water and concentrates, and the provision of a final treatment fluid. However, the analyzed process here is defined to include detectable and correctable errors during the process that provisions the final treatment fluid and errors that result in alarms during treatment. The final impact of errors on the patient's safety along with any correction techniques may also be included in the analysis.

(317) Tolerances may also include ranges resulting from variability in the manufacture of concentrate, which cannot be influenced, tolerances in testing of intermediate and final conductivities, measurement error, and the required tolerance range of the final product and any other sources of variability. The analysis can benefit from creative input and ultimately may result in an alteration of the methods. So, an effort was made to analyze the above methods based on tolerances throughout.

(318) Note that in the above processes, adjustments to the C2 as a result of water loss may not be necessary. That is because the upward adjustment due to the higher concentration of C1 may be canceled by the downward adjustment due to predicted higher concentration of C2. So, the adjustments may be removed from the procedure of FIG. 25 in embodiments. However, in other embodiments, the cancelation may be incomplete if differences in the propensity for water loss of the two concentrates or their packaging are different.

(319) Note that in embodiments, average preparation time for batches may be minimized by optimizing the initial quantity of water added to the mixing container at **S802**. In embodiments, adjustments may be found to be rare occurrences such that close to 100% of the water may be added initially with the expectation that few adjustments and retries will be required. In practice, time saved by adding 100% of the water at **S802** may totally compensate for any occasional failed batches that cannot be adjusted to the expected concentration.

(320) In any of the embodiments, where the description refers to the conductivity being equal to the target, it should be understood that "equal to" refers to a predefined range around the target. In embodiments, the range may be $\pm 5\%$, for example.

(321) In any of the embodiments in which conductivity is measured, it should be understood that the conductivity may be numerically compensated for temperature deviation from a standard conductivity. In any embodiments in which the conductivity of the mixing container is tested, a mixing operation may be inserted. In addition, any mixing operation may include multiple mixing, testing, and remixing trials until a predefined number of retries is reached.

(322) In any of the embodiments, any of the pumps may be, or include, any of a variety of types

including peristaltic pumps, diaphragm pumps, screw pumps, gear pumps, centrifugal pumps, turbine pumps, syringe pumps, or piston pumps. The foregoing is a list of examples and is not intended to limit the scope of the present disclosure or the claims below.

(323) In any of the embodiments, the containers of concentrate may be replaced with online sources of concentrate such as proportioning systems in a large-scale installation that mixes component ingredients to form concentrates and provides them from a fixed connector. In any of the embodiments, other sources of fluids may be connected to the fluid flow director embodiments described herein. Examples include cleaning fluids, reference testing fluids for calibrating the conductivity sensor or sensors, sample fluids, and fluids for testing membranes such as air. In any of the embodiments, such other fluids may flow through various parts of the fluid circuit including the drain as described with reference to other fluids.

(324) As the term is used herein, “flow director” is a fluid circuit and associated actuators effective for selectively creating flow paths and moving fluids through the flow paths in order to connect fluid channels or vessels including those connected to sources and consumers, repositories, or other receiving elements. A “fluid circuit” is may be any line or branching element and may contain vessels, chambers, sensor portions, actuator portions, or any other type of fluid confining and controlling element.

(325) Any embodiment which recites or shows tubes as portions of a fluid circuit, fluid channel, or other equivalent may have instead other types of fluid channel elements such as channels defined in a casting with a bonded film layer to close the channels, panels with welded patterns to form fluid channels, non-round ducts, or other types of elements. The disclosed tubes may be replaced with such alternative elements to form additional embodiments.

(326) Any embodiment which identifies peritoneal dialysis fluid may be modified to form additional embodiments by replacing the components identified with that particular fluid with corresponding fluids to form other medicaments.

(327) Any component or element identified herein as “disposable” may be sterile. Sterility may be readily provided and assured at a time of use, by providing components as disposable elements as is known in the relevant field of medical devices.

(328) As used herein, “pre-connected” may refer to the integral combination of elements or to their connection in such a manner as to form a sterile boundary or permit the provision of a sterile boundary around their interior. For example, if a connection of connectors of two elements is made (i.e., they are pre-connected or pre-connected) and the connected elements are sterilized as a unit thereafter, the pre-connected or pre-connected elements may protect against the touch contamination that would be required if the corresponding connection were made in the field, for example. When elements are integral they may provide the same benefit.

(329) As the terms are used herein, electrolyte concentrate may include various ionic species as well as non-ionic species as required. As used herein, osmotic agent concentrate may include any osmotic agent such as glucose or dextrose and may include other species including ionic species that may be characterized by the term “electrolytes.”

(330) Any of the embodiments expressly limited to “peritoneal dialysis fluid” may be modified to form additional embodiments by substitution of the term “dialysate” and making appropriate substitutions for the constituents. Any embodiments limited to multiple concentrates, including two, may be changed to employ a single concentrate that is diluted to form a ready-to-use medicament.

(331) Any of the valves or pumps recited herein may be substituted for any of a variety of types of flow directing and fluid conveying devices. For example, a variety of pump and valve types are known and may be substituted for those described herein. Variations based on substitutions of these elements may be made to form additional embodiments.

(332) As the term is used herein, “in-line” means that an element is in a flow path. For example, a flow channel with an in-line sterilizing filter is such that fluid flowing in the flow channel is

filtered by the in-line filter.

(333) A port is any transition for a fluid conveyance such as a channel, tube, integral connection, or connector. Any recitation of “port” may be replaced with the term “connector” to form variations of the disclosed embodiments.

(334) As used herein, a window is any opening in a curved or flat element. A drain is any outlet to an external element and may include a storage vessel.

(335) Any sterilizing filter may be embodied as a channel blocked by a microporous membrane. Such a microporous membrane may have pores whose maximum size is no greater than a minimum pathogen size. Known threshold pore sizes are, for example, 0.2 microns.

(336) Any embodiment element identified with the term “daily” may be changed by substitution of other time intervals to form additional embodiments.

(337) Integral or integrally attached refers to elements that are formed of a single piece or bonded together so as to create a single unit. Elements identified as integral may be changed to identify them as “connected” or “attached” to define additional embodiments.

(338) As used herein, a “source” is any container or plant capable of supplying a recited fluid. A sink is any destination for a fluid such as a container, a consuming device, or a drain.

(339) As user herein, a “line” is tube or other type of fluid channel. In any of the embodiments, lines may be tubes such as polymer tubing commonly used for medical disposable devices.

(340) A “recess” is any concavity. A recess has two ends, an “access” which is the open end, and a “blind end,” which is the closed end.

(341) Any détente mechanism identified herein may be substituted with any type of frictional or interference-based mechanism for locking or restraining one element relative to another to form additional embodiments.

(342) In any of the embodiments, including in the claims, where the integrity of a sterilizing filter is tested, the filter membrane may be subjected to a pressure-decay test or a bubble-point test. Other types of tests such as diffusion test and other known techniques may be used.

(343) Any of the embodiments of a dialysis device may have a digital controller that directs the sequence of operation to perform a treatment on a patient may have a wireless interface that communicates with a transmitter such as a radio frequency identification (RFID) tag, Bluetooth, or a NFC device. Such a device may communicate with a wireless-capable appliance such as a cellular phone, tablet, or other computer. Using the transmitter, the dialysis device may transfer a digital record of therapy data, such as a treatment log, from the transmitter. If the transmitter includes a receiver or if a separate receiver is provided, then the dialysis device may be enabled to receive a prescription for a therapy. For example, a NFC tag or mobile phone may be used to upload data such as a prescription from a mobile or a passive NFC tag to the dialysis device. The upload of a data to the dialysis device may be accomplished using a passive tag such as an RFID or a passive NFC device.

(344) Other information that may be uploaded to the dialysis device includes patient-identifying information as well as patient classifying information. The dialysis device may upload information about the dialysis system for diagnostic purposes using any of the wireless protocols. The dialysis device may transfer data by wireless protocols such as 802.11 a/b/g/ac/n and Bluetooth. The dialysis device may download system logging or diagnostic data from the dialysis device to the cellular phone, tablet, or other computer using any of the wireless protocols. The dialysis device may download treatment summary data to the cellular phone, tablet, or other computer using any of the wireless protocols.

(345) According to first embodiments, the disclosed subject matter includes a method for making a batch of peritoneal dialysis solution sufficient for at least a single patient fill operation, the batch being a final mixture of constituents, the constituents including a final quantity of water, a final quantity of osmotic agent concentrate, and a final quantity of electrolyte concentrate. The method includes using a fluid proportioning device with a controller, actuators, and a conductivity sensor

and attaching a fluid circuit to the actuators, the fluid circuit having a mixing container. The method includes using the controller to control the actuators: pumping a fraction of the final quantity of water into the mixing container; pumping more than the final quantity, plus or minus an error, of electrolyte concentrate into the mixing container; mixing contents of the mixing container; sampling the contents of the mixing container in a manner that reduces volume of fluid in the mixing container and measuring the conductivity thereof; calculating and storing data responsive to a deviation of the measured conductivity from a predefined expected conductivity resulting from the error; calculating an adjusted quantity of water and/or osmotic agent concentrate required to achieve predefined proportions of the constituent final quantities responsive to the data; and pumping the adjusted quantity of water or osmotic agent concentrate into the mixing container.

(346) In variations thereof, the first embodiments include ones in which the method is performed at a location of a peritoneal dialysis treatment. In variations thereof, the first embodiments include ones in which the method is performed at a time of a peritoneal dialysis treatment. In variations thereof, the first embodiments include ones in which the method is performed such that it is completed within a day, within 12 hours, within 6 hours, within 3 hours, or within an hour of a start of a peritoneal dialysis treatment. In variations thereof, the first embodiments include ones in which the fluid proportioning device is located in a same room, within 100 meters, within 10 meters, within 5 meters, or within 2 meters as a patient receiving a peritoneal dialysis treatment.

(347) In variations thereof, the first embodiments include ones in which the electrolyte concentrate is pumped into the mixing concentrate after the fraction of the final quantity of water; the mixing takes place after the pumping of the more than the final quantity of electrolyte concentrate; the sampling takes place after the mixing; the calculating and storing data take place after the sampling; the calculating the adjusted quantity takes place after the calculating and storing the data; and the pumping the adjusted quantity takes place after the calculating the adjusted quantity.

(348) In variations thereof, the first embodiments include ones in which the using a fluid proportioning device includes providing a peritoneal dialysis cycler. In variations thereof, the first embodiments include ones that include, after pumping the adjusted quantity of water and/or osmotic agent concentrate, sampling the contents of the mixing container and measuring a final conductivity thereof. In variations thereof, the first embodiments include ones that include comparing a final conductivity to a predefined final conductivity and permitting use of the batch or preventing use of the batch responsively to a result thereof. In variations thereof, the first embodiments include ones in which the fraction of the final quantity of water pumped into the mixing container is less than 60%. In variations thereof, the first embodiments include ones in which the controller samples the mixing container contents by pumping a sample from the mixing container across a conductivity sensor in a drain line. In variations thereof, the first embodiments include ones in which the fraction of the final quantity of water pumped into the mixing container is less than 90%. In variations thereof, the first embodiments include ones in which the pumping more than the final quantity, plus or minus an error, of electrolyte concentrate occurs before the pumping the adjusted quantity of water or osmotic agent concentrate into the mixing container.

(349) According to second embodiments, the disclosed subject matter includes a method for making a batch of peritoneal dialysis solution sufficient for a patient fill operation, the batch being a mixture of constituents in target proportions, the constituents including water, osmotic agent concentrate, and electrolyte concentrate. The method includes using a fluid proportioning device with a controller, actuators, and a conductivity sensor. The method includes attaching a fluid circuit to the actuators, the fluid circuit having a mixing container. The method includes using the controller to control the actuators: pumping water into the mixing container; pumping electrolyte concentrate into the mixing container in an amount intended to create a predefined ratio of the electrolyte concentrate and the water; mixing contents of the mixing container; sampling the contents of the mixing container and measuring a conductivity thereof; calculating and storing data responsive to a deviation of a measured conductivity of the mixing container contents from one

corresponding to the predefined ratio; calculating an adjusted quantity of water or osmotic agent concentrate responsively to the data; and pumping the adjusted quantity of water or osmotic agent concentrate into the mixing container.

(350) In variations thereof, the second embodiments include ones in which the method is performed at a time of a peritoneal dialysis treatment. In variations thereof, the second embodiments include ones in which the using a fluid proportioning device includes providing a peritoneal dialysis cycler. In variations thereof, the second embodiments include ones that include, after pumping the adjusted quantity of water or osmotic agent concentrate, sampling the contents of the mixing container and measuring a final conductivity thereof. In variations thereof, the second embodiments include ones that include, comparing the measured final conductivity to a predefined final conductivity and permitting use of the contents of the mixing container or preventing use of the contents of the mixing responsively to a result thereof. In variations thereof, the second embodiments include ones that include adding further water to the mixing container to create ready-to-use dialysate therein, wherein the adding water into the mixing container transfers less than 60% of the quantity of water in the ready-to-use dialysate in the mixing container. In variations thereof, the second embodiments include ones in which the controller samples the mixing container contents by pumping a sample from the mixing container across a conductivity sensor in a drain.

(351) According to third embodiments, the disclosed subject matter includes method for making a batch of peritoneal dialysis solution sufficient for least a single patient fill operation, the batch being a final mixture of constituents, the constituents including a final quantity of water, a final quantity of osmotic agent concentrate, and a final quantity electrolyte concentrate, wherein the osmotic agent concentrate includes a predefined proportion of electrolyte. The method includes providing a fluid proportioning device with a controller, actuators, and a conductivity sensor. The method includes attaching a fluid circuit to the actuators, the fluid circuit having a mixing container. The method includes using the controller to control the actuators: pumping a fraction of the final quantity of water into the mixing container; pumping more than the final quantity, plus or minus an error, of osmotic agent concentrate into the mixing container; mixing contents of the mixing container; sampling the contents of the mixing container in a manner that reduces volume of fluid in the mixing container and measuring the conductivity thereof; calculating and storing data responsive to a deviation of the measured conductivity from a predefined expected conductivity resulting from the error; calculating an adjusted quantity of water and/or electrolyte concentrate required to achieve predefined proportions of the constituent final quantities; and pumping the adjusted quantity of water and/or electrolyte concentrate into the mixing container.

(352) In variations thereof, the third embodiments include ones in which the method is performed at a location of a peritoneal dialysis treatment. In variations thereof, the third embodiments include ones in which the method is performed at a time of a peritoneal dialysis treatment. In variations thereof, the third embodiments include ones in which the method is performed such that it is completed within a day, within 12 hours, within 6 hours, within 3 hours, or within an hour of a start of a peritoneal dialysis treatment. In variations thereof, the third embodiments include ones in which the fluid proportioning device is located in a same room, within 100 meters, within 10 meters, within 5 meters, or within 2 meters as a patient receiving a peritoneal dialysis treatment. In variations thereof, the third embodiments include ones that include providing a peritoneal dialysis cycler. In variations thereof, the third embodiments include ones that include, after pumping the adjusted quantity of water and/or electrolyte concentrate, sampling the contents of the mixing container and measuring a final conductivity thereof. In variations thereof, the third embodiments include ones that include comparing the final conductivity to a predefined final conductivity and permitting use of the batch or preventing use of the batch responsively to a result thereof. In variations thereof, the third embodiments include ones in which the fraction of the final quantity of water pumped into the mixing container is less than 60%. In variations thereof, the third

embodiments include ones in which the controller samples the mixing container contents by pumping a sample from the mixing container across a conductivity sensor in a drain line. In variations thereof, the third embodiments include ones in which the fraction of the final quantity of water pumped into the mixing container is less than 90%. In variations thereof, the third embodiments include ones in which the pumping more than the final quantity, plus or minus an error, of osmotic agent concentrate occurs before occurs before the pumping the adjusted quantity of water and/or electrolyte concentrate into the mixing container.

(353) According to fourth embodiments, the disclosed subject matter includes method for making a batch of peritoneal dialysis solution sufficient for at least a single patient fill operation, the batch being a final mixture of constituents, the constituents including a final quantity of water, a final quantity of osmotic agent concentrate, and final quantity of electrolyte concentrate, the method, using a controller of a peritoneal dialysis treatment delivery system. The method includes (a) adding a fraction of the final quantity of water and a first concentrate, the first concentrate being one of osmotic agent concentrate or electrolyte concentrate, to a mixing container and mixing contents of the mixing container; (b) measuring a conductivity of the contents of the mixing container and if within a first predefined range, skipping to (d); (c) computing a new final quantity of a second concentrate, the second concentrate being the other of osmotic agent concentrate or electrolyte concentrate to add to the mixing container responsively to an error of the measuring, the error being in a proportion of the first concentrate detected and the fraction of the final quantity of water measured in (b); (d) adding the second concentrate to the mixing container and mixing the contents of the mixing container; (e) measuring a conductivity of the contents of the mixing container and if the measured conductivity is within a second predefined range, skipping to (h) (f) generating a command to terminate the making of the batch if a new final quantity of the second concentrate was computed in (c); otherwise, computing a first supplemental amount of the second concentrate or water to bring the conductivity to a second predefined range; (g) measuring a conductivity of the contents of the mixing container and if not within a third predefined range, computing a second supplemental amount of the first and second concentrates or water to add to bring the conductivity within the predefined range; and (h) adding one or more further quantities of water, the first concentrate, and/or the second concentrate sufficient to achieve the proportions of the final mixture, responsively to the first and/or second supplemental amounts if computed.

(354) In variations thereof, the fourth embodiments include ones in which the method is performed at a time of a peritoneal dialysis treatment. In variations thereof, the fourth embodiments include ones in which the method is performed at a location of a peritoneal dialysis treatment. In variations thereof, the fourth embodiments include ones in which, if the contents of the mixing container are not within the third predefined range in (g) then generating a command to terminate the making of the final mixture. In variations thereof, the fourth embodiments include ones that include, in response to the command to terminate the making of the batch, preventing the use of the final mixture. In variations thereof, the fourth embodiments include ones that include using the final mixture to perform a fill cycle of a peritoneal dialysis treatment. In variations thereof, the fourth embodiments include ones that include testing a sterilizing filter through which at least one component of the contents of the mixing container flows and generating a command to terminate the method if the test indicates a failure. In variations thereof, the fourth embodiments include ones in which the testing includes applying pressurized air to a wetted membrane and measuring a pressure.

(355) According to fifth embodiments, the disclosed subject matter includes method of making a dialysate. The method includes adding water and a first concentrate (C1) to a mixing container, measuring a first conductivity of the mixing container contents, and if the first conductivity of the contents of the mixing container is in a first range, adding a second concentrate (C2), measuring a second conductivity of the contents of the mixing container, and if the second conductivity is in a second range further diluting the contents of the mixing container. The method includes measuring

a third conductivity of the contents of the mixing container and if the third conductivity is in a third range, using the contents of the mixing container for a treatment; otherwise, if the third conductivity is lower than the third range, adding C1 and C2, and if the third conductivity is higher than the third range, further diluting the contents of the mixing container. The method includes, if the second conductivity of the contents of the mixing container is higher than the second range, adding C1 and water in amounts that are responsive to the second conductivity and if the second conductivity of the contents of the mixing container is lower than the second range, adding C2 in an amount that is responsive to the second conductivity.

(356) In variations thereof, the fifth embodiments include ones that include, if after adding C1 to the mixing container the first conductivity higher than the first range, calculating an additional amount of C2 to add to the mixing container responsive to the first conductivity. In variations thereof, the fifth embodiments include ones that include, if after adding C1 to the mixing container the first conductivity higher than the first range, calculating an additional amount of C1 to add to the mixing container responsive to the first conductivity. In variations thereof, the fifth embodiments includes ones that include if after adding C1 to the mixing container the first conductivity higher than the first range, calculating an additional amount of C1 to add to the mixing container responsive to the first conductivity. In variations thereof, the fifth embodiments include ones that include mixing the contents of the mixing container prior to determining the first or the second conductivity.

(357) According to sixth embodiments, the disclosed subject matter includes a method of generating a batch of treatment fluid, the method including using a controller that stores a treatment prescription, and according to the prescription, pumping a calculated ratio of water and electrolyte concentrate into a mixing container by regulating a pump to control a net volume of each that is transferred to the mixing container. The controller further stores reference data indicating conductivity of predefined dilution ratios of water and the electrolyte concentrate. The method includes testing a conductivity of the contents of the mixing container resulting from the pumping and further pumping water or electrolyte concentrate responsively to the testing if the conductivity differs by more than a defined threshold from the conductivity indicated by the stored reference data and controlling a further use of a pump to permit the contents of the mixing container to be used thereafter, or immediately controlling a further use of the pump to permit the contents of the mixing container to be used if the conductivity differs by less than the defined threshold.

(358) In variations thereof, the sixth embodiments include ones that include, after the pumping a predefined quantity of water and electrolyte concentrate, mixing contents of the mixing container. In variations thereof, the sixth embodiments include ones that include using the controller to measure temperature of the fluid from the mixing container. In variations thereof, the sixth embodiments include ones that include using the controller to measure temperature of the fluid from the mixing container, temperature-compensate the conductivity, calculate whether the conductivity falls under the threshold to generate a pass/fail result, and outputting one of a command to change a later addition of water or concentrate responsively to the pass/fail result and a command to stop preparation of the batch responsively to the pass/fail result. In variations thereof, the sixth embodiments include ones that include, using the controller to measure temperature of the fluid from the mixing container, temperature-compensating the conductivity, calculating whether the conductivity falls under the threshold to generate a pass/fail result, and outputting one of a command to change the later addition of water or concentrate responsively the pass/fail result and a command to stop preparation of the batch responsively to the pass/fail result, wherein the threshold indicates a conductivity of a diluted osmotic agent electrolyte concentrate.

(359) According to seventh embodiments, the disclosed subject matter includes method of making a batch of peritoneal dialysis fluid. The method includes providing a controller connected to receive signals from a conductivity sensor, the controller storing target conductivities of predefined target ratios of first and second fluids at a body temperature of a human, the controller further

storing a correction factor that indicates a rate of change of conductivity with temperature. The method includes using the controller, in no particular order, adding a predefined volume of the first fluid to a container and adding the second fluid to the container having a composition different from the first. The method includes mixing the first and second fluids in the container to create an in-process mixture. The method includes warming the first and second fluids to a temperature within a predefined range of the body temperature either prior to, during, or after the adding or mixing. The method includes measuring a current conductivity and a current temperature of the in-process mixture from the container. The method includes using the controller, selecting one of the predefined target ratios corresponding to a current target in-process mixture and calculating an additional amount of the first or second fluid to add to the container to achieve the selected one of the predefined target ratios responsively to the current conductivity, the current temperature, and the correction factor; and adding the additional amount to the container.

(360) In variations thereof, the seventh embodiments include ones in which the controller stores correction factors for each of the predefined target ratios and the calculating an additional amount is responsive to a correction factor corresponding to the selected one of the predefined target ratios. In variations thereof, the seventh embodiments include ones in which the container stores a batch of peritoneal dialysis fluid. In variations thereof, the seventh embodiments include ones that include adding a predefined volume of a third fluid at a time before, during, or after the adding the additional amount. In variations thereof, the seventh embodiments include ones in which the adding the additional amount includes adding one of water and electrolyte concentrate. In variations thereof, the seventh embodiments include ones in which the adding the additional amount includes adding one of water and a concentrate including an osmotic agent. In variations thereof, the seventh embodiments include ones in which the osmotic agent concentrate includes electrolyte. In variations thereof, the seventh embodiments include ones in which the first fluid is water and the second fluid is a mixture of electrolytes for peritoneal dialysis fluid. In variations thereof, the seventh embodiments include ones in which the first fluid is water and the second fluid is a mixture of electrolytes and osmotic agent for peritoneal dialysis fluid. In variations thereof, the seventh embodiments include ones in which the predefined target ratios are concentrations of electrolytes in water.

(361) According to eighth embodiments, the disclosed subject matter includes medicament preparation system. A proportioning element that prepares medicament from concentrate and water. A proportioning element controller connects to the proportioning element and configured to control functions thereof. A water preparation element is configured to purify water and has a product water output connected to convey water to the proportioning element. A water preparation element controller connects to the water preparation element and is configured to control functions thereof. The water preparation element controller is controlled by the proportioning controller such that functions of the water preparation element are controlled by the proportioning controller.

(362) In variations thereof, the eighth embodiments include ones in which the water preparation element functions include a filter regeneration function and the filter regeneration function is controlled by the proportioning element controller. eighth the water preparation element has a reversing valve and the proportioning element controller controls the reversing valve.

(363) In variations thereof, the eighth embodiments include ones in which the water preparation element is configured to divert at least a fraction of its product water through a one of multiple filter units therein to regenerate the one of multiple filter units. In variations thereof, the eighth embodiments include ones in which the water preparation element includes an ultraviolet lamp, the proportioning element controller being configured to cycle the ultraviolet lamp in order to eliminate or reduce output when water is not being filtered. In variations thereof, the eighth embodiments include ones in which the water preparation element has a product water heater and the proportioning element controller is configured to regulate a temperature of product water received by it by cycling the product water heater. In variations thereof, the eighth embodiments

include ones in which the proportioning element has a proportioning heater that heats fluid flowing therethrough. In variations thereof, the eighth embodiments include ones in which the proportioning element controller controls the product water heater and the proportioning heater to share a net heating demand between the product water heater and the proportioning heater. In variations thereof, the eighth embodiments include ones in which the water preparation element has a product water heater and the proportioning element controller is configured to regulate a temperature of product water received by it by cycling the water heater. In variations thereof, the eighth embodiments include ones in which the proportioning element has a proportioning heater that heats fluid flowing therethrough. In variations thereof, the eighth embodiments include ones in which the proportioning element controller controls the product water heater and the proportioning heater to share a net heating demand between the product water heater and the proportioning heater. In variations thereof, the eighth embodiments include ones in which the proportioning element includes a treatment element.

(364) In variations thereof, the eighth embodiments include ones in which the treatment element includes a dialysis machine. In variations thereof, the eighth embodiments include ones in which the treatment element includes a dialysis cyler. In variations thereof, the eighth embodiments include ones in which the treatment element includes a peritoneal dialysis cyler. In variations thereof, the eighth embodiments include ones in which the proportioning element controller receives status information from the water preparation element controller. In variations thereof, the eighth embodiments include ones in which the proportioning element controller includes a user interface and the proportioning element controller derives information from the status information and outputs derived data on the user interface, the derived data including indications that a filter of the water preparation element is in a flushing, priming, or cleaning mode. In variations thereof, the eighth embodiments include ones in which the proportioning element controller includes a user interface and the proportioning element controller derives information from the status information and outputs derived data on the user interface, the derived data including indications of water temperature or estimate of time delay till product water is available. In variations thereof, the eighth embodiments include ones in which the proportioning element controller includes a user interface and the proportioning element controller derives information from the status information and outputs derived data on the user interface, the derived data including indications of estimated time left till filter replacement (estimated time to exhaustion).

(365) In variations thereof, the eighth embodiments include ones in which the proportioning element controller receives status information from the water preparation element controller, the proportioning element controller includes a user interface, and the proportioning element controller derives information from the status information and outputs derived data on the user interface, the derived data including indications or amount of life left on the ultraviolet lamp. In variations thereof, the eighth embodiments include ones in which the proportioning element controller includes a user interface and the proportioning element controller derives information from the status information and outputs derived data on the user interface, the derived data including indications time till a next flush or a next cleaning cycle of the water preparation element. In variations thereof, the eighth embodiments include ones in which the proportioning element controller includes a user interface and the proportioning element controller derives information from the status information and outputs derived data on the user interface, the derived data including an indication whether the water preparation element is in a sleep mode and/or how long the before it is available to produce water.

(366) In variations thereof, the eighth embodiments include ones in which the proportioning element controller includes a user interface and the proportioning element controller derives information from the status information and outputs derived data on the user interface, the derived data including forecasts of maintenance tasks such as filter replacement. In variations thereof, the eighth embodiments include ones in which the proportioning element controller receives status

information from the water preparation element controller, the proportioning element controller includes a user interface, and the proportioning element controller derives information from the status information and outputs derived data on the user interface, the derived data including a forecast of a time for ultraviolet lamp replacement. In variations thereof, the eighth embodiments include ones in which the proportioning element controller includes a user interface and the proportioning element controller derives information from the status information and outputs derived data on the user interface, one or more resistivity sensors being provided in a product water outlet line the derived data including resistivity of the product water. In variations thereof, the eighth embodiments include ones in which the proportioning element controller includes a user interface and the proportioning element controller derives information from the status information and outputs derived data on the user interface, one or more resistivity sensors being provided in a product water outlet line the derived data including an alert when the resistivity is out of a predefined range.

(367) In variations thereof, the eighth embodiments include ones in which the proportioning element controller includes a user interface and the proportioning element controller derives information from the status information and outputs derived data on the user interface, one or more resistivity sensors being provided in a tap water inlet line the derived data including an alert when the resistivity is out of a predefined range. In variations thereof, the eighth embodiments include ones in which the derived data may be an estimate of filter life based on resistivity of water in the water inlet line. In variations thereof, the eighth embodiments include ones in which the water preparation element has an off mode, a sleep mode, and an operating mode. In variations thereof, the eighth embodiments include ones in which the proportioning element controller and the water preparation element controller communicate over a network. In variations thereof, the eighth embodiments include ones in which the proportioning element controller and the water preparation element controller communicate over a signal cable. In variations thereof, the eighth embodiments include ones in which the proportioning element controller and the water preparation element controller communicate over a wireless connection. In variations thereof, the eighth embodiments include ones in which the water preparation element controller indicates to the proportioning element controller its status including an indication that the water preparation element is ready to output product water.

(368) In variations thereof, the eighth embodiments include ones in which the proportioning element controller starts and stops water production by applying commands to the water preparation element controller. In variations thereof, the eighth embodiments include ones in which the proportioning element controller transmits commands to start and stop an ultraviolet (germicidal) lamp in the water preparation element. In variations thereof, the eighth embodiments include ones in which the commands are effective for extending a life of such an ultraviolet lamp by ensuring the lamp is operated only when required for treatment of water. In variations thereof, the eighth embodiments include ones in which the commands are effective for extending a life of such an ultraviolet lamp by ensuring the lamp is operated only when water is being filtered. In variations thereof, the eighth embodiments include ones in which the proportioning element controller employs two-way communication with the water preparation element to place the water preparation element in a sleep mode at an end of a treatment such that some or all power functions thereof are switched off to save power and reduce wear. In variations thereof, the eighth embodiments include ones in which the proportioning element controller may send commands to wake up the water preparation element so that it is ready at a time of a predefined treatment stored in the proportioning element controller. In variations thereof, the eighth embodiments include ones in which commands from the proportioning element controller regulate a pressure and flow rate at which product water is delivered by the water preparation element.

(369) In variations thereof, the eighth embodiments include ones in which closed loop control based on a pressure signal is provided by the water preparation element controller. In variations

thereof, the eighth embodiments include ones in which the proportioning element controller employs two-way communication with the water preparation element to transmit alarms generated by the water preparation element and the proportioning responds by ceasing dialysate proportioning in response to predefined alarms. In variations thereof, the eighth embodiments include ones in which alarm or status outputs of the water preparation element are effective to generate specific outputs through a user interface of the proportioning element controller. In variations thereof, the eighth embodiments include ones in which the proportioning element controller has a user interface that outputs guided troubleshooting steps in response to and related to outputs and alarms of the water preparation element controller. In variations thereof, the eighth embodiments include ones in which the water preparation element has a water heater and the proportioning element controller controls the water heater and receives indications from the water preparation element controller of a power output of the water heater, water temperature, and status of the water preparation element. (370) In variations thereof, the eighth embodiments include ones in which the water preparation element controller is configured to auto-order replacements filters through the Internet. In variations thereof, the eighth embodiments include ones in which a timing of the auto-order replacements is such as to effect a required change-out before exhaustion of the filters being replaced. In variations thereof, the eighth embodiments include ones in which the proportioning element has a priming mode in which flushes a fluid circuit thereof with water from the water preparation element. In variations thereof, the eighth embodiments include ones in which the proportioning element controller transmits commands to the water preparation element controller to output water at pressures and flow rates required for the proportioning element. In variations thereof, the eighth embodiments include ones in which the priming is preceded by a flushing operation with purified water to minimize endotoxins in the fluid circuit. In variations thereof, the eighth embodiments include ones in which the water preparation element includes a reservoir sized to provide water sufficient for a fill/drain cycle or for a full treatment (multiple cycles). In variations thereof, the eighth embodiments include ones in which the reservoir has one or more sterilizing-grade filters on its inlet (and/or outlet) lines to prevent touch contamination or back-growth contamination. In variations thereof, the eighth embodiments include ones in which the reservoir includes one or more check valves on its outlet lines to prevent backflow. In variations thereof, the eighth embodiments include ones in which an outlet of the reservoir includes a recirculation loop with a pump that maintains a target head pressure.

(371) According to ninth embodiments, the disclosed subject matter includes system for performing peritoneal dialysis with a fluid circuit with at least one fluid inlet and a mixing container. A peritoneal dialysis system has a peritoneal dialysis system controller, valve actuators, one or more pumps, to pump and direct concentrate and water selectively through at least at times and through portions of the fluid circuit to transfer concentrate and water, through the at least one fluid inlet, to the mixing container to form dialysis fluid. A water supply source has a water pump, the water pump being controlled by a water supply controller and being connected to a purified water outlet which is in turn connected to the at least one fluid inlet. A command interface is between the peritoneal dialysis system controller and the water supply controller, the peritoneal dialysis system controller transmitting one or more commands to the water supply controller to start and stop the water pump.

(372) In variations thereof, the ninth embodiments include ones in which the one or pumps are configured to pump concentrate and water from one or more sources.

(373) According to tenth embodiments, the disclosed subject matter includes system for performing peritoneal dialysis. A fluid circuit has a single fluid inlet and a mixing container. A peritoneal dialysis system has a peritoneal dialysis system controller, valve actuators, and a cycler pump that pumps concentrate and water within the fluid circuit. A water source with a water pump and a concentrate source with a concentrate pump are connected to pump water and concentrate through the fluid inlet under control of a fluid source controller connected to control the water and

concentrate pumps. A command interface is connected between the peritoneal dialysis system controller and the fluid source controller, the peritoneal dialysis system controller transmitting one or more commands to the fluid source controller to start and stop the water source and concentrate source pumps.

(374) According to eleventh embodiments, the disclosed subject matter includes system for performing peritoneal dialysis. A fluid circuit has at least one fluid inlet and a mixing container. A peritoneal dialysis system has a controller, valve actuators, one or more pumps, to pump and direct concentrate and water selectively through the fluid circuit to transfer concentrate and water, through the fluid inlet, to the mixing container to form dialysis fluid. A peritoneal dialysis cyler has actuators, including a cyler pump actuator, to direct concentrate and water selectively through the fluid circuit to transfer concentrate and water from one or more external sources, through the fluid inlet, to the mixing container to form dialysis fluid. A water supply source with a water pump having a purified water outlet connected to the at least one fluid inlet. The water supply source has a water source controller that controls the water pump responsively to at least one sensor that detects at least one operating condition of the peritoneal dialysis cyler. The water source controller activates the water pump when the operating condition indicates a requirement for water by the peritoneal dialysis cyler.

(375) In variations thereof, the eleventh embodiments include ones in which operating condition includes an activation of an actuator of the peritoneal dialysis cyler that controls the opening of the fluid inlet. In variations thereof, the eleventh embodiments include ones in which the operating condition includes the activation of the peritoneal dialysis cyler pump actuator. In variations thereof, the eleventh embodiments include ones in which the at least one sensor includes a pressure sensor that provides pressure signals to the water source controller, the water pump being controlled responsively to the pressure signals such that when the cyler pump actuator is activated to draw water from the at least one fluid inlet thereby generating a reduction in pressure in the at least one fluid inlet while the water pump is off, the water pump is turned on by the water source controller. In variations thereof, the eleventh embodiments include ones in which the water pump is turned on by the water source controller when the reduction reaches a predefined magnitude stored by the water source controller. In variations thereof, the eleventh embodiments include ones in which the water source controller controls the water pump to maintain the pressure of the at least one fluid inlet within a predefined range of pressures.

(376) According to twelfth embodiments, the disclosed subject matter includes a system for performing peritoneal dialysis. A fluid circuit has a fluid inlet and a mixing container. A peritoneal dialysis cyler has a cyler controller, actuators, including a cyler pump actuator, to direct concentrate and water selectively through the fluid circuit to transfer concentrate and water, through the fluid inlet, to the mixing container to form dialysis fluid. A water supply source has a water pump having a purified water outlet connected to the at least one fluid inlet. The purified water outlet has a pressure sensor and a water source controller that receives pressure signals from the pressure sensor and controls the water pump responsively to the pressure signals, the cyler pump actuator generating coded pressure pulses in the fluid inlet that are received by the pressure sensor and decoded by the water source controller to command the water source controller to activate and deactivate the water pump responsively to decoded commands encoded in the pressure signals.

(377) In variations thereof, the twelfth embodiments include ones in which the coded pressure pulses encode changes to operating parameters of the water source controller including a closed-loop pressure set point at the fluid inlet. In variations thereof, the twelfth embodiments include ones in which the coded pressure pulses encode changes to operating parameters of the water source controller. In variations thereof, the twelfth embodiments include ones in which the water source controller controls the water pump to maintain the pressure of the at least one fluid inlet within a predefined range of pressures.

(378) According to thirteenth embodiments, the disclosed subject matter includes method for making a peritoneal dialysis fluid, the method including connecting a fluid circuit to a proportioning machine, the fluid circuit including a mixing container. The proportioning machine has actuators that engage with the fluid circuit when received thereby. The method includes connecting a water source and one or more fresh containers of concentrate to the fluid circuit, each of the one or more fresh containers of concentrate having sufficient concentrate for multiple treatments. The method includes using a controller of the proportioning machine, flowing purified water from the water source and concentrate from the one or more containers through the fluid circuit to the mixing container to prepare a dialysis fluid in the mixing container by proportioning the water and concentrate. The flowing includes flowing water and concentrate through at least one sterilizing filter to ensure sterility of the water and concentrate. The at least one sterilizing filter includes serially-connected redundant sterilizing filters or the method including, using the controller, testing the integrity of a membrane of the at least one sterilizing filter and preventing a use of contents of the mixing container responsively to a result of the testing. The method includes using the controller, treating a patient using the dialysis fluid from the mixing container, the treating including performing multiple fill and drain cycles of a peritoneal dialysis treatment. The method includes replacing the fluid circuit with a new fluid circuit. The method includes repeating the connecting a fluid circuit, flowing purified water and concentrate, and repeating the treating a patient, without replacing the one or more fresh containers of concentrate, whereby the one or more fresh concentrate containers are replaced once every multiple treatments.

(379) In variations thereof, the thirteenth embodiments include ones in which the at least one filter is integrally attached to the fluid circuit. In variations thereof, the thirteenth embodiments include ones in which the flowing water and concentrate through at least one sterilizing filter includes flowing water and concentrate through separate filters. In variations thereof, the thirteenth embodiments include ones in which the at least one filter includes a testable filter with an air line, the method including, using the controller, applying a pressure to the air line to test an ability of a wetted membrane of the testable filter to withstand pressure and thereby indicate the membrane's integrity. In variations thereof, the thirteenth embodiments include ones in which the connecting a water source and one or more containers of concentrate to the fluid circuit includes: at a first time, replacing one or more spent containers of concentrate with the one or more fresh containers of concentrate; at a second time, connecting a fluid inlet line of the fluid circuit with the at least one sterilizing filter to a common fluid outlet of a fluid source module; the fluid source module having automatic valves connected to a water source and the one or more fresh containers of concentrate, the automatic valves selecting, under control of the controller, only one of the water source and the one or more fresh containers of concentrate for connection to the fluid inlet line at a given time.

(380) In variations thereof, the thirteenth embodiments include ones in which the flowing water and concentrate includes pumping the water and concentrate by the fluid source module.

(381) According to fourteenth embodiments, the disclosed subject matter includes treatment method including connecting a fluid circuit to a proportioning machine, the fluid circuit including a mixing container. The proportioning machine has actuators that engage with the fluid circuit when received thereby. The method includes connecting one or more containers of medicament concentrate to the fluid circuit, each container having sufficient medicament concentrate for multiple treatments. The method includes using the proportioning machine, flowing purified water and concentrate through the fluid circuit to the mixing container to prepare a medicament in the mixing container by proportioning the purified water and medicament concentrate. The flowing includes flowing water and concentrate through at least one sterilizing filter to ensure sterility of the water and concentrate. The method includes ensuring an integrity of the at least one sterilizing filter by testing the at least one sterilizing filter or providing serially-connected redundant sterilizing filters. The method includes treating a patient using the prepared medicament in the mixing container. The method includes replacing the fluid circuit with a new fluid circuit and

repeating the connecting a fluid circuit, flowing purified water and concentrate, treating a patient, without replacing the one or more containers of medicament concentrate.

(382) In variations thereof, the fourteenth embodiments include ones in which the at least one filter is integrally attached to the fluid circuit. In variations thereof, the fourteenth embodiments include ones in which the flowing water and concentrate through at least one sterilizing filter includes flowing water and concentrate through separate filters.

(383) According to fifteenth embodiments, the disclosed subject matter includes a system for preparation of sterile medical treatment fluid. The system includes at least one fluid circuit with a pumping tube segment and multiple valve segments, at least one pumping actuator, and multiple valve actuators positioned to engage the multiple valve segments. The at least one pumping actuator engages the at least one pumping tube segment. A controller is connected to control the multiple valve actuators and the at least one pumping actuator. A first of the multiple valve segments is along a fluid inlet line with a sterilizing filter. A first multi-treatment concentrate container has sufficient concentrate for preparation of enough peritoneal dialysis fluid to perform multiple peritoneal dialysis treatments, each treatment including multiple fill/drain cycles. The system has a water source. The at least one fluid circuit has, integrally-attached thereto, a first single-treatment concentrate container and a mixing container, the mixing container being sized to hold sufficient peritoneal dialysis fluid for at least a single fill cycle. Ones of the multiple valve segments is/are connected between the fluid inlet line and the water source and between the first multi-treatment concentrate container and the fluid inlet line. The controller, controlling the ones of the multiple valve segments and the at least one pumping actuator, sequentially connects the first single-treatment concentrate container and the water source to the fluid inlet line and controls flow such that water is conveyed from the water source to the mixing container and concentrate is conveyed from the first multi-treatment concentrate container to the first single-treatment concentrate container, and subsequently incorporated in a dialysis fluid formed in the mixing container.

(384) In variations thereof, the fifteenth embodiments include ones in which the controller is configured to perform a fill/drain cycle including draining spent fluid from a patient line and pumping the dialysis fluid from the mixing container to the patient line. In variations thereof, the fifteenth embodiments include ones that include a second multi-treatment concentrate container, wherein, ones of the multiple valve segments are connected the second multi-treatment concentrate container and the fluid inlet line. In variations thereof, the fifteenth embodiments include ones that include a second single-treatment concentrate container connected to the fluid circuit, the controller transferring concentrate from the second multi-treatment concentrate container to the second single-treatment concentrate container to form the dialysis fluid. In variations thereof, the fifteenth embodiments include ones in which the sterilizing filter has an air port to allow a membrane of the sterilizing filter to be pressure tested, the controller being programmed to test the sterilizing filter membrane by applying pressure to the air port and measuring the pressure after pumping water therethrough. In variations thereof, the fifteenth embodiments include ones in which controller generates an alarm signal responsively to a result of a test of the sterilizing filter membrane if the test indicates a loss of integrity of the sterilizing filter membrane.

(385) According to sixteenth embodiments, the disclosed subject matter includes fluid circuit for dialysis solution preparation. A valve network has interconnected channels that can be opened and closed by opening and closing valve portions of the interconnected channels. A fluid inlet line has an inline sterilizing filter, a mixing container, a first concentrate container, a drain line, a patient fill/drain line all empty and pre-connected to the valve network to form a unit and sealed from an external environment. The valve network has a pumping portion to pump fluid between the interconnected channels.

(386) In variations thereof, the sixteenth embodiments include ones in which the patient fill/drain line includes separate branch lines that connect to the valve network which branch lines merge to

form a single line that connects to a patient. In variations thereof, the sixteenth embodiments include ones in which the inline sterilizing filter has an air line attached thereto, the air line being connected such that air forced through the air line applies pressure to a membrane of the inline sterilizing filter to permit an integrity test thereof. In variations thereof, the sixteenth embodiments include ones in which the valve network is attached to a rigid manifold member, the air line being connecting to a port fixedly attached to the rigid manifold member. In variations thereof, the sixteenth embodiments include ones in which the air line is collinear with the fluid inlet line. In variations thereof, the sixteenth embodiments include ones in which valve network is supported by a panel. In variations thereof, the sixteenth embodiments include ones in which the valve network is supported by a panel, the pumping portion being supported by a rigid manifold portion of the valve network which is spaced from the panel. In variations thereof, the sixteenth embodiments include ones in which the rigid manifold portion has pressure sensing diaphragms integrated in and supported thereby.

(387) In variations thereof, the sixteenth embodiments include ones in which the air line is integral with at least a portion of the fluid inlet line. In variations thereof, the sixteenth embodiments include ones in which the rigid manifold portion pressure sensing diaphragms are located one at each end of the pumping portion. In variations thereof, the sixteenth embodiments include ones in which the pumping portion is straight. In variations thereof, the sixteenth embodiments include ones that include a second concentrate container pre-connected to the valve network. In variations thereof, the sixteenth embodiments include ones in which the mixing container and first and second concentrate containers are polymer bags. In variations thereof, the sixteenth embodiments include ones in which the mixing container has a larger internal volume than the first and second concentrate containers. In variations thereof, the sixteenth embodiments include ones in which the panel has windows that overlie the valve portions. In variations thereof, the sixteenth embodiments include ones in which the valve network includes a manifold portion with a pumping tube segment. In variations thereof, the sixteenth embodiments include ones in which the valve portions are portions of a bank of tubes stemming from the manifold portion. In variations thereof, the sixteenth embodiments include ones in which the valve portions are portions of a bank of parallel tubes stemming from the manifold portion. In variations thereof, the sixteenth embodiments include ones that include a second sterilizing filter connected in series with the inline sterilizing filter such that the second and inline sterilizing filters are separated by a flow channel. In variations thereof, the sixteenth embodiments include ones in which the mixing container and first concentrate container are defined by two bonded flexible panels along seams to define the mixing container and concentrate container. In variations thereof, the sixteenth embodiments include ones in which the valve network fluidly interconnects the fluid inlet line to the concentrate container. In variations thereof, the sixteenth embodiments include ones in which the valve network fluidly interconnects the concentrate container with the mixing container. In variations thereof, the sixteenth embodiments include ones in which the valve network fluidly interconnects the mixing container with the patient fill and patient drain lines.

(388) According to seventeenth embodiments, the disclosed subject matter includes system for performing a peritoneal dialysis treatment. At least two multi-treatment concentrate containers have concentrate supply connectors, the at least two multi-treatment concentrate containers having sufficient concentrate to perform multiple dialysis treatments, where each treatment includes multiple fill/drain cycles. A valve network has interconnected channels that can be opened and closed by opening and closing valve portions of the interconnected channels. A fluid inlet line has an inline sterilizing filter, a mixing container, first and second single-treatment concentrate containers, a drain line, a patient fill/drain line all empty and pre-connected to the valve network to form a unit and sealed from an external environment. The valve network has a pumping portion to pump fluid between the interconnected channels.

(389) In variations thereof, the seventeenth embodiments include ones that include a connection

platform that mechanically supports the at least two multi-treatment concentrate containers and selectively couples them to the fluid inlet line. In variations thereof, the seventeenth embodiments include ones that include a connection platform with a water source and attachments for the at least two multi-treatment concentrate containers, the connection platform having a valve system that fluidly couples the at least two multi-treatment concentrate containers and the water source to the fluid inlet line. In variations thereof, the seventeenth embodiments include ones in which the inline sterilizing filter has an air line attached thereto, the air line being connected such that air forced through the air line applies pressure to a membrane of the inline sterilizing filter to permit an integrity test thereof. In variations thereof, the seventeenth embodiments include ones in which the air lines are each collinear with at least a portion of the fluid inlet line. In variations thereof, the seventeenth embodiments include ones in which the air lines are each attached along at least a portion of the fluid inlet line. In variations thereof, the seventeenth embodiments include ones in which the valve network is supported by a panel, the pumping portion being supported by a rigid manifold portion of the valve network which is spaced from the panel. In variations thereof, the seventeenth embodiments include ones in which the manifold portion has pressure sensors integrated therein, one at each end of a pumping tube segment of the pumping portion. In variations thereof, the seventeenth embodiments include ones in which the pumping tube segment is straight. In variations thereof, the seventeenth embodiments include ones in which the pressure sensor includes a pressure pod with a diaphragm that serves as a portion of a wall of a respective one of two separate chambers of the rigid manifold portion. In variations thereof, the seventeenth embodiments include ones in which the valve network is attached to a rigid manifold, the air line being connecting to a port fixedly attached to the rigid manifold. In variations thereof, the seventeenth embodiments include ones in which the air line is collinear with the fluid inlet line. In variations thereof, the seventeenth embodiments include ones in which the valve network is supported by a panel. In variations thereof, the seventeenth embodiments include ones that include a second concentrate container pre-connected to the valve network.

(390) In variations thereof, the seventeenth embodiments include ones in which the mixing container and first and second concentrate containers are polymer bags. In variations thereof, the seventeenth embodiments include ones in which the mixing container has a larger internal volume than the first and second single-treatment concentrate containers. In variations thereof, the seventeenth embodiments include ones in which the panel has windows that overlie the valve portions. In variations thereof, the seventeenth embodiments include ones in which the valve network includes a manifold portion with a pumping tube segment. In variations thereof, the seventeenth embodiments include ones in which the valve portions are portions of a bank of tubes stemming from the manifold. In variations thereof, the seventeenth embodiments include ones in which the valve portions are portions of a bank of parallel tubes stemming from the manifold. In variations thereof, the seventeenth embodiments include ones that include a second sterilizing filter connected in series with the inline sterilizing filter such that the second and inline sterilizing filters are separated by a flow channel.

(391) In variations thereof, the seventeenth embodiments include ones in which the mixing container and first and second single-treatment concentrate containers are defined by two bonded flexible panels along seams to define the mixing container and first and second single-treatment concentrate containers. In variations thereof, the seventeenth embodiments include ones in which the valve network fluidly interconnects the fluid inlet line to the first and second single-treatment concentrate containers. In variations thereof, the seventeenth embodiments include ones in which the valve network fluidly interconnects the first and second single-treatment concentrate containers with the mixing container. In variations thereof, the seventeenth embodiments include ones in which the valve network fluidly interconnects the mixing container with the patient fill/drain line. In variations thereof, the seventeenth embodiments include ones in which the at least two multi-treatment concentrate containers are contained in a single package. In variations thereof, the

seventeenth embodiments include ones in which the single package is housed by a single box. In variations thereof, the seventeenth embodiments include ones that include a connection platform with a water source and attachments for the at least two multi-treatment concentrate containers, the connection platform fluidly coupling the at least two multi-treatment concentrate containers and the water source to the fluid inlet line using control valves that include one for each of the at least two multi-treatment concentrates containers and one the water source, the water source having a water pump. In variations thereof, the seventeenth embodiments include ones that include a connection platform with a water source and attachments for the at least two multi-treatment concentrate containers, the connection platform fluidly coupling the at least two multi-treatment concentrate containers and the water source to the fluid inlet line using control valves that include one for each of the at least two concentrates and one the water source, the at least two concentrates containers connecting to a common line having a concentrate pump. In variations thereof, the seventeenth embodiments include ones that include a connection platform with a water source and attachments for the at least two multi-treatment concentrate containers, the connection platform fluidly coupling the at least two multi-treatment concentrate containers and the water source to the fluid inlet line using control valves that include one for each of the at least two concentrates and one the water source, and the water source having a pump, the at least two concentrates containers connecting to a common line having a concentrate pump.

(392) In variations thereof, the seventeenth embodiments include ones that include a controller programmed to control the connection platform controls valves to connect the at least two multi-treatment concentrate containers sequentially to the fluid inlet line to fill the at least two multi-treatment concentrate containers with concentrate. In variations thereof, the seventeenth embodiments include ones in which the controller controls the connection platform water pump to convey water to the mixing container through the fluid inlet line. In variations thereof, the seventeenth embodiments include ones that include a controller programmed to control the connection platform control valves and the concentrate pump to connect the at least two multi-treatment concentrate containers sequentially to the fluid inlet line to fill the first and second single-treatment concentrate containers with concentrate. In variations thereof, the seventeenth embodiments include ones in which the controller controls the connection platform water pump to convey water to the mixing container through the fluid inlet line. In variations thereof, the seventeenth embodiments include ones that include a controller programmed to control the connection platform control valves and the concentrate pump to connect the at least two multi-treatment concentrate containers sequentially to the fluid inlet line to fill the first and second single-treatment concentrate containers with concentrate and to control the connection platform control valves and the connection platform water pump to fill the mixing container with water.

(393) According to eighteenth embodiments, the disclosed subject matter includes system for performing peritoneal dialysis. A peritoneal dialysis cyler has a fluid circuit with a fluid inlet, a mixing container, and at least two concentrate containers. The peritoneal dialysis cyler has actuators to pump and direct concentrate and water selectively through the fluid circuit to transfer concentrate from an external source, through the fluid inlet, to the at least two concentrate containers, to transfer water through the fluid inlet to the mixing container, and to transfer concentrate from the at least two concentrate containers to the mixing container to form dialysis fluid. The peritoneal dialysis cyler actuators also transferring dialysis fluid to a patient line.

(394) In variations thereof, the eighteenth embodiments include ones in which the at least two concentrate containers are empty. **203.** In variations thereof, the eighteenth embodiments include ones that include a programmable controller that controls the actuators. In variations thereof, the eighteenth embodiments include ones in which the actuators include pumping and valve actuators. In variations thereof, the eighteenth embodiments include ones in which the fluid circuit includes valve segments that are pinched by the valve actuators. In variations thereof, the eighteenth embodiments include ones in which the fluid inlet has an inline sterilizing filter. In variations

thereof, the eighteenth embodiments include ones in which the inline sterilizing filter includes two filters or a single testable filter having an air line for applying air pressure to a membrane thereof. In variations thereof, the eighteenth embodiments include ones that include a fluid source module with input connections for concentrate and water and an outlet connection connectable to the fluid inlet. In variations thereof, the eighteenth embodiments include ones in which the fluid source module has actuators that sequentially connect concentrate and water to the outlet connection. In variations thereof, the eighteenth embodiments include ones in which the peritoneal dialysis cyler controls the fluid source module actuators. In variations thereof, the eighteenth embodiments include ones in which the fluid source module actuators include valve and pump actuators. In variations thereof, the eighteenth embodiments include ones in which the fluid source pump actuators include a water pump that pumps water through a filter system to generate purified water flowing through a purified water supply line connected to the outlet connection and the fluid source module valve actuators include a water valve actuator that selectively closes and opens the purified water supply line. In variations thereof, the eighteenth embodiments include ones in which the fluid source pump actuators include a concentrate pump that pumps concentrate from concentrate containers connected through respective concentrate feed lines to a common concentrate line that connect to the outlet connection, the fluid source module valve actuators including concentrate valve actuators that selectively close and open the respective concentrate feed lines. In variations thereof, the eighteenth embodiments include ones in which the peritoneal dialysis cyler has a programmable controller that controls the peritoneal dialysis cyler actuators.

(395) In variations thereof, the eighteenth embodiments include ones in which the fluid source module pump actuators include a water pump, controlled by the programmable controller, that pumps water through a filter system to generate purified water flowing through a purified water supply line connected to the outlet connection and the fluid source module valve actuators include a water valve actuator that selectively closes and opens the purified water supply line under control of the programmable controller. In variations thereof, the eighteenth embodiments include ones in which the fluid source module pump actuators include a concentrate pump, controlled by the programmable controller, that pumps concentrate from concentrate containers connected through respective concentrate feed lines to a common concentrate line that connect to the outlet connection, the fluid source module valve actuators including concentrate valve actuators that selectively close and open the respective concentrate feed lines under the control of the programmable controller.

(396) In variations thereof, the eighteenth embodiments include ones in which the fluid source module pump actuators include a concentrate pump, controlled by the programmable controller, that pumps concentrate from concentrate containers connected through respective concentrate feed lines to a common concentrate line that connect to the outlet connection, the fluid source module valve actuators including concentrate valve actuators that selectively close and open the respective concentrate feed lines under the control of the programmable controller and wherein the fluid source pump actuators include a water pump, controlled by the programmable controller, that pumps water through a filter system to generate purified water flowing through a purified water supply line connected to the outlet connection and the fluid source module valve actuators include a water valve actuator that selectively closes and opens the purified water supply line under the control of the programmable controller.

(397) According to nineteenth embodiments, the disclosed subject matter includes fluid system for peritoneal dialysis and dialysis solution preparation. A pre-connected fluid circuit has a disposable mixing container of polymeric material, an empty concentrate container of polymeric material, a fluid multiplexer that includes a valve network that has junctions and valve portions that mechanically interface with valve actuators to define selectable flow paths in the valve network. The valve network further includes a concentrate line connected to the concentrate container, a fluid inlet line terminated by a fluid inlet line connector, and a pair of lines connected to the mixing

container to permit simultaneous flow into, and flow out from, the mixing container. The fluid circuit is preconnected and sealed as a unit to isolate an internal volume thereof from an external environment to preserve sterility. An actuator device has valve actuators, sensors, and a pumping actuator. The fluid circuit has sensor and pumping portions that engage, respectively, along with the valve portions, with effectors of the actuator device.

(398) In variations thereof, the nineteenth embodiments include ones in which the fluid inlet line has an inline sterilizing filter with an air line attached thereto, the air line being connected such that air forced through the air line applies pressure to a membrane of the inline sterilizing filter to permit an integrity test thereof. In variations thereof, the nineteenth embodiments include ones in which the fluid inlet line has respective sterilizing filters serially-connected sterilizing filter elements. In variations thereof, the nineteenth embodiments include ones in which the valve network is positioned and held in a cartridge that has a pumping portion supported by a rigid manifold member, the manifold member being hollow and defining at least some of the junctions and the air line connecting to a port fixedly attached to the manifold member. In variations thereof, the nineteenth embodiments include ones in which the valve network is in a cartridge with the pumping portion held by a rigid manifold member thereof, the manifold member being hollow and defining at least some of the junctions. In variations thereof, the nineteenth embodiments include ones in which the air line connects to a port fixedly attached to the manifold member. In variations thereof, the nineteenth embodiments include ones in which the manifold member is rigid and has two separate chambers connected by the pumping portion.

(399) In variations thereof, the nineteenth embodiments include ones in which the valve network is supported by a panel providing support for the cartridge, the manifold member being connected to the panel. In variations thereof, the nineteenth embodiments include ones in which the valve network is supported by a panel, the manifold member being spaced apart from the panel. In variations thereof, the nineteenth embodiments include ones in which at least one of the two separate chambers has pressure sensors integrated therein, one at each end of the pumping portion. In variations thereof, the nineteenth embodiments include ones in which the pressure sensor includes a pressure pod with a diaphragm that serves as a portion of a wall of a respective one of the two separate chambers. In variations thereof, the nineteenth embodiments include ones in which the respective concentrate line connectors are connected by a frame that support a portion of the concentrate line. In variations thereof, the nineteenth embodiments include ones in which frame has a window and the portion of the concentrate line passes across the window. In variations thereof, the nineteenth embodiments include ones in which valve network has a drain line. In variations thereof, the nineteenth embodiments include ones in which valve network has a dialysis solution fill/drain line connectable to a peritoneal catheter. In variations thereof, the nineteenth embodiments include ones in which fill/drain line is sealed by a removable end cap. In variations thereof, the nineteenth embodiments include ones in which the dialysis solution fill/drain line has a second air line collinear with the dialysis solution fill/drain line, connected at an end of the dialysis solution fill/drain line to a pressure pod connected to the dialysis solution fill/drain line to measure a pressure therewithin. In variations thereof, the nineteenth embodiments include ones in which drain and fluid inlet lines are connected by a frame that support portions of the drain and fluid inlet lines. In variations thereof, the nineteenth embodiments include ones in which frame has a window and portions of the drain and fluid inlet lines pass across the window. In variations thereof, the nineteenth embodiments include ones in which the valve portions are supported by a planar element. In variations thereof, the nineteenth embodiments include ones in which planar element includes a pair of sheets shaped to hold the valve portions in predefined positions. In variations thereof, the nineteenth embodiments include ones in which the planar element includes a pair of sheets shaped to hold the valve portions in predefined positions, at least one of the pair of sheets having holes in it to permit valve actuators to contact the valve portions. In variations thereof, the nineteenth embodiments include ones in which the valve portions are tube segments. In variations

thereof, the nineteenth embodiments include ones in which the valve portions are tube segments. In variations thereof, the nineteenth embodiments include ones in which the concentrate line is sealed by a frangible seal. In variations thereof, the nineteenth embodiments include ones in which the mixing container and concentrate container are defined by two bonded flexible panels along seams to define the mixing container and concentrate container. In variations thereof, the nineteenth embodiments include ones in which the seams are a result of thermal welding. In variations thereof, the nineteenth embodiments include ones in which the fluid circuit encloses a sterile internal volume. In variations thereof, the nineteenth embodiments include ones in which the actuator device includes a peritoneal dialysis cyclor.

(400) According to twentieth embodiments, the disclosed subject matter includes a system for administering a peritoneal dialysis treatment. A peritoneal dialysis system component is connectable to one or more long-term containers of dialysis fluid concentrate and a water source. A disposable fluid circuit has a pumping portion, a mixing container, and one or more short-term concentrate containers. Pumping and valve actuators are controlled by a controller, which controls them to engage the disposable fluid circuit to create a mixed batch of peritoneal dialysis fluid by transferring sufficient concentrate for multiple cycles of a single treatment from the one or more long-term containers of dialysis fluid concentrate to the one or more short-term concentrate containers and, for each cycle of a treatment, transferring sufficient concentrate for a fill cycle from the one or more short-term concentrate containers to the mixing container and transferring sufficient water to form a ready-to-use dialysate to the mixing container from the water source.

(401) In variations thereof, the twentieth embodiments include ones in which the mixing container and the short-term concentrate containers are polymeric bags. In variations thereof, the twentieth embodiments include ones in which the pumping and valve actuators are controlled to perform a fill cycle of an automated peritoneal dialysis treatment using the contents of the mixing container. In variations thereof, the twentieth embodiments include ones that include at least one conductivity sensor connected to a drain line of the fluid circuit, wherein the pumping and valve actuators are controlled to sample contents of the mixing container to obtain a conductivity measurement thereof.

(402) According to twenty-first embodiments, the disclosed subject matter includes a fluid circuit for peritoneal dialysis and dialysis solution preparation. A pre-connected fluid circuit has a disposable mixing container of polymeric material, a concentrate container of polymeric material, a fluid multiplexer that includes a valve network that has junctions and valve portions that mechanically interface with valve actuators to define selectable flow paths in the valve network. The valve network further includes a concentrate line connected to the concentrate container, a fluid inlet line terminated by a fluid inlet line connector, and a pair of lines connected to the mixing container to permit simultaneous flow into, and flow out from, the mixing container. The fluid inlet line has an inline sterilizing filter. The valve network is positioned and held in a cartridge that has a pumping portion supported by a manifold member, the manifold member being hollow and defining at least some of the junctions. The fluid circuit is preconnected and sealed as a unit to isolate an internal volume thereof from an external environment to preserve sterility.

(403) In variations thereof, the twenty-first embodiments include ones in which the manifold member is rigid and defines two separate chambers connected by the pumping portion. In variations thereof, the twenty-first embodiments include ones in which fluid inlet line has an air line that is collinear with the fluid inlet line and connects to the inline sterilizing filter. In variations thereof, the twenty-first embodiments include ones in which the valve network is supported by a panel, the manifold member being connected to the panel. In variations thereof, the twenty-first embodiments include ones in which the valve network is supported by a panel, the manifold member being spaced apart from the panel. In variations thereof, the twenty-first embodiments include ones in which the manifold has pressure sensors integrated therein, one at each end of a pumping tube segment. In variations thereof, the twenty-first embodiments include ones in which

the pumping tube segment is straight. In variations thereof, the twenty-first embodiments include ones in which the pressure sensors include a pressure pod with a diaphragm that serves as a portion of a wall of a respective one of the two separate chambers. In variations thereof, the twenty-first embodiments include ones in which the valve network has a drain line. In variations thereof, the twenty-first embodiments include ones in which the drain and fluid lines are connected by a frame that support portions of the drain and fluid lines. In variations thereof, the twenty-first embodiments include ones in which the frame has a window and the portion of the drain and fluid lines passes across the window. In variations thereof, the twenty-first embodiments include ones in which the valve network has a dialysis solution fill/drain line connectable to a peritoneal catheter. In variations thereof, the twenty-first embodiments include ones in which the fill/drain line is sealed by a removable end cap. In variations thereof, the twenty-first embodiments include ones in which the valve network has a dialysis solution fill/drain line connectable to a peritoneal catheter and the dialysis solution fill/drain line has a second air line collinear with the dialysis solution fill/drain line, connected at an end of the dialysis solution fill/drain line to a pressure pod connected to the dialysis solution fill/drain line to measure a pressure therewithin. In variations thereof, the twenty-first embodiments include ones in which the drain and fluid inlet lines are connected by a frame that support portions of the drain and fluid inlet lines. In variations thereof, the twenty-first embodiments include ones in which the frame has a window and portions of the drain and fluid inlet lines pass across the window. In variations thereof, the twenty-first embodiments include ones in which the valve portions are supported by a planar element. In variations thereof, the twenty-first embodiments include ones in which the planar element includes a pair of sheets shaped to hold the valve portions in predefined positions. In variations thereof, the twenty-first embodiments include ones in which the planar element includes a pair of sheets shaped to hold the valve portions in predefined positions, at least one of the pair of sheets having holes in it to permit valve actuators to contact the valve portions. In variations thereof, the twenty-first embodiments include ones in which the valve portions are tube segments. In variations thereof, the twenty-first embodiments include ones in which the valve portions are tube segments. In variations thereof, the twenty-first embodiments include ones in which the mixing container and concentrate container are defined by two bonded flexible panels along seams to define the mixing container and concentrate container. In variations thereof, the twenty-first embodiments include ones in which the seams are a result of thermal welding. In variations thereof, the twenty-first embodiments include ones in which the fluid circuit encloses a sterile internal volume.

(404) According to twenty-second embodiments, the disclosed subject matter includes a fluid circuit for peritoneal dialysis and dialysate preparation. A disposable mixing container of polymeric material has a pre-attached fluid circuit, the mixing container and fluid circuit being sealed from an external environment. A concentrate container of polymeric material is pre-attached to the fluid circuit, the concentrate container being sealed from an external environment. The fluid circuit includes a fluid multiplexer that includes a valve network that has junctions and valve portions that mechanically interface with valve actuators to define selectable flow paths in the valve network. The valve network further including a concentrate line connected to the concentrate container, a water line terminated by a water line connector, and a at least one mixing container line connected to the mixing container to permit simultaneous flow into, and flow out from, the mixing container. The water line has an inline sterilizing filter. The valve network is positioned and held in a cartridge that has a pumping portion supported by a manifold member, the manifold member being hollow and defining at least some of the junctions. The manifold member defines two separate chambers connected by a pumping tube segment.

(405) In variations thereof, the twenty-second embodiments include ones in which the water line has an air line attached thereto, the air line being connected such that air forced through the air line applies pressure to a membrane of the inline sterilizing filter to permit an integrity test thereof. In variations thereof, the twenty-second embodiments include ones in which the valve network is

supported by a panel, the manifold member being connected to the panel. In variations thereof, the twenty-second embodiments include ones in which the valve network is supported by a panel, the manifold member being spaced apart from the panel. In variations thereof, the twenty-second embodiments include ones in which the air line is integral with at least a portion of a respective one of the concentrate and water lines. In variations thereof, the twenty-second embodiments include ones in which the manifold has pressure sensors integrated therein, one at each end of the pumping portion. In variations thereof, the twenty-second embodiments include ones in which the pumping portion is straight. In variations thereof, the twenty-second embodiments include ones in which the pressure sensor includes a pressure pod with a diaphragm that serves as a portion of a wall of a respective one of the two separate chambers. In variations thereof, the twenty-second embodiments include ones in which the valve network has a drain line and the respective water and drain lines are connected by a frame that support portions thereof. In variations thereof, the twenty-second embodiments include ones in which the frame has a window and the portions pass across the window. In variations thereof, the twenty-second embodiments include ones in which the valve network has a drain line. In variations thereof, the twenty-second embodiments include ones in which the valve network has a dialysate fill/drain line connectable to a peritoneal catheter. In variations thereof, the twenty-second embodiments include ones in which the fill/drain line is sealed by a removable end cap. In variations thereof, the twenty-second embodiments include ones in which the valve network has a dialysate fill/drain line connectable to a peritoneal catheter and wherein the dialysate fill/drain line has a second air line collinear with the dialysate fill/drain line, connected at an end of the dialysate fill/drain line to a pressure pod connected to the dialysate fill/drain line to measure a pressure therewithin. In variations thereof, the twenty-second embodiments include ones in which the drain and water lines are connected by a frame that support portions of the drain and water lines. In variations thereof, the twenty-second embodiments include ones in which the frame has a window and portions of the drain and water lines pass across the window. In variations thereof, the twenty-second embodiments include ones in which the valve portions are supported by a planar element. In variations thereof, the twenty-second embodiments include ones in which the planar element includes a pair of sheets shaped to hold the valve portions in predefined positions. In variations thereof, the twenty-second embodiments include ones in which the planar element includes a pair of sheets shaped to hold the valve portions in predefined positions, at least one of the pair of sheets having holes in it to permit valve actuators to contact the valve portions.

(406) In variations thereof, the twenty-second embodiments include ones in which the valve portions are tube segments. In variations thereof, the twenty-second embodiments include ones in which the valve portions are tube segments. In variations thereof, the twenty-second embodiments include ones in which the concentrate line is sealed by a frangible seal. In variations thereof, the twenty-second embodiments include ones in which the cartridge includes parallel panels with the valve network sandwiched between them, the frangible seal held in the cartridge aligned with windows in at least one of the panels to permit an actuator to fracture them prior to use thereby allowing the concentrate to flow through the concentrate line. In variations thereof, the twenty-second embodiments include ones in which the cartridge includes a single folded panel forming parallel panel portions with the valve network sandwiched between them, the frangible seal being held in the cartridge aligned with windows in at least one of the panels to permit an actuator to fracture them prior to use thereby allowing the concentrate to flow through the concentrate line. In variations thereof, the twenty-second embodiments include ones in which the valve network includes the concentrate line which is sealed by a frangible seal thereby separating the concentrate from the rest of the fluid circuit until the frangible seal is fractured. In variations thereof, the twenty-second embodiments include ones that include a second sterilizing filter connected in series with the inline sterilizing filter such that the second and inline sterilizing filters are separated by a flow channel to prevent grow-through contamination between membranes thereof. In variations

thereof, the twenty-second embodiments include ones in which the mixing container and concentrate container are defined by two bonded flexible panels along seams to define the mixing container and concentrate container. In variations thereof, the twenty-second embodiments include ones in which seams are a result of thermal welding. In variations thereof, the twenty-second embodiments include ones in which the fluid circuit encloses a sterile internal volume.

(407) According to twenty-third embodiments, the disclosed subject matter includes a fluid system for peritoneal dialysis and dialysate preparation. A disposable mixing container of polymeric material has a pre-attached fluid circuit, the mixing container and fluid circuit being sealed from an external environment. A concentrate container of polymeric material is pre-attached to the fluid circuit, the concentrate container being sealed from an external environment. The fluid circuit includes a fluid multiplexer that includes a valve network that has junctions and valve portions that mechanically interface with valve actuators to define selectable flow paths in the valve network. The valve network further includes a concentrate line connected to the concentrate container, a water line terminated by a water line connector, and a pair of lines connected to the mixing container to permit simultaneous flow into, and flow out from, the mixing container. The water line has an inline sterilizing filter with an air line attached thereto, the air line being connected such that air forced through the air line applies pressure to a membrane of the inline sterilizing filter to permit an integrity test thereof. An actuator device has valve actuators, sensors, and a pumping actuator. The fluid circuit has sensor and pumping portions that engage, respectively, along with the valve portions, with effectors of the actuator device.

(408) In variations thereof, the twenty-third embodiments include ones in which the valve network is in a cartridge with the pumping portion held by a rigid manifold member thereof, the manifold member being hollow and defining at least some of the junctions. In variations thereof, the twenty-third embodiments include ones in which the air line connects to a port fixedly attached to the manifold member. In variations thereof, the twenty-third embodiments include ones in which the manifold member is rigid and has two separate chambers connected by the pumping portion. In variations thereof, the twenty-third embodiments include ones in which the valve network is supported by a panel providing support for the cartridge, the manifold member being connected to the panel. In variations thereof, the twenty-third embodiments include ones in which the valve network is supported by a panel, the manifold member being spaced apart from the panel. In variations thereof, the twenty-third embodiments include ones in which the manifold has pressure sensors integrated therein, one at each end of the pumping portion. In variations thereof, the twenty-third embodiments include ones in which pressure sensor includes a pressure pod with a diaphragm that serves as a portion of a wall of a respective one of the two separate chambers. In variations thereof, the twenty-third embodiments include ones in which respective concentrate line connectors are connected by a frame that support a portion of the concentrate line. In variations thereof, the twenty-third embodiments include ones in which frame has a window and the portion of the concentrate line passes across the window. In variations thereof, the twenty-third embodiments include ones in which valve network has a drain line.

(409) In variations thereof, the twenty-third embodiments include ones in which valve network has a dialysate fill/drain line connectable to a peritoneal catheter. In variations thereof, the twenty-third embodiments include ones in which fill/drain line is sealed by a removable end cap. In variations thereof, the twenty-third embodiments include ones in which dialysate fill/drain line has a second air line collinear with the dialysate fill/drain line, connected at an end of the dialysate fill/drain line to a pressure pod connected to the dialysate fill/drain line to measure a pressure therewithin. In variations thereof, the twenty-third embodiments include ones in which drain and water lines connected by a frame that support portions of the drain and water lines. In variations thereof, the twenty-third embodiments include ones in which In variations thereof, the twenty-third embodiments include ones in which frame has a window and portions of the drain and water lines pass across the window. In variations thereof, the twenty-third embodiments include ones in which

the valve portions are supported by a planar element. In variations thereof, the twenty-third embodiments include ones in which the planar element includes a pair of sheets shaped to hold the valve portions in predefined positions. In variations thereof, the twenty-third embodiments include ones in which planar element includes a pair of sheets shaped to hold the valve portions in predefined positions, at least one of the pair of sheets having holes in it to permit valve actuators to contact the valve portions. In variations thereof, the twenty-third embodiments include ones in which the valve portions are tube segments. In variations thereof, the twenty-third embodiments include ones in which valve portions are tube segments. In variations thereof, the twenty-third embodiments include ones in which the concentrate line is sealed by a frangible seal. In variations thereof, the twenty-third embodiments include ones in which the cartridge includes parallel panels with the valve network sandwiched between them, the frangible seal held in the cartridge aligned with windows in at least one of the panels to permit an actuator to fracture them prior to use thereby allowing the concentrate to flow through the concentrate line. In variations thereof, the twenty-third embodiments include ones in which the cartridge includes a single folded panel forming parallel panel portions with the valve network sandwiched between them, the frangible seal being held in the cartridge aligned with windows in at least one of the panels to permit an actuator to fracture them prior to use thereby allowing the concentrate to flow through the concentrate line. In variations thereof, the twenty-third embodiments include ones in which the valve network includes the concentrate line which is sealed by a frangible seal thereby separating the concentrate from the rest of the fluid circuit until the frangible seal is fractured. In variations thereof, the twenty-third embodiments include ones that include a second sterilizing filter connected in series with the inline sterilizing filter such that the second and inline sterilizing filters are separated by a flow channel to prevent grow-through contamination between membranes thereof. In variations thereof, the twenty-third embodiments include ones in which the batch container and concentrate container are defined by two bonded flexible panels along seams to define the batch container and concentrate container. In variations thereof, the twenty-third embodiments include ones in which the seams are a result of thermal welding. In variations thereof, the twenty-third embodiments include ones in which the fluid circuit encloses a sterile internal volume. In variations thereof, the twenty-third embodiments include ones in which actuator device includes a peritoneal dialysis cyclor. In variations thereof, the twenty-third embodiments include ones in which the drain and water lines connected by a frame that support portions of the drain and water lines and the actuator device has a cut-and-seal device and a receiving slot that receives the frame and aligns a windows of the frame with the cut-and-seal device. In variations thereof, the twenty-third embodiments include ones in which the actuator device has a controller programmed to activate the cut-and-seal device to cut and seal the concentrate line thereby permitting the fluid circuit to be separated from the frame and a concentrate line connector as well as a stub portion of the concentrate line, which collectively remain in place on the actuator device to act as a seal on connectors of the actuator device.

(410) According to twenty-fourth embodiments, the disclosed subject matter includes a treatment method. The method includes using a peritoneal cyclor device with a fluid circuit having valve, container, and pumping portions, the peritoneal cyclor device having actuators and sensors controlled by a controller that interface with the valve and pumping portions for preparing peritoneal dialysis fluid, and under control of the controller: accessing a priming bolus comprising a first volume of a first fluid; priming at least a patient fill line with the priming bolus; preparing a treatment batch comprising a second volume of a second fluid, wherein the second volume is larger than the first volume; and performing at least one fill/drain cycle of a renal replacement therapy through the fluid circuit and using the treatment batch.

(411) In variations thereof, the twenty-fourth embodiments include ones in which the accessing a priming bolus and the preparing a treatment batch both include diluting and mixing at least one concentrate and the preparing the accessing a priming bolus takes less time than the preparing of

the treatment batch. In variations thereof, the twenty-fourth embodiments include ones that include, prior to the preparing a treatment batch, determining that a fluid circuit is connected to a patient and preventing the preparing a treatment batch until a fluid circuit is connected to a patient. In variations thereof, the twenty-fourth embodiments include ones in which the first fluid and the second fluid have a same composition according to a same prescription. In variations thereof, the twenty-fourth embodiments include ones in which first fluid and the second fluid have different compositions. In variations thereof, the twenty-fourth embodiments include ones in which first fluid is a non-prescription fluid. In variations thereof, the twenty-fourth embodiments include ones in which the first fluid is water or saline.

(412) In variations thereof, the twenty-fourth embodiments include ones that include receiving by the controller an indication through a user interface that quick priming is desired or determining whether a patient is full or empty and if not, skipping the accessing and the priming. In variations thereof, the twenty-fourth embodiments include ones in which the priming bolus and the treatment batch are stored in a same mixing container of the container portions. In variations thereof, the twenty-fourth embodiments include ones in which at least one of the priming bolus and the treatment batch is prepared by flowing purified water and a medicament concentrate to the mixing container to proportion and dilute the medicament concentrate. In variations thereof, the twenty-fourth embodiments include ones in which mixing container is disposable. In variations thereof, the twenty-fourth embodiments include ones in which fluid circuit is disposable and includes a pumping tube segment and multiple valve segments of the valve portions, wherein peritoneal cyclor device includes at least one pumping actuator positioned to engage the pumping tube segment, wherein the peritoneal cyclor device further includes multiple valve actuators positioned to engage the valve segments. In variations thereof, the twenty-fourth embodiments include ones in which the preparing of the priming bolus comprises drawing a concentrate and water through a sterilizing filter in predefined quantities to make the first volume of the first fluid. In variations thereof, the twenty-fourth embodiments include ones in which the preparing of the treatment batch comprises drawing a concentrate and water through a sterilizing filter in predefined quantities to make the second volume of the second fluid, wherein the second fluid is peritoneal dialysis fluid, wherein the second volume provides a sufficient quantity of peritoneal dialysis fluid for at least a single fill of a treatment cycle.

(413) In variations thereof, the twenty-fourth embodiments include ones in which the drawing includes, using an interconnection module, connecting water and concentrate at different times to a common inlet of the fluid circuit to which the sterilizing filter is integrally attached. In variations thereof, the twenty-fourth embodiments include ones that include testing the sterilizing filter by an air pressure test and using, or preventing use of, the quantity for a peritoneal dialysis fill and drain cycle depending on a result of the testing. In variations thereof, the twenty-fourth embodiments include ones that include connecting a long-term concentrate container to the interconnection module once every multiple peritoneal dialysis treatments. In variations thereof, the twenty-fourth embodiments include ones in which the fluid circuit, having a sterilizing filter integrally attached thereto, is connected to the interconnection module once every single peritoneal dialysis treatment.

(414) According to twenty-fifth embodiments, the disclosed subject matter includes a system for administering a peritoneal dialysis treatment. A peritoneal dialysis cyclor portion is connectable to a source of priming fluid. A controller, with a user interface, controls a fill/drain pump of the peritoneal dialysis cyclor portion. The controller requests input through the user interface indicating whether a patient is full or empty. In response to the controller receiving input through the user interface indicating the patient is empty, preparing a full batch of peritoneal dialysis fluid prior to beginning a treatment. In response to the controller receiving input through the user interface indicating the patient is full, initiating a quick prime mode prior to beginning a treatment. The quick prime mode including preparing or accessing a quick prime bolus and using it to prime a patient line.

(415) In variations thereof, the twenty-fifth embodiments include ones in which the quick prime bolus is of a different composition from a peritoneal dialysis fluid. In variations thereof, the twenty-fifth embodiments include ones in which the quick prime bolus is of water. In variations thereof, the twenty-fifth embodiments include ones that include, after the quick prime mode, using the controller, draining a patient. In variations thereof, the twenty-fifth embodiments include ones that include, in response to the controller receiving input through the user interface indicating the patient is empty, generating a command to prevent access by a user to the quick prime mode.

(416) According to twenty-sixth embodiments, the disclosed subject matter includes a treatment method that includes preparing a priming batch comprising a first volume of a first fluid and priming a patient fill/drain line with the priming batch. The method includes determining that a fluid circuit is connected to a patient. The method includes preparing a treatment batch comprising a second volume of a second fluid, wherein the second volume is larger than the first volume. The method includes performing at least one fill/drain cycle of a renal replacement therapy through the fluid circuit and using the treatment batch.

(417) In variations thereof, the twenty-sixth embodiments include ones in which the preparing of the priming batch takes less time than the preparing of the treatment batch. In variations thereof, the twenty-sixth embodiments include ones in which the first fluid and the second fluid have a same composition according to a same prescription. In variations thereof, the twenty-sixth embodiments include ones in which first fluid and the second fluid have different compositions. In variations thereof, the twenty-sixth embodiments include ones in which the first fluid is a non-prescription fluid. In variations thereof, the twenty-sixth embodiments include ones in which the first fluid is water or saline. In variations thereof, the twenty-sixth embodiments include ones in which the method is performed after receiving an indication from the patient to perform quick priming. In variations thereof, the twenty-sixth embodiments include ones in which the priming batch and the treatment batch are stored in a same mixing container. In variations thereof, the twenty-sixth embodiments include ones in which at least one of the priming batch and the treatment batch is prepared by flowing purified water and a medicament concentrate to the mixing container to proportion and dilute the medicament concentrate.

(418) In variations thereof, the twenty-sixth embodiments include ones in which the method is performed by a proportioning and treatment device having actuators that engage with the fluid circuit when received thereby. In variations thereof, the twenty-sixth embodiments include ones in which the mixing container is disposable. In variations thereof, the twenty-sixth embodiments include ones in which the fluid circuit is disposable and includes a pumping tube segment and multiple valve segments, wherein the proportioning and treatment device includes at least one pumping actuator positioned to engage the pumping tube segment, wherein the proportioning and treatment device further includes multiple valve actuators positioned to engage the valve segments. In variations thereof, the twenty-sixth embodiments include ones in which the preparing of the priming batch comprises drawing a concentrate and water through a sterilizing filter in predefined quantities to make the first volume of the first fluid. In variations thereof, the twenty-sixth embodiments include ones in which the preparing of the treatment batch comprises drawing a concentrate and water through a sterilizing filter in predefined quantities to make the second volume of the second fluid, wherein the second fluid is peritoneal dialysate, wherein the second volume provides a sufficient quantity of peritoneal dialysate for a single fill of a treatment cycle. In variations thereof, the twenty-sixth embodiments include ones in which the drawing includes, using an interconnection module, connecting water and concentrate at different times to a common inlet of the fluid circuit to which the sterilizing filter is integrally attached. In variations thereof, the twenty-sixth embodiments include ones that include testing the sterilizing filter by an air pressure test and using, or preventing use of, the quantity for a peritoneal dialysis fill and drain cycle depending on a result of the testing. In variations thereof, the twenty-sixth embodiments include ones that include connecting a long-term concentrate container to the interconnection

module once every multiple peritoneal dialysis treatments. In variations thereof, the twenty-sixth embodiments include ones in which the fluid circuit having the sterilizing filter integrally attached thereto is connected to the interconnection module once every single peritoneal dialysis treatment. (419) According to twenty-seventh embodiments, the disclosed subject matter includes a system for preparation of sterile medical treatment fluid with a disposable fluid circuit with a pumping tube segment and multiple valve segments. A proportioning and treatment device with a pumping actuator is shaped to engage the pumping tube segment and multiple valve actuators positioned to engage the valve segments. A first of the multiple valve segments is connected to a water inlet. A second of the multiple valve segments being connected to a first concentrate inlet. The disposable fluid circuit has a sterilizing filter connected between each of the water inlet and the first concentrate inlet and respective ones of the first and second of the multiple valve segments. A first concentrate container has sufficient concentrate for preparation of enough peritoneal dialysate to perform multiple peritoneal dialysis treatments, each treatment including multiple fill/drain cycles. The disposable fluid circuit has a first concentrate inlet connector for the first concentrate inlet which is adapted to be connected to the first concentrate container. The disposable fluid circuit having an integrally-attached mixing container sized to hold sufficient peritoneal dialysate for at least a single fill/drain cycle. The proportioning and treatment device has a programmable controller programmed to control the pumping actuator to pump concentrate and water into the mixing container to make a batch of peritoneal dialysate and subsequently to perform a fill/drain cycle including draining spent peritoneal dialysate and pumping a fill of the peritoneal dialysate from the mixing container.

(420) In variations thereof, the twenty-seventh embodiments include ones in which the disposable fluid circuit has a second concentrate inlet with a sterilizing filter connected between the second concentrate inlet and a third of the multiple valve segments. In variations thereof, the twenty-seventh embodiments include ones that include a second concentrate container having concentrate for the preparation of enough peritoneal dialysate to perform multiple peritoneal dialysis treatments each treatment including multiple fill/drain cycles, wherein the first and second concentrate inlets are connected to the first and second concentrate containers by a double connector that carries the first concentrate inlet connector and a second concentrate inlet connector of the disposable fluid circuit, the double connector making connections for the first concentrate inlet connector and the second concentrate inlet simultaneously to the first and second concentrate containers. In variations thereof, the twenty-seventh embodiments include ones that include an interconnection module that has a primary connector, to which the first concentrate container is connected once every multiple treatments, and a secondary connector to which the disposable fluid circuit first concentrate inlet connector is connected once every treatment. In variations thereof, the twenty-seventh embodiments include ones in which the water inlet has a sterilizing filter with an air port controller to allow a membrane of the sterilizing filter to be pressure tested such as by a bubble point test, the controller being programmed to test the sterilizing filter membrane by applying pressure to the air port controller and measuring the pressure after pumping water therethrough. In variations thereof, the twenty-seventh embodiments include ones in which the controller generates an alarm signal responsively to a result of a test of the sterilizing filter membrane if the test indicates a disintegration of the sterilizing filter membrane.

(421) According to twenty-eighth embodiments, the disclosed subject matter includes a fluid circuit for peritoneal dialysis and dialysate preparation. A disposable mixing container of polymeric material has a pre-attached fluid circuit, the mixing container and fluid circuit being sealed from an external environment. The fluid circuit includes a fluid multiplexer that has junctions and valve portions that mechanically interface with valve actuators to define selectable flow paths in the fluid circuit. The fluid circuit includes at least two concentrate lines terminated by respective concentrate line connectors, a water line terminated by a water line connector, and one or more lines connected to permit flow into and out of the mixing container. Each of the concentrate and water lines has a

testable inline sterilizing filter or a redundant serially-connected pair of sterilizing filters. The fluid circuit has a pumping portion.

(422) In variations thereof, the twenty-eighth embodiments include ones in which the testable inline sterilizing filters each have air lines that are each collinear with at least a portion of a respective one of the concentrate and water lines. In variations thereof, the twenty-eighth embodiments include ones in which the testable inline sterilizing filters each have air lines that are each integral with at least a portion of a respective one of the concentrate and water lines. In variations thereof, the twenty-eighth embodiments include ones that include a rigid manifold chamber with pressure sensors integrated therein, one at each end of a pumping tube segment of the pumping portion. In variations thereof, the twenty-eighth embodiments include ones in which the pumping tube segment is straight. In variations thereof, the twenty-eighth embodiments include ones in which the rigid manifold has two separate chambers and the pressure sensor includes a pressure pod with a diaphragm that serves as a portion of a wall of a respective one of the two separate chambers. In variations thereof, the twenty-eighth embodiments include ones in which the respective concentrate line connectors are connected by a frame that support portions of the concentrate lines. In variations thereof, the twenty-eighth embodiments include ones in which the frame has a window and the portions of the concentrate lines pass across the window. In variations thereof, the twenty-eighth embodiments include ones in which the fluid circuit has a drain line. In variations thereof, the twenty-eighth embodiments include ones in which the drain and water lines connected by a frame that support portions of the drain and water lines. In variations thereof, the twenty-eighth embodiments include ones in which the frame has a window and portions of the drain and water lines pass across the window. In variations thereof, the twenty-eighth embodiments include ones in which the valve portions are supported by a planar element. In variations thereof, the twenty-eighth embodiments include ones in which the planar element includes a pair of sheets shaped to hold the valve portions in predefined positions. In variations thereof, the twenty-eighth embodiments include ones in which the planar element includes a pair of sheets shaped to hold the valve portions in predefined positions, at least one of the pair of sheets having holes in it to permit valve actuators to contact the valve portions. In variations thereof, the twenty-eighth embodiments include ones in which the valve portions are tube segments. In variations thereof, the twenty-eighth embodiments include ones in which the valve portions are tube segments.

(423) In variations thereof, the twenty-eighth embodiments include ones in which the fluid circuit is held by a cartridge that includes parallel panels with the valve portions sandwiched between them, at least two frangible seals being held in the cartridge aligned with windows in at least one of the panels to permit an actuator to fracture them prior to use thereby allowing the concentrate to flow through the at least two concentrate lines.

(424) According to twenty-ninth embodiments, the disclosed subject matter includes a method of making a peritoneal dialysis fluid including drawing a concentrate and water through a sterilizing filter in predefined quantities and proportioning the concentrate and water to make a sufficient quantity of peritoneal dialysis fluid for at least a single fill of a peritoneal dialysis treatment. The drawing includes, using an interconnection module, connecting water and concentrate at different times to a common inlet of a disposable fluid circuit to which the sterilizing filter is integrally attached and testing the sterilizing filter by an air pressure test and using, or preventing use of, the quantity for a peritoneal dialysis fill and drain cycle depending on a result of the testing.

(425) In variations thereof, the twenty-ninth embodiments include ones in which connecting a long-term concentrate container to the interconnection module once every multiple peritoneal dialysis treatments. In variations thereof, the twenty-ninth embodiments include ones that include connecting a treatment circuit having the sterilizing filter integrally attached thereto, to the interconnection module once every single peritoneal dialysis treatments. In variations thereof, the twenty-ninth embodiments include ones that include mixing the water and the concentrate. In variations thereof, the twenty-ninth embodiments include ones in which the drawing and the

mixing are performed using a single common pump. In variations thereof, the twenty-ninth embodiments include ones in which the disposable fluid circuit has at least one concentrate container that is initially empty and the drawing a concentrate includes filling the at least one concentrate container with concentrate. In variations thereof, the twenty-ninth embodiments include ones in which the proportioning includes transferring concentrate from the at least one concentrate container to a mixing container. In variations thereof, the twenty-ninth embodiments include ones in which the proportioning includes transferring water through the common inlet to a mixing container. In variations thereof, the twenty-ninth embodiments include ones in which the proportioning includes transferring concentrate from the at least one concentrate container to a mixing container and transferring water through the common inlet to a mixing container.

(426) According to thirtieth embodiments, the disclosed subject matter includes a method of performing a peritoneal dialysis treatment including drawing a concentrate and water through a sterilizing filter in predefined quantities to make a sufficient quantity of peritoneal dialysate for a single fill of a peritoneal dialysis treatment. The drawing includes connecting water and concentrate at different times to a common inlet of a disposable fluid circuit to which the sterilizing filter is integrally attached.

(427) In variations thereof, the thirtieth embodiments include ones in which the sterilizing filters includes separate filter elements connected in series by a flow channel. In variations thereof, the thirtieth embodiments include ones that include testing the sterilizing filter by an air pressure test and using, or preventing use of, the quantity for a peritoneal dialysis fill and drain cycle depending on a result of the testing. In variations thereof, the thirtieth embodiments include ones that include connecting a long term concentrate container to an interconnection module once every multiple peritoneal dialysis treatments. In variations thereof, the thirtieth embodiments include ones that include connecting a treatment circuit having the sterilizing filter integrally attached thereto, to the interconnection module once every single peritoneal dialysis treatments. In variations thereof, the thirtieth embodiments include ones that include mixing the water and the concentrate. In variations thereof, the thirtieth embodiments include ones in which the drawing and the mixing are performed using a single common pump.

(428) According to thirty-first embodiments, the disclosed subject matter includes a method of performing a peritoneal dialysis treatment including drawing a concentrate and water through respective sterilizing filters in predefined quantities to make a sufficient quantity of peritoneal dialysate for a single fill of a peritoneal dialysis treatment. The drawing includes, using an interconnection module, flowing water and concentrate in succession to a mixing container the flowing water and concentrate in succession including switching flow paths in a peritoneal dialysis cyclor. The method includes ensuring an integrity of the respective sterilizing filters by testing them or providing the respective sterilizing filters as serially-connected redundant sterilizing filter elements.

(429) In variations thereof, the thirty-first embodiments include ones that include connecting a long term concentrate container to the interconnection module once every multiple peritoneal dialysis treatments. In variations thereof, the thirty-first embodiments include ones that include connecting a treatment circuit having the respective sterilizing filters integrally attached thereto, to the interconnection module once every single peritoneal dialysis treatments. In variations thereof, the thirty-first embodiments include ones that include mixing the water and the concentrate. In variations thereof, the thirty-first embodiments include ones in which the drawing and the mixing are performed using a single common pump. In variations thereof, the thirty-first embodiments include ones in which the connecting a treatment circuit includes removing at least one sterile seal from water and concentrate connectors and connecting one or more new connectors of the treatment circuit to water and concentrate connectors and wherein following the using the quantity, cutting one or more portions of the one or more new connectors to create at least one new sterile seal. In variations thereof, the thirty-first embodiments include ones in which the interconnection

module supports a connector of the concentrate container, the connecting a long term concentrate connector including replacing the connector of the concentrate container and the connecting a treatment circuit includes connecting the treatment circuit to the connector of the concentrate container. In variations thereof, the thirty-first embodiments include ones in which the flowing water and concentrate in succession using the interconnection module includes washing a fixed volume of concentrate from a common outlet of the interconnection module and an inlet of a disposable fluid circuit, the method further comprising, using a controller used to make the sufficient quantity, calculating an amount of the fixed volume and controlling an amount of water pumped to form the sufficient quantity responsively to a result of the calculating.

(430) According to thirty-second embodiments, the disclosed subject matter includes a system for preparation of sterile medical treatment fluid. A disposable fluid circuit has a pumping tube segment and multiple valve segments. A proportioning and treatment device has at least one pumping actuator positioned to engage the at least one pumping tube segment and multiple valve actuators positioned to engage the multiple valve segments. A first of the multiple valve segments is connected to a fluid inlet. The disposable fluid circuit has a sterilizing filter connected between a fluid inlet connector and the first of the multiple valve segments. A first concentrate container has sufficient concentrate for preparation of enough peritoneal dialysate to perform multiple peritoneal dialysis treatments, each treatment including multiple fill/drain cycles. The disposable fluid circuit having an integrally-attached mixing container sized to hold sufficient peritoneal dialysate for at least a single fill/drain cycle. An interconnection module has a primary concentrate connector and a primary water connector, to which the first concentrate container is connected once every multiple treatments. The interconnection module also has a common secondary connector to which the disposable fluid circuit fluid inlet connector is connected once every treatment. The interconnection module has a valve network controlled by a programmable controller that selects water or concentrate to flow through the common secondary connector. The proportioning and treatment device has a programmable controller programmed to control the at least one pumping actuator to pump concentrate and water into the mixing container to make a batch of peritoneal dialysate and subsequently to perform a fill/drain cycle including draining spent peritoneal dialysate and pumping a fill of the peritoneal dialysate from the mixing container.

(431) In variations thereof, the thirty-third embodiments include ones that include a controller, the controller being programmed to calculate and store data representing a volume of water or concentrate remaining in a portion of the valve network after selecting water or concentrate to be drawn by the proportioning and treatment device and to control the pump responsively to the data representing a volume of water or concentrate.

(432) According to thirty-fourth embodiments, the disclosed subject matter includes a method of making a fluid circuit having a chamber prefilled with medicament concentrate. The method includes integrally connecting a fluid circuit with a chamber and connecting a sterilizing filter with the chamber. The integrally connecting and connecting a sterilizing filter forms an assembly with a sealed volume that is separated from an outside environment by walls thereof, a frangible plug in a concentrate outlet line stemming from the chamber, and a membrane of the sterilizing filter. The method includes sterilizing the assembly. The method includes sterile-filling the chamber with concentrate through the sterilizing filter. The method includes permanently sealing and then cutting a line connecting the sterilizing filter and the chamber and subjecting the fluid circuit and chamber to gamma or e-beam sterilization.

(433) According to thirty-fifth embodiments, the disclosed subject matter includes a method of making a fluid circuit having a chamber prefilled with medicament concentrate. The method includes integrally connecting a fluid circuit with a chamber. The method includes connecting a sterilizing filter with the chamber. The integrally connecting and connecting a sterilizing filter form an assembly with a sealed volume that is separated from an outside environment by walls thereof, a frangible plug in a concentrate outlet line stemming from the chamber, and a membrane of the

sterilizing filter. The method includes sterilizing the assembly. The method includes sterile-filling the chamber with concentrate through the sterilizing filter. The method includes heat welding and cutting a line connecting the sterilizing filter and the chamber and subjecting the fluid circuit and chamber to gamma or e-beam sterilization.

(434) According to thirty-fifth embodiments, the disclosed subject matter includes a fluid line connector with at least one thermoplastic tube supported in a frame such that the at least one thermoplastic tube is accessible from opposite sides of the frame. The frame has an overhanging ridge at one end and at least one connector that is fluidly coupled at an opposite end to the at least one thermoplastic tube. A cap is fitted to the frame to cover the at least one connector. The at least one tube extends through holes in the frame at an end thereof adjacent the overhanging ridge.

(435) In variations thereof, the thirty-fifth embodiments include ones in which the frame has a recess shaped to engage a détente pin along an elongate side thereof. In variations thereof, the thirty-fifth embodiments include ones in which the frame has an oval-shaped recess, the at least one connector being located within the oval-shaped recess. In variations thereof, the thirty-fifth embodiments include ones in which the cap fits in the oval-shaped recess to define a tortuous path between the at least one connector and an access of the oval-shaped recess. In variations thereof, the thirty-fifth embodiments include ones in which at least one connector and the at least one thermoplastic tubes are at least two.

(436) According to thirty-sixth embodiments, the disclosed subject matter includes a connector system. A connector component has at least one thermoplastic tube supported in a frame such that the at least one thermoplastic tube is accessible from opposite sides of the frame. The frame has an overhanging ridge at one end and at least one connector that is fluidly coupled at an opposite end to the at least one thermoplastic tube. A cap is fitted to the frame to cover the at least one connector. The at least one tube extends through holes in the frame at an end thereof adjacent the overhanging ridge. A fluid supply device has at least one supply connector that mates with the at least one connector, the fluid supply device having a portion shaped to engage the frame to align the at least one thermoplastic tube with a tube cut-and-seal device.

(437) In variations thereof, the thirty-sixth embodiments include ones in which the cut-and-seal device cuts the at least one thermoplastic tube and seals it at both ends, the connector component being configured to permit the at least one thermoplastic tube to be withdrawn from the one end leaving the frame and at least one connector in place on the at least one supply connector to cover and protect it from contamination until it is replaced by another connector component. In variations thereof, the thirty-sixth embodiments include ones in which the frame has a recess shaped to engage a détente pin along an elongate side thereof. In variations thereof, the thirty-sixth embodiments include ones in which the frame has an oval-shaped recess, the at least one connector being located within the oval-shaped recess. In variations thereof, the thirty-sixth embodiments include ones in which the cap fits in the oval-shaped recess to define a tortuous path between the at least one connector and an access of the oval-shaped recess. In variations thereof, the thirty-sixth embodiments include ones in which at least one connector and the at least one thermoplastic tubes are at least two. In variations thereof, the thirty-sixth embodiments include ones in which the frame has a recess shaped to engage a détente pin along an elongate side thereof. In variations thereof, the thirty-sixth embodiments include ones in which the frame has an oval-shaped recess, the at least one connector being located within the oval-shaped recess.

(438) In variations thereof, the thirty-sixth embodiments include ones in which the cap fits in the oval-shaped recess to define a tortuous path between the at least one connector and an access of the oval-shaped recess. In variations thereof, the thirty-sixth embodiments include ones in which at least one connector and the at least one thermoplastic tubes are at least two.

(439) According to thirty-seventh embodiments, the disclosed subject matter includes a fluid proportioning system with first and second manifolds connected by a pump. A port on the first manifold is provided for connection of a last-fill medicament and/or an auxiliary fluid. A controller

is programmed to control the pump to draw, according to a command generated by the controller, a last fill or an auxiliary fluid.

(440) In variations thereof, the thirty-seventh embodiments include ones that include a mixing container, the controller being programmed to transfer the auxiliary fluid to the mixing container and to use contents thereof to fill a peritoneum. In variations thereof, the thirty-seventh embodiments include ones in which the controller fills the mixing container with a fill of peritoneal dialysate prior to controlling the pump to draw a last fill or an auxiliary fluid. In variations thereof, the thirty-seventh embodiments include ones in which the controller is programmed to use contents of the mixing container to perform a peritoneal dialysis treatment.

(441) According to thirty-eighth embodiments, the disclosed subject matter includes a method of mixing a medicament, the method including using a controller, combining respective quantities of water and liquid first medicament concentrate in a first target concentration calculated by the controller responsively to a map of allowed and disallowed ratios and a final prescribed concentration of the first medicament to generate an initial mixture. The method includes using the controller, testing the concentration of the initial mixture including measuring a conductivity of thereof. The method includes using the controller, responsively to the testing, diluting the initial mixture to a second target concentration of first medicament and further testing the concentration of a resulting second mixture including measuring a conductivity thereof.

(442) In variations thereof, the thirty-eighth embodiments include ones that include, using the controller, adding a second medicament concentrate to the second mixture.

(443) In variations thereof, the thirty-eighth embodiments include ones in which the first target is based on an optimization of total pumping time to minimize the time it to prepare a completed mixed batch of medicament.

(444) According to thirty-ninth embodiments, the disclosed subject matter includes a system for making a peritoneal dialysis fluid. The system includes a peritoneal dialysis system component connectable to first and second containers of first and second concentrates and a water source and a disposable fluid circuit with a pumping portion and a mixing container. The system includes pumping and valve actuators controlled by a controller, which controls them to engage the disposable fluid circuit to create a predefined mixture of water, a first concentrate, and a second concentrate to form a ready-to-use peritoneal dialysate by: (a) pumping a first quantity of water into the mixing container; (b) pumping an amount of the first concentrate into the mixing container estimated to achieve a target conductivity of contents of the mixing container; (c) testing a conductivity of the mixing container contents and, responsively to a result of the testing, adjusting a target amount of water and a target amount of a second concentrate to add to the mixing container if a result of the testing indicates a conductivity above the target conductivity; (d) outputting an indication of a failed in-process mixture if the conductivity is below the target conductivity; (e) adding an adjusted target amount of water and an adjusted target amount of second concentrate to the mixing container; and (f) testing a conductivity of contents of the mixing container and depending on a result of the testing, outputting an indication of a successful or failed in-process mixture.

(445) In variations thereof, the thirty-ninth embodiments include ones in which, after the adding an adjusted target amount of water, testing a conductivity of the contents of the mixing container and adding a further amount of water if a conductivity resulting from the testing is higher than a target. In variations thereof, the thirty-ninth embodiments include ones in which an amount of water added by the adding a further amount of water is responsive to the conductivity resulting from the testing.

(446) According to fortieth embodiments, the disclosed subject matter includes a method of forming a batch of treatment fluid. The method includes adding water to a mixing container. The method includes adding a first concentrate to the mixing container and testing a conductivity of its contents. The method includes outputting an indication of a failed batch in the mixing container if the conductivity is below a first predefined level. The method includes, responsively to the

conductivity, calculating an additional quantity of water and an additional quantity of a second concentrate to be added to the mixing container if the conductivity is above the predefined level. The method includes adding water and the second concentrate, including the additional quantities, to the mixing container.

(447) In variations thereof, the fortieth embodiments include ones that include testing the conductivity of the mixing container contents and responsively to the conductivity outputting an indication of a failed batch in the mixing container if the conductivity is below a second predefined level.

(448) According to forty-first embodiments, the disclosed subject matter includes a method of preparing a batch of treatment fluid. The method includes adding a quantity of an osmotic agent to a mixing container containing an electrolyte and detecting quantity of the added osmotic agent by a reduction in a conductivity of a solution in the mixing container.

(449) In variations thereof, the forty-first embodiments includes ones that include adjusting a concentration of water or electrolyte responsively to a result of the detecting in order to achieve a target mixture of electrolyte and osmotic agent.

(450) According to forty-second embodiments, the disclosed subject matter includes a method of preparing a batch of treatment fluid. The method includes adding a fraction of a final quantity of water plus a first concentrate to a mixing container; mixing the contents of the mixing container and testing a first conductivity of the contents; if the first conductivity is below a first predefined range, outputting an indication of a failure of the mixing container contents; if the first conductivity is above the first predefined range, calculating a first additional amount of water, to add to the final quantity, responsive to the first conductivity, plus an additional quantity beyond a final quantity of a second concentrate and add the second concentrate to the mixing container; if the first conductivity is in the first predefined range, add the second concentrate to the mixing container; adding a remainder of the final quantity of water plus the additional amount of water, if calculated, to the mixing container; mixing the contents of the mixing container and testing a second conductivity of the contents; if the second conductivity is below a second predefined range, outputting an indication of a failure of the mixing container contents; and if the second conductivity is within the second predefined range, making the contents of the mixing container available for a treatment.

(451) In variations thereof, the forty-second embodiments include ones in which, if the second conductivity is above the second predefined range, adding the first additional amount of water plus a second additional amount of water responsive to the second conductivity. In variations thereof, the forty-second embodiments include ones that include using the contents of the mixing container for a dialysis treatment. In variations thereof, the forty-second embodiments include ones that include using the contents of the mixing container for a peritoneal dialysis treatment.

(452) According to forty-third embodiments, the disclosed subject matter includes method of making a batch of peritoneal dialysis fluid. The method includes: (a) adding a first amount of water to a mixing container that is less than required to make the batch of peritoneal dialysis fluid; (b) adding a first concentrate to the mixing container, mixing the mixing container contents, measuring a resulting first conductivity of the mixing container contents, and determining if the first conductivity is in a first range; (c) if the first conductivity is in the first range, adding a second concentrate to the mixing container, mixing the mixing container contents, and measuring a resulting second conductivity of the mixing container contents; (d) if the second conductivity is in a second range, adding water to the mixing container, mixing and measuring a resulting third conductivity of the mixing container contents; (e) if the third conductivity falls in a third range, generating a signal indicating the contents of the mixing container form a usable batch of peritoneal dialysis fluid; (f) if the first conductivity is outside the first range, calculating an amount of water or first concentrate responsively to the first conductivity and an estimated quantity of fluid in the mixing container and adding the amount of water or first concentrate to the mixing container,

mixing the mixing container contents, and measuring a resulting fourth conductivity of the mixing container contents; (g) if the fourth conductivity is in the first range, adding the second concentrate to the mixing container, mixing the mixing container contents, and measuring a resulting fifth conductivity of the mixing container contents; (h) if the fifth conductivity is in the second range, adding water to the mixing container, mixing the mixing container contents, measuring a resulting sixth conductivity of the mixing container; (i) if the sixth conductivity is in the third range, generating a signal indicating the contents of the mixing container form a usable batch of peritoneal dialysis fluid; and (j) if the second conductivity is outside the second range, the third conductivity is outside the third range, the fourth conductivity is outside the first range, the fifth conductivity is outside the second range, or the sixth conductivity is outside the third range, generating a signal indicating to terminate the making of a batch.

(453) In variations thereof, the forty-third embodiments include ones in which the first concentrate is electrolyte concentrate and the second concentrate is osmotic agent concentrate. In variations thereof, the forty-third embodiments include ones in which the first concentrate is osmotic agent concentrate and the second concentrate is electrolyte concentrate.

(454) According to forty-fourth embodiments, the disclosed subject matter includes a method for making a batch of peritoneal dialysis fluid. The method includes: (a) adding water to a mixing container; (b) adding electrolyte concentrate to the mixing container; (c) mixing contents of the mixing container and measuring the conductivity of its contents; (d) if the conductivity measured at (c) is in a first range, performing step (h) and if the conductivity measured at (c) is outside the first range performing step (e); (e) estimating an amount of water or electrolyte concentrate, responsively to the conductivity measured in step (c), to bring the conductivity of the contents of the mixing container within the first range; (f) adding the amount of water estimated in (e) to the mixing container, mixing the contents of the mixing container, and measuring the conductivity of its contents; (g) if the conductivity measured in step (f) is outside a second range, generating a command to abort the making of the batch and performing step (p); (h) calculating a quantity of a second concentrate according to a predefined ratio of the first and second concentrates responsively to a calculated quantity of fluid held by the mixing container and the conductivity measured at step (d) if the conductivity measured at step (c) was in the first range or the conductivity measured at (f) if not; (i) adding the quantity of the second concentrate calculated at step (h) to the mixing container, mixing the contents of the mixing container, and measuring the conductivity thereof; (j) if the conductivity measured at step (i) is outside the second range, generating a command to abort the making of the batch and going to step (p); (k) if the conductivity measured at step (i) is in the second range, then calculating a quantity of water to add to the mixing container responsively to the conductivity measured at step (i) and a calculated quantity of fluid held by the mixing container; (m) adding the quantity of water calculated at step (k) to the mixing container, mixing the contents of the mixing container, and measuring the conductivity of its contents; (n) if the conductivity measured at step (m) falls in a third range, generating a command indicating the mixing container contents are usable; (o) if the conductivity measured at step (m) fall outside the third range, generating a command to abort the making of the batch; and (p) terminating the method.

(455) In variations thereof, the forty-fourth embodiments include ones in which the first concentrate is electrolyte concentrate and the second concentrate is osmotic agent concentrate. In variations thereof, the forty-fourth embodiments include ones in which the first concentrate is osmotic agent concentrate and the second concentrate is electrolyte concentrate. In variations thereof, the forty-fourth embodiments include ones in which a quantity of the adding electrolyte at step (b) is responsive to an estimate of an amount required for a completed batch. In variations thereof, the forty-fourth embodiments include ones in which each of the measuring the conductivity includes draining a portion of the contents of the mixing container. In variations thereof, the forty-fourth embodiments include ones in which the quantity of the adding electrolyte at step (b) is

responsive to an estimate of a quantity of every instance of draining a portion.

(456) According to forty-fifth embodiments, the disclosed subject matter includes a method of preparing a batch of treatment fluid. The method includes adding a quantity of an osmotic agent to a mixing container containing an electrolyte and detecting quantity of the added osmotic agent by a reduction in a conductivity of a solution in the mixing container.

(457) In variations thereof, the forty-fifth embodiments include ones in which adjusting a concentration of water or electrolyte responsively to a result of the detecting in order to achieve a target mixture of electrolyte and osmotic agent.

(458) According to forty-sixth embodiments, the disclosed subject matter includes a method of performing a peritoneal dialysis treatment. The method includes performing a fill cycle of a peritoneal dialysis treatment. The method includes performing a drain cycle of a peritoneal dialysis treatment and during the drain cycle, diverting at least one fraction of spent peritoneal dialysis fluid to a sample container to collect a sample.

(459) In variations thereof, the forty-sixth embodiments include ones in which the sample includes multiple fractions of spent peritoneal dialysis diverted at different times during the drain cycle. In variations thereof, the forty-sixth embodiments include ones in which the different times, stored in a controller, are calculated to make the sample representative of the composition of all of the spent peritoneal dialysis fluid of a full drain cycle. In variations thereof, the forty-sixth embodiments include ones in which the diverting includes filling a container of less than 500 ml. In variations thereof, the forty-sixth embodiments include ones that include, using a controller, outputting instructions for handling the sample container. In variations thereof, the forty-sixth embodiments include ones that include, using a controller, outputting instructions for handling the sample container. In variations thereof, the forty-sixth embodiments include ones that include, using a controller, outputting instructions for removing, sealing, and delivering a sample collected in the sample container.

(460) According to forty-seventh embodiments, the disclosed subject matter includes a method of performing a peritoneal dialysis treatment. The method includes using a controller, during a peritoneal dialysis drain cycle, according to a schedule of fractioning times stored in a controller, diverting fractions of spent peritoneal dialysis fluid from spent peritoneal dialysis fluid to a sample container. The schedule is responsive to predicted variations in the composition of the spent peritoneal dialysis fluid during a drain cycle and the fractioning times indicate times and durations of the fractions.

(461) In variations thereof, the forty-seventh embodiments include ones in which the times and durations are independent of each other. In variations thereof, the forty-seventh embodiments include ones in which at least two of the durations are different from each other. In variations thereof, the forty-seventh embodiments include ones that include, diverting spent dialysis fluid other than the fractions to a drain responsively to the schedule.

(462) According to forty-eighth embodiments, the disclosed subject matter includes a method of performing a peritoneal dialysis treatment. The method includes, using a controller, performing multiple drain cycles over the course of a peritoneal dialysis treatment and, for at least one of the drain cycles, diverting one or more fractions of spent peritoneal dialysis fluid from one or more of the multiple drain cycles and to a respective sample container for each of the multiple drain cycles. The method includes diverting one or more portions of the spent peritoneal dialysis fluid other than the one or more fractions, to a drain or waste collection container. The timings of the diverting of the one or more fractions are selected such that the resulting composition of the contents of each sample represent a composition of all, or a portion, of the entire contents of a respective one of the drain cycles.

(463) In variations thereof, the forty-eighth embodiments include ones that include comparing the contents of one or more of the respective sample containers to a model that estimates the composition of all, or a portion, of the entire contents of a respective one of the drain cycles. In

variations thereof, the forty-eighth embodiments include ones that include accepting input from a user interface of the controller indicating a total volume of the one or more fractions for each of the one or more of the multiple drain cycles, the controller using the input to control the total volume during the peritoneal dialysis treatment. In variations thereof, the forty-eighth embodiments include ones that include accepting input from a user interface of the controller indicating spacings of timings of the one or more fractions for each of the one or more of the multiple drain cycles, the controller using the input to control the spacings of timings during the peritoneal dialysis treatment. (464) In variations thereof, the forty-eighth embodiments include ones in which the one or more fractions is a plurality of fractions, the method further comprising accepting input from a user interface of the controller indicating a timing of a first of the plurality of fractions for each of the one or more of the multiple drain cycles, the controller using the input to control the timing of a first of the plurality of fractions during the peritoneal dialysis treatment. In variations thereof, the forty-eighth embodiments include ones in which the one or more fractions is a single fraction, the method further comprising accepting input from a user interface of the controller indicating a timing of the single fraction for each of the one or more of the multiple drain cycles, the controller using the input to control the timing of the single fraction during the peritoneal dialysis treatment. In variations thereof, the forty-eighth embodiments include ones that include accepting input from a user interface of the controller indicating a quantity of an initial one of the portions of the spent peritoneal dialysis other than the one or more fractions, the controller using the input to control the quantity of an initial one of the portions during the peritoneal dialysis treatment. In variations thereof, the forty-eighth embodiments include ones that include accepting input from a user interface of the controller indicating treatment days on which to collect the one or more fractions and corresponding combinations of parameters for each of the treatment days to create a sampling schedule, the controller using the schedule to control the collection of the one or more fractions according to corresponding combinations of parameters over successive peritoneal dialysis treatments.

(465) In variations thereof, the forty-eighth embodiments include ones in which a user interface of the controller accepts input indicating a maximum number of reschedulings of days on which to collect the one or more fractions, the method further comprising, using the controller, preventing input attempting to reschedule more than the maximum number of days on which to collect the one or more fractions. In variations thereof, the forty-eighth embodiments include ones in which a user interface of the controller accepts input indicating a schedule of days on which to collect the one or more fractions by date, day of week, day of month, or number of times in a predefined interval, the method further comprising, using the controller, controlling the days on which the one or more fractions are collected over successive peritoneal dialysis treatments. In variations thereof, the forty-eighth embodiments include ones in which the controller controls a number of the one or more fractions per drain cycle, a number of sample containers to fill with corresponding ones of the one or more fractions during a treatment, or a flow rate of draining, or any combination thereof, responsively to input received from a user interface.

(466) According to forty-ninth embodiments, the disclosed subject matter includes a dialysis system. A dialysis device has a proportioning element configured to generate dialysis fluid and a cyclor to deliver dialysis fluid to a patient to perform dialysis therapy. The dialysis device further has a digital controller configured to direct a sequence of operations for the therapy. The dialysis device further includes a wireless interface configured to communicate with a wireless device or to write to or read from a data carrier including one of a near field communication (NFC) device and a radio frequency identification (RFID) device.

(467) In variations thereof, the forty-ninth embodiments include ones in which the dialysis device is configured to upload a prescription for a peritoneal dialysis therapy through the wireless interface. In variations thereof, the forty-ninth embodiments include ones in which the wireless interface is configured to transfer a digital record of therapy data following a treatment to the

wireless device. In variations thereof, the forty-ninth embodiments include ones in which the wireless interface is configured to read a prescription or peritoneal dialysis therapy from the wireless device. In variations thereof, the forty-ninth embodiments include ones in which the wireless interface is configured to read patient identifying information from a phone, a tablet, a computer, NFC, or RFID device. In variations thereof, the forty-ninth embodiments include ones in which the wireless interface is configured to read patient information from the wireless device. In variations thereof, the forty-ninth embodiments include ones in which the wireless interface is configured to transfer system logging information to the wireless device. In variations thereof, the forty-ninth embodiments include ones in which the wireless interface is configured to transfer diagnostic system logging information to the wireless device. In variations thereof, the forty-ninth embodiments include ones in which the wireless device includes a phone, a tablet, and NFC device or an RFID device or a computer.

(468) According to fiftieth embodiments, the disclosed subject matter includes a method of priming a dialysis fluid circuit. The method includes priming a dialysis fluid circuit with priming fluid using a pump having a pumping tube segment and running the pump with priming fluid by recirculating the priming fluid for a predetermined period of time beyond that required for priming the dialysis fluid circuit.

(469) In variations thereof, the fiftieth embodiments include ones in which the pump is a peristaltic pump. In variations thereof, the fiftieth embodiments include ones in which the predetermined period of time is effective to break-in the pumping tube segment. In variations thereof, the fiftieth embodiments include ones in which the predetermined period of time is determined based on an estimate of the time or number of pump rotations required to cause a relationship between pump cycles and flow rate to vary by less than a predetermined rate. In variations thereof, the fiftieth embodiments include ones in which the priming includes recirculating priming fluid in a loop through the pumping tube segment. In variations thereof, the fiftieth embodiments include ones in which the predetermined period of time is determined responsive to an estimate of a relationship between pump cycles and flow rate to vary by less than a predetermined rate.

(470) It will be appreciated that the modules, processes, systems, and sections described above can be implemented in hardware, hardware programmed by software, software instruction stored on a non-transitory computer readable medium or a combination of the above. For example, a method for preparing a treatment fluid and/or treating a patient can be implemented, for example, using a processor configured to execute a sequence of programmed instructions stored on a non-transitory computer readable medium. For example, the processor can include, but not be limited to, a personal computer or workstation or other such computing system that includes a processor, microprocessor, microcontroller device, or is comprised of control logic including integrated circuits such as, for example, an Application Specific Integrated Circuit (ASIC). The instructions can be compiled from source code instructions provided in accordance with a programming language such as Java, C++, C#.net or the like. The instructions can also comprise code and data objects provided in accordance with, for example, the Visual Basic™ language, LabVIEW, or another structured or object-oriented programming language. The sequence of programmed instructions and data associated therewith can be stored in a non-transitory computer-readable medium such as a computer memory or storage device which may be any suitable memory apparatus, such as, but not limited to read-only memory (ROM), programmable read-only memory (PROM), electrically erasable programmable read-only memory (EEPROM), random-access memory (RAM), flash memory, disk drive and the like.

(471) Furthermore, the modules, processes, systems, and sections can be implemented as a single processor or as a distributed processor. Further, it should be appreciated that the steps mentioned above may be performed on a single or distributed processor (single and/or multi-core). Also, the processes, modules, and sub-modules described in the various figures of and for embodiments above may be distributed across multiple computers or systems or may be co-located in a single

processor or system. Exemplary structural embodiments suitable for implementing the modules, sections, systems, means, or processes described herein are provided below.

(472) The modules, processors or systems described above can be implemented as a programmed general purpose computer, an electronic device programmed with microcode, a hard-wired analog logic circuit, software stored on a computer-readable medium or signal, an optical computing device, a networked system of electronic and/or optical devices, a special purpose computing device, an integrated circuit device, a semiconductor chip, and a software module or object stored on a computer-readable medium or signal, for example.

(473) Embodiments of the method and system (or their sub-components or modules), may be implemented on a general-purpose computer, a special-purpose computer, a programmed microprocessor or microcontroller and peripheral integrated circuit element, an ASIC or other integrated circuit, a digital signal processor, a hardwired electronic or logic circuit such as a discrete element circuit, a programmed logic circuit such as a programmable logic device (PLD), programmable logic array (PLA), field-programmable gate array (FPGA), programmable array logic (PAL) device, or the like. In general, any process capable of implementing the functions or steps described herein can be used to implement embodiments of the method, system, or a computer program product (software program stored on a non-transitory computer readable medium).

(474) It will be evident from the context that in many instances that a water source may be, or include, a water purifier or a water filtration system. See for example, water filtration system **551** in FIGS. **22A** through **22C**.

(475) Furthermore, embodiments of the disclosed method, system, and computer program product may be readily implemented, fully or partially, in software using, for example, object or object-oriented software development environments that provide portable source code that can be used on a variety of computer platforms. Alternatively, embodiments of the disclosed method, system, and computer program product can be implemented partially or fully in hardware using, for example, standard logic circuits or a very-large-scale integration (VLSI) design. Other hardware or software can be used to implement embodiments depending on the speed and/or efficiency requirements of the systems, the particular function, and/or particular software or hardware system, microprocessor, or microcomputer being utilized. Embodiments of the method, system, and computer program product can be implemented in hardware and/or software using any known or later developed systems or structures, devices and/or software by those of ordinary skill in the applicable art from the function description provided herein and with a general basic knowledge of control system, fluid handling systems, medical treatment and/or computer programming arts.

(476) Moreover, embodiments of the disclosed method, system, and computer program product can be implemented in software executed on a programmed general purpose computer, a special purpose computer, a microprocessor, or the like.

(477) FIG. **14** shows a block diagram of an example computer system according to embodiments of the disclosed subject matter. In various embodiments, all or parts of system **1000** may be included in a medical treatment device/system such as a renal replacement therapy system. In these embodiments, all or parts of system **1000** may provide the functionality of a controller of the medical treatment device/systems. In some embodiments, all or parts of system **1000** may be implemented as a distributed system, for example, as a cloud-based system.

(478) System **1000** includes a computer **1002** such as a personal computer or workstation or other such computing system that includes a processor **1006**. However, alternative embodiments may implement more than one processor and/or one or more microprocessors, microcontroller devices, or control logic including integrated circuits such as ASIC.

(479) Computer **1002** further includes a bus **1004** that provides communication functionality among various modules of computer **1002**. For example, bus **1004** may allow for communicating information/data between processor **1006** and a memory **1008** of computer **1002** so that processor

1006 may retrieve stored data from memory **1008** and/or execute instructions stored on memory **1008**. In one embodiment, such instructions may be compiled from source code/objects provided in accordance with a programming language such as Java, C++, C#, .net, Visual Basic™ language, LabVIEW, or another structured or object-oriented programming language. In one embodiment, the instructions include software modules that, when executed by processor **1006**, provide renal replacement therapy functionality according to any of the embodiments disclosed herein.

(480) Memory **1008** may include any volatile or non-volatile computer-readable memory that can be read by computer **1002**. For example, memory **1008** may include a non-transitory computer-readable medium such as ROM, PROM, EEPROM, RAM, flash memory, disk drive, etc. Memory **1008** may be a removable or non-removable medium.

(481) Bus **1004** may further allow for communication between computer **1002** and a display **1018**, a keyboard **1020**, a mouse **1022**, and a speaker **1024**, each providing respective functionality in accordance with various embodiments disclosed herein, for example, for configuring a treatment for a patient and monitoring a patient during a treatment.

(482) Computer **1002** may also implement a communication interface **1010** to communicate with a network **1012** to provide any functionality disclosed herein, for example, for alerting a healthcare professional and/or receiving instructions from a healthcare professional, reporting patient/device conditions in a distributed system for training a machine learning algorithm, logging data to a remote repository, etc. Communication interface **1010** may be any such interface known in the art to provide wireless and/or wired communication, such as a network card or a modem.

(483) Bus **1004** may further allow for communication with a sensor **1014** and/or an actuator **1016**, each providing respective functionality in accordance with various embodiments disclosed herein, for example, for measuring signals indicative of a patient/device condition and for controlling the operation of the device accordingly. For example, sensor **1014** may provide a signal indicative of a viscosity of a fluid in a fluid circuit in a renal replacement therapy device, and actuator **1016** may operate a pump that controls the flow of the fluid responsively to the signals of sensor **1014**.

(484) It is, thus, apparent that there is provided, in accordance with the present disclosure, methods, devices, and system for preparing fluids, managing fluids, sterilizing fluids, treating patients and other functions. Many alternatives, modifications, and variations are enabled by the present disclosure. Features of the disclosed embodiments can be combined, rearranged, omitted, etc., within the scope of the invention to produce additional embodiments. Furthermore, certain features may sometimes be used to advantage without a corresponding use of other features. Accordingly, Applicants intend to embrace all such alternatives, modifications, equivalents, and variations that are within the spirit and scope of the present invention.

Claims

1. A system for preparation of a sterile medical treatment fluid, comprising: at least one fluid circuit with a pumping tube segment and multiple valve segments; at least one pumping actuator configured to engage the pumping tube segment; multiple valve actuators configured to engage said multiple valve segments; a controller configured to control said multiple valve actuators and said at least one pumping actuator; a first of the multiple valve segments being along a fluid inlet line with a sterilizing filter; a first multi-treatment concentrate container having a quantity of a first concentrate that is sufficient for preparation of enough peritoneal dialysis fluid to perform multiple peritoneal dialysis treatments, each of the multiple peritoneal dialysis treatments including multiple fill/drain cycles; a water source; the at least one fluid circuit having, integrally-attached thereto, a first single-treatment concentrate container and a mixing container, the mixing container being sized to hold sufficient peritoneal dialysis fluid for at least a single fill cycle and the first single-treatment concentrate container being empty when the at least one fluid circuit is initially connected to the first multi-treatment concentrate container; ones of said multiple valve segments

connected between said fluid inlet line and said water source and between said first multi-treatment concentrate container and said fluid inlet line, wherein the controller is configured to control said ones of said multiple valve actuators and said at least one pumping actuator, to sequentially connect the first single-treatment concentrate container and the water source to the fluid inlet line and to control flow through the fluid inlet line such that water is conveyed from the water source to the mixing container and some of the first concentrate is conveyed from the first multi-treatment concentrate container to the first single-treatment concentrate container, and subsequently to pump the first concentrate from the first single-treatment concentrate container to the mixing container so that the first concentrate is incorporated in a dialysis fluid formed in the mixing container.

2. The system of claim 1, wherein the controller is configured to perform a fill/drain cycle including draining spent fluid from a patient line and pumping the dialysis fluid from the mixing container to the patient line.

3. The system of claim 1, further comprising a second multi-treatment concentrate container that contains a second concentrate, wherein, ones of said multiple valve segments are connected to said second multi-treatment concentrate container and said fluid inlet line.

4. The system of claim 3, further comprising: a second single-treatment concentrate container connected to said fluid circuit that is initially empty when the at least one fluid circuit is initially connected to the second multi-treatment concentrate container, wherein said controller is configured to control said ones of said multiple valve actuators and said at least one pumping actuator to transfer some of the second concentrate from the second multi-treatment concentrate container to the second single-treatment concentrate container, and to subsequently transfer the second concentrate from the second single-treatment concentrate container to the mixing container to form said dialysis fluid.

5. The system of claim 3, wherein the sterilizing filter has an air port to allow a membrane of the sterilizing filter to be pressure tested, the controller being programmed to test the membrane by applying pressure to the air port and measuring the pressure after pumping water therethrough.

6. The system of claim 5, wherein the controller is configured to generate an alarm signal responsively to a result of a test of said membrane if said test indicates a loss of integrity of said membrane.
