

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409465
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Ebertowski; Alexander T. et al.

Liquid spray gun, connector ring, liquid spraying apparatus and adapter system

Abstract

The invention provides a liquid spray gun connectable to a fluid reservoir through a fluid outlet. The spray gun comprises a socket geometry arranged for engagement with a co-operating connector for releasable connecting the spray gun with the fluid outlet. The socket geometry comprises a bore having an opening on one end, an end surface surrounding the bore's opening at least partially, and a lug portion spaced apart from the end surface in an axial direction parallel to a central axis of the bore. The lug portion has a lower surface being adapted to engage with the connector and to retain the connector in the axial direction. The end surface comprises a first keying geometry that is adapted to restrict rotation of the connector in at least one direction.

Inventors:	Ebertowski; Alexander T. (St. Paul, MN), Joseph; Stephen C. P. (Woodbury, MN), Gullicks; Scott D. (River Falls, WI)
Applicant:	3M INNOVATIVE PROPERTIES COMPANY (St. Paul, MN)
Family ID:	69005767
Assignee:	3M Innovative Properties Company (St. Paul, MN)
Appl. No.:	17/299707
Filed (or PCT Filed):	December 05, 2019
PCT No.:	PCT/IB2019/060498
PCT Pub. No.:	WO2020/121137
PCT Pub. Date:	June 18, 2020

Prior Publication Data

Document Identifier

US 20220055047 A1

Publication Date

Feb. 24, 2022

Related U.S. Application Data

us-provisional-application US 62778625 20181212

Publication Classification

Int. Cl.: B05B7/24 (20060101)

U.S. Cl.:

CPC B05B7/2408 (20130101); B05B7/2478 (20130101);

Field of Classification Search

CPC: B05B (7/2408); B05B (7/2478)

USPC: 239/345

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3157360	12/1963	Heard	N/A	N/A
7036752	12/2005	Hsiang	239/290	B05B 7/2408
7083119	12/2005	Bouic	285/361	B05B 7/2408
7090148	12/2005	Petrie	239/600	B05B 15/40
7165732	12/2006	Kosmyna	285/361	B05B 7/2478
7374111	12/2007	Joseph	141/2	B05B 7/247
7614571	12/2008	Camilleri	N/A	N/A
7789324	12/2009	Bouic	N/A	N/A
7823806	12/2009	Schmon	N/A	N/A
2017/0239681	12/2016	Bierie	N/A	B05B 7/2408

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2078564	12/2008	EP	N/A
WO 1998-032539	12/1997	WO	N/A
WO 2001-012337	12/2000	WO	N/A
WO 2004-094072	12/2003	WO	N/A
WO 2005-068220	12/2004	WO	N/A
WO 2006-098623	12/2005	WO	N/A
WO 2018-104826	12/2017	WO	N/A

OTHER PUBLICATIONS

Primary Examiner: Lee; Chee-Chong

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a national stage filing under 35 U.S.C. 371 of PCT/IB2019/060498, filed Dec. 5, 2019, which claims the benefit of U.S. Application No. 62/778,625, filed Dec. 12, 2018, the disclosure of which is incorporated by reference in its/their entirety herein.

FIELD OF THE INVENTION

(1) The present invention relates to a liquid spray gun and a connector ring. In addition, the present invention relates to a liquid spraying apparatus comprising the liquid spray gun and a connector, e.g. said connector ring. Moreover, the present invention relates to an adapter system comprising the connector ring and a corresponding adapter.

BACKGROUND

(2) In the prior art most handheld spray guns comprise a threaded inlet in order to attach the traditional fluid reservoir or paint cup. With the introduction of disposable paint cup systems such as the 3M PPS™, DeVilbiss DeKUPS®, Norton's Paint Cup System and similar products, an adapter (usually CNC machined metal) is provided that converts the threaded inlet of the spray gun to a different connection geometry.

(3) In the case of the SATAjet® 5000 B RP spray gun (equipped with Sata QCC connection), the fluid inlet is non-threaded. In this example, a “screw wedge” geometry which locates and “wedges” under a lug portion (protrusion), itself being integral to the body or socket of the spray gun, is incorporated into the fluid outlet of the lid to facilitate connection.

(4) In US 2017/0239681 A1 a conversion sleeve is described to provide a means for attaching a threaded adapter to a non-threaded fluid inlet. However, the conversion sleeve does not sit flush with the lug portion provided at the socket of the spray gun.

(5) In EP 2 078 564 A1 a tubular coupling member is described that can be push fitted into a non-threaded spray gun inlet. A cutout portion inhibits rotation of the body portion of the insert in the spray gun socket. A threaded adapter can be screwed in accordingly. However, said tubular coupling member does not comprise a mechanical retention that prevents the tubular coupling member from being pulled out of the spray gun socket.

(6) In EP 2 027 931 A1 a stop element is described that is arranged a distance from the upper end of the screw wedge element in the circumferential direction. However, the stop element is made of plastic as it is part of the lid that is made of plastic. Should the lid be over rotated during assembly, the stop element may deform, distort or even be destroyed by the application of excessive force. The stop element does therefore not provide a robust stop for the lid during connection of the lid to the socket of the spray gun.

SUMMARY

(7) It is an object of the present invention to simplify and improve the prior art connection systems. In particular, one object of the present invention is to provide simplified and improved restriction of rotation of the connector in at least one direction. The object is achieved by the features of the independent claims. Dependent claims relate to further embodiments of the present invention.

(8) According to a first aspect the present invention provides a liquid spray gun connectable to a fluid reservoir through a fluid outlet. The spray gun comprises a socket geometry arranged for

engagement with a co-operating connector for releasable connecting the spray gun with the fluid outlet. The socket geometry comprises a bore having an opening on one end, an end surface surrounding the bore's opening at least partially, and a lug portion spaced apart from the end surface in an axial direction parallel to a central axis of the bore. The lug portion has a lower surface being adapted to engage with the connector and to retain the connector in the axial direction and the end surface comprises a first keying geometry that is adapted to restrict rotation of the connector in at least one direction.

(9) Thus, due to the provision of a first keying geometry on the socket geometry of the spray gun, different connectors may be easily attached to the spray gun with improved stability and rotational restriction in at least one direction.

(10) The fluid outlet may be an outlet of a reservoir for mixing of paint directly therein.

(11) The reservoir may further comprise a re-usable outer cup and collar. A disposable liner may be provided in the outer cup in order to mix paint therein.

(12) The disposable liner may be closed with a disposable filter lid.

(13) Such systems are disclosed, for example, in applicant's WO 98/32539 A1 (which is incorporated by reference herein in its entirety). Alternatively, other types of liners for spray gun reservoirs are known, for example, from U.S. Pat. No. 3,157,360.

(14) One example of a reservoir is the PPS™ system by 3M Company (Maplewood, Minnesota, U.S.).

(15) Alternatively, the reservoir may comprise a cup that is usually injection molded, does not collapse as the paint is dispensed from the gun, and may thus be provided with a vent. One example is the RPS™ system sold by SATA (Kornwestheim, Germany).

(16) Such vented disposable cups for preparing, applying and preserving paint are known from, for example, U.S. Pat. No. 7,614,571 (which is incorporated by reference herein in its entirety).

(17) Further non-collapsible cups are known from, for example, WO 2005/068220 A1, WO 2006/098623 A1, and applicant's WO 98/32539 A1 (all of which are incorporated by reference herein in their entirety).

(18) The end surface of the socket geometry may be planar.

(19) The connector may be the lid of the reservoir. For example, the lid may comprise a respective second keying geometry to releasable connect the spray gun with the fluid outlet and to restrict rotation of the lid in at least one direction. For example, such a lid may be a lid used in the RPS™ system sold by SATA (Kornwestheim, Germany). Such a lid is known from EP 2 027 931 A1, for example. As outlined above, such a lid may comprise a screw wedge structure, which may be defined as a second keying geometry as will be further described below.

(20) The lid may be directly connected to the socket geometry of the spray gun without any further adapter necessary.

(21) Alternatively, the connector may be a connector ring as further described below, wherein the connector ring comprises a respective second keying geometry.

(22) The connector ring may be used to enable a connection of a threaded adapter or lid to a non-threaded socket geometry. However, other conversions from the non-threaded socket geometry are possible using a connector ring in accordance with the present invention, e.g. a bayonet fitting or friction fitting.

(23) The first keying geometry may comprise at least one protrusion and/or at least one recess.

(24) The use of at least one protrusion and/or at least one recess may provide a rotational restriction in both directions, and thus, may provide a more stable fit.

(25) The at least one protrusion and/or at least one recess may be provided on a section of the end surface not directly underneath the lug portion when viewed along an axis parallel to the central axis of the bore.

(26) The at least one protrusion and/or at least one recess may be a single protrusion or recess.

(27) The projection of the center of the lug portion onto the end surface of the socket geometry may

be defined as a reference location on the end surface at 0°. In this case, the protrusion or recess may be provided on the end surface at any location between 15° and 345°, preferably between 30° and 330°, more preferably between 45° and 315°.

(28) The protrusion or recess may be located at 30° or 330°, preferably at 45° or 315°, more preferably at 90° or 270°, in accordance to the above definition.

(29) The angular ranges starting from 0° as referred to herein may extend in a clockwise direction along the end surface.

(30) The at least one protrusion and/or at least one recess may be a plurality of protrusions and/or recesses.

(31) The plurality of protrusions and/or recesses may be provided on the end surface at equidistances or irregular distances to one another.

(32) The plurality of protrusions and/or recesses may be provided on the end surface in an area that is located opposite the lug portion.

(33) Taking the above given definition, i.e. that the projection of the center of the lug portion onto the end surface of the socket geometry may be defined as a reference location on the end surface at 0°. In this case, the plurality of protrusions and/or recesses may be provided on the end surface between 15° and 345°, preferably between 30° and 330°, more preferably between 45° and 315°.

(34) The plurality of protrusions and/or recesses may be located at 15°, 180° and/or 345°, preferably at 30°, 180° and/or 330°, more preferably at 45°, 180° and/or 315°, in accordance to the above definition.

(35) If the connector is the aforementioned lid used in the RPS™ system sold by SATA (Kornwestheim, Germany), the first keying geometry may be at least one protrusion. That is, the first keying geometry, i.e. the at least one protrusion, may restrict rotation of the screw wedge located on the outside circumference of the lid by engagement of the leading edge of the screw wedge with the protrusion.

(36) Although the leading edge of the lid of the RPS™ system may be a sloped leading edge, the leading edge may be adjusted to comprise a flat leading edge, thereby providing a more robust end stop, i.e. rotational stop, when engaging with the at least one protrusion on the end surface of the socket geometry.

(37) Nevertheless, other lids than the lid of the RPS™ system may also be used as a connector in connection with the present invention. Thus, for any kind of lid, the first keying geometry may comprise at least one protrusion and/or at least one recess. The respective second keying geometry, similar to the second keying geometry described below in connection with the connector ring, may be provided at the lid to releasably connecting the spray gun with the fluid outlet and to restrict rotation of the lid in at least one direction.

(38) If the connector is a connector ring (as further described below), the first keying geometry may comprise at least one protrusion and/or at least one recess.

(39) The at least one protrusion and/or at least one recess may extend in an axial direction of the bore.

(40) The lug portion may project from the socket geometry towards the central axis of the bore.

(41) The lug portion may project from the socket geometry towards a central axis of the bore about the same distance as the width of the end surface. Thus, not blocking the bore for inserting an adapter or lid.

(42) Preferably a radial inner surface of the lug portion surrounding the bore is at least partially curved when viewed along an axial direction parallel to the central axis of the bore.

(43) Taking the above given definition, i.e. that the projection of the center of the lug portion onto the end surface of the socket geometry may be defined as a reference location on the end surface at 0°. The lug portion may extend within an angular range of 40° in both directions, more preferably 30° in both directions, and even more preferably 20° in both directions, and most preferably 10° in both directions.

- (44) The lug portion being spaced apart from the end surface in an axial direction thereof may define a recess between the end surface of the socket geometry and the lower surface of the lug portion.
- (45) The lower surface of the lug portion may be a chamfered surface.
- (46) The lower surface may be spaced from the end surface by at least 1 mm, preferably at least 2 mm, more preferably at least 3 mm, and even more preferably at least 4 mm.
- (47) The end surface may be at least one of the following: wavy shaped, saw-tooth shaped, regular shaped, irregular shaped.
- (48) The end surface may comprise a repeating or non-repeating shape.
- (49) The end surface may comprise a combination of raised and recessed surfaces.
- (50) The above-mentioned shapes of the end surface may define the first keying geometry. That is, the first keying geometry may be defined by the shape of the end surface.
- (51) According to a second aspect, the present invention provides a liquid spraying apparatus comprising the spray gun described above and a connector. The connector comprising: a first surface adapted to engage with the lower surface of the lug portion to retain the connector in the axial direction, and a second keying geometry that is adapted to engage with the first keying geometry to restrict rotation of the connector in at least one direction.
- (52) The first surface may face away from the end surface, preferably when engaged with the lower surface of the lug portion.
- (53) The connector may comprise a connector ring with the second keying geometry.
- (54) The first keying geometry comprises preferably the inverse structure of the second keying geometry.
- (55) The connector ring may be a C-shaped connector ring having a gap along the circumference of the connector ring and the second keying geometry may be defined by the gap of the C-shaped connector ring.
- (56) The C-shape may only be a part of the connector ring and does not exclude other geometric parts that may be comprised in the connector ring as long as the functional geometry is a C-shape. That is, as long as the connector ring comprises a C-shape that defines a second keying geometry to be engaged with a first keying geometry.
- (57) The C-shaped part of the connector ring may follow the end surface of the socket geometry.
- (58) The second keying geometry may comprise at least one recess or at least one protrusion on a second surface of the connector ring facing towards the end surface of the socket geometry.
- (59) Both the C-shape and the at least one recess or at least one protrusion may provide a rotational stop for the connector ring in two directions.
- (60) The connector ring comprising the C-shape may further comprise at least one protrusion and/or at least one recess in accordance with the first keying geometry provided on the end surface of the socket geometry to provide a more robust fitting.
- (61) The connector ring may comprise a threaded internal surface.
- (62) Alternatively, the connector ring may comprise a bayonet fitting or a friction fit as long as it is able to provide a way to retain an adapter or a lid in the connector ring and therefore the adapter or the lid in the bore of the socket geometry.
- (63) The liquid spraying apparatus may further comprise an adapter with a threaded outer surface to engage with the threaded inner surface of the connector ring.
- (64) The adapter may be adapted to be screwed into the connector ring and adapted to abut against the spray gun so that the connector ring is forced against the lower surface of the lug portion as the adapter is screwed into the connector ring so as to provide a fluid-tight connection between the liquid spray gun and the adapter.
- (65) Alternatively, in accordance with the connector ring, the adapter may comprise a pin to engage with the bayonet fitting of the connector ring or a corresponding friction fit to retain the adapter in the connector ring and therefore the adapter in the bore of the socket geometry.

(66) The adapter may have a tubular pipe (also referred to as a fluid outlet or fluid conduit) adapted to extend into the bore.

(67) The fluid-tight connection between the liquid spray gun and the adapter may be provided by forcing the tubular pipe against the bore.

(68) A front-end surface of the tubular pipe may be forced against a constriction within the bore.

(69) The front-end surface of the tubular pipe may be chamfered.

(70) The socket geometry of the spray gun may comprise an additional adapter part as a separate part to the socket geometry, wherein the adapter part is connectable to the socket geometry, and wherein the adapter part comprises a bore with an end surface surrounding the bore's opening at least partially and a lug portion spaced apart from the end surface in an axial direction of the bore. The lug portion has a lower surface being adapted to engage with the connector and to retain the connector in the axial direction and the end surface of the socket geometry comprises a first keying geometry that is adapted to restrict rotation of the connector in at least one direction.

(71) In other words, an additional adapter part may be provided to be connectable to the socket geometry of the spray gun, wherein the adapter part comprises the aforementioned lug portion and the first keying geometry in addition or instead of the socket geometry of the spray gun.

(72) According to a third aspect, the present invention provides a connector ring for releasable connecting a liquid spray gun to a fluid outlet for a liquid to be sprayed, wherein the liquid spray gun comprising a socket geometry with a bore having an opening on one end, an end surface surrounding the bore's opening at least partially, and a lug portion spaced apart from the end surface in an axial direction parallel to a central axis of the bore. The connector ring comprises: a first surface adapted to engage with a lower surface of the lug portion to retain the connector ring in the axial direction, and a second keying geometry that is adapted to engage with a first keying geometry of the socket geometry to restrict rotation of the connector ring in at least one direction.

(73) The first surface may face away from the end surface. That is, when engaged with the end surface of the socket geometry, the first surface may be defined as the surface that faces away from the end surface.

(74) The connector ring may be a C-shaped connector ring with a gap along the circumference of the connector ring and wherein the second keying geometry is defined by the gap of the C-shaped connector ring.

(75) The second keying geometry may comprise at least one recess or at least one protrusion on a second surface of the connector ring facing away from the first surface of the connector ring.

(76) The connector ring may comprise a threaded inside surface.

(77) According to a fourth aspect, the present invention provides an adapter system for releasable connecting a liquid spray gun to a fluid outlet for a liquid to be sprayed, wherein the liquid spray gun comprises a socket geometry with a bore having an opening on one end, an end surface surrounding the bore's opening at least partially, and a lug portion spaced apart from the end surface in an axial direction parallel to a central axis of the bore. The adapter system comprising: a connector ring as described above; and an adapter configured to engage with the connector ring.

(78) The connector ring may comprise a threaded inside surface and the adapter may comprise a threaded outer surface to engage with the inside surface of the connector ring.

(79) The adapter may be adapted to be screwed into the connector ring and adapted to abut against the spray gun so that the connector ring is forced against the lower surface of the lug portion as the adapter is screwed into the connector ring so as to provide a fluid-tight connection between the liquid spray gun and the adapter.

(80) The connector ring may alternatively comprise a bayonet fitting or a friction fit, and the adapter may comprise a corresponding pin to engage with the bayonet fitting of the connector ring or a corresponding friction fit to engage with the connector ring and thereby retain the adapter in the connector ring.

(81) Thus, the present invention provides for an improved connection between a spray gun and a

fluid outlet for a liquid to be sprayed. Further advantages may be apparent to a person skilled in the art from the description of the present invention herein.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The present invention is further described with respect to exemplary embodiments by referring to the FIGURES, where
- (2) FIG. 1 illustrates a perspective view of a socket geometry of a liquid spray gun according to an embodiment of the present invention,
- (3) FIG. 2A illustrates a side view of the socket geometry of a liquid spray gun according to FIG. 1,
- (4) FIG. 2B illustrates a top view of the socket geometry of a liquid spray gun according to FIG. 1,
- (5) FIG. 3 illustrates a perspective view of a lid according to an embodiment of the present invention,
- (6) FIG. 4 illustrates a perspective view of the socket geometry of a liquid spray gun according to FIG. 1 connected to the lid of FIG. 3,
- (7) FIG. 5 illustrates a perspective view of an adapter according to an embodiment of the present invention,
- (8) FIG. 6A illustrates a perspective view of a connector ring according an embodiment of the present invention,
- (9) FIG. 6B illustrates a side view of the connector ring of FIG. 6A,
- (10) FIG. 6C illustrates a perspective view of a connector ring according an embodiment of the present invention,
- (11) FIG. 7 illustrates a perspective view of the socket geometry of FIG. 1, the adapter of FIG. 5 and the connector ring of FIG. 6A assembled together,
- (12) FIG. 8 illustrates a perspective view of a socket geometry of a liquid spray gun according to an embodiment of the present invention,
- (13) FIG. 9A illustrates a perspective view of a connector ring according an embodiment of the present invention,
- (14) FIG. 9B illustrates a top view of the connector ring of FIG. 9A,
- (15) FIG. 10 illustrates a perspective view of a socket geometry of a liquid spray gun according to an embodiment of the present invention,
- (16) FIG. 11 illustrates a perspective view of a connector ring according an embodiment of the present invention,
- (17) FIG. 12 illustrates a perspective view of a socket geometry of a liquid spray gun according to an embodiment of the present invention,
- (18) FIG. 13 illustrates a perspective view of a connector ring according an embodiment of the present invention,
- (19) FIG. 14A illustrates a perspective view of a connector ring according an embodiment of the present invention,
- (20) FIG. 14B illustrates a back view of the connector ring of FIG. 14A,
- (21) FIG. 14C illustrates a front view of the connector ring of FIG. 14A,
- (22) FIG. 15A illustrates a perspective view of an adapter according to an embodiment of the present invention, and
- (23) FIG. 15B illustrates a side view of the adapter of FIG. 15A.

DETAILED DESCRIPTION

(24) Some preferred embodiments are now described with reference to the drawings. For explanation purpose, various specific details are set forth, without departing from the scope of the present invention as claimed. Like numerals refer to the same features. In addition, the description

of features that are described with reference to a certain embodiment is not repeated for the other embodiments. However, the description thereof shall apply to the other embodiments as well.

(25) FIG. 1 shows perspective view of a socket geometry **10** of a liquid spray gun (not shown). In some embodiments, the socket geometry may be integrally formed with the spray gun body. The socket geometry **10** comprises, as shown in FIG. 1, a bore **11**, an end surface **12**, a lug portion **13**, a radial inner surface **131** of the lug portion **13**, a protrusion **14** and a connecting surface **15**.

(26) The end surface **12** surrounds the bore's opening. It is preferable that the end surface **12** surrounds the bore's opening completely, i.e. the end surface **12** extends completely around the bore's opening. In some embodiments, as illustrated in FIG. 1, the end surface **12** of the socket geometry is planar.

(27) The end surface **12** further comprises the protrusion **14**, which is one example for a keying geometry in the sense of the present invention. That is, a keying geometry as used herein, e.g. the protrusion **14**, defines a geometry that is configured to be engaged with a corresponding geometry, preferably a complementary negative thereof, e.g. a recess in the case of the protrusion **14**.

However, as outlined below, the protrusion **14** may also be engaged with a different corresponding structure than a recess, e.g. a leading edge of a lid (as will be described below).

(28) The protrusion **14** extends in an axial direction from the end surface **12**. That is, the protrusion **14** extends from the end surface **12** in a direction parallel to central axis, A.sub.1, of the bore **11**.

The protrusion **14** may extend over the whole width, W.sub.1, of the end surface **12** or just a part of the end surface **12**. In the latter, the protrusion **14** may extend from the outer side **16** of the end surface **12** towards the inner side **17**, i.e. the side located at the bore **11**, of the end surface **12**, but not all the way to the inner side of the end surface **12** to leave some space on the end surface **12** between the protrusion **14** and the inner side of the end surface **12**.

(29) The lug portion **13** is spaced apart from the end surface **12** in an axial direction parallel to the central axis A.sub.1. The lug portion **13** relates to the part that extends from the main body of the socket geometry **10** towards the center of the bore **11**, i.e. towards the central axis, A.sub.1, of the bore **11**.

(30) The lug portion **13** has a radial inner surface **131** that surrounds the bore **11** partially and is curved when viewed along an axial direction. In some embodiments, the radial inner surface **131** follows the curvature of the end surface **12**.

(31) The lug portion **13** and the end surface **12** are connected by the connecting surface **15**. The connecting surface **15** extends in an axial direction from the end surface **12** and connects the end surface **12** and the lug portion **13**. The above mentioned spacing between the lug portion **13** and the end surface **12** is defined by the extension of the connecting surface **15** in said axial direction from the end surface **12**.

(32) The connecting surface **15** is located on the outer side **16** of the end surface **12**. The lug portion **13** extends from the connecting surface **15** towards the central axis of the bore **11** about the same length as the width, W.sub.1, of the end surface **12**.

(33) The connecting surface **15** has the same curvature as the end surface **12** and the radial inner surface **131**.

(34) The lug portion **13** comprises an upper surface **18** that faces away from the end surface **12** and a lower surface **19** that faces towards the end surface **12**. The lower surface is defined as the extension from the connecting surface **15** to the radial inner surface **131**.

(35) The projection of the center of the lug portion **13** onto the end surface **12** of the socket geometry **10** may be defined as a reference location **23** on the end surface **12** at 0°. In this case, the protrusion **14** is located on the end surface **12** at 90° according to FIG. 1, wherein the angular range starting from 0° extends in a clockwise direction along the end surface.

(36) Accordingly, the lug portion **13** extends within an angular range of approximately 40° in both directions, i.e. from 0° to 40° and from 320° to 0°.

(37) FIGS. 2A and 2B show a side view and top view, respectively, of the socket geometry **10** of

FIG. 1. FIGS. 2A and 2B show the end surface **12**, the lug portion **13**, the protrusion **14** and the connecting surface **15**. In addition, the extension of the connecting surface **15** is indicated by d . That is, the connecting surface **15** extends in an axial direction from the end surface **12** to the lower surface of the lug portion **13** by the parameter d .

(38) FIG. 2B also illustrates the center line c that is defined by the center of the lug portion **13** and the center of the bore's opening. The center line c may be used to define the angular relations described herein. As defined above, the projection of the center of the lug portion **13** onto the end surface **12** of the socket geometry **10** may be defined as a reference location **23** on the end surface **12** at 0° . Therefore, the angles α and β indicated in FIG. 2B define the above mentioned angular range that the lug portion **13** extends in both directions from the indicated center line c . In addition, the angle γ indicated in FIG. 2B defines the above-mentioned location of the protrusion **14** on the end surface **12**. This illustrative concept applies to all angles and angular ranges defined herein.

(39) FIG. 3 shows a perspective view of a lid **20**. The lid **20** may also be generally referred to as a connector. The lid **20**, as shown in FIG. 3, comprises a fluid outlet having a "screw wedge" geometry **21** with an upper surface **211**, a lower surface **224**, and a leading edge **212**.

(40) The fluid outlet **22** is to be inserted into the bore **11** of the socket geometry **10** as described with reference to FIGS. 1 and 2.

(41) The screw wedge geometry **21** protrudes from the outer surface of the fluid outlet **22** extending partially around the circumference of the fluid outlet **22**. The screw wedge geometry **21** has a chamfered upper surface **211** and a leading edge **212** at the front part, i.e. the thin part, of the screw wedge geometry **21**.

(42) The lid may be a lid of the RPS' system sold by SATA (Kornwestheim, Germany). Such a lid is known from EP 2 027 931 A1, for example.

(43) FIG. 4 shows a perspective view of a connection between the socket geometry **10** as described with reference to FIGS. 1 and 2 and the lid **20** as described with reference to FIG. 3. As can be seen from FIG. 4, the screw wedge geometry **21** is inserted between the end surface **12** and the lug portion **13**. This may be achieved by inserting the leading edge **212** in the opening between the lug portion **13** and the end surface **12** from the side, where the protrusion **14** is not located. By a screwing, turning or twisting motion, the upper surface **211** of the screw wedge geometry **21** is engaged with the lower surface of the lug portion **13** and the lower surface of the screw wedge geometry **21** is engaged with the end surface **12** of the socket geometry **10**. Thereby the lid **20** or rather the fluid outlet **22** of the lid **20** is retained within the socket geometry's bore **11** by the screw wedge geometry **21** being screwed in between the lug portion **13** and the end surface **12**. Thus, the lug portion **13** and the end surface **12** retain the lid **20** in an axial direction thereof.

(44) In addition, the leading edge **212** of the screw wedge geometry **21** is engaged with, interferes with or abuts against the protrusion **14**, thereby preventing a further rotational movement of the lid **20** in the screwing direction. Thus, the protrusion **14** provides a rotational stop for the lid **20** by engaging with the leading edge **212** of the screw wedge geometry **21**.

(45) The leading edge **212** of the screw wedge geometry **21** may be chamfered or straight. By providing the leading edge **212** as a straight edge, a more robust rotational stop may be achieved when engaging with a corresponding straight surface, i.e. a side surface, of the protrusion **14**.

(46) FIG. 5 shows a perspective view of an adapter **30**. The adapter **30** comprises, as can be seen in FIG. 5, a fluid outlet **31** and a threaded outer surface **32** protruding from the outer surface of the fluid outlet **31**, i.e. in an axial direction of the fluid outlet **31**. The adapter **30** further comprises a connecting geometry **33** configured to connect to a fluid outlet of a reservoir (not shown) for mixing paint. The function of the adapter **30** will be further described below with reference to FIG. 7.

(47) FIGS. 6A and 6B show a perspective view and side view, respectively, of a connector ring **40**. The connector ring **40** comprises, as can be seen in FIG. 6A, a first surface **41**, a second surface **42**, an internal surface **43**, a recess **44** and a bridge portion **441**.

(48) The connector ring **40** may also be referred to generally as a connector. In particular, the connector ring **40** as well as the lid **20** described above may be referred to as connectors, because both serve the purpose to connect a reservoir to the socket geometry **10** of the spray gun either directly or by use of additional components, e.g. an adapter **30** as described above.

(49) The first surface **41** may be referred to as a top surface and the second surface **42** may be referred to as a lower surface of the connector ring **40**. The first and second surfaces **41**, **42** surround the opening of the connector ring **40**. The first and second surfaces **41**, **42** lie in planes that are parallel to each other.

(50) The internal surface **43** connects the first surface **41** and the second surface **42**. The internal surface **43** may be threaded, as shown in FIG. **6A**, to receive, for example, a corresponding threaded adapter **30** as described with reference to FIG. **5**. In this case, the internal surface **43** may also be referred to as a threaded internal surface **43**.

(51) The recess **44** is defined by cutting out a part of the connector ring **40** from the side of the second surface **42**, leaving the bridge portion **441** on the first surface **41**. That is, the recess **44** is a cutout from the side of the second surface **42**, wherein a bridge portion **441** of a predetermined width, $W_{sub.2}$, is defined by end surfaces **50** of the recess **44** and the first surface **41** of the connector ring **40**.

(52) As will be evident from the description below with reference to FIG. **7**, the recess **44** is configured to engage with the protrusion **14** of the socket geometry **10** as described with reference to FIG. **1** and the threaded internal surface **43** of the connector ring **40** is configured to engage with the threaded outer surface **32** of the adapter **30** as described with reference to FIG. **5**.

(53) However, it is clear that the threaded internal surface **43** of the connector ring **40** according to the present invention is not restricted to engage with an adapter **30**. The threaded internal surface **43** of the connector ring **40** can engage with any corresponding threaded connector between a socket geometry **10** and a fluid outlet of a reservoir for mixing paint. For example, the corresponding threaded surface may be comprised on a lid, which connects to a respective reservoir, thus, allowing for a connection between the socket geometry **10** and the reservoir without the use of an adapter **30**.

(54) FIG. **6C** shows a perspective view of a connector ring **40** that comprises a C-shape with a gap (or cutout) **45** along the circumference of the connector ring **40** and where the second keying geometry is defined by the gap **45** of the C-shaped connector ring **40**.

(55) In other words, the connector ring **40** of FIGS. **6A** and **6B** is modified in that the bridge portion **441** is omitted or cut out, and thus, defining the gap **45** in the connector ring **40**.

(56) FIG. **7** shows a perspective view of a connection between the socket geometry **10** as described with reference to FIGS. **1** and **2**, the adapter **30** as described with reference to FIG. **5** and the connector ring **40** as described with reference to FIGS. **6A** and **6B**.

(57) First, the connector ring **40** is engaged with the socket geometry **10** such that the second surface **42** faces the end surface **12** of the socket geometry **10** and the first surface **41** faces the lower surface of the lug portion **13** of the socket geometry **10**. That is, the connector ring **40** is located at least in part between the lug portion **13** and the end surface **12** of the socket geometry **10**. In addition, the protrusion **14** of the socket geometry **10** is engaged with the recess of the connector ring **40**, thereby preventing rotation of the connector ring **40**.

(58) Second, the adapter **30** is screwed into the connector ring **40**, i.e. the threaded internal surface **43** of the connector ring **40** is engaged with the threaded outer surface **32** of the adapter **30** and a rotational motion is thereby converted into a downward motion. Thus, the adapter **30** or rather the fluid outlet **31** of the adapter **30** is being moved into the bore **11** of the socket geometry **10**. As soon as the lower surface of the fluid outlet **31** comes in contact with a bottom surface of the bore **11**, the first surface **41** of connector ring **40** is forced against the lower surface of the lug portion **13** by the rotation of the adapter **30**. Thereby, the adapter **30** is secured in the socket geometry **10**.

(59) FIG. **8** shows perspective view of a socket geometry **10** of a liquid spray gun (not shown)

according to another embodiment. In particular, the socket geometry **10** according to FIG. **8** differs from the socket geometry **10** according to FIG. **1** in that two protrusions **141**, **142** are provided at opposite sides of the end surface **12** of the socket geometry **10**.

(60) Again, the projection of the center of the lug portion **13** onto the end surface **12** of the socket geometry **10** as a reference location **23** on the end surface **12** may be defined as 0° , wherein the angular range starting from 0° extends in a clockwise direction along the end surface. In this case, the first protrusion **141** is located on the end surface **12** at 90° and the second protrusion **142** is located on the end surface **12** at 270° according to FIG. **8**. That is, the first protrusion **141** is located relative to the second protrusion **142** by 180° on the end surface **12**.

(61) FIGS. **9A** and **9B** show a perspective view and a top view, respectively, of a connector ring **40** in accordance with the socket geometry **10** of FIG. **8**. That is, the connector ring **40** of FIGS. **9A** and **9B** are configured to engage with the socket geometry **10** of FIG. **8** comprising two protrusions **141**, **142**. Therefore, the connector ring **40** of FIGS. **9A** and **9B** comprises two recesses **461**, **462** at opposite sides of the connector ring **40**. That is, according to the above definition of the angular range, the first recess **461** is located relative to the second recess **462** by 180° on the first surface **41**.

(62) In addition, the recesses **461**, **462** differ from the recess **44** shown in FIGS. **6A** and **6B** in that the recesses **461**, **462** are defined as cutouts from the first and the second surface **41**, **42**, thus, leaving respective bridge portions **421**, **422**, which comprise the first and the second surfaces **41**, **42**. In contrast, the bridge portion **441** described with reference to FIG. **6A** comprises only the first surface **41**.

(63) In other words, the recesses **461**, **462** are cutouts that reduce the width, $W_{sub.3}$, of the connector ring **40** at the recesses **461**, **462**. In contrast, the recess **44** described with reference to FIG. **6A** forms a gap in the second surface **42** and the width of the first surface **41** is uniform along the whole extend of the connector ring **40**.

(64) The recesses **461**, **462** are configured to engage with the respective protrusions **141**, **142** of the socket geometry **10** of FIG. **8**.

(65) FIG. **10** shows a perspective view of a socket geometry **10** of a liquid spray gun (not shown) according to another embodiment. In particular, the socket geometry **10** according to FIG. **10** differs from the socket geometry **10** according to FIG. **8** in that one protrusion **141** and one recess **143** are provided on the end surface **12**.

(66) The recess **143** and the protrusion **141** are located on the end surface **12** opposite each other. Taken the above-mentioned definition, i.e. the projection of the center of the lug portion **13** onto the end surface **12** of the socket geometry **10** as a reference location **23** on the end surface **12** may be defined as 0° . The angular range starts from 0° and extends in a clockwise direction along the end surface **12**. In this case, the protrusion **141** is located on the end surface **12** at 90° and the recess **143** is located on the end surface **12** at 270° according to FIG. **10**. That is, the protrusion **141** is located relative to the recess **143** by 180° on the end surface **12**.

(67) The recess **143** is shown in FIG. **10** extends on the outer surface **35** of the bore **11**. However, the recess **143** may also extend on the internal surface **36** of the bore **11**. In addition, the recess **143** may also extend over the whole width of the end surface **12**.

(68) FIG. **11** shows a perspective view of a connector ring **40** in accordance with the socket geometry **10** as described with respect to FIG. **10**. That is, the connector ring **40** comprises one protrusion **47** and one recess **461** having a bridge portion **421**. The recess **461** is configured to engage with the corresponding protrusion **141** of the socket geometry **10** of FIG. **10**. The protrusion **47** is configured to engage with the corresponding recess **143** of the socket geometry **10** of FIG. **10**.

(69) Therefore, the protrusion **47** extends only partly over the width of the second surface **42**. However, if the recess **143** on the socket geometry **10** is provided over the whole width of the end surface **12**, the protrusion **47** may also extend over the whole width of the second surface **42**. In addition, the location of the protrusion **47** on the second surface **42** may correspond to the location

of the recess **143** on the socket geometry **10**. That is, if the recess **143** on the socket geometry **10** is formed in the outer surface **35** of the bore **11**, as illustrated in FIG. **10**, the protrusion **47** may extend from the outer side **37** of the connector ring **40** at least partly over the width of the connector ring **40**. Likewise, if the recess **143** on the socket geometry **10** extends from the inner surface **36** of the bore **11**, the protrusion **47** may extend from the inner side **38** of the connector ring **40** at least partly over the width of the connector ring **40**.

(70) FIG. **12** shows a perspective view of a socket geometry **10** of a liquid spray gun (not shown) according to another embodiment. In particular, the socket geometry **10** according to FIG. **12** differs from the socket geometry **10** according to FIG. **8** in that the second protrusion **142** is located at a different position on the end surface **12**. Whereas, the first protrusion **141** is located at the same position on the end surface **12** as in FIG. **8**.

(71) In terms of the above given definition of the angular range along the end surface **12**, the first protrusion **141** is located at 90° on the end surface **12** and the second protrusion **142** is located at 180° on the end surface **12**. That is, the second protrusion **142** is located 90° further along the end surface **12** than the first protrusion **141**.

(72) FIG. **13** shows a perspective view of a connector ring **40** according to the socket geometry **10** of FIG. **12**. That is, the connector ring **40** comprises a first recess **461** and a second recess **462**, which basically correspond to the ones shown in FIGS. **9A** and **9B**. However, the second recess **462** is located at a different position on the connector ring **40**. The second recess **462** is located 90° further along the circumference of the connector ring **40** in relation to the first recess **461**. Thus, the connector ring **40** fits to the socket geometry **10** of FIG. **12**, so that the protrusions **141**, **142** can mate with the recesses **461**, **462**, respectively.

(73) FIGS. **14A-C** show different views of an alternative connector ring **40**. In contrast to the connector rings **40** described above, the connector ring **40** of FIGS. **14A-C** does not comprise a threaded internal surface. Rather, the connector ring **40** of FIGS. **14A-C** comprises a bayonet fitting **48** to engage with a corresponding pin of an adapter as further described below.

(74) In particular, the bayonet fitting **48** comprises a first cutout **52** that extends from the second surface **42** a predetermined distance towards the first surface **41** under a predetermined angle. In addition, the bayonet fitting **48** comprises a second cutout **53** that extends a predetermined distance from the first cutout in a direction parallel to the first and second surface **41**, **42**.

(75) In addition, the connector ring **40** comprises a cutout **49** along the side surface of the connector ring **40**. The cutout **49** is configured to receive the lug portion **13** of the socket geometry **10**. That is, the cutout **49** has predetermined dimensions that allow the cutout **49** to accommodate the lug portion **13**.

(76) The cutout **49** is located opposite the bayonet fitting **48** and at an equal distance from the first and second surface **41**, **42**.

(77) FIGS. **15A-B** show a respective adapter **30** comprising a pin **321**, which can be received by the bayonet fitting **48** of the connector ring **40** of FIGS. **14a-c** to retain the adapter in the connector ring **40** and therefore the fluid outlet **31** of the adapter **30** in the bore **11** of the socket geometry **10**.

(78) The pin **321** is configured to be inserted into the bayonet fitting **48** by placing the pin **321** into the first cutout **52** of the bayonet fitting **48**. The pin **321** is thus guided from the first cutout **52** in a rotational and downward motion to the second cutout **53** of the bayonet fitting **48**, where a final rotational movement has to be applied to the adapter **30** to place the pin **321** at the end portion of the second cutout **53** and thus retain the adapter **30** in the connector ring **40**.

(79) In addition to the bayonet fitting **48**, alternative fittings to retain, e.g. an adapter, in a connector ring **40** may be employed with the present invention. For example, the present invention may be used with a connector ring that comprises a friction fit in cooperation with a respective adapter, (provided the connector ring can undergo some degree of axial movement to locate and become secured etc.)

(80) It should be appreciated that any kind of recess described above and below may be used in

connection with any of the connector rings **40** described herein. The same is true for different designs of the protrusions, either on the socket geometry **10** or the connector ring **40**, described herein. That is, the specific design of a protrusion and recess is not limited to that specific embodiment it is described with. The only requirement should be that the protrusion is configured to engage with a respective recess. Also, different protrusion and/or recess designs may be used within one embodiment.

(81) In addition, the locations of the different protrusions and recesses on the end surface **12** are not limited to a particular location or configuration. That is, one or more protrusion(s) and recess(es) may be located at any location on the end surface **12** and in any relation to one another.

(82) Although the present invention has been described based on exemplary embodiments, this should not in any way restrict the scope of the invention. It will be understood by a person skilled in the art, that various modification to the exemplary embodiments are possible without departing from the scope of the present invention as defined by the claims.

(83) In addition, it is clear for a skilled person that certain features only described with reference to one specific embodiment may be combined with other features of another embodiment. Furthermore, in the claims the word “comprising” does not exclude other elements or steps, and the indefinite article “a” or “an” does not exclude a plurality. A single unit may fulfil the functions of several features recited in the claims. The terms “essentially”, “about”, “approximately” and the like in connection with an attribute or a value particularly also define exactly the attribute or exactly the value, respectively.

Claims

1. A liquid spray gun connectable to a fluid reservoir through a fluid outlet, the spray gun comprising a socket geometry arranged for engagement with a co-operating connector for releasable connecting the spray gun with the fluid outlet, wherein the socket geometry comprises a bore having an opening on one end, an end surface surrounding the bore's opening at least partially, and a lug portion spaced apart from the end surface in an axial direction parallel to a central axis of the bore, wherein the lug portion projects towards the central axis of the bore, wherein the lug portion has a lower surface being adapted to engage with the connector and to retain the connector in the axial direction, and wherein the end surface comprises a first keying geometry that is adapted to restrict rotation of the connector in at least one direction; wherein the connector comprises a connector ring with a second keying geometry.
2. The liquid spray gun of claim 1, wherein the end surface of the socket geometry is planar.
3. The liquid spray gun of claim 1, wherein the first keying geometry comprises at least one protrusion and/or at least one recess.
4. The liquid spray gun of claim 3, wherein the at least one protrusion and/or at least one recess extends in the axial direction from the end surface.
5. The liquid spray gun of claim 1, wherein a radial inner surface of the lug portion surrounding the bore is at least partially curved when viewed along an axial direction parallel to the central axis of the bore.
6. A liquid spraying apparatus comprising the spray gun according to claim 1, wherein the connector comprises: a first surface adapted to engage with the lower surface of the lug portion to retain the connector in the axial direction, and the second keying geometry that is adapted to engage with the first keying geometry to restrict rotation of the connector in at least one direction.
7. The liquid spraying apparatus of claim 1, wherein the connector ring is a C-shaped connecting ring having a gap along the circumference of the connector ring, and wherein the second keying geometry is defined by the gap of the C-shaped connector ring.
8. The liquid spraying apparatus of claim 1, wherein the second keying geometry comprises at least one recess or at least one protrusion on a second surface of the connector ring facing towards the

end surface of the socket geometry.

9. The liquid spraying apparatus of claim 1, wherein the connector ring comprises a threaded internal surface.

10. The liquid spraying apparatus of claim 9, further comprising an adapter with a threaded outer surface to engage with the threaded inner surface of the connector ring.

11. The liquid spraying apparatus of claim 10, wherein the adapter is adapted to be screwed into the connector ring and adapted to abut against the spray gun so that the connector ring is forced against the lower surface of the lug portion as the adapter is screwed into the connector ring so as to provide a fluid-tight connection between the liquid spray gun and the adapter.

12. The liquid spray gun of claim 1, wherein the lug portion and the end surface are connected by a connecting surface, wherein the spacing between the lug portion and the end surface is defined by the extension of the connecting surface in the axial direction from the end surface.

13. The liquid spray gun of claim 12, wherein the lug portion extends from the connecting surface towards the central axis of the bore at least the same length as a width of the end surface.

14. The liquid spray gun of claim 1, wherein the lug portion comprises an upper surface that faces away from the end surface and the lower surface faces towards the end surface.

15. The liquid spray gun of claim 1, wherein the connector comprises a screw wedge geometry that protrudes from an outer surface of the fluid outlet extending partially around the circumference of the fluid outlet.

16. The liquid spray gun of claim 1, wherein the socket geometry comprises a main body and the lug portion extends away from the main body.

17. The liquid spray gun of claim 1, wherein the first keying geometry is integral with the end surface, and the end surface is integral with the bore.
