

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411340
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Khaderi; Syed Khizer Rahim et al.

Modular display and sensor system for attaching to eyeglass frames and capturing physiological data

Abstract

Methods and systems for tracking vision performance use various techniques such as and not limited to electrooculography. A modular device is integrated with frames of eyeglasses that can be worn by a user. The device incorporates one or more biosensors such as EOG sensors. EOG recording may be used to estimate eyelid and eye motion, and eye gaze direction. The modular device may be fitted into new eyewear or retrofitted into existing eyewear for tracking eyes of the wearer. Systems and methods enable seamless integration of eye tracking into everyday life to maximize productivity and performance.

Inventors: Khaderi; Syed Khizer Rahim (Venice, CA), Reddy; Mohan Komalla (Fremont, CA)

Applicant: Sphairos, Inc. (Venice, CA)

Family ID: 67908447

Assignee: VIZZARIO, INC. (Venice, CA)

Appl. No.: 18/530823

Filed: December 06, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240176137 A1	May. 30, 2024

Related U.S. Application Data

continuation parent-doc US 17451195 20211018 US 11874461 child-doc US 18530823
continuation parent-doc US 16355546 20190315 US 11163156 20211102 child-doc US 17451195
us-provisional-application US 62643475 20180315

Publication Classification

Int. Cl.: **G02B27/00** (20060101); **A61B5/00** (20060101); **A61B5/0245** (20060101); **G02B27/01** (20060101)

U.S. Cl.:

CPC **G02B27/0093** (20130101); **A61B5/0245** (20130101); **A61B5/6814** (20130101); **G02B27/0172** (20130101); G02B2027/014 (20130101); G02B2027/0178 (20130101)

Field of Classification Search

CPC: G02B (27/0093); G02B (27/0172); G02B (2027/014); G02B (2027/0178); G02B (27/017); G02B (27/02); A61B (5/0245); A61B (5/6814); A61B (5/053); A61B (2562/0204); A61B (5/6803); A61B (5/0496); A61B (5/0002)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6456721	12/2001	Fukuda	N/A	N/A
7513622	12/2008	Khaderi	N/A	N/A
7621639	12/2008	Khaderi	N/A	N/A
7631968	12/2008	Dobson	N/A	N/A
7740353	12/2009	Jannard	N/A	N/A
7938539	12/2010	Khaderi	N/A	N/A
8251508	12/2011	Khaderi	N/A	N/A
9470909	12/2015	Wiley	N/A	N/A
9513482	12/2015	Abdollahi	N/A	N/A
9538912	12/2016	Khaderi	N/A	N/A
10039445	12/2017	Torch	N/A	A61B 5/18
10209773	12/2018	Khaderi	N/A	N/A
10299673	12/2018	Khaderi	N/A	N/A
10535364	12/2019	Zhong	N/A	N/A
11096570	12/2020	Khaderi	N/A	N/A
11163156	12/2020	Khaderi	N/A	N/A
2008/0239232	12/2007	Guerrero	N/A	N/A
2009/0287067	12/2008	Dorogusker	600/300	A61B 5/02055
2009/0296044	12/2008	Howell	N/A	N/A
2011/0077548	12/2010	Torch	N/A	N/A
2014/0232981	12/2013	Sugihara	N/A	N/A
2014/0253868	12/2013	Jannard	N/A	N/A
2014/0270244	12/2013	Fan	N/A	N/A
2014/0347265	12/2013	Aimone	N/A	N/A
2015/0126281	12/2014	Lewis	N/A	N/A
2015/0341717	12/2014	Song	N/A	N/A
2016/0100676	12/2015	Sandanger	224/181	A45F 5/00
2017/0026744	12/2016	Farzbod	N/A	N/A
2017/0150897	12/2016	Komaki	N/A	N/A

2017/0208289	12/2016	Feller	N/A	N/A
2017/0293356	12/2016	Khaderi	N/A	N/A
2018/0203240	12/2017	Jones	N/A	G02B 27/0179
2019/0113774	12/2018	Anderson	N/A	G02B 27/017
2019/0391638	12/2018	Khaderi	N/A	N/A
2022/0099966	12/2021	Khaderi	N/A	N/A

OTHER PUBLICATIONS

International Search Report for PCT/US19/22605, Jul. 1, 2019. cited by applicant

Written Opinion of the International Searching Authority for PCT/US19/22605, Jul. 1, 2019. cited by applicant

Primary Examiner: Earles; Bryan

Attorney, Agent or Firm: Novel IP

Background/Summary

CROSS-REFERENCE (1) The present application is a continuation application of U.S. patent application Ser. No. 17/451,195, titled “Modular Display and Sensor System for Attaching to Eyeglass Frames and Capturing Physiological Data” and filed on Oct. 18, 2021, which is a continuation application of U.S. patent application Ser. No. 16/355,546, of the same title, filed on Mar. 15, 2019, and issued as U.S. Pat. No. 11,163,156 on Nov. 2, 2021, which relies on U.S. Provisional Patent Application No. 62/643,475, entitled “Modular Sensor System for Capturing Physiological Data” and filed on Mar. 15, 2018, for priority, all of which are incorporated herein by reference in their entirety. (2) The present application is also related to U.S. patent application Ser. No. 15/482,544, entitled “Methods and Systems for Obtaining, Analyzing, and Generating Vision Performance Data and Modifying Media Based on the Vision Performance Data” and filed on Apr. 7, 2017, and U.S. patent application Ser. No. 15/482,560, entitled “Methods and Systems for Obtaining, Aggregating, and Analyzing Vision Data to Assess a Person's Vision Performance”, filed on Apr. 7, 2017, and issued as U.S. Pat. No. 10,209,773 on Feb. 19, 2019, both of which are incorporated herein by reference in their entirety.

FIELD

(1) The present specification relates generally to vision performance and more specifically to methods and systems for gathering vision performance data by integrating modular bio-sensors with eyewear.

BACKGROUND

(2) In the last few years, augmented reality and virtual reality headsets and glasses have been specially developed to enable athletes, gamers, and other individuals to perform certain tasks. While delivering an adequate augmented reality or virtual reality experience, these specially designed headsets and/or glasses have a number of drawbacks. First, they require a person to make a special investment in hardware that can only be used for augmented or virtual reality tasks. Second, people who are dependent on prescription glasses are often restricted from using these specially designed headsets or glasses or required to invest in duplicative vision wear. Third, these specially designed headsets or glasses are integrated solutions, as opposed to open hardware platforms, thereby restricting the ability of third parties to introduce accessories that may improve on individual features or may provide entirely new functionality into the specially designed headsets or glasses.

(3) Fourth, current approaches are often not flexible enough to encourage patient compliance with visual testing or sufficiently easy to use such that vision tracking can be integrated into every day tasks. Various medical tests may be performed to determine an overall fitness level of individuals, which may entail using sensors to monitor physiological parameters such as, but not limited to, biosensors for detecting signals from eyes, brain, muscles, nerves, and the like. However, these tests are often performed separately and usually when the individual is in an environment that is different from their actual work environment. Therefore, the tests may not provide accurate results, or the results may vary in an actual scenario when the individual is performing their tasks.

Furthermore, currently known methods for tracking vision performance either require devices that are bulky or require the user to sit in front of a designated device. In one example, eyeglasses, or other forms of headgear, contain integrated electrodes that provide EOG measurements. These devices are required to be worn by users while the tests are conducted. There is no cheap, easy, and reliable way to incorporate eye-tracking into everyday life.

(4) For vision wear to transform into an augmented reality, display, and computing tool, it would be preferable for different components, including display, audio, sensing, and processing components, to be developed by different companies and be sufficiently compatible to integrate into an open hardware platform. It would be further beneficial, and assist in driving innovation, if different companies can develop and commercialize individual components, whether that be the sensing, display, audio, or glasses component, with the expectation that these varied components could, when placed into operation, automatically communicate with each other.

(5) There is also a need for a hardware platform that can easily adapt to, and work with, existing vision wear, thereby allowing people with prescription eyewear to easily adopt an augmented reality solution. Finally, it is also desirable to have a plug and play platform which would allow disparate components, configured to attach to conventional eyeglasses, to automatically, and cooperatively, communicate with each when placed into operation.

SUMMARY

(6) The following embodiments and aspects thereof are described and illustrated in conjunction with systems, tools and methods, which are meant to be exemplary and illustrative, and not limiting in scope. The present application discloses numerous embodiments.

(7) The present specification discloses a system for sensing physiological data of a user and configured to attach to at least one arm of an eyeglasses frame, the system comprising: a housing comprising a rigid material, wherein the rigid material defines a channel configured to receive the at least one arm; a processor positioned within the rigid material of the housing; a microphone positioned on an exterior surface of the rigid material; a display attached to the rigid material by a first flexible arm; and a sensor, such as a bone conduction sensor, transducer, vibration sensor, or actuator, attached to the rigid material by a second flexible arm.

(8) Optionally, the channel is partially open.

(9) Optionally, the rigid material of the housing is configured to be positioned on the at least one arm such that the at least one arm is positioned between at least 50% of the rigid material and the user's head.

(10) Optionally, the system further comprises an elastic material attached to the rigid material and configured to enclose the channel.

(11) Optionally, the display is dimensioned to be smaller than one lens of the eyeglasses.

(12) Optionally, the system further comprises a wired pathway incorporated into each of the first flexible arm and the second flexible arm.

(13) Optionally, the system further comprises an electrooculography sensor configured to be attached to a bridge of the eyeglasses frame and be in electrical communication with the processor. Optionally, the electrooculography sensor comprises at least two electrodes configured to physically contact a portion of the user's face.

(14) Optionally, the microphone is positioned on the exterior surface of the rigid material that is

closest to a front portion of the eyeglasses frame.

(15) Optionally, the processor is configured to be in wireless communication with a remotely located server.

(16) The present specification also discloses a kit comprising a first module and a second module, each configured to attach to portions of an eyeglasses frame and configured to sense physiological data of a user, the kit comprising: the first module comprising: a first housing made of a rigid material, wherein the rigid material defines a first channel configured to receive a first arm of the eyeglasses frame; a first processor positioned within the rigid material of the first housing; a first microphone positioned on an exterior surface of the rigid material; a first display attached to the rigid material by a first flexible arm; and a first bone conduction sensor attached to the rigid material by a second flexible arm; and the second module, physically separate from the first module, comprising an electrooculography sensor configured to be attached to a bridge of the eyeglasses frame and be in electrical communication with the first processor.

(17) Optionally, the first channel is partially open.

(18) Optionally, the rigid material of the first housing is configured to be positioned on the first arm such that the first arm is positioned between at least 50% of the rigid material and the user's head.

(19) Optionally, the system further comprises a first elastic material attached to the rigid material and configured to enclose the first channel.

(20) Optionally, the first display is dimensioned to be smaller than a first lens in the eyeglasses frame.

(21) Optionally, the system further comprises a wired pathway incorporated into each of the first flexible arm and the second flexible arm.

(22) Optionally, the electrooculography sensor comprises at least two electrodes configured to physically contact a portion of the user's face.

(23) Optionally, the first microphone is positioned on the exterior surface of the rigid material that is closest to a front portion of the eyeglasses frame.

(24) Optionally, the system further comprises a third module, physically separate from the first module and the second module, wherein the third module comprises: a second housing made of a rigid material, wherein the rigid material defines a second channel configured to receive a second arm of the eyeglasses frame; a second processor positioned within the rigid material of the second housing; a second microphone positioned on an exterior surface of the rigid material; a second display attached to the rigid material by a third flexible arm; and a second bone conduction sensor attached to the rigid material by a fourth flexible arm.

(25) Optionally, the second channel is partially open.

(26) Optionally, the rigid material of the second housing is configured to be positioned on the second arm such that the second arm is positioned between at least 50% of the rigid material and the user's head.

(27) Optionally, the system further comprises a second elastic material attached to the rigid material and configured to enclose the second channel.

(28) Optionally, the second display is dimensioned to be smaller than a second lens in the eyeglasses frame.

(29) Optionally, the system further comprises a wired pathway incorporated into each of the third flexible arm and the fourth flexible arm.

(30) Optionally, the second microphone is positioned on the exterior surface of the rigid material that is closest to a front portion of the eyeglasses frame.

(31) The present specification discloses a modular system for sensing physiological data of a user, the system comprising: a wearable headgear configured to be worn by the user; a first component configured to be attached to said wearable headgear and sense a first physiological data of the user; a second component configured to be attached to said wearable headgear and sense a second physiological data of the user; a processor for receiving and processing said first and second

physiological data; wherein said second component is different and separate from said first component and wherein said first component and said second component are configured to communicate with each other and with said processor.

(32) Optionally, said first component or second component comprises a biometric sensor for tracking eye movements of the user.

(33) Optionally, said first component or second component comprises a sensor, such as a bone conduction sensor.

(34) Optionally, the modular system further comprises at least one display.

(35) Optionally, the modular system further comprises a microphone.

(36) Optionally, said wearable headgear comprises eyewear. The eyewear may comprise any one of eyeglasses, sunglasses, and goggles. The first component or second component may be attached to a sleeve configured to be slid over an arm of said eyewear. The first component or second component may be configured to be positioned under a bridge of said eyewear. The first component or second component may be configured to be positioned along a nose pad of said eyewear.

(37) Optionally, said first component and said second component communicate wirelessly with one another.

(38) Optionally, the modular system further comprises a cable connecting said first component to said second component to enable communication between said first component and said second component.

(39) The present specification also discloses a method of operating a modular system for sensing physiological data of a user, the method comprising: attaching a first component to a wearable headgear of said system; activating said first component; receiving data collected or processed by said first component; attaching a separate component to said wearable headgear; activating said second component, wherein, with said activation, said second component communicates with said first component; and receiving data collected or processed by said first component and by said second component; wherein second component is different and separate from said first component.

(40) Optionally, activation of said first component includes switching said first component on such that said first component communicates with a processor of said system and establishes an on-line connection.

(41) Optionally, activation of said second component includes switching said second component on such that said second component communicates with said first component and with said processor and establishes an on-line connection.

(42) Optionally, said first component and said second component communicate wirelessly with one another.

(43) Optionally, said system further comprises a cable connecting said first component to said second component to enable communication between said first component and said second component.

(44) Optionally, said second component communicates automatically with said first component when said second component is activated.

(45) Optionally, said method further includes manually linking said second component to said first component to enable said second component to communicate with said first component.

(46) Optionally, said wearable headgear comprises eyewear and said first component or said second component comprises a biometric sensor for tracking eye movements of the user.

(47) The aforementioned and other embodiments of the present specification shall be described in greater depth in the drawings and detailed description provided below.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) These and other features and advantages of the present specification will be further appreciated, as they become better understood by reference to the detailed description when considered in connection with the accompanying drawings, wherein:
- (2) FIG. 1A is a schematic drawing of a modular device that may be integrated with an eyeglass frame, in accordance with some embodiments of the present specification;
- (3) FIG. 1B is a schematic drawing of a sliding sleeve with an attached or integrated device, over an arm of an eyeglass frame, in accordance with some embodiments of the present specification;
- (4) FIG. 2A is another drawing of a modular device that may be integrated with an arm of a frame, in accordance with some embodiments of the present specification;
- (5) FIG. 2B is another view of the modular device of FIG. 2A, in accordance with some embodiments of the present specification;
- (6) FIG. 3 is an overview of an exemplary frame incorporating certain embodiments of the present specification;
- (7) FIG. 4A is an illustration of a component within a modular device, which may be removably positioned on an arm of an eyeglass frame, in accordance with some embodiments of the present specification;
- (8) FIG. 4B is a drawing of an EOG sensor block and associated components, which may be positioned under a bridge of an eyeglass frame as shown in FIG. 3, in accordance with some embodiments of the present specification;
- (9) FIG. 4C illustrates components of a display, which may adorn at least a portion of a lens portion of a pair of eyeglasses as shown in FIG. 3, in accordance with some embodiments of the present specification;
- (10) FIG. 5A illustrates an exemplary overview of a communication network within which embodiments in accordance with the present specification may be deployed;
- (11) FIG. 5B is a flowchart illustrating one embodiment of a method of using a modular sensing system of the present specification;
- (12) FIG. 6 is a flowchart illustrating a method of using an exemplary system in accordance with the embodiments of the present specification; and
- (13) FIG. 7 is an illustration of a wearable system provided in a kit in accordance with some embodiments of the present specification.

DETAILED DESCRIPTION

- (14) In various embodiments, the present specification provides methods and systems for tracking vision performance, using various techniques such as and not limited to electrooculography (EOG). In embodiments, a modular device is integrated with the frame of a pair of eyeglasses that can be worn by a user. In some embodiments, the device incorporates one or more biosensors such as EOG sensors. EOG recording may be used to estimate eyelid and eye motion, and/or eye gaze direction. The modular device may be retrofitted onto conventional eyewear for tracking the eyes of the wearer. Embodiments of the present specification provide systems and methods to enable seamless integration of eye tracking into everyday life to maximize productivity and performance.
- (15) In various embodiments, the methods and systems of the present specification include or use sensing devices disclosed in US Patent Application Publication Number 2017-0293556 A1, entitled “Methods and Systems for Obtaining, Analyzing, and Generating Vision Performance Data and Modifying Media Based on the Vision Performance Data” and filed on Apr. 7, 2017 as U.S. patent application Ser. No. 15/482,544, and U.S. Patent Application Publication Number 2017-0290504 A1, entitled “Methods and Systems for Obtaining, Aggregating, and Analyzing Vision Data to Assess a Person's Vision Performance” filed on Apr. 7, 2017 as U.S. patent application Ser. No. 15/482,560, and issued as U.S. Pat. No. 10,209,773 on Feb. 19, 2019, both of which are herein incorporated by reference in their entirety.

(16) The present specification is directed towards multiple embodiments. The following disclosure is provided in order to enable a person having ordinary skill in the art to practice the specification. Language used in this specification should not be interpreted as a general disavowal of any one specific embodiment or used to limit the claims beyond the meaning of the terms used therein. The general principles defined herein may be applied to other embodiments and applications without departing from the spirit and scope of the specification. Also, the terminology and phraseology used is for the purpose of describing exemplary embodiments and should not be considered limiting. Thus, the present specification is to be accorded the widest scope encompassing numerous alternatives, modifications and equivalents consistent with the principles and features disclosed. For purpose of clarity, details relating to technical material that is known in the technical fields related to the specification have not been described in detail so as not to unnecessarily obscure the present specification.

(17) In the description and claims of the application, each of the words “comprise” “include” and “have”, and forms thereof, are not necessarily limited to members in a list with which the words may be associated.

(18) It should be noted herein that any feature or component described in association with a specific embodiment may be used and implemented with any other embodiment unless clearly indicated otherwise.

(19) In various embodiments, systems and methods of the present specification provide a modular device that may be integrated in to different types of wearable devices such as and not limited to headgears, eyewear, and earphones. Headgear may include wearable objects that may be wrapped around the head, such as hats, helmets, headphones, and masks. Eyewear may include any apparatus through which the eyes can peer, such as eyeglasses, sunglasses, goggles, or others.

(20) FIGS. 1A and B illustrate an exemplary overview of an embodiment of a modular device **102** that may be integrated with a frame **100** of a pair of eyeglasses **104**. Modular device **102** may be integrated with frame **100** by attaching device **102** on at least one arm **106** of frame **100**. In embodiments of the present specification, device **102** comprise a housing **107** that encompasses a circuit comprising multiple bio-sensors and related components. The housing **107** is an elongated structure having one portion thereof being made of a rigid plastic, metallic or glass structure **108b** and another portion thereof being made of an elastic material **108a**. In one embodiment 25% to 75% of the housing approximately comprises the rigid plastic, metallic or glass structure **108b** and while 75% to 25% of the housing approximately comprises the flexible elastic material **108a**. Regardless of the specific rigid to clastic composition, the rigid and flexible portions of the housing **107** are connected to form a length that is greater than its width and to have an internal, enclosed lumen **109** that is dimensionally sized to receive an arm **106** of the frame **100** and hold the arm **106** in place via a friction fit.

(21) Frame **100** may be a conventional frame that is worn by its user on a day-to-day basis. In embodiments, the sleeve **108a** is stretchable and is configured to enable the device **102** to slide onto, and fit snugly on, frame arm **106**. In some embodiments, the rigid portion **108b** of device **102** is attached to sleeve **108a** with an adhesive. In some embodiments, the adhesive is glue. In some exemplary embodiments, sleeve **108a** is manufactured using one or more of polyurethane, neoprene, and silicone. In one embodiment, the rigid plastic, metallic or glass structure **108b** is configured such that, upon being positioned around the arm **106**, it is positioned against the wearer's head, and the flexible elastic material **108a** is configured to be on the opposing side such that the rigid plastic, metallic or glass structure **108b** and arm **106** are positioned between the flexible elastic material **108a** and the wearer's head. In another embodiment, the flexible elastic material **108a** is configured such that, upon being positioned around the arm **106**, it is positioned against the wearer's head and the rigid plastic, metallic or glass structure **108b** is configured to be on the opposing side such that the flexible elastic material **108a** and arm **106** are positioned between the rigid plastic, metallic or glass structure **108b** and the wearer's head.

(22) FIG. 1B illustrates an exemplary manner of sliding housing **107** over arm **106**. Housing **107** may be slid from the open end of arm **106** and positioned centrally over the straight portion of arm **106**. In embodiments, material of sleeve **108a** is elastic and stretchable, and can therefore adapt to different sizes of arms **106** of different types of frames **100**. Sleeve **108** may also be manufacture at different sizes with elastic and stretchable material to enhance their ability to adopt to different sizes of arms **106** of frames **100**. In another embodiment the housing may be made of 100% rigid plastic, metallic or glass structure and be sized to slide over, clasp on to (by closing two portions of the rigid plastic over the arm), or otherwise connect to the arm, and remain in place via friction fit.

(23) Referring back to FIG. 1A, in some embodiments, at least one of the lenses of the eyeglasses **104** is overlaid with a display **110** dimensioned to fit over, but not exceed the entire circumference or periphery of a lens of the eyeglasses **104**. Display **110** may incorporate a mini-projector to transmit light or any other type of visuals to a retina, fovea, and optic nerve, of the eye of wearer of frame **100**, thereby allowing the wearer to see a digital image layered on top of their actual eye sight. In one embodiment, display **110** covers a portion of a lens **104**. In some embodiments, display **110** covers 5-80% of the region of lens **104**, although preferably in a range of 10% to 30% and even more preferably around 20%. In embodiments, display **110** is in communication with device **102**. Display **110** may communicate with device **102** using a flat ribbon cable, or any other wired or wireless communication means that may enable communication of visual and/or optical data between display **110** and device **102**. In embodiments, display **110** may be modularly integrated with frame **100**, thereby allowing a user to attach and remove display **110**. In some embodiments, display **110** may be touch-sensitive so that it can be made operational by tapping sleeve **108** that embeds device **102**. In some embodiments, a button is positioned on sleeve **108b** and attached to device **102**, such that switching on the button activates display **110**. Wearer of frame **100** may operate display **110** by touching or pressing the button on sleeve **108b**.

(24) FIG. 2A illustrates another exemplary embodiment of a modular device **202** that may be integrated with an arm **206** of a frame **200**. A display **210** covers a portion of at least one of the lenses **204**. Display **210** may be similar to display **110** described in context of FIGS. 1A and 1B. The illustrated embodiment of FIG. 2A shows a housing **230** that encases modular device **202**. Housing **230** has a narrow opening **212** along one side. Housing **230** may be provided in different sizes with openings **212** of different sizes to accommodate arms **206** of different types of frames **200**. In some embodiment, housing **230** is made from a stretchable material so as to adjust according to the size of arm **206**. Arm **206** may be slipped through this opening **212**, such that device **202** is attached to arm **206**. In embodiments, opening **212** is sufficiently large to allow passage of an arm of an eyeglass frame to pass through, and sufficiently narrow to enable device **202** to stay positioned on a central straight portion of arm **206**.

(25) FIG. 2B illustrates an exemplary view of modular device **202** of FIG. 2A. The figure also shows additional components, such as a sensor **214** and a microphone **216**. The sensor **214** may be a bone conduction sensor, a vibrational sensor, an actuator, transducer, or any sensor configured to detect and measure vibrations.

(26) In some embodiments, additional components sensor **214** and microphone **216**, and any other components or devices may be modularly attached to modular device **202**. In embodiments, the additional components provide added data for analyzing physiological parameters of a user wearing frame **200**. In some embodiments, device **202** and components **210**, **214**, and **216** communicate with each other. In some embodiments, device and components **202**, **210**, **214**, and **216** communicate through a common cable that connects them. In some embodiments, a flat ribbon cable connects all of device **202** and components **210**, **214**, and **216**. In some embodiments, a first flat ribbon cable **211** connects the display module **210** to the device **202** and a second flat ribbon cable **213** connects the sensor **214** to the device **202**. In some embodiments, the device **202** and components **210**, **214**, and **216** communicate wirelessly.

(27) More specifically, in one embodiment, the modular device **202** comprises a housing **207** which

is made up of a rigid portion **208b**, configured to be positioned on the side opposing the wearer's head. This rigid portion **208b** may form an open channel **209** into which an arm **206** of the frame **200** may be placed and secured through a friction fit. Optionally, the channel **209** may be enclosed by adding a flexible elastic or sleeve portion (shown in FIGS. **1A** and **1B**). Within the rigid portion **208b** of the housing, a processor and energy source, such as a preferably rechargeable battery, is encased. The processor is in data communication with a sensor **214** wirelessly or via a wired connection **213**. The sensor **214** is preferably attached to the housing via a solid, yet flexible, arm that can also function as a wired data communication path **213**. The processor is also in data communication with a display module **210** wirelessly or via a wired connection **211**. The display **210**, as previously described above, is preferably attached to the housing via a solid, yet flexible, arm that can also function as a wired data communication path **211**. Operationally, the two arms **211**, **213** may be manipulated by the wearer to insure that the sensor **214** is appropriately positioned on the wearer's head, such as on the wearer's temple or behind the wearer's ear, and that the display **210** is appropriately positioned over the wearer's lens.

(28) A button, trackpad, or switch **217** positioned on the exterior surface of the rigid portion **208b** is in data communication with the processor positioned within the housing **207** and, when manipulated, serves to activate, via the processor, the one or more sensors, including the bone conduction sensor **214**, and the EOG sensors, as further described below, the display, data transfers, acquisitions, transmissions, or other manipulations, and the microphone **216** which is also positioned on an exterior surface of the housing **207**, preferably at an end of the housing **207** closest to the wearer's mouth.

(29) It should be appreciated that, for the modular devices to not put excessive weight on the frames, it is important for them to be very light. As such, it is preferable for the display and bone conduction sensor (or vibrational sensor or transducer) to not be integrated into a single housing with the processor and microphone. Rather, the modular devices are designed to have a small form factor and fit on the arm of a frame with the display and sensor extending therefrom via a lightweight member that permits the flexible adjustment of each of the display and the sensor relative to the wearer's head.

(30) FIG. **3** illustrates an overview of a modular sensing system **300** for capturing physiological data comprising an exemplary frame **301** incorporating some of the embodiments in accordance with the present specification. Modular devices **302a** and **302b** are each positioned on a right arm **306a** and a left arm **306b**, respectively, of frame **301**. It should be appreciated that, in a kit form, a right and left version of the devices **302a** and **302b** would be included, with one having a display and sensor positioned in a manner that is flipped relative to the other. In embodiments, modular device **302a** and **302b** are removably positioned over arms **306a** and **306b** of frame **301**. A right eyeglass lens **302a** and a left eyeglass lens **302b** are each layered over with a display **310a** and **310b**, respectively.

(31) In some embodiments, an EOG sensor block **320** is positioned under a bridge **318**. In some embodiments, block **320** includes a pair of EOG sensors that are positioned under bridge **318** with one sensor on either side of bridge **318**. In some embodiments, EOG sensor block **320** is positioned on or near the nose pads of frame **301**. Block **320** is modularly attached to frame **301** and communicates with modular device **302**. In some embodiments, block **320** is in wireless communication with device **302**. In some embodiments, the form of wireless communication between block **320** and device **302** is Bluetooth Low Energy (BLE).

(32) FIG. **4A** illustrates exemplary components within a modular device **402**, which may be removably positioned on an arm of a frame, in accordance with some embodiments of the present specification. Modular device **402** is equivalent to device **102** of FIG. **1A** and device **202** of FIG. **2A**. In some embodiments, the components include at least include a battery **440**, a PCB **442**, a sensor **444**, such as a bone conduction device, and power and data channels **446**. PCB **442** may provide electronics that enables communication between device **402** and another devices, such as a

phone, laptop, tablet, or remote server. In an example, the communication between device **402** and the phone is performed using Bluetooth LTE. Power and data channels **446** may also connect with an EOG sensor block(s) **420**, equivalent to block **320** of FIG. **3**. Power and data channels **446** are, in an embodiment, included within a flat ribbon cable which, in turn, may be incorporated into one or more flexible arms, as described above in relation to elements **211** and **213**.

(33) FIG. **4B** illustrates exemplary components of an EOG sensor block **420**, which may be positioned under a bridge of a frame as shown in FIG. **3** by adhesive, a snap fit, or a mating, in accordance with some embodiments of the present specification. Power and data channels **446** connect device **402** and block **420** and provide power to charge battery **448** that powers block **420**. Block **420** is shown to connect at least two sensors **450a** and **450b** that are respectively positioned on a left and a right side under a nose bridge of a frame such as frame **100/200/301**. In some embodiments, sensors **450a** and **450b** include dry electrodes that are configured to contact the wearer's skin at a specific location on their face/around their eyes.

(34) FIG. **4C** illustrates exemplary components of a display **410**, which may be positioned in front of a portion of the eyeglasses of a frame as shown in FIG. **3**, in accordance with some embodiments of the present specification. In embodiments, data collected by sensors **450a** and **450b** of EOG block **420** is communicated to PCB **442**, enabling dynamic change of the display projected by display **410**, based on the data. Power and data channels **446** connect display **410** with device **402** and block **420** and provide the path for data communication. In some embodiments, display **410** includes a low power micro-LED display **452** to project display data.

(35) Referring to FIGS. **3** through **4C** simultaneously, in various embodiments, a modular sensing system **300** for capturing physiological data may include eyeglasses with frames **301**, and one or more sensing components, such as modular devices **302a**, **302b**, **402**, and sensor blocks **320**, **420**. The system **300** may further include one or more displays, such as displays **310a**, **310b**, **410**. The sensing components may communicate, through wired or wireless connections, with each other and/or with a processor located within the system **300** or remotely, such as on-line, to generate data and display said data on said one or more displays. A network for enabling communication of the system components and processing and display of sensed data is described further with reference to FIG. **5A**. The system **300** of the present specification provides a plug and play platform which allows for disparate components, configured to be attached to headgear, to automatically and cooperatively communicate with one another when placed in operation. In various embodiments, the components include those disclosed in U.S. Patent Application Publication Numbers 2017-0293556 A1 and 2017-0290504 A1. As new sensing components are developed, they may be added to the modular system and communicate with the pre-existing system and components.

(36) FIG. **5A** illustrates an exemplary overview of a communication network **500** within which embodiments in accordance with the present specification may be deployed. In embodiments, a frame **502**, in accordance with the embodiments of the frame described in context of FIG. **1A**, communicates with a computing system **504**. In one embodiment, computing system **504** is a sensory data exchange that collects and processes user data communicated by frame **502**. System **504** may include software elements that may be executed in association with hardware elements. Examples of software elements may include software applications (apps), or any other types of software elements that may contribute to calculation and presentation of insights, recommendations, and/or notifications and alerts for the user of frame **502**. In embodiments, a collection of software elements **506** work together to analyze data collected by system **504** to determine fitness levels of the user.

(37) While one part **507** of the software **506** may calculate different parameters that reflect on a user's fitness level, another part **509** may collect this information and associate it with various classifications, such as demographics, for the purpose of deep learning. Collected data may be tagged with information about the user, the software application, the media presented to the user, the session during which the user interacted with the system, the biometric signals detected by one

or more sensors including EOG sensors, or any other data. Processed/transformed data is provided to a machine learning system. In embodiments, machine learning (ML) system processes transformed data using one or more known and customized data models, such as but not limited to naïve Bayes, decision trees, and others.

(38) A combination of hardware and software elements **508** may be used to present the results of the analysis. The results may be provided in the form of insights, recommendations, alerts and/or notifications, or in any other form that may be useful to reflect the visual fitness of the user. In some embodiments, elements **508** may be used to reflect the visual fitness data of a group of users.

(39) FIG. 5B is a flowchart illustrating one embodiment of a method of using a modular sensing system of the present specification. The method includes modularly or serially adding a different, disparate, stand-alone new component to the system and having the new component attach to the headgear and communicate on-line with existing components. Prior art systems are integrated and do not allow the addition of new components. At step **520**, a first component is attached to a headgear. In some embodiments, the headgear comprises a pair of eyeglasses of a modular sensing system. The first component is activated at step **522**. In some embodiments, activation of the first component includes switching the first component on wherein, once activated, the first component communicates wired or wirelessly with a processor of the system to establish an on-line connection. The system receives data collected or processed from the first component at step **524**. At step **526**, a second component is attached to the headgear. The second component is activated at step **528**, wherein, with said activation, the second component communicates with the first component. In some embodiments, activation of the second component involves switching the second component on such that the second component communicates wired or wirelessly with the first component and the processor of the system via an on-line connection. In some embodiments, the connection is established automatically when the second component is activated. In other embodiments, further intervention is required to enable the second component to communicate with the first component, such as manually linking the two components. The system then receives data collected or processed from both the first component and the second component at step **530**.

(40) Referring to the flowchart of FIG. 6, a method of using an exemplary system in accordance with the embodiments of the present specification is described. In embodiments, the wearable system of the present specification is provided in the form of a kit. The kit may be available to a user for assembling, wearing, and operating at a suitable and convenient time. Components of the kit may be assembled by the user on a frame of eyeglasses already worn by the user. Alternatively, the kit may include a frame of eyeglasses that can be worn by the user. The kit may include at least one or two housings manufactured using a rigid material. Each housing is in the form of a channel with at least one open end to receive an arm of the eyeglasses frame. In some embodiments, clastic material is attached to the rigid material of each housing and configured to enclose the channel. At **602**, the user places a first housing, comprising a first module, over a first arm of the frame. At **604**, the user places a second housing, comprising a second module, over the other or second arm of the frame. In embodiments, each arm is positioned between at least 50% of the rigid material of each housing and the user's head when the user wears the eyeglasses frame. In embodiments, each housing encases a processor. Additionally, each housing is attached to a microphone, which may be positioned on an exterior surface of the housing. A bone conduction sensor is also attached to each housing with a flexible arm extending to each housing from each bone conduction sensor. A display for each lens of the eyeglasses frame is also attached through flexible arms to each housing. Wired pathways are incorporated into all the flexible arms so as to electrically connect the housings to their corresponding displays and bone conduction sensors.

(41) The kit further includes an EOG sensor module with at least one or two EOG sensor electrodes configured to physically contact portions of the user's face once the user wears the frame after assembling the kit's components. At **606**, the user attaches the EOG sensor (third module) to a nose bridge between the eyeglasses frame. The EOG sensor module may be attached such that the sensor

electrodes are positioned just below the bridge on either side of the bridge, between the eyeglasses frame, and are in a position to contact user's face on either side of the frame's nose bridge once the user wears the frame. The EOG sensor module is in electrical communication with the processors within each housing.

(42) At **608**, the user wears (puts on) the eyeglasses frame with the assembled components. In some cases, the user may be required to, and therefore, adjust the position of the arms of the frame and the bone conduction sensors with each housing on each arm. The sensors are adjusted so that each bone conduction sensor is in physical contact with the head of the user. At **610**, the user adjusts the displays to be comfortably positioned over each lens. At **612**, the user adjusts the EOG sensor electrodes so that they are comfortably positioned on and are in physical contact with the user's face. At **614**, the user enables operation of the assembled system. In some embodiments, at least one button is provide on at least one housing to enable and/or disable operation of the system. The user presses the at least on button to turn the system on. Once the system is enabled, the processor within the housing communicates with each module and sensor in order to collect and process data, and to control information relayed through the displays. In some embodiments, the processor also wirelessly communicates with a computing system that presents the data and its analysis through a graphical user interface. In embodiments, upon start up, the processor is preconfigured to connect with, and communicate wirelessly with, all sensors and modules.

(43) FIG. 7 is an illustration of a wearable system provided in a kit **700** in accordance with some embodiments of the present specification. In various embodiments, the kit **710** comprises a first module **702a**, a second module **720**, and a third module **702b**. The first module **702a** is similar to modular device **302a** of FIG. 3 and modular device **202** of FIG. 2B and is configured to be received on a right arm of a glasses frame. The third module is similar to modular device **302b** of FIG. 3 and modular device **202** of FIG. 2B and is configured to be received on a left arm of a glasses frame.

(44) In some embodiments, each of the first and third modules **702a**, **702b** comprises a housing with a processor within. In some embodiments, each of the first and third modules **702a**, **702b** further comprises at least one or any combination of a microphone **716a**, **716b**, display **710a**, **710b**, and bone conduction sensor **714a**, **714b**, which may be connected to the modules **702a**, **702b** via cables or arms. The second module **720** comprises an electrooculography sensor and is similar to EOG sensor block **420** of FIG. 4B. The second module **720** is configured to attach to a bridge of a glasses frame and be in electrical communication with the processors of the first and third modules **702a**, **702b**. In some embodiments, the second module **720** includes power and data channels **746** to connect the first and third modules **702a**, **702b** to the second module **720** and provide power to a charge battery **748** that powers the second module **720**. In some embodiments, the second module **720** comprises at least two sensors **750a** and **750b** that are respectively positioned on a left and a right side under a nose bridge of a frame. First, second, and third modules **702a**, **720**, and **720b** are physically separate from each other but are configured to automatically wirelessly communicate with each other upon start up. Alternatively, the first, second, and third modules **702a**, **720**, and **720b** may be connected to each other via physical wires. Operation of the kit **700** is similar to that described with respect to FIG. 6. In some embodiments, the kit **700** comprises only the first module **702a** and the third module **720** with the remaining characteristics being the same as above.

(45) In some embodiments, EOG sensors detect closed or partially closed eyes, and indicate fatigue. Closed or partially closed eyes, especially for extended periods, can be a sign of fatigue. Prolonged periods of (mostly) closed eyes can be considered indicative of fatigue. For example, when the proportion of time that the eyes are at least 50% open is less than 75% ($P_{\text{sub.eyes open}}(\text{where } p_{\text{sub.both eyes open}} \geq 50\%) < 0.75$), the system considers a user to be fatigued.

(46) One visible sign of transition to fatigue is determined through eye movements. In an embodiment, the system determines decrease in saccade velocity and magnitude, and decrease in frequency of fixations, to be a sign of slow eye movements, and therefore a sign of an onset of or

increase in fatigue.

(47) Also, in an embodiment, transitions to shorter and higher frequency of blinks is considered as an indication of fatigue onset. In this condition, user's eyes begin to close, partially or completely, and blinking goes from the normal pattern to a series of small, fast rhythmic blinks. In another embodiment, sudden vertical eye movements is considered as indicative of fatigue. A user transitioning to a state of fatigue may display a depth of gaze that drifts out towards infinity (zero convergence) and eye movements that may no longer track moving stimuli or may not respond to the appearance of stimuli. Therefore, in another embodiment, a 3-D depth of gaze towards infinity for extended periods is considered as indicative of fatigue.

(48) In additional embodiments of the present specification, physiological sensors may be used to determine physiological indication of fatigue and other parameters that determine vision fitness of a user.

(49) In an embodiment, significant decreases in heart rate and/or body temperature is associated with sleep, and is considered as indication of fatigue when the user displays these signs when awake.

(50) In an embodiment, increased energy in low frequency EEG signals (for example, slow-wave sleep patterns) are interpreted as a signal of fatigue. For example, a trade-off where low frequency (<10 Hz) EEG energy increases and high frequency (≥ 10 Hz) EEG energy decreases is an indication of fatigue.

(51) Transitions to fatigue may be determined from changes in behavior and other states over time, based on a significant deviation from an established baseline. Transitional measures of fatigue may be observed through visible signs as well as through behavioral measures.

(52) In embodiments, system 504 uses machine learning to be able to discover new correlations between different types of measures such as physiological and/or visible measures. The system 504 may correlate all available measures and look for trends and/or enable modifications to media or vision performance analysis based on identified trends. In some embodiments, trends are correlated to determine a person's visual fatigue. United States Patent Publication Number 20170293356, entitled "Methods and System for Obtaining, Analyzing, and Generating Vision Performance Data and Modifying Media Based on the Vision Performance Data", filed on Oct. 12, 2017 is herein incorporated by reference in its entirety. In addition, United States Patent Publication Number 20170290504, entitled "Methods and System for Obtaining, Aggregating, and Analyzing Vision Data to Assess a Person's Vision Performance", filed on Oct. 12, 2017 is also herein incorporated by reference in its entirety.

(53) The above examples are merely illustrative of the many applications of the system and method of present specification. Although only a few embodiments of the present specification have been described herein, it should be understood that the present specification might be embodied in many other specific forms without departing from the spirit or scope of the specification. Therefore, the present examples and embodiments are to be considered as illustrative and not restrictive, and the specification may be modified within the scope of the appended claims.

Claims

1. A system for sensing physiological data of a user and configured to attach to at least one arm of an eyeglasses frame, the system comprising: a linear-shaped housing comprising a rigid material, wherein the rigid material defines a channel configured to receive the at least one arm and wherein a majority of the linear-shaped housing extends along a length of the at least one arm; a processor positioned within the rigid material of the housing; a microphone positioned on an exterior surface of the rigid material; and a display attached to the rigid material by a first arm, wherein the display is configured to be controlled by tapping said linear-shaped housing.

2. The system of claim 1 wherein the channel is partially open.

3. The system of claim 1 wherein the rigid material of the housing is configured to be positioned on the at least one arm such that the at least one arm is positioned between at least 50% of the rigid material and the user's head.
4. The system of claim 1 further comprising an elastic material attached to the rigid material and configured to enclose the channel.
5. The system of claim 1 wherein the display is dimensioned to be smaller than one lens of the eyeglasses.
6. The system of claim 1 further comprising a second flexible arm attached to a sensor and a wired pathway incorporated into each of the first flexible arm and the second flexible arm.
7. The system of claim 1 further comprising an electrooculography sensor configured to be attached to a bridge of the eyeglasses frame and be in electrical communication with the processor.
8. The system of claim 7 wherein the electrooculography sensor comprises at least two electrodes configured to physically contact a portion of the user's face.
9. The system of claim 1 wherein the microphone is positioned on the exterior surface of the rigid material that is closest to a front portion of the eyeglasses frame.
10. The system of claim 1 wherein the processor is configured to be in wireless communication with a remotely located server.
11. A kit comprising a first module and a second module, each configured to attach to portions of an eyeglasses frame and configured to sense physiological data of a user, the kit comprising: the first module comprising a first housing made of a rigid material, wherein the rigid material defines a first channel configured to receive a first arm of the eyeglasses frame and wherein a majority of the first linear-shaped housing extends along a length of the first arm; a first processor positioned within the rigid material of the first housing; a first microphone positioned on an exterior surface of the rigid material; and a first display attached to the rigid material by an arm, wherein the display is configured to be controlled by tapping said linear-shaped housing; and the second module, physically separate from the first module, comprising an electrooculography sensor configured to be attached to a bridge of the eyeglasses frame and be in electrical communication with the first processor.
12. The kit of claim 11 wherein the first channel is partially open.
13. The kit of claim 11 wherein the rigid material of the first housing is configured to be positioned on the first arm such that the first arm is positioned between at least 50% of the rigid material and the user's head.
14. The kit of claim 11 further comprising a first elastic material attached to the rigid material and configured to enclose the first channel.
15. The kit of claim 11 wherein the first display is dimensioned to be smaller than a first lens in the eyeglasses frame.
16. The kit of claim 11 further comprising a second flexible arm attached to a sensor and a wired pathway incorporated into each of the first flexible arm and the second flexible arm.
17. The kit of claim 11 wherein the electrooculography sensor comprises at least two electrodes configured to physically contact a portion of the user's face.
18. The kit of claim 11 wherein the first microphone is positioned on the exterior surface of the rigid material that is closest to a front portion of the eyeglasses frame.
19. The kit of claim 11 further comprising a third module, physically separate from the first module and the second module, wherein the third module comprises a second housing made of a rigid material, wherein the rigid material defines a second channel configured to receive a second arm of the eyeglasses frame; a second processor positioned within the rigid material of the second housing; a second microphone positioned on an exterior surface of the rigid material; and a sensor attached to the rigid material by a second arm, wherein the sensor is at least one of a bone conduction sensor, a vibrational sensor, or a transducer.
20. The kit of claim 19 wherein the second channel is partially open.

