

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411349
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Aschwanden; Manuel et al.

Optical device for enhancing resolution of an image or for reducing speckle noise

Abstract

The invention relates to an optical device (1) for enhancing the resolution of an image or for reducing speckle noise.

Inventors: Aschwanden; Manuel (Allenwinden, CH), Suter; Marcel (Zürich, CH), Smolka; Stephan (Zürich, CH), Patscheider; Roman (Winterthur, CH), Niederer; David Andreas (Küttigen, CH)

Applicant: OPTOTUNE AG (Dietikon, CH)

Family ID: 67659897

Assignee: OPTOTUNE SWITZERLAND AG (Dietikon, CH)

Appl. No.: 18/418384

Filed: January 22, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240160027 A1	May. 16, 2024

Foreign Application Priority Data

EP	18189834	Aug. 20, 2018
EP	19154900	Jan. 31, 2019

Related U.S. Application Data

continuation parent-doc US 17270021 US 11880044 WO PCT/EP2019/072306 20190820 child-doc US 18418384

Publication Classification

Int. Cl.: G02B27/48 (20060101); G02B27/09 (20060101); G03B21/14 (20060101)

U.S. Cl.:

CPC G02B27/0933 (20130101); G02B27/48 (20130101);

Field of Classification Search

CPC: G02B (27/0933); G02B (27/48); G03B (21/142)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5402184	12/1994	O'Grady	N/A	N/A
5898515	12/1998	Furlani	N/A	N/A
7279812	12/2006	Barnes	N/A	N/A
11880044	12/2023	Aschwanden	N/A	B06B 1/045
2010/0118278	12/2009	Kobayashi	N/A	N/A
2011/0043768	12/2010	Nakayama	N/A	N/A
2019/0196175	12/2018	Hsu	N/A	N/A
2020/0033704	12/2019	Chao	N/A	G03B 21/142

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1727980	12/2005	CN	N/A
101718908	12/2009	CN	N/A
101770071	12/2009	CN	N/A
102207634	12/2010	CN	N/A
105242395	12/2015	CN	N/A
105763017	12/2015	CN	N/A
206039040	12/2016	CN	N/A
107430268	12/2016	CN	N/A
207020408	12/2017	CN	N/A
2884637	12/2014	EP	N/A
2007222203	12/2006	JP	N/A
2008002871	12/2007	JP	N/A
2009093081	12/2008	JP	N/A
2016071233	12/2015	JP	N/A
2017009998	12/2016	JP	N/A
101671924	12/2015	KR	N/A
201736904	12/2016	TW	N/A
2010078662	12/2009	WO	N/A
2016166980	12/2015	WO	N/A
2018019831	12/2017	WO	N/A

OTHER PUBLICATIONS

Primary Examiner: Howard; Ryan D

Attorney, Agent or Firm: JMB Davis Ben-David

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This is a continuation of U.S. patent application Ser. No. 17/270,021, filed on Feb. 21, 2021, which is the U.S. National Stage of International Patent Application No. PCT/EP2019/072306 filed on Aug. 20, 2019, which in turn claims the benefit of European Patent Application No. 18189834.7 filed on Aug. 20, 2018 and European Patent Application No. 19154900.5 filed on Jan. 31, 2019.

FIELD

(1) The present invention relates to optical devices, particularly for enhancing resolution of an image or for reducing speckle noise.

BACKGROUND

(2) Such an optical device for enhancing resolution of an image usually comprises a transparent plate (e.g. glass window) configured for refracting a light beam passing through the plate, which light beam can project an image comprised of rows and columns of pixels. The plate is configured to be tilted between a first and a second position (e.g. about a first axis), such that the plate is tilted back and forth between the first and the second position, whereby said light beam is shifted (e.g. said projected image is shifted by a fraction of a pixel (usually by a half of a pixel) along a first direction). The device further comprises an actuator that is configured to tilt the plate between the first and the second position. Optical devices of this kind are for instance disclosed in U.S. Pat. No. 7,279,812 as well as in U.S. Pat. No. 5,402,184.

(3) The afore-mentioned enhancement of an image by overlapping of pixels is also known as super resolution projection or imaging. Here, e.g. a temporal sequence of frames is split into two sub-frames, wherein successive sub-frames may be displaced with respect to each other by a fraction of a pixel (e.g. one-half or one-third). The sub-frames are projected in a sufficiently fast manner so that they appear to the human eye as if they are being projected simultaneously and superimposed. For instance, in case the sub-frames are aligned such that the corners of the pixels in one sub-frame are projected on the centers of the next sub-frame and so on, the illusion of a resolution can be achieved that seems twice as high. These kind of pixel shifting can be performed in one dimension (e.g. shifting in x-direction), but may also be performed in two dimensions (2D), e.g. shifting in x- as well as in y-direction of the image (i.e. shifting along the rows and columns of the digital image or shifting the pixel diagonally).

(4) Furthermore, optical devices that are configured to reduce speckle noise generated by a laser usually comprise at least one optical element that acts as a diffuser, i.e., scatters light, and that extends along an extension plane as well as an actuator means designed for oscillating said first optical element along said extension plane, e.g. in a first and/or second motion direction along said plane. Alternatively, the diffuser/optical element can also be tilted about an axis that may extend in a plane along which the diffuser extends.

(5) An optical device of this kind is often used with laser light in order to suppress Speckle noise, which is an interference pattern that is created on the screen (objective speckles) or the retina of the

human eye (subjective speckles) due to the high coherency of the laser light.

(6) Such a reduction can be accomplished by letting the light or laser beam pass through or reflect on a moving/oscillating diffuser. In case the frequency is high enough, the human brain integrates the perceived light over time which reduces the perceived speckle noise significantly. Such an optical device is for instance disclosed in US2011/0043768 which describes a magnet-coil based moving diffuser with complex springs as well as in WO2010078662 which relates to a movable diffuser based on an actuation by means of electroactive polymers.

SUMMARY

(7) Based on the above the problem underlying the present invention is to provide an improved optical device, particularly for enhancing resolution of an image or for reducing speckle noise.

(8) This problem is solved by an optical device having the features of claim 1. Further aspects of the present invention are also described below. Preferred embodiments of the aspects of the present invention are stated in the corresponding sub claims and are described below.

Description

BRIEF DESCRIPTION OF THE FIGURES

(1) In the following, embodiments of the various aspects of the present invention as well as further features and advantages of the present invention shall be described with reference to the Figures, wherein

(2) FIGS. 1A-1C shows an exploded view (FIG. 1A) and a perspective view (FIG. 1B) of an embodiment of an optical device according to the present invention comprising a tiltable transparent plate for enhancing resolution of an optical image, wherein (FIG. 1C) shows a top view of a tiltable frame of the device;

(3) FIGS. 2A-2B show an exploded view (FIG. 2A) and a perspective view (FIG. 2B) of an embodiment of an optical device according to the present invention comprising two tiltable transparent plates for enhancing resolution of an optical image;

(4) FIGS. 3A-3D show top views (FIG. 3A) and (FIG. 3B) of an embodiment of an actuator that can be used in conjunction with the embodiment of the device shown in FIG. 2A-2B, as well as top views (FIG. 3C) and (FIG. 3D) of an embodiment of an actuator that can be used in conjunction with the embodiment of the device shown in FIG. 1A-1C;

(5) FIG. 4 shows a top view of a further embodiment of an actuator that can be used with the device shown in FIG. 1; and

(6) FIGS. 5A-5B show a perspective view (FIG. 5A) of a further embodiment of an optical device according to the present invention comprising a tiltable optical element supported through springs, wherein (FIG. 5B) shows a top view of an actuator of the device;

(7) FIG. 6 shows a schematical cross sectional view of a detail of an actuator that can be used for tilting an optical element/transparent plate, wherein particularly the respective coil of the actuator is directly integrated in a printed circuit board, and wherein particularly the actuator uses a component of the magnetic field B of the respective magnet that is preferably perpendicular to the current in the respective coil and particularly perpendicular to the force $F_{sub.L}$ generated by the actuator;

(8) FIG. 7 shows a schematical cross-sectional view of a further embodiment of an optical device according to the present invention comprising a diffuser supported on elastic polymer pillars for achieving speckle pattern reduction;

(9) FIG. 8 shows a schematical cross-sectional view of a further embodiment of an optical device according to the present invention comprising a diffuser supported on an elastic membrane for achieving speckle pattern reduction;

(10) FIGS. 9A-9B show schematical cross-sectional views (FIG. 9A), (FIG. 9B) of further

embodiments of an optical device according to the present invention comprising a diffusor supported on an elastic membrane for achieving speckle pattern reduction;

(11) FIGS. **10A-10C** show a schematical cross-sectional view (FIG. **10A**) and a top view (FIG. **10B**) of a further embodiment of an optical device according to the present invention comprising a diffusor supported on an elastic membrane for achieving speckle pattern reduction, as well as a top view (FIG. **10C**) of an embodiment of an optical device according to the present invention comprising a diffusor supported on an elastic polymer string for achieving speckle pattern reduction;

(12) FIG. **11** shows a schematical cross-sectional view of a further embodiment of an optical device according to the present invention comprising a diffusor supported on elastic polymer pillars for achieving speckle pattern reduction;

(13) FIG. **12** shows a schematical cross-sectional view of a further embodiment of an optical device according to the present invention comprising a diffusor supported on elastic polymer pillars for achieving speckle pattern reduction;

(14) FIGS. **13A-13C** show a schematical top view (FIG. **13A**) and a schematical cross-sectional view (FIG. **13B**) of a further embodiment of an optical device according to the present invention comprising a diffusor supported on an elastic membrane for achieving speckle pattern reduction, and (FIG. **13C**) shows top views of components of an actuator of the device;

(15) FIGS. **14A-14B** show schematical top views (FIG. **14A**), (FIG. **14B**) of embodiments of an optical device according to the present invention comprising a diffusor supported on at least one elastic membrane for achieving speckle pattern reduction;

(16) FIG. **15** shows a perspective view of a further embodiment of an optical device according to the present invention comprising a diffusor being supported on at least one elastic membrane for achieving speckle pattern reduction;

(17) FIGS. **16A-16B** show a perspective view (FIG. **16A**) of an embodiment of an optical device according to the present invention comprising a tiltable transparent plate for enhancing resolution of an optical image, wherein (FIG. **16B**) shows an exploded view of the device.

DETAILED DESCRIPTION

(18) According to claim **1** an optical device, particularly for enhancing the resolution of an image or for reducing speckle noise, is disclosed, comprising: an optical element configured to interact with a light beam when the light beam impinges on the optical element (e.g. a transparent first plate for refracting a light beam when the light beam passes through said first plate), a support structure for supporting the optical element, at least one elastic member (or several such members) connected to the support structure and to the optical element so that the optical element is movable (e.g. tiltable about a first axis) with respect to the support structure, an actuator configured to move (particularly tilt) the optical element by means of a Lorentz force, wherein the actuator comprises a first coil and a second coil, wherein each coil comprises multiple windings, wherein the windings of the respective coil extend around a winding axis of the respective coil, and wherein said coils are integrated into the support structure, and wherein the actuator comprises a first magnet facing the first coil and a second magnet facing the second coil, wherein the first and the second magnet are connected to the optical element; preferably, the magnets each comprise a magnetization oriented at an angle between 80° and 100° degree with respect to a plane that extends perpendicular to the winding axes of said coils.

(19) According to an embodiment, the support structure comprises a front side and a back side facing away from the front side.

(20) Furthermore, the support structure is a support frame configured to support the optical element, wherein the support structure surrounds an opening of the support structure that extends from the front side of the support structure to the back side of the support structure so that light can pass the support structure (particularly, in case the optical element is a mirror, the support structure does not need to comprise such an opening).

(21) Furthermore, in an embodiment, the at least one elastic member is a first spring structure connected to the front side of the support structure (or support frame), wherein the first spring structure comprises a first frame to which the optical element is connected, wherein the first frame is tiltable about a first axis with respect to the support frame, and wherein the actuator is configured to tilt the optical element about the first axis.

(22) Furthermore, according to an embodiment of the optical device, the support structure (e.g. support frame) is formed by a printed circuit board (PCB), wherein particularly the first coil and the second coil (and particularly also the third and the fourth coil if present) are embedded in the printed circuit board. In other words, the coils are preferably formed as PCB coils, wherein each coil comprises a conductor forming windings that are integrated in the printed circuit board (or substrate) of the device/support structure. Particularly, the coils of all aspects and embodiments of the present invention described herein can be integrated into a substrate (e.g. printed circuit board).

(23) Furthermore, according to an embodiment of the optical device, the support structure (particularly support frame) comprises a first arm that opposes a second arm of the support frame, wherein particularly the first and the second arm of the support frame extend parallel, and wherein the first and the second arm of the support frame are connected by a third and a fourth arm of the support frame, wherein particularly the third arm opposes the fourth arm, and wherein particularly the third arm and the fourth of the support frame arm extend parallel.

(24) Furthermore, according to an embodiment of the optical device, the first spring structure comprises a first holding member that is connected via a first torsion bar to the first frame, and wherein the first spring structure comprises a second holding member that is connected via a second torsion bar to the first frame, wherein the first holding member is connected to the third arm of the support frame on the front side of the support frame and wherein the second holding member is connected to the fourth arm of the support frame on the front side of the support frame.

(25) Furthermore, according to an embodiment of the optical device, the first torsion bar and the second torsion bar are aligned with the first axis.

(26) Particularly, the first axis extends at an angle of 45° to each arm of the support frame of the device.

(27) Further, particularly, the first holding member is separated from the first frame by two slots that comprise a width that increases towards the first torsion bar, and/or wherein the second holding member is separated from the first frame by two slots that comprise a width that increases towards the second torsion bar.

(28) Further, according to an embodiment, the first coil is an L-shaped first coil that comprises a first portion that is integrated into the first arm of the support frame and a second portion that runs perpendicular to the first portion of the first coil, wherein the second portion of the first coil is integrated into the fourth arm of the support frame, and wherein the second coil is an L-shaped second coil that comprises a first portion that is integrated into the second arm of the support frame and a second portion that runs perpendicular to the first portion of the second coil, wherein the second portion of the second coil is integrated into the third arm of the support frame

(29) Further, according to an embodiment, the optical device comprises a third magnet facing the second coil and a fourth magnet facing the first coil, wherein the third and the fourth magnet are connected to the first frame, and wherein the first magnet faces the first portion of the first coil, and wherein the second magnet faces the first portion of the second coil, and wherein the third magnet faces the second portion of the second coil, and wherein the fourth magnet faces the second portion of the first coil, wherein particularly the third and the fourth magnet each comprise a magnetization that is oriented at an angle between 80° and 100° with respect to said plane.

(30) Particularly, the magnetizations of the first and the second magnet point in the same direction. Furthermore, particularly, the magnetization of the third and the fourth magnet points in the same direction.

(31) Furthermore, according to an embodiment of the optical device, the first magnet faces the first

portion of the first coil such that a magnetic field generated by the first magnet comprises a component parallel to the support frame and perpendicular to a current flowing through the first portion of the first coil at the location of the first portion of the first coil such that a Lorentz force is generated when an electrical current is applied to the first coil that pushes the first magnet away from the first portion of the first coil or pulls the first magnet towards the first portion of the first coil depending on the direction of the electrical current in the first portion of the first coil.

(32) Furthermore, in an embodiment, the fourth magnet faces the second portion of the first coil such that a magnetic field generated by the fourth magnet comprises a component parallel to the support frame and perpendicular to a current flowing through the second portion of the first coil at the location of the second portion of the first coil such that a Lorentz force is generated when an electrical current is applied to the first coil that pushes the fourth magnet away from the second portion of the first coil or pulls the fourth magnet towards the second portion of the first coil depending on the direction of the electrical current in the second portion of the first coil.

(33) Furthermore, according to an embodiment, the second magnet faces the first portion of the second coil such that a magnetic field generated by the second magnet comprises a component parallel to the support frame and perpendicular to a current flowing through the first portion of the second coil at the location of the first portion of the second coil such that a Lorentz force is generated when an electrical current is applied to the second coil that pushes the second magnet away from the first portion of the second coil or pulls the second magnet towards the first portion of the second coil depending on the direction of the electrical current in the first portion of the second coil.

(34) Furthermore, according to an embodiment, the third magnet faces the second portion of the second coil such that a magnetic field generated by the third magnet comprises a component parallel to the support frame and perpendicular to a current flowing through the second portion of the second coil at the location of the second portion of the second coil such that a Lorentz force is generated when an electrical current is applied to the second coil that pushes the third magnet away from the second portion of the second coil or pulls the third magnet towards the second portion of the second coil depending on the direction of the electrical current in the second portion of the second coil.

(35) Furthermore, according to an alternative embodiment, instead of L-shaped coils, the first coil is an outer coil and the second coil is an inner coil, wherein the outer coil surrounds the inner coil, particularly with respect to a common extension plane of the inner and the outer coil (e.g. the inner and the outer coil may have parallel winding axes), and wherein the outer coil comprises a first section and an opposing second section, and wherein the inner coil comprises a first section and an opposing second section, wherein the first section of the outer coil extends adjacent the first section of the inner coil, and wherein the second section of the outer coil extends adjacent the second section of the inner coil.

(36) Further, according to an embodiment, the outer coil comprises a third section connecting the first section of the outer coil to the second section of the outer coil, and wherein the inner coil comprises a third section extending adjacent the third section of the outer coil, wherein the third section of the inner coil connects the first section of the inner coil to the second section of the inner coil, and wherein the outer coil comprises a fourth section connecting the first section of the outer coil to the second section of the outer coil, and wherein the inner coil comprises a fourth section extending adjacent the fourth section of the outer coil, wherein the fourth section of the inner coil connects the first section of the inner coil to the second section of the inner coil.

(37) Furthermore, according to an embodiment, the first sections of the outer and inner coil are integrated into the first arm of the support structure, wherein the second sections of the outer and inner coil are integrated into the second arm of the support structure, wherein the third sections of the outer and inner coil are integrated into the third arm of the support structure, and wherein the fourth sections of the outer and inner coil are integrated into the fourth arm of the support structure.

(38) Further, according to an embodiment, the optical device comprises a third magnet connected to the first frame and a fourth magnet connected to the first frame, wherein the first magnet faces the first portions of the outer coil and the inner coil in a direction normal to a front side of the support structure (e.g. support frame), and wherein the second magnet faces the second portions of the outer and the inner coil in a direction normal to a front side of the support structure (e.g. support frame), and wherein the third magnet faces the third portions of the outer coil and the inner coil in a direction normal to a front side of the support structure (e.g. support frame), and wherein the fourth magnet faces the fourth portions of the outer and the inner coil in a direction normal to a front side of the support structure (e.g. support frame). Further, particularly, the third and the fourth magnet each comprise a magnetization that is oriented at an angle between 80° and 100° with respect to said plane. Further, according to an embodiment, the first magnet comprises a first magnetization, and wherein the second magnet comprises a second magnetization, and wherein the third magnet comprises a third magnetization, and wherein the fourth magnet comprises a fourth magnetization, and wherein the respective magnetization extends orthogonal to the first plate, and wherein the first and the fourth magnetization point in the same direction while the second and the third magnetization point in the opposite direction.

(39) Further, according to an embodiment, the first magnet faces the first portions of the outer and the inner coil and the fourth magnet faces the fourth portions of the outer and the inner coil such that a magnetic field generated by the first magnet comprises a component parallel to the support frame and perpendicular to a current flowing through the first portion of the outer coil and an opposite current flowing through the first portion of the inner coil and such that a magnetic field generated by the fourth magnet comprises a component parallel to the support frame and perpendicular to a current flowing through the fourth portion of the outer coil and an opposite current flowing through the fourth portion of the inner coil such that a resultant Lorentz force is generated that pushes the first magnet away from the first portions of the outer and the inner coil and the fourth magnet from the fourth portions of the outer and the inner coil or that pulls the first magnet towards the first portions of the outer and the inner coil and the fourth magnet towards the fourth portions of the outer and the inner coil; and/or that the third magnet faces the third portions of the outer and the inner coil and the second magnet faces the second portions of the outer and the inner coil such that a magnetic field generated by the third magnet comprises a component parallel to the support frame and perpendicular to a current flowing through the third portion of the outer coil and an opposite current flowing through the third portion of the inner coil and such that a magnetic field generated by the second magnet comprises a component parallel to the support frame and perpendicular to a current flowing through the second portion of the outer coil and an opposite current flowing through the second portion of the inner coil such that a resultant Lorentz force is generated that pushes the third magnet away from the third portions of the outer and the inner coil and the second magnet from the second portions of the outer and the inner coil or that pulls the third magnet towards the third portions of the outer and the inner coil and the second magnet towards the second portions of the outer and the inner coil.

(40) Further, in an embodiment, the optical device comprises a transparent second plate for refracting the light beam when the light beam passes through said second plate, wherein the first plate faces the second plate, and wherein the support frame is configured to support the second plate.

(41) Particularly, the two plates may also be substituted by a diffuser, respectively, wherein the first and the second diffuser can be tilted such that laser speckles can be reduced, i.e. due to the different angles of the diffusers, overlapping speckle patterns are generated which help to reduce the laser speckles contrast overall.

(42) Further, according to an embodiment, the optical device comprises a second spring structure connected to the back side of the support frame, wherein the second spring structure comprises a second frame to which the second plate is connected, wherein the second frame is tiltable about a

second axis with respect to the support frame, and wherein the actuator is configured to tilt the second plate about the second axis by means of a Lorentz force.

(43) Further, in an embodiment, the actuator comprises a third and a fourth coil, wherein each of the third and the fourth coil comprises multiple windings extending around a winding axis of the respective (third or fourth) coil that extends perpendicular to said plane, wherein the third and the fourth coil are integrated into the support structure (e.g. support frame), and wherein the actuator comprises a third magnet facing the third coil and a fourth magnet facing the fourth coil, and wherein the third and the fourth magnet are connected to the second frame. Particularly, the third and the fourth magnet each comprise a magnetization that is oriented at an angle between 80° and 100° with respect to said plane.

(44) Further, in an embodiment, the third coil is integrated into the third arm, and wherein the fourth coil is integrated into the fourth arm of the support frame (e.g. printed circuit board).

(45) Further, in an embodiment, the second spring structure comprises a third holding member that is connected via a third torsion bar to the second frame, and wherein the second spring structure comprises a fourth holding member that is connected via a fourth torsion bar to the second frame, wherein the third holding member is connected to the first arm of the support frame on the back side of the support frame and wherein the fourth holding member is connected to the second arm of the support frame on the back side of the support frame.

(46) Further, particularly, the third torsion bar and the fourth torsion bar are aligned with the second axis.

(47) Furthermore, according to an embodiment, the respective magnet faces its associated coil such that a magnetic field generated by the respective magnet comprises a component parallel to the support frame and perpendicular to a current flowing through the respective coil at the location of the respective coil such that a Lorentz force is generated when an electrical current is applied to the respective coil that pushes the respective magnet away from the respective coil or pulls the respective magnet towards the respective coil depending on the direction of the electrical current in the respective coil.

(48) Furthermore, according to an embodiment of the optical device, the magnetization of the first and the second magnet points in the same direction. Furthermore, particularly, the magnetization of the third and the fourth magnet points in the same direction.

(49) Furthermore, according to an embodiment, the optical element is one of: a transparent first plate (see also above) for refracting a light beam when the light beam passes through said first plate, a diffusor, a mirror, a prism.

(50) Further, in an embodiment, the optical device comprises a static diffusor that faces the optical element (particularly in case the optical element is a moveable or tiltable diffusor).

(51) Further, according to an embodiment of the optical device, wherein the at least one elastic member is one of the following components or comprises one or more of the following components: an elastically deformable membrane (wherein particularly the membrane comprises a polymer or is formed out of a polymer), an elastically deformable string (90); an elastically deformable, particularly bendable, pillar.

(52) Furthermore, according to yet another aspect of the present invention, an optical device, particularly for enhancing the resolution of an image (or for speckle pattern reduction), is disclosed, wherein the optical device comprises: an optical element configured to interact with a light beam impinging on the optical element, a support frame (or support structure) configured to support the optical element, a (preferably monolithic) spring structure connected to the support frame, wherein the spring structure comprises a frame to which the optical element is connected, wherein the frame is moveable with respect to the support frame, and wherein the spring structure comprises a first holding member that is connected via a first spring element to the frame, and an actuator configured to move the frame with respect to the support frame by means of a Lorentz force.

(53) Preferably, in an embodiment, the spring structure comprises a second holding member that is

connected via a second spring element to the frame, and wherein the spring structure comprises a third holding member that is connected via a third spring element to the frame, and wherein the spring structure comprises a fourth holding member that is connected via a fourth spring element to the frame, and wherein the respective spring element comprises a curved or angled shape or portion. Particularly said curved shape or portion comprises at least one inflection point,

(54) Particularly, due to the elastic, preferably monolithic suspension, the frame of the spring structure does not comprise explicit rotational joints. Particularly, the optical device allows to move/tilt an optical element in the form of window, a mirror, a transparent plate, a lens, or a prism in two degrees of freedom, wherein due to the specific design the optical device is cost effective, can be formed as a flat device with a small height in the direction of the optical path, and can comprise a large aperture in relation to the device footprint. Furthermore, power demands of the actuator are low and a linear actuation is possible, i.e. an electrical current used by the actuator is proportional to a force generated by the actuator for moving/tilting the optical element. Furthermore, the force comprises a very small dependence on the position of the actuator in contrast to a reluctance actuator.

(55) Furthermore, particularly, the actuation can be controlled in a simple manner (e.g. open loop, wherein particularly no calibration is needed).

(56) Particularly, at the respective inflection point, the curvature of the respective spring element changes its sign, i.e. at the respective inflection point a left-curved portion of the respective spring element joins a right-curved portion of the spring element. Particularly, the fact that the respective spring element comprises at least one inflection point can mean that the respective spring element comprises an s-shape or a meandering shape.

(57) Particularly, according to an embodiment, the support frame is formed by a printed circuit board (PCB) or comprises a PCB.

(58) Particularly, in an embodiment, the support frame surrounds an opening of the support frame that extends from a front side of the support frame to a back side of the support frame so that light can pass the support frame.

(59) Furthermore, according to an embodiment, the support frame comprises a first arm that opposes a second arm of the support frame, and wherein the first and the second arm are connected by a third and a fourth arm of the support frame to form the support frame.

(60) Furthermore, according to an embodiment, the first and the third arm are joined at a first corner portion of the support frame, and wherein the third and the second arm are joined at a second corner portion of the support frame, and wherein the second and the fourth arm are joined at a third corner portion of the support frame, and wherein the fourth and the first arm are joined at a fourth corner portion of the support frame.

(61) Furthermore, according to an embodiment, the first holding member is connected to the first corner portion of the support frame (e.g. on the front side of the support frame), and wherein the second holding member is connected to the second corner portion of the support frame (e.g. on the front side of the support frame), and wherein the third holding member is connected to the third corner portion of the support frame (e.g. on the front side of the support frame), and wherein the fourth holding member is connected to the fourth corner portion of the support frame (e.g. on the front side of the support frame).

(62) Particularly, the respective corner portion forms a protrusion to which the respective holding member is connected.

(63) Furthermore, according to an embodiment, the actuator comprises a first coil, a second coil, a third coil and a fourth coil, wherein said coils are integrated into the support frame, and wherein the actuator comprises a first magnet facing the first coil, a second magnet facing the second coil, a third magnet facing the third coil, and a fourth magnet facing the fourth coil, wherein the magnets are connected to the frame.

(64) Furthermore, according to an embodiment, the first coil is integrated into the first arm of the

support frame, and wherein the second coil is integrated into the second arm of the support frame, and wherein the third coil is integrated into the third arm of the support frame, and wherein the fourth coil is integrated into the fourth arm of the support frame (e.g. printed circuit board).

(65) Furthermore, according to an embodiment, the first magnet comprises a first magnetization, and wherein the second magnet comprises a second magnetization, and wherein the third magnet comprises a third magnetization, and wherein the fourth magnet comprises a fourth magnetization, and wherein the respective magnetization extends orthogonal to the frame, and wherein particularly the first and the second magnetization point in opposite directions, and wherein particularly the third and the fourth magnetization point in the opposite direction.

(66) Furthermore, according to an embodiment, the respective magnet faces the respective coil such that a magnetic field generated by the respective magnet comprises a component parallel to the support frame and perpendicular to a current flowing through the respective coil at the location of the respective coil such that a Lorentz force is generated when an electrical current is applied to the respective coil that pushes the respective magnet away from the respective coil or pulls the respective magnet towards the respective coil depending on the direction of the electrical current in the respective coil.

(67) Furthermore, according to an embodiment, the actuator is configured to apply electrical currents to the opposing first and second coil so that the first magnet and the first coil attract one another and the second magnet and the second coil repel one another so that the frame and therewith the optical element is tilted about a first axis, or wherein the actuator is configured to apply electrical currents to the opposing first and second coil so that the first magnet and the first coil repel one another and the second magnet and the second coil attract one another so that the frame and therewith the optical element are tilted about the first axis in the opposite direction.

(68) Furthermore, according to an embodiment, the actuator is configured to apply electrical currents to the opposing third and fourth coil so that the third magnet and the third coil attract one another and the fourth magnet and the fourth coil repel one another so that the frame and therewith the optical element is tilted about a second axis, or wherein the actuator is configured to apply electrical currents to the opposing third and fourth coil so that the third magnet and the third coil repel one another and the fourth magnet and the fourth coil attract one another so that the frame and therewith the optical element are tilted about the second axis in the opposite direction.

(69) Furthermore, the currents in the coils can be such in such a way as to tilt the optical element around any axis that can be constituted by a linear combination of the tilt around the first axis and the tilt around the second axis. Particularly, this axis can be in a diagonal direction.

(70) Furthermore, according to an embodiment, the optical element is one of: a transparent plate, particularly a transparent flat plate, a mirror, a lens, a prism, a diffusor.

(71) Particularly, in case the optical element is a transparent plate, the optical element is configured to interact with a light beam impinging on the optical element, such that the light beam is refracted by the optical element. Here the optical device can be used to enhance the resolution of an image as described above.

(72) Furthermore, according to an embodiment, the optical device comprises a static diffusor that faces the optical element.

(73) Particularly, in all embodiments/aspects of the present invention described herein, the optical device can comprise an energy source for generating the respective electrical current applied to the respective coil of the actuator, and a control unit for controlling the respective electrical current and therewith the movement of the movable structure along the first motion direction and/or along the second motion direction, wherein particularly the respective electrical current is a current pulse or comprises current pulses.

(74) Furthermore, in this regard, the optical device may also comprise at least one sensor, particularly a Hall sensor, for measuring an actual position of the optical element, wherein the control unit is configured to control the respective current such that the measured actual position

reaches a pre-defined reference position.

(75) According to a further aspect of the present invention, an optical device, particularly for reducing speckle noise, is disclosed comprising: a movable diffuser for diffusing a light beam passing through said diffuser, a support structure for supporting the diffuser, wherein the movable diffuser is supported on the support structure by at least one elastically deformable member comprising particularly a polymer or a metal (or being formed out of a polymer or a metal) such that the diffuser is movable along a first motion direction extending along the support structure and/or along a second motion direction extending along the support structure. Particularly, the polymer can be one of: an elastomer, a silicone, a rubber. This also applies to the polymers used in the embodiments described in the following.

(76) Furthermore, according to an embodiment of the optical device, the at least one elastically deformable member is an elastically deformable membrane that particularly comprises a polymer or is formed out of a polymer.

(77) Furthermore, according to an embodiment of the optical device, the membrane comprises a circumferential edge region that is connected to the support structure.

(78) Furthermore, according to an embodiment of the optical device, the diffuser is connected to a front side of the membrane, particularly via a spacer or a holding element connecting the movable diffuser to the membrane, wherein the front side of the membrane faces away from the support structure.

(79) Furthermore, according to an embodiment of the optical device, the diffuser is arranged on a back side of the membrane, wherein the back side of the membrane faces the support structure.

(80) Furthermore, according to an embodiment of the optical device, the diffuser is supported on the support structure by at least two elastically deformable members, wherein each elastically deformable member comprises a polymer or a metal (or is formed out of a polymer or a metal) such that the diffuser is movable along the first motion direction and/or along the second motion direction.

(81) Furthermore, according to an embodiment of the optical device, the diffuser is supported on the support structure by three or four elastically deformable members, wherein each elastically deformable member comprises a polymer or a metal (or is formed out of a polymer or a metal) such that the diffuser is movable along the first motion direction and/or along the second motion direction. Particularly, the elastically deformable members are configured such that the diffuser can be moved parallel to the support structure.

(82) Furthermore, according to an embodiment of the optical device, the respective elastically deformable member is an elastically deformable string comprising a polymer or being formed out of a polymer, wherein particularly the two strings extend parallel to one another along the support structure and are preferably integrally formed with two opposing fastening portions, via which fastening portions the two strings are fastened to the support structure, particularly to a substrate (e.g. printed circuit board) into which a coil assembly (e.g. first and/or second coil assembly) can be integrated.

(83) Furthermore, according to an embodiment of the optical device, the diffuser is connected to the back side of the respective string, which back side faces the support structure.

(84) Furthermore, according to an embodiment of the optical device, the respective string comprises a first end section and an opposing second end section, wherein the end sections are connected to the support structure.

(85) Furthermore, according to an embodiment of the optical device, the respective elastically deformable member is an elastically deformable, particularly bendable pillar protruding from the support structure. Particularly, the pillars are bendable such that the diffuser can be moved parallel to the support structure.

(86) Furthermore, according to an embodiment of the optical device, each polymer pillar is connected to a corner region of the diffuser or to a holding member, wherein the diffuser is

connected to the holding member.

(87) Furthermore, according to an embodiment of the optical device, the support structure delimits at least one recess or delimits at least one through-opening extending from a front side of the support structure to a back side of the support structure, wherein particularly said membrane extends over said through-opening.

(88) Furthermore, according to an embodiment, the diffuser or said at least one holding element is arranged in front of said at least one recess or through-opening (e.g. on the front side of the support structure), particularly such that light can pass through the diffuser and through the support structure via said opening.

(89) Furthermore, according to an embodiment, the diffuser forms a cantilever (and particularly protrudes beyond the support structure in a first direction and/or beyond the support structure in an opposite second direction). Further, particularly, the diffuser is connected to the front side of the membrane via a spacer.

(90) Furthermore, according to an embodiment of the optical device, the optical device comprises a static diffuser that faces the movable diffuser. Particularly, the static diffuser can be at least one of: arranged in said at least one through-opening, arranged in front of said at least one through-opening, connected to a back side of the support structure, formed as a cantilever (wherein particularly the static diffuser protrudes beyond the support structure in said first direction and/or beyond the support structure in said opposite second direction).

(91) Furthermore, according to an embodiment of the optical device, the optical device comprises an actuator for moving the diffuser along the first motion direction, and/or along the second motion direction, wherein the actuator comprises at least a first coil assembly connected to the support structure and at least a first magnet connected to the at least one elastically deformable member (particularly membrane) and/or to the movable diffuser such that the at least one first magnet faces the at least one first coil assembly.

(92) Further, according to an embodiment, the first coil assembly comprises a first layer comprising a first and a second coil arranged side by side so that a section of the first coil extends along an adjacent section of the second coil, wherein particularly the first and the second coil are configured such that an electrical current that flows through the first and through the second coil flows in the same direction in said adjacent sections, and wherein the first coil assembly comprises a second layer, wherein the first and the second layer are arranged on top of one another, and wherein the second layer comprises a third and a fourth coil arranged side by side so that a section of the third coil extends along an adjacent section of the fourth coil, wherein particularly the third and the fourth coil are configured such that an electrical current that flows through the third and the fourth coil flows in the same direction in said section of the third coil and in said adjacent section of the fourth coil, and wherein, in a crossing region of the first coil assembly, the section of the first coil and the section of the second coil each cross the section of the third coil and the section of the fourth coil, wherein particularly the at least one first magnet faces said crossing region.

(93) Further, according to an embodiment, the actuator comprises a second coil assembly opposing the first coil assembly, wherein the second coil assembly is connected to the support structure, and wherein the actuator comprises a second magnet connected to the at least one elastically deformable member (particularly membrane) and/or to the movable diffuser such that the second magnet faces the second coil assembly.

(94) Further, according to an embodiment, the second coil assembly comprises a first layer comprising a first and a second coil arranged side by side so that a section of the first coil of the second coil assembly extends along an adjacent section of the second coil of the second coil assembly, wherein particularly the first and the second coil of the second coil assembly are configured such that an electrical current that flows through the first and through the second coil of the second coil assembly flows through said adjacent sections of the second coil assembly in the same direction, and wherein the second coil assembly comprises a second layer, wherein the first

and the second layer of the second coil assembly are arranged on top of one another, and wherein the second layer of the second coil assembly comprises a third and a fourth coil arranged side by side so that a section of the third coil of the second coil assembly extends along an adjacent section of the fourth coil of the second coil assembly, wherein particularly the third and the fourth coil of the second coil assembly are configured such that an electrical current that flows through the third and the fourth coil of the second coil assembly flows through said section of the third coil of the second coil assembly and through said adjacent section of the fourth coil of the second coil assembly in the same direction, and wherein, in a crossing region of the second coil assembly, the section of the first coil of the second coil assembly and the section of the second coil of the second coil assembly each cross the section of the third coil of the second coil assembly and the section of the fourth coil of the second coil assembly.

(95) Further, according to an embodiment, the first magnet comprises a first magnetization that points towards or away from the crossing region of the first coil assembly, and/or wherein the second magnet comprises a second magnetization that points towards or away from the crossing region of the second coil assembly.

(96) Particularly, the first magnetization is orthogonal to a front side of the first magnet, which front side faces the crossing region of the first coil assembly. Further, particularly, the second magnetization is orthogonal to a front side of the second magnet, which front side of the second magnet faces the crossing region of the second coil assembly. Particularly, the respective front side is quadrangular, particularly square.

(97) Particularly, the first magnetization is preferably orthogonal to an electrical current flowing through one of the sections, in the crossing region of the first coil assembly (particularly when the diffusor extends parallel to the coils of the first coil assembly). Furthermore, particularly, the second magnetization is preferably orthogonal to a current flowing through one of the sections in the crossing region of the second coil assembly (particularly when the diffusor extends parallel to the coils of the second coil assembly).

(98) Furthermore, particularly, said adjacent sections of the first and second coil of the first layer of the respective coil assembly extend along the second motion direction.

(99) Furthermore, particularly, said adjacent sections of the third and fourth coil of the second layer of the respective coil assembly extend along the first motion direction

(100) Furthermore, according to an embodiment, the optical device is configured to apply an electrical current to the first and the second coil of the first layer of the at least one first coil assembly such that the electrical current flows in the same direction in said adjacent sections of the first layer of the at least one first coil assembly, and wherein particularly (optionally) the optical device is configured to also apply an electrical current to the first and the second coil of the first layer of the second coil assembly such that the electrical current flows in the same direction in said adjacent sections of the first layer of the second coil assembly, such that a Lorentz force is generated that moves the diffusor along the first motion direction, particularly depending on the direction of the current in said adjacent sections of the first layer of the first coil assembly and optionally in said adjacent sections of the first layer of the second coil assembly.

(101) Further, according to an embodiment, the optical device is configured to apply an electrical current to the third and to the fourth coil of the second layer of the first coil assembly such that the electrical current flows in the same direction in said adjacent sections of the second layer of the first coil assembly, and wherein particularly (optionally) the optical device is configured to also apply an electrical current to the third and the fourth coil of the second layer of the second coil assembly such that the electrical current flows in the same direction in said adjacent sections of the second layer of the second coil assembly, such that a Lorentz force is generated that moves the diffusor along the second motion direction, particularly depending on the direction of the current in said adjacent sections of the second layer of the first coil assembly and optionally in said adjacent sections of the second layer of the second coil assembly.

(102) Further, according to an embodiment, the support structure comprises or is formed as a substrate, particularly in form of a printed circuit board (PCB), wherein the at least one first coil assembly and/or the second coil assembly is/are integrated into the substrate (e.g. PCB).

(103) Optionally, a soft-magnetic plate can be arranged on a back side of the support structure or of the substrate so that the support structure or the substrate is arranged between the soft-magnetic plate and the first and/or second magnet.

(104) Furthermore, according to an embodiment, the support structure delimits at least a first through-opening extending from a front side of the support structure to a back side of the support structure, and a first recess (the first recess can form a second through-opening), wherein the diffuser is arranged in front of the first (e.g. central) through-opening, wherein the movable diffuser is supported on the support structure by the at least one elastically deformable member which is formed as a membrane (or an elastic deformable pin) that is connected to the support structure such that it extends in or over the first recess (e.g. second through-opening, see above), and wherein particularly the optical device comprises said least one first magnet that is connected to the at least one elastically deformable member (and arranged in front or in the second through-opening), and wherein particularly the optical device comprises at least one holding element, wherein particularly the diffuser is connected via the at least one holding element to the at least one first magnet (so as to hold the diffuser in front of the first through-opening of the support structure), and wherein the at least one magnet is arranged such it faces said at least one first coil assembly.

(105) Particularly, the optical device can comprise a plurality of first recesses (or second through-openings), wherein each first recess (e.g. second through-opening) can be covered by the at least one elastically deformable member (e.g. membrane), wherein alternatively a separate elastically deformable member (e.g. membrane) comprising a polymer or being formed out of a polymer can be arranged in or over each first recess (e.g. second through-opening), wherein a magnet is arranged in front of or in the respective first recess (or second through-opening) and connected to the at least one membrane or the respective membrane, wherein each magnet is arranged in front of a coil assembly. Further, each magnet is connected via a holding element to the diffuser to hold the latter in front of the first through-opening. Further, particularly, the respective coil assembly can be designed as the at least one first coil assembly described above. The respective magnet is preferably configured as the at least one first magnet described above. Further, the first recesses (or second through-openings) can be arranged around the (e.g. central) first through-opening. Thus, with help of the actuator formed by the coil assemblies and the associated magnets, the diffuser is movable along a first motion direction extending along the support structure and/or along a second motion direction extending along the support structure.

(106) Furthermore, according to an embodiment, the support structure delimits a first, a second and a third recess (e.g. in form of a through-opening extending from a front side of the support structure to a back side of the support structure, respectively), wherein the movable diffuser is arranged in front of a fourth recess of the support structure, and wherein the movable diffuser is supported on the support structure by the at least one elastically deformable member which is formed as a membrane that is connected to the support structure such that it covers said recesses (e.g. through-openings), and wherein particularly the at least one first magnet is connected to the at least one elastically deformable member and arranged in front of the first recess, and wherein particularly the optical device comprises a holding element, wherein particularly the diffuser is connected via the holding element to the at least one first magnet so as to hold the diffuser in front of the first recess of the support structure, and wherein particularly the holding element comprises a first arm that connects the at least one first magnet to a first protrusion of the holding element, wherein the first protrusion is supported on the membrane and arranged in front of the second recess, and wherein the holding element comprises a second arm that connects the at least one first magnet to a second protrusion of the holding element, wherein the second protrusion is supported on the membrane

and arranged in front of the third recess, and wherein the diffusor is connected to the first and to the second arm, and wherein the at least one first magnet is arranged such it faces said at least one first coil assembly.

(107) Particularly, the fourth recess is arranged in an edge region of the support structure. Further, particularly the optical device comprises a static diffusor which extends over the fourth recess on the back side of the support structure and faces the movable diffusor. Further, particularly, the first and the second arm are integrally connected to one another and enclose an acute angle.

(108) Furthermore, according to an embodiment of the optical device, the optical device comprises slide bearings arranged on the back side of the elastically deformable membrane.

(109) Furthermore, according to an embodiment of the optical device, the at least one first magnet and/or the second magnet is/are arranged on the back side of the membrane.

(110) Furthermore, according to an embodiment of the optical device, the at least one first magnet and/or the second magnet of the actuator is/are connected to the diffusor.

(111) Furthermore, according to an embodiment of the optical device, the at least one first magnet and/or the second magnet of the actuator is/are configured to slide on a front surface of the support structure.

(112) Furthermore, according to an embodiment of the optical device, the at least one first magnet and/or the second magnet of the actuator is/are configured to slide on a ferro-fluid arranged on a front surface of the support structure. Particularly, ferro-fluids are colloidal liquids made of nanoscale ferromagnetic or ferrimagnetic particles suspended in a carrier fluid.

(113) Furthermore, according to an embodiment of the optical device, the front surface is formed by a layer of the support structure, which layer is formed out of a glass or a non-magnetic metal.

(114) According to yet another aspect of the present invention, an optical device, particularly for enhancing the resolution of an image, is disclosed, comprising: a transparent plate for refracting a light beam passing through said plate, wherein the plate is tiltable (e.g. about a first axis and a second axis), and wherein the plate comprises a first end section and an opposing second end section, wherein the optical device comprises a first spring structure and an opposing second spring structure, wherein the first spring structure comprises an elongated first holding arm connected (particularly glued) to the first end section of the plate, and wherein the second spring structure comprises an elongated second holding arm connected (particularly glued) to the second end section of the plate, and wherein the first holding arm is connected via a first bar to a first bendable member of the first spring structure and via a second bar to a second bendable member of the first spring structure, and wherein the second holding arm is connected via a third bar to a third bendable member of the second spring structure and via a fourth bar to a fourth bendable member of the second spring structure.

(115) Furthermore, according to an embodiment of the optical device, the respective bar is integrally connected to the associated bendable portion.

(116) Furthermore, according to an embodiment of the optical device, the first bendable member comprises a top portion and a pillar extending perpendicular to the top portion of the first bendable member, wherein the pillar of the first bendable member connects the top portion of the first bendable member to a bottom portion of the first spring structure, and wherein the second bendable member comprises a top portion and a pillar extending perpendicular to the top portion of the second bendable member, wherein the pillar of the second bendable member connects the top portion of the second bendable member to the bottom portion of the first spring structure, and wherein the third bendable member comprises a top portion and a pillar extending perpendicular to the top portion of the third bendable member, wherein the pillar of the third bendable member connects the top portion of the third bendable member to a bottom portion of the second spring structure, and wherein the fourth bendable member comprises a top portion and a pillar extending perpendicular to the top portion of the fourth bendable member, wherein the pillar of the fourth bendable member connects the top portion of the fourth bendable member to the bottom portion of

the second spring structure.

(117) Furthermore, according to an embodiment of the optical device, the optical device comprises an actuator for tilting the plate, wherein the actuator comprises a first and a second coil arranged on the bottom portion of the first spring structure such that the top portion of the first bendable member faces the first coil and forms a first air gap with the first coil, and such that the top portion of the second bendable member faces the second coil and forms a second air gap with the second coil, and wherein the actuator comprises a third and a fourth coil arranged on the bottom portion of the second spring structure such that the top portion of the third bendable member faces the third coil and forms a third air gap with the third coil, and such that the top portion of the fourth bendable member faces the fourth coil and forms a fourth air gap with the fourth coil.

(118) Furthermore, according to an embodiment of the optical device, the first spring structure is configured to guide magnetic flux generated by the first or second coil (when an electrical current is applied to the first or second coil), and wherein the second spring structure is configured to guide magnetic flux generated by the third or fourth coil (when an electrical current is applied to the third or fourth coil).

(119) Furthermore, according to an embodiment of the optical device, the optical device is configured to apply an electrical current to the respective coil such that the respective coil attracts the top portion of the associated bendable portion due to a reluctance force generated by the respective coil of the actuator.

(120) Furthermore, according to an embodiment of the optical device, the optical device is configured to apply an electrical current to the first and to the second coil or to the third and to the fourth coil to tilt the plate about a first axis extending parallel to the holding arms.

(121) Furthermore, according to an embodiment of the optical device, the optical device is configured to apply an electrical current to the first and to the third coil or to the second and to the fourth coil to tilt the plate about a second axis extending perpendicular to the holding arms.

(122) Furthermore, according to an embodiment of the optical device, the respective coil comprises a coil core extending perpendicular to the top portion of the respective bendable member.

(123) Furthermore, according to an embodiment of the optical device, the actuator comprises a first substrate, wherein the first and the second coil are integrated into the first substrate (the first substrate can e.g. be a printed circuit board), and wherein the actuator comprises a second substrate, wherein the third and the fourth coil are integrated into the second substrate (the second substrate can e.g. be a printed circuit board).

(124) Furthermore, according to an embodiment of the optical device, the first spring structure comprises a first latching arm for engaging with the first substrate of the actuator, wherein the first latching arm protrudes from the bottom portion of the first spring structure between the first and the second bendable member of the first spring structure and is configured to fasten the first substrate to the bottom portion of the first spring structure. Further, according to an embodiment, the second spring structure comprises a second latching arm for engaging with the second substrate of the actuator, wherein the second latching arm protrudes from the bottom portion of the second spring structure between the third and the fourth bendable member of the second spring structure and is configured to fasten the second substrate to the bottom portion of the second spring structure.

(125) According to yet another aspect of the present invention, an optical device, particularly for enhancing the resolution of an image or for reducing speckle noise is disclosed, comprising: a movable structure comprising an optical region for interacting with a light beam passing through said optical region, a support structure for supporting the movable structure, the movable structure is supported on the support structure via balls such that the movable structure is movable along a first motion direction extending along the support structure.

(126) Particularly, in an embodiment, the movable structure is supported on the support structure via balls such that the movable structure is movable along the support structure in a second motion direction extending along the support structure.

(127) Particularly, in an embodiment, each ball engages with an associated recess of the support structure.

(128) Particularly, in an embodiment, each ball engages with an associated recess of the movable structure.

(129) Particularly, in an embodiment, the optical region for interacting with a light beam passing through said optical region is a transparent region for refracting a light beam passing through said transparent region.

(130) Particularly, in an embodiment, the movable structure is supported on the support structure via said balls such that the movable structure is movable along a first motion direction extending along the support structure, and such that the movable structure is tilted about a first axis with respect to the support structure when the movable structure moves in the first motion direction.

(131) Particularly, in an embodiment, the movable structure is supported on the support structure via said balls such that the movable structure is movable along the support structure in a second motion direction extending along the support structure and such that the movable structure is tilted about a second axis with respect to the support structure when the movable structure moves in the second motion direction.

(132) Particularly, in an embodiment, the respective recess of the support structure comprises a bottom for contacting the ball engaging with the respective recess of the support structure, wherein the bottom comprises a slope.

(133) Particularly, in an embodiment, the respective recess of the movable structure comprises a bottom for contacting the ball engaging with the respective recess of the movable structure, wherein the bottom of the respective recess of the movable structure comprises a slope.

(134) Furthermore, the respective optical device described herein can be configured to be glued into an optical system (e.g. to form a component of the latter. Furthermore, the respective optical device described herein can also be configured to be slid into an optical system, using e.g. the support frame (particularly the printed circuit board) as a guiding structure for said sliding.

(135) FIG. 1(A) shows in conjunction with FIGS. 1(B) and 1(C) an embodiment of an optical device **1** according to the present invention, wherein the optical device **1** is particularly configured for enhancing the resolution of an image (by shifting pixels as described herein). Particularly, the optical element **21** (e.g. transparent plate **21**, particularly a glass) is configured for interacting with a light beam L passing through said plate **21** so that the light beam L gets refracted when passing through said transparent plate **21**. In case the light beam L projects an image comprised of rows and columns of pixels and the plate **22** is tilted between a first and a second position (e.g. about a first axis A), the light beam L is shifted (e.g. said projected image is shifted by a fraction of a pixel (usually by a half of a pixel) along a first direction). In addition, the light beam L may also be shifted by tilting the plate **21** about a further (e.g. orthogonal) axis (not shown in FIG. 1) so that the light beam L is also shifted along a second direction.

(136) Furthermore, using such a device **1**, a temporal sequence of frames can be split into two sub-frames, wherein to successive sub-frames may be displaced with respect to each other by a fraction of a pixel (e.g. one-half or one-third). The sub-frames are projected in a sufficiently fast manner so that they appear to the human eye as if they are being projected simultaneously and superimposed. For instance, in case the sub-frames are aligned such that the corners of the pixels in one sub-frame are projected on the centers of the next sub-frame and so on, the illusion of a resolution can be achieved that seems twice as high. These kind of pixel shifting can be performed in one dimension (e.g. shifting in x-direction), but may also be performed in two dimensions (2D), e.g. shifting in x- as well as in y-direction of the image (i.e. shifting along the rows and columns of the digital image or shifting the pixel diagonally).

(137) However, the device shown in FIG. 1 may also be used to reduce a so called speckle pattern, which is an interference pattern that is created on a screen (objective speckles) or the retina of the human eye (subjective speckles) due to the high coherency of the laser light.

(138) The reduction of such a Speckle pattern can be accomplished by letting the light or laser beam pass through or reflect on an optical element **21** in form of a moving/oscillating diffuser. In case the frequency is high enough, the human brain integrates the perceived light over time which reduces the perceived speckle noise significantly.

(139) Particularly, the device shown in FIG. **1** preferably comprises a transparent first plate **21** for refracting a light beam **L** when the light beam passes through said first plate **21**, a support frame or structure **3** configured to support the first plate **21**, wherein the support frame **3** surrounds an opening **31** of the support frame **3** that extends from a front side **3a** of the support frame **3** to a back side **3b** of the support frame **3** so that light can pass the support frame **3**, a first spring structure **600** connected to the front side **3a** of the support frame **3**, wherein the first spring structure **600** comprises a first frame **607** to which the first plate **21** is connected, wherein the first frame **607** is tiltable about a first axis **A** with respect to the support frame **3**, and an actuator **5** configured to tilt the first plate **21** about the first axis **A** by means of a Lorentz force, wherein the actuator **5** comprises a first coil **60** and a second coil **61**, wherein said coils **60**, **61** are integrated into the support frame **3**, and wherein the actuator **5** comprises a first magnet **70** facing the first coil **60** and a second magnet **71** facing the second coil **61**, wherein the first and the second magnet **70**, **71** are connected to the first frame **607**.

(140) Particularly, the magnets **70**, **71** each comprise a magnetization oriented at an angle α between 80° and 100° with respect to a plane that extends perpendicular to the winding axes **W** of said coils **60**, **61** (cf. e.g. FIG. **6**).

(141) Particularly, the support frame **3** of the optical device **1** is formed by a printed circuit board, and preferably comprises a first arm **350** that opposes a second arm **351** of the support frame **3**, wherein the first and the second arm **350**, **351** are connected by a third and a fourth arm **352**, **353** of the support frame **3**.

(142) Furthermore, the first spring structure **600** comprises a first holding member **602** that is connected via a first torsion bar **601** to the first frame **607**, and a second holding member **604** that is connected via a second torsion bar **603** to the first frame **607**, wherein the first holding member **602** is connected to the third arm **352** of the support frame **3** on the front side of the support frame **3**, and wherein the second holding member **604** is connected to the fourth arm **353** of the support frame **3** on the front side of the support frame **3**. Particularly, the first holding member **602** can be connected to a first overmold **300** protruding from the support frame **3** (e.g. printed circuit board). Likewise the second holding member **604** can be connected to a second overmold **301** protruding from the support frame **3**.

(143) As indicated in FIG. **1(C)**, the first torsion bar **601** and the second torsion bar **602** are aligned with the first axis **A**, about which the plate **21** can be tilted.

(144) Further, particularly, the first holding member **602** is separated from the first frame **607** by two slots **605a**, **605b** that comprise a width that increases towards the first torsion bar. Furthermore, also the second holding member **604** can be separated from the first frame **607** by two slots **606a**, **606b** that comprise a width that increases towards the second torsion bar **603**. Particularly, for controlled etching, portions of the slots on either side of the respective torsion bar **601**, **603** can be symmetric as shown in FIG. **1(C)**.

(145) Particularly, the optical element (e.g. glass) **21** can be tilted about the axis **A** that extends at an angle of 45° with respect to the third arm **352** of the support frame, i.e. diagonally across the first frame **607**. Particularly, the tilt angle of the optical element **21** about axis **A** depends on pixel size and thickness of the optical element **21**. The thickness can e.g. be in the range from 0.5 mm to 1 mm resulting in an tilt angle in the range of e.g. 0.4° to 1.5° .

(146) As further shown in FIGS. **1(A)**, **3(C)** and **3(D)**, the first coil **60** is an L-shaped first coil **60** that comprises a first portion **60a** that is integrated into the first arm **351** of the support frame **3** and a second portion **60b** that runs perpendicular to the first portion **60a** of the first coil **60**, wherein the second portion **60b** of the first coil **60** is integrated into the fourth arm **353** of the support frame **3**,

and wherein the second coil **61** is an L-shaped second coil **61** that comprises a first portion **61a** that is integrated into the second arm **351** of the support frame **3** and a second portion **61b** that runs perpendicular to the first portion **61a** of the second coil **61**, wherein the second portion **61b** of the second coil **61** is integrated into the third arm **352** of the support frame **3**.

(147) Furthermore, the optical device **1** comprises a third magnet **72** facing the second coil **61** and a fourth magnet **73** facing the first coil **60**, wherein the third and the fourth magnet **72**, **73** are connected to the first frame **607**, and wherein the first magnet **70** faces the first portion **60a** of the first coil **60**, and wherein the second magnet **71** faces the first portion **61a** of the second coil **61**, and wherein the third magnet **72** faces the second portion **61b** of the second coil **61**, and wherein the fourth magnet **73** faces the second portion **60b** of the first coil **61**. Particularly, the magnets **72**, **73** can each comprise a magnetization **M3**, **M4** oriented at an angle α between 80° and 100° with respect to said plane mentioned above (cf. e.g. FIG. 6).

(148) Particularly, the first magnet **70** faces the first portion **60a** of the first coil **60** such that a magnetic field **B** generated by the first magnet **70** comprises a component parallel to the support frame **3** and perpendicular to a current **I** flowing through the first portion **60a** of the first coil **60** at the location of the first portion **60a** of the first coil **60** such that a Lorentz force **F.sub.L** is generated when an electrical current **I** is applied to the first coil **60** that pushes the first magnet **70** away from the first portion **60a** of the first coil **60** or pulls the first magnet **70** towards the first portion **60a** of the first coil **60** depending on the direction of the electrical current **I** in the first portion **60a** of the first coil **60** (cf. FIGS. 6 and 3(C)).

(149) In a similar fashion the fourth magnet **73** faces the second portion **60b** of the first coil **60** such that a magnetic field **B** generated by the fourth magnet **73** comprises a component parallel to the support frame **3** and perpendicular to a current **I** flowing through the second portion **60b** of the first coil **60** at the location of the second portion **60b** of the first coil **60** such that a Lorentz force **F.sub.L** is generated when an electrical current **I** is applied to the first coil **60** that pushes the fourth magnet **73** away from the second portion **60b** of the first coil **60** or pulls the fourth magnet **73** towards the second portion **60b** of the first coil **60** depending on the direction of the electrical current **I** in the second portion **60b** of the first coil **60** (cf. FIGS. 6 and 26(C)).

(150) Furthermore, analogously, the second magnet **71** faces the first portion **61a** of the second coil **61** such that a magnetic field **B** generated by the second magnet **71** comprises a component parallel to the support frame **3** and perpendicular to a current **I** flowing through the first portion **61a** of the second coil **61** at the location of the first portion **61a** of the second coil **61** such that a Lorentz force **F.sub.L** is generated when an electrical current **I** is applied to the second coil **61** that pushes the second magnet **71** away from the first portion **61a** of the second coil **61** or pulls the second magnet **71** towards the first portion **61a** of the second coil **61** depending on the direction of the electrical current **I** in the first portion **61a** of the second coil **61** (cf. FIGS. 6 and 3(C)).

(151) Finally, the third magnet **72** faces the second portion **61b** of the second coil **61** such that a magnetic field **B** generated by the third magnet **72** comprises a component parallel to the support frame **3** and perpendicular to a current **I** flowing through the second portion **61b** of the second coil **61** at the location of the second portion **61b** of the second coil **61** such that a Lorentz force **F.sub.L** is generated when an electrical current **I** is applied to the second coil **61** that pushes the third magnet **72** away from the second portion **61b** of the second coil **61** or pulls the third magnet **72** towards the second portion **61b** of the second coil **61** depending on the direction of the electrical current **I** in the second portion **61b** of the second coil **61**.

(152) Thus, by controlling the electrical currents applied to the first and to the second coil, the plate **21** can be tilted about the axis **A** shown in FIG. 1(C).

(153) Further, optionally the device **1** can comprise a static diffusor **211** (e.g. in case the optical element **21** is a diffusor), wherein the static diffusor faces the optical element **21**/diffusor **21**. Such a static diffusor **211** may also be used in other embodiments (e.g. FIG. 5).

(154) Furthermore, the optical device **1** may also comprise a Hall sensor **H** or another sensor **H** to

measure a position of the first spring structure **600**. Electrical contacts **305** for electrically contacting the device **1** can be arranged on one of the arms of the support frame **3**, e.g. on the first arm **350** or on the second arm **351**. As indicated in FIG. 3(D) the support frame (e.g. printed circuit board **36**) can comprise a flexible part comprising the contacts **305** for the electrical connections to the device **1**. However, such contacts **305** can in general be provided also on other locations of the device **1**.

(155) Furthermore, FIG. 2 shows a modification of the embodiment of the optical device **1** shown in FIG. 1, wherein here (in addition to the components shown in FIG. 1), the optical device **1** comprises a transparent second plate **210** for refracting the light beam L when the light beam L passes through said second plate **210**, wherein the first plate **21** faces the second plate **210**, and wherein the support frame **3** is configured to support the second plate **210**.

(156) Particularly, the optical device **1** comprises a second spring structure **700** connected to the back side **3b** of the support frame **3**, wherein the second spring structure **700** comprises a second frame to which the second plate **210** is connected, wherein the second frame **707** is tiltable about a second axis A' with respect to the support frame **3**, and wherein the actuator **5** is configured to tilt the second plate **210** about the second axis A' by means of a Lorentz force.

(157) To this end, the actuator **5** comprises a third **62** and a fourth coil **63**, wherein the third and the fourth coil **62**, **63** are integrated into the support frame **3**, and wherein the actuator comprises a third magnet **72** facing the third coil **63** and a fourth magnet **73** facing the fourth coil **63**, and wherein the third and the fourth magnet **73**, **74** are connected the second frame **707**.

(158) Particularly, in contrast to FIG. 1, the first and the second coil **60**, **61** do not comprise an L-shape but are arranged according to FIGS. 3(A) and 3(B), wherein the first coil **61** is integrated into the first arm **350** of the support frame **3** and the second coil is integrated into the opposing second arm **351** of the support frame **3**.

(159) In a similar fashion, the third coil **62** is integrated into the third arm **352**, and the fourth coil **63** is integrated into the fourth arm **353** of the support frame **3** (e.g. printed circuit board). Particularly, the first coil **60** and the second coil **61** can be electrically connected for push pull action on the axis A. Furthermore, the third coil **62** and the fourth coil **63** can be electrically connected for push pull action on the axis A'.

(160) Furthermore, as indicated in FIG. 3(B), one or more electronic components **306** of the device **1** can be arranged on the support frame **3**, e.g. on one of the arms (e.g. second arm **351**). Particularly, the respective electronic component **306** is arranged in the vicinity of the electrical contacts **305** (e.g. on the second arm **351**). Optionally, the device can comprise a Hall sensor H for each frame **607**, **707** for measuring the position of the corresponding frame **607**, **707**, particularly of the respective optical element **21**, **210**.

(161) Furthermore, as shown in FIGS. 2(A) and 2(B), the second spring structure **700** comprises a third holding member **702** that is connected via a third torsion bar **701** to the second frame **707**, and wherein the second spring structure **700** comprises a fourth holding member **704** that is connected via a fourth torsion bar **703** to the second frame **707**, wherein the third holding member **702** is connected to the first arm **350** of the support frame **3** on the back side **3b** of the support frame **3**, and wherein the fourth holding member **704** is connected to the second arm **351** of the support frame **3** on the back side **3b** of the support frame **3**. Also here, the respective holding member **604**, **602**, **702**, **704** can each be connected to an associated overmold **300**, **301**, **302**, **303** protruding from the support frame **3** (e.g. printed circuit board). Also here, electrical contacts **305** for electrically contacting the device **1** can be arranged on one of the arms of the support frame **3**, e.g. on the second arm **351**.

(162) Particularly, the third torsion bar **701** and the fourth torsion bar **703** are aligned with the second axis A' as shown in FIG. 2(A).

(163) Furthermore, the respective magnet **70**, **71**, **72**, **73** faces the respective coil **60**, **61**, **62**, **63** (cf. also FIG. 6) such that a magnetic field B generated by the respective magnet **70**, **71**, **72**, **73**

comprises a component parallel to the support frame 3 and perpendicular to a current I flowing through the respective coil 60, 61, 62, 63 at the location of the respective coil 60, 61, 62, 63 such that a Lorentz force is generated when an electrical current is applied to the respective coil 60, 61, 62, 63 that pushes the respective magnet 70, 71, 72, 73 away from the respective coil 60, 61, 62, 63 or pulls the respective magnet 70, 71, 72, 73 towards the respective coil 60, 61, 62, 63 depending on the direction of the electrical current I in the respective coil 60, 61, 62, 63. This allows to tilt the first frame 607 and therewith the first plate 21 about the first axis A and the second frame 707 and therewith the second plate 210 about the orthogonal second axis A'.

(164) Also here, the tilt angle about the respective axis A, A' depends on the pixel size and thickness of the respective optical element 21, 210. Particularly, the respective thickness can be in the range from 0.5 mm to 1 mm resulting in a respective tilt angle in the range from e.g. 0.4° to 1.5°.

(165) FIG. 4 shows a further arrangement of coils 60, 61 that can be used with the embodiment of the optical device 1 shown in FIG. 1(A) instead of the two L-shaped coils 60, 61.

(166) According to FIG. 4, the first coil 60 is an outer coil 60 and the second coil 61 is an inner coil 61, wherein the outer coil 60 surrounds the inner coil 61, and wherein the outer coil 60 comprises a first section 60a and an opposing second section 60b, and wherein the inner coil 61 comprises a first section 61a and an opposing second section 61b, wherein the first section 60a of the outer coil 60 extends adjacent the first section 61a of the inner coil 60, and wherein the second section 60b of the outer coil 60 extends adjacent the second section 61b of the inner coil 61.

(167) Furthermore, the outer coil 60 comprises a third section 60c connecting the first section 60a of the outer coil 60 to the second section 60b of the outer coil 60, and the inner coil 61 comprises a third section 61c extending adjacent the third section 60c of the outer coil 60, wherein the third section 61c of the inner coil 61 connects the first section 61a of the inner coil 61 to the second section 61b of the inner coil 60, and wherein the outer coil 60 comprises a fourth section 60d connecting the first section 60a of the outer coil 60 to the second section 60b of the outer coil 60, and wherein the inner coil 61 comprises a fourth section 61d extending adjacent the fourth section 60d of the outer coil 60, wherein the fourth section 61d of the inner coil 61 connects the first section 61a of the inner coil 61 to the second section 61b of the inner coil 61.

(168) Furthermore, as shown in FIG. 4, the first sections 60a, 61a of the outer and inner coil 60, 61 are integrated into the first arm 350 of the support structure 3, and the second sections 60b, 61b of the outer and inner coil 60, 61 are integrated into the second arm 351 of the support structure 3. Further, the third sections 60c, 61c of the outer and inner coil 60, 61 are integrated into the third arm 352 of the support structure 3, and the fourth sections 60d, 61d of the outer and inner coil 60, 61 are integrated into the fourth arm 353 of the support structure 3.

(169) Also here, the optical device 1 comprises magnets 70, 71, 72, 73 connected to the first frame 607 that are attracted or repelled by means of the coils 60, 61 to tilt the frame 607 and therewith the optical element 21 accordingly.

(170) Particularly, the first magnet 70 faces the first portions 60a, 61a of the outer coil 60 and the inner coil 60, 61 in a direction normal to a front side 3a of the support frame 3, and the second magnet 71 faces the second portions 60b, 61b of the outer and the inner coil 60, 61 in a direction normal to the front side 3a of the support frame 3. Furthermore, the third magnet 72 faces the third portions 60c, 61c of the outer coil 60 and the inner coil 61 in a direction normal to the front side 3a of the support frame 3, and the fourth magnet 73 faces the fourth portions 60d, 61d of the outer and the inner coil 60, 61 in a direction normal to the front side 3a of the support frame 3.

(171) Furthermore, each magnet 70, 71, 72, 73 comprises a magnetization M1, M2, M3, M4, wherein the respective magnetization M1, M2, M3, M4 extends orthogonal to the first plate 21, wherein the magnetization M1, M4 of the first and the fourth magnet 70, 73 point in the same direction while the magnetizations M2, M3 of the second and the third magnet 71, 72 point in the opposite direction.

(172) Particularly, the first magnet **70** faces the first portions **60a**, **61a** of the outer and the inner coil **60**, **61** and the fourth magnet **73** faces the fourth portions **60d**, **61d** of the outer and the inner coil **60**, **61** such that a magnetic field **B** generated by the first magnet **70** comprises a component parallel to the support frame **3** and perpendicular to a current **I** flowing through the first portion **60a** of the outer coil **60** and to an opposite current **I'** flowing through the first portion **61a** of the inner coil **61**, and such that a magnetic field **B** generated by the fourth magnet **73** comprises a component parallel to the support frame **3** and perpendicular to a current **I** flowing through the fourth portion **60d** of the outer coil **60** and to an opposite current **I'** flowing through the fourth portion **61d** of the inner coil **61** such that a resultant Lorentz force $F_{\text{sub.L}}$ is generated that pushes the first magnet **70** away from the first portions **60a**, **61a** of the outer and the inner coil **60**, **61** and the fourth magnet **73** from the fourth portions **60d**, **61d** of the outer and the inner coil **60**, **61** or that pulls the first magnet **70** towards the first portions **60a**, **61a** of the outer and the inner coil **60**, **61** and the fourth magnet **73** towards the fourth portions **60d**, **61d** of the outer and the inner coil **60**, **61**.

(173) In a similar manner, the third magnet **72** faces the third portions **60c**, **61c** of the outer and the inner coil **60**, **61** and the second magnet **71** faces the second portions **60b**, **61b** of the outer and the inner coil **60**, **61** such that a magnetic field **B** generated by the third magnet **72** comprises a component parallel to the support frame **3** and perpendicular to a current **I** flowing through the third portion **60c** of the outer coil **60** and to an opposite current **I'** flowing through the third portion **61c** of the inner coil **61** and such that a magnetic field **B** generated by the second magnet **71** comprises a component parallel to the support frame **3** and perpendicular to a current **I** flowing through the second portion **60b** of the outer coil **60** and to an opposite current **I'** flowing through the second portion **61b** of the inner coil **61** such that a resultant Lorentz force $F_{\text{sub.L}}$ is generated that pushes the third magnet **72** away from the third portions **60c**, **61c** of the outer and the inner coil **60**, **61** and the second magnet **71** from the second portions **60b**, **61b** of the outer and the inner coil **60**, **61** or that pulls the third magnet **72** towards the third portions **60c**, **61c** of the outer and the inner coil **60**, **61** and the second magnet **71** towards the second portions **60b**, **61b** of the outer and the inner coil **60**, **61**.

(174) Furthermore, FIG. 5 shows yet another embodiment of an optical device **1** that is particularly configured for enhancing the resolution of an image and/or for reduction of speckle patterns. According to FIG. 5, the optical device **1** comprises at least an optical element **21** configured to interact with a light beam **L** impinging on the optical element **21**, a support frame **3** configured to support the optical element **21**, a preferably monolithic spring structure **900** connected to the support frame **3**, wherein the spring structure **900** comprises a frame **909** to which the optical element **21** is connected, wherein the frame **909** is moveable with respect to the support frame **3**, and wherein the spring structure **900** comprises a first holding member **902** that is connected via a first spring element **901** to the frame **909**, and wherein the spring structure **900** comprises a second holding member **904** that is connected via a second spring element **903** to the frame **909**, and wherein the spring structure **900** comprises a third holding member **906** that is connected via a third spring element **905** to the frame **909**, and wherein the spring structure **900** comprises a fourth holding member **908** that is connected via a fourth spring element **907** to the frame **909**.

(175) Preferably, the monolithic spring structure **900** is formed out of a metal sheet. Furthermore, preferably, the respective spring element **901**, **903**, **905**, **907** comprises a curved shape comprising at least one inflection point **P1**, **P2**, **P3**, **P4**.

(176) Particularly, at the respective inflection point **P1**, **P2**, **P3**, **P4**, the curvature of the respective spring element **901**, **903**, **905**, **907** changes its sign, i.e. at the respective inflection point **P1**, **P2**, **P3**, **P4** a left-curved portion of the respective spring element **901**, **903**, **905**, **907** joins a right-curved portion of the spring element **901**, **903**, **905**, **907**. Particularly, the respective spring element **901**, **903**, **905**, **907** is curved in a manner that the respective spring element **901**, **903**, **905**, **907** comprises two arc-shaped portions that are connected such that the respective spring element **901**, **903**, **905**, **907** comprises an s-shape or a meandering shape as depicted in FIG. 5.

(177) Further, the optical device **1** comprises an actuator **5** that is configured to move the frame **909** with respect to the support frame **3** by means of a Lorentz force.

(178) According to a preferred embodiment, the support frame **3** is formed by a printed circuit board. Particularly, the support frame **3** preferably surrounds an opening **31** of the support frame **3** that extends from a front side **3a** of the support frame **3** to a back side **3b** of the support frame **3** so that light can pass the support frame **3**.

(179) Particularly, the support frame **3** comprises a first arm **350** that opposes a second arm **351** of the support frame **3**, and wherein the first and the second arm **350**, **351** are connected by a third and a fourth arm **352**, **353** of the support frame **3**.

(180) Furthermore, the first and the third arm **350**, **352** are joined at a first corner portion **910** of the support frame **3**, and wherein the third and the second arm **352**, **351** are joined at a second corner portion **911** of the support frame **3**, and wherein the second and the fourth arm **351**, **353** are joined at a third corner portion **912** of the support frame **3**, and wherein the fourth and the first arm **353**, **350** are joined at a fourth corner portion **913** of the support frame **3**.

(181) Now, for connecting the spring structure **900** to the support frame **3**, the first holding member **902** is connected to the first corner portion **910** of the support frame **3**, the second holding member **904** is connected to the second corner portion **911** of the support frame **3**, the third holding member **906** is connected to the third corner portion **912** of the support frame **3**, and the fourth holding member **908** is connected to the fourth corner portion **913** of the support frame **3**.

(182) Particularly, the respective corner portion **910**, **911**, **912**, **913** forms a protrusion to which the respective holding member **902**, **904**, **906**, **908** is connected.

(183) For tilting the frame **909**, the actuator **5** comprises a first coil **60**, a second coil **61**, a third coil **62** and a fourth coil **63**, wherein said coils **60**, **61**, **62**, **63** are preferably integrated into the support frame **3**. Furthermore, the actuator **5** comprises a first magnet **70** facing the first coil **60**, a second magnet **71** facing the second coil **61**, a third magnet **72** facing the third coil **62**, and a fourth magnet **73** facing the fourth coil **63**, wherein the magnets **70**, **71**, **72**, **73** are connected to the frame **909**.

(184) Particularly, each magnet **70**, **71**, **72**, **73** comprises a magnetization **M1**, **M2**, **M3**, **M4**, wherein the respective magnetization **M1**, **M2**, **M3**, **M4** extends orthogonal to the frame **909**, wherein particularly the first and the second magnetization **M1**, **M2** point in opposite directions (or in the same direction), and wherein particularly the third and the fourth magnetization **M3**, **M4** point in opposite directions (or in the same direction).

(185) Particularly, the first coil **60** is integrated into the first arm **350** of the support frame **3**, the second coil **61** is integrated into the second arm **351** of the support frame **3**, the third coil **62** is integrated into the third arm **352** of the support frame **3**, and the fourth coil **63** is integrated into the fourth arm **353** of the support frame **3**. Particularly, the support frame **3** can comprise or can be formed as a printed circuit board into which the coils **60**, **61**, **62**, **63** are integrated.

(186) As shown in FIG. 5(B), the respective magnet **70**, **71**, **72**, **73** faces the respective coil **60**, **61**, **62**, **63** such that a magnetic field **B** generated by the respective magnet **70**, **71**, **72**, **73** comprises a component parallel to the support frame **3** and perpendicular to a current **I** flowing through the respective coil **60**, **61**, **62**, **63** at the location of the respective coil **60**, **61**, **62**, **63** (cf. also FIG. 6) such that a Lorentz force is generated when an electrical current is applied to the respective coil **60**, **61**, **62**, **63** that pushes the respective magnet **70**, **71**, **72**, **73** away from the respective coil **60**, **61**, **62**, **63** or pulls the respective magnet **70**, **71**, **72**, **73** towards the respective coil **60**, **61**, **62**, **63** depending on the direction of the electrical current **I** in the respective coil **60**, **61**, **62**, **63**.

(187) Particularly, the actuator **5** is configured to apply electrical currents to the opposing first and second coil **60**, **61** so that the first magnet **70** and the first coil **60** attract one another and the second magnet **71** and the second coil **61** repel one another so that the frame **909** and therewith the optical element **21** is tilted about a first axis **A**, or wherein the actuator **5** is configured to apply electrical currents to the opposing first and second coil **60**, **61** so that the first magnet **70** and the first coil **60** repel one another and the second magnet **71** and the second coil **61** attract one another so that the

frame **909** and therewith the optical element **21** are tilted about the first axis A in the opposite direction.

(188) In the same fashion, the actuator **5** is preferably configured to apply electrical currents to the opposing third and fourth coil **62**, **63** so that the third magnet **72** and the third coil **62** attract one another and the fourth magnet **73** and the fourth coil **63** repel one another so that the frame **909** and therewith the optical element **21** are tilted about a second axis A', or wherein the actuator **5** is configured to apply electrical currents to the opposing third and fourth coil **62**, **63** so that the third magnet **72** and the third coil **62** repel one another and the fourth magnet **73** and the fourth coil **63** attract one another so that the frame **909** and therewith the optical element **21** are tilted about the second axis A' in the opposite direction.

(189) As shown in FIG. 5, the optical element **21** is a flat transparent plate having plane-parallel surfaces. However, in other embodiments, the optical elements **21** can be one of: a mirror, a lens, a prism or any other optical element that shall be tilted about e.g. two independent axes A, A'.

(190) In the following, relating to FIGS. 7 to 15, an aspect of the present invention is described in more detail, wherein the optical device **1** is preferably used for reducing speckle pattern (also referred to as speckle noise), wherein the device **1** comprises a movable diffuser **21** for diffusing a light beam L passing through said diffuser **21**, and a support structure **3** for supporting the diffuser **21**, wherein, as shown e.g. in FIG. 7, the movable diffuser **21** is supported on the support structure **3** by at least one elastically deformable member **90** comprising e.g. a polymer or e.g. a metal (or being formed out of a polymer or a metal) such that the diffuser **21** is movable along a first motion direction x extending along the support structure **3** and/or along a second motion direction y (perpendicular to the cross-sectional plane shown in FIG. 7) that also extends along the support structure **3**.

(191) As shown in FIGS. 7 and 11, the diffuser **21** can be supported on the support structure **3** by at least two elastically deformable members **90** that protrude from the support structure **3** (e.g. normal to a front side **3a** of the support structure **3**), wherein each elastically deformable member **90** comprises a polymer or a metal, or may be formed out of a polymer or a metal. Preferably, the diffuser **21** is supported on the support structure **3** by three or four such elastically deformable members **90**.

(192) Particularly, as shown in FIGS. 7 and 11, the respective elastically deformable member **90** is an elastically deformable, particularly bendable, pillar **90** protruding from the support structure **3** (e.g. from the front side **3a** of the support structure **3**). Particularly the pillars **90** can be configured so as to allow only lateral movement of the optical element/diffuser **21** (e.g. parallel to the support structure **3**/along the extension plane of the diffuser **21**).

(193) Particularly, as shown in FIG. 7, each pillar **90** can be connected to a corner region **21c** of the diffuser **21**.

(194) Alternatively, as shown in FIG. 11, the respective pillar **90** can be connected to a holding member **23**, wherein the diffuser **21** is connected to the holding member **23**.

(195) In the embodiments shown in FIGS. 7 and 11, the respective support structures **3** can delimit a through-opening **31** (not visible in FIG. 7) extending from a front side **3a** of the support structure **3** to a back side **3b** of the support structure **3**. Particularly, the respective diffuser **21** is arranged in front of said through-opening **31**, so that light L can pass through the diffuser **21** and through the support structure **3** via said through-opening **31**.

(196) Furthermore, as shown in FIG. 11, the optical device **1** can also comprise a static diffuser **210** that faces the movable diffuser **21**, wherein the static diffuser **210** can be arranged in front of or in said opening **31**. Particularly, the static diffuser **210** can be connected to the back side **3b** of the support structure **3**.

(197) For moving the diffuser **21** in the embodiments of the optical device **1** shown in FIGS. 7 and 11, an actuator can be used as described in conjunction with FIG. 13 (see below). Therefore, the optical device **1** preferably comprises a first and a second magnet **70**, **71** that can be connected to

the diffuser **21** as shown in FIG. **11**. Furthermore, each magnet **70**, **71** preferably faces an associated coil assembly **80**, **81** connected to the support structure **3**. Particularly, the respective coil assembly is integrated into the support structure, particularly into a printed circuit board **36** comprises by the support structure **3** or forming the support structure **3**.

(198) As an alternative to the pillars **90**, the optical device **1** can also comprise an elastically deformable membrane **90** as e.g. shown in FIGS. **8**, **9**, **10** and **12**. Also here, the membrane **90** can be configured so as to allow only lateral movement of the optical element/diffuser **21** (e.g. parallel to the support structure **3**/along the extension plane of the diffuser **21**).

(199) Here, the optical device **1** for reducing speckle noise, particularly comprises a movable diffuser **21** for diffusing a light beam **L** passing through said diffuser **21**, and, as before, a support structure **3** for supporting the diffuser **21**, wherein the movable diffuser **21** is supported on the support structure **3** by at least one elastically deformable membrane **90** that e.g. comprises a polymer (or is formed out of a polymer) such that the diffuser **21** is movable along a first motion direction **x** extending along the support structure **3** and/or along a second motion direction **y** extending along the support structure (the second motion direction **y** extends perpendicular to the shown cross-sectional plane of FIGS. **8**, **9**, **10(A)**, and **12**).

(200) Particularly, as shown in FIGS. **8**, **9**, **10(A)**, and **12**, the membrane **90** can comprise a circumferential edge region **90c** via which the membrane **90** is connected to the support structure **3** (cf. e.g. FIG. **10(B)**). Furthermore, as indicated in FIGS. **8**, **9**, **10(A)**, the diffuser **21** can be connected to a front side **90a** of the membrane **90**, wherein the front side **90a** of the membrane **90** faces away from the support structure (**3**). Alternatively, as shown in FIG. **12** for instance, the diffuser **21** can also be arranged on a back side **90b** of the membrane **90**, wherein the back side **90b** of the membrane **90** faces the support structure **3**.

(201) Furthermore, as shown in FIG. **9(A)**, the optical device **1** can comprise slide bearings **6** that are connected to the back side **90b** of the membrane **90**, which slide bearings **6** can be configured to slide on the support structure **3**. The slide bearings **6** can be sliding ruby discs. The slide bearings **6** can also be formed by the magnets that are then sliding directly on a surface of the device (e.g. a spacer glass).

(202) Alternatively or in addition, a first and a second magnet **70**, **71** of an actuator of the device **1** can be configured to slide on a front surface **3aa** of the support structure **3** as shown in FIG. **9(B)**. Particularly, as shown in FIGS. **10(A)** and **12**, said magnets **70**, **71** can be configured to slide on a ferro-fluid **7** arranged on a front surface **3aa** of the support structure **3**. Particularly, the respective front surface **3aa** can be formed by a layer formed out of a glass or a non-magnetic metal. The ferro-fluid lubricant reduces friction and serves for position definition and potential vibration elimination. Furthermore, the ferro-fluid can increase the magnetic field of the actuator. Optionally, a thin glass or non-magnetic metal plate **77** can be arranged on the support structure **3** and above the coil assemblies **80**, **81**, particularly on the printed circuit board **36**.

(203) Also in the embodiments relating to FIGS. **8**, **9**, **10(A)**, and **12** the respective support structure **3** (comprising or being formed as a printed circuit board **36**) can delimit a through-opening **31** extending from a front side **3a** of the support structure **3** to a back side **3b** of the support structure **3**. Particularly, the respective diffuser **21** can be arranged in front of said through-opening **31**, so that light **L** can pass through the diffuser **21** and through the support structure **3** via said through-opening **31**. Particularly, as shown in FIG. **12**, the optical device can comprise a static diffuser **210** that faces the movable diffuser **21**, wherein the static diffuser **210** can be arranged in front of or in said opening **31**. Particularly, the static diffuser **210** can be connected to the back side **3b** of the support structure **3**.

(204) For moving the diffuser **21** in the embodiments of the optical device **1** shown in FIGS. **8**, **9(B)**, **10(A)**, and **12**, an actuator can be used as described in conjunction with FIG. **13** (see e.g. below). In this case, the optical device **1** preferably comprises a first and a second magnet **70**, **71** that can be connected to the membrane **90** (particularly to the back side **90b**) as shown in FIGS. **8**,

9(B), and 10(A), or the diffuser 21 as shown in FIG. 12. Furthermore, each magnet 70, 71 preferably faces an associated coil assembly 80, 81 connected to the support structure 3. Particularly, as shown in FIGS. 9(B) and 10(A) the device 1 can comprise a return structure 38 arranged on a side of the printed circuit board 36, which side faces away from the diffuser 21.

(205) Particularly, instead of an elastically deformable membrane 90 as described above, the optical device 1 can also comprise at least one elastically deformable string. The string may comprise a polymer or may be formed out of a polymer.

(206) According to the embodiment shown in FIG. 10(C), the optical device 1 can comprise two such strings 90. Particularly, the two strings 90 extend parallel to one another along the support structure 3. Particularly, the respective string 90 comprises a first end section 90d and an opposing second end section 90e, wherein the end sections 90d, 90e are connected to the support structure 3. Particularly, the strings 90 can be integrally formed (e.g. by way of injection molding) with two opposing fastening portions 91, 92, via which fastening portions 91, 92 the two strings 90 are fastened to the support structure 3. The support structure 3 comprises or forms a substrate (e.g. printed circuit board 36) into which a coil assembly 80 as described herein can be integrated. Particularly, the fastening portions 91, 92 can be mounted to the printed circuit board 36. Furthermore, the diffuser 21 can be connected to a back side of the respective string 90, which back side faces the support structure 3. A magnet 70 can be connected to the diffuser 21 and is movable to move the diffuser 21 by means of the coil assembly 80 as will be described in more detail below in conjunction with FIG. 13.

(207) FIG. 13 shows yet another embodiment of an optical device 1 for reducing speckle noise that comprises an elastically deformable member in form of a membrane 90 for supporting the diffuser 21. Particularly, the device 1 comprises: a movable diffuser 21 for diffusing a light beam L passing through said diffuser 21, and a support structure 3 (e.g. frame) for supporting the diffuser 21, wherein the movable diffuser 21 is supported on the support structure 3 by an elastically deformable membrane 90 (comprising e.g. a polymer or being e.g. formed out of a polymer) such that the diffuser 21 is movable along a first motion direction x extending along the support structure 3 and/or along a second motion direction y extending along the support structure 3. The support structure 3 can comprise a printed circuit board. Particularly, the support structure 3 can be a printed circuit board.

(208) Particularly, the diffuser 21 can be connected to a front side 90a of the membrane 90, particularly via a spacer 95 (cf. FIG. 13(B)), wherein the front side 90a of the membrane 90 faces away from the support structure 3. The spacer 95 can be a double sided tape or a plastic part.

(209) Furthermore, preferably, the diffuser 21 forms a cantilever and protrudes beyond the support structure 3 in a first direction D1 as shown in FIG. 13(A).

(210) Further, the optical device 1 can also comprise a static diffuser 210 that faces the movable diffuser 21 (cf. FIG. 13(B)).

(211) For moving the diffuser 21 back and forth the first and/or second motion direction x, y, the optical device 1 comprises an actuator 5 that comprises a coil assembly 80 connected to the support structure 3 as shown in FIG. 13(B) and a magnet 70 connected to the membrane 90 (or alternatively to the movable diffuser 21) such that the magnet 70 faces the coil assembly 80. Particularly, the coil assembly is integrated into the support structure, particularly into the printed circuit board.

(212) As shown in FIG. 13(C), the coil assembly 80 comprises a first layer 80a comprising a first and a second coil 800, 801 arranged side by side so that a section 800a of the first coil 800 extends along an adjacent section 801a of the second coil 801, wherein particularly the first and the second coil 800, 801 are configured such that an electrical current I that flows through the first and through the second coil 800, 801 flows in the same direction in said adjacent sections 800a, 801a, and wherein the coil assembly 80 comprises a second layer 80b, wherein the first and the second layer 80a, 80b are arranged on top of one another, and wherein the second layer 80a comprises a third

and a fourth coil **802**, **803** arranged side by side so that a section **802a** of the third coil **802** extends along an adjacent section **803a** of the fourth coil **803**, wherein particularly the third and the fourth coil **802**, **803** are configured such that an electrical current I that flows through the third and the fourth coil **802**, **803** flows in the same direction in said section **802a** of the third coil **802** and in said adjacent section **803a** of the fourth coil **803**, and wherein, in a crossing region C of the coil assembly **80**, the section **800a** of the first coil **800** and the section **801a** of the second coil **801** each cross the section **802a** of the third coil **802** and the section **803a** of the fourth coil **802**.

(213) Furthermore, the magnet **70** comprises a magnetization $M1$ that points towards or away from the crossing region C of the coil assembly **80**. Particularly, the magnetization $M1$ is preferably orthogonal to a back side **70a** of the magnet **70**, which back side **70a** faces the crossing region C of the coil assembly **80** (cf. FIG. 13(B)).

(214) Furthermore, the magnetization $M1$ is preferably orthogonal to an electrical current I flowing through one of the sections **800a**, **801a**, **802a**, **803a** in the crossing region C of the coil assembly **80**

(215) Furthermore, said adjacent sections **800a**, **801a** of the first and second coil **800**, **801** of the first layer **80a** of the coil assembly **80** preferably extend along the second motion direction y .

Furthermore, said adjacent sections **802a**, **803a** of the third and fourth coil **802**, **803** of the second layer **80b** of the coil assembly **80** preferably extend along the first motion direction x .

(216) In order to move the diffusor **21** using the magnet **70** and coils **800**, **801**, **802**, **803** the optical device **1** is configured to apply an electrical current I to the first and the second coil **800**, **801** of the first layer **80a** of the coil assembly **80** such that the electrical current I flows in the same direction in said adjacent sections **800a**, **801a** of the first layer **80a** of the first coil assembly **80** such that a Lorentz force $F_{\text{sub.L}}$ is generated that moves the diffusor **21** along the first motion direction x .

(217) Similarly, the optical device **1** is preferably configured to apply an electrical current I to the third and to the fourth coil (**802**, **803**) of the second layer **80b** of the coil assembly **80** such that the electrical current I flows in the same direction in said adjacent sections **802a**, **803a** of the second layer **80b** of the coil assembly **80** such that a Lorentz force $F_{\text{sub.L}}$ is generated that moves the diffusor **21** along the second motion direction y .

(218) Particularly, the support structure **3** comprises or is formed as a substrate **36**, particularly in form of a printed circuit board, wherein the coil assembly **80** is integrated into this substrate **36**.

(219) FIG. 14(A) shows a modification of the embodiment shown in FIG. 13, wherein here in contrast to FIG. 13, the diffusor **21**, which is also supported on the support structure **3** via an elastically deformable membrane **90**, protrudes in two opposite direction $D1$ and $D2$ past the support structure **3**, so that light L can pass through the protruding portions of the diffusor **21** without being affected by the support structure **3**. Possible dimensions of the device **1** are indicated as an example in FIG. 14(A). Also here, the magnet **70** can face a coil assembly **80** of an actuator that can be configured as described in conjunction with FIG. 13. Particularly, having the diffusor protrude in both directions $D1$, $D2$ increases stability of the system.

(220) FIG. 14(B) shows a modification of the embodiment of the optical device **1** shown in FIG. 14(A). The optical device comprises a movable diffusor **21** for reducing speckle noise, wherein the diffusor is supported on a support structure **3**. Here, one or more membrane units (including motors) can be used to move the diffusor.

(221) Particularly, the support structure **3** delimits at least a first and a second through-opening **3c**, **31** extending from a front side **3a** of the support structure **3** to a back side (not shown) of the support structure **3**, respectively, wherein the movable diffusor **21** is arranged in front of the first (e.g. central) through-opening **3c**. Particularly, the second through-opening **31** can also be a recess that does not extend completely through the support structure **3**.

(222) The movable diffusor **21** is supported on the support structure **3** by at least one elastically deformable membrane **90** that is connected to the support structure **3** such that it extends in or over the second through-opening **31**. Particularly, a magnet **70** is connected to the at least one elastically deformable membrane **90**, wherein the diffusor **21** is connected via at least one holding element **96**

to the magnet **70**. Preferably, the magnet **70** is arranged such that it faces a coil assembly **80** connected to the support structure **3**. Also here, the magnet **70** and coil assembly **80** can form part of an actuator described in conjunction with FIG. **13**.

(223) Furthermore, as explicitly shown in FIG. **14(B)**, the optical device **1** may comprise a plurality of second through-openings or recesses **31** (e.g. four such through-openings **31**), wherein each second through-opening **31** can be covered by the at least one elastically deformable membrane **90**, wherein alternatively a separate elastically deformable membrane comprising a polymer or being formed out of a polymer can be arranged in or over each second through-opening **31**. Furthermore, a magnet **70** is arranged in front of or in the respective second through-opening **31** and connected to the at least one membrane **90** or the respective membrane **90**, wherein each magnet **70** is arranged in front of a coil assembly **80**. Further, each magnet **70** is connected via a holding element **96** to the diffusor **21** to hold the latter in front of the first (e.g. central) through-opening **3c** of the support structure **3**. Further, particularly, the respective coil assembly **80** and the respective magnet **70** that faces the coil assembly **80** can form part of an actuator described above in conjunction with FIG. **13**.

(224) Further, the second through-openings **31** can be arranged around the (e.g. central) first through-opening **3c**. Thus, with help of the actuator formed by the coil assemblies **80** and the associated magnets **70**, the diffusor is movable along a first motion direction x extending along the support structure **3** and/or along a second motion direction y extending along the support structure **3** according to the principles described herein.

(225) Particularly, the support structure **3** of the optical device **1** shown in FIG. **14** comprises or is formed as a substrate **36**, particularly in form of a printed circuit board, wherein the coil assembly **80** (or the coil assemblies **80**) is integrated into this substrate **36**.

(226) FIG. **15** shows yet another embodiment of an optical device **1** for speckle noise reduction. Also here, the device **1** comprises a movable diffusor **21** (and an optional static diffusor **210** facing the movable diffusor **21**), wherein the diffuser **21** (and the static diffuser **210**) are supported on a support structure **3**.

(227) Particularly, the support structure **3** delimits a first, a second and a third through-opening **31a**, **31b**, **31c** extending from a front side **3a** of the support structure **3** to a back side **3b** of the support structure **3**, respectively, wherein the movable diffusor **21** is arranged in front of a recess **3c** of the support structure **3**, and wherein the movable diffusor **21** is supported on the support structure **3** by an elastically deformable membrane **90** that is connected to the support structure **3** such that it covers said through-opening **31a**, **31b**, **31c**. Alternatively, the openings **31a**, **31b**, **31c** can be covered by separate membranes. Furthermore, the through-openings **31a**, **31b**, **31c** can also be formed as recesses that do not extend completely through the support structure **3**.

(228) Furthermore, a magnet **70** is connected to the membrane **90** covering the first through-opening **31a** and arranged in front of the first through-opening **31a**, wherein particularly the optical device **1** comprises a holding element **96** that connects the diffusor **21** to the magnet **70**. As shown in FIG. **15**, the holding element **96** can comprise a first arm **96a** that connects the magnet **70** to a first protrusion **961** of the holding element **96**, wherein the first protrusion **961** is supported on the membrane **90** and arranged in front of the second through-opening **31b**, and wherein the holding element **96** can comprise a second arm **96b** that connects the magnet **70** to a second protrusion **962** of the holding element **96**, wherein the second protrusion **962** is supported on the membrane **90** arranged in front of the third through-opening **31c**. Furthermore, the diffusor **21** is connected to the first and to the second arm **96a**, **96b**), and the magnet **70** is arranged such it faces a coil assembly **80** arranged in front of the opening **31a**.

(229) Particularly, the support structure **3** of the optical device **1** shown in FIG. **14** comprises or is formed as a substrate **36**, particularly in form of a printed circuit board, wherein the coil assembly **80** is integrated into this substrate **36**.

(230) Furthermore, particularly, the coil assembly **80** and the magnet **70** that faces the coil

assembly **80** can form part of an actuator described above in conjunction with FIG. **13** for moving the diffuser **21** along the first and/or second motion direction x, y.

(231) FIG. **16** shows another embodiment of an optical device **1** of the present invention that allows tilting of an optical element **21** (e.g. a transparent plate **21**) about two different axes A, A' so that the device can be used for pixel shifting/enhancing of a resolution of an image as described herein.

(232) Particularly, according to FIG. **16**, the optical device **1**, comprises a transparent plate **21** for refracting a light beam L passing through said plate **21**, wherein the plate **21** is tiltable, and wherein the plate **21** comprises a first end section **21e** and an opposing second end section **21f**. The transparent plate **21** can be a glass plate **21**.

(233) Further, the optical device **1** comprises a first spring structure **400** and an opposing second spring structure **500**, wherein the first spring structure **400** comprises an elongated first holding arm **401** connected to the first end section **21e** of the plate **21**, and wherein the second spring structure **500** comprises an elongated second holding arm **501** connected to the second end section **21f** of the plate **21**. Particularly, the plate **21** is glued to the holding arms **401**, **501**.

(234) The first holding arm **401** is connected via a first bar **402** to a first bendable member **403** of the first spring structure **400** and via a second bar **404** to a second bendable member **405** of the first spring structure **400**, and wherein the second holding arm **501** is connected via a third bar **502** to a third bendable member **503** of the second spring structure **500** and via a fourth bar **504** to a fourth bendable member **505** of the second spring structure **500**.

(235) Furthermore, the first bendable member **403** comprises a top portion **403a** and a pillar **403b** extending perpendicular to the top portion **403a** of the first bendable member **403**, wherein the pillar **403b** of the first bendable member **403** connects the top portion **403a** of the first bendable member **403** to a bottom portion **406** of the first spring structure **400**.

(236) Similarly, the second bendable member **405** comprises a top portion **405a** and a pillar **405b** extending perpendicular to the top portion **405a** of the second bendable member **405**, wherein the pillar **405b** of the second bendable member **405** connects the top portion **405a** of the second bendable member **405** to the bottom portion **406** of the first spring structure **400**.

(237) Furthermore, the third bendable member **503** comprises a top portion **503a** and a pillar **503b** extending perpendicular to the top portion **503a** of the third bendable member **503**, wherein the pillar **503b** of the third bendable member **503** connects the top portion **503a** of the third bendable member **503** to a bottom portion **506** of the second spring structure **500**.

(238) Similarly, the fourth bendable member **505** comprises a top portion **505a** and a pillar **505b** extending perpendicular to the top portion **505a** of the fourth bendable member **505**, wherein the pillar **505b** of the fourth bendable member **505** connects the top portion **505a** of the fourth bendable member **505** to the bottom portion **506** of the second spring structure **500**.

(239) For tilting the plate **21**, the optical device **1** according to FIG. **16** comprises an actuator **5** that comprises a first and a second coil **60**, **61** arranged on the bottom portion **406** of the first spring structure **400** such that the top portion **403a** of the first bendable member **403** faces the first coil **60** and forms a first air gap G with the first coil **60**, and such that the top portion **405a** of the second bendable member **405** faces the second coil **61** and forms a second air gap G' with the second coil **61**.

(240) In a similar fashion the actuator **5** further comprises a third and a fourth coil **62**, **63** arranged on the bottom portion **506** of the second spring structure **500** such that the top portion **503a** of the third bendable member **503** faces the third coil **62** and forms a third air gap G'' with the third coil **62**, and such that the top portion **505a** of the fourth bendable member **505** faces the fourth coil **63** and forms a fourth air gap G''' with the fourth coil **63**.

(241) These air gaps G, G', G'', G''' are preferably utilized to generate forces for tilting the plate **21** as will be described in the following.

(242) To this end, the first spring structure **400** is configured to guide magnetic flux generated by

the first or second coil **60, 61** (when an electrical current is applied to the first or second coil), and wherein the second spring structure **500** is configured to guide magnetic flux generated by the third or fourth coil **62, 63** (when an electrical current is applied to the third or fourth coil). In other words, each spring structure **400, 500** also forms a return structure for the magnetic flux.

(243) Particularly, the optical device **1** is configured to apply an electrical current to the respective coil **60, 61, 62, 63** such that the respective coil **60, 61, 62, 63** attracts the top portion **403a, 405a, 503a, 505a** of the associated bendable portion **403, 405, 503, 505** due to a reluctance force generated by the respective coil **60, 61, 62, 63** of the actuator **5**.

(244) Particularly, the optical device **1** is configured to apply an electrical current to the first and to the second coil **60, 61** or to the third and to the fourth coil **62, 63** to tilt the plate **21** about a first axis **A** extending parallel to the holding arms **401, 501**.

(245) Furthermore, the optical device **1** is configured to apply an electrical current to the first and to the third coil **60, 62** or to the second and to the fourth coil **61, 63** to tilt the plate about a second axis **A'** extending perpendicular to the holding arms **401, 501**.

(246) Preferably, the respective coil **60, 61, 62, 63** comprises a coil core **64** extending perpendicular to the top portion **403a, 405a, 503a, 505a** of the respective bendable member **403, 405, 503, 505**.

(247) Furthermore, the actuator **5** preferably comprises a first substrate **36a**, wherein the first and the second coil **60, 61** are integrated into the first substrate **36a** (the first substrate **36a** can be a printed circuit board), and a second substrate **36b**, wherein the third and the fourth coil **62, 63** are integrated into the second substrate **36b** (the second substrate **36b** can be a printed circuit board, too).

(248) Furthermore, for connecting the substrates **36a, 36b** with the respective spring structure **400, 500**, the first spring structure **400** comprises a first latching arm **407** for engaging with the first substrate **36a** of the actuator **5**, wherein the first latching arm **407** protrudes from the bottom portion **406** of the first spring structure **400** between the first and the second bendable member **403, 405** of the first spring structure (**400**), and the second spring structure **500** comprises a second latching arm **507** for engaging with the second substrate **36b** of the actuator **5**, wherein the second latching arm **507** protrudes from the bottom portion **506** of the second spring structure **500** between the third and the fourth bendable member **503, 505** of the second spring structure **500**.

Claims

1. An Optical device for speckle pattern reduction, comprising: a diffusor configured to diffuse a light beam passing through said diffusor to reduce a speckle pattern, a support frame configured to support the diffusor, a spring structure connected to the support frame, wherein the spring structure comprises a frame to which the diffusor is connected, wherein the frame is moveable with respect to the support frame, and wherein the spring structure comprises a first holding member that is connected via a first spring element to the frame, and an actuator configured to move the frame with respect to the support frame by means of a Lorentz force.
2. The optical device according to claim 1, wherein the spring structure comprises a second holding member that is connected via a second spring element to the frame.
3. The optical device according to claim 2, wherein the spring structure comprises a third holding member that is connected via a third spring element to the frame.
4. The optical device according to claim 3, wherein the spring structure comprises a fourth holding member that is connected via a fourth spring element to the frame.
5. The optical device according to claim 4, wherein the respective spring element comprises one of: a curved portion, an angled portion.
6. The optical device according to claim 1, wherein the spring structure is monolithic.
7. The optical device according to one of the claim 1, wherein the support frame is formed by or

comprises a printed circuit board.

8. The optical device according to one of the claim 1, wherein the support frame comprises a first arm that opposes a second arm of the support frame, and wherein the first and the second arm are connected by a third and a fourth arm of the support frame.

9. The optical device according to claim 8, wherein the first and the third arm are joined at a first corner portion of the support frame, and wherein the third and the second arm are joined at a second corner portion of the support frame.

10. The optical device according to claim 1, wherein the actuator comprises a first coil, a second coil, a third coil and a fourth coil, wherein said coils are integrated into the support frame, and wherein the actuator comprises a first magnet facing the first coil, a second magnet facing the second coil, a third magnet facing the third coil, wherein the magnets are connected to the frame.

11. The optical device according to claim 10, wherein the first coil is integrated into a first arm of the support frame, and wherein the second coil is integrated into a second arm of the support frame, and wherein the third coil is integrated into a third arm of the support frame.

12. An optical device for reducing speckle noise, comprising: a movable diffuser for diffusing a light beam passing through said diffuser, a support structure supporting the diffuser, wherein the movable diffuser is supported on the support structure by at least one elastically deformable member such that the diffuser is movable along a first motion direction extending along the support structure and/or along a second motion direction extending along the support structure, and wherein the at least one elastically deformable member is an elastically deformable pillar protruding from the support structure and being configured to allow lateral movement of the diffuser parallel to the support structure.

13. The optical device according to claim 12, wherein the at least one elastically deformable member comprises a metal or is formed out of a metal.

14. The optical device according to claim 12, wherein the diffuser is supported on the support structure by three or four elastically deformable members, wherein each elastically deformable member comprises or is formed out of a metal.

15. The optical device according to claim 12, wherein the pillars are bendable such that the diffuser can be moved parallel to the support structure.

16. The optical device according to claim 12, wherein the support structure delimits at least one recess or delimits at least one through-opening extending from a front side of the support structure to a back side of the support structure.

17. The optical device according to claim 16, wherein the diffuser is arranged in front of said at least one recess or through-opening such that light can pass through the diffuser and through the support structure via said recess or through-opening.

18. The optical device according to claim 12, wherein the optical device comprises an actuator for moving the diffuser along the first motion direction and/or along the second motion direction, wherein the actuator comprises at least a first coil assembly connected to the support structure and at least a first magnet connected to the at least one elastically deformable member and/or to the movable diffuser such that the at least one first magnet faces the at least one first coil assembly.

19. The optical device according to claim 12, wherein the support structure comprises a printed circuit board.
