

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250281313

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

KARMELI; Ron et al.

GRAFT SECURING SYSTEM, APPLICATOR AND METHOD

Abstract

A graft securing system including at least one expandable frame moveable from a collapsed state to an expanded state, and at least one anchor coupled to the frame via an elastic support strut, said anchor including: an anchor base, at least one deflectable prong protruding from said anchor base and having at least one penetration tip and at least one restraining sleeve at least partially slideably moveable along the at least one prong and wherein in the collapsed state, the support strut is biased radially centrally bringing the at least one anchor to point generally axially, parallel to a longitudinal axis of the frame.

Inventors: KARMELI; Ron (Haifa, IL), TEICHMAN; Eyal (Hod HaSharon, IL)

Applicant: Endoron Medical Ltd. (Kfar Saba, IL)

Family ID: 68843063

Assignee: Endoron Medical Ltd. (Kfar Saba, IL)

Appl. No.: 19/202953

Filed: May 08, 2025

Related U.S. Application Data

parent US continuation 18830465 20240910 parent-grant-document US 12295868 child US 19202953

parent US continuation 17120179 20201213 parent-grant-document US 12097136 child US 18830465

parent WO continuation PCT/IL2019/050664 20190612 PENDING child US 17120179

us-provisional-application US 62684339 20180613

Publication Classification

Int. Cl.: A61F2/848 (20130101); **A61B17/064** (20060101); **A61F2/07** (20130101)

U.S. Cl.:

CPC **A61F2/848** (20130101); **A61B17/064** (20130101); **A61F2/07** (20130101);
A61B2017/0645 (20130101); A61F2002/8483 (20130101); A61F2220/0008 (20130101);
A61F2220/0016 (20130101)

Background/Summary

RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 18/830,465, filed Sep. 10, 2024, now U.S. Pat. No. 12,295,868, which is a continuation of U.S. patent application Ser. No. 17/120,179, filed Dec. 13, 2020, now U.S. Pat. No. 12,097,136, which is a continuation of PCT Patent Application No. PCT/IL2019/050664 having the international filing date of Jun. 12, 2019, which claims the benefit of priority under 35 USC § 119(e) of U.S. Provisional Patent Application No. 62/684,339, filed on Jun. 13, 2018, the entire contents of each of which are incorporated herein by reference. [0002] This application is also related to U.S. patent application Ser. No. 12/224,601, filed on Sep. 2, 2008, entitled “FASTENING DEVICE”, and published as U.S. Patent Application Pub. No. 2009/0048665 to Miron et al., the entire contents of which are incorporated herein by reference.

FIELD OF THE INVENTION

[0003] The present invention, in some embodiments thereof, relates to systems and methods for repairing aneurysms and, more particularly, but not exclusively, to systems and methods for securing grafts to blood vessel walls.

BACKGROUND OF THE INVENTION

[0004] An aneurysm is a bulging, weak spot in the aorta that may be at risk for rupturing. In some cases, the aneurysm is in the descending aorta that is in the abdomen.

[0005] Open repair that involves a large incision in the abdomen to expose the aorta and application of a graft to repair the aneurysm. Open repair remains the standard procedure for an abdominal aortic aneurysm repair.

[0006] Endovascular aneurysm repair (EVAR) is a minimally invasive option in which case the large abdominal incision is replaced by a small incision in the groin. Surgical instruments are driven through a catheter in an artery in the groin and threaded up to the aneurysm. At the aneurysm, a stent and a graft are deployed and positioned to support the aneurysm. An exemplary EVAR aneurysm repair method is disclosed in U.S. patent application Ser. No. 12/224,601, published as U.S. Patent Application Pub. No. 2009/0048665 to Miron et al.

[0007] The foregoing examples of the related art and limitations related therewith are intended to be illustrative and not exclusive. Other limitations of the related art will become apparent to those of skill in the art upon a reading of the specification and a study of the figures.

SUMMARY OF THE INVENTION

[0008] The following embodiments and aspects thereof are described and illustrated in conjunction with systems, tools and methods which are meant to be exemplary and illustrative, not limiting in scope.

[0009] According to an aspect in accordance with some embodiments of the invention, there is provided a graft securing system, including: at least one expandable frame moveable from a collapsed state to an expanded state, and at least one anchor coupled to the frame via an elastic support strut, the anchor including: an anchor base, at least one deflectable prong protruding from the anchor base and having at least one penetration tip, and at least one restraining sleeve at least

partially slideably moveable along the at least one prong, and in the collapsed state, the support strut is biased radially centrally bringing the at least one anchor to point generally axially, parallel to a longitudinal axis of the frame. In some embodiments, in the expanded state, the support strut moves from the biased radially centrally state to a free straightened state bringing the at least one anchor to point radially outwards.

[0010] According to some embodiments, the system includes a graft at least partially enveloping the frame. In some embodiments, movement of the frame from the collapsed state to the expanded state drives the anchor through the graft and into the tissue. In some embodiments, the anchor includes a plurality of prongs biased in an open configuration to be at least partially deflected away from each other. In some embodiments, in a fully open state, the prongs are deflected away from each other and apply force radially centrally securing the graft between the tissue and the frame. In some embodiments, the anchor includes at least two juxtaposed prongs and the sleeve-stop includes a resilient outwardly curved proximal portion of at least one of the prongs.

[0011] According to some embodiments, at least a portion of the sleeve-stop abuts the anchor base. In some embodiments, the sleeve-stop interferes with proximal movement of the restricting sleeve urged against the sleeve-stop at a first force at which the anchor partially penetrates the tissue via the graft. In some embodiments, at a second force, greater than the first force the restricting sleeve is configured to urge the resilient outwardly curved proximal portion of at least one of the prongs radially centrally in respect to the prongs and slide proximally over the sleeve-stop. In some embodiments, at the second force the anchor fully penetrates the tissue via the graft.

[0012] According to some embodiments, the anchor includes at least two juxtaposed prongs including a buckling prevention lock. In some embodiments, the buckling prevention lock includes at least one protrusion extending from a first prong and received within a recess in a juxtaposed second prong. In some embodiments, the sleeve is a penetrating sleeve. In some embodiments, the sleeve includes at least one sharp tapered penetration tip. In some embodiments, a tip of the anchor is ground along at least one distal edge of at least one prong and forms at least one penetrating blade. In some embodiments, the distal edge is pointed from its narrow aspect and flat from its wide aspect. In some embodiments, the distal edge is pointed from both its narrow aspect and its wide aspect. In some embodiments, the frame includes a partially expanded state at which configured to maintain longitudinal stability of the frame during axial movement along a vessel wall.

[0013] According to some embodiments, the at the partially expanded state the frame includes one of a bottle neck shape and an hourglass shape. In some embodiments, the system includes an anchor-to-frame mounting system. In some embodiments, the anchor-to-frame mounting system includes: at least one anchor including a cutout, an elastic support strut includes a matching end having a pinhole, and a locking pin, and in a mounted state, the anchor elastic support strut matching end is threaded inside the cutout and the locking pin is threaded through the pinhole. In some embodiments, the pin is welded to the anchor elastic support strut matching end by single point welding.

[0014] According to an aspect of some embodiments in accordance with the current invention there is provided an applicator for a graft securing system, including: a control handle, an applicator head including a container portion, and at least one lumen connecting the handle to the applicator head, the container sized to accommodate a graft securing system including: at least one expandable frame moveable from a collapsed state to an expanded state, and at least one anchor coupled to the frame via a flexible support strut, the anchor including: an anchor base, at least one deflectable prong protruding from the anchor base and having at least one penetration tip, and at least one restraining sleeve at least partially slideably moveable along the at least one prong, and in the collapsed state, the support strut is biased radially centrally bringing the at least one anchor to point generally axially, parallel to a longitudinal axis of the frame.

[0015] In some embodiments, the head includes at least one balloon. In some embodiments, the

applicator includes a protective sleeve over the balloon. In some embodiments, the protective sleeve is made of silicone. In some embodiments, the balloon is axially moveable at least within the container. In some embodiments, the balloon and the frame are arranged concentrically. In some embodiments, the balloon is positioned distally to the frame. In some embodiments, the container includes at least one graft securing system frame holder and driver and at least one releasing sheath slidable over the graft securing frame holder and driver. In some embodiments, the frame holder and driver includes at least one frame holding pin disposed circumferentially at an external surface of the holder and driver.

[0016] In some embodiments, the frame includes at least one hole at least one end sized to receive the at least one holding pin. In some embodiments, the at least one releasing sheath is slidable distally towards the applicator tip over the frame and configured to lock the frame in place. In some embodiments, the at least one releasing sheath is slidable proximally away from the applicator tip releasing the frame.

[0017] According to an aspect of some embodiments of the current invention there is provided a method for deploying a graft securing system including: positioning a graft securing system applicator at a desired location, partially expanding a frame and partially driving one or more anchors into tissue via a graft, optionally verifying the deployment location and orientation of the frame in respect to the tissue and at least one of fully expanding the frame and fully driving the anchors into the tissue, and retracting the frame and repositioning the applicator. In some embodiments, the method comprises locking at least one end of the frame prior to positioning the graft securing system. In some embodiments, the method comprises partially expanding the frame while the at least one end is locked. In some embodiments, the method comprises locking the frame by sliding a releasing sheath distally over the frame. In some embodiments, the method comprises releasing the frame by retracting a releasing sheath proximally and exposing the frame.

[0018] According to an aspect of some embodiments in accordance with the current invention there is provided a method for deploying a graft securing system including: positioning a graft securing system applicator at a desired location, positioning a balloon within a distal portion of graft securing system frame, concurrently or consecutively partially exposing at least a portion of the graft securing system frame and allowing self-expansion of at least the distal portion, expanding the balloon from a deflated state to an expanded state and urging the partially expanded distal portion of the frame against a graft and the tissue, deflating the balloon, fully exposing and allowing self-expansion of the frame, while concurrently releasing and urging anchors of the graft securing system radially outwards to at least partially penetrate the graft and tissue, translating the balloon proximally and positioning the balloon fully within the frame, and fully expanding and urging the frame against the graft tissue thereby fully implanting the anchors in the tissue and securing the graft to the tissue.

[0019] According to an aspect of some embodiments in accordance with the current invention there is provided a graft securing kit including: at least one graft securing system, including: at least one expandable frame moveable from a collapsed state to an expanded state, and at least one anchor coupled to the frame via a flexible support strut, the anchor including: an anchor base, at least one deflectable prong protruding from the anchor base and having at least one penetration tip, and at least one restraining sleeve at least partially slideably moveable along the at least one prong, and in the collapsed state, the support strut is biased radially centrally bringing the at least one anchor to point generally axially, parallel to a longitudinal axis of the frame, and at least one applicator including: a control handle, an applicator head including a container portion, and at least one lumen connecting the handle to the applicator head, the container sized to accommodate at least the graft securing system.

[0020] In addition to the exemplary aspects and embodiments described above, further aspects and embodiments will become apparent by reference to the figures and by study of the following

Description

DETAILED DESCRIPTION

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

[0021] Exemplary embodiments are illustrated in referenced figures. Dimensions of components and features shown in the figures are generally chosen for convenience and clarity of presentation and are not necessarily shown to scale. The figures are listed below.

[0022] FIG. 1A is a top view simplified illustration of a graft securing system in accordance with some embodiments of the invention;

[0023] FIGS. 1B, 1C and 1D are perspective view and side view simplified illustrations of a graft securing system in accordance with some embodiments of the invention;

[0024] FIGS. 2A-2D are side view and perspective view simplified illustrations of an anchor of a graft securing system in accordance with some embodiments of the invention;

[0025] FIGS. 3A and 3B, are side view simplified illustrations of an anchor of a graft securing system in accordance with some embodiments of the invention;

[0026] FIGS. 4A, 4B, 4C, 4D and 4E are plan view, partial cross-section view, side view and perspective view simplified illustrations of an anchor of a graft securing system in accordance with some embodiments of the invention;

[0027] FIG. 5 is a perspective view simplified illustration of an anchor of a graft securing system in accordance with some embodiments of the invention;

[0028] FIGS. 6A, 6B and 6C are side view simplified illustrations of implementation of a graft securing system in accordance with some embodiments of the invention;

[0029] FIGS. 7A and 7B are perspective view simplified illustrations of a graft securing system in accordance with some embodiments of the invention;

[0030] FIGS. 8A and 8B are perspective view simplified illustrations of a graft securing system in accordance with some embodiments of the invention;

[0031] FIGS. 9A and 9B are perspective view, side view and cross section view simplified illustrations of a delivery system for a graft securing system delivery device in accordance with some embodiments of the invention;

[0032] FIGS. 10A and 10B are side view simplified illustrations of a graft securing system delivery device for in accordance with some embodiments of the invention;

[0033] FIGS. 11A, 11B, 11C and 11D are cross section view simplified illustrations of a graft securing system delivery device in accordance with some embodiments of the invention;

[0034] FIG. 12 is a perspective view simplified illustration of an anchor release system of a graft securing system in accordance with some embodiments of the invention; and

[0035] FIGS. 13A, 13B, 13C and 13D are cross-section view simplified illustrations of frame types in according with some embodiments of the current invention.

DESCRIPTION OF SPECIFIC EMBODIMENTS OF THE INVENTION

[0036] According to an aspect of some embodiments of the invention there is provided a graft securing system, having a frame and a plurality of anchors mounted on the frame and configured to approximate and attach a graft to a blood vessel wall. In some embodiments, the blood vessel is the aorta. In some embodiments, the graft is a stent-graft. In some embodiments, the graft is sandwiched between the frame and the blood vessel wall. In some embodiments the frame comprises a ring form.

[0037] In accordance with some embodiments of the invention, the frame is expandable to an expanded state and collapsible to a retracted state. In some embodiments, in the expanded state, the frame urges the anchors that translate radially outwards and penetrate a wall of a tubular structure e.g., a blood vessel, from an internal surface (e.g., endothelial side) of the vessel facing the frame through the vessel wall. As is explained in detail elsewhere herein, once the anchors penetrate the

vessel wall, they deform to engage an external surface of the vessel wall. In some embodiments, the anchors are urged through a graft prior to penetrating the wall of the vessel, so that the anchors penetrate the graft followed by the vessel wall and affix the graft to the blood vessel wall. In some embodiments, the frame applies a radially outwards force to the anchors.

[0038] According to an aspect of some embodiments of the invention there is provided a graft securing system, comprising a frame and a plurality of anchors mounted on the frame, and comprising one or more prongs protruding from a base of the anchor, and a restraining sleeve slidably mounted on and encircling the prongs, wherein the prongs comprise a distal (away from the frame and towards the tissue) penetration tip and one or more sleeve-stops e.g., restraining grooves, configured to temporarily prevent sliding of the restraining sleeve along the prongs and/or the penetration tip.

[0039] In some embodiments, the anchor penetration tip is wider than a prong portion just proximal (towards the frame and away from the anchor tip) to and adjacent to the penetration tip. In some embodiments, a sleeve-stop is formed on at least one prong and restricts at least a portion of the restraining sleeve from sliding distally over the penetration tip. In some embodiments, the sleeve length is shorter than the length of the prongs, so that the sleeve is slidable along the prongs between the sleeve-stop and the anchor base.

[0040] In some embodiments, sliding the restraining sleeve from the distal end of the anchor to the proximal end of the anchor brings the anchor from a restrained-closed state to an unrestrained-open state. In some embodiments, in the restrained configuration, the anchor prongs are juxtaposed in a closed state. In some embodiments, in the unrestrained configuration the anchor prongs are in an open state in which the prongs are at least partially deflected away from each other. In some embodiments, the prongs are resilient. In some embodiments, the prongs are made of a shape memory material. According to some embodiments of the invention, when the restraining sleeve is urged towards the base of the anchor, the restraining sleeve slides towards the base of the anchor over the prongs, thereby freeing the prongs to bend in any direction.

[0041] According to an aspect of some embodiments of the invention there is provided a graft securing system, comprising one or more ring-shaped frames, comprising a plurality of anchors protruding radially outward. In some embodiments, the ring-shaped frames are configured to penetrate tissue when urged against the tissue by radial expansion of the ring-shaped frames. In some embodiments, the system comprises two or more ring-shaped frames, and one or more latches configured to secure at least two rings to each other after being axially juxtaposed.

[0042] According to some embodiments of the invention, one or more of the rings form a stent-like frame configured to be secured to and support a blood vessel. According to some embodiments of the invention, the anchors of at least one of the rings comprise a penetration tip at the distal end and an anchor base at the proximal end, two or more prongs protruding distally from the anchor base and forming the penetration tip of the anchor at their distal end and a restraining sleeve, slidably enclosing the anchor prongs and restricting the deflection of the prongs. In some embodiments, the restraining sleeve is slidable on and along the prongs between the anchor base and the penetration tip.

[0043] According to an aspect of some embodiments of the invention there is provided a graft securing system applicator comprising: one or more lumens coupled at a distal end to an applicator head. In some embodiments, the applicator comprises a container portion at a proximal end of the applicator lumen. In some embodiments, the graft securing system is disposed within the container portion prior to applying the securing system within a treatment site. In some embodiments, applicator container comprises one or more axially movable sheaths disposed over the at least a portion of the securing system. In some embodiments, a securing system holder is disposed at a proximal end of the head lumen.

[0044] According to some embodiments, the graft securing system is delivered by the applicator to a treatment site via a delivery catheter.

Graft Securing System

[0045] Reference is now made to FIGS. 1A to 1C, which are top view and perspective view simplified illustrations of a graft securing system in accordance with some embodiments of the invention. As shown in FIGS. 1A-1C, graft securing system **10** comprises: a frame **40** and a plurality of anchors **100**. In some embodiments, anchors **100** comprise one or more prongs **140** connected at a base **142** and held in a restricted configuration by a restraining sleeve **160**. In some embodiments, frame **40** is cylindrical or tubular.

[0046] In accordance with some embodiments of the invention, the anchors **100** secure a graft **80** to a blood vessel wall **90**. In some embodiments, the frame **40** moves the anchors **100** radially outward (away from the frame **40**), which, in turn penetrate the graft **80** and the wall of blood vessel **90**. In some embodiments, the anchors **100** translate the radially outward force applied by frame **40** into a penetrating force and penetrate graft **80**. Anchors **100** approximate and attach graft **80** to the blood vessel wall **90**.

[0047] According to some embodiments, after penetrating the graft **80** and blood vessel wall **90**, the anchors **100** assume an expanded state, in which prongs **140** of the anchors **100** deflect to lie against an outer surface **92** of blood vessel wall **90** and urge blood vessel wall radially centrally (towards the frame **40**) against graft **80** and, optionally, frame **40**.

[0048] A potential advantage in this configuration for approximating blood vessel wall **90** and graft **80** is in that in the fully expanded state, prongs **140** are deflected away from each other and apply force radially centrally securing the graft between the tissue and the frame **40** so that graft **80** and the vessel wall **90** are sandwiched between anchor **100** prongs **102** and base **142** and frame **40** struts.

[0049] Blood vessel wall **90** and graft **80** are secured to each other at the blood vessel wall site of penetration by anchor **100** with no necessary physical contact between frame **40** and the graft. In some embodiments, the graft **80** is a stent-graft.

[0050] In the exemplary embodiment depicted in FIGS. 1A-1C anchors **100** are mounted on frame **40** via one or more anchor support struts **45**. In some embodiments and as shown in FIGS. 1A-1C, anchors **100** are mounted on anchor support struts **45** at an angle (e.g., 90 degrees) in respect to a longitudinal axis of frame **40** pointing radially outward. In some embodiments and as explained elsewhere herein, frame **40** is radially expandable and collapsible.

[0051] As shown in FIGS. 1A-1D, in accordance with some embodiments of the invention, the frame **40** is expandable and collapsible. In some embodiments, the frame **40** is a radially expandable securing ring. In some embodiments as shown in FIGS. 1B, 1C and 1D, the frame **40** is stent-like however, frame **40** may comprise any suitable collapsible/expandable structure. In some embodiments, frame **40** is expandable from a collapsed state (FIG. 1D) to an expanded state (FIGS. 1B and 1C). In some embodiments, the system comprises a stent graft within or outside frame **40**. In some embodiments, the stent graft lies between frame **40** and the vessel wall.

[0052] In some embodiments, and as showed in FIG. 1A, in the collapsed state, frame **40** e.g., when within releasing sheath **1230** as explained in greater detail herein, anchor support struts **45** are elastically biased radially centrally bringing anchors **100** to point generally axially, parallel to longitudinal axis of frame **40**.

[0053] In some embodiments, in the expanded state shown for example in FIG. 1B, anchor support struts **45** move by an elastic force from the biased radially centrally state to a free straight state in which support struts **45** are straightened and are realigned with the longitudinal axis of frame **40**, bringing anchors **100** to point radially outward. In some embodiments, at the expanded state anchors **100** are angled generally perpendicularly to longitudinal axis of frame **40**.

[0054] As shown in FIG. 1A-1C, anchor **100** comprises an anchor base **142** configured for mounting the anchor **100** on the frame **40** and two or more adjacent prongs **140** protruding from the anchor base **142** and forming a penetration tip **120**. Anchor **100** comprises a restraining sleeve **160** mounted on prongs **140**. In some embodiments, restraining sleeve **160** encircles prongs **140**. In

some embodiments, restraining sleeve **160** limits the prongs **140** from deflecting in opposing directions.

[0055] Turning to FIGS. **2A** to **2D**, which are side view and perspective view simplified illustrations of implementation of an anchor **200** in accordance with some embodiments of the invention. For the purpose of simplifying the explanation the anchors shown in FIGS. **2A-2C**, **3A-3B**, **4A-4C** and **5**, anchors are shown detached from the frame **40** and the anchor support strut **45**.

[0056] As shown in FIG. **2A**, a graft **280** and the blood vessel wall **290** are disposed adjacent to each other. As shown in FIGS. **2A** and **2B**, anchor **200** is urged against graft **280** and blood vessel wall **290** by a force (indicated by arrow **201**) applied to anchor base **260** in a radially outward direction. In operation, force **201** is generated by expansion of frame **40**. The penetration tips **220** of anchor **200** penetrate the graft **280** from an inner surface **284** of the graft **280**, through graft **280** and into an inner (e.g., endothelial) surface **294** of the blood vessel wall **290**, to engage an opposing outer surface **296** thereof.

[0057] As shown in FIG. **2A**, anchor **200** comprises one or more prongs **240** and a restraining sleeve **230**. In some embodiments, the length of restraining sleeve **230** is shorter than the length of prongs **240**, thereby the restraining sleeve **230** is slidable over and along the prongs **240** between the penetration tip **220** and base **260**. In some embodiments, the restraining sleeve **230** is blocked from sliding over the distal ends of prongs **240-1** and **240-4** by a restraining sleeve-stop **245** formed by the tips **220** of the prongs **240**. In some embodiments, the base **260** of the anchor **200** is wider than the internal cross section of the restraining sleeve **230**, thereby, sleeve **230** is limited from sliding proximally over the base **260** of the anchor **200**. In some embodiments, the restraining sleeve-stop **245** is shaped as a rib protruding laterally outwards from prongs **240** and extend beyond an internal cross section of the restraining sleeve **230**. As shown in FIGS. **2A** to **2C**, the prongs **240** are resilient and are made of a shape memory material e.g. Nitinol. The prongs **240** are pre-shaped to assume the pre-shaped unrestrained configuration in which the anchor prongs **240** are in an open state and the prongs **240** are deflected away from each other as indicated by broken-line arrows **250**.

[0058] FIG. **2A** depicts an exemplary embodiment in which anchor **200** is at a maximally restrained state, in which the anchor prongs **240-1** to **240-4** are juxtaposed throughout their length. FIG. **2C** is an exemplified embodiment in which anchor **200** is at a maximally unrestrained state, and FIG. **2B** is an exemplary embodiment in which anchor **200** is at a partially restrained state (or a partially unrestrained state). Anchor **200** is configured to assume a maximally restrained state (FIG. **2A**) when restraining sleeve **230** engages restraining sleeve-stop **245** and pre-shaped to assume a maximally unrestrained state (FIG. **2C**) when restraining sleeve **230** engages anchor base **260**, is distant of the restraining sleeve-stop **245** and frees prongs **102** to bend into their pre-shaped open (unrestrained) state. In some embodiments as shown in FIG. **2B**, the penetration tip **220** of any one of the prongs **240-1** to **240-4** is deflected laterally at a partially restrained state.

[0059] In some embodiments, and as shown in FIGS. **2A-2C**, anchor **200** comprises four prongs **240** (**240-1** to **240-4**). Two prongs are internal prongs **240-2/240-3**, disposed between two prongs **240-1/240-3** and **240-2/240-4** respectively). In some embodiments, two of the prongs are external prongs **240-1/240-4**, each positioned next to an internal prong **240-2/240-3** respectively so that to form two pairs of prongs **240-1/240-2** and **240-3/240-4**. In some embodiments, the two pairs of prongs **240-1/240-2** and **240-3/240-4** deflect away from each other when assuming an unrestrained state. In some embodiments, the internal prongs **240-2** and **240-3** are slidable along the adjacent external prongs **240-1** and **240-4** respectively when deflecting outwards towards an unrestrained state. In some embodiments, the internal prongs **240-2** and **240-3** apply deflecting force on the adjacent external prongs **240-1** and **240-4** respectively when deflecting to an open-unrestrained state.

[0060] As shown in FIGS. **2B** and **2C**, as restraining sleeve **260** slides towards the anchor base **230**, the pair of the external prongs **240-1/240-4** and the internal prongs **240-2/240-3** deflect in opposite

directions into the unrestrained state distancing penetration tips **220** from each other. In some embodiments, the internal prongs **240-2/240-3** and external prongs **240-1/240-4** apply an outwards oriented force vector to each side of the anchor **200**. In the exemplary embodiment shown in FIGS. **2A-2C**, the tip of the anchor **200** comprises a dual tip **220** of the two pairs of the internal prongs **240-2/240-3** and external prongs **240-1/240-4**. In some embodiments, the force **201** applied on the anchor **200** by expanding the frame **40**, is translated into a mechanical change in anchor **100** configuration allowing prongs **240** to bend in opposite directions and bring penetrating tips **220** to urge against external surface **296** of the blood vessel wall **290**, opposite to the penetration direction thereby affixing the blood vessel wall **290** to graft **280**.

[0061] In some embodiments the anchor **200** is in a fully expanded state and the graft **280** is sandwiched between the anchor **200** base **260** and the blood vessel wall **290** when restraining sleeve **230** is moved towards base **260**. In some embodiments, sleeve **230** is moved to fully abut base **260** as shown in FIG. **2C**.

[0062] In some embodiments as shown in FIGS. **1A** and **2A-2C**, a force applied on the restraining sleeve **160/230** initiates the sliding of the restraining sleeve **160/230** towards the anchor tip **120/220** (distally) or towards the anchor base **142/260** (proximally). In the exemplary embodiment depicted in FIGS. **2A-2C**, blood vessel wall **290** and/or graft **280** resist penetration of restraining sleeve **160/230** creating a reactive force opposite to force **201**. In some embodiments, the restraining sleeve **160/230** comprises an anchor base-facing flat surface **232** of restraining sleeve **160/230**. In some embodiments, the restraining sleeve **160/230** comprises an anchor tip-facing flat surface **234**. In some embodiments, the restraining sleeve **160/230** is urged in a proximal direction by a force applied on a base-facing surface **232** or a tip-facing flat surface **234** of the restraining sleeve **160/230**. In some embodiments, as shown in FIGS. **2A-2C**, restraining sleeve **230** is flat and short in length and is configured to remain inside the blood vessel and urged against the graft **280** while the prongs **240** penetrate the graft **280** and the blood vessel wall **290**. In some embodiments, the sleeve **230** does not engage the inside (endothelial) surface of the blood vessel wall **290**.

[0063] In some embodiments, and as shown in FIG. **2D**, which is a perspective view of anchor **100**-to-frame **40** mounting system. In FIG. **2D**, anchor **100** is mounted on frame **40** being in an expanded state similar to that shown in FIG. **1B**. In some embodiments, the anchor base **260** comprises a cutout **265**, which is used to attach the anchor **200** onto an anchor support strut **45** of the frame **40** (e.g. a stent-like frame **40**), by fitting the cutout **265** onto a matching end **45-1** of anchor support strut **45**. In some embodiments, a locking pin **255** is driven via a pinhole in matching end **45-1** locking anchor **200** to the matching end **45-1** of anchor support strut **45**. Since matching end **45-1** and cutout **265/365** as well as locking pin **255** share the stress involved with implementation of system **100**, only movement of locking pin **255** within the pinhole needs to be secured. In some embodiments, pin **255** is glued, welded, bonded or attached in any other suitable technique to support strut **45**. In some embodiments, the anchor **200** is locked to the frame **40** after being fitted on the frame **40**. In some embodiments, the anchor **200** is integrally formed on the frame **40** by laser cutting and thermoforming manufacturing process.

[0064] A potential advantage in the locking mechanism of anchor **200** to support strut **45-1** attachment is in that the point of flexion or bending of support strut **45** is proximal and relatively distant from the attachment and thus and a zone surrounding locking pin **255** encounter minimal stress, at least than the stress encountered by support strut **45**, while the anchor is forcibly aligned by the frame **40** and is not affected by bending elastic forces applied to support strut **45** reducing chances of weakening, breakage or detachment of anchor **100** from support strut **45**.

[0065] A potential advantage in the locking mechanism of anchor **200** to support strut **45-1** is in that welded Nitinol is very sensitive to stress (e.g., stress resulting from bending). The described attachment-by-locking pin **255** solution includes single point welding to secure the locking pin **255**.

[0066] A potential advantage in the locking mechanism of anchor **200** to support strut **45-1** is in that a restraining sleeve can be threaded onto the anchor prongs in a distal direction from the base

of the anchor, which is relatively narrow, towards the tip of the anchor, which is relatively wider, as indicated in FIG. 4E by arrow 450.

[0067] According to some embodiments of the invention as shown in FIGS. 2A-2C, the anchor 200 comprises an even number of prongs (four) 240 (240-1 to 240-4). In the exemplified embodiment of FIGS. 2A-2C two prongs 240-2/240-3 are internal prongs, disposed between two other prongs 240-1/240-3 and 240-2/240-4 respectively. Two of the prongs 240-1/240-4 are external prongs, each positioned next to an internal prong 240-2/240-3 respectively so that to form two pairs of prongs 240-1/240-2 and 240-3/240-4. In some embodiments, the anchor comprises an odd number of prongs. In some embodiments, the anchor comprises an odd number of internal prongs.

[0068] Referring now to FIGS. 3A and 3B, which are side view and perspective view simplified illustrations of an anchor 300 (excluding its restraining sleeve), in accordance with some embodiments of the invention. As shown in FIGS. 3A and 3B, in some embodiments, the anchor 300 comprises a pair of external prongs 340-1/340-2 and is free of internal prongs.

[0069] The anchor 300 shown in FIG. 3A in a maximally restrained position and FIG. 3B in maximally unrestrained position, comprise two prongs 340-1/340-2. The tip 320 of the anchor 300 is formed by two tip halves 320-1/320-2-one half on each prong so that juxtaposed prongs 340-1/340-2 bring tip halves 320-1/320-2 into juxtaposition to form a single complete tip 320. A potential advantage of this configuration is in that a force applied on the anchor 300 by a frame (not shown) results in juxtaposed prongs tip halves 320-1/320-2 to act as a single penetrating tip 320 in a closed state (FIG. 3A) while maintaining a lower material (e.g., Nitinol) volume and a low-profile in an open deployed state (FIG. 3B).

[0070] A potential advantage of this configuration is in that a single tip or a single tip comprising two halves of a tip has a smaller surface area in respect to a double-tipped anchor as shown in FIGS. 2A-2D and reduced resistance when penetrating graft 280 and blood vessel wall 290.

[0071] In the exemplary embodiment depicted in FIGS. 3A and 3B the anchor base 360 comprises a rectangular cut 365, which is used to attach the anchor 300 onto anchor support strut 45 of a frame 40, e.g. a stent or an expandable ring (not shown). As shown in FIGS. 3A and 3B, the restraining sleeve (not shown) is blocked from sliding over the anchor penetration tip 320 by a protruding restraining sleeve-stop 345 formed at the distal ends of prongs 340-1/2. In addition, the sliding of the restraining sleeve (not shown) towards base 360 is temporarily limited by a second protruding restraining sleeve-stop 347 formed between protruding restraining sleeve-stop 345 and the anchor base 360.

[0072] Reference is now made to FIGS. 4A to 4E which are plan, partial cross-section, side and perspective view simplified illustrations of penetration portions anchors, in accordance with some embodiments of the invention. The embodiments of the restraining sleeves depicted in FIGS. 4A to 4C can be combined mutatis mutandis with any one of the anchors shown in FIGS. 2A-3B.

[0073] In some embodiments (e.g. FIG. 4B), the restraining sleeve 425 is absent a tapered tip. In some embodiments, and as shown in FIG. 4A, restraining sleeve 425 of anchor 420 is a tissue penetrating restraining sleeve comprising one or more distal tapered penetration tips 427 configured to penetrate a graft and/or tissue. In some embodiments, penetration tips 427 comprise one or more sharp edges. A potential advantage in tapered penetrating tips is in that tapered tips reduce the level of resistance necessary for driving anchor 100 through the graft and/or vessel wall.

[0074] Additionally, and as shown in the exemplary embodiment depicted in FIG. 4A, restraining sleeve 425 is an in-tissue dwelling restraining sleeve and comprises a base-facing flange 426 that protrudes radially outwards from an external surface of sleeve 425. During implementation, tissue penetrating restraining sleeve 425 penetrates graft 280 and blood vessel wall 290 up to a point at which flange 426 abuts an internal surface of graft 280 and stops further penetration of tissue penetrating restraining sleeve 425 into the tissue. Continued application of force on base 260 by frame 40 brings anchor 420 prongs 421 to slide axially outwards in respect to tissue penetrating restraining sleeve 425 freeing prongs 421 to bend in opposite directions and bring penetrating tips

220 to urge against external surface **296** of the blood vessel wall **290**, opposite to the penetration direction thereby affixing the blood vessel wall **290** to graft **280**.

[0075] In some embodiments and as shown in the exemplary embodiment depicted in FIG. **4B**, restraining sleeve **445** is an intra-lumen dwelling restraining sleeve. Intra-lumen dwelling restraining sleeve **445** is devoid penetrating tips and comprises a blunt distal (tip-facing) surface **447**. During implementation, intra-lumen dwelling restraining sleeve **445** abuts an internal surface of graft **280** stopping intra-lumen dwelling restraining sleeve **445** from penetrating graft **280** or into the tissue. Continued application of force on base **260** by frame **40** brings anchor **440** prongs **421** to slide axially outwards in respect to intra-lumen dwelling restraining sleeve **445** freeing prongs **421** to bend in opposite directions and bring penetrating tips **220** to urge against external surface **296** of the blood vessel wall **290**, opposite to the penetration direction thereby affixing the blood vessel wall **290** to graft **280**.

[0076] As shown in FIGS. **4A** and **4C**, in some embodiments, restraining sleeve **425/465** comprises a base-facing flange **426/466**. As shown in FIGS. **4A** and **4B**, in some embodiments, internal prongs **421-3/4** and **441-3/4** are shorter than the external prongs **421-1/2/441-1/2** and comprise blunt tips. In some embodiments, the anchor **420** comprises internal prongs **421-3/4** having blunt tips.

[0077] As shown in FIGS. **4A** and **4B**, in some embodiments, anchor **420/440** comprises a buckling prevention lock **428/448** at tip **422/442** configured to prevent anchor buckling during penetration into a graft and/or a tissue. In some embodiments, buckling lock **428** is formed by a protrusion (e.g., tongue-shaped) **430** protruding from a first prong **421-2** towards a juxtaposed second prong **421-1** and a recess **431** in the second prong **421-1** facing the protrusion **430** so that in a juxtaposed configuration of the first **421-1** and second **421-2** prongs, protrusion **430** is accommodated by recess **431** forming the buckling lock **428**. In operation, when anchor **420** is urged by a frame (not shown) against and into a graft and a blood vessel wall (not shown). Buckling causes shear forces between layers, expressed as longitudinal movement between adjacent prongs. Lock **428** is configured to stop relative movement between the prongs **421-1/421-2** (e.g., relative axial movement of each prong in respect to the juxtaposed prong) and thus prevents the buckling of anchor **420** during penetration a graft and/or a blood vessel wall.

[0078] As shown in FIGS. **4A** to **4C**, in some embodiments, restraining sleeve-stop **423/443/463** is shaped as a rib protruding outward from a surface of the prong **421/441/461** and forming a ridge wider than that of an internal width of the restraining sleeve **425/445/465**. In some embodiments, as shown in FIG. **4A**, the external width of the prongs **421-1** to **421-4** between the protrusions **423** is equal or smaller than the external width of the restraining sleeve **425**, thereby rib **423** does not protrude externally to the restraining sleeve **425**. In some embodiments (FIGS. **4A** to **4C**) tips **422/442/462** protrude in an opposite direction to the restraining sleeve-stop **423/443/463**.

[0079] According to some embodiments of the invention, a cross section of one or more prongs has a rectangular, flat, circular, triangular or any other suitable geometry. In some embodiments, the cross section of any one of the prongs varies along its length. In some embodiments, the cross section of the restraining sleeve is either one or a combination of: rectangular, flat, and circular.

[0080] In some embodiments, and as shown in the exemplary embodiments depicted, for example, in FIGS. **4A**, **4B** and **4C**, a tip **422**, **442** and **462** respectively of anchors **420**, **440** and **460** respectively is cut (e.g., by laser) to form pointed (e.g., triangular) geometry. In some embodiments, during manufacturing distal edges **427/467** of restraining sleeve **425/465** are optionally ground to shape.

[0081] In some embodiments, and as shown in the exemplary embodiment depicted in FIG. **4D**, a tip **482** of anchor **480** is ground along a distal edge **484** of the anchor to form a penetrating blade **486**. In some embodiments, distal edge **484** is pointed from its narrow aspect and flat from its wide aspect. The blade-edge of the anchor tip depicted in FIG. **4D** improved the penetrability of the anchor through the graft and the tissue.

[0082] In some embodiments, and as shown in the exemplary embodiment depicted in FIG. 4E, a tip **495** of anchor **490** is ground along both sides of a distal edge **494** of the anchor to form a pointed penetrating blade **496**. In some embodiments, distal edge **494** is pointed from both its narrow aspect as well as from its wide aspect. The pointed blade-edge of the anchor tip depicted in FIG. 4E adds additional cutting edges than the single cutting blade edge of FIG. 4D adding additional penetrability of the anchor through the graft and the tissue. The selection between anchors **480** and **490** depends on the type of tissue and/or graft material the anchor is expected to penetrate.

[0083] Turning to FIG. 5 which is a perspective view simplified illustration of a 3D-anchoring anchor (excluding a restraining sleeve), in accordance with some embodiments of the invention. The anchor **500** shown in FIG. 5 comprises three or more prongs **540-1**, **540-2**, **540-3** and **540-4**., In the exemplary embodiment depicted in FIG. 5, anchor **500** comprises two pairs of prongs **540** each pair comprising two diametrically opposed prongs **540** (e.g., **540-1/540-3** and **540-2/540-4**) the prongs of each pair configured to bend in opposite directions along a common plane (e.g., plane G and Plane W respectively). In some embodiments, the planes G and W are angled in respect to each other. In some embodiments, the planes G and W are perpendicular in respect to each other.

[0084] A potential advantage of anchor **500** is in that it provides at least three points of pressure on an external surface of the blood vessel. A potential advantage of anchor **500** is in that it prevents rising or curving of the wall **290** of the blood vessel along sides of prongs **540**, preventing partial detachment of blood vessel wall **290** from graft **280**. In some embodiments, anchor **500** is made of flat/round NiTi wire or cut and shaped out of NiTi tube.

[0085] In some embodiments, an anchor such as anchor **500** is manufactured by cutting the anchor from sheet metal and forming the final anchor by bending the cut piece. In some embodiments, an anchor such as anchor **500** is manufactured by cutting the anchor from a tube (e.g., by laser) and forming the final anchor form with thermal treatment.

[0086] The prong **540-1** to **540-4** are oriented on the base so each prong is disposed between two other prongs (e.g. **540-1** is disposed between **540-2** and **540-3**). In some embodiments, a restraining sleeve-stop is formed at the prongs.

[0087] Reference is now made to FIGS. 6A, 6B, and 6C, which are side view simplified illustrations of implementation of a securing system **100** anchor **600** in accordance with some embodiments of the invention. In the exemplary embodiment of FIGS. 6A-6C, anchor **600** is double pronged, at least one prong **602** comprising a resilient outwardly curved proximal portion **604**. In some embodiments, resilient outwardly curved proximal portion **604** are adjacent or abutting anchor **600** base **616**. In some embodiments, resilient outwardly curved proximal portion **604** is resilient in a lateral direction (radially centrally and outwards) and is configured to move centrally and optionally axially (increasing the length of prongs **602**) when urged radially inwards. In some embodiments, restraining sleeve **625** has cylinder geometry and comprises a flange **650** attached to a proximal (towards the frame **606**) end of sleeve **625**.

[0088] In some embodiments, anchor **600** is deployed into a blood vessel wall in a two-stepped process. At a first step, and as depicted in FIG. 6A, a low first force, represented by a thin arrow **608** is applied to frame **606** driving anchor **600** into tissue. The applied low force is sufficient to drive anchor **600** into the tissue but insufficient to force restraining sleeve **625** over resilient outwardly curved proximal portions **604**.

As shown in FIG. 6B, a second force, higher than the first low force, represented by a thick arrow **610** is sufficient to urging flange **650** against a graft **612** and blood vessel endothelium **614**, force restraining sleeve **625** to move in a proximal direction over resilient outwardly curved proximal portions **604** urging them in a radially inward direction. Proximal movement of restraining sleeve **625** further drives anchor **600** into tissue and frees at least a portion of anchor **600** prongs **602** to bend away from each other.

[0089] The exemplary embodiment shown in FIG. 6C shows the final deployment stage in which

anchor **600** is fully deployed, restraining sleeve **625** abuts base **616** and prongs **602** are fully free and bent against an outside surface of the blood vessel wall securing graft **612** to the blood vessel wall.

Ring-Shaped Anchoring Securing Systems

[0090] Reference is now made to FIGS. **7A** and **7B**, which are perspective view simplified illustrations of a graft securing system in accordance with some embodiments of the invention. As shown in FIGS. **7A** and **7B**, the system comprises two ring-shaped frames **710** and **750**, each comprising a plurality of anchors **730/770** protruding radially outwards from frame rings **720/760** and configured to penetrate a graft **780** and tissue (e.g., blood vessel wall) **790** when being urged by radial expansion of the frame rings **720** and **760**. In some embodiments, at least one of the frame rings **720/760** has one or more latches **740/745**. In some embodiments, at least one of latches **740/745** on a first ring frame is configured to interlock with a respective latch on a second adjacent ring frame when the frame rings **710/750** are axially juxtaposed.

[0091] As shown in the exemplary embodiment depicted in FIGS. **7A** and **7B**, anchors **730/770** protrude in various angles from their respective frame rings **710/750**. For example, anchors **770** are perpendicular to a plane defined by a circumferential opening of ring **750**, and anchors **730** are angled in respect to a plane defined by a circumferential opening of ring **710**. In some embodiments, at least one of anchors **730/770** of at least one of frame rings **720/760** extends towards one or more anchors **730/770** of an adjacent frame ring, thereby, upon deployment of frame rings **720/760** anchors **730/770** of deployed frame rings **720** and **760** interlock. A potential advantage of this configuration is in that interlocked anchors support each other and prevent axial movement of the secured system **700**. In some embodiments the anchors of at least one ring **730/770** protrude in varying angles to the axis of the ring **730/770**.

[0092] Turning to FIGS. **8A** and **8B**, which are perspective view simplified illustrations of a graft securing system in accordance with some embodiments of the invention. As shown in FIGS. **8A** and **8B**, the system comprises: a radially expandable base frame **810** shaped as a ring, and a radially expandable guiding frame **850** shaped as a ring. In some embodiments, at least one of the frames **810/850** are collapsible. In some embodiments, the base frame **810** comprises a plurality of anchors **830** protruding generally perpendicular to a plane defined by a circumferential opening of ring **810**. In some embodiments, guiding frame **850** comprises a plurality of guiding channels **802** disposed at the ring wall **860**.

[0093] The guiding channels **802** are formed generally perpendicular to a plane defined by a circumferential opening of the frame **850** and comprise an entry port **872** and an exit port **874**. Anchors **830** connect a tissue (e.g., blood vessel wall) **890** to a graft **880** by penetrating the graft **895** and tissue **890** after passing through guiding channels **802** when the base ring **810** and guiding ring **850** are axially juxtaposed. At least one of frames **810** and **850** is expandable from a retracted state (e.g., within the applicator) to an expanded state in which the frame **850** engages graft **895**.

[0094] Anchors **830** are shaped and directed into the graft **895** and tissue **890** by guides **802**. As shown in FIG. **8B**, guiding channels **802** are angled in respect to frame **850** wall and guide the anchors **830** to bend at an angle and receive a post-penetration angled configuration during their deployment through the guides **802**. The anchors **830** are deployed within the guiding channels **802** by entering through entry port **872** and existing through exit port **874** during an axial displacement of at least one of the frame **810/850** toward the other **850/810** until frames **810/850** are juxtaposed. In some embodiments as shown in FIG. **8B**, the anchors **830** are resilient and are made of a shape memory material e.g. Nitinol.

[0095] In some embodiments, the anchors **830** are pre-shaped and assume a pre-shaped unrestrained configuration when not being restrained. In some embodiments, the anchors **830** are held in a restrained position by a restraining sleeve (not show) prior to entering the anchor guide **870** formed at the guide frame **850**. In some embodiments, the anchors **830** are formed according to anchors embodiments explained elsewhere herein (e.g. FIGS. **2A** to **5**). In some embodiments,

when entering guides **802**, an anchor restraining sleeve slides away of the distal tip **832** of the anchor **830**, so that the anchors **830** assume an unrestrained state upon exiting the guiding channels **802** through port **874**. Thereby, when penetrating the graft **895** and the tissue **890**, anchors **830** connect the tissue **890** to the graft **895** by assuming a secured configuration in which the tip **832** of the anchor **830** is pressed on the tissue. In some embodiments, the restraining sleeves are parallel to the axis of the restraining sleeve frame.

[0096] In some embodiments, components of the graft securing system are manufactured from one or more of the following biocompatible materials: Nitinol, Stainless Steel and Polymer. For example, in some embodiments, at least one of the frame, anchors and restraining sleeve are made of metal, e.g., Nitinol or Stainless Steel. In some embodiments, the restraining sleeve is made of a polymer e.g., Ethylene Propylene Diene Monomer (EPDM), Polytetrafluoroethylene (PTFE) and/or nitrile-butadiene rubber (NBR).

Graft Securing System Applicator

[0097] Reference is now made to FIGS. **9A** and **9B**, which are perspective view, side view and cross section view simplified illustrations of a graft securing system applicator in accordance with some embodiments of the invention. The applicator **1000** comprises: one or more applicator lumens **1400**, coupled at a distal end to an applicator head **1200**, and at a proximal end to an applicator control handle **1600**. As shown in enlarged view A of FIG. **9A** and FIG. **9B** (section A-A of FIG. **9A**), the applicator head **1200** comprises: a head lumen **1280**, an applicator tip **1205** disposed at a distal end of the head lumen **1280**, a container portion **1202** located proximally to the applicator tip **1205**, an axially movable container sheath **1220** surrounding the container portion **1202**, a graft securing system **1100** frame **40** holder and driver **1240** carrying a balloon **1300** and graft securing frame **1100**, and an frame **1100** releasing sheath **1230** arranged between graft releasing frame **1100** and movable container sheath **1220**. In some embodiments, balloon **1300** is a non-compliant balloon. In some embodiments, balloon **1300** is a compliant balloon. In some embodiments, balloon **1300** is a semi-compliant balloon. In some embodiments, holder and driver **1240** comprises a lumen sized to receive a guide wire. In some embodiments, applicator **1000** is guided over the guide wire to a target location for deployment.

[0098] In some embodiments, applicator **1000** comprises a resilient protective layer **1302** covering at least a portion of balloon **1300**. In some embodiments, protective layer **1302** comprises a sleeve. In some embodiments, protective layer **1302** comprises a balloon. In some embodiments, protective layer **1302** is made of a biocompatible material e.g., fabric, nitinol mesh, nylon, silicone or any other suitable material. In some embodiments, protective layer **1302** is between 0.05-0.6 mm in thickness. A potential advantage in protective layer is in that it protects balloon **1300** from coming into contact with sharp edges of frame **40** or anchors **100** and being damaged or punctured. In some embodiments, the graft securing system **1100** is one of the graft securing systems described elsewhere herein. In some embodiments, prior to applying the graft securing system **1100** by the applicator **1000**, system **1100** is fitted within the container portion **1202** at a maximally folded state. In some embodiments, a graft envelops one of the graft securing systems described elsewhere herein disposed at a retracted state. At the maximally retracted state, the graft securing system **1100** is folded, so that the penetration tip of anchors **100** (not shown) is disposed on graft securing system **1100** directed axially distally towards a tip of the dispenser. In some embodiments, when the securing system is released and expanded to an expanded state, the anchors disposed on the graft securing system **1100** are directed radially outwards towards to the graft and the tissue (e.g., blood vessel wall).

[0099] In some embodiments, all anchors **100** are biased together by the frame **40** e.g., as shown in FIGS. **1A** to **1C**. In cases in which frame **40** is re-collapsed into the retracted state (e.g., repositioning) and re-covered with releasing sheath **1230**, movement distally (axially forward) of releasing sheath **1230** urges anchors **100** radially centrally into the retracted state in which anchors **100** to point again generally axially, in respect to frame **40**.

[0100] Reference is now made to FIGS. 9A, 10A and 10B and 11A-D. In some embodiments, a container portion **1202** sheath **1220** is axially movable over container **1202** to assume the following applicator head **1200** states: [0101] 1) A closed state (FIGS. 9A-B) in which the container sheath **1220** covers the container **1202** and has a distal rim **1222** adjacent the tip **1205**, [0102] 2) A partially open state (FIG. 10A) in which the container sheath **1220** is partially retracted proximally, thereby partially exposing the container **1202** and the graft securing system **1100** fitted within the container **1202**, and [0103] 3) An open state (FIG. 10B) in which the container sheath **1220** is fully retracted proximally fully exposes the frame securing system **1100**.

[0104] In some embodiment, the applicator head **1200** transitions from a closed state to an open state and vice versa, by sliding the container sheath **1220** axially distally over the container **1202** or axially proximally exposing the container **1202**.

[0105] In some embodiments of the invention, the frame **40** is locked onto a frame **40** holder and driver **1240** until the frame **40** is unsheathed and exposed. In some embodiments, the frame **40** is unlocked when being unsheathed of the container sheath **1220**. In some embodiments, as shown in FIG. 10B, frame **40** holder and driver **1240** comprises one or more of frame **40** holding pins **1235** disposed circumferentially at an external surface **1242** of the holder and driver **1240**. In some embodiments, frame **40** comprises one or more holes **1275** at a proximal end of a frame **40** (e.g., frame **40**) sized to fit over and receive holding pins **1235**. In some embodiments, the frame **40** is axially locked to the frame **40** holder and driver **1240** by one or more of the pins **1235**. In some embodiments, the frame **40** is fitted on the pins **1235** by mounting a proximal pin holes formed at a distal end of frame **40**, so that an axial movement or full expansion of the frame **40** is prevented until the frame **40** is released of the pins **1235**.

[0106] In some embodiments, the applicator head **1200** comprises an axially movable releasing sheath **1230**, having a closed state (10A) in which the releasing sheath **1230** is positioned over the holding pins **1235**, a partially open state (FIG. 11B) and an open state (FIGS. 10C and 11D) in which the releasing sheath **1230** is retracted proximally and exposes the holding pins **1235**. In some embodiments, re-sheathing the frame **40** by either one of the releasing sheath **1230** or the container sheath **1220** is enabled when the frame **40** is locked within the applicator head **1200**.

[0107] In some embodiments as shown in FIGS. 9A-B, the frame **40** is expandable by a balloon **1300** disposed in lumen **1280** and fixed to holder and driver **1240** and enveloped by frame **40**. In some embodiments, the balloon **1300** is inflatable via the lumen **1280** or, in some embodiments, via a space created by adding additional sheath around **1280**. In some embodiments as shown in FIGS. 10A, 10B, the frame **40** is folded over the balloon **1300** disposed at a deflated state within the container **1202** prior to applying the frame **40**. In some embodiments, balloon **1300** is a non-compliant balloon.

[0108] In some embodiment, the method of delivery and the application of the frame **40** by the applicator **1000** comprises: [0109] a) Positioning the applicator head **1200** at the deployment site within a blood vessel. In some embodiments, a marker **1210** disposed at the tip **1205** assists in the initial positioning of the applicator head. [0110] b) Partial unsheathing of the frame **40** by proximally retracing the container sheath **1260** from the distal end **1200** frame **40** partially expands assuming a partially open state. [0111] c) Verifying positioning of frame **40** within the blood vessel. [0112] d) Optionally re-sheathing frame **40** by sliding container sheath **1260** distally over frame **40** so that the head **1200** re-assumes a closed state and repositioning graft securing system **1100** if required followed by repeating stages (1) to (3)

Unsheathing the securing system **1100**, by retracting the container sheath **1260** so that the head **1200** assumes a partial open state and the securing system is free to expand within the treatment site. [0113] e) Release the securing system from locking pins **1235** by retracting the releasing sheath **1230** to a fully open state. [0114] f) Inflating an actuating balloon **1300** and expanding the frame **40**. Urging frame **40** against the graft and/or tissue, thereby securing the graft to the tissue (e.g., blood vessel wall).

[0115] Releasing applicator by deflating balloon **1300**, re-sheathing with sheath **1230** and **1220**, retracting applicator out of the treatment site. Reference is now made to FIGS. **11A**, **11B**, **11C** and **11D**, collectively referred to as FIG. **11**, which are cross section view simplified illustrations of implementation of a graft securing system applicator device **2000** in accordance with some embodiments of the invention.

In some embodiments, as shown in FIG. **11**, the applicator **2000** comprises an applicator head **2200** and an axially movable balloon **2760** and positioned within head **2200** distally to a graft securing system **2100** disposed within the applicator **2000** head **2200**. In some embodiments, applicator **2000** comprises a handle coupled over a dedicated wire or carrier and a frame on the handle configured control axially moveable balloon **2760** via the handle frame. In some embodiments, balloon **2760** is inflatable or deflatable via a conduit **2765**. In some embodiments, balloon **2760** and frame **40** are arranged concentrically. In some embodiments, balloon **2760** is positioned distally (closer to the applicator tip) to frame **40** and axially slidable towards and away from frame **40**.

[0116] In some embodiments, the frame **40** is made of self-expanding shape memory material and configured to at least partially self-expand as the outer sheath **1230** is proximally moved by the handle of securing system **2100**.

[0117] An exemplary method of deployment and application of the graft securing system **1100** by applicator **2000** is depicted in FIG. **11**. For simplicity of explanation, the embodiment depicted in FIG. **11** is shown in general outlines and some components of applicator **2000** have been removed altogether.

[0118] To better understand the following explanation of operation of applicator **2000** as disclosed in the exemplary embodiment depicted in FIG. **11**, the arrangement of applicator **2000** head **2200** components from inside outwards is as follows: [0119] a) Guide wire lumen **2763** configured to receive at least one guidewire (not shown) and, optionally, balloon inflation lumen **2765**. In some embodiments, and as shown in FIG. **11**, guide wire lumen **2763** and balloon inflation lumen **2765** are collocated adjacent to each other along at least a portion of their length; [0120] b) At least one balloon; [0121] c) One or more balloon inflation/deflation lumina **2765**, optionally slidable over guidewire lumen **2763**, in which case guide wire lumen **2763** and balloon inflation lumen **2765** are coaxial. In some embodiments, balloon inflation/deflation lumen **2765** and guide wire lumen **2763** are located in separate locations along container portion **1202** and are disposed generally along each other; [0122] d) frame **40** holder and driver **1240**, configured to support and hold frame **40** (e.g., in a retracted-closed state) and/or drive frame **40** out of or into applicator **2000** during deployment; and [0123] e) releasing sheath **1230** slidable over frame **40** as explained elsewhere herein.

[0124] As shown in the exemplary embodiment depicted in FIG. **11**, and explained in detail herein, graft securing system **1100** comprises at least two actuating elements: frame **40** and balloon **2760**. In some embodiments, one or more components is configured to move along the guide wire. In some embodiments, balloon lumen **2765** is axially and controllably moveable in respect to frame **40** and over guidewire lumen **2763**. In some embodiments, moving balloon lumen **2765** translates balloon **2760** towards (proximally) or away from (distally) frame **40**.

[0125] Once at least a distal portion of frame **40** is at least partially expanded as explained elsewhere herein, applicator device **2000** is configured to move the balloon **2760**, still at a deflated state axially proximally to be disposed within the interior of the graft securing system **2100** at least partially expanded portion (e.g. by a wire **2730**). In some embodiment, inflating the balloon **2760** positioned within the graft securing system **2100** expands the graft securing system, such that it secures a graft to a blood vessel wall as described elsewhere herein. A potential advantage of a configuration of the applicator **2000** as shown in FIG. **11** is in that the balloon **2760** and the graft securing system **2100** are mounted in tandem requiring less radial space and reducing the external diameter of the applicator head **2200** e.g., to fit within a catheter tube.

[0126] In some embodiments the applicator **2200** is configured to enable a re-sheathing of graft

securing system **1100** by moving the container sheath **1220** distally. In some embodiments, the applicator **2200** comprises an unsheathing lock, which is provided, for example as a latch, pin, ring, wire, etc. The unsheathing lock is configured to prevent a premature unsheathing of the securing system **1100**. In some embodiments, the container sheath **1220** is movable by a nut on the applicator controlling handle **1600**.

[0127] As shown in FIG. **11A**, prior to deployment, axially movable balloon **2760** is positioned distally to frame **40**, between frame **40** and applicator tip **1205**. Anchors **100** are urged centrally, radially centrally and held in place by releasing sheath **1230**. The method of deployment of frame **40** comprises, as depicted in FIG. **11B**, moving axially movable balloon **2760** in a deflated state **2760-1** axially proximally and positioning balloon **2760** within a distal portion of frame **40** distally to anchors **100**. Concurrently or consecutively partially retracting releasing sheath **1230** and allowing self-expansion of a distal portion of frame **40**. Expanding axially movable balloon **2760** from a deflated state **2760-1** to an expanded state **2760-2** and urging the partially expanded distal portion of frame **40** against graft **280** and blood vessel wall **290**.

[0128] At this point the method comprises verifying the deployment location and orientation of frame **40** in respect to blood vessel wall **290**.

[0129] As depicted in FIG. **11C**, the method of deployment is continued by deflating axially movable balloon **2760** and concurrently or consecutively fully retracting releasing sheath **1230**. Fully retracting releasing sheath **1230** releases support struts **45** that retain their original erect configuration urging anchors **100** radially outwards and at least partially penetrating graft **280** and blood vessel wall **290**. Additionally, fully retracting releasing sheath **1230** releases frame **40** from locking pins **1235** and frees frame **40** to at least partially self-expand.

[0130] The method is concluded, as shown in FIG. **11D**, by expanding axially movable balloon **2760** from a deflated state **2760-1** to an expanded state **2760-2**, expanding and urging graft securing system **1100** frame **40** against graft **280** and blood vessel wall **290** fully implanting anchors **100** in place.

[0131] In some embodiments of the invention, at least some of the tips of the anchors of the graft securing system **1100** are directed transversely to the graft and/or blood vessel wall after being unsheathed and exposed to the treatment site. In some embodiments (not shown) the applicator head **1200/2200** comprises a plurality of anchor wires, having their tension controllable by the applicator **1000/2000**, e.g. through the applicator control handle **1600**. The anchor wires are connected at their distal end to a plurality of anchors disposed at the securing system **1100**. In some embodiments, one or more anchors disposed on the graft securing system **1100** are selected to be directed toward the graft or the blood vessel wall after the positioning the applicator at the treatment site. In some embodiments, the selected anchors are flexed from a folded state (tips pointing away from the graft/tissue) to a penetration state by a tension applied on the frame **40** or directly on the anchors by the anchor wires. In some embodiments, the balloon is inflated via a dedicated port on the handle of the applicator.

[0132] Referring now to FIG. **12**, which is a perspective view simplified illustration of an anchor release system in according to some embodiments of the invention. In some embodiments, movement of support strut **45** from a fully bent (closed) state to a fully straightened (open) state is controlled via a control wire **1204**. Control wire **1204** is movable generally axially, the movement controlled by applicator control handle **1600**. Axially proximally movement of control wire **1204** places tension on support strut **45** and pulls strut **45** radially centrally into a bent-biased closed state. Alternatively, axially distally movement of control wire **1204** release tension on support strut **45** and enable strut **45** to straighten by moving radially outwards to acquire its preformed shape.

[0133] In some embodiments, the shape (e.g., longitudinal cross-section) of frame **40** varies. In some embodiments, the shape of frame **40** is set at the manufacturing stage, e.g., by heat treatment.

[0134] Reference is now made to FIGS. **13A**, **13B**, **13C** and **13D**, which are cross-section view simplified illustrations of frame types in according with some embodiments of the current

invention. In some embodiments, and as depicted in FIG. 13A, frame **40** comprises a partially expanded state in which frame **40** assumes a bottle-neck shape. In some embodiments, in the bottle-neck shape proximal portion **40-2** of frame **40** is at least partially collapsed, distal portion **40-1** of frame **40** is expanded sufficiently to come into contact with vessel wall **290** and anchors **100** are extended radially outwards but are distant from and do not contact graft **80/280/612/780/895** and/or vessel wall **290**. A potential advantage in this configuration is in that the exact insertion of anchors **100** into the graft **80/280/612/780/895** and/or vessel wall **290** is known and frame **40** can be positioned accordingly in the vessel e.g., by pulling frame **40** proximally as indicated by arrow **1250**, without damaging the vessel wall e.g., by anchors **100**. In this configuration, a circumference of distal portion **40-1** of frame **40** is in contact with vessel wall **290** maintaining longitudinal stability when frame **40** is moved axially along vessel wall **290**.

[0135] In the exemplary embodiment depicted in FIG. 13B, Frame **40** comprises an hourglass shaped partially expanded state in which a middle portion **40-4** of frame **40** is at least partially collapsed, proximal **40-5** and distal **40-3** portions of frame **40** are expanded sufficiently to come into contact with vessel wall **290** and anchors **100** are extended radially outwards but are distant from and do not contact graft **80/280/612/780/895** and/or vessel wall **290**. A potential advantage in this configuration is in that the exact insertion of anchors **100** into the graft **80/280/612/780/895** and/or vessel wall **290** is known and frame **40** can be positioned accordingly in the vessel e.g., by pulling frame **40** proximally as indicated by arrow **1250**, without damaging the vessel wall e.g., by anchors **100**. In this configuration, a circumference of both proximal **40-5** and distal **40-3** portions of frame **40** are in contact with vessel wall **290** maintaining.

[0136] In some embodiments, and as shown in FIGS. 13C and 13D, graft **80/280/612/780/895** follows the shape of frame **40** throughout the length of frame **40** (FIG. 13C). Alternatively, and optionally, in some embodiments, graft **80/280/612/780/895** follows only the shape of proximal **40-5** and distal **40-3** portions of frame **40** (FIG. 13D) and is stretched freely in between gapping the recess formed by portion **40-4** of frame **40**.

[0137] In all embodiments described herein, once frame **40** is fully expanded, all portions thereof are in direct or indirect (via graft **80/280/612/780/895**) contact with vessel wall **290**. In some embodiments, expansion of a balloon (e.g., balloon **1300**) expands and urges frame **40**, throughout its full length directly or indirectly (via graft **80/280/612/780/895**) against vessel wall **290**.

[0138] Throughout this application, various embodiments of this invention may be presented in a range format. It should be understood that the description in range format is merely for convenience and brevity and should not be construed as an inflexible limitation on the scope of the invention. Accordingly, the description of a range should be considered to have specifically disclosed all the possible subranges as well as individual numerical values within that range. For example, description of a range such as from 1 to 6 should be considered to have specifically disclosed subranges such as from 1 to 3, from 1 to 4, from 1 to 5, from 2 to 4, from 2 to 6, from 3 to 6 etc., as well as individual numbers within that range, for example, 1, 2, 3, 4, 5, and 6. This applies regardless of the breadth of the range.

[0139] Whenever a numerical range is indicated herein, it is meant to include any cited numeral (fractional or integral) within the indicated range. The phrases “ranging/ranges between” a first indicate number and a second indicate number and “ranging/ranges from” a first indicate number “to” a second indicate number are used herein interchangeably and are meant to include the first and second indicated numbers and all the fractional and integral numerals therebetween.

[0140] In the description and claims of the application, each of the words “comprise” “include” and “have”, and forms thereof, are not necessarily limited to members in a list with which the words may be associated. In addition, where there are inconsistencies between this application and any document incorporated by reference, it is hereby intended that the present application controls.

[0141] The descriptions of the various embodiments of the invention have been presented for purposes of illustration but are not intended to be exhaustive or limited to the embodiments

disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art without departing from the scope and spirit of the described embodiments. The terminology used herein was chosen to best explain the principles of the embodiments, the practical application or technical improvement over technologies found in the marketplace, or to enable others of ordinary skill in the art to understand the embodiments disclosed herein.

[0142] It is the intent of the applicant(s) that all publications, patents and patent applications referred to in this specification are to be incorporated in their entirety by reference into the specification, as if each individual publication, patent or patent application was specifically and individually noted when referenced that it is to be incorporated herein by reference. In addition, citation or identification of any reference in this application shall not be construed as an admission that such reference is available as prior art to the present invention. To the extent that section headings are used, they should not be construed as necessarily limiting. In addition, any priority document(s) of this application is/are hereby incorporated herein by reference in its/their entirety.

Claims

1. A device for anchoring to tissue, the device comprising: an expandable frame; and at least one anchor coupled to the expandable frame, the at least one anchor comprising two external prongs each having a tissue penetrating tip, two internal prongs, and a restraining element configured to restrain the at least one anchor at a first configuration during penetration of the tissue by the tissue penetrating tip, the restraining element configured to move along the at least one anchor to release the two external prongs and the two internal prongs to a second configuration for securement to the tissue.
2. The device of claim 1, wherein the internal prongs are configured to apply a deflecting force on adjacent external prongs when the restraining element is moved along the at least one anchor.
3. The device of claim 1, wherein the two internal prongs are shorter than the two external prongs.
4. The device of claim 3, wherein the two internal prongs each have a blunt tip.
5. The device of claim 1, wherein the restraining element is a restraining sleeve.
6. The device of claim 1, wherein the restraining element is configured to maintain the two external prongs and the two internal prongs juxtaposed throughout their length for penetration and to, upon the movement, release the at least one anchor such that the two external prongs and the two internal prongs splay outwards.
7. The device of claim 1, wherein the at least one anchor is coupled to the expandable frame through an elastic support strut.
8. The device of claim 1, wherein the two external prongs comprise a stop configured to interfere with proximal movement of the restraining element, such that movement of the restraining element past the stop requires a force of a predetermined magnitude.
9. The device of claim 1, wherein the two external prongs comprise a stop configured to prevent distal movement of the restraining element.
10. The device of claim 1, wherein the at least one anchor comprises an anti-buckling lock.
11. The device of claim 10, wherein the anti-buckling lock comprises a protrusion and a recess configured to receive the protrusion.
12. The device of claim 1, wherein the expandable frame is configured to transition from a collapsed state during delivery within a blood vessel to an expanded state at a treatment site for anchoring to the tissue.
13. The device of claim 12, wherein the expandable frame is configured to transition to the expanded state at the treatment site having a graft within the blood vessel, and wherein the restraining element is configured to restrain the at least one anchor at the first configuration during penetration into the graft and the tissue.
14. The device of claim 13, wherein the device is configured to secure the graft to the blood vessel

at the treatment site for repairing the blood vessel having an aneurysm.

15. The device of claim 1, wherein the two external prongs and the two internal prongs are made of shape memory material.

16. The device of claim 15, wherein the shape memory material comprises nitinol.

17. The device of claim 1, wherein the at least one anchor comprises a plurality of anchors mounted around the expandable frame.

18. The device of claim 1, wherein, when the expandable frame is in an expanded state, the at least one anchor is generally perpendicular to a longitudinal axis of the expandable frame.

19. The device of claim 1, wherein the expandable frame is configured to self-expand upon deployment from a catheter.

20. A method for securing a device to a blood vessel, the method comprising: advancing an expandable frame in a collapsed state to a treatment site within the blood vessel; transitioning the expandable frame from the collapsed state to an expanded state; and deploying at least one anchor such that tissue penetrating tips of two external prongs of the at least one anchor penetrate a wall of the blood vessel, the at least one anchor further comprising two internal prongs and a restraining element configured to restrain the at least one anchor at a first configuration during penetration of the wall, the restraining element configured to move along the at least one anchor to release the two external prongs and the two internal prongs to a second configuration for securement of the expandable frame to the blood vessel.

21. The method of claim 20, wherein the treatment site comprises a graft, and wherein deploying the at least one anchor comprises penetrating the graft and the wall of the blood vessel by the tissue penetrating tips to anchor the graft to the blood vessel.

22. The method of claim 21, wherein the device is configured to anchor the graft to the blood vessel having an aneurysm.
